

Continuous aerial water delivery by vacuum-lift airship: a first-order model

Version 1 · 9 August 2026

Every model figure is cited by key and checked against the simulation that produces it; source figures are cited in place. Nothing described here has been built.

Energy reading, 2026-10-02. Energy conclusions in this earlier report are superseded by the [generated closure record](#). Its cited tables now show supplied effort on the prescribed, unsupported profile. They do not establish delivery, endurance, savings or operating cost. Historical arrows retain earlier figures. Feasible delivery, cycle minutes, both energy bases and the requirements are in the generated record.

THE RESULT

A buoyant hull that never lands turns aerial firefighting from a sortie problem into a flow-rate problem. The reference vehicle here is the **P-100**: 110 m long, smaller than the Hindenburg, delivering **175 tonnes an hour indefinitely** — about 2,100 tonnes in a twelve-hour day against roughly 560 for a very large airtanker, and it does not stop at dusk. Two larger classes are modelled to find where the arithmetic breaks; it breaks on the descent, not on the structure or the power. This paper is that arithmetic and the list of what would have to be true.

Status. Every headline quantity below is an output of the simulation in this repository, cited by key and verified automatically against `research/figures.json`; figures from catalogued sources are cited plainly. Superseded values, historical comparisons and one-off derivations are written unmarked and sit outside that gate — they are identified as such where they appear. Nothing has been built. The model is first-order throughout, and §8 lists the seventeen defects and unjustified assumptions the project has found in itself — fifteen open, two corrected on 2026-08-09 and kept in place with what they cost.

The flight model assumes a hull that floats; no drawn hull does, as the [structural assessment](#) explains.

1. The problem, and why an airship is a plausible shape for it

Aerial firefighting is a duty cycle problem before it is an aviation problem. A very large airtanker carries something like 70 t, releases it in seconds, and then spends 30–90 minutes flying to a base, loading, and flying back. Its instantaneous delivery rate is enormous and its *sustained* rate is set almost entirely by the turnaround. Helicopters with buckets shorten the turnaround by dipping from a nearby lake, and pay for it in payload — a Chinook carries about 10 t.

The gap in the middle is a vehicle that dips like a helicopter and carries like a tanker. Nothing occupies it, and the reason is that lift-per-unit-mass for rotorcraft is bought continuously with power, so payload and endurance trade against each other directly.

Buoyant flight does not have that trade. A hull that displaces its own weight in air holds altitude at zero power, and the marginal cost of carrying more is the cost of building a bigger hull, once. That is the argument for an airship, and it is not a new one: it has been made for cargo, for surveillance, and for high-altitude platforms for a century, and it has generally lost to the fact that the vehicle is enormous, slow, and vulnerable to weather.

Firefighting is a plausible exception on three counts. The mission is short-range and repetitive, so slowness costs little. The vehicle can be uncrewed, so the risk calculus that has historically killed large airships changes. And — the point of this paper — the water source and the fire are usually within tens of kilometres of each other, so the duty cycle is dominated by loading and unloading rather than by transit, which is precisely where a buoyant vehicle wins.

2. Why vacuum rather than helium

At sea level, with air at 1.225 kg/m^3 and helium at 0.169 kg/m^3 , a vacuum is about 16% more buoyant than helium. Helium lifts about 14% less than vacuum at that reference state. It also cannot leak away, cannot be embargoed, and cannot be priced by a supply chain with two producers of consequence.

The reason nobody flies one is structural. A gas envelope is in tension and can be a fabric; a vacuum envelope is in compression and must resist 101 kPa of atmosphere trying to crush it, which means it must be stiff, which historically means it must be heavy. Lana de Terzi proposed it in 1670 and the arithmetic has failed ever since.

The modern case rests on discrete lattice construction — ultralight periodic cellular structures assembled from many identical mass-produced parts, which hold their stiffness as they lose density where foams and honeycombs do not. Applied to the vacuum balloon that moves the binding constraint **from buckling to strength**, and the distinction is the whole reopening of the question. Buckling is a geometry failure: sudden, total, and not fixable by a better material. Strength is a number you can look up, test on a bench, and buy more of. The question stops being *this impossible* and becomes *how light can we build it*, which is an engineering question, and those get answered. Jenett et al. (NASA, 2019) is this project's structural precedent, and the honest summary of it appears in §8.1: **their own numbers do not close our mass budget**. Akhmeteli & Gavrilin (2021) reach a positive result for a vacuum balloon by a different route, and their published payload fraction is 0.1 against our implied 0.5.

So the correct statement is: vacuum lift is not obviously impossible any more, and this model assumes a structure that the two best available sources say is not yet available. Everything downstream inherits that assumption.

3. The vehicle

Three classes, geometrically similar, sized by a single safety requirement (§4). **The P-100 is the reference vehicle and everything below is worked through on it unless it says otherwise.** It is the smallest of the three and the only one smaller than something that has already flown: 110 m against the Hindenburg's 245. The P-1000 and P-10000 are the same arithmetic extrapolated, and §6 is about what that extrapolation runs into.




Figure 1. The three hulls at true relative scale, against the largest aircraft and the largest airship ever flown. Drawn from the same lengths and diameters as the table below.

	P-100	P-1000	P-10000
Payload	100 t	1,000 t	10,000 t
Displacement	220,000 m ³	2,200,000 m ³	22,000,000 m ³
Length × diameter	110 × 55 m	238 × 119 m	512 × 256 m
Cruise	90 km/h	110 km/h	130 km/h
Rotors / disc area	4 / 2,500 m ²	6 / 12,000 m ²	14 / 160,000 m ²
Battery	20 MWh	120 MWh	2,000 MWh
Fill rate	0.5 m ³ /s	3 m ³ /s	15 m ³ /s
Descent bag	125 t	1,250 t	12,400 t

These energy figures come from the earlier flight model, which understates the force needed to hold an empty hull down. Corrected figures will be higher, and some cycles may not be flyable as drawn.

Dry mass is set equal to payload in every class. That is an assumption, not a result, and §8.1 is about it.

4. What sizes the hull: fail-safe float-up

The displacement is not chosen to make the numbers work. It is chosen so that a ship that cannot release its water still rises.

*A hull must be positively buoyant at its working altitude while **fully loaded with water and unable to drop it.***

An uncrewed vehicle whose outlets jam must not sink into the fire it is fighting. Making that a sizing constraint rather than a design goal means the failure mode of a stuck valve is an inconvenient ascent rather than a crash.

The fleet model assumes dry mass equals payload: loaded mass is 2 t per tonne of water. In its P-10000 scenario, lift is 26,950 t at sea level and 21,050.9 t at 2,500 m, against an assumed 20,000 t loaded mass. The corresponding lift-to-mass ratios are 1.348 and 1.053. No structural safety factor, pressure sizing or knockdown establishes this allowance. A complete hull and equipment bill must fit the assumed mass and pass load tests before this becomes a vehicle.

The separate 52 m structural drawing and its bill disagree in the end caps, in both directions. These readings retain structural safety factor 1.2 against full sea-level pressure. The favourable basis assumes knockdown 0.65 and a 1,450 MPa carbon-laminate compressive ceiling, both unverified. Across five readings, the favourable lift-to-mass ratio ranges from 0.751 to 0.998 at sea level and from 0.586 to 0.780 at 2,500 m. No reading reaches one; none is a checked design because the sizing checks do not resolve station lengths or connections. The [member census](#) records 20 disagreements between the drawing and the bill.

This is where a correction made on 2026-08-09 belongs. The ledger previously bought its lift at sea-level density and spent it at altitude, which overstated lift by 22%. Correcting it grew every hull by 22.2% and, in doing so, created the descent problem in §6 — the buoyancy that guarantees the ship comes up is exactly the buoyancy that stops it going back down.

The two extremes are not the same case, and the model evaluates both:

- **Float-up is hardest at the ceiling, 2,500 m MSL, in the thinnest air.**
- **Descent is hardest at the water, 1,300 m MSL, in air 16% denser.**

Nothing else in this model changes conclusions as often as remembering which of those two applies.

5. The cycle

Six phases, timed rather than asserted. For the reference P-100 at 15 km one way:

Phase	Minutes	What happens
SOURCE_APPROACH	2.00	arrive over the lake, come to a dead stop , lower the anchor and pumps
WATER_FILL	3.33	pump at 0.5 m ³ /s, no yaw (the lines would tangle)
OUTBOUND_TRANSIT	11.76	climb and run to the fire at 90 km/h
WATER_RELEASE	3.33	one long pass, 450 m AGL
BUOYANCY_ESCAPE	2.00	rise off the line on buoyancy alone, no propulsion
RETURN_TRANSIT	11.76	run back, make nitrogen, let down onto the lake
total	34.20	100 t delivered




Figure 2. Sustained delivery, and the cycle behind it. Water handling is the longest part of every cycle, which is the signature of a vehicle that never lands.

That is 175 t/h sustained, and 1.75 drops an hour. Transit is 23.5 of the 34.2 minutes on this class and the model names it as the bottleneck: water handling is fixed by the pumps while transit grows with every kilometre.

Compare it to the right quantity. 175 t/h is not a rival to an airtanker's seventy-tonne drop; it is a rival to that airtanker's *day*. Twelve hours of a P-100 is about 2,100 tonnes against roughly 560 for eight sorties, and the airtanker then stops while the airship does not.

The drop is one pass, not three. Three circuits meant two turns of a large hull over a fire, which is a manoeuvre the model had no business assuming. A single long release removes them.

Scaled up, the same cycle gives 1,697 t/h and 13,183, on cycles of 35.4 and 45.5 minutes — the cycle barely lengthens because only the transit term scales with distance and none of these scale with payload.

6. What limits the size: the descent, and the lake as its solution

6.1 The problem

Buoyancy that guarantees the ship rises when loaded must be overcome when it is empty, and it is worst at the bottom of the letdown where the air is 16% denser than the air the hull was sized in. **This is the term that decides how large one of these can usefully be**, which is why the two larger classes are in this paper at all: not as a proposal, but as the arithmetic finding its own ceiling.

2026-10-02 correction: record basis, INFEASIBLE. Arrows preserve the dated value on the left and give the current model on the right. Energy and battery hours describe supplied effort on an unsupported profile, not achieved flight.

	P-100	P-1000	P-10000
Source buoyant surplus	135.6 t	1,366.9 t	13,722.5 t
Rotor capability (earlier 1)	267.2	1,318.1	12,666.2
Rotor capability (earlier 2)	141.4	687.6	7,124.3
Rotor capability (current)	140.5 t	683.3 t	7,079.2 t
Rotors close (old model)?	yes, $\times 1.97$	no	no

The reference ship is comfortable and the extrapolations are not. The P-100 closes with $1.97 \times$ headroom. The P-1000 is 4% short and the P-10000 is 8% short: neither can reach its own water under power. This was discovered by moving the force balance from the ceiling — where it had always been struck, and where it closed — to the place where the descent actually ends.

Nothing here is a structural or a power limit. It is geometry and air density, and it is the first thing that bites as the hull grows.




Figure 3. The vehicle at the source, rendered from the same model: six pump pods on hoses to the surface, and the anchor cable running down to a bag in the water with its contact rings. The bag is to scale. The wash blows upward because the rotors are pushing the hull down against its own buoyancy.




Figure 4. What has to be held down at the water, and what holds it. The bar is the job; the tick is how far the rotors reach unaided.

6.2 Three ways out, costed

1. **Retain water as ballast.** Directly reduces delivery, which is the metric.
2. **Make ballast from air.** Liquefy nitrogen on the return leg. The plant is in the model and it is sized for something else (§7.2): at cycle rate it makes 21.12 t against a need of thousands. Making the whole 12,400 t as LN2 costs about **475 MWh**, eleven times the entire cycle.
3. **Never enter the dense air.** Hover at 1,350 m and fill through a long hose. Costed at **44 MWh** a cycle in pump work, with a 2 m bore at 140 bar at the pod.

These energy figures come from the earlier flight model, which understates the force needed to hold an empty hull down. Corrected figures will be higher, and some cycles may not be flyable as drawn.

6.3 What was actually chosen: borrow the lake

Lower a cable with a collapsible bag, fill it, winch it clear of the surface. Water hanging on a line is downward force at the cost of the lift needed to break the surface — 15 m of it.

2026-10-02 correction: record basis, INFEASIBLE. Arrows preserve the dated value on the left and give the current model on the right. Energy and battery hours describe supplied effort on an unsupported profile, not achieved flight.

	P-100	P-1000	P-10000
Bag	125 t	1,250 t	12,400 t
Cable	350 m	600 m	850 m
Pull	1.2 MN	12.3 MN	121.6 MN
Energy cost (earlier 1)	0.006	0.060	0.596
Energy cost (current)	0.003 MWh	0.059 MWh	0.596 MWh

These energy figures come from the earlier flight model, which understates the force needed to hold an empty hull down. Corrected figures will be higher, and some cycles may not be flyable as drawn.

2026-10-02 correction: record basis, INFEASIBLE. Arrows preserve the dated value on the left and give the current model on the right. Energy and battery hours describe supplied effort on an unsupported profile, not achieved flight.

These energy figures come from the earlier flight model, which understates the force needed to hold an empty hull down. Corrected figures will be higher, and some cycles may not be flyable as drawn.

The leverage is in the exponent. Induced rotor power goes as $\text{thrust}^{1.5}$, so moving load off the rotors pays superlinearly: carrying 90% of the hold on the bag drops the required rotor power from 1,748 MW to 52.3 → 1405.7 MW, a 97% reduction, and the letdown term from 34.20 MWh to 1.420 → 117.284 → 117.219 MWh.

These energy figures come from the earlier flight model, which understates the force needed to hold an empty hull down. Corrected figures will be higher, and some cycles may not be flyable as drawn.

That is why the bag is sized to do the *whole* descent rather than to cover the 1,056 t shortfall that revealed the problem. The shortfall was the symptom; the exponent was the finding.

Three consequences worth stating plainly:

2026-10-02 correction: record basis, INFEASIBLE. Arrows preserve the dated value on the left and give the current model on the right. Energy and battery hours describe supplied effort on an unsupported profile, not achieved flight.

- **Every class carries one, including the P-100 whose descent closes without it.** Removing its bag costs 1.526 MWh a cycle against 1.391 → 8.042 → 8.192: a 34% saving on a class that does not need the mechanism. A bucket is cheaper than thrust everywhere.
- **The mechanism cannot be over-sized.** The most water a ship can lift out of a lake is its own surplus lift; a bag equal to the surplus leaves the hull neutral. The physics supplies the ceiling.
- **A cable is a much better thing to hang than a hose.** 121.6 MN is about 440 mm of UHMWPE massing 125 t — 1.25% of payload in rope, and **not charged as dry mass anywhere in this model.**

These energy figures come from the earlier flight model, which understates the force needed to hold an empty hull down. Corrected figures will be higher, and some cycles may not be flyable as drawn.

6.4 What the anchor forces on the flight profile

The mechanism only works if the ship is not moving. A 12,400 t bag on an 850 m cable at 130 km/h is not an anchor, it is an accident. The model therefore requires: a dead stop before the cable goes out; no yaw while the lines are down; and departure permitted as soon as the pumps clear the water. This costs the 5 -minute approach phase and buys the mechanism.

7. The energy ledger

7.1 The budget

P-10000, 15 km one way, balanced, still air. Printed from the model, not transcribed:

2026-10-02 correction: record basis, INFEASIBLE. Arrows preserve the dated value on the left and give the current model on the right. Energy and battery hours describe supplied effort on an unsupported profile, not achieved flight.

Term	MWh
RETURN_TRANSIT (drag × 0.55 + cryogenic plant) (earlier 1)	16.611
RETURN_TRANSIT (drag × 0.55 + cryogenic plant) (earlier 2)	112.360
RETURN_TRANSIT (drag × 0.55 + cryogenic plant) (current)	114.038
WATER_FILL (pumping 10,000 t up 300 m) (earlier 1)	10.900
WATER_FILL (pumping 10,000 t up 300 m) (earlier 2)	213.327
WATER_FILL (pumping 10,000 t up 300 m) (current)	214.046
other (hotel + manoeuvring drag)	13.772[historical]
OUTBOUND_TRANSIT (drag, loaded) (earlier 1)	12.926
OUTBOUND_TRANSIT (drag, loaded) (earlier 2)	34.838
OUTBOUND_TRANSIT (drag, loaded) (current)	34.345
letdown (rotor work, with the anchor deployed) (earlier 1)	1.420
letdown (rotor work, with the anchor deployed) (earlier 2)	117.284
letdown (rotor work, with the anchor deployed) (current)	117.219
anchor (lifting the bag 15 m) (earlier 1)	0.596
anchor (lifting the bag 15 m) (current)	0.596
recovery (nitrogen store, credited back)	−1.900
total (earlier 1)	54.325
total (earlier 2)	697.586
total (current)	694.378

These energy figures come from the earlier flight model, which understates the force needed to hold an empty hull down. Corrected figures will be higher, and some cycles may not be flyable as drawn.

Shares are on the figure rather than in the table. They were in both, and the table's column was still dividing by the pre-correction 43.0 MWh cycle — so the same seven numbers carried two sets of percentages on one page. A share is derived and has no figure key, which means the citation gate cannot see it; the chart computes it from the ledger, so the chart is where it belongs.

These energy figures come from the earlier flight model, which understates the force needed to hold an empty hull down. Corrected figures will be higher, and some cycles may not be flyable as drawn.




Figure 5. The reference ship's cycle ledger, printed from the model rather than transcribed. Three quarters of it is the return leg; the anchor is the smallest positive line and it is the reason the letdown is the second smallest.

These energy figures come from the earlier flight model, which understates the force needed to hold an empty hull down. Corrected figures will be higher, and some cycles may not be flyable as drawn.




Figure 6. The same ledger at the limit case. The proportions invert: pumping and water handling dominate where flying did, which is the square-cube law seen from the other side.

These energy figures come from the earlier flight model, which understates the force needed to hold an empty hull down. Corrected figures will be higher, and some cycles may not be flyable as drawn.

2026-10-02 correction: record basis, INFEASIBLE. Arrows preserve the dated value on the left and give the current model on the right. Energy and battery hours describe supplied effort on an unsupported profile, not achieved flight.

13.91 → 80.42 → 81.92 kWh/t delivered, against 8.45 → 62.50 → 62.31 for the P-1000 and 5.43 → 69.76 → 69.44 for the largest. Larger is cheaper per tonne, as the square-cube law demands — which is the reason to model the larger classes at all, and §6 is the reason not to assume you can build them.

These energy figures come from the earlier flight model, which understates the force needed to hold an empty hull down. Corrected figures will be higher, and some cycles may not be flyable as drawn.

Note what dominates on the reference ship and does not at the limit: **the return leg is 75% of a P-100's cycle** and 32% of a P-10000's. The small ship spends its energy flying; the large one spends it moving water. That is the same square-cube law seen from the other side.

The bottom two rows were one row until 2026-08-09, and merging them was hiding an error: the recovery was netted against the pump bill under a $\max(0, \dots)$, so on the smaller classes the recovery exceeded the pumping and the excess was *deleted*, taking the whole pump bill with it. Splitting them moved the P-100 from 1.308 to 1.005 MWh. **The lesson generalises: the two most consequential errors found in this model were both accounting, not physics.**

These energy figures come from the earlier flight model, which understates the force needed to hold an empty hull down. Corrected figures will be higher, and some cycles may not be flyable as drawn.

7.2 What the cryogenic plant is actually for

The cryogenic plant is not cycle ballast. It is a rescue system, and the two get confused because they share a tank. As cycle ballast it makes 21.12 t against a 15,500 t tank — three orders of magnitude short, and saying so is more useful than defending it.

These energy figures come from the earlier flight model, which understates the force needed to hold an empty hull down. Corrected figures will be higher, and some cycles may not be flyable as drawn.

Its real job is unpowered recovery. The tank is sized so that an empty hull can be made heavy enough to **land with no rotor authority at all**, at ground level rather than at the ceiling — 14,456.1 t of ballast to sink an empty P-10000 at 1,000 m MSL. Filling it costs about 6,505 MWh: 2.7 days at rated plant power, 12.9 days on solar. That is a rescue that takes days, and it should stop being confused with a cycle that takes an hour.

These energy figures come from the earlier flight model, which understates the force needed to hold an empty hull down. Corrected figures will be higher, and some cycles may not be flyable as drawn.

7.3 Generation, and the deficit

2026-10-02 correction: record basis, INFEASIBLE. Arrows preserve the dated value on the left and give the current model on the right. Energy and battery hours describe supplied effort on an unsupported profile, not achieved flight.

	solar	per cycle	spend	deficit	endurance
P-100 (earlier 1)			1.391	1.24	
P-100 (earlier 2)			8.042	7.89	9.2
P-100 (current)	0.27 MW	0.15 MWh	8.192	8.04	1.4 h
P-1000 (earlier 1)			8.454	7.71	
P-1000 (earlier 2)			62.500	61.76	9.2
P-1000 (current)	1.26 MW	0.74 MWh	62.314	61.57	1.1 h
P-10000 (earlier 1)			54.325	50.23	
P-10000 (earlier 2)			697.586	693.49	30.2
P-10000 (current)	5.40 MW	4.10 MWh	694.378	690.28	2.2 h

These energy figures come from the earlier flight model, which understates the force needed to hold an empty hull down. Corrected figures will be higher, and some cycles may not be flyable as drawn.




Figure 7. What each hull spends against what its skin makes, and how long a full battery lasts.

These energy figures come from the earlier flight model, which understates the force needed to hold an empty hull down. Corrected figures will be higher, and some cycles may not be flyable as drawn.

Every hull runs a deficit every cycle, and this is the project's central public conclusion: without an energy import chain the fleet is a battery being spent. It is not a perpetual machine and does not claim to be.

One open defect still attacks this table. The generation each class advertises — 8, 40 and 150 MW — is counted for thrust authority and never as energy. Crediting it would not shrink the deficit: that generation runs on the nitrogen store, which is storage rather than a source, and its round

trip loses. Modelling it honestly moves the conclusion further in the direction it already points, not back. The solar half of the table was corrected on 2026-08-09 and the figures above are post-correction; §8.2 has what moved.

These energy figures come from the earlier flight model, which understates the force needed to hold an empty hull down. Corrected figures will be higher, and some cycles may not be flyable as drawn.

8. What is wrong with this model

Seventeen entries are documented in `docs/OPEN-QUESTIONS.md`. Seven were found by inspection, two by auditing all 89 published claims against the code, four by reading the sources, one by an outside reader asking a question none of them had, and three by an adversarial review of the model on 2026-08-10 — including one that says the two power models in §8.5 disagree by $5.05\times$ rather than the $2.83\times$ recorded there. The four from the sources are the serious ones and they are given here in full.

8.1 The dry-mass budget fails twice, independently — the largest open question

$\text{dryT} = \text{payloadT}$ implies a hull-average density of **0.455 kg/m^3** — and it is the same figure on every class, because displacement is sized per tonne of payload. 100 t inside $220,000 \text{ m}^3$ and 10,000 t inside 22,000,000 both come out there. **Choosing the smaller reference ship does not soften this one**, which is what makes it the concept's single point of failure rather than a scaling limit.

- **Jenett et al. 2019** (NASA NTRS) — the structural precedent this project cites — gives a bare discrete-lattice shell at **0.508 kg/m^3** in its own Table 2, at every radius. That is 12% over our *entire* dry allowance, before skin, joints, rotors, tanks, batteries, or the 125 t of anchor cable §6.3 admits is uncharged.
- **Metlen & Palazotto 2013**'s only real-materials vacuum-lift design has a structure-to-buoyancy ratio of **0.94** — structure alone consuming what we allocate to structure and payload together.
- **Akhmeteli & Gavrilin 2021** publish a payload fraction of **0.1** against our implied 0.5, on a shell of 1.16 kg/m^3 .
- Independently, every class carries **0.2 MWh of battery per tonne of dry mass**, requiring 200 Wh/kg at *pack* level with nothing left for anything else. NASA flew 149 Wh/kg on X-57; Lvovich (2020) sees no clear path past 500 Wh/kg at pack level, where the battery still consumes 40% of the budget.

These energy figures come from the earlier flight model, which understates the force needed to hold an empty hull down. Corrected figures will be higher, and some cycles may not be flyable as drawn.

Four sources, four different objections, one conclusion: **the mass premise is not supported by the literature this project itself cites**. Everything in §§5–7 is conditional on it.

8.2 The solar skin needed 76% conversion efficiency — FIXED 2026-08-09

state.js credited 200 W/m² of *electrical output*, continuously, in **five separate files**. NRCan's dataset gives 6.34 kWh/m²/day mean July horizontal insolation across eight BC interior fire-belt towns — 264 W/m² incident, day-averaged. 200 out of 264 is **76% conversion**, three and a half times the best cell ever made in a laboratory.

These energy figures come from the earlier flight model, which understates the force needed to hold an empty hull down. Corrected figures will be higher, and some cycles may not be flyable as drawn.

It is CFG.solarWPerM2 = 45 ' now: 264 × 0.21 flexible module × 0.81 for curvature, cell temperature, soiling and conversion, applied to a *projected* area --- solarM2' is 80–87% of each hull's plan ellipse, so the curvature is paid for once, in the area.

2026-10-02 correction: record basis, INFEASIBLE. Arrows preserve the dated value on the left and give the current model on the right. Energy and battery hours describe supplied effort on an unsupported profile, not achieved flight.

	solar	per cycle	deficit	endurance
P-100 (earlier 1)			0.32	
P-100 (earlier 2)			1.24	35.4
P-100 (earlier 3)	1.20	0.68	7.89	9.2
P-100 (current)	0.27 MW	0.15 MWh	8.04	1.4 h
P-1000 (earlier 1)			3.09	
P-1000 (earlier 2)			7.71	22.9
P-1000 (earlier 3)	5.60	3.30	61.76	9.2
P-1000 (current)	1.26 MW	0.74 MWh	61.57	1.1 h
P-10000 (earlier 1)			24.81	
P-10000 (earlier 2)			50.23	61.1
P-10000 (earlier 3)	24.00	18.20	693.49	30.2
P-10000 (current)	5.40 MW	4.10 MWh	690.28	2.2 h

These energy figures come from the earlier flight model, which understates the force needed to hold an empty hull down. Corrected figures will be higher, and some cycles may not be flyable as drawn.

Three things this exposed are worth more than the correction. The constant was duplicated five times and wrong in every copy — there is one now, plus one on the far side of the 3d/ boundary and a parity test that reads both. **No published figure moved**, because generation is not in planCycle's ledger: cycle energy, throughput and kWh/t came out bit-identical across a 4.4× change to the vehicle's power supply, which is defect 6 in §8.5 stated as sharply as it can be. And the honest number strengthens the project's conclusion rather than weakening it.

These energy figures come from the earlier flight model, which understates the force needed to hold an empty hull down. Corrected figures will be higher, and some cycles may not be flyable as drawn.

Still open: 45 W/m² is a 24-hour average — right for energy over a cycle, wrong for power at an instant. There is no sun at 03:00 and the storage gauge draws it anyway.

8.3 r_{tLN2} returned more work than the nitrogen contains — FIXED 2026-08-09

$r_{tLN2} = 0.50$ against ' $e_{LN2} = 0.45$ ' kWh/kg recovered **225 kWh per tonne** of liquid nitrogen. The physical exergy of LN2 at 1 bar against a 288 K ambient is **173.4 kWh/t** (Arnaiz-del-Pozo et al. 2020; corroborated at 205–214 kWh/t under more favourable assumptions). The term returned $1.3 \times$ the work available in the liquid, before any turbine or generator efficiency. Not an optimistic efficiency — a violation, and it was on the page.

These energy figures come from the earlier flight model, which understates the force needed to hold an empty hull down. Corrected figures will be higher, and some cycles may not be flyable as drawn.

2026-10-02 correction: record basis, INFEASIBLE. Arrows preserve the dated value on the left and give the current model on the right. Energy and battery hours describe supplied effort on an unsupported profile, not achieved flight.

It is **0.20** now: 90 kWh/t, 52% of the exergy, about what a cryogenic expander returns with no external heat source. E_{recovery} fell from -4.751 to -1.900 MWh and the P-10000's cycle rose to $54.325 \rightarrow 697.586 \rightarrow 694.378$. Two tests enforce $r_{tLN2} \times e_{LN2} \times 1000 \leq 173.4$, one on each copy of the constant, because a second law is not a tuning bound.

These energy figures come from the earlier flight model, which understates the force needed to hold an empty hull down. Corrected figures will be higher, and some cycles may not be flyable as drawn.

8.4 The drop may not arrive, and tonnes may be the wrong metric

The US Forest Service's 2022 assessment states that a drop released 1,000 ft above ground/vegetation "would completely dissipate". ALT_{drop} is 450 m — **1,476 ft** — raised for hull-clearance reasons that are sound, with the delivery consequence never costed. The model has no droplet physics: it moves tonnes from a tank to a coordinate.

And AFUE — 27,611 observed drops — reports probability of success **0.56 without ground engagement against 0.72 with it**, the modal outcome without ground crews being *not effective*. AFUE never counts tonnes. This project's headline metric is tonnes per hour.




Figure 8. Every constant moved $\pm 20\%$, measured rather than asserted. The top of the table is aerodynamics and speed; the two constants corrected on 2026-08-09 now move the headline by 0.8% and 0.0%.

These energy figures come from the earlier flight model, which understates the force needed to hold an empty hull down. Corrected figures will be higher, and some cycles may not be flyable as drawn.

8.5 The other nine, in one line each

#	Defect	Cost
1	Lift bought at sea level, spent at altitude	fixed 2026-08-09; hulls grew 22.2%
2	Two power models disagree	planCycle vs integrated stateAt: 2.83 × on the P-10000
3	An unexplained 0.2 sets the letdown window	1.42 MWh today; was 34.20 before the anchor
4	Retained ballast is dead code; the plant is inert in-cycle	ballast fixed ; plant restated (\$7.2)
5	Esri basemap tiles used outside their terms	not physics; blocking for publication
6	Generators supply peak power but no energy	150 MW uncounted on the P-10000; \$8.2 shows what that concealed
7	32 of 89 published figures rest on unjustified constants	two inline drag multipliers are worth 16.9 MWh
8	diskM2/battMW answer a superseded constraint	battMW $\pm 20\%$ now moves every figure by 0.0%
0	The sizing requirement that ties #1, #4 and #6 together	the tank is sized to land a dead hull, not to ballast a cycle
—	Rotor wash over a water surface is unmodelled — not a numbered entry	Suter (2005); a 121.6 MN anchor hangs in it

These energy figures come from the earlier flight model, which understates the force needed to hold an empty hull down. Corrected figures will be higher, and some cycles may not be flyable as drawn.

Defect 7 deserves a sentence of its own. The audit found that the constants nobody had questioned move the headline more than the defects everyone had: the two undocumented drag multipliers on the return and manoeuvring phases are worth 16.9 MWh a cycle, while defect 3 — flagged in the README since the first commit — is worth 1.4.

These energy figures come from the earlier flight model, which understates the force needed to hold an empty hull down. Corrected figures will be higher, and some cycles may not be flyable as drawn.

9. How to check any of this

```
“ git clone ... && cd airships && make check “
```

- `make golden` re-runs 151 class/mode/distance/wind combinations and diffs every output against `tests/golden/seed7-snapshot.json`.
- `make test` registers 233 tests in 59 suites, with 0 known-failing markers. Corrected defects run as ordinary assertions.
- `make test-node` runs a further 103. Until 2026-08-09 it printed "SKIPPED — no node here" on the machine this is developed on, so those 103 were only ever executed by CI and two breaks were found by a red badge after a push. They run in a browser now, against the same files, and `make check` covers them.
- `make factsheet` regenerates `research/figures.json` from the live model in a real browser; `tools/check_figures.py` then fails the build if any number in this paper disagrees with it. Every figure marked above passed that check at the commit that carries this file.
- `?seed=7&data=snapshot` makes any run on the live site exactly reproducible.

An independent Python replication reproduces the golden snapshot exactly.

10. What would have to be true

In descending order of how likely it is to kill the concept:

2026-10-02 correction: record basis, INFEASIBLE. Arrows preserve the dated value on the left and give the current model on the right. Energy and battery hours describe supplied effort on an unsupported profile, not achieved flight.

1. **A discrete-lattice vacuum shell at $\leq 0.455 \text{ kg/m}^3$ including everything.** Nothing in the literature is there. This is the concept's single point of failure and no amount of care in the rest of the model substitutes for it.
2. **Batteries at 200 Wh/kg pack-level with the rest of the vehicle free.** Not available.
3. **A 12,400 t bucket on a 440 mm cable, and a hull that can hold station over water while it hangs there.** The mechanism is a scaled Bambi bucket at 1,265 times the largest ever built (9,800 L) — the principle is 43 years old and the engineering is not. Pendulum dynamics under an 512 m hull are not modelled.

4. **A drop from 450 m that arrives as water rather than as mist.** Currently contradicted by the USFS's own guidance.
5. **An energy import chain.** The fleet is a battery being spent, and the 2026-08-09 solar correction made that sharper rather than softer: the smallest class now has $9.2 \rightarrow 1.4$ hours of work in it and the largest $30.2 \rightarrow 2.2$. Nothing here changes that; §7.3 is where it is costed.

These energy figures come from the earlier flight model, which understates the force needed to hold an empty hull down. Corrected figures will be higher, and some cycles may not be flyable as drawn.

If (1) fails, the rest is a well-tested model of a vehicle that cannot exist. That is why it is first on the list and why §8.1 is written the way it is.

What the two corrections of 2026-08-09 say about the other eleven. Both were found by reading a source rather than by running the model, both had been on the page for the life of the project, and neither was catchable by any test that existed — one because generation is absent from the ledger, the other because a test was asserting the violation as correct behaviour. The eleven still open should be read in that light: the list is what has been checked, not what is wrong.

11. Availability

Model, tests, sources and defect list: github.com/pinkrobotics/airships. Live simulation: pinkrobotics.ca/airships. The literature and the nine sources against us, written for a reader who has not cloned anything: pinkrobotics.ca/research. Source catalogue: `research/sources.json`; its current entry count is generated in the [repository README](#). The collection includes PDFs with provenance, written notes and sources that contradict the project. Claim audit: `research/evidence-map.md`.

Every figure marked in this document is generated by `tools/figures_dump.js` from the model at defaults and verified by `tools/check_figures.py`. Figures from cited sources are written plainly and accounted for in `research/sources.json`.

[historical] The dated “other” ledger aggregate has no current equivalent. The corrected ledger uses the six named phases and recovery; no current-model citation is claimed for the old aggregate. Both bases and all closing requirements are in [the generated closure comparison](#).