

no mac address-table static [MAC] vlan 1 interface [interface]

copy running-config startup-config

switchport mode access
switchport port-security maximum 1
switchport port-security violation shutdown
switchport port-security mac-address [mac]
show port-security interface [interfaz]
show port-security address

int VLAN 1 vlan 1 interface Fa0/5 switchport mode trunk
ip address [IP] [mask] name <nombre> switchport mode access switchport trunk allowed vlan [add/remove] 1
line vty 0 15 no vlan 1 switchport access vlan 1 show interfaces trunk
password cisco
login

ip dhcp pool [nombre]
network [ip] [mask]
default-router [ip] puerta de enlace de los hosts
dns-server [ip] servidor DNS (8.8.8.8)
ip dhcp excluded-address [ip]
show ip DHCP pool <nombre>
channel-group [numero] mode on
show etherchannel port

switchport access vlan [numero]
encapsulation dot1q [numero] interface fa0/1.10
encapsulation dot1q <10>
router rip ip address 192.168.1.1 255.255.255.0 (puerta de enlace)
version 2

router ospf [proceso]
network <dir_red><wildcard><area>

router bgp [AS]

RTB(config-router)# neighbor [IP] remote-as [AS]

Router(config)#

access-list <num_acl> [dynamic <nombre>]
{permit / deny}

<Protocolo>

<IP_origen> [<operador><puerto origen>]

<IP_destino> [<operador><puerto destino>]

[tipo_ICMP]

[established]

[precedence <p>]

[tos <t>]

[time-range <tiempo>]

[remark <comentario>]