



ENGINEERING EXCELLENCE

Brentwood Series #4BR132T


SPECIFICATION SHEET

DESCRIPTION

- Single Handle Tub and Shower Trim Set
- Beaux Lever Handle
- Ceramic Disc Cartridge with Temperature Limit Stop
- Four Function 3-3/8" Diameter Showerhead
- Shower Arm and Flange
- Combo 1/2" IPS/ Slip-On Diverter Tub Spout
- Tub Spout Escutcheon
- Color Match Sleeve and Retaining Ring

FINISHES

- PC PVD Polished Chrome
- BN PVD Brushed Nickel
- ORB Oil Rubbed Bronze



#4BR132T SHOWN * ADA



STANDARDS APPLICABLE

- ASME A112.18.1
- ANSI A117.1
- ADA COMPLIANT

FLOW

- Showerhead Limited to 2.5 GPM

Model #: _____

Specific Features: _____

Project Name: _____

Submitted For: _____

Model	Description	Finishes	
#4BR132T	Single Handle Tub and Shower Trim Set	<input type="checkbox"/> PC	<input type="checkbox"/> Other____
Required Valve			
#4020B	Single Handle Tub and Shower-Valve Set	<input type="checkbox"/> N/A	

DMSP4BR132T/REV. 03 2013

Page 1 of 2



ENGINEERING EXCELLENCE

Pioneer: 1-800-338-9468


Commerce, CA 90040

www.pioneerind.com

Pioneer Industries, Inc. © 2013

Installation Note:

Please refer to Installation Guide For this Product. Also Please refer to Installation Guide For the Rough-in Valve. Avoid Cross Flow Connections. Do not install a Shut off valve to any of the outlets. Install a 305 MM [12"] Straight Pipe with single elbow for bath between the rough-in valve and the tub spout.



Product Diagram



ENGINEERING EXCELLENCE

Pioneer: 1-800-338-9468

Commerce, CA 90040

www.pioneerind.com

Pioneer Industries, Inc. © 2013

DMSP4BR132T/REV. 03 2013

Page 2 of 2