



## ENGINEERING EXCELLENCE

Legacy Series #4LG300T

SPECIFICATION SHEET

### DESCRIPTION

- Single Handle Shower Trim Set
- Metal Lever Handle
- Ceramic Disc Cartridge with Temperature Limit Stop
- Four Function 3-3/8" Diameter Showerhead
- Shower Arm and Flange
- Color Match Sleeve and Retaining Ring

### FINISHES

- PC PVD Polished Chrome
- SS PVD Stainless Steel
- BN PVD Brushed Nickel
- PB PVD Polished Brass
- ORB Oil Rubbed Bronze



#4LG300T SHOWN \* ADA 

### STANDARDS APPLICABLE

- ASME A112.18.1
- CUPC / IAPMO LISTED

### FLOW

- Showerhead Limited to 1.75 GPM



Model #: \_\_\_\_\_

Specific Features: \_\_\_\_\_

Project Name: \_\_\_\_\_

Submitted For: \_\_\_\_\_

Model	Description	Finishes	
#4LG300T	Single Handle Shower Trim Set	<input type="checkbox"/> PC	<input type="checkbox"/> Other____
Required Valve			
#4020B	Single Handle Tub and Shower-Valve Set	<input type="checkbox"/> N/A	




ENGINEERING EXCELLENCE

Pioneer: 1-800-338-9468  
Commerce, CA 90040  
www.pioneerind.com  
Pioneer Industries, Inc. © 2013

DMSP4LG300T/REV. 12 2012  
Page 1 of 2

### Installation Note:

Please refer to Installation Guide For this Product. Also Please refer to Installation Guide For the Rough-in Valve. Avoid Cross Flow Connections. Do not install a Shut off valve to any of the outlets. Cap the Tub Port for Shower Only Installation



Product Diagram



ENGINEERING EXCELLENCE

Pioneer: 1-800-338-9468

Commerce, CA 90040

www.pioneerind.com

Pioneer Industries, Inc. © 2013

DMSP4LG300T/REV. 12 2012

Page 2 of 2