

HARNESS

GLASS ORDER — SEALED UNITS

Batch: **Batch T26**

Projects: P-26 (T26)

Date: 06/09/2026

Rev: **A**Units: **3**

Page: 1 / 3

GLASS SCHEDULE

#	Window	Sash	Width (mm)	Height (mm)	Shape	Type	Makeup	Spec	Coating	Gas	Finish	Spacer	Bars
1	SEMI-HUB springing 898.5 (69%) · 7 bars — see table	arched leaf	789	1293	 arched · R 394.5	double	4x16x4	toughened	Standard	Argon	clear	silver · warm	hub ast
2	TC-BARS springing 1198.5 (93%) · H1 y 599.3 · L 789 · V1 x 263 · 131.7 from apex L · L 1286.5 · V2 x 526 · 131.7 from apex R · L 1286.5	arched leaf	789	1293	 arched · R 44.5/1294.5	double	4x16x4	toughened	Standard	Argon	clear	silver · warm	1H×2V ast
3	GOthic-X springing 832.5 (53%) · 6 bars — see table	arched leaf	789	1574.2	 arched · R 894.5	double	4x16x4	toughened	Standard	Argon	clear	silver · warm	intersect ast

HARNESS

GLASS ORDER — SEALED UNITS

Batch: Batch T26


Projects: P-26 (T26)

Date: 06/09/2026


Rev: A

Units: 3


Page: 2 / 3



1 · SEMI-HUB — ARCHED LEAF GLASS
double 4x16x4 · toughened · Standard · Argon · clear · spacer: silver (warm edge) · bars: hub-spoke astragal · arched · R 394.5 · rise 394.5 · springing 898.5



2 · TC-BARS — ARCHED LEAF GLASS
double 4x16x4 · toughened · Standard · Argon · clear · spacer: silver (warm edge) · bars: 1H x 2V astragal · arched · R 44.5/1294.5 · rise 94.5 · springing 1198.5



3 · GOTHIC-X — ARCHED LEAF GLASS
double 4x16x4 · toughened · Standard · Argon · clear · spacer: silver (warm edge) · bars: intersecting astragal · arched · R 894.5 · rise 741.7 · springing 832.5

HARNESS

GLASS ORDER — SEALED UNITS

Batch: Batch T26

Projects: P-26 (T26)


Date: 06/09/2026

Rev: A

Units: 3


Page: 3 / 3

GLAZING BARS — POSITIONS PER SHAPED UNIT (ids as on the drawings)




1 · SEMI-HUB — ARCHED LEAF GLASS — arched · R 394.5 · 7 bars

ID	s from apex / position	L	angle / R
R1	R 118.4	372	c 394.5 / 898.5
S1	y 898.5	276	0°
K1	206.6 from apex R	276	60°
K2	206.6 from apex L	276	120°
S2	y 898.5	276	0°
V1	x 276.2	898.5	90°
V2	x 512.9	898.5	90°



2 · TC-BARS — ARCHED LEAF GLASS — arched · R 44.5/1294.5 · 3 bars

ID	s from apex / position	L	angle / R
H1	y 599.3	789	0°
V1	131.7 from apex L	1286.5	90°
V2	131.7 from apex R	1286.5	90°



3 · GOTHIC-X — ARCHED LEAF GLASS — arched · R 894.5 · 6 bars

ID	s from apex / position	L	angle / R
V1	x 197.3	832.5	90°
T1	450.5 from apex L	424	R 894.5
T2	125.3 from apex R	749.5	R 894.5
V2	x 591.8	832.5	90°
T3	125.3 from apex L	749.5	R 894.5
T4	450.5 from apex R	424	R 894.5