

HARNESS

GLASS ORDER — SEALED UNITS

Batch: Batch T26

Date: 06/09/2026

Rev: A

Projects: P-26 (T26)

Units: 3

Page: 1 / 3

GLASS SCHEDULE

#	Window	Sash	Width (mm)	Height (mm)	Shape	Type	Makeup	Spec	Coating	Gas	Finish	Spacer	Bars
1	SEMI-HUB springing 898.5 (69%) · 7 bars — see table	arched leaf	811	1304	 arched · R 405.5	double	4x16x4	toughened	Standard	Argon	clear	silver · warm	hub ast
2	TC-BARS springing 1198.5 (92%) · H1 y 599.3 · L 811 · V1 x 270.3 · 135.4 from apex L · L 1297 · V2 x 540.7 · 135.4 from apex R · L 1297	arched leaf	811	1304	 arched · R 55.5/1305.5	double	4x16x4	toughened	Standard	Argon	clear	silver · warm	1H×2V ast
3	GOTHIC-X springing 832.5 (52%) · 6 bars — see table	arched leaf	811	1587.4	 arched · R 905.5	double	4x16x4	toughened	Standard	Argon	clear	silver · warm	intersect ast

HARNESS

GLASS ORDER — SEALED UNITS

Batch: Batch T26


Projects: P-26 (T26)

Date: 06/09/2026


Rev: A

Units: 3


Page: 2 / 3



1 · SEMI-HUB — ARCHED LEAF GLASS
double 4x16x4 · toughened · Standard · Argon · clear · spacer: silver (warm edge) · bars: hub-spoke astragal · arched · R 405.5 · rise 405.5 · springing 898.5



2 · TC-BARS — ARCHED LEAF GLASS
double 4x16x4 · toughened · Standard · Argon · clear · spacer: silver (warm edge) · bars: 1H × 2V astragal · arched · R 55.5/1305.5 · rise 105.5 · springing 1198.5



3 · GOTHIC-X — ARCHED LEAF GLASS
double 4x16x4 · toughened · Standard · Argon · clear · spacer: silver (warm edge) · bars: intersecting astragal · arched · R 905.5 · rise 754.9 · springing 832.5

HARNESS

GLASS ORDER — SEALED UNITS

Batch: Batch T26

Projects: P-26 (T26)


Date: 06/09/2026

Rev: A

Units: 3


Page: 3 / 3

GLAZING BARS — POSITIONS PER SHAPED UNIT (ids as on the drawings)




1 · SEMI-HUB — ARCHED LEAF GLASS — arched · R 405.5 · 7 bars

ID	s from apex / position	L	angle / R
R1	R 121.7	382	c 405.5 / 898.5
S1	y 898.5	284	0°
K1	212.3 from apex R	284	60°
K2	212.3 from apex L	284	120°
S2	y 898.5	284	0°
V1	x 283.9	898.5	90°
V2	x 527.2	898.5	90°



2 · TC-BARS — ARCHED LEAF GLASS — arched · R 55.5/1305.5 · 3 bars

ID	s from apex / position	L	angle / R
H1	y 599.3	811	0°
V1	135.4 from apex L	1297	90°
V2	135.4 from apex R	1297	90°



3 · GOTHIC-X — ARCHED LEAF GLASS — arched · R 905.5 · 6 bars

ID	s from apex / position	L	angle / R
V1	x 202.8	832.5	90°
T1	460.1 from apex L	432.5	R 905.5
T2	128 from apex R	764.5	R 905.5
V2	x 608.3	832.5	90°
T3	128 from apex L	764.5	R 905.5
T4	460.1 from apex R	432.5	R 905.5