TD – laboratoria 0

Piotr Rogulski 305867

Szymon Sieradzki 305881

7 listopada 2020

```
Output
20  R1#show interfaces
21  Ethernet0/0 is administratively down, line protocol is down
22    Hardware is AmdP2, address is cc02.1a35.0000 (bia cc02.1a35.0000)
23    Internet address is 192.168.0.1/24
24    MTU 1500 bytes, BW 10000 Kbit/sec, DLY 1000 usec,
25       reliability 255/255, txload 1/255, rxload 1/255
26    Encapsulation ARPA, loopback not set
27    Keepalive set (10 sec)
28    ARP type: ARPA, ARP Timeout 04:00:00
29    Last input never, output never, output hang never
30    Last clearing of "show interface" counters never
31    Input queue: 0/75/0/0 (size/max/drops/flushes); Total output drops: 0
32    Queueing strategy: fifo
33    Output queue: 0/40 (size/max)
34    5 minute input rate 0 bits/sec, 0 packets/sec
35    5 minute output rate 0 bits/sec, 0 packets/sec
36       0 packets input, 0 bytes, 0 no buffer
37       Received 0 broadcasts, 0 runts, 0 giants, 0 throttles
38       0 input errors, 0 CRC, 0 frame, 0 overrun, 0 ignored
39       0 input packets with dribble condition detected
40       0 packets output, 0 bytes, 0 underruns
41       0 output errors, 0 collisions, 0 interface resets
42       0 unknown protocol drops
43       0 babbles, 0 late collision, 0 deferred
```

1 Konfiguracja ipv4

1.1 Konfiguracja routera R1

1.2 Konfiguracja routera R2

1.3 Połączenie między routerami

2 Konfiguracja ipv6

2.1 Konfiguracja routera R1

2.2 Konfiguracja routera R2

2.3 Połączenie między routerami