

III Akademickie Mistrzostwa Polski w Programowaniu Zespołowym



PROBLEM E

Moulds

In a factory, moulds for casting metal objects are produced by a special cutting device. The device is equipped with cuboid-shaped blade of size $1\text{ mm} \times 1\text{ mm} \times 30\text{ mm}$ (its height) which operates with each of its sides thus producing the mould from cuboid of size $250\text{ mm} \times 250\text{ mm} \times 30\text{ mm}$ (its height). The end of the blade never lowers below the bottom surface of the cuboid. In any moment the distance between initial and current position doesn't exceed 1000.

The machine understands special command language which has the following grammar:

```
<command block> ::= [ <command> ; {<command> ; } ]  
<command>      ::= <lift> | <shift> | <command block>  
<lift>         ::= ^ <distance>  
<shift>        ::= @ <direction> <distance>  
<direction>    ::= N | S | W | E  
<distance>     ::= <sign> <number> | <number>  
<number>       ::= <digit> {<digit>}  
<sign>         ::= - | +  
<digit>        ::= 0 | 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9
```

where $\{exp\}$ means zero or more exp s.

The command $\langle\text{lift}\rangle$ causes moving the blade downwards when the distance is a positive number and upwards otherwise. The command $\langle\text{shift}\rangle$ moves the blade in the appropriate direction (N—north, S—south, W—west, E—east).

Task

Write a program which for each data set from a sequence of several data sets:

- reads a command block from the text file E.IN,
- computes the volume of hollows made by the machine commanded by a given command block (assuming that before the execution the blade is located 1 mm above the north-west corner of the virgin cuboid),
- writes the result to the text file E.OUT.

Input

The first line of the input file E.IN contains one integer d , $1 \leq d \leq 10$, which is the number of data sets. The data sets follow. Each data set occupies one line of the input file and is a word derived from $\langle\text{command block}\rangle$ of the above grammar of length not exceeding 10000 characters.

Output

The i -th line of the text file E.OUT should contain one integer—the volume (in cubic mm) of the hollows made by the machine controlled by the command block given in the i -th data set.

Example

For the input file `E.IN`:

1

`[^2;@S2;]`

the correct result is the output file `E.OUT`:

3