

Best/Worst/Always and Asymptotic Notation

- ▶ The number of comparisons that InsertionSort makes on inputs of size n is:
 - ▶ $n - 1$ in the best case
 - ▶ $n(n - 1)/2$ in the worst case
 - ▶ $\geq n - 1$ and $\leq n(n - 1)/2$ on every input

Best/Worst/Always and Asymptotic Notation

- ▶ The number of comparisons that InsertionSort makes on inputs of size n is:
 - ▶ $n - 1$ in the best case
 - ▶ $n(n - 1)/2$ in the worst case
 - ▶ $\geq n - 1$ and $\leq n(n - 1)/2$ on every input
- ▶ The number of comparisons that InsertionSort makes on inputs of size n is:
 - ▶ $\Theta(n)$ in the best case
 - ▶ $\Theta(n^2)$ in the worst case
 - ▶ $\Omega(n)$ and $O(n^2)$ on every input

Best/Worst/Always and Asymptotic Notation

- ▶ The number of comparisons that InsertionSort makes on inputs of size n is:
 - ▶ $n - 1$ in the best case
 - ▶ $n(n - 1)/2$ in the worst case
 - ▶ $\geq n - 1$ and $\leq n(n - 1)/2$ on every input
- ▶ The number of comparisons that InsertionSort makes on inputs of size n is:
 - ▶ $\Theta(n)$ in the best case
 - ▶ $\Theta(n^2)$ in the worst case
 - ▶ $\Omega(n)$ and $O(n^2)$ on every input
- ▶ Typically we just say: InsertionSort makes $O(n^2)$ comparisons (suggesting implicitly that there is no better bound for the worst case).