

Welcome to COMP1081 - Algorithms and Data Structures

The lecture will begin at 5 past. While you wait, join respond to the PollEverywhere question by SMS or on the web at

<https://pollev.com/eamonn>

Consider the sequence of Fibonacci numbers $F(n)$ defined by

$$F(n) = \begin{cases} 0 & \text{for } n = 0 \\ 1 & \text{for } n = 1 \\ F(n-1) + F(n-2) & \text{for } n \geq 2 \end{cases}$$

Calculate $F(10)$.

Topic 5: Recursion and Backtracking

Eamonn Bell

`eamonn.bell@durham.ac.uk`

Recursive Algorithms: Factorials

- The factorial of a positive integer n is the product of all integers from 1 to n , often denoted $n!$.
- For example, $5! = 5 \times 4 \times 3 \times 2 \times 1$

Recursive Algorithms: Factorials

- The factorial of a positive integer n is the product of all integers from 1 to n , often denoted $n!$.
- For example, $5! = 5 \times 4 \times 3 \times 2 \times 1$
- Observe that $5! = 5 \times 4!$

Recursive Algorithms: Factorials

- The factorial of a positive integer n is the product of all integers from 1 to n , often denoted $n!$.
- For example, $5! = 5 \times 4 \times 3 \times 2 \times 1$
- Observe that $5! = 5 \times 4!$
- In this way, the problem of computing $5!$ breaks down into two subproblems:
 - Computing $4!$
 - ...and multiplying the result of that, by 5

Recursive Algorithms: Factorials

- The factorial of a positive integer n is the product of all integers from 1 to n , often denoted $n!$.
- For example, $5! = 5 \times 4 \times 3 \times 2 \times 1$
- Observe that $5! = 5 \times 4!$
- In this way, the problem of computing $5!$ breaks down into two subproblems:
 - Computing $4!$
 - ...and multiplying the result of that, by 5
- In turn, the problem of computing $4!$ can be broken down in a similar way.

Recursive Algorithms: Factorials

- The factorial of a positive integer n is the product of all integers from 1 to n , often denoted $n!$.
- For example, $5! = 5 \times 4 \times 3 \times 2 \times 1$
- Observe that $5! = 5 \times 4!$
- In this way, the problem of computing $5!$ breaks down into two subproblems:
 - Computing $4!$
 - ...and multiplying the result of that, by 5
- In turn, the problem of computing $4!$ can be broken down in a similar way.
- This makes the factorial function a candidate for implementation as a **recursive** algorithm.

Recursive Factorial: factorial(n)

if n=1 **then**

return 1

else

return $n \times \text{factorial}(n-1)$

end if

Recursive Factorial: factorial(n)

```
if n=1 then  
    return 1  
else  
    return n  $\times$  factorial(n-1)  
end if
```

Iterative Factorial

```
total = 1  
for i=1 to n do  
    total = total  $\times$  i  
end for  
return total
```

Recursive Algorithms

- A **recursive** algorithm is an algorithm that calls itself to do part of its work.
- A recursive algorithm must have a **base case**.
- A recursive algorithm must **change** its state and move toward the base case.
- A recursive algorithm must **call itself**, **recursively**.

Iterative Sum of a list L

```
sum = 0
for i in L do
    sum = sum + i
end for
return sum
```

Iterative Sum of a list L

```
sum = 0
for i in L do
    sum = sum + i
end for
return sum
```

Recursive Sum of a list L: listsum(L)

```
if len(L) = 1 then
    return L[0]
else
    return L[0] + listsum(L[1:])
end if
```

Memoization

- A recursive implementation of the function to compute the n th Fibonacci number will be called **several times** with the same argument.
- We could **store** the result of these intermediate function calls, because these results do not change over time.

Memoization

- A recursive implementation of the function to compute the n th Fibonacci number will be called **several times** with the same argument.
- We could **store** the result of these intermediate function calls, because these results do not change over time.
- **Storing the result of a computation so that it can be subsequently retrieved without repeating the computation** is called **memoization**.
- **Hash tables** are a good choice of data structure to implement **memoization**.

The lecture will begin at 5 past. While you wait, join respond to the PollEverywhere question by SMS or on the web at <https://pollev.com/eamonn>

Consider an implementation of the function **floodfill** given below, where x and y represent pixel locations in a 2D screen

floodfill(x, y)

if (x,y) is out of range or already filled **then**

return

end if

colour in pixel at location (x,y)

floodfill(x+1,y)

floodfill(x-1,y)

floodfill(x,y+1)

floodfill(x,y-1)

A Recursive Technique: Backtracking

- A technique for problems with many **candidate** solutions but too many to try.
- For example: there are 6,670,903,752,021,072,936,960 ways to fill in a sudoku grid.

A Recursive Technique: Backtracking

- A technique for problems with many **candidate** solutions but too many to try.
- For example: there are 6,670,903,752,021,072,936,960 ways to fill in a sudoku grid.
- **General idea**: build up the solution one step at a time, **backtracking** when unable to continue.

Generic algorithm (informal)

- 1 Do I have a solution yet?
- 2 No. Can I extend my solution by one “step”?
- 3 If yes, do that.
- 4 Do I have a solution now? If yes, I’m done.
- 5 If not, try and extend again.
- 6 When I can’t extend, take one step back and try a different way.
- 7 If no other extension available, then give up — no solution can be found.

► Sudoku demo from Wikimedia Commons

Generic algorithm

extend_solution(current solution)

```
if current solution is valid then  
    if current solution is complete then  
        return current solution  
    else  
        for each extension of the current solution do  
            extend_solution(extension)  
        end for  
    end if  
end if
```

Generic algorithm


extend_solution(current solution)

```
if current solution is valid then  
    if current solution is complete then  
        return current solution  
    else  
        for each extension of the current solution do  
            extend_solution(extension)  
        end for  
    end if  
end if
```

For sudoku, start by calling extend_solution with the partially filled grid that is given to you.


Knights

A knight is a chess piece that can move by moving one square in one direction and two squares in a perpendicular direction.



A Knight's Tour

A Knight's Tour: to move a knight around a chessboard such that each square is visited exactly **once**.



A Knight's Tour: using the generic algorithm

- What is a (partial) solution?

A Knight's Tour: using the generic algorithm

- What is a (partial) solution?
 - Just a list of squares in the order they are visited.

A Knight's Tour: using the generic algorithm

- What is a (partial) solution?
 - Just a list of squares in the order they are visited.
- When is it valid?

A Knight's Tour: using the generic algorithm

- What is a (partial) solution?
 - Just a list of squares in the order they are visited.
- When is it valid?
 - No squares visited more than once.

A Knight's Tour: using the generic algorithm

- What is a (partial) solution?
 - Just a list of squares in the order they are visited.
- When is it valid?
 - No squares visited more than once.
 - Knight has not jumped off the board

A Knight's Tour: using the generic algorithm

- What is a (partial) solution?
 - Just a list of squares in the order they are visited.
- When is it valid?
 - No squares visited more than once.
 - Knight has not jumped off the board
- When is it complete?

A Knight's Tour: using the generic algorithm


- What is a (partial) solution?
 - Just a list of squares in the order they are visited.
- When is it valid?
 - No squares visited more than once.
 - Knight has not jumped off the board
- When is it complete?
 - Every square visited: 64 items in the list.

A Knight's Tour: using the generic algorithm

- What is a (partial) solution?
 - Just a list of squares in the order they are visited.
- When is it valid?
 - No squares visited more than once.
 - Knight has not jumped off the board
- When is it complete?
 - Every square visited: 64 items in the list.
- How can the current solution be extended?

A Knight's Tour: using the generic algorithm

- What is a (partial) solution?
 - Just a list of squares in the order they are visited.
- When is it valid?
 - No squares visited more than once.
 - Knight has not jumped off the board
- When is it complete?
 - Every square visited: 64 items in the list.
- How can the current solution be extended?
 - Consider each of the eight possible moves.



Using the generic algorithm

extend_solution(current solution)

```
if current solution is valid then  
    if current solution is complete then  
        return current solution  
    else  
        for each extension of the current solution do  
            extend_solution(extension)  
        end for  
    end if  
end if
```

Using the generic algorithm

extend_solution(current solution)

if current solution is valid **then**

if current solution is complete **then**

return current solution

else

for each extension of the current solution **do**

 extend_solution(extension)

end for

end if

end if

Using the generic algorithm

```
extend_solution(current solution)  
if current solution is valid then  
    if current solution is complete then  
        return current solution  
    else  
        for each of eight possible moves do  
            extend_solution(extension)  
        end for  
    end if  
end if
```

Using the generic algorithm

extend_solution(current solution)

```
if current solution is valid then  
    if current solution is complete then  
        return current solution  
    else  
        for each of eight possible moves do  
            extend_solution(current solution with move  
                           added)  
        end for  
    end if  
end if
```

Using the generic algorithm

extend_solution(current solution)

```
if current solution is valid then  
    if current solution is complete then  
        return current solution  
    else  
        for each of eight possible moves do  
            extend_solution(with move added)  
        end for  
    end if  
end if
```

Using the generic algorithm

extend_solution(current solution)

```
if new move is to unvisited square on the board then  
    if current solution is complete then  
        return current solution  
    else  
        for each of eight possible moves do  
            extend_solution(with move added)  
        end for  
    end if  
end if
```

Using the generic algorithm

extend_solution(current solution)

```
if new move is to unvisited square on the board then  
    if current solution is complete then  
        return current solution  
    else  
        for each of eight possible moves do  
            extend_solution(with move added)  
        end for  
    end if  
end if
```

Using the generic algorithm

extend_solution(current solution)

```
if new move is to unvisited square on the board then  
    if every square has been visited then  
        return current solution  
    else  
        for each of eight possible moves do  
            extend_solution(with move added)  
        end for  
    end if  
end if
```

Using the generic algorithm

extend_solution(current solution)

```
if new move is to unvisited square on the board then
    if every square has been visited then
        return current solution
    else
        for each of eight possible moves do
            extend_solution(with move added)
        end for
    end if
end if
```

So we have an algorithm for Knight's Tour . . .

Implementing Knight's Tour

- Rather than having a list of moves made, it is easier to maintain an 8×8 array recording when each square was visited (initially all values are zero).

Implementing Knight's Tour

- Rather than having a list of moves made, it is easier to maintain an 8×8 array recording when each square was visited (initially all values are zero).
- Use a counter to record how many squares have been visited.

Implementing Knight's Tour

- Rather than having a list of moves made, it is easier to maintain an 8×8 array recording when each square was visited (initially all values are zero).
- Use a counter to record how many squares have been visited.

The algorithm is practical for a 6×6 board, but rather slow for an 8×8 board and impractical for much larger boards. What additional ideas could we add to the algorithm?