

Needle Valves - Male/Male

Mod. 054 - 056



Applications:

• Pressure instruments isolation (gauges, switches, transmitters, etc.)

Connections:

Threaded to ANSI-ASME B1.20.1 ISO 228 - ISO 7/1

Rating:

Standard: 6,000 PSI (420 bar)Optional: 10,000 PSI (700 bar)

Seals:


Standard: PTFE (T ≤ 200° C)
Optional: Graphite (T > 200° C)


Features:


- Non rotating trim
- Bonnet locking pin
- Dust cup
- Easy operation



Ordering Information







Dimensions		L	W	Н	M
В	1/4"	80	39	32	98
С	3/8"	80	39	32	98
D	1/2"	80	39	32	98
Е	3/4"	80	44	40	115
F	1"	80	44	40	115



Options

		Availability				
-H	-L -P	Needle Valves	Manifolds	Monoflanges	Ball Valves	
Α	Antitamper Actuator	~	~	~	~	
В	Bolted Bonnet			~	~	
F	Oval Flange		~			
G	Graphite seals		~	~	~	
Н	Rating 10.000 PSI (2)		~			
K1	Mechanical Electrical Contact				~	
K2	Magnetic Electrical Contact				~	
KG	Graphite bonnet seals replacement kit		~	~	~	
KT	PTFE bonnet seals replacement kit		~	~	~	
L	Locking Device			~	~	
0	Oxygen Service	~	~	~	~	
Р	Padlock	~		~	~	
Q	Quick Locking Device	~	~	~	~	
R	Swivelling Fitting	~		~	~	
Υ	Bonnet O.S.&Y.	~		~	~	
TV	Painting Treatment		~	~	~	
TF	Phosphatization Treatment (1)		~	~	~	
TZ	Zinc Plating Treatment (1)	~	~	~	~	
U45-V	7/16" UNF L=45 mm screws and nuts kit (2 screws - 2 nuts) for 2 valves manifold		~			
U75-2V	7/16" UNF L=75 mm screws and nuts kit (2 screws - 2 nuts) for 2 valves manifold		~			
U45-3/5V	7/16" UNF L=45 mm screws and nuts kit (4 screws - 4 nuts) for 3 and 5 valves manifold		~			
U75-3/5V	7/16" UNF L=75 mm screws and nuts kit (4 screws - 4 nuts) for 3 and 5 valves manifold		~			
W	2" Pipe bracket		~			
AT	Atex Version	~	~	~	~	
GR	Gost R Version	~	~	~	~	
FS	Fire Safe Version		~	~	~	
TA	Fugitive Emission TA-LUFT Version	~	~	~	~	
CRN	CURRENT CRN COMPLIANCE FOR 10 CANADIAN PROVINCES	~	~	~	~	
	n steel versions only					

⁽¹⁾ For carbon steel versions only.



Options

		Availability			
-H	-L -P	Needle Valves	Manifolds	Monoflanges	Ball Valves
IDX	Vent Bottom Right		~		
ISX	X Vent Bottom Left		~	~	~
M	Monel Trim		~	~	~
SPC 1	Special Marking - See descriptor		~	~	~
DIN 7756	Inlet Special Insert 1/8" NPT-M x DIN 7756 VG 8		~	~	~
2.0515 /DN15	Special DN15 marking requirement	~	~	~	~
3-G-GR -CUTR	GOST & CU-TR Certificate		~	~	~
X	Not Coded Option		~	~	~
?	?	~	~	~	~
?	?	~	~	~	~
?	?	~	~	~	~
?	?	~	~	~	~
?	?	~	~	~	~
?	?	~	~	~	~
?	?	~	~	~	~
?	?	~	~	~	~
?	?		~	~	~
?	?		~	~	~
?	?	~	~	~	~
?	?	~	~	~	~
?	?	~	~	~	~
?	?	~	~	~	~
?	?	~	~	~	~
?	?	~	~	~	~
?	?	~	~	~	~
?	?	~	~	~	~
?	?	~	~	~	~
?	?	~	~	~	~

⁽¹⁾ For carbon steel versions only.

⁽²⁾ For flanged, BW, SW versions operating limits as for reference rules.



Available Bonnet Styles

S.S. Dust Cap Bonnet



O.S.&Y. Bonnet with locking device



Original Bonnet

O.S.&Y. Bonnet



Bolted Bonnet



O.S.&Y. Bonnet



Anti-Tamper Bonnet



Standard Bonnet with locking device

