
Exercises: Advanced Lesson 15

Your Name: Mikey Ferguson

Your Math Class: MATH 7013 – Advanced Mathematical Modeling

1: What Is The Current Context?

```
$Context
```

2: What Is The Current Context Path?

```
$ContextPath
```

3: Create a new symbol (with name: "newSymbol") in the current context and assign it the value: "Current".

```
Clear[newSymbol];  
newSymbol = "Current";  
{Context[newSymbol], newSymbol}
```

4: Specify a new context (with name: newContext) and create the same symbol with a completely different value of: "New".

```
Begin["newContext`"];  
newSymbol = "New";  
End[]  
  
{Context[newSymbol], newSymbol, NameQ["newContext`newSymbol"]}  
  
newSymbol = "Current";  
newContext`newSymbol = "New";  
{newSymbol, newContext`newSymbol}
```

5: Ask for information on "newSymbol" in both contexts

```
?Global`newSymbol  
  
?newContext`newSymbol
```

6: Why must you use the Remove command (rather than just the Clear or ClearAll commands) on a symbol listed in context Global` if you want to access that same symbol in a different context (assume that the default context is Global`)?

```
Clear[newSymbol];  
{Context[newSymbol], ValueQ[newSymbol], NameQ["Global`newSymbol"]}  
  
Remove["Global`newSymbol"];  
NameQ["Global`newSymbol"]
```

Clear only empties the symbol; the name `Global`newSymbol` still exists, and since `Global`` comes first on the context path it is still the one found when `newSymbol` is typed. `Remove` deletes the name itself, so the search moves past it and finds the symbol in the other context.