

Analysis Cluster

All content

Space settings

Content

Search by title

Login Node (submit0) A...

Connecting to submit...

Connecting to submit...

Slurm

Application Managemen...

Storage Access

Posit Workbench

Apps

Courses

Connecting to submit0 from macOS

RS

Owned by [Ryan Seaman](#) ...

Last updated: Mar 28, 2025 · 1 min read · [🔗](#) 7 people viewed

Open a terminal

The first step is to open a terminal. It doesn't matter whether you use the Terminal application from the Utilities folder or an xterm from the X11 application, either will work.

Configure your terminal for X11 forwarding

You need to have these variables defined in your bash and ssh config files in order to properly forward X11 applications from the analysis servers to your display.

```
1 echo "export DISPLAY=:0" >> ~/.bash_profile
2 echo "export DISPLAY=:0" >> ~/.zshrc
3 echo -e "Host *\n\tXAuthLocation /opt/X11/bin/xauth" >> ~/.ssh/config
4 exit
```

Also from Terminal, run the following command:

```
1 defaults write org.xquartz.X11 enable_iglx -bool true
```

Close and reopen your terminal to apply your changes.

Connect to submit0 via SSH

Once a terminal is opened, connect to the server you want to use with a command like this:

```
1 ssh -YC submit0.laureateinstitute.org
2 ssh -YC <username>@submit0.laureateinstitute.org
```

The options used above are:

- Y - enable X11 forwarding
- C - enable compression
- <username>@ - specify a username if it's different from the username on your local machine. If it's the same, it can be left out. In the majority of cases, you'll leave this out.

Example

```
1 ssh -YC submit0.laureateinstitute.org
2 ssh -YC rseaman@submit0.laureateinstitute.org
```

Run your application

- Double-click the session you want to load. If you'd like to run a windowed application interactively, there are [a few steps to take](#) prior to connecting to submit0. If you don't intend to run an interactive job or have already followed the instructions in the previous link, you can submit a job for the cluster to run ([Submitting jobs](#)).

Related content ⓘ

Connecting to submit0 from Windows

Analysis Cluster

🔍 More like this

Slurm

Analysis Cluster

📄 Read with this

Informational Commands

Analysis Cluster

📄 Read with this

Using an Interactive Bash Shell on the Analysis Cluster

Analysis Cluster

🔍 More like this

Application Management (Lmod)

Analysis Cluster

📄 Read with this

Partitions

Analysis Cluster

📄 Read with this