

- All content
- Space settings

Content

Search by title

- Login Node (submit0) A...
- Connecting to submit...
- Connecting to submit...
- Slurm
- Partitions
- Informational Comma...
- Job Management Co...
- Using an Interactive ...
- Job Submission Exam...
- Scrontab
- Application Managemen...
- Python Modules
- R Modules
- Storage Access
- Posit Workbench

Apps

Courses

R Modules

Owned by [Ryan Seaman](#)

Last updated: May 13, 2025 · 2 people viewed

R modules are configured to create a specific directory for users where they can install packages for the specific version of R that module loads. The modules also automatically set the environment variables so that R knows where to install and find these packages.

The directory looks like this (replace <user> with your username and <version> with the version of R you are using):

```
1 /home/librad.laureateinstitute.org/<user>/R/<R_version>
```

These are the variables and how they are set:

```
1 R_LIBS = $R_LIBS:/home/librad.laureateinstitute.org/<user>/R/<version>
2 R_USER_LIBS = /home/librad.laureateinstitute.org/<user>/R/<version>
```

Sample Output:

```
1 [user@submit0 ~]$ echo $R_LIBS
2 ~/R/3.5.1:/opt/apps/core/R/3.5.1/lib64/R/library
3 Within the R shell:
4 > install.packages('car')
```

Related content

Python Modules

Analysis Cluster

More like this

Application Management (Lmod)

Analysis Cluster

More like this

Storage Access

Analysis Cluster

More like this

Be the first to add a reaction