

AD 2-LHBC-RNAV_(GNSS) 35

Only aircraft, equipment and aircrew approved by the State of the Operator to carry out GNSS approaches, may use the procedure.

Arrivals:

Arrivals on 081° clockwise to 321° may enter the initial approach directly at 4000, according to the advice of BÉKÉSCSABA INFO.

Other arrivals must enter the holding.

Holding procedure:
Holding fix: BC001 (IAWP/MAHWP).
Right hand holding pattern.
Inbound track: 021°
Outbound track: 201°
Rate of turn: 3°/sec or 35°

3°/sec. or 25° bank angle (whichever requires lesser bank)

Outbound distance: 4,0 km Minimum holding altitude: 4000

Final approach descent: 3,00°

WAYPOINT COORDINATES

AD 2-LHBC-RNAV _(GNSS) 35			
WAYPOINT	LATITUDE	LONGITUDE	WAYPOINT TYPE
BC001	N46 39 53.6	E021 09 54.3	IAWP
BC002	N46 32 06.3	E021 04 45.2	IAWP
BC003	N46 32 30.8	E021 10 55.7	IWP
BC004	N46 36 03.6	E021 10 26.2	FAWP
BC005	N46 40 39.2	E021 09 48.0	MAWP
BC006	N46 47 15.8	E021 08 52.8	MATWP
BC001	N46 39 53.6	E021 09 54.3	MAHWP

HungaroControl C **AIRAC AMDT 004/2010**