

RDBI External API specification 1.0 draft

Erik Hollensbe <erik@hollensbe.org>

Table of Contents

1	All Classes	1
2	module DBI	2
	Method Index	3

1 All Classes

Boolean reload

[Method on All Classes]

this method will semantically refresh items, such as Schema objects or rows, depending on the context of the object in question.

2 module DBI

DBH connect (*Class klass, Array *args, Proc &block*) [Method on DBI]

class is a ruby class which corresponds to the database driver. it is no longer a string.

*args is a hash with parameter -> value associations, such as :host or :username.

Optionally yields a block for usage, yields a freshly connected DBH.

Array of Class drivers [Method on DBI]

accessor to get at known classes that can be used as drivers.

DBH connect_cached (*Class klass, Array *args*) [Method on DBI]

connect to a new resource if one is required (or desired, see below) with similar parameters as connect().

additional arguments :pool_name and :pool_size can be used to define a Pool (object, see below) which holds a specific subset of connected database handles. Playing with the size here introduces the ability for connect_cached to maintain a minimum number of connections which can be re-used over the lifetime of a program.

Pool pool (*String pool_name*) [Method on DBI]

a pool as described above is an array of database handles. this returns that data as a "Pool" object, with its own API. See later on in the document.

Pool all_connections [Method on DBI]

similar to pool(), this returns all the connections, but ignores pools.

Integer ping (*Class klass, Array *args*) [Method on DBI]

similar to connect(), this issues a ping to the databases. This may issue a connect() before the ping() to do it properly depending on the database implementation.

Boolean reconnect_all [Method on DBI]

reconnects all the known database handles.

DBH last_dbh [Method on DBI]

returns the last returned dbh from connect() or connect_cached()

this method, by definition, can be unpredictable in threaded environments.

Method Index

A

`all_connections` on DBI 2

C

`connect` on DBI 2

`connect_cached` on DBI 2

D

`drivers` on DBI 2

L

`last_dbh` on DBI 2

P

`ping` on DBI 2

`pool` on DBI 2

R

`reconnect_all` on DBI 2

`reload` on All Classes 1