The CLI (`v0.1.10`) handles authentication, QR sideloading, and app packaging.

Installation

```bash
npm install -D @evenrealities/evenhub-cli
```

Or install globally:

```bash
npm install -g @evenrealities/evenhub-cli
```

> **npm:** [@evenrealities/evenhub-cli]

Commands

`evenhub login`

Authenticate with your Even Hub developer account.

```bash
evenhub login
evenhub login -e your@email.com
```

Option	Description
`-e` , `--email <email>`	Your account email

`evenhub init`

Generate a starter `app.json` manifest in the current or specified directory.

bash

```bash
evenhub init
evenhub init -d ./my-project
evenhub init -o ./config/app.json
```

Option	Description
`-d` , `--directory <dir>`	Directory to create the file in (default: `./`)
`-o` , `--output <path>`	Output file path (overrides `--directory`)

`evenhub qr`

Generate a QR code for sideloading your app during development.

bash

```bash
# Simplest usage — provide the full URL
evenhub qr --url "http://192.168.1.100:5173"

# Or build the URL from parts
evenhub qr -i 192.168.1.100 -p 5173 --path /my-app

# Output to a file instead of terminal
evenhub qr --url "http://192.168.1.100:5173" -e
```

Option	Description
`-u` , `--url <url>`	Full URL (ignores other URL options)
`-i` , `--ip <ip>`	IP address or hostname
`-p` , `--port <port>`	Port number
`--path <path>`	URL path
`--https`	Use HTTPS instead of HTTP
`--http`	Use HTTP (default)
`-e` , `--external`	Open QR in external program instead of terminal

Option	Description
`-s` , `--scale <n>`	Scale factor for file output (default: 4)
`--clear`	Clear cached scheme, IP, port, and path

Scan the QR code with the **Even Realities App** on your phone. Your app loads on the glasses with hot reload support.

`evenhub pack`

Package your built app into an `.ehpk` file for distribution.

```bash
evenhub pack app.json dist -o myapp.ehpk
```

Argument / Option	Description
`<json>`	Path to your `app.json` manifest
`<project>`	Path to your built output folder (`dist` , `build` , etc.)
`-o` , `--output <file>`	Output filename (default: `out.ehpk`)
`--no-ignore`	Include hidden files (dotfiles)
`-c` , `--check`	Check if the `package_id` is available on Even Hub

See [Packaging & Deployment](#) for the full `app.json` schema, validation rules, and troubleshooting guide.

Shell Completions

Generate completions for your shell:

```bash
evenhub --completion-bash   # Bash
evenhub --completion-zsh    # Zsh
evenhub --completion-fish   # Fish
```

Previous page
Packaging & Deployment