The `app.json` Manifest

Every Even Hub app requires an `app.json` manifest. Generate a starter file with:

```bash
evenhub init
```

This creates the following template:

```json
{
  "package_id": "com.example.g2demo",
  "edition": "202601",
  "name": "G2 Demo",
  "version": "0.1.0",
  "min_app_version": "2.0.0",
  "min_sdk_version": "0.0.7",
  "entrypoint": "index.html",
  "permissions": [
    {
      "name": "network",
      "desc": "This app needs to access the network in order to ...",
      "whitelist": ["https://example.com"]
    }
  ],
  "supported_languages": ["en"]
}
```

Field Reference

Field	Type	Required	Rules
`package_id`	string	Yes	Reverse-domain format (e.g., `com.yourname.appname`). Each segment must start with a **lowercase letter** and contain only **lowercase letters or numbers**. Minimum two segments. No hyphens.
`edition`	string	Yes	Must be `"202601"` (current edition).
`name`	string	Yes	**20 characters or fewer.**
`version`	string	Yes	Semver format: `x.y.z` (e.g., `"1.0.0"`).
`min_app_version`	string	Yes	Minimum Even Realities App version required (e.g., `"2.0.0"`).
`min_sdk_version`	string	Yes	Minimum SDK version required (e.g., `"0.0.7"`).
`entrypoint`	string	Yes	Path to your HTML entry file relative to the build folder (e.g., `"index.html"`).
`permissions`	array	Yes	Array of permission objects (see below). Can be empty `[]`.
`supported_languages`	array	Yes	Array of language codes. Valid values: `en`, `de`, `fr`, `es`, `it`, `zh`, `ja`, `ko`.

Permissions Format

Permissions are an **array of objects**, not a key-value map. Each object must have:

Key	Type	Required	Notes
`name`	string	Yes	One of: `network`, `location`, `g2-microphone`, `phone-microphone`, `album`, `camera`
`desc`	string	Yes	Human-readable reason, **1–300 characters**.

Key	Type	Required	Notes
`whitelist`	string[]	`network` only	List of allowed domains. Optional, defaults to `[]` .

Example with multiple permissions:

```json
"permissions": [
  {
    "name": "network",
    "desc": "Fetches weather data from the API.",
    "whitelist": ["https://api.weather.com"]
  },
  {
    "name": "g2-microphone",
    "desc": "Enables voice commands for hands-free control."
  },
  {
    "name": "location",
    "desc": "Shows nearby points of interest on the display."
  }
]
```

:::caution[Common mistake] The permissions field must be an **array of objects** — not a key-value map. This format is incorrect and will fail validation:

```json
"permissions": { "network": ["example.com"] }
```

:::

Building and Packing

Step 1: Build your web app

```bash
npm run build
```

This produces your output directory (typically `dist/` or `build/`).

Step 2: Pack into `.ehpk`

bash

```bash
evenhub pack app.json dist -o myapp.ehpk
```

Argument	Description
`app.json`	Path to your manifest file
`dist`	Path to your **built** output folder
`-o myapp.ehpk`	Output filename (defaults to `out.ehpk`)
`--no-ignore`	Include hidden files (dotfiles) — excluded by default
`-c` , `--check`	Check if your `package_id` is available on Even Hub

TIP

The `entrypoint` in your `app.json` must point to a file that **exists inside the build folder**. If your manifest says `"entrypoint": "index.html"` but the build folder doesn't contain `index.html` , packing will fail with:

```
Entrypoint file not found: dist/index.html
```

Troubleshooting `evenhub pack`

When packing fails, the CLI prints specific validation errors. Here are the most common ones and how to fix them:

`Invalid package id`

```
package_id: must be a valid package name (e.g., com.example.app).
Each segment must start with a lowercase letter and contain only
```

```
lowercase letters or numbers. Two or more segments are required.
```

Fix: Use lowercase reverse-domain format with at least two segments. No hyphens, no uppercase, no leading numbers in any segment.

Invalid	Valid
`My-App`	`com.myname.myapp`
`com.my-app.v2`	`com.myapp.v2`
`myapp`	`com.example.myapp`
`com.2fast.app`	`com.twofast.app`

`name: must be 20 characters or fewer`

Fix: Shorten your app name. Use the `tagline` or `description` fields for longer text.

`version: must be in x.y.z format`

Fix: Use three-part semver: `"1.0.0"`, not `"1.0"` or `"v1.0.0"`.

`min_app_version / min_sdk_version: expected string, received undefined`

Fix: Both fields are **required**. Add them to your `app.json`:

```json
"min_app_version": "2.0.0",
"min_sdk_version": "0.0.7"
```

`permissions: each permission must be an object with "name" ...`

Fix: Permissions must be an array of objects with `name` and `desc` keys. See the Permissions Format section above.

`supported_languages: invalid language`

Fix: Use lowercase ISO codes from the supported set: `en` , `de` , `fr` , `es` , `it` , `zh` , `ja` , `ko` .

Entrypoint file not found

Fix: Make sure the file referenced by `entrypoint` exists inside your build folder. If your Vite output goes to `dist/` and your entrypoint is `index.html` , check that `dist/index.html` exists.

Project folder not found

Fix: The second argument to `evenhub pack` must be a **path to an existing directory** containing your built files. Run your build step first (`npm run build`).

Distribution

Once submitted, your app becomes available on **Even Hub**. Users can:

- **Download** your app from the Even Hub page
- **Launch** it from the glasses menu or through the Even Realities App on their phone

---

Previous page
Simulator

Next page
CLI