The simulator (`v0.6.2`) lets you preview UI layouts and test logic without physical hardware. It is a supplement to — not a replacement for — hardware testing.

Installation

```bash
npm install -g @evenrealities/evenhub-simulator
```

> **npm:** @evenrealities/evenhub-simulator — cross-platform (macOS, Linux, Windows)

Usage

```bash
evenhub-simulator [OPTIONS] [targetUrl]
```

Options

Option	Description
`-c` , `--config <path>`	Path to config file (use `--print-config-path` to see the default)
`-g` , `--glow`	Enable glow effect on glasses display
`--no-glow`	Disable glow effect (overrides config)
`-b` , `--bounce <type>`	Bounce animation type: `default` or `spring`

Option	Description
`--list-audio-input-devices`	List available audio input devices
`--aid <device>`	Choose a specific audio input device
`--no-aid`	Use default audio device (overrides config)
`--print-config-path`	Print the default config file path and exit
`--completions <shell>`	Generate shell completions: `bash` , `elvish` , `fish` , `powershell` , `zsh`
`-V` , `--version`	Print version
`-h` , `--help`	Print help

Default Config File Paths

Platform	Location
Linux	`$XDG_CONFIG_HOME` or `$HOME/.config`
macOS	`$HOME/Library/Application Support`
Windows	`{FOLDERID_RoamingAppData}` (e.g., `C:\Users\<user>\AppData\Roaming`)

Audio

The simulator emits `audioEvents` with the following specification:

- Sample rate: 16,000 Hz
- Format: signed 16-bit little-endian PCM
- 100ms of data per event (3,200 bytes / 1,600 samples)

Screenshot (v0.5.0+)

The simulator supports exporting the glasses display as an RGBA PNG file. Upon clicking the screenshot button, it exports to your current working directory with a timestamp-based filename. The file path is logged to both the simulator stdout and the glasses web inspector console.

The screenshot is not affected by the glow flag — that is a visual post-processing effect only.

Caveats

- **Display rendering** may not perfectly match hardware (font rendering, greyscale levels). Sufficient for layout validation and logic testing.
- **List scrolling** behavior (focused-item positioning) can differ from real glasses.
- **Image processing** is faster and does not enforce hardware size limits.
- **Events:** Status events are not emitted (user/device profiles are hardcoded). Supported inputs: Up, Down, Click, Double Click.
- **Error handling** may differ from hardware under abnormal conditions.

Always validate on actual hardware before deployment. If you find discrepancies that affect logic, please file a bug report in the Discord.

Previous page
Community Resources

Next page
Packaging & Deployment