

Objective(s):

- To implement a sorting algorithm as specified.
- To measure its performance.

### Task 1:

0 to blockSize - 1		blockSize to 2 * blockSize - 1		2blockSize to 3 * blockSize - 1		3blockSize to 4 * blockSize - 1		4blockSize to 5 * blockSize - 1		5blockSize to arr.length - 1
10	13	9	15	18	21	13	8	5	11	3
10	13	9	15	18	21	8	13	5	11	3
9	10	13	15	8	13	18	21	3	5	11
8	9	10	13	13	15	18	21	3	5	11
3	5	8	9	10	11	13	13	15	18	21

The figure above shows the process of sorting  $n$  numbers. This algorithm process is as follows:

- Break the data into chunks of blockSize i.e., if the blockSize is 32, blocks are as follows: 0 – 31, 32 – 63, ...,  $(n - 2) * blockSize - (n - 1) * blockSize - 1$ , lastBlock. Keep in mind that lastBlock may not be full.
- For each block, sort it.
- Repeat

Keep merging 2 consecutive blocks through all blocks. After each merge, the merged block's size is double, and its data is sorted.

Until there is only one block left.

.....

Complete the code given.

```
private static void whatSortIsThis(int [] arr) {
    int BLOCK_SIZE = arr.length / 4 > 32 ? 32 : arr.length / 4;
    for (int start = 0; start < arr.length; start += BLOCK_SIZE) {
        int end = Math.min(start + BLOCK_SIZE - 1, arr.length - 1);
        bite_size_sort(arr, start, end);
    }

    for (int mergeSize = BLOCK_SIZE; mergeSize < arr.length; mergeSize *= 2) {
        for (int left = 0; left < arr.length; left += 2 * mergeSize) {
            int mid = left + mergeSize - 1;
            int right = Math.min(0, 0 /* your code1 */);
            if (mid < right)
                merge(arr, left, mid, right);
        }
    }
    System.out.println(Arrays.toString(arr));
}

private static void bite_size_sort(int [] b, int start, int end) {
    for (int i = 0 /* your code2 */; i < end; i++) {
        int j = i;
        int tmp = b[j];
        while (j > start && b[j - 1] > tmp) {
            b[j] = b[j-1];
            j--;
        }
        b[j] = tmp;
    }
}

private static void merge(int [] twob, int low, int mid, int high) {
    int [] leftArr = new int[mid - low + 1];
    int [] rightArr = new int[high - mid];
    System.arraycopy(twob, low, leftArr, 0, leftArr.length);
    System.arraycopy(twob, mid + 1, rightArr, 0, rightArr.length);

    int leftCounter = 0;
    int rightCounter = 0;
    int twobCounter = low;
    while (leftCounter < leftArr.length && rightCounter < rightArr.length) {
        twob[twobCounter++] = leftArr[leftCounter] < rightArr[rightCounter]
            ? /* your code3 */;
    }
    while (leftCounter < leftArr.length)
        twob[twobCounter++] = leftArr[leftCounter++];
    while (rightCounter < rightArr.length)
        twob[twobCounter++] = rightArr[rightCounter++];
}
```

You may double check that the `println(Arrays.toString(arr));` in `whatSortIsThis()` produces the same output in main (i.e. array reference in main and `arr` in `whatSortIsThis` refers to the same array).

## Task 2:

Use the below code to test whatSortIsThis performance. Arrays of 2,000,000 values random by shuffle are created. After each call, its elapse time is stored in its corresponded time array.

```
private static void testRuntime() {
    int ARRAY_SIZE = 2_000_000;
    int [] arr32 = new int[1];
    int [] arr2048 = new int[1];
    int [] arr3 = new int[1];
    int numIter = 20;
    int [] size32Time = new int[numIter];
    int [] size2048Time = new int[numIter];
    int [] sizeSortTime = new int[numIter];
    ArrayList<Integer> list = new ArrayList<>();
    for (int i = 1; i <= ARRAY_SIZE; i++)
        list.add(i);

    for (int i = 0; i < numIter; i++) {
        Collections.shuffle(list);

        arr32 = list.stream().mapToInt(Integer::intValue).toArray();
        arr2048 = list.stream().mapToInt(Integer::intValue).toArray();
        arr3 = list.stream().mapToInt(Integer::intValue).toArray();

        long startElapse = System.currentTimeMillis();
        whatSortIsThis(arr32, 32);
        size32Time[i] = (int)(System.currentTimeMillis() - startElapse);

        startElapse = System.currentTimeMillis();
        whatSortIsThis(arr2048, 2048);
        size2048Time[i] = (int)(System.currentTimeMillis() - startElapse);

        startElapse = System.currentTimeMillis();
        Arrays.sort(arr3);
        sizeSortTime[i] = (int)(System.currentTimeMillis() - startElapse);
    }
    System.out.println("confirm isSort " + isSort(arr32)
        + " " + isSort(arr2048) + " " + isSort(arr3));
    System.out.println("takes " + Arrays.toString(size32Time));
    System.out.println("takes " + Arrays.toString(size2048Time));
    System.out.println("takes " + Arrays.toString(sizeSortTime));
}

private static boolean isSort(int [] arr) {
    for (int i = 1; i < arr.length; i++)
        if (arr[i - 1] > arr[i])
            return false;
    return true;
}
```

01286222

Lab 78b Name..... id

.....

## Instructions

1. capture your code

1.1 (your code 1)

1.2 (your code 2)

1.3 (your code 3)

2. Change numIter to 10. Capture your output.

3. What a brief opinion on which and why algorithm produced least elapse time outperforms the others.

**Submission:** This pdf

Due date: TBA