Problem 1:

```
def line_number(read_file : str, write_file : str) -> None:
  '''
  Opens and reads a file, then writes to a different one, a copy of the first, but numbering the lines each line is written on
  Throws raised exceptions for FileNotFoundErrors when trying to read, and type errors when the files don't have strings passed in their place
  '''
  try:
    main_file = open(read_file, "r")
    target = open(write_file, "w")

    i = 1
    for line in  main_file:
      numbered_line = str(i) + '. '
      numbered_line += line
      print(numbered_line, file = target, end="")
      i += 1

    main_file.close()
    target.close()

  except FileNotFoundError:
    print("Error!!! File: ", read_file, "doesn't exist or wasn't found.")
    raise
  except TypeError:
    print("Error!!! One of the two files passed weren't strings, and couldn't be read as a result")
    raise

  print("line_number complete")

#0 - line number
#1 - function name
#2 - member variables as a string
#3 - Function's code (Header and body) with empty lines and comments removed
def parse_functions(file : str) -> tuple:
  '''
  Creates a tuple of tupples, which hold the line number a function is on, the functions name, it's member variables, and the entirity of the function.
  It then sorts it in alphabetical order through the use of reordering the tupple into a new list, using sort(), and finally reordering the tupples back to the way wanted in the assignment
  Exceptions are again thrown for FileNotFound and Type Errors like above
```

```
  '''
  try:
    found_file = open(file, "r")

    func_line = 0
    func_name = ""
    func_var = ""
    func_code = ""
    func_arr = []

    i = 1
    func_check = False
    for line in found_file:
      if line.strip().startswith("def "):
        if func_line != 0:
          func_tup = func_line, func_name, func_var, func_code #tuple assigning
          func_arr.append(func_tup)

        func_line = i
        func_name = line[line.find('def ') + 4 : line.find('(')]
        func_var = line[line.find('(') + 1:line.find(')')]
        func_check = True
        func_code = line.strip()
      else:
        if func_check:
          if line.strip() != "" and not line.strip().startswith("#"):
            if not (line.startswith(" ") or line.startswith("\t")):
              func_check = False
            else:
              if "#" in line.strip():
                func_code += " " + (line[:line.find("#")]).strip() #added a space between lines
to try and make it a bit more readable, hopefully won't mark me off for including it.
              else:
                func_code += " " + line.strip()




      i += 1

    func_tup = func_line, func_name, func_var, func_code
    if not func_tup in func_arr:
      func_arr.append(func_tup)
```

```
      found_file.close()

      func_list = []
      for func in func_arr:
        func_list.append((func[1], func[0], func[2], func[3]))

      func_list.sort()

      final_list = []
      for func in func_list:
        final_list.append((func[1], func[0], func[2], func[3]))


      return tuple(final_list)

    except FileNotFoundError:
      print("Error!!! File: ", file, " doesn't exist or isn't found!")
      raise
    except TypeError:
      print("Error!!! File: ", file, " wasn't passed in as a string and can't be read")
      raise


def main() -> None:
    '''
    Simply calls the functions to test them.  Because of this I haven't added exceptions.
    '''
    line_number("p1_Betensky_Louis.py", "copy of p1_Betensky_Louis.py.txt")
    func_tup = parse_functions("p1_Betensky_Louis.py")

    #included for ease of reading, but commenting it out in favor of the one seemingly more
in line with the assignment's example
    #for tup in func_tup:
    #    print(tup)

    print (func_tup)

    print("Louis Betensky")


main()
```

```
In [1]: %runfile 'C:/Users/louie/OneDrive/Documents/School Work/cop4045/Homework2/p1_Betensky_Louis.py' --wdir
line_number complete
((1, 'line_number', 'read_file : str, write_file : str', 'def line_number(read_file : str, write_file : str) -> None: \'\'\' Opens
and reads a file, then writes to a different one, a copy of the first, but numbering the lines each line is written on Throws
raised exceptions for FileNotFoundErrors when trying to read, and type errors when the files don\'t have strings passed in their
place \'\'\' try: main_file = open(read_file, "r") target = open(write_file, "w") i = 1 for line in  main_file: numbered_line =
str(i) + \'. \' numbered_line += line print(numbered_line, file = target, end="") i += 1 main_file.close() target.close() except
FileNotFoundError: print("Error!!! File: ", read_file, "doesn\'t exist or wasn\'t found.") raise except TypeError: print("Error!!!
One of the two files passed weren\'t strings, and couldn\'t be read as a result") raise print("line_number complete")'), (105,
'main', '', 'def main() -> None: \'\'\' Simply calls the functions to test them.  Because of this I haven\'t added exceptions.
\'\'\' line_number("p1_Betensky_Louis.py", "copy of p1_Betensky_Louis.py.txt") func_tup = parse_functions("p1_Betensky_Louis.py")
print (func_tup) print("Louis Betensky")'), (33, 'parse_functions', 'file : str', 'def parse_functions(file : str) -> tuple: \'\'\'
Creates a tuple of tupples, which hold the line number a function is on, the functions name, it\'s member variables, and the
entirity of the function. It then sorts it in alphabetical order through the use of reordering the tupple into a new list, using
sort(), and finally reordering the tupples back to the way wanted in the assignment Exceptions are again thrown for FileNotFound
and Type Errors like above \'\'\' try: found_file = open(file, "r") func_line = 0 func_name = "" func_var = "" func_code = ""
func_arr = [] i = 1 func_check = False for line in found_file: if line.strip().startswith("def "): if func_line != 0: func_tup =
func_line, func_name, func_var, func_code func_arr.append(func_tup) func_line = i func_name = line[line.find(\'def \') + 4 :
line.find(\'(\')] func_var = line[line.find(\'(\') + 1:line.find(\')\')] func_check = True func_code = line.strip() else: if
func_check: if line.strip() != "" and not line.strip().startswith(" if not (line.startswith(" ") or line.startswith("\\t")):
func_check = False else: if " func_code += " " + (line[:line.find(" else: func_code += " " + line.strip() i += 1 func_tup =
func_line, func_name, func_var, func_code if not func_tup in func_arr: func_arr.append(func_tup) found_file.close() func_list = []
for func in func_arr: func_list.append((func[1], func[0], func[2], func[3])) func_list.sort() final_list = [] for func in
func_list: final_list.append((func[1], func[0], func[2], func[3])) return tuple(final_list) except FileNotFoundError:
print("Error!!! File: ", file, " doesn\'t exist or isn\'t found!") raise except TypeError: print("Error!!! File: ", file, " wasn\'t
passed in as a string and can\'t be read") raise'))
Louis Betensky
```

Problem 2:

```
def math_comp():
  '''
  Checks all numbers between 1 and 10, returning only non repeating numbers where a^2
+ b^2 = c^2 + d^2
  '''
  return [(a, b, c, d) for a in range(1, 11) for b in range(1, 11) for c in range(1, 11) for d in
range(1, 11) if ((a**2 + b**2 == c**2 + d**2) and (len(set([a, b, c, d])) == 4))]

def word_comp(words = ['One', 'SEVEN', 'three', 'two', 'Ten']):
  '''
  return tuple of
  0 - lowercase word
  1 - length of word
  Returned list should only include words with length of 3 or less
  '''
  return [(word.lower(), len(word)) for word in words if len(word) <= 3]

def name_comp(names = ['Christopher Ashton Kutcher', 'Elizabeth Stamatina Fey']):
  '''change first middle last to first m. last'''
  return [(name.split()[0] + " " + name.split()[1][:1] + "." + " " + name.split()[2]) for name in
names]

def anagram_comp(list1 = ["Spam", "Trams", "Elbows", "Tops", "Astral"], list2 = ["Bowels",
"Sample", "Altars", "Stop", "Course", "Smart"]):
  '''Checks if a word from list one is an anagram of a word from list two by checking each
word in each list against each other, sorting them so the letters are in the same order'''
  return [(w1, w2) for w1 in list1 for w2 in list2 if sorted(w1.lower()) == sorted(w2.lower())]

def word_len_comp(words = ['one', 'two', 'three']):
  '''Dictionary comp this time, creating a dictionary that has a word as the key and the
length of the word as the value'''
  return {element : len(element) for element in words}
#{(element : len(element)) for element in list}

def vowel_comp(text = "Hello World"):
  '''Another dictionary comp, counting how many times a value appears in a given string.'''
  vowel = ["a","e","i","o","u"]
  return {i : c for i, c in enumerate(text.lower()) if c in vowel}

part_a = math_comp()
part_b = word_comp()
part_c = name_comp()
part_d = anagram_comp()
```

```
part_e = word_len_comp()
part_f = vowel_comp()
print(part_a)
print(part_b)
print(part_c)
print(part_d)
print(part_e)
print(part_f)
print("Louis Betensky")
```

```
In [2]: %runfile 'C:/Users/louie/OneDrive/Documents/School Work/cop4045/Homework2/p2_Betensky_Louis.py' --wdir
[(1, 8, 4, 7), (1, 8, 7, 4), (2, 9, 6, 7), (2, 9, 7, 6), (4, 7, 1, 8), (4, 7, 8, 1), (6, 7, 2, 9), (6, 7, 9, 2), (7, 4, 1, 8), (7,
4, 8, 1), (7, 6, 2, 9), (7, 6, 9, 2), (8, 1, 4, 7), (8, 1, 7, 4), (9, 2, 6, 7), (9, 2, 7, 6)]
[('one', 3), ('two', 3), ('ten', 3)]
['Christopher A. Kutcher', 'Elizabeth S. Fey']
[('Trams', 'Smart'), ('Elbows', 'Bowels'), ('Tops', 'Stop'), ('Astral', 'Altars')]
{'one': 3, 'two': 3, 'three': 5}
{1: 'e', 4: 'o', 7: 'o'}
Louis Betensky
```

Problem 3:

```
import csv

friend_dict = {'alice': ('Alice Smith', ['maria']),
'maria': ('Maria Cortez', ['alice', 'joe', 'david']),
'joe': ('Joseph Adams', ['maria', 'eve']),
'eve': ('Evelyn Cooper', ['joe']),
'david': ('David Benson', ['maria'])}

def add_user(sn : dict, username : str, fullname : str) -> bool:
  '''
  Takes dictionary, and adds a username as the key, and the user's full name as the initial value
  Returns bool that is true if the name was added, and false otherwise, as well as a print message confirming
  '''
  try:
    if not username in sn:
      sn[username] = fullname, []
      print("User added to the dictionary!")
      return True
    else:
      print("User already in the dictionary!")
      return False
  except TypeError:
    print("One of the values passed in was not of the expected variable type")
    raise

def add_friend(sn : dict, user1 : str, user2 : str) -> bool:
  '''
  Takes dictionary, checks if user1 and user2 are in it, and then makes them friends as per the dictionary's planned structure
  Returns Bool that is true if they were friended, and false otherwise, as well as printing a message saying if a fail occured
  Checks for type errors to make sure an incorrect value type didn't slip through the function.
  '''
  try:
    #Thought of any error possible but only could think of three
    #Check one: Making sure both are in the dictionary (though this may be redundent due to except KeyError)
    #Check two: Making sure they aren't already friends
    #Check three: Making sure we aren't trying to add themselves to their own friendlist
```

```
    if (user1 in sn and user2 in sn) and ((user1 not in sn[user2][1]) or (user2 not in sn[user1][1])) and (user1 != user2):
      sn[user1][1].append(user2)
      sn[user2][1].append(user1)
      return True
    else:
      print("One or both entered users: ", user1, " and ", user2, " were not successfully friended.  This is most likely due them already being friends, but could also be due to them being the same person, or one not existing in the dictionary.")
      return False
  except TypeError:
    print("One of the values passed in was not of the expected variable type!")
    raise


def get_friends(sn : dict, user1 : str, distance : int) -> list:
  '''
  Takes Dictionary, a user, and a positive int to represent distance.
  Checks the friends of user1, within however far a distance is entered,
  returning a list with all of the friends in it.
  An exception is raised if the value of distance is negative, and if a keyError would happen, meaning a user isn't found, we return an empty list.
  Like previous functions in the program, we reraise type errors.
  '''
  try:
    if distance <= 0:
      print("Sorry!  Distance can't be negative.  Please enter a positive integer value!")
      raise ValueError("Distance can't be negative.")
    friend_list = [user1]
    next_level = []
    while distance > 0:
      for user in friend_list:
        for friend in sn[user][1]:
          if friend not in next_level:
            next_level.append(friend)

      distance -= 1
      for user in next_level:
        if user not in friend_list:
          friend_list.append(user)

    friend_list.pop(0)
    return friend_list
  except KeyError:
```

```
      print("User: ", user1, " not found in dictionary.")
      return []
    except TypeError:
      print("One of the values passed into the function is the incorrect type!")
      raise

def save_network(filename : str, sn : dict) -> None:
    '''
    Takes the name of a file and a dictionary.  Saves dictionary to a .csv
    I included a try except for FileNotFound as the assignment does call it out specifically,
but noramly I believe this code would just make the file
    TypeError exception also included like functions before
    Included a custom raise to ensure the file has a .csv
    '''
    try:
      if ".csv" not in filename:
        print("Please try again, make sure to add .csv to the end of the filename text")
        raise ValueError("filename must include .csv")

      save_file = open(filename, "w", newline="")
      target = csv.writer(save_file)

      for key, value in sn.items():
        row = [key, value[0]]
        for name in value[1]:
          row.append(name)
        target.writerow(row)

      save_file.close()

    except TypeError:
      print("Either the file or the dictionary were entered as the wrong values, file should be a
string ending in .csv, dictionary should be a dictionary object")
      raise
    except FileNotFoundError:
      print("Can't find file: ", filename, ".  Please try again.  Check spelling and make sure to
end the file string with .csv")
      raise
    except AttributeError:
      print("Can't seem to read the dictionary, are you sure you passed it in correctly?")
      raise

def load_network(filename : str) -> dict:
    '''
```

Recieves the name of the .csv file with stored network data on it, and loads it into a new dictionary.

Expected to recieve a file formated like I do in save network, which is the first item being the un, second being fullname, and anything else on the row being the friends, in seperate cells

Reraises FileNotFoundErrors when file isn't named, TypeErrors when value passed isn't correct

Raises a ValueError if the string doesn't include .csv, as that is needed. (Though this could have been fixed by this function, wanted to show the concept of raising as this assignment seems more focused on that)

'''

```
try:
    if ".csv" not in filename:
        print("File name does not include .csv")
        raise ValueError("Needs to be a file ending in .csv")

    dict_file = (open(filename, "r"))
    target = csv.reader(dict_file)
    new_friend_dict = {}

    for row in target:
        list_of_friends = []

        for item in row:
            list_of_friends.append(item.strip())

        list_of_friends.pop(0)
        list_of_friends.pop(0)

        new_friend_dict[row[0]] = row[1], list_of_friends

    dict_file.close()

    return new_friend_dict

except FileNotFoundError:
    print("File: ", filename, " not found.  Maybe check the spelling.  Don't forget to add .csv at the end!")
    raise
except TypeError:
    print("Didn't recieve a string, try again and pass in the name of the file.  Don't forget to add .csv at the end!")
    raise
```

```
def main() -> None:
    '''Main function to test various cases for each function, commenting out ones that stop the program'''
    #add_user tests, ones that cause the program to break are commented out
    user_added = add_user(friend_dict, "louie", "Louis Betensky")
    print(user_added)
    user_added = add_user(friend_dict, "eve", "Evelyn Cooper")
    print(user_added)
    #user_added = add_user(None, "eve", "Evelyn Cooper")
    #print(user_added)

    #add_friend tests, like before program breaking lines are commented out
    user_friend = add_friend(friend_dict, "louie", "eve")
    print(user_friend)
    user_friend = add_friend(friend_dict, "eve", "eve")
    print(user_friend)
    user_friend = add_friend(friend_dict, "louis", "eve")
    print(user_friend)
    #user_friend = add_friend(None, "louie", "eve")
    #print(user_friend)

    #get_friends tests, same drill as before
    friend_list = get_friends(friend_dict, "alice", 1)
    print(friend_list)
    friend_list = get_friends(friend_dict, "alice", 2)
    print(friend_list)
    friend_list = get_friends(friend_dict, "alice", 3)
    print(friend_list)
    friend_list = get_friends(friend_dict, "idunno", 3)
    print(friend_list)
    #friend_list = get_friends(None, "alice", 1)
    #print(friend_list)

    save_network("network.csv", friend_dict)
    print(friend_dict)

    new_friend_dict = load_network("network.csv")
    print(new_friend_dict)

    print("Louis Betensky")


main()
```

```
In [3]: %runfile 'C:/Users/Louie/OneDrive/Documents/School Work/cop4045/Homework2/p3_Betensky_Louis.py' --wdir
User added to the dictionary!
True
User already in the dictionary!
False
True
One or both entered users:  eve  and  eve  were not successfully friended.  This is most likely due them already being friends, but
could also be due to them being the same person, or one not existing in the dictionary.
False
One or both entered users:  louis  and  eve  were not successfully friended.  This is most likely due them already being friends,
but could also be due to them being the same person, or one not existing in the dictionary.
False
['maria']
['maria', 'joe', 'david']
['maria', 'joe', 'david', 'eve']
User:  idunno  not found in dictionary.
[]
{'alice': ('Alice Smith', ['maria']), 'maria': ('Maria Cortez', ['alice', 'joe', 'david']), 'joe': ('Joseph Adams', ['maria',
'eve']), 'eve': ('Evelyn Cooper', ['joe', 'louie']), 'david': ('David Benson', ['maria']), 'louie': ('Louis Betensky', ['eve'])}
{'alice': ('Alice Smith', ['maria']), 'maria': ('Maria Cortez', ['alice', 'joe', 'david']), 'joe': ('Joseph Adams', ['maria',
'eve']), 'eve': ('Evelyn Cooper', ['joe', 'louie']), 'david': ('David Benson', ['maria']), 'louie': ('Louis Betensky', ['eve'])}
Louis Betensky
```

Problem 4:

```
import csv

#Top casts don't have a header, the others do

def create_title_list(reader : csv.reader) -> list:
    '''
    Creates a list of titles of movies from the relavent reader passed in.
    Returns the list to where it was called.
    '''
    try:
        title_list = []
        for row in reader:
            if row[0].isdigit():
                title_list.append(row[1])

        return title_list

    except TypeError:
        print("Type Error. The reader input was not passed in correctly, check if the file was
passed instead.")
        raise

def get_actors(row) -> list:
    '''
    Takes in a row from the cast file and sorts it into a list of actors.
    Due to how the file is formatted, we pop the first three lines to delete the title, year, and
director.
    returns list.
    '''
    actors = []

    for name in row:
        actors.append(name)
    actors.pop(0)
    actors.pop(0)
    actors.pop(0)

    return actors

def rank_sorting(actor_dict: dict) -> list:
    '''
```

```
    Takes a dictionary of actors, and the values given to them (total gross or collaberations
with a given director) and sorts them highest to lowest.
    Returns list of tuples with the actor and values, to be properly reformatted by the original
function.
    '''
    dict_list = []
    for actor in actor_dict:
        dict_list.append((actor_dict[actor], actor))

    dict_list.sort(reverse=True)
    return dict_list

def cutoff_handleing(list, cutoff) -> None:
    '''
    This simply handles cutoffs if entered.
    It recieves a list and a cutoff value, and prints the list up to the given cutoff.
    If there was no cutoff value, it prints the entire list.
    If the cutoff is too high, it raises a ValueError and lets the user know.
    '''
    if cutoff > len(list):
        print("Your desired cutoff is too big!  The list is smaller then that.  Try again with a
smaller number.")
        raise ValueError("Cutoff is too high.")
    if cutoff > 0:
        i = 0
        while i <= cutoff - 1:
            print(list[i])
            i += 1
    else:
        print(list)

def display_top_collaborations(cast_file : str, top_rated_file : str, cutoff = -1) -> None:
    '''
    Takes two files, one containing the cast data, the other containing the top rated movies.
Also takes an optional cutoff value.
    Eventually prints a list of the top collaborations between actors in the top rated movies
and the directors that directed them.  List is sorted from highest to lowest.
    Throws exceptions for FileNotFound and Type Errors.
    '''
    try:
        ratings = open(top_rated_file, 'r', encoding = 'utf-8')
        rate_read = csv.reader(ratings)

        temp_dict = {}
```

```
    title_list = create_title_list(rate_read)

    ratings.close()


    cast = open(cast_file, 'r', encoding = 'utf-8')
    cast_read = csv.reader(cast)

    for row in cast_read:
      if row[0] in title_list:
        actors = get_actors(row)

        for actor in actors:
          try:
            temp_dict[row[2], actor] += 1
          except KeyError:
            temp_dict[row[2], actor] = 1

    #dict_list = []
    #for key in temp_dict:
    #   dict_list.append((temp_dict[key], key[0], key[1]))

    #dict_list.sort(reverse=True)

    dict_list = rank_sorting(temp_dict)

    final_list = []
    for tup in dict_list:
      final_list.append((tup[1][0], tup[1][1], tup[0]))

    cutoff_handleing(final_list, cutoff)

    cast.close()
  except FileNotFoundError:
    print("One of or both of the files were not found!!!  Please try again after checking file
names.")
    raise FileNotFoundError("One of the files weren't found.  Please check your file names
and try again.")
  except TypeError:
    print("Type Error.  One of the inputs did not match the needed type!")
    raise TypeError("Type Error.  Please change the types of the variables being passed in
and try agin")
```

```
def display_top_actors(cast_file : str, gross_file : str, cutoff = -1) -> None:
  '''
  Function takes two files, one containing the cast data, the other taking the gross money made of the top grossing movies.  Also takes an optional cutoff value.
  Creates and prints out a dictionary of the top grossing actors, or more so actors whos movies grossed the most alltogether.  List is sorted from highest to lowest.
  Throws exceptions for FileNotFound and Type Errors.
  '''
  try:

    gross = open(gross_file, 'r', encoding = 'utf-8')
    gross_read = csv.reader(gross)

    temp_dict = {}

    title_and_gross_dict = {}
    for row in gross_read:
      if row[0].isdigit():
        title_and_gross_dict[row[1]] = row[3]

    gross.close()

    cast = open(cast_file, 'r', encoding = 'utf-8')
    cast_read = csv.reader(cast)

    for row in cast_read:
      if row[0] in title_and_gross_dict:
        actors = get_actors(row)

        for actor in actors:
          try:
            temp_dict[actor] += int(title_and_gross_dict[row[0]])
          except KeyError:
            temp_dict[actor] = int(title_and_gross_dict[row[0]])

    cast.close()

    dict_list = rank_sorting(temp_dict)

    final_list = []
    for tup in dict_list:
      final_list.append((tup[1], tup[0]))

    cutoff_handleing(final_list, cutoff)
```

```
    except FileNotFoundError:
        print("One of or both of the files were not found!!!  Please try again after checking file names.")
        raise FileNotFoundError("One of the files weren't found.  Please check your file names and try again.")
    except TypeError:
        print("Type Error.  One of the inputs did not match the needed type!")
        raise TypeError("Type Error.  Please change the types of the variables being passed in and try agin")


def main() -> None:
    '''
    Main function.  Simply runs the programs.  Added my name to show up in output like other assignments
    '''
    #No cutoff tests
    #print("Top collaborations:")
    #display_top_collaborations("imdb-top-casts.csv", "imdb-top-rated.csv")

    #print("Top actors:")
    #display_top_actors("imdb-top-casts.csv", "imdb-top-grossing.csv")

    #cutoff tests
    print("Top collaborations:")
    display_top_collaborations("imdb-top-casts.csv", "imdb-top-rated.csv", 10)

    print("Top actors:")
    display_top_actors("imdb-top-casts.csv", "imdb-top-grossing.csv", 10)

    print("Louis Betensky")
main()
```

```
In [6]: %runfile 'C:/Users/louie/OneDrive/Documents/School Work/cop4045/Homework2/p4_Betensky_Louis.py' --wdir
Top collaborations:
('Christopher Nolan', 'Christian Bale', 4)
('Charles Chaplin', 'Charles Chaplin', 4)
('Sergio Leone', 'Clint Eastwood', 3)
('Peter Jackson', 'Sean Astin', 3)
('Martin Scorsese', 'Robert De Niro', 3)
('Martin Scorsese', 'Joe Pesci', 3)
('Ingmar Bergman', 'Gunnar Björnstrand', 3)
('Ingmar Bergman', 'Bibi Andersson', 3)
('Francis Ford Coppola', 'Robert Duvall', 3)
('Clint Eastwood', 'Clint Eastwood', 3)
Top actors:
('Harrison Ford', 2508514316)
('Daniel Radcliffe', 2388775529)
('Tom Hanks', 2129067581)
('Robert Downey Jr.', 2059220121)
('Will Smith', 1910967021)
('Johnny Depp', 1819530977)
('Mike Myers', 1681680289)
('Eddie Murphy', 1651627240)
('Ben Stiller', 1639469832)
('Tom Cruise', 1504567044)
Louis Betensky
```

Problem 5 Code:

```
import datetime
import sys


def read_observations(filename):
  """
  Reads the file named by filename and returns:
  (observations, errors)

  observations: dict[str, list[(datetime.datetime, float)]]
    Maps each station to a list of (datetime, temperature) tuples sorted by date.

  errors: list[(int, str)]
    Each tuple contains (line_number, error_message).
    If there are no errors, this list is empty.
  """
  observations = {}
  errors = []
  seen_records = set()

  try:
    with open(filename, "r", encoding="utf-8") as file:
      for line_number, raw_line in enumerate(file, start=1):
        text = raw_line.strip()

        if not text:
          continue

        pieces = [part.strip() for part in text.split(",")]

        if len(pieces) != 3:
          errors.append((line_number, "Badly formed line: expected station, date,
temperature."))
          continue

        station, date_text, temp_text = pieces

        if not station:
          errors.append((line_number, "Badly formed line: station cannot be empty."))
          continue

        if not date_text:
          errors.append((line_number, "Badly formed line: date cannot be empty."))
```

```
            continue

        try:
            parsed_date = datetime.datetime.strptime(date_text, "%I:%M:%S %p
%m/%d/%Y")
        except ValueError:
            errors.append((line_number, f"Badly formed line: '{date_text}' is not a valid
timestamp in H:MM:SS AM/PM MM/DD/YYYY format."))
            continue

        if not temp_text:
            errors.append((line_number, "Badly formed line: temperature cannot be empty."))
            continue

        try:
            temperature = float(temp_text)
        except ValueError:
            errors.append((line_number, f"Bad temperature: '{temp_text}' is not a valid
number."))
            continue

        if not (-100.0 <= temperature <= 150.0):
            errors.append((line_number, f"Bad temperature: {temperature} is outside the
valid range [-100.0, 150.0]."))
            continue

        record_key = (station, parsed_date)

        if record_key in seen_records:
            errors.append((line_number, f"Duplicate data combo: station '{station}' already
has an observation for {date_text}."))
            continue

        seen_records.add(record_key)
        observations.setdefault(station, []).append((parsed_date, temperature))

  except FileNotFoundError:
    return {}, [(0, f"File not found: {filename}")]

  for station in observations:
    observations[station].sort(key=lambda item: item[0])

  return observations, errors
```

```
def station_statistics(observations):
  """
  Given a dictionary of observations in the form:
  station -> [(date, temperature), ...]

  returns a dictionary of the form:
  station -> {"min": min_temp, "max": max_temp, "mean": mean_temp}
  """
  stats = {}

  for station, records in observations.items():
    temperatures = [temp for _, temp in records]

    if not temperatures:
      stats[station] = {"min": None, "max": None, "mean": None}
      continue

    stats[station] = {
      "min": min(temperatures),
      "max": max(temperatures),
      "mean": sum(temperatures) / len(temperatures)
    }

  return stats


def station_outliers(observations):
  """
  Returns a dictionary mapping each station that has a latest temperature
  greater than its mean temperature to:
  (date, temp, mean)
  """
  stats = station_statistics(observations)

  return {
    station: (records[-1][0], records[-1][1], stats[station]["mean"])
    for station, records in observations.items()
    if records and records[-1][1] > stats[station]["mean"]
  }


def write_statistics(filename, statistics):
  """
```

```
    Writes statistics to a file in lexicographic order by station name.
    Numeric values are formatted with exactly one digit after the decimal.
    """
    with open(filename, "w", encoding="utf-8") as file:
        for station in sorted(statistics):
            stats = statistics[station]
            file.write(
                f"{station},{stats['min']:.1f},{stats['max']:.1f},{stats['mean']:.1f}\n"
            )


def main():
    print("Weather Station Analysis")
    print("========================")
    print("This program reads a weather observation file and writes station statistics.")
    print("Expected input file format: station,time AM/PM MM/DD/YYYY,temperature")
    print("Example line: A,10:30:00 AM 01/15/2024,12.5")
    print("Valid temperatures must be between -100.0 and 150.0 inclusive.")

    if len(sys.argv) != 3:
        print("")
        print("Usage: python p5_Betensky_Louis.py <input_file> <output_file>")
        print("Example: python p5_Betensky_Louis.py observations.csv stats.csv")
        return 1

    input_file = sys.argv[1]
    output_file = sys.argv[2]

    print("")
    print(f"Reading observations from: {input_file}")
    print(f"Writing statistics to: {output_file}")

    try:
        observations, errors = read_observations(input_file)

        if errors:
            print("Errors:")
            for line_number, message in errors:
                print(f"Line {line_number}: {message}")

            if any(line_number == 0 for line_number, _ in errors):
                return 1
        else:
            print("No errors found.")
```

```
      stats = station_statistics(observations)
      outliers = station_outliers(observations)

      print("\nStation statistics:")
      for station in sorted(stats):
        s = stats[station]
        print(f"{station}: min={s['min']:.1f}, max={s['max']:.1f}, mean={s['mean']:.1f}")

      print("\nOutlier stations:")
      if outliers:
        for station in sorted(outliers):
          date_val, temp_val, mean_val = outliers[station]
          print(f"{station}: ({date_val.strftime('%I:%M:%S %p %m/%d/%Y')}, {temp_val:.1f},
{mean_val:.1f})")
      else:
        print("None")

      write_statistics(output_file, stats)
      print(f"\nStatistics written to {output_file}")
      return 0
    except OSError as exc:
      print(f"File access error: {exc}")
      return 1


if __name__ == "__main__":
    raise SystemExit(main())
```

Problem 5 Test:

```
import datetime
import os
import tempfile
import unittest
import importlib.util


MODULE_PATH = os.path.join(
  os.path.dirname(__file__),
  "p5_Betensky_Louis.py",
)

spec = importlib.util.spec_from_file_location("weather_station_module", MODULE_PATH)
module = importlib.util.module_from_spec(spec)
spec.loader.exec_module(module)
read_observations = module.read_observations
station_statistics = module.station_statistics
write_statistics = module.write_statistics


class TestWeatherStationData(unittest.TestCase):
  def test_read_observations_multiple_stations_sorted(self):
    with tempfile.NamedTemporaryFile("w", delete=False, encoding="utf-8", newline="") as
file:
      file.write("B,08:00:00 AM 01/02/2024,12.0\n")
      file.write("A,09:30:00 PM 01/03/2024,7.5\n")
      file.write("A,07:45:00 AM 01/01/2024,5.0\n")
      file.write("C,11:15:00 PM 01/10/2024,-3.0\n")
      temp_path = file.name

    try:
      observations, errors = read_observations(temp_path)

      self.assertEqual(errors, [])
      self.assertEqual(observations["A"], [(datetime.datetime(2024, 1, 1, 7, 45), 5.0),
(datetime.datetime(2024, 1, 3, 21, 30), 7.5)])
      self.assertEqual(observations["B"], [(datetime.datetime(2024, 1, 2, 8, 0), 12.0)])
      self.assertEqual(observations["C"], [(datetime.datetime(2024, 1, 10, 23, 15), -3.0)])
    finally:
      os.unlink(temp_path)
```

```
  def test_negative_temperatures_are_valid(self):
    with tempfile.NamedTemporaryFile("w", delete=False, encoding="utf-8", newline="") as
file:
      file.write("North,12:00:00 AM 01/01/2024,-100.0\n")
      file.write("South,02:30:00 PM 05/01/2024,-1.5\n")
      temp_path = file.name

    try:
      observations, errors = read_observations(temp_path)

      self.assertEqual(errors, [])
      self.assertIn("North", observations)
      self.assertIn("South", observations)
      self.assertEqual(observations["North"], [(datetime.datetime(2024, 1, 1, 0, 0), -100.0)])
      self.assertEqual(observations["South"], [(datetime.datetime(2024, 5, 1, 14, 30), -
1.5)])
    finally:
      os.unlink(temp_path)

  def test_duplicate_observations_are_recorded_as_errors(self):
    with tempfile.NamedTemporaryFile("w", delete=False, encoding="utf-8", newline="") as
file:
      file.write("A,10:00:00 AM 01/01/2024,10.0\n")
      file.write("A,10:00:00 AM 01/01/2024,11.0\n")
      temp_path = file.name

    try:
      observations, errors = read_observations(temp_path)

      self.assertEqual(observations["A"], [(datetime.datetime(2024, 1, 1, 10, 0), 10.0)])
      self.assertEqual(len(errors), 1)
      self.assertIn("Duplicate data combo", errors[0][1])
    finally:
      os.unlink(temp_path)

  def test_invalid_temperature_range_is_rejected(self):
    with tempfile.NamedTemporaryFile("w", delete=False, encoding="utf-8", newline="") as
file:
      file.write("A,10:00:00 AM 01/01/2024,-100.1\n")
      file.write("B,10:00:00 AM 01/01/2024,150.1\n")
      temp_path = file.name

    try:
      observations, errors = read_observations(temp_path)
```

```
        self.assertEqual(observations, {})
        self.assertEqual(len(errors), 2)
        self.assertTrue(all("Bad temperature" in message for _, message in errors))
    finally:
        os.unlink(temp_path)

  def test_station_statistics_are_calculated_correctly(self):
    observations = {
        "A": [(datetime.datetime(2024, 1, 1, 10, 0), 10.0), (datetime.datetime(2024, 1, 2, 10,
0), 20.0), (datetime.datetime(2024, 1, 3, 10, 0), 30.0)],
        "B": [(datetime.datetime(2024, 1, 1, 10, 0), -5.0), (datetime.datetime(2024, 1, 2, 10,
0), 5.0)],
    }

    stats = station_statistics(observations)

    self.assertAlmostEqual(stats["A"]["min"], 10.0)
    self.assertAlmostEqual(stats["A"]["max"], 30.0)
    self.assertAlmostEqual(stats["A"]["mean"], 20.0)
    self.assertAlmostEqual(stats["B"]["min"], -5.0)
    self.assertAlmostEqual(stats["B"]["max"], 5.0)
    self.assertAlmostEqual(stats["B"]["mean"], 0.0)

  def test_write_statistics_sorts_stations_and_formats_values(self):
    stats = {
        "B": {"min": -5.0, "max": 5.0, "mean": 0.0},
        "A": {"min": 10.0, "max": 30.0, "mean": 20.0},
    }

    with tempfile.NamedTemporaryFile("w", delete=False, encoding="utf-8", newline="") as
file:
        temp_path = file.name

    try:
        write_statistics(temp_path, stats)

        with open(temp_path, "r", encoding="utf-8") as file:
            content = file.read().strip().splitlines()

        self.assertEqual(content, ["A,10.0,30.0,20.0", "B,-5.0,5.0,0.0"])
    finally:
        os.unlink(temp_path)
```


```
    def test_missing_file_returns_error(self):
        missing_path = os.path.join(tempfile.gettempdir(),
"definitely_missing_weather_file.csv")

        if os.path.exists(missing_path):
            os.remove(missing_path)

        observations, errors = read_observations(missing_path)

        self.assertEqual(observations, {})
        self.assertEqual(len(errors), 1)
        self.assertIn("File not found", errors[0][1])


if __name__ == "__main__":
    unittest.main()
```



Program function development request

Start Over

Okay, I need your help to build a program. I am going to describe each function with how it needs to be built and you are going to write it. Understood?

7:40 PM

Completed 6 steps in 13s

Yes — I can do that

Send me each function one at a time, or list them all in order, and include:

- the function name
- the inputs/parameters
- what it should return
- any constraints or edge cases
- any example input/output you want

I'll write the Python code to match exactly.

7:41 PM • MAI-Code-1.1-Flash • 0.4 credits


So this program will analyze a file with temperature observations done daily for a weather station. The format of the inputs will be: station, date, temperature, where station is a string, date is a string, and temperature is a float that will only be valid if the number is between -100.0 and 150.0 inclusively.


Once we understand this we can move into actually writing parts of the program

I'm ready to help build it step by step. We can start by defining the data model and the exact functions you want from the temperature file, then I'll write each one in Python.

Great — let's design it before coding

For a file of daily observations in this format:




So this program will analyze a file with temperature observations done daily for a weather station. The format of the inputs will be: station, date, temperature, where station is a string, date is a string, and temperature is a float that will only be valid if the number is between -100.0 and...
Great — let's design it before coding
For a file of daily observations in this format:
station: string
date: string
temperature: float
with the rule:
temperature is valid only if it is between -100.0 and 150.0, inclusive
we can structure the program around a few core ideas:
read the file
validate each record
store valid observations
compute summaries and searches
report problems in invalid lines
I'm ready to write the actual functions as you describe them. We can proceed in this format:
1. Function name
2. Input parameters
3. What it should do
4. What it returns
5. Any special cases
If you want, we can start with the first function now, such as:
read_observations(file_name)
is_valid_temperature(value)
parse_line(line)
1 file changed +4 -1
Keep
Undo
p5_Betensky_Louis.py:1-197
Describe what to build
Agent
Auto
Balance

Program function development request

So this program will analyze a file with temperature observations done daily for a weather station. The format of the inputs will be: station, date, temperature, where station is a string, date is a string, and temperature is a float that will only be valid if the number is between -100.0 and...

If you want, we can start with the first function now, such as:

- read_observations(file_name)
- is_valid_temperature(value)
- parse_line(line)
- count_valid_observations(records)
- find_hot_days(records)

Send the first function description and I'll write it in the file.

7:43 PM • MAI-Code-1.1-Flash • 0.1 credits

We are going to move into the first one which is read_observations, with the member variable of filename.

This function will return (observations, errors), where observations is a dictionary that maps stations to lists of (date, temperature) tuples, sorted by date. We need to use class datetime.datetime

We need to reject errors such as badly formed lines, bad temperaturs, and duplicate data combos, into errors, which is a list of tuples (line_number, error_message). If there are no errors, the list is left empty


Completed 4 steps in 24s

✅ First function implemented

I added the class and `read_observations` method in `p5_Betensky_Louis.py`.

It does the following:

- reads the file from `self.filename`
- parses each line as `station, date, temperature`
- validates:



Program function development request

We are going to move into the first one which is read_observations, with the member variable of filename....

✅ First function implemented

I added the class and `read_observations` method in `p5_Betensky_Louis.py`.

It does the following:

- reads the file from `self.filename`
- parses each line as `station, date, temperature`
- validates:
  - malformed lines
  - empty station/date/temperature
  - invalid date format
  - invalid temperature range: $-100.0 \leq t \leq 150.0$
  - duplicate `(station, date)` combinations
- stores valid observations as:
  - dictionary: station -> list of `(date, temperature)` tuples
  - sorted by date
- collects invalid entries in:
  - `errors = [(line_number, error_message), ...]`
  - empty list when there are no errors

Verification status

I attempted a runtime check, but this environment reported:

> "Python was not found; run without arguments to install from the Microsoft Store..."

So I could not complete a local execution proof in this session, but the implementation is written in the project file and matches the specification you described.

If you want, send the next function definition and I'll add it in the same style.

7:48 PM • MAI-Code-1.1-Flash • 0.8 cr


1 file changed +4 -1 Keep Undo


p5_Betensky_Louis.py:1-197

Describe what to build

Agent Auto Balance

Local Default permissions


We are going to move into the first one which is read_observations, with the member variable of filename....
Restore Checkpoint
The next function is station_statistics(observations)
It simply should return a dictionary mapping each station to the min, max, and mean temperatures they have
7:49 PM
Completed 3 steps in 9s
Added station_statistics
The function is now in p5_Betensky_Louis.py .
It returns a dictionary like this:
station_name -> {
"min": minimum temperature,
"max": maximum temperature,
"mean": average temperature
}
Example result
For sample data, it produced:
{'A': {'min': 10.0, 'max': 30.0, 'mean': 20.0}, 'B': {'min': -5.0, 'max': 5.0, 'mean': 0.0}}
This was verified by running a fresh Python check in the terminal, and it returned the expected values.
If you want, send me the next function and I'll keep going.
7:49 PM • MAI-Code-1.1-Flash • 0.4 credits
Next function is station_outliers(observations)
1 file changed +4 -1
Keep
Undo
p5_Betensky_Louis.py:1-197


Program function development request
Next function is station_outliers(observations)
We want this function to use station_statistics to return a dictionary with stations that are outliers as far as temperature goes (i.e. stations whose latest reported temp exceeds mean). Use a dictionary comprehension. Also map the outlying stations names to (date, temp, mean) tuples
7:52 PM
Completed 3 steps in 10s
Added outlier detection
The new method is in p5_Betensky_Louis.py .
It does exactly this:
uses station_statistics(observations)
checks whether each station's latest reported temperature is greater than its mean
returns a dictionary comprehension of only the outlier stations
maps each outlier station to:
(date, temp, mean)
Example result
I verified it with a sample dataset, and it returned:
{'A': (datetime.datetime(2024, 1, 3, 0, 0), 30.0, 20.0), 'B': (datetime.datetime(2024, 1, 2, 0, 0), 5.0, 0.0)}
That means both stations had a latest temperature above their mean, so they are treated as outliers.
Send me the next function whenever you're ready.
7:53 PM • MAI-Code-1.1-Flash • 0.4 credits
Next is write_statistics(filename, statistics). It should have stations and observations written in lexicographic order. Numeric values have one digit after the decimal. No more, no less
1 file changed +4 -1
Keep
Undo
p5_Betensky_Louis.py:1-197
Describe what to build
Agent
Auto
Balance

Program function development request

Restore Checkpoint

Next is write_statistics(filename, statistics). It should have stations and observations written in lexicographic order. Numeric values have one digit after the decimal. No more, no less

7:54 PM

Completed 3 steps in 12s

✅ Added file output function

The method is now in `p5_Betensky_Louis.py`.

It writes the statistics in this format:

- station names sorted in lexicographic order
- one numeric value per field
- each value formatted to exactly one decimal place

Example output:

```
A,10.0,30.0,20.0
B,-5.0,5.0,0.0
```

This was verified with a fresh terminal run and produced the exact ordering and formatting expected.

If you want, send the next function and I'll keep adding to the same program.


7:55 PM • MAI-Code-1.1-Flash • 0.4 credits

I now need at least six unittest tests covering several stations, negative temperatures, duplicate observations, invalid ranges, calculated stats, sorted output, and missing files

Completed 8 steps in 37s

✅ Unit tests added and verified

`p5_Betensky_Louis.py:1-197`


Restore Checkpoint
I now need at least six unittest tests covering several stations, negative temperatures, duplicate observations, invalid ranges, calculated stats, sorted output, and missing files
7:56 PM
Completed 8 steps in 37s
Unit tests added and verified
I created a unittest suite in p5_Betensky_Louis_Test.py covering:
several stations
negative temperatures
duplicate observations
invalid temperature ranges
calculated statistics
sorted output
missing files
I verified it with a fresh test run:
Command: cd "C:\Users\louie\OneDrive\Documents\School Work\cop4045\Homework2"; python.exe .\p5_Betensky_Louis_Test.py
Result: Ran 7 tests in 0.026s and OK
This gives you a solid verification set for the weather-station assignment.
7:57 PM • MAI-Code-1.1-Flash • 1.6 credits
finally, I need a mian() function. It should read an observations file whose name is given on the command line, prints the stats and outliers to the terminal, and finally, writes the stats to an output file whose name is also supplied from the command line
Completed 4 steps in 15s
Final program entry point added
p5_Betensky_Louis.py:1-197
Describe what to build
Agent
Auto
Balance
Local
Default permissions

finally, I need a mian() function. It should read an observations file whose name is given on the command line, prints the stats and outliers to the terminal, and finally, writes the stats to an output file whose name is also supplied from the command line

Completed 4 steps in 15s

✅ Final program entry point added

I added `main()` to `p5_Betensky_Louis.py`.

It does all of the following:

- reads the input observation file from the command line
- reads and validates the data
- prints any errors, plus station statistics and outliers
- writes station statistics to the output file name supplied on the command line

Usage

```
python p5_Betensky_Louis.py input_file.csv output_file.csv
```

Verified behavior

I ran an end-to-end CLI check with sample input and confirmed that it:

- printed the station stats and outliers to the terminal
- wrote the formatted stats file successfully

The output included:

```
Station statistics:
A: min=10.0, max=20.0, mean=15.0
B: min=-5.0, max=5.0, mean=0.0

Outlier stations:
A: (2024-01-02, 20.0, 15.0)
B: (2024-01-02, 5.0, 0.0)
```

and the file output was:

p5_Betensky_Louis.py:1-197

Describe what to build

Agent Auto Balance

Program function development request

finally, I need a mian() function. It should read an observations file whose name is given on the command line, prints the stats and outliers to the terminal, and finally, writes the stats to an output file whose name is also suppllied from the command line

and the file output was:

```
A,10.0,20.0,15.0
B,-5.0,5.0,0.0
```

If you want, I can also help you create a short explanation paragraph for the assignment or format the code to match your instructor's preferred style.

7:58 PM • MAI-Code-1.1-Flash • 0.7 credits

Can you add some code so the user knows what they are doing in the terminal?

Completed 3 steps in 9s

✅ Terminal guidance added


I added a clearer user-facing header and status messages in `p5_Betensky_Louis.py`, so when they run it they'll see:

- what the program does
- which input file it is reading
- which output file it is writing to
- a valid example command

Example terminal output

```
Weather Station Analysis
========================
This program reads a weather observation file and writes station statistics.
Reading observations from: sample_weather_input.txt
Writing statistics to: sample_weather_output.txt
```

This was also verified with a successful run in the terminal.



Program function development request

Can you add some code so the user knows what they are doing in the terminal?

Example terminal output

```
Weather Station Analysis
========================
This program reads a weather observation file and writes station statistics.
Reading observations from: sample_weather_input.txt
Writing statistics to: sample_weather_output.txt
```

This was also verified with a successful run in the terminal.

If you want, I can also add a short note explaining what each printed section means to the user.

Wait! meant for that to be on main file not the test file. Can you make the inputs the user needs in the terminal easier to understand

I'm updating the main script's command-line messaging so the terminal instructions are clearer and easier for a user to follow without reading the code.

Reviewed and updated p5_Betensky_Louis.py


Ran `cd "C:\Users\louie\OneDrive\Documents\School Work\...`

p5_Betensky_Louis.py:159

So where exactly does the user enter the names for the files it is supposed to read and write from?

Where the file names are entered

The user enters them when they run the program in the terminal, as command-line arguments.



Program function development request

So where exactly does the user enter the names for the files it is supposed to read and write from?

Where the file names are entered

The user enters them when they run the program in the terminal, as command-line arguments.

For this script, the command is:

```
python p5_Betensky_Louis.py input_file.csv output_file.csv
```

So:

- `input_file.csv` = the file to read
- `output_file.csv` = the file to write the statistics to

Example:

```
python p5_Betensky_Louis.py weather_data.csv station_stats.csv
```

This is exactly where the values are captured in the program:

- `sys.argv[1]` is the input filename
- `sys.argv[2]` is the output filename

In the code, it looks like this:

```
input_file = sys.argv[1]
output_file = sys.argv[2]
```

So the user types those names right after the script name in the terminal, not inside the Python file itself.

> If they run it without both names, the program prints a usage message and exits.

If you want, I can also give you a one-line explanation you can paste into your assignment comments.

p5_Betensky_Louis.py:1-197

Describe what to build

Agent Auto Balance

Program function development request

When I try and run it all I get is this:

This program reads a weather observation file and writes station statistics.
Expected input file format: station,date,temperature
Example line: A,2024-01-15,12.5
Valid temperatures must be between -100.0 and 150.0 inclusive.

Usage: python p5_Betensky_Louis.py <input_file> <output_file>
Example: python p5_Betensky_Louis.py observations.csv stats.csv
spyder PS C:\Users\louie\OneDrive\Documents\School Work\cop4045\Homework2>

No chance to input

Why it appears to stop

This script is not using a prompt like `input()`; it is reading arguments from the command line. That means the user must type the file names when launching the program, not after it starts.

The program checks:

```
if len(sys.argv) != 3:
    print("Usage: ...")
    return 1
```


So when you run it with no arguments, it immediately prints the usage message and exits.

How to run it correctly

Open a terminal in the folder and type:

```
cd "C:\Users\louie\OneDrive\Documents\School Work\cop4045\Homework2"
python p5_Betensky_Louis.py input.csv output.csv
```

For example:



Program function development request

When I try and run it all I get is this:...

How to run it correctly

Open a terminal in the folder and type:

```
cd "C:\Users\louie\OneDrive\Documents\School Work\cop4045\Homework2"
python p5_Betensky_Louis.py input.csv output.csv
```

For example:

```
python p5_Betensky_Louis.py weather_data.csv stats.csv
```

Then the program will read:

- `weather_data.csv` as the input file
- `stats.csv` as the output file

If you are using Spyder

Spyder usually does not prompt you for command-line arguments unless you configure them. So the "no chance to input" behavior is expected there.

The easiest fix is:


- run the script from a normal terminal/PowerShell window
- not from the Spyder Run button

One-line explanation for your assignment

The file names are entered after the script name in the terminal, like:

```
python p5_Betensky_Louis.py observations.csv stats.csv
```

That is how the program gets the input and output file names.



Program function development request

Okay so I realized a few things I failed to elaborate fully on as we did this. So I need you to go through and change some things. ready?

I'm ready to adjust the design based on the missing details, and I'll update the implementation to match the corrected behavior before we finish.

Absolutely — go ahead and tell me the missing details or corrections, and I'll update the program accordingly.

Please give me:

- what changed in the requirements
- which functions need to be modified
- any exact output format or examples
- anything you want kept the same

Once you list them, I'll revise the code and make the fixes.

p5_Betensky_Louis.py:1-195

First, date is a string but the date is meant to have the order of time(HOUR:MINUTE:SECOND), am/pm, and then MM/DD/YYYY

So please change anywhere in the file this is an issue

Completed 5 steps in 18s

✅ Date format corrected

I updated the code so the date is now treated as:

- time first
- then AM/PM
- then the date in MM/DD/YYYY format

Example format:

```
10:30:00 AM 01/15/2024
```

p5_Betensky_Louis.py:1-197

Describe what to build

Agent Auto Balance

Local Default permissions

Program function development request

First, date is a string but the date is meant to have the order of time(HOUR:MINUTE:SECOND), am/pm, and then MM/DD/YYYY...

Completed 5 steps in 18s

✅ Date format corrected

I updated the code so the date is now treated as:

- time first
- then AM/PM
- then the date in MM/DD/YYYY format

Example format:

```
10:30:00 AM 01/15/2024
```

I changed the relevant parsing in `p5_Betensky_Louis.py` from the old `YYYY-MM-DD` style to:

```
"%I:%M:%S %p %m/%d/%Y"
```

I also updated the examples and the test file to match that format.

Verification

I ran the test suite after the change and it passed:

- `Ran 7 tests in 0.047s`
- `OK`

If you want, send me the next correction to the requirements and I'll update the rest of the program in the same way.

p5_Betensky_Louis.py:1-

p5_Betensky_Louis.py:1-197

Describe what to build

Agent Auto Balance

Local Default permissions

Program function development request

p5_Betensky_Louis.py:1-195

main is meant to catch file access errors and exit gracefully, preferably with a messge for the user as well as raising/reraising the error

Completed 4 steps in 23s

Updated behavior

I changed the entry point in `p5_Betensky_Louis.py` so that:

- it catches file-related exceptions in `main()`
- prints a clear message to the user
- then re-raises the exception with `raise`

That gives the user a friendly message, while still preserving the real error for debugging.

The relevant pattern is:

```
try:
    ...
except OSError as exc:
    print(f"File access error: {exc}")
    raise
```

Important note

For a missing input file, your `read_observations()` already handles it gracefully by returning:

```
({}, [(0, "File not found: ...")])
```

So the user gets a readable message there as well, and the `main()` `OSError` handler covers the real filesystem failures such as permission issues or write failures.

If you want, I can also tighten the message wording so it sounds more polished for a class assignment.

p5_Betensky_Louis.py:1-197

Describe what to build

Agent Auto Balance

Program function development request

I also notice you have read observations in a class? I don't recall asking you to do this

Completed 4 steps in 38s

Good catch — you were right

I removed the class-based structure and converted the implementation to standalone functions, as requested.

The program now uses:

- `read_observations(filename)`
- `station_statistics(observations)`
- `station_outliers(observations)`
- `write_statistics(filename, statistics)`
- `main()`

This matches the design you described, instead of building everything inside a class.

Verification

I re-ran the test suite after the refactor and it still passes:

- `Ran 7 tests in 0.021s`
- `OK`

The working file is here:

- `p5_Betensky_Louis.py`

If you want, I can now help you tighten the wording in the function docstrings or make the `main()` output even more polished for an assignment submission.

Program function development request

The assignment asks for graceful handling of code. With this in mind should we be reraising the errors?

Recommendation

Yes — for this assignment, the better pattern is to handle the error gracefully but not hide it.

In other words:

- print a clear message to the user
- then re-raise the exception so the program still reports the real failure

That is the right balance between user-friendly behavior and debugging correctness.

This matches the intent in `p5_Betensky_Louis.py` : the `main()` function should not silently fail on a missing file or bad path.

Best interpretation

Use this pattern:

```
except OSError as exc:
    print(f"File access error: {exc}")
    raise
```

Why this is good:

- the user sees a readable message
- the exception is not swallowed
- the traceback still makes debugging easier if needed

Important distinction

"Graceful" does not mean "ignore the error."

If you only print the message and return, the program may appear to work but the underlying issue is hidden.

For a command-line app, a more polished version is often:

```
except OSError as exc:
    print(f"File access error: {exc}", file=sys.stderr)
    raise SystemExit(1)
```

p5_Betensky_Louis.py:1-197

Describe what to build

Agent Auto Balance

Program function development request

The assignment asks for graceful handling of code. With this in mind should we be reraising the errors?

If you only print the message and return, the program may appear to work but the underlying issue is hidden.

For a command-line app, a more polished version is often:

```
except OSError as exc:
    print(f"File access error: {exc}", file=sys.stderr)
    raise SystemExit(1)
```

This exits cleanly without a traceback, but it is a bit different from the assignment wording. Since your requirement specifically mentions raising or re-raising, the `raise` version is the safer choice.

> So: yes, re-raising is appropriate here if the goal is to be graceful and still honest about the error.

p5_Betensky_Louis.py:1-194

I think it should be ending the program smoothly, not crashing and showing the tracebacks

Completed 8 steps in 18s

You're right. A graceful failure should not show a traceback.

I updated `main()` so that it:

- prints the file error
- stops immediately
- returns exit code `1`
- does not create an output file
- does not re-raise the exception or show a traceback

The missing-file test now exits cleanly with code `1`, and all 7 unit tests still pass.

p5_Betensky_Louis.py:1-197

Describe what to build

Agent Auto Balance

Local Default permissions