

4 Design patterns

Main concepts to be covered

- Why design patterns matters
- Classification of patterns
- Some common patterns
 - Composite
 - Decorator
 - Singleton
 - Factory method
 - Observer

Objektorienterade applikationer, DAT055, DAIZ, 11/12, lp 3

Nr 7 2

Why design patterns matters

- Inter-class relationships are important, and can be complex.
- Some relationships recur in different applications.
- Design patterns help clarify relationships, and promote reuse.
- Don't reinvent the wheel!

Objektorienterade applikationer, DAT055, DAIZ, 11/12, lp 3

Nr 7 3

Small and large Patterns

- Architectural patterns (large scale)
- Design patterns (medium scale)
- Idioms (small scale)

Objektorienterade applikationer, DAT055, DAIZ, 11/12, lp 3

Nr 7 4

Architectural Pattern

- Fundamental structural organization template for a whole software system.
- It provides
 - a set of predefined subsystems
 - responsibilities of subsystems
 - relationships between subsystems
- Example Model View Controller

Objektorienterade applikationer, DAT055, DAIZ, 11/12, lp 3

Nr 7 5

Design pattern

- Medium scale organization scheme for components of a software system.
- It provides
 - a scheme for refining components and their relationships.
 - communication rules for cooperating components.
- It is independent of programming language.
- Example Observer

Objektorienterade applikationer, DAT055, DAIZ, 11/12, lp 3

Nr 7 6

Idiom

- Low level design pattern.
- Programming language specific implementation techniques.
- Example: The string copy loop idiom for the C/C++ programming language

```
- while ((*t++ = *s++) != '\0') ;
```

Objektorienterade applikationer, DAT055, DA12, 11/12, lp 3

Nr 7 7

Design pattern categories

- **Creational patterns:** Object creation.
 - Singleton, Factory, Abstract Factory, Factory Method, ...
- **Structural patterns:** Static composition.
 - Composite, Decorator, Adapter, ...
- **Behavioral patterns:** Dynamic object interaction.
 - Iterator, Command, State, Template Method, Strategy, ...

Objektorienterade applikationer, DAT055, DA12, 11/12, lp 3

Nr 7 8

Design pattern description

A design pattern description consists of

- **Pattern name.**
- **Category:**
 - Creational, Structural, or behavioral.
- **Intent:**
 - The problem addressed by it.
- **Structure:**
 - Class diagram showing participants and relationships.
- **Participants:**
 - A list of participating classes or objects and their collaboration.
- **Applicability:**
 - Situations in which it is useful.
- **Its consequences:**
 - Results, trade-offs.

Objektorienterade applikationer, DAT055, DA12, 11/12, lp 3

Nr 7 9

Composite

- Composite defines a part-whole relationship between objects in a tree hierarchy.
- Simple objects and composite objects can be treated **uniformly** by clients
 - uniformly with respect to their **common interface**.

Objektorienterade applikationer, DAT055, DA12, 11/12, lp 3

Nr 7 10

Composite (2)


Example instances:

- Component, Container, JPanel, JButton, ...
- Hierarchical file systems have two kinds of files
 - "Ordinary" files (Leaf) contain data.
 - Directories (Composite) contain files.

Objektorienterade applikationer, DAT055, DA12, 11/12, lp 3







Nr 7 11

An instance of Composite: Hierarchical file systems




Objektorienterade applikationer, DAT055, DA12, 11/12, lp 3


Nr 7 12




Extension by inheritance




Extension using Decorator pattern




Example: Number generator




Decorated NumberGenerator



Using the BufferedNumberGenerator



Using the BufferedNumberGenerator



Java implementation

```
public class BufferedNumberGenerator implements NumberGenerator {
    private NumberGenerator decoratedObject;

    public BufferedNumberGenerator(NumberGenerator decoratedObject) {
        this.decoratedObject = decoratedObject;
    }

    public void computeNext() { decoratedObject.computeNext(); }
    public void reset() { decoratedObject.reset(); }
    public long getValue() { return decoratedObject.getValue(); }

    public long[] getSequence(int n) {
        long[] numArray = new long[n];
        for (int i = 0; i < n; i++) {
            numArray[i] = decoratedObject.getValue();
            decoratedObject.computeNext();
        }
        return numArray;
    }
}
```

Delegation

New

Objektorienterade applikationer, DAT055, DA12, 11/12, lp 3

Nr 7 25

Singleton

- Ensures only a **single instance** of a class exists.
 - All clients use the same object.
- Constructor is private to prevent external instantiation.
- Single instance obtained via a static **getInstance** method.
- Example: Canvas in *shapes* project.

Objektorienterade applikationer, DAT055, DA12, 11/12, lp 3

Nr 7 26

Singleton Java implementation template

```
public class Singleton {
    private static Singleton instance = null;

    // Private prevents external object creation
    private Singleton() {}

    // Return the single object of this class
    // create (lazily) if necessary
    public static synchronized Singleton getInstance() {
        if (instance == null)
            instance = new Singleton();

        return instance;
    }
}
```

Objektorienterade applikationer, DAT055, DA12, 11/12, lp 3

Nr 7 27

Singleton: an example

```
public class TicketMachine {
    private static TicketMachine instance = null;
    private int count;

    // This forbids external object creation
    private TicketMachine() { count = 0; }

    // Return the single object of this class,
    // create if necessary
    public static synchronized TicketMachine getInstance() {
        if (instance == null)
            instance = new TicketMachine();
        return instance;
    }

    public synchronized int getTicket() {
        return ++count;
    }
}
```

Ticket numbers are guaranteed to be **unique** as there can only exist one object of this class.


Objektorienterade applikationer, DAT055, DA12, 11/12, lp 3

Nr 7 28

Using the ticket machine

```
//Client 1
TicketMachine tm = TicketMachine.getInstance();
int ticket = tm.getTicket();
...

//Client 2
TicketMachine tm = TicketMachine.getInstance();
int ticket = tm.getTicket();
...
```



Objektorienterade applikationer, DAT055, DA12, 11/12, lp 3

Nr 7 29


Factory method

- A creational pattern.
- Clients require an object of a particular interface type or superclass type.
- A factory method is free to return an implementing-class object or subclass object.
- Exact type returned depends on context.
- Example: **iterator** methods of the Collection classes.

Objektorienterade applikationer, DAT055, DA12, 11/12, lp 3

Nr 7 30


Factory method (2)



Objektorienterade applikationer, DAT055, DA12, 11/12, lp 3

Nr 7 31


Example: SimpleArrayList



Objektorienterade applikationer, DAT055, DA12, 11/12, lp 3

Nr 7 32

Example: SimpleArrayList (2)



Objektorienterade applikationer, DAT055, DA12, 11/12, lp 3

Nr 7 33


Observer

- Supports separation of internal model from a view of that model.
- Observer defines a one-to-many relationship between objects.
- The object-observed notifies all Observers of any state change.
- Example SimulatorView in the *foxes-and-rabbits* project.

Objektorienterade applikationer, DAT055, DA12, 11/12, lp 3

Nr 7 34

Observers



Objektorienterade applikationer, DAT055, DA12, 11/12, lp 3

Nr 7 35

Review

- Design flexible, extendible and maintainable class structures.
- Being aware of existing design patterns will help you to do this.

Objektorienterade applikationer, DAT055, DA12, 11/12, lp 3

Nr 7 36