

Kick Start 2021 - Round A

K-Goodness String

Problem

Charles defines the goodness score of a string as the number of indices i such that $S_i \neq S_{N-i+1}$ where $1 \leq i \leq N/2$ (1-indexed). For example, the string `CABABC` has a goodness score of 2 since $S_2 \neq S_5$ and $S_3 \neq S_4$.

Charles gave Ada a string S of length N , consisting of uppercase letters and asked her to convert it into a string with a goodness score of K . In one operation, Ada can change any character in the string to any uppercase letter. Could you help Ada find the *minimum* number of operations required to transform the given string into a string with goodness score equal to K ?

Input

The first line of the input gives the number of test cases, T . T test cases follow.

The first line of each test case contains two integers N and K . The second line of each test case contains a string S of length N , consisting of uppercase letters.

Output

For each test case, output one line containing `Case #x: y`, where x is the test case number (starting from 1) and y is the minimum number of operations required to transform the given string S into a string with goodness score equal to K .

Limits

Memory limit: 1 GB.

$1 \leq T \leq 100$.

$0 \leq K \leq N/2$.

Test Set 1

Time limit: 20 seconds.

$1 \leq N \leq 100$.

Test Set 2

Time limit: 40 seconds.

$1 \leq N \leq 2 \times 10^5$ for at most 10 test cases.

For the remaining cases, $1 \leq N \leq 100$.

Sample

Sample Input

```
2
5 1
```

Sample Output

```
Case #1: 0
Case #2: 1
```

ABCAA
4 2
ABAA

In Sample Case #1, the given string already has a goodness score of 1. Therefore the minimum number of operations required is 0.

In Sample Case #2, one option is to change the character at index 1 to **B** in order to have a goodness score of 2. Therefore, the minimum number of operations required is 1.