Assignment – 5

Code :

```
import React from "react";

export default function Home() {
  return (
    <div className="font-sans">

      {/* Navbar */}
      <nav className="flex justify-between items-center p-5 bg-white shadow-md">
        <h1 className="text-2xl font-bold text-blue-600">Destination Luxe</h1>
        <ul className="flex gap-6">
          <li>Home</li>
          <li>Destinations</li>
          <li>Packages</li>
          <li>Contact</li>
        </ul>
      </nav>

      {/* Hero Section */}
      <section className="h-[80vh] bg-cover bg-center flex items-center justify-center text-white"
        style={{ backgroundImage: "url('/travel.jpg')" }}>
        <div className="text-center">
          <h2 className="text-5xl font-bold">Explore The World</h2>
          <p className="mt-4">Luxury travel experiences curated for you</p>
          <button className="mt-6 px-6 py-3 bg-blue-600 rounded-lg">
            Book Now
          </button>
        </div>
      </section>

    </div>
  );
}const destinations = [
  { name: "Paris", image: "/paris.jpg" },
  { name: "Bali", image: "/bali.jpg" },
  { name: "Dubai", image: "/dubai.jpg" },
];

export default function Destinations() {
  return (
    <div className="p-10">
      <h2 className="text-3xl font-bold text-center mb-8">
        Popular Destinations
      </h2>
```

```
    <div className="grid grid-cols-3 gap-6">
     {destinations.map((place, index) => (
      <div key={index} className="rounded-xl overflow-hidden shadow-lg">
       <img src={place.image} alt={place.name} />
       <h3 className="text-xl text-center p-3">{place.name}</h3>
      </div>
     ))}
    </div>
   </div>
  );
}import { useState } from "react";

export default function BookingForm() {
  const [form, setForm] = useState({
    name: "",
    email: "",
    destination: "",
  });

  const handleSubmit = (e) => {
    e.preventDefault();
    console.log(form);
    alert("Booking Submitted!");
  };

  return (
    <form onSubmit={handleSubmit} className="p-6 bg-gray-100 rounded-lg">
      <input
        type="text"
        placeholder="Your Name"
        className="block mb-4 p-2 w-full"
        onChange={(e) => setForm({ ...form, name: e.target.value })}
      />

      <input
        type="email"
        placeholder="Email"
        className="block mb-4 p-2 w-full"
        onChange={(e) => setForm({ ...form, email: e.target.value })}
      />

      <select
        className="block mb-4 p-2 w-full"
        onChange={(e) => setForm({ ...form, destination: e.target.value })}
      >
        <option>Select Destination</option>
        <option>Paris</option>
```

```
      <option>Bali</option>
      <option>Dubai</option>
    </select>

    <button className="bg-blue-600 text-white px-4 py-2 rounded">
      Submit
    </button>
  </form>
 );
}
const express = require("express");
const app = express();
app.use(express.json());

let bookings = [];

app.post("/book", (req, res) => {
 const data = req.body;
 bookings.push(data);
 res.send("Booking saved successfully");
});

app.get("/bookings", (req, res) => {
 res.json(bookings);
});

app.listen(3000, () => console.log("Server running on port 3000"));
const mongoose = require("mongoose");

const bookingSchema = new mongoose.Schema({
 name: String,
 email: String,
 destination: String,
});

module.exports = mongoose.model("Booking", bookingSchema); export default function Footer() {
 return (
  <footer className="bg-black text-white text-center p-5 mt-10">
   <p>© 2026 Destination Luxe. All Rights Reserved.</p>
  </footer>
 );
}
```