Assignment – 6

Code :

```
import React, { useState } from "react";


export function Home() {
  return (
    <div className="font-sans">

      {/* Navbar */}
      <nav className="flex justify-between p-4 shadow-md bg-white">
        <h1 className="text-2xl font-bold text-green-600">ReMarket</h1>
        <div className="space-x-5">
          <button>Home</button>
          <button>Sell</button>
          <button>Login</button>
        </div>
      </nav>

      {/* Hero Section */}
      <section className="text-center py-12 bg-gray-100">
        <h2 className="text-4xl font-bold">Buy & Sell Anything</h2>
        <p className="mt-3">Best marketplace for second-hand items</p>
      </section>

    </div>
  );
}
export function ProductList() {
  const products = [
    { name: "iPhone 13", price: "₹45,000", image: "/iphone.jpg" },
    { name: "Bike", price: "₹30,000", image: "/bike.jpg" },
    { name: "Laptop", price: "₹55,000", image: "/laptop.jpg" },
  ];
  return (
```

```
    <div className="p-8 grid grid-cols-3 gap-6">
      {products.map((item, index) => (
        <div key={index} className="shadow-lg rounded-xl p-4">
          <img src={item.image} alt={item.name} />
          <h2 className="text-xl font-semibold">{item.name}</h2>
          <p className="text-green-600">{item.price}</p>
          <button className="mt-3 bg-green-500 text-white px-4 py-2 rounded">
            View Details
          </button>
        </div>
      ))}
    </div>
  );
}

export function SellForm() {
  const [product, setProduct] = useState({
    name: "",
    price: "",
    description: "",
  });

  const handleSubmit = (e) => {
    e.preventDefault();
    console.log(product);
    alert("Product Listed Successfully!");
  };

  return (
    <form onSubmit={handleSubmit} className="p-6 bg-gray-100 rounded-lg">
      <input
        type="text"
        placeholder="Product Name"
        className="block mb-3 p-2 w-full"
```

```
      onChange={(e) => setProduct({ ...product, name: e.target.value })}
    />

    <input
      type="text"
      placeholder="Price"
      className="block mb-3 p-2 w-full"
      onChange={(e) => setProduct({ ...product, price: e.target.value })}
    />

    <textarea
      placeholder="Description"
      className="block mb-3 p-2 w-full"
      onChange={(e) => setProduct({ ...product, description: e.target.value })}
    />

    <button className="bg-green-600 text-white px-4 py-2 rounded">
      Post Ad
    </button>
  </form>
 );
}

export function Login() {
 return (
  <div className="flex justify-center items-center h-screen">
   <form className="p-6 bg-white shadow-lg rounded">
    <h2 className="text-xl mb-4">Login</h2>

    <input type="email" placeholder="Email" className="block mb-3 p-2 w-full" />
    <input type="password" placeholder="Password" className="block mb-3 p-2 w-full" />
    <button className="bg-green-600 text-white px-4 py-2 w-full">
     Login
    </button>
```

```
    </form>
   </div>
  );
}

const express = require("express");
const app = express();

app.use(express.json());

let products = [];

// Add Product API
app.post("/add-product", (req, res) => {
  const data = req.body;
  products.push(data);
  res.send("Product added successfully");
});

// Get All Products API
app.get("/products", (req, res) => {
  res.json(products);
});

app.listen(3000, () => {
  console.log("Server running on port 3000");
});
const mongoose = require("mongoose");

const productSchema = new mongoose.Schema({
  name: String,
  price: String,
  description: String,});
module.exports = mongoose.model("Product", productSchema);
```