

Relational Language

Swarup Kr Ghosh

swarupg1@gmail.com

@ SKG 9/9/2020 1

Relational Model Concepts

- ❑ Language in which user requests information from the database
- ❖ The relational Model of Data is based on the concept of a **Relation**.
- ❖ A **Relation** is a mathematical concept based on the ideas of sets
- ❖ The strength of the relational approach to data management comes from the formal foundation provided by the theory of relations

@ SKG 9/9/2020 2

Query Languages


- Categories of languages
 - ❖ procedural
 - ❖ non-procedural
- “Pure” languages:
 - ❖ Relational Algebra
 - ❖ Relational Calculus
 - Tuple Relational Calculus
 - Domain Relational Calculus
- Pure languages form underlying basis of query languages that people use

@ SKG

9/9/2020

3

RELATIONAL ALGEBRA



Extended Relational-Algebra-Operations

The operators take one or more relations as inputs
and give a new relation as a result

@ SKG

9/9/2020

4

Example of Relation

emp

eno	ename	sal
e1	Sam	700
e2	John	500
e3	Smith	1000
e4	Sarah	900

@ SKG

9/9/2020

5

Select ()

<search condition> (Relation Name)

❖Query:

emp

eno	ename	sal
e1	Sam	700
e2	John	500
e3	Smith	1000
e4	Sarah	900

Q1. Select all the information of the employee whose salary is more than Rs.700

sal>700(emp);

SELECT * FROM emp WHERE sal> 700;

eno	ename	sal
e3	Smith	1000
e4	Sarah	900

@ SKG

9/9/2020

6

Select ()

❖Query:

Q2. Select all the information of the employee whose salary is more than Rs.500 but less than 1000

$sal > 500 \wedge sal < 1000$ (emp);

emp

eno	ename	sal
e1	Sam	700
e2	John	500
e3	Smith	1000
e4	Sarah	900

SELECT * FROM emp WHERE sal > 700 AND sal < 1000;

eno	ename	sal
e4	Sarah	900

@ SKG

9/9/2020

7

Select ()

❖Query:

Q3. Select all the information of the employee whose employee id is e1

$eno = e1$ (emp);

SELECT * FROM EMP WHERE eno=e1;

emp

eno	ename	sal
e1	Sam	700
e2	John	500
e3	Smith	1000
e4	Sarah	900



eno	ename	sal
e1	Sam	700

@ SKG

9/9/2020

8

Select ()

❖ Query:

Q4. Select all the information of the employee

(emp)

SELECT * FROM emp;

emp

eno	ename	sal
e1	Sam	700
e2	John	500
e3	Smith	1000
e4	Sarah	900



eno	ename	sal
e1	Sam	700
e2	John	500
e3	Smith	1000
e4	Sarah	900

@ SKG

9/9/2020

9

Select Operation

- Notation: $\uparrow_p(r)$
- p is called the **selection predicate**
- Defined as:

OPERATORS in RA is not always same as SQL

$$\uparrow_p(r) = \{t \mid t \in r \text{ and } p(t)\}$$

Where p is a formula in propositional calculus consisting of **terms** connected by : \wedge (**and**), \vee (**or**), \neg (**not**)

Each **term** is one of:

$\langle \text{attribute} \rangle$ op $\langle \text{attribute} \rangle$ or $\langle \text{constant} \rangle$

where op is one of: $=, \neq, >, \geq, <, \leq$

- Example of selection:

$\uparrow_{\text{branch_name} = \text{"Perryridge"}}(\text{account})$

@ SKG

9/9/2020

10

SELECT Operation Properties

- ❑ The SELECT operation $\sigma_{\langle \text{selection condition} \rangle}(R)$ produces a relation S that has the same schema as R
- ❑ The SELECT operation is **commutative**; i.e.,

$$\sigma_{\langle \text{condition1} \rangle}(\sigma_{\langle \text{condition2} \rangle}(R)) = \sigma_{\langle \text{condition2} \rangle}(\sigma_{\langle \text{condition1} \rangle}(R))$$
- ❑ A cascaded SELECT operation **may be applied in any order**; i.e.,

$$\sigma_{\langle \text{condition1} \rangle}(\sigma_{\langle \text{condition2} \rangle}(\sigma_{\langle \text{condition3} \rangle}(R))) = \sigma_{\langle \text{condition2} \rangle}(\sigma_{\langle \text{condition3} \rangle}(\sigma_{\langle \text{condition1} \rangle}(R)))$$
- ❑ A cascaded SELECT operation may be replaced by a single selection with a conjunction of all the conditions; i.e.,


$$\sigma_{\langle \text{condition1} \rangle}(\sigma_{\langle \text{condition2} \rangle}(\sigma_{\langle \text{condition3} \rangle}(R))) = \sigma_{\langle \text{condition1} \rangle \text{ AND } \langle \text{condition2} \rangle \text{ AND } \langle \text{condition3} \rangle}(R)$$

@ SKG

9/9/2020

11

RELATIONAL ALGEBRA



The operators take one or more relations as inputs
and give a new relation as a result

@ SKG

9/9/2020

12

Project ()

<attribute name> (Relation Name)

❖Query:

<attr₁,attr₂,..... > (Relation Name)

Q5. Select the employee id of the employee.

SELECT eno FROM emp;

emp

eno	ename	sal
e1	Sam	700
e2	John	500
e3	Smith	1000
e4	Sarah	900

eno(emp)



eno
e1
e2
e3
e4

@ SKG

9/9/2020

13

Project ()

❖Query:

Q6. Select the employee id and the name of the employee

eno,ename (emp)

SELECT eno, ename FROM emp;

emp

eno	ename	sal
e1	Sam	700
e2	John	500
e3	Smith	1000
e4	Sarah	900



eno	ename
e1	Sam
e2	John
e3	Smith
e4	Sarah

@ SKG

9/9/2020

14

Project ()

❖ Query:

Q7. Select all the information of the employee

eno,ename,sal (emp)

(emp)

SELECT * FROM emp;

emp

eno	ename	sal
e1	Sam	700
e2	John	500
e3	Smith	1000
e4	Sarah	900



eno	ename	sal
e1	Sam	700
e2	John	500
e3	Smith	1000
e4	Sarah	900

@ SKG

9/9/2020

15

PROJECT Operation Properties

- ❖ The number of tuples in the result of projection $\pi_{\langle \text{list} \rangle}(R)$ is always less or equal to the number of tuples in R .
- ❖ If the list of attributes includes a key of R , then the number of tuples is equal to the number of tuples in R .
- ❖ $\pi_{\langle \text{list1} \rangle}(\pi_{\langle \text{list2} \rangle}(R)) = \pi_{\langle \text{list1} \rangle}(R)$ as long as $\langle \text{list2} \rangle$ contains the attributes in $\langle \text{list1} \rangle$

@ SKG

9/9/2020

16

Select + Project

❖Query:

Q8. Select the name of the employee whose salary is more than Rs.700

ename (sal>700(emp))

SELECT ename FROM emp WHERE sal> 700;

emp

eno	ename	sal
e1	Sam	700
e2	John	500
e3	Smith	1000
e4	Sarah	900

ename

Smith
Sarah

Is the following sequences are Equivalent?

SELECT @ PROJECT

PROJECT @ ~~SELECT~~

@ SKG

9/9/2020

17

Example of Relations

emp

eno	ename	dno
e1	Sam	d2
e2	John	d1
e3	Smith	d1
e4	Sarah	d3

dept

dnum	dname
d1	Sales
d2	Marketing
d3	HR

❖Query:

❖Q9. Find the employee id, name and departmental information of the employee.

@ SKG

9/9/2020

18

Example of Relations

❖ Q9. Find the employee id, name and departmental information of the employee.

emp

eno	ename	dno
e1	Sam	d2
e2	John	d1
e3	Smith	d1
e4	Sarah	d3

dept

dnum	dname
d1	Sales
d2	Marketing
d3	HR



eno	ename	dno	dname
e1	Sam	d2	Marketing
e2	John	d1	Sales
e3	Smith	d1	Sales
e4	Sarah	d3	HR

@ SKG

9/9/2020

19

RELATIONAL ALGEBRA

❖ Relational Algebra

❖ Unary Operator

➤ Select ()

➤ Project ()

➤ Rename ()

❖ Binary Operator

➤ **Cartesian Product (×)**

➤ Union (U)

➤ Set Difference (—)

Extended Relational-Algebra-Operations

The operators take one or more relations as inputs
and give a new relation as a result

@ SKG

9/9/2020

20

Cartesian-Product Operation

- ❖ Notation $r \times s$
- ❖ Defined as:
- ❖
$$r \times s = \{t \mid t \in r \text{ and } t \in s\}$$
- ❖ Assume that attributes of $r(R)$ and $s(S)$ are disjoint. (That is, $R \cap S = \emptyset$).
- ❖ If attributes of $r(R)$ and $s(S)$ are not disjoint, then renaming must be used.

@ SKG

9/9/2020

21

Cartesian Product

emp

eno	ename	dno
e1	Sam	d2
e2	John	d1
e3	Smith	d1
e4	Sarah	d3

dept

dnum	dname
d1	Sales
d2	Marketing
d3	HR

×

```
SELECT * FROM emp, dept;
```

@ SKG

9/9/2020

22

Cartesian Product

emp \times dept

eno	ename	dno	dnum	dname
e1	Sam	d2	d1	Sales
e1	Sam	d2	d2	Marketing
e1	Sam	d2	d3	HR
e2	John	d1	d1	Sales
e2	John	d1	d2	Marketing
e2	John	d1	d3	HR
e3	Smith	d1	d1	Sales
e3	Smith	d1	d2	Marketing
e3	Smith	d1	d3	HR
e4	Sarah	d3	d1	Sales
e4	Sarah	d3	d2	Marketing
e4	Sarah	d3	d3	HR

@ SKG

9/9/2020

23

Cartesian Product

emp \times dept



dno=dnum (emp \times dept)

eno	ename	dno	dnum	dname
e1	Sam	d2	d2	Marketing
e2	John	d1	d1	Sales
e3	Smith	d1	d1	Sales
e4	Sarah	d3	d3	HR

**JOINING/
INNERJOIN**

emp \bowtie dept
dno=dnum

SELECT * FROM emp, dept WHERE dno=dnum;

@ SKG

9/9/2020

24

Join Operation : Derived Operator

- ❖ The **sequence of cartesian product followed by select** is used quite commonly to identify and select related tuples from two relations, a special operation, called **JOIN**
- ❖ This operation is very important for any relational database with more than a single relation, because it allows us to process relationships among relations
- ❖ The general form of a join operation on two relations $R(A_1, A_2, \dots, A_n)$ and $S(B_1, B_2, \dots, B_m)$ is:

$$R \bowtie_{\langle \text{join condition} \rangle} S$$

where R and S can be any relations that result from general *relational algebra expressions*

@ SKG

9/9/2020

25

Joining : Derived Operator

JOINING ① Cartesian Product Followed by a Select Operation

EQUI JOIN

THETA JOIN / JOIN

NATURAL JOIN

SELF JOIN

OUTER JOIN

@ SKG

9/9/2020

26

Joining : Derived Operator

EQUI JOIN

emp ⋈_{dno=dnum} dept

THETA JOIN / JOIN

emp ⋈_{dno=dnum sal>700} dept

R ⋈ S

@ SKG

9/9/2020

27

Cartesian Product

THETA JOIN

emp ⋈_{dno=dnum} dept

emp

eno	ename	sal	dno
e1	Sam	100	d2
e2	John	800	d1
e3	Smith	1000	d1
e4	Sarah	400	d3

eno	ename	sal	dno	dnum	dname
e1	Sam	100	d2	d2	Marketing
e2	John	800	d1	d1	Sales
e3	Smith	1000	d1	d1	Sales
e4	Sarah	400	d3	d3	HR

emp ⋈_{dno=dnum sal>700} dept

dept

dnum	dname
d1	Sales
d2	Marketing
d3	HR

SELECT * FROM emp, dept WHERE dno=dnum AND sal>700;

eno	ename	sal	dno	dnum	dname
e2	John	800	d1	d1	Sales
e3	Smith	1000	d1	d1	Sales

@ SKG

9/9/2020

28

Joining : Derived Operator

$\text{emp} \bowtie_{\text{dno=dnum}} \text{dept}$ **Redundancy**

eno	ename	dno	dnum	dname
e1	Sam	d2	d2	Marketing
e2	John	d1	d1	Sales
e3	Smith	d1	d1	Sales
e4	Sarah	d3	d3	HR


@ SKG

9/9/2020

29

Joining : Derived Operator

$\text{emp} \times \text{dept}$  $\text{emp} \bowtie_{\text{dno=dnum}} \text{dept}$

 $\text{eno, ename, dno, dname} (\text{dno=dnum} (\text{emp} \times \text{dept}))$

eno	ename	dno	dname
e1	Sam	d2	Marketing
e2	John	d1	Sales
e3	Smith	d1	Sales
e4	Sarah	d3	HR

SELECT eno,ename,dno,dname FROM emp, dept WHERE dno=dnum;

@ SKG

9/9/2020

30

Example of Relation

emp

eno	ename	dno
e1	Sam	d2
e2	John	d1
e3	Smith	d1
e4	Sarah	d3

dept

dno	dname
d1	Sales
d2	Marketing
d3	HR

❖Query:

Find the employee id, name and departmental information of the employee.

emp ⋈ **dept**
emp.dno=dept.dno

SELECT * FROM emp, dept WHERE emp.dno=dept.dno;

@ SKG

9/9/2020

31

Example of Relation

emp ⋈ **dept**
emp.dno=dept.dno

SELECT * FROM emp, dept WHERE emp.dno=dept.dno;

eno	ename	dno	dno	dname
e1	Sam	d2	d2	Marketing
e2	John	d1	d1	Sales
e3	Smith	d1	d1	Sales
e4	Sarah	d3	d3	HR

@ SKG

9/9/2020

32

Joining : Derived Operator

$\text{emp.dno} = \text{dept.dno} (\text{emp} \times \text{dept})$



$\text{eno,ename,emp.dno,dname} (\text{emp.dno}=\text{dept.dno} (\text{emp} \times \text{dept}))$

eno	ename	dno	dname
e1	Sam	d2	Marketing
e2	John	d1	Sales
e3	Smith	d1	Sales
e4	Sarah	d3	HR

NATURAL JOINING

$\text{emp} \bowtie \text{dept}$

**SELECT eno,ename,emp.dno,dname FROM emp, dept WHERE
emp.dno=dept.dno;**

10/20/2020

Assistant Professor Radio Physics and Electronics

33

Joining : Derived Operator

emp			dept	
eno	ename	dno	dno	dname
e1	Sam	d2	d1	Sales
e2	John	d1	d2	Marketing
e3	Smith	d1	d3	HR
e4	Sarah	d3		

eno	ename	dno	dname
e1	Sam	d2	Marketing
e2	John	d1	Sales
e3	Smith	d1	Sales
e4	Sarah	d3	HR

$\text{emp} \bowtie \text{dept}$

$\text{eno,ename,emp.dno,dname} (\text{emp.dno}=\text{dept.dno} (\text{emp} \times \text{dept}))$

@ SKG

9/9/2020

34

Natural-Join Operation

- Let r and s be relations on schemas R and S respectively. Then, $r \bowtie s$ is a relation on schema $R \cup S$ obtained as follows:

$$r \bowtie s = \pi_{R \cup S} \left(\sigma_{r.A_1=s.A_1 \wedge r.A_2=s.A_2 \wedge \dots \wedge r.A_n=s.A_n} (r \times s) \right)$$

$$R \cap S = \{A_1, A_2, \dots, A_n\}$$

Example:

$R = (A, B, C, D)$

$S = (E, B, D)$

Result schema = (A, B, C, D, E)

$r \bowtie s$ is defined as:

$$\pi_{r.A, r.B, r.C, r.D, s.E} (\sigma_{r.B=s.B \wedge r.D=s.D} (r \times s))$$

@ SKG

9/9/2020

35

Natural Join Operation – Example

- Relations r , s :

A	B	C	D
r	1	r	a
s	2	x	a
x	4	s	b
r	1	x	a
u	2	s	b

r

B	D	E
1	a	r
3	a	s
1	a	x
2	b	u
3	b	e

s

$r \bowtie s$

A	B	C	D	E
r	1	r	a	r
r	1	r	a	x
r	1	x	a	r
r	1	x	a	x
u	2	s	b	u

@ SKG

9/9/2020

36

Joining : Derived Operator

JOINING ①

Cartesian Product Followed by a Selection

EQUI JOIN

THETA JOIN / JOIN

NATURAL JOIN

SELF JOIN

OUTER JOIN

@ SKG

9/9/2020

37

Self Joining : Derived Operator

Find the manager's name of employee having employee id e3
emp

<u>eno</u>	ename	mgr_eno
e1	A	e5
e2	B	e4
e3	D	e2
e4	A	e1
e5	C	e3

?

@ SKG

9/9/2020

38

Self Joining : Derived Operator

emp

<u>eno</u>	ename	mgr_eno
e1	A	e5
e2	B	e4
e3	D	e2
e4	A	e1
e5	C	e3

X

emp

<u>eno</u>	ename	mgr_eno
e1	A	e5
e2	B	e4
e3	D	e2
e4	A	e1
e5	C	e3

@ SKG

9/9/2020

39

emp × emp

mgr_eno=eno(emp×emp)

mgr_eno=eno^p=e3(emp×emp)

ename(mgr_eno=eno(emp×emp))

eno	ename	mgr_eno	eno	ename	mgr_eno
e1	A	e5	e1	A	e5
e1	A	e5	e2	B	e4
e1	A	e5	e3	D	e2
e1	A	e5	e4	A	e1
e1	A	e5	e5	C	e3
e2	B	e4	e1	A	e5
e2	B	e4	e2	B	e4
e2	B	e4	e3	D	e2
e2	B	e4	e4	A	e1
e2	B	e4	e5	C	e3
e3	D	e2	e1	A	e5
e3	D	e2	e2	B	e4
e3	D	e2	e3	D	e2
e3	D	e2	e4	A	e1
e3	D	e2	e5	C	e3
e4	A	e1	e1	A	e5
e4	A	e1	e2	B	e4
e4	A	e1	e3	D	e2
e4	A	e1	e4	A	e1
e4	A	e1	e5	C	e3
e5	C	e3	e1	A	e5
e5	C	e3	e2	B	e4
e5	C	e3	e3	D	e2
e5	C	e3	e4	A	e1
e5	C	e3	e5	C	e3

2020/09/09 14:40:10

Self Joining : Derived Operator

<u>eno</u>	ename	mgr_eno
e1	A	e5
e2	B	e4
e3	D	e2
e4	A	e1
e5	C	e3

×

<u>eno</u>	ename	mgr_eno
e1	A	e5
e2	B	e4
e3	D	e2
e4	A	e1
e5	C	e3

```
SELECT ename FROM emp, emp WHERE emp. mgr_eno =emp. eno AND
emp. eno=e3;
```

@ SKG

9/9/2020

41

Self Joining

Option1

<u>eno</u>	ename	mgr_eno
e1	A	e5
e2	B	e4
e3	D	e2
e4	A	e1
e5	C	e3

<u>eno</u>	ename	mgr_eno
e1	A	e5
e2	B	e4
e3	D	e2
e4	A	e1
e5	C	e3

```
SELECT emp1. ename FROM emp, emp1 WHERE emp.
mgr_eno=emp1.eno AND emp. eno=e3;
```

@ SKG

9/9/2020

42

Self Joining

Option2

RENAME

emp

<u>eno</u>	ename	mgr_eno
e1	A	e5
e2	B	e4
e3	D	e2
e4	A	e1
e5	C	e3

@ SKG

9/9/2020

43

RELATIONAL ALGEBRA

❖ Relational Algebra

❖ Unary Operator

➤ Select ()

➤ Project ()

➤ **Rename ()**

❖ Binary Operator

➤ Cartesian Product (×)

➤ Union (U)

➤ Set Difference (—)

Extended Relational-Algebra-Operations

The operators take one or more relations as inputs
and give a new relation as a result

@ SKG

9/9/2020

44

Rename Operator

- ❖ Refer a relation by more than one name.

$$X(E);$$

returns the expression E under the name X

```
SELECT * FROM emp employee;
```

- ❖ Refer the relation and the attribute of the relation by more than one name

$$X(A_1, A_2, \dots, A_n)(E);$$

```
SELECT eno eid, ename name, mgr_eno supervisor_id FROM emp employee;
```

@ SKG

9/9/2020

45

Self Joining

Option2

RENAME

emp

<u>eno</u>	ename	mgr_eno
e1	A	e5
e2	B	e4
e3	D	e3
e4	A	e1
e5	C	e2

```
SELECT emp1. ename FROM emp, emp1 WHERE emp.
mgr_eno=emp1.eno AND emp. eno=e3;
```


```
SELECT b. ename FROM emp a, emp b WHERE a. mgr_eno=b.eno AND
a. eno=e3;
```

@ SKG

9/9/2020

46

RELATIONAL ALGEBRA



Extended Relational-Algebra-Operations

The operators take one or more relations as inputs
and give a new relation as a result

@ SKG

9/9/2020

47

Union Operation – Example

□ Relations r, s :

A	B
r	1
r	2
s	1

r

A	B
r	2
s	3

s

$r \cup s$:

A	B
r	1
r	2
s	1
s	3

```

SELECT * FROM r
union
SELECT * FROM s;
  
```

@ SKG

9/9/2020

48

Union Operation

□ Notation: $r \cup s$

□ Defined as:

$$r \cup s = \{t \mid t \in r \text{ or } t \in s\}$$

□ For $r \cup s$ to be valid

1. r, s must have the **same number of attributes**
2. The **attribute domains** must be **compatible** (e.g., 2nd column of r deals with the same type of values as does the 2nd column of s)
3. The **sequence of the attributes in the both the relation must be same**

$$n(r \cup s) = n(r) + n(s) - n(r \cap s)$$

@ SKG

9/9/2020

49

RELATIONAL ALGEBRA

❖ Relational Algebra

❖ Unary Operator

- Select (σ)
- Project (π)
- Rename (ρ)

❖ Binary Operator

- Cartesian Product (\times)
- Union (\cup)
- **Set Difference ($-$)**

Extended Relational-Algebra-Operations

The operators take one or more relations as inputs
and give a new relation as a result

@ SKG

9/9/2020

50

Set Difference Operation – Example

□ Relations r, s :

A	B
r	1
r	2
s	1

r

A	B
r	2
s	3

s

$r - s$:

A	B
r	1
s	1

@ SKG

9/9/2020

51

Set Difference Operation

□ Notation $r - s$

□ Defined as:

$$r - s = \{t \mid t \in r \text{ and } t \notin s\}$$

□ Set differences must be taken between *compatible* relations

- ❖ r and s must have the *same arity*
- ❖ attribute domains of r and s must be *compatible*
- ❖ sequence of the attributes in the both the relation must be same


$$n(r-s) = n(r) - n(r \cap s)$$

@ SKG

9/9/2020

52

RELATIONAL ALGEBRA



Extended Relational-Algebra-Operations

The operators take one or more relations as inputs and give a new relation as a result

@ SKG

9/9/2020

53

Set Intersection Operation – Example

□ Relations r, s :

A	B
r	1
r	2
s	1

r

A	B
r	2
s	3

s

$r \cap s$:

A	B
r	2

@ SKG

9/9/2020

54

Set Difference Operation

□ Notation $r - s$

□ Defined as:

$$r - s = \{t \mid t \in r \text{ and } t \notin s\}$$

□ Set intersection must be taken between *compatible* relations.

- ❖ r and s must have the *same arity*
- ❖ attribute domains of r and s must be compatible
- ❖ sequence of the attributes in the both the relation must be same

@ SKG

9/9/2020

55

Extended Relational-Algebra-Operations

Assignment Operation

❖ The assignment operation (\leftarrow) provides a convenient way to express complex queries.

- Write query as a sequential program consisting of
 - a series of assignments
 - followed by an expression whose value is displayed as a result of the query
- Assignment must always be made to a temporary relation variable

❖ Example:

ename($\text{sal} > 700$ (emp));

temp₁ \leftarrow $\text{sal} > 700$ (emp); result \leftarrow ename (temp₁);

@ SKG

9/9/2020

56

Generalized Projection

- Extends the projection operation by allowing arithmetic functions to be used in the projection list.

$$\Pi_{F_1, F_2, \dots, F_n}(E)$$

- E is any relational-algebra expression
- Each of F_1, F_2, \dots, F_n are arithmetic expressions involving constants and attributes in the schema of E .
- Given relation *credit-info(customer-name, limit, credit-balance)*, find how much more each person can spend:

$$\Pi_{customer-name, limit - credit-balance}(credit-info);$$

@ SKG

9/9/2020

57

Aggregate Functions and Operations

- ❖ **Aggregation function** takes a collection of values and returns a single value as a result

avg: average value
min: minimum value
max: maximum value
sum: sum of values
count: number of values

- ❖ **Aggregate operation** in relational algebra

$$G_1, G_2, \dots, G_n \mathcal{G} F_1(A_1), F_2(A_2), \dots, F_n(A_n)(E)$$

- E is any relational-algebra expression
- G_1, G_2, \dots, G_n is a list of attributes on which to group (can be empty)
- Each F_i is an aggregate function
- Each A_i is an attribute name

@ SKG

9/9/2020

58

Aggregate Operation – Example

❖ Relation r:

A	B	C
r	r	7
r	s	7
s	s	3
s	s	10

SELECT SUM(c) FROM r;

$g_{\text{sum}(c)}(r);$

sum(c)
27

@ SKG

9/9/2020

59

Aggregate Operation – Example

❖ Relation *account*:

<i>branch-name</i>	<i>account-number</i>	<i>balance</i>
Perryridge	A-102	400
Perryridge	A-201	900
Brighton	A-217	750
Brighton	A-215	750
Redwood	A-222	700

❖ Query: Find the minimum account balance from the account relation

$g_{\text{min}(\text{balance})}(\text{account});$

min(balance)

400

SELECT MIN (balance) FROM account;

@ SKG

9/9/2020

60

Aggregate Operation – Example

❖ Relation *account*:

<i>branch-name</i>	<i>account-number</i>	<i>balance</i>
Perryridge	A-102	400
Perryridge	A-201	900
Brighton	A-217	750
Brighton	A-215	750
Redwood	A-222	700

❖ Query: Find the number of account holder present in the bank

$\rho_{count(branch-name)}(account);$

<i>count (branch-name)</i>
5

SELECT COUNT (branch-name) FROM account;

$\rho_{distinct-count(branch-name)}(account);$

<i>distinct count (branch-name)</i>
4

SELECT COUNT(DISTINCT branch-name) FROM account;

@ SKG

9/9/2020

61

Aggregate Operation – Example

❖ Relation *account* grouped by *branch-name*:

<i>branch-name</i>	<i>account-number</i>	<i>balance</i>
Perryridge	A-102	400
Perryridge	A-201	900
Brighton	A-217	750
Brighton	A-215	750
Redwood	A-222	700

❖ Query: Find the total balance of each branch

$\rho_{sum(balance)}(account);$

↓

branch-name $\rho_{sum(balance)}(account);$

<i>branch-name</i>	<i>sum (balance)</i>
Perryridge	1300
Brighton	1500
Redwood	700

SELECT branch-name, SUM (balance) FROM account GROUP BY branch-name;

@ SKG

9/9/2020

62

62

Aggregate Functions: Renaming

- ❑ Result of aggregation does not have a name
 - Can use rename operation to give it a name
 - For convenience, we permit renaming as part of aggregate operation

branch-name **g** *sum(balance) as sum-balance(account);*

@ SKG

9/9/2020

63

Outer Join

- ❖ An extension of the join operation that avoids loss of information
- ❖ Computes the join and then adds tuples from one relation that do not match tuples in the other relation to the result of the join.
- ❖ Uses *null* values:
 - *null* signifies that the value is unknown or does not exist
 - All comparisons involving *null* are (roughly speaking) **false** by definition.
 - Will study precise meaning of comparisons with nulls later

@ SKG

9/9/2020

64

Outer Join – Example

❖ Relation *loan*

<i>loan-number</i>	<i>branch-name</i>	<i>amount</i>
L-170	Downtown	3000
L-230	Redwood	4000
L-260	Perryridge	1700

❖ Relation *borrower*

<i>customer-name</i>	<i>loan-number</i>
Jones	L-170
Smith	L-230
Hayes	L-155

❖ **Natural Join** $loan \bowtie Borrower$

<i>loan-number</i>	<i>branch-name</i>	<i>amount</i>	<i>customer-name</i>
L-170	Downtown	3000	Jones
L-230	Redwood	4000	Smith

@ SKG

9/9/2020

65

Outer Join – Example

❖ Relation *loan*

<i>loan-number</i>	<i>branch-name</i>	<i>amount</i>
L-170	Downtown	3000
L-230	Redwood	4000
L-260	Perryridge	1700

❖ Relation *borrower*

<i>customer-name</i>	<i>loan-number</i>
Jones	L-170
Smith	L-230
Hayes	L-155

■ **Left Outer Join** $loan \leftarrow \bowtie Borrower$

<i>loan-number</i>	<i>branch-name</i>	<i>amount</i>	<i>customer-name</i>
L-170	Downtown	3000	Jones
L-230	Redwood	4000	Smith
L-260	Perryridge	1700	<i>null</i>

@ SKG

9/9/2020

66

Outer Join – Example

❖ Relation *loan*

<i>loan-number</i>	<i>branch-name</i>	<i>amount</i>
L-170	Downtown	3000
L-230	Redwood	4000
L-260	Perryridge	1700

❖ Relation *borrower*

<i>customer-name</i>	<i>loan-number</i>
Jones	L-170
Smith	L-230
Hayes	L-155

□ Right Outer Join *loan* ⋈_R *Borrower*

<i>loan-number</i>	<i>branch-name</i>	<i>amount</i>	<i>customer-name</i>
L-170	Downtown	3000	Jones
L-230	Redwood	4000	Smith
L-155	<i>null</i>	<i>null</i>	Hayes

@ SKG

9/9/2020

67

Outer Join – Example

❖ Relation *loan*

<i>loan-number</i>	<i>branch-name</i>	<i>amount</i>
L-170	Downtown	3000
L-230	Redwood	4000
L-260	Perryridge	1700

❖ Relation *borrower*

<i>customer-name</i>	<i>loan-number</i>
Jones	L-170
Smith	L-230
Hayes	L-155

■ Full Outer Join *loan* ⋈_F *borrower*

<i>loan-number</i>	<i>branch-name</i>	<i>amount</i>	<i>customer-name</i>
L-170	Downtown	3000	Jones
L-230	Redwood	4000	Smith
L-260	Perryridge	1700	<i>null</i>
L-155	<i>null</i>	<i>null</i>	Hayes

@ SKG

9/9/2020

68

Modification of the Database

- ❑ The content of the database may be modified using the following operations:
 - ❖ Deletion
 - ❖ Insertion
 - ❖ Updating
- ❑ All these operations are expressed using the assignment operator

@ SKG

9/9/2020

69

Deletion

- ❖ A delete request is expressed similarly to a query, except instead of displaying tuples to the user, the **selected tuples are removed from the database**
- ❖ **Can delete only whole tuples**; cannot delete values on only particular attributes
- ❖ A deletion is expressed in relational algebra by:

$$r \leftarrow r - E$$

where r is a relation and E is a relational algebra query

@ SKG

9/9/2020

70

Deletion Examples

- ❖ Relation *loan*

<i>loan-number</i>	<i>branch-name</i>	<i>amount</i>
L-170	Downtown	3000
L-230	Redwood	4000
L-260	Perryridge	1700

- Delete all loan records in the Perryridge branch

$loan \leftarrow loan - \sigma_{branch-name = "Perryridge"}(loan);$

DELETE FROM loan WHERE branch-name='Perryridge';

- Delete all loan records with amount in the range of 0 to 50

@ SKG

9/9/2020

71

Deletion Examples

- Let us consider two relational schema:

- ❖ branch(branch-name, branch-city, assets);
- ❖ account (account-number, branch-name, balance);

- Delete all accounts at branches located in Needham.

@ SKG

9/9/2020

72

Insertion

- To insert data into a relation, we either:
 - specify a tuple to be inserted
 - write a query whose result is a set of tuples to be inserted
- in relational algebra, an insertion is expressed by:

$$r \leftarrow r \cup E$$

where r is a relation and E is a relational algebra expression.


- The insertion of a single tuple is expressed by letting E be a constant relation containing one tuple.

@ SKG

9/9/2020

73

- Let us consider this schema diagram



@ SKG

9/9/2020

74

Insertion Examples

❖ `account (account-number, branch-name, balance);`

- Insert information in the database specifying that Smith has \$1200 in account A-973 at the Perryridge branch

$$account \leftarrow account \cup \{(A-973, \text{"Perryridge"}, 1200)\};$$

- Insert information in the database specifying that Smith has deposited \$500 in account A-973 at the Perryridge branch

@ SKG

9/9/2020

75

Insertion Examples

- Suppose, a new savings account has been created with the loan number serve as the account number for the new savings account. Provide as a gift for all loan customers in the Perryridge branch, a \$200, in their new savings account

@ SKG

9/9/2020

76

Updating

- A mechanism to change a value in a tuple without changing *all* values in the tuple
- Use the generalized projection operator to do this task

$$r \leftarrow \Pi_{F_1, F_2, \dots, F_i}(r)$$

- Each F_i is either
 - the i th attribute of r , if the i th attribute is not updated, or,
 - if the attribute is to be updated F_i is an expression, involving only constants and the attributes of r , which gives the new value for the attribute

© SKG

9/9/2020

77

Update Examples

- ❖ account (account-number, branch-name, balance);
- Make interest payments by increasing all balances by 5 percent.

$$account \leftarrow \Pi_{account-number, branch-name, balance * 1.05}(account)$$
- Pay all accounts with balances over \$10,000, 6 percent interest and pay all others 5 percent

© SKG

9/9/2020

78

Thank You

?

@ SKG 9/9/2020 79