

Cucumber JVM explanation



give me the deep and detailed explanation of Cucumber JVM in java so that i can able to understand it well and do not have any type of doubt in this.

so give me the deep and detailed explanation

Alright Piyush 👍

I'll explain **Cucumber JVM** from **absolute basics** → **internal working** → **real project structure** → **execution flow** → **best practices**, in **simple language**, step by step, so that **no confusion remains**.



What is Cucumber JVM (in Java)?

Cucumber JVM is a **testing tool** that allows you to write **automated tests in plain English**, and then **connect those English steps to Java code**.

It follows **BDD (Behavior Driven Development)**.

👉 Instead of writing only Java test code, you write:

- **Human-readable test scenarios**
- Then **Java code executes those steps**

♦ Why the name "Cucumber JVM"?

- **Cucumber** → the BDD testing framework
- **JVM** → it runs on the **Java Virtual Machine**

So:

Cucumber JVM = Cucumber framework + Java ecosystem

It integrates smoothly with:

- JUnit
- TestNG
- Selenium, REST Assured, Spring Boot, etc.



Problem Cucumber Solves



Traditional Testing Problem

```
java
```

```
@Test
public void testLogin() {
    // lots of code
}
```

- ✗ Only developers understand
- ✗ Business people / QA / Product owners cannot read it

✓ Cucumber Solution

```
gherkin
```

```
Scenario: Successful login
  Given user is on login page
  When user enters valid credentials
  Then user should be redirected to dashboard
```

- ✓ Readable by **non-technical people**
- ✓ Executable by **Java code**

Core Concepts of Cucumber JVM

Let's break everything down.

1 BDD (Behavior Driven Development)

BDD focuses on:

- **Behavior of the application**
- **From user's perspective**
- Written in **simple language**

BDD answers:

- What should the system do?
- Under what conditions?
- What should be the result?

2 Gherkin Language (VERY IMPORTANT)

Cucumber scenarios are written using **Gherkin**.

👉 Gherkin is **not Java**, it's a **plain-text language**.

Keywords:

- Feature
- Scenario
- Given
- When
- Then
- And
- But

Example Feature File

```
gherkin

Feature: Login functionality

  Scenario: Successful login
    Given user is on login page
    When user enters valid username and password
    Then user should see dashboard
```

📌 This file is usually saved as:

```
pgsql

login.feature
```

Meaning of Keywords (Important!)

Keyword	Meaning
Feature	High-level functionality
Scenario	A test case
Given	Precondition
When	Action
Then	Expected outcome
And/But	Additional steps

3 Feature File (WHAT to test)

- Written in **.feature** files
- Contains **business-readable tests**
- No Java code here

📁 Location:

```
swift
```

```
src/test/resources/features/
```

4 Step Definitions (HOW to test)

This is where **Java code lives**.

Each Gherkin step is **mapped to a Java method**.

Example Step Definition

```
java

@Given("user is on login page")
public void user_is_on_login_page() {
    System.out.println("Opening login page");
}
```

Annotation Mapping:

Gherkin Step	Java Annotation
Given	@Given
When	@When
Then	@Then

IMPORTANT RULE

Each Gherkin step must match exactly **ONE** Java method

If not:

- ✗ Undefined step error
- ✗ Ambiguous step error

5 How Cucumber Executes Tests (INTERNAL FLOW)

This is **very important for clarity**.

Execution Flow:

```
mathematica

Feature File
  ↓
Scenario
```

```

↓
Steps (Given/When/Then)
↓
Matching Java Step Definition
↓
Java Code Executes
↓
Pass / Fail

```

Step Matching Logic

```

gherkin

Given user is on login page

```

Cucumber looks for:

```

java

@Given("user is on login page")

```

✓ Exact match → executed

✗ No match → test fails

6 Regular Expressions & Parameters

Steps can take **dynamic values**.

Feature File:

```

gherkin

When user enters username "admin" and password "1234"

```

Step Definition:

```

java

@When("user enters username {string} and password {string}")
public void enterCredentials(String username, String password) {
    System.out.println(username + " " + password);
}

```

✗ {string}, {int}, {double} → placeholders

7 Cucumber Test Runner (HOW tests start)

Cucumber needs a **runner class**.

This class:

- Tells where feature files are
- Tells where step definitions are
- Configures reports

Example Runner Class (JUnit)

```
java

@RunWith(Cucumber.class)
@CucumberOptions(
    features = "src/test/resources/features",
    glue = "stepdefinitions",
    plugin = {"pretty", "html:target/report.html"},
    monochrome = true
)
public class TestRunner {
}
```

 Uses:

- JUnit
- `@RunWith(Cucumber.class)`



8 Glue Code (VERY IMPORTANT)

```
java

glue = "stepdefinitions"
```

Means:

“Cucumber, search for step definition classes in this package.”

-  Wrong glue → steps not found
-  Correct glue → steps executed

9 Hooks (Before & After)

Hooks are used to:

- Setup before scenario
- Cleanup after scenario

Example Hooks

```
java

@Before
public void setup() {
```

```

    System.out.println("Before scenario");
}

@After
public void teardown() {
    System.out.println("After scenario");
}

```

Use cases:

- Open browser
- Close browser
- DB setup
- Cleanup test data

10 Tags (Selective Execution)

You can **tag scenarios**.

```

gherkin

@smoke
Scenario: Successful login

```

Run only tagged tests:

```

java

@cucumberOptions(tags = "@smoke")

```

- ✓ Smoke testing
- ✓ Regression testing
- ✓ Fast execution

1 1 Reporting in Cucumber

Cucumber provides:

- HTML reports
- JSON reports
- Extent reports (with plugins)

```

java

plugin = {
    "pretty",
    "html:target/cucumber-report.html",
    "json:target/cucumber.json"
}

```

1 2 Integration with Selenium (Real Use Case)

Cucumber itself:

✗ Does NOT automate browser

It **controls tools like Selenium**.

Flow:

css

Gherkin → Step Definition → Selenium **Code** → Browser

Example

java

```
@Given("user opens browser")
public void openBrowser() {
    WebDriver driver = new ChromeDriver();
    driver.get("https://example.com");
}
```

1 3 Folder Structure (BEST PRACTICE)

bash

```
src/test/java
├── runner
│   └── TestRunner.java
├── stepdefinitions
│   └── LoginSteps.java
├── hooks
│   └── Hooks.java
src/test/resources
├── features
│   └── login.feature
```

1 4 Common Errors (IMPORTANT)

✗ Undefined Step

- Step exists in feature
- No Java mapping

✗ Ambiguous Step

- Same step mapped to **multiple methods**

✗ Glue Issue

- Wrong package path

1 5 Why Cucumber is Widely Used

- ✓ Business-readable tests
- ✓ Collaboration between Dev + QA + Business
- ✓ Reusable steps
- ✓ Clean separation of WHAT vs HOW
- ✓ Excellent for automation frameworks

Final Mental Model (Remember This)

CSS

```
Feature File → WHAT to test
Step Defs   → HOW to test (Java)
Runner      → HOW to run
Hooks       → Setup & Cleanup
Tags        → Control execution
```

If you want, next I can:

- ♦ Explain **Cucumber + Selenium framework design**
- ♦ Explain **Cucumber with Spring Boot**
- ♦ Explain **Real interview questions on Cucumber**
- ♦ Build a **complete end-to-end project structure**

Just tell me 👍