

- What are Graphs?
- Graph Representation
- BFS
- DFS
- Find cycle in detected graph

Mock Interview : 60 mins


- a) Intro and Flow Explanation by Mentor (3-5 min)
- b) Q and A (25 mins)
- c) Feedback and Discussion (5 mins)

PS → Sat 27 Jan

4-5 Ques

Introduction to Graphs

Graph - A collection of nodes connected to each other using edges.



Tree is a Directed Graph

- ① Tree is a hierarchical data structure
- ② N nodes $\rightarrow N-1$ Edges

Instagram


$A \rightarrow B$
Directed

Facebook


$A - B$
undirected

Classification of Graphs

I




Directed Graph




Undirected Graph

II




Weighted graph




Unweighted Graph

III




Undirected Cyclic Graph




Undirected Acyclic Graph

Directed Cyclic Graph



Directed Acyclic Graph



Cyclic Graph -

Start from a node and you reach same node back without repeating an edge

Indegree of a Node


No. of edges which are coming into that node

$$\text{indegree}(C) = 2$$

Outdegree \rightarrow outgoing edges


$$\text{Outdegree}(C) = 0$$

$$\text{Outdegree}(A) = 2$$



Simple Graph -

A graph in which there is no self loop and no multiple edges b/w any 2 nodes



What Input is given for Graph?

(Given an undirected graph with N nodes & M edges)


1st line $\rightarrow N \quad M$

M lines
where
each line
contains
 $u \quad v$

\downarrow
edge b/w
 u and v

N	M
6	6
2	3 ✓
4	5 ✓
0	5 ✓
4	1 ✓
1	3 ✓
3	4 ✓


6 \rightarrow 1 to 6
OR
0 to 5



Storing a Graph

Input

5	7	
1	4	✓
2	0	✓
3	2	✓
4	3	✓
2	4	✓
3	0	✓
1	2	✓



2 \rightarrow 4

1 \leftrightarrow 4

Representation 1 (Adj Matrix)

int mat[N][N] → mat[5][5]

cols → neighbours

rows
↓
Actual nodes

	0	1	2	3	4
0	0	0	1	1	0
1	0	0	1	0	1
2	1	1	0	1	1
3	1	0	1	0	1
4	0	1	1	1	0

u → v

0
↓
No edge

1
↓
edge

Given N and E, mat[N][N]

// u, v	unweighted	weighted
Undirected	$\text{mat}[u][v] = 1$ $\text{mat}[v][u] = 1$	$\text{mat}[u][v] = w$ $\text{mat}[v][u] = w$
Directed	$\text{mat}[u][v] = 1$ u → v	$\text{mat}[u][v] = w$

// u v w

6 7
4 v w |
|
|
|
|
|
|

5 Nodes → 100 cells
5 edges → 10 cells

N^2 cells

Space Wastage

Storing a Graph

S (List)

↓
N+E

Input

5 6

→ 1 4


→ 2 0

→ 3 2


→ 4 3

→ 2 4

→ 3 0



list<int> ar[5]



list<int> ar[N]

Representation 2 (Adjacency List)

// u v w

// u, v

	unweighted	weighted
undirected	ar[u].add(v) ar[v].add(u)	ar[u].add(<v, w>) ar[v].add(<u, w>)
Directed	ar[u].add(v)	ar[u].add(<v, w>)

u → v

10:22

list<pair> ar[N]

↓

pair<int, int>
nbr wt

Breadth first search \rightarrow Level order Traversal

- Given an undirected graph, source node and dest node. Check if node can be visited from source node.

Input

6 7

1 2

1 4


2 4

2 3

3 5

5 0

4 5



Src 1
Dest 0

True

Queue

1 2 4 3 5 0

0	$\rightarrow \langle 5 \rangle$
1	$\rightarrow \langle 2, 4 \rangle$
2	$\rightarrow \langle 1, 4, 3 \rangle$
3	$\rightarrow \langle 2, 5 \rangle$
4	$\rightarrow \langle 1, 2, 5 \rangle$
5	$\rightarrow \langle \overset{0}{3}, \overset{1}{0}, \overset{2}{4} \rangle$

1	2	4	3	5	0
--------------	--------------	--------------	--------------	--------------	--------------

0	1	2	3	4	5
✓	✓	✓	✓	✓	✓
T	T	T	T	T	T

visited[n]

↓
6

If visited[dest] = T

path exists

else

path does not exist

bool bfs (list<int> adj[], int s, int d) {

bool vis[N] = {F}

// Nodes N
↓
[0 - N-1]

Queue<int> q

q.enqueue(s)

vis[s] = true

TC: O(V+E)

SC: O(V)

visited[]
queue[]

while (q.size() > 0) {

int u = q.front()

q.dequeue()

print(u)

adj[u]

// put u's unvisited neighbours

for (i = 0 ; i < adj[u].size() ; i++) {

nbr = adj[u][i]

if (vis[nbr] == false) {

q.enqueue(nbr)

vis[nbr] = true

return vis[d]

V → Nodes

E → Edges


for (i=1 ; i ≤ n ; i++) <

for (j=1 ; j ≤ n ; j++) <


$$\begin{aligned} \text{Total} &= \text{Outer} + \text{Inner} \\ &= N + N^2 \end{aligned}$$

i	j	Total
1	1 → n	n
2		n
...		...
n		n
<hr/>		<hr/>
n		n ²

DFS (Depth First Search)



unvisited
4, 11, 6



DFS (src, adj, vis)

```
void DFS (int u, list<int> adj[], int vis[])
```

```
    vis[u] = true
```

```
    for (i = 0; i < adj[u].size(); i++) {
```

```
        nbr = adj[u][i]
```

```
        if (vis[nbr] == false)
```


```
            dfs(nbr, adj, vis)
```

```
    return vis[u]
```


$V + E /$
 TC: $O(N + E)$
 SC: $O(N)$

List $\rightarrow N + E / V + E$

3. Check if a simple directed graph has a cycle



True



False

If a visited node is encountered again \rightarrow cycle X

A node can be a part of multiple paths

1 → 2 → 5

1 → 2 → 4

1 → 2
↓
3 → 4

If a node is encountered again in current path → cycle

1 → 2 → 5 → 6 → 2 YES

list<int> path

bool cycle(int u, list<int> adj[], int vis[])

vis[u] = true

path.add(u)

for (i = 0 ; i < adj[u].size() ; i++)

nbr = adj[u][i]

if (path.contains(nbr)) return true



else if (!vis[nbr])

if (cycle(nbr, adj, vis) == true) return true

path.delete(u)

return false

↑ T



4 nodes	min edges	max edges
	3	6



①	②	③	...	②
N Nodes	N-1	N-2	N-3	N-4 ... 0

Min edges	Max edges
N-1	$\frac{N-1(N)}{2}$

★ How to store path in Cycle Finding Ques?


path.contains(nbr) \rightarrow path[nbr] == T

① path \rightarrow use a hashset (finding any node in hashset $\rightarrow O(1)$)

② bool path[N]

Whatever comes in the path, mark T
On returning from a node, mark F

N = 5 [0 \rightarrow 4]



path [5]

0	1	2	3	4
F	F	F	F	F
	T	T		