

Step 1 Creating Stack

Creating new stackset in my parent account.

Permissions

Choose an IAM role to explicitly define how CloudFormation will manage your target accounts. [Learn more](#)

Permission model

☒ **Service-managed permissions**

StackSets automatically configures the permissions required to deploy to target accounts managed by AWS Organizations. With this option, you can enable automatic deployment to accounts in your organization.

☐ **Self-service permissions**

You create the IAM roles required to deploy to target accounts. If you don't choose a role, CloudFormation uses permissions based on your user credentials.

Prerequisite - Prepare template

You can also import a template by scanning your existing resources in the [laC generator](#).

Prepare template

Every stack is based on a template. A template is a JSON or YAML file that contains configuration information about the AWS resources you want to include in the stack.

☒ **Template is ready**

☐ **Use a sample template**

Specify template

This [GitHub repository](#) contains sample CloudFormation templates that can help you get started on new infrastructure projects. [Learn more](#)

Template source

Selecting a template generates an Amazon S3 URL where it will be stored. A template is a JSON or YAML file that describes your stack's resources and properties.

☐ **Amazon S3 URL**

☒ **Upload a template file**

Upload a template file

newStackSet.yml

JSON or YAML formatted file

S3 URL: Will be generated when template file is uploaded

[Cancel](#) [Next](#)

```
File Edit Selection View Go Run Terminal Help
StackSet.yml 2 x
> sahal-imran > cloudForm > newStackSet.yml > YAML > {} Outputs > {} BucketName > abc Description
Validate and Deploy | Visualize with Infrastructure Composer
AWSTemplateFormatVersion: "2010-09-09"
Description: StackSet Template to create S3 bucket

Resources:
  StackSetBucket:
    Type: AWS::S3::Bucket
    Properties:
      BucketName: !Sub stackset-demo-bucket-${AWS::AccountId}-${AWS::Region}

Outputs:
  BucketName:
    Value: !Ref StackSetBucket
    Description: Name of created S3 bucket
```

StackSet template

ou-9stp-v9k371sy

Add another OU

You can add 49 more OUs

Account filter type - optional

Set deployment targets to specific individual accounts within OUs instead of targeting entire OUs.

Select account filter type

Auto-deployment options

Automatic deployment

With automatic deployment enabled, if an account is added to an OU, StackSets automatically deploys additional stack instances to this account. If an account is added to an OU, StackSets automatically deploys additional stack instances to this account. If an account is added to an OU, StackSets automatically deploys additional stack instances to this account.

Activated

Deactivated

Account removal behavior

When an account is removed from a target OU, should stack instances in the account be deleted or retained?

Delete stacks

Retain stacks

Stack set dependencies - optional

Stack sets with dependencies will automatically deploy stack instances only after all dependent stack sets complete their deployments in the same account. You can set up to 10 dependencies for each stack set and up to 100 dependencies in the account.

If a dependency stack set does not exist or has automatic deployments disabled, it will be ignored. However, any transitive dependencies will be ignored.

No stack set ARNs specified.

Add another stack set ARN

You can add 10 more stack set ARNs.

Specify Regions

Choose the Regions in which you want to deploy stacks. Stacks are deployed in these Regions in the order that you specify. Note that you can only specify one region per account. Note that you can only specify one region per account. Note that you can only specify one region per account. [Learn more](#)

US East (Ohio)
us-east-2

^

v

Remove

Adding OU id and region.

Operations

Search operations

	Operation ID	Type	Status
	efeec603-b79a-ab92-2182-cca988dd3e9d	CREATE	ⓘ RUNNING

Operations

Search operations

	Operation ID	Type	Status
	efeec603-b79a-ab92-2182-cca988dd3e9d	CREATE	✓ SUCCEEDED

Buckets

General purpose buckets

All AWS Regions

Directory buckets

General purpose buckets (1) [Info](#)

Buckets are containers for data stored in S3.

< 1 > [Settings](#)

	Name	AWS Region	Creation date
☐	stackset-demo-bucket-683745388462-us-east-2	US East (Ohio) us-east-2	March 1, 2026, 14:52:03 (UTC+05:30)

Step 2

AWS OU ID

ou-9stp-v9k371sy

[Add another OU](#)

You can add 49 more OUs

Account filter type - optional

Set deployment targets to specific individual accounts within OUs instead of targeting entire OUs.

Specify Regions

Choose the Regions in which you want to deploy stacks. Stacks are deployed in these Regions in the order that you specify. Note that during stack set operations, administrator arn and stacks involved. [Learn more](#)

US East (Ohio)
us-east-2

⬆ ⬇

[Remove](#)

[Add all regions](#)

[Remove all regions](#)

Deployment options

Maximum concurrent accounts - optional

Number of accounts per Region to deploy stacks to simultaneously. A higher number speeds up the operation.

Number

1

Failure tolerance - optional

Number of accounts per Region where stack deployments can fail before the operation stops. If the operation is stopped in one Region, it will not continue in other Regions. A lower number is safer.

Number

0

Retain stacks

When you retain stacks, CloudFormation leaves stacks in individual accounts and Regions intact. Stacks are disassociated from the stack set, but the stack and its resources are saved.

☒ Retain stacks

Deleting the stackset but when retain stacks is enabled the stack will be deleted but the resources will not be.

Operations

	Operation ID	Type	Status
☐	2bb1a461-88d1-6016-779d-8378e9d982d2	DELETE	SUCCEEDED

Stack set deleted successfully.

Step 3 :

Select trusted entity [Info](#)

Trusted entity type

☒ **AWS service**
Allow AWS services like EC2, Lambda, or others to perform actions in this account.

☐ **AWS account**
Allow entities in other AWS accounts belonging to you or a 3rd party to perform actions in this account.

☐ **Web identity**
Allows users federated by the specified external web identity provider to assume this role to perform actions in this account.

☐ **SAML 2.0 federation**
Allow users federated with SAML 2.0 from a corporate directory to perform actions in this account.

☐ **Custom trust policy**
Create a custom trust policy to enable others to perform actions in this account.

Use case

Allow an AWS service like EC2, Lambda, or others to perform actions in this account.

Service or use case

CloudFormation

Choose a use case for the specified service.

Use case

☒ **CloudFormation**
Allows CloudFormation to create and manage AWS stacks and resources on your behalf.

Name, review, and create

Role details

Role name
Enter a meaningful name to identify this role.

AWSCloudFormationStackSetExecutionRole

Maximum 64 characters. Use alphanumeric and '+', '@', '-' characters.

Description
Add a short explanation for this role.

Maximum 1000 characters. Use letters (A-Z and a-z), numbers (0-9), tabs, new lines, or any of the following characters: '_', '+', '@', '-', '/', '[', ']', '#', '\$', '%', '^', '*', '~', ' '.

Step 1: Select trusted entities

Trust policy

```

1  {
2    "Version": "2012-10-17",
3    "Statement": [
4      {
5        "Effect": "Allow",
6        "Action": "sts:AssumeRole",

```

Creating IAM role and admin Role in child account.

Step 4:

Choose a template

Specify stack set details

Configure stack set options

Deployment options

Review

Choose a template

Permissions

Choose an IAM role to explicitly define how CloudFormation will manage your target accounts. [Learn more](#)

Permission model

☐ **Service-managed permissions**
StackSets automatically configures the permissions required to deploy to target accounts managed by AWS Organizations. With this option, you can enable automatic deployment to accounts in your organization.

☒ **Self-service permissions**
You create the IAM roles required to deploy to target accounts. If you use permissions based on your user credentials.

IAM admin role ARN - optional
Choose the IAM role for CloudFormation to use for all operations performed on the stack.

IAM role name: AWSCloudFormationStackSetAdministrationRole [Remove](#) [Create new](#)

StackSets will use this role for administering your individual accounts.

IAM execution role name

AWSCloudFormationStackSetExecutionRole

IAM execution role name can include letters (A-Z and a-z), numbers (0-9), and select special characters (+, @, -) characters. Maximum length is 64 characters.

Prerequisite - Prepare template

Creating stackset using self service permission.

Choose a template

Step 2

Specify stack set details

Step 3

Configure stack set options

Step 4

Deployment options

Step 5

Review

Set deployment options

Add stacks to stack set

☐ Deploy new stacks

☒ Import stacks to stack set

Stacks to import

Stack source

☒ Stack ID

☐ Stack IDs Url

Stack ID

arn:aws:cloudformation:us-east-2:683745388462:stack/StackSet-asgQuestionOrg-3a824dbf-97

Remove

Add another stack ID

You can add 9 more IDs

Deployment options

Maximum concurrent accounts - optional

Number of accounts per Region to deploy stacks to simultaneously. A higher number speeds up the operation.

Number

1

Failure tolerance - optional

Number of accounts per Region where stack deployments can fail before the operation stops. If the operation is stopped in one Region, it will not continue in other Regions. A lower number is safer.

Number

0

Region concurrency

Choose to process Regions sequentially or in parallel.

☒ Sequential

Deploy stacks into one Region at a time, following the specified Region order.

☐ Parallel

Deploy stacks simultaneously across all specified Regions.

Concurrency mode

Specifies how concurrency level behaves during operation execution.

☒ Strict failure tolerance

Passing stackid from previous created stack in child account.

Operations		
Search operations		
	Operation ID	Type
☐	70dcfa39-0111-450d-e652-434d86d94126	IMPORT
	STATUS RUNNING	

Stack is running

Operations		
Search operations		
	Operation ID	Type
☐	70dcfa39-0111-450d-e652-434d86d94126	IMPORT
	STATUS SUCCEEDED	

Operation successful.