

King Crimson Testing Order:

1. FILL in this order until OTC 115 ~ OTC112 (Needs to be toleranced) and approximate calculated time (to be calculated)
 - a. NHV-301A/B (Manual->Open)
 - b. NHV-319(Manual->Close)
 - c. NRG-311(Manual->Open)
 - d. NRG-302 (Manual->Open)
 - e. OHV101 (Manual->Open)
 - f. OPV110 (Close) (starts once operator reaches safe distance)
 - g. Operator Back button pressed
 - h. OPV106 (Close) (no delay)
 - i. OPV109 (Open) ~ 2sec delay
 - j. OPV104 (Open) ~2sec delay
 - k. OPV104 (Close) Operator input
 - l. Finish Fill button pressed
 - m. OPV109 (Close) ~2 sec delay
 - n. OPV106 (Open) ~2 sec delay
2. PRE-TEST in this order
 - a. OPV118 (Close) condition/delay tbd
 - b. FPV203 (Close) condition/delay tbd
 - c. NMV305 (Open) condition/delay tbd
 - d. OPV121 (Throttle) based off NPT303~FPT202
 - i. Side note: maybe extra PT
 - ii. DONOT FULLY OPEN SLIGHTLY OPEN
 - e. OPV110 (Open)
 - i. NOTE: HAZOPS OPV-120 and OPV-110 proximity
 - f. OPV110 (Close) either by camera or by OTC-124
 - g. FPV-204 (Open) ~1sec delay
 - h. Operator ends the state with large LAUNCH button**
3. TEST starts as soon as PRE-TEST is done
 - a. Ignitor (activate) no delay
 - b. FPV-205 (Open) delay ~ 1 sec
 - c. OPV-120 (Open) x ms delay
 - d. OPV-120 (Close) delay TEST_TIME
 - e. FPV-204 (Close) x ms delay
 - f. NPV-315 (Open) x ms delay
 - g. NMV-305 (Close)

- h. OPV-118 (Open) delay .25 sec
 - i. FPV-203 (Open)
 - j. FPV-205 (Close) delay 10 sec
 - k. **Operator ends state with button**
- 4. POST-TEST as soon as TEST is done
 - a. TBD