

Process Automation

Butterfly Valve



Butterfly Valve is a compact, quarter-turn rotary valve used to quickly isolate or regulate the flow of the fluids. Central disc in the valve which rotates on a shaft to block or open the passage resembling the wings of a butterfly.

Features

- Durable and Low Maintenance**
 Durable CF8/CF8M construction ensures high strength and required relatively low maintenance.
- Sealings**
 Highly reliable & tight seals able to close securely in extreme temperatures and harsh media.
- Blow out Proof Stem & Ball Design**
 Valve stem is designed with an internal ridge, preventing it from during extreme pressure buildup in the system.
- Minimal Pressure Drop**
 Enhanced design provides zero flow restriction and prevents from pressure loss.
- Versatile Design**
 Butterfly valve with variable design end connections can enable various applications.
- High Temperature & Pressure**
 Industrial butterfly valve are constructed to withstand extreme temperature and pressure environments.
- Easy Actuation & Integration**
 Pneumatically actuated offer rapid opening & closing times, makes them ideal for high-speed automation systems.



Pneumatic Actuated Type



Bare Shaft Type



Electric Actuated Type



Manual Type

Technical Specification

Design Type	: Centric / Double Offset
End Connection Type	: Wafer End / Lugged End
Design Standard	: API 609 / IS 13095 / EN 593
Port Size Ranges	: 1-1/2", 2", 2-1/2", 3", 4", 5", 6" & 8"
Nominal Diameter DN (mm)	: 40, 50, 65, 80, 100, 125, 150 & 200
Pressure Rating Class	: PN10 / PN16
Working Temperature	: -20°C to 180°C (PTFE) & -20°C to 150°C (EPDM)
Medium	: Water, Oil, Gas, Steam, Chemicals, Heavy sludge, etc.,
Actuation Type	: Manual Lever Operated / Pneumatic Actuator / Motorized
Material of Construction	: Body : CF8 / CF8M / Cast Iron / Aluminium Die Cast Disc : CF8 / CF8M Seat : PTFE / EPDM / NBR Shaft : SS304 / SS316

Applications



Water & Waste water
Treatment plants



Food & Beverage
Processing



Chemical
Industries



Oil & Gas
production



Power Generation
Units



Pharmaceutical
and Bio-tech



Pulp & Paper
Manufacturing

Product Ordering No

BF		1		1		69			1		1			P		1			
Model		Body Design		End Connection Type		Port Size		DN		Pressure Rating		Body Material		Disc		Seat & Seals		Actuation Type	
BF	Butterfly Valve	1	Centric	1	Wafer End	69	1 1/2"	40	1	PN10	1	CF8	CF8	P	PTFE	1	Manual		
		2	Double Offset	2	Lugged End	76	2"	50	2	PN16	2	CF8	CF8M	E	EPDM	2	Pneumatic – Single Acting		
						77	2 1/2"	65			3	CI	CF8	N	NBR	3	Pneumatic – Double Acting		
						78	3"	80			4	CI	CF8M			4	Electrical – ON / OFF*		
						80	4"	100			5	AL	CF8						
						82	5"	125			6	AL	CF8M						
						84	6"	150											
						86	8"	200											
																	Maximum Output Torque (Nm)*		
																	30, 50, 80, 100, 150, 200, 400, 600, 800, 1000 & 2000		

Maximum Output Torque (Nm)*

30, 50, 80, 100, 150, 200, 400, 600, 800, 1000 & 2000

Note : EPDM and NBR – Based on request.

JANATICS INDUSTRIAL AUTOMATION PRIVATE LIMITED

Registered office: 409/2, SIDCO Industrial Estate Malumichampatti P.O., Coimbatore - 641050, Tamil Nadu

Works: Sf. No.271/1A, Kodangipalayam, Kinathukadavu, Coimbatore - 642109, Tamil Nadu India

+ 91 422 2655077

info@janaticsia.com

www.janatics.com

