

Process Automation

Pulse Valve

Pulse Valve is dust collection systems to clean filters by releasing the short, high pressure burst compressed air into filter bags to dislodge the accumulated dust, maintaining airflow and efficiency.



Features

- **Durable Valve Body**
Durable body material aluminium alloy can provide high strength & reduce their size-weight ratio.
- **Variable Valve Design**
Different valve design and mounting connection can offer multiple working applications.
- **High Peak Pressure**
Designed for to maximize the shock force can improve the cleaning depth.
- **High Flow Efficiency and Low Pressure Loss**
Optimized internal geometries allows high air volumes to release powerful cleaning pulse.
- **Integral Pilot Control**
Direct pilot attachment simplifies automation while reducing costs and maintenance.
- **Springless Diaphragm Design**
Springless diaphragm design use high-strength elastomer material ensure extended service life.
- **Fast Actuation**
Pneumatically actuated offer rapid opening & closing times, makes them ideal for high-speed automation systems.

Technical Specification

Product Range	: Right Angle Type, Submerged Type, Dresser Nut Type, Straight through Type & Flange Type
Type	: 2/2 Normally Closed
Port Sizes	: G3/4", G1", G1-1/2", G2", G2-1/2", G3" & G4"
External Pilot Port Sizes	: G1/8", G1/4"
Response Time	: 50 ms
Operating Pressure (bar)	: 3 – 8
External Pilot Pressure (bar)	: 2 – 6
Flow Factor (m3/hr)	: 17 – 270
Ambient Temperature	: -5°C to +80 °C (NBR), -30°C to +130°C (EPDM) and -10°C to +150°C (FKM)
Type of Coil Protection	: IP65
Operating Medium	: Compressed air
Material of Construction	: Housing : Aluminum alloy die-casting Seal : NBR, EPDM & FKM (VITON)

Product Ordering No

PV		01		05		N		A	
		Body Type		Port Size		Seal		Voltage	
01	Right Angle - Solenoid	05	G3/4"	N	NBR	A	220 V AC		
02	Submerged - Solenoid	06	G1"	E	EPDM	W	24 V DC		
03	Dresser Nut - Solenoid	08	G1 1/2"	V	FKM				
04	Straight Through - Solenoid	10	G2"						
05	Flanged - Solenoid	12	G2 1/2"						
06	Right Angle - Pilot	14	G3"						
07	Submerged - Pilot	18	G4"						
08	Dresser Nut - Pilot								
09	Straight Through - Pilot								
10	Flanged - Pilot								



Right Angle Type



Submerged Type



Dresser Nut Type



Straight Through Type



Flange Type

