CF-Initialize

This is the quickest and easiest way to complete the your payments. It allows for a seamless payment process without the need for additional queries such as card front side checks, BIN queries, installment queries, 3D Secure checks, or card information saving integrations. By following this process, you can ensure a smooth and efficient integration with iyzico, providing a streamlined payment experience for your customers.

By incorporating these features, you can provide a seamless payment experience for your customers, with real-time feedback on the success or failure of their transactions.

CF Initialize Request

`POST` `https://api.iyzipay.com/payment/iyzipos/checkoutform/initialize/auth/ecom`

Request Body

Name	Type	Description
price*	Decimal	Total amount of basket. The sum of basket items' amount must be equal to the price of basket
contactName(BillingAddress)*	String	Contact name of billing address
registrationAddress(Buyer)*	String	Registration address of buyer
ip(Buyer)*	String	IP of buyer
email(Buyer)*	String	Email of buyer
country(Buyer)*	String	Country of buyer
city(Buyer)*	String	City of buyer
identityNumber(Buyer)*	String	Identity number of buyer. TCKN for Turkish merchants, passport number for foreign merchants
surname(Buyer)*	String	Surname of buyer
name(Buyer)*	String	Name of buyer
id(Buyer)*	String	ID of buyer.
currency*	String	Currency (default: TRY). Alternatively, you can set USD, EUR, GBP and IRR
paidPrice*	Decimal	Final amount (including installment fee) that will be charged to customer's card
zipCode(BillingAddress)	String	Zip code of billing address
zipCode(ShippingAddress)	String	Zip code of shipping address

zipCode(Buyer)	String	Zip code of buyer
category1(BasketItems)	String	Category 1 for item in the basket
name(BasketItems)	String	Name of the item in the basket
price(BasketItems)	Decimal	Price value for each item. Must be greater than zero
itemType(BasketItems)	String	Item Type. Valid values are PHYSICAL,VIRTUAL
id(BasketItems)	String	Basket Item ID
address(ShippingAddress)*	String	Address details of shipping address. If one of the itemType in basket is PHYSICAL, then this parameter will be mandatory
country(ShippingAddress)*	String	Country name of shipping address. If one of the itemType in basket is PHYSICAL, then this parameter will be mandatory
city(ShippingAddress)*	String	City name of shipping address. If one of the itemType in basket is PHYSICAL, then this parameter will be mandatory
contactName(ShippingAddress)*	String	Contact name of shipping address. If one of the itemType in basket is PHYSICAL, then this parameter will be mandatory
address(BillingAddress)*	String	Address details of billing address
		Country name of billing

country(BillingAddress)*	String	address
city(BillingAddress)*	String	City name of billing address
paymentGroup	String	Payment group (default: PRODUCT). Valid values are PRODUCT, LISTING, SUBSCRIPTION
paymentChannel	String	Payment channel. Valid values are WEB, MOBILE, MOBILE_WEB, MOBILE_IOS, MOBILE_ANDROID, MOBILE_WINDOWS, MOBILE_TABLET, MOBILE_PHONE
basketId	String	Merchant's basket ID
conversationId	String	Conversation ID to match request and response
locale	String	Language (default: tr)
lastLoginDate(Buyer)	String	Last login date of buyer. Format should be “2015-09-17 23:45:06”
registrationDate(Buyer)	String	Registration date of buyer. Format should be “2015-09-17 23:45:06”
subMerchantKey(BasketItem)	String	Submerchant ID value. Mandatory value for marketplace solution
subMerchantPrice(BasketItem)	Decimal	Payout amount to subMerchant of each item. Must be greater than zero. Mandatory value for marketplace solution
gsmNumber(Buyer)	String	GSM number of buyer
category2(BasketItems)	String	Category 2 for item in the

category2(BasketItems)	String	basket
paymentSource	String	Payment source. Valid values are SHOPIFY, MAGENTO, PRESTASHOP, WOOCOMMERCE, OPENCART
callbackUrl	String	Merchant callback URL for payment result notification
enabledInstallments	Integer	Enabled installments value. it should be set as 1

200: OK

CF Initialize Response

Parameters to be returned from the service are as follows:

Input Name	Type	Description
checkoutFormContent	String	HTML code of checkout form
paymentPageUrl	String	URL of iyzico payment page
token	String	Unique value created for each checkout form request. This token is used to access the payment result
tokenExpireTime	Integer	Expiration time of the token
status	String	Service response result (success / failure)
errorCode	String	Error code if service response status is failure
errorMessage	String	Error message if service response status is failure
errorGroup	String	Error group if service response status is failure
locale	String	Language (default: tr)
systemTime	Integer	Response system timestamp value
conversationId	String	If set, conversation ID to match request and response

Previous
CF Implementation

Next
CF-Retrieve

Last updated 4 months ago

iyzico DOCS

Company

About

Career

Social

Youtube

Community

Github

Medium

Integration

Brand Guide

Solution Partners

Open Source

Contact

Contact Us

Support Center