Init 3DS

Init 3DS API is responsible for processing the customer's card payments with 3DS.

As like Its ancestor NON-3DS;

- It supports transactions made with TROY, MASTERCARD, VISA, and AMEX branded cards.
- For cards participating in installment programs such as BONUS, WORLD, MAXIMUM, AXESS, CARDFINANS, PARAF, and ADVANTAGE, the service allows options for 2, 3, 6, 9, and 12 installments.
- Successful transactions are displayed in green, while failed transactions are displayed in red on the panel.
- The merchant can utilize the conversationId and basketId parameters as order numbers on their side.

By incorporating these features, you can provide a seamless payment experience for your customers, with real-time feedback on the success or failure of their transactions.

Init 3DS Request

`POST` `https://api.iyzipay.com/payment/3dsecure/initialize`

Request Body

Name	Type	Description
price*	Decimal	Total amount of basket. The sum of basket items' amount must be equal to the price of basket
contactName(BillingAddress)*	String	Contact name of billing address
registrationAddress(Buyer)*	String	Registration address of buyer
ip(Buyer)*	String	IP of buyer
email(Buyer)*	String	Email of buyer
country(Buyer)*	String	Country of buyer
city(Buyer)*	String	City of buyer
identityNumber(Buyer)*	String	Identity number of buyer. TCKN for Turkish merchants, passport number for foreign merchants
surname(Buyer)*	String	Surname of buyer
name(Buyer)*	String	Name of buyer
id(Buyer)*	String	ID of buyer.
cardHolderName*	String	Name of the card owner
cvc*	String	4 (AMEX) or 3 (VISA, MC, TROY) digits card verification code
expireMonth*	String	Expiration month of the card (2 digits)
expireYear*	String	Expiration year of the card
cardNumber*	String	15 (AMEX) or 16 (VISA, MC) digits card number

installment*	Integer	Installment value. For single installment payments it should be 1 (valid values: 1, 2, 3, 6, 9, 12)
currency*	String	Currency (default: TRY). Alternatively, you can set USD, EUR, GBP and IRR
paidPrice*	Decimal	Final amount (including installment fee) that will be charged to customer's card
zipCode(BillingAddress)	String	Zip code of billing address
zipCode(ShippingAddress)	String	Zip code of shipping address
zipCode(Buyer)	String	Zip code of buyer
category1(BasketItems)	String	Category 1 for item in the basket
name(BasketItems)	String	Name of the item in the basket
price(BasketItems)	Decimal	Price value for each item. Must be greater than zero
itemType(BasketItems)	String	Item Type. Valid values are PHYSICAL,VIRTUAL
id(BasketItems)	String	Basket Item ID
address(ShippingAddress)*	String	Address details of shipping address. If one of the itemType in basket is PHYSICAL, then this parameter will be mandatory
country(ShippingAddress)*	String	Country name of shipping address. If one of the itemType in basket is PHYSICAL, then this

		parameter will be mandatory
city(ShippingAddress)*	String	City name of shipping address. If one of the itemType in basket is PHYSICAL, then this parameter will be mandatory
contactName(ShippingAddress)*	String	Contact name of shipping address. If one of the itemType in basket is PHYSICAL, then this parameter will be mandatory
address(BillingAddress)*	String	Address details of billing address
country(BillingAddress)*	String	Country name of billing address
city(BillingAddress)*	String	City name of billing address
paymentGroup	String	Payment group (default: PRODUCT). Valid values are PRODUCT, LISTING, SUBSCRIPTION
paymentChannel	String	Payment channel. Valid values are WEB, MOBILE, MOBILE_WEB, MOBILE_IOS, MOBILE_ANDROID, MOBILE_WINDOWS, MOBILE_TABLET, MOBILE_PHONE
basketId	String	Merchant's basket ID
conversationId	String	Conversation ID to match request and response
locale	String	Language (default: tr)
		Last login date of buyer.

lastLoginDate(Buyer)	String	Format should be “2015-09-17 23:45:06”
registrationDate(Buyer)	String	Registration date of buyer. Format should be “2015-09-17 23:45:06”
cardAlias	Integer	If registerCard value is 1 cardAlias can send within request.
registerCard	Integer	Parameter that shows card details will store or not. Default value is 0 and valid values are 0 or 1
subMerchantKey(BasketItem)	String	Submerchant ID value. Mandatory value for marketplace solution
subMerchantPrice(BasketItem)	Decimal	Payout amount to subMerchant of each item. Must be greater than zero. Mandatory value for marketplace solution
gsmNumber(Buyer)	String	GSM number of buyer
category2(BasketItems)	String	Category 2 for item in the basket
paymentSource	String	Payment source. Valid values are SHOPIFY, MAGENTO, PRESTASHOP, WOOCOMMERCE, OPENCART
callbackUrl*	String	Redirection URL

Init 3DS Response

Output Name	Type	Description
status	String	Service response result (success / failure)
errorCode	String	Error code if service response status is failure
errorMessage	String	Error message if service response status is failure
errorGroup	String	Error group if service response status is failure
locale	String	Language (default: tr)
systemTime	Long	Response system timestamp value
conversationId	String	If set, conversation ID to match request and response
threeDSHtmlContent	String	3D verification screen in HTML format

Lastly analyzing following headlines, you can effectively handle and respond to the outcome of the payment inquiry, ensuring a smooth and reliable payment process for your customers.

- The `status` parameter provides information about the status of the transaction. `success` indicates that the transaction has been successfully completed and the payment has been processed. `failure` indicates that the transaction has failed, and an error message related to the failure reason is provided.
- The `paymentStatus` parameter is null for this service.
- The `paymentId` and `paymentTransactionId` values should be stored for future reference and tracking.
- In the event of a failed transaction (`failure` status), the `errorCode`, `errorMessage`, and `errorGroup` parameters will be returned with corresponding values, providing details about the error.

Previous
3DS Implementation

Next
Auth 3DS

Last updated 4 months ago