

Please read [the new rule regarding the restriction on the use of AI tools](#).

## C. Robin Hood in Town

 time limit per test: 2 seconds  
 memory limit per test: 256 megabytes

*In Sherwood, we judge a man  
not by his wealth, but by his  
merit.*

*Look around, the rich are getting richer, and the poor are getting poorer. We need to take from the rich and give to the poor. We need Robin Hood!*

There are  $n$  people living in the town. Just now, the wealth of the  $i$ -th person was  $a_i$  gold. But guess what? The richest person has found an extra pot of gold!

More formally, find an  $a_j = \max(a_1, a_2, \dots, a_n)$ , change  $a_j$  to  $a_j + x$ , where  $x$  is a non-negative integer number of gold found in the pot. If there are multiple maxima, it can be any one of them.

A person is unhappy if their wealth is **strictly less than half** of the average wealth\*.

If **strictly more than half** of the total population  $n$  are unhappy, Robin Hood will appear by popular demand.

Determine the minimum value of  $x$  for Robin Hood to appear, or output  $-1$  if it is impossible.

\*The average wealth is defined as the total wealth divided by the total population  $n$ , that is,  $\frac{\sum a_i}{n}$ , the result is a real number.

### Input

The first line of input contains one integer  $t$  ( $1 \leq t \leq 10^4$ ) — the number of test cases.

The first line of each test case contains an integer  $n$  ( $1 \leq n \leq 2 \cdot 10^5$ ) — the total population.

The second line of each test case contains  $n$  integers  $a_1, a_2, \dots, a_n$  ( $1 \leq a_i \leq 10^6$ ) — the wealth of each person.

It is guaranteed that the sum of  $n$  across all test cases does not exceed  $2 \cdot 10^5$ .

### Output

For each test case, output one integer — the minimum number of gold that the richest person must find for Robin Hood to appear. If it is impossible, output  $-1$  instead.

### Example

input

Copy

```
6
1
2
2
2 19
3
1 3 20
4
1 2 3 4
5
1 2 3 4 5
6
```

### Codeforces Round 974 (Div. 3)

Finished

Practice



### → Virtual participation

Virtual contest is a way to take part in past contest, as close as possible to participation on time. It is supported only ICPC mode for virtual contests. If you've seen these problems, a virtual contest is not for you - solve these problems in the archive. If you just want to solve some problem from a contest, a virtual contest is not for you - solve this problem in the archive. Never use someone else's code, read the tutorials or communicate with other person during a virtual contest.

Start virtual contest

### → Submit?

Language: GNU G++20 13.2 (64 bit, wir)

Choose file: Choose File No file chosen

Submit

### → Problem tags

math math

No tag edit access

```
1 2 1 1 1 25
```

**output**[Copy](#)

```
-1  
-1  
0  
15  
16  
0
```

**Note**

In the first test case, it is impossible for a single person to be unhappy.

In the second test case, there is always 1 happy person (the richest).

In the third test case, no additional gold are required, so the answer is 0.

In the fourth test case, after adding 15 gold, the average wealth becomes  $\frac{25}{4}$ , and half of this average is  $\frac{25}{8}$ , resulting in 3 people being unhappy.

In the fifth test case, after adding 16 gold, the average wealth becomes  $\frac{31}{5}$ , resulting in 3 people being unhappy.

---

[Codeforces](#) (c) Copyright 2010-2024 Mike Mirzayanov  
The only programming contests Web 2.0 platform  
Server time: Sep/21/2024 23:06:20<sup>UTC+6</sup> (13).  
Desktop version, switch to [mobile version](#).  
[Privacy Policy](#)

Supported by

**ITMO**