

Clients / service_to_service_id

Client - service_to_service_id

Save Client

Clone Client

Delete Client

Settings

Name

Basics

Authentication/Logout

Token

Consent Screen

Device Flow

Name

ClientId

service_to_service_id

Client Name

ServiceToService

Save Client

Clone Client

Delete Client

Client - service_to_service_id

Save Client

Clone Client

Delete Client

Settings

Name

Basics

Authentication/Logout

Token

Consent Screen

Device Flow

Basics

Enabled

Description

service to service

Protocol Type

OpenID Connect ▾

Require Client Secret

Require Request Object

Require Pkce

Allow Plain Text Pkce

Allow Offline Access

Allow Access Token Via Browser

Allowed Scopes

Enter 2 and more characters

Selected item/s:

service_to_service

Suggested items:

roles

profile

openid

IdentityServerApild_api

email

Console_api

address

more +

Redirect Uris

Enter 2 and more characters

Selected item/s:

sample-windows-client://callback

Allowed Grant Types

Enter 2 and more characters

Selected item/s:

client_credentials

Suggested items:

urn:ietf:params:oauth:grant-type:device_code

password

implicit

hybrid

delegation

more +

Client Secrets

Manage Client Secrets

Properties

Manage Client Properties

Save Client

Clone Client

Delete Client

Clients / service_to_service_id

Client - service_to_service_id

Save Client

Clone Client

Delete Client

Settings

Name

Basics

Authentication/Logout

Token

Consent Screen

Device Flow

Authentication/Logout

Front Channel Logout Uri

Front Channel Logout Session Required

Back Channel Logout Uri

Back Channel Logout Session Required

Enable Local Login

Post Logout Redirect Uris

Enter 2 and more characters

No item/s selected

Identity Provider Restrictions

Enter 2 and more characters

No item/s selected

User Sso Lifetime

Save Client

Clone Client

Delete Client

Clients / service_to_service_id

Client - service_to_service_id

Save Client

Clone Client

Delete Client

Settings

Name

Basics

Authentication/Logout

Token

Consent Screen

Device Flow

Token

Identity Token Lifetime

300

Allowed Identity Token Signing Algorithms

Enter 2 and more characters

No item/s selected

Suggested items:

PS384

PS512

RS256

RS384

RS512

more +

Access Token Lifetime

3600

Access Token Type

Jwt

Authorization Code Lifetime

300

Absolute Refresh Token Lifetime

2592000

Sliding Refresh Token Lifetime

1296000

Refresh Token Usage

OneTimeOnly

Refresh Token Expiration

Absolute

Allowed Cors Origins

Enter 2 and more characters

No item/s selected

Update Access Token Claims On Refresh

Include Jwt Id

Always Send Client Claims

Always Include User Claims In IdToken

Client Claims Prefix

client_

Pair Wise Subject Salt

Claims

Manage Client Claims

Save Client

Clone Client

Delete Client

Clients / service_to_service_id

Client - service_to_service_id

Save Client

Clone Client

Delete Client

Settings

Name

Basics

Authentication/Logout

Token

Consent Screen

Device Flow

Consent Screen

Require Consent

Allow Remember Consent

Client Uri

Logo Uri

Save Client

Clone Client

Delete Client

Clients / service_to_service_id

Client - service_to_service_id

Save Client

Clone Client

Delete Client

Settings

Name

Basics

Authentication/Logout

Token

Consent Screen

Device Flow

Device Flow

User Code Type ▾

Device Code Lifetime ▾

300

Save Client

Clone Client

Delete Client

Api Scope

Api Scope

Name ▾

service_to_service

Display Name ▾

service_to_service

Description ▾

Enabled ▾

Show In Discovery Document ▾

Required ▾

Emphasize ▾

Properties ▾

Manage Api Scope Properties

User Claims ▾

Enter 2 and more characters

No item/s selected

Suggested items:

zoneinfowebsiteupdated_atprofilepreferred_usernamemore +

Save Api Scope