API 文件

目錄

1. 列出可用模型
2. 對話補全（支援串流與工具呼叫）
3. 產生文字向量

AI Gateway 提供與 OpenAI 相容的端點，讓既有的 OpenAI SDK 或工具只改網址與金鑰就能透過 MaiAgent 呼叫模型。這組端點只在 `/api/v1/` 底下、路徑不以 `/` 結尾；認證用 `Authorization: Bearer`（金鑰就是 MaiAgent 的 API Key，但 Gateway 端點只認 `Bearer` 前綴，`Api-Key` 前綴會回 `401`）。AI Gateway 需由 MaiAgent 為組織開通，金鑰可呼叫的模型由管理者在 API Key 管理設定。完整說明見技術手冊 AI Gateway：OpenAI 相容 API 串接。

列出可用模型

GET `/api/v1/models`

回傳這把金鑰可呼叫的模型識別碼與定價，識別碼的規則見技術手冊模型識別。

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/models"

  -H "Authorization: Bearer YOUR_API_KEY"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Bearer YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/models", config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/models"
headers = {
    "Authorization": "Bearer YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/models", [
        'headers' => [
            'Authorization' => 'Bearer YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
{
  "object"?: string (enum: list) // 非必填
  "data"?: [ // 非必填
    {
```

```
      "id"?: string // 呼叫時填入 model 的 id (非必填)
      "object"?: string (enum: model) // 非必填
      "created"?: integer // Unix 秒 (非必填)
      "owned_by"?: string // 非必填
      "name"?: string // 非必填
      "icon"?: string // 非必填
      "type"?: string (enum: language) // 非必填
      "tags"?: [ // 非必填
        string (enum: tool-use, multimodal, reasoning, prompt-caching,
streaming)
      ]
      "pricing"?: { // 平台模型為 input／output／unit=credits_per_1k_tokens
／currency；組織自有模型為 traffic_fee_percent／unit=percent_of_total_tokens
／currency (非必填)
      {
        "input"?: string // 非必填
        "output"?: string // 非必填
        "traffic_fee_percent"?: string // 非必填
        "unit"?: string // 非必填
        "currency"?: string // 非必填
      }
      }
      "providers"?: [ // 非必填
        {
          "slug"?: string // 非必填
          "name"?: string // 非必填
          "icon_url"?: string // 非必填
          "color"?: string // 非必填
        }
      ]
      "context_window"?: integer // 模型有設定時才出現 (非必填)
      "max_tokens"?: integer // 模型有設定時才出現 (非必填)
    }
  ]
}
```

回應範例值

```
{
  "object": "list",
  "data": [
    {
      "id": "回應字串",
      "object": "model",
```

```
      "created": 456,
      "owned_by": "回應字串",
      "name": "回應字串",
      "icon": "回應字串",
      "type": "language",
      "tags": [
        "tool-use"
      ],
      "pricing": {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "name": "回應範例名稱",
        "description": "回應範例描述"
      },
      "providers": [
        {
          "slug": "回應字串",
          "name": "回應字串",
          "icon_url": "回應字串",
          "color": "回應字串"
        }
      ],
      "context_window": 456,
      "max_tokens": 456
    }
  ]
}
```


對話補全（支援串流與工具呼叫）

POST `/api/v1/chat/completions`

請求與回應格式同 OpenAI chat/completions（model、messages、stream、tools 等），平台 schema 未列欄位；參數與範例見技術手冊對話補全參數與最小範例。

請求內容

請求參數

欄位	類型	必填	說明
model	string	是	模型 id，取自 GET /v1/models
messages	array[object]	是	
stream	boolean	否	true 時以 text/event-stream 回傳
stream_options	object	否	
stream_options.include_usage	boolean	否	
temperature	number	否	
max_tokens	integer	否	
top_p	number	否	
stop	object	否	
n	integer	否	
provider	object	否	
provider.order	array[string]	否	指定後端供應商；目前只採用第一個
tools	array[object]	否	
tool_choice	object	否	
parallel_tool_calls	boolean	否	
response_format	object	否	type 為 text、json_object 或 json_schema；json_schema 時需帶 json_schema 物件
reasoning_effort	string (enum: none, minimal, low, medium, high, xhigh, max)	否	

請求結構範例

```
{
  "model": string // 模型 id，取自 GET /v1/models
  "messages": [
    {
      "role": string (enum: system, user, assistant, tool)
      "content": object // 文字，或 OpenAI 多模態 content parts 陣列
      "tool_calls"?: [ // 非必填
        {
          "id"?: string // 非必填
          "type"?: string (enum: function) // 非必填
          "function"?: { // 非必填
          {
            "name"?: string // 非必填
            "arguments"?: string // JSON 字串 (非必填)
          }
          }
        }
      ]
      "tool_call_id"?: string // 非必填
      "name"?: string // 非必填
    }
  ]
  "stream"?: boolean // true 時以 text/event-stream 回傳 (非必填)
  "stream_options"?: { // 非必填
  {
    "include_usage"?: boolean // 非必填
  }
  }
  "temperature"?: number // 非必填
  "max_tokens"?: integer // 非必填
  "top_p"?: number // 非必填
  "stop"?: // 可能有不同的類型 (非必填)
  string // 非必填
  "n"?: integer // 非必填
  "provider"?: { // 非必填
  {
    "order"?: [ // 指定後端供應商；目前只採用第一個 (非必填)
      string
    ]
  }
  }
  "tools"?: [ // 非必填
    {
      "type": string (enum: function)
```

```
      "function": {
      {
        "name": string
        "description"?: string // 非必填
        "parameters"?: object // JSON Schema (非必填)
        "strict"?: boolean // 非必填
      }
      }
    }
  ]
  "tool_choice"?: // 可能有不同的類型 (非必填)
  string (enum: auto, none, required) // 非必填
  "parallel_tool_calls"?: boolean // 非必填
  "response_format"?: object // type 為 text、json_object 或 json_schema；
json_schema 時需帶 json_schema 物件 (非必填)
  "reasoning_effort"?: string (enum: none, minimal, low, medium, high,
xhigh, max) // 非必填
}
```

請求範例值

```
{
  "model": "openai/gpt-5.4-mini",
  "messages": [
    {
      "role": "user",
      "content": "你好，請用一句話介紹你自己。"
    }
  ]
}
```

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X POST "https://api.maiagent.ai/api/v1/chat/completions"

  -H "Authorization: Bearer YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "model": "openai/gpt-5.4-mini",
    "messages": [
      {
        "role": "user",
        "content": "你好，請用一句話介紹你自己。"
      }
    ]
  }'

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Bearer YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// 請求內容 (payload)
const data = {
    "model": "openai/gpt-5.4-mini",
    "messages": [
      {
        "role": "user",
        "content": "你好，請用一句話介紹你自己。"
      }
    ]
  };

axios.post("https://api.maiagent.ai/api/v1/chat/completions", data,
config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```python
import requests

url = "https://api.maiagent.ai/api/v1/chat/completions"
headers = {
    "Authorization": "Bearer YOUR_API_KEY",
    "Content-Type": "application/json"
}

# 請求內容 (payload)
data = {
    "model": "openai/gpt-5.4-mini",
    "messages": [
        {
            "role": "user",
            "content": "你好，請用一句話介紹你自己。"
        }
    ]
}

response = requests.post(url, json=data, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>post("https://api.maiagent.ai/api/v1/chat/completions", [
        'headers' => [
            'Authorization' => 'Bearer YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'model' => 'openai/gpt-5.4-mini',
            'messages' => [
                [
                    'role' => 'user',
                    'content' => '你好，請用一句話介紹你自己。'
                ]
            ]
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼：200 - stream=false 時回 chat.completion 物件；stream=true 時回 SSE

回應結構範例

```
{
  "id"?: string // 非必填
  "object"?: string (enum: chat.completion) // 非必填
  "created"?: integer // Unix 秒 (非必填)
  "model"?: string // 非必填
  "choices"?: [ // 非必填
    {
      "index"?: integer // 非必填
      "message"?: { // 非必填
      {
        "role"?: string (enum: assistant) // 非必填
        "content"?: string // 非必填
        "tool_calls"?: [ // 非必填
          {
            "id"?: string // 非必填
            "type"?: string (enum: function) // 非必填
            "function"?: { // 非必填
            {
              "name"?: string // 非必填
              "arguments"?: string // JSON 字串 (非必填)
            }
            }
          }
        ]
      }
      }
      "finish_reason"?: string // 非必填
    }
  ]
  "usage"?: { // 非必填
  {
    "prompt_tokens"?: integer // 非必填
    "completion_tokens"?: integer // 非必填
    "total_tokens"?: integer // 非必填
  }
  }
}
```

回應範例值

```
{
  "id": "回應字串",
  "object": "chat.completion",
  "created": 456,
  "model": "回應字串",
  "choices": [
    {
      "index": 456,
      "message": {
        "id": "msg_550e8400e29b41d4a716446655440000",
        "content": "這是回應的訊息內容",
        "timestamp": "2025-01-01T00:00:00.000Z"
      },
      "finish_reason": "回應字串"
    }
  ],
  "usage": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應範例名稱",
    "description": "回應範例描述"
  }
}
```

產生文字向量

POST `/api/v1/embeddings`

請求與回應格式同 OpenAI embeddings（model、input），範例見技術手冊向量化。

請求內容

請求參數

欄位	類型	必填	說明
model	string	是	

欄位	類型	必填	說明
input	object	是	非空字串或非空字串陣列
encoding_format	string (enum: float, base64)	否	
dimensions	integer	否	
user	string	否	

請求結構範例

```
{
  "model": string
  "input": // 可能有不同的類型
  string // 非空字串或非空字串陣列
  "encoding_format"?: string (enum: float, base64) // 非必填
  "dimensions"?: integer // 非必填
  "user"?: string // 非必填
}
```

請求範例值

```
{
  "model": "text-embedding-3-large",
  "input": "今天天氣很好"
}
```

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X POST "https://api.maiagent.ai/api/v1/embeddings"

  -H "Authorization: Bearer YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "model": "text-embedding-3-large",
    "input": "今天天氣很好"
  }'

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Bearer YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// 請求內容 (payload)
const data = {
    "model": "text-embedding-3-large",
    "input": "今天天氣很好"
  };

axios.post("https://api.maiagent.ai/api/v1/embeddings", data,
config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/embeddings"
headers = {
    "Authorization": "Bearer YOUR_API_KEY",
    "Content-Type": "application/json"
}

# 請求內容 (payload)
data = {
    "model": "text-embedding-3-large",
    "input": "今天天氣很好"
}

response = requests.post(url, json=data, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>post("https://api.maiagent.ai/api/v1/embeddings", [
        'headers' => [
            'Authorization' => 'Bearer YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'model' => 'text-embedding-3-large',
            'input' => '今天天氣很好'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
{
  "object"?: string (enum: list) // 非必填
  "data"?: [ // 非必填
    {
      "object"?: string (enum: embedding) // 非必填
      "index"?: integer // 非必填
      "embedding"?: // 可能有不同的類型 (非必填)
      array[number] // encoding_format=float 為數字陣列；base64 為 little-endian float32 的 base64 字串 (非必填)
    }
  ]
  "model"?: string // 非必填
  "usage"?: { // 非必填
  {
    "prompt_tokens"?: integer // 非必填
    "total_tokens"?: integer // 非必填
  }
  }
}
```

回應範例值

```
{
  "object": "list",
  "data": [
    {
      "object": "embedding",
      "index": 456,
      "embedding": [
        456
      ]
    }
  ],
  "model": "回應字串",
  "usage": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應範例名稱",
    "description": "回應範例描述"
  }
}
```

呼叫 API 示例 (Shell)

目錄

1. 建立新 AI 助理
2. 列出 Embedding Model
3. 列出 Reranker Model
4. 列出大型語言模型
5. 取得 AI 助理列表
6. 取得特定 AI 助理
7. 更新 AI 助理
8. 部分更新 AI 助理
9. 刪除 AI 助理
10. 複製 AI 助理
11. 啟用或停用評估功能
12. 列出組織的 Hook
13. 依樣板建立 Hook
14. 取得特定 Hook
15. 部分更新 Hook
16. 刪除 Hook
17. 列出 AI 助理掛載的 Hook
18. 整批替換 AI 助理掛載的 Hook
19. 列出排程
20. 建立排程
21. 取得特定排程
22. 部分更新排程
23. 刪除排程
24. 立即執行排程
25. 啟用或停用排程

呼叫 API 示例 (Shell)

建立新 AI 助理

`POST` `/api/v1/chatbots/`

請求內容

請求參數

欄位	類型	必填	說明
name	string	是	Chatbot name. In Agent mode it carries semantic meaning; in other modes it only distinguishes chatbots.
largeLanguageModel	string (uuid)	是	機器人使用的大型語言模型，用於生成回答（含組織自建的 AI Gateway 模型）
embeddingModel	string (uuid)	否	用於向量化文本的嵌入模型，非必填項目
rerankerModel	string (uuid)	否	用於重新排序的模型，非必填項目
instructions	string	否	Role instructions describing the chatbot's role and behavior.
knowledgeBases	array[IdName]	否	機器人可存取的知識庫列表
databases	array[IdName]	否	機器人可存取的 SQL 資料庫列表（用於 Text-to-SQL 功能）
organization	string (uuid)	否	機器人所屬的組織，如果為空則為個人機器人
replyMode	object	否	回覆模式：一般回覆或串流回覆 `normal`：正常；`template`：模板；`hybrid`：混合；`agent`：代理;
template	string	否	Template used by Template and Hybrid modes.
unanswerableTemplate	string	否	Template used by Template and Hybrid modes when the question cannot be answered.
totalWordsCount	integer (int64)	否	Accumulated total word count used.
outputMode	object	否	輸出模式：文字、表格或自定義格式 `text`：文字；`json_schema`：JSON Schema;
rawOutputFormat	object	否	自定義輸出格式的JSON結構定義
groups	array[IdName]	否	機器人可存取的群組列表
tools	array[ToolSummary]	否	機器人可使用的工具列表
skills	array[SkillSummary]	否	機器人關聯的技能列表
connectors	array[IdName]	否	Connectors associated with this chatbot, gating per-contact OAuth authorization
agentMode	object	否	代理模式：一般、SQL或工作流程模式 `normal`：正常；`canvas`：畫布；`team`：團隊;

欄位	類型	必填	說明
numberOfRetrievedChunks	integer	否	提取的參考資料數量，預設為 12，最小值為 1
defaultLabelRelations	object	否	助理層級的預設知識庫標籤過濾條件，格式同 query_metadata.label_relations；null 表示不過濾。僅在呼叫端未帶 query_metadata 時作為最低優先序兜底套用。
useFullRetrievalRange	boolean	否	啟用後忽略 LLM 的 top_k 截斷，回傳完整 reranker 結果
enableEvaluation	boolean	否	
enableInlineCitations	boolean	否	Enables inline citations, inserting citation markers such as [1][2] into responses.
enableCodeInterpreter	boolean	否	When enabled, provides the Code Interpreter tool to run code in an isolated container.
enableBrowserTool	boolean	否	Enable browser automation tool for web tasks
enableImageSearch	boolean	否	Provide the image_search tool when any attached knowledge base uses a multimodal embedding model. Disable to remove the tool entirely.
enableClaudeStreamRetry	boolean	否	When a Claude streaming call stalls (first-chunk or mid-stream), abort and re-issue the call once in non-streaming mode. Mid-stream retries send a reset signal so the client discards any partial outpu...
customMaxLlmOutputTokens	integer	否	自訂最大 LLM 輸出 token 數，最小值為 512
voiceConfig	object	否	
voiceConfig.enabled	boolean	否	Whether this chatbot can be used as a voice agent. Checked by every conversation platform (WebChat, SIP phone, admin/marketplace voice test) instead of a per-platform toggle.
voiceConfig.voiceAgentType	string (uuid)	否	Voice agent mode type.
voiceConfig.sttProvider	string (uuid)	否	Speech-to-Text service provider.
voiceConfig.sttConfig	object	否	STT configuration parameters (JSON).
voiceConfig.ttsProvider	string (uuid)	否	Text-to-Speech service provider.
voiceConfig.ttsConfig	object	否	TTS configuration parameters (JSON).

欄位	類型	必填	說明
voiceConfig.realtimeProvider	string (uuid)	否	Realtime end-to-end voice model provider.
voiceConfig.realtimeConfig	object	否	Realtime configuration parameters (JSON).
voiceConfig.realtimeInstructions	string	否	Prompt dedicated to the realtime voice session; falls back to chatbot instructions when empty
voiceConfig.turnHandling	object	否	Turn-taking and interruption settings for the voice agent.
voiceConfig.enableVoiceReply	boolean	否	When disabled, the voice agent replies in text only and does not speak
thinkingConfig	object	否	思考等級：null（模型預設）或 {"reasoning_effort": "off
enableToolSearching	boolean	否	啟用動態工具搜尋功能，允許 agent 透過 tool_searching_tool 動態發現和加載工具
maxAgentIterations	integer	否	Maximum number of iterations for AgentWorkflow (1-100, default: 20)
agentTimeoutSeconds	integer	否	Timeout in seconds for AgentWorkflow execution (30-1200, default: 600)
agentTimeoutMessage	string	否	Custom user-facing message shown when AgentWorkflow times out (max 500 chars). Leave empty to use the system default.
requireTextWithFlexCards	boolean	否	When enabled, a turn that would end with only Flex Message cards and no text for the user is re-issued to the LLM once, asking it to write the text first and then send the card. Each retry incurs a se...
enableSizeBasedToolResultTruncation	boolean	否	When enabled, tool results exceeding the character threshold are kept as head+tail (with the identifiers found in the cut part) when written to conversation history; knowledge base, SQL and conversati...
toolResultMaxChars	integer	否	Character threshold for size-based tool result truncation (500-50000). Only effective when enable_size_based_tool_result_truncation is True.
enableVectorMemory	boolean	否	When enabled, archived messages are vectorized and processed by fact extraction for semantic retrieval (existing behavior). When disabled, archived

欄位	類型	必填	說明
			messages are discarded and only the active chat hist...
longTermMemoryTopK	integer	否	長期記憶每次檢索取回的記憶節點數（向量檢索的 similarity_top_k），預設為 10，範圍 1–50
enableCrossConversationSearch	boolean	否	When enabled, the conversation history tools also reach this contact's other conversations in the same inbox, within the lookback window. When disabled, they only reach the current conversation.
crossConversationLookbackDays	integer	否	How far back cross-conversation search may reach, measured from each conversation's last message (1-365 days). Leave empty to fall back to 90 days. Only effective when enable_cross_conversation_search...
useGatewayFallback	boolean	否	When enabled, use the fallback group instead of the single LLM
gatewayFallbackGroup	string (uuid)	否	
enableSearchMessagesTool	boolean	否	Allow the AI to search past messages in the current conversation.
enableGetMessageContextTool	boolean	否	Allow the AI to retrieve messages surrounding a specific message for context.
enableReadAttachmentFullTextTool	boolean	否	Allow the AI to read the full text of plain-text attachments. AGENT mode only.
enableParseAttachmentContentTool	boolean	否	Allow the AI to parse PDF, Office, audio, and other attachments. AGENT mode only.
enableListAvailableParsersTool	boolean	否	Allow the AI to list available parsers and their capabilities. AGENT mode only.
enableGetDownloadLinkTool	boolean	否	Allow the AI to generate shareable download links for produced content. AGENT mode only.
webChatIsActive	boolean	否	Optional, create only. Whether the web widget channel starts active. Omitted or null: follows the organization's default for new chatbot channels (inactive unless a platform admin turned it on). Ignor...
apiIsActive	boolean	否	Optional, create only. Whether the API channel starts active. Omitted or null: follows the organization's default for new

欄位	類型	必填	說明
			chatbot channels (inactive unless a platform admin turned it on). Ignored on u...
fileWorkspaceMode	object	否	File workspace mode in Work internal conversations: none, bound or user_mount. `none` : None ; `bound` : Bound workspace ; `user_mount` : User mount;
fileWorkspaceFolder	string (uuid)	否	The bound workspace (folder id); required when the mode is bound, cleared otherwise.

請求結構範例

```
{
  "name": string // Chatbot name. In Agent mode it carries semantic meaning; in other modes it only distinguishes chatbots.
  "largeLanguageModel": string (uuid) // 機器人使用的大型語言模型，用於生成回答（含組織自建的 AI Gateway 模型）
  "embeddingModel"?: string (uuid) // 用於向量化文本的嵌入模型，非必填項目 (非必填)
  "rerankerModel"?: string (uuid) // 用於重新排序的模型，非必填項目 (非必填)
  "instructions"?: string // Role instructions describing the chatbot's role and behavior. (非必填)
  "knowledgeBases"?: [ // 機器人可存取的知識庫列表 (非必填)
    {
      "id": string (uuid)
    }
  ]
  "databases"?: [ // 機器人可存取的 SQL 資料庫列表（用於 Text-to-SQL 功能） (非必填)
    {
      "id": string (uuid)
    }
  ]
  "organization"?: string (uuid) // 機器人所屬的組織，如果為空則為個人機器人 (非必填)
  "replyMode"?:  // 回覆模式：一般回覆或串流回覆

* `normal` - 正常
* `template` - 模板
* `hybrid` - 混合
* `agent` - 代理 (非必填)
  {
  }
  "template"?: string // Template used by Template and Hybrid modes. (非必填)
  "unanswerableTemplate"?: string // Template used by Template and Hybrid modes when the question cannot be answered. (非必填)
  "totalWordsCount"?: integer (int64) // Accumulated total word count used. (非必填)
  "outputMode"?:  // 輸出模式：文字、表格或自定義格式

* `text` - 文字
```

```
* `json_schema` - JSON Schema (非必填)
  {
  }
  "rawOutputFormat"?: object // 自定義輸出格式的JSON結構定義 (非必填)
  "groups"?: [ // 機器人可存取的群組列表 (非必填)
    {
      "id": string (uuid)
    }
  ]
  "tools"?: [ // 機器人可使用的工具列表 (非必填)
    {
      "id": string (uuid)
    }
  ]
  "skills"?: [ // 機器人關聯的技能列表 (非必填)
    {
      "id": string (uuid)
    }
  ]
  "connectors"?: [ // Connectors associated with this chatbot, gating per-contact OAuth
authorization (非必填)
    {
      "id": string (uuid)
    }
  ]
  "agentMode"?:  // 代理模式：一般、SQL或工作流程模式

* `normal` - 正常
* `canvas` - 畫布
* `team` - 團隊 (非必填)
  {
  }
  "numberOfRetrievedChunks"?: integer // 提取的參考資料數量，預設為 12，最小值為 1 (非必填)
  "defaultLabelRelations"?: object // 助理層級的預設知識庫標籤過濾條件，格式同
query_metadata.label_relations；null 表示不過濾。僅在呼叫端未帶 query_metadata 時作為最低優先序兜
底套用。 (非必填)
  "useFullRetrievalRange"?: boolean // 啟用後忽略 LLM 的 top_k 截斷，回傳完整 reranker 結果
(非必填)
  "enableEvaluation"?: boolean // 非必填
  "enableInlineCitations"?: boolean // Enables inline citations, inserting citation
markers such as [1][2] into responses. (非必填)
  "enableCodeInterpreter"?: boolean // When enabled, provides the Code Interpreter tool
to run code in an isolated container. (非必填)
  "enableBrowserTool"?: boolean // Enable browser automation tool for web tasks (非必填)
  "enableImageSearch"?: boolean // Provide the image_search tool when any attached
knowledge base uses a multimodal embedding model. Disable to remove the tool entirely.
(非必填)
  "enableClaudeStreamRetry"?: boolean // When a Claude streaming call stalls (first-chunk
or mid-stream), abort and re-issue the call once in non-streaming mode. Mid-stream
retries send a reset signal so the client discards any partial output already rendered.
Each retry incurs a second billing for the same prompt. (非必填)
  "customMaxLlmOutputTokens"?: integer // 自訂最大 LLM 輸出 token 數，最小值為 512 (非必填)
  "voiceConfig"?: { // 非必填
```

```
  {
    "enabled"?: boolean // Whether this chatbot can be used as a voice agent. Checked by every conversation platform (WebChat, SIP phone, admin/marketplace voice test) instead of a per-platform toggle. (非必填)
    "voiceAgentType"?: string (uuid) // Voice agent mode type. (非必填)
    "sttProvider"?: string (uuid) // Speech-to-Text service provider. (非必填)
    "sttConfig"?: object // STT configuration parameters (JSON). (非必填)
    "ttsProvider"?: string (uuid) // Text-to-Speech service provider. (非必填)
    "ttsConfig"?: object // TTS configuration parameters (JSON). (非必填)
    "realtimeProvider"?: string (uuid) // Realtime end-to-end voice model provider. (非必填)
    "realtimeConfig"?: object // Realtime configuration parameters (JSON). (非必填)
    "realtimeInstructions"?: string // Prompt dedicated to the realtime voice session; falls back to chatbot instructions when empty (非必填)
    "turnHandling"?: object // Turn-taking and interruption settings for the voice agent. (非必填)
    "enableVoiceReply"?: boolean // When disabled, the voice agent replies in text only and does not speak (非必填)
  }
  }
  "thinkingConfig"?: object // 思考等級：null（模型預設）或 {"reasoning_effort": "off|minimal|low|medium|high|xhigh|max"} (非必填)
  "enableToolSearching"?: boolean // 啟用動態工具搜尋功能，允許 agent 透過 tool_searching_tool 動態發現和加載工具 (非必填)
  "maxAgentIterations"?: integer // Maximum number of iterations for AgentWorkflow (1-100, default: 20) (非必填)
  "agentTimeoutSeconds"?: integer // Timeout in seconds for AgentWorkflow execution (30-1200, default: 600) (非必填)
  "agentTimeoutMessage"?: string // Custom user-facing message shown when AgentWorkflow times out (max 500 chars). Leave empty to use the system default. (非必填)
  "requireTextWithFlexCards"?: boolean // When enabled, a turn that would end with only Flex Message cards and no text for the user is re-issued to the LLM once, asking it to write the text first and then send the card. Each retry incurs a second billing for the same prompt. (非必填)
  "enableSizeBasedToolResultTruncation"?: boolean // When enabled, tool results exceeding the character threshold are kept as head+tail (with the identifiers found in the cut part) when written to conversation history; knowledge base, SQL and conversation search results keep their 100-character cut either way. Reduces memory bloat from large tool outputs (code interpreter bash stdout, web search results, etc.). (非必填)
  "toolResultMaxChars"?: integer // Character threshold for size-based tool result truncation (500-50000). Only effective when enable_size_based_tool_result_truncation is True. (非必填)
  "enableVectorMemory"?: boolean // When enabled, archived messages are vectorized and processed by fact extraction for semantic retrieval (existing behavior). When disabled, archived messages are discarded and only the active chat history window is used for multi-turn context. (非必填)
  "longTermMemoryTopK"?: integer // 長期記憶每次檢索取回的記憶節點數（向量檢索的 similarity_top_k），預設為 10，範圍 1–50 (非必填)
  "enableCrossConversationSearch"?: boolean // When enabled, the conversation history tools also reach this contact's other conversations in the same inbox, within the lookback window. When disabled, they only reach the current conversation. (非必填)
  "crossConversationLookbackDays"?: integer // How far back cross-conversation search may reach, measured from each conversation's last message (1-365 days). Leave empty to fall
```

```
back to 90 days. Only effective when enable_cross_conversation_search is True. (非必填)
  "useGatewayFallback"?: boolean // When enabled, use the fallback group instead of the
single LLM (非必填)
  "gatewayFallbackGroup"?: string (uuid) // 非必填
  "enableSearchMessagesTool"?: boolean // Allow the AI to search past messages in the
current conversation. (非必填)
  "enableGetMessageContextTool"?: boolean // Allow the AI to retrieve messages
surrounding a specific message for context. (非必填)
  "enableReadAttachmentFullTextTool"?: boolean // Allow the AI to read the full text of
plain-text attachments. AGENT mode only. (非必填)
  "enableParseAttachmentContentTool"?: boolean // Allow the AI to parse PDF, Office,
audio, and other attachments. AGENT mode only. (非必填)
  "enableListAvailableParsersTool"?: boolean // Allow the AI to list available parsers
and their capabilities. AGENT mode only. (非必填)
  "enableGetDownloadLinkTool"?: boolean // Allow the AI to generate shareable download
links for produced content. AGENT mode only. (非必填)
  "webChatIsActive"?: boolean // Optional, create only. Whether the web widget channel
starts active. Omitted or null: follows the organization's default for new chatbot
channels (inactive unless a platform admin turned it on). Ignored on update; change an
existing channel from its channel settings instead. (非必填)
  "apiIsActive"?: boolean // Optional, create only. Whether the API channel starts
active. Omitted or null: follows the organization's default for new chatbot channels
(inactive unless a platform admin turned it on). Ignored on update; change an existing
channel from its channel settings instead. The backstage (admin) channel always starts
active and cannot be set here. (非必填)
  "fileWorkspaceMode"?:  // File workspace mode in Work internal conversations: none,
bound or user_mount.

* `none` - None
* `bound` - Bound workspace
* `user_mount` - User mount (非必填)
  {
  }
  "fileWorkspaceFolder"?: string (uuid) // The bound workspace (folder id); required when
the mode is bound, cleared otherwise. (非必填)
}
```

請求範例值

```
{
  "name": "範例名稱",
  "largeLanguageModel": "550e8400-e29b-41d4-a716-446655440000",
  "embeddingModel": "550e8400-e29b-41d4-a716-446655440000",
  "rerankerModel": "550e8400-e29b-41d4-a716-446655440000",
  "instructions": "範例字串",
  "knowledgeBases": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000"
    }
  ],
  "databases": [
    {
```

```
      "id": "550e8400-e29b-41d4-a716-446655440000"
    }
  ],
  "organization": "550e8400-e29b-41d4-a716-446655440000",
  "replyMode": {},
  "template": "範例字串",
  "unanswerableTemplate": "範例字串",
  "totalWordsCount": 123,
  "outputMode": {},
  "rawOutputFormat": null,
  "groups": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000"
    }
  ],
  "tools": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000"
    }
  ],
  "skills": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000"
    }
  ],
  "connectors": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000"
    }
  ],
  "agentMode": {},
  "numberOfRetrievedChunks": 123,
  "defaultLabelRelations": null,
  "useFullRetrievalRange": true,
  "enableEvaluation": true,
  "enableInlineCitations": true,
  "enableCodeInterpreter": true,
  "enableBrowserTool": true,
  "enableImageSearch": true,
  "enableClaudeStreamRetry": true,
  "customMaxLlmOutputTokens": 123,
  "voiceConfig": {
    "enabled": true,
    "voiceAgentType": "550e8400-e29b-41d4-a716-446655440000",
    "sttProvider": "550e8400-e29b-41d4-a716-446655440000",
    "sttConfig": null,
    "ttsProvider": "550e8400-e29b-41d4-a716-446655440000",
    "ttsConfig": null,
    "realtimeProvider": "550e8400-e29b-41d4-a716-446655440000",
    "realtimeConfig": null,
    "realtimeInstructions": "範例字串",
    "turnHandling": null,
    "enableVoiceReply": true
```

```
  },
  "thinkingConfig": null,
  "enableToolSearching": true,
  "maxAgentIterations": 123,
  "agentTimeoutSeconds": 123,
  "agentTimeoutMessage": "範例字串",
  "requireTextWithFlexCards": true,
  "enableSizeBasedToolResultTruncation": true,
  "toolResultMaxChars": 123,
  "enableVectorMemory": true,
  "longTermMemoryTopK": 123,
  "enableCrossConversationSearch": true,
  "crossConversationLookbackDays": 123,
  "useGatewayFallback": true,
  "gatewayFallbackGroup": "550e8400-e29b-41d4-a716-446655440000",
  "enableSearchMessagesTool": true,
  "enableGetMessageContextTool": true,
  "enableReadAttachmentFullTextTool": true,
  "enableParseAttachmentContentTool": true,
  "enableListAvailableParsersTool": true,
  "enableGetDownloadLinkTool": true,
  "webChatIsActive": true,
  "apiIsActive": true,
  "fileWorkspaceMode": {},
  "fileWorkspaceFolder": "550e8400-e29b-41d4-a716-446655440000"
}
```


程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X POST "

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "name": "範例名稱",
    "largeLanguageModel": "550e8400-e29b-41d4-a716-446655440000",
    "embeddingModel": "550e8400-e29b-41d4-a716-446655440000",
    "rerankerModel": "550e8400-e29b-41d4-a716-446655440000",
    "instructions": "範例字串",
    "knowledgeBases": [
      {
        "id": "550e8400-e29b-41d4-a716-446655440000"
      }
    ],
    "databases": [
      {
        "id": "550e8400-e29b-41d4-a716-446655440000"
      }
    ],
    "organization": "550e8400-e29b-41d4-a716-446655440000",
    "replyMode": {},
    "template": "範例字串",
    "unanswerableTemplate": "範例字串",
    "totalWordsCount": 123,
    "outputMode": {},
    "rawOutputFormat": null,
    "groups": [
      {
        "id": "550e8400-e29b-41d4-a716-446655440000"
      }
    ],
    "tools": [
      {
        "id": "550e8400-e29b-41d4-a716-446655440000"
      }
    ],
    "skills": [
      {
        "id": "550e8400-e29b-41d4-a716-446655440000"
      }
    ],
    "connectors": [
      {
        "id": "550e8400-e29b-41d4-a716-446655440000"
```

```
        }
      ],
      "agentMode": {},
      "numberOfRetrievedChunks": 123,
      "defaultLabelRelations": null,
      "useFullRetrievalRange": true,
      "enableEvaluation": true,
      "enableInlineCitations": true,
      "enableCodeInterpreter": true,
      "enableBrowserTool": true,
      "enableImageSearch": true,
      "enableClaudeStreamRetry": true,
      "customMaxLlmOutputTokens": 123,
      "voiceConfig": {
        "enabled": true,
        "voiceAgentType": "550e8400-e29b-41d4-a716-446655440000",
        "sttProvider": "550e8400-e29b-41d4-a716-446655440000",
        "sttConfig": null,
        "ttsProvider": "550e8400-e29b-41d4-a716-446655440000",
        "ttsConfig": null,
        "realtimeProvider": "550e8400-e29b-41d4-a716-446655440000",
        "realtimeConfig": null,
        "realtimeInstructions": "範例字串",
        "turnHandling": null,
        "enableVoiceReply": true
      },
      "thinkingConfig": null,
      "enableToolSearching": true,
      "maxAgentIterations": 123,
      "agentTimeoutSeconds": 123,
      "agentTimeoutMessage": "範例字串",
      "requireTextWithFlexCards": true,
      "enableSizeBasedToolResultTruncation": true,
      "toolResultMaxChars": 123,
      "enableVectorMemory": true,
      "longTermMemoryTopK": 123,
      "enableCrossConversationSearch": true,
      "crossConversationLookbackDays": 123,
      "useGatewayFallback": true,
      "gatewayFallbackGroup": "550e8400-e29b-41d4-a716-446655440000",
      "enableSearchMessagesTool": true,
      "enableGetMessageContextTool": true,
      "enableReadAttachmentFullTextTool": true,
      "enableParseAttachmentContentTool": true,
      "enableListAvailableParsersTool": true,
      "enableGetDownloadLinkTool": true,
      "webChatIsActive": true,
      "apiIsActive": true,
      "fileWorkspaceMode": {},
      "fileWorkspaceFolder": "550e8400-e29b-41d4-a716-446655440000"
    }'

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// 請求內容 (payload)
const data = {
    "name": "範例名稱",
    "largeLanguageModel": "550e8400-e29b-41d4-a716-446655440000",
    "embeddingModel": "550e8400-e29b-41d4-a716-446655440000",
    "rerankerModel": "550e8400-e29b-41d4-a716-446655440000",
    "instructions": "範例字串",
    "knowledgeBases": [
      {
        "id": "550e8400-e29b-41d4-a716-446655440000"
      }
    ],
    "databases": [
      {
        "id": "550e8400-e29b-41d4-a716-446655440000"
      }
    ],
    "organization": "550e8400-e29b-41d4-a716-446655440000",
    "replyMode": {},
    "template": "範例字串",
    "unanswerableTemplate": "範例字串",
    "totalWordsCount": 123,
    "outputMode": {},
    "rawOutputFormat": null,
    "groups": [
      {
        "id": "550e8400-e29b-41d4-a716-446655440000"
      }
    ],
    "tools": [
      {
        "id": "550e8400-e29b-41d4-a716-446655440000"
      }
    ],
    "skills": [
      {
        "id": "550e8400-e29b-41d4-a716-446655440000"
      }
```

```
  ],
  "connectors": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000"
    }
  ],
  "agentMode": {},
  "numberOfRetrievedChunks": 123,
  "defaultLabelRelations": null,
  "useFullRetrievalRange": true,
  "enableEvaluation": true,
  "enableInlineCitations": true,
  "enableCodeInterpreter": true,
  "enableBrowserTool": true,
  "enableImageSearch": true,
  "enableClaudeStreamRetry": true,
  "customMaxLlmOutputTokens": 123,
  "voiceConfig": {
    "enabled": true,
    "voiceAgentType": "550e8400-e29b-41d4-a716-446655440000",
    "sttProvider": "550e8400-e29b-41d4-a716-446655440000",
    "sttConfig": null,
    "ttsProvider": "550e8400-e29b-41d4-a716-446655440000",
    "ttsConfig": null,
    "realtimeProvider": "550e8400-e29b-41d4-a716-446655440000",
    "realtimeConfig": null,
    "realtimeInstructions": "範例字串",
    "turnHandling": null,
    "enableVoiceReply": true
  },
  "thinkingConfig": null,
  "enableToolSearching": true,
  "maxAgentIterations": 123,
  "agentTimeoutSeconds": 123,
  "agentTimeoutMessage": "範例字串",
  "requireTextWithFlexCards": true,
  "enableSizeBasedToolResultTruncation": true,
  "toolResultMaxChars": 123,
  "enableVectorMemory": true,
  "longTermMemoryTopK": 123,
  "enableCrossConversationSearch": true,
  "crossConversationLookbackDays": 123,
  "useGatewayFallback": true,
  "gatewayFallbackGroup": "550e8400-e29b-41d4-a716-446655440000",
  "enableSearchMessagesTool": true,
  "enableGetMessageContextTool": true,
  "enableReadAttachmentFullTextTool": true,
  "enableParseAttachmentContentTool": true,
  "enableListAvailableParsersTool": true,
  "enableGetDownloadLinkTool": true,
  "webChatIsActive": true,
  "apiIsActive": true,
  "fileWorkspaceMode": {},
```

```
    "fileWorkspaceFolder": "550e8400-e29b-41d4-a716-446655440000"
  };

axios.post(" data, config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# 請求內容 (payload)
data = {
    "name": "範例名稱",
    "largeLanguageModel": "550e8400-e29b-41d4-a716-446655440000",
    "embeddingModel": "550e8400-e29b-41d4-a716-446655440000",
    "rerankerModel": "550e8400-e29b-41d4-a716-446655440000",
    "instructions": "範例字串",
    "knowledgeBases": [
        {
            "id": "550e8400-e29b-41d4-a716-446655440000"
        }
    ],
    "databases": [
        {
            "id": "550e8400-e29b-41d4-a716-446655440000"
        }
    ],
    "organization": "550e8400-e29b-41d4-a716-446655440000",
    "replyMode": {},
    "template": "範例字串",
    "unanswerableTemplate": "範例字串",
    "totalWordsCount": 123,
    "outputMode": {},
    "rawOutputFormat": None,
    "groups": [
        {
            "id": "550e8400-e29b-41d4-a716-446655440000"
        }
    ],
    "tools": [
        {
            "id": "550e8400-e29b-41d4-a716-446655440000"
        }
    ],
    "skills": [
        {
            "id": "550e8400-e29b-41d4-a716-446655440000"
        }
    ],
    "connectors": [
```

```
            {
                "id": "550e8400-e29b-41d4-a716-446655440000"
            }
        ],
        "agentMode": {},
        "numberOfRetrievedChunks": 123,
        "defaultLabelRelations": None,
        "useFullRetrievalRange": True,
        "enableEvaluation": True,
        "enableInlineCitations": True,
        "enableCodeInterpreter": True,
        "enableBrowserTool": True,
        "enableImageSearch": True,
        "enableClaudeStreamRetry": True,
        "customMaxLlmOutputTokens": 123,
        "voiceConfig": {
            "enabled": True,
            "voiceAgentType": "550e8400-e29b-41d4-a716-446655440000",
            "sttProvider": "550e8400-e29b-41d4-a716-446655440000",
            "sttConfig": None,
            "ttsProvider": "550e8400-e29b-41d4-a716-446655440000",
            "ttsConfig": None,
            "realtimeProvider": "550e8400-e29b-41d4-a716-446655440000",
            "realtimeConfig": None,
            "realtimeInstructions": "範例字串",
            "turnHandling": None,
            "enableVoiceReply": True
        },
        "thinkingConfig": None,
        "enableToolSearching": True,
        "maxAgentIterations": 123,
        "agentTimeoutSeconds": 123,
        "agentTimeoutMessage": "範例字串",
        "requireTextWithFlexCards": True,
        "enableSizeBasedToolResultTruncation": True,
        "toolResultMaxChars": 123,
        "enableVectorMemory": True,
        "longTermMemoryTopK": 123,
        "enableCrossConversationSearch": True,
        "crossConversationLookbackDays": 123,
        "useGatewayFallback": True,
        "gatewayFallbackGroup": "550e8400-e29b-41d4-a716-446655440000",
        "enableSearchMessagesTool": True,
        "enableGetMessageContextTool": True,
        "enableReadAttachmentFullTextTool": True,
        "enableParseAttachmentContentTool": True,
        "enableListAvailableParsersTool": True,
        "enableGetDownloadLinkTool": True,
        "webChatIsActive": True,
        "apiIsActive": True,
        "fileWorkspaceMode": {},
        "fileWorkspaceFolder": "550e8400-e29b-41d4-a716-446655440000"
    }
```

```
response = requests.post(url, json=data, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->post(" [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'name' => '範例名稱',
            'largeLanguageModel' => '550e8400-e29b-41d4-a716-446655440000',
            'embeddingModel' => '550e8400-e29b-41d4-a716-446655440000',
            'rerankerModel' => '550e8400-e29b-41d4-a716-446655440000',
            'instructions' => '範例字串',
            'knowledgeBases' => [
                [
                    'id' => '550e8400-e29b-41d4-a716-446655440000'
                ]
            ],
            'databases' => [
                [
                    'id' => '550e8400-e29b-41d4-a716-446655440000'
                ]
            ],
            'organization' => '550e8400-e29b-41d4-a716-446655440000',
            'replyMode' => new \stdClass(),
            'template' => '範例字串',
            'unanswerableTemplate' => '範例字串',
            'totalWordsCount' => 123,
            'outputMode' => new \stdClass(),
            'rawOutputFormat' => null,
            'groups' => [
                [
                    'id' => '550e8400-e29b-41d4-a716-446655440000'
                ]
            ],
            'tools' => [
                [
                    'id' => '550e8400-e29b-41d4-a716-446655440000'
                ]
            ],
            'skills' => [
                [
                    'id' => '550e8400-e29b-41d4-a716-446655440000'
                ]
```

```
            ],
            'connectors' => [
                [
                    'id' => '550e8400-e29b-41d4-a716-446655440000'
                ]
            ],
            'agentMode' => new \stdClass(),
            'numberOfRetrievedChunks' => 123,
            'defaultLabelRelations' => null,
            'useFullRetrievalRange' => true,
            'enableEvaluation' => true,
            'enableInlineCitations' => true,
            'enableCodeInterpreter' => true,
            'enableBrowserTool' => true,
            'enableImageSearch' => true,
            'enableClaudeStreamRetry' => true,
            'customMaxLlmOutputTokens' => 123,
            'voiceConfig' => [
                'enabled' => true,
                'voiceAgentType' => '550e8400-e29b-41d4-a716-446655440000',
                'sttProvider' => '550e8400-e29b-41d4-a716-446655440000',
                'sttConfig' => null,
                'ttsProvider' => '550e8400-e29b-41d4-a716-446655440000',
                'ttsConfig' => null,
                'realtimeProvider' => '550e8400-e29b-41d4-a716-446655440000',
                'realtimeConfig' => null,
                'realtimeInstructions' => '範例字串',
                'turnHandling' => null,
                'enableVoiceReply' => true
            ],
            'thinkingConfig' => null,
            'enableToolSearching' => true,
            'maxAgentIterations' => 123,
            'agentTimeoutSeconds' => 123,
            'agentTimeoutMessage' => '範例字串',
            'requireTextWithFlexCards' => true,
            'enableSizeBasedToolResultTruncation' => true,
            'toolResultMaxChars' => 123,
            'enableVectorMemory' => true,
            'longTermMemoryTopK' => 123,
            'enableCrossConversationSearch' => true,
            'crossConversationLookbackDays' => 123,
            'useGatewayFallback' => true,
            'gatewayFallbackGroup' => '550e8400-e29b-41d4-a716-446655440000',
            'enableSearchMessagesTool' => true,
            'enableGetMessageContextTool' => true,
            'enableReadAttachmentFullTextTool' => true,
            'enableParseAttachmentContentTool' => true,
            'enableListAvailableParsersTool' => true,
            'enableGetDownloadLinkTool' => true,
            'webChatIsActive' => true,
            'apiIsActive' => true,
            'fileWorkspaceMode' => new \stdClass(),
```

```
            'fileWorkspaceFolder' => '550e8400-e29b-41d4-a716-446655440000'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 201

回應結構範例

```
{
  "id": string (uuid)
  "name": string // Chatbot name. In Agent mode it carries semantic meaning; in other modes it only distinguishes chatbots.
  "largeLanguageModel": string (uuid) // 機器人使用的大型語言模型，用於生成回答（含組織自建的 AI Gateway 模型）
  "llm":  // 綁定模型的 id、name 與退役資訊，直接讀取 FK，即使該模型已被組織停用仍會回傳
  {
    "id": string (uuid)
    "name": string
    "retiresAt": string (date) // 供應商退役日；到期後每日排程會把助理換到 replacement 並停用此模型。null 表示未排定退役
    "replacement":  // 退役後接手的模型（id 與 name）；null 表示未指定，到期時不會自動搬移
    {
      "id": string (uuid)
      "name": string
    }
  }
  "embeddingModel"?: string (uuid) // 用於向量化文本的嵌入模型，非必填項目 (非必填)
  "rerankerModel"?: string (uuid) // 用於重新排序的模型，非必填項目 (非必填)
  "instructions"?: string // Role instructions describing the chatbot's role and behavior. (非必填)
  "knowledgeBases"?: [ // 機器人可存取的知識庫列表 (非必填)
    {
      "id": string (uuid)
      "name": string
    }
```

```
  ]
  "databases"?: [ // 機器人可存取的 SQL 資料庫列表（用於 Text-to-SQL 功能） (非必填)
    {
      "id": string (uuid)
      "name": string
    }
  ]
  "updatedAt": string (timestamp)
  "organization"?: string (uuid) // 機器人所屬的組織，如果為空則為個人機器人 (非必填)
  "replyMode"?:  // 回覆模式：一般回覆或串流回覆

* `normal` - 正常
* `template` - 模板
* `hybrid` - 混合
* `agent` - 代理 (非必填)
  {
  }
  "template"?: string // Template used by Template and Hybrid modes. (非必填)
  "unanswerableTemplate"?: string // Template used by Template and Hybrid modes when the
question cannot be answered. (非必填)
  "totalWordsCount"?: integer (int64) // Accumulated total word count used. (非必填)
  "outputMode"?:  // 輸出模式：文字、表格或自定義格式

* `text` - 文字
* `json_schema` - JSON Schema (非必填)
  {
  }
  "rawOutputFormat"?: object // 自定義輸出格式的JSON結構定義 (非必填)
  "groups"?: [ // 機器人可存取的群組列表 (非必填)
    {
      "id": string (uuid)
      "name": string
    }
  ]
  "tools"?: [ // 機器人可使用的工具列表 (非必填)
    {
      "id": string (uuid)
      "name": string
      "description": string
      "displayName": string
      "toolType": string
    }
  ]
  "skills"?: [ // 機器人關聯的技能列表 (非必填)
    {
      "id": string (uuid)
      "name": string
      "description": string
    }
  ]
  "connectors"?: [ // Connectors associated with this chatbot, gating per-contact OAuth
authorization (非必填)
    {
```

```
      "id": string (uuid)
      "name": string
    }
  ]
  "agentMode"?:  // 代理模式：一般、SQL或工作流程模式

* `normal` - 正常
* `canvas` - 畫布
* `team` - 團隊 (非必填)
  {
  }
  "numberOfRetrievedChunks"?: integer // 提取的參考資料數量，預設為 12，最小值為 1 (非必填)
  "defaultLabelRelations"?: object // 助理層級的預設知識庫標籤過濾條件，格式同 query_metadata.label_relations；null 表示不過濾。僅在呼叫端未帶 query_metadata 時作為最低優先序兜底套用。 (非必填)
  "useFullRetrievalRange"?: boolean // 啟用後忽略 LLM 的 top_k 截斷，回傳完整 reranker 結果 (非必填)
  "enableEvaluation"?: boolean // 非必填
  "enableInlineCitations"?: boolean // Enables inline citations, inserting citation markers such as [1][2] into responses. (非必填)
  "enableCodeInterpreter"?: boolean // When enabled, provides the Code Interpreter tool to run code in an isolated container. (非必填)
  "enableBrowserTool"?: boolean // Enable browser automation tool for web tasks (非必填)
  "enableImageSearch"?: boolean // Provide the image_search tool when any attached knowledge base uses a multimodal embedding model. Disable to remove the tool entirely. (非必填)
  "enableClaudeStreamRetry"?: boolean // When a Claude streaming call stalls (first-chunk or mid-stream), abort and re-issue the call once in non-streaming mode. Mid-stream retries send a reset signal so the client discards any partial output already rendered. Each retry incurs a second billing for the same prompt. (非必填)
  "customMaxLlmOutputTokens"?: integer // 自訂最大 LLM 輸出 token 數，最小值為 512 (非必填)
  "voiceConfig"?: { // 非必填
  {
    "enabled"?: boolean // Whether this chatbot can be used as a voice agent. Checked by every conversation platform (WebChat, SIP phone, admin/marketplace voice test) instead of a per-platform toggle. (非必填)
    "voiceAgentType"?: string (uuid) // Voice agent mode type. (非必填)
    "sttProvider"?: string (uuid) // Speech-to-Text service provider. (非必填)
    "sttConfig"?: object // STT configuration parameters (JSON). (非必填)
    "ttsProvider"?: string (uuid) // Text-to-Speech service provider. (非必填)
    "ttsConfig"?: object // TTS configuration parameters (JSON). (非必填)
    "realtimeProvider"?: string (uuid) // Realtime end-to-end voice model provider. (非必填)
    "realtimeConfig"?: object // Realtime configuration parameters (JSON). (非必填)
    "realtimeInstructions"?: string // Prompt dedicated to the realtime voice session; falls back to chatbot instructions when empty (非必填)
    "turnHandling"?: object // Turn-taking and interruption settings for the voice agent. (非必填)
    "enableVoiceReply"?: boolean // When disabled, the voice agent replies in text only and does not speak (非必填)
  }
  }
  "thinkingConfig"?: object // 思考等級：null（模型預設）或 {"reasoning_effort":
```

```
"off|minimal|low|medium|high|xhigh|max"} (非必填)
  "enableToolSearching"?: boolean // 啟用動態工具搜尋功能，允許 agent 透過 tool_searching_tool 動態發現和加載工具 (非必填)
  "maxAgentIterations"?: integer // Maximum number of iterations for AgentWorkflow (1-100, default: 20) (非必填)
  "agentTimeoutSeconds"?: integer // Timeout in seconds for AgentWorkflow execution (30-1200, default: 600) (非必填)
  "agentTimeoutMessage"?: string // Custom user-facing message shown when AgentWorkflow times out (max 500 chars). Leave empty to use the system default. (非必填)
  "requireTextWithFlexCards"?: boolean // When enabled, a turn that would end with only Flex Message cards and no text for the user is re-issued to the LLM once, asking it to write the text first and then send the card. Each retry incurs a second billing for the same prompt. (非必填)
  "isMultimodalLlm": boolean // Whether the chatbot LLM supports multimodal (read-only)
  "enableSizeBasedToolResultTruncation"?: boolean // When enabled, tool results exceeding the character threshold are kept as head+tail (with the identifiers found in the cut part) when written to conversation history; knowledge base, SQL and conversation search results keep their 100-character cut either way. Reduces memory bloat from large tool outputs (code interpreter bash stdout, web search results, etc.). (非必填)
  "toolResultMaxChars"?: integer // Character threshold for size-based tool result truncation (500-50000). Only effective when enable_size_based_tool_result_truncation is True. (非必填)
  "enableVectorMemory"?: boolean // When enabled, archived messages are vectorized and processed by fact extraction for semantic retrieval (existing behavior). When disabled, archived messages are discarded and only the active chat history window is used for multi-turn context. (非必填)
  "longTermMemoryTopK"?: integer // 長期記憶每次檢索取回的記憶節點數（向量檢索的 similarity_top_k），預設為 10，範圍 1–50 (非必填)
  "enableCrossConversationSearch"?: boolean // When enabled, the conversation history tools also reach this contact's other conversations in the same inbox, within the lookback window. When disabled, they only reach the current conversation. (非必填)
  "crossConversationLookbackDays"?: integer // How far back cross-conversation search may reach, measured from each conversation's last message (1-365 days). Leave empty to fall back to 90 days. Only effective when enable_cross_conversation_search is True. (非必填)
  "useGatewayFallback"?: boolean // When enabled, use the fallback group instead of the single LLM (非必填)
  "gatewayFallbackGroup"?: string (uuid) // 非必填
  "enableSearchMessagesTool"?: boolean // Allow the AI to search past messages in the current conversation. (非必填)
  "enableGetMessageContextTool"?: boolean // Allow the AI to retrieve messages surrounding a specific message for context. (非必填)
  "enableReadAttachmentFullTextTool"?: boolean // Allow the AI to read the full text of plain-text attachments. AGENT mode only. (非必填)
  "enableParseAttachmentContentTool"?: boolean // Allow the AI to parse PDF, Office, audio, and other attachments. AGENT mode only. (非必填)
  "enableListAvailableParsersTool"?: boolean // Allow the AI to list available parsers and their capabilities. AGENT mode only. (非必填)
  "enableGetDownloadLinkTool"?: boolean // Allow the AI to generate shareable download links for produced content. AGENT mode only. (非必填)
  "isLocked": boolean // Locked instance: config follows the official version; only the dedicated KB can be modified
  "sourceBuildInAgent": string (uuid) // Points to the official Build-in Agent blueprint when instantiated by a rental
```

```
  "canUpdate": boolean // Return whether the current user can update this resource.
  "canDelete": boolean // Return whether the current user can delete this resource.
  "team":
  {
    "id": string (uuid)
    "name": string
  }
  "webChatIsActive"?: boolean // Optional, create only. Whether the web widget channel
starts active. Omitted or null: follows the organization's default for new chatbot
channels (inactive unless a platform admin turned it on). Ignored on update; change an
existing channel from its channel settings instead. (非必填)
  "apiIsActive"?: boolean // Optional, create only. Whether the API channel starts
active. Omitted or null: follows the organization's default for new chatbot channels
(inactive unless a platform admin turned it on). Ignored on update; change an existing
channel from its channel settings instead. The backstage (admin) channel always starts
active and cannot be set here. (非必填)
  "fileWorkspaceMode"?:  // File workspace mode in Work internal conversations: none,
bound or user_mount.

* `none` - None
* `bound` - Bound workspace
* `user_mount` - User mount (非必填)
  {
  }
  "fileWorkspaceFolder"?: string (uuid) // The bound workspace (folder id); required when
the mode is bound, cleared otherwise. (非必填)
  "fileWorkspaceStatus": object // Read-only. {"folder": {"id", "name"} | null, "state":
"ok" | "missing" | "builder_lost_edit" | null}
  "fileWorkspaceAvailable": boolean // Read-only. Whether the organization has the file
library and this agent can configure a file workspace.
}
```

回應範例值

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "name": "回應字串",
  "largeLanguageModel": "550e8400-e29b-41d4-a716-446655440000",
  "llm": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應字串",
    "retiresAt": "回應字串",
    "replacement": {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "回應字串"
    }
  },
  "embeddingModel": "550e8400-e29b-41d4-a716-446655440000",
  "rerankerModel": "550e8400-e29b-41d4-a716-446655440000",
  "instructions": "回應字串",
  "knowledgeBases": [
    {
```

```
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "回應字串"
    }
  ],
  "databases": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "回應字串"
    }
  ],
  "updatedAt": "回應字串",
  "organization": "550e8400-e29b-41d4-a716-446655440000",
  "replyMode": {},
  "template": "回應字串",
  "unanswerableTemplate": "回應字串",
  "totalWordsCount": 456,
  "outputMode": {},
  "rawOutputFormat": null,
  "groups": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "回應字串"
    }
  ],
  "tools": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "回應字串",
      "description": "回應字串",
      "displayName": "回應字串",
      "toolType": "回應字串"
    }
  ],
  "skills": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "回應字串",
      "description": "回應字串"
    }
  ],
  "connectors": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "回應字串"
    }
  ],
  "agentMode": {},
  "numberOfRetrievedChunks": 456,
  "defaultLabelRelations": null,
  "useFullRetrievalRange": false,
  "enableEvaluation": false,
  "enableInlineCitations": false,
  "enableCodeInterpreter": false,
```

```
  "enableBrowserTool": false,
  "enableImageSearch": false,
  "enableClaudeStreamRetry": false,
  "customMaxLlmOutputTokens": 456,
  "voiceConfig": {
    "enabled": false,
    "voiceAgentType": "550e8400-e29b-41d4-a716-446655440000",
    "sttProvider": "550e8400-e29b-41d4-a716-446655440000",
    "sttConfig": null,
    "ttsProvider": "550e8400-e29b-41d4-a716-446655440000",
    "ttsConfig": null,
    "realtimeProvider": "550e8400-e29b-41d4-a716-446655440000",
    "realtimeConfig": null,
    "realtimeInstructions": "回應字串",
    "turnHandling": null,
    "enableVoiceReply": false
  },
  "thinkingConfig": null,
  "enableToolSearching": false,
  "maxAgentIterations": 456,
  "agentTimeoutSeconds": 456,
  "agentTimeoutMessage": "回應字串",
  "requireTextWithFlexCards": false,
  "isMultimodalLlm": false,
  "enableSizeBasedToolResultTruncation": false,
  "toolResultMaxChars": 456,
  "enableVectorMemory": false,
  "longTermMemoryTopK": 456,
  "enableCrossConversationSearch": false,
  "crossConversationLookbackDays": 456,
  "useGatewayFallback": false,
  "gatewayFallbackGroup": "550e8400-e29b-41d4-a716-446655440000",
  "enableSearchMessagesTool": false,
  "enableGetMessageContextTool": false,
  "enableReadAttachmentFullTextTool": false,
  "enableParseAttachmentContentTool": false,
  "enableListAvailableParsersTool": false,
  "enableGetDownloadLinkTool": false,
  "isLocked": false,
  "sourceBuildInAgent": "550e8400-e29b-41d4-a716-446655440000",
  "canUpdate": false,
  "canDelete": false,
  "team": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應字串"
  },
  "webChatIsActive": false,
  "apiIsActive": false,
  "fileWorkspaceMode": {},
  "fileWorkspaceFolder": "550e8400-e29b-41d4-a716-446655440000",
  "fileWorkspaceStatus": {
    "name": "example.pdf",
    "content": "base64encoded_content",
```

```
    "contentType": "application/pdf"
  },
  "fileWorkspaceAvailable": false
}
```


列出 Embedding Model

GET `/api/v1/embedding-models/`

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/embedding-models/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/embedding-models/", config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/embedding-models/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->get("https://api.maiagent.ai/api/v1/embedding-models/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
[
  {
    "id": string (uuid)
    "name": string
    "isDefault"?: boolean // 非必填
    "isMultimodal"?: boolean // Whether this embedding model supports multimodal (text + image) embeddings (非必填)
    "icon":
    {
      "id": string (uuid)
      "name": string
      "image": string (uri)
    }
```

```
  }
]
```

回應範例值


```
[
  {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應字串",
    "isDefault": false,
    "isMultimodal": false,
    "icon": {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "回應字串",
      "image": "https://example.com/file.jpg"
    }
  }
]
```


列出 Reranker Model

`GET` `/api/v1/reranker-models/`

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/reranker-models/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/reranker-models/", config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/reranker-models/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->get("https://api.maiagent.ai/api/v1/reranker-models/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
[
  {
    "id": string (uuid)
    "name": string
    "isDefault"?: boolean // 非必填
    "icon":
    {
      "id": string (uuid)
      "name": string
      "image": string (uri)
    }
```

```
  }
]
```

回應範例值

```
[
  {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應字串",
    "isDefault": false,
    "icon": {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "回應字串",
      "image": "https://example.com/file.jpg"
    }
  }
]
```

列出大型語言模型

GET `/api/v1/large-language-models/`

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/large-language-models/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/large-language-models/", config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/large-language-models/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->get("https://api.maiagent.ai/api/v1/large-language-models/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
[
  {
    "id": string (uuid)
    "name": string
    "retiresAt": string (date) // 供應商退役日；到期後每日排程會把助理換到 replacement 並停用此模型。null 表示未排定退役
    "replacement":  // 退役後接手的模型（id 與 name）；null 表示未指定，到期時不會自動搬移
    {
      "id": string (uuid)
      "name": string
    }
    "contextWindow"?: integer // Used only by OpenAILike or Ollama models; other models
```

```
ignore this value. (非必填)
    "isDefault"?: boolean // 非必填
    "provider": string
    "servedBy": string // Who runs inference, which is where prompts are sent (for
example OpenRouter, AWS Bedrock); models on a customer credential show Customer
credential.
    "icon":
    {
      "id": string (uuid)
      "name": string
      "image": string (uri)
    }
    "isMultiModalSupport"?: boolean // 非必填
    "isFunctionalCallingAvailable": boolean // Deprecated: same value as
isToolCallingAvailable; use isToolCallingAvailable.
    "isToolCallingAvailable"?: boolean // 非必填
    "isTemplateAvailable": boolean
    "isOutputFormatAvailable": boolean
    "isThinkingAvailable"?: boolean // When checked, this model shows the thinking depth
setting and requests carry thinking parameters (thinking_budget for Gemini,
reasoning_effort for OpenAI-compatible hosts). Unchecking stops sending them; saved
thinking settings are kept but have no effect. Check only for models known to support
thinking parameters, otherwise the provider returns 4xx. (非必填)
    "defaultThinkingLevel"?: // 可能有不同的類型 (非必填)
    string (enum: off, minimal, low, medium, high, xhigh, max) // The thinking level sent
when neither the conversation nor the assistant sets one. Empty sends no thinking
parameter, so the provider default applies. A level the model does not accept is lowered
to the nearest one it does. Takes effect only when Supports Thinking is checked.

* `off` - off
* `minimal` - minimal
* `low` - low
* `medium` - medium
* `high` - high
* `xhigh` - xhigh
* `max` - max (非必填)
    "thinkingConfigSchema": { // 此模型的思考設定表單；null 表示此模型沒有思考設定
    {
      "type"?: string // 表單類型，固定為 reasoning_effort (非必填)
      "fields"?: object // reasoning_effort 欄位：options 列出此模型接受的思考等級（由弱到強），
default 固定為 null (非必填)
      "canDisable"?: boolean // 此模型能否關閉思考；true 時 options 含 off (非必填)
      "unsetBehavior"?: string (enum: off, model_default) // 對話與助理都沒設思考等級時的實際行
為：off＝不思考（最快）；model_default＝模型自行思考，或平台預設等級會開啟思考 (非必填)
      "unsetLevel"?: string // 沒設等級時平台實際送出的等級；null 表示不送思考參數，交給模型自身預設
(非必填)
    }
    }
    "replyMode": [
      string
    ]
    "outputMode": [
      string
```

```
    ]
    "agentMode": [
      string
    ]
    "maxTokens"?: integer // 非必填
    "minTokens": integer
    "isCustomModel": boolean // Whether the row is organization-owned (materialized from
an AI Gateway custom model).
    "originCountry": string // ISO 3166-1 alpha-2 code of the country the model developer
is based in (e.g. US, CN, FR); null when unknown. Follows the model, not who runs
inference.
    "originRegion": // 可能有不同的類型
    string (enum: cn, us, other) // Origin group for labels and filters: cn / us / other;
null when unknown (no label).

* `cn` - China
* `us` - United States
* `other` - Other countries
    "originRegionDisplay": string // Translated origin group name (e.g. 中國／美國／其他國
家); null when unknown.
  }
]
```

回應範例值

```
[
  {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應字串",
    "retiresAt": "回應字串",
    "replacement": {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "回應字串"
    },
    "contextWindow": 456,
    "isDefault": false,
    "provider": "回應字串",
    "servedBy": "回應字串",
    "icon": {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "回應字串",
      "image": "https://example.com/file.jpg"
    },
    "isMultiModalSupport": false,
    "isFunctionalCallingAvailable": false,
    "isToolCallingAvailable": false,
    "isTemplateAvailable": false,
    "isOutputFormatAvailable": false,
    "isThinkingAvailable": false,
    "defaultThinkingLevel": "off",
    "thinkingConfigSchema": {
      "id": "550e8400-e29b-41d4-a716-446655440000",
```

```
      "name": "回應範例名稱",
      "description": "回應範例描述"
    },
    "replyMode": [
      "回應字串"
    ],
    "outputMode": [
      "回應字串"
    ],
    "agentMode": [
      "回應字串"
    ],
    "maxTokens": 456,
    "minTokens": 456,
    "isCustomModel": false,
    "originCountry": "回應字串",
    "originRegion": "cn",
    "originRegionDisplay": "回應字串"
  }
]
```


取得 AI 助理列表

`GET` `/api/v1/chatbots/`

參數

參數名稱	必填	類型	說明
`createdByMember`	X	string	建立者篩選：本組織成員 id（成員名冊回傳的 id，含已停用成員），只回該成員建立的 AI 助理
`largeLanguageModel`	X	string	
`page`	X	integer	A page number within the paginated result set.
`pageSize`	X	integer	Number of results to return per page.
`pagination`	X	string	是否分頁 (true/false)
`query`	X	string	
`replyMode`	X	string	

`source`	X	string	`self_built`: self_built ; `built_in`: built_in ; `all`: all;

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X GET "

  -H "Authorization: Api-Key YOUR_API_KEY"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get(" config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```python
import requests

url = "
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->get(" [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
{
  "count": integer
  "next"?: string (uri) // 非必填
  "previous"?: string (uri) // 非必填
  "results": [
    {
      "id": string (uuid)
      "name": string // Chatbot name. In Agent mode it carries semantic meaning; in other
modes it only distinguishes chatbots.
      "groups": [
        {
          "id": string (uuid)
          "name": string
        }
      ]
      "largeLanguageModel": { // LLM 的基礎序列化器：識別欄位加上退役資訊，供前端在模型即將退役時提
示。
      {
        "id": string (uuid)
        "name": string
        "retiresAt": string (date) // 供應商退役日；到期後每日排程會把助理換到 replacement 並停用
此模型。null 表示未排定退役
        "replacement":  // 退役後接手的模型（id 與 name）；null 表示未指定，到期時不會自動搬移
        {
          "id": string (uuid)
          "name": string
        }
      }
      }
      "embeddingModel": {
      {
        "id": string (uuid)
        "name": string
        "isDefault"?: boolean // 非必填
        "isMultimodal"?: boolean // Whether this embedding model supports multimodal
(text + image) embeddings (非必填)
        "icon":
        {
          "id": string (uuid)
          "name": string
          "image": string (uri)
        }
      }
```

```
      }
      "rerankerModel": {
      {
        "id": string (uuid)
        "name": string
        "isDefault"?: boolean // 非必填
        "icon":
        {
          "id": string (uuid)
          "name": string
          "image": string (uri)
        }
      }
      }
      "knowledgeBases": [
        {
          "id": string (uuid)
          "name": string
        }
      ]
      "tools": [
        {
          "id": string (uuid)
          "name": string
          "description": string
          "displayName": string
          "toolType": string
        }
      ]
      "skills": [
        {
          "id": string (uuid)
          "name": string
          "description": string
        }
      ]
      "agentMode"?:  // Agent mode: Canvas or Normal. Canvas mode generates answers on a
canvas; Normal mode generates regular answers.

* `normal` - 正常
* `canvas` - 畫布
* `team` - 團隊 (非必填)
      {
      }
      "replyMode"?:  // Reply mode: Normal, Template, Hybrid, or Agent.

* `normal` - 正常
* `template` - 模板
* `hybrid` - 混合
* `agent` - 代理 (非必填)
      {
      }
      "updatedAt": string (timestamp)
```

```
      "enableEvaluation"?: boolean // 非必填
      "enableInlineCitations"?: boolean // Enables inline citations, inserting citation markers such as [1][2] into responses. (非必填)
      "enableToolSearching"?: boolean // Enables dynamic tool search, letting the agent discover and load tools via tool_searching_tool. (非必填)
      "enableCodeInterpreter"?: boolean // When enabled, provides the Code Interpreter tool to run code in an isolated container. (非必填)
      "enableBrowserTool"?: boolean // Enable browser automation tool for web tasks (非必填)
      "enableImageSearch"?: boolean // Provide the image_search tool when any attached knowledge base uses a multimodal embedding model. Disable to remove the tool entirely. (非必填)
      "numberOfRetrievedChunks"?: integer // 非必填
      "useFullRetrievalRange"?: boolean // When enabled, the retrieval tool ignores the top_k set by the LLM and returns the full reranker result up to the maximum number of retrieved chunks. Useful for knowledge bases with long tables that need a wider retrieval range. (非必填)
      "isMultimodalLlm": boolean // Return whether the chatbot's LLM supports multimodal.
      "voiceConfig":
      {
        "enabled"?: boolean // Whether this chatbot can be used as a voice agent. Checked by every conversation platform (WebChat, SIP phone, admin/marketplace voice test) instead of a per-platform toggle. (非必填)
      }
      "createdBy":
      {
        "id": string (uuid)
        "name": string
      }
      "isLocked"?: boolean // Locked instance: config follows the official version; only the dedicated KB can be modified (非必填)
      "sourceBuildInAgent"?: string (uuid) // Points to the official Build-in Agent blueprint when instantiated by a rental (非必填)
      "canUpdate": boolean // Return whether the current user can update this resource.
      "canDelete": boolean // Return whether the current user can delete this resource.
      "team":
      {
        "id": string (uuid)
        "name": string
      }
    }
  ]
}
```

回應範例值

```
{
  "count": 123,
  "next": "http://api.example.org/accounts/?page=4",
  "previous": "http://api.example.org/accounts/?page=2",
  "results": [
    {
```

```
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "name": "回應字串",
  "groups": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "回應字串"
    }
  ],
  "largeLanguageModel": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應字串",
    "retiresAt": "回應字串",
    "replacement": {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "回應字串"
    }
  },
  "embeddingModel": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應字串",
    "isDefault": false,
    "isMultimodal": false,
    "icon": {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "回應字串",
      "image": "https://example.com/file.jpg"
    }
  },
  "rerankerModel": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應字串",
    "isDefault": false,
    "icon": {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "回應字串",
      "image": "https://example.com/file.jpg"
    }
  },
  "knowledgeBases": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "回應字串"
    }
  ],
  "tools": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "回應字串",
      "description": "回應字串",
      "displayName": "回應字串",
      "toolType": "回應字串"
    }
  ],
```

```
      "skills": [
        {
          "id": "550e8400-e29b-41d4-a716-446655440000",
          "name": "回應字串",
          "description": "回應字串"
        }
      ],
      "agentMode": {},
      "replyMode": {},
      "updatedAt": "回應字串",
      "enableEvaluation": false,
      "enableInlineCitations": false,
      "enableToolSearching": false,
      "enableCodeInterpreter": false,
      "enableBrowserTool": false,
      "enableImageSearch": false,
      "numberOfRetrievedChunks": 456,
      "useFullRetrievalRange": false,
      "isMultimodalLlm": false,
      "voiceConfig": {
        "enabled": false
      },
      "createdBy": {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "name": "回應字串"
      },
      "isLocked": false,
      "sourceBuildInAgent": "550e8400-e29b-41d4-a716-446655440000",
      "canUpdate": false,
      "canDelete": false,
      "team": {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "name": "回應字串"
      }
    }
  ]
}
```


取得特定 AI 助理

GET `/api/v1/chatbots/{id}`

參數

參數名稱	必填	類型	說明
id	V	string	

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X GET "

  -H "Authorization: Api-Key YOUR_API_KEY"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get(" config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```python
import requests

url = "
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->get(" [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
{
  "id": string (uuid)
  "name": string // Chatbot name. In Agent mode it carries semantic meaning; in other
modes it only distinguishes chatbots.
  "largeLanguageModel": string (uuid) // 機器人使用的大型語言模型，用於生成回答（含組織自建的 AI
Gateway 模型）
  "llm":  // 綁定模型的 id、name 與退役資訊，直接讀取 FK，即使該模型已被組織停用仍會回傳
  {
    "id": string (uuid)
    "name": string
    "retiresAt": string (date) // 供應商退役日；到期後每日排程會把助理換到 replacement 並停用此模
型。null 表示未排定退役
    "replacement":  // 退役後接手的模型（id 與 name）；null 表示未指定，到期時不會自動搬移
    {
      "id": string (uuid)
      "name": string
    }
  }
  "embeddingModel"?: string (uuid) // 用於向量化文本的嵌入模型，非必填項目 (非必填)
  "rerankerModel"?: string (uuid) // 用於重新排序的模型，非必填項目 (非必填)
  "instructions"?: string // Role instructions describing the chatbot's role and
behavior. (非必填)
  "knowledgeBases"?: [ // 機器人可存取的知識庫列表 (非必填)
    {
      "id": string (uuid)
      "name": string
    }
  ]
  "databases"?: [ // 機器人可存取的 SQL 資料庫列表（用於 Text-to-SQL 功能） (非必填)
    {
      "id": string (uuid)
      "name": string
    }
  ]
  "updatedAt": string (timestamp)
  "organization"?: string (uuid) // 機器人所屬的組織，如果為空則為個人機器人 (非必填)
  "replyMode"?:  // 回覆模式：一般回覆或串流回覆

* `normal` - 正常
* `template` - 模板
* `hybrid` - 混合
* `agent` - 代理 (非必填)
  {
```

```
  }
  "template"?: string // Template used by Template and Hybrid modes. (非必填)
  "unanswerableTemplate"?: string // Template used by Template and Hybrid modes when the
question cannot be answered. (非必填)
  "totalWordsCount"?: integer (int64) // Accumulated total word count used. (非必填)
  "outputMode"?:  // 輸出模式：文字、表格或自定義格式

* `text` - 文字
* `json_schema` - JSON Schema (非必填)
  {
  }
  "rawOutputFormat"?: object // 自定義輸出格式的JSON結構定義 (非必填)
  "groups"?: [ // 機器人可存取的群組列表 (非必填)
    {
      "id": string (uuid)
      "name": string
    }
  ]
  "tools"?: [ // 機器人可使用的工具列表 (非必填)
    {
      "id": string (uuid)
      "name": string
      "description": string
      "displayName": string
      "toolType": string
    }
  ]
  "skills"?: [ // 機器人關聯的技能列表 (非必填)
    {
      "id": string (uuid)
      "name": string
      "description": string
    }
  ]
  "connectors"?: [ // Connectors associated with this chatbot, gating per-contact OAuth
authorization (非必填)
    {
      "id": string (uuid)
      "name": string
    }
  ]
  "agentMode"?:  // 代理模式：一般、SQL或工作流程模式

* `normal` - 正常
* `canvas` - 畫布
* `team` - 團隊 (非必填)
  {
  }
  "numberOfRetrievedChunks"?: integer // 提取的參考資料數量，預設為 12，最小值為 1 (非必填)
  "defaultLabelRelations"?: object // 助理層級的預設知識庫標籤過濾條件，格式同
query_metadata.label_relations；null 表示不過濾。僅在呼叫端未帶 query_metadata 時作為最低優先序兜
底套用。 (非必填)
  "useFullRetrievalRange"?: boolean // 啟用後忽略 LLM 的 top_k 截斷，回傳完整 reranker 結果
```

```
(非必填)
  "enableEvaluation"?: boolean // 非必填
  "enableInlineCitations"?: boolean // Enables inline citations, inserting citation
markers such as [1][2] into responses. (非必填)
  "enableCodeInterpreter"?: boolean // When enabled, provides the Code Interpreter tool
to run code in an isolated container. (非必填)
  "enableBrowserTool"?: boolean // Enable browser automation tool for web tasks (非必填)
  "enableImageSearch"?: boolean // Provide the image_search tool when any attached
knowledge base uses a multimodal embedding model. Disable to remove the tool entirely.
(非必填)
  "enableClaudeStreamRetry"?: boolean // When a Claude streaming call stalls (first-chunk
or mid-stream), abort and re-issue the call once in non-streaming mode. Mid-stream
retries send a reset signal so the client discards any partial output already rendered.
Each retry incurs a second billing for the same prompt. (非必填)
  "customMaxLlmOutputTokens"?: integer // 自訂最大 LLM 輸出 token 數，最小值為 512 (非必填)
  "voiceConfig"?: { // 非必填
  {
    "enabled"?: boolean // Whether this chatbot can be used as a voice agent. Checked by
every conversation platform (WebChat, SIP phone, admin/marketplace voice test) instead of
a per-platform toggle. (非必填)
    "voiceAgentType"?: string (uuid) // Voice agent mode type. (非必填)
    "sttProvider"?: string (uuid) // Speech-to-Text service provider. (非必填)
    "sttConfig"?: object // STT configuration parameters (JSON). (非必填)
    "ttsProvider"?: string (uuid) // Text-to-Speech service provider. (非必填)
    "ttsConfig"?: object // TTS configuration parameters (JSON). (非必填)
    "realtimeProvider"?: string (uuid) // Realtime end-to-end voice model provider. (非必
填)
    "realtimeConfig"?: object // Realtime configuration parameters (JSON). (非必填)
    "realtimeInstructions"?: string // Prompt dedicated to the realtime voice session;
falls back to chatbot instructions when empty (非必填)
    "turnHandling"?: object // Turn-taking and interruption settings for the voice agent.
(非必填)
    "enableVoiceReply"?: boolean // When disabled, the voice agent replies in text only
and does not speak (非必填)
  }
  }
  "thinkingConfig"?: object // 思考等級：null（模型預設）或 {"reasoning_effort":
"off|minimal|low|medium|high|xhigh|max"} (非必填)
  "enableToolSearching"?: boolean // 啟用動態工具搜尋功能，允許 agent 透過 tool_searching_tool
動態發現和加載工具 (非必填)
  "maxAgentIterations"?: integer // Maximum number of iterations for AgentWorkflow (1-
100, default: 20) (非必填)
  "agentTimeoutSeconds"?: integer // Timeout in seconds for AgentWorkflow execution (30-
1200, default: 600) (非必填)
  "agentTimeoutMessage"?: string // Custom user-facing message shown when AgentWorkflow
times out (max 500 chars). Leave empty to use the system default. (非必填)
  "requireTextWithFlexCards"?: boolean // When enabled, a turn that would end with only
Flex Message cards and no text for the user is re-issued to the LLM once, asking it to
write the text first and then send the card. Each retry incurs a second billing for the
same prompt. (非必填)
  "isMultimodalLlm": boolean // Whether the chatbot LLM supports multimodal (read-only)
  "enableSizeBasedToolResultTruncation"?: boolean // When enabled, tool results exceeding
the character threshold are kept as head+tail (with the identifiers found in the cut
```

```
part) when written to conversation history; knowledge base, SQL and conversation search results keep their 100-character cut either way. Reduces memory bloat from large tool outputs (code interpreter bash stdout, web search results, etc.). (非必填)
  "toolResultMaxChars"?: integer // Character threshold for size-based tool result truncation (500-50000). Only effective when enable_size_based_tool_result_truncation is True. (非必填)
  "enableVectorMemory"?: boolean // When enabled, archived messages are vectorized and processed by fact extraction for semantic retrieval (existing behavior). When disabled, archived messages are discarded and only the active chat history window is used for multi-turn context. (非必填)
  "longTermMemoryTopK"?: integer // 長期記憶每次檢索取回的記憶節點數（向量檢索的 similarity_top_k），預設為 10，範圍 1–50 (非必填)
  "enableCrossConversationSearch"?: boolean // When enabled, the conversation history tools also reach this contact's other conversations in the same inbox, within the lookback window. When disabled, they only reach the current conversation. (非必填)
  "crossConversationLookbackDays"?: integer // How far back cross-conversation search may reach, measured from each conversation's last message (1-365 days). Leave empty to fall back to 90 days. Only effective when enable_cross_conversation_search is True. (非必填)
  "useGatewayFallback"?: boolean // When enabled, use the fallback group instead of the single LLM (非必填)
  "gatewayFallbackGroup"?: string (uuid) // 非必填
  "enableSearchMessagesTool"?: boolean // Allow the AI to search past messages in the current conversation. (非必填)
  "enableGetMessageContextTool"?: boolean // Allow the AI to retrieve messages surrounding a specific message for context. (非必填)
  "enableReadAttachmentFullTextTool"?: boolean // Allow the AI to read the full text of plain-text attachments. AGENT mode only. (非必填)
  "enableParseAttachmentContentTool"?: boolean // Allow the AI to parse PDF, Office, audio, and other attachments. AGENT mode only. (非必填)
  "enableListAvailableParsersTool"?: boolean // Allow the AI to list available parsers and their capabilities. AGENT mode only. (非必填)
  "enableGetDownloadLinkTool"?: boolean // Allow the AI to generate shareable download links for produced content. AGENT mode only. (非必填)
  "isLocked": boolean // Locked instance: config follows the official version; only the dedicated KB can be modified
  "sourceBuildInAgent": string (uuid) // Points to the official Build-in Agent blueprint when instantiated by a rental
  "canUpdate": boolean // Return whether the current user can update this resource.
  "canDelete": boolean // Return whether the current user can delete this resource.
  "team":
  {
    "id": string (uuid)
    "name": string
  }
  "webChatIsActive"?: boolean // Optional, create only. Whether the web widget channel starts active. Omitted or null: follows the organization's default for new chatbot channels (inactive unless a platform admin turned it on). Ignored on update; change an existing channel from its channel settings instead. (非必填)
  "apiIsActive"?: boolean // Optional, create only. Whether the API channel starts active. Omitted or null: follows the organization's default for new chatbot channels (inactive unless a platform admin turned it on). Ignored on update; change an existing channel from its channel settings instead. The backstage (admin) channel always starts active and cannot be set here. (非必填)
```

```
  "fileWorkspaceMode"?:  // File workspace mode in Work internal conversations: none,
bound or user_mount.

* `none` - None
* `bound` - Bound workspace
* `user_mount` - User mount (非必填)
  {
  }
  "fileWorkspaceFolder"?: string (uuid) // The bound workspace (folder id); required when
the mode is bound, cleared otherwise. (非必填)
  "fileWorkspaceStatus": object // Read-only. {"folder": {"id", "name"} | null, "state":
"ok" | "missing" | "builder_lost_edit" | null}
  "fileWorkspaceAvailable": boolean // Read-only. Whether the organization has the file
library and this agent can configure a file workspace.
}
```

回應範例值

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "name": "回應字串",
  "largeLanguageModel": "550e8400-e29b-41d4-a716-446655440000",
  "llm": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應字串",
    "retiresAt": "回應字串",
    "replacement": {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "回應字串"
    }
  },
  "embeddingModel": "550e8400-e29b-41d4-a716-446655440000",
  "rerankerModel": "550e8400-e29b-41d4-a716-446655440000",
  "instructions": "回應字串",
  "knowledgeBases": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "回應字串"
    }
  ],
  "databases": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "回應字串"
    }
  ],
  "updatedAt": "回應字串",
  "organization": "550e8400-e29b-41d4-a716-446655440000",
  "replyMode": {},
  "template": "回應字串",
  "unanswerableTemplate": "回應字串",
  "totalWordsCount": 456,
```

```
  "outputMode": {},
  "rawOutputFormat": null,
  "groups": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "回應字串"
    }
  ],
  "tools": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "回應字串",
      "description": "回應字串",
      "displayName": "回應字串",
      "toolType": "回應字串"
    }
  ],
  "skills": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "回應字串",
      "description": "回應字串"
    }
  ],
  "connectors": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "回應字串"
    }
  ],
  "agentMode": {},
  "numberOfRetrievedChunks": 456,
  "defaultLabelRelations": null,
  "useFullRetrievalRange": false,
  "enableEvaluation": false,
  "enableInlineCitations": false,
  "enableCodeInterpreter": false,
  "enableBrowserTool": false,
  "enableImageSearch": false,
  "enableClaudeStreamRetry": false,
  "customMaxLlmOutputTokens": 456,
  "voiceConfig": {
    "enabled": false,
    "voiceAgentType": "550e8400-e29b-41d4-a716-446655440000",
    "sttProvider": "550e8400-e29b-41d4-a716-446655440000",
    "sttConfig": null,
    "ttsProvider": "550e8400-e29b-41d4-a716-446655440000",
    "ttsConfig": null,
    "realtimeProvider": "550e8400-e29b-41d4-a716-446655440000",
    "realtimeConfig": null,
    "realtimeInstructions": "回應字串",
    "turnHandling": null,
    "enableVoiceReply": false
```

```
  },
  "thinkingConfig": null,
  "enableToolSearching": false,
  "maxAgentIterations": 456,
  "agentTimeoutSeconds": 456,
  "agentTimeoutMessage": "回應字串",
  "requireTextWithFlexCards": false,
  "isMultimodalLlm": false,
  "enableSizeBasedToolResultTruncation": false,
  "toolResultMaxChars": 456,
  "enableVectorMemory": false,
  "longTermMemoryTopK": 456,
  "enableCrossConversationSearch": false,
  "crossConversationLookbackDays": 456,
  "useGatewayFallback": false,
  "gatewayFallbackGroup": "550e8400-e29b-41d4-a716-446655440000",
  "enableSearchMessagesTool": false,
  "enableGetMessageContextTool": false,
  "enableReadAttachmentFullTextTool": false,
  "enableParseAttachmentContentTool": false,
  "enableListAvailableParsersTool": false,
  "enableGetDownloadLinkTool": false,
  "isLocked": false,
  "sourceBuildInAgent": "550e8400-e29b-41d4-a716-446655440000",
  "canUpdate": false,
  "canDelete": false,
  "team": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應字串"
  },
  "webChatIsActive": false,
  "apiIsActive": false,
  "fileWorkspaceMode": {},
  "fileWorkspaceFolder": "550e8400-e29b-41d4-a716-446655440000",
  "fileWorkspaceStatus": {
    "name": "example.pdf",
    "content": "base64encoded_content",
    "contentType": "application/pdf"
  },
  "fileWorkspaceAvailable": false
}
```


更新 AI 助理

PUT `/api/v1/chatbots/{id}`

參數

參數名稱	必填	類型	說明
`id`	V	string	

請求內容

請求參數

欄位	類型	必填	說明
name	string	是	Chatbot name. In Agent mode it carries semantic meaning; in other modes it only distinguishes chatbots.
largeLanguageModel	string (uuid)	是	機器人使用的大型語言模型，用於生成回答（含組織自建的 AI Gateway 模型）
embeddingModel	string (uuid)	否	用於向量化文本的嵌入模型，非必填項目
rerankerModel	string (uuid)	否	用於重新排序的模型，非必填項目
instructions	string	否	Role instructions describing the chatbot's role and behavior.
knowledgeBases	array[IdName]	否	機器人可存取的知識庫列表
databases	array[IdName]	否	機器人可存取的 SQL 資料庫列表（用於 Text-to-SQL 功能）
organization	string (uuid)	否	機器人所屬的組織，如果為空則為個人機器人
replyMode	object	否	回覆模式：一般回覆或串流回覆 `normal`：正常；`template`：模板；`hybrid`：混合；`agent`：代理;
template	string	否	Template used by Template and Hybrid modes.
unanswerableTemplate	string	否	Template used by Template and Hybrid modes when the question cannot be answered.
totalWordsCount	integer (int64)	否	Accumulated total word count used.
outputMode	object	否	輸出模式：文字、表格或自定義格式 `text`：文字；`json_schema`：JSON Schema;

欄位	類型	必填	說明
rawOutputFormat	object	否	自定義輸出格式的JSON結構定義
groups	array[IdName]	否	機器人可存取的群組列表
tools	array[ToolSummary]	否	機器人可使用的工具列表
skills	array[SkillSummary]	否	機器人關聯的技能列表
connectors	array[IdName]	否	Connectors associated with this chatbot, gating per-contact OAuth authorization
agentMode	object	否	代理模式：一般、SQL或工作流程模式 `normal`：正常；`canvas`：畫布；`team`：團隊;
numberOfRetrievedChunks	integer	否	提取的參考資料數量，預設為 12，最小值為 1
defaultLabelRelations	object	否	助理層級的預設知識庫標籤過濾條件，格式同 query_metadata.label_relations；null 表示不過濾。僅在呼叫端未帶 query_metadata 時作為最低優先序兜底套用。
useFullRetrievalRange	boolean	否	啟用後忽略 LLM 的 top_k 截斷，回傳完整 reranker 結果
enableEvaluation	boolean	否	
enableInlineCitations	boolean	否	Enables inline citations, inserting citation markers such as [1][2] into responses.
enableCodeInterpreter	boolean	否	When enabled, provides the Code Interpreter tool to run code in an isolated container.
enableBrowserTool	boolean	否	Enable browser automation tool for web tasks
enableImageSearch	boolean	否	Provide the image_search tool when any attached knowledge base uses a multimodal embedding model. Disable to remove the tool entirely.
enableClaudeStreamRetry	boolean	否	When a Claude streaming call stalls (first-chunk or mid-stream), abort and re-issue the call once in non-streaming mode. Mid-stream retries send a reset signal so the client discards any partial outpu...
customMaxLlmOutputTokens	integer	否	自訂最大 LLM 輸出 token 數，最小值為 512
voiceConfig	object	否	

欄位	類型	必填	說明
voiceConfig.enabled	boolean	否	Whether this chatbot can be used as a voice agent. Checked by every conversation platform (WebChat, SIP phone, admin/marketplace voice test) instead of a per-platform toggle.
voiceConfig.voiceAgentType	string (uuid)	否	Voice agent mode type.
voiceConfig.sttProvider	string (uuid)	否	Speech-to-Text service provider.
voiceConfig.sttConfig	object	否	STT configuration parameters (JSON).
voiceConfig.ttsProvider	string (uuid)	否	Text-to-Speech service provider.
voiceConfig.ttsConfig	object	否	TTS configuration parameters (JSON).
voiceConfig.realtimeProvider	string (uuid)	否	Realtime end-to-end voice model provider.
voiceConfig.realtimeConfig	object	否	Realtime configuration parameters (JSON).
voiceConfig.realtimeInstructions	string	否	Prompt dedicated to the realtime voice session; falls back to chatbot instructions when empty
voiceConfig.turnHandling	object	否	Turn-taking and interruption settings for the voice agent.
voiceConfig.enableVoiceReply	boolean	否	When disabled, the voice agent replies in text only and does not speak
thinkingConfig	object	否	思考等級：null（模型預設）或 {"reasoning_effort": "off
enableToolSearching	boolean	否	啟用動態工具搜尋功能，允許 agent 透過 tool_searching_tool 動態發現和加載工具
maxAgentIterations	integer	否	Maximum number of iterations for AgentWorkflow (1-100, default: 20)
agentTimeoutSeconds	integer	否	Timeout in seconds for AgentWorkflow execution (30-1200, default: 600)
agentTimeoutMessage	string	否	Custom user-facing message shown when AgentWorkflow times out (max 500 chars). Leave empty to use the system default.
requireTextWithFlexCards	boolean	否	When enabled, a turn that would end with only Flex Message cards and no text for the user is re-issued to the LLM once, asking it to write the text first and then send the card. Each retry incurs a se...
enableSizeBasedToolResultTruncation	boolean	否	When enabled, tool results exceeding the character threshold are kept as head+tail

欄位	類型	必填	說明
			(with the identifiers found in the cut part) when written to conversation history; knowledge base, SQL and conversati...
toolResultMaxChars	integer	否	Character threshold for size-based tool result truncation (500-50000). Only effective when enable_size_based_tool_result_truncation is True.
enableVectorMemory	boolean	否	When enabled, archived messages are vectorized and processed by fact extraction for semantic retrieval (existing behavior). When disabled, archived messages are discarded and only the active chat hist...
longTermMemoryTopK	integer	否	長期記憶每次檢索取回的記憶節點數（向量檢索的 similarity_top_k），預設為 10，範圍 1–50
enableCrossConversationSearch	boolean	否	When enabled, the conversation history tools also reach this contact's other conversations in the same inbox, within the lookback window. When disabled, they only reach the current conversation.
crossConversationLookbackDays	integer	否	How far back cross-conversation search may reach, measured from each conversation's last message (1-365 days). Leave empty to fall back to 90 days. Only effective when enable_cross_conversation_search...
useGatewayFallback	boolean	否	When enabled, use the fallback group instead of the single LLM
gatewayFallbackGroup	string (uuid)	否	
enableSearchMessagesTool	boolean	否	Allow the AI to search past messages in the current conversation.
enableGetMessageContextTool	boolean	否	Allow the AI to retrieve messages surrounding a specific message for context.
enableReadAttachmentFullTextTool	boolean	否	Allow the AI to read the full text of plain-text attachments. AGENT mode only.
enableParseAttachmentContentTool	boolean	否	Allow the AI to parse PDF, Office, audio, and other attachments. AGENT mode only.

欄位	類型	必填	說明
enableListAvailableParsersTool	boolean	否	Allow the AI to list available parsers and their capabilities. AGENT mode only.
enableGetDownloadLinkTool	boolean	否	Allow the AI to generate shareable download links for produced content. AGENT mode only.
webChatIsActive	boolean	否	Optional, create only. Whether the web widget channel starts active. Omitted or null: follows the organization's default for new chatbot channels (inactive unless a platform admin turned it on). Ignor...
apiIsActive	boolean	否	Optional, create only. Whether the API channel starts active. Omitted or null: follows the organization's default for new chatbot channels (inactive unless a platform admin turned it on). Ignored on u...
fileWorkspaceMode	object	否	File workspace mode in Work internal conversations: none, bound or user_mount. `none` : None ; `bound` : Bound workspace ; `user_mount` : User mount;
fileWorkspaceFolder	string (uuid)	否	The bound workspace (folder id); required when the mode is bound, cleared otherwise.

請求結構範例

```
{
  "name": string // Chatbot name. In Agent mode it carries semantic meaning; in other modes it only distinguishes chatbots.
  "largeLanguageModel": string (uuid) // 機器人使用的大型語言模型，用於生成回答（含組織自建的 AI Gateway 模型）
  "embeddingModel"?: string (uuid) // 用於向量化文本的嵌入模型，非必填項目 (非必填)
  "rerankerModel"?: string (uuid) // 用於重新排序的模型，非必填項目 (非必填)
  "instructions"?: string // Role instructions describing the chatbot's role and behavior. (非必填)
  "knowledgeBases"?: [ // 機器人可存取的知識庫列表 (非必填)
    {
      "id": string (uuid)
    }
  ]
  "databases"?: [ // 機器人可存取的 SQL 資料庫列表（用於 Text-to-SQL 功能） (非必填)
    {
      "id": string (uuid)
    }
  ]
```

```
  "organization"?: string (uuid) // 機器人所屬的組織，如果為空則為個人機器人 (非必填)
  "replyMode"?:  // 回覆模式：一般回覆或串流回覆

* `normal` - 正常
* `template` - 模板
* `hybrid` - 混合
* `agent` - 代理 (非必填)
  {
  }
  "template"?: string // Template used by Template and Hybrid modes. (非必填)
  "unanswerableTemplate"?: string // Template used by Template and Hybrid modes when the
question cannot be answered. (非必填)
  "totalWordsCount"?: integer (int64) // Accumulated total word count used. (非必填)
  "outputMode"?:  // 輸出模式：文字、表格或自定義格式

* `text` - 文字
* `json_schema` - JSON Schema (非必填)
  {
  }
  "rawOutputFormat"?: object // 自定義輸出格式的JSON結構定義 (非必填)
  "groups"?: [ // 機器人可存取的群組列表 (非必填)
    {
      "id": string (uuid)
    }
  ]
  "tools"?: [ // 機器人可使用的工具列表 (非必填)
    {
      "id": string (uuid)
    }
  ]
  "skills"?: [ // 機器人關聯的技能列表 (非必填)
    {
      "id": string (uuid)
    }
  ]
  "connectors"?: [ // Connectors associated with this chatbot, gating per-contact OAuth
authorization (非必填)
    {
      "id": string (uuid)
    }
  ]
  "agentMode"?:  // 代理模式：一般、SQL或工作流程模式

* `normal` - 正常
* `canvas` - 畫布
* `team` - 團隊 (非必填)
  {
  }
  "numberOfRetrievedChunks"?: integer // 提取的參考資料數量，預設為 12，最小值為 1 (非必填)
  "defaultLabelRelations"?: object // 助理層級的預設知識庫標籤過濾條件，格式同
query_metadata.label_relations；null 表示不過濾。僅在呼叫端未帶 query_metadata 時作為最低優先序兜
底套用。 (非必填)
  "useFullRetrievalRange"?: boolean // 啟用後忽略 LLM 的 top_k 截斷，回傳完整 reranker 結果
```

```
(非必填)
  "enableEvaluation"?: boolean // 非必填
  "enableInlineCitations"?: boolean // Enables inline citations, inserting citation
markers such as [1][2] into responses. (非必填)
  "enableCodeInterpreter"?: boolean // When enabled, provides the Code Interpreter tool
to run code in an isolated container. (非必填)
  "enableBrowserTool"?: boolean // Enable browser automation tool for web tasks (非必填)
  "enableImageSearch"?: boolean // Provide the image_search tool when any attached
knowledge base uses a multimodal embedding model. Disable to remove the tool entirely.
(非必填)
  "enableClaudeStreamRetry"?: boolean // When a Claude streaming call stalls (first-chunk
or mid-stream), abort and re-issue the call once in non-streaming mode. Mid-stream
retries send a reset signal so the client discards any partial output already rendered.
Each retry incurs a second billing for the same prompt. (非必填)
  "customMaxLlmOutputTokens"?: integer // 自訂最大 LLM 輸出 token 數，最小值為 512 (非必填)
  "voiceConfig"?: { // 非必填
  {
    "enabled"?: boolean // Whether this chatbot can be used as a voice agent. Checked by
every conversation platform (WebChat, SIP phone, admin/marketplace voice test) instead of
a per-platform toggle. (非必填)
    "voiceAgentType"?: string (uuid) // Voice agent mode type. (非必填)
    "sttProvider"?: string (uuid) // Speech-to-Text service provider. (非必填)
    "sttConfig"?: object // STT configuration parameters (JSON). (非必填)
    "ttsProvider"?: string (uuid) // Text-to-Speech service provider. (非必填)
    "ttsConfig"?: object // TTS configuration parameters (JSON). (非必填)
    "realtimeProvider"?: string (uuid) // Realtime end-to-end voice model provider. (非必
填)
    "realtimeConfig"?: object // Realtime configuration parameters (JSON). (非必填)
    "realtimeInstructions"?: string // Prompt dedicated to the realtime voice session;
falls back to chatbot instructions when empty (非必填)
    "turnHandling"?: object // Turn-taking and interruption settings for the voice agent.
(非必填)
    "enableVoiceReply"?: boolean // When disabled, the voice agent replies in text only
and does not speak (非必填)
  }
  }
  "thinkingConfig"?: object // 思考等級：null（模型預設）或 {"reasoning_effort":
"off|minimal|low|medium|high|xhigh|max"} (非必填)
  "enableToolSearching"?: boolean // 啟用動態工具搜尋功能，允許 agent 透過 tool_searching_tool
動態發現和加載工具 (非必填)
  "maxAgentIterations"?: integer // Maximum number of iterations for AgentWorkflow (1-
100, default: 20) (非必填)
  "agentTimeoutSeconds"?: integer // Timeout in seconds for AgentWorkflow execution (30-
1200, default: 600) (非必填)
  "agentTimeoutMessage"?: string // Custom user-facing message shown when AgentWorkflow
times out (max 500 chars). Leave empty to use the system default. (非必填)
  "requireTextWithFlexCards"?: boolean // When enabled, a turn that would end with only
Flex Message cards and no text for the user is re-issued to the LLM once, asking it to
write the text first and then send the card. Each retry incurs a second billing for the
same prompt. (非必填)
  "enableSizeBasedToolResultTruncation"?: boolean // When enabled, tool results exceeding
the character threshold are kept as head+tail (with the identifiers found in the cut
part) when written to conversation history; knowledge base, SQL and conversation search
```

```
results keep their 100-character cut either way. Reduces memory bloat from large tool outputs (code interpreter bash stdout, web search results, etc.). (非必填)
  "toolResultMaxChars"?: integer // Character threshold for size-based tool result truncation (500-50000). Only effective when enable_size_based_tool_result_truncation is True. (非必填)
  "enableVectorMemory"?: boolean // When enabled, archived messages are vectorized and processed by fact extraction for semantic retrieval (existing behavior). When disabled, archived messages are discarded and only the active chat history window is used for multi-turn context. (非必填)
  "longTermMemoryTopK"?: integer // 長期記憶每次檢索取回的記憶節點數（向量檢索的 similarity_top_k），預設為 10，範圍 1–50 (非必填)
  "enableCrossConversationSearch"?: boolean // When enabled, the conversation history tools also reach this contact's other conversations in the same inbox, within the lookback window. When disabled, they only reach the current conversation. (非必填)
  "crossConversationLookbackDays"?: integer // How far back cross-conversation search may reach, measured from each conversation's last message (1-365 days). Leave empty to fall back to 90 days. Only effective when enable_cross_conversation_search is True. (非必填)
  "useGatewayFallback"?: boolean // When enabled, use the fallback group instead of the single LLM (非必填)
  "gatewayFallbackGroup"?: string (uuid) // 非必填
  "enableSearchMessagesTool"?: boolean // Allow the AI to search past messages in the current conversation. (非必填)
  "enableGetMessageContextTool"?: boolean // Allow the AI to retrieve messages surrounding a specific message for context. (非必填)
  "enableReadAttachmentFullTextTool"?: boolean // Allow the AI to read the full text of plain-text attachments. AGENT mode only. (非必填)
  "enableParseAttachmentContentTool"?: boolean // Allow the AI to parse PDF, Office, audio, and other attachments. AGENT mode only. (非必填)
  "enableListAvailableParsersTool"?: boolean // Allow the AI to list available parsers and their capabilities. AGENT mode only. (非必填)
  "enableGetDownloadLinkTool"?: boolean // Allow the AI to generate shareable download links for produced content. AGENT mode only. (非必填)
  "webChatIsActive"?: boolean // Optional, create only. Whether the web widget channel starts active. Omitted or null: follows the organization's default for new chatbot channels (inactive unless a platform admin turned it on). Ignored on update; change an existing channel from its channel settings instead. (非必填)
  "apiIsActive"?: boolean // Optional, create only. Whether the API channel starts active. Omitted or null: follows the organization's default for new chatbot channels (inactive unless a platform admin turned it on). Ignored on update; change an existing channel from its channel settings instead. The backstage (admin) channel always starts active and cannot be set here. (非必填)
  "fileWorkspaceMode"?:  // File workspace mode in Work internal conversations: none, bound or user_mount.

* `none` - None
* `bound` - Bound workspace
* `user_mount` - User mount (非必填)
  {
  }
  "fileWorkspaceFolder"?: string (uuid) // The bound workspace (folder id); required when the mode is bound, cleared otherwise. (非必填)
}
```

請求範例值


```
{
  "name": "範例名稱",
  "largeLanguageModel": "550e8400-e29b-41d4-a716-446655440000",
  "embeddingModel": "550e8400-e29b-41d4-a716-446655440000",
  "rerankerModel": "550e8400-e29b-41d4-a716-446655440000",
  "instructions": "範例字串",
  "knowledgeBases": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000"
    }
  ],
  "databases": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000"
    }
  ],
  "organization": "550e8400-e29b-41d4-a716-446655440000",
  "replyMode": {},
  "template": "範例字串",
  "unanswerableTemplate": "範例字串",
  "totalWordsCount": 123,
  "outputMode": {},
  "rawOutputFormat": null,
  "groups": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000"
    }
  ],
  "tools": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000"
    }
  ],
  "skills": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000"
    }
  ],
  "connectors": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000"
    }
  ],
  "agentMode": {},
  "numberOfRetrievedChunks": 123,
  "defaultLabelRelations": null,
  "useFullRetrievalRange": true,
  "enableEvaluation": true,
  "enableInlineCitations": true,
  "enableCodeInterpreter": true,
  "enableBrowserTool": true,
```

```
  "enableImageSearch": true,
  "enableClaudeStreamRetry": true,
  "customMaxLlmOutputTokens": 123,
  "voiceConfig": {
    "enabled": true,
    "voiceAgentType": "550e8400-e29b-41d4-a716-446655440000",
    "sttProvider": "550e8400-e29b-41d4-a716-446655440000",
    "sttConfig": null,
    "ttsProvider": "550e8400-e29b-41d4-a716-446655440000",
    "ttsConfig": null,
    "realtimeProvider": "550e8400-e29b-41d4-a716-446655440000",
    "realtimeConfig": null,
    "realtimeInstructions": "範例字串",
    "turnHandling": null,
    "enableVoiceReply": true
  },
  "thinkingConfig": null,
  "enableToolSearching": true,
  "maxAgentIterations": 123,
  "agentTimeoutSeconds": 123,
  "agentTimeoutMessage": "範例字串",
  "requireTextWithFlexCards": true,
  "enableSizeBasedToolResultTruncation": true,
  "toolResultMaxChars": 123,
  "enableVectorMemory": true,
  "longTermMemoryTopK": 123,
  "enableCrossConversationSearch": true,
  "crossConversationLookbackDays": 123,
  "useGatewayFallback": true,
  "gatewayFallbackGroup": "550e8400-e29b-41d4-a716-446655440000",
  "enableSearchMessagesTool": true,
  "enableGetMessageContextTool": true,
  "enableReadAttachmentFullTextTool": true,
  "enableParseAttachmentContentTool": true,
  "enableListAvailableParsersTool": true,
  "enableGetDownloadLinkTool": true,
  "webChatIsActive": true,
  "apiIsActive": true,
  "fileWorkspaceMode": {},
  "fileWorkspaceFolder": "550e8400-e29b-41d4-a716-446655440000"
}
```


程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X PUT "

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "name": "範例名稱",
    "largeLanguageModel": "550e8400-e29b-41d4-a716-446655440000",
    "embeddingModel": "550e8400-e29b-41d4-a716-446655440000",
    "rerankerModel": "550e8400-e29b-41d4-a716-446655440000",
    "instructions": "範例字串",
    "knowledgeBases": [
      {
        "id": "550e8400-e29b-41d4-a716-446655440000"
      }
    ],
    "databases": [
      {
        "id": "550e8400-e29b-41d4-a716-446655440000"
      }
    ],
    "organization": "550e8400-e29b-41d4-a716-446655440000",
    "replyMode": {},
    "template": "範例字串",
    "unanswerableTemplate": "範例字串",
    "totalWordsCount": 123,
    "outputMode": {},
    "rawOutputFormat": null,
    "groups": [
      {
        "id": "550e8400-e29b-41d4-a716-446655440000"
      }
    ],
    "tools": [
      {
        "id": "550e8400-e29b-41d4-a716-446655440000"
      }
    ],
    "skills": [
      {
        "id": "550e8400-e29b-41d4-a716-446655440000"
      }
    ],
    "connectors": [
      {
        "id": "550e8400-e29b-41d4-a716-446655440000"
```

```
        }
      ],
      "agentMode": {},
      "numberOfRetrievedChunks": 123,
      "defaultLabelRelations": null,
      "useFullRetrievalRange": true,
      "enableEvaluation": true,
      "enableInlineCitations": true,
      "enableCodeInterpreter": true,
      "enableBrowserTool": true,
      "enableImageSearch": true,
      "enableClaudeStreamRetry": true,
      "customMaxLlmOutputTokens": 123,
      "voiceConfig": {
        "enabled": true,
        "voiceAgentType": "550e8400-e29b-41d4-a716-446655440000",
        "sttProvider": "550e8400-e29b-41d4-a716-446655440000",
        "sttConfig": null,
        "ttsProvider": "550e8400-e29b-41d4-a716-446655440000",
        "ttsConfig": null,
        "realtimeProvider": "550e8400-e29b-41d4-a716-446655440000",
        "realtimeConfig": null,
        "realtimeInstructions": "範例字串",
        "turnHandling": null,
        "enableVoiceReply": true
      },
      "thinkingConfig": null,
      "enableToolSearching": true,
      "maxAgentIterations": 123,
      "agentTimeoutSeconds": 123,
      "agentTimeoutMessage": "範例字串",
      "requireTextWithFlexCards": true,
      "enableSizeBasedToolResultTruncation": true,
      "toolResultMaxChars": 123,
      "enableVectorMemory": true,
      "longTermMemoryTopK": 123,
      "enableCrossConversationSearch": true,
      "crossConversationLookbackDays": 123,
      "useGatewayFallback": true,
      "gatewayFallbackGroup": "550e8400-e29b-41d4-a716-446655440000",
      "enableSearchMessagesTool": true,
      "enableGetMessageContextTool": true,
      "enableReadAttachmentFullTextTool": true,
      "enableParseAttachmentContentTool": true,
      "enableListAvailableParsersTool": true,
      "enableGetDownloadLinkTool": true,
      "webChatIsActive": true,
      "apiIsActive": true,
      "fileWorkspaceMode": {},
      "fileWorkspaceFolder": "550e8400-e29b-41d4-a716-446655440000"
    }'

  # 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// 請求內容 (payload)
const data = {
    "name": "範例名稱",
    "largeLanguageModel": "550e8400-e29b-41d4-a716-446655440000",
    "embeddingModel": "550e8400-e29b-41d4-a716-446655440000",
    "rerankerModel": "550e8400-e29b-41d4-a716-446655440000",
    "instructions": "範例字串",
    "knowledgeBases": [
      {
        "id": "550e8400-e29b-41d4-a716-446655440000"
      }
    ],
    "databases": [
      {
        "id": "550e8400-e29b-41d4-a716-446655440000"
      }
    ],
    "organization": "550e8400-e29b-41d4-a716-446655440000",
    "replyMode": {},
    "template": "範例字串",
    "unanswerableTemplate": "範例字串",
    "totalWordsCount": 123,
    "outputMode": {},
    "rawOutputFormat": null,
    "groups": [
      {
        "id": "550e8400-e29b-41d4-a716-446655440000"
      }
    ],
    "tools": [
      {
        "id": "550e8400-e29b-41d4-a716-446655440000"
      }
    ],
    "skills": [
      {
        "id": "550e8400-e29b-41d4-a716-446655440000"
      }
```

```
    ],
    "connectors": [
      {
        "id": "550e8400-e29b-41d4-a716-446655440000"
      }
    ],
    "agentMode": {},
    "numberOfRetrievedChunks": 123,
    "defaultLabelRelations": null,
    "useFullRetrievalRange": true,
    "enableEvaluation": true,
    "enableInlineCitations": true,
    "enableCodeInterpreter": true,
    "enableBrowserTool": true,
    "enableImageSearch": true,
    "enableClaudeStreamRetry": true,
    "customMaxLlmOutputTokens": 123,
    "voiceConfig": {
      "enabled": true,
      "voiceAgentType": "550e8400-e29b-41d4-a716-446655440000",
      "sttProvider": "550e8400-e29b-41d4-a716-446655440000",
      "sttConfig": null,
      "ttsProvider": "550e8400-e29b-41d4-a716-446655440000",
      "ttsConfig": null,
      "realtimeProvider": "550e8400-e29b-41d4-a716-446655440000",
      "realtimeConfig": null,
      "realtimeInstructions": "範例字串",
      "turnHandling": null,
      "enableVoiceReply": true
    },
    "thinkingConfig": null,
    "enableToolSearching": true,
    "maxAgentIterations": 123,
    "agentTimeoutSeconds": 123,
    "agentTimeoutMessage": "範例字串",
    "requireTextWithFlexCards": true,
    "enableSizeBasedToolResultTruncation": true,
    "toolResultMaxChars": 123,
    "enableVectorMemory": true,
    "longTermMemoryTopK": 123,
    "enableCrossConversationSearch": true,
    "crossConversationLookbackDays": 123,
    "useGatewayFallback": true,
    "gatewayFallbackGroup": "550e8400-e29b-41d4-a716-446655440000",
    "enableSearchMessagesTool": true,
    "enableGetMessageContextTool": true,
    "enableReadAttachmentFullTextTool": true,
    "enableParseAttachmentContentTool": true,
    "enableListAvailableParsersTool": true,
    "enableGetDownloadLinkTool": true,
    "webChatIsActive": true,
    "apiIsActive": true,
    "fileWorkspaceMode": {},
```

```
    "fileWorkspaceFolder": "550e8400-e29b-41d4-a716-446655440000"
  };

axios.put(" data, config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# 請求內容 (payload)
data = {
    "name": "範例名稱",
    "largeLanguageModel": "550e8400-e29b-41d4-a716-446655440000",
    "embeddingModel": "550e8400-e29b-41d4-a716-446655440000",
    "rerankerModel": "550e8400-e29b-41d4-a716-446655440000",
    "instructions": "範例字串",
    "knowledgeBases": [
        {
            "id": "550e8400-e29b-41d4-a716-446655440000"
        }
    ],
    "databases": [
        {
            "id": "550e8400-e29b-41d4-a716-446655440000"
        }
    ],
    "organization": "550e8400-e29b-41d4-a716-446655440000",
    "replyMode": {},
    "template": "範例字串",
    "unanswerableTemplate": "範例字串",
    "totalWordsCount": 123,
    "outputMode": {},
    "rawOutputFormat": None,
    "groups": [
        {
            "id": "550e8400-e29b-41d4-a716-446655440000"
        }
    ],
    "tools": [
        {
            "id": "550e8400-e29b-41d4-a716-446655440000"
        }
    ],
    "skills": [
        {
            "id": "550e8400-e29b-41d4-a716-446655440000"
        }
    ],
    "connectors": [
```

```
            {
                "id": "550e8400-e29b-41d4-a716-446655440000"
            }
        ],
        "agentMode": {},
        "numberOfRetrievedChunks": 123,
        "defaultLabelRelations": None,
        "useFullRetrievalRange": True,
        "enableEvaluation": True,
        "enableInlineCitations": True,
        "enableCodeInterpreter": True,
        "enableBrowserTool": True,
        "enableImageSearch": True,
        "enableClaudeStreamRetry": True,
        "customMaxLlmOutputTokens": 123,
        "voiceConfig": {
            "enabled": True,
            "voiceAgentType": "550e8400-e29b-41d4-a716-446655440000",
            "sttProvider": "550e8400-e29b-41d4-a716-446655440000",
            "sttConfig": None,
            "ttsProvider": "550e8400-e29b-41d4-a716-446655440000",
            "ttsConfig": None,
            "realtimeProvider": "550e8400-e29b-41d4-a716-446655440000",
            "realtimeConfig": None,
            "realtimeInstructions": "範例字串",
            "turnHandling": None,
            "enableVoiceReply": True
        },
        "thinkingConfig": None,
        "enableToolSearching": True,
        "maxAgentIterations": 123,
        "agentTimeoutSeconds": 123,
        "agentTimeoutMessage": "範例字串",
        "requireTextWithFlexCards": True,
        "enableSizeBasedToolResultTruncation": True,
        "toolResultMaxChars": 123,
        "enableVectorMemory": True,
        "longTermMemoryTopK": 123,
        "enableCrossConversationSearch": True,
        "crossConversationLookbackDays": 123,
        "useGatewayFallback": True,
        "gatewayFallbackGroup": "550e8400-e29b-41d4-a716-446655440000",
        "enableSearchMessagesTool": True,
        "enableGetMessageContextTool": True,
        "enableReadAttachmentFullTextTool": True,
        "enableParseAttachmentContentTool": True,
        "enableListAvailableParsersTool": True,
        "enableGetDownloadLinkTool": True,
        "webChatIsActive": True,
        "apiIsActive": True,
        "fileWorkspaceMode": {},
        "fileWorkspaceFolder": "550e8400-e29b-41d4-a716-446655440000"
    }
```

```
response = requests.put(url, json=data, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->put(" [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'name' => '範例名稱',
            'largeLanguageModel' => '550e8400-e29b-41d4-a716-446655440000',
            'embeddingModel' => '550e8400-e29b-41d4-a716-446655440000',
            'rerankerModel' => '550e8400-e29b-41d4-a716-446655440000',
            'instructions' => '範例字串',
            'knowledgeBases' => [
                [
                    'id' => '550e8400-e29b-41d4-a716-446655440000'
                ]
            ],
            'databases' => [
                [
                    'id' => '550e8400-e29b-41d4-a716-446655440000'
                ]
            ],
            'organization' => '550e8400-e29b-41d4-a716-446655440000',
            'replyMode' => new \stdClass(),
            'template' => '範例字串',
            'unanswerableTemplate' => '範例字串',
            'totalWordsCount' => 123,
            'outputMode' => new \stdClass(),
            'rawOutputFormat' => null,
            'groups' => [
                [
                    'id' => '550e8400-e29b-41d4-a716-446655440000'
                ]
            ],
            'tools' => [
                [
                    'id' => '550e8400-e29b-41d4-a716-446655440000'
                ]
            ],
            'skills' => [
                [
                    'id' => '550e8400-e29b-41d4-a716-446655440000'
                ]
```

```
            ],
            'connectors' => [
                [
                    'id' => '550e8400-e29b-41d4-a716-446655440000'
                ]
            ],
            'agentMode' => new \stdClass(),
            'numberOfRetrievedChunks' => 123,
            'defaultLabelRelations' => null,
            'useFullRetrievalRange' => true,
            'enableEvaluation' => true,
            'enableInlineCitations' => true,
            'enableCodeInterpreter' => true,
            'enableBrowserTool' => true,
            'enableImageSearch' => true,
            'enableClaudeStreamRetry' => true,
            'customMaxLlmOutputTokens' => 123,
            'voiceConfig' => [
                'enabled' => true,
                'voiceAgentType' => '550e8400-e29b-41d4-a716-446655440000',
                'sttProvider' => '550e8400-e29b-41d4-a716-446655440000',
                'sttConfig' => null,
                'ttsProvider' => '550e8400-e29b-41d4-a716-446655440000',
                'ttsConfig' => null,
                'realtimeProvider' => '550e8400-e29b-41d4-a716-446655440000',
                'realtimeConfig' => null,
                'realtimeInstructions' => '範例字串',
                'turnHandling' => null,
                'enableVoiceReply' => true
            ],
            'thinkingConfig' => null,
            'enableToolSearching' => true,
            'maxAgentIterations' => 123,
            'agentTimeoutSeconds' => 123,
            'agentTimeoutMessage' => '範例字串',
            'requireTextWithFlexCards' => true,
            'enableSizeBasedToolResultTruncation' => true,
            'toolResultMaxChars' => 123,
            'enableVectorMemory' => true,
            'longTermMemoryTopK' => 123,
            'enableCrossConversationSearch' => true,
            'crossConversationLookbackDays' => 123,
            'useGatewayFallback' => true,
            'gatewayFallbackGroup' => '550e8400-e29b-41d4-a716-446655440000',
            'enableSearchMessagesTool' => true,
            'enableGetMessageContextTool' => true,
            'enableReadAttachmentFullTextTool' => true,
            'enableParseAttachmentContentTool' => true,
            'enableListAvailableParsersTool' => true,
            'enableGetDownloadLinkTool' => true,
            'webChatIsActive' => true,
            'apiIsActive' => true,
            'fileWorkspaceMode' => new \stdClass(),
```

```
            'fileWorkspaceFolder' => '550e8400-e29b-41d4-a716-446655440000'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
{
  "id": string (uuid)
  "name": string // Chatbot name. In Agent mode it carries semantic meaning; in other modes it only distinguishes chatbots.
  "largeLanguageModel": string (uuid) // 機器人使用的大型語言模型，用於生成回答（含組織自建的 AI Gateway 模型）
  "llm":  // 綁定模型的 id、name 與退役資訊，直接讀取 FK，即使該模型已被組織停用仍會回傳
  {
    "id": string (uuid)
    "name": string
    "retiresAt": string (date) // 供應商退役日；到期後每日排程會把助理換到 replacement 並停用此模型。null 表示未排定退役
    "replacement":  // 退役後接手的模型（id 與 name）；null 表示未指定，到期時不會自動搬移
    {
      "id": string (uuid)
      "name": string
    }
  }
  "embeddingModel"?: string (uuid) // 用於向量化文本的嵌入模型，非必填項目 (非必填)
  "rerankerModel"?: string (uuid) // 用於重新排序的模型，非必填項目 (非必填)
  "instructions"?: string // Role instructions describing the chatbot's role and behavior. (非必填)
  "knowledgeBases"?: [ // 機器人可存取的知識庫列表 (非必填)
    {
      "id": string (uuid)
      "name": string
    }
```

```
  ]
  "databases"?: [ // 機器人可存取的 SQL 資料庫列表（用於 Text-to-SQL 功能） (非必填)
    {
      "id": string (uuid)
      "name": string
    }
  ]
  "updatedAt": string (timestamp)
  "organization"?: string (uuid) // 機器人所屬的組織，如果為空則為個人機器人 (非必填)
  "replyMode"?:  // 回覆模式：一般回覆或串流回覆

* `normal` - 正常
* `template` - 模板
* `hybrid` - 混合
* `agent` - 代理 (非必填)
  {
  }
  "template"?: string // Template used by Template and Hybrid modes. (非必填)
  "unanswerableTemplate"?: string // Template used by Template and Hybrid modes when the
question cannot be answered. (非必填)
  "totalWordsCount"?: integer (int64) // Accumulated total word count used. (非必填)
  "outputMode"?:  // 輸出模式：文字、表格或自定義格式

* `text` - 文字
* `json_schema` - JSON Schema (非必填)
  {
  }
  "rawOutputFormat"?: object // 自定義輸出格式的JSON結構定義 (非必填)
  "groups"?: [ // 機器人可存取的群組列表 (非必填)
    {
      "id": string (uuid)
      "name": string
    }
  ]
  "tools"?: [ // 機器人可使用的工具列表 (非必填)
    {
      "id": string (uuid)
      "name": string
      "description": string
      "displayName": string
      "toolType": string
    }
  ]
  "skills"?: [ // 機器人關聯的技能列表 (非必填)
    {
      "id": string (uuid)
      "name": string
      "description": string
    }
  ]
  "connectors"?: [ // Connectors associated with this chatbot, gating per-contact OAuth
authorization (非必填)
    {
```

```
      "id": string (uuid)
      "name": string
    }
  ]
  "agentMode"?:  // 代理模式：一般、SQL或工作流程模式

* `normal` - 正常
* `canvas` - 畫布
* `team` - 團隊 (非必填)
  {
  }
  "numberOfRetrievedChunks"?: integer // 提取的參考資料數量，預設為 12，最小值為 1 (非必填)
  "defaultLabelRelations"?: object // 助理層級的預設知識庫標籤過濾條件，格式同 query_metadata.label_relations；null 表示不過濾。僅在呼叫端未帶 query_metadata 時作為最低優先序兜底套用。 (非必填)
  "useFullRetrievalRange"?: boolean // 啟用後忽略 LLM 的 top_k 截斷，回傳完整 reranker 結果 (非必填)
  "enableEvaluation"?: boolean // 非必填
  "enableInlineCitations"?: boolean // Enables inline citations, inserting citation markers such as [1][2] into responses. (非必填)
  "enableCodeInterpreter"?: boolean // When enabled, provides the Code Interpreter tool to run code in an isolated container. (非必填)
  "enableBrowserTool"?: boolean // Enable browser automation tool for web tasks (非必填)
  "enableImageSearch"?: boolean // Provide the image_search tool when any attached knowledge base uses a multimodal embedding model. Disable to remove the tool entirely. (非必填)
  "enableClaudeStreamRetry"?: boolean // When a Claude streaming call stalls (first-chunk or mid-stream), abort and re-issue the call once in non-streaming mode. Mid-stream retries send a reset signal so the client discards any partial output already rendered. Each retry incurs a second billing for the same prompt. (非必填)
  "customMaxLlmOutputTokens"?: integer // 自訂最大 LLM 輸出 token 數，最小值為 512 (非必填)
  "voiceConfig"?: { // 非必填
  {
    "enabled"?: boolean // Whether this chatbot can be used as a voice agent. Checked by every conversation platform (WebChat, SIP phone, admin/marketplace voice test) instead of a per-platform toggle. (非必填)
    "voiceAgentType"?: string (uuid) // Voice agent mode type. (非必填)
    "sttProvider"?: string (uuid) // Speech-to-Text service provider. (非必填)
    "sttConfig"?: object // STT configuration parameters (JSON). (非必填)
    "ttsProvider"?: string (uuid) // Text-to-Speech service provider. (非必填)
    "ttsConfig"?: object // TTS configuration parameters (JSON). (非必填)
    "realtimeProvider"?: string (uuid) // Realtime end-to-end voice model provider. (非必填)
    "realtimeConfig"?: object // Realtime configuration parameters (JSON). (非必填)
    "realtimeInstructions"?: string // Prompt dedicated to the realtime voice session; falls back to chatbot instructions when empty (非必填)
    "turnHandling"?: object // Turn-taking and interruption settings for the voice agent. (非必填)
    "enableVoiceReply"?: boolean // When disabled, the voice agent replies in text only and does not speak (非必填)
  }
  }
  "thinkingConfig"?: object // 思考等級：null（模型預設）或 {"reasoning_effort":
```

```
"off|minimal|low|medium|high|xhigh|max"} (非必填)
  "enableToolSearching"?: boolean // 啟用動態工具搜尋功能，允許 agent 透過 tool_searching_tool 動態發現和加載工具 (非必填)
  "maxAgentIterations"?: integer // Maximum number of iterations for AgentWorkflow (1-100, default: 20) (非必填)
  "agentTimeoutSeconds"?: integer // Timeout in seconds for AgentWorkflow execution (30-1200, default: 600) (非必填)
  "agentTimeoutMessage"?: string // Custom user-facing message shown when AgentWorkflow times out (max 500 chars). Leave empty to use the system default. (非必填)
  "requireTextWithFlexCards"?: boolean // When enabled, a turn that would end with only Flex Message cards and no text for the user is re-issued to the LLM once, asking it to write the text first and then send the card. Each retry incurs a second billing for the same prompt. (非必填)
  "isMultimodalLlm": boolean // Whether the chatbot LLM supports multimodal (read-only)
  "enableSizeBasedToolResultTruncation"?: boolean // When enabled, tool results exceeding the character threshold are kept as head+tail (with the identifiers found in the cut part) when written to conversation history; knowledge base, SQL and conversation search results keep their 100-character cut either way. Reduces memory bloat from large tool outputs (code interpreter bash stdout, web search results, etc.). (非必填)
  "toolResultMaxChars"?: integer // Character threshold for size-based tool result truncation (500-50000). Only effective when enable_size_based_tool_result_truncation is True. (非必填)
  "enableVectorMemory"?: boolean // When enabled, archived messages are vectorized and processed by fact extraction for semantic retrieval (existing behavior). When disabled, archived messages are discarded and only the active chat history window is used for multi-turn context. (非必填)
  "longTermMemoryTopK"?: integer // 長期記憶每次檢索取回的記憶節點數（向量檢索的 similarity_top_k），預設為 10，範圍 1–50 (非必填)
  "enableCrossConversationSearch"?: boolean // When enabled, the conversation history tools also reach this contact's other conversations in the same inbox, within the lookback window. When disabled, they only reach the current conversation. (非必填)
  "crossConversationLookbackDays"?: integer // How far back cross-conversation search may reach, measured from each conversation's last message (1-365 days). Leave empty to fall back to 90 days. Only effective when enable_cross_conversation_search is True. (非必填)
  "useGatewayFallback"?: boolean // When enabled, use the fallback group instead of the single LLM (非必填)
  "gatewayFallbackGroup"?: string (uuid) // 非必填
  "enableSearchMessagesTool"?: boolean // Allow the AI to search past messages in the current conversation. (非必填)
  "enableGetMessageContextTool"?: boolean // Allow the AI to retrieve messages surrounding a specific message for context. (非必填)
  "enableReadAttachmentFullTextTool"?: boolean // Allow the AI to read the full text of plain-text attachments. AGENT mode only. (非必填)
  "enableParseAttachmentContentTool"?: boolean // Allow the AI to parse PDF, Office, audio, and other attachments. AGENT mode only. (非必填)
  "enableListAvailableParsersTool"?: boolean // Allow the AI to list available parsers and their capabilities. AGENT mode only. (非必填)
  "enableGetDownloadLinkTool"?: boolean // Allow the AI to generate shareable download links for produced content. AGENT mode only. (非必填)
  "isLocked": boolean // Locked instance: config follows the official version; only the dedicated KB can be modified
  "sourceBuildInAgent": string (uuid) // Points to the official Build-in Agent blueprint when instantiated by a rental
```

```
  "canUpdate": boolean // Return whether the current user can update this resource.
  "canDelete": boolean // Return whether the current user can delete this resource.
  "team":
  {
    "id": string (uuid)
    "name": string
  }
  "webChatIsActive"?: boolean // Optional, create only. Whether the web widget channel
starts active. Omitted or null: follows the organization's default for new chatbot
channels (inactive unless a platform admin turned it on). Ignored on update; change an
existing channel from its channel settings instead. (非必填)
  "apiIsActive"?: boolean // Optional, create only. Whether the API channel starts
active. Omitted or null: follows the organization's default for new chatbot channels
(inactive unless a platform admin turned it on). Ignored on update; change an existing
channel from its channel settings instead. The backstage (admin) channel always starts
active and cannot be set here. (非必填)
  "fileWorkspaceMode"?:  // File workspace mode in Work internal conversations: none,
bound or user_mount.

* `none` - None
* `bound` - Bound workspace
* `user_mount` - User mount (非必填)
  {
  }
  "fileWorkspaceFolder"?: string (uuid) // The bound workspace (folder id); required when
the mode is bound, cleared otherwise. (非必填)
  "fileWorkspaceStatus": object // Read-only. {"folder": {"id", "name"} | null, "state":
"ok" | "missing" | "builder_lost_edit" | null}
  "fileWorkspaceAvailable": boolean // Read-only. Whether the organization has the file
library and this agent can configure a file workspace.
}
```

回應範例值

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "name": "回應字串",
  "largeLanguageModel": "550e8400-e29b-41d4-a716-446655440000",
  "llm": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應字串",
    "retiresAt": "回應字串",
    "replacement": {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "回應字串"
    }
  },
  "embeddingModel": "550e8400-e29b-41d4-a716-446655440000",
  "rerankerModel": "550e8400-e29b-41d4-a716-446655440000",
  "instructions": "回應字串",
  "knowledgeBases": [
    {
```

```
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "回應字串"
    }
  ],
  "databases": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "回應字串"
    }
  ],
  "updatedAt": "回應字串",
  "organization": "550e8400-e29b-41d4-a716-446655440000",
  "replyMode": {},
  "template": "回應字串",
  "unanswerableTemplate": "回應字串",
  "totalWordsCount": 456,
  "outputMode": {},
  "rawOutputFormat": null,
  "groups": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "回應字串"
    }
  ],
  "tools": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "回應字串",
      "description": "回應字串",
      "displayName": "回應字串",
      "toolType": "回應字串"
    }
  ],
  "skills": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "回應字串",
      "description": "回應字串"
    }
  ],
  "connectors": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "回應字串"
    }
  ],
  "agentMode": {},
  "numberOfRetrievedChunks": 456,
  "defaultLabelRelations": null,
  "useFullRetrievalRange": false,
  "enableEvaluation": false,
  "enableInlineCitations": false,
  "enableCodeInterpreter": false,
```

```
  "enableBrowserTool": false,
  "enableImageSearch": false,
  "enableClaudeStreamRetry": false,
  "customMaxLlmOutputTokens": 456,
  "voiceConfig": {
    "enabled": false,
    "voiceAgentType": "550e8400-e29b-41d4-a716-446655440000",
    "sttProvider": "550e8400-e29b-41d4-a716-446655440000",
    "sttConfig": null,
    "ttsProvider": "550e8400-e29b-41d4-a716-446655440000",
    "ttsConfig": null,
    "realtimeProvider": "550e8400-e29b-41d4-a716-446655440000",
    "realtimeConfig": null,
    "realtimeInstructions": "回應字串",
    "turnHandling": null,
    "enableVoiceReply": false
  },
  "thinkingConfig": null,
  "enableToolSearching": false,
  "maxAgentIterations": 456,
  "agentTimeoutSeconds": 456,
  "agentTimeoutMessage": "回應字串",
  "requireTextWithFlexCards": false,
  "isMultimodalLlm": false,
  "enableSizeBasedToolResultTruncation": false,
  "toolResultMaxChars": 456,
  "enableVectorMemory": false,
  "longTermMemoryTopK": 456,
  "enableCrossConversationSearch": false,
  "crossConversationLookbackDays": 456,
  "useGatewayFallback": false,
  "gatewayFallbackGroup": "550e8400-e29b-41d4-a716-446655440000",
  "enableSearchMessagesTool": false,
  "enableGetMessageContextTool": false,
  "enableReadAttachmentFullTextTool": false,
  "enableParseAttachmentContentTool": false,
  "enableListAvailableParsersTool": false,
  "enableGetDownloadLinkTool": false,
  "isLocked": false,
  "sourceBuildInAgent": "550e8400-e29b-41d4-a716-446655440000",
  "canUpdate": false,
  "canDelete": false,
  "team": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應字串"
  },
  "webChatIsActive": false,
  "apiIsActive": false,
  "fileWorkspaceMode": {},
  "fileWorkspaceFolder": "550e8400-e29b-41d4-a716-446655440000",
  "fileWorkspaceStatus": {
    "name": "example.pdf",
    "content": "base64encoded_content",
```

```
    "contentType": "application/pdf"
  },
  "fileWorkspaceAvailable": false
}
```


部分更新 AI 助理

PATCH `/api/v1/chatbots/{id}`

參數

參數名稱	必填	類型	說明
id	V	string	

請求內容

請求參數

欄位	類型	必填	說明
name	string	否	Chatbot name. In Agent mode it carries semantic meaning; in other modes it only distinguishes chatbots.
largeLanguageModel	string (uuid)	否	機器人使用的大型語言模型，用於生成回答（含組織自建的 AI Gateway 模型）
embeddingModel	string (uuid)	否	用於向量化文本的嵌入模型，非必填項目
rerankerModel	string (uuid)	否	用於重新排序的模型，非必填項目
instructions	string	否	Role instructions describing the chatbot's role and behavior.
knowledgeBases	array[IdName]	否	機器人可存取的知識庫列表
databases	array[IdName]	否	機器人可存取的 SQL 資料庫列表（用於 Text-to-SQL 功能）

欄位	類型	必填	說明
organization	string (uuid)	否	機器人所屬的組織，如果為空則為個人機器人
replyMode	object	否	回覆模式：一般回覆或串流回覆 `normal`：正常；`template`：模板；`hybrid`：混合；`agent`：代理;
template	string	否	Template used by Template and Hybrid modes.
unanswerableTemplate	string	否	Template used by Template and Hybrid modes when the question cannot be answered.
totalWordsCount	integer (int64)	否	Accumulated total word count used.
outputMode	object	否	輸出模式：文字、表格或自定義格式 `text`：文字；`json_schema`：JSON Schema;
rawOutputFormat	object	否	自定義輸出格式的JSON結構定義
groups	array[IdName]	否	機器人可存取的群組列表
tools	array[ToolSummary]	否	機器人可使用的工具列表
skills	array[SkillSummary]	否	機器人關聯的技能列表
connectors	array[IdName]	否	Connectors associated with this chatbot, gating per-contact OAuth authorization
agentMode	object	否	代理模式：一般、SQL或工作流程模式 `normal`：正常；`canvas`：畫布；`team`：團隊;
numberOfRetrievedChunks	integer	否	提取的參考資料數量，預設為 12，最小值為 1
defaultLabelRelations	object	否	助理層級的預設知識庫標籤過濾條件，格式同 query_metadata.label_relations；null 表示不過濾。僅在呼叫端未帶 query_metadata 時作為最低優先序兜底套用。
useFullRetrievalRange	boolean	否	啟用後忽略 LLM 的 top_k 截斷，回傳完整 reranker 結果
enableEvaluation	boolean	否	
enableInlineCitations	boolean	否	Enables inline citations, inserting citation markers such as [1][2] into responses.
enableCodeInterpreter	boolean	否	When enabled, provides the Code Interpreter tool to run code in an isolated container.

欄位	類型	必填	說明
enableBrowserTool	boolean	否	Enable browser automation tool for web tasks
enableImageSearch	boolean	否	Provide the image_search tool when any attached knowledge base uses a multimodal embedding model. Disable to remove the tool entirely.
enableClaudeStreamRetry	boolean	否	When a Claude streaming call stalls (first-chunk or mid-stream), abort and re-issue the call once in non-streaming mode. Mid-stream retries send a reset signal so the client discards any partial outpu...
customMaxLlmOutputTokens	integer	否	自訂最大 LLM 輸出 token 數，最小值為 512
voiceConfig	object	否	
voiceConfig.enabled	boolean	否	Whether this chatbot can be used as a voice agent. Checked by every conversation platform (WebChat, SIP phone, admin/marketplace voice test) instead of a per-platform toggle.
voiceConfig.voiceAgentType	string (uuid)	否	Voice agent mode type.
voiceConfig.sttProvider	string (uuid)	否	Speech-to-Text service provider.
voiceConfig.sttConfig	object	否	STT configuration parameters (JSON).
voiceConfig.ttsProvider	string (uuid)	否	Text-to-Speech service provider.
voiceConfig.ttsConfig	object	否	TTS configuration parameters (JSON).
voiceConfig.realtimeProvider	string (uuid)	否	Realtime end-to-end voice model provider.
voiceConfig.realtimeConfig	object	否	Realtime configuration parameters (JSON).
voiceConfig.realtimeInstructions	string	否	Prompt dedicated to the realtime voice session; falls back to chatbot instructions when empty
voiceConfig.turnHandling	object	否	Turn-taking and interruption settings for the voice agent.
voiceConfig.enableVoiceReply	boolean	否	When disabled, the voice agent replies in text only and does not speak
thinkingConfig	object	否	思考等級：null（模型預設）或 {"reasoning_effort": "off
enableToolSearching	boolean	否	啟用動態工具搜尋功能，允許 agent 透過 tool_searching_tool 動態發現和加載工具

欄位	類型	必填	說明
maxAgentIterations	integer	否	Maximum number of iterations for AgentWorkflow (1-100, default: 20)
agentTimeoutSeconds	integer	否	Timeout in seconds for AgentWorkflow execution (30-1200, default: 600)
agentTimeoutMessage	string	否	Custom user-facing message shown when AgentWorkflow times out (max 500 chars). Leave empty to use the system default.
requireTextWithFlexCards	boolean	否	When enabled, a turn that would end with only Flex Message cards and no text for the user is re-issued to the LLM once, asking it to write the text first and then send the card. Each retry incurs a se...
enableSizeBasedToolResultTruncation	boolean	否	When enabled, tool results exceeding the character threshold are kept as head+tail (with the identifiers found in the cut part) when written to conversation history; knowledge base, SQL and conversati...
toolResultMaxChars	integer	否	Character threshold for size-based tool result truncation (500-50000). Only effective when enable_size_based_tool_result_truncation is True.
enableVectorMemory	boolean	否	When enabled, archived messages are vectorized and processed by fact extraction for semantic retrieval (existing behavior). When disabled, archived messages are discarded and only the active chat hist...
longTermMemoryTopK	integer	否	長期記憶每次檢索取回的記憶節點數（向量檢索的 similarity_top_k），預設為 10，範圍 1–50
enableCrossConversationSearch	boolean	否	When enabled, the conversation history tools also reach this contact's other conversations in the same inbox, within the lookback window. When disabled, they only reach the current conversation.
crossConversationLookbackDays	integer	否	How far back cross-conversation search may reach, measured from each conversation's last message (1-365 days). Leave empty to fall back to 90 days. Only effective when enable_cross_conversation_search...

欄位	類型	必填	說明
useGatewayFallback	boolean	否	When enabled, use the fallback group instead of the single LLM
gatewayFallbackGroup	string (uuid)	否	
enableSearchMessagesTool	boolean	否	Allow the AI to search past messages in the current conversation.
enableGetMessageContextTool	boolean	否	Allow the AI to retrieve messages surrounding a specific message for context.
enableReadAttachmentFullTextTool	boolean	否	Allow the AI to read the full text of plain-text attachments. AGENT mode only.
enableParseAttachmentContentTool	boolean	否	Allow the AI to parse PDF, Office, audio, and other attachments. AGENT mode only.
enableListAvailableParsersTool	boolean	否	Allow the AI to list available parsers and their capabilities. AGENT mode only.
enableGetDownloadLinkTool	boolean	否	Allow the AI to generate shareable download links for produced content. AGENT mode only.
webChatIsActive	boolean	否	Optional, create only. Whether the web widget channel starts active. Omitted or null: follows the organization's default for new chatbot channels (inactive unless a platform admin turned it on). Ignor...
apiIsActive	boolean	否	Optional, create only. Whether the API channel starts active. Omitted or null: follows the organization's default for new chatbot channels (inactive unless a platform admin turned it on). Ignored on u...
fileWorkspaceMode	object	否	File workspace mode in Work internal conversations: none, bound or user_mount. `none` : None ; `bound` : Bound workspace ; `user_mount` : User mount;
fileWorkspaceFolder	string (uuid)	否	The bound workspace (folder id); required when the mode is bound, cleared otherwise.

請求結構範例

```
{
  "name"?: string // Chatbot name. In Agent mode it carries semantic meaning; in other modes it only distinguishes chatbots. (非必填)
```

```
  "largeLanguageModel"?: string (uuid) // 機器人使用的大型語言模型，用於生成回答（含組織自建的 AI Gateway 模型）（非必填）
  "embeddingModel"?: string (uuid) // 用於向量化文本的嵌入模型，非必填項目（非必填）
  "rerankerModel"?: string (uuid) // 用於重新排序的模型，非必填項目（非必填）
  "instructions"?: string // Role instructions describing the chatbot's role and behavior.（非必填）
  "knowledgeBases"?: [ // 機器人可存取的知識庫列表（非必填）
    {
      "id": string (uuid)
    }
  ]
  "databases"?: [ // 機器人可存取的 SQL 資料庫列表（用於 Text-to-SQL 功能）（非必填）
    {
      "id": string (uuid)
    }
  ]
  "organization"?: string (uuid) // 機器人所屬的組織，如果為空則為個人機器人（非必填）
  "replyMode"?:  // 回覆模式：一般回覆或串流回覆

* `normal` - 正常
* `template` - 模板
* `hybrid` - 混合
* `agent` - 代理（非必填）
  {
  }
  "template"?: string // Template used by Template and Hybrid modes.（非必填）
  "unanswerableTemplate"?: string // Template used by Template and Hybrid modes when the question cannot be answered.（非必填）
  "totalWordsCount"?: integer (int64) // Accumulated total word count used.（非必填）
  "outputMode"?:  // 輸出模式：文字、表格或自定義格式

* `text` - 文字
* `json_schema` - JSON Schema（非必填）
  {
  }
  "rawOutputFormat"?: object // 自定義輸出格式的JSON結構定義（非必填）
  "groups"?: [ // 機器人可存取的群組列表（非必填）
    {
      "id": string (uuid)
    }
  ]
  "tools"?: [ // 機器人可使用的工具列表（非必填）
    {
      "id": string (uuid)
    }
  ]
  "skills"?: [ // 機器人關聯的技能列表（非必填）
    {
      "id": string (uuid)
    }
  ]
  "connectors"?: [ // Connectors associated with this chatbot, gating per-contact OAuth authorization（非必填）
```

```
    {
      "id": string (uuid)
    }
  ]
  "agentMode"?:  // 代理模式：一般、SQL或工作流程模式

* `normal` - 正常
* `canvas` - 畫布
* `team` - 團隊 (非必填)
  {
  }
  "numberOfRetrievedChunks"?: integer // 提取的參考資料數量，預設為 12，最小值為 1 (非必填)
  "defaultLabelRelations"?: object // 助理層級的預設知識庫標籤過濾條件，格式同 query_metadata.label_relations；null 表示不過濾。僅在呼叫端未帶 query_metadata 時作為最低優先序兜底套用。 (非必填)
  "useFullRetrievalRange"?: boolean // 啟用後忽略 LLM 的 top_k 截斷，回傳完整 reranker 結果 (非必填)
  "enableEvaluation"?: boolean // 非必填
  "enableInlineCitations"?: boolean // Enables inline citations, inserting citation markers such as [1][2] into responses. (非必填)
  "enableCodeInterpreter"?: boolean // When enabled, provides the Code Interpreter tool to run code in an isolated container. (非必填)
  "enableBrowserTool"?: boolean // Enable browser automation tool for web tasks (非必填)
  "enableImageSearch"?: boolean // Provide the image_search tool when any attached knowledge base uses a multimodal embedding model. Disable to remove the tool entirely. (非必填)
  "enableClaudeStreamRetry"?: boolean // When a Claude streaming call stalls (first-chunk or mid-stream), abort and re-issue the call once in non-streaming mode. Mid-stream retries send a reset signal so the client discards any partial output already rendered. Each retry incurs a second billing for the same prompt. (非必填)
  "customMaxLlmOutputTokens"?: integer // 自訂最大 LLM 輸出 token 數，最小值為 512 (非必填)
  "voiceConfig"?: { // 非必填
  {
    "enabled"?: boolean // Whether this chatbot can be used as a voice agent. Checked by every conversation platform (WebChat, SIP phone, admin/marketplace voice test) instead of a per-platform toggle. (非必填)
    "voiceAgentType"?: string (uuid) // Voice agent mode type. (非必填)
    "sttProvider"?: string (uuid) // Speech-to-Text service provider. (非必填)
    "sttConfig"?: object // STT configuration parameters (JSON). (非必填)
    "ttsProvider"?: string (uuid) // Text-to-Speech service provider. (非必填)
    "ttsConfig"?: object // TTS configuration parameters (JSON). (非必填)
    "realtimeProvider"?: string (uuid) // Realtime end-to-end voice model provider. (非必填)
    "realtimeConfig"?: object // Realtime configuration parameters (JSON). (非必填)
    "realtimeInstructions"?: string // Prompt dedicated to the realtime voice session; falls back to chatbot instructions when empty (非必填)
    "turnHandling"?: object // Turn-taking and interruption settings for the voice agent. (非必填)
    "enableVoiceReply"?: boolean // When disabled, the voice agent replies in text only and does not speak (非必填)
  }
  }
  "thinkingConfig"?: object // 思考等級：null（模型預設）或 {"reasoning_effort":
```

```
"off|minimal|low|medium|high|xhigh|max"} (非必填)
  "enableToolSearching"?: boolean // 啟用動態工具搜尋功能，允許 agent 透過 tool_searching_tool 動態發現和加載工具 (非必填)
  "maxAgentIterations"?: integer // Maximum number of iterations for AgentWorkflow (1-100, default: 20) (非必填)
  "agentTimeoutSeconds"?: integer // Timeout in seconds for AgentWorkflow execution (30-1200, default: 600) (非必填)
  "agentTimeoutMessage"?: string // Custom user-facing message shown when AgentWorkflow times out (max 500 chars). Leave empty to use the system default. (非必填)
  "requireTextWithFlexCards"?: boolean // When enabled, a turn that would end with only Flex Message cards and no text for the user is re-issued to the LLM once, asking it to write the text first and then send the card. Each retry incurs a second billing for the same prompt. (非必填)
  "enableSizeBasedToolResultTruncation"?: boolean // When enabled, tool results exceeding the character threshold are kept as head+tail (with the identifiers found in the cut part) when written to conversation history; knowledge base, SQL and conversation search results keep their 100-character cut either way. Reduces memory bloat from large tool outputs (code interpreter bash stdout, web search results, etc.). (非必填)
  "toolResultMaxChars"?: integer // Character threshold for size-based tool result truncation (500-50000). Only effective when enable_size_based_tool_result_truncation is True. (非必填)
  "enableVectorMemory"?: boolean // When enabled, archived messages are vectorized and processed by fact extraction for semantic retrieval (existing behavior). When disabled, archived messages are discarded and only the active chat history window is used for multi-turn context. (非必填)
  "longTermMemoryTopK"?: integer // 長期記憶每次檢索取回的記憶節點數（向量檢索的 similarity_top_k），預設為 10，範圍 1–50 (非必填)
  "enableCrossConversationSearch"?: boolean // When enabled, the conversation history tools also reach this contact's other conversations in the same inbox, within the lookback window. When disabled, they only reach the current conversation. (非必填)
  "crossConversationLookbackDays"?: integer // How far back cross-conversation search may reach, measured from each conversation's last message (1-365 days). Leave empty to fall back to 90 days. Only effective when enable_cross_conversation_search is True. (非必填)
  "useGatewayFallback"?: boolean // When enabled, use the fallback group instead of the single LLM (非必填)
  "gatewayFallbackGroup"?: string (uuid) // 非必填
  "enableSearchMessagesTool"?: boolean // Allow the AI to search past messages in the current conversation. (非必填)
  "enableGetMessageContextTool"?: boolean // Allow the AI to retrieve messages surrounding a specific message for context. (非必填)
  "enableReadAttachmentFullTextTool"?: boolean // Allow the AI to read the full text of plain-text attachments. AGENT mode only. (非必填)
  "enableParseAttachmentContentTool"?: boolean // Allow the AI to parse PDF, Office, audio, and other attachments. AGENT mode only. (非必填)
  "enableListAvailableParsersTool"?: boolean // Allow the AI to list available parsers and their capabilities. AGENT mode only. (非必填)
  "enableGetDownloadLinkTool"?: boolean // Allow the AI to generate shareable download links for produced content. AGENT mode only. (非必填)
  "webChatIsActive"?: boolean // Optional, create only. Whether the web widget channel starts active. Omitted or null: follows the organization's default for new chatbot channels (inactive unless a platform admin turned it on). Ignored on update; change an existing channel from its channel settings instead. (非必填)
  "apiIsActive"?: boolean // Optional, create only. Whether the API channel starts
```

```
active. Omitted or null: follows the organization's default for new chatbot channels (inactive unless a platform admin turned it on). Ignored on update; change an existing channel from its channel settings instead. The backstage (admin) channel always starts active and cannot be set here. (非必填)
  "fileWorkspaceMode"?:  // File workspace mode in Work internal conversations: none, bound or user_mount.

* `none` - None
* `bound` - Bound workspace
* `user_mount` - User mount (非必填)
  {
  }
  "fileWorkspaceFolder"?: string (uuid) // The bound workspace (folder id); required when the mode is bound, cleared otherwise. (非必填)
}
```

請求範例值

```
{
  "name": "範例名稱",
  "largeLanguageModel": "550e8400-e29b-41d4-a716-446655440000",
  "embeddingModel": "550e8400-e29b-41d4-a716-446655440000",
  "rerankerModel": "550e8400-e29b-41d4-a716-446655440000",
  "instructions": "範例字串",
  "knowledgeBases": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000"
    }
  ],
  "databases": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000"
    }
  ],
  "organization": "550e8400-e29b-41d4-a716-446655440000",
  "replyMode": {},
  "template": "範例字串",
  "unanswerableTemplate": "範例字串",
  "totalWordsCount": 123,
  "outputMode": {},
  "rawOutputFormat": null,
  "groups": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000"
    }
  ],
  "tools": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000"
    }
  ],
  "skills": [
```

```
    {
      "id": "550e8400-e29b-41d4-a716-446655440000"
    }
  ],
  "connectors": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000"
    }
  ],
  "agentMode": {},
  "numberOfRetrievedChunks": 123,
  "defaultLabelRelations": null,
  "useFullRetrievalRange": true,
  "enableEvaluation": true,
  "enableInlineCitations": true,
  "enableCodeInterpreter": true,
  "enableBrowserTool": true,
  "enableImageSearch": true,
  "enableClaudeStreamRetry": true,
  "customMaxLlmOutputTokens": 123,
  "voiceConfig": {
    "enabled": true,
    "voiceAgentType": "550e8400-e29b-41d4-a716-446655440000",
    "sttProvider": "550e8400-e29b-41d4-a716-446655440000",
    "sttConfig": null,
    "ttsProvider": "550e8400-e29b-41d4-a716-446655440000",
    "ttsConfig": null,
    "realtimeProvider": "550e8400-e29b-41d4-a716-446655440000",
    "realtimeConfig": null,
    "realtimeInstructions": "範例字串",
    "turnHandling": null,
    "enableVoiceReply": true
  },
  "thinkingConfig": null,
  "enableToolSearching": true,
  "maxAgentIterations": 123,
  "agentTimeoutSeconds": 123,
  "agentTimeoutMessage": "範例字串",
  "requireTextWithFlexCards": true,
  "enableSizeBasedToolResultTruncation": true,
  "toolResultMaxChars": 123,
  "enableVectorMemory": true,
  "longTermMemoryTopK": 123,
  "enableCrossConversationSearch": true,
  "crossConversationLookbackDays": 123,
  "useGatewayFallback": true,
  "gatewayFallbackGroup": "550e8400-e29b-41d4-a716-446655440000",
  "enableSearchMessagesTool": true,
  "enableGetMessageContextTool": true,
  "enableReadAttachmentFullTextTool": true,
  "enableParseAttachmentContentTool": true,
  "enableListAvailableParsersTool": true,
  "enableGetDownloadLinkTool": true,
```

```
  "webChatIsActive": true,
  "apiIsActive": true,
  "fileWorkspaceMode": {},
  "fileWorkspaceFolder": "550e8400-e29b-41d4-a716-446655440000"
}
```


程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X PATCH "

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "name": "範例名稱",
    "largeLanguageModel": "550e8400-e29b-41d4-a716-446655440000",
    "embeddingModel": "550e8400-e29b-41d4-a716-446655440000",
    "rerankerModel": "550e8400-e29b-41d4-a716-446655440000",
    "instructions": "範例字串",
    "knowledgeBases": [
      {
        "id": "550e8400-e29b-41d4-a716-446655440000"
      }
    ],
    "databases": [
      {
        "id": "550e8400-e29b-41d4-a716-446655440000"
      }
    ],
    "organization": "550e8400-e29b-41d4-a716-446655440000",
    "replyMode": {},
    "template": "範例字串",
    "unanswerableTemplate": "範例字串",
    "totalWordsCount": 123,
    "outputMode": {},
    "rawOutputFormat": null,
    "groups": [
      {
        "id": "550e8400-e29b-41d4-a716-446655440000"
      }
    ],
    "tools": [
      {
        "id": "550e8400-e29b-41d4-a716-446655440000"
      }
    ],
    "skills": [
      {
        "id": "550e8400-e29b-41d4-a716-446655440000"
      }
    ],
    "connectors": [
      {
        "id": "550e8400-e29b-41d4-a716-446655440000"
```

```
        }
      ],
      "agentMode": {},
      "numberOfRetrievedChunks": 123,
      "defaultLabelRelations": null,
      "useFullRetrievalRange": true,
      "enableEvaluation": true,
      "enableInlineCitations": true,
      "enableCodeInterpreter": true,
      "enableBrowserTool": true,
      "enableImageSearch": true,
      "enableClaudeStreamRetry": true,
      "customMaxLlmOutputTokens": 123,
      "voiceConfig": {
        "enabled": true,
        "voiceAgentType": "550e8400-e29b-41d4-a716-446655440000",
        "sttProvider": "550e8400-e29b-41d4-a716-446655440000",
        "sttConfig": null,
        "ttsProvider": "550e8400-e29b-41d4-a716-446655440000",
        "ttsConfig": null,
        "realtimeProvider": "550e8400-e29b-41d4-a716-446655440000",
        "realtimeConfig": null,
        "realtimeInstructions": "範例字串",
        "turnHandling": null,
        "enableVoiceReply": true
      },
      "thinkingConfig": null,
      "enableToolSearching": true,
      "maxAgentIterations": 123,
      "agentTimeoutSeconds": 123,
      "agentTimeoutMessage": "範例字串",
      "requireTextWithFlexCards": true,
      "enableSizeBasedToolResultTruncation": true,
      "toolResultMaxChars": 123,
      "enableVectorMemory": true,
      "longTermMemoryTopK": 123,
      "enableCrossConversationSearch": true,
      "crossConversationLookbackDays": 123,
      "useGatewayFallback": true,
      "gatewayFallbackGroup": "550e8400-e29b-41d4-a716-446655440000",
      "enableSearchMessagesTool": true,
      "enableGetMessageContextTool": true,
      "enableReadAttachmentFullTextTool": true,
      "enableParseAttachmentContentTool": true,
      "enableListAvailableParsersTool": true,
      "enableGetDownloadLinkTool": true,
      "webChatIsActive": true,
      "apiIsActive": true,
      "fileWorkspaceMode": {},
      "fileWorkspaceFolder": "550e8400-e29b-41d4-a716-446655440000"
    }'

  # 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// 請求內容 (payload)
const data = {
    "name": "範例名稱",
    "largeLanguageModel": "550e8400-e29b-41d4-a716-446655440000",
    "embeddingModel": "550e8400-e29b-41d4-a716-446655440000",
    "rerankerModel": "550e8400-e29b-41d4-a716-446655440000",
    "instructions": "範例字串",
    "knowledgeBases": [
      {
        "id": "550e8400-e29b-41d4-a716-446655440000"
      }
    ],
    "databases": [
      {
        "id": "550e8400-e29b-41d4-a716-446655440000"
      }
    ],
    "organization": "550e8400-e29b-41d4-a716-446655440000",
    "replyMode": {},
    "template": "範例字串",
    "unanswerableTemplate": "範例字串",
    "totalWordsCount": 123,
    "outputMode": {},
    "rawOutputFormat": null,
    "groups": [
      {
        "id": "550e8400-e29b-41d4-a716-446655440000"
      }
    ],
    "tools": [
      {
        "id": "550e8400-e29b-41d4-a716-446655440000"
      }
    ],
    "skills": [
      {
        "id": "550e8400-e29b-41d4-a716-446655440000"
      }
```

```
  ],
  "connectors": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000"
    }
  ],
  "agentMode": {},
  "numberOfRetrievedChunks": 123,
  "defaultLabelRelations": null,
  "useFullRetrievalRange": true,
  "enableEvaluation": true,
  "enableInlineCitations": true,
  "enableCodeInterpreter": true,
  "enableBrowserTool": true,
  "enableImageSearch": true,
  "enableClaudeStreamRetry": true,
  "customMaxLlmOutputTokens": 123,
  "voiceConfig": {
    "enabled": true,
    "voiceAgentType": "550e8400-e29b-41d4-a716-446655440000",
    "sttProvider": "550e8400-e29b-41d4-a716-446655440000",
    "sttConfig": null,
    "ttsProvider": "550e8400-e29b-41d4-a716-446655440000",
    "ttsConfig": null,
    "realtimeProvider": "550e8400-e29b-41d4-a716-446655440000",
    "realtimeConfig": null,
    "realtimeInstructions": "範例字串",
    "turnHandling": null,
    "enableVoiceReply": true
  },
  "thinkingConfig": null,
  "enableToolSearching": true,
  "maxAgentIterations": 123,
  "agentTimeoutSeconds": 123,
  "agentTimeoutMessage": "範例字串",
  "requireTextWithFlexCards": true,
  "enableSizeBasedToolResultTruncation": true,
  "toolResultMaxChars": 123,
  "enableVectorMemory": true,
  "longTermMemoryTopK": 123,
  "enableCrossConversationSearch": true,
  "crossConversationLookbackDays": 123,
  "useGatewayFallback": true,
  "gatewayFallbackGroup": "550e8400-e29b-41d4-a716-446655440000",
  "enableSearchMessagesTool": true,
  "enableGetMessageContextTool": true,
  "enableReadAttachmentFullTextTool": true,
  "enableParseAttachmentContentTool": true,
  "enableListAvailableParsersTool": true,
  "enableGetDownloadLinkTool": true,
  "webChatIsActive": true,
  "apiIsActive": true,
  "fileWorkspaceMode": {},
```

```
    "fileWorkspaceFolder": "550e8400-e29b-41d4-a716-446655440000"
  };

axios.patch(" data, config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# 請求內容 (payload)
data = {
    "name": "範例名稱",
    "largeLanguageModel": "550e8400-e29b-41d4-a716-446655440000",
    "embeddingModel": "550e8400-e29b-41d4-a716-446655440000",
    "rerankerModel": "550e8400-e29b-41d4-a716-446655440000",
    "instructions": "範例字串",
    "knowledgeBases": [
        {
            "id": "550e8400-e29b-41d4-a716-446655440000"
        }
    ],
    "databases": [
        {
            "id": "550e8400-e29b-41d4-a716-446655440000"
        }
    ],
    "organization": "550e8400-e29b-41d4-a716-446655440000",
    "replyMode": {},
    "template": "範例字串",
    "unanswerableTemplate": "範例字串",
    "totalWordsCount": 123,
    "outputMode": {},
    "rawOutputFormat": None,
    "groups": [
        {
            "id": "550e8400-e29b-41d4-a716-446655440000"
        }
    ],
    "tools": [
        {
            "id": "550e8400-e29b-41d4-a716-446655440000"
        }
    ],
    "skills": [
        {
            "id": "550e8400-e29b-41d4-a716-446655440000"
        }
    ],
    "connectors": [
```

```
            {
                "id": "550e8400-e29b-41d4-a716-446655440000"
            }
        ],
        "agentMode": {},
        "numberOfRetrievedChunks": 123,
        "defaultLabelRelations": None,
        "useFullRetrievalRange": True,
        "enableEvaluation": True,
        "enableInlineCitations": True,
        "enableCodeInterpreter": True,
        "enableBrowserTool": True,
        "enableImageSearch": True,
        "enableClaudeStreamRetry": True,
        "customMaxLlmOutputTokens": 123,
        "voiceConfig": {
            "enabled": True,
            "voiceAgentType": "550e8400-e29b-41d4-a716-446655440000",
            "sttProvider": "550e8400-e29b-41d4-a716-446655440000",
            "sttConfig": None,
            "ttsProvider": "550e8400-e29b-41d4-a716-446655440000",
            "ttsConfig": None,
            "realtimeProvider": "550e8400-e29b-41d4-a716-446655440000",
            "realtimeConfig": None,
            "realtimeInstructions": "範例字串",
            "turnHandling": None,
            "enableVoiceReply": True
        },
        "thinkingConfig": None,
        "enableToolSearching": True,
        "maxAgentIterations": 123,
        "agentTimeoutSeconds": 123,
        "agentTimeoutMessage": "範例字串",
        "requireTextWithFlexCards": True,
        "enableSizeBasedToolResultTruncation": True,
        "toolResultMaxChars": 123,
        "enableVectorMemory": True,
        "longTermMemoryTopK": 123,
        "enableCrossConversationSearch": True,
        "crossConversationLookbackDays": 123,
        "useGatewayFallback": True,
        "gatewayFallbackGroup": "550e8400-e29b-41d4-a716-446655440000",
        "enableSearchMessagesTool": True,
        "enableGetMessageContextTool": True,
        "enableReadAttachmentFullTextTool": True,
        "enableParseAttachmentContentTool": True,
        "enableListAvailableParsersTool": True,
        "enableGetDownloadLinkTool": True,
        "webChatIsActive": True,
        "apiIsActive": True,
        "fileWorkspaceMode": {},
        "fileWorkspaceFolder": "550e8400-e29b-41d4-a716-446655440000"
    }
```

```
response = requests.patch(url, json=data, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->patch(" [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'name' => '範例名稱',
            'largeLanguageModel' => '550e8400-e29b-41d4-a716-446655440000',
            'embeddingModel' => '550e8400-e29b-41d4-a716-446655440000',
            'rerankerModel' => '550e8400-e29b-41d4-a716-446655440000',
            'instructions' => '範例字串',
            'knowledgeBases' => [
                [
                    'id' => '550e8400-e29b-41d4-a716-446655440000'
                ]
            ],
            'databases' => [
                [
                    'id' => '550e8400-e29b-41d4-a716-446655440000'
                ]
            ],
            'organization' => '550e8400-e29b-41d4-a716-446655440000',
            'replyMode' => new \stdClass(),
            'template' => '範例字串',
            'unanswerableTemplate' => '範例字串',
            'totalWordsCount' => 123,
            'outputMode' => new \stdClass(),
            'rawOutputFormat' => null,
            'groups' => [
                [
                    'id' => '550e8400-e29b-41d4-a716-446655440000'
                ]
            ],
            'tools' => [
                [
                    'id' => '550e8400-e29b-41d4-a716-446655440000'
                ]
            ],
            'skills' => [
                [
                    'id' => '550e8400-e29b-41d4-a716-446655440000'
                ]
```

```
            ],
            'connectors' => [
                [
                    'id' => '550e8400-e29b-41d4-a716-446655440000'
                ]
            ],
            'agentMode' => new \stdClass(),
            'numberOfRetrievedChunks' => 123,
            'defaultLabelRelations' => null,
            'useFullRetrievalRange' => true,
            'enableEvaluation' => true,
            'enableInlineCitations' => true,
            'enableCodeInterpreter' => true,
            'enableBrowserTool' => true,
            'enableImageSearch' => true,
            'enableClaudeStreamRetry' => true,
            'customMaxLlmOutputTokens' => 123,
            'voiceConfig' => [
                'enabled' => true,
                'voiceAgentType' => '550e8400-e29b-41d4-a716-446655440000',
                'sttProvider' => '550e8400-e29b-41d4-a716-446655440000',
                'sttConfig' => null,
                'ttsProvider' => '550e8400-e29b-41d4-a716-446655440000',
                'ttsConfig' => null,
                'realtimeProvider' => '550e8400-e29b-41d4-a716-446655440000',
                'realtimeConfig' => null,
                'realtimeInstructions' => '範例字串',
                'turnHandling' => null,
                'enableVoiceReply' => true
            ],
            'thinkingConfig' => null,
            'enableToolSearching' => true,
            'maxAgentIterations' => 123,
            'agentTimeoutSeconds' => 123,
            'agentTimeoutMessage' => '範例字串',
            'requireTextWithFlexCards' => true,
            'enableSizeBasedToolResultTruncation' => true,
            'toolResultMaxChars' => 123,
            'enableVectorMemory' => true,
            'longTermMemoryTopK' => 123,
            'enableCrossConversationSearch' => true,
            'crossConversationLookbackDays' => 123,
            'useGatewayFallback' => true,
            'gatewayFallbackGroup' => '550e8400-e29b-41d4-a716-446655440000',
            'enableSearchMessagesTool' => true,
            'enableGetMessageContextTool' => true,
            'enableReadAttachmentFullTextTool' => true,
            'enableParseAttachmentContentTool' => true,
            'enableListAvailableParsersTool' => true,
            'enableGetDownloadLinkTool' => true,
            'webChatIsActive' => true,
            'apiIsActive' => true,
            'fileWorkspaceMode' => new \stdClass(),
```

```
            'fileWorkspaceFolder' => '550e8400-e29b-41d4-a716-446655440000'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
{
  "id": string (uuid)
  "name": string // Chatbot name. In Agent mode it carries semantic meaning; in other modes it only distinguishes chatbots.
  "largeLanguageModel": string (uuid) // 機器人使用的大型語言模型，用於生成回答（含組織自建的 AI Gateway 模型）
  "llm":  // 綁定模型的 id、name 與退役資訊，直接讀取 FK，即使該模型已被組織停用仍會回傳
  {
    "id": string (uuid)
    "name": string
    "retiresAt": string (date) // 供應商退役日；到期後每日排程會把助理換到 replacement 並停用此模型。null 表示未排定退役
    "replacement":  // 退役後接手的模型（id 與 name）；null 表示未指定，到期時不會自動搬移
    {
      "id": string (uuid)
      "name": string
    }
  }
  "embeddingModel"?: string (uuid) // 用於向量化文本的嵌入模型，非必填項目 (非必填)
  "rerankerModel"?: string (uuid) // 用於重新排序的模型，非必填項目 (非必填)
  "instructions"?: string // Role instructions describing the chatbot's role and behavior. (非必填)
  "knowledgeBases"?: [ // 機器人可存取的知識庫列表 (非必填)
    {
      "id": string (uuid)
      "name": string
    }
```

```
  ]
  "databases"?: [ // 機器人可存取的 SQL 資料庫列表（用於 Text-to-SQL 功能） (非必填)
    {
      "id": string (uuid)
      "name": string
    }
  ]
  "updatedAt": string (timestamp)
  "organization"?: string (uuid) // 機器人所屬的組織，如果為空則為個人機器人 (非必填)
  "replyMode"?:  // 回覆模式：一般回覆或串流回覆

* `normal` - 正常
* `template` - 模板
* `hybrid` - 混合
* `agent` - 代理 (非必填)
  {
  }
  "template"?: string // Template used by Template and Hybrid modes. (非必填)
  "unanswerableTemplate"?: string // Template used by Template and Hybrid modes when the
question cannot be answered. (非必填)
  "totalWordsCount"?: integer (int64) // Accumulated total word count used. (非必填)
  "outputMode"?:  // 輸出模式：文字、表格或自定義格式

* `text` - 文字
* `json_schema` - JSON Schema (非必填)
  {
  }
  "rawOutputFormat"?: object // 自定義輸出格式的JSON結構定義 (非必填)
  "groups"?: [ // 機器人可存取的群組列表 (非必填)
    {
      "id": string (uuid)
      "name": string
    }
  ]
  "tools"?: [ // 機器人可使用的工具列表 (非必填)
    {
      "id": string (uuid)
      "name": string
      "description": string
      "displayName": string
      "toolType": string
    }
  ]
  "skills"?: [ // 機器人關聯的技能列表 (非必填)
    {
      "id": string (uuid)
      "name": string
      "description": string
    }
  ]
  "connectors"?: [ // Connectors associated with this chatbot, gating per-contact OAuth
authorization (非必填)
    {
```

```
      "id": string (uuid)
      "name": string
    }
  ]
  "agentMode"?:  // 代理模式：一般、SQL或工作流程模式

* `normal` - 正常
* `canvas` - 畫布
* `team` - 團隊 (非必填)
  {
  }
  "numberOfRetrievedChunks"?: integer // 提取的參考資料數量，預設為 12，最小值為 1 (非必填)
  "defaultLabelRelations"?: object // 助理層級的預設知識庫標籤過濾條件，格式同 query_metadata.label_relations；null 表示不過濾。僅在呼叫端未帶 query_metadata 時作為最低優先序兜底套用。 (非必填)
  "useFullRetrievalRange"?: boolean // 啟用後忽略 LLM 的 top_k 截斷，回傳完整 reranker 結果 (非必填)
  "enableEvaluation"?: boolean // 非必填
  "enableInlineCitations"?: boolean // Enables inline citations, inserting citation markers such as [1][2] into responses. (非必填)
  "enableCodeInterpreter"?: boolean // When enabled, provides the Code Interpreter tool to run code in an isolated container. (非必填)
  "enableBrowserTool"?: boolean // Enable browser automation tool for web tasks (非必填)
  "enableImageSearch"?: boolean // Provide the image_search tool when any attached knowledge base uses a multimodal embedding model. Disable to remove the tool entirely. (非必填)
  "enableClaudeStreamRetry"?: boolean // When a Claude streaming call stalls (first-chunk or mid-stream), abort and re-issue the call once in non-streaming mode. Mid-stream retries send a reset signal so the client discards any partial output already rendered. Each retry incurs a second billing for the same prompt. (非必填)
  "customMaxLlmOutputTokens"?: integer // 自訂最大 LLM 輸出 token 數，最小值為 512 (非必填)
  "voiceConfig"?: { // 非必填
  {
    "enabled"?: boolean // Whether this chatbot can be used as a voice agent. Checked by every conversation platform (WebChat, SIP phone, admin/marketplace voice test) instead of a per-platform toggle. (非必填)
    "voiceAgentType"?: string (uuid) // Voice agent mode type. (非必填)
    "sttProvider"?: string (uuid) // Speech-to-Text service provider. (非必填)
    "sttConfig"?: object // STT configuration parameters (JSON). (非必填)
    "ttsProvider"?: string (uuid) // Text-to-Speech service provider. (非必填)
    "ttsConfig"?: object // TTS configuration parameters (JSON). (非必填)
    "realtimeProvider"?: string (uuid) // Realtime end-to-end voice model provider. (非必填)
    "realtimeConfig"?: object // Realtime configuration parameters (JSON). (非必填)
    "realtimeInstructions"?: string // Prompt dedicated to the realtime voice session; falls back to chatbot instructions when empty (非必填)
    "turnHandling"?: object // Turn-taking and interruption settings for the voice agent. (非必填)
    "enableVoiceReply"?: boolean // When disabled, the voice agent replies in text only and does not speak (非必填)
  }
  }
  "thinkingConfig"?: object // 思考等級：null（模型預設）或 {"reasoning_effort":
```

```
"off|minimal|low|medium|high|xhigh|max"} (非必填)
  "enableToolSearching"?: boolean // 啟用動態工具搜尋功能，允許 agent 透過 tool_searching_tool 動態發現和加載工具 (非必填)
  "maxAgentIterations"?: integer // Maximum number of iterations for AgentWorkflow (1-100, default: 20) (非必填)
  "agentTimeoutSeconds"?: integer // Timeout in seconds for AgentWorkflow execution (30-1200, default: 600) (非必填)
  "agentTimeoutMessage"?: string // Custom user-facing message shown when AgentWorkflow times out (max 500 chars). Leave empty to use the system default. (非必填)
  "requireTextWithFlexCards"?: boolean // When enabled, a turn that would end with only Flex Message cards and no text for the user is re-issued to the LLM once, asking it to write the text first and then send the card. Each retry incurs a second billing for the same prompt. (非必填)
  "isMultimodalLlm": boolean // Whether the chatbot LLM supports multimodal (read-only)
  "enableSizeBasedToolResultTruncation"?: boolean // When enabled, tool results exceeding the character threshold are kept as head+tail (with the identifiers found in the cut part) when written to conversation history; knowledge base, SQL and conversation search results keep their 100-character cut either way. Reduces memory bloat from large tool outputs (code interpreter bash stdout, web search results, etc.). (非必填)
  "toolResultMaxChars"?: integer // Character threshold for size-based tool result truncation (500-50000). Only effective when enable_size_based_tool_result_truncation is True. (非必填)
  "enableVectorMemory"?: boolean // When enabled, archived messages are vectorized and processed by fact extraction for semantic retrieval (existing behavior). When disabled, archived messages are discarded and only the active chat history window is used for multi-turn context. (非必填)
  "longTermMemoryTopK"?: integer // 長期記憶每次檢索取回的記憶節點數（向量檢索的 similarity_top_k），預設為 10，範圍 1–50 (非必填)
  "enableCrossConversationSearch"?: boolean // When enabled, the conversation history tools also reach this contact's other conversations in the same inbox, within the lookback window. When disabled, they only reach the current conversation. (非必填)
  "crossConversationLookbackDays"?: integer // How far back cross-conversation search may reach, measured from each conversation's last message (1-365 days). Leave empty to fall back to 90 days. Only effective when enable_cross_conversation_search is True. (非必填)
  "useGatewayFallback"?: boolean // When enabled, use the fallback group instead of the single LLM (非必填)
  "gatewayFallbackGroup"?: string (uuid) // 非必填
  "enableSearchMessagesTool"?: boolean // Allow the AI to search past messages in the current conversation. (非必填)
  "enableGetMessageContextTool"?: boolean // Allow the AI to retrieve messages surrounding a specific message for context. (非必填)
  "enableReadAttachmentFullTextTool"?: boolean // Allow the AI to read the full text of plain-text attachments. AGENT mode only. (非必填)
  "enableParseAttachmentContentTool"?: boolean // Allow the AI to parse PDF, Office, audio, and other attachments. AGENT mode only. (非必填)
  "enableListAvailableParsersTool"?: boolean // Allow the AI to list available parsers and their capabilities. AGENT mode only. (非必填)
  "enableGetDownloadLinkTool"?: boolean // Allow the AI to generate shareable download links for produced content. AGENT mode only. (非必填)
  "isLocked": boolean // Locked instance: config follows the official version; only the dedicated KB can be modified
  "sourceBuildInAgent": string (uuid) // Points to the official Build-in Agent blueprint when instantiated by a rental
```

```
  "canUpdate": boolean // Return whether the current user can update this resource.
  "canDelete": boolean // Return whether the current user can delete this resource.
  "team":
  {
    "id": string (uuid)
    "name": string
  }
  "webChatIsActive"?: boolean // Optional, create only. Whether the web widget channel
starts active. Omitted or null: follows the organization's default for new chatbot
channels (inactive unless a platform admin turned it on). Ignored on update; change an
existing channel from its channel settings instead. (非必填)
  "apiIsActive"?: boolean // Optional, create only. Whether the API channel starts
active. Omitted or null: follows the organization's default for new chatbot channels
(inactive unless a platform admin turned it on). Ignored on update; change an existing
channel from its channel settings instead. The backstage (admin) channel always starts
active and cannot be set here. (非必填)
  "fileWorkspaceMode"?:  // File workspace mode in Work internal conversations: none,
bound or user_mount.

* `none` - None
* `bound` - Bound workspace
* `user_mount` - User mount (非必填)
  {
  }
  "fileWorkspaceFolder"?: string (uuid) // The bound workspace (folder id); required when
the mode is bound, cleared otherwise. (非必填)
  "fileWorkspaceStatus": object // Read-only. {"folder": {"id", "name"} | null, "state":
"ok" | "missing" | "builder_lost_edit" | null}
  "fileWorkspaceAvailable": boolean // Read-only. Whether the organization has the file
library and this agent can configure a file workspace.
}
```

回應範例值

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "name": "回應字串",
  "largeLanguageModel": "550e8400-e29b-41d4-a716-446655440000",
  "llm": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應字串",
    "retiresAt": "回應字串",
    "replacement": {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "回應字串"
    }
  },
  "embeddingModel": "550e8400-e29b-41d4-a716-446655440000",
  "rerankerModel": "550e8400-e29b-41d4-a716-446655440000",
  "instructions": "回應字串",
  "knowledgeBases": [
    {
```

```
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "回應字串"
    }
  ],
  "databases": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "回應字串"
    }
  ],
  "updatedAt": "回應字串",
  "organization": "550e8400-e29b-41d4-a716-446655440000",
  "replyMode": {},
  "template": "回應字串",
  "unanswerableTemplate": "回應字串",
  "totalWordsCount": 456,
  "outputMode": {},
  "rawOutputFormat": null,
  "groups": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "回應字串"
    }
  ],
  "tools": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "回應字串",
      "description": "回應字串",
      "displayName": "回應字串",
      "toolType": "回應字串"
    }
  ],
  "skills": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "回應字串",
      "description": "回應字串"
    }
  ],
  "connectors": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "回應字串"
    }
  ],
  "agentMode": {},
  "numberOfRetrievedChunks": 456,
  "defaultLabelRelations": null,
  "useFullRetrievalRange": false,
  "enableEvaluation": false,
  "enableInlineCitations": false,
  "enableCodeInterpreter": false,
```

```
  "enableBrowserTool": false,
  "enableImageSearch": false,
  "enableClaudeStreamRetry": false,
  "customMaxLlmOutputTokens": 456,
  "voiceConfig": {
    "enabled": false,
    "voiceAgentType": "550e8400-e29b-41d4-a716-446655440000",
    "sttProvider": "550e8400-e29b-41d4-a716-446655440000",
    "sttConfig": null,
    "ttsProvider": "550e8400-e29b-41d4-a716-446655440000",
    "ttsConfig": null,
    "realtimeProvider": "550e8400-e29b-41d4-a716-446655440000",
    "realtimeConfig": null,
    "realtimeInstructions": "回應字串",
    "turnHandling": null,
    "enableVoiceReply": false
  },
  "thinkingConfig": null,
  "enableToolSearching": false,
  "maxAgentIterations": 456,
  "agentTimeoutSeconds": 456,
  "agentTimeoutMessage": "回應字串",
  "requireTextWithFlexCards": false,
  "isMultimodalLlm": false,
  "enableSizeBasedToolResultTruncation": false,
  "toolResultMaxChars": 456,
  "enableVectorMemory": false,
  "longTermMemoryTopK": 456,
  "enableCrossConversationSearch": false,
  "crossConversationLookbackDays": 456,
  "useGatewayFallback": false,
  "gatewayFallbackGroup": "550e8400-e29b-41d4-a716-446655440000",
  "enableSearchMessagesTool": false,
  "enableGetMessageContextTool": false,
  "enableReadAttachmentFullTextTool": false,
  "enableParseAttachmentContentTool": false,
  "enableListAvailableParsersTool": false,
  "enableGetDownloadLinkTool": false,
  "isLocked": false,
  "sourceBuildInAgent": "550e8400-e29b-41d4-a716-446655440000",
  "canUpdate": false,
  "canDelete": false,
  "team": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應字串"
  },
  "webChatIsActive": false,
  "apiIsActive": false,
  "fileWorkspaceMode": {},
  "fileWorkspaceFolder": "550e8400-e29b-41d4-a716-446655440000",
  "fileWorkspaceStatus": {
    "name": "example.pdf",
    "content": "base64encoded_content",
```

```
    "contentType": "application/pdf"
  },
  "fileWorkspaceAvailable": false
}
```

刪除 AI 助理

DELETE `/api/v1/chatbots/{id}`

參數

參數名稱	必填	類型	說明
id	V	string	

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X DELETE "

  -H "Authorization: Api-Key YOUR_API_KEY"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

// 請求內容 (payload)
const data = null;

axios.delete(" data, config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```python
import requests

url = "
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.delete(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->delete(" [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼	說明
204	No response body

複製 AI 助理

POST `/api/v1/chatbots/{id}/duplicate/`

參數

參數名稱	必填	類型	說明
id	V	string	

請求內容

請求參數

欄位	類型	必填	說明
name	string	是	

請求結構範例

```
{
  "name": string
}
```

請求範例值

```
{
  "name": "範例名稱"
}
```

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X POST "

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "name": "範例名稱"
  }'

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// 請求內容 (payload)
const data = {
    "name": "範例名稱"
  };

axios.post(" data, config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# 請求內容 (payload)
data = {
    "name": "範例名稱"
}

response = requests.post(url, json=data, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->post(" [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'name' => '範例名稱'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 201

回應結構範例

```
{
  "id": string (uuid)
  "name": string // Chatbot name. In Agent mode it carries semantic meaning; in other modes it only distinguishes chatbots.
  "largeLanguageModel": string (uuid) // 機器人使用的大型語言模型，用於生成回答（含組織自建的 AI Gateway 模型）
  "llm":  // 綁定模型的 id、name 與退役資訊，直接讀取 FK，即使該模型已被組織停用仍會回傳
  {
    "id": string (uuid)
```

```
    "name": string
    "retiresAt": string (date) // 供應商退役日；到期後每日排程會把助理換到 replacement 並停用此模型。null 表示未排定退役
    "replacement":  // 退役後接手的模型（id 與 name）；null 表示未指定，到期時不會自動搬移
    {
      "id": string (uuid)
      "name": string
    }
  }
  "embeddingModel"?: string (uuid) // 用於向量化文本的嵌入模型，非必填項目 (非必填)
  "rerankerModel"?: string (uuid) // 用於重新排序的模型，非必填項目 (非必填)
  "instructions"?: string // Role instructions describing the chatbot's role and behavior. (非必填)
  "knowledgeBases"?: [ // 機器人可存取的知識庫列表 (非必填)
    {
      "id": string (uuid)
      "name": string
    }
  ]
  "databases"?: [ // 機器人可存取的 SQL 資料庫列表（用於 Text-to-SQL 功能） (非必填)
    {
      "id": string (uuid)
      "name": string
    }
  ]
  "updatedAt": string (timestamp)
  "organization"?: string (uuid) // 機器人所屬的組織，如果為空則為個人機器人 (非必填)
  "replyMode"?:  // 回覆模式：一般回覆或串流回覆

* `normal` - 正常
* `template` - 模板
* `hybrid` - 混合
* `agent` - 代理 (非必填)
  {
  }
  "template"?: string // Template used by Template and Hybrid modes. (非必填)
  "unanswerableTemplate"?: string // Template used by Template and Hybrid modes when the question cannot be answered. (非必填)
  "totalWordsCount"?: integer (int64) // Accumulated total word count used. (非必填)
  "outputMode"?:  // 輸出模式：文字、表格或自定義格式

* `text` - 文字
* `json_schema` - JSON Schema (非必填)
  {
  }
  "rawOutputFormat"?: object // 自定義輸出格式的JSON結構定義 (非必填)
  "groups"?: [ // 機器人可存取的群組列表 (非必填)
    {
      "id": string (uuid)
      "name": string
    }
  ]
  "tools"?: [ // 機器人可使用的工具列表 (非必填)
```

```
    {
      "id": string (uuid)
      "name": string
      "description": string
      "displayName": string
      "toolType": string
    }
  ]
  "skills"?: [ // 機器人關聯的技能列表 (非必填)
    {
      "id": string (uuid)
      "name": string
      "description": string
    }
  ]
  "connectors"?: [ // Connectors associated with this chatbot, gating per-contact OAuth
authorization (非必填)
    {
      "id": string (uuid)
      "name": string
    }
  ]
  "agentMode"?:  // 代理模式：一般、SQL或工作流程模式

* `normal` - 正常
* `canvas` - 畫布
* `team` - 團隊 (非必填)
  {
  }
  "numberOfRetrievedChunks"?: integer // 提取的參考資料數量，預設為 12，最小值為 1 (非必填)
  "defaultLabelRelations"?: object // 助理層級的預設知識庫標籤過濾條件，格式同
query_metadata.label_relations；null 表示不過濾。僅在呼叫端未帶 query_metadata 時作為最低優先序兜
底套用。 (非必填)
  "useFullRetrievalRange"?: boolean // 啟用後忽略 LLM 的 top_k 截斷，回傳完整 reranker 結果
(非必填)
  "enableEvaluation"?: boolean // 非必填
  "enableInlineCitations"?: boolean // Enables inline citations, inserting citation
markers such as [1][2] into responses. (非必填)
  "enableCodeInterpreter"?: boolean // When enabled, provides the Code Interpreter tool
to run code in an isolated container. (非必填)
  "enableBrowserTool"?: boolean // Enable browser automation tool for web tasks (非必填)
  "enableImageSearch"?: boolean // Provide the image_search tool when any attached
knowledge base uses a multimodal embedding model. Disable to remove the tool entirely.
(非必填)
  "enableClaudeStreamRetry"?: boolean // When a Claude streaming call stalls (first-chunk
or mid-stream), abort and re-issue the call once in non-streaming mode. Mid-stream
retries send a reset signal so the client discards any partial output already rendered.
Each retry incurs a second billing for the same prompt. (非必填)
  "customMaxLlmOutputTokens"?: integer // 自訂最大 LLM 輸出 token 數，最小值為 512 (非必填)
  "voiceConfig"?: { // 非必填
  {
    "enabled"?: boolean // Whether this chatbot can be used as a voice agent. Checked by
every conversation platform (WebChat, SIP phone, admin/marketplace voice test) instead of
```

```
a per-platform toggle. (非必填)
    "voiceAgentType"?: string (uuid) // Voice agent mode type. (非必填)
    "sttProvider"?: string (uuid) // Speech-to-Text service provider. (非必填)
    "sttConfig"?: object // STT configuration parameters (JSON). (非必填)
    "ttsProvider"?: string (uuid) // Text-to-Speech service provider. (非必填)
    "ttsConfig"?: object // TTS configuration parameters (JSON). (非必填)
    "realtimeProvider"?: string (uuid) // Realtime end-to-end voice model provider. (非必填)
    "realtimeConfig"?: object // Realtime configuration parameters (JSON). (非必填)
    "realtimeInstructions"?: string // Prompt dedicated to the realtime voice session; falls back to chatbot instructions when empty (非必填)
    "turnHandling"?: object // Turn-taking and interruption settings for the voice agent. (非必填)
    "enableVoiceReply"?: boolean // When disabled, the voice agent replies in text only and does not speak (非必填)
  }
  }
  "thinkingConfig"?: object // 思考等級：null（模型預設）或 {"reasoning_effort": "off|minimal|low|medium|high|xhigh|max"} (非必填)
  "enableToolSearching"?: boolean // 啟用動態工具搜尋功能，允許 agent 透過 tool_searching_tool 動態發現和加載工具 (非必填)
  "maxAgentIterations"?: integer // Maximum number of iterations for AgentWorkflow (1-100, default: 20) (非必填)
  "agentTimeoutSeconds"?: integer // Timeout in seconds for AgentWorkflow execution (30-1200, default: 600) (非必填)
  "agentTimeoutMessage"?: string // Custom user-facing message shown when AgentWorkflow times out (max 500 chars). Leave empty to use the system default. (非必填)
  "requireTextWithFlexCards"?: boolean // When enabled, a turn that would end with only Flex Message cards and no text for the user is re-issued to the LLM once, asking it to write the text first and then send the card. Each retry incurs a second billing for the same prompt. (非必填)
  "isMultimodalLlm": boolean // Whether the chatbot LLM supports multimodal (read-only)
  "enableSizeBasedToolResultTruncation"?: boolean // When enabled, tool results exceeding the character threshold are kept as head+tail (with the identifiers found in the cut part) when written to conversation history; knowledge base, SQL and conversation search results keep their 100-character cut either way. Reduces memory bloat from large tool outputs (code interpreter bash stdout, web search results, etc.). (非必填)
  "toolResultMaxChars"?: integer // Character threshold for size-based tool result truncation (500-50000). Only effective when enable_size_based_tool_result_truncation is True. (非必填)
  "enableVectorMemory"?: boolean // When enabled, archived messages are vectorized and processed by fact extraction for semantic retrieval (existing behavior). When disabled, archived messages are discarded and only the active chat history window is used for multi-turn context. (非必填)
  "longTermMemoryTopK"?: integer // 長期記憶每次檢索取回的記憶節點數（向量檢索的 similarity_top_k），預設為 10，範圍 1–50 (非必填)
  "enableCrossConversationSearch"?: boolean // When enabled, the conversation history tools also reach this contact's other conversations in the same inbox, within the lookback window. When disabled, they only reach the current conversation. (非必填)
  "crossConversationLookbackDays"?: integer // How far back cross-conversation search may reach, measured from each conversation's last message (1-365 days). Leave empty to fall back to 90 days. Only effective when enable_cross_conversation_search is True. (非必填)
  "useGatewayFallback"?: boolean // When enabled, use the fallback group instead of the
```

```
single LLM (非必填)
  "gatewayFallbackGroup"?: string (uuid) // 非必填
  "enableSearchMessagesTool"?: boolean // Allow the AI to search past messages in the
current conversation. (非必填)
  "enableGetMessageContextTool"?: boolean // Allow the AI to retrieve messages
surrounding a specific message for context. (非必填)
  "enableReadAttachmentFullTextTool"?: boolean // Allow the AI to read the full text of
plain-text attachments. AGENT mode only. (非必填)
  "enableParseAttachmentContentTool"?: boolean // Allow the AI to parse PDF, Office,
audio, and other attachments. AGENT mode only. (非必填)
  "enableListAvailableParsersTool"?: boolean // Allow the AI to list available parsers
and their capabilities. AGENT mode only. (非必填)
  "enableGetDownloadLinkTool"?: boolean // Allow the AI to generate shareable download
links for produced content. AGENT mode only. (非必填)
  "isLocked": boolean // Locked instance: config follows the official version; only the
dedicated KB can be modified
  "sourceBuildInAgent": string (uuid) // Points to the official Build-in Agent blueprint
when instantiated by a rental
  "canUpdate": boolean // Return whether the current user can update this resource.
  "canDelete": boolean // Return whether the current user can delete this resource.
  "team":
  {
    "id": string (uuid)
    "name": string
  }
  "webChatIsActive"?: boolean // Optional, create only. Whether the web widget channel
starts active. Omitted or null: follows the organization's default for new chatbot
channels (inactive unless a platform admin turned it on). Ignored on update; change an
existing channel from its channel settings instead. (非必填)
  "apiIsActive"?: boolean // Optional, create only. Whether the API channel starts
active. Omitted or null: follows the organization's default for new chatbot channels
(inactive unless a platform admin turned it on). Ignored on update; change an existing
channel from its channel settings instead. The backstage (admin) channel always starts
active and cannot be set here. (非必填)
  "fileWorkspaceMode"?:  // File workspace mode in Work internal conversations: none,
bound or user_mount.

* `none` - None
* `bound` - Bound workspace
* `user_mount` - User mount (非必填)
  {
  }
  "fileWorkspaceFolder"?: string (uuid) // The bound workspace (folder id); required when
the mode is bound, cleared otherwise. (非必填)
  "fileWorkspaceStatus": object // Read-only. {"folder": {"id", "name"} | null, "state":
"ok" | "missing" | "builder_lost_edit" | null}
  "fileWorkspaceAvailable": boolean // Read-only. Whether the organization has the file
library and this agent can configure a file workspace.
}
```

回應範例值

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "name": "回應字串",
  "largeLanguageModel": "550e8400-e29b-41d4-a716-446655440000",
  "llm": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應字串",
    "retiresAt": "回應字串",
    "replacement": {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "回應字串"
    }
  },
  "embeddingModel": "550e8400-e29b-41d4-a716-446655440000",
  "rerankerModel": "550e8400-e29b-41d4-a716-446655440000",
  "instructions": "回應字串",
  "knowledgeBases": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "回應字串"
    }
  ],
  "databases": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "回應字串"
    }
  ],
  "updatedAt": "回應字串",
  "organization": "550e8400-e29b-41d4-a716-446655440000",
  "replyMode": {},
  "template": "回應字串",
  "unanswerableTemplate": "回應字串",
  "totalWordsCount": 456,
  "outputMode": {},
  "rawOutputFormat": null,
  "groups": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "回應字串"
    }
  ],
  "tools": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "回應字串",
      "description": "回應字串",
      "displayName": "回應字串",
      "toolType": "回應字串"
    }
  ],
  "skills": [
    {
```

```
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "回應字串",
      "description": "回應字串"
    }
  ],
  "connectors": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "回應字串"
    }
  ],
  "agentMode": {},
  "numberOfRetrievedChunks": 456,
  "defaultLabelRelations": null,
  "useFullRetrievalRange": false,
  "enableEvaluation": false,
  "enableInlineCitations": false,
  "enableCodeInterpreter": false,
  "enableBrowserTool": false,
  "enableImageSearch": false,
  "enableClaudeStreamRetry": false,
  "customMaxLlmOutputTokens": 456,
  "voiceConfig": {
    "enabled": false,
    "voiceAgentType": "550e8400-e29b-41d4-a716-446655440000",
    "sttProvider": "550e8400-e29b-41d4-a716-446655440000",
    "sttConfig": null,
    "ttsProvider": "550e8400-e29b-41d4-a716-446655440000",
    "ttsConfig": null,
    "realtimeProvider": "550e8400-e29b-41d4-a716-446655440000",
    "realtimeConfig": null,
    "realtimeInstructions": "回應字串",
    "turnHandling": null,
    "enableVoiceReply": false
  },
  "thinkingConfig": null,
  "enableToolSearching": false,
  "maxAgentIterations": 456,
  "agentTimeoutSeconds": 456,
  "agentTimeoutMessage": "回應字串",
  "requireTextWithFlexCards": false,
  "isMultimodalLlm": false,
  "enableSizeBasedToolResultTruncation": false,
  "toolResultMaxChars": 456,
  "enableVectorMemory": false,
  "longTermMemoryTopK": 456,
  "enableCrossConversationSearch": false,
  "crossConversationLookbackDays": 456,
  "useGatewayFallback": false,
  "gatewayFallbackGroup": "550e8400-e29b-41d4-a716-446655440000",
  "enableSearchMessagesTool": false,
  "enableGetMessageContextTool": false,
  "enableReadAttachmentFullTextTool": false,
```

```
  "enableParseAttachmentContentTool": false,
  "enableListAvailableParsersTool": false,
  "enableGetDownloadLinkTool": false,
  "isLocked": false,
  "sourceBuildInAgent": "550e8400-e29b-41d4-a716-446655440000",
  "canUpdate": false,
  "canDelete": false,
  "team": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應字串"
  },
  "webChatIsActive": false,
  "apiIsActive": false,
  "fileWorkspaceMode": {},
  "fileWorkspaceFolder": "550e8400-e29b-41d4-a716-446655440000",
  "fileWorkspaceStatus": {
    "name": "example.pdf",
    "content": "base64encoded_content",
    "contentType": "application/pdf"
  },
  "fileWorkspaceAvailable": false
}
```


啟用或停用評估功能

PATCH `/api/v1/chatbots/{id}/enable-evaluation/`

參數

參數名稱	必填	類型	說明
id	V	string	

請求內容

請求參數

欄位	類型	必填	說明
enableEvaluation	boolean	否	

請求結構範例

```
{
  "enableEvaluation"?: boolean // 非必填
}
```

請求範例值

```
{
  "enableEvaluation": true
}
```

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X PATCH "

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "enableEvaluation": true
  }'

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// 請求內容 (payload)
const data = {
    "enableEvaluation": true
  };

axios.patch(" data, config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# 請求內容 (payload)
data = {
    "enableEvaluation": True
}

response = requests.patch(url, json=data, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->patch(" [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'enableEvaluation' => true
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
{
  "enableEvaluation"?: boolean // 非必填
}
```

回應範例值

```
{
  "enableEvaluation": false
```

```
}
```

列出組織的 Hook

GET `/api/v1/hooks/`

Hook 由 Hook 樣板建立，觸發點與處理方式由樣板決定，建立時不能自行指定；掛載到 AI 助理後會在訊息進出時執行。功能說明見使用者手冊 Hook 訊息攔截。

參數

參數名稱	必填	類型	說明
`page`	X	integer	A page number within the paginated result set.
`pageSize`	X	integer	Number of results to return per page.
`search`	X	string	A search term.

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/hooks/?page=1&pageSize=1&search=example"

  -H "Authorization: Api-Key YOUR_API_KEY"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/hooks/?page=1&pageSize=1&search=example",
config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/hooks/?page=1&pageSize=1&search=example"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->get("https://api.maiagent.ai/api/v1/hooks/?
page=1&pageSize=1&search=example", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
{
  "count": integer
  "next"?: string (uri) // 非必填
  "previous"?: string (uri) // 非必填
  "results": [
    {
      "id": string (uuid)
      "organization": string (uuid)
      "templateId": string (uuid)
      "templateName": string
      "templateTypeLabel": string
      "scope": string
```

```
      "name": string
      "description": string
      "triggerPoint": string
      "action": string
      "handlerType": string
      "config": object
      "blockMessage": string
      "enabled": boolean
      "createdBy": object
      "chatbots": [ // Attached AI assistants for the list column. Uses the prefetched
``chatbot_attachments`` (see ``HookViewSet.get_queryset``) to avoid N+1.
        object
      ]
      "canUpdate": boolean // Return whether the current user can update this resource.
      "canDelete": boolean // Return whether the current user can delete this resource.
      "createdAt": string (timestamp)
      "updatedAt": string (timestamp)
    }
  ]
}
```

回應範例值

```
{
  "count": 123,
  "next": "http://api.example.org/accounts/?page=4",
  "previous": "http://api.example.org/accounts/?page=2",
  "results": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "organization": "550e8400-e29b-41d4-a716-446655440000",
      "templateId": "550e8400-e29b-41d4-a716-446655440000",
      "templateName": "回應字串",
      "templateTypeLabel": "回應字串",
      "scope": "回應字串",
      "name": "回應字串",
      "description": "回應字串",
      "triggerPoint": "回應字串",
      "action": "回應字串",
      "handlerType": "回應字串",
      "config": null,
      "blockMessage": "回應字串",
      "enabled": false,
      "createdBy": {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "name": "回應範例名稱",
        "description": "回應範例描述"
      },
      "chatbots": [
        {
          "id": "550e8400-e29b-41d4-a716-446655440000",
          "name": "回應範例名稱",
```

```
          "description": "回應範例描述"
        }
      ],
      "canUpdate": false,
      "canDelete": false,
      "createdAt": "回應字串",
      "updatedAt": "回應字串"
    }
  ]
}
```

依樣板建立 Hook

POST `/api/v1/hooks/`

請求內容

請求參數

欄位	類型	必填	說明
templateId	string (uuid)	是	
name	string	是	
description	string	否	
config	object	否	
blockMessage	string	否	
enabled	boolean	否	

請求結構範例

```
{
  "templateId": string (uuid)
  "name": string
  "description"?: string // 非必填
  "config"?: object // 非必填
  "blockMessage"?: string // 非必填
  "enabled"?: boolean // 非必填
}
```

請求範例值


```
{
  "template_id": "00000000-0000-0000-0000-000000000001",
  "name": "Customer PII Redaction",
  "description": "Mask phone numbers and emails in inbound messages.",
  "config": {
    "data": {
      "patterns": [
        "phone",
        "email"
      ],
      "mode": "mask"
    }
  },
  "block_message": "",
  "enabled": true
}
```


程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X POST "https://api.maiagent.ai/api/v1/hooks/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "template_id": "00000000-0000-0000-0000-000000000001",
    "name": "Customer PII Redaction",
    "description": "Mask phone numbers and emails in inbound messages.",
    "config": {
      "data": {
        "patterns": [
          "phone",
          "email"
        ],
        "mode": "mask"
      }
    },
    "block_message": "",
    "enabled": true
  }'

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// 請求內容 (payload)
const data = {
    "template_id": "00000000-0000-0000-0000-000000000001",
    "name": "Customer PII Redaction",
    "description": "Mask phone numbers and emails in inbound messages.",
    "config": {
      "data": {
        "patterns": [
          "phone",
          "email"
        ],
        "mode": "mask"
      }
    },
    "block_message": "",
    "enabled": true
  };

axios.post("https://api.maiagent.ai/api/v1/hooks/", data, config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/hooks/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# 請求內容 (payload)
data = {
    "template_id": "00000000-0000-0000-0000-000000000001",
    "name": "Customer PII Redaction",
    "description": "Mask phone numbers and emails in inbound messages.",
    "config": {
        "data": {
            "patterns": [
                "phone",
                "email"
            ],
            "mode": "mask"
        }
    },
    "block_message": "",
    "enabled": True
}

response = requests.post(url, json=data, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->post("https://api.maiagent.ai/api/v1/hooks/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'template_id' => '00000000-0000-0000-0000-000000000001',
            'name' => 'Customer PII Redaction',
            'description' => 'Mask phone numbers and emails in inbound messages.',
            'config' => [
                'data' => [
                    'patterns' => [
                        'phone',
                        'email'
                    ],
                    'mode' => 'mask'
                ]
            ],
            'block_message' => '',
            'enabled' => true
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 201

回應結構範例

```
{
  "id": string (uuid)
  "organization": string (uuid)
  "templateId": string (uuid)
  "templateName": string
  "templateTypeLabel": string
  "scope": string
  "name": string
  "description": string
  "triggerPoint": string
  "action": string
  "handlerType": string
  "config": object
  "blockMessage": string
  "enabled": boolean
  "createdBy": object
  "chatbots": [ // Attached AI assistants for the list column. Uses the prefetched
``chatbot_attachments`` (see ``HookViewSet.get_queryset``) to avoid N+1.
    object
  ]
  "canUpdate": boolean // Return whether the current user can update this resource.
  "canDelete": boolean // Return whether the current user can delete this resource.
  "createdAt": string (timestamp)
  "updatedAt": string (timestamp)
}
```

回應範例值

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "organization": "550e8400-e29b-41d4-a716-446655440000",
  "templateId": "550e8400-e29b-41d4-a716-446655440000",
  "templateName": "回應字串",
  "templateTypeLabel": "回應字串",
  "scope": "回應字串",
  "name": "回應字串",
  "description": "回應字串",
  "triggerPoint": "回應字串",
  "action": "回應字串",
  "handlerType": "回應字串",
  "config": null,
  "blockMessage": "回應字串",
  "enabled": false,
  "createdBy": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應範例名稱",
    "description": "回應範例描述"
  },
  "chatbots": [
```

```
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "回應範例名稱",
      "description": "回應範例描述"
    }
  ],
  "canUpdate": false,
  "canDelete": false,
  "createdAt": "回應字串",
  "updatedAt": "回應字串"
}
```

取得特定 Hook

GET `/api/v1/hooks/{id}`

參數

參數名稱	必填	類型	說明
id	V	string	

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/hooks/550e8400-e29b-41d4-a716-
446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/hooks/550e8400-e29b-41d4-a716-
446655440000/", config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/hooks/550e8400-e29b-41d4-a716-446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->get("https://api.maiagent.ai/api/v1/hooks/550e8400-e29b-
41d4-a716-446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
{
  "id": string (uuid)
  "organization": string (uuid)
  "templateId": string (uuid)
  "templateName": string
  "templateTypeLabel": string
  "scope": string
  "name": string
  "description": string
  "triggerPoint": string
  "action": string
  "handlerType": string
```

```
  "config": object
  "blockMessage": string
  "enabled": boolean
  "createdBy": object
  "chatbots": [ // Attached AI assistants for the list column. Uses the prefetched
``chatbot_attachments`` (see ``HookViewSet.get_queryset``) to avoid N+1.
    object
  ]
  "canUpdate": boolean // Return whether the current user can update this resource.
  "canDelete": boolean // Return whether the current user can delete this resource.
  "createdAt": string (timestamp)
  "updatedAt": string (timestamp)
}
```

回應範例值

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "organization": "550e8400-e29b-41d4-a716-446655440000",
  "templateId": "550e8400-e29b-41d4-a716-446655440000",
  "templateName": "回應字串",
  "templateTypeLabel": "回應字串",
  "scope": "回應字串",
  "name": "回應字串",
  "description": "回應字串",
  "triggerPoint": "回應字串",
  "action": "回應字串",
  "handlerType": "回應字串",
  "config": null,
  "blockMessage": "回應字串",
  "enabled": false,
  "createdBy": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應範例名稱",
    "description": "回應範例描述"
  },
  "chatbots": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "回應範例名稱",
      "description": "回應範例描述"
    }
  ],
  "canUpdate": false,
  "canDelete": false,
  "createdAt": "回應字串",
  "updatedAt": "回應字串"
}
```

部分更新 Hook

PATCH `/api/v1/hooks/{id}`

參數

參數名稱	必填	類型	說明
id	V	string	

請求內容

請求參數

欄位	類型	必填	說明
name	string	否	
description	string	否	
config	object	否	
blockMessage	string	否	
enabled	boolean	否	

請求結構範例

```
{
  "name"?: string // 非必填
  "description"?: string // 非必填
  "config"?: object // 非必填
  "blockMessage"?: string // 非必填
  "enabled"?: boolean // 非必填
}
```

請求範例值

```
{
  "name": "範例名稱",
  "description": "範例字串",
  "config": null,
```

```
  "blockMessage": "範例字串",
  "enabled": true
}
```

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X PATCH "https://api.maiagent.ai/api/v1/hooks/550e8400-e29b-41d4-a716-
446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "name": "範例名稱",
    "description": "範例字串",
    "config": null,
    "blockMessage": "範例字串",
    "enabled": true
  }'

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// 請求內容 (payload)
const data = {
    "name": "範例名稱",
    "description": "範例字串",
    "config": null,
    "blockMessage": "範例字串",
    "enabled": true
  };

axios.patch("https://api.maiagent.ai/api/v1/hooks/550e8400-e29b-41d4-a716-
446655440000/", data, config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/hooks/550e8400-e29b-41d4-a716-446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# 請求內容 (payload)
data = {
    "name": "範例名稱",
    "description": "範例字串",
    "config": None,
    "blockMessage": "範例字串",
    "enabled": True
}

response = requests.patch(url, json=data, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->patch("https://api.maiagent.ai/api/v1/hooks/550e8400-e29b-41d4-a716-446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'name' => '範例名稱',
            'description' => '範例字串',
            'config' => null,
            'blockMessage' => '範例字串',
            'enabled' => true
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
{
  "id": string (uuid)
  "organization": string (uuid)
  "templateId": string (uuid)
```

```
  "templateName": string
  "templateTypeLabel": string
  "scope": string
  "name": string
  "description": string
  "triggerPoint": string
  "action": string
  "handlerType": string
  "config": object
  "blockMessage": string
  "enabled": boolean
  "createdBy": object
  "chatbots": [ // Attached AI assistants for the list column. Uses the prefetched
``chatbot_attachments`` (see ``HookViewSet.get_queryset``) to avoid N+1.
    object
  ]
  "canUpdate": boolean // Return whether the current user can update this resource.
  "canDelete": boolean // Return whether the current user can delete this resource.
  "createdAt": string (timestamp)
  "updatedAt": string (timestamp)
}
```

回應範例值

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "organization": "550e8400-e29b-41d4-a716-446655440000",
  "templateId": "550e8400-e29b-41d4-a716-446655440000",
  "templateName": "回應字串",
  "templateTypeLabel": "回應字串",
  "scope": "回應字串",
  "name": "回應字串",
  "description": "回應字串",
  "triggerPoint": "回應字串",
  "action": "回應字串",
  "handlerType": "回應字串",
  "config": null,
  "blockMessage": "回應字串",
  "enabled": false,
  "createdBy": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應範例名稱",
    "description": "回應範例描述"
  },
  "chatbots": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "回應範例名稱",
      "description": "回應範例描述"
    }
  ],
  "canUpdate": false,
```

```
  "canDelete": false,
  "createdAt": "回應字串",
  "updatedAt": "回應字串"
}
```

刪除 Hook

DELETE `/api/v1/hooks/{id}`

參數

參數名稱	必填	類型	說明
id	V	string	

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X DELETE "https://api.maiagent.ai/api/v1/hooks/550e8400-e29b-41d4-a716-
446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

// 請求內容 (payload)
const data = null;

axios.delete("https://api.maiagent.ai/api/v1/hooks/550e8400-e29b-41d4-a716-
446655440000/", data, config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/hooks/550e8400-e29b-41d4-a716-446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.delete(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->delete("https://api.maiagent.ai/api/v1/hooks/550e8400-e29b-
41d4-a716-446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼	說明
204	No response body

列出 AI 助理掛載的 Hook

GET `/api/v1/chatbots/{chatbotId}/hooks/`

參數

參數名稱	必填	類型	說明
chatbotId	V	string	

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X GET "

  -H "Authorization: Api-Key YOUR_API_KEY"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get(" config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->get(" [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
{
  "results": [
    {
      "id": string (uuid)
      "name": string
      "scope": string
      "templateName": string
      "templateTypeLabel": string
      "triggerPoint": string
      "action": string
      "enabled": boolean
      "order": integer
    }
```

```
  ]
}
```

回應範例值

```
{
  "results": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "回應字串",
      "scope": "回應字串",
      "templateName": "回應字串",
      "templateTypeLabel": "回應字串",
      "triggerPoint": "回應字串",
      "action": "回應字串",
      "enabled": false,
      "order": 456
    }
  ]
}
```

整批替換 AI 助理掛載的 Hook

PUT `/api/v1/chatbots/{chatbotId}/hooks/`

參數

參數名稱	必填	類型	說明
chatbotId	V	string	

請求內容

請求參數

欄位	類型	必填	說明
hookIds	array[string]	是	

請求結構範例

```
{
  "hookIds": [
    string (uuid)
  ]
}
```

請求範例值

```
{
  "hookIds": [
    "550e8400-e29b-41d4-a716-446655440000"
  ]
}
```

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X PUT "

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "hookIds": [
      "550e8400-e29b-41d4-a716-446655440000"
    ]
  }'

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// 請求內容 (payload)
const data = {
    "hookIds": [
      "550e8400-e29b-41d4-a716-446655440000"
    ]
  };

axios.put(" data, config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# 請求內容 (payload)
data = {
    "hookIds": [
        "550e8400-e29b-41d4-a716-446655440000"
    ]
}

response = requests.put(url, json=data, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->put(" [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'hookIds' => [
                '550e8400-e29b-41d4-a716-446655440000'
            ]
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
{
  "results": [
    {
      "id": string (uuid)
      "name": string
      "scope": string
      "templateName": string
```

```
      "templateTypeLabel": string
      "triggerPoint": string
      "action": string
      "enabled": boolean
      "order": integer
    }
  ]
}
```

回應範例值

```
{
  "results": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "回應字串",
      "scope": "回應字串",
      "templateName": "回應字串",
      "templateTypeLabel": "回應字串",
      "triggerPoint": "回應字串",
      "action": "回應字串",
      "enabled": false,
      "order": 456
    }
  ]
}
```

列出排程

`GET` `/api/v1/schedules/`

排程會在指定時間以 AI 助理執行一段指令；建立時系統自動配置專用的聯絡人與對話。

參數

參數名稱	必填	類型	說明
`page`	X	integer	A page number within the paginated result set.
`pageSize`	X	integer	Number of results to return per page.

程式碼範例

Shell/Bash

```shell
# 呼叫 API 示例 (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/schedules/?page=1&pageSize=1"

  -H "Authorization: Api-Key YOUR_API_KEY"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```javascript
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/schedules/?page=1&pageSize=1", config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/schedules/?page=1&pageSize=1"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->get("https://api.maiagent.ai/api/v1/schedules/?
page=1&pageSize=1", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
{
  "count": integer
  "next"?: string (uri) // 非必填
  "previous"?: string (uri) // 非必填
  "results": [
    {
      "id": string (uuid)
      "name": string
      "prompt": string
      "chatbot": string (uuid)
      "chatbotName": string
      "executionMode": string (enum: in_context, isolated) // * `in_context` - In Context
* `isolated` - Isolated
      "scheduleType": string (enum: cron, interval, one_shot) // * `cron` - Cron
* `interval` - Interval
* `one_shot` - One Shot
      "cronExpression"?: string // 非必填
      "intervalSeconds"?: integer // 非必填
      "oneShotAt"?: string (timestamp) // 非必填
      "deliveryConversationIds"?: [ // 非必填
        string (uuid)
      ]
      "deliveryWebhookUrls"?: [ // 非必填
        string (uri)
      ]
      "saveResultToContext"?: boolean // 非必填
      "enabled"?: boolean // 非必填
      "lastExecutedAt"?: string (timestamp) // 非必填
      "executionCount"?: integer // 非必填
      "maxExecutions"?: integer // 非必填
      "countsTowardLimit": boolean
      "createdAt": string (timestamp)
    }
  ]
}
```

回應範例值

```
{
  "count": 123,
  "next": "http://api.example.org/accounts/?page=4",
```

```
  "previous": "http://api.example.org/accounts/?page=2",
  "results": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "回應字串",
      "prompt": "回應字串",
      "chatbot": "550e8400-e29b-41d4-a716-446655440000",
      "chatbotName": "回應字串",
      "executionMode": "in_context",
      "scheduleType": "cron",
      "cronExpression": "回應字串",
      "intervalSeconds": 456,
      "oneShotAt": "回應字串",
      "deliveryConversationIds": [
        "550e8400-e29b-41d4-a716-446655440000"
      ],
      "deliveryWebhookUrls": [
        "https://example.com/file.jpg"
      ],
      "saveResultToContext": false,
      "enabled": false,
      "lastExecutedAt": "回應字串",
      "executionCount": 456,
      "maxExecutions": 456,
      "countsTowardLimit": false,
      "createdAt": "回應字串"
    }
  ]
}
```


建立排程

`POST` `/api/v1/schedules/`

請求內容

請求參數

欄位	類型	必填	說明
chatbot	string (uuid)	是	
name	string	是	

欄位	類型	必填	說明
executionMode	string (enum: in_context, isolated)	是	`in_context` : In Context ; `isolated` : Isolated;
prompt	string	是	
contextVariables	object	否	
inbox	string (uuid)	是	
saveResultToContext	boolean	否	
deliveryConversationIds	array[string]	否	
deliveryWebhookUrls	array[string]	否	
scheduleType	string (enum: cron, interval, one_shot)	是	`cron` : Cron ; `interval` : Interval ; `one_shot` : One Shot;
cronExpression	string	否	
intervalSeconds	integer	否	
oneShotAt	string (timestamp)	否	
timezone	string	否	
enabled	boolean	否	
maxExecutions	integer	否	

請求結構範例

```
{
  "chatbot": string (uuid)
  "name": string
  "executionMode": string (enum: in_context, isolated) // * `in_context` - In Context
* `isolated` - Isolated
  "prompt": string
  "contextVariables"?: object // 非必填
  "inbox": string (uuid)
  "saveResultToContext"?: boolean // 非必填
  "deliveryConversationIds"?: [ // 非必填
    string (uuid)
  ]
  "deliveryWebhookUrls"?: [ // 非必填
    string (uri)
  ]
  "scheduleType": string (enum: cron, interval, one_shot) // * `cron` - Cron
* `interval` - Interval
* `one_shot` - One Shot
  "cronExpression"?: string // 非必填
  "intervalSeconds"?: integer // 非必填
```

```
  "oneShotAt"?: string (timestamp) // 非必填
  "timezone"?: string // 非必填
  "enabled"?: boolean // 非必填
  "maxExecutions"?: integer // 非必填
}
```

請求範例值

```
{
  "chatbot": "550e8400-e29b-41d4-a716-446655440000",
  "name": "範例名稱",
  "executionMode": "in_context",
  "prompt": "範例字串",
  "contextVariables": null,
  "inbox": "550e8400-e29b-41d4-a716-446655440000",
  "saveResultToContext": true,
  "deliveryConversationIds": [
    "550e8400-e29b-41d4-a716-446655440000"
  ],
  "deliveryWebhookUrls": [
    "https://example.com/file.jpg"
  ],
  "scheduleType": "cron",
  "cronExpression": "範例字串",
  "intervalSeconds": 123,
  "oneShotAt": "範例字串",
  "timezone": "範例字串",
  "enabled": true,
  "maxExecutions": 123
}
```

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X POST "https://api.maiagent.ai/api/v1/schedules/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "chatbot": "550e8400-e29b-41d4-a716-446655440000",
    "name": "範例名稱",
    "executionMode": "in_context",
    "prompt": "範例字串",
    "contextVariables": null,
    "inbox": "550e8400-e29b-41d4-a716-446655440000",
    "saveResultToContext": true,
    "deliveryConversationIds": [
      "550e8400-e29b-41d4-a716-446655440000"
    ],
    "deliveryWebhookUrls": [
      "https://example.com/file.jpg"
    ],
    "scheduleType": "cron",
    "cronExpression": "範例字串",
    "intervalSeconds": 123,
    "oneShotAt": "範例字串",
    "timezone": "範例字串",
    "enabled": true,
    "maxExecutions": 123
  }'

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// 請求內容 (payload)
const data = {
    "chatbot": "550e8400-e29b-41d4-a716-446655440000",
    "name": "範例名稱",
    "executionMode": "in_context",
    "prompt": "範例字串",
    "contextVariables": null,
    "inbox": "550e8400-e29b-41d4-a716-446655440000",
    "saveResultToContext": true,
    "deliveryConversationIds": [
      "550e8400-e29b-41d4-a716-446655440000"
    ],
    "deliveryWebhookUrls": [
      "https://example.com/file.jpg"
    ],
    "scheduleType": "cron",
    "cronExpression": "範例字串",
    "intervalSeconds": 123,
    "oneShotAt": "範例字串",
    "timezone": "範例字串",
    "enabled": true,
    "maxExecutions": 123
  };

axios.post("https://api.maiagent.ai/api/v1/schedules/", data, config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/schedules/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# 請求內容 (payload)
data = {
    "chatbot": "550e8400-e29b-41d4-a716-446655440000",
    "name": "範例名稱",
    "executionMode": "in_context",
    "prompt": "範例字串",
    "contextVariables": None,
    "inbox": "550e8400-e29b-41d4-a716-446655440000",
    "saveResultToContext": True,
    "deliveryConversationIds": [
        "550e8400-e29b-41d4-a716-446655440000"
    ],
    "deliveryWebhookUrls": [
        "https://example.com/file.jpg"
    ],
    "scheduleType": "cron",
    "cronExpression": "範例字串",
    "intervalSeconds": 123,
    "oneShotAt": "範例字串",
    "timezone": "範例字串",
    "enabled": True,
    "maxExecutions": 123
}

response = requests.post(url, json=data, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->post("https://api.maiagent.ai/api/v1/schedules/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'chatbot' => '550e8400-e29b-41d4-a716-446655440000',
            'name' => '範例名稱',
            'executionMode' => 'in_context',
            'prompt' => '範例字串',
            'contextVariables' => null,
            'inbox' => '550e8400-e29b-41d4-a716-446655440000',
            'saveResultToContext' => true,
            'deliveryConversationIds' => [
                '550e8400-e29b-41d4-a716-446655440000'
            ],
            'deliveryWebhookUrls' => [
                'https://example.com/file.jpg'
            ],
            'scheduleType' => 'cron',
            'cronExpression' => '範例字串',
            'intervalSeconds' => 123,
            'oneShotAt' => '範例字串',
            'timezone' => '範例字串',
            'enabled' => true,
            'maxExecutions' => 123
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 201

回應結構範例

```
{
  "id": string (uuid)
  "chatbot": string (uuid)
  "organization": string (uuid)
  "name": string
  "executionMode": string (enum: in_context, isolated) // * `in_context` - In Context
* `isolated` - Isolated
  "prompt": string
  "contextVariables"?: object // 非必填
  "inbox": string (uuid)
  "saveResultToContext"?: boolean // 非必填
  "dedicatedContact": string (uuid)
  "dedicatedConversation": string (uuid)
  "deliveryConversationIds"?: [ // 非必填
    string (uuid)
  ]
  "deliveryWebhookUrls"?: [ // 非必填
    string (uri)
  ]
  "scheduleType": string (enum: cron, interval, one_shot) // * `cron` - Cron
* `interval` - Interval
* `one_shot` - One Shot
  "cronExpression"?: string // 非必填
  "intervalSeconds"?: integer // 非必填
  "oneShotAt"?: string (timestamp) // 非必填
  "timezone"?: string // 非必填
  "periodicTask": integer
  "enabled"?: boolean // 非必填
  "lastExecutedAt": string (timestamp)
  "executionCount": integer
  "maxExecutions"?: integer // 非必填
  "countsTowardLimit": boolean
  "createdAt": string (timestamp)
  "updatedAt": string (timestamp)
}
```

回應範例值

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "chatbot": "550e8400-e29b-41d4-a716-446655440000",
  "organization": "550e8400-e29b-41d4-a716-446655440000",
  "name": "回應字串",
```

```
  "executionMode": "in_context",
  "prompt": "回應字串",
  "contextVariables": null,
  "inbox": "550e8400-e29b-41d4-a716-446655440000",
  "saveResultToContext": false,
  "dedicatedContact": "550e8400-e29b-41d4-a716-446655440000",
  "dedicatedConversation": "550e8400-e29b-41d4-a716-446655440000",
  "deliveryConversationIds": [
    "550e8400-e29b-41d4-a716-446655440000"
  ],
  "deliveryWebhookUrls": [
    "https://example.com/file.jpg"
  ],
  "scheduleType": "cron",
  "cronExpression": "回應字串",
  "intervalSeconds": 456,
  "oneShotAt": "回應字串",
  "timezone": "回應字串",
  "periodicTask": 456,
  "enabled": false,
  "lastExecutedAt": "回應字串",
  "executionCount": 456,
  "maxExecutions": 456,
  "countsTowardLimit": false,
  "createdAt": "回應字串",
  "updatedAt": "回應字串"
}
```


取得特定排程

`GET` `/api/v1/schedules/{id}`

參數

參數名稱	必填	類型	說明
`id`	V	string	A UUID string identifying this Chatbot Schedule.

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/schedules/550e8400-e29b-41d4-a716-
446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/schedules/550e8400-e29b-41d4-a716-
446655440000/", config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/schedules/550e8400-e29b-41d4-a716-
446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->get("https://api.maiagent.ai/api/v1/schedules/550e8400-e29b-41d4-a716-446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
{
  "id": string (uuid)
  "chatbot": string (uuid)
  "organization": string (uuid)
  "name": string
  "executionMode": string (enum: in_context, isolated) // * `in_context` - In Context
* `isolated` - Isolated
  "prompt": string
  "contextVariables"?: object // 非必填
  "inbox": string (uuid)
  "saveResultToContext"?: boolean // 非必填
  "dedicatedContact": string (uuid)
```

```
  "dedicatedConversation": string (uuid)
  "deliveryConversationIds"?: [ // 非必填
    string (uuid)
  ]
  "deliveryWebhookUrls"?: [ // 非必填
    string (uri)
  ]
  "scheduleType": string (enum: cron, interval, one_shot) // * `cron` - Cron
* `interval` - Interval
* `one_shot` - One Shot
  "cronExpression"?: string // 非必填
  "intervalSeconds"?: integer // 非必填
  "oneShotAt"?: string (timestamp) // 非必填
  "timezone"?: string // 非必填
  "periodicTask": integer
  "enabled"?: boolean // 非必填
  "lastExecutedAt": string (timestamp)
  "executionCount": integer
  "maxExecutions"?: integer // 非必填
  "countsTowardLimit": boolean
  "createdAt": string (timestamp)
  "updatedAt": string (timestamp)
}
```

回應範例值

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "chatbot": "550e8400-e29b-41d4-a716-446655440000",
  "organization": "550e8400-e29b-41d4-a716-446655440000",
  "name": "回應字串",
  "executionMode": "in_context",
  "prompt": "回應字串",
  "contextVariables": null,
  "inbox": "550e8400-e29b-41d4-a716-446655440000",
  "saveResultToContext": false,
  "dedicatedContact": "550e8400-e29b-41d4-a716-446655440000",
  "dedicatedConversation": "550e8400-e29b-41d4-a716-446655440000",
  "deliveryConversationIds": [
    "550e8400-e29b-41d4-a716-446655440000"
  ],
  "deliveryWebhookUrls": [
    "https://example.com/file.jpg"
  ],
  "scheduleType": "cron",
  "cronExpression": "回應字串",
  "intervalSeconds": 456,
  "oneShotAt": "回應字串",
  "timezone": "回應字串",
  "periodicTask": 456,
  "enabled": false,
  "lastExecutedAt": "回應字串",
```

```
  "executionCount": 456,
  "maxExecutions": 456,
  "countsTowardLimit": false,
  "createdAt": "回應字串",
  "updatedAt": "回應字串"
}
```


部分更新排程

`PATCH` `/api/v1/schedules/{id}`

參數

參數名稱	必填	類型	說明
`id`	V	string	A UUID string identifying this Chatbot Schedule.

請求內容

請求參數

欄位	類型	必填	說明
name	string	否	
prompt	string	否	
contextVariables	object	否	
saveResultToContext	boolean	否	
deliveryConversationIds	array[string]	否	
deliveryWebhookUrls	array[string]	否	
scheduleType	string (enum: cron, interval, one_shot)	否	`cron` : Cron ; `interval` : Interval ; `one_shot` : One Shot;
cronExpression	string	否	
intervalSeconds	integer	否	

欄位	類型	必填	說明
oneShotAt	string (timestamp)	否	
timezone	string	否	
enabled	boolean	否	
maxExecutions	integer	否	

請求結構範例

```
{
  "name"?: string // 非必填
  "prompt"?: string // 非必填
  "contextVariables"?: object // 非必填
  "saveResultToContext"?: boolean // 非必填
  "deliveryConversationIds"?: [ // 非必填
    string (uuid)
  ]
  "deliveryWebhookUrls"?: [ // 非必填
    string (uri)
  ]
  "scheduleType"?: string (enum: cron, interval, one_shot) // * `cron` - Cron
* `interval` - Interval
* `one_shot` - One Shot (非必填)
  "cronExpression"?: string // 非必填
  "intervalSeconds"?: integer // 非必填
  "oneShotAt"?: string (timestamp) // 非必填
  "timezone"?: string // 非必填
  "enabled"?: boolean // 非必填
  "maxExecutions"?: integer // 非必填
}
```

請求範例值

```
{
  "name": "範例名稱",
  "prompt": "範例字串",
  "contextVariables": null,
  "saveResultToContext": true,
  "deliveryConversationIds": [
    "550e8400-e29b-41d4-a716-446655440000"
  ],
  "deliveryWebhookUrls": [
    "https://example.com/file.jpg"
  ],
  "scheduleType": "cron",
  "cronExpression": "範例字串",
  "intervalSeconds": 123,
```

```
  "oneShotAt": "範例字串",
  "timezone": "範例字串",
  "enabled": true,
  "maxExecutions": 123
}
```

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X PATCH "https://api.maiagent.ai/api/v1/schedules/550e8400-e29b-41d4-a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "name": "範例名稱",
    "prompt": "範例字串",
    "contextVariables": null,
    "saveResultToContext": true,
    "deliveryConversationIds": [
      "550e8400-e29b-41d4-a716-446655440000"
    ],
    "deliveryWebhookUrls": [
      "https://example.com/file.jpg"
    ],
    "scheduleType": "cron",
    "cronExpression": "範例字串",
    "intervalSeconds": 123,
    "oneShotAt": "範例字串",
    "timezone": "範例字串",
    "enabled": true,
    "maxExecutions": 123
  }'

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// 請求內容 (payload)
const data = {
    "name": "範例名稱",
    "prompt": "範例字串",
    "contextVariables": null,
    "saveResultToContext": true,
    "deliveryConversationIds": [
      "550e8400-e29b-41d4-a716-446655440000"
    ],
    "deliveryWebhookUrls": [
      "https://example.com/file.jpg"
    ],
    "scheduleType": "cron",
    "cronExpression": "範例字串",
    "intervalSeconds": 123,
    "oneShotAt": "範例字串",
    "timezone": "範例字串",
    "enabled": true,
    "maxExecutions": 123
  };

axios.patch("https://api.maiagent.ai/api/v1/schedules/550e8400-e29b-41d4-a716-
446655440000/", data, config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/schedules/550e8400-e29b-41d4-a716-
446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# 請求內容 (payload)
data = {
    "name": "範例名稱",
    "prompt": "範例字串",
    "contextVariables": None,
    "saveResultToContext": True,
    "deliveryConversationIds": [
        "550e8400-e29b-41d4-a716-446655440000"
    ],
    "deliveryWebhookUrls": [
        "https://example.com/file.jpg"
    ],
    "scheduleType": "cron",
    "cronExpression": "範例字串",
    "intervalSeconds": 123,
    "oneShotAt": "範例字串",
    "timezone": "範例字串",
    "enabled": True,
    "maxExecutions": 123
}

response = requests.patch(url, json=data, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->patch("https://api.maiagent.ai/api/v1/schedules/550e8400-e29b-41d4-a716-446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'name' => '範例名稱',
            'prompt' => '範例字串',
            'contextVariables' => null,
            'saveResultToContext' => true,
            'deliveryConversationIds' => [
                '550e8400-e29b-41d4-a716-446655440000'
            ],
            'deliveryWebhookUrls' => [
                'https://example.com/file.jpg'
            ],
            'scheduleType' => 'cron',
            'cronExpression' => '範例字串',
            'intervalSeconds' => 123,
            'oneShotAt' => '範例字串',
            'timezone' => '範例字串',
            'enabled' => true,
            'maxExecutions' => 123
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
{
  "id": string (uuid)
  "chatbot": string (uuid)
  "organization": string (uuid)
  "name": string
  "executionMode":
  {
  }
  "prompt": string
  "contextVariables"?: object // 非必填
  "inbox": string (uuid)
  "saveResultToContext"?: boolean // 非必填
  "dedicatedContact": string (uuid)
  "dedicatedConversation": string (uuid)
  "deliveryConversationIds"?: [ // 非必填
    string (uuid)
  ]
  "deliveryWebhookUrls"?: [ // 非必填
    string (uri)
  ]
  "scheduleType": string (enum: cron, interval, one_shot) // * `cron` - Cron
* `interval` - Interval
* `one_shot` - One Shot
  "cronExpression"?: string // 非必填
  "intervalSeconds"?: integer // 非必填
  "oneShotAt"?: string (timestamp) // 非必填
  "timezone"?: string // 非必填
  "periodicTask": integer
  "enabled"?: boolean // 非必填
  "lastExecutedAt": string (timestamp)
  "executionCount": integer
  "maxExecutions"?: integer // 非必填
  "countsTowardLimit": boolean
  "createdAt": string (timestamp)
  "updatedAt": string (timestamp)
}
```

回應範例值

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "chatbot": "550e8400-e29b-41d4-a716-446655440000",
  "organization": "550e8400-e29b-41d4-a716-446655440000",
```

```
  "name": "回應字串",
  "executionMode": {},
  "prompt": "回應字串",
  "contextVariables": null,
  "inbox": "550e8400-e29b-41d4-a716-446655440000",
  "saveResultToContext": false,
  "dedicatedContact": "550e8400-e29b-41d4-a716-446655440000",
  "dedicatedConversation": "550e8400-e29b-41d4-a716-446655440000",
  "deliveryConversationIds": [
    "550e8400-e29b-41d4-a716-446655440000"
  ],
  "deliveryWebhookUrls": [
    "https://example.com/file.jpg"
  ],
  "scheduleType": "cron",
  "cronExpression": "回應字串",
  "intervalSeconds": 456,
  "oneShotAt": "回應字串",
  "timezone": "回應字串",
  "periodicTask": 456,
  "enabled": false,
  "lastExecutedAt": "回應字串",
  "executionCount": 456,
  "maxExecutions": 456,
  "countsTowardLimit": false,
  "createdAt": "回應字串",
  "updatedAt": "回應字串"
}
```


刪除排程

DELETE `/api/v1/schedules/{id}`

參數

參數名稱	必填	類型	說明
`id`	V	string	A UUID string identifying this Chatbot Schedule.

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X DELETE "https://api.maiagent.ai/api/v1/schedules/550e8400-e29b-41d4-a716-
446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

// 請求內容 (payload)
const data = null;

axios.delete("https://api.maiagent.ai/api/v1/schedules/550e8400-e29b-41d4-a716-
446655440000/", data, config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/schedules/550e8400-e29b-41d4-a716-
446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.delete(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->delete("https://api.maiagent.ai/api/v1/schedules/550e8400-
e29b-41d4-a716-446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼	說明
204	No response body

立即執行排程

POST `/api/v1/schedules/{id}/run-now/`

參數

參數名稱	必填	類型	說明
`id`	V	string	A UUID string identifying this Chatbot Schedule.

請求內容

請求參數

欄位	類型	必填	說明
chatbot	string (uuid)	是	
name	string	是	
executionMode	string (enum: in_context, isolated)	是	`in_context` : In Context ; `isolated` : Isolated;
prompt	string	是	
contextVariables	object	否	
inbox	string (uuid)	是	
saveResultToContext	boolean	否	
deliveryConversationIds	array[string]	否	
deliveryWebhookUrls	array[string]	否	
scheduleType	string (enum: cron, interval, one_shot)	是	`cron` : Cron ; `interval` : Interval ; `one_shot` : One Shot;
cronExpression	string	否	
intervalSeconds	integer	否	
oneShotAt	string (timestamp)	否	
timezone	string	否	
enabled	boolean	否	
maxExecutions	integer	否	

請求結構範例

```
{
  "chatbot": string (uuid)
  "name": string
  "executionMode": string (enum: in_context, isolated) // * `in_context` - In Context
* `isolated` - Isolated
```

```
  "prompt": string
  "contextVariables"?: object // 非必填
  "inbox": string (uuid)
  "saveResultToContext"?: boolean // 非必填
  "deliveryConversationIds"?: [ // 非必填
    string (uuid)
  ]
  "deliveryWebhookUrls"?: [ // 非必填
    string (uri)
  ]
  "scheduleType": string (enum: cron, interval, one_shot) // * `cron` - Cron
* `interval` - Interval
* `one_shot` - One Shot
  "cronExpression"?: string // 非必填
  "intervalSeconds"?: integer // 非必填
  "oneShotAt"?: string (timestamp) // 非必填
  "timezone"?: string // 非必填
  "enabled"?: boolean // 非必填
  "maxExecutions"?: integer // 非必填
}
```

請求範例值

```
{
  "chatbot": "550e8400-e29b-41d4-a716-446655440000",
  "name": "範例名稱",
  "executionMode": "in_context",
  "prompt": "範例字串",
  "contextVariables": null,
  "inbox": "550e8400-e29b-41d4-a716-446655440000",
  "saveResultToContext": true,
  "deliveryConversationIds": [
    "550e8400-e29b-41d4-a716-446655440000"
  ],
  "deliveryWebhookUrls": [
    "https://example.com/file.jpg"
  ],
  "scheduleType": "cron",
  "cronExpression": "範例字串",
  "intervalSeconds": 123,
  "oneShotAt": "範例字串",
  "timezone": "範例字串",
  "enabled": true,
  "maxExecutions": 123
}
```

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X POST "https://api.maiagent.ai/api/v1/schedules/550e8400-e29b-41d4-a716-
446655440000/run-now/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "chatbot": "550e8400-e29b-41d4-a716-446655440000",
    "name": "範例名稱",
    "executionMode": "in_context",
    "prompt": "範例字串",
    "contextVariables": null,
    "inbox": "550e8400-e29b-41d4-a716-446655440000",
    "saveResultToContext": true,
    "deliveryConversationIds": [
      "550e8400-e29b-41d4-a716-446655440000"
    ],
    "deliveryWebhookUrls": [
      "https://example.com/file.jpg"
    ],
    "scheduleType": "cron",
    "cronExpression": "範例字串",
    "intervalSeconds": 123,
    "oneShotAt": "範例字串",
    "timezone": "範例字串",
    "enabled": true,
    "maxExecutions": 123
  }'

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// 請求內容 (payload)
const data = {
    "chatbot": "550e8400-e29b-41d4-a716-446655440000",
    "name": "範例名稱",
    "executionMode": "in_context",
    "prompt": "範例字串",
    "contextVariables": null,
    "inbox": "550e8400-e29b-41d4-a716-446655440000",
    "saveResultToContext": true,
    "deliveryConversationIds": [
      "550e8400-e29b-41d4-a716-446655440000"
    ],
    "deliveryWebhookUrls": [
      "https://example.com/file.jpg"
    ],
    "scheduleType": "cron",
    "cronExpression": "範例字串",
    "intervalSeconds": 123,
    "oneShotAt": "範例字串",
    "timezone": "範例字串",
    "enabled": true,
    "maxExecutions": 123
  };

axios.post("https://api.maiagent.ai/api/v1/schedules/550e8400-e29b-41d4-a716-
446655440000/run-now/", data, config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/schedules/550e8400-e29b-41d4-a716-
446655440000/run-now/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# 請求內容 (payload)
data = {
    "chatbot": "550e8400-e29b-41d4-a716-446655440000",
    "name": "範例名稱",
    "executionMode": "in_context",
    "prompt": "範例字串",
    "contextVariables": None,
    "inbox": "550e8400-e29b-41d4-a716-446655440000",
    "saveResultToContext": True,
    "deliveryConversationIds": [
        "550e8400-e29b-41d4-a716-446655440000"
    ],
    "deliveryWebhookUrls": [
        "https://example.com/file.jpg"
    ],
    "scheduleType": "cron",
    "cronExpression": "範例字串",
    "intervalSeconds": 123,
    "oneShotAt": "範例字串",
    "timezone": "範例字串",
    "enabled": True,
    "maxExecutions": 123
}

response = requests.post(url, json=data, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->post("https://api.maiagent.ai/api/v1/schedules/550e8400-
e29b-41d4-a716-446655440000/run-now/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'chatbot' => '550e8400-e29b-41d4-a716-446655440000',
            'name' => '範例名稱',
            'executionMode' => 'in_context',
            'prompt' => '範例字串',
            'contextVariables' => null,
            'inbox' => '550e8400-e29b-41d4-a716-446655440000',
            'saveResultToContext' => true,
            'deliveryConversationIds' => [
                '550e8400-e29b-41d4-a716-446655440000'
            ],
            'deliveryWebhookUrls' => [
                'https://example.com/file.jpg'
            ],
            'scheduleType' => 'cron',
            'cronExpression' => '範例字串',
            'intervalSeconds' => 123,
            'oneShotAt' => '範例字串',
            'timezone' => '範例字串',
            'enabled' => true,
            'maxExecutions' => 123
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 202

回應結構範例

```
{
  "status"?: string // 非必填
}
```

回應範例值

```
{
  "status": "scheduled"
}
```

啟用或停用排程

POST `/api/v1/schedules/{id}/toggle/`

參數

參數名稱	必填	類型	說明
id	V	string	A UUID string identifying this Chatbot Schedule.

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X POST "https://api.maiagent.ai/api/v1/schedules/550e8400-e29b-41d4-a716-
446655440000/toggle/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

// 請求內容 (payload)
const data = null;

axios.post("https://api.maiagent.ai/api/v1/schedules/550e8400-e29b-41d4-a716-
446655440000/toggle/", data, config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/schedules/550e8400-e29b-41d4-a716-
446655440000/toggle/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.post(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->post("https://api.maiagent.ai/api/v1/schedules/550e8400-
e29b-41d4-a716-446655440000/toggle/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
{
  "id": string (uuid)
  "chatbot": string (uuid)
  "organization": string (uuid)
  "name": string
  "executionMode": string (enum: in_context, isolated) // * `in_context` - In Context
* `isolated` - Isolated
  "prompt": string
  "contextVariables"?: object // 非必填
  "inbox": string (uuid)
  "saveResultToContext"?: boolean // 非必填
  "dedicatedContact": string (uuid)
```

```
  "dedicatedConversation": string (uuid)
  "deliveryConversationIds"?: [ // 非必填
    string (uuid)
  ]
  "deliveryWebhookUrls"?: [ // 非必填
    string (uri)
  ]
  "scheduleType": string (enum: cron, interval, one_shot) // * `cron` - Cron
* `interval` - Interval
* `one_shot` - One Shot
  "cronExpression"?: string // 非必填
  "intervalSeconds"?: integer // 非必填
  "oneShotAt"?: string (timestamp) // 非必填
  "timezone"?: string // 非必填
  "periodicTask": integer
  "enabled"?: boolean // 非必填
  "lastExecutedAt": string (timestamp)
  "executionCount": integer
  "maxExecutions"?: integer // 非必填
  "countsTowardLimit": boolean
  "createdAt": string (timestamp)
  "updatedAt": string (timestamp)
}
```

回應範例值

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "chatbot": "550e8400-e29b-41d4-a716-446655440000",
  "organization": "550e8400-e29b-41d4-a716-446655440000",
  "name": "回應字串",
  "executionMode": "in_context",
  "prompt": "回應字串",
  "contextVariables": null,
  "inbox": "550e8400-e29b-41d4-a716-446655440000",
  "saveResultToContext": false,
  "dedicatedContact": "550e8400-e29b-41d4-a716-446655440000",
  "dedicatedConversation": "550e8400-e29b-41d4-a716-446655440000",
  "deliveryConversationIds": [
    "550e8400-e29b-41d4-a716-446655440000"
  ],
  "deliveryWebhookUrls": [
    "https://example.com/file.jpg"
  ],
  "scheduleType": "cron",
  "cronExpression": "回應字串",
  "intervalSeconds": 456,
  "oneShotAt": "回應字串",
  "timezone": "回應字串",
  "periodicTask": 456,
  "enabled": false,
  "lastExecutedAt": "回應字串",
```

```
  "executionCount": 456,
  "maxExecutions": 456,
  "countsTowardLimit": false,
  "createdAt": "回應字串",
  "updatedAt": "回應字串"
}
```

狀態碼: 400

回應結構範例

```
{
  "detail"?: string // 非必填
}
```

回應範例值

```
{
  "detail": "回應字串"
}
```

前置説明

目錄

1. 查詢 Credit 餘額
2. 取得錢包詳情
3. 取得錢包餘額
4. 查詢即將到期額度
5. 查詢入帳紀錄
6. 列出消耗明細
7. 取得單筆消耗明細
8. 查詢消耗紀錄
9. 查詢消耗總計
10. 查詢各分類 Credit 用量
11. 查詢單一分類 Credit 用量
12. 查詢計價項目的成員用量
13. 查詢單一成員的計價項目用量
14. 列出成員額度現況
15. 列出角色額度現況
16. 列出對話平台額度現況
17. 列出成員的額度設定
18. 取得成員的單筆額度設定
19. 為成員設定額度
20. 更新成員的額度設定
21. 列出角色的額度設定
22. 取得角色的單筆額度設定
23. 查詢角色成員額度統計
24. 依角色批次分配額度
25. 查詢自己的額度
26. 查詢自己所屬角色的額度
27. 列出計價規則
28. 取得單一計價規則
29. 列出計價項目
30. 取得單一計價項目

前置說明

Credit 分類提供組織 Credit 的查詢與額度分配：餘額、即將到期額度、入帳紀錄、消耗明細與總計、用量統計、成員／角色／對話平台的額度現況、計價規則與計價項目，以及為單一成員設定額度、依角色批次分配額度。

前置說明

認證與路徑參數

除「計價規則」與「計價項目」外，所有 API 都要在 HTTP Header 帶 API Key：

```
Authorization: Api-Key {API_KEY}
```

系統會依 API Key 自動帶出所屬組織與成員身分，`/api/v1/credit/` 開頭的 API 不需要另外傳組織識別。路徑中需要的 ID 可以這樣取得：

- `organizationPk`：呼叫 `GET /api/v1/organizations/`，取回應中組織的 `id`。
- 錢包的 `id`：呼叫 `GET /api/v1/organizations/{id}/`，取回應中的 `creditWallet.id`。

呼叫頻率上限

需要 API Key 的 API，呼叫頻率上限是**每一把 API Key 各自設定的每分鐘次數**，由組織管理者在「組織設定 → API 金鑰」的「每分鐘請求數（RPM）」設定；同一把金鑰呼叫平台上所有 API 的次數合併計算，沒有設定上限的金鑰不受此限制。超過上限的請求會被拒絕並回傳 HTTP 429，請等到下一分鐘再重試。

「計價規則」與「計價項目」不需要 API Key，呼叫上限另依來源 IP 計算，見各 API 的標註。

權限與計費模式

每支 API 下方都標明所需權限與計費模式前提。API Key 以建立它的成員身分呼叫，權限依該成員所屬角色判斷。以下兩種情形會被拒絕並回傳 HTTP 403：

- **權限不足**：金鑰所屬成員的角色沒有該 API 標明的權限（「Credit 管理權限」、「用量統計權限」或「組織概覽權限」）。請組織管理者到「組織設定 → 角色」為該成員的角色開啟對應權限。
- **組織不是 Credit 計費模式**：標明「組織須為 Credit 計費模式」的 API，只開放給 Credit 計費模式的組織。可呼叫 `GET /api/v1/organizations/{id}/` 確認：回應中 `organizationPlan.billingMode` 為 `credit`（或組織尚未有方案、`organizationPlan` 為空）即可使用這些 API；如需改用 Credit 計費模式，請聯繫 MaiAgent 窗口。

查詢 Credit 餘額

GET `/api/v1/credit/wallets/`

所需權限：Credit 管理權限。計費模式：不限，任何計費模式的組織都可呼叫。

參數

參數名稱	必填	類型	說明
`page`	X	integer	A page number within the paginated result set.
`pageSize`	X	integer	Number of results to return per page.

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/credit/wallets/?
page=1&pageSize=1"

  -H "Authorization: Api-Key YOUR_API_KEY"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/credit/wallets/?
page=1&pageSize=1", config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/credit/wallets/?
page=1&pageSize=1"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/credit/wallets/?
page=1&pageSize=1", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
{
  "count": integer
  "next"?: string (uri) // 非必填
```

```
  "previous"?: string (uri) // 非必填
  "results": [
    {
      "totalCredits": string (decimal)
      "autoTopup": object // Format auto-topup configuration.
      "balanceAlert": object // Format balance alert configuration.
      "nextGrant": object // Format the next grant, or None when nothing
will actually be granted.

Amount-first: a missing/zero ``amount`` always wins over any schedule
(stale ``next_grant_at`` row, Stripe period_end with zero-grant plan),
so the frontend never receives a "scheduled in X days for 0 credits"
entry — the API decides whether the block renders at all.
      "lastGrant": object // Format the most recent PLAN_GRANT topup, or
None when wallet has none.
      "consumptionHint": object // Return 7-day daily average consumption
hint, or None if insufficient data.
      "billingProvider": string // Return the organization's billing
provider so the Credit page can pick its card layout.
      "periodCreditGrant": string // Return current-period credit grant
total; None unless AWS Marketplace billed.
      "periodMeteredUsage": string // Return current-period accepted
metered usage; None unless AWS Marketplace billed.
    }
  ]
}
```

回應範例值

```
{
  "count": 123,
  "next": "http://api.example.org/accounts/?page=4",
  "previous": "http://api.example.org/accounts/?page=2",
  "results": [
    {
      "totalCredits": "回應字串",
      "autoTopup": {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "name": "回應範例名稱",
        "description": "回應範例描述"
      },
      "balanceAlert": {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "name": "回應範例名稱",
```

```
        "description": "回應範例描述"
      },
      "nextGrant": {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "name": "回應範例名稱",
        "description": "回應範例描述"
      },
      "lastGrant": {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "name": "回應範例名稱",
        "description": "回應範例描述"
      },
      "consumptionHint": {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "name": "回應範例名稱",
        "description": "回應範例描述"
      },
      "billingProvider": "回應字串",
      "periodCreditGrant": "回應字串",
      "periodMeteredUsage": "回應字串"
    }
  ]
}
```


取得錢包詳情

`GET` `/api/v1/credit/wallets/{id}`

所需權限：Credit 管理權限。計費模式：不限，任何計費模式的組織都可呼叫。

參數

參數名稱	必填	類型	說明
id	V	string	A UUID string identifying this Credit Wallet.

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/credit/wallets/550e8400-
e29b-41d4-a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/credit/wallets/550e8400-
e29b-41d4-a716-446655440000/", config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/credit/wallets/550e8400-e29b-41d4-a716-446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/credit/wallets/550e8400-e29b-
41d4-a716-446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
{
  "totalCredits": string (decimal)
  "autoTopup": object // Format auto-topup configuration.
```

```
  "balanceAlert": object // Format balance alert configuration.
  "nextGrant": object // Format the next grant, or None when nothing will
actually be granted.

Amount-first: a missing/zero ``amount`` always wins over any schedule
(stale ``next_grant_at`` row, Stripe period_end with zero-grant plan),
so the frontend never receives a "scheduled in X days for 0 credits"
entry — the API decides whether the block renders at all.
  "lastGrant": object // Format the most recent PLAN_GRANT topup, or None
when wallet has none.
  "consumptionHint": object // Return 7-day daily average consumption
hint, or None if insufficient data.
  "billingProvider": string // Return the organization's billing provider
so the Credit page can pick its card layout.
  "periodCreditGrant": string // Return current-period credit grant
total; None unless AWS Marketplace billed.
  "periodMeteredUsage": string // Return current-period accepted metered
usage; None unless AWS Marketplace billed.
}
```

回應範例值

```
{
  "totalCredits": "回應字串",
  "autoTopup": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應範例名稱",
    "description": "回應範例描述"
  },
  "balanceAlert": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應範例名稱",
    "description": "回應範例描述"
  },
  "nextGrant": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應範例名稱",
    "description": "回應範例描述"
  },
  "lastGrant": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應範例名稱",
    "description": "回應範例描述"
  },
```

```
  "consumptionHint": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應範例名稱",
    "description": "回應範例描述"
  },
  "billingProvider": "回應字串",
  "periodCreditGrant": "回應字串",
  "periodMeteredUsage": "回應字串"
}
```


取得錢包餘額

GET `/api/v1/credit/wallets/{id}/balance/`

所需權限：Credit 管理權限。計費模式：不限，任何計費模式的組織都可呼叫。

參數

參數名稱	必填	類型	說明
`id`	V	string	A UUID string identifying this Credit Wallet.

程式碼範例

Shell/Bash

```shell
# 呼叫 API 示例 (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/credit/wallets/550e8400-e29b-41d4-a716-446655440000/balance/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```javascript
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/credit/wallets/550e8400-e29b-41d4-a716-446655440000/balance/", config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/credit/wallets/550e8400-e29b-41d4-a716-446655440000/balance/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/credit/wallets/550e8400-e29b-
41d4-a716-446655440000/balance/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
{
  "totalCredits": string (decimal)
  "autoTopup": object // Format auto-topup configuration.
```

```
  "balanceAlert": object // Format balance alert configuration.
  "nextGrant": object // Format the next grant, or None when nothing will
actually be granted.

Amount-first: a missing/zero ``amount`` always wins over any schedule
(stale ``next_grant_at`` row, Stripe period_end with zero-grant plan),
so the frontend never receives a "scheduled in X days for 0 credits"
entry — the API decides whether the block renders at all.
  "lastGrant": object // Format the most recent PLAN_GRANT topup, or None
when wallet has none.
  "consumptionHint": object // Return 7-day daily average consumption
hint, or None if insufficient data.
  "billingProvider": string // Return the organization's billing provider
so the Credit page can pick its card layout.
  "periodCreditGrant": string // Return current-period credit grant
total; None unless AWS Marketplace billed.
  "periodMeteredUsage": string // Return current-period accepted metered
usage; None unless AWS Marketplace billed.
}
```

回應範例值

```
{
  "totalCredits": "回應字串",
  "autoTopup": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應範例名稱",
    "description": "回應範例描述"
  },
  "balanceAlert": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應範例名稱",
    "description": "回應範例描述"
  },
  "nextGrant": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應範例名稱",
    "description": "回應範例描述"
  },
  "lastGrant": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應範例名稱",
    "description": "回應範例描述"
  },
```

```
  "consumptionHint": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應範例名稱",
    "description": "回應範例描述"
  },
  "billingProvider": "回應字串",
  "periodCreditGrant": "回應字串",
  "periodMeteredUsage": "回應字串"
}
```

查詢即將到期額度

GET `/api/v1/credit/wallets/{id}/expiring-credits/`

所需權限：Credit 管理權限。計費模式：不限，任何計費模式的組織都可呼叫。只列出有設到期日的額度；沒有到期日的額度不會出現在結果中，不代表組織的全部餘額。days 參數指定查詢幾天內到期（預設 30；傳 all 列出所有有到期日的額度）。

參數

參數名稱	必填	類型	說明
`id`	V	string	A UUID string identifying this Credit Wallet.

程式碼範例

Shell/Bash

```shell
# 呼叫 API 示例 (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/credit/wallets/550e8400-e29b-41d4-a716-446655440000/expiring-credits/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```javascript
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/credit/wallets/550e8400-e29b-41d4-a716-446655440000/expiring-credits/", config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/credit/wallets/550e8400-e29b-41d4-a716-446655440000/expiring-credits/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/credit/wallets/550e8400-e29b-
41d4-a716-446655440000/expiring-credits/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
{
  "totalCredits": string (decimal)
  "autoTopup": object // Format auto-topup configuration.
```

```
  "balanceAlert": object // Format balance alert configuration.
  "nextGrant": object // Format the next grant, or None when nothing will
actually be granted.

Amount-first: a missing/zero ``amount`` always wins over any schedule
(stale ``next_grant_at`` row, Stripe period_end with zero-grant plan),
so the frontend never receives a "scheduled in X days for 0 credits"
entry — the API decides whether the block renders at all.
  "lastGrant": object // Format the most recent PLAN_GRANT topup, or None
when wallet has none.
  "consumptionHint": object // Return 7-day daily average consumption
hint, or None if insufficient data.
  "billingProvider": string // Return the organization's billing provider
so the Credit page can pick its card layout.
  "periodCreditGrant": string // Return current-period credit grant
total; None unless AWS Marketplace billed.
  "periodMeteredUsage": string // Return current-period accepted metered
usage; None unless AWS Marketplace billed.
}
```

回應範例值

```
{
  "totalCredits": "回應字串",
  "autoTopup": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應範例名稱",
    "description": "回應範例描述"
  },
  "balanceAlert": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應範例名稱",
    "description": "回應範例描述"
  },
  "nextGrant": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應範例名稱",
    "description": "回應範例描述"
  },
  "lastGrant": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應範例名稱",
    "description": "回應範例描述"
  },
```

```
  "consumptionHint": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應範例名稱",
    "description": "回應範例描述"
  },
  "billingProvider": "回應字串",
  "periodCreditGrant": "回應字串",
  "periodMeteredUsage": "回應字串"
}
```


查詢入帳紀錄

`GET` `/api/v1/credit/wallets/{id}/topup-history/`

所需權限：Credit 管理權限。計費模式：不限，任何計費模式的組織都可呼叫。

參數

參數名稱	必填	類型	說明
`id`	V	string	A UUID string identifying this Credit Wallet.

程式碼範例

Shell/Bash

```shell
# 呼叫 API 示例 (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/credit/wallets/550e8400-e29b-41d4-a716-446655440000/topup-history/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```javascript
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/credit/wallets/550e8400-e29b-41d4-a716-446655440000/topup-history/", config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/credit/wallets/550e8400-e29b-41d4-a716-446655440000/topup-history/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/credit/wallets/550e8400-e29b-
41d4-a716-446655440000/topup-history/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
{
  "totalCredits": string (decimal)
  "autoTopup": object // Format auto-topup configuration.
```

```
  "balanceAlert": object // Format balance alert configuration.
  "nextGrant": object // Format the next grant, or None when nothing will
actually be granted.

Amount-first: a missing/zero ``amount`` always wins over any schedule
(stale ``next_grant_at`` row, Stripe period_end with zero-grant plan),
so the frontend never receives a "scheduled in X days for 0 credits"
entry — the API decides whether the block renders at all.
  "lastGrant": object // Format the most recent PLAN_GRANT topup, or None
when wallet has none.
  "consumptionHint": object // Return 7-day daily average consumption
hint, or None if insufficient data.
  "billingProvider": string // Return the organization's billing provider
so the Credit page can pick its card layout.
  "periodCreditGrant": string // Return current-period credit grant
total; None unless AWS Marketplace billed.
  "periodMeteredUsage": string // Return current-period accepted metered
usage; None unless AWS Marketplace billed.
}
```

回應範例值

```
{
  "totalCredits": "回應字串",
  "autoTopup": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應範例名稱",
    "description": "回應範例描述"
  },
  "balanceAlert": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應範例名稱",
    "description": "回應範例描述"
  },
  "nextGrant": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應範例名稱",
    "description": "回應範例描述"
  },
  "lastGrant": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應範例名稱",
    "description": "回應範例描述"
  },
```

```
  "consumptionHint": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應範例名稱",
    "description": "回應範例描述"
  },
  "billingProvider": "回應字串",
  "periodCreditGrant": "回應字串",
  "periodMeteredUsage": "回應字串"
}
```


列出消耗明細

GET `/api/v1/credit/transactions/`

所需權限：Credit 管理權限。計費模式：不限，任何計費模式的組織都可呼叫。

參數

參數名稱	必填	類型	說明
`page`	X	integer	A page number within the paginated result set.
`pageSize`	X	integer	Number of results to return per page.

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/credit/transactions/?
page=1&pageSize=1"

  -H "Authorization: Api-Key YOUR_API_KEY"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/credit/transactions/?
page=1&pageSize=1", config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/credit/transactions/?
page=1&pageSize=1"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/credit/transactions/?
page=1&pageSize=1", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
{
  "count": integer
  "next"?: string (uri) // 非必填
```

```
  "previous"?: string (uri) // 非必填
  "results": [
    {
      "id": string (uuid)
      "eventDatetime": string (timestamp)
      "createdAt": string (timestamp)
      "transactionType": string
      "creditItem": object
      "amount": string (decimal)
      "balanceAfter": string (decimal)
      "quantity": string (decimal)
      "provider": string
      "modelCode": string
      "unitPriceSnapshot": string (decimal)
      "member": object
      "description": string
      "metadata": object
      "targetObject": object // Return frontend deep-link target for this
transaction's GFK content.

``{kind: 'chat.message', objectId, chatbotId}`` opens the AgentOps record
modal;
``{kind: 'dataset.evaluation', objectId, isMultiTurn}`` opens the
evaluation results page.
Returns None when no GFK is attached, the content type is unsupported,
or the target no longer resolves inside this organization.
    }
  ]
}
```

回應範例值

```
{
  "count": 123,
  "next": "http://api.example.org/accounts/?page=4",
  "previous": "http://api.example.org/accounts/?page=2",
  "results": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "eventDatetime": "回應字串",
      "createdAt": "回應字串",
      "transactionType": "回應字串",
      "creditItem": {
        "id": "550e8400-e29b-41d4-a716-446655440000",
```

```
        "name": "回應範例名稱",
        "description": "回應範例描述"
      },
      "amount": "回應字串",
      "balanceAfter": "回應字串",
      "quantity": "回應字串",
      "provider": "回應字串",
      "modelCode": "回應字串",
      "unitPriceSnapshot": "回應字串",
      "member": {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "name": "回應範例名稱",
        "description": "回應範例描述"
      },
      "description": "回應字串",
      "metadata": null,
      "targetObject": {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "name": "回應範例名稱",
        "description": "回應範例描述"
      }
    }
  ]
}
```


取得單筆消耗明細

`GET` `/api/v1/credit/transactions/{id}`

所需權限：Credit 管理權限。計費模式：不限，任何計費模式的組織都可呼叫。

參數

參數名稱	必填	類型	說明

id	V	string	A UUID string identifying this Credit Transaction.

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X GET
"https://api.maiagent.ai/api/v1/credit/transactions/550e8400-e29b-
41d4-a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/credit/transactions/550e84
00-e29b-41d4-a716-446655440000/", config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/credit/transactions/550e8400-
e29b-41d4-a716-446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/credit/transactions/550e8400-
e29b-41d4-a716-446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
{
  "id": string (uuid)
  "eventDatetime": string (timestamp)
```

```
  "createdAt": string (timestamp)
  "transactionType": string
  "creditItem": object
  "amount": string (decimal)
  "balanceAfter": string (decimal)
  "quantity": string (decimal)
  "provider": string
  "modelCode": string
  "unitPriceSnapshot": string (decimal)
  "member": object
  "description": string
  "metadata": object
  "targetObject": object // Return frontend deep-link target for this
transaction's GFK content.

``{kind: 'chat.message', objectId, chatbotId}`` opens the AgentOps record
modal;
``{kind: 'dataset.evaluation', objectId, isMultiTurn}`` opens the
evaluation results page.
Returns None when no GFK is attached, the content type is unsupported,
or the target no longer resolves inside this organization.
}
```

回應範例值

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "eventDatetime": "回應字串",
  "createdAt": "回應字串",
  "transactionType": "回應字串",
  "creditItem": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應範例名稱",
    "description": "回應範例描述"
  },
  "amount": "回應字串",
  "balanceAfter": "回應字串",
  "quantity": "回應字串",
  "provider": "回應字串",
  "modelCode": "回應字串",
  "unitPriceSnapshot": "回應字串",
  "member": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應範例名稱",
```

```
    "description": "回應範例描述"
  },
  "description": "回應字串",
  "metadata": null,
  "targetObject": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應範例名稱",
    "description": "回應範例描述"
  }
}
```


查詢消耗紀錄

`GET` `/api/v1/credit/transactions/history/`

所需權限：Credit 管理權限。計費模式：不限，任何計費模式的組織都可呼叫。

參數

參數名稱	必填	類型	說明
`category`	X	string	Credit item category (e.g. llm_token, platform_fee); agent_memory selects the AI memory lines, which llm_token then leaves out
`endDate`	X	string	End date (inclusive, whole day in the platform timezone Asia/Taipei), format: YYYY-MM-DD
`limit`	X	integer	Rows per page, capped at 100
`page`	X	integer	1-based page number
`search`	X	string	Case-insensitive match against transaction description and metadata

`startDate`	X	string	Start date (inclusive, whole day in the platform timezone Asia/Taipei), format: YYYY-MM-DD
`type`	X	string	Which rows to include: all ledger entries, consumption only, or credited only

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X GET
"https://api.maiagent.ai/api/v1/credit/transactions/history/?
category=example&endDate=example&limit=1&page=1&search=example&start
Date=example&type=all"

  -H "Authorization: Api-Key YOUR_API_KEY"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/credit/transactions/histor
y/?
category=example&endDate=example&limit=1&page=1&search=example&start
Date=example&type=all", config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/credit/transactions/history/?
category=example&endDate=example&limit=1&page=1&search=example&start
Date=example&type=all"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/credit/transactions/history/?
category=example&endDate=example&limit=1&page=1&search=example&start
Date=example&type=all", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
{
  "id": string (uuid)
```

```
  "eventDatetime": string (timestamp)
  "createdAt": string (timestamp)
  "transactionType": string
  "creditItem": object
  "amount": string (decimal)
  "balanceAfter": string (decimal)
  "quantity": string (decimal)
  "provider": string
  "modelCode": string
  "unitPriceSnapshot": string (decimal)
  "member": object
  "description": string
  "metadata": object
  "targetObject": object // Return frontend deep-link target for this
transaction's GFK content.

``{kind: 'chat.message', objectId, chatbotId}`` opens the AgentOps record
modal;
``{kind: 'dataset.evaluation', objectId, isMultiTurn}`` opens the
evaluation results page.
Returns None when no GFK is attached, the content type is unsupported,
or the target no longer resolves inside this organization.
}
```

回應範例值

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "eventDatetime": "回應字串",
  "createdAt": "回應字串",
  "transactionType": "回應字串",
  "creditItem": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應範例名稱",
    "description": "回應範例描述"
  },
  "amount": "回應字串",
  "balanceAfter": "回應字串",
  "quantity": "回應字串",
  "provider": "回應字串",
  "modelCode": "回應字串",
  "unitPriceSnapshot": "回應字串",
  "member": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
```

```
    "name": "回應範例名稱",
    "description": "回應範例描述"
  },
  "description": "回應字串",
  "metadata": null,
  "targetObject": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應範例名稱",
    "description": "回應範例描述"
  }
}
```


查詢消耗總計

`GET` `/api/v1/credit/transactions/history-summary/`

所需權限：Credit 管理權限。計費模式：不限，任何計費模式的組織都可呼叫。

參數

參數名稱	必填	類型	說明
`category`	X	string	Credit item category (e.g. llm_token, platform_fee); agent_memory selects the AI memory lines, which llm_token then leaves out
`endDate`	X	string	End date (inclusive, whole day in the platform timezone Asia/Taipei), format: YYYY-MM-DD
`search`	X	string	Case-insensitive match against transaction description and metadata
`startDate`	X	string	Start date (inclusive, whole day in the platform timezone Asia/Taipei), format: YYYY-MM-DD

type	X	string	Which rows to include: all ledger entries, consumption only, or credited only

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X GET
"https://api.maiagent.ai/api/v1/credit/transactions/history-
summary/?
category=example&endDate=example&search=example&startDate=example&ty
pe=all"

  -H "Authorization: Api-Key YOUR_API_KEY"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/credit/transactions/history-summary/?category=example&endDate=example&search=example&startDate=example&type=all", config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/credit/transactions/history-summary/?category=example&endDate=example&search=example&startDate=example&type=all"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/credit/transactions/history-
summary/?
category=example&endDate=example&search=example&startDate=example&ty
pe=all", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
{
  "consumedTotal": string (decimal)
  "creditedTotal": string (decimal)
  "count": integer
}
```

回應範例值

```
{
  "consumedTotal": "回應字串",
  "creditedTotal": "回應字串",
  "count": 456
}
```

查詢各分類 Credit 用量

GET `/api/v1/organizations/{organizationPk}/usage-statistics/credit-categories/`

所需權限：用量統計權限。計費模式：組織須為 Credit 計費模式。

參數

參數名稱	必填	類型	說明
`organizationPk`	V	string	A UUID string identifying this 組織 ID
`endDate`	X	string	End date, format: YYYY-MM-DD
`page`	X	integer	A page number within the paginated result set.
`pageSize`	X	integer	Number of results to return per page.
`startDate`	V	string	Start date, format: YYYY-MM-DD

`timeGranularity`	X	string	Time granularity (hour/day/month)

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/organizations/550e8400-
e29b-41d4-a716-446655440000/usage-statistics/credit-categories/?
endDate=example&page=1&pageSize=1&startDate=example&timeGranularity=
day"

  -H "Authorization: Api-Key YOUR_API_KEY"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/organizations/550e8400-
e29b-41d4-a716-446655440000/usage-statistics/credit-categories/?
endDate=example&page=1&pageSize=1&startDate=example&timeGranularity=
day", config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-
41d4-a716-446655440000/usage-statistics/credit-categories/?
endDate=example&page=1&pageSize=1&startDate=example&timeGranularity=
day"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-
41d4-a716-446655440000/usage-statistics/credit-categories/?
endDate=example&page=1&pageSize=1&startDate=example&timeGranularity=
day", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
{
  "count": integer
  "next"?: string (uri) // 非必填
  "previous"?: string (uri) // 非必填
  "results": [
    object
  ]
}
```

回應範例值

```
{
  "count": 123,
  "next": "http://api.example.org/accounts/?page=4",
  "previous": "http://api.example.org/accounts/?page=2",
  "results": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "回應範例名稱",
      "description": "回應範例描述"
    }
  ]
}
```

查詢單一分類 Credit 用量

GET `/api/v1/organizations/{organizationPk}/usage-statistics/credit-categories/{id}`

所需權限：用量統計權限。計費模式：組織須為 Credit 計費模式。

參數

參數名稱	必填	類型	說明

`id`	V	string	
`organizationPk`	V	string	A UUID string identifying this 組織 ID
`endDate`	X	string	End date, format: YYYY-MM-DD
`startDate`	V	string	Start date, format: YYYY-MM-DD
`timeGranularity`	X	string	Time granularity (hour/day/month)

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/organizations/550e8400-
e29b-41d4-a716-446655440000/usage-statistics/credit-
categories/550e8400-e29b-41d4-a716-446655440000/?
endDate=example&startDate=example&timeGranularity=day"

  -H "Authorization: Api-Key YOUR_API_KEY"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/organizations/550e8400-
e29b-41d4-a716-446655440000/usage-statistics/credit-
categories/550e8400-e29b-41d4-a716-446655440000/?
endDate=example&startDate=example&timeGranularity=day", config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-
41d4-a716-446655440000/usage-statistics/credit-categories/550e8400-
e29b-41d4-a716-446655440000/?
endDate=example&startDate=example&timeGranularity=day"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-
41d4-a716-446655440000/usage-statistics/credit-categories/550e8400-
e29b-41d4-a716-446655440000/?
endDate=example&startDate=example&timeGranularity=day", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
object
```

回應範例值

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "name": "回應範例名稱",
  "description": "回應範例描述"
}
```

查詢計價項目的成員用量

GET `/api/v1/organizations/{organizationPk}/usage-statistics/credit-categories/{itemPk}/members/`

所需權限：用量統計權限。計費模式：組織須為 Credit 計費模式。

參數

參數名稱	必填	類型	說明
`itemPk`	V	string	
`organizationPk`	V	string	A UUID string identifying this 組織 ID
`endDate`	X	string	End date, format: YYYY-MM-DD
`page`	X	integer	A page number within the paginated result set.
`pageSize`	X	integer	Number of results to return per page.
`startDate`	V	string	Start date, format: YYYY-MM-DD

`timeGranularity`	X	string	Time granularity (hour/day/month)

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/organizations/550e8400-
e29b-41d4-a716-446655440000/usage-statistics/credit-
categories/{itemPk}/members/?
endDate=example&page=1&pageSize=1&startDate=example&timeGranularity=
day"

  -H "Authorization: Api-Key YOUR_API_KEY"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/organizations/550e8400-
e29b-41d4-a716-446655440000/usage-statistics/credit-
categories/{itemPk}/members/?
endDate=example&page=1&pageSize=1&startDate=example&timeGranularity=
day", config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-
41d4-a716-446655440000/usage-statistics/credit-
categories/{itemPk}/members/?
endDate=example&page=1&pageSize=1&startDate=example&timeGranularity=
day"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-
41d4-a716-446655440000/usage-statistics/credit-
categories/{itemPk}/members/?
endDate=example&page=1&pageSize=1&startDate=example&timeGranularity=
day", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
{
  "count": integer
  "next"?: string (uri) // 非必填
  "previous"?: string (uri) // 非必填
  "results": [
    object
  ]
}
```

回應範例值

```
{
  "count": 123,
  "next": "http://api.example.org/accounts/?page=4",
  "previous": "http://api.example.org/accounts/?page=2",
  "results": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "回應範例名稱",
      "description": "回應範例描述"
    }
  ]
}
```

查詢單一成員的計價項目用量

GET `/api/v1/organizations/{organizationPk}/usage-statistics/credit-categories/{itemPk}/members/{id}`

所需權限：用量統計權限。計費模式：組織須為 Credit 計費模式。

參數

參數名稱	必填	類型	說明

`id`	V	string	
`itemPk`	V	string	
`organizationPk`	V	string	A UUID string identifying this 組織 ID
`endDate`	X	string	End date, format: YYYY-MM-DD
`startDate`	V	string	Start date, format: YYYY-MM-DD
`timeGranularity`	X	string	Time granularity (hour/day/month)

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/organizations/550e8400-
e29b-41d4-a716-446655440000/usage-statistics/credit-
categories/{itemPk}/members/550e8400-e29b-41d4-a716-446655440000/?
endDate=example&startDate=example&timeGranularity=day"

  -H "Authorization: Api-Key YOUR_API_KEY"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/organizations/550e8400-
e29b-41d4-a716-446655440000/usage-statistics/credit-
categories/{itemPk}/members/550e8400-e29b-41d4-a716-446655440000/?
endDate=example&startDate=example&timeGranularity=day", config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-41d4-a716-446655440000/usage-statistics/credit-categories/{itemPk}/members/550e8400-e29b-41d4-a716-446655440000/?endDate=example&startDate=example&timeGranularity=day"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-
41d4-a716-446655440000/usage-statistics/credit-
categories/{itemPk}/members/550e8400-e29b-41d4-a716-446655440000/?
endDate=example&startDate=example&timeGranularity=day", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
object
```

回應範例值

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "name": "回應範例名稱",
  "description": "回應範例描述"
}
```

列出成員額度現況

GET `/api/v1/organizations/{organizationPk}/credit-quota-members/`

所需權限：Credit 管理權限。計費模式：組織須為 Credit 計費模式。

參數

參數名稱	必填	類型	說明
`organizationPk`	V	string	A UUID string identifying this 組織 ID
`ordering`	X	string	Sort field (default '-created_at')
`page`	X	integer	Page number
`pageSize`	X	integer	Rows per page (max 100)
`quotaStatus`	X	string	Filter by quota status
`search`	X	string	Filter by member name, email, or member ID (case-insensitive substring)

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/organizations/550e8400-
e29b-41d4-a716-446655440000/credit-quota-members/?ordering=-
created_at&page=1&pageSize=1&quotaStatus=allocated&search=example"

  -H "Authorization: Api-Key YOUR_API_KEY"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/organizations/550e8400-
e29b-41d4-a716-446655440000/credit-quota-members/?ordering=-
created_at&page=1&pageSize=1&quotaStatus=allocated&search=example",
config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-41d4-a716-446655440000/credit-quota-members/?ordering=-created_at&page=1&pageSize=1&quotaStatus=allocated&search=example"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-
41d4-a716-446655440000/credit-quota-members/?ordering=-
created_at&page=1&pageSize=1&quotaStatus=allocated&search=example",
[
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
{
  "count": integer
  "next"?: string (uri) // 非必填
  "previous"?: string (uri) // 非必填
  "results": [
    {
      "count"?: integer // 非必填
      "next"?: string (uri) // 非必填
      "previous"?: string (uri) // 非必填
      "results"?: [ // 非必填
        {
          "id"?: string (uuid) // 非必填
          "name"?: string // 非必填
          "email"?: string // 非必填
          "credit_quota_required"?: boolean // 非必填
          "active_quota"?: { // Most recent quota summary (active first);
same shape as the members API active_quota. (非必填)
          {
            "id"?: string (uuid) // 非必填
            "quota_limit"?: string // 非必填
            "consumed_amount"?: string // 非必填
            "remaining"?: string // 非必填
            "valid_from"?: string (date-time) // 非必填
            "valid_until"?: string (date-time) // 非必填
            "is_active"?: boolean // 非必填
            "expired_at"?: string (date-time) // 非必填
            "note"?: string // 非必填
          }
          }
        }
      ]
      "stats"?: { // Organization-wide member counts, unaffected by
search or quota_status filter. (非必填)
      {
        "total"?: integer // 非必填
        "allocated"?: integer // 非必填
        "expired"?: integer // 非必填
        "unallocated"?: integer // 非必填
      }
      }
    }
  ]
}
```

回應範例值


```
{
  "count": 123,
  "next": "http://api.example.org/accounts/?page=4",
  "previous": "http://api.example.org/accounts/?page=2",
  "results": [
    {
      "count": 456,
      "next": "https://example.com/file.jpg",
      "previous": "https://example.com/file.jpg",
      "results": [
        {
          "id": "550e8400-e29b-41d4-a716-446655440000",
          "name": "回應字串",
          "email": "回應字串",
          "credit_quota_required": false,
          "active_quota": {
            "id": "550e8400-e29b-41d4-a716-446655440000",
            "name": "回應範例名稱",
            "description": "回應範例描述"
          }
        }
      ],
      "stats": {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "name": "回應範例名稱",
        "description": "回應範例描述"
      }
    }
  ]
}
```


列出角色額度現況

`GET` `/api/v1/organizations/{organizationPk}/credit-quota-groups/`

所需權限：Credit 管理權限。計費模式：組織須為 Credit 計費模式。

參數

參數名稱	必填	類型	說明
`organizationPk`	V	string	A UUID string identifying this 組織 ID
`ordering`	X	string	Sort field (default '-created_at')
`page`	X	integer	Page number
`pageSize`	X	integer	Rows per page (max 100)
`quotaStatus`	X	string	Filter by quota status
`search`	X	string	Filter by group name or group ID (case-insensitive substring)

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/organizations/550e8400-
e29b-41d4-a716-446655440000/credit-quota-groups/?ordering=-
created_at&page=1&pageSize=1&quotaStatus=allocated&search=example"

  -H "Authorization: Api-Key YOUR_API_KEY"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/organizations/550e8400-
e29b-41d4-a716-446655440000/credit-quota-groups/?ordering=-
created_at&page=1&pageSize=1&quotaStatus=allocated&search=example",
config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-41d4-a716-446655440000/credit-quota-groups/?ordering=-created_at&page=1&pageSize=1&quotaStatus=allocated&search=example"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-
41d4-a716-446655440000/credit-quota-groups/?ordering=-
created_at&page=1&pageSize=1&quotaStatus=allocated&search=example",
[
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
{
  "count": integer
  "next"?: string (uri) // 非必填
  "previous"?: string (uri) // 非必填
  "results": [
    {
      "count"?: integer // 非必填
      "next"?: string (uri) // 非必填
      "previous"?: string (uri) // 非必填
      "results"?: [ // 非必填
        {
          "id"?: string (uuid) // 非必填
          "name"?: string // 非必填
          "type"?: string (enum: owner, default, custom) // 非必填
          "credit_quota_required"?: boolean // 非必填
          "active_quota"?: { // Most recent quota summary (active first);
same shape as the member/inbox variants. (非必填)
          {
            "id"?: string (uuid) // 非必填
            "quota_limit"?: string // 非必填
            "consumed_amount"?: string // 非必填
            "remaining"?: string // 非必填
            "valid_from"?: string (date-time) // 非必填
            "valid_until"?: string (date-time) // 非必填
            "is_active"?: boolean // 非必填
            "expired_at"?: string (date-time) // 非必填
            "note"?: string // 非必填
          }
          }
        }
      ]
      "stats"?: { // Organization-wide group counts, unaffected by search
or quota_status filter. (非必填)
      {
        "total"?: integer // 非必填
        "allocated"?: integer // 非必填
        "expired"?: integer // 非必填
        "unallocated"?: integer // 非必填
      }
      }
    }
  ]
}
```

回應範例值


```
{
  "count": 123,
  "next": "http://api.example.org/accounts/?page=4",
  "previous": "http://api.example.org/accounts/?page=2",
  "results": [
    {
      "count": 456,
      "next": "https://example.com/file.jpg",
      "previous": "https://example.com/file.jpg",
      "results": [
        {
          "id": "550e8400-e29b-41d4-a716-446655440000",
          "name": "回應字串",
          "type": "owner",
          "credit_quota_required": false,
          "active_quota": {
            "id": "550e8400-e29b-41d4-a716-446655440000",
            "name": "回應範例名稱",
            "description": "回應範例描述"
          }
        }
      ],
      "stats": {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "name": "回應範例名稱",
        "description": "回應範例描述"
      }
    }
  ]
}
```


列出對話平台額度現況

`GET` `/api/v1/organizations/{organizationPk}/credit-quota-inboxes/`

所需權限：Credit 管理權限。計費模式：組織須為 Credit 計費模式。

參數

參數名稱	必填	類型	說明
`organizationPk`	V	string	A UUID string identifying this 組織 ID
`ordering`	X	string	Which field to use when ordering the results.
`page`	X	integer	A page number within the paginated result set.
`pageSize`	X	integer	Number of results to return per page.
`search`	X	string	A search term.

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/organizations/550e8400-
e29b-41d4-a716-446655440000/credit-quota-inboxes/?
ordering=example&page=1&pageSize=1&search=example"

  -H "Authorization: Api-Key YOUR_API_KEY"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/organizations/550e8400-
e29b-41d4-a716-446655440000/credit-quota-inboxes/?
ordering=example&page=1&pageSize=1&search=example", config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-
41d4-a716-446655440000/credit-quota-inboxes/?
ordering=example&page=1&pageSize=1&search=example"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-
41d4-a716-446655440000/credit-quota-inboxes/?
ordering=example&page=1&pageSize=1&search=example", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
{
  "count": integer
```

```
  "next"?: string (uri) // 非必填
  "previous"?: string (uri) // 非必填
  "results": [
    {
      "id": string (uuid)
      "name": string
      "channelType":
      {
      }
      "channelTypeLabel": string
      "webChatAccessType": string // Sub-type for web channels (web =
public embed, admin = internal Q&A, api = completions).

A chatbot ships with three same-named web inboxes, so the frontend needs
this to tell them apart. None for non-web channels. Reads the prefetched
generic ``channel`` relation (no extra query on the list path).
      "chatbot": object
      "creditQuotaRequired": boolean // When True, this inbox must have
an active credit quota for the AI to reply
      "activeQuota": object // Return the most recent quota summary
(active first), via prefetch to avoid N+1.
      "canUpdate": boolean // Return whether the current user can update
this resource.
    }
  ]
}
```

回應範例值

```
{
  "count": 123,
  "next": "http://api.example.org/accounts/?page=4",
  "previous": "http://api.example.org/accounts/?page=2",
  "results": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "回應字串",
      "channelType": {},
      "channelTypeLabel": "回應字串",
      "webChatAccessType": "回應字串",
      "chatbot": {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "name": "回應範例名稱",
        "description": "回應範例描述"
```

```
      },
      "creditQuotaRequired": false,
      "activeQuota": {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "name": "回應範例名稱",
        "description": "回應範例描述"
      },
      "canUpdate": false
    }
  ]
}
```


列出成員的額度設定

`GET` `/api/v1/organizations/{organizationPk}/members/{memberPk}/credit-quotas/`

所需權限：Credit 管理權限。計費模式：組織須為 Credit 計費模式。

參數

參數名稱	必填	類型	說明
`memberPk`	V	string	
`organizationPk`	V	string	A UUID string identifying this 組織 ID
`page`	X	integer	A page number within the paginated result set.
`pageSize`	X	integer	Number of results to return per page.

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/organizations/550e8400-
e29b-41d4-a716-446655440000/members/{memberPk}/credit-quotas/?
page=1&pageSize=1"

  -H "Authorization: Api-Key YOUR_API_KEY"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/organizations/550e8400-
e29b-41d4-a716-446655440000/members/{memberPk}/credit-quotas/?
page=1&pageSize=1", config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-
41d4-a716-446655440000/members/{memberPk}/credit-quotas/?
page=1&pageSize=1"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-
41d4-a716-446655440000/members/{memberPk}/credit-quotas/?
page=1&pageSize=1", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
{
  "count": integer
```

```
  "next"?: string (uri) // 非必填
  "previous"?: string (uri) // 非必填
  "results": [
    {
      "id": string (uuid)
      "member": object
      "quotaLimit": string (decimal) // Maximum credits this member may
consume
      "consumedAmount": string (decimal) // Credits consumed so far
(updated via F() for concurrency safety)
      "remaining": string (decimal)
      "validFrom": string (timestamp)
      "validUntil": string (timestamp) // NULL means permanent
      "resetPeriod":  // Cycle on which consumed_amount is automatically
zeroed; "none" keeps the one-shot ceiling

* `none` - No Reset
* `daily` - Daily
* `weekly` - Weekly
* `monthly` - Monthly
      {
      }
      "nextResetAt": string (timestamp) // Local-midnight boundary of the
next automatic reset; NULL when reset_period is "none"
      "isActive": boolean
      "expiredAt": string (timestamp) // Actual deactivation time (cron
or manual)
      "createdBy": object
      "note": string
      "createdAt": string (timestamp)
      "updatedAt": string (timestamp)
    }
  ]
}
```

回應範例值

```
{
  "count": 123,
  "next": "http://api.example.org/accounts/?page=4",
  "previous": "http://api.example.org/accounts/?page=2",
  "results": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
```

```
      "member": {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "name": "回應範例名稱",
        "description": "回應範例描述"
      },
      "quotaLimit": "回應字串",
      "consumedAmount": "回應字串",
      "remaining": "回應字串",
      "validFrom": "回應字串",
      "validUntil": "回應字串",
      "resetPeriod": {},
      "nextResetAt": "回應字串",
      "isActive": false,
      "expiredAt": "回應字串",
      "createdBy": {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "name": "回應範例名稱",
        "description": "回應範例描述"
      },
      "note": "回應字串",
      "createdAt": "回應字串",
      "updatedAt": "回應字串"
    }
  ]
}
```


取得成員的單筆額度設定

GET `/api/v1/organizations/{organizationPk}/members/{memberPk}/credit-quotas/{id}`

所需權限：Credit 管理權限。計費模式：組織須為 Credit 計費模式。

參數

參數名稱	必填	類型	說明

`id`	V	string	
`memberPk`	V	string	
`organizationPk`	V	string	A UUID string identifying this 組織 ID

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/organizations/550e8400-
e29b-41d4-a716-446655440000/members/{memberPk}/credit-
quotas/550e8400-e29b-41d4-a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/organizations/550e8400-
e29b-41d4-a716-446655440000/members/{memberPk}/credit-
quotas/550e8400-e29b-41d4-a716-446655440000/", config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-41d4-a716-446655440000/members/{memberPk}/credit-quotas/550e8400-e29b-41d4-a716-446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-
41d4-a716-446655440000/members/{memberPk}/credit-quotas/550e8400-
e29b-41d4-a716-446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
{
  "id": string (uuid)
```

```
  "member": object
  "quotaLimit": string (decimal) // Maximum credits this member may
consume
  "consumedAmount": string (decimal) // Credits consumed so far (updated
via F() for concurrency safety)
  "remaining": string (decimal)
  "validFrom": string (timestamp)
  "validUntil": string (timestamp) // NULL means permanent
  "resetPeriod":  // Cycle on which consumed_amount is automatically
zeroed; "none" keeps the one-shot ceiling

* `none` - No Reset
* `daily` - Daily
* `weekly` - Weekly
* `monthly` - Monthly
  {
  }
  "nextResetAt": string (timestamp) // Local-midnight boundary of the
next automatic reset; NULL when reset_period is "none"
  "isActive": boolean
  "expiredAt": string (timestamp) // Actual deactivation time (cron or
manual)
  "createdBy": object
  "note": string
  "createdAt": string (timestamp)
  "updatedAt": string (timestamp)
}
```

回應範例值

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "member": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應範例名稱",
    "description": "回應範例描述"
  },
  "quotaLimit": "回應字串",
  "consumedAmount": "回應字串",
  "remaining": "回應字串",
  "validFrom": "回應字串",
  "validUntil": "回應字串",
  "resetPeriod": {},
  "nextResetAt": "回應字串",
```

```
  "isActive": false,
  "expiredAt": "回應字串",
  "createdBy": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應範例名稱",
    "description": "回應範例描述"
  },
  "note": "回應字串",
  "createdAt": "回應字串",
  "updatedAt": "回應字串"
}
```


為成員設定額度

POST `/api/v1/organizations/{organizationPk}/members/{memberPk}/credit-quotas/`

所需權限：Credit 管理權限。計費模式：組織須為 Credit 計費模式。

參數

參數名稱	必填	類型	說明
`memberPk`	V	string	
`organizationPk`	V	string	A UUID string identifying this 組織 ID

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X POST "https://api.maiagent.ai/api/v1/organizations/550e8400-
e29b-41d4-a716-446655440000/members/{memberPk}/credit-quotas/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{}'

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// 請求內容 (payload)
const data = {};

axios.post("https://api.maiagent.ai/api/v1/organizations/550e8400-
e29b-41d4-a716-446655440000/members/{memberPk}/credit-quotas/",
data, config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-
41d4-a716-446655440000/members/{memberPk}/credit-quotas/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# 請求內容 (payload)
data = {}

response = requests.post(url, json=data, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>post("https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-
41d4-a716-446655440000/members/{memberPk}/credit-quotas/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => new \stdClass()
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 201

回應結構範例

```
{
  "id": string (uuid)
  "member": object
  "quotaLimit": string (decimal) // Maximum credits this member may
consume
  "consumedAmount": string (decimal) // Credits consumed so far (updated
via F() for concurrency safety)
  "remaining": string (decimal)
  "validFrom": string (timestamp)
  "validUntil": string (timestamp) // NULL means permanent
  "resetPeriod":  // Cycle on which consumed_amount is automatically
zeroed; "none" keeps the one-shot ceiling

* `none` - No Reset
* `daily` - Daily
* `weekly` - Weekly
* `monthly` - Monthly
  {
  }
  "nextResetAt": string (timestamp) // Local-midnight boundary of the
next automatic reset; NULL when reset_period is "none"
  "isActive": boolean
  "expiredAt": string (timestamp) // Actual deactivation time (cron or
manual)
  "createdBy": object
  "note": string
  "createdAt": string (timestamp)
  "updatedAt": string (timestamp)
}
```

回應範例值

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "member": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應範例名稱",
    "description": "回應範例描述"
  },
  "quotaLimit": "回應字串",
  "consumedAmount": "回應字串",
  "remaining": "回應字串",
  "validFrom": "回應字串",
```

```
  "validUntil": "回應字串",
  "resetPeriod": {},
  "nextResetAt": "回應字串",
  "isActive": false,
  "expiredAt": "回應字串",
  "createdBy": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應範例名稱",
    "description": "回應範例描述"
  },
  "note": "回應字串",
  "createdAt": "回應字串",
  "updatedAt": "回應字串"
}
```


更新成員的額度設定

PATCH `/api/v1/organizations/{organizationPk}/members/{memberPk}/credit-quotas/{id}`

所需權限：Credit 管理權限。計費模式：組織須為 Credit 計費模式。

參數

參數名稱	必填	類型	說明
`id`	V	string	
`memberPk`	V	string	
`organizationPk`	V	string	A UUID string identifying this 組織 ID

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X PATCH
"https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-41d4-
a716-446655440000/members/{memberPk}/credit-quotas/550e8400-e29b-
41d4-a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{}'

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// 請求內容 (payload)
const data = {};

axios.patch("https://api.maiagent.ai/api/v1/organizations/550e8400-
e29b-41d4-a716-446655440000/members/{memberPk}/credit-
quotas/550e8400-e29b-41d4-a716-446655440000/", data, config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-41d4-a716-446655440000/members/{memberPk}/credit-quotas/550e8400-e29b-41d4-a716-446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# 請求內容 (payload)
data = {}

response = requests.patch(url, json=data, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>patch("https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-
41d4-a716-446655440000/members/{memberPk}/credit-quotas/550e8400-
e29b-41d4-a716-446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => new \stdClass()
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
{
  "id": string (uuid)
  "member": object
  "quotaLimit": string (decimal) // Maximum credits this member may
consume
  "consumedAmount": string (decimal) // Credits consumed so far (updated
via F() for concurrency safety)
  "remaining": string (decimal)
  "validFrom": string (timestamp)
  "validUntil": string (timestamp) // NULL means permanent
  "resetPeriod":  // Cycle on which consumed_amount is automatically
zeroed; "none" keeps the one-shot ceiling

* `none` - No Reset
* `daily` - Daily
* `weekly` - Weekly
* `monthly` - Monthly
  {
  }
  "nextResetAt": string (timestamp) // Local-midnight boundary of the
next automatic reset; NULL when reset_period is "none"
  "isActive": boolean
  "expiredAt": string (timestamp) // Actual deactivation time (cron or
manual)
  "createdBy": object
  "note": string
  "createdAt": string (timestamp)
  "updatedAt": string (timestamp)
}
```

回應範例值

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "member": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應範例名稱",
    "description": "回應範例描述"
  },
  "quotaLimit": "回應字串",
  "consumedAmount": "回應字串",
  "remaining": "回應字串",
  "validFrom": "回應字串",
```

```
  "validUntil": "回應字串",
  "resetPeriod": {},
  "nextResetAt": "回應字串",
  "isActive": false,
  "expiredAt": "回應字串",
  "createdBy": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應範例名稱",
    "description": "回應範例描述"
  },
  "note": "回應字串",
  "createdAt": "回應字串",
  "updatedAt": "回應字串"
}
```


列出角色的額度設定

`GET` `/api/v1/organizations/{organizationPk}/groups/{groupPk}/credit-quotas/`

所需權限：Credit 管理權限。計費模式：組織須為 Credit 計費模式。

參數

參數名稱	必填	類型	說明
`groupPk`	V	string	
`organizationPk`	V	string	A UUID string identifying this 組織 ID
`page`	X	integer	A page number within the paginated result set.
`pageSize`	X	integer	Number of results to return per page.

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/organizations/550e8400-
e29b-41d4-a716-446655440000/groups/{groupPk}/credit-quotas/?
page=1&pageSize=1"

  -H "Authorization: Api-Key YOUR_API_KEY"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/organizations/550e8400-
e29b-41d4-a716-446655440000/groups/{groupPk}/credit-quotas/?
page=1&pageSize=1", config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-
41d4-a716-446655440000/groups/{groupPk}/credit-quotas/?
page=1&pageSize=1"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-
41d4-a716-446655440000/groups/{groupPk}/credit-quotas/?
page=1&pageSize=1", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
{
  "count": integer
```

```
  "next"?: string (uri) // 非必填
  "previous"?: string (uri) // 非必填
  "results": [
    {
      "id": string (uuid)
      "group": object
      "quotaLimit": string (decimal) // Maximum credits members of this
group may consume
      "consumedAmount": string (decimal) // Credits consumed so far
(updated via F() for concurrency safety)
      "remaining": string (decimal)
      "validFrom": string (timestamp)
      "validUntil": string (timestamp) // NULL means permanent
      "resetPeriod":  // Cycle on which consumed_amount is automatically
zeroed; "none" keeps the one-shot ceiling

* `none` - No Reset
* `daily` - Daily
* `weekly` - Weekly
* `monthly` - Monthly
      {
      }
      "nextResetAt": string (timestamp) // Local-midnight boundary of the
next automatic reset; NULL when reset_period is "none"
      "isActive": boolean
      "expiredAt": string (timestamp) // Actual deactivation time (cron
or manual)
      "createdBy": object
      "note": string
      "createdAt": string (timestamp)
      "updatedAt": string (timestamp)
    }
  ]
}
```

回應範例值

```
{
  "count": 123,
  "next": "http://api.example.org/accounts/?page=4",
  "previous": "http://api.example.org/accounts/?page=2",
  "results": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
```

```
      "group": {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "name": "回應範例名稱",
        "description": "回應範例描述"
      },
      "quotaLimit": "回應字串",
      "consumedAmount": "回應字串",
      "remaining": "回應字串",
      "validFrom": "回應字串",
      "validUntil": "回應字串",
      "resetPeriod": {},
      "nextResetAt": "回應字串",
      "isActive": false,
      "expiredAt": "回應字串",
      "createdBy": {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "name": "回應範例名稱",
        "description": "回應範例描述"
      },
      "note": "回應字串",
      "createdAt": "回應字串",
      "updatedAt": "回應字串"
    }
  ]
}
```


取得角色的單筆額度設定

`GET` `/api/v1/organizations/{organizationPk}/groups/{groupPk}/credit-quotas/{id}`

所需權限：Credit 管理權限。計費模式：組織須為 Credit 計費模式。

參數

參數名稱	必填	類型	說明

`groupPk`	V	string	
`id`	V	string	
`organizationPk`	V	string	A UUID string identifying this 組織 ID

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/organizations/550e8400-
e29b-41d4-a716-446655440000/groups/{groupPk}/credit-quotas/550e8400-
e29b-41d4-a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/organizations/550e8400-
e29b-41d4-a716-446655440000/groups/{groupPk}/credit-quotas/550e8400-
e29b-41d4-a716-446655440000/", config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-
41d4-a716-446655440000/groups/{groupPk}/credit-quotas/550e8400-e29b-
41d4-a716-446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-
41d4-a716-446655440000/groups/{groupPk}/credit-quotas/550e8400-e29b-
41d4-a716-446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
{
  "id": string (uuid)
```

```
  "group": object
  "quotaLimit": string (decimal) // Maximum credits members of this group
may consume
  "consumedAmount": string (decimal) // Credits consumed so far (updated
via F() for concurrency safety)
  "remaining": string (decimal)
  "validFrom": string (timestamp)
  "validUntil": string (timestamp) // NULL means permanent
  "resetPeriod":  // Cycle on which consumed_amount is automatically
zeroed; "none" keeps the one-shot ceiling

* `none` - No Reset
* `daily` - Daily
* `weekly` - Weekly
* `monthly` - Monthly
  {
  }
  "nextResetAt": string (timestamp) // Local-midnight boundary of the
next automatic reset; NULL when reset_period is "none"
  "isActive": boolean
  "expiredAt": string (timestamp) // Actual deactivation time (cron or
manual)
  "createdBy": object
  "note": string
  "createdAt": string (timestamp)
  "updatedAt": string (timestamp)
}
```

回應範例值

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "group": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應範例名稱",
    "description": "回應範例描述"
  },
  "quotaLimit": "回應字串",
  "consumedAmount": "回應字串",
  "remaining": "回應字串",
  "validFrom": "回應字串",
  "validUntil": "回應字串",
  "resetPeriod": {},
  "nextResetAt": "回應字串",
```

```
  "isActive": false,
  "expiredAt": "回應字串",
  "createdBy": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應範例名稱",
    "description": "回應範例描述"
  },
  "note": "回應字串",
  "createdAt": "回應字串",
  "updatedAt": "回應字串"
}
```


查詢角色成員額度統計

`GET` `/api/v1/organizations/{organizationPk}/groups/{id}/credit-quota-stats/`

所需權限：Credit 管理權限。計費模式：組織須為 Credit 計費模式。

參數

參數名稱	必填	類型	說明
`id`	V	string	A UUID string identifying this Group.
`organizationPk`	V	string	A UUID string identifying this 組織 ID

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/organizations/550e8400-
e29b-41d4-a716-446655440000/groups/550e8400-e29b-41d4-a716-
446655440000/credit-quota-stats/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/organizations/550e8400-
e29b-41d4-a716-446655440000/groups/550e8400-e29b-41d4-a716-
446655440000/credit-quota-stats/", config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-41d4-a716-446655440000/groups/550e8400-e29b-41d4-a716-446655440000/credit-quota-stats/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-
41d4-a716-446655440000/groups/550e8400-e29b-41d4-a716-
446655440000/credit-quota-stats/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
{
  "activeQuotaMembersCount": integer
```

```
  "quotaRequiredMembersCount": integer
}
```

回應範例值

```
{
  "activeQuotaMembersCount": 456,
  "quotaRequiredMembersCount": 456
}
```

依角色批次分配額度

POST `/api/v1/organizations/{organizationPk}/groups/{id}/batch-distribute-credit-quota/`

所需權限：Credit 管理權限＋組織概覽權限。計費模式：組織須為 Credit 計費模式。

參數

參數名稱	必填	類型	說明
`id`	V	string	A UUID string identifying this Group.
`organizationPk`	V	string	A UUID string identifying this 組織 ID

請求內容

請求參數

欄位	類型	必填	說明
name	string	是	
canCreateChatbot	boolean	否	
canCreateKnowledgeBase	boolean	否	
canCreateInbox	boolean	否	
canCreateDatabase	boolean	否	
canCreateTool	boolean	否	
canCreateAgentUiTool	boolean	否	
canCreateSkill	boolean	否	
maigptCanCodeInterpreter	boolean	否	Whether members of this role may use the code interpreter built-in tool in MaiGPT.
maigptCanRag	boolean	否	Whether members of this role may use the knowledge base RAG built-in tool in MaiGPT.
maigptCanDeepResearch	boolean	否	Whether members of this role may use Deep Research in MaiGPT. Deep Research reaches the public internet through its own built-in search, so a role that revokes the official web-search tools needs this...
maigptCanBrowserTool	boolean	否	Whether members of this role may use the browser built-in tool in MaiGPT.
maigptAllLlms	boolean	否	Whether members of this role may use every organization-available LLM in MaiGPT. Off = only the bound LLMs; an empty binding then means none.
maigptAllTools	boolean	否	Whether members of this role may call every official (global) tool in MaiGPT. Off = only the bound tools; an empty binding then means none.
maigptAllConnectors	boolean	否	Whether members of this role may call every official (global) MCP connector in

欄位	類型	必填	說明
			MaiGPT. Off = only the bound connectors; an empty binding then means none.
maigptAllSkills	boolean	否	Whether members of this role may use every official (global) skill in MaiGPT. Off = only the bound skills; an empty binding then means none.
usageStatisticsScope	object	否	What this role's usage statistics permission shows: the whole organization, or only the AI assistants granted to the member's roles. A member with any organization-wide granting role sees the whole or...

請求結構範例

```
{
  "name": string
  "canCreateChatbot"?: boolean // 非必填
  "canCreateKnowledgeBase"?: boolean // 非必填
  "canCreateInbox"?: boolean // 非必填
  "canCreateDatabase"?: boolean // 非必填
  "canCreateTool"?: boolean // 非必填
  "canCreateAgentUiTool"?: boolean // 非必填
  "canCreateSkill"?: boolean // 非必填
  "maigptCanCodeInterpreter"?: boolean // Whether members of this role may use the code interpreter built-in tool in MaiGPT. (非必填)
  "maigptCanRag"?: boolean // Whether members of this role may use the knowledge base RAG built-in tool in MaiGPT. (非必填)
  "maigptCanDeepResearch"?: boolean // Whether members of this role may use Deep Research in MaiGPT. Deep Research reaches the public internet through its own built-in search, so a role that revokes the official web-search tools needs this switch too. (非必填)
  "maigptCanBrowserTool"?: boolean // Whether members of this role may use the browser built-in tool in MaiGPT. (非必填)
  "maigptAllLlms"?: boolean // Whether members of this role may use every organization-available LLM in MaiGPT. Off = only the bound LLMs; an empty binding then means none. (非必填)
  "maigptAllTools"?: boolean // Whether members of this role may call every official (global) tool in MaiGPT. Off = only the bound tools; an empty binding then means none. (非必填)
```

```
  "maigptAllConnectors"?: boolean // Whether members of this role may call every official (global) MCP connector in MaiGPT. Off = only the bound connectors; an empty binding then means none. (非必填)
  "maigptAllSkills"?: boolean // Whether members of this role may use every official (global) skill in MaiGPT. Off = only the bound skills; an empty binding then means none. (非必填)
  "usageStatisticsScope"?:  // What this role's usage statistics permission shows: the whole organization, or only the AI assistants granted to the member's roles. A member with any organization-wide granting role sees the whole organization.

* `organization` - Organization-wide
* `accessible_chatbots` - Authorized AI assistants only (非必填)
  {
  }
}
```

請求範例值

```
{
  "name": "範例名稱",
  "canCreateChatbot": true,
  "canCreateKnowledgeBase": true,
  "canCreateInbox": true,
  "canCreateDatabase": true,
  "canCreateTool": true,
  "canCreateAgentUiTool": true,
  "canCreateSkill": true,
  "maigptCanCodeInterpreter": true,
  "maigptCanRag": true,
  "maigptCanDeepResearch": true,
  "maigptCanBrowserTool": true,
  "maigptAllLlms": true,
  "maigptAllTools": true,
  "maigptAllConnectors": true,
  "maigptAllSkills": true,
  "usageStatisticsScope": {}
}
```

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X POST "https://api.maiagent.ai/api/v1/organizations/550e8400-
e29b-41d4-a716-446655440000/groups/550e8400-e29b-41d4-a716-
446655440000/batch-distribute-credit-quota/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "name": "範例名稱",
    "canCreateChatbot": true,
    "canCreateKnowledgeBase": true,
    "canCreateInbox": true,
    "canCreateDatabase": true,
    "canCreateTool": true,
    "canCreateAgentUiTool": true,
    "canCreateSkill": true,
    "maigptCanCodeInterpreter": true,
    "maigptCanRag": true,
    "maigptCanDeepResearch": true,
    "maigptCanBrowserTool": true,
    "maigptAllLlms": true,
    "maigptAllTools": true,
    "maigptAllConnectors": true,
    "maigptAllSkills": true,
    "usageStatisticsScope": {}
  }'

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// 請求內容 (payload)
const data = {
    "name": "範例名稱",
    "canCreateChatbot": true,
    "canCreateKnowledgeBase": true,
    "canCreateInbox": true,
    "canCreateDatabase": true,
    "canCreateTool": true,
    "canCreateAgentUiTool": true,
    "canCreateSkill": true,
    "maigptCanCodeInterpreter": true,
    "maigptCanRag": true,
    "maigptCanDeepResearch": true,
    "maigptCanBrowserTool": true,
    "maigptAllLlms": true,
    "maigptAllTools": true,
    "maigptAllConnectors": true,
    "maigptAllSkills": true,
    "usageStatisticsScope": {}
  };

axios.post("https://api.maiagent.ai/api/v1/organizations/550e8400-
e29b-41d4-a716-446655440000/groups/550e8400-e29b-41d4-a716-
446655440000/batch-distribute-credit-quota/", data, config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
```

```
  console.error(error.response?.data || error.message);
});
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-
41d4-a716-446655440000/groups/550e8400-e29b-41d4-a716-
446655440000/batch-distribute-credit-quota/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# 請求內容 (payload)
data = {
    "name": "範例名稱",
    "canCreateChatbot": True,
    "canCreateKnowledgeBase": True,
    "canCreateInbox": True,
    "canCreateDatabase": True,
    "canCreateTool": True,
    "canCreateAgentUiTool": True,
    "canCreateSkill": True,
    "maigptCanCodeInterpreter": True,
    "maigptCanRag": True,
    "maigptCanDeepResearch": True,
    "maigptCanBrowserTool": True,
    "maigptAllLlms": True,
    "maigptAllTools": True,
    "maigptAllConnectors": True,
    "maigptAllSkills": True,
    "usageStatisticsScope": {}
}

response = requests.post(url, json=data, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>post("https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-
41d4-a716-446655440000/groups/550e8400-e29b-41d4-a716-
446655440000/batch-distribute-credit-quota/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'name' => '範例名稱',
            'canCreateChatbot' => true,
            'canCreateKnowledgeBase' => true,
            'canCreateInbox' => true,
            'canCreateDatabase' => true,
            'canCreateTool' => true,
            'canCreateAgentUiTool' => true,
            'canCreateSkill' => true,
            'maigptCanCodeInterpreter' => true,
            'maigptCanRag' => true,
            'maigptCanDeepResearch' => true,
            'maigptCanBrowserTool' => true,
            'maigptAllLlms' => true,
            'maigptAllTools' => true,
            'maigptAllConnectors' => true,
            'maigptAllSkills' => true,
            'usageStatisticsScope' => new \stdClass()
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
```

```
  }
  ?>
```

回應內容

狀態碼: 200

回應結構範例

```
{
  "id": string (uuid)
  "name": string
  "type":
  {
  }
  "permissions": [
    object
  ]
  "membersPreview": [
    string
  ]
  "membersCount": integer // 返回剩餘成員數量（扣除列表顯示的 3 人後），用於前端 +N badge 顯示

與資源 count 不同：
<ul>
  <li>members_count: 返回 total - 3（用於 +N badge），None 表示總數 <= 3</li>
  <li>chatbots_count/knowledge_bases_count/inboxes_count: 返回總數量</li>
</ul>
  "chatbotsCount": integer
  "chatbotsPreview": [
    string
  ]
  "knowledgeBasesCount": integer
  "knowledgeBasesPreview": [
    string
  ]
```

```
  "inboxesCount": integer
  "inboxesPreview": [
    string
  ]
  "databasesCount": integer
  "databasesPreview": [
    string
  ]
  "canCreateChatbot"?: boolean // 非必填
  "canCreateKnowledgeBase"?: boolean // 非必填
  "canCreateInbox"?: boolean // 非必填
  "canCreateDatabase"?: boolean // 非必填
  "canCreateTool"?: boolean // 非必填
  "canCreateAgentUiTool"?: boolean // 非必填
  "canCreateSkill"?: boolean // 非必填
  "maigptCanCodeInterpreter"?: boolean // Whether members of this role
may use the code interpreter built-in tool in MaiGPT. (非必填)
  "maigptCanRag"?: boolean // Whether members of this role may use the
knowledge base RAG built-in tool in MaiGPT. (非必填)
  "maigptCanDeepResearch"?: boolean // Whether members of this role may
use Deep Research in MaiGPT. Deep Research reaches the public internet
through its own built-in search, so a role that revokes the official web-
search tools needs this switch too. (非必填)
  "maigptCanBrowserTool"?: boolean // Whether members of this role may
use the browser built-in tool in MaiGPT. (非必填)
  "maigptAllLlms"?: boolean // Whether members of this role may use every
organization-available LLM in MaiGPT. Off = only the bound LLMs; an empty
binding then means none. (非必填)
  "maigptAllTools"?: boolean // Whether members of this role may call
every official (global) tool in MaiGPT. Off = only the bound tools; an
empty binding then means none. (非必填)
  "maigptAllConnectors"?: boolean // Whether members of this role may
call every official (global) MCP connector in MaiGPT. Off = only the
bound connectors; an empty binding then means none. (非必填)
  "maigptAllSkills"?: boolean // Whether members of this role may use
every official (global) skill in MaiGPT. Off = only the bound skills; an
empty binding then means none. (非必填)
  "usageStatisticsScope"?:  // What this role's usage statistics
permission shows: the whole organization, or only the AI assistants
granted to the member's roles. A member with any organization-wide
granting role sees the whole organization.

* `organization` - Organization-wide
* `accessible_chatbots` - Authorized AI assistants only (非必填)
  {
```

```
  }
  "createdAt": string (timestamp)
}
```

回應範例值

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "name": "回應字串",
  "type": {},
  "permissions": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "回應範例名稱",
      "description": "回應範例描述"
    }
  ],
  "membersPreview": [
    "回應字串"
  ],
  "membersCount": 456,
  "chatbotsCount": 456,
  "chatbotsPreview": [
    "回應字串"
  ],
  "knowledgeBasesCount": 456,
  "knowledgeBasesPreview": [
    "回應字串"
  ],
  "inboxesCount": 456,
  "inboxesPreview": [
    "回應字串"
  ],
  "databasesCount": 456,
  "databasesPreview": [
    "回應字串"
  ],
  "canCreateChatbot": false,
  "canCreateKnowledgeBase": false,
  "canCreateInbox": false,
  "canCreateDatabase": false,
  "canCreateTool": false,
  "canCreateAgentUiTool": false,
  "canCreateSkill": false,
```

```
  "maigptCanCodeInterpreter": false,
  "maigptCanRag": false,
  "maigptCanDeepResearch": false,
  "maigptCanBrowserTool": false,
  "maigptAllLlms": false,
  "maigptAllTools": false,
  "maigptAllConnectors": false,
  "maigptAllSkills": false,
  "usageStatisticsScope": {},
  "createdAt": "回應字串"
}
```


查詢自己的額度

GET `/api/v1/organizations/{organizationPk}/me/credit-quota/`

所需權限：不需額外權限，任何組織成員都能查自己的額度。計費模式：組織須為 Credit 計費模式。

參數

參數名稱	必填	類型	說明
`organizationPk`	V	string	A UUID string identifying this 組織 ID

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/organizations/550e8400-
e29b-41d4-a716-446655440000/me/credit-quota/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/organizations/550e8400-
e29b-41d4-a716-446655440000/me/credit-quota/", config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-41d4-a716-446655440000/me/credit-quota/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-
41d4-a716-446655440000/me/credit-quota/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼	說明
200	No response body

查詢自己所屬角色的額度

`GET` `/api/v1/organizations/{organizationPk}/me/group-credit-quotas/`

所需權限：不需額外權限，任何組織成員都能查自己的額度。計費模式：組織須為 Credit 計費模式。

參數

參數名稱	必填	類型	說明
`organizationPk`	V	string	A UUID string identifying this 組織 ID

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/organizations/550e8400-
e29b-41d4-a716-446655440000/me/group-credit-quotas/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/organizations/550e8400-
e29b-41d4-a716-446655440000/me/group-credit-quotas/", config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-
41d4-a716-446655440000/me/group-credit-quotas/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-
41d4-a716-446655440000/me/group-credit-quotas/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼	說明
200	No response body

列出計價規則

GET `/api/v1/credit/pricing-rules/`

免登入：不需 API Key 即可呼叫。呼叫上限：每分鐘 60 次，依來源 IP 計算，超過回傳 HTTP 429。

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/credit/pricing-rules/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/credit/pricing-rules/",
config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/credit/pricing-rules/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/credit/pricing-rules/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
[
  {
    "id": string (uuid)
    "creditItem": string (uuid)
```

```
    "provider": string
    "modelCode": string
    "creditPerUnit": string (decimal)
    "priority": integer // Higher priority = more specific (model-
specific=20, provider-level=10)
    "effectiveFrom": string (timestamp)
    "effectiveUntil": string (timestamp)
    "isActive": boolean
    "notes": string // Internal notes about this pricing rule
  }
]
```

回應範例值


```
[
  {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "creditItem": "550e8400-e29b-41d4-a716-446655440000",
    "provider": "回應字串",
    "modelCode": "回應字串",
    "creditPerUnit": "回應字串",
    "priority": 456,
    "effectiveFrom": "回應字串",
    "effectiveUntil": "回應字串",
    "isActive": false,
    "notes": "回應字串"
  }
]
```


取得單一計價規則

`GET` `/api/v1/credit/pricing-rules/{id}`

免登入：不需 API Key 即可呼叫。呼叫上限：每分鐘 60 次，依來源 IP 計算，超過回傳 HTTP 429。

參數

參數名稱	必填	類型	說明
`id`	V	string	A UUID string identifying this Credit Pricing Rule.

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/credit/pricing-
rules/550e8400-e29b-41d4-a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/credit/pricing-
rules/550e8400-e29b-41d4-a716-446655440000/", config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/credit/pricing-rules/550e8400-e29b-41d4-a716-446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/credit/pricing-rules/550e8400-
e29b-41d4-a716-446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
{
  "id": string (uuid)
  "creditItem": string (uuid)
```

```
  "provider": string
  "modelCode": string
  "creditPerUnit": string (decimal)
  "priority": integer // Higher priority = more specific (model-
specific=20, provider-level=10)
  "effectiveFrom": string (timestamp)
  "effectiveUntil": string (timestamp)
  "isActive": boolean
  "notes": string // Internal notes about this pricing rule
}
```

回應範例值

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "creditItem": "550e8400-e29b-41d4-a716-446655440000",
  "provider": "回應字串",
  "modelCode": "回應字串",
  "creditPerUnit": "回應字串",
  "priority": 456,
  "effectiveFrom": "回應字串",
  "effectiveUntil": "回應字串",
  "isActive": false,
  "notes": "回應字串"
}
```

列出計價項目

GET `/api/v1/credit/items/`

免登入：不需 API Key 即可呼叫。呼叫上限：每分鐘 60 次，依來源 IP 計算，超過回傳 HTTP 429。

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/credit/items/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/credit/items/", config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/credit/items/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/credit/items/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
[
  {
    "id": string (uuid)
    "code": string // Unique identifier like llm_input_token
```

```
    "name": string
    "category":
    {
    }
    "unit": string // token, character, minute, etc.
    "creditPerUnit": string (decimal)
    "baseCreditPerUnit": string (decimal)
    "effectiveFrom": string (timestamp)
    "isActive": boolean
    "description": string
    "displayGroup": string // Items with the same display_group are
merged into one expandable row on the pricing page. Empty means the item
stands alone.
    "displayOrder": integer // Controls display ordering. Lower numbers
appear first.
    "attachmentRetentionDays": integer // Current Config retention
setting, so the pricing-page tooltip day count follows admin changes.
    "gatewayTrafficFeeDefaultPercent": string // System default AI
Gateway traffic-fee percent, for pricing pages without an org context.

This endpoint is AllowAny with no organization, so it can only surface
the system default ("for reference only" on the frontend); logged-in
pricing pages read the organization's actual percent from the
organization detail API instead.
  }
]
```

回應範例值

```
[
  {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "code": "回應字串",
    "name": "回應字串",
    "category": {},
    "unit": "回應字串",
    "creditPerUnit": "回應字串",
    "baseCreditPerUnit": "回應字串",
    "effectiveFrom": "回應字串",
    "isActive": false,
    "description": "回應字串",
    "displayGroup": "回應字串",
    "displayOrder": 456,
    "attachmentRetentionDays": 456,
```

```
    "gatewayTrafficFeeDefaultPercent": "回應字串"
  }
]
```

取得單一計價項目

GET `/api/v1/credit/items/{id}`

免登入：不需 API Key 即可呼叫。呼叫上限：每分鐘 60 次，依來源 IP 計算，超過回傳 HTTP 429。

參數

參數名稱	必填	類型	說明
`id`	V	string	A UUID string identifying this Credit Item.

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/credit/items/550e8400-
e29b-41d4-a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/credit/items/550e8400-
e29b-41d4-a716-446655440000/", config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/credit/items/550e8400-e29b-
41d4-a716-446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/credit/items/550e8400-e29b-
41d4-a716-446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
{
  "id": string (uuid)
  "code": string // Unique identifier like llm_input_token
```

```
  "name": string
  "category":
  {
  }
  "unit": string // token, character, minute, etc.
  "creditPerUnit": string (decimal)
  "baseCreditPerUnit": string (decimal)
  "effectiveFrom": string (timestamp)
  "isActive": boolean
  "description": string
  "displayGroup": string // Items with the same display_group are merged into one expandable row on the pricing page. Empty means the item stands alone.
  "displayOrder": integer // Controls display ordering. Lower numbers appear first.
  "attachmentRetentionDays": integer // Current Config retention setting, so the pricing-page tooltip day count follows admin changes.
  "gatewayTrafficFeeDefaultPercent": string // System default AI Gateway traffic-fee percent, for pricing pages without an org context.

This endpoint is AllowAny with no organization, so it can only surface the system default ("for reference only" on the frontend); logged-in pricing pages read the organization's actual percent from the organization detail API instead.
}
```

回應範例值

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "code": "回應字串",
  "name": "回應字串",
  "category": {},
  "unit": "回應字串",
  "creditPerUnit": "回應字串",
  "baseCreditPerUnit": "回應字串",
  "effectiveFrom": "回應字串",
  "isActive": false,
  "description": "回應字串",
  "displayGroup": "回應字串",
  "displayOrder": 456,
  "attachmentRetentionDays": 456,
```

```
  "gatewayTrafficFeeDefaultPercent": "回應字串"
}
```

呼叫 API 示例 (Shell)

目錄

1. 取得服務提供者設定（IdP 探索用）
2. 列出或查詢成員（支援 `filter`、`startIndex`、`count`）
3. 建立成員
4. 取得特定成員
5. 整筆取代成員
6. 局部更新成員（停用、改名、改 externalId）
7. 停用成員
8. 列出群組（對應 MaiAgent 角色）
9. 建立群組
10. 取得特定群組
11. 整筆取代群組
12. 局部更新群組（改名、增減成員）
13. 刪除群組

呼叫 API 示例 (Shell)

SCIM 2.0 端點讓您的身分提供者（Entra ID、Okta 等）自動開通、更新與停用組織成員。基底網址是 https://api.maiagent.ai/api/v1/scim/{orgUuid}，路徑不以 `/` 結尾；認證用 `Authorization: Bearer`（在後台身分同步設定取得，不是 API Key），`Content-Type: application/scim+json`，每個組織每分鐘 100 次請求。欄位對應與停用語意見技術手冊成員開通。

取得服務提供者設定（IdP 探索用）

GET `/api/v1/scim/{orgUuid}/ServiceProviderConfig`

參數

參數名稱	必填	類型	說明
`orgUuid`	V	string	

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/scim/550e8400-e29b-41d4-
a716-446655440000/ServiceProviderConfig"

  -H "Authorization: Bearer YOUR_SCIM_TOKEN"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Bearer YOUR_SCIM_TOKEN'
  }
};

axios.get("https://api.maiagent.ai/api/v1/scim/550e8400-e29b-41d4-
a716-446655440000/ServiceProviderConfig", config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/scim/550e8400-e29b-41d4-a716-446655440000/ServiceProviderConfig"
headers = {
    "Authorization": "Bearer YOUR_SCIM_TOKEN"
}


response = requests.get(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/scim/550e8400-e29b-41d4-a716-
446655440000/ServiceProviderConfig", [
        'headers' => [
            'Authorization' => 'Bearer YOUR_SCIM_TOKEN'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼	說明
200	No response body

列出或查詢成員（支援 `filter`、`startIndex`、`count`）

`GET` `/api/v1/scim/{orgUuid}/Users`

參數

參數名稱	必填	類型	說明
`orgUuid`	V	string	

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/scim/550e8400-e29b-41d4-
a716-446655440000/Users"

  -H "Authorization: Bearer YOUR_SCIM_TOKEN"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Bearer YOUR_SCIM_TOKEN'
  }
};

axios.get("https://api.maiagent.ai/api/v1/scim/550e8400-e29b-41d4-
a716-446655440000/Users", config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/scim/550e8400-e29b-41d4-a716-446655440000/Users"
headers = {
    "Authorization": "Bearer YOUR_SCIM_TOKEN"
}


response = requests.get(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/scim/550e8400-e29b-41d4-a716-
446655440000/Users", [
        'headers' => [
            'Authorization' => 'Bearer YOUR_SCIM_TOKEN'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼	說明
200	No response body

建立成員

POST `/api/v1/scim/{orgUuid}/Users`

參數

參數名稱	必填	類型	說明
`orgUuid`	V	string	

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X POST "https://api.maiagent.ai/api/v1/scim/550e8400-e29b-
41d4-a716-446655440000/Users"

  -H "Authorization: Bearer YOUR_SCIM_TOKEN"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Bearer YOUR_SCIM_TOKEN'
  }
};

// 請求內容 (payload)
const data = null;

axios.post("https://api.maiagent.ai/api/v1/scim/550e8400-e29b-41d4-
a716-446655440000/Users", data, config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/scim/550e8400-e29b-41d4-a716-446655440000/Users"
headers = {
    "Authorization": "Bearer YOUR_SCIM_TOKEN"
}


response = requests.post(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>post("https://api.maiagent.ai/api/v1/scim/550e8400-e29b-41d4-a716-
446655440000/Users", [
        'headers' => [
            'Authorization' => 'Bearer YOUR_SCIM_TOKEN'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼	說明
200	No response body

取得特定成員

`GET` `/api/v1/scim/{orgUuid}/Users/{userId}`

參數

參數名稱	必填	類型	說明
`orgUuid`	V	string	
`userId`	V	string	

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/scim/550e8400-e29b-41d4-
a716-446655440000/Users/550e8400-e29b-41d4-a716-446655440000"

  -H "Authorization: Bearer YOUR_SCIM_TOKEN"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Bearer YOUR_SCIM_TOKEN'
  }
};

axios.get("https://api.maiagent.ai/api/v1/scim/550e8400-e29b-41d4-
a716-446655440000/Users/550e8400-e29b-41d4-a716-446655440000",
config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/scim/550e8400-e29b-41d4-a716-446655440000/Users/550e8400-e29b-41d4-a716-446655440000"
headers = {
    "Authorization": "Bearer YOUR_SCIM_TOKEN"
}


response = requests.get(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/scim/550e8400-e29b-41d4-a716-
446655440000/Users/550e8400-e29b-41d4-a716-446655440000", [
        'headers' => [
            'Authorization' => 'Bearer YOUR_SCIM_TOKEN'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼	說明
200	No response body

整筆取代成員

PUT `/api/v1/scim/{orgUuid}/Users/{userId}`

參數

參數名稱	必填	類型	說明
`orgUuid`	V	string	
`userId`	V	string	

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X PUT "https://api.maiagent.ai/api/v1/scim/550e8400-e29b-41d4-
a716-446655440000/Users/550e8400-e29b-41d4-a716-446655440000"

  -H "Authorization: Bearer YOUR_SCIM_TOKEN"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Bearer YOUR_SCIM_TOKEN'
  }
};

// 請求內容 (payload)
const data = null;

axios.put("https://api.maiagent.ai/api/v1/scim/550e8400-e29b-41d4-
a716-446655440000/Users/550e8400-e29b-41d4-a716-446655440000", data,
config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/scim/550e8400-e29b-41d4-a716-446655440000/Users/550e8400-e29b-41d4-a716-446655440000"
headers = {
    "Authorization": "Bearer YOUR_SCIM_TOKEN"
}


response = requests.put(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>put("https://api.maiagent.ai/api/v1/scim/550e8400-e29b-41d4-a716-
446655440000/Users/550e8400-e29b-41d4-a716-446655440000", [
        'headers' => [
            'Authorization' => 'Bearer YOUR_SCIM_TOKEN'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼	說明
200	No response body

局部更新成員（停用、改名、改 externalId）

PATCH `/api/v1/scim/{orgUuid}/Users/{userId}`

參數

參數名稱	必填	類型	說明
`orgUuid`	V	string	
`userId`	V	string	

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X PATCH "https://api.maiagent.ai/api/v1/scim/550e8400-e29b-
41d4-a716-446655440000/Users/550e8400-e29b-41d4-a716-446655440000"

  -H "Authorization: Bearer YOUR_SCIM_TOKEN"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Bearer YOUR_SCIM_TOKEN'
  }
};

// 請求內容 (payload)
const data = null;

axios.patch("https://api.maiagent.ai/api/v1/scim/550e8400-e29b-41d4-
a716-446655440000/Users/550e8400-e29b-41d4-a716-446655440000", data,
config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/scim/550e8400-e29b-41d4-a716-446655440000/Users/550e8400-e29b-41d4-a716-446655440000"
headers = {
    "Authorization": "Bearer YOUR_SCIM_TOKEN"
}


response = requests.patch(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>patch("https://api.maiagent.ai/api/v1/scim/550e8400-e29b-41d4-a716-
446655440000/Users/550e8400-e29b-41d4-a716-446655440000", [
        'headers' => [
            'Authorization' => 'Bearer YOUR_SCIM_TOKEN'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼	說明
200	No response body

停用成員

DELETE `/api/v1/scim/{orgUuid}/Users/{userId}`

參數

參數名稱	必填	類型	說明
`orgUuid`	V	string	
`userId`	V	string	

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X DELETE "https://api.maiagent.ai/api/v1/scim/550e8400-e29b-
41d4-a716-446655440000/Users/550e8400-e29b-41d4-a716-446655440000"

  -H "Authorization: Bearer YOUR_SCIM_TOKEN"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Bearer YOUR_SCIM_TOKEN'
  }
};

// 請求內容 (payload)
const data = null;

axios.delete("https://api.maiagent.ai/api/v1/scim/550e8400-e29b-
41d4-a716-446655440000/Users/550e8400-e29b-41d4-a716-446655440000",
data, config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/scim/550e8400-e29b-41d4-a716-446655440000/Users/550e8400-e29b-41d4-a716-446655440000"
headers = {
    "Authorization": "Bearer YOUR_SCIM_TOKEN"
}


response = requests.delete(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>delete("https://api.maiagent.ai/api/v1/scim/550e8400-e29b-41d4-
a716-446655440000/Users/550e8400-e29b-41d4-a716-446655440000", [
        'headers' => [
            'Authorization' => 'Bearer YOUR_SCIM_TOKEN'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼	說明
204	No response body

列出群組（對應 MaiAgent 角色）

GET `/api/v1/scim/{orgUuid}/Groups`

參數

參數名稱	必填	類型	說明
`orgUuid`	V	string	

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/scim/550e8400-e29b-41d4-
a716-446655440000/Groups"

  -H "Authorization: Bearer YOUR_SCIM_TOKEN"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Bearer YOUR_SCIM_TOKEN'
  }
};

axios.get("https://api.maiagent.ai/api/v1/scim/550e8400-e29b-41d4-
a716-446655440000/Groups", config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/scim/550e8400-e29b-41d4-a716-446655440000/Groups"
headers = {
    "Authorization": "Bearer YOUR_SCIM_TOKEN"
}


response = requests.get(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/scim/550e8400-e29b-41d4-a716-
446655440000/Groups", [
        'headers' => [
            'Authorization' => 'Bearer YOUR_SCIM_TOKEN'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼	說明
200	No response body

建立群組

`POST` `/api/v1/scim/{orgUuid}/Groups`

參數

參數名稱	必填	類型	說明
`orgUuid`	V	string	

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X POST "https://api.maiagent.ai/api/v1/scim/550e8400-e29b-
41d4-a716-446655440000/Groups"

  -H "Authorization: Bearer YOUR_SCIM_TOKEN"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Bearer YOUR_SCIM_TOKEN'
  }
};

// 請求內容 (payload)
const data = null;

axios.post("https://api.maiagent.ai/api/v1/scim/550e8400-e29b-41d4-
a716-446655440000/Groups", data, config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/scim/550e8400-e29b-41d4-a716-446655440000/Groups"
headers = {
    "Authorization": "Bearer YOUR_SCIM_TOKEN"
}


response = requests.post(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>post("https://api.maiagent.ai/api/v1/scim/550e8400-e29b-41d4-a716-
446655440000/Groups", [
        'headers' => [
            'Authorization' => 'Bearer YOUR_SCIM_TOKEN'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼	說明
200	No response body

取得特定群組

`GET` `/api/v1/scim/{orgUuid}/Groups/{groupId}`

參數

參數名稱	必填	類型	說明
`groupId`	V	string	
`orgUuid`	V	string	

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/scim/550e8400-e29b-41d4-
a716-446655440000/Groups/550e8400-e29b-41d4-a716-446655440000"

  -H "Authorization: Bearer YOUR_SCIM_TOKEN"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Bearer YOUR_SCIM_TOKEN'
  }
};

axios.get("https://api.maiagent.ai/api/v1/scim/550e8400-e29b-41d4-
a716-446655440000/Groups/550e8400-e29b-41d4-a716-446655440000",
config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/scim/550e8400-e29b-41d4-a716-446655440000/Groups/550e8400-e29b-41d4-a716-446655440000"
headers = {
    "Authorization": "Bearer YOUR_SCIM_TOKEN"
}


response = requests.get(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/scim/550e8400-e29b-41d4-a716-
446655440000/Groups/550e8400-e29b-41d4-a716-446655440000", [
        'headers' => [
            'Authorization' => 'Bearer YOUR_SCIM_TOKEN'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼	說明
200	No response body

整筆取代群組

PUT `/api/v1/scim/{orgUuid}/Groups/{groupId}`

參數

參數名稱	必填	類型	說明
`groupId`	V	string	
`orgUuid`	V	string	

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X PUT "https://api.maiagent.ai/api/v1/scim/550e8400-e29b-41d4-
a716-446655440000/Groups/550e8400-e29b-41d4-a716-446655440000"

  -H "Authorization: Bearer YOUR_SCIM_TOKEN"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Bearer YOUR_SCIM_TOKEN'
  }
};

// 請求內容 (payload)
const data = null;

axios.put("https://api.maiagent.ai/api/v1/scim/550e8400-e29b-41d4-
a716-446655440000/Groups/550e8400-e29b-41d4-a716-446655440000",
data, config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/scim/550e8400-e29b-41d4-a716-446655440000/Groups/550e8400-e29b-41d4-a716-446655440000"
headers = {
    "Authorization": "Bearer YOUR_SCIM_TOKEN"
}


response = requests.put(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>put("https://api.maiagent.ai/api/v1/scim/550e8400-e29b-41d4-a716-
446655440000/Groups/550e8400-e29b-41d4-a716-446655440000", [
        'headers' => [
            'Authorization' => 'Bearer YOUR_SCIM_TOKEN'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼	說明
200	No response body

局部更新群組（改名、增減成員）

PATCH `/api/v1/scim/{orgUuid}/Groups/{groupId}`

參數

參數名稱	必填	類型	說明
`groupId`	V	string	
`orgUuid`	V	string	

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X PATCH "https://api.maiagent.ai/api/v1/scim/550e8400-e29b-
41d4-a716-446655440000/Groups/550e8400-e29b-41d4-a716-446655440000"

  -H "Authorization: Bearer YOUR_SCIM_TOKEN"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Bearer YOUR_SCIM_TOKEN'
  }
};

// 請求內容 (payload)
const data = null;

axios.patch("https://api.maiagent.ai/api/v1/scim/550e8400-e29b-41d4-
a716-446655440000/Groups/550e8400-e29b-41d4-a716-446655440000",
data, config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/scim/550e8400-e29b-41d4-a716-446655440000/Groups/550e8400-e29b-41d4-a716-446655440000"
headers = {
    "Authorization": "Bearer YOUR_SCIM_TOKEN"
}


response = requests.patch(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>patch("https://api.maiagent.ai/api/v1/scim/550e8400-e29b-41d4-a716-
446655440000/Groups/550e8400-e29b-41d4-a716-446655440000", [
        'headers' => [
            'Authorization' => 'Bearer YOUR_SCIM_TOKEN'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼	說明
200	No response body

刪除群組

`DELETE` `/api/v1/scim/{orgUuid}/Groups/{groupId}`

參數

參數名稱	必填	類型	說明
`groupId`	V	string	
`orgUuid`	V	string	

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X DELETE "https://api.maiagent.ai/api/v1/scim/550e8400-e29b-
41d4-a716-446655440000/Groups/550e8400-e29b-41d4-a716-446655440000"

  -H "Authorization: Bearer YOUR_SCIM_TOKEN"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Bearer YOUR_SCIM_TOKEN'
  }
};

// 請求內容 (payload)
const data = null;

axios.delete("https://api.maiagent.ai/api/v1/scim/550e8400-e29b-
41d4-a716-446655440000/Groups/550e8400-e29b-41d4-a716-446655440000",
data, config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/scim/550e8400-e29b-41d4-a716-446655440000/Groups/550e8400-e29b-41d4-a716-446655440000"
headers = {
    "Authorization": "Bearer YOUR_SCIM_TOKEN"
}


response = requests.delete(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>delete("https://api.maiagent.ai/api/v1/scim/550e8400-e29b-41d4-
a716-446655440000/Groups/550e8400-e29b-41d4-a716-446655440000", [
        'headers' => [
            'Authorization' => 'Bearer YOUR_SCIM_TOKEN'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼	說明
204	No response body

呼叫 API 示例 (Shell)

目錄

1. 建立 Web Chat
2. 列出 Web Chat
3. 取得特定 Web Chat
4. 更新 Web Chat
5. 部分更新 Web Chat
6. 設定聯絡人憑證
7. 取得語音助理 Token
8. 上傳批次 QA 檔案
9. 匯出批次 QA 為 Excel
10. 取得 LLM 使用統計
11. 取得 AI 助理統計數據

呼叫 API 示例 (Shell)

建立 Web Chat

`POST` `/api/v1/web-chats/`

請求內容

請求參數

欄位	類型	必填	說明
avatar	string (uri)	否	
logo	string (uri)	否	
description	string	否	
cover	string (uri)	否	
backUrl	string	否	
isActive	boolean	否	
theme	object	是	
theme.primaryColor	string	否	

欄位	類型	必填	說明
theme.navbarTextColor	string	否	
theme.conversationBackgroundColor	string	否	
theme.chatbotMessageTextColor	string	否	
theme.userMessageTextColor	string	否	
theme.chatbotMessageBackgroundColor	string	否	
theme.userMessageBackgroundColor	string	否	
theme.chatbotMessageBackgroundShadowEnabled	boolean	否	
theme.userMessageBackgroundShadowEnabled	boolean	否	
theme.chatbotMessageGradientEnabled	boolean	否	
theme.userMessageGradientEnabled	boolean	否	
darkTheme	object	是	
darkTheme.primaryColor	string	否	
darkTheme.navbarTextColor	string	否	
darkTheme.conversationBackgroundColor	string	否	
darkTheme.chatbotMessageTextColor	string	否	
darkTheme.userMessageTextColor	string	否	
darkTheme.chatbotMessageBackgroundColor	string	否	
darkTheme.userMessageBackgroundColor	string	否	
darkTheme.chatbotMessageBackgroundShadowEnabled	boolean	否	
darkTheme.userMessageBackgroundShadowEnabled	boolean	否	
darkTheme.chatbotMessageGradientEnabled	boolean	否	
darkTheme.userMessageGradientEnabled	boolean	否	
enableFileUpload	boolean	否	
enableDisplayCitations	boolean	否	
toolDisplayMode	string (enum: full, compact, hidden)	否	`full` : Full ; `compact` : Compact ; `hidden` : Hidden;
enableAskOptionButtons	boolean	否	開啟後 ask_user_question 選項以按鈕列浮在輸入框上方（輸入框保持可用）；關閉則維持現行覆蓋式面板。灰度開關，可隨時關閉回退。

欄位	類型	必填	說明
enableConversationHandoff	boolean	否	開啟後此對話平台的 webchat 顯示交接 UI（提示條、摘要卡、接續按鈕）並註冊交接工具；仍受系統設定的全域交接開關管制（全域關＝一律關）。MaiGPT 免此開關恆顯示。底部的上下文使用量百分比條另由「顯示上下文使用量」控制。預設關閉，客戶對外 webchat 不會看到任何交接 UI；灰度開關，關閉即回退、不需退版。
enableDisplayContextUsage	boolean	否	開啟後此對話平台的 webchat 在輸入框下方顯示上下文使用量百分比條。與對話交接互相獨立：不受交接開關（含全域交接開關）影響，也不影響交接提示條。MaiGPT 免此開關恆顯示。預設關閉；關閉即回退、不需退版。
enableDisplayThinking	boolean	否	
enableUserThinkingControl	boolean	否	
enableDisplayQueryMetadata	boolean	否	
enableDisplayHookMarkers	boolean	否	
hookMarkerTextInputModify	string	否	
hookMarkerTextOutputModify	string	否	
hookMarkerTextInputBlock	string	否	
hookMarkerTextOutputBlock	string	否	
enableShareConversation	boolean	否	
enableLocation	boolean	否	
enableShowPoweredBy	boolean	否	
poweredByLogo	string (uri)	否	
enableAnonymous	boolean	否	
enableDisplayPreviousConversation	boolean	否	
enableDisplayConversationHistory	boolean	否	
enableConversationTimer	boolean	否	
conversationTimerDuration	integer	否	計時器逾時時長，範圍 3-60 分鐘
enableAutoNewConversationOnTimeout	boolean	否	
enableSatisfactionSurvey	boolean	否	
satisfactionSurveyDelayMinutes	integer	否	最後一則 AI 回覆後幾分鐘彈出問卷，範圍 1-60 分鐘

欄位	類型	必填	說明
satisfactionSurveyPrompt	string	否	自訂問卷標題文字，留空則使用前端多語系預設文字
enableThemeModeToggle	boolean	否	
enableDisplayFontSizeSwitch	boolean	否	
defaultThemeMode	object	否	
enableDownloadCitations	boolean	否	
customDomain	object (含 3 個屬性: id, domain, status)	否	
customDomain.domain	string	是	
enableDisplayChatbotAvatar	boolean	否	
enableDisplayChatbotName	boolean	否	
buttonIcon	string (uri)	否	
conversationStartersDisplayCount	integer	否	
preChatFormEnabled	boolean	否	
preChatFormFields	object	否	
preChatFormTitle	object	否	
preChatFormSubtitle	object	否	
loadingDisplayMode	object	否	Waiting-experience style. `narrative` shows per-stage copy; `brand_animation` plays the uploaded asset and hides every system narration line. Defaults to `narrative`, which with no copy configured beh...
loadingStageCopyByLocale	object	否	Locale-keyed per-stage waiting copy, shaped {locale: {stage: text}} where stage is one of LoadingStage. An absent locale or stage falls back to the built-in copy, so a partially filled dict is valid a...
loadingLongWaitCopyByLocale	object	否	Locale-keyed line shown once the wait exceeds `loading_long_wait_threshold_seconds`, shaped {locale: text}. Written in the brand character voice for the animation mode, but applies to both modes. Empt...

欄位	類型	必填	說明
loadingLongWaitThresholdSeconds	integer	否	How long a single reply must be pending before the long-wait copy appears.
loadingAnimationUseSharedAsset	boolean	否	True (default) means every stage plays `loading_animation_shared_asset_url`, so the admin only uploads once. False expands per-stage assets, each falling back to the shared asset when its own slot is ...
loadingAnimationSharedAssetUrl	string (uri)	否	
loadingAnimationAssetUrlsByStage	object	否	Shaped {stage: url} keyed by LoadingStage. Only consulted when `loading_animation_use_shared_asset` is False; a missing stage falls back to the shared asset.
loadingTypingShowCopy	boolean	否	Only affects the first "typing" stage. True (default, the pre-existing behavior) shows the typing-stage copy next to the pre-first-char animation/dot; False plays only the animation with no text line....
toolCardRunningIconUrl	string (uri)	否	
toolCardCompletedIconUrl	string (uri)	否	

請求結構範例

```
{
  "avatar"?: string (uri) // 非必填
  "logo"?: string (uri) // 非必填
  "description"?: string // 非必填
  "cover"?: string (uri) // 非必填
  "backUrl"?: string // 非必填
  "isActive"?: boolean // 非必填
  "theme": {
  {
    "primaryColor"?: string // 非必填
    "navbarTextColor"?: string // 非必填
    "conversationBackgroundColor"?: string // 非必填
    "chatbotMessageTextColor"?: string // 非必填
    "userMessageTextColor"?: string // 非必填
    "chatbotMessageBackgroundColor"?: string // 非必填
    "userMessageBackgroundColor"?: string // 非必填
    "chatbotMessageBackgroundShadowEnabled"?: boolean // 非必填
    "userMessageBackgroundShadowEnabled"?: boolean // 非必填
    "chatbotMessageGradientEnabled"?: boolean // 非必填
    "userMessageGradientEnabled"?: boolean // 非必填
```

```
  }
  }
  "darkTheme": {
  {
    "primaryColor"?: string // 非必填
    "navbarTextColor"?: string // 非必填
    "conversationBackgroundColor"?: string // 非必填
    "chatbotMessageTextColor"?: string // 非必填
    "userMessageTextColor"?: string // 非必填
    "chatbotMessageBackgroundColor"?: string // 非必填
    "userMessageBackgroundColor"?: string // 非必填
    "chatbotMessageBackgroundShadowEnabled"?: boolean // 非必填
    "userMessageBackgroundShadowEnabled"?: boolean // 非必填
    "chatbotMessageGradientEnabled"?: boolean // 非必填
    "userMessageGradientEnabled"?: boolean // 非必填
  }
  }
  "enableFileUpload"?: boolean // 非必填
  "enableDisplayCitations"?: boolean // 非必填
  "toolDisplayMode"?: string (enum: full, compact, hidden) // * `full` - Full
* `compact` - Compact
* `hidden` - Hidden (非必填)
  "enableAskOptionButtons"?: boolean // 開啟後 ask_user_question 選項以按鈕列浮在輸入框上方（輸入框保持可用）；關閉則維持現行覆蓋式面板。灰度開關，可隨時關閉回退。 (非必填)
  "enableConversationHandoff"?: boolean // 開啟後此對話平台的 webchat 顯示交接 UI（提示條、摘要卡、接續按鈕）並註冊交接工具；仍受系統設定的全域交接開關管制（全域關＝一律關）。MaiGPT 免此開關恆顯示。底部的上下文使用量百分比條另由「顯示上下文使用量」控制。預設關閉，客戶對外 webchat 不會看到任何交接 UI；灰度開關，關閉即回退、不需退版。 (非必填)
  "enableDisplayContextUsage"?: boolean // 開啟後此對話平台的 webchat 在輸入框下方顯示上下文使用量百分比條。與對話交接互相獨立：不受交接開關（含全域交接開關）影響，也不影響交接提示條。MaiGPT 免此開關恆顯示。預設關閉；關閉即回退、不需退版。 (非必填)
  "enableDisplayThinking"?: boolean // 非必填
  "enableUserThinkingControl"?: boolean // 非必填
  "enableDisplayQueryMetadata"?: boolean // 非必填
  "enableDisplayHookMarkers"?: boolean // 非必填
  "hookMarkerTextInputModify"?: string // 非必填
  "hookMarkerTextOutputModify"?: string // 非必填
  "hookMarkerTextInputBlock"?: string // 非必填
  "hookMarkerTextOutputBlock"?: string // 非必填
  "enableShareConversation"?: boolean // 非必填
  "enableLocation"?: boolean // 非必填
  "enableShowPoweredBy"?: boolean // 非必填
  "poweredByLogo"?: string (uri) // 非必填
  "enableAnonymous"?: boolean // 非必填
  "enableDisplayPreviousConversation"?: boolean // 非必填
  "enableDisplayConversationHistory"?: boolean // 非必填
  "enableConversationTimer"?: boolean // 非必填
  "conversationTimerDuration"?: integer // 計時器逾時時長，範圍 3-60 分鐘 (非必填)
  "enableAutoNewConversationOnTimeout"?: boolean // 非必填
  "enableSatisfactionSurvey"?: boolean // 非必填
  "satisfactionSurveyDelayMinutes"?: integer // 最後一則 AI 回覆後幾分鐘彈出問卷，範圍 1-60 分鐘 (非必填)
  "satisfactionSurveyPrompt"?: string // 自訂問卷標題文字，留空則使用前端多語系預設文字 (非必填)
  "enableThemeModeToggle"?: boolean // 非必填
  "enableDisplayFontSizeSwitch"?: boolean // 非必填
  "defaultThemeMode"?:  // 非必填
```

```
  {
  }
  "enableDownloadCitations"?: boolean // 非必填
  "customDomain"?:  // 非必填
  {
    "domain": string
  }
  "enableDisplayChatbotAvatar"?: boolean // 非必填
  "enableDisplayChatbotName"?: boolean // 非必填
  "buttonIcon"?: string (uri) // 非必填
  "conversationStartersDisplayCount"?: integer // 非必填
  "preChatFormEnabled"?: boolean // 非必填
  "preChatFormFields"?: object // 非必填
  "preChatFormTitle"?: object // 非必填
  "preChatFormSubtitle"?: object // 非必填
  "loadingDisplayMode"?:  // Waiting-experience style. `narrative` shows per-stage copy;
`brand_animation` plays the uploaded asset and hides every system narration line. Defaults to
`narrative`, which with no copy configured behaves exactly as before this field existed.

* `narrative` - Narrative copy
* `brand_animation` - Brand animation (非必填)
  {
  }
  "loadingStageCopyByLocale"?: object // Locale-keyed per-stage waiting copy, shaped {locale:
{stage: text}} where stage is one of LoadingStage. An absent locale or stage falls back to
the built-in copy, so a partially filled dict is valid and never blocks a reply. (非必填)
  "loadingLongWaitCopyByLocale"?: object // Locale-keyed line shown once the wait exceeds
`loading_long_wait_threshold_seconds`, shaped {locale: text}. Written in the brand character
voice for the animation mode, but applies to both modes. Empty means no long-wait line is
shown. (非必填)
  "loadingLongWaitThresholdSeconds"?: integer // How long a single reply must be pending
before the long-wait copy appears. (非必填)
  "loadingAnimationUseSharedAsset"?: boolean // True (default) means every stage plays
`loading_animation_shared_asset_url`, so the admin only uploads once. False expands per-stage
assets, each falling back to the shared asset when its own slot is empty. (非必填)
  "loadingAnimationSharedAssetUrl"?: string (uri) // 非必填
  "loadingAnimationAssetUrlsByStage"?: object // Shaped {stage: url} keyed by LoadingStage.
Only consulted when `loading_animation_use_shared_asset` is False; a missing stage falls back
to the shared asset. (非必填)
  "loadingTypingShowCopy"?: boolean // Only affects the first "typing" stage. True (default,
the pre-existing behavior) shows the typing-stage copy next to the pre-first-char
animation/dot; False plays only the animation with no text line. Thinking / analyzing / long-
wait stages are unaffected. (非必填)
  "toolCardRunningIconUrl"?: string (uri) // 非必填
  "toolCardCompletedIconUrl"?: string (uri) // 非必填
}
```

請求範例值

```
{
  "avatar": "https://example.com/file.jpg",
  "logo": "https://example.com/file.jpg",
  "description": "範例字串",
  "cover": "https://example.com/file.jpg",
```

```
  "backUrl": "範例字串",
  "isActive": true,
  "theme": {
    "primaryColor": "範例字串",
    "navbarTextColor": "範例字串",
    "conversationBackgroundColor": "範例字串",
    "chatbotMessageTextColor": "範例字串",
    "userMessageTextColor": "範例字串",
    "chatbotMessageBackgroundColor": "範例字串",
    "userMessageBackgroundColor": "範例字串",
    "chatbotMessageBackgroundShadowEnabled": true,
    "userMessageBackgroundShadowEnabled": true,
    "chatbotMessageGradientEnabled": true,
    "userMessageGradientEnabled": true
  },
  "darkTheme": {
    "primaryColor": "範例字串",
    "navbarTextColor": "範例字串",
    "conversationBackgroundColor": "範例字串",
    "chatbotMessageTextColor": "範例字串",
    "userMessageTextColor": "範例字串",
    "chatbotMessageBackgroundColor": "範例字串",
    "userMessageBackgroundColor": "範例字串",
    "chatbotMessageBackgroundShadowEnabled": true,
    "userMessageBackgroundShadowEnabled": true,
    "chatbotMessageGradientEnabled": true,
    "userMessageGradientEnabled": true
  },
  "enableFileUpload": true,
  "enableDisplayCitations": true,
  "toolDisplayMode": "full",
  "enableAskOptionButtons": true,
  "enableConversationHandoff": true,
  "enableDisplayContextUsage": true,
  "enableDisplayThinking": true,
  "enableUserThinkingControl": true,
  "enableDisplayQueryMetadata": true,
  "enableDisplayHookMarkers": true,
  "hookMarkerTextInputModify": "範例字串",
  "hookMarkerTextOutputModify": "範例字串",
  "hookMarkerTextInputBlock": "範例字串",
  "hookMarkerTextOutputBlock": "範例字串",
  "enableShareConversation": true,
  "enableLocation": true,
  "enableShowPoweredBy": true,
  "poweredByLogo": "https://example.com/file.jpg",
  "enableAnonymous": true,
  "enableDisplayPreviousConversation": true,
  "enableDisplayConversationHistory": true,
  "enableConversationTimer": true,
  "conversationTimerDuration": 123,
  "enableAutoNewConversationOnTimeout": true,
  "enableSatisfactionSurvey": true,
  "satisfactionSurveyDelayMinutes": 123,
  "satisfactionSurveyPrompt": "範例字串",
  "enableThemeModeToggle": true,
```

```
  "enableDisplayFontSizeSwitch": true,
  "defaultThemeMode": {},
  "enableDownloadCitations": true,
  "customDomain": {
    "domain": "範例字串"
  },
  "enableDisplayChatbotAvatar": true,
  "enableDisplayChatbotName": true,
  "buttonIcon": "https://example.com/file.jpg",
  "conversationStartersDisplayCount": 123,
  "preChatFormEnabled": true,
  "preChatFormFields": null,
  "preChatFormTitle": null,
  "preChatFormSubtitle": null,
  "loadingDisplayMode": {},
  "loadingStageCopyByLocale": null,
  "loadingLongWaitCopyByLocale": null,
  "loadingLongWaitThresholdSeconds": 123,
  "loadingAnimationUseSharedAsset": true,
  "loadingAnimationSharedAssetUrl": "https://example.com/file.jpg",
  "loadingAnimationAssetUrlsByStage": null,
  "loadingTypingShowCopy": true,
  "toolCardRunningIconUrl": "https://example.com/file.jpg",
  "toolCardCompletedIconUrl": "https://example.com/file.jpg"
}
```


程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X POST "https://api.maiagent.ai/api/v1/web-chats/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "avatar": "https://example.com/file.jpg",
    "logo": "https://example.com/file.jpg",
    "description": "範例字串",
    "cover": "https://example.com/file.jpg",
    "backUrl": "範例字串",
    "isActive": true,
    "theme": {
      "primaryColor": "範例字串",
      "navbarTextColor": "範例字串",
      "conversationBackgroundColor": "範例字串",
      "chatbotMessageTextColor": "範例字串",
      "userMessageTextColor": "範例字串",
      "chatbotMessageBackgroundColor": "範例字串",
      "userMessageBackgroundColor": "範例字串",
      "chatbotMessageBackgroundShadowEnabled": true,
      "userMessageBackgroundShadowEnabled": true,
      "chatbotMessageGradientEnabled": true,
      "userMessageGradientEnabled": true
    },
    "darkTheme": {
      "primaryColor": "範例字串",
      "navbarTextColor": "範例字串",
      "conversationBackgroundColor": "範例字串",
      "chatbotMessageTextColor": "範例字串",
      "userMessageTextColor": "範例字串",
      "chatbotMessageBackgroundColor": "範例字串",
      "userMessageBackgroundColor": "範例字串",
      "chatbotMessageBackgroundShadowEnabled": true,
      "userMessageBackgroundShadowEnabled": true,
      "chatbotMessageGradientEnabled": true,
      "userMessageGradientEnabled": true
    },
    "enableFileUpload": true,
    "enableDisplayCitations": true,
    "toolDisplayMode": "full",
    "enableAskOptionButtons": true,
    "enableConversationHandoff": true,
    "enableDisplayContextUsage": true,
    "enableDisplayThinking": true,
    "enableUserThinkingControl": true,
    "enableDisplayQueryMetadata": true,
    "enableDisplayHookMarkers": true,
```

```
    "hookMarkerTextInputModify": "範例字串",
    "hookMarkerTextOutputModify": "範例字串",
    "hookMarkerTextInputBlock": "範例字串",
    "hookMarkerTextOutputBlock": "範例字串",
    "enableShareConversation": true,
    "enableLocation": true,
    "enableShowPoweredBy": true,
    "poweredByLogo": "https://example.com/file.jpg",
    "enableAnonymous": true,
    "enableDisplayPreviousConversation": true,
    "enableDisplayConversationHistory": true,
    "enableConversationTimer": true,
    "conversationTimerDuration": 123,
    "enableAutoNewConversationOnTimeout": true,
    "enableSatisfactionSurvey": true,
    "satisfactionSurveyDelayMinutes": 123,
    "satisfactionSurveyPrompt": "範例字串",
    "enableThemeModeToggle": true,
    "enableDisplayFontSizeSwitch": true,
    "defaultThemeMode": {},
    "enableDownloadCitations": true,
    "customDomain": {
      "domain": "範例字串"
    },
    "enableDisplayChatbotAvatar": true,
    "enableDisplayChatbotName": true,
    "buttonIcon": "https://example.com/file.jpg",
    "conversationStartersDisplayCount": 123,
    "preChatFormEnabled": true,
    "preChatFormFields": null,
    "preChatFormTitle": null,
    "preChatFormSubtitle": null,
    "loadingDisplayMode": {},
    "loadingStageCopyByLocale": null,
    "loadingLongWaitCopyByLocale": null,
    "loadingLongWaitThresholdSeconds": 123,
    "loadingAnimationUseSharedAsset": true,
    "loadingAnimationSharedAssetUrl": "https://example.com/file.jpg",
    "loadingAnimationAssetUrlsByStage": null,
    "loadingTypingShowCopy": true,
    "toolCardRunningIconUrl": "https://example.com/file.jpg",
    "toolCardCompletedIconUrl": "https://example.com/file.jpg"
  }'

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// 請求內容 (payload)
const data = {
    "avatar": "https://example.com/file.jpg",
    "logo": "https://example.com/file.jpg",
    "description": "範例字串",
    "cover": "https://example.com/file.jpg",
    "backUrl": "範例字串",
    "isActive": true,
    "theme": {
      "primaryColor": "範例字串",
      "navbarTextColor": "範例字串",
      "conversationBackgroundColor": "範例字串",
      "chatbotMessageTextColor": "範例字串",
      "userMessageTextColor": "範例字串",
      "chatbotMessageBackgroundColor": "範例字串",
      "userMessageBackgroundColor": "範例字串",
      "chatbotMessageBackgroundShadowEnabled": true,
      "userMessageBackgroundShadowEnabled": true,
      "chatbotMessageGradientEnabled": true,
      "userMessageGradientEnabled": true
    },
    "darkTheme": {
      "primaryColor": "範例字串",
      "navbarTextColor": "範例字串",
      "conversationBackgroundColor": "範例字串",
      "chatbotMessageTextColor": "範例字串",
      "userMessageTextColor": "範例字串",
      "chatbotMessageBackgroundColor": "範例字串",
      "userMessageBackgroundColor": "範例字串",
      "chatbotMessageBackgroundShadowEnabled": true,
      "userMessageBackgroundShadowEnabled": true,
      "chatbotMessageGradientEnabled": true,
      "userMessageGradientEnabled": true
    },
    "enableFileUpload": true,
    "enableDisplayCitations": true,
    "toolDisplayMode": "full",
    "enableAskOptionButtons": true,
    "enableConversationHandoff": true,
    "enableDisplayContextUsage": true,
```

```
      "enableDisplayThinking": true,
      "enableUserThinkingControl": true,
      "enableDisplayQueryMetadata": true,
      "enableDisplayHookMarkers": true,
      "hookMarkerTextInputModify": "範例字串",
      "hookMarkerTextOutputModify": "範例字串",
      "hookMarkerTextInputBlock": "範例字串",
      "hookMarkerTextOutputBlock": "範例字串",
      "enableShareConversation": true,
      "enableLocation": true,
      "enableShowPoweredBy": true,
      "poweredByLogo": "https://example.com/file.jpg",
      "enableAnonymous": true,
      "enableDisplayPreviousConversation": true,
      "enableDisplayConversationHistory": true,
      "enableConversationTimer": true,
      "conversationTimerDuration": 123,
      "enableAutoNewConversationOnTimeout": true,
      "enableSatisfactionSurvey": true,
      "satisfactionSurveyDelayMinutes": 123,
      "satisfactionSurveyPrompt": "範例字串",
      "enableThemeModeToggle": true,
      "enableDisplayFontSizeSwitch": true,
      "defaultThemeMode": {},
      "enableDownloadCitations": true,
      "customDomain": {
        "domain": "範例字串"
      },
      "enableDisplayChatbotAvatar": true,
      "enableDisplayChatbotName": true,
      "buttonIcon": "https://example.com/file.jpg",
      "conversationStartersDisplayCount": 123,
      "preChatFormEnabled": true,
      "preChatFormFields": null,
      "preChatFormTitle": null,
      "preChatFormSubtitle": null,
      "loadingDisplayMode": {},
      "loadingStageCopyByLocale": null,
      "loadingLongWaitCopyByLocale": null,
      "loadingLongWaitThresholdSeconds": 123,
      "loadingAnimationUseSharedAsset": true,
      "loadingAnimationSharedAssetUrl": "https://example.com/file.jpg",
      "loadingAnimationAssetUrlsByStage": null,
      "loadingTypingShowCopy": true,
      "toolCardRunningIconUrl": "https://example.com/file.jpg",
      "toolCardCompletedIconUrl": "https://example.com/file.jpg"
    };

  axios.post("https://api.maiagent.ai/api/v1/web-chats/", data, config)
    .then(response => {
      console.log('成功取得回應:');
      console.log(response.data);
    })
    .catch(error => {
      console.error('請求發生錯誤:');
```

```
    console.error(error.response?.data || error.message);
});
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/web-chats/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# 請求內容 (payload)
data = {
    "avatar": "https://example.com/file.jpg",
    "logo": "https://example.com/file.jpg",
    "description": "範例字串",
    "cover": "https://example.com/file.jpg",
    "backUrl": "範例字串",
    "isActive": True,
    "theme": {
        "primaryColor": "範例字串",
        "navbarTextColor": "範例字串",
        "conversationBackgroundColor": "範例字串",
        "chatbotMessageTextColor": "範例字串",
        "userMessageTextColor": "範例字串",
        "chatbotMessageBackgroundColor": "範例字串",
        "userMessageBackgroundColor": "範例字串",
        "chatbotMessageBackgroundShadowEnabled": True,
        "userMessageBackgroundShadowEnabled": True,
        "chatbotMessageGradientEnabled": True,
        "userMessageGradientEnabled": True
    },
    "darkTheme": {
        "primaryColor": "範例字串",
        "navbarTextColor": "範例字串",
        "conversationBackgroundColor": "範例字串",
        "chatbotMessageTextColor": "範例字串",
        "userMessageTextColor": "範例字串",
        "chatbotMessageBackgroundColor": "範例字串",
        "userMessageBackgroundColor": "範例字串",
        "chatbotMessageBackgroundShadowEnabled": True,
        "userMessageBackgroundShadowEnabled": True,
        "chatbotMessageGradientEnabled": True,
        "userMessageGradientEnabled": True
    },
    "enableFileUpload": True,
    "enableDisplayCitations": True,
    "toolDisplayMode": "full",
    "enableAskOptionButtons": True,
    "enableConversationHandoff": True,
    "enableDisplayContextUsage": True,
    "enableDisplayThinking": True,
    "enableUserThinkingControl": True,
```

```
    "enableDisplayQueryMetadata": True,
    "enableDisplayHookMarkers": True,
    "hookMarkerTextInputModify": "範例字串",
    "hookMarkerTextOutputModify": "範例字串",
    "hookMarkerTextInputBlock": "範例字串",
    "hookMarkerTextOutputBlock": "範例字串",
    "enableShareConversation": True,
    "enableLocation": True,
    "enableShowPoweredBy": True,
    "poweredByLogo": "https://example.com/file.jpg",
    "enableAnonymous": True,
    "enableDisplayPreviousConversation": True,
    "enableDisplayConversationHistory": True,
    "enableConversationTimer": True,
    "conversationTimerDuration": 123,
    "enableAutoNewConversationOnTimeout": True,
    "enableSatisfactionSurvey": True,
    "satisfactionSurveyDelayMinutes": 123,
    "satisfactionSurveyPrompt": "範例字串",
    "enableThemeModeToggle": True,
    "enableDisplayFontSizeSwitch": True,
    "defaultThemeMode": {},
    "enableDownloadCitations": True,
    "customDomain": {
        "domain": "範例字串"
    },
    "enableDisplayChatbotAvatar": True,
    "enableDisplayChatbotName": True,
    "buttonIcon": "https://example.com/file.jpg",
    "conversationStartersDisplayCount": 123,
    "preChatFormEnabled": True,
    "preChatFormFields": None,
    "preChatFormTitle": None,
    "preChatFormSubtitle": None,
    "loadingDisplayMode": {},
    "loadingStageCopyByLocale": None,
    "loadingLongWaitCopyByLocale": None,
    "loadingLongWaitThresholdSeconds": 123,
    "loadingAnimationUseSharedAsset": True,
    "loadingAnimationSharedAssetUrl": "https://example.com/file.jpg",
    "loadingAnimationAssetUrlsByStage": None,
    "loadingTypingShowCopy": True,
    "toolCardRunningIconUrl": "https://example.com/file.jpg",
    "toolCardCompletedIconUrl": "https://example.com/file.jpg"
}

response = requests.post(url, json=data, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->post("https://api.maiagent.ai/api/v1/web-chats/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'avatar' => 'https://example.com/file.jpg',
            'logo' => 'https://example.com/file.jpg',
            'description' => '範例字串',
            'cover' => 'https://example.com/file.jpg',
            'backUrl' => '範例字串',
            'isActive' => true,
            'theme' => [
                'primaryColor' => '範例字串',
                'navbarTextColor' => '範例字串',
                'conversationBackgroundColor' => '範例字串',
                'chatbotMessageTextColor' => '範例字串',
                'userMessageTextColor' => '範例字串',
                'chatbotMessageBackgroundColor' => '範例字串',
                'userMessageBackgroundColor' => '範例字串',
                'chatbotMessageBackgroundShadowEnabled' => true,
                'userMessageBackgroundShadowEnabled' => true,
                'chatbotMessageGradientEnabled' => true,
                'userMessageGradientEnabled' => true
            ],
            'darkTheme' => [
                'primaryColor' => '範例字串',
                'navbarTextColor' => '範例字串',
                'conversationBackgroundColor' => '範例字串',
                'chatbotMessageTextColor' => '範例字串',
                'userMessageTextColor' => '範例字串',
                'chatbotMessageBackgroundColor' => '範例字串',
                'userMessageBackgroundColor' => '範例字串',
                'chatbotMessageBackgroundShadowEnabled' => true,
                'userMessageBackgroundShadowEnabled' => true,
                'chatbotMessageGradientEnabled' => true,
                'userMessageGradientEnabled' => true
            ],
            'enableFileUpload' => true,
            'enableDisplayCitations' => true,
            'toolDisplayMode' => 'full',
            'enableAskOptionButtons' => true,
            'enableConversationHandoff' => true,
            'enableDisplayContextUsage' => true,
```

```
                'enableDisplayThinking' => true,
                'enableUserThinkingControl' => true,
                'enableDisplayQueryMetadata' => true,
                'enableDisplayHookMarkers' => true,
                'hookMarkerTextInputModify' => '範例字串',
                'hookMarkerTextOutputModify' => '範例字串',
                'hookMarkerTextInputBlock' => '範例字串',
                'hookMarkerTextOutputBlock' => '範例字串',
                'enableShareConversation' => true,
                'enableLocation' => true,
                'enableShowPoweredBy' => true,
                'poweredByLogo' => 'https://example.com/file.jpg',
                'enableAnonymous' => true,
                'enableDisplayPreviousConversation' => true,
                'enableDisplayConversationHistory' => true,
                'enableConversationTimer' => true,
                'conversationTimerDuration' => 123,
                'enableAutoNewConversationOnTimeout' => true,
                'enableSatisfactionSurvey' => true,
                'satisfactionSurveyDelayMinutes' => 123,
                'satisfactionSurveyPrompt' => '範例字串',
                'enableThemeModeToggle' => true,
                'enableDisplayFontSizeSwitch' => true,
                'defaultThemeMode' => new \stdClass(),
                'enableDownloadCitations' => true,
                'customDomain' => [
                    'domain' => '範例字串'
                ],
                'enableDisplayChatbotAvatar' => true,
                'enableDisplayChatbotName' => true,
                'buttonIcon' => 'https://example.com/file.jpg',
                'conversationStartersDisplayCount' => 123,
                'preChatFormEnabled' => true,
                'preChatFormFields' => null,
                'preChatFormTitle' => null,
                'preChatFormSubtitle' => null,
                'loadingDisplayMode' => new \stdClass(),
                'loadingStageCopyByLocale' => null,
                'loadingLongWaitCopyByLocale' => null,
                'loadingLongWaitThresholdSeconds' => 123,
                'loadingAnimationUseSharedAsset' => true,
                'loadingAnimationSharedAssetUrl' => 'https://example.com/file.jpg',
                'loadingAnimationAssetUrlsByStage' => null,
                'loadingTypingShowCopy' => true,
                'toolCardRunningIconUrl' => 'https://example.com/file.jpg',
                'toolCardCompletedIconUrl' => 'https://example.com/file.jpg'
            ]
        ]);

        $data = json_decode($response->getBody(), true);
        echo "成功取得回應:\n";
        print_r($data);
    } catch (Exception $e) {
        echo '請求發生錯誤: ' . $e->getMessage();
```

```
}
?>
```

回應內容

狀態碼: 201

回應結構範例

```
{
  "id": string (uuid)
  "name": string
  "avatar"?: string (uri) // 非必填
  "logo"?: string (uri) // 非必填
  "description"?: string // 非必填
  "cover"?: string (uri) // 非必填
  "backUrl"?: string // 非必填
  "isActive"?: boolean // 非必填
  "enableSpeech": boolean
  "displayConversationStarters": [
    string
  ]
  "theme": {
  {
    "primaryColor"?: string // 非必填
    "navbarTextColor"?: string // 非必填
    "conversationBackgroundColor"?: string // 非必填
    "chatbotMessageTextColor"?: string // 非必填
    "userMessageTextColor"?: string // 非必填
    "chatbotMessageBackgroundColor"?: string // 非必填
    "userMessageBackgroundColor"?: string // 非必填
    "chatbotMessageBackgroundShadowEnabled"?: boolean // 非必填
    "userMessageBackgroundShadowEnabled"?: boolean // 非必填
    "chatbotMessageGradientEnabled"?: boolean // 非必填
    "userMessageGradientEnabled"?: boolean // 非必填
  }
  }
  "darkTheme": {
  {
    "primaryColor"?: string // 非必填
    "navbarTextColor"?: string // 非必填
    "conversationBackgroundColor"?: string // 非必填
    "chatbotMessageTextColor"?: string // 非必填
    "userMessageTextColor"?: string // 非必填
    "chatbotMessageBackgroundColor"?: string // 非必填
    "userMessageBackgroundColor"?: string // 非必填
    "chatbotMessageBackgroundShadowEnabled"?: boolean // 非必填
```

```
    "userMessageBackgroundShadowEnabled"?: boolean // 非必填
    "chatbotMessageGradientEnabled"?: boolean // 非必填
    "userMessageGradientEnabled"?: boolean // 非必填
  }
  }
  "enableFileUpload"?: boolean // 非必填
  "enableDisplayCitations"?: boolean // 非必填
  "toolDisplayMode"?: string (enum: full, compact, hidden) // * `full` - Full
* `compact` - Compact
* `hidden` - Hidden (非必填)
  "enableAskOptionButtons"?: boolean // 開啟後 ask_user_question 選項以按鈕列浮在輸入框上方（輸入框保持可用）；關閉則維持現行覆蓋式面板。灰度開關，可隨時關閉回退。 (非必填)
  "enableConversationHandoff"?: boolean // 開啟後此對話平台的 webchat 顯示交接 UI（提示條、摘要卡、接續按鈕）並註冊交接工具；仍受系統設定的全域交接開關管制（全域關＝一律關）。MaiGPT 免此開關恆顯示。底部的上下文使用量百分比條另由「顯示上下文使用量」控制。預設關閉，客戶對外 webchat 不會看到任何交接 UI；灰度開關，關閉即回退、不需退版。 (非必填)
  "enableDisplayContextUsage"?: boolean // 開啟後此對話平台的 webchat 在輸入框下方顯示上下文使用量百分比條。與對話交接互相獨立：不受交接開關（含全域交接開關）影響，也不影響交接提示條。MaiGPT 免此開關恆顯示。預設關閉；關閉即回退、不需退版。 (非必填)
  "enableDisplayThinking"?: boolean // 非必填
  "enableUserThinkingControl"?: boolean // 非必填
  "enableDisplayQueryMetadata"?: boolean // 非必填
  "enableDisplayHookMarkers"?: boolean // 非必填
  "hookMarkerTextInputModify"?: string // 非必填
  "hookMarkerTextOutputModify"?: string // 非必填
  "hookMarkerTextInputBlock"?: string // 非必填
  "hookMarkerTextOutputBlock"?: string // 非必填
  "enableShareConversation"?: boolean // 非必填
  "enableLocation"?: boolean // 非必填
  "enableShowPoweredBy"?: boolean // 非必填
  "poweredByLogo"?: string (uri) // 非必填
  "enableAnonymous"?: boolean // 非必填
  "enableDisplayPreviousConversation"?: boolean // 非必填
  "enableDisplayConversationHistory"?: boolean // 非必填
  "enableConversationTimer"?: boolean // 非必填
  "conversationTimerDuration"?: integer // 計時器逾時時長，範圍 3-60 分鐘 (非必填)
  "enableAutoNewConversationOnTimeout"?: boolean // 非必填
  "enableSatisfactionSurvey"?: boolean // 非必填
  "satisfactionSurveyDelayMinutes"?: integer // 最後一則 AI 回覆後幾分鐘彈出問卷，範圍 1-60 分鐘 (非必填)
  "satisfactionSurveyPrompt"?: string // 自訂問卷標題文字，留空則使用前端多語系預設文字 (非必填)
  "accessType":
  {
  }
  "enableThemeModeToggle"?: boolean // 非必填
  "enableDisplayFontSizeSwitch"?: boolean // 非必填
  "defaultThemeMode"?:  // 非必填
  {
  }
  "enableDownloadCitations"?: boolean // 非必填
  "customDomain"?:  // 非必填
  {
    "id": string (uuid)
    "domain": string
    "status":
    {
```

```
    }
  }
  "enableDisplayChatbotAvatar"?: boolean // 非必填
  "enableDisplayChatbotName"?: boolean // 非必填
  "buttonIcon"?: string (uri) // 非必填
  "enableCodeInterpreter": boolean // Read enable_code_interpreter from the inbox's chatbot.
  "voiceAgentEnabled": boolean // Whether the bound chatbot has the voice agent turned on
(read-only)
  "conversationStartersDisplayCount"?: integer // 非必填
  "includeGreetingInContext": boolean // When enabled, the conversation greeting and the
numbered conversation starters (in configured order, unshuffled and untruncated) are injected
into the LLM context so the agent can resolve short replies like "1" to the matching starter
option.
  "tools": [ // Expose chatbot tools to SDK for the tool_mask selector.

Name resolution prefers ``display_name`` (set on MCP tools, where
``name`` is null) and falls back to ``name`` for API tools where
``display_name`` is null. Tools missing both are skipped — SDK
should never show an unnamed tool to a contact. Quick Menu tools are
static input-bar UI, never an LLM tool, so masking one is meaningless.
    object
  ]
  "preChatFormEnabled"?: boolean // 非必填
  "preChatFormFields"?: object // 非必填
  "preChatFormTitle"?: object // 非必填
  "preChatFormSubtitle"?: object // 非必填
  "loadingDisplayMode"?:  // Waiting-experience style. `narrative` shows per-stage copy;
`brand_animation` plays the uploaded asset and hides every system narration line. Defaults to
`narrative`, which with no copy configured behaves exactly as before this field existed.

* `narrative` - Narrative copy
* `brand_animation` - Brand animation (非必填)
  {
  }
  "loadingStageCopyByLocale"?: object // Locale-keyed per-stage waiting copy, shaped {locale:
{stage: text}} where stage is one of LoadingStage. An absent locale or stage falls back to
the built-in copy, so a partially filled dict is valid and never blocks a reply. (非必填)
  "loadingLongWaitCopyByLocale"?: object // Locale-keyed line shown once the wait exceeds
`loading_long_wait_threshold_seconds`, shaped {locale: text}. Written in the brand character
voice for the animation mode, but applies to both modes. Empty means no long-wait line is
shown. (非必填)
  "loadingLongWaitThresholdSeconds"?: integer // How long a single reply must be pending
before the long-wait copy appears. (非必填)
  "loadingAnimationUseSharedAsset"?: boolean // True (default) means every stage plays
`loading_animation_shared_asset_url`, so the admin only uploads once. False expands per-stage
assets, each falling back to the shared asset when its own slot is empty. (非必填)
  "loadingAnimationSharedAssetUrl"?: string (uri) // 非必填
  "loadingAnimationAssetUrlsByStage"?: object // Shaped {stage: url} keyed by LoadingStage.
Only consulted when `loading_animation_use_shared_asset` is False; a missing stage falls back
to the shared asset. (非必填)
  "loadingTypingShowCopy"?: boolean // Only affects the first "typing" stage. True (default,
the pre-existing behavior) shows the typing-stage copy next to the pre-first-char
animation/dot; False plays only the animation with no text line. Thinking / analyzing / long-
wait stages are unaffected. (非必填)
  "toolCardRunningIconUrl"?: string (uri) // 非必填
  "toolCardCompletedIconUrl"?: string (uri) // 非必填
```

```
  "inbox": object
  "quickMenu": object // Mounted Quick Menu Agent UI config for the web chat input bar; null
when absent (read-only)
}
```

回應範例值


```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "name": "回應字串",
  "avatar": "https://example.com/file.jpg",
  "logo": "https://example.com/file.jpg",
  "description": "回應字串",
  "cover": "https://example.com/file.jpg",
  "backUrl": "回應字串",
  "isActive": false,
  "enableSpeech": false,
  "displayConversationStarters": [
    "回應字串"
  ],
  "theme": {
    "primaryColor": "回應字串",
    "navbarTextColor": "回應字串",
    "conversationBackgroundColor": "回應字串",
    "chatbotMessageTextColor": "回應字串",
    "userMessageTextColor": "回應字串",
    "chatbotMessageBackgroundColor": "回應字串",
    "userMessageBackgroundColor": "回應字串",
    "chatbotMessageBackgroundShadowEnabled": false,
    "userMessageBackgroundShadowEnabled": false,
    "chatbotMessageGradientEnabled": false,
    "userMessageGradientEnabled": false
  },
  "darkTheme": {
    "primaryColor": "回應字串",
    "navbarTextColor": "回應字串",
    "conversationBackgroundColor": "回應字串",
    "chatbotMessageTextColor": "回應字串",
    "userMessageTextColor": "回應字串",
    "chatbotMessageBackgroundColor": "回應字串",
    "userMessageBackgroundColor": "回應字串",
    "chatbotMessageBackgroundShadowEnabled": false,
    "userMessageBackgroundShadowEnabled": false,
    "chatbotMessageGradientEnabled": false,
    "userMessageGradientEnabled": false
  },
  "enableFileUpload": false,
  "enableDisplayCitations": false,
  "toolDisplayMode": "full",
  "enableAskOptionButtons": false,
  "enableConversationHandoff": false,
  "enableDisplayContextUsage": false,
  "enableDisplayThinking": false,
  "enableUserThinkingControl": false,
```

```
  "enableDisplayQueryMetadata": false,
  "enableDisplayHookMarkers": false,
  "hookMarkerTextInputModify": "回應字串",
  "hookMarkerTextOutputModify": "回應字串",
  "hookMarkerTextInputBlock": "回應字串",
  "hookMarkerTextOutputBlock": "回應字串",
  "enableShareConversation": false,
  "enableLocation": false,
  "enableShowPoweredBy": false,
  "poweredByLogo": "https://example.com/file.jpg",
  "enableAnonymous": false,
  "enableDisplayPreviousConversation": false,
  "enableDisplayConversationHistory": false,
  "enableConversationTimer": false,
  "conversationTimerDuration": 456,
  "enableAutoNewConversationOnTimeout": false,
  "enableSatisfactionSurvey": false,
  "satisfactionSurveyDelayMinutes": 456,
  "satisfactionSurveyPrompt": "回應字串",
  "accessType": {},
  "enableThemeModeToggle": false,
  "enableDisplayFontSizeSwitch": false,
  "defaultThemeMode": {},
  "enableDownloadCitations": false,
  "customDomain": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "domain": "回應字串",
    "status": {}
  },
  "enableDisplayChatbotAvatar": false,
  "enableDisplayChatbotName": false,
  "buttonIcon": "https://example.com/file.jpg",
  "enableCodeInterpreter": false,
  "voiceAgentEnabled": false,
  "conversationStartersDisplayCount": 456,
  "includeGreetingInContext": false,
  "tools": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "回應範例名稱",
      "description": "回應範例描述"
    }
  ],
  "preChatFormEnabled": false,
  "preChatFormFields": null,
  "preChatFormTitle": null,
  "preChatFormSubtitle": null,
  "loadingDisplayMode": {},
  "loadingStageCopyByLocale": null,
  "loadingLongWaitCopyByLocale": null,
  "loadingLongWaitThresholdSeconds": 456,
  "loadingAnimationUseSharedAsset": false,
  "loadingAnimationSharedAssetUrl": "https://example.com/file.jpg",
  "loadingAnimationAssetUrlsByStage": null,
  "loadingTypingShowCopy": false,
  "toolCardRunningIconUrl": "https://example.com/file.jpg",
```

```
  "toolCardCompletedIconUrl": "https://example.com/file.jpg",
  "inbox": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應範例名稱",
    "description": "回應範例描述"
  },
  "quickMenu": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應範例名稱",
    "description": "回應範例描述"
  }
}
```


列出 Web Chat

GET `/api/v1/web-chats/`

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/web-chats/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/web-chats/", config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/web-chats/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->get("https://api.maiagent.ai/api/v1/web-chats/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
[
  {
    "id": string (uuid)
    "avatar"?: string (uri) // 非必填
    "name": string
  }
]
```

回應範例值

```
[
  {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "avatar": "https://example.com/file.jpg",
```

```
    "name": "回應字串"
  }
]
```

取得特定 Web Chat

GET `/api/v1/web-chats/{id}`

參數

參數名稱	必填	類型	說明
id	V	string	A UUID string identifying this web chat.

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/web-chats/550e8400-e29b-41d4-a716-
446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/web-chats/550e8400-e29b-41d4-a716-
446655440000/", config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/web-chats/550e8400-e29b-41d4-a716-446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->get("https://api.maiagent.ai/api/v1/web-chats/550e8400-e29b-
41d4-a716-446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
{
  "id": string (uuid)
  "name": string
  "avatar"?: string (uri) // 非必填
  "logo"?: string (uri) // 非必填
  "description"?: string // 非必填
  "cover"?: string (uri) // 非必填
  "backUrl"?: string // 非必填
  "isActive"?: boolean // 非必填
  "enableSpeech": boolean
  "displayConversationStarters": [
    string
  ]
  "theme": {
  {
```

```
    "primaryColor"?: string // 非必填
    "navbarTextColor"?: string // 非必填
    "conversationBackgroundColor"?: string // 非必填
    "chatbotMessageTextColor"?: string // 非必填
    "userMessageTextColor"?: string // 非必填
    "chatbotMessageBackgroundColor"?: string // 非必填
    "userMessageBackgroundColor"?: string // 非必填
    "chatbotMessageBackgroundShadowEnabled"?: boolean // 非必填
    "userMessageBackgroundShadowEnabled"?: boolean // 非必填
    "chatbotMessageGradientEnabled"?: boolean // 非必填
    "userMessageGradientEnabled"?: boolean // 非必填
  }
  }
  "darkTheme": {
  {
    "primaryColor"?: string // 非必填
    "navbarTextColor"?: string // 非必填
    "conversationBackgroundColor"?: string // 非必填
    "chatbotMessageTextColor"?: string // 非必填
    "userMessageTextColor"?: string // 非必填
    "chatbotMessageBackgroundColor"?: string // 非必填
    "userMessageBackgroundColor"?: string // 非必填
    "chatbotMessageBackgroundShadowEnabled"?: boolean // 非必填
    "userMessageBackgroundShadowEnabled"?: boolean // 非必填
    "chatbotMessageGradientEnabled"?: boolean // 非必填
    "userMessageGradientEnabled"?: boolean // 非必填
  }
  }
  "enableFileUpload"?: boolean // 非必填
  "enableDisplayCitations"?: boolean // 非必填
  "toolDisplayMode"?: string (enum: full, compact, hidden) // * `full` - Full
* `compact` - Compact
* `hidden` - Hidden (非必填)
  "enableAskOptionButtons"?: boolean // 開啟後 ask_user_question 選項以按鈕列浮在輸入框上方（輸入框保持可用）；關閉則維持現行覆蓋式面板。灰度開關，可隨時關閉回退。 (非必填)
  "enableConversationHandoff"?: boolean // 開啟後此對話平台的 webchat 顯示交接 UI（提示條、摘要卡、接續按鈕）並註冊交接工具；仍受系統設定的全域交接開關管制（全域關＝一律關）。MaiGPT 免此開關恆顯示。底部的上下文使用量百分比條另由「顯示上下文使用量」控制。預設關閉，客戶對外 webchat 不會看到任何交接 UI；灰度開關，關閉即回退、不需退版。 (非必填)
  "enableDisplayContextUsage"?: boolean // 開啟後此對話平台的 webchat 在輸入框下方顯示上下文使用量百分比條。與對話交接互相獨立：不受交接開關（含全域交接開關）影響，也不影響交接提示條。MaiGPT 免此開關恆顯示。預設關閉；關閉即回退、不需退版。 (非必填)
  "enableDisplayThinking"?: boolean // 非必填
  "enableUserThinkingControl"?: boolean // 非必填
  "enableDisplayQueryMetadata"?: boolean // 非必填
  "enableDisplayHookMarkers"?: boolean // 非必填
  "hookMarkerTextInputModify"?: string // 非必填
  "hookMarkerTextOutputModify"?: string // 非必填
  "hookMarkerTextInputBlock"?: string // 非必填
  "hookMarkerTextOutputBlock"?: string // 非必填
  "enableShareConversation"?: boolean // 非必填
  "enableLocation"?: boolean // 非必填
  "enableShowPoweredBy"?: boolean // 非必填
  "poweredByLogo"?: string (uri) // 非必填
  "enableAnonymous"?: boolean // 非必填
  "enableDisplayPreviousConversation"?: boolean // 非必填
```

```
  "enableDisplayConversationHistory"?: boolean // 非必填
  "enableConversationTimer"?: boolean // 非必填
  "conversationTimerDuration"?: integer // 計時器逾時時長，範圍 3-60 分鐘 (非必填)
  "enableAutoNewConversationOnTimeout"?: boolean // 非必填
  "enableSatisfactionSurvey"?: boolean // 非必填
  "satisfactionSurveyDelayMinutes"?: integer // 最後一則 AI 回覆後幾分鐘彈出問卷，範圍 1-60 分鐘 (非必填)
  "satisfactionSurveyPrompt"?: string // 自訂問卷標題文字，留空則使用前端多語系預設文字 (非必填)
  "accessType":
  {
  }
  "enableThemeModeToggle"?: boolean // 非必填
  "enableDisplayFontSizeSwitch"?: boolean // 非必填
  "defaultThemeMode"?:  // 非必填
  {
  }
  "enableDownloadCitations"?: boolean // 非必填
  "customDomain"?:  // 非必填
  {
    "id": string (uuid)
    "domain": string
    "status":
    {
    }
  }
  "enableDisplayChatbotAvatar"?: boolean // 非必填
  "enableDisplayChatbotName"?: boolean // 非必填
  "buttonIcon"?: string (uri) // 非必填
  "enableCodeInterpreter": boolean // Read enable_code_interpreter from the inbox's chatbot.
  "voiceAgentEnabled": boolean // Whether the bound chatbot has the voice agent turned on (read-only)
  "conversationStartersDisplayCount"?: integer // 非必填
  "includeGreetingInContext": boolean // When enabled, the conversation greeting and the numbered conversation starters (in configured order, unshuffled and untruncated) are injected into the LLM context so the agent can resolve short replies like "1" to the matching starter option.
  "tools": [ // Expose chatbot tools to SDK for the tool_mask selector.

Name resolution prefers ``display_name`` (set on MCP tools, where
``name`` is null) and falls back to ``name`` for API tools where
``display_name`` is null. Tools missing both are skipped — SDK
should never show an unnamed tool to a contact. Quick Menu tools are
static input-bar UI, never an LLM tool, so masking one is meaningless.
    object
  ]
  "preChatFormEnabled"?: boolean // 非必填
  "preChatFormFields"?: object // 非必填
  "preChatFormTitle"?: object // 非必填
  "preChatFormSubtitle"?: object // 非必填
  "loadingDisplayMode"?:  // Waiting-experience style. `narrative` shows per-stage copy; `brand_animation` plays the uploaded asset and hides every system narration line. Defaults to `narrative`, which with no copy configured behaves exactly as before this field existed.

* `narrative` - Narrative copy
* `brand_animation` - Brand animation (非必填)
  {
```

```
  }
  "loadingStageCopyByLocale"?: object // Locale-keyed per-stage waiting copy, shaped {locale: {stage: text}} where stage is one of LoadingStage. An absent locale or stage falls back to the built-in copy, so a partially filled dict is valid and never blocks a reply. (非必填)
  "loadingLongWaitCopyByLocale"?: object // Locale-keyed line shown once the wait exceeds `loading_long_wait_threshold_seconds`, shaped {locale: text}. Written in the brand character voice for the animation mode, but applies to both modes. Empty means no long-wait line is shown. (非必填)
  "loadingLongWaitThresholdSeconds"?: integer // How long a single reply must be pending before the long-wait copy appears. (非必填)
  "loadingAnimationUseSharedAsset"?: boolean // True (default) means every stage plays `loading_animation_shared_asset_url`, so the admin only uploads once. False expands per-stage assets, each falling back to the shared asset when its own slot is empty. (非必填)
  "loadingAnimationSharedAssetUrl"?: string (uri) // 非必填
  "loadingAnimationAssetUrlsByStage"?: object // Shaped {stage: url} keyed by LoadingStage. Only consulted when `loading_animation_use_shared_asset` is False; a missing stage falls back to the shared asset. (非必填)
  "loadingTypingShowCopy"?: boolean // Only affects the first "typing" stage. True (default, the pre-existing behavior) shows the typing-stage copy next to the pre-first-char animation/dot; False plays only the animation with no text line. Thinking / analyzing / long-wait stages are unaffected. (非必填)
  "toolCardRunningIconUrl"?: string (uri) // 非必填
  "toolCardCompletedIconUrl"?: string (uri) // 非必填
  "inbox": object
  "quickMenu": object // Mounted Quick Menu Agent UI config for the web chat input bar; null when absent (read-only)
}
```

回應範例值


```
{
  "id": "123e4567-e89b-12d3-a456-426614174000",
  "name": "測試 doc",
  "avatar": "https://example.com/static/images/default-chatbot-avatar.png",
  "logo": null,
  "description": "",
  "cover": null,
  "backUrl": "",
  "isActive": true,
  "enableSpeech": false,
  "displayGreeting": null,
  "displayConversationStarters": [],
  "theme": {
    "primaryColor": "#3854d8",
    "dialogColor": "#ddeaf6",
    "navbarTextColor": "#ffffff"
  },
  "enableFileUpload": true,
  "enableDisplayCitations": true,
  "enableShareConversation": false,
  "enableLocation": false,
  "enableShowPoweredBy": true,
  "poweredByLogo": null,
  "accessType": "web",
```

```
  "inbox": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "測試 doc",
    "signAuth": {
      "id": "6ba7b810-9dad-11d1-80b4-00c04fd430c8",
      "signSource": {
        "id": "7c9e6679-7425-40de-944b-e07fc1f90ae7",
        "accessType": "keycloak"
      },
      "signParams": {
        "keycloak": {
          "url": "example.com",
          "realm": "example",
          "clientId": "example"
        }
      }
    }
  }
}
```


更新 Web Chat

PUT `/api/v1/web-chats/{id}`

參數

參數名稱	必填	類型	說明
`id`	V	string	A UUID string identifying this web chat.

請求內容

請求參數

欄位	類型	必填	說明
avatar	string (uri)	否	
logo	string (uri)	否	

欄位	類型	必填	說明
description	string	否	
cover	string (uri)	否	
backUrl	string	否	
isActive	boolean	否	
theme	object	是	
theme.primaryColor	string	否	
theme.navbarTextColor	string	否	
theme.conversationBackgroundColor	string	否	
theme.chatbotMessageTextColor	string	否	
theme.userMessageTextColor	string	否	
theme.chatbotMessageBackgroundColor	string	否	
theme.userMessageBackgroundColor	string	否	
theme.chatbotMessageBackgroundShadowEnabled	boolean	否	
theme.userMessageBackgroundShadowEnabled	boolean	否	
theme.chatbotMessageGradientEnabled	boolean	否	
theme.userMessageGradientEnabled	boolean	否	
darkTheme	object	是	
darkTheme.primaryColor	string	否	
darkTheme.navbarTextColor	string	否	
darkTheme.conversationBackgroundColor	string	否	
darkTheme.chatbotMessageTextColor	string	否	
darkTheme.userMessageTextColor	string	否	
darkTheme.chatbotMessageBackgroundColor	string	否	
darkTheme.userMessageBackgroundColor	string	否	
darkTheme.chatbotMessageBackgroundShadowEnabled	boolean	否	
darkTheme.userMessageBackgroundShadowEnabled	boolean	否	
darkTheme.chatbotMessageGradientEnabled	boolean	否	
darkTheme.userMessageGradientEnabled	boolean	否	
enableFileUpload	boolean	否	

欄位	類型	必填	說明
enableDisplayCitations	boolean	否	
toolDisplayMode	string (enum: full, compact, hidden)	否	`full` : Full ; `compact` : Compact ; `hidden` : Hidden;
enableAskOptionButtons	boolean	否	開啟後 ask_user_question 選項以按鈕列浮在輸入框上方（輸入框保持可用）；關閉則維持現行覆蓋式面板。灰度開關，可隨時關閉回退。
enableConversationHandoff	boolean	否	開啟後此對話平台的 webchat 顯示交接 UI（提示條、摘要卡、接續按鈕）並註冊交接工具；仍受系統設定的全域交接開關管制（全域關＝一律關）。MaiGPT 免此開關恆顯示。底部的上下文使用量百分比條另由「顯示上下文使用量」控制。預設關閉，客戶對外 webchat 不會看到任何交接 UI；灰度開關，關閉即回退、不需退版。
enableDisplayContextUsage	boolean	否	開啟後此對話平台的 webchat 在輸入框下方顯示上下文使用量百分比條。與對話交接互相獨立：不受交接開關（含全域交接開關）影響，也不影響交接提示條。MaiGPT 免此開關恆顯示。預設關閉；關閉即回退、不需退版。
enableDisplayThinking	boolean	否	
enableUserThinkingControl	boolean	否	
enableDisplayQueryMetadata	boolean	否	
enableDisplayHookMarkers	boolean	否	
hookMarkerTextInputModify	string	否	
hookMarkerTextOutputModify	string	否	
hookMarkerTextInputBlock	string	否	
hookMarkerTextOutputBlock	string	否	
enableShareConversation	boolean	否	
enableLocation	boolean	否	
enableShowPoweredBy	boolean	否	
poweredByLogo	string (uri)	否	
enableAnonymous	boolean	否	

欄位	類型	必填	說明
enableDisplayPreviousConversation	boolean	否	
enableDisplayConversationHistory	boolean	否	
enableConversationTimer	boolean	否	
conversationTimerDuration	integer	否	計時器逾時時長，範圍 3-60 分鐘
enableAutoNewConversationOnTimeout	boolean	否	
enableSatisfactionSurvey	boolean	否	
satisfactionSurveyDelayMinutes	integer	否	最後一則 AI 回覆後幾分鐘彈出問卷，範圍 1-60 分鐘
satisfactionSurveyPrompt	string	否	自訂問卷標題文字，留空則使用前端多語系預設文字
enableThemeModeToggle	boolean	否	
enableDisplayFontSizeSwitch	boolean	否	
defaultThemeMode	object	否	
enableDownloadCitations	boolean	否	
customDomain	object (含 3 個屬性: id, domain, status)	否	
customDomain.domain	string	是	
enableDisplayChatbotAvatar	boolean	否	
enableDisplayChatbotName	boolean	否	
buttonIcon	string (uri)	否	
conversationStartersDisplayCount	integer	否	
preChatFormEnabled	boolean	否	
preChatFormFields	object	否	
preChatFormTitle	object	否	
preChatFormSubtitle	object	否	
loadingDisplayMode	object	否	Waiting-experience style. `narrative` shows per-stage copy; `brand_animation` plays the uploaded asset and hides every system narration line. Defaults to `narrative`, which with no copy configured beh...

欄位	類型	必填	說明
loadingStageCopyByLocale	object	否	Locale-keyed per-stage waiting copy, shaped {locale: {stage: text}} where stage is one of LoadingStage. An absent locale or stage falls back to the built-in copy, so a partially filled dict is valid a...
loadingLongWaitCopyByLocale	object	否	Locale-keyed line shown once the wait exceeds `loading_long_wait_threshold_seconds`, shaped {locale: text}. Written in the brand character voice for the animation mode, but applies to both modes. Empt...
loadingLongWaitThresholdSeconds	integer	否	How long a single reply must be pending before the long-wait copy appears.
loadingAnimationUseSharedAsset	boolean	否	True (default) means every stage plays `loading_animation_shared_asset_url`, so the admin only uploads once. False expands per-stage assets, each falling back to the shared asset when its own slot is ...
loadingAnimationSharedAssetUrl	string (uri)	否	
loadingAnimationAssetUrlsByStage	object	否	Shaped {stage: url} keyed by LoadingStage. Only consulted when `loading_animation_use_shared_asset` is False; a missing stage falls back to the shared asset.
loadingTypingShowCopy	boolean	否	Only affects the first "typing" stage. True (default, the pre-existing behavior) shows the typing-stage copy next to the pre-first-char animation/dot; False plays only the animation with no text line....
toolCardRunningIconUrl	string (uri)	否	
toolCardCompletedIconUrl	string (uri)	否	

請求結構範例

```
{
  "avatar"?: string (uri) // 非必填
  "logo"?: string (uri) // 非必填
  "description"?: string // 非必填
  "cover"?: string (uri) // 非必填
  "backUrl"?: string // 非必填
  "isActive"?: boolean // 非必填
```

```
  "theme": {
  {
    "primaryColor"?: string // 非必填
    "navbarTextColor"?: string // 非必填
    "conversationBackgroundColor"?: string // 非必填
    "chatbotMessageTextColor"?: string // 非必填
    "userMessageTextColor"?: string // 非必填
    "chatbotMessageBackgroundColor"?: string // 非必填
    "userMessageBackgroundColor"?: string // 非必填
    "chatbotMessageBackgroundShadowEnabled"?: boolean // 非必填
    "userMessageBackgroundShadowEnabled"?: boolean // 非必填
    "chatbotMessageGradientEnabled"?: boolean // 非必填
    "userMessageGradientEnabled"?: boolean // 非必填
  }
  }
  "darkTheme": {
  {
    "primaryColor"?: string // 非必填
    "navbarTextColor"?: string // 非必填
    "conversationBackgroundColor"?: string // 非必填
    "chatbotMessageTextColor"?: string // 非必填
    "userMessageTextColor"?: string // 非必填
    "chatbotMessageBackgroundColor"?: string // 非必填
    "userMessageBackgroundColor"?: string // 非必填
    "chatbotMessageBackgroundShadowEnabled"?: boolean // 非必填
    "userMessageBackgroundShadowEnabled"?: boolean // 非必填
    "chatbotMessageGradientEnabled"?: boolean // 非必填
    "userMessageGradientEnabled"?: boolean // 非必填
  }
  }
  "enableFileUpload"?: boolean // 非必填
  "enableDisplayCitations"?: boolean // 非必填
  "toolDisplayMode"?: string (enum: full, compact, hidden) // * `full` - Full
* `compact` - Compact
* `hidden` - Hidden (非必填)
  "enableAskOptionButtons"?: boolean // 開啟後 ask_user_question 選項以按鈕列浮在輸入框上方（輸入框保持可用）；關閉則維持現行覆蓋式面板。灰度開關，可隨時關閉回退。 (非必填)
  "enableConversationHandoff"?: boolean // 開啟後此對話平台的 webchat 顯示交接 UI（提示條、摘要卡、接續按鈕）並註冊交接工具；仍受系統設定的全域交接開關管制（全域關＝一律關）。MaiGPT 免此開關恆顯示。底部的上下文使用量百分比條另由「顯示上下文使用量」控制。預設關閉，客戶對外 webchat 不會看到任何交接 UI；灰度開關，關閉即回退、不需退版。 (非必填)
  "enableDisplayContextUsage"?: boolean // 開啟後此對話平台的 webchat 在輸入框下方顯示上下文使用量百分比條。與對話交接互相獨立：不受交接開關（含全域交接開關）影響，也不影響交接提示條。MaiGPT 免此開關恆顯示。預設關閉；關閉即回退、不需退版。 (非必填)
  "enableDisplayThinking"?: boolean // 非必填
  "enableUserThinkingControl"?: boolean // 非必填
  "enableDisplayQueryMetadata"?: boolean // 非必填
  "enableDisplayHookMarkers"?: boolean // 非必填
  "hookMarkerTextInputModify"?: string // 非必填
  "hookMarkerTextOutputModify"?: string // 非必填
  "hookMarkerTextInputBlock"?: string // 非必填
  "hookMarkerTextOutputBlock"?: string // 非必填
  "enableShareConversation"?: boolean // 非必填
  "enableLocation"?: boolean // 非必填
  "enableShowPoweredBy"?: boolean // 非必填
  "poweredByLogo"?: string (uri) // 非必填
```

```
  "enableAnonymous"?: boolean // 非必填
  "enableDisplayPreviousConversation"?: boolean // 非必填
  "enableDisplayConversationHistory"?: boolean // 非必填
  "enableConversationTimer"?: boolean // 非必填
  "conversationTimerDuration"?: integer // 計時器逾時時長，範圍 3-60 分鐘 (非必填)
  "enableAutoNewConversationOnTimeout"?: boolean // 非必填
  "enableSatisfactionSurvey"?: boolean // 非必填
  "satisfactionSurveyDelayMinutes"?: integer // 最後一則 AI 回覆後幾分鐘彈出問卷，範圍 1-60 分鐘 (非必填)
  "satisfactionSurveyPrompt"?: string // 自訂問卷標題文字，留空則使用前端多語系預設文字 (非必填)
  "enableThemeModeToggle"?: boolean // 非必填
  "enableDisplayFontSizeSwitch"?: boolean // 非必填
  "defaultThemeMode"?:  // 非必填
  {
  }
  "enableDownloadCitations"?: boolean // 非必填
  "customDomain"?:  // 非必填
  {
    "domain": string
  }
  "enableDisplayChatbotAvatar"?: boolean // 非必填
  "enableDisplayChatbotName"?: boolean // 非必填
  "buttonIcon"?: string (uri) // 非必填
  "conversationStartersDisplayCount"?: integer // 非必填
  "preChatFormEnabled"?: boolean // 非必填
  "preChatFormFields"?: object // 非必填
  "preChatFormTitle"?: object // 非必填
  "preChatFormSubtitle"?: object // 非必填
  "loadingDisplayMode"?:  // Waiting-experience style. `narrative` shows per-stage copy; `brand_animation` plays the uploaded asset and hides every system narration line. Defaults to `narrative`, which with no copy configured behaves exactly as before this field existed.

* `narrative` - Narrative copy
* `brand_animation` - Brand animation (非必填)
  {
  }
  "loadingStageCopyByLocale"?: object // Locale-keyed per-stage waiting copy, shaped {locale: {stage: text}} where stage is one of LoadingStage. An absent locale or stage falls back to the built-in copy, so a partially filled dict is valid and never blocks a reply. (非必填)
  "loadingLongWaitCopyByLocale"?: object // Locale-keyed line shown once the wait exceeds `loading_long_wait_threshold_seconds`, shaped {locale: text}. Written in the brand character voice for the animation mode, but applies to both modes. Empty means no long-wait line is shown. (非必填)
  "loadingLongWaitThresholdSeconds"?: integer // How long a single reply must be pending before the long-wait copy appears. (非必填)
  "loadingAnimationUseSharedAsset"?: boolean // True (default) means every stage plays `loading_animation_shared_asset_url`, so the admin only uploads once. False expands per-stage assets, each falling back to the shared asset when its own slot is empty. (非必填)
  "loadingAnimationSharedAssetUrl"?: string (uri) // 非必填
  "loadingAnimationAssetUrlsByStage"?: object // Shaped {stage: url} keyed by LoadingStage. Only consulted when `loading_animation_use_shared_asset` is False; a missing stage falls back to the shared asset. (非必填)
  "loadingTypingShowCopy"?: boolean // Only affects the first "typing" stage. True (default, the pre-existing behavior) shows the typing-stage copy next to the pre-first-char animation/dot; False plays only the animation with no text line. Thinking / analyzing / long-wait stages are unaffected. (非必填)
```

```
  "toolCardRunningIconUrl"?: string (uri) // 非必填
  "toolCardCompletedIconUrl"?: string (uri) // 非必填
}
```

請求範例值

```
{
  "avatar": "https://example.com/file.jpg",
  "logo": "https://example.com/file.jpg",
  "description": "範例字串",
  "cover": "https://example.com/file.jpg",
  "backUrl": "範例字串",
  "isActive": true,
  "theme": {
    "primaryColor": "範例字串",
    "navbarTextColor": "範例字串",
    "conversationBackgroundColor": "範例字串",
    "chatbotMessageTextColor": "範例字串",
    "userMessageTextColor": "範例字串",
    "chatbotMessageBackgroundColor": "範例字串",
    "userMessageBackgroundColor": "範例字串",
    "chatbotMessageBackgroundShadowEnabled": true,
    "userMessageBackgroundShadowEnabled": true,
    "chatbotMessageGradientEnabled": true,
    "userMessageGradientEnabled": true
  },
  "darkTheme": {
    "primaryColor": "範例字串",
    "navbarTextColor": "範例字串",
    "conversationBackgroundColor": "範例字串",
    "chatbotMessageTextColor": "範例字串",
    "userMessageTextColor": "範例字串",
    "chatbotMessageBackgroundColor": "範例字串",
    "userMessageBackgroundColor": "範例字串",
    "chatbotMessageBackgroundShadowEnabled": true,
    "userMessageBackgroundShadowEnabled": true,
    "chatbotMessageGradientEnabled": true,
    "userMessageGradientEnabled": true
  },
  "enableFileUpload": true,
  "enableDisplayCitations": true,
  "toolDisplayMode": "full",
  "enableAskOptionButtons": true,
  "enableConversationHandoff": true,
  "enableDisplayContextUsage": true,
  "enableDisplayThinking": true,
  "enableUserThinkingControl": true,
  "enableDisplayQueryMetadata": true,
  "enableDisplayHookMarkers": true,
  "hookMarkerTextInputModify": "範例字串",
  "hookMarkerTextOutputModify": "範例字串",
  "hookMarkerTextInputBlock": "範例字串",
  "hookMarkerTextOutputBlock": "範例字串",
  "enableShareConversation": true,
```

```
  "enableLocation": true,
  "enableShowPoweredBy": true,
  "poweredByLogo": "https://example.com/file.jpg",
  "enableAnonymous": true,
  "enableDisplayPreviousConversation": true,
  "enableDisplayConversationHistory": true,
  "enableConversationTimer": true,
  "conversationTimerDuration": 123,
  "enableAutoNewConversationOnTimeout": true,
  "enableSatisfactionSurvey": true,
  "satisfactionSurveyDelayMinutes": 123,
  "satisfactionSurveyPrompt": "範例字串",
  "enableThemeModeToggle": true,
  "enableDisplayFontSizeSwitch": true,
  "defaultThemeMode": {},
  "enableDownloadCitations": true,
  "customDomain": {
    "domain": "範例字串"
  },
  "enableDisplayChatbotAvatar": true,
  "enableDisplayChatbotName": true,
  "buttonIcon": "https://example.com/file.jpg",
  "conversationStartersDisplayCount": 123,
  "preChatFormEnabled": true,
  "preChatFormFields": null,
  "preChatFormTitle": null,
  "preChatFormSubtitle": null,
  "loadingDisplayMode": {},
  "loadingStageCopyByLocale": null,
  "loadingLongWaitCopyByLocale": null,
  "loadingLongWaitThresholdSeconds": 123,
  "loadingAnimationUseSharedAsset": true,
  "loadingAnimationSharedAssetUrl": "https://example.com/file.jpg",
  "loadingAnimationAssetUrlsByStage": null,
  "loadingTypingShowCopy": true,
  "toolCardRunningIconUrl": "https://example.com/file.jpg",
  "toolCardCompletedIconUrl": "https://example.com/file.jpg"
}
```


程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X PUT "https://api.maiagent.ai/api/v1/web-chats/550e8400-e29b-41d4-a716-
446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "avatar": "https://example.com/file.jpg",
    "logo": "https://example.com/file.jpg",
    "description": "範例字串",
    "cover": "https://example.com/file.jpg",
    "backUrl": "範例字串",
    "isActive": true,
    "theme": {
      "primaryColor": "範例字串",
      "navbarTextColor": "範例字串",
      "conversationBackgroundColor": "範例字串",
      "chatbotMessageTextColor": "範例字串",
      "userMessageTextColor": "範例字串",
      "chatbotMessageBackgroundColor": "範例字串",
      "userMessageBackgroundColor": "範例字串",
      "chatbotMessageBackgroundShadowEnabled": true,
      "userMessageBackgroundShadowEnabled": true,
      "chatbotMessageGradientEnabled": true,
      "userMessageGradientEnabled": true
    },
    "darkTheme": {
      "primaryColor": "範例字串",
      "navbarTextColor": "範例字串",
      "conversationBackgroundColor": "範例字串",
      "chatbotMessageTextColor": "範例字串",
      "userMessageTextColor": "範例字串",
      "chatbotMessageBackgroundColor": "範例字串",
      "userMessageBackgroundColor": "範例字串",
      "chatbotMessageBackgroundShadowEnabled": true,
      "userMessageBackgroundShadowEnabled": true,
      "chatbotMessageGradientEnabled": true,
      "userMessageGradientEnabled": true
    },
    "enableFileUpload": true,
    "enableDisplayCitations": true,
    "toolDisplayMode": "full",
    "enableAskOptionButtons": true,
    "enableConversationHandoff": true,
    "enableDisplayContextUsage": true,
    "enableDisplayThinking": true,
    "enableUserThinkingControl": true,
    "enableDisplayQueryMetadata": true,
```

```
      "enableDisplayHookMarkers": true,
      "hookMarkerTextInputModify": "範例字串",
      "hookMarkerTextOutputModify": "範例字串",
      "hookMarkerTextInputBlock": "範例字串",
      "hookMarkerTextOutputBlock": "範例字串",
      "enableShareConversation": true,
      "enableLocation": true,
      "enableShowPoweredBy": true,
      "poweredByLogo": "https://example.com/file.jpg",
      "enableAnonymous": true,
      "enableDisplayPreviousConversation": true,
      "enableDisplayConversationHistory": true,
      "enableConversationTimer": true,
      "conversationTimerDuration": 123,
      "enableAutoNewConversationOnTimeout": true,
      "enableSatisfactionSurvey": true,
      "satisfactionSurveyDelayMinutes": 123,
      "satisfactionSurveyPrompt": "範例字串",
      "enableThemeModeToggle": true,
      "enableDisplayFontSizeSwitch": true,
      "defaultThemeMode": {},
      "enableDownloadCitations": true,
      "customDomain": {
        "domain": "範例字串"
      },
      "enableDisplayChatbotAvatar": true,
      "enableDisplayChatbotName": true,
      "buttonIcon": "https://example.com/file.jpg",
      "conversationStartersDisplayCount": 123,
      "preChatFormEnabled": true,
      "preChatFormFields": null,
      "preChatFormTitle": null,
      "preChatFormSubtitle": null,
      "loadingDisplayMode": {},
      "loadingStageCopyByLocale": null,
      "loadingLongWaitCopyByLocale": null,
      "loadingLongWaitThresholdSeconds": 123,
      "loadingAnimationUseSharedAsset": true,
      "loadingAnimationSharedAssetUrl": "https://example.com/file.jpg",
      "loadingAnimationAssetUrlsByStage": null,
      "loadingTypingShowCopy": true,
      "toolCardRunningIconUrl": "https://example.com/file.jpg",
      "toolCardCompletedIconUrl": "https://example.com/file.jpg"
    }'

  # 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// 請求內容 (payload)
const data = {
    "avatar": "https://example.com/file.jpg",
    "logo": "https://example.com/file.jpg",
    "description": "範例字串",
    "cover": "https://example.com/file.jpg",
    "backUrl": "範例字串",
    "isActive": true,
    "theme": {
      "primaryColor": "範例字串",
      "navbarTextColor": "範例字串",
      "conversationBackgroundColor": "範例字串",
      "chatbotMessageTextColor": "範例字串",
      "userMessageTextColor": "範例字串",
      "chatbotMessageBackgroundColor": "範例字串",
      "userMessageBackgroundColor": "範例字串",
      "chatbotMessageBackgroundShadowEnabled": true,
      "userMessageBackgroundShadowEnabled": true,
      "chatbotMessageGradientEnabled": true,
      "userMessageGradientEnabled": true
    },
    "darkTheme": {
      "primaryColor": "範例字串",
      "navbarTextColor": "範例字串",
      "conversationBackgroundColor": "範例字串",
      "chatbotMessageTextColor": "範例字串",
      "userMessageTextColor": "範例字串",
      "chatbotMessageBackgroundColor": "範例字串",
      "userMessageBackgroundColor": "範例字串",
      "chatbotMessageBackgroundShadowEnabled": true,
      "userMessageBackgroundShadowEnabled": true,
      "chatbotMessageGradientEnabled": true,
      "userMessageGradientEnabled": true
    },
    "enableFileUpload": true,
    "enableDisplayCitations": true,
    "toolDisplayMode": "full",
    "enableAskOptionButtons": true,
    "enableConversationHandoff": true,
    "enableDisplayContextUsage": true,
```

```
    "enableDisplayThinking": true,
    "enableUserThinkingControl": true,
    "enableDisplayQueryMetadata": true,
    "enableDisplayHookMarkers": true,
    "hookMarkerTextInputModify": "範例字串",
    "hookMarkerTextOutputModify": "範例字串",
    "hookMarkerTextInputBlock": "範例字串",
    "hookMarkerTextOutputBlock": "範例字串",
    "enableShareConversation": true,
    "enableLocation": true,
    "enableShowPoweredBy": true,
    "poweredByLogo": "https://example.com/file.jpg",
    "enableAnonymous": true,
    "enableDisplayPreviousConversation": true,
    "enableDisplayConversationHistory": true,
    "enableConversationTimer": true,
    "conversationTimerDuration": 123,
    "enableAutoNewConversationOnTimeout": true,
    "enableSatisfactionSurvey": true,
    "satisfactionSurveyDelayMinutes": 123,
    "satisfactionSurveyPrompt": "範例字串",
    "enableThemeModeToggle": true,
    "enableDisplayFontSizeSwitch": true,
    "defaultThemeMode": {},
    "enableDownloadCitations": true,
    "customDomain": {
      "domain": "範例字串"
    },
    "enableDisplayChatbotAvatar": true,
    "enableDisplayChatbotName": true,
    "buttonIcon": "https://example.com/file.jpg",
    "conversationStartersDisplayCount": 123,
    "preChatFormEnabled": true,
    "preChatFormFields": null,
    "preChatFormTitle": null,
    "preChatFormSubtitle": null,
    "loadingDisplayMode": {},
    "loadingStageCopyByLocale": null,
    "loadingLongWaitCopyByLocale": null,
    "loadingLongWaitThresholdSeconds": 123,
    "loadingAnimationUseSharedAsset": true,
    "loadingAnimationSharedAssetUrl": "https://example.com/file.jpg",
    "loadingAnimationAssetUrlsByStage": null,
    "loadingTypingShowCopy": true,
    "toolCardRunningIconUrl": "https://example.com/file.jpg",
    "toolCardCompletedIconUrl": "https://example.com/file.jpg"
  };

axios.put("https://api.maiagent.ai/api/v1/web-chats/550e8400-e29b-41d4-a716-
446655440000/", data, config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
```

```
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/web-chats/550e8400-e29b-41d4-a716-446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# 請求內容 (payload)
data = {
    "avatar": "https://example.com/file.jpg",
    "logo": "https://example.com/file.jpg",
    "description": "範例字串",
    "cover": "https://example.com/file.jpg",
    "backUrl": "範例字串",
    "isActive": True,
    "theme": {
        "primaryColor": "範例字串",
        "navbarTextColor": "範例字串",
        "conversationBackgroundColor": "範例字串",
        "chatbotMessageTextColor": "範例字串",
        "userMessageTextColor": "範例字串",
        "chatbotMessageBackgroundColor": "範例字串",
        "userMessageBackgroundColor": "範例字串",
        "chatbotMessageBackgroundShadowEnabled": True,
        "userMessageBackgroundShadowEnabled": True,
        "chatbotMessageGradientEnabled": True,
        "userMessageGradientEnabled": True
    },
    "darkTheme": {
        "primaryColor": "範例字串",
        "navbarTextColor": "範例字串",
        "conversationBackgroundColor": "範例字串",
        "chatbotMessageTextColor": "範例字串",
        "userMessageTextColor": "範例字串",
        "chatbotMessageBackgroundColor": "範例字串",
        "userMessageBackgroundColor": "範例字串",
        "chatbotMessageBackgroundShadowEnabled": True,
        "userMessageBackgroundShadowEnabled": True,
        "chatbotMessageGradientEnabled": True,
        "userMessageGradientEnabled": True
    },
    "enableFileUpload": True,
    "enableDisplayCitations": True,
    "toolDisplayMode": "full",
    "enableAskOptionButtons": True,
    "enableConversationHandoff": True,
    "enableDisplayContextUsage": True,
    "enableDisplayThinking": True,
    "enableUserThinkingControl": True,
```

```
    "enableDisplayQueryMetadata": True,
    "enableDisplayHookMarkers": True,
    "hookMarkerTextInputModify": "範例字串",
    "hookMarkerTextOutputModify": "範例字串",
    "hookMarkerTextInputBlock": "範例字串",
    "hookMarkerTextOutputBlock": "範例字串",
    "enableShareConversation": True,
    "enableLocation": True,
    "enableShowPoweredBy": True,
    "poweredByLogo": "https://example.com/file.jpg",
    "enableAnonymous": True,
    "enableDisplayPreviousConversation": True,
    "enableDisplayConversationHistory": True,
    "enableConversationTimer": True,
    "conversationTimerDuration": 123,
    "enableAutoNewConversationOnTimeout": True,
    "enableSatisfactionSurvey": True,
    "satisfactionSurveyDelayMinutes": 123,
    "satisfactionSurveyPrompt": "範例字串",
    "enableThemeModeToggle": True,
    "enableDisplayFontSizeSwitch": True,
    "defaultThemeMode": {},
    "enableDownloadCitations": True,
    "customDomain": {
        "domain": "範例字串"
    },
    "enableDisplayChatbotAvatar": True,
    "enableDisplayChatbotName": True,
    "buttonIcon": "https://example.com/file.jpg",
    "conversationStartersDisplayCount": 123,
    "preChatFormEnabled": True,
    "preChatFormFields": None,
    "preChatFormTitle": None,
    "preChatFormSubtitle": None,
    "loadingDisplayMode": {},
    "loadingStageCopyByLocale": None,
    "loadingLongWaitCopyByLocale": None,
    "loadingLongWaitThresholdSeconds": 123,
    "loadingAnimationUseSharedAsset": True,
    "loadingAnimationSharedAssetUrl": "https://example.com/file.jpg",
    "loadingAnimationAssetUrlsByStage": None,
    "loadingTypingShowCopy": True,
    "toolCardRunningIconUrl": "https://example.com/file.jpg",
    "toolCardCompletedIconUrl": "https://example.com/file.jpg"
}

response = requests.put(url, json=data, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->put("https://api.maiagent.ai/api/v1/web-chats/550e8400-e29b-41d4-a716-446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'avatar' => 'https://example.com/file.jpg',
            'logo' => 'https://example.com/file.jpg',
            'description' => '範例字串',
            'cover' => 'https://example.com/file.jpg',
            'backUrl' => '範例字串',
            'isActive' => true,
            'theme' => [
                'primaryColor' => '範例字串',
                'navbarTextColor' => '範例字串',
                'conversationBackgroundColor' => '範例字串',
                'chatbotMessageTextColor' => '範例字串',
                'userMessageTextColor' => '範例字串',
                'chatbotMessageBackgroundColor' => '範例字串',
                'userMessageBackgroundColor' => '範例字串',
                'chatbotMessageBackgroundShadowEnabled' => true,
                'userMessageBackgroundShadowEnabled' => true,
                'chatbotMessageGradientEnabled' => true,
                'userMessageGradientEnabled' => true
            ],
            'darkTheme' => [
                'primaryColor' => '範例字串',
                'navbarTextColor' => '範例字串',
                'conversationBackgroundColor' => '範例字串',
                'chatbotMessageTextColor' => '範例字串',
                'userMessageTextColor' => '範例字串',
                'chatbotMessageBackgroundColor' => '範例字串',
                'userMessageBackgroundColor' => '範例字串',
                'chatbotMessageBackgroundShadowEnabled' => true,
                'userMessageBackgroundShadowEnabled' => true,
                'chatbotMessageGradientEnabled' => true,
                'userMessageGradientEnabled' => true
            ],
            'enableFileUpload' => true,
            'enableDisplayCitations' => true,
            'toolDisplayMode' => 'full',
            'enableAskOptionButtons' => true,
            'enableConversationHandoff' => true,
```

```
                'enableDisplayContextUsage' => true,
                'enableDisplayThinking' => true,
                'enableUserThinkingControl' => true,
                'enableDisplayQueryMetadata' => true,
                'enableDisplayHookMarkers' => true,
                'hookMarkerTextInputModify' => '範例字串',
                'hookMarkerTextOutputModify' => '範例字串',
                'hookMarkerTextInputBlock' => '範例字串',
                'hookMarkerTextOutputBlock' => '範例字串',
                'enableShareConversation' => true,
                'enableLocation' => true,
                'enableShowPoweredBy' => true,
                'poweredByLogo' => 'https://example.com/file.jpg',
                'enableAnonymous' => true,
                'enableDisplayPreviousConversation' => true,
                'enableDisplayConversationHistory' => true,
                'enableConversationTimer' => true,
                'conversationTimerDuration' => 123,
                'enableAutoNewConversationOnTimeout' => true,
                'enableSatisfactionSurvey' => true,
                'satisfactionSurveyDelayMinutes' => 123,
                'satisfactionSurveyPrompt' => '範例字串',
                'enableThemeModeToggle' => true,
                'enableDisplayFontSizeSwitch' => true,
                'defaultThemeMode' => new \stdClass(),
                'enableDownloadCitations' => true,
                'customDomain' => [
                    'domain' => '範例字串'
                ],
                'enableDisplayChatbotAvatar' => true,
                'enableDisplayChatbotName' => true,
                'buttonIcon' => 'https://example.com/file.jpg',
                'conversationStartersDisplayCount' => 123,
                'preChatFormEnabled' => true,
                'preChatFormFields' => null,
                'preChatFormTitle' => null,
                'preChatFormSubtitle' => null,
                'loadingDisplayMode' => new \stdClass(),
                'loadingStageCopyByLocale' => null,
                'loadingLongWaitCopyByLocale' => null,
                'loadingLongWaitThresholdSeconds' => 123,
                'loadingAnimationUseSharedAsset' => true,
                'loadingAnimationSharedAssetUrl' => 'https://example.com/file.jpg',
                'loadingAnimationAssetUrlsByStage' => null,
                'loadingTypingShowCopy' => true,
                'toolCardRunningIconUrl' => 'https://example.com/file.jpg',
                'toolCardCompletedIconUrl' => 'https://example.com/file.jpg'
            ]
        ]);

        $data = json_decode($response->getBody(), true);
        echo "成功取得回應:\n";
        print_r($data);
    } catch (Exception $e) {
        echo '請求發生錯誤: ' . $e->getMessage();
```

```
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
{
  "id": string (uuid)
  "name": string
  "avatar"?: string (uri) // 非必填
  "logo"?: string (uri) // 非必填
  "description"?: string // 非必填
  "cover"?: string (uri) // 非必填
  "backUrl"?: string // 非必填
  "isActive"?: boolean // 非必填
  "enableSpeech": boolean
  "displayConversationStarters": [
    string
  ]
  "theme": {
  {
    "primaryColor"?: string // 非必填
    "navbarTextColor"?: string // 非必填
    "conversationBackgroundColor"?: string // 非必填
    "chatbotMessageTextColor"?: string // 非必填
    "userMessageTextColor"?: string // 非必填
    "chatbotMessageBackgroundColor"?: string // 非必填
    "userMessageBackgroundColor"?: string // 非必填
    "chatbotMessageBackgroundShadowEnabled"?: boolean // 非必填
    "userMessageBackgroundShadowEnabled"?: boolean // 非必填
    "chatbotMessageGradientEnabled"?: boolean // 非必填
    "userMessageGradientEnabled"?: boolean // 非必填
  }
  }
  "darkTheme": {
  {
    "primaryColor"?: string // 非必填
    "navbarTextColor"?: string // 非必填
    "conversationBackgroundColor"?: string // 非必填
    "chatbotMessageTextColor"?: string // 非必填
    "userMessageTextColor"?: string // 非必填
    "chatbotMessageBackgroundColor"?: string // 非必填
    "userMessageBackgroundColor"?: string // 非必填
    "chatbotMessageBackgroundShadowEnabled"?: boolean // 非必填
```

```
    "userMessageBackgroundShadowEnabled"?: boolean // 非必填
    "chatbotMessageGradientEnabled"?: boolean // 非必填
    "userMessageGradientEnabled"?: boolean // 非必填
  }
  }
  "enableFileUpload"?: boolean // 非必填
  "enableDisplayCitations"?: boolean // 非必填
  "toolDisplayMode"?: string (enum: full, compact, hidden) // * `full` - Full
* `compact` - Compact
* `hidden` - Hidden (非必填)
  "enableAskOptionButtons"?: boolean // 開啟後 ask_user_question 選項以按鈕列浮在輸入框上方（輸入框保持可用）；關閉則維持現行覆蓋式面板。灰度開關，可隨時關閉回退。 (非必填)
  "enableConversationHandoff"?: boolean // 開啟後此對話平台的 webchat 顯示交接 UI（提示條、摘要卡、接續按鈕）並註冊交接工具；仍受系統設定的全域交接開關管制（全域關＝一律關）。MaiGPT 免此開關恆顯示。底部的上下文使用量百分比條另由「顯示上下文使用量」控制。預設關閉，客戶對外 webchat 不會看到任何交接 UI；灰度開關，關閉即回退、不需退版。 (非必填)
  "enableDisplayContextUsage"?: boolean // 開啟後此對話平台的 webchat 在輸入框下方顯示上下文使用量百分比條。與對話交接互相獨立：不受交接開關（含全域交接開關）影響，也不影響交接提示條。MaiGPT 免此開關恆顯示。預設關閉；關閉即回退、不需退版。 (非必填)
  "enableDisplayThinking"?: boolean // 非必填
  "enableUserThinkingControl"?: boolean // 非必填
  "enableDisplayQueryMetadata"?: boolean // 非必填
  "enableDisplayHookMarkers"?: boolean // 非必填
  "hookMarkerTextInputModify"?: string // 非必填
  "hookMarkerTextOutputModify"?: string // 非必填
  "hookMarkerTextInputBlock"?: string // 非必填
  "hookMarkerTextOutputBlock"?: string // 非必填
  "enableShareConversation"?: boolean // 非必填
  "enableLocation"?: boolean // 非必填
  "enableShowPoweredBy"?: boolean // 非必填
  "poweredByLogo"?: string (uri) // 非必填
  "enableAnonymous"?: boolean // 非必填
  "enableDisplayPreviousConversation"?: boolean // 非必填
  "enableDisplayConversationHistory"?: boolean // 非必填
  "enableConversationTimer"?: boolean // 非必填
  "conversationTimerDuration"?: integer // 計時器逾時時長，範圍 3-60 分鐘 (非必填)
  "enableAutoNewConversationOnTimeout"?: boolean // 非必填
  "enableSatisfactionSurvey"?: boolean // 非必填
  "satisfactionSurveyDelayMinutes"?: integer // 最後一則 AI 回覆後幾分鐘彈出問卷，範圍 1-60 分鐘 (非必填)
  "satisfactionSurveyPrompt"?: string // 自訂問卷標題文字，留空則使用前端多語系預設文字 (非必填)
  "accessType":
  {
  }
  "enableThemeModeToggle"?: boolean // 非必填
  "enableDisplayFontSizeSwitch"?: boolean // 非必填
  "defaultThemeMode"?:  // 非必填
  {
  }
  "enableDownloadCitations"?: boolean // 非必填
  "customDomain"?:  // 非必填
  {
    "id": string (uuid)
    "domain": string
    "status":
    {
```

```
    }
  }
  "enableDisplayChatbotAvatar"?: boolean // 非必填
  "enableDisplayChatbotName"?: boolean // 非必填
  "buttonIcon"?: string (uri) // 非必填
  "enableCodeInterpreter": boolean // Read enable_code_interpreter from the inbox's chatbot.
  "voiceAgentEnabled": boolean // Whether the bound chatbot has the voice agent turned on
(read-only)
  "conversationStartersDisplayCount"?: integer // 非必填
  "includeGreetingInContext": boolean // When enabled, the conversation greeting and the
numbered conversation starters (in configured order, unshuffled and untruncated) are injected
into the LLM context so the agent can resolve short replies like "1" to the matching starter
option.
  "tools": [ // Expose chatbot tools to SDK for the tool_mask selector.

Name resolution prefers ``display_name`` (set on MCP tools, where
``name`` is null) and falls back to ``name`` for API tools where
``display_name`` is null. Tools missing both are skipped — SDK
should never show an unnamed tool to a contact. Quick Menu tools are
static input-bar UI, never an LLM tool, so masking one is meaningless.
    object
  ]
  "preChatFormEnabled"?: boolean // 非必填
  "preChatFormFields"?: object // 非必填
  "preChatFormTitle"?: object // 非必填
  "preChatFormSubtitle"?: object // 非必填
  "loadingDisplayMode"?:  // Waiting-experience style. `narrative` shows per-stage copy;
`brand_animation` plays the uploaded asset and hides every system narration line. Defaults to
`narrative`, which with no copy configured behaves exactly as before this field existed.

* `narrative` - Narrative copy
* `brand_animation` - Brand animation (非必填)
  {
  }
  "loadingStageCopyByLocale"?: object // Locale-keyed per-stage waiting copy, shaped {locale:
{stage: text}} where stage is one of LoadingStage. An absent locale or stage falls back to
the built-in copy, so a partially filled dict is valid and never blocks a reply. (非必填)
  "loadingLongWaitCopyByLocale"?: object // Locale-keyed line shown once the wait exceeds
`loading_long_wait_threshold_seconds`, shaped {locale: text}. Written in the brand character
voice for the animation mode, but applies to both modes. Empty means no long-wait line is
shown. (非必填)
  "loadingLongWaitThresholdSeconds"?: integer // How long a single reply must be pending
before the long-wait copy appears. (非必填)
  "loadingAnimationUseSharedAsset"?: boolean // True (default) means every stage plays
`loading_animation_shared_asset_url`, so the admin only uploads once. False expands per-stage
assets, each falling back to the shared asset when its own slot is empty. (非必填)
  "loadingAnimationSharedAssetUrl"?: string (uri) // 非必填
  "loadingAnimationAssetUrlsByStage"?: object // Shaped {stage: url} keyed by LoadingStage.
Only consulted when `loading_animation_use_shared_asset` is False; a missing stage falls back
to the shared asset. (非必填)
  "loadingTypingShowCopy"?: boolean // Only affects the first "typing" stage. True (default,
the pre-existing behavior) shows the typing-stage copy next to the pre-first-char
animation/dot; False plays only the animation with no text line. Thinking / analyzing / long-
wait stages are unaffected. (非必填)
  "toolCardRunningIconUrl"?: string (uri) // 非必填
  "toolCardCompletedIconUrl"?: string (uri) // 非必填
```

```
  "inbox": object
  "quickMenu": object // Mounted Quick Menu Agent UI config for the web chat input bar; null
when absent (read-only)
}
```

回應範例值

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "name": "回應字串",
  "avatar": "https://example.com/file.jpg",
  "logo": "https://example.com/file.jpg",
  "description": "回應字串",
  "cover": "https://example.com/file.jpg",
  "backUrl": "回應字串",
  "isActive": false,
  "enableSpeech": false,
  "displayConversationStarters": [
    "回應字串"
  ],
  "theme": {
    "primaryColor": "回應字串",
    "navbarTextColor": "回應字串",
    "conversationBackgroundColor": "回應字串",
    "chatbotMessageTextColor": "回應字串",
    "userMessageTextColor": "回應字串",
    "chatbotMessageBackgroundColor": "回應字串",
    "userMessageBackgroundColor": "回應字串",
    "chatbotMessageBackgroundShadowEnabled": false,
    "userMessageBackgroundShadowEnabled": false,
    "chatbotMessageGradientEnabled": false,
    "userMessageGradientEnabled": false
  },
  "darkTheme": {
    "primaryColor": "回應字串",
    "navbarTextColor": "回應字串",
    "conversationBackgroundColor": "回應字串",
    "chatbotMessageTextColor": "回應字串",
    "userMessageTextColor": "回應字串",
    "chatbotMessageBackgroundColor": "回應字串",
    "userMessageBackgroundColor": "回應字串",
    "chatbotMessageBackgroundShadowEnabled": false,
    "userMessageBackgroundShadowEnabled": false,
    "chatbotMessageGradientEnabled": false,
    "userMessageGradientEnabled": false
  },
  "enableFileUpload": false,
  "enableDisplayCitations": false,
  "toolDisplayMode": "full",
  "enableAskOptionButtons": false,
  "enableConversationHandoff": false,
  "enableDisplayContextUsage": false,
  "enableDisplayThinking": false,
  "enableUserThinkingControl": false,
```

```
  "enableDisplayQueryMetadata": false,
  "enableDisplayHookMarkers": false,
  "hookMarkerTextInputModify": "回應字串",
  "hookMarkerTextOutputModify": "回應字串",
  "hookMarkerTextInputBlock": "回應字串",
  "hookMarkerTextOutputBlock": "回應字串",
  "enableShareConversation": false,
  "enableLocation": false,
  "enableShowPoweredBy": false,
  "poweredByLogo": "https://example.com/file.jpg",
  "enableAnonymous": false,
  "enableDisplayPreviousConversation": false,
  "enableDisplayConversationHistory": false,
  "enableConversationTimer": false,
  "conversationTimerDuration": 456,
  "enableAutoNewConversationOnTimeout": false,
  "enableSatisfactionSurvey": false,
  "satisfactionSurveyDelayMinutes": 456,
  "satisfactionSurveyPrompt": "回應字串",
  "accessType": {},
  "enableThemeModeToggle": false,
  "enableDisplayFontSizeSwitch": false,
  "defaultThemeMode": {},
  "enableDownloadCitations": false,
  "customDomain": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "domain": "回應字串",
    "status": {}
  },
  "enableDisplayChatbotAvatar": false,
  "enableDisplayChatbotName": false,
  "buttonIcon": "https://example.com/file.jpg",
  "enableCodeInterpreter": false,
  "voiceAgentEnabled": false,
  "conversationStartersDisplayCount": 456,
  "includeGreetingInContext": false,
  "tools": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "回應範例名稱",
      "description": "回應範例描述"
    }
  ],
  "preChatFormEnabled": false,
  "preChatFormFields": null,
  "preChatFormTitle": null,
  "preChatFormSubtitle": null,
  "loadingDisplayMode": {},
  "loadingStageCopyByLocale": null,
  "loadingLongWaitCopyByLocale": null,
  "loadingLongWaitThresholdSeconds": 456,
  "loadingAnimationUseSharedAsset": false,
  "loadingAnimationSharedAssetUrl": "https://example.com/file.jpg",
  "loadingAnimationAssetUrlsByStage": null,
  "loadingTypingShowCopy": false,
  "toolCardRunningIconUrl": "https://example.com/file.jpg",
```

```
  "toolCardCompletedIconUrl": "https://example.com/file.jpg",
  "inbox": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應範例名稱",
    "description": "回應範例描述"
  },
  "quickMenu": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應範例名稱",
    "description": "回應範例描述"
  }
}
```


部分更新 Web Chat

PATCH `/api/v1/web-chats/{id}`

參數

參數名稱	必填	類型	說明
`id`	V	string	A UUID string identifying this web chat.

請求內容

請求參數

欄位	類型	必填	說明
avatar	string (uri)	否	
logo	string (uri)	否	
description	string	否	
cover	string (uri)	否	
backUrl	string	否	
isActive	boolean	否	

欄位	類型	必填	說明
theme	object	否	
theme.primaryColor	string	否	
theme.navbarTextColor	string	否	
theme.conversationBackgroundColor	string	否	
theme.chatbotMessageTextColor	string	否	
theme.userMessageTextColor	string	否	
theme.chatbotMessageBackgroundColor	string	否	
theme.userMessageBackgroundColor	string	否	
theme.chatbotMessageBackgroundShadowEnabled	boolean	否	
theme.userMessageBackgroundShadowEnabled	boolean	否	
theme.chatbotMessageGradientEnabled	boolean	否	
theme.userMessageGradientEnabled	boolean	否	
darkTheme	object	否	
darkTheme.primaryColor	string	否	
darkTheme.navbarTextColor	string	否	
darkTheme.conversationBackgroundColor	string	否	
darkTheme.chatbotMessageTextColor	string	否	
darkTheme.userMessageTextColor	string	否	
darkTheme.chatbotMessageBackgroundColor	string	否	
darkTheme.userMessageBackgroundColor	string	否	
darkTheme.chatbotMessageBackgroundShadowEnabled	boolean	否	
darkTheme.userMessageBackgroundShadowEnabled	boolean	否	
darkTheme.chatbotMessageGradientEnabled	boolean	否	
darkTheme.userMessageGradientEnabled	boolean	否	
enableFileUpload	boolean	否	
enableDisplayCitations	boolean	否	
toolDisplayMode	string (enum: full, compact, hidden)	否	`full` : Full ; `compact` : Compact ; `hidden` : Hidden;

欄位	類型	必填	說明
enableAskOptionButtons	boolean	否	開啟後 ask_user_question 選項以按鈕列浮在輸入框上方（輸入框保持可用）；關閉則維持現行覆蓋式面板。灰度開關，可隨時關閉回退。
enableConversationHandoff	boolean	否	開啟後此對話平台的 webchat 顯示交接 UI（提示條、摘要卡、接續按鈕）並註冊交接工具；仍受系統設定的全域交接開關管制（全域關＝一律關）。MaiGPT 免此開關恆顯示。底部的上下文使用量百分比條另由「顯示上下文使用量」控制。預設關閉，客戶對外 webchat 不會看到任何交接 UI；灰度開關，關閉即回退、不需退版。
enableDisplayContextUsage	boolean	否	開啟後此對話平台的 webchat 在輸入框下方顯示上下文使用量百分比條。與對話交接互相獨立：不受交接開關（含全域交接開關）影響，也不影響交接提示條。MaiGPT 免此開關恆顯示。預設關閉；關閉即回退、不需退版。
enableDisplayThinking	boolean	否	
enableUserThinkingControl	boolean	否	
enableDisplayQueryMetadata	boolean	否	
enableDisplayHookMarkers	boolean	否	
hookMarkerTextInputModify	string	否	
hookMarkerTextOutputModify	string	否	
hookMarkerTextInputBlock	string	否	
hookMarkerTextOutputBlock	string	否	
enableShareConversation	boolean	否	
enableLocation	boolean	否	
enableShowPoweredBy	boolean	否	
poweredByLogo	string (uri)	否	
enableAnonymous	boolean	否	
enableDisplayPreviousConversation	boolean	否	
enableDisplayConversationHistory	boolean	否	
enableConversationTimer	boolean	否	
conversationTimerDuration	integer	否	計時器逾時時長，範圍 3-60 分鐘
enableAutoNewConversationOnTimeout	boolean	否	

欄位	類型	必填	說明
enableSatisfactionSurvey	boolean	否	
satisfactionSurveyDelayMinutes	integer	否	最後一則 AI 回覆後幾分鐘彈出問卷，範圍 1-60 分鐘
satisfactionSurveyPrompt	string	否	自訂問卷標題文字，留空則使用前端多語系預設文字
enableThemeModeToggle	boolean	否	
enableDisplayFontSizeSwitch	boolean	否	
defaultThemeMode	object	否	
enableDownloadCitations	boolean	否	
customDomain	object (含 3 個屬性: id, domain, status)	否	
customDomain.domain	string	是	
enableDisplayChatbotAvatar	boolean	否	
enableDisplayChatbotName	boolean	否	
buttonIcon	string (uri)	否	
conversationStartersDisplayCount	integer	否	
preChatFormEnabled	boolean	否	
preChatFormFields	object	否	
preChatFormTitle	object	否	
preChatFormSubtitle	object	否	
loadingDisplayMode	object	否	Waiting-experience style. `narrative` shows per-stage copy; `brand_animation` plays the uploaded asset and hides every system narration line. Defaults to `narrative`, which with no copy configured beh...
loadingStageCopyByLocale	object	否	Locale-keyed per-stage waiting copy, shaped {locale: {stage: text}} where stage is one of LoadingStage. An absent locale or stage falls back to the built-in copy, so a partially filled dict is valid a...
loadingLongWaitCopyByLocale	object	否	Locale-keyed line shown once the wait exceeds `loading_long_wait_threshold_seconds`,

欄位	類型	必填	說明
			shaped {locale: text}. Written in the brand character voice for the animation mode, but applies to both modes. Empt...
loadingLongWaitThresholdSeconds	integer	否	How long a single reply must be pending before the long-wait copy appears.
loadingAnimationUseSharedAsset	boolean	否	True (default) means every stage plays `loading_animation_shared_asset_url`, so the admin only uploads once. False expands per-stage assets, each falling back to the shared asset when its own slot is ...
loadingAnimationSharedAssetUrl	string (uri)	否	
loadingAnimationAssetUrlsByStage	object	否	Shaped {stage: url} keyed by LoadingStage. Only consulted when `loading_animation_use_shared_asset` is False; a missing stage falls back to the shared asset.
loadingTypingShowCopy	boolean	否	Only affects the first "typing" stage. True (default, the pre-existing behavior) shows the typing-stage copy next to the pre-first-char animation/dot; False plays only the animation with no text line....
toolCardRunningIconUrl	string (uri)	否	
toolCardCompletedIconUrl	string (uri)	否	

請求結構範例

```
{
  "avatar"?: string (uri) // 非必填
  "logo"?: string (uri) // 非必填
  "description"?: string // 非必填
  "cover"?: string (uri) // 非必填
  "backUrl"?: string // 非必填
  "isActive"?: boolean // 非必填
  "theme"?: { // 非必填
  {
    "primaryColor"?: string // 非必填
    "navbarTextColor"?: string // 非必填
    "conversationBackgroundColor"?: string // 非必填
    "chatbotMessageTextColor"?: string // 非必填
    "userMessageTextColor"?: string // 非必填
    "chatbotMessageBackgroundColor"?: string // 非必填
    "userMessageBackgroundColor"?: string // 非必填
    "chatbotMessageBackgroundShadowEnabled"?: boolean // 非必填
```

```
    "userMessageBackgroundShadowEnabled"?: boolean // 非必填
    "chatbotMessageGradientEnabled"?: boolean // 非必填
    "userMessageGradientEnabled"?: boolean // 非必填
  }
  }
  "darkTheme"?: { // 非必填
  {
    "primaryColor"?: string // 非必填
    "navbarTextColor"?: string // 非必填
    "conversationBackgroundColor"?: string // 非必填
    "chatbotMessageTextColor"?: string // 非必填
    "userMessageTextColor"?: string // 非必填
    "chatbotMessageBackgroundColor"?: string // 非必填
    "userMessageBackgroundColor"?: string // 非必填
    "chatbotMessageBackgroundShadowEnabled"?: boolean // 非必填
    "userMessageBackgroundShadowEnabled"?: boolean // 非必填
    "chatbotMessageGradientEnabled"?: boolean // 非必填
    "userMessageGradientEnabled"?: boolean // 非必填
  }
  }
  "enableFileUpload"?: boolean // 非必填
  "enableDisplayCitations"?: boolean // 非必填
  "toolDisplayMode"?: string (enum: full, compact, hidden) // * `full` - Full
* `compact` - Compact
* `hidden` - Hidden (非必填)
  "enableAskOptionButtons"?: boolean // 開啟後 ask_user_question 選項以按鈕列浮在輸入框上方（輸入框保持可用）；關閉則維持現行覆蓋式面板。灰度開關，可隨時關閉回退。 (非必填)
  "enableConversationHandoff"?: boolean // 開啟後此對話平台的 webchat 顯示交接 UI（提示條、摘要卡、接續按鈕）並註冊交接工具；仍受系統設定的全域交接開關管制（全域關＝一律關）。MaiGPT 免此開關恆顯示。底部的上下文使用量百分比條另由「顯示上下文使用量」控制。預設關閉，客戶對外 webchat 不會看到任何交接 UI；灰度開關，關閉即回退、不需退版。 (非必填)
  "enableDisplayContextUsage"?: boolean // 開啟後此對話平台的 webchat 在輸入框下方顯示上下文使用量百分比條。與對話交接互相獨立：不受交接開關（含全域交接開關）影響，也不影響交接提示條。MaiGPT 免此開關恆顯示。預設關閉；關閉即回退、不需退版。 (非必填)
  "enableDisplayThinking"?: boolean // 非必填
  "enableUserThinkingControl"?: boolean // 非必填
  "enableDisplayQueryMetadata"?: boolean // 非必填
  "enableDisplayHookMarkers"?: boolean // 非必填
  "hookMarkerTextInputModify"?: string // 非必填
  "hookMarkerTextOutputModify"?: string // 非必填
  "hookMarkerTextInputBlock"?: string // 非必填
  "hookMarkerTextOutputBlock"?: string // 非必填
  "enableShareConversation"?: boolean // 非必填
  "enableLocation"?: boolean // 非必填
  "enableShowPoweredBy"?: boolean // 非必填
  "poweredByLogo"?: string (uri) // 非必填
  "enableAnonymous"?: boolean // 非必填
  "enableDisplayPreviousConversation"?: boolean // 非必填
  "enableDisplayConversationHistory"?: boolean // 非必填
  "enableConversationTimer"?: boolean // 非必填
  "conversationTimerDuration"?: integer // 計時器逾時時長，範圍 3-60 分鐘 (非必填)
  "enableAutoNewConversationOnTimeout"?: boolean // 非必填
  "enableSatisfactionSurvey"?: boolean // 非必填
  "satisfactionSurveyDelayMinutes"?: integer // 最後一則 AI 回覆後幾分鐘彈出問卷，範圍 1-60 分鐘 (非必填)
  "satisfactionSurveyPrompt"?: string // 自訂問卷標題文字，留空則使用前端多語系預設文字 (非必填)
```

```
  "enableThemeModeToggle"?: boolean // 非必填
  "enableDisplayFontSizeSwitch"?: boolean // 非必填
  "defaultThemeMode"?:  // 非必填
  {
  }
  "enableDownloadCitations"?: boolean // 非必填
  "customDomain"?:  // 非必填
  {
    "domain": string
  }
  "enableDisplayChatbotAvatar"?: boolean // 非必填
  "enableDisplayChatbotName"?: boolean // 非必填
  "buttonIcon"?: string (uri) // 非必填
  "conversationStartersDisplayCount"?: integer // 非必填
  "preChatFormEnabled"?: boolean // 非必填
  "preChatFormFields"?: object // 非必填
  "preChatFormTitle"?: object // 非必填
  "preChatFormSubtitle"?: object // 非必填
  "loadingDisplayMode"?:  // Waiting-experience style. `narrative` shows per-stage copy;
`brand_animation` plays the uploaded asset and hides every system narration line. Defaults to
`narrative`, which with no copy configured behaves exactly as before this field existed.

* `narrative` - Narrative copy
* `brand_animation` - Brand animation (非必填)
  {
  }
  "loadingStageCopyByLocale"?: object // Locale-keyed per-stage waiting copy, shaped {locale:
{stage: text}} where stage is one of LoadingStage. An absent locale or stage falls back to
the built-in copy, so a partially filled dict is valid and never blocks a reply. (非必填)
  "loadingLongWaitCopyByLocale"?: object // Locale-keyed line shown once the wait exceeds
`loading_long_wait_threshold_seconds`, shaped {locale: text}. Written in the brand character
voice for the animation mode, but applies to both modes. Empty means no long-wait line is
shown. (非必填)
  "loadingLongWaitThresholdSeconds"?: integer // How long a single reply must be pending
before the long-wait copy appears. (非必填)
  "loadingAnimationUseSharedAsset"?: boolean // True (default) means every stage plays
`loading_animation_shared_asset_url`, so the admin only uploads once. False expands per-stage
assets, each falling back to the shared asset when its own slot is empty. (非必填)
  "loadingAnimationSharedAssetUrl"?: string (uri) // 非必填
  "loadingAnimationAssetUrlsByStage"?: object // Shaped {stage: url} keyed by LoadingStage.
Only consulted when `loading_animation_use_shared_asset` is False; a missing stage falls back
to the shared asset. (非必填)
  "loadingTypingShowCopy"?: boolean // Only affects the first "typing" stage. True (default,
the pre-existing behavior) shows the typing-stage copy next to the pre-first-char
animation/dot; False plays only the animation with no text line. Thinking / analyzing / long-
wait stages are unaffected. (非必填)
  "toolCardRunningIconUrl"?: string (uri) // 非必填
  "toolCardCompletedIconUrl"?: string (uri) // 非必填
}
```

請求範例值

```
{
  "avatar": "https://example.com/file.jpg",
```

```
  "logo": "https://example.com/file.jpg",
  "description": "範例字串",
  "cover": "https://example.com/file.jpg",
  "backUrl": "範例字串",
  "isActive": true,
  "theme": {
    "primaryColor": "範例字串",
    "navbarTextColor": "範例字串",
    "conversationBackgroundColor": "範例字串",
    "chatbotMessageTextColor": "範例字串",
    "userMessageTextColor": "範例字串",
    "chatbotMessageBackgroundColor": "範例字串",
    "userMessageBackgroundColor": "範例字串",
    "chatbotMessageBackgroundShadowEnabled": true,
    "userMessageBackgroundShadowEnabled": true,
    "chatbotMessageGradientEnabled": true,
    "userMessageGradientEnabled": true
  },
  "darkTheme": {
    "primaryColor": "範例字串",
    "navbarTextColor": "範例字串",
    "conversationBackgroundColor": "範例字串",
    "chatbotMessageTextColor": "範例字串",
    "userMessageTextColor": "範例字串",
    "chatbotMessageBackgroundColor": "範例字串",
    "userMessageBackgroundColor": "範例字串",
    "chatbotMessageBackgroundShadowEnabled": true,
    "userMessageBackgroundShadowEnabled": true,
    "chatbotMessageGradientEnabled": true,
    "userMessageGradientEnabled": true
  },
  "enableFileUpload": true,
  "enableDisplayCitations": true,
  "toolDisplayMode": "full",
  "enableAskOptionButtons": true,
  "enableConversationHandoff": true,
  "enableDisplayContextUsage": true,
  "enableDisplayThinking": true,
  "enableUserThinkingControl": true,
  "enableDisplayQueryMetadata": true,
  "enableDisplayHookMarkers": true,
  "hookMarkerTextInputModify": "範例字串",
  "hookMarkerTextOutputModify": "範例字串",
  "hookMarkerTextInputBlock": "範例字串",
  "hookMarkerTextOutputBlock": "範例字串",
  "enableShareConversation": true,
  "enableLocation": true,
  "enableShowPoweredBy": true,
  "poweredByLogo": "https://example.com/file.jpg",
  "enableAnonymous": true,
  "enableDisplayPreviousConversation": true,
  "enableDisplayConversationHistory": true,
  "enableConversationTimer": true,
  "conversationTimerDuration": 123,
  "enableAutoNewConversationOnTimeout": true,
  "enableSatisfactionSurvey": true,
```

```
  "satisfactionSurveyDelayMinutes": 123,
  "satisfactionSurveyPrompt": "範例字串",
  "enableThemeModeToggle": true,
  "enableDisplayFontSizeSwitch": true,
  "defaultThemeMode": {},
  "enableDownloadCitations": true,
  "customDomain": {
    "domain": "範例字串"
  },
  "enableDisplayChatbotAvatar": true,
  "enableDisplayChatbotName": true,
  "buttonIcon": "https://example.com/file.jpg",
  "conversationStartersDisplayCount": 123,
  "preChatFormEnabled": true,
  "preChatFormFields": null,
  "preChatFormTitle": null,
  "preChatFormSubtitle": null,
  "loadingDisplayMode": {},
  "loadingStageCopyByLocale": null,
  "loadingLongWaitCopyByLocale": null,
  "loadingLongWaitThresholdSeconds": 123,
  "loadingAnimationUseSharedAsset": true,
  "loadingAnimationSharedAssetUrl": "https://example.com/file.jpg",
  "loadingAnimationAssetUrlsByStage": null,
  "loadingTypingShowCopy": true,
  "toolCardRunningIconUrl": "https://example.com/file.jpg",
  "toolCardCompletedIconUrl": "https://example.com/file.jpg"
}
```


程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X PATCH "https://api.maiagent.ai/api/v1/web-chats/550e8400-e29b-41d4-a716-
446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "avatar": "https://example.com/file.jpg",
    "logo": "https://example.com/file.jpg",
    "description": "範例字串",
    "cover": "https://example.com/file.jpg",
    "backUrl": "範例字串",
    "isActive": true,
    "theme": {
      "primaryColor": "範例字串",
      "navbarTextColor": "範例字串",
      "conversationBackgroundColor": "範例字串",
      "chatbotMessageTextColor": "範例字串",
      "userMessageTextColor": "範例字串",
      "chatbotMessageBackgroundColor": "範例字串",
      "userMessageBackgroundColor": "範例字串",
      "chatbotMessageBackgroundShadowEnabled": true,
      "userMessageBackgroundShadowEnabled": true,
      "chatbotMessageGradientEnabled": true,
      "userMessageGradientEnabled": true
    },
    "darkTheme": {
      "primaryColor": "範例字串",
      "navbarTextColor": "範例字串",
      "conversationBackgroundColor": "範例字串",
      "chatbotMessageTextColor": "範例字串",
      "userMessageTextColor": "範例字串",
      "chatbotMessageBackgroundColor": "範例字串",
      "userMessageBackgroundColor": "範例字串",
      "chatbotMessageBackgroundShadowEnabled": true,
      "userMessageBackgroundShadowEnabled": true,
      "chatbotMessageGradientEnabled": true,
      "userMessageGradientEnabled": true
    },
    "enableFileUpload": true,
    "enableDisplayCitations": true,
    "toolDisplayMode": "full",
    "enableAskOptionButtons": true,
    "enableConversationHandoff": true,
    "enableDisplayContextUsage": true,
    "enableDisplayThinking": true,
    "enableUserThinkingControl": true,
    "enableDisplayQueryMetadata": true,
```

```
      "enableDisplayHookMarkers": true,
      "hookMarkerTextInputModify": "範例字串",
      "hookMarkerTextOutputModify": "範例字串",
      "hookMarkerTextInputBlock": "範例字串",
      "hookMarkerTextOutputBlock": "範例字串",
      "enableShareConversation": true,
      "enableLocation": true,
      "enableShowPoweredBy": true,
      "poweredByLogo": "https://example.com/file.jpg",
      "enableAnonymous": true,
      "enableDisplayPreviousConversation": true,
      "enableDisplayConversationHistory": true,
      "enableConversationTimer": true,
      "conversationTimerDuration": 123,
      "enableAutoNewConversationOnTimeout": true,
      "enableSatisfactionSurvey": true,
      "satisfactionSurveyDelayMinutes": 123,
      "satisfactionSurveyPrompt": "範例字串",
      "enableThemeModeToggle": true,
      "enableDisplayFontSizeSwitch": true,
      "defaultThemeMode": {},
      "enableDownloadCitations": true,
      "customDomain": {
        "domain": "範例字串"
      },
      "enableDisplayChatbotAvatar": true,
      "enableDisplayChatbotName": true,
      "buttonIcon": "https://example.com/file.jpg",
      "conversationStartersDisplayCount": 123,
      "preChatFormEnabled": true,
      "preChatFormFields": null,
      "preChatFormTitle": null,
      "preChatFormSubtitle": null,
      "loadingDisplayMode": {},
      "loadingStageCopyByLocale": null,
      "loadingLongWaitCopyByLocale": null,
      "loadingLongWaitThresholdSeconds": 123,
      "loadingAnimationUseSharedAsset": true,
      "loadingAnimationSharedAssetUrl": "https://example.com/file.jpg",
      "loadingAnimationAssetUrlsByStage": null,
      "loadingTypingShowCopy": true,
      "toolCardRunningIconUrl": "https://example.com/file.jpg",
      "toolCardCompletedIconUrl": "https://example.com/file.jpg"
    }'

  # 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// 請求內容 (payload)
const data = {
    "avatar": "https://example.com/file.jpg",
    "logo": "https://example.com/file.jpg",
    "description": "範例字串",
    "cover": "https://example.com/file.jpg",
    "backUrl": "範例字串",
    "isActive": true,
    "theme": {
      "primaryColor": "範例字串",
      "navbarTextColor": "範例字串",
      "conversationBackgroundColor": "範例字串",
      "chatbotMessageTextColor": "範例字串",
      "userMessageTextColor": "範例字串",
      "chatbotMessageBackgroundColor": "範例字串",
      "userMessageBackgroundColor": "範例字串",
      "chatbotMessageBackgroundShadowEnabled": true,
      "userMessageBackgroundShadowEnabled": true,
      "chatbotMessageGradientEnabled": true,
      "userMessageGradientEnabled": true
    },
    "darkTheme": {
      "primaryColor": "範例字串",
      "navbarTextColor": "範例字串",
      "conversationBackgroundColor": "範例字串",
      "chatbotMessageTextColor": "範例字串",
      "userMessageTextColor": "範例字串",
      "chatbotMessageBackgroundColor": "範例字串",
      "userMessageBackgroundColor": "範例字串",
      "chatbotMessageBackgroundShadowEnabled": true,
      "userMessageBackgroundShadowEnabled": true,
      "chatbotMessageGradientEnabled": true,
      "userMessageGradientEnabled": true
    },
    "enableFileUpload": true,
    "enableDisplayCitations": true,
    "toolDisplayMode": "full",
    "enableAskOptionButtons": true,
    "enableConversationHandoff": true,
    "enableDisplayContextUsage": true,
```

```
    "enableDisplayThinking": true,
    "enableUserThinkingControl": true,
    "enableDisplayQueryMetadata": true,
    "enableDisplayHookMarkers": true,
    "hookMarkerTextInputModify": "範例字串",
    "hookMarkerTextOutputModify": "範例字串",
    "hookMarkerTextInputBlock": "範例字串",
    "hookMarkerTextOutputBlock": "範例字串",
    "enableShareConversation": true,
    "enableLocation": true,
    "enableShowPoweredBy": true,
    "poweredByLogo": "https://example.com/file.jpg",
    "enableAnonymous": true,
    "enableDisplayPreviousConversation": true,
    "enableDisplayConversationHistory": true,
    "enableConversationTimer": true,
    "conversationTimerDuration": 123,
    "enableAutoNewConversationOnTimeout": true,
    "enableSatisfactionSurvey": true,
    "satisfactionSurveyDelayMinutes": 123,
    "satisfactionSurveyPrompt": "範例字串",
    "enableThemeModeToggle": true,
    "enableDisplayFontSizeSwitch": true,
    "defaultThemeMode": {},
    "enableDownloadCitations": true,
    "customDomain": {
      "domain": "範例字串"
    },
    "enableDisplayChatbotAvatar": true,
    "enableDisplayChatbotName": true,
    "buttonIcon": "https://example.com/file.jpg",
    "conversationStartersDisplayCount": 123,
    "preChatFormEnabled": true,
    "preChatFormFields": null,
    "preChatFormTitle": null,
    "preChatFormSubtitle": null,
    "loadingDisplayMode": {},
    "loadingStageCopyByLocale": null,
    "loadingLongWaitCopyByLocale": null,
    "loadingLongWaitThresholdSeconds": 123,
    "loadingAnimationUseSharedAsset": true,
    "loadingAnimationSharedAssetUrl": "https://example.com/file.jpg",
    "loadingAnimationAssetUrlsByStage": null,
    "loadingTypingShowCopy": true,
    "toolCardRunningIconUrl": "https://example.com/file.jpg",
    "toolCardCompletedIconUrl": "https://example.com/file.jpg"
  };

axios.patch("https://api.maiagent.ai/api/v1/web-chats/550e8400-e29b-41d4-a716-
446655440000/", data, config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
```

```
    console.error(error.response?.data || error.message);
});
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/web-chats/550e8400-e29b-41d4-a716-446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# 請求內容 (payload)
data = {
    "avatar": "https://example.com/file.jpg",
    "logo": "https://example.com/file.jpg",
    "description": "範例字串",
    "cover": "https://example.com/file.jpg",
    "backUrl": "範例字串",
    "isActive": True,
    "theme": {
        "primaryColor": "範例字串",
        "navbarTextColor": "範例字串",
        "conversationBackgroundColor": "範例字串",
        "chatbotMessageTextColor": "範例字串",
        "userMessageTextColor": "範例字串",
        "chatbotMessageBackgroundColor": "範例字串",
        "userMessageBackgroundColor": "範例字串",
        "chatbotMessageBackgroundShadowEnabled": True,
        "userMessageBackgroundShadowEnabled": True,
        "chatbotMessageGradientEnabled": True,
        "userMessageGradientEnabled": True
    },
    "darkTheme": {
        "primaryColor": "範例字串",
        "navbarTextColor": "範例字串",
        "conversationBackgroundColor": "範例字串",
        "chatbotMessageTextColor": "範例字串",
        "userMessageTextColor": "範例字串",
        "chatbotMessageBackgroundColor": "範例字串",
        "userMessageBackgroundColor": "範例字串",
        "chatbotMessageBackgroundShadowEnabled": True,
        "userMessageBackgroundShadowEnabled": True,
        "chatbotMessageGradientEnabled": True,
        "userMessageGradientEnabled": True
    },
    "enableFileUpload": True,
    "enableDisplayCitations": True,
    "toolDisplayMode": "full",
    "enableAskOptionButtons": True,
    "enableConversationHandoff": True,
    "enableDisplayContextUsage": True,
    "enableDisplayThinking": True,
    "enableUserThinkingControl": True,
```

```
    "enableDisplayQueryMetadata": True,
    "enableDisplayHookMarkers": True,
    "hookMarkerTextInputModify": "範例字串",
    "hookMarkerTextOutputModify": "範例字串",
    "hookMarkerTextInputBlock": "範例字串",
    "hookMarkerTextOutputBlock": "範例字串",
    "enableShareConversation": True,
    "enableLocation": True,
    "enableShowPoweredBy": True,
    "poweredByLogo": "https://example.com/file.jpg",
    "enableAnonymous": True,
    "enableDisplayPreviousConversation": True,
    "enableDisplayConversationHistory": True,
    "enableConversationTimer": True,
    "conversationTimerDuration": 123,
    "enableAutoNewConversationOnTimeout": True,
    "enableSatisfactionSurvey": True,
    "satisfactionSurveyDelayMinutes": 123,
    "satisfactionSurveyPrompt": "範例字串",
    "enableThemeModeToggle": True,
    "enableDisplayFontSizeSwitch": True,
    "defaultThemeMode": {},
    "enableDownloadCitations": True,
    "customDomain": {
        "domain": "範例字串"
    },
    "enableDisplayChatbotAvatar": True,
    "enableDisplayChatbotName": True,
    "buttonIcon": "https://example.com/file.jpg",
    "conversationStartersDisplayCount": 123,
    "preChatFormEnabled": True,
    "preChatFormFields": None,
    "preChatFormTitle": None,
    "preChatFormSubtitle": None,
    "loadingDisplayMode": {},
    "loadingStageCopyByLocale": None,
    "loadingLongWaitCopyByLocale": None,
    "loadingLongWaitThresholdSeconds": 123,
    "loadingAnimationUseSharedAsset": True,
    "loadingAnimationSharedAssetUrl": "https://example.com/file.jpg",
    "loadingAnimationAssetUrlsByStage": None,
    "loadingTypingShowCopy": True,
    "toolCardRunningIconUrl": "https://example.com/file.jpg",
    "toolCardCompletedIconUrl": "https://example.com/file.jpg"
}

response = requests.patch(url, json=data, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->patch("https://api.maiagent.ai/api/v1/web-chats/550e8400-e29b-41d4-a716-446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'avatar' => 'https://example.com/file.jpg',
            'logo' => 'https://example.com/file.jpg',
            'description' => '範例字串',
            'cover' => 'https://example.com/file.jpg',
            'backUrl' => '範例字串',
            'isActive' => true,
            'theme' => [
                'primaryColor' => '範例字串',
                'navbarTextColor' => '範例字串',
                'conversationBackgroundColor' => '範例字串',
                'chatbotMessageTextColor' => '範例字串',
                'userMessageTextColor' => '範例字串',
                'chatbotMessageBackgroundColor' => '範例字串',
                'userMessageBackgroundColor' => '範例字串',
                'chatbotMessageBackgroundShadowEnabled' => true,
                'userMessageBackgroundShadowEnabled' => true,
                'chatbotMessageGradientEnabled' => true,
                'userMessageGradientEnabled' => true
            ],
            'darkTheme' => [
                'primaryColor' => '範例字串',
                'navbarTextColor' => '範例字串',
                'conversationBackgroundColor' => '範例字串',
                'chatbotMessageTextColor' => '範例字串',
                'userMessageTextColor' => '範例字串',
                'chatbotMessageBackgroundColor' => '範例字串',
                'userMessageBackgroundColor' => '範例字串',
                'chatbotMessageBackgroundShadowEnabled' => true,
                'userMessageBackgroundShadowEnabled' => true,
                'chatbotMessageGradientEnabled' => true,
                'userMessageGradientEnabled' => true
            ],
            'enableFileUpload' => true,
            'enableDisplayCitations' => true,
            'toolDisplayMode' => 'full',
            'enableAskOptionButtons' => true,
            'enableConversationHandoff' => true,
```

```
                'enableDisplayContextUsage' => true,
                'enableDisplayThinking' => true,
                'enableUserThinkingControl' => true,
                'enableDisplayQueryMetadata' => true,
                'enableDisplayHookMarkers' => true,
                'hookMarkerTextInputModify' => '範例字串',
                'hookMarkerTextOutputModify' => '範例字串',
                'hookMarkerTextInputBlock' => '範例字串',
                'hookMarkerTextOutputBlock' => '範例字串',
                'enableShareConversation' => true,
                'enableLocation' => true,
                'enableShowPoweredBy' => true,
                'poweredByLogo' => 'https://example.com/file.jpg',
                'enableAnonymous' => true,
                'enableDisplayPreviousConversation' => true,
                'enableDisplayConversationHistory' => true,
                'enableConversationTimer' => true,
                'conversationTimerDuration' => 123,
                'enableAutoNewConversationOnTimeout' => true,
                'enableSatisfactionSurvey' => true,
                'satisfactionSurveyDelayMinutes' => 123,
                'satisfactionSurveyPrompt' => '範例字串',
                'enableThemeModeToggle' => true,
                'enableDisplayFontSizeSwitch' => true,
                'defaultThemeMode' => new \stdClass(),
                'enableDownloadCitations' => true,
                'customDomain' => [
                    'domain' => '範例字串'
                ],
                'enableDisplayChatbotAvatar' => true,
                'enableDisplayChatbotName' => true,
                'buttonIcon' => 'https://example.com/file.jpg',
                'conversationStartersDisplayCount' => 123,
                'preChatFormEnabled' => true,
                'preChatFormFields' => null,
                'preChatFormTitle' => null,
                'preChatFormSubtitle' => null,
                'loadingDisplayMode' => new \stdClass(),
                'loadingStageCopyByLocale' => null,
                'loadingLongWaitCopyByLocale' => null,
                'loadingLongWaitThresholdSeconds' => 123,
                'loadingAnimationUseSharedAsset' => true,
                'loadingAnimationSharedAssetUrl' => 'https://example.com/file.jpg',
                'loadingAnimationAssetUrlsByStage' => null,
                'loadingTypingShowCopy' => true,
                'toolCardRunningIconUrl' => 'https://example.com/file.jpg',
                'toolCardCompletedIconUrl' => 'https://example.com/file.jpg'
            ]
        ]);

        $data = json_decode($response->getBody(), true);
        echo "成功取得回應:\n";
        print_r($data);
    } catch (Exception $e) {
        echo '請求發生錯誤: ' . $e->getMessage();
```

```
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
{
  "id": string (uuid)
  "name": string
  "avatar"?: string (uri) // 非必填
  "logo"?: string (uri) // 非必填
  "description"?: string // 非必填
  "cover"?: string (uri) // 非必填
  "backUrl"?: string // 非必填
  "isActive"?: boolean // 非必填
  "enableSpeech": boolean
  "displayConversationStarters": [
    string
  ]
  "theme": {
  {
    "primaryColor"?: string // 非必填
    "navbarTextColor"?: string // 非必填
    "conversationBackgroundColor"?: string // 非必填
    "chatbotMessageTextColor"?: string // 非必填
    "userMessageTextColor"?: string // 非必填
    "chatbotMessageBackgroundColor"?: string // 非必填
    "userMessageBackgroundColor"?: string // 非必填
    "chatbotMessageBackgroundShadowEnabled"?: boolean // 非必填
    "userMessageBackgroundShadowEnabled"?: boolean // 非必填
    "chatbotMessageGradientEnabled"?: boolean // 非必填
    "userMessageGradientEnabled"?: boolean // 非必填
  }
  }
  "darkTheme": {
  {
    "primaryColor"?: string // 非必填
    "navbarTextColor"?: string // 非必填
    "conversationBackgroundColor"?: string // 非必填
    "chatbotMessageTextColor"?: string // 非必填
    "userMessageTextColor"?: string // 非必填
    "chatbotMessageBackgroundColor"?: string // 非必填
    "userMessageBackgroundColor"?: string // 非必填
    "chatbotMessageBackgroundShadowEnabled"?: boolean // 非必填
```

```
    "userMessageBackgroundShadowEnabled"?: boolean // 非必填
    "chatbotMessageGradientEnabled"?: boolean // 非必填
    "userMessageGradientEnabled"?: boolean // 非必填
  }
  }
  "enableFileUpload"?: boolean // 非必填
  "enableDisplayCitations"?: boolean // 非必填
  "toolDisplayMode"?: string (enum: full, compact, hidden) // * `full` - Full
* `compact` - Compact
* `hidden` - Hidden (非必填)
  "enableAskOptionButtons"?: boolean // 開啟後 ask_user_question 選項以按鈕列浮在輸入框上方（輸入框保持可用）；關閉則維持現行覆蓋式面板。灰度開關，可隨時關閉回退。 (非必填)
  "enableConversationHandoff"?: boolean // 開啟後此對話平台的 webchat 顯示交接 UI（提示條、摘要卡、接續按鈕）並註冊交接工具；仍受系統設定的全域交接開關管制（全域關＝一律關）。MaiGPT 免此開關恆顯示。底部的上下文使用量百分比條另由「顯示上下文使用量」控制。預設關閉，客戶對外 webchat 不會看到任何交接 UI；灰度開關，關閉即回退、不需退版。 (非必填)
  "enableDisplayContextUsage"?: boolean // 開啟後此對話平台的 webchat 在輸入框下方顯示上下文使用量百分比條。與對話交接互相獨立：不受交接開關（含全域交接開關）影響，也不影響交接提示條。MaiGPT 免此開關恆顯示。預設關閉；關閉即回退、不需退版。 (非必填)
  "enableDisplayThinking"?: boolean // 非必填
  "enableUserThinkingControl"?: boolean // 非必填
  "enableDisplayQueryMetadata"?: boolean // 非必填
  "enableDisplayHookMarkers"?: boolean // 非必填
  "hookMarkerTextInputModify"?: string // 非必填
  "hookMarkerTextOutputModify"?: string // 非必填
  "hookMarkerTextInputBlock"?: string // 非必填
  "hookMarkerTextOutputBlock"?: string // 非必填
  "enableShareConversation"?: boolean // 非必填
  "enableLocation"?: boolean // 非必填
  "enableShowPoweredBy"?: boolean // 非必填
  "poweredByLogo"?: string (uri) // 非必填
  "enableAnonymous"?: boolean // 非必填
  "enableDisplayPreviousConversation"?: boolean // 非必填
  "enableDisplayConversationHistory"?: boolean // 非必填
  "enableConversationTimer"?: boolean // 非必填
  "conversationTimerDuration"?: integer // 計時器逾時時長，範圍 3-60 分鐘 (非必填)
  "enableAutoNewConversationOnTimeout"?: boolean // 非必填
  "enableSatisfactionSurvey"?: boolean // 非必填
  "satisfactionSurveyDelayMinutes"?: integer // 最後一則 AI 回覆後幾分鐘彈出問卷，範圍 1-60 分鐘 (非必填)
  "satisfactionSurveyPrompt"?: string // 自訂問卷標題文字，留空則使用前端多語系預設文字 (非必填)
  "accessType":
  {
  }
  "enableThemeModeToggle"?: boolean // 非必填
  "enableDisplayFontSizeSwitch"?: boolean // 非必填
  "defaultThemeMode"?:  // 非必填
  {
  }
  "enableDownloadCitations"?: boolean // 非必填
  "customDomain"?:  // 非必填
  {
    "id": string (uuid)
    "domain": string
    "status":
    {
```

```
    }
  }
  "enableDisplayChatbotAvatar"?: boolean // 非必填
  "enableDisplayChatbotName"?: boolean // 非必填
  "buttonIcon"?: string (uri) // 非必填
  "enableCodeInterpreter": boolean // Read enable_code_interpreter from the inbox's chatbot.
  "voiceAgentEnabled": boolean // Whether the bound chatbot has the voice agent turned on
(read-only)
  "conversationStartersDisplayCount"?: integer // 非必填
  "includeGreetingInContext": boolean // When enabled, the conversation greeting and the
numbered conversation starters (in configured order, unshuffled and untruncated) are injected
into the LLM context so the agent can resolve short replies like "1" to the matching starter
option.
  "tools": [ // Expose chatbot tools to SDK for the tool_mask selector.

Name resolution prefers ``display_name`` (set on MCP tools, where
``name`` is null) and falls back to ``name`` for API tools where
``display_name`` is null. Tools missing both are skipped — SDK
should never show an unnamed tool to a contact. Quick Menu tools are
static input-bar UI, never an LLM tool, so masking one is meaningless.
    object
  ]
  "preChatFormEnabled"?: boolean // 非必填
  "preChatFormFields"?: object // 非必填
  "preChatFormTitle"?: object // 非必填
  "preChatFormSubtitle"?: object // 非必填
  "loadingDisplayMode"?:  // Waiting-experience style. `narrative` shows per-stage copy;
`brand_animation` plays the uploaded asset and hides every system narration line. Defaults to
`narrative`, which with no copy configured behaves exactly as before this field existed.

* `narrative` - Narrative copy
* `brand_animation` - Brand animation (非必填)
  {
  }
  "loadingStageCopyByLocale"?: object // Locale-keyed per-stage waiting copy, shaped {locale:
{stage: text}} where stage is one of LoadingStage. An absent locale or stage falls back to
the built-in copy, so a partially filled dict is valid and never blocks a reply. (非必填)
  "loadingLongWaitCopyByLocale"?: object // Locale-keyed line shown once the wait exceeds
`loading_long_wait_threshold_seconds`, shaped {locale: text}. Written in the brand character
voice for the animation mode, but applies to both modes. Empty means no long-wait line is
shown. (非必填)
  "loadingLongWaitThresholdSeconds"?: integer // How long a single reply must be pending
before the long-wait copy appears. (非必填)
  "loadingAnimationUseSharedAsset"?: boolean // True (default) means every stage plays
`loading_animation_shared_asset_url`, so the admin only uploads once. False expands per-stage
assets, each falling back to the shared asset when its own slot is empty. (非必填)
  "loadingAnimationSharedAssetUrl"?: string (uri) // 非必填
  "loadingAnimationAssetUrlsByStage"?: object // Shaped {stage: url} keyed by LoadingStage.
Only consulted when `loading_animation_use_shared_asset` is False; a missing stage falls back
to the shared asset. (非必填)
  "loadingTypingShowCopy"?: boolean // Only affects the first "typing" stage. True (default,
the pre-existing behavior) shows the typing-stage copy next to the pre-first-char
animation/dot; False plays only the animation with no text line. Thinking / analyzing / long-
wait stages are unaffected. (非必填)
  "toolCardRunningIconUrl"?: string (uri) // 非必填
  "toolCardCompletedIconUrl"?: string (uri) // 非必填
```

```
  "inbox": object
  "quickMenu": object // Mounted Quick Menu Agent UI config for the web chat input bar; null
when absent (read-only)
}
```

回應範例值

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "name": "回應字串",
  "avatar": "https://example.com/file.jpg",
  "logo": "https://example.com/file.jpg",
  "description": "回應字串",
  "cover": "https://example.com/file.jpg",
  "backUrl": "回應字串",
  "isActive": false,
  "enableSpeech": false,
  "displayConversationStarters": [
    "回應字串"
  ],
  "theme": {
    "primaryColor": "回應字串",
    "navbarTextColor": "回應字串",
    "conversationBackgroundColor": "回應字串",
    "chatbotMessageTextColor": "回應字串",
    "userMessageTextColor": "回應字串",
    "chatbotMessageBackgroundColor": "回應字串",
    "userMessageBackgroundColor": "回應字串",
    "chatbotMessageBackgroundShadowEnabled": false,
    "userMessageBackgroundShadowEnabled": false,
    "chatbotMessageGradientEnabled": false,
    "userMessageGradientEnabled": false
  },
  "darkTheme": {
    "primaryColor": "回應字串",
    "navbarTextColor": "回應字串",
    "conversationBackgroundColor": "回應字串",
    "chatbotMessageTextColor": "回應字串",
    "userMessageTextColor": "回應字串",
    "chatbotMessageBackgroundColor": "回應字串",
    "userMessageBackgroundColor": "回應字串",
    "chatbotMessageBackgroundShadowEnabled": false,
    "userMessageBackgroundShadowEnabled": false,
    "chatbotMessageGradientEnabled": false,
    "userMessageGradientEnabled": false
  },
  "enableFileUpload": false,
  "enableDisplayCitations": false,
  "toolDisplayMode": "full",
  "enableAskOptionButtons": false,
  "enableConversationHandoff": false,
  "enableDisplayContextUsage": false,
  "enableDisplayThinking": false,
  "enableUserThinkingControl": false,
```

```
  "enableDisplayQueryMetadata": false,
  "enableDisplayHookMarkers": false,
  "hookMarkerTextInputModify": "回應字串",
  "hookMarkerTextOutputModify": "回應字串",
  "hookMarkerTextInputBlock": "回應字串",
  "hookMarkerTextOutputBlock": "回應字串",
  "enableShareConversation": false,
  "enableLocation": false,
  "enableShowPoweredBy": false,
  "poweredByLogo": "https://example.com/file.jpg",
  "enableAnonymous": false,
  "enableDisplayPreviousConversation": false,
  "enableDisplayConversationHistory": false,
  "enableConversationTimer": false,
  "conversationTimerDuration": 456,
  "enableAutoNewConversationOnTimeout": false,
  "enableSatisfactionSurvey": false,
  "satisfactionSurveyDelayMinutes": 456,
  "satisfactionSurveyPrompt": "回應字串",
  "accessType": {},
  "enableThemeModeToggle": false,
  "enableDisplayFontSizeSwitch": false,
  "defaultThemeMode": {},
  "enableDownloadCitations": false,
  "customDomain": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "domain": "回應字串",
    "status": {}
  },
  "enableDisplayChatbotAvatar": false,
  "enableDisplayChatbotName": false,
  "buttonIcon": "https://example.com/file.jpg",
  "enableCodeInterpreter": false,
  "voiceAgentEnabled": false,
  "conversationStartersDisplayCount": 456,
  "includeGreetingInContext": false,
  "tools": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "回應範例名稱",
      "description": "回應範例描述"
    }
  ],
  "preChatFormEnabled": false,
  "preChatFormFields": null,
  "preChatFormTitle": null,
  "preChatFormSubtitle": null,
  "loadingDisplayMode": {},
  "loadingStageCopyByLocale": null,
  "loadingLongWaitCopyByLocale": null,
  "loadingLongWaitThresholdSeconds": 456,
  "loadingAnimationUseSharedAsset": false,
  "loadingAnimationSharedAssetUrl": "https://example.com/file.jpg",
  "loadingAnimationAssetUrlsByStage": null,
  "loadingTypingShowCopy": false,
  "toolCardRunningIconUrl": "https://example.com/file.jpg",
```

```
  "toolCardCompletedIconUrl": "https://example.com/file.jpg",
  "inbox": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應範例名稱",
    "description": "回應範例描述"
  },
  "quickMenu": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應範例名稱",
    "description": "回應範例描述"
  }
}
```


設定聯絡人憑證

POST `/api/v1/web-chats/{id}/setup-contact-credentials/`

參數

參數名稱	必填	類型	說明
`id`	V	string	A UUID string identifying this web chat.

請求內容

請求參數

欄位	類型	必填	說明
sourceId	string	是	Unique identifier for the contact
name	string	否	Contact display name
mcpCredentials	object (含 2 個屬性: toolId, headers)	否	MCP credentials configuration
mcpCredentials.toolId	string (uuid)	是	MCP Tool ID
mcpCredentials.headers	object	否	Authentication headers
embedOrigin	string	否	Origin of the embedding page (forwarded by the web chat frontend) for allowlist validation

欄位	類型	必填	說明
ts	integer	否	Unix timestamp (seconds, UTC) the signature was computed with. Required when the inbox login settings enable Source ID access with signature verification.
sig	string	否	Hex HMAC-SHA256 of "{webChatId}.{sourceId}.{ts}" computed by the embedding site backend

請求結構範例

```
{
  "sourceId": string // Unique identifier for the contact
  "name"?: string // Contact display name (非必填)
  "mcpCredentials"?:  // MCP credentials configuration (非必填)
  {
    "toolId": string (uuid) // MCP Tool ID
    "headers"?: object // Authentication headers (非必填)
  }
  "embedOrigin"?: string // Origin of the embedding page (forwarded by the web chat frontend)
for allowlist validation (非必填)
  "ts"?: integer // Unix timestamp (seconds, UTC) the signature was computed with. Required
when the inbox login settings enable Source ID access with signature verification. (非必填)
  "sig"?: string // Hex HMAC-SHA256 of "{webChatId}.{sourceId}.{ts}" computed by the
embedding site backend (非必填)
}
```

請求範例值

```
{
  "sourceId": "範例字串",
  "name": "範例名稱",
  "mcpCredentials": {
    "toolId": "550e8400-e29b-41d4-a716-446655440000",
    "headers": {}
  },
  "embedOrigin": "範例字串",
  "ts": 123,
  "sig": "範例字串"
}
```

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X POST "https://api.maiagent.ai/api/v1/web-chats/550e8400-e29b-41d4-a716-
446655440000/setup-contact-credentials/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "sourceId": "範例字串",
    "name": "範例名稱",
    "mcpCredentials": {
      "toolId": "550e8400-e29b-41d4-a716-446655440000",
      "headers": {}
    },
    "embedOrigin": "範例字串",
    "ts": 123,
    "sig": "範例字串"
  }'

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// 請求內容 (payload)
const data = {
    "sourceId": "範例字串",
    "name": "範例名稱",
    "mcpCredentials": {
      "toolId": "550e8400-e29b-41d4-a716-446655440000",
      "headers": {}
    },
    "embedOrigin": "範例字串",
    "ts": 123,
    "sig": "範例字串"
  };

axios.post("https://api.maiagent.ai/api/v1/web-chats/550e8400-e29b-41d4-a716-
446655440000/setup-contact-credentials/", data, config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/web-chats/550e8400-e29b-41d4-a716-
446655440000/setup-contact-credentials/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# 請求內容 (payload)
data = {
    "sourceId": "範例字串",
    "name": "範例名稱",
    "mcpCredentials": {
        "toolId": "550e8400-e29b-41d4-a716-446655440000",
        "headers": {}
    },
    "embedOrigin": "範例字串",
    "ts": 123,
    "sig": "範例字串"
}

response = requests.post(url, json=data, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->post("https://api.maiagent.ai/api/v1/web-chats/550e8400-e29b-
41d4-a716-446655440000/setup-contact-credentials/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'sourceId' => '範例字串',
            'name' => '範例名稱',
            'mcpCredentials' => [
                'toolId' => '550e8400-e29b-41d4-a716-446655440000',
                'headers' => new \stdClass()
            ],
            'embedOrigin' => '範例字串',
            'ts' => 123,
            'sig' => '範例字串'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
{
  "contactId": string (uuid) // The created or existing contact ID
  "created": boolean // Whether the contact was created by this call. False means an existing
```

```
contact matched the source_id; in that case the request name is not applied (update names via
PATCH /contacts/{id}/).
}
```

回應範例值

```
{
  "contactId": "550e8400-e29b-41d4-a716-446655440000",
  "created": false
}
```

狀態碼: 400 - No response body

取得語音助理 Token

POST `/api/v1/web-chats/{id}/voice-agent/token/`

參數

參數名稱	必填	類型	說明
id	V	string	A UUID string identifying this web chat.

請求內容

請求參數

欄位	類型	必填	說明
avatar	string (uri)	否	
logo	string (uri)	否	
description	string	否	
cover	string (uri)	否	
backUrl	string	否	

欄位	類型	必填	說明
isActive	boolean	否	
theme	object	是	
theme.primaryColor	string	否	
theme.navbarTextColor	string	否	
theme.conversationBackgroundColor	string	否	
theme.chatbotMessageTextColor	string	否	
theme.userMessageTextColor	string	否	
theme.chatbotMessageBackgroundColor	string	否	
theme.userMessageBackgroundColor	string	否	
theme.chatbotMessageBackgroundShadowEnabled	boolean	否	
theme.userMessageBackgroundShadowEnabled	boolean	否	
theme.chatbotMessageGradientEnabled	boolean	否	
theme.userMessageGradientEnabled	boolean	否	
darkTheme	object	是	
darkTheme.primaryColor	string	否	
darkTheme.navbarTextColor	string	否	
darkTheme.conversationBackgroundColor	string	否	
darkTheme.chatbotMessageTextColor	string	否	
darkTheme.userMessageTextColor	string	否	
darkTheme.chatbotMessageBackgroundColor	string	否	
darkTheme.userMessageBackgroundColor	string	否	
darkTheme.chatbotMessageBackgroundShadowEnabled	boolean	否	
darkTheme.userMessageBackgroundShadowEnabled	boolean	否	
darkTheme.chatbotMessageGradientEnabled	boolean	否	
darkTheme.userMessageGradientEnabled	boolean	否	
enableFileUpload	boolean	否	
enableDisplayCitations	boolean	否	
toolDisplayMode	string (enum: full, compact, hidden)	否	`full` : Full ; `compact` : Compact ; `hidden` : Hidden;

欄位	類型	必填	說明
enableAskOptionButtons	boolean	否	開啟後 ask_user_question 選項以按鈕列浮在輸入框上方（輸入框保持可用）；關閉則維持現行覆蓋式面板。灰度開關，可隨時關閉回退。
enableConversationHandoff	boolean	否	開啟後此對話平台的 webchat 顯示交接 UI（提示條、摘要卡、接續按鈕）並註冊交接工具；仍受系統設定的全域交接開關管制（全域關＝一律關）。MaiGPT 免此開關恆顯示。底部的上下文使用量百分比條另由「顯示上下文使用量」控制。預設關閉，客戶對外 webchat 不會看到任何交接 UI；灰度開關，關閉即回退、不需退版。
enableDisplayContextUsage	boolean	否	開啟後此對話平台的 webchat 在輸入框下方顯示上下文使用量百分比條。與對話交接互相獨立：不受交接開關（含全域交接開關）影響，也不影響交接提示條。MaiGPT 免此開關恆顯示。預設關閉；關閉即回退、不需退版。
enableDisplayThinking	boolean	否	
enableUserThinkingControl	boolean	否	
enableDisplayQueryMetadata	boolean	否	
enableDisplayHookMarkers	boolean	否	
hookMarkerTextInputModify	string	否	
hookMarkerTextOutputModify	string	否	
hookMarkerTextInputBlock	string	否	
hookMarkerTextOutputBlock	string	否	
enableShareConversation	boolean	否	
enableLocation	boolean	否	
enableShowPoweredBy	boolean	否	
poweredByLogo	string (uri)	否	
enableAnonymous	boolean	否	
enableDisplayPreviousConversation	boolean	否	
enableDisplayConversationHistory	boolean	否	
enableConversationTimer	boolean	否	
conversationTimerDuration	integer	否	計時器逾時時長，範圍 3-60 分鐘
enableAutoNewConversationOnTimeout	boolean	否	

欄位	類型	必填	說明
enableSatisfactionSurvey	boolean	否	
satisfactionSurveyDelayMinutes	integer	否	最後一則 AI 回覆後幾分鐘彈出問卷，範圍 1-60 分鐘
satisfactionSurveyPrompt	string	否	自訂問卷標題文字，留空則使用前端多語系預設文字
enableThemeModeToggle	boolean	否	
enableDisplayFontSizeSwitch	boolean	否	
defaultThemeMode	object	否	
enableDownloadCitations	boolean	否	
customDomain	object (含 3 個屬性: id, domain, status)	否	
customDomain.domain	string	是	
enableDisplayChatbotAvatar	boolean	否	
enableDisplayChatbotName	boolean	否	
buttonIcon	string (uri)	否	
conversationStartersDisplayCount	integer	否	
preChatFormEnabled	boolean	否	
preChatFormFields	object	否	
preChatFormTitle	object	否	
preChatFormSubtitle	object	否	
loadingDisplayMode	object	否	Waiting-experience style. `narrative` shows per-stage copy; `brand_animation` plays the uploaded asset and hides every system narration line. Defaults to `narrative`, which with no copy configured beh...
loadingStageCopyByLocale	object	否	Locale-keyed per-stage waiting copy, shaped {locale: {stage: text}} where stage is one of LoadingStage. An absent locale or stage falls back to the built-in copy, so a partially filled dict is valid a...
loadingLongWaitCopyByLocale	object	否	Locale-keyed line shown once the wait exceeds `loading_long_wait_threshold_seconds`,

欄位	類型	必填	說明
			shaped {locale: text}. Written in the brand character voice for the animation mode, but applies to both modes. Empt...
loadingLongWaitThresholdSeconds	integer	否	How long a single reply must be pending before the long-wait copy appears.
loadingAnimationUseSharedAsset	boolean	否	True (default) means every stage plays `loading_animation_shared_asset_url`, so the admin only uploads once. False expands per-stage assets, each falling back to the shared asset when its own slot is ...
loadingAnimationSharedAssetUrl	string (uri)	否	
loadingAnimationAssetUrlsByStage	object	否	Shaped {stage: url} keyed by LoadingStage. Only consulted when `loading_animation_use_shared_asset` is False; a missing stage falls back to the shared asset.
loadingTypingShowCopy	boolean	否	Only affects the first "typing" stage. True (default, the pre-existing behavior) shows the typing-stage copy next to the pre-first-char animation/dot; False plays only the animation with no text line....
toolCardRunningIconUrl	string (uri)	否	
toolCardCompletedIconUrl	string (uri)	否	

請求結構範例

```
{
  "avatar"?: string (uri) // 非必填
  "logo"?: string (uri) // 非必填
  "description"?: string // 非必填
  "cover"?: string (uri) // 非必填
  "backUrl"?: string // 非必填
  "isActive"?: boolean // 非必填
  "theme": {
  {
    "primaryColor"?: string // 非必填
    "navbarTextColor"?: string // 非必填
    "conversationBackgroundColor"?: string // 非必填
    "chatbotMessageTextColor"?: string // 非必填
    "userMessageTextColor"?: string // 非必填
    "chatbotMessageBackgroundColor"?: string // 非必填
    "userMessageBackgroundColor"?: string // 非必填
    "chatbotMessageBackgroundShadowEnabled"?: boolean // 非必填
```

```
    "userMessageBackgroundShadowEnabled"?: boolean // 非必填
    "chatbotMessageGradientEnabled"?: boolean // 非必填
    "userMessageGradientEnabled"?: boolean // 非必填
  }
  }
  "darkTheme": {
  {
    "primaryColor"?: string // 非必填
    "navbarTextColor"?: string // 非必填
    "conversationBackgroundColor"?: string // 非必填
    "chatbotMessageTextColor"?: string // 非必填
    "userMessageTextColor"?: string // 非必填
    "chatbotMessageBackgroundColor"?: string // 非必填
    "userMessageBackgroundColor"?: string // 非必填
    "chatbotMessageBackgroundShadowEnabled"?: boolean // 非必填
    "userMessageBackgroundShadowEnabled"?: boolean // 非必填
    "chatbotMessageGradientEnabled"?: boolean // 非必填
    "userMessageGradientEnabled"?: boolean // 非必填
  }
  }
  "enableFileUpload"?: boolean // 非必填
  "enableDisplayCitations"?: boolean // 非必填
  "toolDisplayMode"?: string (enum: full, compact, hidden) // * `full` - Full
* `compact` - Compact
* `hidden` - Hidden (非必填)
  "enableAskOptionButtons"?: boolean // 開啟後 ask_user_question 選項以按鈕列浮在輸入框上方（輸入框保持可用）；關閉則維持現行覆蓋式面板。灰度開關，可隨時關閉回退。 (非必填)
  "enableConversationHandoff"?: boolean // 開啟後此對話平台的 webchat 顯示交接 UI（提示條、摘要卡、接續按鈕）並註冊交接工具；仍受系統設定的全域交接開關管制（全域關＝一律關）。MaiGPT 免此開關恆顯示。底部的上下文使用量百分比條另由「顯示上下文使用量」控制。預設關閉，客戶對外 webchat 不會看到任何交接 UI；灰度開關，關閉即回退、不需退版。 (非必填)
  "enableDisplayContextUsage"?: boolean // 開啟後此對話平台的 webchat 在輸入框下方顯示上下文使用量百分比條。與對話交接互相獨立：不受交接開關（含全域交接開關）影響，也不影響交接提示條。MaiGPT 免此開關恆顯示。預設關閉；關閉即回退、不需退版。 (非必填)
  "enableDisplayThinking"?: boolean // 非必填
  "enableUserThinkingControl"?: boolean // 非必填
  "enableDisplayQueryMetadata"?: boolean // 非必填
  "enableDisplayHookMarkers"?: boolean // 非必填
  "hookMarkerTextInputModify"?: string // 非必填
  "hookMarkerTextOutputModify"?: string // 非必填
  "hookMarkerTextInputBlock"?: string // 非必填
  "hookMarkerTextOutputBlock"?: string // 非必填
  "enableShareConversation"?: boolean // 非必填
  "enableLocation"?: boolean // 非必填
  "enableShowPoweredBy"?: boolean // 非必填
  "poweredByLogo"?: string (uri) // 非必填
  "enableAnonymous"?: boolean // 非必填
  "enableDisplayPreviousConversation"?: boolean // 非必填
  "enableDisplayConversationHistory"?: boolean // 非必填
  "enableConversationTimer"?: boolean // 非必填
  "conversationTimerDuration"?: integer // 計時器逾時時長，範圍 3-60 分鐘 (非必填)
  "enableAutoNewConversationOnTimeout"?: boolean // 非必填
  "enableSatisfactionSurvey"?: boolean // 非必填
  "satisfactionSurveyDelayMinutes"?: integer // 最後一則 AI 回覆後幾分鐘彈出問卷，範圍 1-60 分鐘 (非必填)
  "satisfactionSurveyPrompt"?: string // 自訂問卷標題文字，留空則使用前端多語系預設文字 (非必填)
```

```
  "enableThemeModeToggle"?: boolean // 非必填
  "enableDisplayFontSizeSwitch"?: boolean // 非必填
  "defaultThemeMode"?:  // 非必填
  {
  }
  "enableDownloadCitations"?: boolean // 非必填
  "customDomain"?:  // 非必填
  {
    "domain": string
  }
  "enableDisplayChatbotAvatar"?: boolean // 非必填
  "enableDisplayChatbotName"?: boolean // 非必填
  "buttonIcon"?: string (uri) // 非必填
  "conversationStartersDisplayCount"?: integer // 非必填
  "preChatFormEnabled"?: boolean // 非必填
  "preChatFormFields"?: object // 非必填
  "preChatFormTitle"?: object // 非必填
  "preChatFormSubtitle"?: object // 非必填
  "loadingDisplayMode"?:  // Waiting-experience style. `narrative` shows per-stage copy;
`brand_animation` plays the uploaded asset and hides every system narration line. Defaults to
`narrative`, which with no copy configured behaves exactly as before this field existed.

* `narrative` - Narrative copy
* `brand_animation` - Brand animation (非必填)
  {
  }
  "loadingStageCopyByLocale"?: object // Locale-keyed per-stage waiting copy, shaped {locale:
{stage: text}} where stage is one of LoadingStage. An absent locale or stage falls back to
the built-in copy, so a partially filled dict is valid and never blocks a reply. (非必填)
  "loadingLongWaitCopyByLocale"?: object // Locale-keyed line shown once the wait exceeds
`loading_long_wait_threshold_seconds`, shaped {locale: text}. Written in the brand character
voice for the animation mode, but applies to both modes. Empty means no long-wait line is
shown. (非必填)
  "loadingLongWaitThresholdSeconds"?: integer // How long a single reply must be pending
before the long-wait copy appears. (非必填)
  "loadingAnimationUseSharedAsset"?: boolean // True (default) means every stage plays
`loading_animation_shared_asset_url`, so the admin only uploads once. False expands per-stage
assets, each falling back to the shared asset when its own slot is empty. (非必填)
  "loadingAnimationSharedAssetUrl"?: string (uri) // 非必填
  "loadingAnimationAssetUrlsByStage"?: object // Shaped {stage: url} keyed by LoadingStage.
Only consulted when `loading_animation_use_shared_asset` is False; a missing stage falls back
to the shared asset. (非必填)
  "loadingTypingShowCopy"?: boolean // Only affects the first "typing" stage. True (default,
the pre-existing behavior) shows the typing-stage copy next to the pre-first-char
animation/dot; False plays only the animation with no text line. Thinking / analyzing / long-
wait stages are unaffected. (非必填)
  "toolCardRunningIconUrl"?: string (uri) // 非必填
  "toolCardCompletedIconUrl"?: string (uri) // 非必填
}
```

請求範例值

```
{
  "avatar": "https://example.com/file.jpg",
```

```
  "logo": "https://example.com/file.jpg",
  "description": "範例字串",
  "cover": "https://example.com/file.jpg",
  "backUrl": "範例字串",
  "isActive": true,
  "theme": {
    "primaryColor": "範例字串",
    "navbarTextColor": "範例字串",
    "conversationBackgroundColor": "範例字串",
    "chatbotMessageTextColor": "範例字串",
    "userMessageTextColor": "範例字串",
    "chatbotMessageBackgroundColor": "範例字串",
    "userMessageBackgroundColor": "範例字串",
    "chatbotMessageBackgroundShadowEnabled": true,
    "userMessageBackgroundShadowEnabled": true,
    "chatbotMessageGradientEnabled": true,
    "userMessageGradientEnabled": true
  },
  "darkTheme": {
    "primaryColor": "範例字串",
    "navbarTextColor": "範例字串",
    "conversationBackgroundColor": "範例字串",
    "chatbotMessageTextColor": "範例字串",
    "userMessageTextColor": "範例字串",
    "chatbotMessageBackgroundColor": "範例字串",
    "userMessageBackgroundColor": "範例字串",
    "chatbotMessageBackgroundShadowEnabled": true,
    "userMessageBackgroundShadowEnabled": true,
    "chatbotMessageGradientEnabled": true,
    "userMessageGradientEnabled": true
  },
  "enableFileUpload": true,
  "enableDisplayCitations": true,
  "toolDisplayMode": "full",
  "enableAskOptionButtons": true,
  "enableConversationHandoff": true,
  "enableDisplayContextUsage": true,
  "enableDisplayThinking": true,
  "enableUserThinkingControl": true,
  "enableDisplayQueryMetadata": true,
  "enableDisplayHookMarkers": true,
  "hookMarkerTextInputModify": "範例字串",
  "hookMarkerTextOutputModify": "範例字串",
  "hookMarkerTextInputBlock": "範例字串",
  "hookMarkerTextOutputBlock": "範例字串",
  "enableShareConversation": true,
  "enableLocation": true,
  "enableShowPoweredBy": true,
  "poweredByLogo": "https://example.com/file.jpg",
  "enableAnonymous": true,
  "enableDisplayPreviousConversation": true,
  "enableDisplayConversationHistory": true,
  "enableConversationTimer": true,
  "conversationTimerDuration": 123,
  "enableAutoNewConversationOnTimeout": true,
  "enableSatisfactionSurvey": true,
```

```
  "satisfactionSurveyDelayMinutes": 123,
  "satisfactionSurveyPrompt": "範例字串",
  "enableThemeModeToggle": true,
  "enableDisplayFontSizeSwitch": true,
  "defaultThemeMode": {},
  "enableDownloadCitations": true,
  "customDomain": {
    "domain": "範例字串"
  },
  "enableDisplayChatbotAvatar": true,
  "enableDisplayChatbotName": true,
  "buttonIcon": "https://example.com/file.jpg",
  "conversationStartersDisplayCount": 123,
  "preChatFormEnabled": true,
  "preChatFormFields": null,
  "preChatFormTitle": null,
  "preChatFormSubtitle": null,
  "loadingDisplayMode": {},
  "loadingStageCopyByLocale": null,
  "loadingLongWaitCopyByLocale": null,
  "loadingLongWaitThresholdSeconds": 123,
  "loadingAnimationUseSharedAsset": true,
  "loadingAnimationSharedAssetUrl": "https://example.com/file.jpg",
  "loadingAnimationAssetUrlsByStage": null,
  "loadingTypingShowCopy": true,
  "toolCardRunningIconUrl": "https://example.com/file.jpg",
  "toolCardCompletedIconUrl": "https://example.com/file.jpg"
}
```


程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X POST "https://api.maiagent.ai/api/v1/web-chats/550e8400-e29b-41d4-a716-
446655440000/voice-agent/token/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "avatar": "https://example.com/file.jpg",
    "logo": "https://example.com/file.jpg",
    "description": "範例字串",
    "cover": "https://example.com/file.jpg",
    "backUrl": "範例字串",
    "isActive": true,
    "theme": {
      "primaryColor": "範例字串",
      "navbarTextColor": "範例字串",
      "conversationBackgroundColor": "範例字串",
      "chatbotMessageTextColor": "範例字串",
      "userMessageTextColor": "範例字串",
      "chatbotMessageBackgroundColor": "範例字串",
      "userMessageBackgroundColor": "範例字串",
      "chatbotMessageBackgroundShadowEnabled": true,
      "userMessageBackgroundShadowEnabled": true,
      "chatbotMessageGradientEnabled": true,
      "userMessageGradientEnabled": true
    },
    "darkTheme": {
      "primaryColor": "範例字串",
      "navbarTextColor": "範例字串",
      "conversationBackgroundColor": "範例字串",
      "chatbotMessageTextColor": "範例字串",
      "userMessageTextColor": "範例字串",
      "chatbotMessageBackgroundColor": "範例字串",
      "userMessageBackgroundColor": "範例字串",
      "chatbotMessageBackgroundShadowEnabled": true,
      "userMessageBackgroundShadowEnabled": true,
      "chatbotMessageGradientEnabled": true,
      "userMessageGradientEnabled": true
    },
    "enableFileUpload": true,
    "enableDisplayCitations": true,
    "toolDisplayMode": "full",
    "enableAskOptionButtons": true,
    "enableConversationHandoff": true,
    "enableDisplayContextUsage": true,
    "enableDisplayThinking": true,
    "enableUserThinkingControl": true,
    "enableDisplayQueryMetadata": true,
```

```
      "enableDisplayHookMarkers": true,
      "hookMarkerTextInputModify": "範例字串",
      "hookMarkerTextOutputModify": "範例字串",
      "hookMarkerTextInputBlock": "範例字串",
      "hookMarkerTextOutputBlock": "範例字串",
      "enableShareConversation": true,
      "enableLocation": true,
      "enableShowPoweredBy": true,
      "poweredByLogo": "https://example.com/file.jpg",
      "enableAnonymous": true,
      "enableDisplayPreviousConversation": true,
      "enableDisplayConversationHistory": true,
      "enableConversationTimer": true,
      "conversationTimerDuration": 123,
      "enableAutoNewConversationOnTimeout": true,
      "enableSatisfactionSurvey": true,
      "satisfactionSurveyDelayMinutes": 123,
      "satisfactionSurveyPrompt": "範例字串",
      "enableThemeModeToggle": true,
      "enableDisplayFontSizeSwitch": true,
      "defaultThemeMode": {},
      "enableDownloadCitations": true,
      "customDomain": {
        "domain": "範例字串"
      },
      "enableDisplayChatbotAvatar": true,
      "enableDisplayChatbotName": true,
      "buttonIcon": "https://example.com/file.jpg",
      "conversationStartersDisplayCount": 123,
      "preChatFormEnabled": true,
      "preChatFormFields": null,
      "preChatFormTitle": null,
      "preChatFormSubtitle": null,
      "loadingDisplayMode": {},
      "loadingStageCopyByLocale": null,
      "loadingLongWaitCopyByLocale": null,
      "loadingLongWaitThresholdSeconds": 123,
      "loadingAnimationUseSharedAsset": true,
      "loadingAnimationSharedAssetUrl": "https://example.com/file.jpg",
      "loadingAnimationAssetUrlsByStage": null,
      "loadingTypingShowCopy": true,
      "toolCardRunningIconUrl": "https://example.com/file.jpg",
      "toolCardCompletedIconUrl": "https://example.com/file.jpg"
    }'

  # 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// 請求內容 (payload)
const data = {
    "avatar": "https://example.com/file.jpg",
    "logo": "https://example.com/file.jpg",
    "description": "範例字串",
    "cover": "https://example.com/file.jpg",
    "backUrl": "範例字串",
    "isActive": true,
    "theme": {
      "primaryColor": "範例字串",
      "navbarTextColor": "範例字串",
      "conversationBackgroundColor": "範例字串",
      "chatbotMessageTextColor": "範例字串",
      "userMessageTextColor": "範例字串",
      "chatbotMessageBackgroundColor": "範例字串",
      "userMessageBackgroundColor": "範例字串",
      "chatbotMessageBackgroundShadowEnabled": true,
      "userMessageBackgroundShadowEnabled": true,
      "chatbotMessageGradientEnabled": true,
      "userMessageGradientEnabled": true
    },
    "darkTheme": {
      "primaryColor": "範例字串",
      "navbarTextColor": "範例字串",
      "conversationBackgroundColor": "範例字串",
      "chatbotMessageTextColor": "範例字串",
      "userMessageTextColor": "範例字串",
      "chatbotMessageBackgroundColor": "範例字串",
      "userMessageBackgroundColor": "範例字串",
      "chatbotMessageBackgroundShadowEnabled": true,
      "userMessageBackgroundShadowEnabled": true,
      "chatbotMessageGradientEnabled": true,
      "userMessageGradientEnabled": true
    },
    "enableFileUpload": true,
    "enableDisplayCitations": true,
    "toolDisplayMode": "full",
    "enableAskOptionButtons": true,
    "enableConversationHandoff": true,
    "enableDisplayContextUsage": true,
```

```
    "enableDisplayThinking": true,
    "enableUserThinkingControl": true,
    "enableDisplayQueryMetadata": true,
    "enableDisplayHookMarkers": true,
    "hookMarkerTextInputModify": "範例字串",
    "hookMarkerTextOutputModify": "範例字串",
    "hookMarkerTextInputBlock": "範例字串",
    "hookMarkerTextOutputBlock": "範例字串",
    "enableShareConversation": true,
    "enableLocation": true,
    "enableShowPoweredBy": true,
    "poweredByLogo": "https://example.com/file.jpg",
    "enableAnonymous": true,
    "enableDisplayPreviousConversation": true,
    "enableDisplayConversationHistory": true,
    "enableConversationTimer": true,
    "conversationTimerDuration": 123,
    "enableAutoNewConversationOnTimeout": true,
    "enableSatisfactionSurvey": true,
    "satisfactionSurveyDelayMinutes": 123,
    "satisfactionSurveyPrompt": "範例字串",
    "enableThemeModeToggle": true,
    "enableDisplayFontSizeSwitch": true,
    "defaultThemeMode": {},
    "enableDownloadCitations": true,
    "customDomain": {
      "domain": "範例字串"
    },
    "enableDisplayChatbotAvatar": true,
    "enableDisplayChatbotName": true,
    "buttonIcon": "https://example.com/file.jpg",
    "conversationStartersDisplayCount": 123,
    "preChatFormEnabled": true,
    "preChatFormFields": null,
    "preChatFormTitle": null,
    "preChatFormSubtitle": null,
    "loadingDisplayMode": {},
    "loadingStageCopyByLocale": null,
    "loadingLongWaitCopyByLocale": null,
    "loadingLongWaitThresholdSeconds": 123,
    "loadingAnimationUseSharedAsset": true,
    "loadingAnimationSharedAssetUrl": "https://example.com/file.jpg",
    "loadingAnimationAssetUrlsByStage": null,
    "loadingTypingShowCopy": true,
    "toolCardRunningIconUrl": "https://example.com/file.jpg",
    "toolCardCompletedIconUrl": "https://example.com/file.jpg"
  };

axios.post("https://api.maiagent.ai/api/v1/web-chats/550e8400-e29b-41d4-a716-
446655440000/voice-agent/token/", data, config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
```

```
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/web-chats/550e8400-e29b-41d4-a716-
446655440000/voice-agent/token/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# 請求內容 (payload)
data = {
    "avatar": "https://example.com/file.jpg",
    "logo": "https://example.com/file.jpg",
    "description": "範例字串",
    "cover": "https://example.com/file.jpg",
    "backUrl": "範例字串",
    "isActive": True,
    "theme": {
        "primaryColor": "範例字串",
        "navbarTextColor": "範例字串",
        "conversationBackgroundColor": "範例字串",
        "chatbotMessageTextColor": "範例字串",
        "userMessageTextColor": "範例字串",
        "chatbotMessageBackgroundColor": "範例字串",
        "userMessageBackgroundColor": "範例字串",
        "chatbotMessageBackgroundShadowEnabled": True,
        "userMessageBackgroundShadowEnabled": True,
        "chatbotMessageGradientEnabled": True,
        "userMessageGradientEnabled": True
    },
    "darkTheme": {
        "primaryColor": "範例字串",
        "navbarTextColor": "範例字串",
        "conversationBackgroundColor": "範例字串",
        "chatbotMessageTextColor": "範例字串",
        "userMessageTextColor": "範例字串",
        "chatbotMessageBackgroundColor": "範例字串",
        "userMessageBackgroundColor": "範例字串",
        "chatbotMessageBackgroundShadowEnabled": True,
        "userMessageBackgroundShadowEnabled": True,
        "chatbotMessageGradientEnabled": True,
        "userMessageGradientEnabled": True
    },
    "enableFileUpload": True,
    "enableDisplayCitations": True,
    "toolDisplayMode": "full",
    "enableAskOptionButtons": True,
    "enableConversationHandoff": True,
    "enableDisplayContextUsage": True,
    "enableDisplayThinking": True,
```

```
        "enableUserThinkingControl": True,
        "enableDisplayQueryMetadata": True,
        "enableDisplayHookMarkers": True,
        "hookMarkerTextInputModify": "範例字串",
        "hookMarkerTextOutputModify": "範例字串",
        "hookMarkerTextInputBlock": "範例字串",
        "hookMarkerTextOutputBlock": "範例字串",
        "enableShareConversation": True,
        "enableLocation": True,
        "enableShowPoweredBy": True,
        "poweredByLogo": "https://example.com/file.jpg",
        "enableAnonymous": True,
        "enableDisplayPreviousConversation": True,
        "enableDisplayConversationHistory": True,
        "enableConversationTimer": True,
        "conversationTimerDuration": 123,
        "enableAutoNewConversationOnTimeout": True,
        "enableSatisfactionSurvey": True,
        "satisfactionSurveyDelayMinutes": 123,
        "satisfactionSurveyPrompt": "範例字串",
        "enableThemeModeToggle": True,
        "enableDisplayFontSizeSwitch": True,
        "defaultThemeMode": {},
        "enableDownloadCitations": True,
        "customDomain": {
            "domain": "範例字串"
        },
        "enableDisplayChatbotAvatar": True,
        "enableDisplayChatbotName": True,
        "buttonIcon": "https://example.com/file.jpg",
        "conversationStartersDisplayCount": 123,
        "preChatFormEnabled": True,
        "preChatFormFields": None,
        "preChatFormTitle": None,
        "preChatFormSubtitle": None,
        "loadingDisplayMode": {},
        "loadingStageCopyByLocale": None,
        "loadingLongWaitCopyByLocale": None,
        "loadingLongWaitThresholdSeconds": 123,
        "loadingAnimationUseSharedAsset": True,
        "loadingAnimationSharedAssetUrl": "https://example.com/file.jpg",
        "loadingAnimationAssetUrlsByStage": None,
        "loadingTypingShowCopy": True,
        "toolCardRunningIconUrl": "https://example.com/file.jpg",
        "toolCardCompletedIconUrl": "https://example.com/file.jpg"
    }

    response = requests.post(url, json=data, headers=headers)
    try:
        print("成功取得回應:")
        print(response.json())
    except Exception as e:
        print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->post("https://api.maiagent.ai/api/v1/web-chats/550e8400-e29b-
41d4-a716-446655440000/voice-agent/token/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'avatar' => 'https://example.com/file.jpg',
            'logo' => 'https://example.com/file.jpg',
            'description' => '範例字串',
            'cover' => 'https://example.com/file.jpg',
            'backUrl' => '範例字串',
            'isActive' => true,
            'theme' => [
                'primaryColor' => '範例字串',
                'navbarTextColor' => '範例字串',
                'conversationBackgroundColor' => '範例字串',
                'chatbotMessageTextColor' => '範例字串',
                'userMessageTextColor' => '範例字串',
                'chatbotMessageBackgroundColor' => '範例字串',
                'userMessageBackgroundColor' => '範例字串',
                'chatbotMessageBackgroundShadowEnabled' => true,
                'userMessageBackgroundShadowEnabled' => true,
                'chatbotMessageGradientEnabled' => true,
                'userMessageGradientEnabled' => true
            ],
            'darkTheme' => [
                'primaryColor' => '範例字串',
                'navbarTextColor' => '範例字串',
                'conversationBackgroundColor' => '範例字串',
                'chatbotMessageTextColor' => '範例字串',
                'userMessageTextColor' => '範例字串',
                'chatbotMessageBackgroundColor' => '範例字串',
                'userMessageBackgroundColor' => '範例字串',
                'chatbotMessageBackgroundShadowEnabled' => true,
                'userMessageBackgroundShadowEnabled' => true,
                'chatbotMessageGradientEnabled' => true,
                'userMessageGradientEnabled' => true
            ],
            'enableFileUpload' => true,
            'enableDisplayCitations' => true,
            'toolDisplayMode' => 'full',
            'enableAskOptionButtons' => true,
            'enableConversationHandoff' => true,
```

```
            'enableDisplayContextUsage' => true,
            'enableDisplayThinking' => true,
            'enableUserThinkingControl' => true,
            'enableDisplayQueryMetadata' => true,
            'enableDisplayHookMarkers' => true,
            'hookMarkerTextInputModify' => '範例字串',
            'hookMarkerTextOutputModify' => '範例字串',
            'hookMarkerTextInputBlock' => '範例字串',
            'hookMarkerTextOutputBlock' => '範例字串',
            'enableShareConversation' => true,
            'enableLocation' => true,
            'enableShowPoweredBy' => true,
            'poweredByLogo' => 'https://example.com/file.jpg',
            'enableAnonymous' => true,
            'enableDisplayPreviousConversation' => true,
            'enableDisplayConversationHistory' => true,
            'enableConversationTimer' => true,
            'conversationTimerDuration' => 123,
            'enableAutoNewConversationOnTimeout' => true,
            'enableSatisfactionSurvey' => true,
            'satisfactionSurveyDelayMinutes' => 123,
            'satisfactionSurveyPrompt' => '範例字串',
            'enableThemeModeToggle' => true,
            'enableDisplayFontSizeSwitch' => true,
            'defaultThemeMode' => new \stdClass(),
            'enableDownloadCitations' => true,
            'customDomain' => [
                'domain' => '範例字串'
            ],
            'enableDisplayChatbotAvatar' => true,
            'enableDisplayChatbotName' => true,
            'buttonIcon' => 'https://example.com/file.jpg',
            'conversationStartersDisplayCount' => 123,
            'preChatFormEnabled' => true,
            'preChatFormFields' => null,
            'preChatFormTitle' => null,
            'preChatFormSubtitle' => null,
            'loadingDisplayMode' => new \stdClass(),
            'loadingStageCopyByLocale' => null,
            'loadingLongWaitCopyByLocale' => null,
            'loadingLongWaitThresholdSeconds' => 123,
            'loadingAnimationUseSharedAsset' => true,
            'loadingAnimationSharedAssetUrl' => 'https://example.com/file.jpg',
            'loadingAnimationAssetUrlsByStage' => null,
            'loadingTypingShowCopy' => true,
            'toolCardRunningIconUrl' => 'https://example.com/file.jpg',
            'toolCardCompletedIconUrl' => 'https://example.com/file.jpg'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
```

```
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
{
  "id": string (uuid)
  "name": string
  "avatar"?: string (uri) // 非必填
  "logo"?: string (uri) // 非必填
  "description"?: string // 非必填
  "cover"?: string (uri) // 非必填
  "backUrl"?: string // 非必填
  "isActive"?: boolean // 非必填
  "enableSpeech": boolean
  "displayConversationStarters": [
    string
  ]
  "theme": {
  {
    "primaryColor"?: string // 非必填
    "navbarTextColor"?: string // 非必填
    "conversationBackgroundColor"?: string // 非必填
    "chatbotMessageTextColor"?: string // 非必填
    "userMessageTextColor"?: string // 非必填
    "chatbotMessageBackgroundColor"?: string // 非必填
    "userMessageBackgroundColor"?: string // 非必填
    "chatbotMessageBackgroundShadowEnabled"?: boolean // 非必填
    "userMessageBackgroundShadowEnabled"?: boolean // 非必填
    "chatbotMessageGradientEnabled"?: boolean // 非必填
    "userMessageGradientEnabled"?: boolean // 非必填
  }
  }
  "darkTheme": {
  {
    "primaryColor"?: string // 非必填
    "navbarTextColor"?: string // 非必填
    "conversationBackgroundColor"?: string // 非必填
    "chatbotMessageTextColor"?: string // 非必填
    "userMessageTextColor"?: string // 非必填
    "chatbotMessageBackgroundColor"?: string // 非必填
    "userMessageBackgroundColor"?: string // 非必填
    "chatbotMessageBackgroundShadowEnabled"?: boolean // 非必填
```

```
    "userMessageBackgroundShadowEnabled"?: boolean // 非必填
    "chatbotMessageGradientEnabled"?: boolean // 非必填
    "userMessageGradientEnabled"?: boolean // 非必填
  }
  }
  "enableFileUpload"?: boolean // 非必填
  "enableDisplayCitations"?: boolean // 非必填
  "toolDisplayMode"?: string (enum: full, compact, hidden) // * `full` - Full
* `compact` - Compact
* `hidden` - Hidden (非必填)
  "enableAskOptionButtons"?: boolean // 開啟後 ask_user_question 選項以按鈕列浮在輸入框上方（輸入框保持可用）；關閉則維持現行覆蓋式面板。灰度開關，可隨時關閉回退。 (非必填)
  "enableConversationHandoff"?: boolean // 開啟後此對話平台的 webchat 顯示交接 UI（提示條、摘要卡、接續按鈕）並註冊交接工具；仍受系統設定的全域交接開關管制（全域關＝一律關）。MaiGPT 免此開關恆顯示。底部的上下文使用量百分比條另由「顯示上下文使用量」控制。預設關閉，客戶對外 webchat 不會看到任何交接 UI；灰度開關，關閉即回退、不需退版。 (非必填)
  "enableDisplayContextUsage"?: boolean // 開啟後此對話平台的 webchat 在輸入框下方顯示上下文使用量百分比條。與對話交接互相獨立：不受交接開關（含全域交接開關）影響，也不影響交接提示條。MaiGPT 免此開關恆顯示。預設關閉；關閉即回退、不需退版。 (非必填)
  "enableDisplayThinking"?: boolean // 非必填
  "enableUserThinkingControl"?: boolean // 非必填
  "enableDisplayQueryMetadata"?: boolean // 非必填
  "enableDisplayHookMarkers"?: boolean // 非必填
  "hookMarkerTextInputModify"?: string // 非必填
  "hookMarkerTextOutputModify"?: string // 非必填
  "hookMarkerTextInputBlock"?: string // 非必填
  "hookMarkerTextOutputBlock"?: string // 非必填
  "enableShareConversation"?: boolean // 非必填
  "enableLocation"?: boolean // 非必填
  "enableShowPoweredBy"?: boolean // 非必填
  "poweredByLogo"?: string (uri) // 非必填
  "enableAnonymous"?: boolean // 非必填
  "enableDisplayPreviousConversation"?: boolean // 非必填
  "enableDisplayConversationHistory"?: boolean // 非必填
  "enableConversationTimer"?: boolean // 非必填
  "conversationTimerDuration"?: integer // 計時器逾時時長，範圍 3-60 分鐘 (非必填)
  "enableAutoNewConversationOnTimeout"?: boolean // 非必填
  "enableSatisfactionSurvey"?: boolean // 非必填
  "satisfactionSurveyDelayMinutes"?: integer // 最後一則 AI 回覆後幾分鐘彈出問卷，範圍 1-60 分鐘 (非必填)
  "satisfactionSurveyPrompt"?: string // 自訂問卷標題文字，留空則使用前端多語系預設文字 (非必填)
  "accessType":
  {
  }
  "enableThemeModeToggle"?: boolean // 非必填
  "enableDisplayFontSizeSwitch"?: boolean // 非必填
  "defaultThemeMode"?:  // 非必填
  {
  }
  "enableDownloadCitations"?: boolean // 非必填
  "customDomain"?:  // 非必填
  {
    "id": string (uuid)
    "domain": string
    "status":
    {
```

```
    }
  }
  "enableDisplayChatbotAvatar"?: boolean // 非必填
  "enableDisplayChatbotName"?: boolean // 非必填
  "buttonIcon"?: string (uri) // 非必填
  "enableCodeInterpreter": boolean // Read enable_code_interpreter from the inbox's chatbot.
  "voiceAgentEnabled": boolean // Whether the bound chatbot has the voice agent turned on
(read-only)
  "conversationStartersDisplayCount"?: integer // 非必填
  "includeGreetingInContext": boolean // When enabled, the conversation greeting and the
numbered conversation starters (in configured order, unshuffled and untruncated) are injected
into the LLM context so the agent can resolve short replies like "1" to the matching starter
option.
  "tools": [ // Expose chatbot tools to SDK for the tool_mask selector.

Name resolution prefers ``display_name`` (set on MCP tools, where
``name`` is null) and falls back to ``name`` for API tools where
``display_name`` is null. Tools missing both are skipped — SDK
should never show an unnamed tool to a contact. Quick Menu tools are
static input-bar UI, never an LLM tool, so masking one is meaningless.
    object
  ]
  "preChatFormEnabled"?: boolean // 非必填
  "preChatFormFields"?: object // 非必填
  "preChatFormTitle"?: object // 非必填
  "preChatFormSubtitle"?: object // 非必填
  "loadingDisplayMode"?:  // Waiting-experience style. `narrative` shows per-stage copy;
`brand_animation` plays the uploaded asset and hides every system narration line. Defaults to
`narrative`, which with no copy configured behaves exactly as before this field existed.

* `narrative` - Narrative copy
* `brand_animation` - Brand animation (非必填)
  {
  }
  "loadingStageCopyByLocale"?: object // Locale-keyed per-stage waiting copy, shaped {locale:
{stage: text}} where stage is one of LoadingStage. An absent locale or stage falls back to
the built-in copy, so a partially filled dict is valid and never blocks a reply. (非必填)
  "loadingLongWaitCopyByLocale"?: object // Locale-keyed line shown once the wait exceeds
`loading_long_wait_threshold_seconds`, shaped {locale: text}. Written in the brand character
voice for the animation mode, but applies to both modes. Empty means no long-wait line is
shown. (非必填)
  "loadingLongWaitThresholdSeconds"?: integer // How long a single reply must be pending
before the long-wait copy appears. (非必填)
  "loadingAnimationUseSharedAsset"?: boolean // True (default) means every stage plays
`loading_animation_shared_asset_url`, so the admin only uploads once. False expands per-stage
assets, each falling back to the shared asset when its own slot is empty. (非必填)
  "loadingAnimationSharedAssetUrl"?: string (uri) // 非必填
  "loadingAnimationAssetUrlsByStage"?: object // Shaped {stage: url} keyed by LoadingStage.
Only consulted when `loading_animation_use_shared_asset` is False; a missing stage falls back
to the shared asset. (非必填)
  "loadingTypingShowCopy"?: boolean // Only affects the first "typing" stage. True (default,
the pre-existing behavior) shows the typing-stage copy next to the pre-first-char
animation/dot; False plays only the animation with no text line. Thinking / analyzing / long-
wait stages are unaffected. (非必填)
  "toolCardRunningIconUrl"?: string (uri) // 非必填
  "toolCardCompletedIconUrl"?: string (uri) // 非必填
```

```
  "inbox": object
  "quickMenu": object // Mounted Quick Menu Agent UI config for the web chat input bar; null
when absent (read-only)
}
```

回應範例值

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "name": "回應字串",
  "avatar": "https://example.com/file.jpg",
  "logo": "https://example.com/file.jpg",
  "description": "回應字串",
  "cover": "https://example.com/file.jpg",
  "backUrl": "回應字串",
  "isActive": false,
  "enableSpeech": false,
  "displayConversationStarters": [
    "回應字串"
  ],
  "theme": {
    "primaryColor": "回應字串",
    "navbarTextColor": "回應字串",
    "conversationBackgroundColor": "回應字串",
    "chatbotMessageTextColor": "回應字串",
    "userMessageTextColor": "回應字串",
    "chatbotMessageBackgroundColor": "回應字串",
    "userMessageBackgroundColor": "回應字串",
    "chatbotMessageBackgroundShadowEnabled": false,
    "userMessageBackgroundShadowEnabled": false,
    "chatbotMessageGradientEnabled": false,
    "userMessageGradientEnabled": false
  },
  "darkTheme": {
    "primaryColor": "回應字串",
    "navbarTextColor": "回應字串",
    "conversationBackgroundColor": "回應字串",
    "chatbotMessageTextColor": "回應字串",
    "userMessageTextColor": "回應字串",
    "chatbotMessageBackgroundColor": "回應字串",
    "userMessageBackgroundColor": "回應字串",
    "chatbotMessageBackgroundShadowEnabled": false,
    "userMessageBackgroundShadowEnabled": false,
    "chatbotMessageGradientEnabled": false,
    "userMessageGradientEnabled": false
  },
  "enableFileUpload": false,
  "enableDisplayCitations": false,
  "toolDisplayMode": "full",
  "enableAskOptionButtons": false,
  "enableConversationHandoff": false,
  "enableDisplayContextUsage": false,
  "enableDisplayThinking": false,
  "enableUserThinkingControl": false,
```

```
  "enableDisplayQueryMetadata": false,
  "enableDisplayHookMarkers": false,
  "hookMarkerTextInputModify": "回應字串",
  "hookMarkerTextOutputModify": "回應字串",
  "hookMarkerTextInputBlock": "回應字串",
  "hookMarkerTextOutputBlock": "回應字串",
  "enableShareConversation": false,
  "enableLocation": false,
  "enableShowPoweredBy": false,
  "poweredByLogo": "https://example.com/file.jpg",
  "enableAnonymous": false,
  "enableDisplayPreviousConversation": false,
  "enableDisplayConversationHistory": false,
  "enableConversationTimer": false,
  "conversationTimerDuration": 456,
  "enableAutoNewConversationOnTimeout": false,
  "enableSatisfactionSurvey": false,
  "satisfactionSurveyDelayMinutes": 456,
  "satisfactionSurveyPrompt": "回應字串",
  "accessType": {},
  "enableThemeModeToggle": false,
  "enableDisplayFontSizeSwitch": false,
  "defaultThemeMode": {},
  "enableDownloadCitations": false,
  "customDomain": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "domain": "回應字串",
    "status": {}
  },
  "enableDisplayChatbotAvatar": false,
  "enableDisplayChatbotName": false,
  "buttonIcon": "https://example.com/file.jpg",
  "enableCodeInterpreter": false,
  "voiceAgentEnabled": false,
  "conversationStartersDisplayCount": 456,
  "includeGreetingInContext": false,
  "tools": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "回應範例名稱",
      "description": "回應範例描述"
    }
  ],
  "preChatFormEnabled": false,
  "preChatFormFields": null,
  "preChatFormTitle": null,
  "preChatFormSubtitle": null,
  "loadingDisplayMode": {},
  "loadingStageCopyByLocale": null,
  "loadingLongWaitCopyByLocale": null,
  "loadingLongWaitThresholdSeconds": 456,
  "loadingAnimationUseSharedAsset": false,
  "loadingAnimationSharedAssetUrl": "https://example.com/file.jpg",
  "loadingAnimationAssetUrlsByStage": null,
  "loadingTypingShowCopy": false,
  "toolCardRunningIconUrl": "https://example.com/file.jpg",
```

```
  "toolCardCompletedIconUrl": "https://example.com/file.jpg",
  "inbox": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應範例名稱",
    "description": "回應範例描述"
  },
  "quickMenu": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應範例名稱",
    "description": "回應範例描述"
  }
}
```


上傳批次 QA 檔案

POST `/api/v1/web-chats/{webchatPk}/batch-qas/`

參數

參數名稱	必填	類型	說明
webchatPk	V	string	

請求內容

請求參數

欄位	類型	必填	說明
file	string (uri)	是	

請求結構範例

```
{
  "file": string (uri)
}
```

請求範例值

```
{
  "file": "https://example.com/file.jpg"
```

```
}
```

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X POST "https://api.maiagent.ai/api/v1/web-chats/550e8400-e29b-41d4-a716-
446655440000/batch-qas/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "file": "https://example.com/file.jpg"
  }'

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// 請求內容 (payload)
const data = {
    "file": "https://example.com/file.jpg"
  };

axios.post("https://api.maiagent.ai/api/v1/web-chats/550e8400-e29b-41d4-a716-
446655440000/batch-qas/", data, config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/web-chats/550e8400-e29b-41d4-a716-
446655440000/batch-qas/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# 請求內容 (payload)
data = {
    "file": "https://example.com/file.jpg"
}

response = requests.post(url, json=data, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->post("https://api.maiagent.ai/api/v1/web-chats/550e8400-e29b-41d4-a716-446655440000/batch-qas/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'file' => 'https://example.com/file.jpg'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 201

回應結構範例

```
{
  "id": string (uuid)
  "file": string (uri)
  "createdAt": string (timestamp)
}
```

回應範例值

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "file": "https://example.com/file.jpg",
  "createdAt": "回應字串"
}
```


匯出批次 QA 為 Excel

GET `/api/v1/web-chats/{webchatPk}/batch-qas/{id}/export-excel/`

參數

參數名稱	必填	類型	說明
`id`	V	string	A UUID string identifying this Chatbot Batch QA File.
`webchatPk`	V	string	

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/web-chats/550e8400-e29b-41d4-a716-
446655440000/batch-qas/550e8400-e29b-41d4-a716-446655440000/export-excel/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/web-chats/550e8400-e29b-41d4-a716-
446655440000/batch-qas/550e8400-e29b-41d4-a716-446655440000/export-excel/", config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/web-chats/550e8400-e29b-41d4-a716-
446655440000/batch-qas/550e8400-e29b-41d4-a716-446655440000/export-excel/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->get("https://api.maiagent.ai/api/v1/web-chats/550e8400-e29b-41d4-a716-446655440000/batch-qas/550e8400-e29b-41d4-a716-446655440000/export-excel/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼	說明
200	Excel 檔案下載

取得 LLM 使用統計

GET `/api/v1/chatbots/{chatbotPk}/llm-usage-statistics/`

參數

參數名稱	必填	類型	說明

`chatbotPk`	V	string	A UUID string identifying this Chatbot ID
`endDate`	X	string	結束日期，格式: YYYY-MM-DD
`startDate`	V	string	開始日期，格式: YYYY-MM-DD
`timeGranularity`	V	string	時間粒度 (day/month)

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X GET "

  -H "Authorization: Api-Key YOUR_API_KEY"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get(" config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->get(" [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
[
  {
    "llmDetails": [
      {
        "chatbotId": string (uuid)
        "wordsCount": integer
        "inputTokenUsage": integer
        "outputTokenUsage": integer
        "cacheCreationInputTokens": integer
        "cacheReadInputTokens": integer
        "totalTokenUsage": integer
        "llmModelId": string (uuid)
        "llmModelName": string
        "llmModelProvider": string
      }
    ]
```

```
    "date"?: string (date) // time_granularity=day 時的日期（非必填）
    "month"?: string (date) // time_granularity=month 時的月份（當月 1 日）（非必填）
    "totalWordsCount": integer
    "totalInputTokenUsage": integer
    "totalOutputTokenUsage": integer
    "totalCacheCreationInputTokens": integer
    "totalCacheReadInputTokens": integer
    "totalTokenUsage": integer
  }
]
```

回應範例值


```
[
  [
    {
      "totalWordsCount": 511,
      "totalInputTokenUsage": 1200,
      "totalOutputTokenUsage": 300,
      "totalCacheCreationInputTokens": 0,
      "totalCacheReadInputTokens": 0,
      "totalTokenUsage": 1500,
      "month": "2025-03-01",
      "llmDetails": [
        {
          "chatbotId": "5b646600-f6e0-4f07-aec7-0207a26c0a9b",
          "wordsCount": 511,
          "inputTokenUsage": 1200,
          "outputTokenUsage": 300,
          "cacheCreationInputTokens": 0,
          "cacheReadInputTokens": 0,
          "totalTokenUsage": 1500,
          "llmModelId": "d4282719-f50e-4a82-88d0-953e202a3383",
          "llmModelName": "GPT-4o-2024-08-06",
          "llmModelProvider": "openai"
        }
      ]
    }
  ]
]
```


狀態碼: 400

回應結構範例

```
{
  "detail"?: string // 非必填
  "valid_types"?: [ // 非必填
    string
  ]
}
```

回應範例值


```
[
  [
    {
      "totalWordsCount": 511,
      "totalInputTokenUsage": 1200,
      "totalOutputTokenUsage": 300,
      "totalCacheCreationInputTokens": 0,
      "totalCacheReadInputTokens": 0,
      "totalTokenUsage": 1500,
      "month": "2025-03-01",
      "llmDetails": [
        {
          "chatbotId": "5b646600-f6e0-4f07-aec7-0207a26c0a9b",
          "wordsCount": 511,
          "inputTokenUsage": 1200,
          "outputTokenUsage": 300,
          "cacheCreationInputTokens": 0,
          "cacheReadInputTokens": 0,
          "totalTokenUsage": 1500,
          "llmModelId": "d4282719-f50e-4a82-88d0-953e202a3383",
          "llmModelName": "GPT-4o-2024-08-06",
          "llmModelProvider": "openai"
        }
      ]
    }
  ]
]
```


取得 AI 助理統計數據

GET `/api/v1/chatbots/{chatbotPk}/statistics/`

參數

參數名稱	必填	類型	說明
`chatbotPk`	V	string	A UUID string identifying this Chatbot ID
`endDate`	X	string	結束日期 (YYYY-MM-DD)，預設今天
`startDate`	X	string	開始日期 (YYYY-MM-DD)，預設今天

`timeGranularity`	V	string	時間粒度 (hour/day/month)

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X GET "

  -H "Authorization: Api-Key YOUR_API_KEY"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get(" config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```python
import requests

url = "
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->get(" [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
[
  {
    "datetime": string // 時間戳（毫秒，字串）
    "messagesCount": integer // 訊息數量
    "conversationsCount": integer // 對話數量
    "avgMessagesPerConversation": number (double) // 平均每對話訊息數
    "avgLikesPerFeedback": number (double) // 滿意度：讚數 / (讚數 + 倒讚數)，無回饋時為 0
    "likesCount": integer // 讚數（不含開場白的回饋；日／月為區間加總）
    "dislikesCount": integer // 倒讚數（不含開場白的回饋；日／月為區間加總）
  }
]
```

回應範例值

```
[
  {
    "datetime": "回應字串",
    "messagesCount": 456,
    "conversationsCount": 456,
    "avgMessagesPerConversation": 456,
    "avgLikesPerFeedback": 456,
    "likesCount": 456,
    "dislikesCount": 456
  }
]
```

呼叫 API 示例 (Shell)

目錄

1. 發送訊息 (串流)
2. 發送訊息 (建立)
3. 發送主動訊息
4. 建立新的對話
5. 取得訊息列表
6. 取得特定訊息
7. 取得對話列表
8. 取得特定對話
9. 重新命名對話
10. 刪除對話
11. 中止 AI 回覆
12. 提交對話滿意度
13. 列出對話事件
14. 指派對話給成員
15. 認領對話
16. 轉接對話給其他成員
17. 轉回 AI 回覆
18. 列出對話產出檔案
19. 分享對話
20. 快速分享對話
21. 列出分享的對話
22. 取得特定分享對話
23. 更新分享對話
24. 刪除分享對話
25. 複製分享對話
26. 取得我的分享列表
27. 建立訊息回饋
28. 更新訊息回饋
29. 刪除訊息回饋
30. 取得對話紀錄列表
31. 取得特定對話紀錄
32. 建立對話紀錄匯出請求
33. 取得對話紀錄匯出狀態

呼叫 API 示例 (Shell)

發送訊息 (串流)

`POST` `/api/v1/chatbots/{chatbotId}/completions/`

參數

參數名稱	必填	類型	說明
`chatbotId`	V	string	

請求內容

請求參數

欄位	類型	必填	說明
conversation	string (uuid)	否	對話的唯一識別碼，如果為空則會建立新對話（可選）
message	object (含 8 個屬性: content, contentPayload, queryMetadata...)	是	要發送的訊息內容
message.content	string	是	訊息的文字內容，若有提供附件則可為空字串
message.contentPayload	object	否	訊息的額外內容負載，JSON 格式（可選）
message.queryMetadata	object	否	查詢元數據，JSON 格式（可選）
message.metadata	object	否	訊息的環境元數據，例如時區等資訊，JSON 格式（可選）
message.attachments	array[AttachmentInput]	否	訊息的附件列表（可選）
message.toolIds	array[string]	否	本次訊息指定啟用的工具 ID 列表（可選）
message.clientTools	array[any]	否	本次訊息由客戶端（如 Chrome extension）提供的工具定義列表

欄位	類型	必填	說明
			（可選）。每筆需含 name(str)、description(str)、input_schema(dict)。LLM 呼叫時後端不會執行，而是回傳 clientToolCall 內容並結束本回合。
message.sender	string (uuid)	否	發送者的 Contact ID（可選）
isStreaming	boolean	否	是否使用串流模式回應，預設為 false（可選）
waitForAttachments	boolean	否	是否等待附件處理完成後再進入 agent workflow，預設為 true（可選）

請求結構範例

```
{
  "conversation"?: string (uuid) // 對話的唯一識別碼，如果為空則會建立新對話（可選） (非必填)
  "message":  // 要發送的訊息內容
  {
    "content": string // 訊息的文字內容，若有提供附件則可為空字串
    "contentPayload"?: object // 訊息的額外內容負載，JSON 格式（可選） (非必填)
    "queryMetadata"?: object // 查詢元數據，JSON 格式（可選） (非必填)
    "metadata"?: object // 訊息的環境元數據，例如時區等資訊，JSON 格式（可選） (非必填)
    "attachments"?: [ // 訊息的附件列表（可選） (非必填)
      {
        "id": string (uuid) // 附件的唯一識別碼
        "type":  // 附件類型，可選值：image（圖片）、video（影片，開發中，尚未支援）、audio（音訊）、sticker（貼圖，開發中，尚未支援）、other（其他）

* `image` - Image
* `video` - Video
* `audio` - Audio
* `sticker` - Sticker
* `other` - Other
        {
        }
        "filename": string // 附件的檔案名稱
        "file": string (uri) // 附件檔案的 URL 位址
      }
    ]
    "toolIds"?: [ // 本次訊息指定啟用的工具 ID 列表（可選） (非必填)
      string (uuid)
    ]
    "clientTools"?: [ // 本次訊息由客戶端（如 Chrome extension）提供的工具定義列表（可
```

```
選）。每筆需含 name(str)、description(str)、input_schema(dict)。LLM 呼叫時後端不會執行，而是回傳 clientToolCall 內容並結束本回合。 (非必填)
      object
    ]
    "sender"?: string (uuid) // 發送者的 Contact ID（可選） (非必填)
  }
  "isStreaming"?: boolean // 是否使用串流模式回應，預設為 false（可選） (非必填)
  "waitForAttachments"?: boolean // 是否等待附件處理完成後再進入 agent workflow，預設為 true（可選） (非必填)
}
```

請求範例值

```
{
  "message": {
    "content": "你好，請介紹一下你自己"
  },
  "is_streaming": true
}
```

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X POST "

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "message": {
      "content": "你好，請介紹一下你自己"
    },
    "is_streaming": true
  }'

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// 請求內容 (payload)
const data = {
    "message": {
      "content": "你好，請介紹一下你自己"
    },
    "is_streaming": true
  };

axios.post(" data, config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# 請求內容 (payload)
data = {
    "message": {
        "content": "你好，請介紹一下你自己"
    },
    "is_streaming": True
}

response = requests.post(url, json=data, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->post(" [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'message' => [
                'content' => '你好，請介紹一下你自己'
            ],
            'is_streaming' => true
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼	說明
200	對話回應內容，若是串流則為事件流
400	請求參數錯誤，可能原因包括：Contact ID 不屬於該組織

發送訊息 (建立)

`POST` `/api/v1/messages/`

請求內容

請求參數

欄位	類型	必填	說明
conversation	string (uuid)	是	
type	string	否	
content	string	否	
contentPayload	object	否	
attachments	array[MessageAttachmentInput]	否	
canvas	object	否	
canvas.name	string	是	
canvas.canvasType	object	是	
canvas.title	string	是	
canvas.content	string	是	
slideTemplate	object (含 3 個屬性: slug, displayName, thumbnailUrls)	否	
slideTemplate.slug	string	是	
slideTemplate.displayName	string	是	
slideTemplate.thumbnailUrls	array[string]	否	
queryMetadata	object	否	查詢元資料，控制可查詢的知識範圍；詳見各端點說明
queryMetadata.knowledgeBases	array[object]	否	可查詢的知識庫清單；空陣列或 null＝全部不可查（無權

欄位	類型	必填	說明
			限），未提供＝不限制
queryMetadata.labelRelations	object	否	標籤過濾條件；conditions 為空陣列＝不做標籤過濾（並非無權限）。必須與 knowledgeBases 一併提供——單獨提供時知識庫檢索不會套用標籤過濾（等同不限制）
queryMetadata.labelRelations.operator	string (enum: AND, OR)	是	標籤條件的組合方式
queryMetadata.labelRelations.conditions	array[any]	否	標籤條件清單，支援巢狀 operator/conditions 組合
metadata	object	否	Message metadata, such as timezone and other environment information
broadcast	boolean	否	
skipCopilotTrigger	boolean	否	
suggestedForId	string (uuid)	否	
skillIds	array[string]	否	Per-message selected skill IDs from the WebChat client (camelCase: skillIds).
toolIds	array[string]	否	Per-message selected tool IDs from the WebChat client (camelCase: toolIds).
templateId	string (uuid)	否	Document/sheet template ID for file-level compilation (camelCase: templateId).

請求結構範例

```
{
  "conversation": string (uuid)
  "type"?: string // 非必填
  "content"?: string // 非必填
  "contentPayload"?: object // 非必填
  "attachments"?: [ // 非必填
    {
      "id": string (uuid) // ID of an already-uploaded attachment, as returned by the attachment upload endpoint. Required: a missing, null or non-UUID id is rejected with HTTP 400 and the message is not created.
      "type"?:  // 非必填
      {
      }
      "filename": string
      "file": string (uri)
      "conversation"?: string (uuid) // 非必填
    }
  ]
  "canvas"?: { // 非必填
  {
    "name": string
    "canvasType":
    {
    }
    "title": string
    "content": string
  }
  }
  "slideTemplate"?:  // 非必填
  {
    "slug": string
    "displayName": string
    "thumbnailUrls"?: [ // 非必填
      string
    ]
  }
  "queryMetadata"?: { // 查詢元資料，控制可查詢的知識範圍；詳見各端點說明 (非必填)
  {
    "knowledgeBases"?: [ // 可查詢的知識庫清單；空陣列或 null＝全部不可查（無權限），未提供＝不限制 (非必填)
      {
        "knowledgeBaseId": string (uuid) // 知識庫 ID
        "chatbotFileIds"?: [ // 檔案 ID 清單（依 hasUserSelectedAll 決定為排除或僅選取） (非必填)
          string (uuid)
        ]
        "knowledgeBaseFileIds"?: [ // 檔案 ID 清單（chatbotFileIds 的新名稱；兩者皆提供
```

```
時以本欄位為準）（非必填）
          string (uuid)
        ]
        "faqIds"?: [ // FAQ ID 清單（依 hasUserSelectedAll 決定為排除或僅選取）（非必填）
          string (uuid)
        ]
        "hasUserSelectedAll"?: boolean // true＝選取知識庫全部內容並排除清單中的項目；
false＝僅選取清單中的項目（非必填）
      }
    ]
    "labelRelations"?: { // 標籤過濾條件；conditions 為空陣列＝不做標籤過濾（並非無權限）。
必須與 knowledgeBases 一併提供—單獨提供時知識庫檢索不會套用標籤過濾（等同不限制）（非必填）
    {
      "operator": string (enum: AND, OR) // 標籤條件的組合方式
      "conditions"?: [ // 標籤條件清單，支援巢狀 operator/conditions 組合（非必填）
        object
      ]
    }
    }
  }
  }
  "metadata"?: object // Message metadata, such as timezone and other environment
information (非必填)
  "broadcast"?: boolean // 非必填
  "skipCopilotTrigger"?: boolean // 非必填
  "suggestedForId"?: string (uuid) // 非必填
  "skillIds"?: [ // Per-message selected skill IDs from the WebChat client
(camelCase: skillIds). (非必填)
    string (uuid)
  ]
  "toolIds"?: [ // Per-message selected tool IDs from the WebChat client
(camelCase: toolIds). (非必填)
    string (uuid)
  ]
  "templateId"?: string (uuid) // Document/sheet template ID for file-level
compilation (camelCase: templateId). (非必填)
}
```

請求範例值

```
{
  "conversation": "c96a0fb9-d106-4b16-8706-3906533bafa2",
  "sender": {
    "id": 2.992461161002561e+38,
    "name": "jessiekuo",
    "avatar": "https://media-dev.maiagent.ai/static/images/default-user-
avatar.png"
  },
```

```
  "type": "incoming",
  "content": "這是一條測試訊息",
  "contentPayload": {
    "content": "這是一條測試訊息",
    "items": [
      {
        "type": "text",
        "text": "這是一條測試訊息",
        "startTimestamp": null,
        "citations": []
      }
    ],
    "metadata": null
  },
  "feedback": "like",
  "createdAt": "1748314926000",
  "attachments": [],
  "citations": [],
  "citationNodes": [],
  "canvas": {
    "id": "034eecd7-e0f4-46e9-88cb-4fefdb5b7ddd",
    "name": "system-architecture-diagram",
    "canvasType": "markdown",
    "title": "系統架構圖",
    "content": "~<del>mermaid\ngraph TD\n    A[用戶] --> B[前端界面]\n    B --> C[API層]\n    C --> D[數據庫]\n</del>~",
    "createdAt": "1748314926000"
  }
}
```


程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X POST "https://api.maiagent.ai/api/v1/messages/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "conversation": "c96a0fb9-d106-4b16-8706-3906533bafa2",
    "sender": {
      "id": 2.992461161002561e+38,
      "name": "jessiekuo",
      "avatar": "https://media-dev.maiagent.ai/static/images/default-user-
avatar.png"
    },
    "type": "incoming",
    "content": "這是一條測試訊息",
    "contentPayload": {
      "content": "這是一條測試訊息",
      "items": [
        {
          "type": "text",
          "text": "這是一條測試訊息",
          "startTimestamp": null,
          "citations": []
        }
      ],
      "metadata": null
    },
    "feedback": "like",
    "createdAt": "1748314926000",
    "attachments": [],
    "citations": [],
    "citationNodes": [],
    "canvas": {
      "id": "034eecd7-e0f4-46e9-88cb-4fefdb5b7ddd",
      "name": "system-architecture-diagram",
      "canvasType": "markdown",
      "title": "系統架構圖",
      "content": "~~~mermaid\ngraph TD\n    A[用戶] --> B[前端界面]\n    B -->
C[API層]\n    C --> D[數據庫]\n~~~",
      "createdAt": "1748314926000"
    }
  }'
```

```
# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// 請求內容 (payload)
const data = {
    "conversation": "c96a0fb9-d106-4b16-8706-3906533bafa2",
    "sender": {
      "id": 2.992461161002561e+38,
      "name": "jessiekuo",
      "avatar": "https://media-dev.maiagent.ai/static/images/default-user-
avatar.png"
    },
    "type": "incoming",
    "content": "這是一條測試訊息",
    "contentPayload": {
      "content": "這是一條測試訊息",
      "items": [
        {
          "type": "text",
          "text": "這是一條測試訊息",
          "startTimestamp": null,
          "citations": []
        }
      ],
      "metadata": null
    },
    "feedback": "like",
    "createdAt": "1748314926000",
    "attachments": [],
    "citations": [],
    "citationNodes": [],
    "canvas": {
      "id": "034eecd7-e0f4-46e9-88cb-4fefdb5b7ddd",
      "name": "system-architecture-diagram",
      "canvasType": "markdown",
      "title": "系統架構圖",
      "content": "~~~mermaid\ngraph TD\n    A[用戶] --> B[前端界面]\n    B -->
```

```
C[API層]\n    C --> D[數據庫]\n~",
      "createdAt": "1748314926000"
    }
  };

axios.post("https://api.maiagent.ai/api/v1/messages/", data, config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/messages/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# 請求內容 (payload)
data = {
    "conversation": "c96a0fb9-d106-4b16-8706-3906533bafa2",
    "sender": {
        "id": 2.992461161002561e+38,
        "name": "jessiekuo",
        "avatar": "https://media-dev.maiagent.ai/static/images/default-user-
avatar.png"
    },
    "type": "incoming",
    "content": "這是一條測試訊息",
    "contentPayload": {
        "content": "這是一條測試訊息",
        "items": [
            {
                "type": "text",
                "text": "這是一條測試訊息",
                "startTimestamp": None,
                "citations": []
            }
        ],
        "metadata": None
    },
    "feedback": "like",
    "createdAt": "1748314926000",
    "attachments": [],
    "citations": [],
    "citationNodes": [],
    "canvas": {
        "id": "034eecd7-e0f4-46e9-88cb-4fefdb5b7ddd",
        "name": "system-architecture-diagram",
        "canvasType": "markdown",
        "title": "系統架構圖",
        "content": "~~~mermaid\ngraph TD\n    A[用戶] --> B[前端界面]\n    B -->
C[API層]\n    C --> D[數據庫]\n~~~",
        "createdAt": "1748314926000"
```

```
    }
}

response = requests.post(url, json=data, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->post("https://api.maiagent.ai/api/v1/messages/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'conversation' => 'c96a0fb9-d106-4b16-8706-3906533bafa2',
            'sender' => [
                'id' => 2.992461161002561e+38,
                'name' => 'jessiekuo',
                'avatar' => 'https://media-
dev.maiagent.ai/static/images/default-user-avatar.png'
            ],
            'type' => 'incoming',
            'content' => '這是一條測試訊息',
            'contentPayload' => [
                'content' => '這是一條測試訊息',
                'items' => [
                    [
                        'type' => 'text',
                        'text' => '這是一條測試訊息',
                        'startTimestamp' => null,
                        'citations' => []
                    ]
                ],
                'metadata' => null
            ],
            'feedback' => 'like',
            'createdAt' => '1748314926000',
            'attachments' => [],
            'citations' => [],
            'citationNodes' => [],
            'canvas' => [
                'id' => '034eecd7-e0f4-46e9-88cb-4fefdb5b7ddd',
                'name' => 'system-architecture-diagram',
                'canvasType' => 'markdown',
                'title' => '系統架構圖',
                'content' => '~~~mermaid
```

```
    graph TD
        A[用戶] --> B[前端界面]
        B --> C[API層]
        C --> D[數據庫]
    ~',
                    'createdAt' => '1748314926000'
                ]
            ]
        ]);

        $data = json_decode($response->getBody(), true);
        echo "成功取得回應:\n";
        print_r($data);
    } catch (Exception $e) {
        echo '請求發生錯誤: ' . $e->getMessage();
    }
    ?>
```

回應內容

狀態碼: 201

回應結構範例

```
{
  "id": string (uuid)
  "conversation": string (uuid)
  "sender":
  {
    "id": string (uuid)
    "name": string
    "avatar": string
    "email"?: string (email) // 非必填
    "phoneNumber"?: string // 非必填
  }
  "type"?: string // 非必填
  "content"?: string // 非必填
  "contentPayload"?: object // 非必填
  "feedback":
  {
    "id": string (uuid)
```

```
    "type":
    {
    }
    "suggestion"?: string // 非必填
    "updatedAt": string (timestamp)
  }
  "createdAt": string (timestamp)
  "attachments"?: [ // 非必填
    {
      "id": string (uuid) // ID of an already-uploaded attachment, as returned by
the attachment upload endpoint. Required: a missing, null or non-UUID id is
rejected with HTTP 400 and the message is not created.
      "type"?:  // 非必填
      {
      }
      "filename": string
      "file": string (uri)
      "expiresAt": string // ISO datetime when this attachment will be auto-
deleted.

For conversation-bound attachments: conversation.last_message_created_at +
retention_days.
For attachments without a conversation: created_at + retention_days.
Returns None when cleanup is disabled (effective_from not set).
      "conversation"?: string (uuid) // 非必填
    }
  ]
  "citations": [
    {
      "id": string (uuid)
      "filename": string // 檔案名稱
      "file": string (uri) // 要上傳的檔案
      "fileType": string
      "knowledgeBase"?:  // 非必填
      {
        "id": string (uuid)
        "name": string
      }
      "size": integer
      "status":
      {
      }
      "parser":
      {
        "id": string (uuid)
        "name": string
        "provider":
        {
        }
        "isTimestampSttProvider": boolean
```

```
      }
      "labels"?: [ // 非必填
        {
          "id": string (uuid)
          "name": string
        }
      ]
      "rawUserDefineMetadata"?: object // 非必填
      "speakerLabels": [
        {
          "id": string (uuid)
          "originalLabel": string // Original speaker label from diarization
(e.g., SPEAKER_00)
          "customName"?: string // User-defined speaker name (e.g., John) (非必填)
          "displayName": string
        }
      ]
      "vectorStorageSize": integer // Size of vectors for this file in
Elasticsearch (bytes)
      "chunksCount": integer // Number of chunks/nodes generated from this file
      "waitingTime": number (double)
      "processingTime": number (double)
      "processingTimeDetails": object
      "previewUrl": string // 簡報（pptx/ppt）回傳可預覽的 pdf 衍生檔 URL（前端用 PDF 預
覽器顯示）；其餘為 None。

用與 `file` 欄位相同的 CustomizedFileFieldSerializer 產 URL，確保格式一致（含各
storage provider 的 presign/host 規則）。不可用 get_absolute_url()——它產出的 URL 格式錯
誤。
      "createdAt": string (timestamp)
    }
  ]
  "citationNodes": [
    {
      "chatbotTextNode": {
      {
        "id": string (uuid)
        "charactersCount": integer
        "hitsCount": integer
        "text": string
        "updatedAt": string (timestamp)
        "filename": string
        "chatbotFile": object // 返回 ChatbotFile 的完整資訊，包含檔案 URL 和類型，以支
援前端圖片預覽
        "knowledgeBaseFile": object // 與 get_chatbot_file 相同，提供向後兼容
        "pageNumber": integer // Backward-compatible alias of ``page_start``.
        "pageStart": integer
        "pageEnd": integer
        "citationTitle": string // Source title shown on the inline citation hover
card.
```

```
        "citationDescription": string // Source description shown on the inline
citation hover card.
        "citationQuote": string // Quoted text snippet shown on the inline
citation hover card.
        "hasImage": boolean // 判斷是否包含圖片（檢查檔案類型或 text 中的 Markdown 圖片）
        "imageUrl": string // 提取圖片 URL（優先使用檔案 URL，否則從 Markdown 提取）
        "displayText": string // 返回移除圖片 Markdown 標記的完整文字
        "displayTitle": string // 返回顯示標題（fallback: citation_title ->
filename）
        "highlightedText": string // Return text with matched terms wrapped in
``<mark>`` tags.

Priority:
1. ES/OpenSearch native highlight (set by retrieve_api via
``_es_highlighted_text``)
2. Python regex fallback (keyword-based, works for all backends)
        "labels": [
          {
            "id": string (uuid)
            "name": string
          }
        ]
        "rawUserDefineMetadata"?: object // Metadata keys and values defined by
the user. (非必填)
        "metadataEnabledForSearch": object // Map each user-defined metadata key
on this node to whether it was sent into the LLM.

A key reaches the LLM only when its ``MetadataKey.enabled_for_search`` is True
*and*
the node carries a value for it. Since this maps over ``raw_user_define_metadata``
(the keys the cited-documents block displays, all of which have a value),
``enabled_for_search`` alone decides the flag. The source of truth is the node's
knowledge base ``MetadataKey`` current setting, matching the AI Search indicator.
        "startCharIdx": integer
        "endCharIdx": integer
      }
      }
      "score"?: number (double) // 非必填
      "displayScore": integer
      "citationNumber"?: integer // Citation number matching the [1], [2] markers
in the reply content (非必填)
      "highlightedText"?: string // ES/OpenSearch highlight result with <mark>
tags (非必填)
    }
  ]
  "canvas"?: { // 非必填
  {
    "id": string (uuid)
    "name": string
    "canvasType":
```

```
    {
    }
    "title": string
    "content": string
    "createdAt": string (timestamp)
  }
  }
  "slideTemplate"?:  // 非必填
  {
    "slug": string
    "displayName": string
    "thumbnailUrls"?: [ // 非必填
      string
    ]
  }
  "queryMetadata"?: { // 查詢元資料，控制可查詢的知識範圍；詳見各端點說明 (非必填)
  {
    "knowledgeBases"?: [ // 可查詢的知識庫清單；空陣列或 null＝全部不可查（無權限），未提供＝不限制 (非必填)
      {
        "knowledgeBaseId": string (uuid) // 知識庫 ID
        "chatbotFileIds"?: [ // 檔案 ID 清單（依 hasUserSelectedAll 決定為排除或僅選取） (非必填)
          string (uuid)
        ]
        "knowledgeBaseFileIds"?: [ // 檔案 ID 清單（chatbotFileIds 的新名稱；兩者皆提供時以本欄位為準） (非必填)
          string (uuid)
        ]
        "faqIds"?: [ // FAQ ID 清單（依 hasUserSelectedAll 決定為排除或僅選取） (非必填)
          string (uuid)
        ]
        "hasUserSelectedAll"?: boolean // true＝選取知識庫全部內容並排除清單中的項目；false＝僅選取清單中的項目 (非必填)
      }
    ]
    "labelRelations"?: { // 標籤過濾條件；conditions 為空陣列＝不做標籤過濾（並非無權限）。必須與 knowledgeBases 一併提供—單獨提供時知識庫檢索不會套用標籤過濾（等同不限制） (非必填)
    {
      "operator": string (enum: AND, OR) // 標籤條件的組合方式
      "conditions"?: [ // 標籤條件清單，支援巢狀 operator/conditions 組合 (非必填)
        object
      ]
    }
    }
  }
  }
  "metadata"?: object // Message metadata, such as timezone and other environment information (非必填)
  "recordId": string // 返回 Message 對應的 ChatbotRecord ID
```

```
Note:
    對於未儲存的 Message（如 streaming 中的虛擬 Message），直接返回 None，
    避免觸發 OneToOneField reverse relation 的 DB 查詢（N+1 問題）。
  "broadcast"?: boolean // 非必填
  "skipCopilotTrigger"?: boolean // 非必填
  "activeRevisionNumber": integer
  "revisions": [
    {
      "id": string (uuid)
      "revisionNumber": integer
      "content": string
      "contentPayload": object
      "isActive": boolean
      "createdAt": string (timestamp)
    }
  ]
  "suggestedForId"?: string (uuid) // 非必填
  "suggestionStatus": string
  "suggestionTriggerSource": string
  "suggestionError": string
  "retryCount": integer // How many times the LLM call was auto-retried during
this message generation. Currently only Bedrock first-chunk stall triggers retry
(max 1). Detailed per-attempt records live in metadata["retry_attempts"].
  "skillIds"?: [ // Per-message selected skill IDs from the WebChat client
(camelCase: skillIds). (非必填)
    string (uuid)
  ]
  "toolIds"?: [ // Per-message selected tool IDs from the WebChat client
(camelCase: toolIds). (非必填)
    string (uuid)
  ]
  "templateId"?: string (uuid) // Document/sheet template ID for file-level
compilation (camelCase: templateId). (非必填)
  "videoGeneration": object // Return the latest GeneratedVideo state for FE
reload recovery;
``errorMessage`` is blank to match the socket emit (raw value stays on the DB
row).
  "isGreeting": boolean // Whether this message is a greeting message.
}
```

回應範例值

```
{
  "conversation": "c96a0fb9-d106-4b16-8706-3906533bafa2",
  "sender": {
    "id": 2.992461161002561e+38,
    "name": "jessiekuo",
```

```
    "avatar": "https://media-dev.maiagent.ai/static/images/default-user-
avatar.png"
  },
  "type": "incoming",
  "content": "這是一條測試訊息",
  "contentPayload": {
    "content": "這是一條測試訊息",
    "items": [
      {
        "type": "text",
        "text": "這是一條測試訊息",
        "startTimestamp": null,
        "citations": []
      }
    ],
    "metadata": null
  },
  "feedback": "like",
  "createdAt": "1748314926000",
  "attachments": [],
  "citations": [],
  "citationNodes": [],
  "canvas": {
    "id": "034eecd7-e0f4-46e9-88cb-4fefdb5b7ddd",
    "name": "system-architecture-diagram",
    "canvasType": "markdown",
    "title": "系統架構圖",
    "content": "~<del>mermaid\ngraph TD\n    A[用戶] --> B[前端界面]\n    B -->
C[API層]\n    C --> D[數據庫]\n</del>~",
    "createdAt": "1748314926000"
  }
}
```


發送主動訊息

POST `/api/v1/messages/outgoing/`

請求內容

請求參數

欄位	類型	必填	說明
conversation	string (uuid)	是	
type	string	否	
content	string	否	
contentPayload	object	否	
attachments	array[MessageAttachmentInput]	否	
canvas	object	否	
canvas.name	string	是	
canvas.canvasType	object	是	
canvas.title	string	是	
canvas.content	string	是	
slideTemplate	object (含 3 個屬性: slug, displayName, thumbnailUrls)	否	
slideTemplate.slug	string	是	
slideTemplate.displayName	string	是	
slideTemplate.thumbnailUrls	array[string]	否	
queryMetadata	object	否	查詢元資料，控制可查詢的知識範圍；詳見各端點說明
queryMetadata.knowledgeBases	array[object]	否	可查詢的知識庫清單；空陣列或 null＝全部不可查（無權限），未提供＝不限制
queryMetadata.labelRelations	object	否	標籤過濾條件；conditions 為空陣列＝不做標籤過濾（並非無權限）。必須與 knowledgeBases 一併提供——單獨提供時知識庫檢索不會套用標籤過濾（等同不限制）
queryMetadata.labelRelations.operator	string (enum: AND, OR)	是	標籤條件的組合方式

欄位	類型	必填	說明
queryMetadata.labelRelations.conditions	array[any]	否	標籤條件清單，支援巢狀 operator/conditions 組合
metadata	object	否	Message metadata, such as timezone and other environment information
broadcast	boolean	否	
skipCopilotTrigger	boolean	否	
suggestedForId	string (uuid)	否	
skillIds	array[string]	否	Per-message selected skill IDs from the WebChat client (camelCase: skillIds).
toolIds	array[string]	否	Per-message selected tool IDs from the WebChat client (camelCase: toolIds).
templateId	string (uuid)	否	Document/sheet template ID for file-level compilation (camelCase: templateId).

請求結構範例

```
{
  "conversation": string (uuid)
  "type"?: string // 非必填
  "content"?: string // 非必填
  "contentPayload"?: object // 非必填
  "attachments"?: [ // 非必填
    {
      "id": string (uuid) // ID of an already-uploaded attachment, as returned by the attachment upload endpoint. Required: a missing, null or non-UUID id is rejected with HTTP 400 and the message is not created.
```

```
      "type"?:  // 非必填
      {
      }
      "filename": string
      "file": string (uri)
      "conversation"?: string (uuid) // 非必填
    }
  ]
  "canvas"?: { // 非必填
  {
    "name": string
    "canvasType":
    {
    }
    "title": string
    "content": string
  }
  }
  "slideTemplate"?:  // 非必填
  {
    "slug": string
    "displayName": string
    "thumbnailUrls"?: [ // 非必填
      string
    ]
  }
  "queryMetadata"?: { // 查詢元資料，控制可查詢的知識範圍；詳見各端點說明 (非必填)
  {
    "knowledgeBases"?: [ // 可查詢的知識庫清單；空陣列或 null＝全部不可查（無權限），未提供＝不限制 (非必填)
      {
        "knowledgeBaseId": string (uuid) // 知識庫 ID
        "chatbotFileIds"?: [ // 檔案 ID 清單（依 hasUserSelectedAll 決定為排除或僅選取） (非必填)
          string (uuid)
        ]
        "knowledgeBaseFileIds"?: [ // 檔案 ID 清單（chatbotFileIds 的新名稱；兩者皆提供時以本欄位為準） (非必填)
          string (uuid)
        ]
        "faqIds"?: [ // FAQ ID 清單（依 hasUserSelectedAll 決定為排除或僅選取） (非必填)
          string (uuid)
        ]
        "hasUserSelectedAll"?: boolean // true＝選取知識庫全部內容並排除清單中的項目；false＝僅選取清單中的項目 (非必填)
      }
    ]
    "labelRelations"?: { // 標籤過濾條件；conditions 為空陣列＝不做標籤過濾（並非無權限）。必須與 knowledgeBases 一併提供——單獨提供時知識庫檢索不會套用標籤過濾（等同不限制） (非必填)
    {
```

```
      "operator": string (enum: AND, OR) // 標籤條件的組合方式
      "conditions"?: [ // 標籤條件清單，支援巢狀 operator/conditions 組合 (非必填)
        object
      ]
    }
    }
  }
  }
  "metadata"?: object // Message metadata, such as timezone and other environment
information (非必填)
  "broadcast"?: boolean // 非必填
  "skipCopilotTrigger"?: boolean // 非必填
  "suggestedForId"?: string (uuid) // 非必填
  "skillIds"?: [ // Per-message selected skill IDs from the WebChat client
(camelCase: skillIds). (非必填)
    string (uuid)
  ]
  "toolIds"?: [ // Per-message selected tool IDs from the WebChat client
(camelCase: toolIds). (非必填)
    string (uuid)
  ]
  "templateId"?: string (uuid) // Document/sheet template ID for file-level
compilation (camelCase: templateId). (非必填)
}
```

請求範例值

```
{
  "conversation": "550e8400-e29b-41d4-a716-446655440000",
  "type": "範例字串",
  "content": "您好！我想了解產品資訊。",
  "contentPayload": null,
  "attachments": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "type": {},
      "filename": "document.pdf",
      "file": "https://example.com/file.jpg",
      "conversation": "550e8400-e29b-41d4-a716-446655440000"
    }
  ],
  "canvas": {
    "name": "範例名稱",
    "canvasType": {},
    "title": "範例名稱",
    "content": "您好！我想了解產品資訊。"
  },
  "slideTemplate": {
```

```
    "slug": "範例字串",
    "displayName": "範例字串",
    "thumbnailUrls": [
      "範例字串"
    ]
  },
  "queryMetadata": {
    "knowledgeBases": [
      {
        "knowledgeBaseId": "550e8400-e29b-41d4-a716-446655440000",
        "chatbotFileIds": [
          "550e8400-e29b-41d4-a716-446655440000"
        ],
        "knowledgeBaseFileIds": [
          "550e8400-e29b-41d4-a716-446655440000"
        ],
        "faqIds": [
          "550e8400-e29b-41d4-a716-446655440000"
        ],
        "hasUserSelectedAll": true
      }
    ],
    "labelRelations": {
      "operator": "AND",
      "conditions": [
        null
      ]
    }
  },
  "metadata": null,
  "broadcast": true,
  "skipCopilotTrigger": true,
  "suggestedForId": "550e8400-e29b-41d4-a716-446655440000",
  "skillIds": [
    "550e8400-e29b-41d4-a716-446655440000"
  ],
  "toolIds": [
    "550e8400-e29b-41d4-a716-446655440000"
  ],
  "templateId": "550e8400-e29b-41d4-a716-446655440000"
}
```


程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X POST "https://api.maiagent.ai/api/v1/messages/outgoing/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "conversation": "550e8400-e29b-41d4-a716-446655440000",
    "type": "範例字串",
    "content": "您好！我想了解產品資訊。",
    "contentPayload": null,
    "attachments": [
      {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "type": {},
        "filename": "document.pdf",
        "file": "https://example.com/file.jpg",
        "conversation": "550e8400-e29b-41d4-a716-446655440000"
      }
    ],
    "canvas": {
      "name": "範例名稱",
      "canvasType": {},
      "title": "範例名稱",
      "content": "您好！我想了解產品資訊。"
    },
    "slideTemplate": {
      "slug": "範例字串",
      "displayName": "範例字串",
      "thumbnailUrls": [
        "範例字串"
      ]
    },
    "queryMetadata": {
      "knowledgeBases": [
        {
          "knowledgeBaseId": "550e8400-e29b-41d4-a716-446655440000",
          "chatbotFileIds": [
            "550e8400-e29b-41d4-a716-446655440000"
          ],
          "knowledgeBaseFileIds": [
            "550e8400-e29b-41d4-a716-446655440000"
          ],
```

```
            "faqIds": [
              "550e8400-e29b-41d4-a716-446655440000"
            ],
            "hasUserSelectedAll": true
          }
        ],
        "labelRelations": {
          "operator": "AND",
          "conditions": [
            null
          ]
        }
      },
      "metadata": null,
      "broadcast": true,
      "skipCopilotTrigger": true,
      "suggestedForId": "550e8400-e29b-41d4-a716-446655440000",
      "skillIds": [
        "550e8400-e29b-41d4-a716-446655440000"
      ],
      "toolIds": [
        "550e8400-e29b-41d4-a716-446655440000"
      ],
      "templateId": "550e8400-e29b-41d4-a716-446655440000"
    }'

  # 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// 請求內容 (payload)
const data = {
    "conversation": "550e8400-e29b-41d4-a716-446655440000",
    "type": "範例字串",
    "content": "您好！我想了解產品資訊。",
    "contentPayload": null,
    "attachments": [
      {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "type": {},
        "filename": "document.pdf",
        "file": "https://example.com/file.jpg",
        "conversation": "550e8400-e29b-41d4-a716-446655440000"
      }
    ],
    "canvas": {
      "name": "範例名稱",
      "canvasType": {},
      "title": "範例名稱",
      "content": "您好！我想了解產品資訊。"
    },
    "slideTemplate": {
      "slug": "範例字串",
      "displayName": "範例字串",
      "thumbnailUrls": [
        "範例字串"
      ]
    },
    "queryMetadata": {
      "knowledgeBases": [
        {
          "knowledgeBaseId": "550e8400-e29b-41d4-a716-446655440000",
          "chatbotFileIds": [
            "550e8400-e29b-41d4-a716-446655440000"
```

```
          ],
          "knowledgeBaseFileIds": [
            "550e8400-e29b-41d4-a716-446655440000"
          ],
          "faqIds": [
            "550e8400-e29b-41d4-a716-446655440000"
          ],
          "hasUserSelectedAll": true
        }
      ],
      "labelRelations": {
        "operator": "AND",
        "conditions": [
          null
        ]
      }
    },
    "metadata": null,
    "broadcast": true,
    "skipCopilotTrigger": true,
    "suggestedForId": "550e8400-e29b-41d4-a716-446655440000",
    "skillIds": [
      "550e8400-e29b-41d4-a716-446655440000"
    ],
    "toolIds": [
      "550e8400-e29b-41d4-a716-446655440000"
    ],
    "templateId": "550e8400-e29b-41d4-a716-446655440000"
  };

axios.post("https://api.maiagent.ai/api/v1/messages/outgoing/", data, config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/messages/outgoing/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# 請求內容 (payload)
data = {
    "conversation": "550e8400-e29b-41d4-a716-446655440000",
    "type": "範例字串",
    "content": "您好！我想了解產品資訊。",
    "contentPayload": None,
    "attachments": [
        {
            "id": "550e8400-e29b-41d4-a716-446655440000",
            "type": {},
            "filename": "document.pdf",
            "file": "https://example.com/file.jpg",
            "conversation": "550e8400-e29b-41d4-a716-446655440000"
        }
    ],
    "canvas": {
        "name": "範例名稱",
        "canvasType": {},
        "title": "範例名稱",
        "content": "您好！我想了解產品資訊。"
    },
    "slideTemplate": {
        "slug": "範例字串",
        "displayName": "範例字串",
        "thumbnailUrls": [
            "範例字串"
        ]
    },
    "queryMetadata": {
        "knowledgeBases": [
            {
                "knowledgeBaseId": "550e8400-e29b-41d4-a716-446655440000",
                "chatbotFileIds": [
                    "550e8400-e29b-41d4-a716-446655440000"
                ],
                "knowledgeBaseFileIds": [
```

```
                    "550e8400-e29b-41d4-a716-446655440000"
                ],
                "faqIds": [
                    "550e8400-e29b-41d4-a716-446655440000"
                ],
                "hasUserSelectedAll": True
            }
        ],
        "labelRelations": {
            "operator": "AND",
            "conditions": [
                None
            ]
        }
    },
    "metadata": None,
    "broadcast": True,
    "skipCopilotTrigger": True,
    "suggestedForId": "550e8400-e29b-41d4-a716-446655440000",
    "skillIds": [
        "550e8400-e29b-41d4-a716-446655440000"
    ],
    "toolIds": [
        "550e8400-e29b-41d4-a716-446655440000"
    ],
    "templateId": "550e8400-e29b-41d4-a716-446655440000"
}

response = requests.post(url, json=data, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>post("https://api.maiagent.ai/api/v1/messages/outgoing/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'conversation' => '550e8400-e29b-41d4-a716-446655440000',
            'type' => '範例字串',
            'content' => '您好！我想了解產品資訊。',
            'contentPayload' => null,
            'attachments' => [
                [
                    'id' => '550e8400-e29b-41d4-a716-446655440000',
                    'type' => new \stdClass(),
                    'filename' => 'document.pdf',
                    'file' => 'https://example.com/file.jpg',
                    'conversation' => '550e8400-e29b-41d4-a716-446655440000'
                ]
            ],
            'canvas' => [
                'name' => '範例名稱',
                'canvasType' => new \stdClass(),
                'title' => '範例名稱',
                'content' => '您好！我想了解產品資訊。'
            ],
            'slideTemplate' => [
                'slug' => '範例字串',
                'displayName' => '範例字串',
                'thumbnailUrls' => [
                    '範例字串'
                ]
            ],
            'queryMetadata' => [
                'knowledgeBases' => [
                    [
                        'knowledgeBaseId' => '550e8400-e29b-41d4-a716-
446655440000',
```

```
                        'chatbotFileIds' => [
                            '550e8400-e29b-41d4-a716-446655440000'
                        ],
                        'knowledgeBaseFileIds' => [
                            '550e8400-e29b-41d4-a716-446655440000'
                        ],
                        'faqIds' => [
                            '550e8400-e29b-41d4-a716-446655440000'
                        ],
                        'hasUserSelectedAll' => true
                    ]
                ],
                'labelRelations' => [
                    'operator' => 'AND',
                    'conditions' => [
                        null
                    ]
                ]
            ],
            'metadata' => null,
            'broadcast' => true,
            'skipCopilotTrigger' => true,
            'suggestedForId' => '550e8400-e29b-41d4-a716-446655440000',
            'skillIds' => [
                '550e8400-e29b-41d4-a716-446655440000'
            ],
            'toolIds' => [
                '550e8400-e29b-41d4-a716-446655440000'
            ],
            'templateId' => '550e8400-e29b-41d4-a716-446655440000'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 201

回應結構範例

```
{
  "id": string (uuid)
  "conversation": string (uuid)
  "sender":
  {
    "id": string (uuid)
    "name": string
    "avatar": string
    "email"?: string (email) // 非必填
    "phoneNumber"?: string // 非必填
  }
  "type"?: string // 非必填
  "content"?: string // 非必填
  "contentPayload"?: object // 非必填
  "feedback":
  {
    "id": string (uuid)
    "type":
    {
    }
    "suggestion"?: string // 非必填
    "updatedAt": string (timestamp)
  }
  "createdAt": string (timestamp)
  "attachments"?: [ // 非必填
    {
      "id": string (uuid) // ID of an already-uploaded attachment, as returned by
the attachment upload endpoint. Required: a missing, null or non-UUID id is
rejected with HTTP 400 and the message is not created.
      "type"?:  // 非必填
      {
      }
      "filename": string
      "file": string (uri)
      "expiresAt": string // ISO datetime when this attachment will be auto-
deleted.

For conversation-bound attachments: conversation.last_message_created_at +
retention_days.
For attachments without a conversation: created_at + retention_days.
Returns None when cleanup is disabled (effective_from not set).
      "conversation"?: string (uuid) // 非必填
    }
  ]
  "citations": [
```

```
    {
      "id": string (uuid)
      "filename": string // 檔案名稱
      "file": string (uri) // 要上傳的檔案
      "fileType": string
      "knowledgeBase"?:  // 非必填
      {
        "id": string (uuid)
        "name": string
      }
      "size": integer
      "status":
      {
      }
      "parser":
      {
        "id": string (uuid)
        "name": string
        "provider":
        {
        }
        "isTimestampSttProvider": boolean
      }
      "labels"?: [ // 非必填
        {
          "id": string (uuid)
          "name": string
        }
      ]
      "rawUserDefineMetadata"?: object // 非必填
      "speakerLabels": [
        {
          "id": string (uuid)
          "originalLabel": string // Original speaker label from diarization
(e.g., SPEAKER_00)
          "customName"?: string // User-defined speaker name (e.g., John) (非必填)
          "displayName": string
        }
      ]
      "vectorStorageSize": integer // Size of vectors for this file in
Elasticsearch (bytes)
      "chunksCount": integer // Number of chunks/nodes generated from this file
      "waitingTime": number (double)
      "processingTime": number (double)
      "processingTimeDetails": object
      "previewUrl": string // 簡報（pptx/ppt）回傳可預覽的 pdf 衍生檔 URL（前端用 PDF 預
覽器顯示）；其餘為 None。

用與 `file` 欄位相同的 CustomizedFileFieldSerializer 產 URL，確保格式一致（含各
storage provider 的 presign/host 規則）。不可用 get_absolute_url()——它產出的 URL 格式錯
```

```
誤。
      "createdAt": string (timestamp)
    }
  ]
  "citationNodes": [
    {
      "chatbotTextNode": {
      {
        "id": string (uuid)
        "charactersCount": integer
        "hitsCount": integer
        "text": string
        "updatedAt": string (timestamp)
        "filename": string
        "chatbotFile": object // 返回 ChatbotFile 的完整資訊，包含檔案 URL 和類型，以支援前端圖片預覽
        "knowledgeBaseFile": object // 與 get_chatbot_file 相同，提供向後兼容
        "pageNumber": integer // Backward-compatible alias of ``page_start``.
        "pageStart": integer
        "pageEnd": integer
        "citationTitle": string // Source title shown on the inline citation hover card.
        "citationDescription": string // Source description shown on the inline citation hover card.
        "citationQuote": string // Quoted text snippet shown on the inline citation hover card.
        "hasImage": boolean // 判斷是否包含圖片（檢查檔案類型或 text 中的 Markdown 圖片）
        "imageUrl": string // 提取圖片 URL（優先使用檔案 URL，否則從 Markdown 提取）
        "displayText": string // 返回移除圖片 Markdown 標記的完整文字
        "displayTitle": string // 返回顯示標題（fallback: citation_title -> filename）
        "highlightedText": string // Return text with matched terms wrapped in ``<mark>`` tags.

Priority:
1. ES/OpenSearch native highlight (set by retrieve_api via ``_es_highlighted_text``)
2. Python regex fallback (keyword-based, works for all backends)
        "labels": [
          {
            "id": string (uuid)
            "name": string
          }
        ]
        "rawUserDefineMetadata"?: object // Metadata keys and values defined by the user. (非必填)
        "metadataEnabledForSearch": object // Map each user-defined metadata key on this node to whether it was sent into the LLM.

A key reaches the LLM only when its ``MetadataKey.enabled_for_search`` is True
```

```
*and*
the node carries a value for it. Since this maps over ``raw_user_define_metadata``
(the keys the cited-documents block displays, all of which have a value),
``enabled_for_search`` alone decides the flag. The source of truth is the node's
knowledge base ``MetadataKey`` current setting, matching the AI Search indicator.
        "startCharIdx": integer
        "endCharIdx": integer
      }
      }
      "score"?: number (double) // 非必填
      "displayScore": integer
      "citationNumber"?: integer // Citation number matching the [1], [2] markers
in the reply content (非必填)
      "highlightedText"?: string // ES/OpenSearch highlight result with <mark>
tags (非必填)
    }
  ]
  "canvas"?: { // 非必填
  {
    "id": string (uuid)
    "name": string
    "canvasType":
    {
    }
    "title": string
    "content": string
    "createdAt": string (timestamp)
  }
  }
  "slideTemplate"?:  // 非必填
  {
    "slug": string
    "displayName": string
    "thumbnailUrls"?: [ // 非必填
      string
    ]
  }
  "queryMetadata"?: { // 查詢元資料，控制可查詢的知識範圍；詳見各端點說明 (非必填)
  {
    "knowledgeBases"?: [ // 可查詢的知識庫清單；空陣列或 null＝全部不可查（無權限），未提供＝
不限制 (非必填)
      {
        "knowledgeBaseId": string (uuid) // 知識庫 ID
        "chatbotFileIds"?: [ // 檔案 ID 清單（依 hasUserSelectedAll 決定為排除或僅選
取） (非必填)
          string (uuid)
        ]
        "knowledgeBaseFileIds"?: [ // 檔案 ID 清單（chatbotFileIds 的新名稱；兩者皆提供
時以本欄位為準） (非必填)
          string (uuid)
```

```
        ]
        "faqIds"?: [ // FAQ ID 清單（依 hasUserSelectedAll 決定為排除或僅選取） (非必填)
          string (uuid)
        ]
        "hasUserSelectedAll"?: boolean // true＝選取知識庫全部內容並排除清單中的項目；
false＝僅選取清單中的項目 (非必填)
      }
    ]
    "labelRelations"?: { // 標籤過濾條件；conditions 為空陣列＝不做標籤過濾（並非無權限）。
必須與 knowledgeBases 一併提供—單獨提供時知識庫檢索不會套用標籤過濾（等同不限制） (非必填)
    {
      "operator": string (enum: AND, OR) // 標籤條件的組合方式
      "conditions"?: [ // 標籤條件清單，支援巢狀 operator/conditions 組合 (非必填)
        object
      ]
    }
    }
  }
  }
  "metadata"?: object // Message metadata, such as timezone and other environment
information (非必填)
  "recordId": string // 返回 Message 對應的 ChatbotRecord ID

Note:
    對於未儲存的 Message（如 streaming 中的虛擬 Message)，直接返回 None，
    避免觸發 OneToOneField reverse relation 的 DB 查詢（N+1 問題)。
  "broadcast"?: boolean // 非必填
  "skipCopilotTrigger"?: boolean // 非必填
  "activeRevisionNumber": integer
  "revisions": [
    {
      "id": string (uuid)
      "revisionNumber": integer
      "content": string
      "contentPayload": object
      "isActive": boolean
      "createdAt": string (timestamp)
    }
  ]
  "suggestedForId"?: string (uuid) // 非必填
  "suggestionStatus": string
  "suggestionTriggerSource": string
  "suggestionError": string
  "retryCount": integer // How many times the LLM call was auto-retried during
this message generation. Currently only Bedrock first-chunk stall triggers retry
(max 1). Detailed per-attempt records live in metadata["retry_attempts"].
  "skillIds"?: [ // Per-message selected skill IDs from the WebChat client
(camelCase: skillIds). (非必填)
    string (uuid)
  ]
```

```
  "toolIds"?: [ // Per-message selected tool IDs from the WebChat client
(camelCase: toolIds). (非必填)
    string (uuid)
  ]
  "templateId"?: string (uuid) // Document/sheet template ID for file-level
compilation (camelCase: templateId). (非必填)
  "videoGeneration": object // Return the latest GeneratedVideo state for FE
reload recovery;
``errorMessage`` is blank to match the socket emit (raw value stays on the DB
row).
  "isGreeting": boolean // Whether this message is a greeting message.
}
```

回應範例值

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "conversation": "550e8400-e29b-41d4-a716-446655440000",
  "sender": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應字串",
    "avatar": "回應字串",
    "email": "response@example.com",
    "phoneNumber": "回應字串"
  },
  "type": "回應字串",
  "content": "回應字串",
  "contentPayload": null,
  "feedback": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "type": {},
    "suggestion": "回應字串",
    "updatedAt": "回應字串"
  },
  "createdAt": "回應字串",
  "attachments": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "type": {},
      "filename": "回應字串",
      "file": "https://example.com/file.jpg",
      "expiresAt": "回應字串",
      "conversation": "550e8400-e29b-41d4-a716-446655440000"
    }
  ],
  "citations": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
```

```
      "filename": "回應字串",
      "file": "https://example.com/file.jpg",
      "fileType": "回應字串",
      "knowledgeBase": {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "name": "回應字串"
      },
      "size": 456,
      "status": {},
      "parser": {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "name": "回應字串",
        "provider": {},
        "isTimestampSttProvider": false
      },
      "labels": [
        {
          "id": "550e8400-e29b-41d4-a716-446655440000",
          "name": "回應字串"
        }
      ],
      "rawUserDefineMetadata": null,
      "speakerLabels": [
        {
          "id": "550e8400-e29b-41d4-a716-446655440000",
          "originalLabel": "回應字串",
          "customName": "回應字串",
          "displayName": "回應字串"
        }
      ],
      "vectorStorageSize": 456,
      "chunksCount": 456,
      "waitingTime": 456,
      "processingTime": 456,
      "processingTimeDetails": null,
      "previewUrl": "回應字串",
      "createdAt": "回應字串"
    }
  ],
  "citationNodes": [
    {
      "chatbotTextNode": {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "charactersCount": 456,
        "hitsCount": 456,
        "text": "回應字串",
        "updatedAt": "回應字串",
        "filename": "回應字串",
        "chatbotFile": {
          "id": "550e8400-e29b-41d4-a716-446655440000",
```

```
          "name": "回應範例名稱",
          "description": "回應範例描述"
        },
        "knowledgeBaseFile": {
          "id": "550e8400-e29b-41d4-a716-446655440000",
          "name": "回應範例名稱",
          "description": "回應範例描述"
        },
        "pageNumber": 456,
        "pageStart": 456,
        "pageEnd": 456,
        "citationTitle": "回應字串",
        "citationDescription": "回應字串",
        "citationQuote": "回應字串",
        "hasImage": false,
        "imageUrl": "回應字串",
        "displayText": "回應字串",
        "displayTitle": "回應字串",
        "highlightedText": "回應字串",
        "labels": [
          {
            "id": "550e8400-e29b-41d4-a716-446655440000",
            "name": "回應字串"
          }
        ],
        "rawUserDefineMetadata": null,
        "metadataEnabledForSearch": {
          "key1": "value1",
          "key2": "value2",
          "createdAt": "2025-01-01T00:00:00.000Z"
        },
        "startCharIdx": 456,
        "endCharIdx": 456
      },
      "score": 456,
      "displayScore": 456,
      "citationNumber": 456,
      "highlightedText": "回應字串"
    }
  ],
  "canvas": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應字串",
    "canvasType": {},
    "title": "回應字串",
    "content": "回應字串",
    "createdAt": "回應字串"
  },
  "slideTemplate": {
    "slug": "回應字串",
```

```
    "displayName": "回應字串",
    "thumbnailUrls": [
      "回應字串"
    ]
  },
  "queryMetadata": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應範例名稱",
    "description": "回應範例描述"
  },
  "metadata": null,
  "recordId": "回應字串",
  "broadcast": false,
  "skipCopilotTrigger": false,
  "activeRevisionNumber": 456,
  "revisions": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "revisionNumber": 456,
      "content": "回應字串",
      "contentPayload": null,
      "isActive": false,
      "createdAt": "回應字串"
    }
  ],
  "suggestedForId": "550e8400-e29b-41d4-a716-446655440000",
  "suggestionStatus": "回應字串",
  "suggestionTriggerSource": "回應字串",
  "suggestionError": "回應字串",
  "retryCount": 456,
  "skillIds": [
    "550e8400-e29b-41d4-a716-446655440000"
  ],
  "toolIds": [
    "550e8400-e29b-41d4-a716-446655440000"
  ],
  "templateId": "550e8400-e29b-41d4-a716-446655440000",
  "videoGeneration": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應範例名稱",
    "description": "回應範例描述"
  },
  "isGreeting": false
}
```

建立新的對話

`POST` `/api/v1/conversations/`

請求內容

請求參數

欄位	類型	必填	說明
webChat	string (uuid)	是	
contact	string (uuid)	否	
clientPlatform	object	否	
workingDirectory	string	否	

請求結構範例

```
{
  "webChat": string (uuid)
  "contact"?: string (uuid) // 非必填
  "clientPlatform"?:  // 非必填
  {
  }
  "workingDirectory"?: string // 非必填
}
```

請求範例值

```
{
  "webChat": "3fa85f64-5717-4562-b3fc-2c963f66afa6"
}
```

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X POST "https://api.maiagent.ai/api/v1/conversations/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "webChat": "3fa85f64-5717-4562-b3fc-2c963f66afa6"
  }'

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// 請求內容 (payload)
const data = {
    "webChat": "3fa85f64-5717-4562-b3fc-2c963f66afa6"
  };

axios.post("https://api.maiagent.ai/api/v1/conversations/", data, config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```python
import requests

url = "https://api.maiagent.ai/api/v1/conversations/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# 請求內容 (payload)
data = {
    "webChat": "3fa85f64-5717-4562-b3fc-2c963f66afa6"
}

response = requests.post(url, json=data, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>post("https://api.maiagent.ai/api/v1/conversations/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'webChat' => '3fa85f64-5717-4562-b3fc-2c963f66afa6'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 201

回應結構範例

```
{
  "id": string (uuid)
  "contact": { // 輕量級 Contact Serializer，用於 Conversation List view

只包含 List view 必要的欄位，移除 inboxes、mcp_credentials 和 api_credentials
```

```
以避免 N+1 查詢問題。email / phone_number / metadata 為 Contact 自身的純量欄位，
前端對話側欄需要顯示，無 N+1 成本。
  {
    "id": string (uuid)
    "name": string
    "avatar"?: string // Stores our own media as a relative storage key, or an
external CDN URL as-is. (非必填)
    "email"?: // 可能有不同的類型 (非必填)
    string (email) // 非必填
    "phoneNumber"?: string // 非必填
    "metadata"?: object // Custom customer information shown in the customer panel
of the conversation page (非必填)
    "sourceId"?: string // 非必填
    "tags": [
      {
        "id": string (uuid)
        "name": string
      }
    ]
  }
  }
  "inbox": { // Inbox summary embedded in a conversation payload.

``unread_conversations_count`` stays here because it is part of the
documented REST conversation API. It is an org-wide denormalized
counter, so WS emit paths must run the payload through
:func:`strip_org_wide_unread_count` before broadcasting it to rooms
that include members without ``GroupInbox.can_view_conversations``.
  {
    "id": string (uuid)
    "name": string
    "channelType": string (enum: line, telegram, teams, web, messenger, instagram,
email, whatsapp, slack, team_plus, line_works, viber) // * `line` - LINE
* `telegram` - Telegram
* `teams` - Teams
* `web` - Web
* `messenger` - Messenger
* `instagram` - Instagram
* `email` - Email
* `whatsapp` - WhatsApp
* `slack` - Slack
* `team_plus` - Team+
* `line_works` - LINE WORKS
* `viber` - Viber
    "unreadConversationsCount"?: integer // 非必填
    "signAuth"?:  // 非必填
    {
      "id": string (uuid)
      "signSource": string (uuid)
      "signParams": {
```

```
      {
        "keycloak":
        {
          "clientId": string
          "url": string
          "realm": string
        }
        "line":
        {
          "liffId": string
        }
        "ad":
        {
          "saml": string
        }
        "google"?:  // 非必填
        {
          "enabled": boolean
        }
      }
      }
      "sourceIdAccessEnabled"?: boolean // When enabled, embedded visitors
presenting a Source ID (verified per the verify mode below) may chat without going
through the login flow. Disabled keeps every existing behavior unchanged. (非必填)
      "sourceIdVerifyMode"?:  // "Require signature verification": the embedding
site must send an HMAC signature computed on its backend. "Source ID only": anyone
knowing a Source ID can act as that contact; suitable only for testing or closed
networks.

* `signature` - Require signature verification
* `raw` - Source ID only (非必填)
      {
      }
      "sourceIdSignatureTtlMinutes"?:  // How long a signature can be used to
obtain the contact identity. Not a session lifetime: once exchanged, the session
follows the existing WebChat mechanism.

* `1` - 1
* `5` - 5
* `15` - 15 (非必填)
      {
      }
      "keycloakTokenPassthrough"?: boolean // When enabled, the Keycloak access
token a visitor logged in with is forwarded as the Authorization header when the
AI calls MCP and API tools on their behalf, so tools do not require a separate
per-tool login. Only for the Keycloak sign source. Never overrides an
Authorization header a tool already resolves from its own credentials. The visitor
identity is the organization member bound to the conversation at login, never the
contact Source ID. (非必填)
      "keycloakTokenPassthroughAllowedHosts"?: [ // Hostnames (or "*.example.com"
```

```
wildcards) of the tools the visitor Keycloak token may be sent to (非必填)
        string
      ]
    }
    "enableAnalysis"?: boolean // 非必填
  }
  }
  "chatbot": object // Chatbot (Agent) summary from the conversation's inbox,
already eager-loaded.

``is_maigpt`` lets the client tell the default MaiGPT agent apart (icon, feature
gate) without comparing against the organization's ``maigpt_inbox`` id;
``file_workspace_mode`` is the effective P6 mode (MaiGPT, blueprint and the
organization's file-library switch already applied).
  "title": string
  "lastMessage"?: { // 非必填
  {
    "id": string (uuid)
    "type"?: string // 非必填
    "content"?: string // 非必填
    "createdAt": string (timestamp)
  }
  }
  "callRecord":
  {
    "id": string (uuid)
    "status"?: string (enum: initiated, ringing, in-progress, completed, failed,
busy, no-answer, canceled) // * `initiated` - Initiated
* `ringing` - Ringing
* `in-progress` - In Progress
* `completed` - Completed
* `failed` - Failed
* `busy` - Busy
* `no-answer` - No Answer
* `canceled` - Canceled (非必填)
    "direction": string (enum: inbound, outbound) // * `inbound` - Inbound
* `outbound` - Outbound
    "isActive": boolean
    "canHangup": boolean
  }
  "lastMessageCreatedAt": string (timestamp)
  "unreadMessagesCount": integer
  "autoReplyEnabled": boolean
  "isAutoReplyNow": boolean
  "willAiReplyNow": boolean // Whether a text message arriving through the inbox
gets an AI reply right now.

The messaging channels are gated by ``is_auto_reply_now`` (auto reply on and
inside the
inbox auto-reply schedule) and by the inbox having a chatbot. The chatbot's API
```

```
web chat
is answered by the completions endpoint, which ignores the schedule, so there the
conversation switch alone decides. The channel is only looked up for a web inbox
outside
its schedule.

Surfaces that ignore the schedule on any inbox answer from their own rule instead:
the
completions endpoint continuing an existing conversation
(``completions_progress_status``)
and voice turns, which the voice agent answers.
  "lastReadAt": string (timestamp)
  "createdAt": string (timestamp)
  "isGroupChat": boolean
  "enableGroupMention"?: boolean // 非必填
  "queryMetadata"?: { // 查詢元資料，控制可查詢的知識範圍；詳見各端點說明 (非必填)
  {
    "knowledgeBases"?: [ // 可查詢的知識庫清單；空陣列或 null＝全部不可查（無權限），未提供＝
不限制 (非必填)
      {
        "knowledgeBaseId": string (uuid) // 知識庫 ID
        "chatbotFileIds"?: [ // 檔案 ID 清單（依 hasUserSelectedAll 決定為排除或僅選
取） (非必填)
          string (uuid)
        ]
        "knowledgeBaseFileIds"?: [ // 檔案 ID 清單（chatbotFileIds 的新名稱；兩者皆提供
時以本欄位為準） (非必填)
          string (uuid)
        ]
        "faqIds"?: [ // FAQ ID 清單（依 hasUserSelectedAll 決定為排除或僅選取） (非必填)
          string (uuid)
        ]
        "hasUserSelectedAll"?: boolean // true＝選取知識庫全部內容並排除清單中的項目；
false＝僅選取清單中的項目 (非必填)
      }
    ]
    "labelRelations"?: { // 標籤過濾條件；conditions 為空陣列＝不做標籤過濾（並非無權限）。
必須與 knowledgeBases 一併提供—單獨提供時知識庫檢索不會套用標籤過濾（等同不限制） (非必填)
    {
      "operator": string (enum: AND, OR) // 標籤條件的組合方式
      "conditions"?: [ // 標籤條件清單，支援巢狀 operator/conditions 組合 (非必填)
        object
      ]
    }
    }
  }
  }
  "toolMask"?: object // Enabled/disabled state per tool: {tool_id: bool} (非必填)
  "connectorMask"?: object // Enabled/disabled state per connector: {connector_id:
bool} (非必填)
```

```
  "thinkingConfig"?: object // None = not set (inherit the chatbot setting);
otherwise {"reasoning_effort": <level>} (非必填)
  "thinkingConfigSchema": { // 此模型的思考設定表單；null 表示此模型沒有思考設定
  {
    "type"?: string // 表單類型，固定為 reasoning_effort (非必填)
    "fields"?: object // reasoning_effort 欄位：options 列出此模型接受的思考等級（由弱到
強），default 固定為 null (非必填)
    "canDisable"?: boolean // 此模型能否關閉思考；true 時 options 含 off (非必填)
    "unsetBehavior"?: string (enum: off, model_default) // 對話與助理都沒設思考等級時的
實際行為：off＝不思考（最快）；model_default＝模型自行思考，或平台預設等級會開啟思考 (非必填)
    "unsetLevel"?: string // 沒設等級時平台實際送出的等級；null 表示不送思考參數，交給模型自
身預設 (非必填)
  }
  }
  "effectiveThinkingConfig": object // The level the next reply sends on this
conversation's model, after gating and clamping.

The stored choice resolves conversation > chatbot > the LLM row's default level;
None means
the model sends no thinking parameter, so the provider default applies.
  "llm": string (uuid) // The model the next reply runs on: the conversation's
pin, else its assistant's current model.

TC-0205: returning the stored ``conversation.llm`` would show a model an unpinned
conversation no
longer uses once its assistant switches model, while ``thinking_config_schema``
already follows the
effective model. Read-only: displaying it never marks the conversation as
explicitly selected;
only the update-llm endpoint does.
  "deepResearchStatus":  // Status of deep research for this conversation

* `not_used` - Not Used
* `started` - Started
* `running` - Running
* `completed` - Completed
* `failed` - Failed
  {
  }
  "deepResearchOutputFormat": // 可能有不同的類型
  string (enum: canvas, chat, file) // Chosen delivery form for the finished
report. Set only when the user clicks a format in the pre-research choice card;
reset to NULL each time Deep Research is (re-)armed. NULL means no explicit choice
(or a plan-skipping request) and falls back to Canvas at render time, but stays
distinct from an explicit canvas pick so the frontend can lock the card only after
a real selection. To roll back to fixed-Canvas behavior, force this to NULL/canvas
— no redeploy needed.

* `canvas` - Canvas
* `chat` - Chat reply
```

```
* `file` - Downloadable file
  "ipAddress": string
  "ipCountryCode": string
  "ipRecordedAt": string (timestamp)
  "assignee":
  {
    "id": string (uuid)
    "name": string
    "userId": string (uuid)
  }
  "status"?: string (enum: open, resolved, queued) // * `open` - Open
* `resolved` - Resolved
* `queued` - Queued (非必填)
  "tags": [
    {
      "id": string (uuid)
      "name": string
      "memberIds"?: [ // 非必填
        string (uuid)
      ]
    }
  ]
  "progressStatus": string
  "firstResponseAt"?: string (timestamp) // 非必填
  "queuedAt"?: string (timestamp) // 非必填
  "assignedAt"?: string (timestamp) // 非必填
  "transferReason"?: string // 非必填
  "satisfactionScore": integer // Conversation satisfaction rating on a 5-point
scale (1=very dissatisfied, 5=very satisfied)
  "satisfactionComment": string
  "satisfactionSubmittedAt": string (timestamp)
  "latestAnalysisSummary": string // The conversation's current analysis summary
(its active summary revision).

Reads the `latest_analysis_summary` annotation added by `setup_eager_loading`
to avoid an N+1 query. All read paths (list / retrieve / create) eager-load,
so the annotation is present; it falls back to '' only for instances built
outside `setup_eager_loading`.
  "clientPlatform":  // Client platform that created this conversation (web,
desktop)

* `web` - Web
* `desktop` - Desktop
  {
  }
  "workingDirectory": string // Absolute path of the local folder bound to a
desktop conversation. Only set for desktop conversations; null for web
conversations.
  "slideProjectId": string
  "matchedField": string // Cached per instance: ``get_matched_message_id`` /
```

```
``get_matched_snippet``
both read this, so resolving it once avoids recomputing the keyword and
title-match logic three times per serialized conversation.
  "matchedSnippet": string // Keyword-centred excerpt of the matched message, with
ellipses.

Reads the ``matched_message_content`` annotation added by
``ConversationViewSet._annotate_keyword_match``; no extra query.
  "matchedMessageId": string
  "pinnedAt": string (timestamp) // When the conversation was pinned. Null means
unpinned.
  "folder": string (uuid) // The user-defined sidebar folder this conversation is
grouped into. Null means unclassified (shown under the time groups). Deleting the
folder resets this to null without deleting the conversation.
  "hasActiveBrowserSession": boolean // Whether a browser_use session snapshot
exists to resume.

Lets the frontend know it should proactively re-request the browser
panel (emit ``browser:start``) after a page reload, instead of only
ever showing the panel when a live ``browser:frame`` push happens to
arrive first.
  "callerOrganizationId": string // Bound caller organization (stamped at
conversation start); null when unbound
  "handoff": object // 交接資訊：enabled=平台開關；接續對話帶
source_conversation_id/source_title；被交接的原對話帶
continued_to_conversation_id/continued_to_title 與 latest_summary_message_id
  "displayContextUsage": boolean // 是否顯示上下文使用量百分比條（對話平台開關，MaiGPT 恆
為 true；與交接開關互相獨立）
}
```

回應範例值

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "contact": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應字串",
    "avatar": "回應字串",
    "email": "response@example.com",
    "phoneNumber": "回應字串",
    "metadata": null,
    "sourceId": "回應字串",
    "tags": [
      {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "name": "回應字串"
      }
    ]
```

```
  },
  "inbox": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應字串",
    "channelType": "line",
    "unreadConversationsCount": 456,
    "signAuth": {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "signSource": "550e8400-e29b-41d4-a716-446655440000",
      "signParams": {
        "keycloak": {
          "clientId": "回應字串",
          "url": "回應字串",
          "realm": "回應字串"
        },
        "line": {
          "liffId": "回應字串"
        },
        "ad": {
          "saml": "回應字串"
        },
        "google": {
          "enabled": false
        }
      },
      "sourceIdAccessEnabled": false,
      "sourceIdVerifyMode": {},
      "sourceIdSignatureTtlMinutes": {},
      "keycloakTokenPassthrough": false,
      "keycloakTokenPassthroughAllowedHosts": [
        "回應字串"
      ]
    },
    "enableAnalysis": false
  },
  "chatbot": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應範例名稱",
    "description": "回應範例描述"
  },
  "title": "回應字串",
  "lastMessage": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "type": "回應字串",
    "content": "回應字串",
    "createdAt": "回應字串"
  },
  "callRecord": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "status": "initiated",
```

```
      "direction": "inbound",
      "isActive": false,
      "canHangup": false
    },
    "lastMessageCreatedAt": "回應字串",
    "unreadMessagesCount": 456,
    "autoReplyEnabled": false,
    "isAutoReplyNow": false,
    "willAiReplyNow": false,
    "lastReadAt": "回應字串",
    "createdAt": "回應字串",
    "isGroupChat": false,
    "enableGroupMention": false,
    "queryMetadata": {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "回應範例名稱",
      "description": "回應範例描述"
    },
    "toolMask": null,
    "connectorMask": null,
    "thinkingConfig": null,
    "thinkingConfigSchema": {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "回應範例名稱",
      "description": "回應範例描述"
    },
    "effectiveThinkingConfig": {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "回應範例名稱",
      "description": "回應範例描述"
    },
    "llm": "550e8400-e29b-41d4-a716-446655440000",
    "deepResearchStatus": {},
    "deepResearchOutputFormat": "canvas",
    "ipAddress": "回應字串",
    "ipCountryCode": "回應字串",
    "ipRecordedAt": "回應字串",
    "assignee": {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "回應字串",
      "userId": "550e8400-e29b-41d4-a716-446655440000"
    },
    "status": "open",
    "tags": [
      {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "name": "回應字串",
        "memberIds": [
          "550e8400-e29b-41d4-a716-446655440000"
        ]
```

```
    }
  ],
  "progressStatus": "回應字串",
  "firstResponseAt": "回應字串",
  "queuedAt": "回應字串",
  "assignedAt": "回應字串",
  "transferReason": "回應字串",
  "satisfactionScore": 456,
  "satisfactionComment": "回應字串",
  "satisfactionSubmittedAt": "回應字串",
  "latestAnalysisSummary": "回應字串",
  "clientPlatform": {},
  "workingDirectory": "回應字串",
  "slideProjectId": "回應字串",
  "matchedField": "回應字串",
  "matchedSnippet": "回應字串",
  "matchedMessageId": "回應字串",
  "pinnedAt": "回應字串",
  "folder": "550e8400-e29b-41d4-a716-446655440000",
  "hasActiveBrowserSession": false,
  "callerOrganizationId": "回應字串",
  "handoff": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應範例名稱",
    "description": "回應範例描述"
  },
  "displayContextUsage": false
}
```


取得訊息列表

GET `/api/v1/messages/`

參數

參數名稱	必填	類型	說明
`conversation`	V	string	對話 ID
`cursor`	X	string	The pagination cursor value.

pageSize	X	integer	Number of results to return per page.

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/messages/?
conversation=example&cursor=example&pageSize=1"

  -H "Authorization: Api-Key YOUR_API_KEY"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/messages/?
conversation=example&cursor=example&pageSize=1", config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/messages/?
conversation=example&cursor=example&pageSize=1"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->get("https://api.maiagent.ai/api/v1/messages/?conversation=example&cursor=example&pageSize=1", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
{
  "count": integer
  "next"?: string (uri) // 非必填
  "previous"?: string (uri) // 非必填
  "results": [
    {
      "id": string (uuid)
      "conversation": string (uuid)
      "sender":
```

```
      {
        "id": string (uuid)
        "name": string
        "avatar": string
        "email"?: string (email) // 非必填
        "phoneNumber"?: string // 非必填
      }
      "type"?: string // 非必填
      "content"?: string // 非必填
      "contentPayload"?: object // 非必填
      "feedback":
      {
        "id": string (uuid)
        "type":
        {
        }
        "suggestion"?: string // 非必填
        "updatedAt": string (timestamp)
      }
      "createdAt": string (timestamp)
      "attachments"?: [ // 非必填
        {
          "id": string (uuid) // ID of an already-uploaded attachment, as returned
by the attachment upload endpoint. Required: a missing, null or non-UUID id is
rejected with HTTP 400 and the message is not created.
          "type"?:  // 非必填
          {
          }
          "filename": string
          "file": string (uri)
          "expiresAt": string // ISO datetime when this attachment will be auto-
deleted.

For conversation-bound attachments: conversation.last_message_created_at +
retention_days.
For attachments without a conversation: created_at + retention_days.
Returns None when cleanup is disabled (effective_from not set).
          "conversation"?: string (uuid) // 非必填
        }
      ]
      "citations": [
        {
          "id": string (uuid)
          "filename": string // 檔案名稱
          "file": string (uri) // 要上傳的檔案
          "fileType": string
          "knowledgeBase"?:  // 非必填
          {
            "id": string (uuid)
            "name": string
```

```
          }
          "size": integer
          "status":
          {
          }
          "parser":
          {
            "id": string (uuid)
            "name": string
            "provider":
            {
            }
            "isTimestampSttProvider": boolean
          }
          "labels"?: [ // 非必填
            {
              "id": string (uuid)
              "name": string
            }
          ]
          "rawUserDefineMetadata"?: object // 非必填
          "speakerLabels": [
            {
              "id": string (uuid)
              "originalLabel": string // Original speaker label from diarization
(e.g., SPEAKER_00)
              "customName"?: string // User-defined speaker name (e.g., John) (非
必填)
              "displayName": string
            }
          ]
          "vectorStorageSize": integer // Size of vectors for this file in
Elasticsearch (bytes)
          "chunksCount": integer // Number of chunks/nodes generated from this
file
          "waitingTime": number (double)
          "processingTime": number (double)
          "processingTimeDetails": object
          "previewUrl": string // 簡報（pptx/ppt）回傳可預覽的 pdf 衍生檔 URL（前端用
PDF 預覽器顯示）；其餘為 None。

用與 `file` 欄位相同的 CustomizedFileFieldSerializer 產 URL，確保格式一致（含各
storage provider 的 presign/host 規則）。不可用 get_absolute_url()——它產出的 URL 格式錯
誤。
          "createdAt": string (timestamp)
        }
      ]
      "citationNodes": [
        {
          "chatbotTextNode": {
```

```
          {
            "id": string (uuid)
            "charactersCount": integer
            "hitsCount": integer
            "text": string
            "updatedAt": string (timestamp)
            "filename": string
            "chatbotFile": object // 返回 ChatbotFile 的完整資訊，包含檔案 URL 和類型，
以支援前端圖片預覽
            "knowledgeBaseFile": object // 與 get_chatbot_file 相同，提供向後兼容
            "pageNumber": integer // Backward-compatible alias of ``page_start``.
            "pageStart": integer
            "pageEnd": integer
            "citationTitle": string // Source title shown on the inline citation
hover card.
            "citationDescription": string // Source description shown on the
inline citation hover card.
            "citationQuote": string // Quoted text snippet shown on the inline
citation hover card.
            "hasImage": boolean // 判斷是否包含圖片（檢查檔案類型或 text 中的 Markdown
圖片）
            "imageUrl": string // 提取圖片 URL（優先使用檔案 URL，否則從 Markdown 提取）
            "displayText": string // 返回移除圖片 Markdown 標記的完整文字
            "displayTitle": string // 返回顯示標題（fallback: citation_title ->
filename）
            "highlightedText": string // Return text with matched terms wrapped in
``<mark>`` tags.

Priority:
1. ES/OpenSearch native highlight (set by retrieve_api via
``_es_highlighted_text``)
2. Python regex fallback (keyword-based, works for all backends)
            "labels": [
              {
                "id": string (uuid)
                "name": string
              }
            ]
            "rawUserDefineMetadata"?: object // Metadata keys and values defined
by the user. (非必填)
            "metadataEnabledForSearch": object // Map each user-defined metadata
key on this node to whether it was sent into the LLM.

A key reaches the LLM only when its ``MetadataKey.enabled_for_search`` is True
*and*
the node carries a value for it. Since this maps over ``raw_user_define_metadata``
(the keys the cited-documents block displays, all of which have a value),
``enabled_for_search`` alone decides the flag. The source of truth is the node's
knowledge base ``MetadataKey`` current setting, matching the AI Search indicator.
            "startCharIdx": integer
```

```
            "endCharIdx": integer
          }
          }
          "score"?: number (double) // 非必填
          "displayScore": integer
          "citationNumber"?: integer // Citation number matching the [1], [2]
markers in the reply content (非必填)
          "highlightedText"?: string // ES/OpenSearch highlight result with <mark>
tags (非必填)
        }
      ]
      "canvas"?: { // 非必填
      {
        "id": string (uuid)
        "name": string
        "canvasType":
        {
        }
        "title": string
        "content": string
        "createdAt": string (timestamp)
      }
      }
      "slideTemplate"?:  // 非必填
      {
        "slug": string
        "displayName": string
        "thumbnailUrls"?: [ // 非必填
          string
        ]
      }
      "queryMetadata"?: { // 查詢元資料，控制可查詢的知識範圍；詳見各端點說明 (非必填)
      {
        "knowledgeBases"?: [ // 可查詢的知識庫清單；空陣列或 null＝全部不可查（無權限），未
提供＝不限制 (非必填)
          {
            "knowledgeBaseId": string (uuid) // 知識庫 ID
            "chatbotFileIds"?: [ // 檔案 ID 清單（依 hasUserSelectedAll 決定為排除或僅
選取） (非必填)
              string (uuid)
            ]
            "knowledgeBaseFileIds"?: [ // 檔案 ID 清單（chatbotFileIds 的新名稱；兩者
皆提供時以本欄位為準） (非必填)
              string (uuid)
            ]
            "faqIds"?: [ // FAQ ID 清單（依 hasUserSelectedAll 決定為排除或僅選取） (非
必填)
              string (uuid)
            ]
            "hasUserSelectedAll"?: boolean // true＝選取知識庫全部內容並排除清單中的項
```

```
目；false＝僅選取清單中的項目 (非必填)
          }
        ]
        "labelRelations"?: { // 標籤過濾條件；conditions 為空陣列＝不做標籤過濾（並非無權限）。必須與 knowledgeBases 一併提供—單獨提供時知識庫檢索不會套用標籤過濾（等同不限制） (非必填)
        {
          "operator": string (enum: AND, OR) // 標籤條件的組合方式
          "conditions"?: [ // 標籤條件清單，支援巢狀 operator/conditions 組合 (非必填)
            object
          ]
        }
        }
      }
      }
      "metadata"?: object // Message metadata, such as timezone and other environment information (非必填)
      "recordId": string // 返回 Message 對應的 ChatbotRecord ID

Note:
    對於未儲存的 Message（如 streaming 中的虛擬 Message)，直接返回 None，
    避免觸發 OneToOneField reverse relation 的 DB 查詢（N+1 問題)。
      "broadcast"?: boolean // 非必填
      "skipCopilotTrigger"?: boolean // 非必填
      "activeRevisionNumber": integer
      "revisions": [
        {
          "id": string (uuid)
          "revisionNumber": integer
          "content": string
          "contentPayload": object
          "isActive": boolean
          "createdAt": string (timestamp)
        }
      ]
      "suggestedForId"?: string (uuid) // 非必填
      "suggestionStatus": string
      "suggestionTriggerSource": string
      "suggestionError": string
      "retryCount": integer // How many times the LLM call was auto-retried during this message generation. Currently only Bedrock first-chunk stall triggers retry (max 1). Detailed per-attempt records live in metadata["retry_attempts"].
      "skillIds"?: [ // Per-message selected skill IDs from the WebChat client (camelCase: skillIds). (非必填)
        string (uuid)
      ]
      "toolIds"?: [ // Per-message selected tool IDs from the WebChat client (camelCase: toolIds). (非必填)
        string (uuid)
      ]
```

```
      "templateId"?: string (uuid) // Document/sheet template ID for file-level
compilation (camelCase: templateId). (非必填)
      "videoGeneration": object // Return the latest GeneratedVideo state for FE
reload recovery;
``errorMessage`` is blank to match the socket emit (raw value stays on the DB
row).
      "isGreeting": boolean // Whether this message is a greeting message.
    }
  ]
}
```

回應範例值

```
{
  "count": 123,
  "next": "http://api.example.org/accounts/?page=4",
  "previous": "http://api.example.org/accounts/?page=2",
  "results": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "conversation": "550e8400-e29b-41d4-a716-446655440000",
      "sender": {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "name": "回應字串",
        "avatar": "回應字串",
        "email": "response@example.com",
        "phoneNumber": "回應字串"
      },
      "type": "回應字串",
      "content": "回應字串",
      "contentPayload": null,
      "feedback": {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "type": {},
        "suggestion": "回應字串",
        "updatedAt": "回應字串"
      },
      "createdAt": "回應字串",
      "attachments": [
        {
          "id": "550e8400-e29b-41d4-a716-446655440000",
          "type": {},
          "filename": "回應字串",
          "file": "https://example.com/file.jpg",
          "expiresAt": "回應字串",
          "conversation": "550e8400-e29b-41d4-a716-446655440000"
        }
      ],
```

```
      "citations": [
        {
          "id": "550e8400-e29b-41d4-a716-446655440000",
          "filename": "回應字串",
          "file": "https://example.com/file.jpg",
          "fileType": "回應字串",
          "knowledgeBase": {
            "id": "550e8400-e29b-41d4-a716-446655440000",
            "name": "回應字串"
          },
          "size": 456,
          "status": {},
          "parser": {
            "id": "550e8400-e29b-41d4-a716-446655440000",
            "name": "回應字串",
            "provider": {},
            "isTimestampSttProvider": false
          },
          "labels": [
            {
              "id": "550e8400-e29b-41d4-a716-446655440000",
              "name": "回應字串"
            }
          ],
          "rawUserDefineMetadata": null,
          "speakerLabels": [
            {
              "id": "550e8400-e29b-41d4-a716-446655440000",
              "originalLabel": "回應字串",
              "customName": "回應字串",
              "displayName": "回應字串"
            }
          ],
          "vectorStorageSize": 456,
          "chunksCount": 456,
          "waitingTime": 456,
          "processingTime": 456,
          "processingTimeDetails": null,
          "previewUrl": "回應字串",
          "createdAt": "回應字串"
        }
      ],
      "citationNodes": [
        {
          "chatbotTextNode": {
            "id": "550e8400-e29b-41d4-a716-446655440000",
            "charactersCount": 456,
            "hitsCount": 456,
            "text": "回應字串",
            "updatedAt": "回應字串",
```

```
          "filename": "回應字串",
          "chatbotFile": {
            "id": "550e8400-e29b-41d4-a716-446655440000",
            "name": "回應範例名稱",
            "description": "回應範例描述"
          },
          "knowledgeBaseFile": {
            "id": "550e8400-e29b-41d4-a716-446655440000",
            "name": "回應範例名稱",
            "description": "回應範例描述"
          },
          "pageNumber": 456,
          "pageStart": 456,
          "pageEnd": 456,
          "citationTitle": "回應字串",
          "citationDescription": "回應字串",
          "citationQuote": "回應字串",
          "hasImage": false,
          "imageUrl": "回應字串",
          "displayText": "回應字串",
          "displayTitle": "回應字串",
          "highlightedText": "回應字串",
          "labels": [
            {
              "id": "550e8400-e29b-41d4-a716-446655440000",
              "name": "回應字串"
            }
          ],
          "rawUserDefineMetadata": null,
          "metadataEnabledForSearch": {
            "key1": "value1",
            "key2": "value2",
            "createdAt": "2025-01-01T00:00:00.000Z"
          },
          "startCharIdx": 456,
          "endCharIdx": 456
        },
        "score": 456,
        "displayScore": 456,
        "citationNumber": 456,
        "highlightedText": "回應字串"
      }
    ],
    "canvas": {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "回應字串",
      "canvasType": {},
      "title": "回應字串",
      "content": "回應字串",
      "createdAt": "回應字串"
```

```
      },
      "slideTemplate": {
        "slug": "回應字串",
        "displayName": "回應字串",
        "thumbnailUrls": [
          "回應字串"
        ]
      },
      "queryMetadata": {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "name": "回應範例名稱",
        "description": "回應範例描述"
      },
      "metadata": null,
      "recordId": "回應字串",
      "broadcast": false,
      "skipCopilotTrigger": false,
      "activeRevisionNumber": 456,
      "revisions": [
        {
          "id": "550e8400-e29b-41d4-a716-446655440000",
          "revisionNumber": 456,
          "content": "回應字串",
          "contentPayload": null,
          "isActive": false,
          "createdAt": "回應字串"
        }
      ],
      "suggestedForId": "550e8400-e29b-41d4-a716-446655440000",
      "suggestionStatus": "回應字串",
      "suggestionTriggerSource": "回應字串",
      "suggestionError": "回應字串",
      "retryCount": 456,
      "skillIds": [
        "550e8400-e29b-41d4-a716-446655440000"
      ],
      "toolIds": [
        "550e8400-e29b-41d4-a716-446655440000"
      ],
      "templateId": "550e8400-e29b-41d4-a716-446655440000",
      "videoGeneration": {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "name": "回應範例名稱",
        "description": "回應範例描述"
      },
      "isGreeting": false
    }
  ]
}
```

取得特定訊息

GET `/api/v1/messages/{id}`

參數

參數名稱	必填	類型	說明
`id`	V	string	A UUID string identifying this Message.
`conversation`	V	string	對話 ID

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/messages/550e8400-e29b-41d4-a716-446655440000/?conversation=example"

  -H "Authorization: Api-Key YOUR_API_KEY"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/messages/550e8400-e29b-41d4-a716-
446655440000/?conversation=example", config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/messages/550e8400-e29b-41d4-a716-446655440000/?conversation=example"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/messages/550e8400-e29b-41d4-a716-
446655440000/?conversation=example", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
{
  "id": string (uuid)
  "conversation": string (uuid)
  "sender":
  {
    "id": string (uuid)
    "name": string
    "avatar": string
```

```
    "email"?: string (email) // 非必填
    "phoneNumber"?: string // 非必填
  }
  "type"?: string // 非必填
  "content"?: string // 非必填
  "contentPayload"?: object // 非必填
  "feedback":
  {
    "id": string (uuid)
    "type":
    {
    }
    "suggestion"?: string // 非必填
    "updatedAt": string (timestamp)
  }
  "createdAt": string (timestamp)
  "attachments"?: [ // 非必填
    {
      "id": string (uuid) // ID of an already-uploaded attachment, as returned by
the attachment upload endpoint. Required: a missing, null or non-UUID id is
rejected with HTTP 400 and the message is not created.
      "type"?:  // 非必填
      {
      }
      "filename": string
      "file": string (uri)
      "expiresAt": string // ISO datetime when this attachment will be auto-
deleted.

For conversation-bound attachments: conversation.last_message_created_at +
retention_days.
For attachments without a conversation: created_at + retention_days.
Returns None when cleanup is disabled (effective_from not set).
      "conversation"?: string (uuid) // 非必填
    }
  ]
  "citations": [
    {
      "id": string (uuid)
      "filename": string // 檔案名稱
      "file": string (uri) // 要上傳的檔案
      "fileType": string
      "knowledgeBase"?:  // 非必填
      {
        "id": string (uuid)
        "name": string
      }
      "size": integer
      "status":
      {
```

```
      }
      "parser":
      {
        "id": string (uuid)
        "name": string
        "provider":
        {
        }
        "isTimestampSttProvider": boolean
      }
      "labels"?: [ // 非必填
        {
          "id": string (uuid)
          "name": string
        }
      ]
      "rawUserDefineMetadata"?: object // 非必填
      "speakerLabels": [
        {
          "id": string (uuid)
          "originalLabel": string // Original speaker label from diarization
(e.g., SPEAKER_00)
          "customName"?: string // User-defined speaker name (e.g., John) (非必填)
          "displayName": string
        }
      ]
      "vectorStorageSize": integer // Size of vectors for this file in
Elasticsearch (bytes)
      "chunksCount": integer // Number of chunks/nodes generated from this file
      "waitingTime": number (double)
      "processingTime": number (double)
      "processingTimeDetails": object
      "previewUrl": string // 簡報（pptx/ppt）回傳可預覽的 pdf 衍生檔 URL（前端用 PDF 預
覽器顯示）；其餘為 None。

用與 `file` 欄位相同的 CustomizedFileFieldSerializer 產 URL，確保格式一致（含各
storage provider 的 presign/host 規則）。不可用 get_absolute_url()——它產出的 URL 格式錯
誤。
      "createdAt": string (timestamp)
    }
  ]
  "citationNodes": [
    {
      "chatbotTextNode": {
      {
        "id": string (uuid)
        "charactersCount": integer
        "hitsCount": integer
        "text": string
        "updatedAt": string (timestamp)
```

```
        "filename": string
        "chatbotFile": object // 返回 ChatbotFile 的完整資訊，包含檔案 URL 和類型，以支援前端圖片預覽
        "knowledgeBaseFile": object // 與 get_chatbot_file 相同，提供向後兼容
        "pageNumber": integer // Backward-compatible alias of ``page_start``.
        "pageStart": integer
        "pageEnd": integer
        "citationTitle": string // Source title shown on the inline citation hover card.
        "citationDescription": string // Source description shown on the inline citation hover card.
        "citationQuote": string // Quoted text snippet shown on the inline citation hover card.
        "hasImage": boolean // 判斷是否包含圖片（檢查檔案類型或 text 中的 Markdown 圖片）
        "imageUrl": string // 提取圖片 URL（優先使用檔案 URL，否則從 Markdown 提取）
        "displayText": string // 返回移除圖片 Markdown 標記的完整文字
        "displayTitle": string // 返回顯示標題（fallback: citation_title -> filename）
        "highlightedText": string // Return text with matched terms wrapped in ``<mark>`` tags.

Priority:
1. ES/OpenSearch native highlight (set by retrieve_api via ``_es_highlighted_text``)
2. Python regex fallback (keyword-based, works for all backends)
        "labels": [
          {
            "id": string (uuid)
            "name": string
          }
        ]
        "rawUserDefineMetadata"?: object // Metadata keys and values defined by the user. (非必填)
        "metadataEnabledForSearch": object // Map each user-defined metadata key on this node to whether it was sent into the LLM.

A key reaches the LLM only when its ``MetadataKey.enabled_for_search`` is True *and*
the node carries a value for it. Since this maps over ``raw_user_define_metadata``
(the keys the cited-documents block displays, all of which have a value),
``enabled_for_search`` alone decides the flag. The source of truth is the node's
knowledge base ``MetadataKey`` current setting, matching the AI Search indicator.
        "startCharIdx": integer
        "endCharIdx": integer
      }
      }
      "score"?: number (double) // 非必填
      "displayScore": integer
      "citationNumber"?: integer // Citation number matching the [1], [2] markers in the reply content (非必填)
```

```
      "highlightedText"?: string // ES/OpenSearch highlight result with <mark>
tags (非必填)
    }
  ]
  "canvas"?: { // 非必填
  {
    "id": string (uuid)
    "name": string
    "canvasType":
    {
    }
    "title": string
    "content": string
    "createdAt": string (timestamp)
  }
  }
  "slideTemplate"?:  // 非必填
  {
    "slug": string
    "displayName": string
    "thumbnailUrls"?: [ // 非必填
      string
    ]
  }
  "queryMetadata"?: { // 查詢元資料，控制可查詢的知識範圍；詳見各端點說明 (非必填)
  {
    "knowledgeBases"?: [ // 可查詢的知識庫清單；空陣列或 null＝全部不可查（無權限），未提供＝
不限制 (非必填)
      {
        "knowledgeBaseId": string (uuid) // 知識庫 ID
        "chatbotFileIds"?: [ // 檔案 ID 清單（依 hasUserSelectedAll 決定為排除或僅選
取） (非必填)
          string (uuid)
        ]
        "knowledgeBaseFileIds"?: [ // 檔案 ID 清單（chatbotFileIds 的新名稱；兩者皆提供
時以本欄位為準） (非必填)
          string (uuid)
        ]
        "faqIds"?: [ // FAQ ID 清單（依 hasUserSelectedAll 決定為排除或僅選取） (非必填)
          string (uuid)
        ]
        "hasUserSelectedAll"?: boolean // true＝選取知識庫全部內容並排除清單中的項目；
false＝僅選取清單中的項目 (非必填)
      }
    ]
    "labelRelations"?: { // 標籤過濾條件；conditions 為空陣列＝不做標籤過濾（並非無權限）。
必須與 knowledgeBases 一併提供——單獨提供時知識庫檢索不會套用標籤過濾（等同不限制） (非必填)
    {
      "operator": string (enum: AND, OR) // 標籤條件的組合方式
      "conditions"?: [ // 標籤條件清單，支援巢狀 operator/conditions 組合 (非必填)
```

```
        object
      ]
    }
    }
  }
  }
  "metadata"?: object // Message metadata, such as timezone and other environment
information (非必填)
  "recordId": string // 返回 Message 對應的 ChatbotRecord ID

Note:
    對於未儲存的 Message（如 streaming 中的虛擬 Message），直接返回 None，
    避免觸發 OneToOneField reverse relation 的 DB 查詢（N+1 問題）。
  "broadcast"?: boolean // 非必填
  "skipCopilotTrigger"?: boolean // 非必填
  "activeRevisionNumber": integer
  "revisions": [
    {
      "id": string (uuid)
      "revisionNumber": integer
      "content": string
      "contentPayload": object
      "isActive": boolean
      "createdAt": string (timestamp)
    }
  ]
  "suggestedForId"?: string (uuid) // 非必填
  "suggestionStatus": string
  "suggestionTriggerSource": string
  "suggestionError": string
  "retryCount": integer // How many times the LLM call was auto-retried during
this message generation. Currently only Bedrock first-chunk stall triggers retry
(max 1). Detailed per-attempt records live in metadata["retry_attempts"].
  "skillIds"?: [ // Per-message selected skill IDs from the WebChat client
(camelCase: skillIds). (非必填)
    string (uuid)
  ]
  "toolIds"?: [ // Per-message selected tool IDs from the WebChat client
(camelCase: toolIds). (非必填)
    string (uuid)
  ]
  "templateId"?: string (uuid) // Document/sheet template ID for file-level
compilation (camelCase: templateId). (非必填)
  "videoGeneration": object // Return the latest GeneratedVideo state for FE
reload recovery;
``errorMessage`` is blank to match the socket emit (raw value stays on the DB
row).
  "isGreeting": boolean // Whether this message is a greeting message.
}
```

回應範例值


```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "conversation": "550e8400-e29b-41d4-a716-446655440000",
  "sender": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應字串",
    "avatar": "回應字串",
    "email": "response@example.com",
    "phoneNumber": "回應字串"
  },
  "type": "回應字串",
  "content": "回應字串",
  "contentPayload": null,
  "feedback": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "type": {},
    "suggestion": "回應字串",
    "updatedAt": "回應字串"
  },
  "createdAt": "回應字串",
  "attachments": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "type": {},
      "filename": "回應字串",
      "file": "https://example.com/file.jpg",
      "expiresAt": "回應字串",
      "conversation": "550e8400-e29b-41d4-a716-446655440000"
    }
  ],
  "citations": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "filename": "回應字串",
      "file": "https://example.com/file.jpg",
      "fileType": "回應字串",
      "knowledgeBase": {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "name": "回應字串"
      },
      "size": 456,
      "status": {},
      "parser": {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "name": "回應字串",
        "provider": {},
        "isTimestampSttProvider": false
```

```
      },
      "labels": [
        {
          "id": "550e8400-e29b-41d4-a716-446655440000",
          "name": "回應字串"
        }
      ],
      "rawUserDefineMetadata": null,
      "speakerLabels": [
        {
          "id": "550e8400-e29b-41d4-a716-446655440000",
          "originalLabel": "回應字串",
          "customName": "回應字串",
          "displayName": "回應字串"
        }
      ],
      "vectorStorageSize": 456,
      "chunksCount": 456,
      "waitingTime": 456,
      "processingTime": 456,
      "processingTimeDetails": null,
      "previewUrl": "回應字串",
      "createdAt": "回應字串"
    }
  ],
  "citationNodes": [
    {
      "chatbotTextNode": {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "charactersCount": 456,
        "hitsCount": 456,
        "text": "回應字串",
        "updatedAt": "回應字串",
        "filename": "回應字串",
        "chatbotFile": {
          "id": "550e8400-e29b-41d4-a716-446655440000",
          "name": "回應範例名稱",
          "description": "回應範例描述"
        },
        "knowledgeBaseFile": {
          "id": "550e8400-e29b-41d4-a716-446655440000",
          "name": "回應範例名稱",
          "description": "回應範例描述"
        },
        "pageNumber": 456,
        "pageStart": 456,
        "pageEnd": 456,
        "citationTitle": "回應字串",
        "citationDescription": "回應字串",
        "citationQuote": "回應字串",
```

```
        "hasImage": false,
        "imageUrl": "回應字串",
        "displayText": "回應字串",
        "displayTitle": "回應字串",
        "highlightedText": "回應字串",
        "labels": [
          {
            "id": "550e8400-e29b-41d4-a716-446655440000",
            "name": "回應字串"
          }
        ],
        "rawUserDefineMetadata": null,
        "metadataEnabledForSearch": {
          "key1": "value1",
          "key2": "value2",
          "createdAt": "2025-01-01T00:00:00.000Z"
        },
        "startCharIdx": 456,
        "endCharIdx": 456
      },
      "score": 456,
      "displayScore": 456,
      "citationNumber": 456,
      "highlightedText": "回應字串"
    }
  ],
  "canvas": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應字串",
    "canvasType": {},
    "title": "回應字串",
    "content": "回應字串",
    "createdAt": "回應字串"
  },
  "slideTemplate": {
    "slug": "回應字串",
    "displayName": "回應字串",
    "thumbnailUrls": [
      "回應字串"
    ]
  },
  "queryMetadata": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應範例名稱",
    "description": "回應範例描述"
  },
  "metadata": null,
  "recordId": "回應字串",
  "broadcast": false,
  "skipCopilotTrigger": false,
```

```
  "activeRevisionNumber": 456,
  "revisions": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "revisionNumber": 456,
      "content": "回應字串",
      "contentPayload": null,
      "isActive": false,
      "createdAt": "回應字串"
    }
  ],
  "suggestedForId": "550e8400-e29b-41d4-a716-446655440000",
  "suggestionStatus": "回應字串",
  "suggestionTriggerSource": "回應字串",
  "suggestionError": "回應字串",
  "retryCount": 456,
  "skillIds": [
    "550e8400-e29b-41d4-a716-446655440000"
  ],
  "toolIds": [
    "550e8400-e29b-41d4-a716-446655440000"
  ],
  "templateId": "550e8400-e29b-41d4-a716-446655440000",
  "videoGeneration": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應範例名稱",
    "description": "回應範例描述"
  },
  "isGreeting": false
}
```


取得對話列表

`GET` `/api/v1/conversations/`

參數

參數名稱	必填	類型	說明
assignee	X	string	

`chatbot`	X	string	
`contact`	X	string	聯絡人 ID
`contactTags`	X	array	Multiple values may be separated by commas.
`cursor`	X	string	The pagination cursor value.
`endDate`	X	string	
`externalConversationId`	X	string	
`externalSource`	X	string	
`inbox`	X	string	對話平台 ID
`isPinned`	X	string	
`keyword`	X	string	關鍵字搜尋
`mine`	X	boolean	
`mode`	X	string	`chat`: Chat ; `cowork`: Cowork;
`pageSize`	X	integer	Number of results to return per page.
`startDate`	X	string	
`status`	X	array	`open`: Open ; `resolved`: Resolved ; `queued`: Queued;
`tags`	X	array	Multiple values may be separated by commas.
`unassigned`	X	boolean	
`updatedAfter`	X	string	

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/conversations/?assignee=550e8400-e29b-41d4-a716-446655440000&chatbot=550e8400-e29b-41d4-a716-446655440000&contact=550e8400-e29b-41d4-a716-446655440000&contactTags=example&cursor=example&endDate=example&externalConversationId=example&externalSource=example&inbox=550e8400-e29b-41d4-a716-446655440000&isPinned=example&keyword=example&mine=true&mode=chat&pageSize=1&startDate=example&status=example&tags=example&unassigned=true&updatedAfter=2025-01-01T00:00:00.000Z"

  -H "Authorization: Api-Key YOUR_API_KEY"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/conversations/?assignee=550e8400-e29b-41d4-a716-446655440000&chatbot=550e8400-e29b-41d4-a716-446655440000&contact=550e8400-e29b-41d4-a716-446655440000&contactTags=example&cursor=example&endDate=example&externalConversationId=example&externalSource=example&inbox=550e8400-e29b-41d4-a716-446655440000&isPinned=example&keyword=example&mine=true&mode=chat&pageSize=1&startDate=example&status=example&tags=example&unassigned=true&updatedAfter=2025-01-01T00:00:00.000Z", config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/conversations/?assignee=550e8400-e29b-41d4-a716-446655440000&chatbot=550e8400-e29b-41d4-a716-446655440000&contact=550e8400-e29b-41d4-a716-446655440000&contactTags=example&cursor=example&endDate=example&externalConversationId=example&externalSource=example&inbox=550e8400-e29b-41d4-a716-446655440000&isPinned=example&keyword=example&mine=true&mode=chat&pageSize=1&startDate=example&status=example&tags=example&unassigned=true&updatedAfter=2025-01-01T00:00:00.000Z"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->get("https://api.maiagent.ai/api/v1/conversations/?assignee=550e8400-e29b-41d4-a716-446655440000&chatbot=550e8400-e29b-41d4-a716-446655440000&contact=550e8400-e29b-41d4-a716-446655440000&contactTags=example&cursor=example&endDate=example&externalConversationId=example&externalSource=example&inbox=550e8400-e29b-41d4-a716-446655440000&isPinned=example&keyword=example&mine=true&mode=chat&pageSize=1&startDate=example&status=example&tags=example&unassigned=true&updatedAfter=2025-01-01T00:00:00.000Z", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
{
  "count": integer
  "next"?: string (uri) // 非必填
```

```
  "previous"?: string (uri) // 非必填
  "results": [
    {
      "id": string (uuid)
      "contact": { // 輕量級 Contact Serializer，用於 Conversation List view

只包含 List view 必要的欄位，移除 inboxes、mcp_credentials 和 api_credentials
以避免 N+1 查詢問題。email / phone_number / metadata 為 Contact 自身的純量欄位，
前端對話側欄需要顯示，無 N+1 成本。
      {
        "id": string (uuid)
        "name": string
        "avatar"?: string // Stores our own media as a relative storage key, or an
external CDN URL as-is. (非必填)
        "email"?: // 可能有不同的類型 (非必填)
        string (email) // 非必填
        "phoneNumber"?: string // 非必填
        "metadata"?: object // Custom customer information shown in the customer
panel of the conversation page (非必填)
        "sourceId"?: string // 非必填
        "tags": [
          {
            "id": string (uuid)
            "name": string
          }
        ]
      }
      }
      "inbox": { // Inbox summary embedded in a conversation payload.

``unread_conversations_count`` stays here because it is part of the
documented REST conversation API. It is an org-wide denormalized
counter, so WS emit paths must run the payload through
:func:`strip_org_wide_unread_count` before broadcasting it to rooms
that include members without ``GroupInbox.can_view_conversations``.
      {
        "id": string (uuid)
        "name": string
        "channelType": string (enum: line, telegram, teams, web, messenger,
instagram, email, whatsapp, slack, team_plus, line_works, viber) // * `line` -
LINE
* `telegram` - Telegram
* `teams` - Teams
* `web` - Web
* `messenger` - Messenger
* `instagram` - Instagram
* `email` - Email
* `whatsapp` - WhatsApp
* `slack` - Slack
* `team_plus` - Team+
```

```
* `line_works` - LINE WORKS
* `viber` - Viber
        "unreadConversationsCount"?: integer // 非必填
        "signAuth"?:  // 非必填
        {
          "id": string (uuid)
          "signSource": string (uuid)
          "signParams": {
          {
            "keycloak":
            {
              "clientId": string
              "url": string
              "realm": string
            }
            "line":
            {
              "liffId": string
            }
            "ad":
            {
              "saml": string
            }
            "google"?:  // 非必填
            {
              "enabled": boolean
            }
          }
          }
          "sourceIdAccessEnabled"?: boolean // When enabled, embedded visitors presenting a Source ID (verified per the verify mode below) may chat without going through the login flow. Disabled keeps every existing behavior unchanged. (非必填)
          "sourceIdVerifyMode"?:  // "Require signature verification": the embedding site must send an HMAC signature computed on its backend. "Source ID only": anyone knowing a Source ID can act as that contact; suitable only for testing or closed networks.

* `signature` - Require signature verification
* `raw` - Source ID only (非必填)
          {
          }
          "sourceIdSignatureTtlMinutes"?:  // How long a signature can be used to obtain the contact identity. Not a session lifetime: once exchanged, the session follows the existing WebChat mechanism.

* `1` - 1
* `5` - 5
* `15` - 15 (非必填)
          {
          }
```

```
          "keycloakTokenPassthrough"?: boolean // When enabled, the Keycloak
access token a visitor logged in with is forwarded as the Authorization header
when the AI calls MCP and API tools on their behalf, so tools do not require a
separate per-tool login. Only for the Keycloak sign source. Never overrides an
Authorization header a tool already resolves from its own credentials. The visitor
identity is the organization member bound to the conversation at login, never the
contact Source ID. (非必填)
          "keycloakTokenPassthroughAllowedHosts"?: [ // Hostnames (or
"*.example.com" wildcards) of the tools the visitor Keycloak token may be sent to
(非必填)
            string
          ]
        }
        "enableAnalysis"?: boolean // 非必填
      }
      }
      "chatbot": object // Chatbot (Agent) summary from the conversation's inbox,
already eager-loaded.

``is_maigpt`` lets the client tell the default MaiGPT agent apart (icon, feature
gate) without comparing against the organization's ``maigpt_inbox`` id;
``file_workspace_mode`` is the effective P6 mode (MaiGPT, blueprint and the
organization's file-library switch already applied).
      "title": string
      "lastMessage"?: { // 非必填
      {
        "id": string (uuid)
        "type"?: string // 非必填
        "content"?: string // 非必填
        "createdAt": string (timestamp)
      }
      }
      "callRecord":
      {
        "id": string (uuid)
        "status"?: string (enum: initiated, ringing, in-progress, completed,
failed, busy, no-answer, canceled) // * `initiated` - Initiated
* `ringing` - Ringing
* `in-progress` - In Progress
* `completed` - Completed
* `failed` - Failed
* `busy` - Busy
* `no-answer` - No Answer
* `canceled` - Canceled (非必填)
        "direction": string (enum: inbound, outbound) // * `inbound` - Inbound
* `outbound` - Outbound
        "isActive": boolean
        "canHangup": boolean
      }
      "lastMessageCreatedAt": string (timestamp)
```

```
      "unreadMessagesCount": integer
      "autoReplyEnabled": boolean
      "isAutoReplyNow": boolean
      "willAiReplyNow": boolean // Whether a text message arriving through the
inbox gets an AI reply right now.

The messaging channels are gated by ``is_auto_reply_now`` (auto reply on and
inside the
inbox auto-reply schedule) and by the inbox having a chatbot. The chatbot's API
web chat
is answered by the completions endpoint, which ignores the schedule, so there the
conversation switch alone decides. The channel is only looked up for a web inbox
outside
its schedule.

Surfaces that ignore the schedule on any inbox answer from their own rule instead:
the
completions endpoint continuing an existing conversation
(``completions_progress_status``)
and voice turns, which the voice agent answers.
      "lastReadAt": string (timestamp)
      "createdAt": string (timestamp)
      "isGroupChat": boolean
      "enableGroupMention"?: boolean // 非必填
      "queryMetadata"?: { // 查詢元資料，控制可查詢的知識範圍；詳見各端點說明 (非必填)
      {
        "knowledgeBases"?: [ // 可查詢的知識庫清單；空陣列或 null＝全部不可查（無權限），未
提供＝不限制 (非必填)
          {
            "knowledgeBaseId": string (uuid) // 知識庫 ID
            "chatbotFileIds"?: [ // 檔案 ID 清單（依 hasUserSelectedAll 決定為排除或僅
選取） (非必填)
              string (uuid)
            ]
            "knowledgeBaseFileIds"?: [ // 檔案 ID 清單（chatbotFileIds 的新名稱；兩者
皆提供時以本欄位為準） (非必填)
              string (uuid)
            ]
            "faqIds"?: [ // FAQ ID 清單（依 hasUserSelectedAll 決定為排除或僅選取） (非
必填)
              string (uuid)
            ]
            "hasUserSelectedAll"?: boolean // true＝選取知識庫全部內容並排除清單中的項
目；false＝僅選取清單中的項目 (非必填)
          }
        ]
        "labelRelations"?: { // 標籤過濾條件；conditions 為空陣列＝不做標籤過濾（並非無權
限）。必須與 knowledgeBases 一併提供—單獨提供時知識庫檢索不會套用標籤過濾（等同不限制） (非必
填)
        {
```

```
          "operator": string (enum: AND, OR) // 標籤條件的組合方式
          "conditions"?: [ // 標籤條件清單，支援巢狀 operator/conditions 組合 (非必填)
            object
          ]
        }
        }
      }
      }
      "toolMask"?: object // Enabled/disabled state per tool: {tool_id: bool} (非必填)
      "connectorMask"?: object // Enabled/disabled state per connector: {connector_id: bool} (非必填)
      "thinkingConfig"?: object // None = not set (inherit the chatbot setting); otherwise {"reasoning_effort": <level>} (非必填)
      "thinkingConfigSchema": { // 此模型的思考設定表單；null 表示此模型沒有思考設定
      {
        "type"?: string // 表單類型，固定為 reasoning_effort (非必填)
        "fields"?: object // reasoning_effort 欄位：options 列出此模型接受的思考等級（由弱到強），default 固定為 null (非必填)
        "canDisable"?: boolean // 此模型能否關閉思考；true 時 options 含 off (非必填)
        "unsetBehavior"?: string (enum: off, model_default) // 對話與助理都沒設思考等級時的實際行為：off＝不思考（最快）；model_default＝模型自行思考，或平台預設等級會開啟思考 (非必填)
        "unsetLevel"?: string // 沒設等級時平台實際送出的等級；null 表示不送思考參數，交給模型自身預設 (非必填)
      }
      }
      "effectiveThinkingConfig": object // The level the next reply sends on this conversation's model, after gating and clamping.

The stored choice resolves conversation > chatbot > the LLM row's default level; None means
the model sends no thinking parameter, so the provider default applies.
      "llm": string (uuid) // The model the next reply runs on: the conversation's pin, else its assistant's current model.

TC-0205: returning the stored ``conversation.llm`` would show a model an unpinned conversation no
longer uses once its assistant switches model, while ``thinking_config_schema`` already follows the
effective model. Read-only: displaying it never marks the conversation as explicitly selected;
only the update-llm endpoint does.
      "deepResearchStatus":  // Status of deep research for this conversation

* `not_used` - Not Used
* `started` - Started
* `running` - Running
* `completed` - Completed
* `failed` - Failed
```

```
      {
      }
      "deepResearchOutputFormat": // 可能有不同的類型
      string (enum: canvas, chat, file) // Chosen delivery form for the finished
report. Set only when the user clicks a format in the pre-research choice card;
reset to NULL each time Deep Research is (re-)armed. NULL means no explicit choice
(or a plan-skipping request) and falls back to Canvas at render time, but stays
distinct from an explicit canvas pick so the frontend can lock the card only after
a real selection. To roll back to fixed-Canvas behavior, force this to NULL/canvas
— no redeploy needed.

* `canvas` - Canvas
* `chat` - Chat reply
* `file` - Downloadable file
      "ipAddress": string
      "ipCountryCode": string
      "ipRecordedAt": string (timestamp)
      "assignee":
      {
        "id": string (uuid)
        "name": string
        "userId": string (uuid)
      }
      "status"?: string (enum: open, resolved, queued) // * `open` - Open
* `resolved` - Resolved
* `queued` - Queued (非必填)
      "tags": [
        {
          "id": string (uuid)
          "name": string
          "memberIds"?: [ // 非必填
            string (uuid)
          ]
        }
      ]
      "progressStatus": string
      "firstResponseAt"?: string (timestamp) // 非必填
      "queuedAt"?: string (timestamp) // 非必填
      "assignedAt"?: string (timestamp) // 非必填
      "transferReason"?: string // 非必填
      "satisfactionScore": integer // Conversation satisfaction rating on a 5-
point scale (1=very dissatisfied, 5=very satisfied)
      "satisfactionComment": string
      "satisfactionSubmittedAt": string (timestamp)
      "latestAnalysisSummary": string // The conversation's current analysis
summary (its active summary revision).

Reads the `latest_analysis_summary` annotation added by `setup_eager_loading`
to avoid an N+1 query. All read paths (list / retrieve / create) eager-load,
so the annotation is present; it falls back to '' only for instances built
```

```
outside `setup_eager_loading`.
      "clientPlatform":  // Client platform that created this conversation (web,
desktop)

* `web` - Web
* `desktop` - Desktop
      {
      }
      "workingDirectory": string // Absolute path of the local folder bound to a
desktop conversation. Only set for desktop conversations; null for web
conversations.
      "slideProjectId": string
      "matchedField": string // Cached per instance: ``get_matched_message_id`` /
``get_matched_snippet``
both read this, so resolving it once avoids recomputing the keyword and
title-match logic three times per serialized conversation.
      "matchedSnippet": string // Keyword-centred excerpt of the matched message,
with ellipses.

Reads the ``matched_message_content`` annotation added by
``ConversationViewSet._annotate_keyword_match``; no extra query.
      "matchedMessageId": string
      "pinnedAt": string (timestamp) // When the conversation was pinned. Null
means unpinned.
      "folder": string (uuid) // The user-defined sidebar folder this conversation
is grouped into. Null means unclassified (shown under the time groups). Deleting
the folder resets this to null without deleting the conversation.
      "hasActiveBrowserSession": boolean // Whether a browser_use session snapshot
exists to resume.

Lets the frontend know it should proactively re-request the browser
panel (emit ``browser:start``) after a page reload, instead of only
ever showing the panel when a live ``browser:frame`` push happens to
arrive first.
      "callerOrganizationId": string // Bound caller organization (stamped at
conversation start); null when unbound
      "handoff": object // 交接資訊：enabled=平台開關；接續對話帶
source_conversation_id/source_title；被交接的原對話帶
continued_to_conversation_id/continued_to_title 與 latest_summary_message_id
      "displayContextUsage": boolean // 是否顯示上下文使用量百分比條（對話平台開關，
MaiGPT 恆為 true；與交接開關互相獨立）
    }
  ]
}
```

回應範例值

```
{
  "count": 123,
  "next": "http://api.example.org/accounts/?page=4",
  "previous": "http://api.example.org/accounts/?page=2",
  "results": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "contact": {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "name": "回應字串",
        "avatar": "回應字串",
        "email": "response@example.com",
        "phoneNumber": "回應字串",
        "metadata": null,
        "sourceId": "回應字串",
        "tags": [
          {
            "id": "550e8400-e29b-41d4-a716-446655440000",
            "name": "回應字串"
          }
        ]
      },
      "inbox": {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "name": "回應字串",
        "channelType": "line",
        "unreadConversationsCount": 456,
        "signAuth": {
          "id": "550e8400-e29b-41d4-a716-446655440000",
          "signSource": "550e8400-e29b-41d4-a716-446655440000",
          "signParams": {
            "keycloak": {
              "clientId": "回應字串",
              "url": "回應字串",
              "realm": "回應字串"
            },
            "line": {
              "liffId": "回應字串"
            },
            "ad": {
              "saml": "回應字串"
            },
            "google": {
              "enabled": false
            }
          },
          "sourceIdAccessEnabled": false,
          "sourceIdVerifyMode": {},
          "sourceIdSignatureTtlMinutes": {},
```

```
      "keycloakTokenPassthrough": false,
      "keycloakTokenPassthroughAllowedHosts": [
        "回應字串"
      ]
    },
    "enableAnalysis": false
  },
  "chatbot": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應範例名稱",
    "description": "回應範例描述"
  },
  "title": "回應字串",
  "lastMessage": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "type": "回應字串",
    "content": "回應字串",
    "createdAt": "回應字串"
  },
  "callRecord": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "status": "initiated",
    "direction": "inbound",
    "isActive": false,
    "canHangup": false
  },
  "lastMessageCreatedAt": "回應字串",
  "unreadMessagesCount": 456,
  "autoReplyEnabled": false,
  "isAutoReplyNow": false,
  "willAiReplyNow": false,
  "lastReadAt": "回應字串",
  "createdAt": "回應字串",
  "isGroupChat": false,
  "enableGroupMention": false,
  "queryMetadata": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應範例名稱",
    "description": "回應範例描述"
  },
  "toolMask": null,
  "connectorMask": null,
  "thinkingConfig": null,
  "thinkingConfigSchema": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應範例名稱",
    "description": "回應範例描述"
  },
  "effectiveThinkingConfig": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
```

```
        "name": "回應範例名稱",
        "description": "回應範例描述"
      },
      "llm": "550e8400-e29b-41d4-a716-446655440000",
      "deepResearchStatus": {},
      "deepResearchOutputFormat": "canvas",
      "ipAddress": "回應字串",
      "ipCountryCode": "回應字串",
      "ipRecordedAt": "回應字串",
      "assignee": {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "name": "回應字串",
        "userId": "550e8400-e29b-41d4-a716-446655440000"
      },
      "status": "open",
      "tags": [
        {
          "id": "550e8400-e29b-41d4-a716-446655440000",
          "name": "回應字串",
          "memberIds": [
            "550e8400-e29b-41d4-a716-446655440000"
          ]
        }
      ],
      "progressStatus": "回應字串",
      "firstResponseAt": "回應字串",
      "queuedAt": "回應字串",
      "assignedAt": "回應字串",
      "transferReason": "回應字串",
      "satisfactionScore": 456,
      "satisfactionComment": "回應字串",
      "satisfactionSubmittedAt": "回應字串",
      "latestAnalysisSummary": "回應字串",
      "clientPlatform": {},
      "workingDirectory": "回應字串",
      "slideProjectId": "回應字串",
      "matchedField": "回應字串",
      "matchedSnippet": "回應字串",
      "matchedMessageId": "回應字串",
      "pinnedAt": "回應字串",
      "folder": "550e8400-e29b-41d4-a716-446655440000",
      "hasActiveBrowserSession": false,
      "callerOrganizationId": "回應字串",
      "handoff": {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "name": "回應範例名稱",
        "description": "回應範例描述"
      },
      "displayContextUsage": false
    }
```

```
  ]
}
```

取得特定對話

GET `/api/v1/conversations/{id}`

參數

參數名稱	必填	類型	說明
`id`	V	string	A UUID string identifying this Conversation.

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/conversations/550e8400-e29b-41d4-a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/conversations/550e8400-e29b-41d4-a716-446655440000/", config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/conversations/550e8400-e29b-41d4-a716-446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/conversations/550e8400-e29b-41d4-a716-
446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
{
  "id": string (uuid)
  "contact": { // 輕量級 Contact Serializer，用於 Conversation List view

只包含 List view 必要的欄位，移除 inboxes、mcp_credentials 和 api_credentials
以避免 N+1 查詢問題。email / phone_number / metadata 為 Contact 自身的純量欄位，
前端對話側欄需要顯示，無 N+1 成本。
  {
```

```
    "id": string (uuid)
    "name": string
    "avatar"?: string // Stores our own media as a relative storage key, or an
external CDN URL as-is. (非必填)
    "email"?: // 可能有不同的類型 (非必填)
    string (email) // 非必填
    "phoneNumber"?: string // 非必填
    "metadata"?: object // Custom customer information shown in the customer panel
of the conversation page (非必填)
    "sourceId"?: string // 非必填
    "tags": [
      {
        "id": string (uuid)
        "name": string
      }
    ]
  }
  }
  "inbox": { // Inbox summary embedded in a conversation payload.

``unread_conversations_count`` stays here because it is part of the
documented REST conversation API. It is an org-wide denormalized
counter, so WS emit paths must run the payload through
:func:`strip_org_wide_unread_count` before broadcasting it to rooms
that include members without ``GroupInbox.can_view_conversations``.
  {
    "id": string (uuid)
    "name": string
    "channelType": string (enum: line, telegram, teams, web, messenger, instagram,
email, whatsapp, slack, team_plus, line_works, viber) // * `line` - LINE
* `telegram` - Telegram
* `teams` - Teams
* `web` - Web
* `messenger` - Messenger
* `instagram` - Instagram
* `email` - Email
* `whatsapp` - WhatsApp
* `slack` - Slack
* `team_plus` - Team+
* `line_works` - LINE WORKS
* `viber` - Viber
    "unreadConversationsCount"?: integer // 非必填
    "signAuth"?:  // 非必填
    {
      "id": string (uuid)
      "signSource": string (uuid)
      "signParams": {
      {
        "keycloak":
        {
```

```
          "clientId": string
          "url": string
          "realm": string
        }
        "line":
        {
          "liffId": string
        }
        "ad":
        {
          "saml": string
        }
        "google"?:  // 非必填
        {
          "enabled": boolean
        }
      }
      }
      "sourceIdAccessEnabled"?: boolean // When enabled, embedded visitors presenting a Source ID (verified per the verify mode below) may chat without going through the login flow. Disabled keeps every existing behavior unchanged. (非必填)
      "sourceIdVerifyMode"?:  // "Require signature verification": the embedding site must send an HMAC signature computed on its backend. "Source ID only": anyone knowing a Source ID can act as that contact; suitable only for testing or closed networks.

* `signature` - Require signature verification
* `raw` - Source ID only (非必填)
      {
      }
      "sourceIdSignatureTtlMinutes"?:  // How long a signature can be used to obtain the contact identity. Not a session lifetime: once exchanged, the session follows the existing WebChat mechanism.

* `1` - 1
* `5` - 5
* `15` - 15 (非必填)
      {
      }
      "keycloakTokenPassthrough"?: boolean // When enabled, the Keycloak access token a visitor logged in with is forwarded as the Authorization header when the AI calls MCP and API tools on their behalf, so tools do not require a separate per-tool login. Only for the Keycloak sign source. Never overrides an Authorization header a tool already resolves from its own credentials. The visitor identity is the organization member bound to the conversation at login, never the contact Source ID. (非必填)
      "keycloakTokenPassthroughAllowedHosts"?: [ // Hostnames (or "*.example.com" wildcards) of the tools the visitor Keycloak token may be sent to (非必填)
        string
      ]
```

```
    }
    "enableAnalysis"?: boolean // 非必填
  }
  }
  "chatbot": object // Chatbot (Agent) summary from the conversation's inbox,
already eager-loaded.

``is_maigpt`` lets the client tell the default MaiGPT agent apart (icon, feature
gate) without comparing against the organization's ``maigpt_inbox`` id;
``file_workspace_mode`` is the effective P6 mode (MaiGPT, blueprint and the
organization's file-library switch already applied).
  "title": string
  "lastMessage"?: { // 非必填
  {
    "id": string (uuid)
    "type"?: string // 非必填
    "content"?: string // 非必填
    "createdAt": string (timestamp)
  }
  }
  "callRecord":
  {
    "id": string (uuid)
    "status"?: string (enum: initiated, ringing, in-progress, completed, failed,
busy, no-answer, canceled) // * `initiated` - Initiated
* `ringing` - Ringing
* `in-progress` - In Progress
* `completed` - Completed
* `failed` - Failed
* `busy` - Busy
* `no-answer` - No Answer
* `canceled` - Canceled (非必填)
    "direction": string (enum: inbound, outbound) // * `inbound` - Inbound
* `outbound` - Outbound
    "isActive": boolean
    "canHangup": boolean
  }
  "lastMessageCreatedAt": string (timestamp)
  "unreadMessagesCount": integer
  "autoReplyEnabled": boolean
  "isAutoReplyNow": boolean
  "willAiReplyNow": boolean // Whether a text message arriving through the inbox
gets an AI reply right now.

The messaging channels are gated by ``is_auto_reply_now`` (auto reply on and
inside the
inbox auto-reply schedule) and by the inbox having a chatbot. The chatbot's API
web chat
is answered by the completions endpoint, which ignores the schedule, so there the
conversation switch alone decides. The channel is only looked up for a web inbox
```

```
outside
its schedule.

Surfaces that ignore the schedule on any inbox answer from their own rule instead:
the
completions endpoint continuing an existing conversation
(``completions_progress_status``)
and voice turns, which the voice agent answers.
  "lastReadAt": string (timestamp)
  "createdAt": string (timestamp)
  "isGroupChat": boolean
  "enableGroupMention"?: boolean // 非必填
  "queryMetadata"?: { // 查詢元資料，控制可查詢的知識範圍；詳見各端點說明 (非必填)
  {
    "knowledgeBases"?: [ // 可查詢的知識庫清單；空陣列或 null＝全部不可查（無權限），未提供＝
不限制 (非必填)
      {
        "knowledgeBaseId": string (uuid) // 知識庫 ID
        "chatbotFileIds"?: [ // 檔案 ID 清單（依 hasUserSelectedAll 決定為排除或僅選
取） (非必填)
          string (uuid)
        ]
        "knowledgeBaseFileIds"?: [ // 檔案 ID 清單（chatbotFileIds 的新名稱；兩者皆提供
時以本欄位為準） (非必填)
          string (uuid)
        ]
        "faqIds"?: [ // FAQ ID 清單（依 hasUserSelectedAll 決定為排除或僅選取） (非必填)
          string (uuid)
        ]
        "hasUserSelectedAll"?: boolean // true＝選取知識庫全部內容並排除清單中的項目；
false＝僅選取清單中的項目 (非必填)
      }
    ]
    "labelRelations"?: { // 標籤過濾條件；conditions 為空陣列＝不做標籤過濾（並非無權限）。
必須與 knowledgeBases 一併提供——單獨提供時知識庫檢索不會套用標籤過濾（等同不限制） (非必填)
    {
      "operator": string (enum: AND, OR) // 標籤條件的組合方式
      "conditions"?: [ // 標籤條件清單，支援巢狀 operator/conditions 組合 (非必填)
        object
      ]
    }
    }
  }
  }
  "toolMask"?: object // Enabled/disabled state per tool: {tool_id: bool} (非必填)
  "connectorMask"?: object // Enabled/disabled state per connector: {connector_id:
bool} (非必填)
  "thinkingConfig"?: object // None = not set (inherit the chatbot setting);
otherwise {"reasoning_effort": <level>} (非必填)
  "thinkingConfigSchema": { // 此模型的思考設定表單；null 表示此模型沒有思考設定
```

```
  {
    "type"?: string // 表單類型，固定為 reasoning_effort (非必填)
    "fields"?: object // reasoning_effort 欄位：options 列出此模型接受的思考等級（由弱到強），default 固定為 null (非必填)
    "canDisable"?: boolean // 此模型能否關閉思考；true 時 options 含 off (非必填)
    "unsetBehavior"?: string (enum: off, model_default) // 對話與助理都沒設思考等級時的實際行為：off＝不思考（最快）；model_default＝模型自行思考，或平台預設等級會開啟思考 (非必填)
    "unsetLevel"?: string // 沒設等級時平台實際送出的等級；null 表示不送思考參數，交給模型自身預設 (非必填)
  }
  }
  "effectiveThinkingConfig": object // The level the next reply sends on this conversation's model, after gating and clamping.

The stored choice resolves conversation > chatbot > the LLM row's default level; None means
the model sends no thinking parameter, so the provider default applies.
  "llm": string (uuid) // The model the next reply runs on: the conversation's pin, else its assistant's current model.

TC-0205: returning the stored ``conversation.llm`` would show a model an unpinned conversation no
longer uses once its assistant switches model, while ``thinking_config_schema`` already follows the
effective model. Read-only: displaying it never marks the conversation as explicitly selected;
only the update-llm endpoint does.
  "deepResearchStatus":  // Status of deep research for this conversation

* `not_used` - Not Used
* `started` - Started
* `running` - Running
* `completed` - Completed
* `failed` - Failed
  {
  }
  "deepResearchOutputFormat": // 可能有不同的類型
  string (enum: canvas, chat, file) // Chosen delivery form for the finished report. Set only when the user clicks a format in the pre-research choice card; reset to NULL each time Deep Research is (re-)armed. NULL means no explicit choice (or a plan-skipping request) and falls back to Canvas at render time, but stays distinct from an explicit canvas pick so the frontend can lock the card only after a real selection. To roll back to fixed-Canvas behavior, force this to NULL/canvas — no redeploy needed.

* `canvas` - Canvas
* `chat` - Chat reply
* `file` - Downloadable file
  "ipAddress": string
  "ipCountryCode": string
```

```
  "ipRecordedAt": string (timestamp)
  "assignee":
  {
    "id": string (uuid)
    "name": string
    "userId": string (uuid)
  }
  "status"?: string (enum: open, resolved, queued) // * `open` - Open
* `resolved` - Resolved
* `queued` - Queued (非必填)
  "tags": [
    {
      "id": string (uuid)
      "name": string
      "memberIds"?: [ // 非必填
        string (uuid)
      ]
    }
  ]
  "progressStatus": string
  "firstResponseAt"?: string (timestamp) // 非必填
  "queuedAt"?: string (timestamp) // 非必填
  "assignedAt"?: string (timestamp) // 非必填
  "transferReason"?: string // 非必填
  "satisfactionScore": integer // Conversation satisfaction rating on a 5-point
scale (1=very dissatisfied, 5=very satisfied)
  "satisfactionComment": string
  "satisfactionSubmittedAt": string (timestamp)
  "latestAnalysisSummary": string // The conversation's current analysis summary
(its active summary revision).

Reads the `latest_analysis_summary` annotation added by `setup_eager_loading`
to avoid an N+1 query. All read paths (list / retrieve / create) eager-load,
so the annotation is present; it falls back to '' only for instances built
outside `setup_eager_loading`.
  "clientPlatform":  // Client platform that created this conversation (web,
desktop)

* `web` - Web
* `desktop` - Desktop
  {
  }
  "workingDirectory": string // Absolute path of the local folder bound to a
desktop conversation. Only set for desktop conversations; null for web
conversations.
  "slideProjectId": string
  "matchedField": string // Cached per instance: ``get_matched_message_id`` /
``get_matched_snippet``
both read this, so resolving it once avoids recomputing the keyword and
title-match logic three times per serialized conversation.
```

```
  "matchedSnippet": string // Keyword-centred excerpt of the matched message, with
ellipses.

Reads the ``matched_message_content`` annotation added by
``ConversationViewSet._annotate_keyword_match``; no extra query.
  "matchedMessageId": string
  "pinnedAt": string (timestamp) // When the conversation was pinned. Null means
unpinned.
  "folder": string (uuid) // The user-defined sidebar folder this conversation is
grouped into. Null means unclassified (shown under the time groups). Deleting the
folder resets this to null without deleting the conversation.
  "hasActiveBrowserSession": boolean // Whether a browser_use session snapshot
exists to resume.

Lets the frontend know it should proactively re-request the browser
panel (emit ``browser:start``) after a page reload, instead of only
ever showing the panel when a live ``browser:frame`` push happens to
arrive first.
  "callerOrganizationId": string // Bound caller organization (stamped at
conversation start); null when unbound
  "handoff": object // 交接資訊：enabled=平台開關；接續對話帶
source_conversation_id/source_title；被交接的原對話帶
continued_to_conversation_id/continued_to_title 與 latest_summary_message_id
  "displayContextUsage": boolean // 是否顯示上下文使用量百分比條（對話平台開關，MaiGPT 恆
為 true；與交接開關互相獨立）
}
```

回應範例值

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "contact": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應字串",
    "avatar": "回應字串",
    "email": "response@example.com",
    "phoneNumber": "回應字串",
    "metadata": null,
    "sourceId": "回應字串",
    "tags": [
      {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "name": "回應字串"
      }
    ]
  },
  "inbox": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
```

```
    "name": "回應字串",
    "channelType": "line",
    "unreadConversationsCount": 456,
    "signAuth": {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "signSource": "550e8400-e29b-41d4-a716-446655440000",
      "signParams": {
        "keycloak": {
          "clientId": "回應字串",
          "url": "回應字串",
          "realm": "回應字串"
        },
        "line": {
          "liffId": "回應字串"
        },
        "ad": {
          "saml": "回應字串"
        },
        "google": {
          "enabled": false
        }
      },
      "sourceIdAccessEnabled": false,
      "sourceIdVerifyMode": {},
      "sourceIdSignatureTtlMinutes": {},
      "keycloakTokenPassthrough": false,
      "keycloakTokenPassthroughAllowedHosts": [
        "回應字串"
      ]
    },
    "enableAnalysis": false
  },
  "chatbot": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應範例名稱",
    "description": "回應範例描述"
  },
  "title": "回應字串",
  "lastMessage": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "type": "回應字串",
    "content": "回應字串",
    "createdAt": "回應字串"
  },
  "callRecord": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "status": "initiated",
    "direction": "inbound",
    "isActive": false,
    "canHangup": false
```

```
  },
  "lastMessageCreatedAt": "回應字串",
  "unreadMessagesCount": 456,
  "autoReplyEnabled": false,
  "isAutoReplyNow": false,
  "willAiReplyNow": false,
  "lastReadAt": "回應字串",
  "createdAt": "回應字串",
  "isGroupChat": false,
  "enableGroupMention": false,
  "queryMetadata": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應範例名稱",
    "description": "回應範例描述"
  },
  "toolMask": null,
  "connectorMask": null,
  "thinkingConfig": null,
  "thinkingConfigSchema": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應範例名稱",
    "description": "回應範例描述"
  },
  "effectiveThinkingConfig": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應範例名稱",
    "description": "回應範例描述"
  },
  "llm": "550e8400-e29b-41d4-a716-446655440000",
  "deepResearchStatus": {},
  "deepResearchOutputFormat": "canvas",
  "ipAddress": "回應字串",
  "ipCountryCode": "回應字串",
  "ipRecordedAt": "回應字串",
  "assignee": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應字串",
    "userId": "550e8400-e29b-41d4-a716-446655440000"
  },
  "status": "open",
  "tags": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "回應字串",
      "memberIds": [
        "550e8400-e29b-41d4-a716-446655440000"
      ]
    }
  ],
  "progressStatus": "回應字串",
```

```
  "firstResponseAt": "回應字串",
  "queuedAt": "回應字串",
  "assignedAt": "回應字串",
  "transferReason": "回應字串",
  "satisfactionScore": 456,
  "satisfactionComment": "回應字串",
  "satisfactionSubmittedAt": "回應字串",
  "latestAnalysisSummary": "回應字串",
  "clientPlatform": {},
  "workingDirectory": "回應字串",
  "slideProjectId": "回應字串",
  "matchedField": "回應字串",
  "matchedSnippet": "回應字串",
  "matchedMessageId": "回應字串",
  "pinnedAt": "回應字串",
  "folder": "550e8400-e29b-41d4-a716-446655440000",
  "hasActiveBrowserSession": false,
  "callerOrganizationId": "回應字串",
  "handoff": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應範例名稱",
    "description": "回應範例描述"
  },
  "displayContextUsage": false
}
```


重新命名對話

PATCH `/api/v1/conversations/{id}/rename/`

參數

參數名稱	必填	類型	說明
`id`	V	string	A UUID string identifying this Conversation.

請求內容

請求參數

欄位	類型	必填	說明
title	string	否	

請求結構範例

```
{
  "title"?: string // 非必填
}
```

請求範例值

```
{
  "title": "範例名稱"
}
```

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X PATCH "https://api.maiagent.ai/api/v1/conversations/550e8400-e29b-
41d4-a716-446655440000/rename/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "title": "範例名稱"
  }'

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// 請求內容 (payload)
const data = {
    "title": "範例名稱"
  };

axios.patch("https://api.maiagent.ai/api/v1/conversations/550e8400-e29b-41d4-a716-446655440000/rename/", data, config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/conversations/550e8400-e29b-41d4-a716-446655440000/rename/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# 請求內容 (payload)
data = {
    "title": "範例名稱"
}

response = requests.patch(url, json=data, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->patch("https://api.maiagent.ai/api/v1/conversations/550e8400-e29b-41d4-a716-446655440000/rename/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'title' => '範例名稱'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
{
  "id": string (uuid)
  "contact": { // 輕量級 Contact Serializer，用於 Conversation List view
```

```
只包含 List view 必要的欄位，移除 inboxes、mcp_credentials 和 api_credentials
以避免 N+1 查詢問題。email / phone_number / metadata 為 Contact 自身的純量欄位，
前端對話側欄需要顯示，無 N+1 成本。
  {
    "id": string (uuid)
    "name": string
    "avatar"?: string // Stores our own media as a relative storage key, or an
external CDN URL as-is. (非必填)
    "email"?: // 可能有不同的類型 (非必填)
    string (email) // 非必填
    "phoneNumber"?: string // 非必填
    "metadata"?: object // Custom customer information shown in the customer panel
of the conversation page (非必填)
    "sourceId"?: string // 非必填
    "tags": [
      {
        "id": string (uuid)
        "name": string
      }
    ]
  }
  }
  "inbox": { // Inbox summary embedded in a conversation payload.

``unread_conversations_count`` stays here because it is part of the
documented REST conversation API. It is an org-wide denormalized
counter, so WS emit paths must run the payload through
:func:`strip_org_wide_unread_count` before broadcasting it to rooms
that include members without ``GroupInbox.can_view_conversations``.
  {
    "id": string (uuid)
    "name": string
    "channelType": string (enum: line, telegram, teams, web, messenger, instagram,
email, whatsapp, slack, team_plus, line_works, viber) // * `line` - LINE
* `telegram` - Telegram
* `teams` - Teams
* `web` - Web
* `messenger` - Messenger
* `instagram` - Instagram
* `email` - Email
* `whatsapp` - WhatsApp
* `slack` - Slack
* `team_plus` - Team+
* `line_works` - LINE WORKS
* `viber` - Viber
    "unreadConversationsCount"?: integer // 非必填
    "signAuth"?:  // 非必填
    {
      "id": string (uuid)
      "signSource": string (uuid)
```

```
      "signParams": {
      {
        "keycloak":
        {
          "clientId": string
          "url": string
          "realm": string
        }
        "line":
        {
          "liffId": string
        }
        "ad":
        {
          "saml": string
        }
        "google"?:  // 非必填
        {
          "enabled": boolean
        }
      }
      }
      "sourceIdAccessEnabled"?: boolean // When enabled, embedded visitors presenting a Source ID (verified per the verify mode below) may chat without going through the login flow. Disabled keeps every existing behavior unchanged. (非必填)
      "sourceIdVerifyMode"?:  // "Require signature verification": the embedding site must send an HMAC signature computed on its backend. "Source ID only": anyone knowing a Source ID can act as that contact; suitable only for testing or closed networks.

* `signature` - Require signature verification
* `raw` - Source ID only (非必填)
      {
      }
      "sourceIdSignatureTtlMinutes"?:  // How long a signature can be used to obtain the contact identity. Not a session lifetime: once exchanged, the session follows the existing WebChat mechanism.

* `1` - 1
* `5` - 5
* `15` - 15 (非必填)
      {
      }
      "keycloakTokenPassthrough"?: boolean // When enabled, the Keycloak access token a visitor logged in with is forwarded as the Authorization header when the AI calls MCP and API tools on their behalf, so tools do not require a separate per-tool login. Only for the Keycloak sign source. Never overrides an Authorization header a tool already resolves from its own credentials. The visitor identity is the organization member bound to the conversation at login, never the contact Source ID. (非必填)
```

```
      "keycloakTokenPassthroughAllowedHosts"?: [ // Hostnames (or "*.example.com"
wildcards) of the tools the visitor Keycloak token may be sent to (非必填)
        string
      ]
    }
    "enableAnalysis"?: boolean // 非必填
  }
  }
  "chatbot": object // Chatbot (Agent) summary from the conversation's inbox,
already eager-loaded.

``is_maigpt`` lets the client tell the default MaiGPT agent apart (icon, feature
gate) without comparing against the organization's ``maigpt_inbox`` id;
``file_workspace_mode`` is the effective P6 mode (MaiGPT, blueprint and the
organization's file-library switch already applied).
  "title": string
  "lastMessage"?: { // 非必填
  {
    "id": string (uuid)
    "type"?: string // 非必填
    "content"?: string // 非必填
    "createdAt": string (timestamp)
  }
  }
  "callRecord":
  {
    "id": string (uuid)
    "status"?: string (enum: initiated, ringing, in-progress, completed, failed,
busy, no-answer, canceled) // * `initiated` - Initiated
* `ringing` - Ringing
* `in-progress` - In Progress
* `completed` - Completed
* `failed` - Failed
* `busy` - Busy
* `no-answer` - No Answer
* `canceled` - Canceled (非必填)
    "direction": string (enum: inbound, outbound) // * `inbound` - Inbound
* `outbound` - Outbound
    "isActive": boolean
    "canHangup": boolean
  }
  "lastMessageCreatedAt": string (timestamp)
  "unreadMessagesCount": integer
  "autoReplyEnabled": boolean
  "isAutoReplyNow": boolean
  "willAiReplyNow": boolean // Whether a text message arriving through the inbox
gets an AI reply right now.

The messaging channels are gated by ``is_auto_reply_now`` (auto reply on and
inside the
```

```
inbox auto-reply schedule) and by the inbox having a chatbot. The chatbot's API
web chat
is answered by the completions endpoint, which ignores the schedule, so there the
conversation switch alone decides. The channel is only looked up for a web inbox
outside
its schedule.

Surfaces that ignore the schedule on any inbox answer from their own rule instead:
the
completions endpoint continuing an existing conversation
(``completions_progress_status``)
and voice turns, which the voice agent answers.
  "lastReadAt": string (timestamp)
  "createdAt": string (timestamp)
  "isGroupChat": boolean
  "enableGroupMention"?: boolean // 非必填
  "queryMetadata"?: { // 查詢元資料，控制可查詢的知識範圍；詳見各端點說明 (非必填)
  {
    "knowledgeBases"?: [ // 可查詢的知識庫清單；空陣列或 null＝全部不可查（無權限），未提供＝
不限制 (非必填)
      {
        "knowledgeBaseId": string (uuid) // 知識庫 ID
        "chatbotFileIds"?: [ // 檔案 ID 清單（依 hasUserSelectedAll 決定為排除或僅選
取） (非必填)
          string (uuid)
        ]
        "knowledgeBaseFileIds"?: [ // 檔案 ID 清單（chatbotFileIds 的新名稱；兩者皆提供
時以本欄位為準） (非必填)
          string (uuid)
        ]
        "faqIds"?: [ // FAQ ID 清單（依 hasUserSelectedAll 決定為排除或僅選取） (非必填)
          string (uuid)
        ]
        "hasUserSelectedAll"?: boolean // true＝選取知識庫全部內容並排除清單中的項目；
false＝僅選取清單中的項目 (非必填)
      }
    ]
    "labelRelations"?: { // 標籤過濾條件；conditions 為空陣列＝不做標籤過濾（並非無權限）。
必須與 knowledgeBases 一併提供——單獨提供時知識庫檢索不會套用標籤過濾（等同不限制） (非必填)
    {
      "operator": string (enum: AND, OR) // 標籤條件的組合方式
      "conditions"?: [ // 標籤條件清單，支援巢狀 operator/conditions 組合 (非必填)
        object
      ]
    }
    }
  }
  }
  "toolMask"?: object // Enabled/disabled state per tool: {tool_id: bool} (非必填)
  "connectorMask"?: object // Enabled/disabled state per connector: {connector_id:
```

```
bool} (非必填)
  "thinkingConfig"?: object // None = not set (inherit the chatbot setting);
otherwise {"reasoning_effort": <level>} (非必填)
  "thinkingConfigSchema": { // 此模型的思考設定表單；null 表示此模型沒有思考設定
  {
    "type"?: string // 表單類型，固定為 reasoning_effort (非必填)
    "fields"?: object // reasoning_effort 欄位：options 列出此模型接受的思考等級（由弱到
強），default 固定為 null (非必填)
    "canDisable"?: boolean // 此模型能否關閉思考；true 時 options 含 off (非必填)
    "unsetBehavior"?: string (enum: off, model_default) // 對話與助理都沒設思考等級時的
實際行為：off＝不思考（最快）；model_default＝模型自行思考，或平台預設等級會開啟思考 (非必填)
    "unsetLevel"?: string // 沒設等級時平台實際送出的等級；null 表示不送思考參數，交給模型自
身預設 (非必填)
  }
  }
  "effectiveThinkingConfig": object // The level the next reply sends on this
conversation's model, after gating and clamping.

The stored choice resolves conversation > chatbot > the LLM row's default level;
None means
the model sends no thinking parameter, so the provider default applies.
  "llm": string (uuid) // The model the next reply runs on: the conversation's
pin, else its assistant's current model.

TC-0205: returning the stored ``conversation.llm`` would show a model an unpinned
conversation no
longer uses once its assistant switches model, while ``thinking_config_schema``
already follows the
effective model. Read-only: displaying it never marks the conversation as
explicitly selected;
only the update-llm endpoint does.
  "deepResearchStatus":  // Status of deep research for this conversation

* `not_used` - Not Used
* `started` - Started
* `running` - Running
* `completed` - Completed
* `failed` - Failed
  {
  }
  "deepResearchOutputFormat": // 可能有不同的類型
  string (enum: canvas, chat, file) // Chosen delivery form for the finished
report. Set only when the user clicks a format in the pre-research choice card;
reset to NULL each time Deep Research is (re-)armed. NULL means no explicit choice
(or a plan-skipping request) and falls back to Canvas at render time, but stays
distinct from an explicit canvas pick so the frontend can lock the card only after
a real selection. To roll back to fixed-Canvas behavior, force this to NULL/canvas
— no redeploy needed.

* `canvas` - Canvas
```

```
* `chat` - Chat reply
* `file` - Downloadable file
  "ipAddress": string
  "ipCountryCode": string
  "ipRecordedAt": string (timestamp)
  "assignee":
  {
    "id": string (uuid)
    "name": string
    "userId": string (uuid)
  }
  "status"?: string (enum: open, resolved, queued) // * `open` - Open
* `resolved` - Resolved
* `queued` - Queued (非必填)
  "tags": [
    {
      "id": string (uuid)
      "name": string
      "memberIds"?: [ // 非必填
        string (uuid)
      ]
    }
  ]
  "progressStatus": string
  "firstResponseAt"?: string (timestamp) // 非必填
  "queuedAt"?: string (timestamp) // 非必填
  "assignedAt"?: string (timestamp) // 非必填
  "transferReason"?: string // 非必填
  "satisfactionScore": integer // Conversation satisfaction rating on a 5-point
scale (1=very dissatisfied, 5=very satisfied)
  "satisfactionComment": string
  "satisfactionSubmittedAt": string (timestamp)
  "latestAnalysisSummary": string // The conversation's current analysis summary
(its active summary revision).

Reads the `latest_analysis_summary` annotation added by `setup_eager_loading`
to avoid an N+1 query. All read paths (list / retrieve / create) eager-load,
so the annotation is present; it falls back to '' only for instances built
outside `setup_eager_loading`.
  "clientPlatform":  // Client platform that created this conversation (web,
desktop)

* `web` - Web
* `desktop` - Desktop
  {
  }
  "workingDirectory": string // Absolute path of the local folder bound to a
desktop conversation. Only set for desktop conversations; null for web
conversations.
  "slideProjectId": string
```

```
  "matchedField": string // Cached per instance: ``get_matched_message_id`` /
``get_matched_snippet``
both read this, so resolving it once avoids recomputing the keyword and
title-match logic three times per serialized conversation.
  "matchedSnippet": string // Keyword-centred excerpt of the matched message, with
ellipses.

Reads the ``matched_message_content`` annotation added by
``ConversationViewSet._annotate_keyword_match``; no extra query.
  "matchedMessageId": string
  "pinnedAt": string (timestamp) // When the conversation was pinned. Null means
unpinned.
  "folder": string (uuid) // The user-defined sidebar folder this conversation is
grouped into. Null means unclassified (shown under the time groups). Deleting the
folder resets this to null without deleting the conversation.
  "hasActiveBrowserSession": boolean // Whether a browser_use session snapshot
exists to resume.

Lets the frontend know it should proactively re-request the browser
panel (emit ``browser:start``) after a page reload, instead of only
ever showing the panel when a live ``browser:frame`` push happens to
arrive first.
  "callerOrganizationId": string // Bound caller organization (stamped at
conversation start); null when unbound
  "handoff": object // 交接資訊：enabled=平台開關；接續對話帶
source_conversation_id/source_title；被交接的原對話帶
continued_to_conversation_id/continued_to_title 與 latest_summary_message_id
  "displayContextUsage": boolean // 是否顯示上下文使用量百分比條（對話平台開關，MaiGPT 恆
為 true；與交接開關互相獨立）
}
```

回應範例值

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "contact": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應字串",
    "avatar": "回應字串",
    "email": "response@example.com",
    "phoneNumber": "回應字串",
    "metadata": null,
    "sourceId": "回應字串",
    "tags": [
      {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "name": "回應字串"
      }
```

```
      ]
    },
    "inbox": {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "回應字串",
      "channelType": "line",
      "unreadConversationsCount": 456,
      "signAuth": {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "signSource": "550e8400-e29b-41d4-a716-446655440000",
        "signParams": {
          "keycloak": {
            "clientId": "回應字串",
            "url": "回應字串",
            "realm": "回應字串"
          },
          "line": {
            "liffId": "回應字串"
          },
          "ad": {
            "saml": "回應字串"
          },
          "google": {
            "enabled": false
          }
        },
        "sourceIdAccessEnabled": false,
        "sourceIdVerifyMode": {},
        "sourceIdSignatureTtlMinutes": {},
        "keycloakTokenPassthrough": false,
        "keycloakTokenPassthroughAllowedHosts": [
          "回應字串"
        ]
      },
      "enableAnalysis": false
    },
    "chatbot": {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "回應範例名稱",
      "description": "回應範例描述"
    },
    "title": "回應字串",
    "lastMessage": {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "type": "回應字串",
      "content": "回應字串",
      "createdAt": "回應字串"
    },
    "callRecord": {
      "id": "550e8400-e29b-41d4-a716-446655440000",
```

```
    "status": "initiated",
    "direction": "inbound",
    "isActive": false,
    "canHangup": false
  },
  "lastMessageCreatedAt": "回應字串",
  "unreadMessagesCount": 456,
  "autoReplyEnabled": false,
  "isAutoReplyNow": false,
  "willAiReplyNow": false,
  "lastReadAt": "回應字串",
  "createdAt": "回應字串",
  "isGroupChat": false,
  "enableGroupMention": false,
  "queryMetadata": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應範例名稱",
    "description": "回應範例描述"
  },
  "toolMask": null,
  "connectorMask": null,
  "thinkingConfig": null,
  "thinkingConfigSchema": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應範例名稱",
    "description": "回應範例描述"
  },
  "effectiveThinkingConfig": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應範例名稱",
    "description": "回應範例描述"
  },
  "llm": "550e8400-e29b-41d4-a716-446655440000",
  "deepResearchStatus": {},
  "deepResearchOutputFormat": "canvas",
  "ipAddress": "回應字串",
  "ipCountryCode": "回應字串",
  "ipRecordedAt": "回應字串",
  "assignee": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應字串",
    "userId": "550e8400-e29b-41d4-a716-446655440000"
  },
  "status": "open",
  "tags": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "回應字串",
      "memberIds": [
        "550e8400-e29b-41d4-a716-446655440000"
```

```
      ]
    }
  ],
  "progressStatus": "回應字串",
  "firstResponseAt": "回應字串",
  "queuedAt": "回應字串",
  "assignedAt": "回應字串",
  "transferReason": "回應字串",
  "satisfactionScore": 456,
  "satisfactionComment": "回應字串",
  "satisfactionSubmittedAt": "回應字串",
  "latestAnalysisSummary": "回應字串",
  "clientPlatform": {},
  "workingDirectory": "回應字串",
  "slideProjectId": "回應字串",
  "matchedField": "回應字串",
  "matchedSnippet": "回應字串",
  "matchedMessageId": "回應字串",
  "pinnedAt": "回應字串",
  "folder": "550e8400-e29b-41d4-a716-446655440000",
  "hasActiveBrowserSession": false,
  "callerOrganizationId": "回應字串",
  "handoff": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應範例名稱",
    "description": "回應範例描述"
  },
  "displayContextUsage": false
}
```


刪除對話

DELETE `/api/v1/conversations/{id}`

參數

參數名稱	必填	類型	說明
`id`	V	string	A UUID string identifying this Conversation.

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X DELETE "https://api.maiagent.ai/api/v1/conversations/550e8400-e29b-
41d4-a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

// 請求內容 (payload)
const data = null;

axios.delete("https://api.maiagent.ai/api/v1/conversations/550e8400-e29b-
41d4-a716-446655440000/", data, config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/conversations/550e8400-e29b-41d4-a716-446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.delete(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>delete("https://api.maiagent.ai/api/v1/conversations/550e8400-e29b-41d4-
a716-446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼	說明
204	No response body

中止 AI 回覆

POST `/api/v1/conversations/{conversationId}/stop-response/`

參數

參數名稱	必填	類型	說明
conversationId	V	string	

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X POST "https://api.maiagent.ai/api/v1/conversations/550e8400-e29b-
41d4-a716-446655440000/stop-response/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

// 請求內容 (payload)
const data = null;

axios.post("https://api.maiagent.ai/api/v1/conversations/550e8400-e29b-41d4-a716-446655440000/stop-response/", data, config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/conversations/550e8400-e29b-41d4-a716-446655440000/stop-response/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.post(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>post("https://api.maiagent.ai/api/v1/conversations/550e8400-e29b-41d4-a716-
446655440000/stop-response/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼	說明
200	No response body

提交對話滿意度

POST `/api/v1/conversations/{id}/satisfaction/`

每個對話只能提交一次。

參數

參數名稱	必填	類型	說明
id	V	string	A UUID string identifying this Conversation.

請求內容

請求參數

欄位	類型	必填	說明
satisfactionScore	integer	是	Conversation satisfaction rating on a 5-point scale (1=very dissatisfied, 5=very satisfied)
satisfactionComment	string	否	

請求結構範例

```
{
  "satisfactionScore": integer // Conversation satisfaction rating on a 5-point scale (1=very dissatisfied, 5=very satisfied)
  "satisfactionComment"?: string // 非必填
}
```

請求範例值

```
{
  "satisfactionScore": 5,
  "satisfactionComment": "回答清楚，問題已解決"
}
```

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X POST "https://api.maiagent.ai/api/v1/conversations/550e8400-e29b-
41d4-a716-446655440000/satisfaction/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "satisfactionScore": 5,
    "satisfactionComment": "回答清楚，問題已解決"
  }'

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// 請求內容 (payload)
const data = {
    "satisfactionScore": 5,
    "satisfactionComment": "回答清楚，問題已解決"
  };

axios.post("https://api.maiagent.ai/api/v1/conversations/550e8400-e29b-41d4-
a716-446655440000/satisfaction/", data, config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/conversations/550e8400-e29b-41d4-a716-446655440000/satisfaction/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# 請求內容 (payload)
data = {
    "satisfactionScore": 5,
    "satisfactionComment": "回答清楚，問題已解決"
}

response = requests.post(url, json=data, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>post("https://api.maiagent.ai/api/v1/conversations/550e8400-e29b-41d4-a716-
446655440000/satisfaction/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'satisfactionScore' => 5,
            'satisfactionComment' => '回答清楚，問題已解決'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 201

回應結構範例

```
{
  "satisfactionScore": integer
  "satisfactionComment"?: string // 非必填
```

```
  "satisfactionSubmittedAt": string // 提交時間，ISO 8601 UTC 字串，例如 2026-10-09T15:10:48.717193Z
}
```

回應範例值

```
{
  "satisfactionScore": 456,
  "satisfactionComment": "回應字串",
  "satisfactionSubmittedAt": "回應字串"
}
```

狀態碼: 409 - 此對話已提交過滿意度

列出對話事件

GET `/api/v1/conversations/{id}/events/`

轉真人流程的事件紀錄（event_type：transfer_triggered／human_assigned／returned_to_ai／queue_timeout），可與 Webhook 對帳。流程見技術手冊客服系統串接。

參數

參數名稱	必填	類型	說明
id	V	string	A UUID string identifying this Conversation.

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/conversations/550e8400-e29b-41d4-a716-446655440000/events/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/conversations/550e8400-e29b-41d4-a716-446655440000/events/", config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/conversations/550e8400-e29b-41d4-a716-446655440000/events/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/conversations/550e8400-e29b-41d4-a716-
446655440000/events/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
{
  "id": string (uuid)
  "contact": { // 輕量級 Contact Serializer，用於 Conversation List view

只包含 List view 必要的欄位，移除 inboxes、mcp_credentials 和 api_credentials
以避免 N+1 查詢問題。email / phone_number / metadata 為 Contact 自身的純量欄位，
前端對話側欄需要顯示，無 N+1 成本。
  {
```

```
    "id": string (uuid)
    "name": string
    "avatar"?: string // Stores our own media as a relative storage key, or an
external CDN URL as-is. (非必填)
    "email"?: // 可能有不同的類型 (非必填)
    string (email) // 非必填
    "phoneNumber"?: string // 非必填
    "metadata"?: object // Custom customer information shown in the customer panel
of the conversation page (非必填)
    "sourceId"?: string // 非必填
    "tags": [
      {
        "id": string (uuid)
        "name": string
      }
    ]
  }
  }
  "inbox": { // Inbox summary embedded in a conversation payload.

``unread_conversations_count`` stays here because it is part of the
documented REST conversation API. It is an org-wide denormalized
counter, so WS emit paths must run the payload through
:func:`strip_org_wide_unread_count` before broadcasting it to rooms
that include members without ``GroupInbox.can_view_conversations``.
  {
    "id": string (uuid)
    "name": string
    "channelType": string (enum: line, telegram, teams, web, messenger, instagram,
email, whatsapp, slack, team_plus, line_works, viber) // * `line` - LINE
* `telegram` - Telegram
* `teams` - Teams
* `web` - Web
* `messenger` - Messenger
* `instagram` - Instagram
* `email` - Email
* `whatsapp` - WhatsApp
* `slack` - Slack
* `team_plus` - Team+
* `line_works` - LINE WORKS
* `viber` - Viber
    "unreadConversationsCount"?: integer // 非必填
    "signAuth"?:  // 非必填
    {
      "id": string (uuid)
      "signSource": string (uuid)
      "signParams": {
      {
        "keycloak":
        {
```

```
          "clientId": string
          "url": string
          "realm": string
        }
        "line":
        {
          "liffId": string
        }
        "ad":
        {
          "saml": string
        }
        "google"?:  // 非必填
        {
          "enabled": boolean
        }
      }
      }
      "sourceIdAccessEnabled"?: boolean // When enabled, embedded visitors presenting a Source ID (verified per the verify mode below) may chat without going through the login flow. Disabled keeps every existing behavior unchanged. (非必填)
      "sourceIdVerifyMode"?:  // "Require signature verification": the embedding site must send an HMAC signature computed on its backend. "Source ID only": anyone knowing a Source ID can act as that contact; suitable only for testing or closed networks.

* `signature` - Require signature verification
* `raw` - Source ID only (非必填)
      {
      }
      "sourceIdSignatureTtlMinutes"?:  // How long a signature can be used to obtain the contact identity. Not a session lifetime: once exchanged, the session follows the existing WebChat mechanism.

* `1` - 1
* `5` - 5
* `15` - 15 (非必填)
      {
      }
      "keycloakTokenPassthrough"?: boolean // When enabled, the Keycloak access token a visitor logged in with is forwarded as the Authorization header when the AI calls MCP and API tools on their behalf, so tools do not require a separate per-tool login. Only for the Keycloak sign source. Never overrides an Authorization header a tool already resolves from its own credentials. The visitor identity is the organization member bound to the conversation at login, never the contact Source ID. (非必填)
      "keycloakTokenPassthroughAllowedHosts"?: [ // Hostnames (or "*.example.com" wildcards) of the tools the visitor Keycloak token may be sent to (非必填)
        string
      ]
```

```
    }
    "enableAnalysis"?: boolean // 非必填
  }
  }
  "chatbot": object // Chatbot (Agent) summary from the conversation's inbox,
already eager-loaded.

``is_maigpt`` lets the client tell the default MaiGPT agent apart (icon, feature
gate) without comparing against the organization's ``maigpt_inbox`` id;
``file_workspace_mode`` is the effective P6 mode (MaiGPT, blueprint and the
organization's file-library switch already applied).
  "title": string
  "lastMessage"?: { // 非必填
  {
    "id": string (uuid)
    "type"?: string // 非必填
    "content"?: string // 非必填
    "createdAt": string (timestamp)
  }
  }
  "callRecord":
  {
    "id": string (uuid)
    "status"?: string (enum: initiated, ringing, in-progress, completed, failed,
busy, no-answer, canceled) // * `initiated` - Initiated
* `ringing` - Ringing
* `in-progress` - In Progress
* `completed` - Completed
* `failed` - Failed
* `busy` - Busy
* `no-answer` - No Answer
* `canceled` - Canceled (非必填)
    "direction": string (enum: inbound, outbound) // * `inbound` - Inbound
* `outbound` - Outbound
    "isActive": boolean
    "canHangup": boolean
  }
  "lastMessageCreatedAt": string (timestamp)
  "unreadMessagesCount": integer
  "autoReplyEnabled": boolean
  "isAutoReplyNow": boolean
  "willAiReplyNow": boolean // Whether a text message arriving through the inbox
gets an AI reply right now.

The messaging channels are gated by ``is_auto_reply_now`` (auto reply on and
inside the
inbox auto-reply schedule) and by the inbox having a chatbot. The chatbot's API
web chat
is answered by the completions endpoint, which ignores the schedule, so there the
conversation switch alone decides. The channel is only looked up for a web inbox
```

```
outside
its schedule.

Surfaces that ignore the schedule on any inbox answer from their own rule instead:
the
completions endpoint continuing an existing conversation
(``completions_progress_status``)
and voice turns, which the voice agent answers.
  "lastReadAt": string (timestamp)
  "createdAt": string (timestamp)
  "isGroupChat": boolean
  "enableGroupMention"?: boolean // 非必填
  "queryMetadata"?: { // 查詢元資料，控制可查詢的知識範圍；詳見各端點說明 (非必填)
  {
    "knowledgeBases"?: [ // 可查詢的知識庫清單；空陣列或 null＝全部不可查（無權限），未提供＝
不限制 (非必填)
      {
        "knowledgeBaseId": string (uuid) // 知識庫 ID
        "chatbotFileIds"?: [ // 檔案 ID 清單（依 hasUserSelectedAll 決定為排除或僅選
取） (非必填)
          string (uuid)
        ]
        "knowledgeBaseFileIds"?: [ // 檔案 ID 清單（chatbotFileIds 的新名稱；兩者皆提供
時以本欄位為準） (非必填)
          string (uuid)
        ]
        "faqIds"?: [ // FAQ ID 清單（依 hasUserSelectedAll 決定為排除或僅選取） (非必填)
          string (uuid)
        ]
        "hasUserSelectedAll"?: boolean // true＝選取知識庫全部內容並排除清單中的項目；
false＝僅選取清單中的項目 (非必填)
      }
    ]
    "labelRelations"?: { // 標籤過濾條件；conditions 為空陣列＝不做標籤過濾（並非無權限）。
必須與 knowledgeBases 一併提供——單獨提供時知識庫檢索不會套用標籤過濾（等同不限制） (非必填)
    {
      "operator": string (enum: AND, OR) // 標籤條件的組合方式
      "conditions"?: [ // 標籤條件清單，支援巢狀 operator/conditions 組合 (非必填)
        object
      ]
    }
    }
  }
  }
  "toolMask"?: object // Enabled/disabled state per tool: {tool_id: bool} (非必填)
  "connectorMask"?: object // Enabled/disabled state per connector: {connector_id:
bool} (非必填)
  "thinkingConfig"?: object // None = not set (inherit the chatbot setting);
otherwise {"reasoning_effort": <level>} (非必填)
  "thinkingConfigSchema": { // 此模型的思考設定表單；null 表示此模型沒有思考設定
```

```
  {
    "type"?: string // 表單類型，固定為 reasoning_effort (非必填)
    "fields"?: object // reasoning_effort 欄位：options 列出此模型接受的思考等級（由弱到強），default 固定為 null (非必填)
    "canDisable"?: boolean // 此模型能否關閉思考；true 時 options 含 off (非必填)
    "unsetBehavior"?: string (enum: off, model_default) // 對話與助理都沒設思考等級時的實際行為：off＝不思考（最快）；model_default＝模型自行思考，或平台預設等級會開啟思考 (非必填)
    "unsetLevel"?: string // 沒設等級時平台實際送出的等級；null 表示不送思考參數，交給模型自身預設 (非必填)
  }
  }
  "effectiveThinkingConfig": object // The level the next reply sends on this conversation's model, after gating and clamping.

The stored choice resolves conversation > chatbot > the LLM row's default level; None means
the model sends no thinking parameter, so the provider default applies.
  "llm": string (uuid) // The model the next reply runs on: the conversation's pin, else its assistant's current model.

TC-0205: returning the stored ``conversation.llm`` would show a model an unpinned conversation no
longer uses once its assistant switches model, while ``thinking_config_schema`` already follows the
effective model. Read-only: displaying it never marks the conversation as explicitly selected;
only the update-llm endpoint does.
  "deepResearchStatus":  // Status of deep research for this conversation

* `not_used` - Not Used
* `started` - Started
* `running` - Running
* `completed` - Completed
* `failed` - Failed
  {
  }
  "deepResearchOutputFormat": // 可能有不同的類型
  string (enum: canvas, chat, file) // Chosen delivery form for the finished report. Set only when the user clicks a format in the pre-research choice card; reset to NULL each time Deep Research is (re-)armed. NULL means no explicit choice (or a plan-skipping request) and falls back to Canvas at render time, but stays distinct from an explicit canvas pick so the frontend can lock the card only after a real selection. To roll back to fixed-Canvas behavior, force this to NULL/canvas — no redeploy needed.

* `canvas` - Canvas
* `chat` - Chat reply
* `file` - Downloadable file
  "ipAddress": string
  "ipCountryCode": string
```

```
  "ipRecordedAt": string (timestamp)
  "assignee":
  {
    "id": string (uuid)
    "name": string
    "userId": string (uuid)
  }
  "status"?: string (enum: open, resolved, queued) // * `open` - Open
* `resolved` - Resolved
* `queued` - Queued (非必填)
  "tags": [
    {
      "id": string (uuid)
      "name": string
      "memberIds"?: [ // 非必填
        string (uuid)
      ]
    }
  ]
  "progressStatus": string
  "firstResponseAt"?: string (timestamp) // 非必填
  "queuedAt"?: string (timestamp) // 非必填
  "assignedAt"?: string (timestamp) // 非必填
  "transferReason"?: string // 非必填
  "satisfactionScore": integer // Conversation satisfaction rating on a 5-point
scale (1=very dissatisfied, 5=very satisfied)
  "satisfactionComment": string
  "satisfactionSubmittedAt": string (timestamp)
  "latestAnalysisSummary": string // The conversation's current analysis summary
(its active summary revision).

Reads the `latest_analysis_summary` annotation added by `setup_eager_loading`
to avoid an N+1 query. All read paths (list / retrieve / create) eager-load,
so the annotation is present; it falls back to '' only for instances built
outside `setup_eager_loading`.
  "clientPlatform":  // Client platform that created this conversation (web,
desktop)

* `web` - Web
* `desktop` - Desktop
  {
  }
  "workingDirectory": string // Absolute path of the local folder bound to a
desktop conversation. Only set for desktop conversations; null for web
conversations.
  "slideProjectId": string
  "matchedField": string // Cached per instance: ``get_matched_message_id`` /
``get_matched_snippet``
both read this, so resolving it once avoids recomputing the keyword and
title-match logic three times per serialized conversation.
```

```
  "matchedSnippet": string // Keyword-centred excerpt of the matched message, with
ellipses.

Reads the ``matched_message_content`` annotation added by
``ConversationViewSet._annotate_keyword_match``; no extra query.
  "matchedMessageId": string
  "pinnedAt": string (timestamp) // When the conversation was pinned. Null means
unpinned.
  "folder": string (uuid) // The user-defined sidebar folder this conversation is
grouped into. Null means unclassified (shown under the time groups). Deleting the
folder resets this to null without deleting the conversation.
  "hasActiveBrowserSession": boolean // Whether a browser_use session snapshot
exists to resume.

Lets the frontend know it should proactively re-request the browser
panel (emit ``browser:start``) after a page reload, instead of only
ever showing the panel when a live ``browser:frame`` push happens to
arrive first.
  "callerOrganizationId": string // Bound caller organization (stamped at
conversation start); null when unbound
  "handoff": object // 交接資訊：enabled=平台開關；接續對話帶
source_conversation_id/source_title；被交接的原對話帶
continued_to_conversation_id/continued_to_title 與 latest_summary_message_id
  "displayContextUsage": boolean // 是否顯示上下文使用量百分比條（對話平台開關，MaiGPT 恆
為 true；與交接開關互相獨立）
}
```

回應範例值

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "contact": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應字串",
    "avatar": "回應字串",
    "email": "response@example.com",
    "phoneNumber": "回應字串",
    "metadata": null,
    "sourceId": "回應字串",
    "tags": [
      {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "name": "回應字串"
      }
    ]
  },
  "inbox": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
```

```
    "name": "回應字串",
    "channelType": "line",
    "unreadConversationsCount": 456,
    "signAuth": {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "signSource": "550e8400-e29b-41d4-a716-446655440000",
      "signParams": {
        "keycloak": {
          "clientId": "回應字串",
          "url": "回應字串",
          "realm": "回應字串"
        },
        "line": {
          "liffId": "回應字串"
        },
        "ad": {
          "saml": "回應字串"
        },
        "google": {
          "enabled": false
        }
      },
      "sourceIdAccessEnabled": false,
      "sourceIdVerifyMode": {},
      "sourceIdSignatureTtlMinutes": {},
      "keycloakTokenPassthrough": false,
      "keycloakTokenPassthroughAllowedHosts": [
        "回應字串"
      ]
    },
    "enableAnalysis": false
  },
  "chatbot": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應範例名稱",
    "description": "回應範例描述"
  },
  "title": "回應字串",
  "lastMessage": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "type": "回應字串",
    "content": "回應字串",
    "createdAt": "回應字串"
  },
  "callRecord": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "status": "initiated",
    "direction": "inbound",
    "isActive": false,
    "canHangup": false
```

```
  },
  "lastMessageCreatedAt": "回應字串",
  "unreadMessagesCount": 456,
  "autoReplyEnabled": false,
  "isAutoReplyNow": false,
  "willAiReplyNow": false,
  "lastReadAt": "回應字串",
  "createdAt": "回應字串",
  "isGroupChat": false,
  "enableGroupMention": false,
  "queryMetadata": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應範例名稱",
    "description": "回應範例描述"
  },
  "toolMask": null,
  "connectorMask": null,
  "thinkingConfig": null,
  "thinkingConfigSchema": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應範例名稱",
    "description": "回應範例描述"
  },
  "effectiveThinkingConfig": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應範例名稱",
    "description": "回應範例描述"
  },
  "llm": "550e8400-e29b-41d4-a716-446655440000",
  "deepResearchStatus": {},
  "deepResearchOutputFormat": "canvas",
  "ipAddress": "回應字串",
  "ipCountryCode": "回應字串",
  "ipRecordedAt": "回應字串",
  "assignee": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應字串",
    "userId": "550e8400-e29b-41d4-a716-446655440000"
  },
  "status": "open",
  "tags": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "回應字串",
      "memberIds": [
        "550e8400-e29b-41d4-a716-446655440000"
      ]
    }
  ],
  "progressStatus": "回應字串",
```

```
  "firstResponseAt": "回應字串",
  "queuedAt": "回應字串",
  "assignedAt": "回應字串",
  "transferReason": "回應字串",
  "satisfactionScore": 456,
  "satisfactionComment": "回應字串",
  "satisfactionSubmittedAt": "回應字串",
  "latestAnalysisSummary": "回應字串",
  "clientPlatform": {},
  "workingDirectory": "回應字串",
  "slideProjectId": "回應字串",
  "matchedField": "回應字串",
  "matchedSnippet": "回應字串",
  "matchedMessageId": "回應字串",
  "pinnedAt": "回應字串",
  "folder": "550e8400-e29b-41d4-a716-446655440000",
  "hasActiveBrowserSession": false,
  "callerOrganizationId": "回應字串",
  "handoff": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應範例名稱",
    "description": "回應範例描述"
  },
  "displayContextUsage": false
}
```


指派對話給成員

PATCH `/api/v1/conversations/{id}/assign/`

設定接手成員並停用 AI 自動回覆；排隊中的對話會轉為進行中。

參數

參數名稱	必填	類型	說明
`id`	V	string	A UUID string identifying this Conversation.

請求內容

請求參數

欄位	類型	必填	說明
assignee	string (uuid)	否	
transferReason	string	否	
tagIds	array[string]	否	

請求結構範例

```
{
  "assignee"?: string (uuid) // 非必填
  "transferReason"?: string // 非必填
  "tagIds"?: [ // 非必填
    string (uuid)
  ]
}
```

請求範例值

```
{
  "assignee": "550e8400-e29b-41d4-a716-446655440000",
  "transferReason": "範例字串",
  "tagIds": [
    "550e8400-e29b-41d4-a716-446655440000"
  ]
}
```

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X PATCH "https://api.maiagent.ai/api/v1/conversations/550e8400-e29b-
41d4-a716-446655440000/assign/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "assignee": "550e8400-e29b-41d4-a716-446655440000",
    "transferReason": "範例字串",
    "tagIds": [
      "550e8400-e29b-41d4-a716-446655440000"
    ]
  }'

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// 請求內容 (payload)
const data = {
    "assignee": "550e8400-e29b-41d4-a716-446655440000",
    "transferReason": "範例字串",
    "tagIds": [
      "550e8400-e29b-41d4-a716-446655440000"
    ]
  };

axios.patch("https://api.maiagent.ai/api/v1/conversations/550e8400-e29b-41d4-
a716-446655440000/assign/", data, config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/conversations/550e8400-e29b-41d4-a716-446655440000/assign/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# 請求內容 (payload)
data = {
    "assignee": "550e8400-e29b-41d4-a716-446655440000",
    "transferReason": "範例字串",
    "tagIds": [
        "550e8400-e29b-41d4-a716-446655440000"
    ]
}

response = requests.patch(url, json=data, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>patch("https://api.maiagent.ai/api/v1/conversations/550e8400-e29b-41d4-a716-
446655440000/assign/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'assignee' => '550e8400-e29b-41d4-a716-446655440000',
            'transferReason' => '範例字串',
            'tagIds' => [
                '550e8400-e29b-41d4-a716-446655440000'
            ]
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
{
  "id": string (uuid)
  "contact": { // 輕量級 Contact Serializer，用於 Conversation List view

只包含 List view 必要的欄位，移除 inboxes、mcp_credentials 和 api_credentials
以避免 N+1 查詢問題。email / phone_number / metadata 為 Contact 自身的純量欄位，
前端對話側欄需要顯示，無 N+1 成本。
  {
    "id": string (uuid)
    "name": string
    "avatar"?: string // Stores our own media as a relative storage key, or an
external CDN URL as-is. (非必填)
    "email"?: // 可能有不同的類型 (非必填)
    string (email) // 非必填
    "phoneNumber"?: string // 非必填
    "metadata"?: object // Custom customer information shown in the customer panel
of the conversation page (非必填)
    "sourceId"?: string // 非必填
    "tags": [
      {
        "id": string (uuid)
        "name": string
      }
    ]
  }
  }
  "inbox": { // Inbox summary embedded in a conversation payload.

``unread_conversations_count`` stays here because it is part of the
documented REST conversation API. It is an org-wide denormalized
counter, so WS emit paths must run the payload through
:func:`strip_org_wide_unread_count` before broadcasting it to rooms
that include members without ``GroupInbox.can_view_conversations``.
  {
    "id": string (uuid)
    "name": string
    "channelType": string (enum: line, telegram, teams, web, messenger, instagram,
email, whatsapp, slack, team_plus, line_works, viber) // * `line` - LINE
* `telegram` - Telegram
* `teams` - Teams
* `web` - Web
* `messenger` - Messenger
* `instagram` - Instagram
* `email` - Email
* `whatsapp` - WhatsApp
* `slack` - Slack
* `team_plus` - Team+
* `line_works` - LINE WORKS
* `viber` - Viber
```

```
    "unreadConversationsCount"?: integer // 非必填
    "signAuth"?:  // 非必填
    {
      "id": string (uuid)
      "signSource": string (uuid)
      "signParams": {
      {
        "keycloak":
        {
          "clientId": string
          "url": string
          "realm": string
        }
        "line":
        {
          "liffId": string
        }
        "ad":
        {
          "saml": string
        }
        "google"?:  // 非必填
        {
          "enabled": boolean
        }
      }
      }
      "sourceIdAccessEnabled"?: boolean // When enabled, embedded visitors
presenting a Source ID (verified per the verify mode below) may chat without going
through the login flow. Disabled keeps every existing behavior unchanged. (非必填)
      "sourceIdVerifyMode"?:  // "Require signature verification": the embedding
site must send an HMAC signature computed on its backend. "Source ID only": anyone
knowing a Source ID can act as that contact; suitable only for testing or closed
networks.

* `signature` - Require signature verification
* `raw` - Source ID only (非必填)
      {
      }
      "sourceIdSignatureTtlMinutes"?:  // How long a signature can be used to
obtain the contact identity. Not a session lifetime: once exchanged, the session
follows the existing WebChat mechanism.

* `1` - 1
* `5` - 5
* `15` - 15 (非必填)
      {
      }
      "keycloakTokenPassthrough"?: boolean // When enabled, the Keycloak access
token a visitor logged in with is forwarded as the Authorization header when the
```

```
AI calls MCP and API tools on their behalf, so tools do not require a separate
per-tool login. Only for the Keycloak sign source. Never overrides an
Authorization header a tool already resolves from its own credentials. The visitor
identity is the organization member bound to the conversation at login, never the
contact Source ID. (非必填)
      "keycloakTokenPassthroughAllowedHosts"?: [ // Hostnames (or "*.example.com"
wildcards) of the tools the visitor Keycloak token may be sent to (非必填)
        string
      ]
    }
    "enableAnalysis"?: boolean // 非必填
  }
  }
  "chatbot": object // Chatbot (Agent) summary from the conversation's inbox,
already eager-loaded.

``is_maigpt`` lets the client tell the default MaiGPT agent apart (icon, feature
gate) without comparing against the organization's ``maigpt_inbox`` id;
``file_workspace_mode`` is the effective P6 mode (MaiGPT, blueprint and the
organization's file-library switch already applied).
  "title": string
  "lastMessage"?: { // 非必填
  {
    "id": string (uuid)
    "type"?: string // 非必填
    "content"?: string // 非必填
    "createdAt": string (timestamp)
  }
  }
  "callRecord":
  {
    "id": string (uuid)
    "status"?: string (enum: initiated, ringing, in-progress, completed, failed,
busy, no-answer, canceled) // * `initiated` - Initiated
* `ringing` - Ringing
* `in-progress` - In Progress
* `completed` - Completed
* `failed` - Failed
* `busy` - Busy
* `no-answer` - No Answer
* `canceled` - Canceled (非必填)
    "direction": string (enum: inbound, outbound) // * `inbound` - Inbound
* `outbound` - Outbound
    "isActive": boolean
    "canHangup": boolean
  }
  "lastMessageCreatedAt": string (timestamp)
  "unreadMessagesCount": integer
  "autoReplyEnabled": boolean
  "isAutoReplyNow": boolean
```

```
  "willAiReplyNow": boolean // Whether a text message arriving through the inbox
gets an AI reply right now.

The messaging channels are gated by ``is_auto_reply_now`` (auto reply on and
inside the
inbox auto-reply schedule) and by the inbox having a chatbot. The chatbot's API
web chat
is answered by the completions endpoint, which ignores the schedule, so there the
conversation switch alone decides. The channel is only looked up for a web inbox
outside
its schedule.

Surfaces that ignore the schedule on any inbox answer from their own rule instead:
the
completions endpoint continuing an existing conversation
(``completions_progress_status``)
and voice turns, which the voice agent answers.
  "lastReadAt": string (timestamp)
  "createdAt": string (timestamp)
  "isGroupChat": boolean
  "enableGroupMention"?: boolean // 非必填
  "queryMetadata"?: { // 查詢元資料，控制可查詢的知識範圍；詳見各端點說明 (非必填)
  {
    "knowledgeBases"?: [ // 可查詢的知識庫清單；空陣列或 null＝全部不可查（無權限），未提供＝
不限制 (非必填)
      {
        "knowledgeBaseId": string (uuid) // 知識庫 ID
        "chatbotFileIds"?: [ // 檔案 ID 清單（依 hasUserSelectedAll 決定為排除或僅選
取） (非必填)
          string (uuid)
        ]
        "knowledgeBaseFileIds"?: [ // 檔案 ID 清單（chatbotFileIds 的新名稱；兩者皆提供
時以本欄位為準） (非必填)
          string (uuid)
        ]
        "faqIds"?: [ // FAQ ID 清單（依 hasUserSelectedAll 決定為排除或僅選取） (非必填)
          string (uuid)
        ]
        "hasUserSelectedAll"?: boolean // true＝選取知識庫全部內容並排除清單中的項目；
false＝僅選取清單中的項目 (非必填)
      }
    ]
    "labelRelations"?: { // 標籤過濾條件；conditions 為空陣列＝不做標籤過濾（並非無權限）。
必須與 knowledgeBases 一併提供—單獨提供時知識庫檢索不會套用標籤過濾（等同不限制） (非必填)
    {
      "operator": string (enum: AND, OR) // 標籤條件的組合方式
      "conditions"?: [ // 標籤條件清單，支援巢狀 operator/conditions 組合 (非必填)
        object
      ]
    }
```

```
    }
  }
  }
  "toolMask"?: object // Enabled/disabled state per tool: {tool_id: bool} (非必填)
  "connectorMask"?: object // Enabled/disabled state per connector: {connector_id:
bool} (非必填)
  "thinkingConfig"?: object // None = not set (inherit the chatbot setting);
otherwise {"reasoning_effort": <level>} (非必填)
  "thinkingConfigSchema": { // 此模型的思考設定表單；null 表示此模型沒有思考設定
  {
    "type"?: string // 表單類型，固定為 reasoning_effort (非必填)
    "fields"?: object // reasoning_effort 欄位：options 列出此模型接受的思考等級（由弱到
強），default 固定為 null (非必填)
    "canDisable"?: boolean // 此模型能否關閉思考；true 時 options 含 off (非必填)
    "unsetBehavior"?: string (enum: off, model_default) // 對話與助理都沒設思考等級時的
實際行為：off＝不思考（最快）；model_default＝模型自行思考，或平台預設等級會開啟思考 (非必填)
    "unsetLevel"?: string // 沒設等級時平台實際送出的等級；null 表示不送思考參數，交給模型自
身預設 (非必填)
  }
  }
  "effectiveThinkingConfig": object // The level the next reply sends on this
conversation's model, after gating and clamping.

The stored choice resolves conversation > chatbot > the LLM row's default level;
None means
the model sends no thinking parameter, so the provider default applies.
  "llm": string (uuid) // The model the next reply runs on: the conversation's
pin, else its assistant's current model.

TC-0205: returning the stored ``conversation.llm`` would show a model an unpinned
conversation no
longer uses once its assistant switches model, while ``thinking_config_schema``
already follows the
effective model. Read-only: displaying it never marks the conversation as
explicitly selected;
only the update-llm endpoint does.
  "deepResearchStatus":  // Status of deep research for this conversation

* `not_used` - Not Used
* `started` - Started
* `running` - Running
* `completed` - Completed
* `failed` - Failed
  {
  }
  "deepResearchOutputFormat": // 可能有不同的類型
  string (enum: canvas, chat, file) // Chosen delivery form for the finished
report. Set only when the user clicks a format in the pre-research choice card;
reset to NULL each time Deep Research is (re-)armed. NULL means no explicit choice
(or a plan-skipping request) and falls back to Canvas at render time, but stays
```

```
distinct from an explicit canvas pick so the frontend can lock the card only after
a real selection. To roll back to fixed-Canvas behavior, force this to NULL/canvas
— no redeploy needed.

* `canvas` - Canvas
* `chat` - Chat reply
* `file` - Downloadable file
  "ipAddress": string
  "ipCountryCode": string
  "ipRecordedAt": string (timestamp)
  "assignee":
  {
    "id": string (uuid)
    "name": string
    "userId": string (uuid)
  }
  "status"?: string (enum: open, resolved, queued) // * `open` - Open
* `resolved` - Resolved
* `queued` - Queued (非必填)
  "tags": [
    {
      "id": string (uuid)
      "name": string
      "memberIds"?: [ // 非必填
        string (uuid)
      ]
    }
  ]
  "progressStatus": string
  "firstResponseAt"?: string (timestamp) // 非必填
  "queuedAt"?: string (timestamp) // 非必填
  "assignedAt"?: string (timestamp) // 非必填
  "transferReason"?: string // 非必填
  "satisfactionScore": integer // Conversation satisfaction rating on a 5-point
scale (1=very dissatisfied, 5=very satisfied)
  "satisfactionComment": string
  "satisfactionSubmittedAt": string (timestamp)
  "latestAnalysisSummary": string // The conversation's current analysis summary
(its active summary revision).

Reads the `latest_analysis_summary` annotation added by `setup_eager_loading`
to avoid an N+1 query. All read paths (list / retrieve / create) eager-load,
so the annotation is present; it falls back to '' only for instances built
outside `setup_eager_loading`.
  "clientPlatform":  // Client platform that created this conversation (web,
desktop)

* `web` - Web
* `desktop` - Desktop
  {
```

```
  }
  "workingDirectory": string // Absolute path of the local folder bound to a
desktop conversation. Only set for desktop conversations; null for web
conversations.
  "slideProjectId": string
  "matchedField": string // Cached per instance: ``get_matched_message_id`` /
``get_matched_snippet``
both read this, so resolving it once avoids recomputing the keyword and
title-match logic three times per serialized conversation.
  "matchedSnippet": string // Keyword-centred excerpt of the matched message, with
ellipses.

Reads the ``matched_message_content`` annotation added by
``ConversationViewSet._annotate_keyword_match``; no extra query.
  "matchedMessageId": string
  "pinnedAt": string (timestamp) // When the conversation was pinned. Null means
unpinned.
  "folder": string (uuid) // The user-defined sidebar folder this conversation is
grouped into. Null means unclassified (shown under the time groups). Deleting the
folder resets this to null without deleting the conversation.
  "hasActiveBrowserSession": boolean // Whether a browser_use session snapshot
exists to resume.

Lets the frontend know it should proactively re-request the browser
panel (emit ``browser:start``) after a page reload, instead of only
ever showing the panel when a live ``browser:frame`` push happens to
arrive first.
  "callerOrganizationId": string // Bound caller organization (stamped at
conversation start); null when unbound
  "handoff": object // 交接資訊：enabled=平台開關；接續對話帶
source_conversation_id/source_title；被交接的原對話帶
continued_to_conversation_id/continued_to_title 與 latest_summary_message_id
  "displayContextUsage": boolean // 是否顯示上下文使用量百分比條（對話平台開關，MaiGPT 恆
為 true；與交接開關互相獨立）
}
```

回應範例值

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "contact": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應字串",
    "avatar": "回應字串",
    "email": "response@example.com",
    "phoneNumber": "回應字串",
    "metadata": null,
    "sourceId": "回應字串",
```

```
    "tags": [
      {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "name": "回應字串"
      }
    ]
  },
  "inbox": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應字串",
    "channelType": "line",
    "unreadConversationsCount": 456,
    "signAuth": {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "signSource": "550e8400-e29b-41d4-a716-446655440000",
      "signParams": {
        "keycloak": {
          "clientId": "回應字串",
          "url": "回應字串",
          "realm": "回應字串"
        },
        "line": {
          "liffId": "回應字串"
        },
        "ad": {
          "saml": "回應字串"
        },
        "google": {
          "enabled": false
        }
      },
      "sourceIdAccessEnabled": false,
      "sourceIdVerifyMode": {},
      "sourceIdSignatureTtlMinutes": {},
      "keycloakTokenPassthrough": false,
      "keycloakTokenPassthroughAllowedHosts": [
        "回應字串"
      ]
    },
    "enableAnalysis": false
  },
  "chatbot": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應範例名稱",
    "description": "回應範例描述"
  },
  "title": "回應字串",
  "lastMessage": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "type": "回應字串",
```

```
      "content": "回應字串",
      "createdAt": "回應字串"
    },
    "callRecord": {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "status": "initiated",
      "direction": "inbound",
      "isActive": false,
      "canHangup": false
    },
    "lastMessageCreatedAt": "回應字串",
    "unreadMessagesCount": 456,
    "autoReplyEnabled": false,
    "isAutoReplyNow": false,
    "willAiReplyNow": false,
    "lastReadAt": "回應字串",
    "createdAt": "回應字串",
    "isGroupChat": false,
    "enableGroupMention": false,
    "queryMetadata": {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "回應範例名稱",
      "description": "回應範例描述"
    },
    "toolMask": null,
    "connectorMask": null,
    "thinkingConfig": null,
    "thinkingConfigSchema": {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "回應範例名稱",
      "description": "回應範例描述"
    },
    "effectiveThinkingConfig": {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "回應範例名稱",
      "description": "回應範例描述"
    },
    "llm": "550e8400-e29b-41d4-a716-446655440000",
    "deepResearchStatus": {},
    "deepResearchOutputFormat": "canvas",
    "ipAddress": "回應字串",
    "ipCountryCode": "回應字串",
    "ipRecordedAt": "回應字串",
    "assignee": {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "回應字串",
      "userId": "550e8400-e29b-41d4-a716-446655440000"
    },
    "status": "open",
    "tags": [
```

```
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "回應字串",
      "memberIds": [
        "550e8400-e29b-41d4-a716-446655440000"
      ]
    }
  ],
  "progressStatus": "回應字串",
  "firstResponseAt": "回應字串",
  "queuedAt": "回應字串",
  "assignedAt": "回應字串",
  "transferReason": "回應字串",
  "satisfactionScore": 456,
  "satisfactionComment": "回應字串",
  "satisfactionSubmittedAt": "回應字串",
  "latestAnalysisSummary": "回應字串",
  "clientPlatform": {},
  "workingDirectory": "回應字串",
  "slideProjectId": "回應字串",
  "matchedField": "回應字串",
  "matchedSnippet": "回應字串",
  "matchedMessageId": "回應字串",
  "pinnedAt": "回應字串",
  "folder": "550e8400-e29b-41d4-a716-446655440000",
  "hasActiveBrowserSession": false,
  "callerOrganizationId": "回應字串",
  "handoff": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應範例名稱",
    "description": "回應範例描述"
  },
  "displayContextUsage": false
}
```


認領對話

`PATCH` `/api/v1/conversations/{id}/claim/`

以呼叫者本人為接手成員，效果同「指派對話」。

參數

參數名稱	必填	類型	說明
id	V	string	A UUID string identifying this Conversation.

請求內容

請求參數

欄位	類型	必填	說明
transferReason	string	否	
tagIds	array[string]	否	

請求結構範例

```
{
  "transferReason"?: string // 非必填
  "tagIds"?: [ // 非必填
    string (uuid)
  ]
}
```

請求範例值

```
{
  "transferReason": "範例字串",
  "tagIds": [
    "550e8400-e29b-41d4-a716-446655440000"
  ]
}
```

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X PATCH "https://api.maiagent.ai/api/v1/conversations/550e8400-e29b-
41d4-a716-446655440000/claim/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "transferReason": "範例字串",
    "tagIds": [
      "550e8400-e29b-41d4-a716-446655440000"
    ]
  }'

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// 請求內容 (payload)
const data = {
    "transferReason": "範例字串",
    "tagIds": [
      "550e8400-e29b-41d4-a716-446655440000"
    ]
  };

axios.patch("https://api.maiagent.ai/api/v1/conversations/550e8400-e29b-41d4-a716-446655440000/claim/", data, config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/conversations/550e8400-e29b-41d4-a716-446655440000/claim/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# 請求內容 (payload)
data = {
    "transferReason": "範例字串",
    "tagIds": [
        "550e8400-e29b-41d4-a716-446655440000"
    ]
}

response = requests.patch(url, json=data, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->patch("https://api.maiagent.ai/api/v1/conversations/550e8400-e29b-41d4-a716-446655440000/claim/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'transferReason' => '範例字串',
            'tagIds' => [
                '550e8400-e29b-41d4-a716-446655440000'
            ]
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
{
  "id": string (uuid)
  "contact": { // 輕量級 Contact Serializer，用於 Conversation List view

只包含 List view 必要的欄位，移除 inboxes、mcp_credentials 和 api_credentials
以避免 N+1 查詢問題。email / phone_number / metadata 為 Contact 自身的純量欄位，
前端對話側欄需要顯示，無 N+1 成本。
  {
    "id": string (uuid)
    "name": string
    "avatar"?: string // Stores our own media as a relative storage key, or an
external CDN URL as-is. (非必填)
    "email"?: // 可能有不同的類型 (非必填)
    string (email) // 非必填
    "phoneNumber"?: string // 非必填
    "metadata"?: object // Custom customer information shown in the customer panel
of the conversation page (非必填)
    "sourceId"?: string // 非必填
    "tags": [
      {
        "id": string (uuid)
        "name": string
      }
    ]
  }
  }
  "inbox": { // Inbox summary embedded in a conversation payload.

``unread_conversations_count`` stays here because it is part of the
documented REST conversation API. It is an org-wide denormalized
counter, so WS emit paths must run the payload through
:func:`strip_org_wide_unread_count` before broadcasting it to rooms
that include members without ``GroupInbox.can_view_conversations``.
  {
    "id": string (uuid)
    "name": string
    "channelType": string (enum: line, telegram, teams, web, messenger, instagram,
email, whatsapp, slack, team_plus, line_works, viber) // * `line` - LINE
* `telegram` - Telegram
* `teams` - Teams
* `web` - Web
* `messenger` - Messenger
* `instagram` - Instagram
* `email` - Email
* `whatsapp` - WhatsApp
* `slack` - Slack
* `team_plus` - Team+
* `line_works` - LINE WORKS
* `viber` - Viber
```

```
    "unreadConversationsCount"?: integer // 非必填
    "signAuth"?:  // 非必填
    {
      "id": string (uuid)
      "signSource": string (uuid)
      "signParams": {
      {
        "keycloak":
        {
          "clientId": string
          "url": string
          "realm": string
        }
        "line":
        {
          "liffId": string
        }
        "ad":
        {
          "saml": string
        }
        "google"?:  // 非必填
        {
          "enabled": boolean
        }
      }
      }
      "sourceIdAccessEnabled"?: boolean // When enabled, embedded visitors
presenting a Source ID (verified per the verify mode below) may chat without going
through the login flow. Disabled keeps every existing behavior unchanged. (非必填)
      "sourceIdVerifyMode"?:  // "Require signature verification": the embedding
site must send an HMAC signature computed on its backend. "Source ID only": anyone
knowing a Source ID can act as that contact; suitable only for testing or closed
networks.

* `signature` - Require signature verification
* `raw` - Source ID only (非必填)
      {
      }
      "sourceIdSignatureTtlMinutes"?:  // How long a signature can be used to
obtain the contact identity. Not a session lifetime: once exchanged, the session
follows the existing WebChat mechanism.

* `1` - 1
* `5` - 5
* `15` - 15 (非必填)
      {
      }
      "keycloakTokenPassthrough"?: boolean // When enabled, the Keycloak access
token a visitor logged in with is forwarded as the Authorization header when the
```

```
AI calls MCP and API tools on their behalf, so tools do not require a separate
per-tool login. Only for the Keycloak sign source. Never overrides an
Authorization header a tool already resolves from its own credentials. The visitor
identity is the organization member bound to the conversation at login, never the
contact Source ID. (非必填)
      "keycloakTokenPassthroughAllowedHosts"?: [ // Hostnames (or "*.example.com"
wildcards) of the tools the visitor Keycloak token may be sent to (非必填)
        string
      ]
    }
    "enableAnalysis"?: boolean // 非必填
  }
  }
  "chatbot": object // Chatbot (Agent) summary from the conversation's inbox,
already eager-loaded.

``is_maigpt`` lets the client tell the default MaiGPT agent apart (icon, feature
gate) without comparing against the organization's ``maigpt_inbox`` id;
``file_workspace_mode`` is the effective P6 mode (MaiGPT, blueprint and the
organization's file-library switch already applied).
  "title": string
  "lastMessage"?: { // 非必填
  {
    "id": string (uuid)
    "type"?: string // 非必填
    "content"?: string // 非必填
    "createdAt": string (timestamp)
  }
  }
  "callRecord":
  {
    "id": string (uuid)
    "status"?: string (enum: initiated, ringing, in-progress, completed, failed,
busy, no-answer, canceled) // * `initiated` - Initiated
* `ringing` - Ringing
* `in-progress` - In Progress
* `completed` - Completed
* `failed` - Failed
* `busy` - Busy
* `no-answer` - No Answer
* `canceled` - Canceled (非必填)
    "direction": string (enum: inbound, outbound) // * `inbound` - Inbound
* `outbound` - Outbound
    "isActive": boolean
    "canHangup": boolean
  }
  "lastMessageCreatedAt": string (timestamp)
  "unreadMessagesCount": integer
  "autoReplyEnabled": boolean
  "isAutoReplyNow": boolean
```

```
  "willAiReplyNow": boolean // Whether a text message arriving through the inbox
gets an AI reply right now.

The messaging channels are gated by ``is_auto_reply_now`` (auto reply on and
inside the
inbox auto-reply schedule) and by the inbox having a chatbot. The chatbot's API
web chat
is answered by the completions endpoint, which ignores the schedule, so there the
conversation switch alone decides. The channel is only looked up for a web inbox
outside
its schedule.

Surfaces that ignore the schedule on any inbox answer from their own rule instead:
the
completions endpoint continuing an existing conversation
(``completions_progress_status``)
and voice turns, which the voice agent answers.
  "lastReadAt": string (timestamp)
  "createdAt": string (timestamp)
  "isGroupChat": boolean
  "enableGroupMention"?: boolean // 非必填
  "queryMetadata"?: { // 查詢元資料，控制可查詢的知識範圍；詳見各端點說明 (非必填)
  {
    "knowledgeBases"?: [ // 可查詢的知識庫清單；空陣列或 null＝全部不可查（無權限），未提供＝
不限制 (非必填)
      {
        "knowledgeBaseId": string (uuid) // 知識庫 ID
        "chatbotFileIds"?: [ // 檔案 ID 清單（依 hasUserSelectedAll 決定為排除或僅選
取） (非必填)
          string (uuid)
        ]
        "knowledgeBaseFileIds"?: [ // 檔案 ID 清單（chatbotFileIds 的新名稱；兩者皆提供
時以本欄位為準） (非必填)
          string (uuid)
        ]
        "faqIds"?: [ // FAQ ID 清單（依 hasUserSelectedAll 決定為排除或僅選取） (非必填)
          string (uuid)
        ]
        "hasUserSelectedAll"?: boolean // true＝選取知識庫全部內容並排除清單中的項目；
false＝僅選取清單中的項目 (非必填)
      }
    ]
    "labelRelations"?: { // 標籤過濾條件；conditions 為空陣列＝不做標籤過濾（並非無權限）。
必須與 knowledgeBases 一併提供—單獨提供時知識庫檢索不會套用標籤過濾（等同不限制） (非必填)
    {
      "operator": string (enum: AND, OR) // 標籤條件的組合方式
      "conditions"?: [ // 標籤條件清單，支援巢狀 operator/conditions 組合 (非必填)
        object
      ]
    }
```

```
    }
  }
  }
  "toolMask"?: object // Enabled/disabled state per tool: {tool_id: bool} (非必填)
  "connectorMask"?: object // Enabled/disabled state per connector: {connector_id:
bool} (非必填)
  "thinkingConfig"?: object // None = not set (inherit the chatbot setting);
otherwise {"reasoning_effort": <level>} (非必填)
  "thinkingConfigSchema": { // 此模型的思考設定表單；null 表示此模型沒有思考設定
  {
    "type"?: string // 表單類型，固定為 reasoning_effort (非必填)
    "fields"?: object // reasoning_effort 欄位：options 列出此模型接受的思考等級（由弱到
強），default 固定為 null (非必填)
    "canDisable"?: boolean // 此模型能否關閉思考；true 時 options 含 off (非必填)
    "unsetBehavior"?: string (enum: off, model_default) // 對話與助理都沒設思考等級時的
實際行為：off＝不思考（最快）；model_default＝模型自行思考，或平台預設等級會開啟思考 (非必填)
    "unsetLevel"?: string // 沒設等級時平台實際送出的等級；null 表示不送思考參數，交給模型自
身預設 (非必填)
  }
  }
  "effectiveThinkingConfig": object // The level the next reply sends on this
conversation's model, after gating and clamping.

The stored choice resolves conversation > chatbot > the LLM row's default level;
None means
the model sends no thinking parameter, so the provider default applies.
  "llm": string (uuid) // The model the next reply runs on: the conversation's
pin, else its assistant's current model.

TC-0205: returning the stored ``conversation.llm`` would show a model an unpinned
conversation no
longer uses once its assistant switches model, while ``thinking_config_schema``
already follows the
effective model. Read-only: displaying it never marks the conversation as
explicitly selected;
only the update-llm endpoint does.
  "deepResearchStatus":  // Status of deep research for this conversation

* `not_used` - Not Used
* `started` - Started
* `running` - Running
* `completed` - Completed
* `failed` - Failed
  {
  }
  "deepResearchOutputFormat": // 可能有不同的類型
  string (enum: canvas, chat, file) // Chosen delivery form for the finished
report. Set only when the user clicks a format in the pre-research choice card;
reset to NULL each time Deep Research is (re-)armed. NULL means no explicit choice
(or a plan-skipping request) and falls back to Canvas at render time, but stays
```

```
distinct from an explicit canvas pick so the frontend can lock the card only after
a real selection. To roll back to fixed-Canvas behavior, force this to NULL/canvas
— no redeploy needed.

* `canvas` - Canvas
* `chat` - Chat reply
* `file` - Downloadable file
  "ipAddress": string
  "ipCountryCode": string
  "ipRecordedAt": string (timestamp)
  "assignee":
  {
    "id": string (uuid)
    "name": string
    "userId": string (uuid)
  }
  "status"?: string (enum: open, resolved, queued) // * `open` - Open
* `resolved` - Resolved
* `queued` - Queued (非必填)
  "tags": [
    {
      "id": string (uuid)
      "name": string
      "memberIds"?: [ // 非必填
        string (uuid)
      ]
    }
  ]
  "progressStatus": string
  "firstResponseAt"?: string (timestamp) // 非必填
  "queuedAt"?: string (timestamp) // 非必填
  "assignedAt"?: string (timestamp) // 非必填
  "transferReason"?: string // 非必填
  "satisfactionScore": integer // Conversation satisfaction rating on a 5-point
scale (1=very dissatisfied, 5=very satisfied)
  "satisfactionComment": string
  "satisfactionSubmittedAt": string (timestamp)
  "latestAnalysisSummary": string // The conversation's current analysis summary
(its active summary revision).

Reads the `latest_analysis_summary` annotation added by `setup_eager_loading`
to avoid an N+1 query. All read paths (list / retrieve / create) eager-load,
so the annotation is present; it falls back to '' only for instances built
outside `setup_eager_loading`.
  "clientPlatform":  // Client platform that created this conversation (web,
desktop)

* `web` - Web
* `desktop` - Desktop
  {
```

```
  }
  "workingDirectory": string // Absolute path of the local folder bound to a
desktop conversation. Only set for desktop conversations; null for web
conversations.
  "slideProjectId": string
  "matchedField": string // Cached per instance: ``get_matched_message_id`` /
``get_matched_snippet``
both read this, so resolving it once avoids recomputing the keyword and
title-match logic three times per serialized conversation.
  "matchedSnippet": string // Keyword-centred excerpt of the matched message, with
ellipses.

Reads the ``matched_message_content`` annotation added by
``ConversationViewSet._annotate_keyword_match``; no extra query.
  "matchedMessageId": string
  "pinnedAt": string (timestamp) // When the conversation was pinned. Null means
unpinned.
  "folder": string (uuid) // The user-defined sidebar folder this conversation is
grouped into. Null means unclassified (shown under the time groups). Deleting the
folder resets this to null without deleting the conversation.
  "hasActiveBrowserSession": boolean // Whether a browser_use session snapshot
exists to resume.

Lets the frontend know it should proactively re-request the browser
panel (emit ``browser:start``) after a page reload, instead of only
ever showing the panel when a live ``browser:frame`` push happens to
arrive first.
  "callerOrganizationId": string // Bound caller organization (stamped at
conversation start); null when unbound
  "handoff": object // 交接資訊：enabled=平台開關；接續對話帶
source_conversation_id/source_title；被交接的原對話帶
continued_to_conversation_id/continued_to_title 與 latest_summary_message_id
  "displayContextUsage": boolean // 是否顯示上下文使用量百分比條（對話平台開關，MaiGPT 恆
為 true；與交接開關互相獨立）
}
```

回應範例值

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "contact": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應字串",
    "avatar": "回應字串",
    "email": "response@example.com",
    "phoneNumber": "回應字串",
    "metadata": null,
    "sourceId": "回應字串",
```

```
    "tags": [
      {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "name": "回應字串"
      }
    ]
  },
  "inbox": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應字串",
    "channelType": "line",
    "unreadConversationsCount": 456,
    "signAuth": {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "signSource": "550e8400-e29b-41d4-a716-446655440000",
      "signParams": {
        "keycloak": {
          "clientId": "回應字串",
          "url": "回應字串",
          "realm": "回應字串"
        },
        "line": {
          "liffId": "回應字串"
        },
        "ad": {
          "saml": "回應字串"
        },
        "google": {
          "enabled": false
        }
      },
      "sourceIdAccessEnabled": false,
      "sourceIdVerifyMode": {},
      "sourceIdSignatureTtlMinutes": {},
      "keycloakTokenPassthrough": false,
      "keycloakTokenPassthroughAllowedHosts": [
        "回應字串"
      ]
    },
    "enableAnalysis": false
  },
  "chatbot": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應範例名稱",
    "description": "回應範例描述"
  },
  "title": "回應字串",
  "lastMessage": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "type": "回應字串",
```

```
      "content": "回應字串",
      "createdAt": "回應字串"
    },
    "callRecord": {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "status": "initiated",
      "direction": "inbound",
      "isActive": false,
      "canHangup": false
    },
    "lastMessageCreatedAt": "回應字串",
    "unreadMessagesCount": 456,
    "autoReplyEnabled": false,
    "isAutoReplyNow": false,
    "willAiReplyNow": false,
    "lastReadAt": "回應字串",
    "createdAt": "回應字串",
    "isGroupChat": false,
    "enableGroupMention": false,
    "queryMetadata": {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "回應範例名稱",
      "description": "回應範例描述"
    },
    "toolMask": null,
    "connectorMask": null,
    "thinkingConfig": null,
    "thinkingConfigSchema": {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "回應範例名稱",
      "description": "回應範例描述"
    },
    "effectiveThinkingConfig": {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "回應範例名稱",
      "description": "回應範例描述"
    },
    "llm": "550e8400-e29b-41d4-a716-446655440000",
    "deepResearchStatus": {},
    "deepResearchOutputFormat": "canvas",
    "ipAddress": "回應字串",
    "ipCountryCode": "回應字串",
    "ipRecordedAt": "回應字串",
    "assignee": {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "回應字串",
      "userId": "550e8400-e29b-41d4-a716-446655440000"
    },
    "status": "open",
    "tags": [
```

```
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "回應字串",
      "memberIds": [
        "550e8400-e29b-41d4-a716-446655440000"
      ]
    }
  ],
  "progressStatus": "回應字串",
  "firstResponseAt": "回應字串",
  "queuedAt": "回應字串",
  "assignedAt": "回應字串",
  "transferReason": "回應字串",
  "satisfactionScore": 456,
  "satisfactionComment": "回應字串",
  "satisfactionSubmittedAt": "回應字串",
  "latestAnalysisSummary": "回應字串",
  "clientPlatform": {},
  "workingDirectory": "回應字串",
  "slideProjectId": "回應字串",
  "matchedField": "回應字串",
  "matchedSnippet": "回應字串",
  "matchedMessageId": "回應字串",
  "pinnedAt": "回應字串",
  "folder": "550e8400-e29b-41d4-a716-446655440000",
  "hasActiveBrowserSession": false,
  "callerOrganizationId": "回應字串",
  "handoff": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應範例名稱",
    "description": "回應範例描述"
  },
  "displayContextUsage": false
}
```


轉接對話給其他成員

`PATCH` `/api/v1/conversations/{id}/transfer/`

參數

參數名稱	必填	類型	說明
id	V	string	A UUID string identifying this Conversation.

請求內容

請求參數

欄位	類型	必填	說明
assignee	string (uuid)	否	
transferReason	string	否	
tagIds	array[string]	否	

請求結構範例

```
{
  "assignee"?: string (uuid) // 非必填
  "transferReason"?: string // 非必填
  "tagIds"?: [ // 非必填
    string (uuid)
  ]
}
```

請求範例值

```
{
  "assignee": "550e8400-e29b-41d4-a716-446655440000",
  "transferReason": "範例字串",
  "tagIds": [
    "550e8400-e29b-41d4-a716-446655440000"
  ]
}
```

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X PATCH "https://api.maiagent.ai/api/v1/conversations/550e8400-e29b-
41d4-a716-446655440000/transfer/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "assignee": "550e8400-e29b-41d4-a716-446655440000",
    "transferReason": "範例字串",
    "tagIds": [
      "550e8400-e29b-41d4-a716-446655440000"
    ]
  }'

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// 請求內容 (payload)
const data = {
    "assignee": "550e8400-e29b-41d4-a716-446655440000",
    "transferReason": "範例字串",
    "tagIds": [
      "550e8400-e29b-41d4-a716-446655440000"
    ]
  };

axios.patch("https://api.maiagent.ai/api/v1/conversations/550e8400-e29b-41d4-
a716-446655440000/transfer/", data, config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/conversations/550e8400-e29b-41d4-a716-446655440000/transfer/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# 請求內容 (payload)
data = {
    "assignee": "550e8400-e29b-41d4-a716-446655440000",
    "transferReason": "範例字串",
    "tagIds": [
        "550e8400-e29b-41d4-a716-446655440000"
    ]
}

response = requests.patch(url, json=data, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>patch("https://api.maiagent.ai/api/v1/conversations/550e8400-e29b-41d4-a716-
446655440000/transfer/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'assignee' => '550e8400-e29b-41d4-a716-446655440000',
            'transferReason' => '範例字串',
            'tagIds' => [
                '550e8400-e29b-41d4-a716-446655440000'
            ]
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
{
  "id": string (uuid)
  "contact": { // 輕量級 Contact Serializer，用於 Conversation List view

只包含 List view 必要的欄位，移除 inboxes、mcp_credentials 和 api_credentials
以避免 N+1 查詢問題。email / phone_number / metadata 為 Contact 自身的純量欄位，
前端對話側欄需要顯示，無 N+1 成本。
  {
    "id": string (uuid)
    "name": string
    "avatar"?: string // Stores our own media as a relative storage key, or an
external CDN URL as-is. (非必填)
    "email"?: // 可能有不同的類型 (非必填)
    string (email) // 非必填
    "phoneNumber"?: string // 非必填
    "metadata"?: object // Custom customer information shown in the customer panel
of the conversation page (非必填)
    "sourceId"?: string // 非必填
    "tags": [
      {
        "id": string (uuid)
        "name": string
      }
    ]
  }
  }
  "inbox": { // Inbox summary embedded in a conversation payload.

``unread_conversations_count`` stays here because it is part of the
documented REST conversation API. It is an org-wide denormalized
counter, so WS emit paths must run the payload through
:func:`strip_org_wide_unread_count` before broadcasting it to rooms
that include members without ``GroupInbox.can_view_conversations``.
  {
    "id": string (uuid)
    "name": string
    "channelType": string (enum: line, telegram, teams, web, messenger, instagram,
email, whatsapp, slack, team_plus, line_works, viber) // * `line` - LINE
* `telegram` - Telegram
* `teams` - Teams
* `web` - Web
* `messenger` - Messenger
* `instagram` - Instagram
* `email` - Email
* `whatsapp` - WhatsApp
* `slack` - Slack
* `team_plus` - Team+
* `line_works` - LINE WORKS
* `viber` - Viber
```

```
    "unreadConversationsCount"?: integer // 非必填
    "signAuth"?:  // 非必填
    {
      "id": string (uuid)
      "signSource": string (uuid)
      "signParams": {
      {
        "keycloak":
        {
          "clientId": string
          "url": string
          "realm": string
        }
        "line":
        {
          "liffId": string
        }
        "ad":
        {
          "saml": string
        }
        "google"?:  // 非必填
        {
          "enabled": boolean
        }
      }
      }
      "sourceIdAccessEnabled"?: boolean // When enabled, embedded visitors
presenting a Source ID (verified per the verify mode below) may chat without going
through the login flow. Disabled keeps every existing behavior unchanged. (非必填)
      "sourceIdVerifyMode"?:  // "Require signature verification": the embedding
site must send an HMAC signature computed on its backend. "Source ID only": anyone
knowing a Source ID can act as that contact; suitable only for testing or closed
networks.

* `signature` - Require signature verification
* `raw` - Source ID only (非必填)
      {
      }
      "sourceIdSignatureTtlMinutes"?:  // How long a signature can be used to
obtain the contact identity. Not a session lifetime: once exchanged, the session
follows the existing WebChat mechanism.

* `1` - 1
* `5` - 5
* `15` - 15 (非必填)
      {
      }
      "keycloakTokenPassthrough"?: boolean // When enabled, the Keycloak access
token a visitor logged in with is forwarded as the Authorization header when the
```

```
AI calls MCP and API tools on their behalf, so tools do not require a separate
per-tool login. Only for the Keycloak sign source. Never overrides an
Authorization header a tool already resolves from its own credentials. The visitor
identity is the organization member bound to the conversation at login, never the
contact Source ID. (非必填)
      "keycloakTokenPassthroughAllowedHosts"?: [ // Hostnames (or "*.example.com"
wildcards) of the tools the visitor Keycloak token may be sent to (非必填)
        string
      ]
    }
    "enableAnalysis"?: boolean // 非必填
  }
  }
  "chatbot": object // Chatbot (Agent) summary from the conversation's inbox,
already eager-loaded.

``is_maigpt`` lets the client tell the default MaiGPT agent apart (icon, feature
gate) without comparing against the organization's ``maigpt_inbox`` id;
``file_workspace_mode`` is the effective P6 mode (MaiGPT, blueprint and the
organization's file-library switch already applied).
  "title": string
  "lastMessage"?: { // 非必填
  {
    "id": string (uuid)
    "type"?: string // 非必填
    "content"?: string // 非必填
    "createdAt": string (timestamp)
  }
  }
  "callRecord":
  {
    "id": string (uuid)
    "status"?: string (enum: initiated, ringing, in-progress, completed, failed,
busy, no-answer, canceled) // * `initiated` - Initiated
* `ringing` - Ringing
* `in-progress` - In Progress
* `completed` - Completed
* `failed` - Failed
* `busy` - Busy
* `no-answer` - No Answer
* `canceled` - Canceled (非必填)
    "direction": string (enum: inbound, outbound) // * `inbound` - Inbound
* `outbound` - Outbound
    "isActive": boolean
    "canHangup": boolean
  }
  "lastMessageCreatedAt": string (timestamp)
  "unreadMessagesCount": integer
  "autoReplyEnabled": boolean
  "isAutoReplyNow": boolean
```

```
  "willAiReplyNow": boolean // Whether a text message arriving through the inbox
gets an AI reply right now.

The messaging channels are gated by ``is_auto_reply_now`` (auto reply on and
inside the
inbox auto-reply schedule) and by the inbox having a chatbot. The chatbot's API
web chat
is answered by the completions endpoint, which ignores the schedule, so there the
conversation switch alone decides. The channel is only looked up for a web inbox
outside
its schedule.

Surfaces that ignore the schedule on any inbox answer from their own rule instead:
the
completions endpoint continuing an existing conversation
(``completions_progress_status``)
and voice turns, which the voice agent answers.
  "lastReadAt": string (timestamp)
  "createdAt": string (timestamp)
  "isGroupChat": boolean
  "enableGroupMention"?: boolean // 非必填
  "queryMetadata"?: { // 查詢元資料，控制可查詢的知識範圍；詳見各端點說明 (非必填)
  {
    "knowledgeBases"?: [ // 可查詢的知識庫清單；空陣列或 null＝全部不可查（無權限），未提供＝
不限制 (非必填)
      {
        "knowledgeBaseId": string (uuid) // 知識庫 ID
        "chatbotFileIds"?: [ // 檔案 ID 清單（依 hasUserSelectedAll 決定為排除或僅選
取） (非必填)
          string (uuid)
        ]
        "knowledgeBaseFileIds"?: [ // 檔案 ID 清單（chatbotFileIds 的新名稱；兩者皆提供
時以本欄位為準） (非必填)
          string (uuid)
        ]
        "faqIds"?: [ // FAQ ID 清單（依 hasUserSelectedAll 決定為排除或僅選取） (非必填)
          string (uuid)
        ]
        "hasUserSelectedAll"?: boolean // true＝選取知識庫全部內容並排除清單中的項目；
false＝僅選取清單中的項目 (非必填)
      }
    ]
    "labelRelations"?: { // 標籤過濾條件；conditions 為空陣列＝不做標籤過濾（並非無權限）。
必須與 knowledgeBases 一併提供—單獨提供時知識庫檢索不會套用標籤過濾（等同不限制） (非必填)
    {
      "operator": string (enum: AND, OR) // 標籤條件的組合方式
      "conditions"?: [ // 標籤條件清單，支援巢狀 operator/conditions 組合 (非必填)
        object
      ]
    }
```

```
    }
  }
  }
  "toolMask"?: object // Enabled/disabled state per tool: {tool_id: bool} (非必填)
  "connectorMask"?: object // Enabled/disabled state per connector: {connector_id:
bool} (非必填)
  "thinkingConfig"?: object // None = not set (inherit the chatbot setting);
otherwise {"reasoning_effort": <level>} (非必填)
  "thinkingConfigSchema": { // 此模型的思考設定表單；null 表示此模型沒有思考設定
  {
    "type"?: string // 表單類型，固定為 reasoning_effort (非必填)
    "fields"?: object // reasoning_effort 欄位：options 列出此模型接受的思考等級（由弱到
強），default 固定為 null (非必填)
    "canDisable"?: boolean // 此模型能否關閉思考；true 時 options 含 off (非必填)
    "unsetBehavior"?: string (enum: off, model_default) // 對話與助理都沒設思考等級時的
實際行為：off＝不思考（最快）；model_default＝模型自行思考，或平台預設等級會開啟思考 (非必填)
    "unsetLevel"?: string // 沒設等級時平台實際送出的等級；null 表示不送思考參數，交給模型自
身預設 (非必填)
  }
  }
  "effectiveThinkingConfig": object // The level the next reply sends on this
conversation's model, after gating and clamping.

The stored choice resolves conversation > chatbot > the LLM row's default level;
None means
the model sends no thinking parameter, so the provider default applies.
  "llm": string (uuid) // The model the next reply runs on: the conversation's
pin, else its assistant's current model.

TC-0205: returning the stored ``conversation.llm`` would show a model an unpinned
conversation no
longer uses once its assistant switches model, while ``thinking_config_schema``
already follows the
effective model. Read-only: displaying it never marks the conversation as
explicitly selected;
only the update-llm endpoint does.
  "deepResearchStatus":  // Status of deep research for this conversation

* `not_used` - Not Used
* `started` - Started
* `running` - Running
* `completed` - Completed
* `failed` - Failed
  {
  }
  "deepResearchOutputFormat": // 可能有不同的類型
  string (enum: canvas, chat, file) // Chosen delivery form for the finished
report. Set only when the user clicks a format in the pre-research choice card;
reset to NULL each time Deep Research is (re-)armed. NULL means no explicit choice
(or a plan-skipping request) and falls back to Canvas at render time, but stays
```

```
distinct from an explicit canvas pick so the frontend can lock the card only after
a real selection. To roll back to fixed-Canvas behavior, force this to NULL/canvas
— no redeploy needed.

* `canvas` - Canvas
* `chat` - Chat reply
* `file` - Downloadable file
  "ipAddress": string
  "ipCountryCode": string
  "ipRecordedAt": string (timestamp)
  "assignee":
  {
    "id": string (uuid)
    "name": string
    "userId": string (uuid)
  }
  "status"?: string (enum: open, resolved, queued) // * `open` - Open
* `resolved` - Resolved
* `queued` - Queued (非必填)
  "tags": [
    {
      "id": string (uuid)
      "name": string
      "memberIds"?: [ // 非必填
        string (uuid)
      ]
    }
  ]
  "progressStatus": string
  "firstResponseAt"?: string (timestamp) // 非必填
  "queuedAt"?: string (timestamp) // 非必填
  "assignedAt"?: string (timestamp) // 非必填
  "transferReason"?: string // 非必填
  "satisfactionScore": integer // Conversation satisfaction rating on a 5-point
scale (1=very dissatisfied, 5=very satisfied)
  "satisfactionComment": string
  "satisfactionSubmittedAt": string (timestamp)
  "latestAnalysisSummary": string // The conversation's current analysis summary
(its active summary revision).

Reads the `latest_analysis_summary` annotation added by `setup_eager_loading`
to avoid an N+1 query. All read paths (list / retrieve / create) eager-load,
so the annotation is present; it falls back to '' only for instances built
outside `setup_eager_loading`.
  "clientPlatform":  // Client platform that created this conversation (web,
desktop)

* `web` - Web
* `desktop` - Desktop
  {
```

```
  }
  "workingDirectory": string // Absolute path of the local folder bound to a
desktop conversation. Only set for desktop conversations; null for web
conversations.
  "slideProjectId": string
  "matchedField": string // Cached per instance: ``get_matched_message_id`` /
``get_matched_snippet``
both read this, so resolving it once avoids recomputing the keyword and
title-match logic three times per serialized conversation.
  "matchedSnippet": string // Keyword-centred excerpt of the matched message, with
ellipses.

Reads the ``matched_message_content`` annotation added by
``ConversationViewSet._annotate_keyword_match``; no extra query.
  "matchedMessageId": string
  "pinnedAt": string (timestamp) // When the conversation was pinned. Null means
unpinned.
  "folder": string (uuid) // The user-defined sidebar folder this conversation is
grouped into. Null means unclassified (shown under the time groups). Deleting the
folder resets this to null without deleting the conversation.
  "hasActiveBrowserSession": boolean // Whether a browser_use session snapshot
exists to resume.

Lets the frontend know it should proactively re-request the browser
panel (emit ``browser:start``) after a page reload, instead of only
ever showing the panel when a live ``browser:frame`` push happens to
arrive first.
  "callerOrganizationId": string // Bound caller organization (stamped at
conversation start); null when unbound
  "handoff": object // 交接資訊：enabled=平台開關；接續對話帶
source_conversation_id/source_title；被交接的原對話帶
continued_to_conversation_id/continued_to_title 與 latest_summary_message_id
  "displayContextUsage": boolean // 是否顯示上下文使用量百分比條（對話平台開關，MaiGPT 恆
為 true；與交接開關互相獨立）
}
```

回應範例值

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "contact": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應字串",
    "avatar": "回應字串",
    "email": "response@example.com",
    "phoneNumber": "回應字串",
    "metadata": null,
    "sourceId": "回應字串",
```

```
    "tags": [
      {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "name": "回應字串"
      }
    ]
  },
  "inbox": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應字串",
    "channelType": "line",
    "unreadConversationsCount": 456,
    "signAuth": {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "signSource": "550e8400-e29b-41d4-a716-446655440000",
      "signParams": {
        "keycloak": {
          "clientId": "回應字串",
          "url": "回應字串",
          "realm": "回應字串"
        },
        "line": {
          "liffId": "回應字串"
        },
        "ad": {
          "saml": "回應字串"
        },
        "google": {
          "enabled": false
        }
      },
      "sourceIdAccessEnabled": false,
      "sourceIdVerifyMode": {},
      "sourceIdSignatureTtlMinutes": {},
      "keycloakTokenPassthrough": false,
      "keycloakTokenPassthroughAllowedHosts": [
        "回應字串"
      ]
    },
    "enableAnalysis": false
  },
  "chatbot": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應範例名稱",
    "description": "回應範例描述"
  },
  "title": "回應字串",
  "lastMessage": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "type": "回應字串",
```

```
      "content": "回應字串",
      "createdAt": "回應字串"
    },
    "callRecord": {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "status": "initiated",
      "direction": "inbound",
      "isActive": false,
      "canHangup": false
    },
    "lastMessageCreatedAt": "回應字串",
    "unreadMessagesCount": 456,
    "autoReplyEnabled": false,
    "isAutoReplyNow": false,
    "willAiReplyNow": false,
    "lastReadAt": "回應字串",
    "createdAt": "回應字串",
    "isGroupChat": false,
    "enableGroupMention": false,
    "queryMetadata": {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "回應範例名稱",
      "description": "回應範例描述"
    },
    "toolMask": null,
    "connectorMask": null,
    "thinkingConfig": null,
    "thinkingConfigSchema": {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "回應範例名稱",
      "description": "回應範例描述"
    },
    "effectiveThinkingConfig": {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "回應範例名稱",
      "description": "回應範例描述"
    },
    "llm": "550e8400-e29b-41d4-a716-446655440000",
    "deepResearchStatus": {},
    "deepResearchOutputFormat": "canvas",
    "ipAddress": "回應字串",
    "ipCountryCode": "回應字串",
    "ipRecordedAt": "回應字串",
    "assignee": {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "回應字串",
      "userId": "550e8400-e29b-41d4-a716-446655440000"
    },
    "status": "open",
    "tags": [
```

```
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "回應字串",
      "memberIds": [
        "550e8400-e29b-41d4-a716-446655440000"
      ]
    }
  ],
  "progressStatus": "回應字串",
  "firstResponseAt": "回應字串",
  "queuedAt": "回應字串",
  "assignedAt": "回應字串",
  "transferReason": "回應字串",
  "satisfactionScore": 456,
  "satisfactionComment": "回應字串",
  "satisfactionSubmittedAt": "回應字串",
  "latestAnalysisSummary": "回應字串",
  "clientPlatform": {},
  "workingDirectory": "回應字串",
  "slideProjectId": "回應字串",
  "matchedField": "回應字串",
  "matchedSnippet": "回應字串",
  "matchedMessageId": "回應字串",
  "pinnedAt": "回應字串",
  "folder": "550e8400-e29b-41d4-a716-446655440000",
  "hasActiveBrowserSession": false,
  "callerOrganizationId": "回應字串",
  "handoff": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應範例名稱",
    "description": "回應範例描述"
  },
  "displayContextUsage": false
}
```


轉回 AI 回覆

`PATCH` `/api/v1/conversations/{id}/return-to-ai/`

清除接手成員並恢復 AI 自動回覆；完成後會送出 handoff.returned_to_ai Webhook 事件。

參數

參數名稱	必填	類型	說明
id	V	string	A UUID string identifying this Conversation.

請求內容

請求參數

欄位	類型	必填	說明
requireContextReady	boolean	否	

請求結構範例

```
{
  "requireContextReady"?: boolean // 非必填
}
```

請求範例值

```
{
  "requireContextReady": true
}
```

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X PATCH "https://api.maiagent.ai/api/v1/conversations/550e8400-e29b-
41d4-a716-446655440000/return-to-ai/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "requireContextReady": true
  }'

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// 請求內容 (payload)
const data = {
    "requireContextReady": true
  };

axios.patch("https://api.maiagent.ai/api/v1/conversations/550e8400-e29b-41d4-a716-446655440000/return-to-ai/", data, config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/conversations/550e8400-e29b-41d4-a716-446655440000/return-to-ai/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# 請求內容 (payload)
data = {
    "requireContextReady": True
}

response = requests.patch(url, json=data, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->patch("https://api.maiagent.ai/api/v1/conversations/550e8400-e29b-41d4-a716-446655440000/return-to-ai/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'requireContextReady' => true
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
{
  "id": string (uuid)
  "contact": { // 輕量級 Contact Serializer，用於 Conversation List view
```

```
只包含 List view 必要的欄位，移除 inboxes、mcp_credentials 和 api_credentials
以避免 N+1 查詢問題。email / phone_number / metadata 為 Contact 自身的純量欄位，
前端對話側欄需要顯示，無 N+1 成本。
  {
    "id": string (uuid)
    "name": string
    "avatar"?: string // Stores our own media as a relative storage key, or an
external CDN URL as-is. (非必填)
    "email"?: // 可能有不同的類型 (非必填)
    string (email) // 非必填
    "phoneNumber"?: string // 非必填
    "metadata"?: object // Custom customer information shown in the customer panel
of the conversation page (非必填)
    "sourceId"?: string // 非必填
    "tags": [
      {
        "id": string (uuid)
        "name": string
      }
    ]
  }
  }
  "inbox": { // Inbox summary embedded in a conversation payload.

``unread_conversations_count`` stays here because it is part of the
documented REST conversation API. It is an org-wide denormalized
counter, so WS emit paths must run the payload through
:func:`strip_org_wide_unread_count` before broadcasting it to rooms
that include members without ``GroupInbox.can_view_conversations``.
  {
    "id": string (uuid)
    "name": string
    "channelType": string (enum: line, telegram, teams, web, messenger, instagram,
email, whatsapp, slack, team_plus, line_works, viber) // * `line` - LINE
* `telegram` - Telegram
* `teams` - Teams
* `web` - Web
* `messenger` - Messenger
* `instagram` - Instagram
* `email` - Email
* `whatsapp` - WhatsApp
* `slack` - Slack
* `team_plus` - Team+
* `line_works` - LINE WORKS
* `viber` - Viber
    "unreadConversationsCount"?: integer // 非必填
    "signAuth"?:  // 非必填
    {
      "id": string (uuid)
      "signSource": string (uuid)
```

```
      "signParams": {
      {
        "keycloak":
        {
          "clientId": string
          "url": string
          "realm": string
        }
        "line":
        {
          "liffId": string
        }
        "ad":
        {
          "saml": string
        }
        "google"?:  // 非必填
        {
          "enabled": boolean
        }
      }
      }
      "sourceIdAccessEnabled"?: boolean // When enabled, embedded visitors presenting a Source ID (verified per the verify mode below) may chat without going through the login flow. Disabled keeps every existing behavior unchanged. (非必填)
      "sourceIdVerifyMode"?:  // "Require signature verification": the embedding site must send an HMAC signature computed on its backend. "Source ID only": anyone knowing a Source ID can act as that contact; suitable only for testing or closed networks.

* `signature` - Require signature verification
* `raw` - Source ID only (非必填)
      {
      }
      "sourceIdSignatureTtlMinutes"?:  // How long a signature can be used to obtain the contact identity. Not a session lifetime: once exchanged, the session follows the existing WebChat mechanism.

* `1` - 1
* `5` - 5
* `15` - 15 (非必填)
      {
      }
      "keycloakTokenPassthrough"?: boolean // When enabled, the Keycloak access token a visitor logged in with is forwarded as the Authorization header when the AI calls MCP and API tools on their behalf, so tools do not require a separate per-tool login. Only for the Keycloak sign source. Never overrides an Authorization header a tool already resolves from its own credentials. The visitor identity is the organization member bound to the conversation at login, never the contact Source ID. (非必填)
```

```
      "keycloakTokenPassthroughAllowedHosts"?: [ // Hostnames (or "*.example.com"
wildcards) of the tools the visitor Keycloak token may be sent to (非必填)
        string
      ]
    }
    "enableAnalysis"?: boolean // 非必填
  }
  }
  "chatbot": object // Chatbot (Agent) summary from the conversation's inbox,
already eager-loaded.

``is_maigpt`` lets the client tell the default MaiGPT agent apart (icon, feature
gate) without comparing against the organization's ``maigpt_inbox`` id;
``file_workspace_mode`` is the effective P6 mode (MaiGPT, blueprint and the
organization's file-library switch already applied).
  "title": string
  "lastMessage"?: { // 非必填
  {
    "id": string (uuid)
    "type"?: string // 非必填
    "content"?: string // 非必填
    "createdAt": string (timestamp)
  }
  }
  "callRecord":
  {
    "id": string (uuid)
    "status"?: string (enum: initiated, ringing, in-progress, completed, failed,
busy, no-answer, canceled) // * `initiated` - Initiated
* `ringing` - Ringing
* `in-progress` - In Progress
* `completed` - Completed
* `failed` - Failed
* `busy` - Busy
* `no-answer` - No Answer
* `canceled` - Canceled (非必填)
    "direction": string (enum: inbound, outbound) // * `inbound` - Inbound
* `outbound` - Outbound
    "isActive": boolean
    "canHangup": boolean
  }
  "lastMessageCreatedAt": string (timestamp)
  "unreadMessagesCount": integer
  "autoReplyEnabled": boolean
  "isAutoReplyNow": boolean
  "willAiReplyNow": boolean // Whether a text message arriving through the inbox
gets an AI reply right now.

The messaging channels are gated by ``is_auto_reply_now`` (auto reply on and
inside the
```

```
inbox auto-reply schedule) and by the inbox having a chatbot. The chatbot's API
web chat
is answered by the completions endpoint, which ignores the schedule, so there the
conversation switch alone decides. The channel is only looked up for a web inbox
outside
its schedule.

Surfaces that ignore the schedule on any inbox answer from their own rule instead:
the
completions endpoint continuing an existing conversation
(``completions_progress_status``)
and voice turns, which the voice agent answers.
  "lastReadAt": string (timestamp)
  "createdAt": string (timestamp)
  "isGroupChat": boolean
  "enableGroupMention"?: boolean // 非必填
  "queryMetadata"?: { // 查詢元資料，控制可查詢的知識範圍；詳見各端點說明 (非必填)
  {
    "knowledgeBases"?: [ // 可查詢的知識庫清單；空陣列或 null＝全部不可查（無權限），未提供＝
不限制 (非必填)
      {
        "knowledgeBaseId": string (uuid) // 知識庫 ID
        "chatbotFileIds"?: [ // 檔案 ID 清單（依 hasUserSelectedAll 決定為排除或僅選
取） (非必填)
          string (uuid)
        ]
        "knowledgeBaseFileIds"?: [ // 檔案 ID 清單（chatbotFileIds 的新名稱；兩者皆提供
時以本欄位為準） (非必填)
          string (uuid)
        ]
        "faqIds"?: [ // FAQ ID 清單（依 hasUserSelectedAll 決定為排除或僅選取） (非必填)
          string (uuid)
        ]
        "hasUserSelectedAll"?: boolean // true＝選取知識庫全部內容並排除清單中的項目；
false＝僅選取清單中的項目 (非必填)
      }
    ]
    "labelRelations"?: { // 標籤過濾條件；conditions 為空陣列＝不做標籤過濾（並非無權限）。
必須與 knowledgeBases 一併提供——單獨提供時知識庫檢索不會套用標籤過濾（等同不限制） (非必填)
    {
      "operator": string (enum: AND, OR) // 標籤條件的組合方式
      "conditions"?: [ // 標籤條件清單，支援巢狀 operator/conditions 組合 (非必填)
        object
      ]
    }
    }
  }
  }
  "toolMask"?: object // Enabled/disabled state per tool: {tool_id: bool} (非必填)
  "connectorMask"?: object // Enabled/disabled state per connector: {connector_id:
```

```
bool} (非必填)
  "thinkingConfig"?: object // None = not set (inherit the chatbot setting);
otherwise {"reasoning_effort": <level>} (非必填)
  "thinkingConfigSchema": { // 此模型的思考設定表單；null 表示此模型沒有思考設定
  {
    "type"?: string // 表單類型，固定為 reasoning_effort (非必填)
    "fields"?: object // reasoning_effort 欄位：options 列出此模型接受的思考等級（由弱到
強），default 固定為 null (非必填)
    "canDisable"?: boolean // 此模型能否關閉思考；true 時 options 含 off (非必填)
    "unsetBehavior"?: string (enum: off, model_default) // 對話與助理都沒設思考等級時的
實際行為：off＝不思考（最快）；model_default＝模型自行思考，或平台預設等級會開啟思考 (非必填)
    "unsetLevel"?: string // 沒設等級時平台實際送出的等級；null 表示不送思考參數，交給模型自
身預設 (非必填)
  }
  }
  "effectiveThinkingConfig": object // The level the next reply sends on this
conversation's model, after gating and clamping.

The stored choice resolves conversation > chatbot > the LLM row's default level;
None means
the model sends no thinking parameter, so the provider default applies.
  "llm": string (uuid) // The model the next reply runs on: the conversation's
pin, else its assistant's current model.

TC-0205: returning the stored ``conversation.llm`` would show a model an unpinned
conversation no
longer uses once its assistant switches model, while ``thinking_config_schema``
already follows the
effective model. Read-only: displaying it never marks the conversation as
explicitly selected;
only the update-llm endpoint does.
  "deepResearchStatus":  // Status of deep research for this conversation

* `not_used` - Not Used
* `started` - Started
* `running` - Running
* `completed` - Completed
* `failed` - Failed
  {
  }
  "deepResearchOutputFormat": // 可能有不同的類型
  string (enum: canvas, chat, file) // Chosen delivery form for the finished
report. Set only when the user clicks a format in the pre-research choice card;
reset to NULL each time Deep Research is (re-)armed. NULL means no explicit choice
(or a plan-skipping request) and falls back to Canvas at render time, but stays
distinct from an explicit canvas pick so the frontend can lock the card only after
a real selection. To roll back to fixed-Canvas behavior, force this to NULL/canvas
— no redeploy needed.

* `canvas` - Canvas
```

```
* `chat` - Chat reply
* `file` - Downloadable file
  "ipAddress": string
  "ipCountryCode": string
  "ipRecordedAt": string (timestamp)
  "assignee":
  {
    "id": string (uuid)
    "name": string
    "userId": string (uuid)
  }
  "status"?: string (enum: open, resolved, queued) // * `open` - Open
* `resolved` - Resolved
* `queued` - Queued (非必填)
  "tags": [
    {
      "id": string (uuid)
      "name": string
      "memberIds"?: [ // 非必填
        string (uuid)
      ]
    }
  ]
  "progressStatus": string
  "firstResponseAt"?: string (timestamp) // 非必填
  "queuedAt"?: string (timestamp) // 非必填
  "assignedAt"?: string (timestamp) // 非必填
  "transferReason"?: string // 非必填
  "satisfactionScore": integer // Conversation satisfaction rating on a 5-point
scale (1=very dissatisfied, 5=very satisfied)
  "satisfactionComment": string
  "satisfactionSubmittedAt": string (timestamp)
  "latestAnalysisSummary": string // The conversation's current analysis summary
(its active summary revision).

Reads the `latest_analysis_summary` annotation added by `setup_eager_loading`
to avoid an N+1 query. All read paths (list / retrieve / create) eager-load,
so the annotation is present; it falls back to '' only for instances built
outside `setup_eager_loading`.
  "clientPlatform":  // Client platform that created this conversation (web,
desktop)

* `web` - Web
* `desktop` - Desktop
  {
  }
  "workingDirectory": string // Absolute path of the local folder bound to a
desktop conversation. Only set for desktop conversations; null for web
conversations.
  "slideProjectId": string
```

```
  "matchedField": string // Cached per instance: ``get_matched_message_id`` /
``get_matched_snippet``
both read this, so resolving it once avoids recomputing the keyword and
title-match logic three times per serialized conversation.
  "matchedSnippet": string // Keyword-centred excerpt of the matched message, with
ellipses.

Reads the ``matched_message_content`` annotation added by
``ConversationViewSet._annotate_keyword_match``; no extra query.
  "matchedMessageId": string
  "pinnedAt": string (timestamp) // When the conversation was pinned. Null means
unpinned.
  "folder": string (uuid) // The user-defined sidebar folder this conversation is
grouped into. Null means unclassified (shown under the time groups). Deleting the
folder resets this to null without deleting the conversation.
  "hasActiveBrowserSession": boolean // Whether a browser_use session snapshot
exists to resume.

Lets the frontend know it should proactively re-request the browser
panel (emit ``browser:start``) after a page reload, instead of only
ever showing the panel when a live ``browser:frame`` push happens to
arrive first.
  "callerOrganizationId": string // Bound caller organization (stamped at
conversation start); null when unbound
  "handoff": object // 交接資訊：enabled=平台開關；接續對話帶
source_conversation_id/source_title；被交接的原對話帶
continued_to_conversation_id/continued_to_title 與 latest_summary_message_id
  "displayContextUsage": boolean // 是否顯示上下文使用量百分比條（對話平台開關，MaiGPT 恆
為 true；與交接開關互相獨立）
}
```

回應範例值

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "contact": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應字串",
    "avatar": "回應字串",
    "email": "response@example.com",
    "phoneNumber": "回應字串",
    "metadata": null,
    "sourceId": "回應字串",
    "tags": [
      {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "name": "回應字串"
      }
```

```
      ]
    },
    "inbox": {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "回應字串",
      "channelType": "line",
      "unreadConversationsCount": 456,
      "signAuth": {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "signSource": "550e8400-e29b-41d4-a716-446655440000",
        "signParams": {
          "keycloak": {
            "clientId": "回應字串",
            "url": "回應字串",
            "realm": "回應字串"
          },
          "line": {
            "liffId": "回應字串"
          },
          "ad": {
            "saml": "回應字串"
          },
          "google": {
            "enabled": false
          }
        },
        "sourceIdAccessEnabled": false,
        "sourceIdVerifyMode": {},
        "sourceIdSignatureTtlMinutes": {},
        "keycloakTokenPassthrough": false,
        "keycloakTokenPassthroughAllowedHosts": [
          "回應字串"
        ]
      },
      "enableAnalysis": false
    },
    "chatbot": {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "回應範例名稱",
      "description": "回應範例描述"
    },
    "title": "回應字串",
    "lastMessage": {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "type": "回應字串",
      "content": "回應字串",
      "createdAt": "回應字串"
    },
    "callRecord": {
      "id": "550e8400-e29b-41d4-a716-446655440000",
```

```
    "status": "initiated",
    "direction": "inbound",
    "isActive": false,
    "canHangup": false
  },
  "lastMessageCreatedAt": "回應字串",
  "unreadMessagesCount": 456,
  "autoReplyEnabled": false,
  "isAutoReplyNow": false,
  "willAiReplyNow": false,
  "lastReadAt": "回應字串",
  "createdAt": "回應字串",
  "isGroupChat": false,
  "enableGroupMention": false,
  "queryMetadata": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應範例名稱",
    "description": "回應範例描述"
  },
  "toolMask": null,
  "connectorMask": null,
  "thinkingConfig": null,
  "thinkingConfigSchema": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應範例名稱",
    "description": "回應範例描述"
  },
  "effectiveThinkingConfig": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應範例名稱",
    "description": "回應範例描述"
  },
  "llm": "550e8400-e29b-41d4-a716-446655440000",
  "deepResearchStatus": {},
  "deepResearchOutputFormat": "canvas",
  "ipAddress": "回應字串",
  "ipCountryCode": "回應字串",
  "ipRecordedAt": "回應字串",
  "assignee": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應字串",
    "userId": "550e8400-e29b-41d4-a716-446655440000"
  },
  "status": "open",
  "tags": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "回應字串",
      "memberIds": [
        "550e8400-e29b-41d4-a716-446655440000"
```

```
      ]
    }
  ],
  "progressStatus": "回應字串",
  "firstResponseAt": "回應字串",
  "queuedAt": "回應字串",
  "assignedAt": "回應字串",
  "transferReason": "回應字串",
  "satisfactionScore": 456,
  "satisfactionComment": "回應字串",
  "satisfactionSubmittedAt": "回應字串",
  "latestAnalysisSummary": "回應字串",
  "clientPlatform": {},
  "workingDirectory": "回應字串",
  "slideProjectId": "回應字串",
  "matchedField": "回應字串",
  "matchedSnippet": "回應字串",
  "matchedMessageId": "回應字串",
  "pinnedAt": "回應字串",
  "folder": "550e8400-e29b-41d4-a716-446655440000",
  "hasActiveBrowserSession": false,
  "callerOrganizationId": "回應字串",
  "handoff": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應範例名稱",
    "description": "回應範例描述"
  },
  "displayContextUsage": false
}
```


狀態碼: 409 - Agent context not ready: `detail` plus `agentContext` (pending failed writes)

列出對話產出檔案

`GET` `/api/v1/conversations/{conversationId}/outputs/`

回應欄位（count、source、results[]）、可見範圍與排序見技術手冊對話產出清單 API。

參數

參數名稱	必填	類型	說明
conversationId	V	string	

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X GET
"https://api.maiagent.ai/api/v1/conversations/{conversationId}/outputs/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/conversations/{conversationId}/outputs/", config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url =
"https://api.maiagent.ai/api/v1/conversations/{conversationId}/outputs/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/conversations/{conversationId}/outputs/"
, [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼	說明
200	No response body

分享對話

POST `/api/v1/conversations/{conversationPk}/share/`

參數

參數名稱	必填	類型	說明
`conversationPk`	V	string	

請求內容

請求參數

欄位	類型	必填	說明
shareScope	string (enum: organization, group, member)	是	`organization` : Organization ; `group` : Group ; `member` : Member;
permission	object	否	
title	string	否	
description	string	否	
groupIds	array[string]	否	
memberIds	array[string]	否	

請求結構範例

```
{
  "shareScope": string (enum: organization, group, member) // * `organization` -
Organization
* `group` - Group
* `member` - Member
  "permission"?:  // 非必填
  {
  }
  "title"?: string // 非必填
  "description"?: string // 非必填
  "groupIds"?: [ // 非必填
    string (uuid)
  ]
  "memberIds"?: [ // 非必填
    string (uuid)
```

```
  ]
}
```

請求範例值

```
{
  "shareScope": "organization",
  "permission": {},
  "title": "範例名稱",
  "description": "範例字串",
  "groupIds": [
    "550e8400-e29b-41d4-a716-446655440000"
  ],
  "memberIds": [
    "550e8400-e29b-41d4-a716-446655440000"
  ]
}
```

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X POST
"https://api.maiagent.ai/api/v1/conversations/{conversationPk}/share/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "shareScope": "organization",
    "permission": {},
    "title": "範例名稱",
    "description": "範例字串",
    "groupIds": [
      "550e8400-e29b-41d4-a716-446655440000"
    ],
    "memberIds": [
      "550e8400-e29b-41d4-a716-446655440000"
    ]
  }'

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// 請求內容 (payload)
const data = {
    "shareScope": "organization",
    "permission": {},
    "title": "範例名稱",
    "description": "範例字串",
    "groupIds": [
      "550e8400-e29b-41d4-a716-446655440000"
    ],
    "memberIds": [
      "550e8400-e29b-41d4-a716-446655440000"
    ]
  };

axios.post("https://api.maiagent.ai/api/v1/conversations/{conversationPk}/sha
re/", data, config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/conversations/{conversationPk}/share/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# 請求內容 (payload)
data = {
    "shareScope": "organization",
    "permission": {},
    "title": "範例名稱",
    "description": "範例字串",
    "groupIds": [
        "550e8400-e29b-41d4-a716-446655440000"
    ],
    "memberIds": [
        "550e8400-e29b-41d4-a716-446655440000"
    ]
}

response = requests.post(url, json=data, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>post("https://api.maiagent.ai/api/v1/conversations/{conversationPk}/share/",
[
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'shareScope' => 'organization',
            'permission' => new \stdClass(),
            'title' => '範例名稱',
            'description' => '範例字串',
            'groupIds' => [
                '550e8400-e29b-41d4-a716-446655440000'
            ],
            'memberIds' => [
                '550e8400-e29b-41d4-a716-446655440000'
            ]
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 201

回應結構範例

```
{
  "shareScope": string (enum: organization, group, member) // * `organization` -
Organization
* `group` - Group
* `member` - Member
  "permission"?:  // 非必填
  {
  }
  "title"?: string // 非必填
  "description"?: string // 非必填
  "groupIds"?: [ // 非必填
    string (uuid)
  ]
  "memberIds"?: [ // 非必填
    string (uuid)
  ]
}
```

回應範例值

```
{
  "shareScope": "organization",
  "permission": {},
  "title": "回應字串",
  "description": "回應字串",
  "groupIds": [
    "550e8400-e29b-41d4-a716-446655440000"
  ],
  "memberIds": [
    "550e8400-e29b-41d4-a716-446655440000"
  ]
}
```

快速分享對話

POST `/api/v1/conversations/{conversationPk}/share/quick/`

參數

參數名稱	必填	類型	說明
`conversationPk`	V	string	

請求內容

請求參數

欄位	類型	必填	說明
shareScope	string (enum: organization, group, member)	是	`organization` : Organization ; `group` : Group ; `member` : Member;
permission	object	否	
title	string	否	
description	string	否	
groupIds	array[string]	否	
memberIds	array[string]	否	

請求結構範例

```
{
  "shareScope": string (enum: organization, group, member) // * `organization` -
Organization
* `group` - Group
* `member` - Member
  "permission"?:  // 非必填
  {
  }
  "title"?: string // 非必填
  "description"?: string // 非必填
  "groupIds"?: [ // 非必填
    string (uuid)
  ]
  "memberIds"?: [ // 非必填
    string (uuid)
```

```
  ]
}
```

請求範例值

```
{
  "shareScope": "organization",
  "permission": {},
  "title": "範例名稱",
  "description": "範例字串",
  "groupIds": [
    "550e8400-e29b-41d4-a716-446655440000"
  ],
  "memberIds": [
    "550e8400-e29b-41d4-a716-446655440000"
  ]
}
```

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X POST
"https://api.maiagent.ai/api/v1/conversations/{conversationPk}/share/quick/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "shareScope": "organization",
    "permission": {},
    "title": "範例名稱",
    "description": "範例字串",
    "groupIds": [
      "550e8400-e29b-41d4-a716-446655440000"
    ],
    "memberIds": [
      "550e8400-e29b-41d4-a716-446655440000"
    ]
  }'

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// 請求內容 (payload)
const data = {
    "shareScope": "organization",
    "permission": {},
    "title": "範例名稱",
    "description": "範例字串",
    "groupIds": [
      "550e8400-e29b-41d4-a716-446655440000"
    ],
    "memberIds": [
      "550e8400-e29b-41d4-a716-446655440000"
    ]
  };

axios.post("https://api.maiagent.ai/api/v1/conversations/{conversationPk}/sha
re/quick/", data, config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url =
"https://api.maiagent.ai/api/v1/conversations/{conversationPk}/share/quick/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# 請求內容 (payload)
data = {
    "shareScope": "organization",
    "permission": {},
    "title": "範例名稱",
    "description": "範例字串",
    "groupIds": [
        "550e8400-e29b-41d4-a716-446655440000"
    ],
    "memberIds": [
        "550e8400-e29b-41d4-a716-446655440000"
    ]
}

response = requests.post(url, json=data, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->post("https://api.maiagent.ai/api/v1/conversations/{conversationPk}/share/quick/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'shareScope' => 'organization',
            'permission' => new \stdClass(),
            'title' => '範例名稱',
            'description' => '範例字串',
            'groupIds' => [
                '550e8400-e29b-41d4-a716-446655440000'
            ],
            'memberIds' => [
                '550e8400-e29b-41d4-a716-446655440000'
            ]
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
{
  "shareScope": string (enum: organization, group, member) // * `organization` -
Organization
* `group` - Group
* `member` - Member
  "permission"?:  // 非必填
  {
  }
  "title"?: string // 非必填
  "description"?: string // 非必填
  "groupIds"?: [ // 非必填
    string (uuid)
  ]
  "memberIds"?: [ // 非必填
    string (uuid)
  ]
}
```

回應範例值

```
{
  "shareScope": "organization",
  "permission": {},
  "title": "回應字串",
  "description": "回應字串",
  "groupIds": [
    "550e8400-e29b-41d4-a716-446655440000"
  ],
  "memberIds": [
    "550e8400-e29b-41d4-a716-446655440000"
  ]
}
```

列出分享的對話

GET `/api/v1/shared-conversations/`

參數

參數名稱	必填	類型	說明
`page`	X	integer	A page number within the paginated result set.
`pageSize`	X	integer	Number of results to return per page.

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/shared-conversations/?
page=1&pageSize=1"

  -H "Authorization: Api-Key YOUR_API_KEY"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/shared-conversations/?
page=1&pageSize=1", config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/shared-conversations/?
page=1&pageSize=1"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->get("https://api.maiagent.ai/api/v1/shared-
conversations/?page=1&pageSize=1", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
{
  "count": integer
  "next"?: string (uri) // 非必填
  "previous"?: string (uri) // 非必填
  "results": [
    {
      "id": string (uuid)
      "title": string // Custom title for the shared conversation
      "description": string // Custom description for the shared conversation
```

```
      "shareScope":
      {
      }
      "permission":
      {
      }
      "sharedBy":
      {
        "id": string (uuid)
        "name": string
      }
      "messageCount": integer // Count what the detail view shows; the view passes
``suggestion_ids`` for the whole page in one query.
      "createdAt": string (timestamp)
    }
  ]
}
```

回應範例值

```
{
  "count": 123,
  "next": "http://api.example.org/accounts/?page=4",
  "previous": "http://api.example.org/accounts/?page=2",
  "results": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "title": "回應字串",
      "description": "回應字串",
      "shareScope": {},
      "permission": {},
      "sharedBy": {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "name": "回應字串"
      },
      "messageCount": 456,
      "createdAt": "回應字串"
    }
  ]
}
```

取得特定分享對話

GET `/api/v1/shared-conversations/{id}`

參數

參數名稱	必填	類型	說明
`id`	V	string	A UUID string identifying this Shared Conversation.

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/shared-conversations/550e8400-
e29b-41d4-a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/shared-conversations/550e8400-e29b-41d4-a716-446655440000/", config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/shared-conversations/550e8400-e29b-41d4-a716-446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->get("https://api.maiagent.ai/api/v1/shared-
conversations/550e8400-e29b-41d4-a716-446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
{
  "id": string (uuid)
  "title": string // Custom title for the shared conversation
  "description": string // Custom description for the shared conversation
  "permission":
  {
  }
  "sharedBy":
  {
```

```
    "id": string (uuid)
    "name": string
  }
  "createdAt": string (timestamp)
  "conversationSnapshot": object // Frozen conversation snapshot: {title,
messages[]}
}
```

回應範例值

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "title": "回應字串",
  "description": "回應字串",
  "permission": {},
  "sharedBy": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應字串"
  },
  "createdAt": "回應字串",
  "conversationSnapshot": null
}
```

更新分享對話

PATCH `/api/v1/shared-conversations/{id}`

參數

參數名稱	必填	類型	說明
id	V	string	A UUID string identifying this Shared Conversation.

請求內容

請求參數

欄位	類型	必填	說明
title	string	否	
description	string	否	
permission	string (enum: readonly, copy)	否	`readonly` : Read Only ; `copy` : Copyable;

請求結構範例

```
{
  "title"?: string // 非必填
  "description"?: string // 非必填
  "permission"?: string (enum: readonly, copy) // * `readonly` - Read Only
* `copy` - Copyable (非必填)
}
```

請求範例值

```
{
  "title": "範例名稱",
  "description": "範例字串",
  "permission": "readonly"
}
```

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X PATCH "https://api.maiagent.ai/api/v1/shared-conversations/550e8400-
e29b-41d4-a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "title": "範例名稱",
    "description": "範例字串",
    "permission": "readonly"
  }'

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// 請求內容 (payload)
const data = {
    "title": "範例名稱",
    "description": "範例字串",
    "permission": "readonly"
  };

axios.patch("https://api.maiagent.ai/api/v1/shared-conversations/550e8400-
e29b-41d4-a716-446655440000/", data, config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/shared-conversations/550e8400-e29b-
41d4-a716-446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# 請求內容 (payload)
data = {
    "title": "範例名稱",
    "description": "範例字串",
    "permission": "readonly"
}

response = requests.patch(url, json=data, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->patch("https://api.maiagent.ai/api/v1/shared-
conversations/550e8400-e29b-41d4-a716-446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'title' => '範例名稱',
            'description' => '範例字串',
            'permission' => 'readonly'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
{
  "title"?: string // 非必填
  "description"?: string // 非必填
```

```
  "permission"?: string (enum: readonly, copy) // * `readonly` - Read Only
* `copy` - Copyable (非必填)
}
```

回應範例值

```
{
  "title": "回應字串",
  "description": "回應字串",
  "permission": "readonly"
}
```

刪除分享對話

DELETE `/api/v1/shared-conversations/{id}`

參數

參數名稱	必填	類型	說明
id	V	string	A UUID string identifying this Shared Conversation.

程式碼範例

Shell/Bash

```shell
# 呼叫 API 示例 (Shell)
curl -X DELETE "https://api.maiagent.ai/api/v1/shared-conversations/550e8400-e29b-41d4-a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```javascript
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

// 請求內容 (payload)
const data = null;

axios.delete("https://api.maiagent.ai/api/v1/shared-conversations/550e8400-e29b-41d4-a716-446655440000/", data, config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/shared-conversations/550e8400-e29b-41d4-a716-446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.delete(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->delete("https://api.maiagent.ai/api/v1/shared-conversations/550e8400-e29b-41d4-a716-446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼	說明
204	No response body

複製分享對話

POST `/api/v1/shared-conversations/{id}/fork/`

參數

參數名稱	必填	類型	說明
id	V	string	A UUID string identifying this Shared Conversation.

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X POST "https://api.maiagent.ai/api/v1/shared-conversations/550e8400-e29b-41d4-a716-446655440000/fork/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{}'

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// 請求內容 (payload)
const data = {};

axios.post("https://api.maiagent.ai/api/v1/shared-conversations/550e8400-
e29b-41d4-a716-446655440000/fork/", data, config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/shared-conversations/550e8400-e29b-
41d4-a716-446655440000/fork/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# 請求內容 (payload)
data = {}

response = requests.post(url, json=data, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->post("https://api.maiagent.ai/api/v1/shared-
conversations/550e8400-e29b-41d4-a716-446655440000/fork/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => new \stdClass()
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
{
  "id": string (uuid)
  "title": string // Custom title for the shared conversation
  "description": string // Custom description for the shared conversation
  "permission":
  {
  }
```

```
  "sharedBy":
  {
    "id": string (uuid)
    "name": string
  }
  "createdAt": string (timestamp)
  "conversationSnapshot": object // Frozen conversation snapshot: {title,
messages[]}
}
```

回應範例值

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "title": "回應字串",
  "description": "回應字串",
  "permission": {},
  "sharedBy": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應字串"
  },
  "createdAt": "回應字串",
  "conversationSnapshot": null
}
```

取得我的分享列表

GET `/api/v1/shared-conversations/my-shares/`

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/shared-conversations/my-shares/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/shared-conversations/my-shares/",
config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/shared-conversations/my-shares/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->get("https://api.maiagent.ai/api/v1/shared-
conversations/my-shares/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
{
  "id": string (uuid)
  "title": string // Custom title for the shared conversation
  "description": string // Custom description for the shared conversation
  "shareScope":
  {
  }
  "permission":
  {
```

```
  }
  "sharedBy":
  {
    "id": string (uuid)
    "name": string
  }
  "messageCount": integer // Count what the detail view shows; the view passes
``suggestion_ids`` for the whole page in one query.
  "createdAt": string (timestamp)
}
```

回應範例值

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "title": "回應字串",
  "description": "回應字串",
  "shareScope": {},
  "permission": {},
  "sharedBy": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應字串"
  },
  "messageCount": 456,
  "createdAt": "回應字串"
}
```

建立訊息回饋

POST `/api/v1/messages/{messagePk}/feedback/`

參數

參數名稱	必填	類型	說明
messagePk	V	string	

請求內容

請求參數

欄位	類型	必填	說明
type	object	是	
suggestion	string	否	

請求結構範例

```
{
  "type":
  {
  }
  "suggestion"?: string // 非必填
}
```

請求範例值

```
{
  "type": {},
  "suggestion": "範例字串"
}
```

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X POST "https://api.maiagent.ai/api/v1/messages/{messagePk}/feedback/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "type": {},
    "suggestion": "範例字串"
  }'

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// 請求內容 (payload)
const data = {
    "type": {},
    "suggestion": "範例字串"
  };

axios.post("https://api.maiagent.ai/api/v1/messages/{messagePk}/feedback/",
data, config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/messages/{messagePk}/feedback/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# 請求內容 (payload)
data = {
    "type": {},
    "suggestion": "範例字串"
}

response = requests.post(url, json=data, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>post("https://api.maiagent.ai/api/v1/messages/{messagePk}/feedback/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'type' => new \stdClass(),
            'suggestion' => '範例字串'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 201

回應結構範例

```
{
  "id": string (uuid)
  "type":
  {
```

```
  }
  "suggestion"?: string // 非必填
  "updatedAt": string (timestamp)
}
```

回應範例值

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "type": {},
  "suggestion": "回應字串",
  "updatedAt": "回應字串"
}
```

狀態碼: 400 - 此訊息已有回饋，請使用 PATCH 方法更新

更新訊息回饋

PUT `/api/v1/messages/{messagePk}/feedback/{id}`

參數

參數名稱	必填	類型	說明
`id`	V	string	A UUID string identifying this Message Feedback.
`messagePk`	V	string	

請求內容

請求參數

欄位	類型	必填	說明
type	object	是	

欄位	類型	必填	說明
suggestion	string	否	

請求結構範例

```
{
  "type":
  {
  }
  "suggestion"?: string // 非必填
}
```

請求範例值

```
{
  "type": {},
  "suggestion": "範例字串"
}
```

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X PUT
"https://api.maiagent.ai/api/v1/messages/{messagePk}/feedback/550e8400-e29b-
41d4-a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "type": {},
    "suggestion": "範例字串"
  }'

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// 請求內容 (payload)
const data = {
    "type": {},
    "suggestion": "範例字串"
  };

axios.put("https://api.maiagent.ai/api/v1/messages/{messagePk}/feedback/550e8
400-e29b-41d4-a716-446655440000/", data, config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/messages/{messagePk}/feedback/550e8400-e29b-41d4-a716-446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# 請求內容 (payload)
data = {
    "type": {},
    "suggestion": "範例字串"
}

response = requests.put(url, json=data, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->put("https://api.maiagent.ai/api/v1/messages/{messagePk}/feedback/550e8400-e29b-41d4-a716-446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'type' => new \stdClass(),
            'suggestion' => '範例字串'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
{
  "id": string (uuid)
  "type":
```

```
  {
  }
  "suggestion"?: string // 非必填
  "updatedAt": string (timestamp)
}
```

回應範例值

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "type": {},
  "suggestion": "回應字串",
  "updatedAt": "回應字串"
}
```

刪除訊息回饋

DELETE `/api/v1/messages/{messagePk}/feedback/{id}`

參數

參數名稱	必填	類型	說明
`id`	V	string	A UUID string identifying this Message Feedback.
`messagePk`	V	string	

程式碼範例

Shell/Bash

```shell
# 呼叫 API 示例 (Shell)
curl -X DELETE
"https://api.maiagent.ai/api/v1/messages/{messagePk}/feedback/550e8400-e29b-
41d4-a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```javascript
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

// 請求內容 (payload)
const data = null;

axios.delete("https://api.maiagent.ai/api/v1/messages/{messagePk}/feedback/55
0e8400-e29b-41d4-a716-446655440000/", data, config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/messages/{messagePk}/feedback/550e8400-e29b-41d4-a716-446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.delete(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->delete("https://api.maiagent.ai/api/v1/messages/{messagePk}/feedback/550e8400-e29b-41d4-a716-446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼	說明
204	成功刪除回饋
400	此回饋不屬於指定的訊息

取得對話紀錄列表

GET `/api/v1/records/`

參數

參數名稱	必填	類型	說明
`callerMember`	X	array	Multiple values may be separated by commas.
`chatbot`	X	string	篩選特定 AI 助理 (UUID)
`endDate`	X	string	結束日期（格式：YYYY-MM-DD，如：2025-01-31）
`endDatetime`	X	string	
`errorType`	X	array	Multiple values may be separated by commas. `system`: System ; `llm`: LLM ; `embedding`: Embedding ; `reranker`: Reranker ; `vector_db`: Vector DB ; `workflow`: Workflow ; `tool`: Tool ; `timeout`: Ti...
`feedbackType`	X	array	Multiple values may be separated by commas. `like`: Like ; `dislike`: Dislike;
`hasError`	X	boolean	
`hasFeedback`	X	boolean	
`keyword`	X	string	關鍵字搜尋 (同時搜尋使用者訊息和機器人回答內容)
`largeLanguageModel`	X	string	篩選特定大型語言模型 (UUID)
`page`	X	integer	A page number within the paginated result set.
`pageSize`	X	integer	Number of results to return per page.
`source`	X	string	篩選記錄來源，逗號分隔；省略時同時回傳兩種來源。interactive = 使用者對話，scheduled = 排程執行。
`startDate`	X	string	開始日期（格式：YYYY-MM-DD，如：2025-01-01）
`startDatetime`	X	string	
`tool`	X	string	

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/records/?
callerMember=example&chatbot=example&endDate=example&endDatetime=2025-01-
01T00:00:00.000Z&errorType=example&feedbackType=example&hasError=true&hasFeed
back=true&keyword=example&largeLanguageModel=example&page=1&pageSize=1&source
=interactive&startDate=example&startDatetime=2025-01-
01T00:00:00.000Z&tool=example"

  -H "Authorization: Api-Key YOUR_API_KEY"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/records/?
callerMember=example&chatbot=example&endDate=example&endDatetime=2025-01-
01T00:00:00.000Z&errorType=example&feedbackType=example&hasError=true&hasFeed
back=true&keyword=example&largeLanguageModel=example&page=1&pageSize=1&source
=interactive&startDate=example&startDatetime=2025-01-
01T00:00:00.000Z&tool=example", config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/records/?
callerMember=example&chatbot=example&endDate=example&endDatetime=2025-01-
01T00:00:00.000Z&errorType=example&feedbackType=example&hasError=true&hasFeed
back=true&keyword=example&largeLanguageModel=example&page=1&pageSize=1&source
=interactive&startDate=example&startDatetime=2025-01-
01T00:00:00.000Z&tool=example"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->get("https://api.maiagent.ai/api/v1/records/?
callerMember=example&chatbot=example&endDate=example&endDatetime=2025-01-
01T00:00:00.000Z&errorType=example&feedbackType=example&hasError=true&hasFeed
back=true&keyword=example&largeLanguageModel=example&page=1&pageSize=1&source
=interactive&startDate=example&startDatetime=2025-01-
01T00:00:00.000Z&tool=example", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
{
  "count": integer
  "next"?: string (uri) // 非必填
  "previous"?: string (uri) // 非必填
  "results": [
```

```
    {
      "id": string (uuid)
      "senderName": string // 返回使用者訊息發送者的名稱
      "callerMemberId": string
      "callerMemberName": string
      "feedback":
      {
        "id": string (uuid)
        "type":
        {
        }
        "suggestion"?: string // 非必填
        "updatedAt": string (timestamp)
      }
      "inputMessage": string
      "condenseMessage": string // User message rewritten from the chat history
and context.
      "outputMessage": string
      "faithfulnessScore": number (double) // Whether the chatbot reply is
grounded in the knowledge base rather than made up.
      "displayFaithfulnessScore": integer
      "answerRelevancyScore": number (double) // Whether the chatbot reply is
relevant to the user's question.
      "displayAnswerRelevancyScore": integer
      "contextPrecisionScore": number (double) // Whether the chatbot reply is
relevant to the reference context.
      "displayContextPrecisionScore": integer
      "answerCorrectnessScore": number (double) // Whether the chatbot reply is
correct (requires a ground-truth answer).
      "displayAnswerCorrectnessScore": integer
      "answerSimilarityScore": number (double) // Whether the chatbot reply is
similar to the ground-truth answer.
      "displayAnswerSimilarityScore": integer
      "contextRecallScore": number (double) // Whether the chatbot reply recalls
the relevant information from the reference context.
      "displayContextRecallScore": integer
      "replyTime": string
      "createdAt": string (timestamp)
      "error": string // Error message raised during execution.
      "errorType": // 可能有不同的類型
      string (enum: system, llm, embedding, reranker, vector_db, workflow, tool,
timeout, client_interrupt, hook_blocked, evaluation, other) // Error source:
system, LLM, embedding, reranker, and so on.

* `system` - System
* `llm` - LLM
* `embedding` - Embedding
* `reranker` - Reranker
* `vector_db` - Vector DB
* `workflow` - Workflow
```

```
* `tool` - Tool
* `timeout` - Timeout
* `client_interrupt` - Client Interrupt
* `hook_blocked` - Hook Blocked
* `evaluation` - Evaluation
* `other` - Other
      "processingTime": object // 回傳各個處理階段的時間統計，含 streaming_metrics waterfall
      "usage": object // 回傳使用量統計，包含字數、token 數和每次 LLM 呼叫的 token 明細
      "citationNodes": [
        {
          "id": string
          "text": string
          "chatbotFileId": string
          "fileName": string
          "url": string
        }
      ]
      "inputHookLogs": [
        {
          "id": string (uuid)
          "hook": string (uuid)
          "hookName": string
          "hookTypeLabel": string
          "hookAction": string
          "conversation": string (uuid)
          "message": string (uuid)
          "messageContent": string // Return the raw message text.
          "chatbotId": string
          "chatbotName": string
          "metadata": object
          "triggerPoint": string
          "createdAt": string (timestamp)
          "updatedAt": string (timestamp)
        }
      ]
      "outputHookLogs": [
        {
          "id": string (uuid)
          "hook": string (uuid)
          "hookName": string
          "hookTypeLabel": string
          "hookAction": string
          "conversation": string (uuid)
          "message": string (uuid)
          "messageContent": string // Return the raw message text.
          "chatbotId": string
          "chatbotName": string
          "metadata": object
          "triggerPoint": string
```

```
          "createdAt": string (timestamp)
          "updatedAt": string (timestamp)
        }
      ]
      "instructionId": string
      "llm":
      {
        "id": string (uuid)
        "name": string
      }
      "effectiveMaxLlmOutputTokens": integer // max_tokens actually used for this
reply, from Chatbot.custom_max_llm_output_tokens or LLM.max_tokens.
      "chatbot":
      {
        "id": string (uuid)
        "name": string
      }
      "context": string
      "conversationId": string (uuid)
      "inboxId": string (uuid)
      "botMessageId": string (uuid)
      "userMessageId": string (uuid)
      "creditCosts": [ // Return credit costs aggregated by item_code for credit-
mode organizations.
        object
      ]
      "cacheSavedCredits": number (double) // Net credits saved by prompt caching
for this reply; ``None`` outside credit mode.

Reuses the usage-statistics saving semantics (``compute_cache_saved_credits``)
on the reply's own billing batch, so the per-reply figure and the hourly
aggregate are defined by the same formula. The net value may be negative
(cache-creation premium exceeding read savings); the frontend hides
non-positive values by design.
      "trace": object // Return the round trace timeline for the detail view;
``None`` for legacy records.
      "llmRawRequest": object // Raw messages array sent to the LLM on the final
round, including system prompt and memory
      "source": string // Origin discriminator for the unified /records/ response.
      "schedule": object // Shape parity with scheduled rows, which link their
owning ChatbotSchedule here.
      "voiceOrigin": object // The voice session and turn that delegated this
question here, if it was a delegation.
    }
  ]
}
```

回應範例值

```
{
  "count": 123,
  "next": "http://api.example.org/accounts/?page=4",
  "previous": "http://api.example.org/accounts/?page=2",
  "results": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "senderName": "回應字串",
      "callerMemberId": "回應字串",
      "callerMemberName": "回應字串",
      "feedback": {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "type": {},
        "suggestion": "回應字串",
        "updatedAt": "回應字串"
      },
      "inputMessage": "回應字串",
      "condenseMessage": "回應字串",
      "outputMessage": "回應字串",
      "faithfulnessScore": 456,
      "displayFaithfulnessScore": 456,
      "answerRelevancyScore": 456,
      "displayAnswerRelevancyScore": 456,
      "contextPrecisionScore": 456,
      "displayContextPrecisionScore": 456,
      "answerCorrectnessScore": 456,
      "displayAnswerCorrectnessScore": 456,
      "answerSimilarityScore": 456,
      "displayAnswerSimilarityScore": 456,
      "contextRecallScore": 456,
      "displayContextRecallScore": 456,
      "replyTime": "回應字串",
      "createdAt": "回應字串",
      "error": "回應字串",
      "errorType": "system",
      "processingTime": {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "name": "回應範例名稱",
        "description": "回應範例描述"
      },
      "usage": {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "name": "回應範例名稱",
        "description": "回應範例描述"
      },
      "citationNodes": [
        {
          "id": "回應字串",
          "text": "回應字串",
```

```
        "chatbotFileId": "回應字串",
        "fileName": "回應字串",
        "url": "回應字串"
      }
    ],
    "inputHookLogs": [
      {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "hook": "550e8400-e29b-41d4-a716-446655440000",
        "hookName": "回應字串",
        "hookTypeLabel": "回應字串",
        "hookAction": "回應字串",
        "conversation": "550e8400-e29b-41d4-a716-446655440000",
        "message": "550e8400-e29b-41d4-a716-446655440000",
        "messageContent": "回應字串",
        "chatbotId": "回應字串",
        "chatbotName": "回應字串",
        "metadata": null,
        "triggerPoint": "回應字串",
        "createdAt": "回應字串",
        "updatedAt": "回應字串"
      }
    ],
    "outputHookLogs": [
      {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "hook": "550e8400-e29b-41d4-a716-446655440000",
        "hookName": "回應字串",
        "hookTypeLabel": "回應字串",
        "hookAction": "回應字串",
        "conversation": "550e8400-e29b-41d4-a716-446655440000",
        "message": "550e8400-e29b-41d4-a716-446655440000",
        "messageContent": "回應字串",
        "chatbotId": "回應字串",
        "chatbotName": "回應字串",
        "metadata": null,
        "triggerPoint": "回應字串",
        "createdAt": "回應字串",
        "updatedAt": "回應字串"
      }
    ],
    "instructionId": "回應字串",
    "llm": {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "回應字串"
    },
    "effectiveMaxLlmOutputTokens": 456,
    "chatbot": {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "回應字串"
```

```
      },
      "context": "回應字串",
      "conversationId": "550e8400-e29b-41d4-a716-446655440000",
      "inboxId": "550e8400-e29b-41d4-a716-446655440000",
      "botMessageId": "550e8400-e29b-41d4-a716-446655440000",
      "userMessageId": "550e8400-e29b-41d4-a716-446655440000",
      "creditCosts": [
        {
          "id": "550e8400-e29b-41d4-a716-446655440000",
          "name": "回應範例名稱",
          "description": "回應範例描述"
        }
      ],
      "cacheSavedCredits": 456,
      "trace": {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "name": "回應範例名稱",
        "description": "回應範例描述"
      },
      "llmRawRequest": null,
      "source": "回應字串",
      "schedule": {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "name": "回應範例名稱",
        "description": "回應範例描述"
      },
      "voiceOrigin": {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "name": "回應範例名稱",
        "description": "回應範例描述"
      }
    }
  ]
}
```


取得特定對話紀錄

GET `/api/v1/records/{id}`

參數

參數名稱	必填	類型	說明
id	V	string	A UUID string identifying this Chatbot Record.

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/records/550e8400-e29b-41d4-a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/records/550e8400-e29b-41d4-a716-446655440000/", config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/records/550e8400-e29b-41d4-a716-
446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/records/550e8400-e29b-41d4-a716-
446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
{
  "id": string (uuid)
  "senderName": string // 返回使用者訊息發送者的名稱
  "callerMemberId": string
  "callerMemberName": string
  "feedback":
  {
    "id": string (uuid)
```

```
    "type":
    {
    }
    "suggestion"?: string // 非必填
    "updatedAt": string (timestamp)
  }
  "inputMessage": string
  "condenseMessage": string // User message rewritten from the chat history and
context.
  "outputMessage": string
  "faithfulnessScore": number (double) // Whether the chatbot reply is grounded in
the knowledge base rather than made up.
  "displayFaithfulnessScore": integer
  "answerRelevancyScore": number (double) // Whether the chatbot reply is relevant
to the user's question.
  "displayAnswerRelevancyScore": integer
  "contextPrecisionScore": number (double) // Whether the chatbot reply is
relevant to the reference context.
  "displayContextPrecisionScore": integer
  "answerCorrectnessScore": number (double) // Whether the chatbot reply is
correct (requires a ground-truth answer).
  "displayAnswerCorrectnessScore": integer
  "answerSimilarityScore": number (double) // Whether the chatbot reply is similar
to the ground-truth answer.
  "displayAnswerSimilarityScore": integer
  "contextRecallScore": number (double) // Whether the chatbot reply recalls the
relevant information from the reference context.
  "displayContextRecallScore": integer
  "replyTime": string
  "createdAt": string (timestamp)
  "error": string // Error message raised during execution.
  "errorType": // 可能有不同的類型
  string (enum: system, llm, embedding, reranker, vector_db, workflow, tool,
timeout, client_interrupt, hook_blocked, evaluation, other) // Error source:
system, LLM, embedding, reranker, and so on.

* `system` - System
* `llm` - LLM
* `embedding` - Embedding
* `reranker` - Reranker
* `vector_db` - Vector DB
* `workflow` - Workflow
* `tool` - Tool
* `timeout` - Timeout
* `client_interrupt` - Client Interrupt
* `hook_blocked` - Hook Blocked
* `evaluation` - Evaluation
* `other` - Other
  "processingTime": object // 回傳各個處理階段的時間統計，含 streaming_metrics
waterfall
```

```
  "usage": object // 回傳使用量統計，包含字數、token 數和每次 LLM 呼叫的 token 明細
  "citationNodes": [
    {
      "id": string
      "text": string
      "chatbotFileId": string
      "fileName": string
      "url": string
    }
  ]
  "inputHookLogs": [
    {
      "id": string (uuid)
      "hook": string (uuid)
      "hookName": string
      "hookTypeLabel": string
      "hookAction": string
      "conversation": string (uuid)
      "message": string (uuid)
      "messageContent": string // Return the raw message text.
      "chatbotId": string
      "chatbotName": string
      "metadata": object
      "triggerPoint": string
      "createdAt": string (timestamp)
      "updatedAt": string (timestamp)
    }
  ]
  "outputHookLogs": [
    {
      "id": string (uuid)
      "hook": string (uuid)
      "hookName": string
      "hookTypeLabel": string
      "hookAction": string
      "conversation": string (uuid)
      "message": string (uuid)
      "messageContent": string // Return the raw message text.
      "chatbotId": string
      "chatbotName": string
      "metadata": object
      "triggerPoint": string
      "createdAt": string (timestamp)
      "updatedAt": string (timestamp)
    }
  ]
  "instructionId": string
  "llm":
  {
    "id": string (uuid)
```

```
    "name": string
  }
  "effectiveMaxLlmOutputTokens": integer // max_tokens actually used for this
reply, from Chatbot.custom_max_llm_output_tokens or LLM.max_tokens.
  "chatbot":
  {
    "id": string (uuid)
    "name": string
  }
  "context": string
  "conversationId": string (uuid)
  "inboxId": string (uuid)
  "botMessageId": string (uuid)
  "userMessageId": string (uuid)
  "creditCosts": [ // Return credit costs aggregated by item_code for credit-mode
organizations.
    object
  ]
  "cacheSavedCredits": number (double) // Net credits saved by prompt caching for
this reply; ``None`` outside credit mode.

Reuses the usage-statistics saving semantics (``compute_cache_saved_credits``)
on the reply's own billing batch, so the per-reply figure and the hourly
aggregate are defined by the same formula. The net value may be negative
(cache-creation premium exceeding read savings); the frontend hides
non-positive values by design.
  "trace": object // Return the round trace timeline for the detail view; ``None``
for legacy records.
  "llmRawRequest": object // Raw messages array sent to the LLM on the final
round, including system prompt and memory
  "source": string // Origin discriminator for the unified /records/ response.
  "schedule": object // Shape parity with scheduled rows, which link their owning
ChatbotSchedule here.
  "voiceOrigin": object // The voice session and turn that delegated this question
here, if it was a delegation.
}
```

回應範例值

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "senderName": "回應字串",
  "callerMemberId": "回應字串",
  "callerMemberName": "回應字串",
  "feedback": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "type": {},
    "suggestion": "回應字串",
```

```
    "updatedAt": "回應字串"
  },
  "inputMessage": "回應字串",
  "condenseMessage": "回應字串",
  "outputMessage": "回應字串",
  "faithfulnessScore": 456,
  "displayFaithfulnessScore": 456,
  "answerRelevancyScore": 456,
  "displayAnswerRelevancyScore": 456,
  "contextPrecisionScore": 456,
  "displayContextPrecisionScore": 456,
  "answerCorrectnessScore": 456,
  "displayAnswerCorrectnessScore": 456,
  "answerSimilarityScore": 456,
  "displayAnswerSimilarityScore": 456,
  "contextRecallScore": 456,
  "displayContextRecallScore": 456,
  "replyTime": "回應字串",
  "createdAt": "回應字串",
  "error": "回應字串",
  "errorType": "system",
  "processingTime": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應範例名稱",
    "description": "回應範例描述"
  },
  "usage": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應範例名稱",
    "description": "回應範例描述"
  },
  "citationNodes": [
    {
      "id": "回應字串",
      "text": "回應字串",
      "chatbotFileId": "回應字串",
      "fileName": "回應字串",
      "url": "回應字串"
    }
  ],
  "inputHookLogs": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "hook": "550e8400-e29b-41d4-a716-446655440000",
      "hookName": "回應字串",
      "hookTypeLabel": "回應字串",
      "hookAction": "回應字串",
      "conversation": "550e8400-e29b-41d4-a716-446655440000",
      "message": "550e8400-e29b-41d4-a716-446655440000",
      "messageContent": "回應字串",
```

```
      "chatbotId": "回應字串",
      "chatbotName": "回應字串",
      "metadata": null,
      "triggerPoint": "回應字串",
      "createdAt": "回應字串",
      "updatedAt": "回應字串"
    }
  ],
  "outputHookLogs": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "hook": "550e8400-e29b-41d4-a716-446655440000",
      "hookName": "回應字串",
      "hookTypeLabel": "回應字串",
      "hookAction": "回應字串",
      "conversation": "550e8400-e29b-41d4-a716-446655440000",
      "message": "550e8400-e29b-41d4-a716-446655440000",
      "messageContent": "回應字串",
      "chatbotId": "回應字串",
      "chatbotName": "回應字串",
      "metadata": null,
      "triggerPoint": "回應字串",
      "createdAt": "回應字串",
      "updatedAt": "回應字串"
    }
  ],
  "instructionId": "回應字串",
  "llm": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應字串"
  },
  "effectiveMaxLlmOutputTokens": 456,
  "chatbot": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應字串"
  },
  "context": "回應字串",
  "conversationId": "550e8400-e29b-41d4-a716-446655440000",
  "inboxId": "550e8400-e29b-41d4-a716-446655440000",
  "botMessageId": "550e8400-e29b-41d4-a716-446655440000",
  "userMessageId": "550e8400-e29b-41d4-a716-446655440000",
  "creditCosts": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "回應範例名稱",
      "description": "回應範例描述"
    }
  ],
  "cacheSavedCredits": 456,
  "trace": {
```

```
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應範例名稱",
    "description": "回應範例描述"
  },
  "llmRawRequest": null,
  "source": "回應字串",
  "schedule": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應範例名稱",
    "description": "回應範例描述"
  },
  "voiceOrigin": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應範例名稱",
    "description": "回應範例描述"
  }
}
```


狀態碼: 404 - 找不到指定的對話記錄

建立對話紀錄匯出請求

`POST` `/api/v1/records/export-excel-requests/`

請求內容

請求參數

欄位	類型	必填	說明
chatbot	string	否	指定要匯出的 Chatbot UUID，支援逗號分隔多個 UUID。留空則匯出組織內所有有權限的 Chatbot。
chatbotId	string (uuid)	否	指定要匯出的 Chatbot UUID（chatbot 的別名，僅支援單個 UUID）。
keyword	string	否	過濾包含特定關鍵字的對話記錄（搜尋用戶訊息和機器人回覆）。

欄位	類型	必填	說明
largeLanguageModel	string	否	指定要匯出的大型語言模型 UUID，支援逗號分隔多個 UUID。
startDate	string (date)	否	開始日期 (YYYY-MM-DD)，包含當天。
endDate	string (date)	否	結束日期 (YYYY-MM-DD)，包含當天。
startDatetime	string (timestamp)	否	精確開始時間（ISO 8601，包含該時間點），與列表下鑽篩選同語意。
endDatetime	string (timestamp)	否	精確結束時間（ISO 8601，不包含該時間點），與列表下鑽篩選同語意。
hasError	boolean	否	過濾是否有錯誤的紀錄（true 僅含有錯誤、false 僅含無錯誤）。
errorType	string	否	過濾錯誤類型，支援逗號分隔多選（OR 邏輯），值域同對話紀錄列表。
hasFeedback	boolean	否	過濾是否有使用者評價（true 僅含有讚/倒讚、false 僅含無評價）。
feedbackType	string	否	過濾使用者評價類型（like / dislike），支援逗號分隔多選（OR 邏輯）。
callerMember	string	否	過濾發話成員 UUID，支援逗號分隔多選（OR 邏輯）。
tool	string (uuid)	否	過濾呼叫過該工具的問答（工具 UUID，含平台內建工具；執行失敗也算）。

請求結構範例

```
{
  "chatbot"?: string // 指定要匯出的 Chatbot UUID，支援逗號分隔多個 UUID。留空則匯出組織內所有有權限的 Chatbot。 (非必填)
  "chatbotId"?: string (uuid) // 指定要匯出的 Chatbot UUID（chatbot 的別名，僅支援單個 UUID）。 (非必填)
  "keyword"?: string // 過濾包含特定關鍵字的對話記錄（搜尋用戶訊息和機器人回覆）。 (非必填)
  "largeLanguageModel"?: string // 指定要匯出的大型語言模型 UUID，支援逗號分隔多個 UUID。 (非必填)
  "startDate"?: string (date) // 開始日期 (YYYY-MM-DD)，包含當天。 (非必填)
  "endDate"?: string (date) // 結束日期 (YYYY-MM-DD)，包含當天。 (非必填)
  "startDatetime"?: string (timestamp) // 精確開始時間（ISO 8601，包含該時間點），與列表下鑽篩選同語意。 (非必填)
  "endDatetime"?: string (timestamp) // 精確結束時間（ISO 8601，不包含該時間點），與列表下鑽篩選同語意。 (非必填)
  "hasError"?: boolean // 過濾是否有錯誤的紀錄（true 僅含有錯誤、false 僅含無錯誤）。 (非必
```

```
填)
  "errorType"?: string // 過濾錯誤類型，支援逗號分隔多選（OR 邏輯），值域同對話紀錄列表。（非必填)
  "hasFeedback"?: boolean // 過濾是否有使用者評價（true 僅含有讚/倒讚、false 僅含無評價）。(非必填)
  "feedbackType"?: string // 過濾使用者評價類型（like / dislike），支援逗號分隔多選（OR 邏輯）。（非必填)
  "callerMember"?: string // 過濾發話成員 UUID，支援逗號分隔多選（OR 邏輯）。（非必填)
  "tool"?: string (uuid) // 過濾呼叫過該工具的問答（工具 UUID，含平台內建工具；執行失敗也算）。（非必填)
}
```

請求範例值

```
{
  "chatbot": "範例字串",
  "chatbotId": "550e8400-e29b-41d4-a716-446655440000",
  "keyword": "範例字串",
  "largeLanguageModel": "範例字串",
  "startDate": "範例字串",
  "endDate": "範例字串",
  "startDatetime": "範例字串",
  "endDatetime": "範例字串",
  "hasError": true,
  "errorType": "範例字串",
  "hasFeedback": true,
  "feedbackType": "範例字串",
  "callerMember": "範例字串",
  "tool": "550e8400-e29b-41d4-a716-446655440000"
}
```

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X POST "https://api.maiagent.ai/api/v1/records/export-excel-requests/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "chatbot": "範例字串",
    "chatbotId": "550e8400-e29b-41d4-a716-446655440000",
    "keyword": "範例字串",
    "largeLanguageModel": "範例字串",
    "startDate": "範例字串",
    "endDate": "範例字串",
    "startDatetime": "範例字串",
    "endDatetime": "範例字串",
    "hasError": true,
    "errorType": "範例字串",
    "hasFeedback": true,
    "feedbackType": "範例字串",
    "callerMember": "範例字串",
    "tool": "550e8400-e29b-41d4-a716-446655440000"
  }'

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```javascript
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// 請求內容 (payload)
const data = {
    "chatbot": "範例字串",
    "chatbotId": "550e8400-e29b-41d4-a716-446655440000",
    "keyword": "範例字串",
    "largeLanguageModel": "範例字串",
    "startDate": "範例字串",
    "endDate": "範例字串",
    "startDatetime": "範例字串",
    "endDatetime": "範例字串",
    "hasError": true,
    "errorType": "範例字串",
    "hasFeedback": true,
    "feedbackType": "範例字串",
    "callerMember": "範例字串",
    "tool": "550e8400-e29b-41d4-a716-446655440000"
  };

axios.post("https://api.maiagent.ai/api/v1/records/export-excel-requests/",
data, config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/records/export-excel-requests/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# 請求內容 (payload)
data = {
    "chatbot": "範例字串",
    "chatbotId": "550e8400-e29b-41d4-a716-446655440000",
    "keyword": "範例字串",
    "largeLanguageModel": "範例字串",
    "startDate": "範例字串",
    "endDate": "範例字串",
    "startDatetime": "範例字串",
    "endDatetime": "範例字串",
    "hasError": True,
    "errorType": "範例字串",
    "hasFeedback": True,
    "feedbackType": "範例字串",
    "callerMember": "範例字串",
    "tool": "550e8400-e29b-41d4-a716-446655440000"
}

response = requests.post(url, json=data, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->post("https://api.maiagent.ai/api/v1/records/export-excel-requests/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'chatbot' => '範例字串',
            'chatbotId' => '550e8400-e29b-41d4-a716-446655440000',
            'keyword' => '範例字串',
            'largeLanguageModel' => '範例字串',
            'startDate' => '範例字串',
            'endDate' => '範例字串',
            'startDatetime' => '範例字串',
            'endDatetime' => '範例字串',
            'hasError' => true,
            'errorType' => '範例字串',
            'hasFeedback' => true,
            'feedbackType' => '範例字串',
            'callerMember' => '範例字串',
            'tool' => '550e8400-e29b-41d4-a716-446655440000'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 201

回應結構範例

```
{
  "id": string (uuid)
  "userEmail": string (email)
  "recordType":  // Which monitoring list this export was requested from. Text exports read filter_params with the text record filters, voice exports with the voice session filters.

* `text` - Text records
* `voice` - Voice sessions
  {
  }
  "chatbotId": string (uuid) // 指定要匯出的 Chatbot（已棄用，請使用 chatbot_ids）
  "chatbotIds": object // 指定要匯出的 Chatbot UUID 列表，留空則匯出組織內所有有權限的 Chatbot
  "startDate": string (date) // 匯出記錄的開始日期（包含）
  "endDate": string (date) // 匯出記錄的結束日期（包含）
  "status":
  {
  }
  "statusDisplay": string
  "fileUrl": string // 返回檔案 URL（永久有效）
  "fileSize": integer // 檔案大小（bytes）
  "recordCount": integer // 匯出的記錄總數
  "errorMessage": string
  "processingDurationSeconds": number (double) // 計算處理時長（秒）
  "createdAt": string (timestamp)
  "startedAt": string (timestamp)
  "completedAt": string (timestamp)
}
```

回應範例值

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "userEmail": "response@example.com",
  "recordType": {},
  "chatbotId": "550e8400-e29b-41d4-a716-446655440000",
  "chatbotIds": null,
  "startDate": "回應字串",
```

```
  "endDate": "回應字串",
  "status": {},
  "statusDisplay": "回應字串",
  "fileUrl": "回應字串",
  "fileSize": 456,
  "recordCount": 456,
  "errorMessage": "回應字串",
  "processingDurationSeconds": 456,
  "createdAt": "回應字串",
  "startedAt": "回應字串",
  "completedAt": "回應字串"
}
```


取得對話紀錄匯出狀態

`GET` `/api/v1/records/export-excel-requests/{exportId}`

參數

參數名稱	必填	類型	說明
exportId	V	string	

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/records/export-excel-
requests/{exportId}
"

  -H "Authorization: Api-Key YOUR_API_KEY"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/records/export-excel-
requests/{exportId}
", config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/records/export-excel-
requests/{exportId}
"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->get("https://api.maiagent.ai/api/v1/records/export-excel-requests/{exportId}
", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
{
  "id": string (uuid)
  "senderName": string // 返回使用者訊息發送者的名稱
  "callerMemberId": string
  "callerMemberName": string
  "inputMessage": string
  "outputMessage": string
  "chatbot":
```

```
  {
    "id": string (uuid)
    "name": string
  }
  "condenseMessage": string // User message rewritten from the chat history and
context.
  "feedback":
  {
    "id": string (uuid)
    "type":
    {
    }
    "suggestion"?: string // 非必填
    "updatedAt": string (timestamp)
  }
  "displayFaithfulnessScore": integer
  "displayAnswerRelevancyScore": integer
  "displayContextPrecisionScore": integer
  "displayAnswerCorrectnessScore": integer
  "displayAnswerSimilarityScore": integer
  "displayContextRecallScore": integer
  "replyTime": string
  "processingTime": object // 回傳列表頁處理時間統計，與詳情頁算式一致但不含
streaming_metrics waterfall
  "usage": object // 回傳使用量統計，包含字數、token 數和每次 LLM 呼叫的 token 明細
  "llm":
  {
    "id": string (uuid)
    "name": string
  }
  "createdAt": string (timestamp)
  "conversationId": string (uuid)
  "errorType": // 可能有不同的類型
  string (enum: system, llm, embedding, reranker, vector_db, workflow, tool,
timeout, client_interrupt, hook_blocked, evaluation, other) // Error source:
system, LLM, embedding, reranker, and so on.

* `system` - System
* `llm` - LLM
* `embedding` - Embedding
* `reranker` - Reranker
* `vector_db` - Vector DB
* `workflow` - Workflow
* `tool` - Tool
* `timeout` - Timeout
* `client_interrupt` - Client Interrupt
* `hook_blocked` - Hook Blocked
* `evaluation` - Evaluation
* `other` - Other
  "creditCosts": [
```

```
    object
  ]
  "source": string // Origin discriminator for the unified /records/ response.
  "schedule": object // Shape parity with scheduled rows, which link their owning
ChatbotSchedule here.
}
```

回應範例值

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "senderName": "回應字串",
  "callerMemberId": "回應字串",
  "callerMemberName": "回應字串",
  "inputMessage": "回應字串",
  "outputMessage": "回應字串",
  "chatbot": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應字串"
  },
  "condenseMessage": "回應字串",
  "feedback": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "type": {},
    "suggestion": "回應字串",
    "updatedAt": "回應字串"
  },
  "displayFaithfulnessScore": 456,
  "displayAnswerRelevancyScore": 456,
  "displayContextPrecisionScore": 456,
  "displayAnswerCorrectnessScore": 456,
  "displayAnswerSimilarityScore": 456,
  "displayContextRecallScore": 456,
  "replyTime": "回應字串",
  "processingTime": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應範例名稱",
    "description": "回應範例描述"
  },
  "usage": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應範例名稱",
    "description": "回應範例描述"
  },
  "llm": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應字串"
  },
```

```
  "createdAt": "回應字串",
  "conversationId": "550e8400-e29b-41d4-a716-446655440000",
  "errorType": "system",
  "creditCosts": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "回應範例名稱",
      "description": "回應範例描述"
    }
  ],
  "source": "回應字串",
  "schedule": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應範例名稱",
    "description": "回應範例描述"
  }
}
```

呼叫 API 示例 (Shell)

目錄

1. 列出對話平台
2. 建立對話平台
3. 取得特定對話平台
4. 更新對話平台
5. 部分更新對話平台
6. 刪除對話平台
7. 列出對話平台的 Webhook
8. 建立 Webhook
9. 取得特定 Webhook
10. 更新 Webhook
11. 部分更新 Webhook
12. 刪除 Webhook

呼叫 API 示例 (Shell)

對話平台（Inbox）是對話的歸屬單位，也是 Webhook 的設定位置：每個對話平台可以設定多組 Webhook，在使用者訊息進入（`incoming`）或 Agent 回覆（`outgoing`）時推送到您的系統。Web Chat 類型的對話平台另有 Web Chat 端點。設定方式與 payload 格式見技術手冊 Webhook。

列出對話平台

GET `/api/v1/inboxes/`

參數

參數名稱	必填	類型	說明
`accessType`	X	string	存取類型過濾
`channelType`	X	string	頻道類型過濾
`chatbot`	X	string	聊天機器人 ID 過濾
`isActive`	X	boolean	是否啟用過濾
`ordering`	X	string	Which field to use when ordering the results.
`page`	X	integer	A page number within the paginated result set.
`pageSize`	X	integer	Number of results to return per page.
`pagination`	X	string	是否分頁 (true/false)。當設為 false 時，會回傳簡化版的資料格式
`query`	X	string	

`source`	X	string	`self_built`: self_built ; `built_in`: built_in ; `all`: all;

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/inboxes/?
accessType=example&channelType=example&chatbot=example&isActive=true&ordering=example&page=1&pag
eSize=1&pagination=example&query=example&source=all"

  -H "Authorization: Api-Key YOUR_API_KEY"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/inboxes/?
accessType=example&channelType=example&chatbot=example&isActive=true&ordering=example&page=1&pag
eSize=1&pagination=example&query=example&source=all", config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```python
import requests

url = "https://api.maiagent.ai/api/v1/inboxes/?
accessType=example&channelType=example&chatbot=example&isActive=true&ordering=example&page=1&pag
eSize=1&pagination=example&query=example&source=all"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->get("https://api.maiagent.ai/api/v1/inboxes/?
accessType=example&channelType=example&chatbot=example&isActive=true&ordering=example&page=1&pag
eSize=1&pagination=example&query=example&source=all", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200 - 對話平台列表

回應結構範例

```
{
  "count": integer
  "next"?: string (uri) // 非必填
  "previous"?: string (uri) // 非必填
  "results": [
    {
      "id": string (uuid)
      "name": string
      "channelType": string (enum: line, telegram, teams, web, messenger, instagram, email, whatsapp,
slack, team_plus, line_works, viber) // * `line` - LINE
* `telegram` - Telegram
* `teams` - Teams
* `web` - Web
* `messenger` - Messenger
* `instagram` - Instagram
* `email` - Email
* `whatsapp` - WhatsApp
* `slack` - Slack
* `team_plus` - Team+
* `line_works` - LINE WORKS
* `viber` - Viber
      "unreadConversationsCount"?: integer // 非必填
      "signAuth"?:  // 非必填
      {
        "id": string (uuid)
        "signSource": string (uuid)
        "signParams": {
        {
          "keycloak":
          {
            "clientId": string
            "url": string
            "realm": string
          }
          "line":
          {
            "liffId": string
          }
          "ad":
          {
            "saml": string
          }
          "google"?:  // 非必填
          {
            "enabled": boolean
          }
        }
        }
        "sourceIdAccessEnabled"?: boolean // When enabled, embedded visitors presenting a Source ID
(verified per the verify mode below) may chat without going through the login flow. Disabled keeps
every existing behavior unchanged. (非必填)
```

```
        "sourceIdVerifyMode"?:  // "Require signature verification": the embedding site must send an HMAC signature computed on its backend. "Source ID only": anyone knowing a Source ID can act as that contact; suitable only for testing or closed networks.

* `signature` - Require signature verification
* `raw` - Source ID only (非必填)
        {
        }
        "sourceIdSignatureTtlMinutes"?:  // How long a signature can be used to obtain the contact identity. Not a session lifetime: once exchanged, the session follows the existing WebChat mechanism.

* `1` - 1
* `5` - 5
* `15` - 15 (非必填)
        {
        }
        "keycloakTokenPassthrough"?: boolean // When enabled, the Keycloak access token a visitor logged in with is forwarded as the Authorization header when the AI calls MCP and API tools on their behalf, so tools do not require a separate per-tool login. Only for the Keycloak sign source. Never overrides an Authorization header a tool already resolves from its own credentials. The visitor identity is the organization member bound to the conversation at login, never the contact Source ID. (非必填)
        "keycloakTokenPassthroughAllowedHosts"?: [ // Hostnames (or "*.example.com" wildcards) of the tools the visitor Keycloak token may be sent to (非必填)
          string
        ]
      }
      "enableAnalysis"?: boolean // 非必填
    }
  ]
}
```

回應範例值


```
{
  "count": 123,
  "next": "http://api.example.org/accounts/?page=4",
  "previous": "http://api.example.org/accounts/?page=2",
  "results": [
    {
      "id": "961dcaac-bd2e-44d3-9050-82596dbb3334",
      "chatbot": {
        "id": "80f3170d-eed7-4651-a8da-6b7e6bdbef8b",
        "name": "客服機器人",
        "groups": [],
        "largeLanguageModel": {
          "id": "933aa8b3-cdf4-47a7-86d5-b5dc27fbb044",
          "name": "llm"
        },
        "embeddingModel": {
          "id": "aefcc4f9-917d-4a8a-bd36-d97e3b7cecfe",
          "name": "embedding",
          "icon": null,
          "isDefault": false
        },
        "rerankerModel": {
          "id": "86c2ddfd-0df9-47b9-8f3b-0c42e3347da3",
          "name": "rerank",
```

```
      "icon": null,
      "isDefault": true
    },
    "knowledgeBases": [],
    "tools": [],
    "agentMode": "normal",
    "replyMode": "normal",
    "updatedAt": "1739519493000",
    "enableEvaluation": false,
    "enableInlineCitations": false,
    "enableKnowledgeBaseRag": true,
    "enableAgenticTextToSql": true,
    "enableToolSearching": true,
    "numberOfRetrievedChunks": 12
  },
  "groups": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "管理員群組"
    }
  ],
  "channelType": "web",
  "channelTypeLabel": "Web",
  "name": "1345",
  "autoReplySchedules": [
    {
      "id": "2f4f6383-d8b5-4d88-b4a1-6d02d731f2a6",
      "weekday": 0,
      "isEnabled": true,
      "timeSlots": [
        [
          "00:00:00",
          "00:00:00"
        ]
      ],
      "weekdayName": "Monday"
    },
    {
      "id": "2866f624-a5c3-4ffb-b980-0f8d6a9f0c93",
      "weekday": 1,
      "isEnabled": true,
      "timeSlots": [
        [
          "00:00:00",
          "00:00:00"
        ]
      ],
      "weekdayName": "Tuesday"
    },
    {
      "id": "3cf1e488-fb13-426d-bd59-e62bd71aca85",
      "weekday": 2,
      "isEnabled": true,
      "timeSlots": [
        [
          "00:00:00",
          "00:00:00"
        ]
      ],
      "weekdayName": "Wednesday"
```

```
    },
    {
      "id": "491776a9-fcf1-4e2e-892f-6d9ad5aebea4",
      "weekday": 3,
      "isEnabled": true,
      "timeSlots": [
        [
          "00:00:00",
          "00:00:00"
        ]
      ],
      "weekdayName": "Thursday"
    },
    {
      "id": "dfecb0a9-5001-4aa0-b2cc-5459b6d64351",
      "weekday": 4,
      "isEnabled": true,
      "timeSlots": [
        [
          "00:00:00",
          "00:00:00"
        ]
      ],
      "weekdayName": "Friday"
    },
    {
      "id": "68b6b4d1-7ac8-450f-8877-41b72b499919",
      "weekday": 5,
      "isEnabled": true,
      "timeSlots": [
        [
          "00:00:00",
          "00:00:00"
        ]
      ],
      "weekdayName": "Saturday"
    },
    {
      "id": "15228ea1-4513-4504-81f4-4e486703d8b9",
      "weekday": 6,
      "isEnabled": true,
      "timeSlots": [
        [
          "00:00:00",
          "00:00:00"
        ]
      ],
      "weekdayName": "Sunday"
    }
  ],
  "unreadConversationsCount": 0,
  "totalConversationsCount": 42,
  "channel": {
    "id": "801a690a-1038-4fdd-8aba-bf003b12c3ef",
    "name": "1345",
    "avatar": "https://media-dev.maiagent.ai/static/images/default-chatbot-avatar.png",
    "logo": null,
    "description": "",
    "cover": null,
    "backUrl": "",
```

```
  "isActive": true,
  "enableSpeech": false,
  "displayGreeting": null,
  "displayConversationStarters": [],
  "theme": {
    "primaryColor": "#3854d8",
    "navbarTextColor": "#ffffff",
    "conversationBackgroundColor": "#ffffff",
    "chatbotMessageTextColor": "#374151",
    "userMessageTextColor": "#374151",
    "chatbotMessageBackgroundColor": "#DCE9F6",
    "userMessageBackgroundColor": "#DDEAF6",
    "chatbotMessageBackgroundShadowEnabled": true,
    "userMessageBackgroundShadowEnabled": true
  },
  "darkTheme": {
    "primaryColor": "#404040",
    "navbarTextColor": "#ffffff",
    "conversationBackgroundColor": "#18181B",
    "chatbotMessageTextColor": "#ffffff",
    "userMessageTextColor": "#ffffff",
    "chatbotMessageBackgroundColor": "#171717",
    "userMessageBackgroundColor": "#333842",
    "chatbotMessageBackgroundShadowEnabled": false,
    "userMessageBackgroundShadowEnabled": false
  },
  "enableFileUpload": true,
  "enableDisplayCitations": true,
  "enableShareConversation": false,
  "enableLocation": false,
  "enableShowPoweredBy": true,
  "enableDisplayChatbotAvatar": true,
  "enableDisplayChatbotName": true,
  "enableDisplayPreviousConversation": true,
  "enableDisplayConversationHistory": true,
  "enableConversationTimer": false,
  "conversationTimerDuration": null,
  "enableAutoNewConversationOnTimeout": false,
  "accessType": "api",
  "greetings": [],
  "greetingsByLocale": {
    "en": [
      "Hello, how can I help you?"
    ],
    "zh-hant": [
      "你好，我可以幫你什麼嗎？"
    ],
    "ja": [
      "こんにちは、何かお手伝いできますか？"
    ],
    "ko": [
      "안녕하세요, 무엇을 도와드릴까요?"
    ]
  },
  "conversationStarters": [],
  "conversationStartersByLocale": {
    "en": [
      "What can I help you with today?"
    ],
    "zh-hant": [
```

```
            "你今天需要什麼幫助？"
          ],
          "ja": [
            "今日は何かお手伝いできますか？"
          ],
          "ko": [
            "오늘 뭘 도와줄수있어？"
          ]
        }
      },
      "webhooks": [],
      "createdAt": "1739519493000",
      "updatedAt": "1739519493000",
      "organization": "24b619d9-e981-4a8b-96da-63dc4f96bda6",
      "signAuth": null
    }
  ]
}
```


建立對話平台

POST `/api/v1/inboxes/`

請求內容

請求參數

欄位	類型	必填	說明
name	string	是	
channelType	string (enum: line, telegram, teams, web, messenger, instagram, email, whatsapp, slack, team_plus, line_works, viber)	是	`line` : LINE ; `telegram` : Telegram ; `teams` : Teams ; `web` : Web ; `messenger` : Messenger ; `instagram` : Instagram ; `email` : Email ; `whatsapp` : WhatsApp ; `slack` : Slack ; `team_plus` : Team+ ; `lin...
unreadConversationsCount	integer	否	
signAuth	object (含 8 個屬性: id, signSource, signParams...)	否	
signAuth.signSource	string (uuid)	是	
signAuth.signParams	object	是	
signAuth.signParams.keycloak	object (含 3 個屬性: clientId, url, realm)	是	

欄位	類型	必填	說明
signAuth.signParams.keycloak.clientId	string	是	
signAuth.signParams.keycloak.url	string	是	
signAuth.signParams.keycloak.realm	string	是	
signAuth.signParams.line	object (含 1 個屬性: liffId)	是	
signAuth.signParams.line.liffId	string	是	
signAuth.signParams.ad	object (含 1 個屬性: saml)	是	
signAuth.signParams.ad.saml	string	是	
signAuth.signParams.google	object (含 1 個屬性: enabled)	否	
signAuth.signParams.google.enabled	boolean	是	
signAuth.sourceIdAccessEnabled	boolean	否	When enabled, embedded visitors presenting a Source ID (verified per the verify mode below) may chat without going through the login flow. Disabled keeps every existing behavior unchanged.
signAuth.sourceIdVerifyMode	object	否	"Require signature verification": the embedding site must send an HMAC signature computed on its backend. "Source ID only": anyone knowing a Source ID can act as that contact; suitable only for testin...
signAuth.sourceIdSignatureTtlMinutes	object	否	How long a signature can be used to obtain the contact identity. Not a session lifetime: once exchanged, the session follows the existing WebChat mechanism. `1` : 1 ; `5` : 5 ; `15` : 15;
signAuth.keycloakTokenPassthrough	boolean	否	When enabled, the Keycloak access token a visitor logged in with is forwarded as the Authorization header when the AI calls MCP and API tools on their behalf, so tools do not require a separate per-to...
signAuth.keycloakTokenPassthroughAllowedHosts	array[string]	否	Hostnames (or "*.example.com" wildcards) of the tools the visitor Keycloak token may be sent to
enableAnalysis	boolean	否	

請求結構範例

```
{
  "name": string
```

```
  "channelType": string (enum: line, telegram, teams, web, messenger, instagram, email, whatsapp,
slack, team_plus, line_works, viber) // * `line` - LINE
* `telegram` - Telegram
* `teams` - Teams
* `web` - Web
* `messenger` - Messenger
* `instagram` - Instagram
* `email` - Email
* `whatsapp` - WhatsApp
* `slack` - Slack
* `team_plus` - Team+
* `line_works` - LINE WORKS
* `viber` - Viber
  "unreadConversationsCount"?: integer // 非必填
  "signAuth"?:  // 非必填
  {
    "signSource": string (uuid)
    "signParams": {
    {
      "keycloak":
      {
        "clientId": string
        "url": string
        "realm": string
      }
      "line":
      {
        "liffId": string
      }
      "ad":
      {
        "saml": string
      }
      "google"?:  // 非必填
      {
        "enabled": boolean
      }
    }
    }
    "sourceIdAccessEnabled"?: boolean // When enabled, embedded visitors presenting a Source ID
(verified per the verify mode below) may chat without going through the login flow. Disabled keeps
every existing behavior unchanged. (非必填)
    "sourceIdVerifyMode"?:  // "Require signature verification": the embedding site must send an HMAC
signature computed on its backend. "Source ID only": anyone knowing a Source ID can act as that
contact; suitable only for testing or closed networks.

* `signature` - Require signature verification
* `raw` - Source ID only (非必填)
    {
    }
    "sourceIdSignatureTtlMinutes"?:  // How long a signature can be used to obtain the contact
identity. Not a session lifetime: once exchanged, the session follows the existing WebChat mechanism.

* `1` - 1
* `5` - 5
* `15` - 15 (非必填)
    {
    }
    "keycloakTokenPassthrough"?: boolean // When enabled, the Keycloak access token a visitor logged
in with is forwarded as the Authorization header when the AI calls MCP and API tools on their behalf,
```

```
so tools do not require a separate per-tool login. Only for the Keycloak sign source. Never overrides
an Authorization header a tool already resolves from its own credentials. The visitor identity is the
organization member bound to the conversation at login, never the contact Source ID. (非必填)
    "keycloakTokenPassthroughAllowedHosts"?: [ // Hostnames (or "*.example.com" wildcards) of the
tools the visitor Keycloak token may be sent to (非必填)
      string
    ]
  }
  "enableAnalysis"?: boolean // 非必填
}
```

請求範例值

```
{
  "chatbot": {
    "id": "80f3170d-eed7-4651-a8da-6b7e6bdbef8b"
  },
  "groups": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000"
    }
  ],
  "name": "更新後的名稱"
}
```

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X POST "https://api.maiagent.ai/api/v1/inboxes/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "chatbot": {
      "id": "80f3170d-eed7-4651-a8da-6b7e6bdbef8b"
    },
    "groups": [
      {
        "id": "550e8400-e29b-41d4-a716-446655440000"
      }
    ],
    "name": "更新後的名稱"
  }'

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// 請求內容 (payload)
const data = {
    "chatbot": {
      "id": "80f3170d-eed7-4651-a8da-6b7e6bdbef8b"
    },
    "groups": [
      {
        "id": "550e8400-e29b-41d4-a716-446655440000"
      }
    ],
    "name": "更新後的名稱"
  };

axios.post("https://api.maiagent.ai/api/v1/inboxes/", data, config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/inboxes/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# 請求內容 (payload)
data = {
    "chatbot": {
        "id": "80f3170d-eed7-4651-a8da-6b7e6bdbef8b"
    },
    "groups": [
        {
            "id": "550e8400-e29b-41d4-a716-446655440000"
        }
    ],
    "name": "更新後的名稱"
}

response = requests.post(url, json=data, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->post("https://api.maiagent.ai/api/v1/inboxes/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'chatbot' => [
                'id' => '80f3170d-eed7-4651-a8da-6b7e6bdbef8b'
            ],
            'groups' => [
                [
                    'id' => '550e8400-e29b-41d4-a716-446655440000'
                ]
            ],
            'name' => '更新後的名稱'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 201

回應結構範例

```
{
  "id": string (uuid)
  "name": string
  "channelType": string (enum: line, telegram, teams, web, messenger, instagram, email, whatsapp,
slack, team_plus, line_works, viber) // * `line` - LINE
* `telegram` - Telegram
* `teams` - Teams
* `web` - Web
```

```
* `messenger` - Messenger
* `instagram` - Instagram
* `email` - Email
* `whatsapp` - WhatsApp
* `slack` - Slack
* `team_plus` - Team+
* `line_works` - LINE WORKS
* `viber` - Viber
  "unreadConversationsCount"?: integer // 非必填
  "signAuth"?:  // 非必填
  {
    "id": string (uuid)
    "signSource": string (uuid)
    "signParams": {
    {
      "keycloak":
      {
        "clientId": string
        "url": string
        "realm": string
      }
      "line":
      {
        "liffId": string
      }
      "ad":
      {
        "saml": string
      }
      "google"?:  // 非必填
      {
        "enabled": boolean
      }
    }
    }
    "sourceIdAccessEnabled"?: boolean // When enabled, embedded visitors presenting a Source ID (verified per the verify mode below) may chat without going through the login flow. Disabled keeps every existing behavior unchanged. (非必填)
    "sourceIdVerifyMode"?:  // "Require signature verification": the embedding site must send an HMAC signature computed on its backend. "Source ID only": anyone knowing a Source ID can act as that contact; suitable only for testing or closed networks.

* `signature` - Require signature verification
* `raw` - Source ID only (非必填)
    {
    }
    "sourceIdSignatureTtlMinutes"?:  // How long a signature can be used to obtain the contact identity. Not a session lifetime: once exchanged, the session follows the existing WebChat mechanism.

* `1` - 1
* `5` - 5
* `15` - 15 (非必填)
    {
    }
    "keycloakTokenPassthrough"?: boolean // When enabled, the Keycloak access token a visitor logged in with is forwarded as the Authorization header when the AI calls MCP and API tools on their behalf, so tools do not require a separate per-tool login. Only for the Keycloak sign source. Never overrides an Authorization header a tool already resolves from its own credentials. The visitor identity is the organization member bound to the conversation at login, never the contact Source ID. (非必填)
    "keycloakTokenPassthroughAllowedHosts"?: [ // Hostnames (or "*.example.com" wildcards) of the
```

```
tools the visitor Keycloak token may be sent to (非必填)
      string
    ]
  }
  "enableAnalysis"?: boolean // 非必填
}
```

回應範例值


```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "name": "回應字串",
  "channelType": "line",
  "unreadConversationsCount": 456,
  "signAuth": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "signSource": "550e8400-e29b-41d4-a716-446655440000",
    "signParams": {
      "keycloak": {
        "clientId": "回應字串",
        "url": "回應字串",
        "realm": "回應字串"
      },
      "line": {
        "liffId": "回應字串"
      },
      "ad": {
        "saml": "回應字串"
      },
      "google": {
        "enabled": false
      }
    },
    "sourceIdAccessEnabled": false,
    "sourceIdVerifyMode": {},
    "sourceIdSignatureTtlMinutes": {},
    "keycloakTokenPassthrough": false,
    "keycloakTokenPassthroughAllowedHosts": [
      "回應字串"
    ]
  },
  "enableAnalysis": false
}
```


取得特定對話平台

`GET` `/api/v1/inboxes/{id}`

參數

參數名稱	必填	類型	說明
id	V	string	A UUID string identifying this Inbox.

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/inboxes/550e8400-e29b-41d4-a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/inboxes/550e8400-e29b-41d4-a716-446655440000/",
config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/inboxes/550e8400-e29b-41d4-a716-446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->get("https://api.maiagent.ai/api/v1/inboxes/550e8400-e29b-41d4-a716-
446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
{
  "id": string (uuid)
  "name": string
  "channelType": string (enum: line, telegram, teams, web, messenger, instagram, email, whatsapp,
slack, team_plus, line_works, viber) // * `line` - LINE
* `telegram` - Telegram
* `teams` - Teams
* `web` - Web
* `messenger` - Messenger
* `instagram` - Instagram
* `email` - Email
* `whatsapp` - WhatsApp
* `slack` - Slack
* `team_plus` - Team+
* `line_works` - LINE WORKS
* `viber` - Viber
  "unreadConversationsCount"?: integer // 非必填
  "signAuth"?:  // 非必填
  {
    "id": string (uuid)
    "signSource": string (uuid)
    "signParams": {
    {
      "keycloak":
      {
        "clientId": string
        "url": string
        "realm": string
      }
      "line":
      {
        "liffId": string
      }
      "ad":
      {
        "saml": string
      }
      "google"?:  // 非必填
      {
        "enabled": boolean
      }
    }
    }
    "sourceIdAccessEnabled"?: boolean // When enabled, embedded visitors presenting a Source ID
(verified per the verify mode below) may chat without going through the login flow. Disabled keeps
every existing behavior unchanged. (非必填)
    "sourceIdVerifyMode"?:  // "Require signature verification": the embedding site must send an HMAC
signature computed on its backend. "Source ID only": anyone knowing a Source ID can act as that
contact; suitable only for testing or closed networks.

* `signature` - Require signature verification
* `raw` - Source ID only (非必填)
    {
    }
    "sourceIdSignatureTtlMinutes"?:  // How long a signature can be used to obtain the contact
```

```
identity. Not a session lifetime: once exchanged, the session follows the existing WebChat mechanism.

* `1` - 1
* `5` - 5
* `15` - 15 (非必填)
    {
    }
    "keycloakTokenPassthrough"?: boolean // When enabled, the Keycloak access token a visitor logged in with is forwarded as the Authorization header when the AI calls MCP and API tools on their behalf, so tools do not require a separate per-tool login. Only for the Keycloak sign source. Never overrides an Authorization header a tool already resolves from its own credentials. The visitor identity is the organization member bound to the conversation at login, never the contact Source ID. (非必填)
    "keycloakTokenPassthroughAllowedHosts"?: [ // Hostnames (or "*.example.com" wildcards) of the tools the visitor Keycloak token may be sent to (非必填)
      string
    ]
  }
  "enableAnalysis"?: boolean // 非必填
}
```

回應範例值


```
{
  "id": "961dcaac-bd2e-44d3-9050-82596dbb3334",
  "chatbot": {
    "id": "80f3170d-eed7-4651-a8da-6b7e6bdbef8b",
    "name": "客服機器人",
    "groups": [],
    "largeLanguageModel": {
      "id": "933aa8b3-cdf4-47a7-86d5-b5dc27fbb044",
      "name": "llm"
    },
    "embeddingModel": {
      "id": "aefcc4f9-917d-4a8a-bd36-d97e3b7cecfe",
      "name": "embedding",
      "icon": null,
      "isDefault": false
    },
    "rerankerModel": {
      "id": "86c2ddfd-0df9-47b9-8f3b-0c42e3347da3",
      "name": "rerank",
      "icon": null,
      "isDefault": true
    },
    "knowledgeBases": [],
    "tools": [],
    "agentMode": "normal",
    "replyMode": "normal",
    "updatedAt": "1739519493000",
    "enableEvaluation": false,
    "enableInlineCitations": false,
    "enableKnowledgeBaseRag": true,
    "enableAgenticTextToSql": true,
    "enableToolSearching": true,
    "numberOfRetrievedChunks": 12
  },
  "groups": [
    {
```

```
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "管理員群組"
    }
  ],
  "channelType": "web",
  "channelTypeLabel": "Web",
  "name": "1345",
  "autoReplySchedules": [
    {
      "id": "2f4f6383-d8b5-4d88-b4a1-6d02d731f2a6",
      "weekday": 0,
      "isEnabled": true,
      "timeSlots": [
        [
          "00:00:00",
          "00:00:00"
        ]
      ],
      "weekdayName": "Monday"
    },
    {
      "id": "2866f624-a5c3-4ffb-b980-0f8d6a9f0c93",
      "weekday": 1,
      "isEnabled": true,
      "timeSlots": [
        [
          "00:00:00",
          "00:00:00"
        ]
      ],
      "weekdayName": "Tuesday"
    },
    {
      "id": "3cf1e488-fb13-426d-bd59-e62bd71aca85",
      "weekday": 2,
      "isEnabled": true,
      "timeSlots": [
        [
          "00:00:00",
          "00:00:00"
        ]
      ],
      "weekdayName": "Wednesday"
    },
    {
      "id": "491776a9-fcf1-4e2e-892f-6d9ad5aebea4",
      "weekday": 3,
      "isEnabled": true,
      "timeSlots": [
        [
          "00:00:00",
          "00:00:00"
        ]
      ],
      "weekdayName": "Thursday"
    },
    {
      "id": "dfecb0a9-5001-4aa0-b2cc-5459b6d64351",
      "weekday": 4,
      "isEnabled": true,
```

```
      "timeSlots": [
        [
          "00:00:00",
          "00:00:00"
        ]
      ],
      "weekdayName": "Friday"
    },
    {
      "id": "68b6b4d1-7ac8-450f-8877-41b72b499919",
      "weekday": 5,
      "isEnabled": true,
      "timeSlots": [
        [
          "00:00:00",
          "00:00:00"
        ]
      ],
      "weekdayName": "Saturday"
    },
    {
      "id": "15228ea1-4513-4504-81f4-4e486703d8b9",
      "weekday": 6,
      "isEnabled": true,
      "timeSlots": [
        [
          "00:00:00",
          "00:00:00"
        ]
      ],
      "weekdayName": "Sunday"
    }
  ],
  "unreadConversationsCount": 0,
  "totalConversationsCount": 42,
  "channel": {
    "id": "801a690a-1038-4fdd-8aba-bf003b12c3ef",
    "name": "1345",
    "avatar": "https://media-dev.maiagent.ai/static/images/default-chatbot-avatar.png",
    "logo": null,
    "description": "",
    "cover": null,
    "backUrl": "",
    "isActive": true,
    "enableSpeech": false,
    "displayGreeting": null,
    "displayConversationStarters": [],
    "theme": {
      "primaryColor": "#3854d8",
      "navbarTextColor": "#ffffff",
      "conversationBackgroundColor": "#ffffff",
      "chatbotMessageTextColor": "#374151",
      "userMessageTextColor": "#374151",
      "chatbotMessageBackgroundColor": "#DCE9F6",
      "userMessageBackgroundColor": "#DDEAF6",
      "chatbotMessageBackgroundShadowEnabled": true,
      "userMessageBackgroundShadowEnabled": true
    },
    "darkTheme": {
      "primaryColor": "#404040",
```

```
      "navbarTextColor": "#ffffff",
      "conversationBackgroundColor": "#18181B",
      "chatbotMessageTextColor": "#ffffff",
      "userMessageTextColor": "#ffffff",
      "chatbotMessageBackgroundColor": "#171717",
      "userMessageBackgroundColor": "#333842",
      "chatbotMessageBackgroundShadowEnabled": false,
      "userMessageBackgroundShadowEnabled": false
    },
    "enableFileUpload": true,
    "enableDisplayCitations": true,
    "enableShareConversation": false,
    "enableLocation": false,
    "enableShowPoweredBy": true,
    "enableDisplayChatbotAvatar": true,
    "enableDisplayChatbotName": true,
    "enableDisplayPreviousConversation": true,
    "enableDisplayConversationHistory": true,
    "enableConversationTimer": false,
    "conversationTimerDuration": null,
    "enableAutoNewConversationOnTimeout": false,
    "accessType": "api",
    "greetings": [],
    "greetingsByLocale": {
      "en": [
        "Hello, how can I help you?"
      ],
      "zh-hant": [
        "你好，我可以幫你什麼嗎？"
      ],
      "ja": [
        "こんにちは、何かお手伝いできますか？"
      ],
      "ko": [
        "안녕하세요, 무엇을 도와드릴까요?"
      ]
    },
    "conversationStarters": [],
    "conversationStartersByLocale": {
      "en": [
        "What can I help you with today?"
      ],
      "zh-hant": [
        "你今天需要什麼幫助？"
      ],
      "ja": [
        "今日は何かお手伝いできますか？"
      ],
      "ko": [
        "오늘 뭘 도와줄수있어？"
      ]
    }
  },
  "webhooks": [],
  "createdAt": "1739519493000",
  "updatedAt": "1739519493000",
  "organization": "24b619d9-e981-4a8b-96da-63dc4f96bda6",
  "signAuth": null
}
```

更新對話平台

PUT `/api/v1/inboxes/{id}`

參數

參數名稱	必填	類型	說明
`id`	V	string	A UUID string identifying this Inbox.

請求內容

請求參數

欄位	類型	必填	說明
name	string	是	
channelType	string (enum: line, telegram, teams, web, messenger, instagram, email, whatsapp, slack, team_plus, line_works, viber)	是	`line` : LINE ; `telegram` : Telegram ; `teams` : Teams ; `web` : Web ; `messenger` : Messenger ; `instagram` : Instagram ; `email` : Email ; `whatsapp` : WhatsApp ; `slack` : Slack ; `team_plus` : Team+ ; `lin...
unreadConversationsCount	integer	否	
signAuth	object (含 8 個屬性: id, signSource, signParams...)	否	
signAuth.signSource	string (uuid)	是	
signAuth.signParams	object	是	
signAuth.signParams.keycloak	object (含 3 個屬性: clientId, url, realm)	是	
signAuth.signParams.keycloak.clientId	string	是	
signAuth.signParams.keycloak.url	string	是	
signAuth.signParams.keycloak.realm	string	是	
signAuth.signParams.line	object (含 1 個屬性: liffId)	是	
signAuth.signParams.line.liffId	string	是	

欄位	類型	必填	說明
signAuth.signParams.ad	object (含 1 個屬性: saml)	是	
signAuth.signParams.ad.saml	string	是	
signAuth.signParams.google	object (含 1 個屬性: enabled)	否	
signAuth.signParams.google.enabled	boolean	是	
signAuth.sourceIdAccessEnabled	boolean	否	When enabled, embedded visitors presenting a Source ID (verified per the verify mode below) may chat without going through the login flow. Disabled keeps every existing behavior unchanged.
signAuth.sourceIdVerifyMode	object	否	"Require signature verification": the embedding site must send an HMAC signature computed on its backend. "Source ID only": anyone knowing a Source ID can act as that contact; suitable only for testin...
signAuth.sourceIdSignatureTtlMinutes	object	否	How long a signature can be used to obtain the contact identity. Not a session lifetime: once exchanged, the session follows the existing WebChat mechanism. `1` : 1 ; `5` : 5 ; `15` : 15;
signAuth.keycloakTokenPassthrough	boolean	否	When enabled, the Keycloak access token a visitor logged in with is forwarded as the Authorization header when the AI calls MCP and API tools on their behalf, so tools do not require a separate per-to...
signAuth.keycloakTokenPassthroughAllowedHosts	array[string]	否	Hostnames (or "*.example.com" wildcards) of the tools the visitor Keycloak token may be sent to
enableAnalysis	boolean	否	

請求結構範例

```
{
  "name": string
  "channelType": string (enum: line, telegram, teams, web, messenger, instagram, email, whatsapp,
slack, team_plus, line_works, viber) // * `line` - LINE
* `telegram` - Telegram
* `teams` - Teams
* `web` - Web
* `messenger` - Messenger
* `instagram` - Instagram
* `email` - Email
* `whatsapp` - WhatsApp
* `slack` - Slack
```

```
* `team_plus` - Team+
* `line_works` - LINE WORKS
* `viber` - Viber
  "unreadConversationsCount"?: integer // 非必填
  "signAuth"?:  // 非必填
  {
    "signSource": string (uuid)
    "signParams": {
    {
      "keycloak":
      {
        "clientId": string
        "url": string
        "realm": string
      }
      "line":
      {
        "liffId": string
      }
      "ad":
      {
        "saml": string
      }
      "google"?:  // 非必填
      {
        "enabled": boolean
      }
    }
    }
    "sourceIdAccessEnabled"?: boolean // When enabled, embedded visitors presenting a Source ID (verified per the verify mode below) may chat without going through the login flow. Disabled keeps every existing behavior unchanged. (非必填)
    "sourceIdVerifyMode"?:  // "Require signature verification": the embedding site must send an HMAC signature computed on its backend. "Source ID only": anyone knowing a Source ID can act as that contact; suitable only for testing or closed networks.

* `signature` - Require signature verification
* `raw` - Source ID only (非必填)
    {
    }
    "sourceIdSignatureTtlMinutes"?:  // How long a signature can be used to obtain the contact identity. Not a session lifetime: once exchanged, the session follows the existing WebChat mechanism.

* `1` - 1
* `5` - 5
* `15` - 15 (非必填)
    {
    }
    "keycloakTokenPassthrough"?: boolean // When enabled, the Keycloak access token a visitor logged in with is forwarded as the Authorization header when the AI calls MCP and API tools on their behalf, so tools do not require a separate per-tool login. Only for the Keycloak sign source. Never overrides an Authorization header a tool already resolves from its own credentials. The visitor identity is the organization member bound to the conversation at login, never the contact Source ID. (非必填)
    "keycloakTokenPassthroughAllowedHosts"?: [ // Hostnames (or "*.example.com" wildcards) of the tools the visitor Keycloak token may be sent to (非必填)
      string
    ]
  }
```

```
  "enableAnalysis"?: boolean // 非必填
}
```

請求範例值

```
{
  "chatbot": {
    "id": "80f3170d-eed7-4651-a8da-6b7e6bdbef8b"
  },
  "groups": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000"
    }
  ],
  "name": "更新後的名稱"
}
```

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X PUT "https://api.maiagent.ai/api/v1/inboxes/550e8400-e29b-41d4-a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "chatbot": {
      "id": "80f3170d-eed7-4651-a8da-6b7e6bdbef8b"
    },
    "groups": [
      {
        "id": "550e8400-e29b-41d4-a716-446655440000"
      }
    ],
    "name": "更新後的名稱"
  }'

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// 請求內容 (payload)
const data = {
    "chatbot": {
      "id": "80f3170d-eed7-4651-a8da-6b7e6bdbef8b"
    },
    "groups": [
      {
        "id": "550e8400-e29b-41d4-a716-446655440000"
      }
    ],
    "name": "更新後的名稱"
  };

axios.put("https://api.maiagent.ai/api/v1/inboxes/550e8400-e29b-41d4-a716-446655440000/", data,
config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/inboxes/550e8400-e29b-41d4-a716-446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# 請求內容 (payload)
data = {
    "chatbot": {
        "id": "80f3170d-eed7-4651-a8da-6b7e6bdbef8b"
    },
    "groups": [
        {
            "id": "550e8400-e29b-41d4-a716-446655440000"
        }
    ],
    "name": "更新後的名稱"
}

response = requests.put(url, json=data, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->put("https://api.maiagent.ai/api/v1/inboxes/550e8400-e29b-41d4-a716-
446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'chatbot' => [
                'id' => '80f3170d-eed7-4651-a8da-6b7e6bdbef8b'
            ],
            'groups' => [
                [
                    'id' => '550e8400-e29b-41d4-a716-446655440000'
                ]
            ],
            'name' => '更新後的名稱'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
{
  "id": string (uuid)
  "name": string
  "channelType": string (enum: line, telegram, teams, web, messenger, instagram, email, whatsapp,
slack, team_plus, line_works, viber) // * `line` - LINE
* `telegram` - Telegram
* `teams` - Teams
```

```
* `web` - Web
* `messenger` - Messenger
* `instagram` - Instagram
* `email` - Email
* `whatsapp` - WhatsApp
* `slack` - Slack
* `team_plus` - Team+
* `line_works` - LINE WORKS
* `viber` - Viber
  "unreadConversationsCount"?: integer // 非必填
  "signAuth"?:  // 非必填
  {
    "id": string (uuid)
    "signSource": string (uuid)
    "signParams": {
    {
      "keycloak":
      {
        "clientId": string
        "url": string
        "realm": string
      }
      "line":
      {
        "liffId": string
      }
      "ad":
      {
        "saml": string
      }
      "google"?:  // 非必填
      {
        "enabled": boolean
      }
    }
    }
    "sourceIdAccessEnabled"?: boolean // When enabled, embedded visitors presenting a Source ID (verified per the verify mode below) may chat without going through the login flow. Disabled keeps every existing behavior unchanged. (非必填)
    "sourceIdVerifyMode"?:  // "Require signature verification": the embedding site must send an HMAC signature computed on its backend. "Source ID only": anyone knowing a Source ID can act as that contact; suitable only for testing or closed networks.

* `signature` - Require signature verification
* `raw` - Source ID only (非必填)
    {
    }
    "sourceIdSignatureTtlMinutes"?:  // How long a signature can be used to obtain the contact identity. Not a session lifetime: once exchanged, the session follows the existing WebChat mechanism.

* `1` - 1
* `5` - 5
* `15` - 15 (非必填)
    {
    }
    "keycloakTokenPassthrough"?: boolean // When enabled, the Keycloak access token a visitor logged in with is forwarded as the Authorization header when the AI calls MCP and API tools on their behalf, so tools do not require a separate per-tool login. Only for the Keycloak sign source. Never overrides an Authorization header a tool already resolves from its own credentials. The visitor identity is the organization member bound to the conversation at login, never the contact Source ID. (非必填)
```

```
    "keycloakTokenPassthroughAllowedHosts"?: [ // Hostnames (or "*.example.com" wildcards) of the
tools the visitor Keycloak token may be sent to (非必填)
      string
    ]
  }
  "enableAnalysis"?: boolean // 非必填
}
```

回應範例值


```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "name": "回應字串",
  "channelType": "line",
  "unreadConversationsCount": 456,
  "signAuth": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "signSource": "550e8400-e29b-41d4-a716-446655440000",
    "signParams": {
      "keycloak": {
        "clientId": "回應字串",
        "url": "回應字串",
        "realm": "回應字串"
      },
      "line": {
        "liffId": "回應字串"
      },
      "ad": {
        "saml": "回應字串"
      },
      "google": {
        "enabled": false
      }
    },
    "sourceIdAccessEnabled": false,
    "sourceIdVerifyMode": {},
    "sourceIdSignatureTtlMinutes": {},
    "keycloakTokenPassthrough": false,
    "keycloakTokenPassthroughAllowedHosts": [
      "回應字串"
    ]
  },
  "enableAnalysis": false
}
```


部分更新對話平台

PATCH `/api/v1/inboxes/{id}`

參數

參數名稱	必填	類型	說明
`id`	V	string	A UUID string identifying this Inbox.

請求內容

請求參數

欄位	類型	必填	說明
groups	array[IdName]	否	可存取此收件匣的群組列表
channelType	string (enum: line, telegram, teams, web, messenger, instagram, email, whatsapp, slack, team_plus, line_works, viber)	否	`line` : LINE ; `telegram` : Telegram ; `teams` : Teams ; `web` : Web ; `messenger` : Messenger ; `instagram` : Instagram ; `email` : Email ; `whatsapp` : WhatsApp ; `slack` : Slack ; `team_plus` : Team+ ; `lin...
name	string	否	
autoReplySchedules	array[AutoReplySchedule]	否	
channel	object	否	
organization	string (uuid)	否	
signAuth	object (含 9 個屬性: id, signSource, signParams...)	否	
signAuth.signSource	string (uuid)	是	
signAuth.signParams	object	是	
signAuth.signParams.keycloak	object (含 3 個屬性: clientId, url, realm)	是	
signAuth.signParams.keycloak.clientId	string	是	
signAuth.signParams.keycloak.url	string	是	
signAuth.signParams.keycloak.realm	string	是	
signAuth.signParams.line	object (含 1 個屬性: liffId)	是	
signAuth.signParams.line.liffId	string	是	
signAuth.signParams.ad	object (含 1 個屬性: saml)	是	
signAuth.signParams.ad.saml	string	是	
signAuth.signParams.google	object (含 1 個屬性: enabled)	否	
signAuth.signParams.google.enabled	boolean	是	

欄位	類型	必填	說明
signAuth.sourceIdAccessEnabled	boolean	否	When enabled, embedded visitors presenting a Source ID (verified per the verify mode below) may chat without going through the login flow. Disabled keeps every existing behavior unchanged.
signAuth.sourceIdVerifyMode	object	否	"Require signature verification": the embedding site must send an HMAC signature computed on its backend. "Source ID only": anyone knowing a Source ID can act as that contact; suitable only for testin...
signAuth.sourceIdSignatureTtlMinutes	object	否	How long a signature can be used to obtain the contact identity. Not a session lifetime: once exchanged, the session follows the existing WebChat mechanism. `1` : 1 ; `5` : 5 ; `15` : 15;
signAuth.keycloakTokenPassthrough	boolean	否	When enabled, the Keycloak access token a visitor logged in with is forwarded as the Authorization header when the AI calls MCP and API tools on their behalf, so tools do not require a separate per-to...
signAuth.keycloakTokenPassthroughAllowedHosts	array[string]	否	Hostnames (or "*.example.com" wildcards) of the tools the visitor Keycloak token may be sent to
enableTimeAwareResponse	boolean	否	Enable time aware responses for this inbox
defaultTimezone	string	否	Default timezone for this inbox (e.g., Asia/Taipei, America/New_York)
enableSenderNameAwareResponse	boolean	否	Enable sender name aware responses for this inbox
enableGpsAwareResponse	boolean	否	Enable GPS aware responses for this inbox
enableOcr	boolean	否	Enable OCR parser, prioritize OCR-enabled parsers when uploading attachments
enableAgentAttachmentDecision	boolean	否	Kill switch for AGENT-mode attachment handling. When False (default), AGENT-mode chatbots skip auto-embedding on upload and let the agent handle attachments at runtime via ParseAttachmentContentTool /...
enableStreamMessage	boolean	否	
enableHumanHandoff	boolean	否	

欄位	類型	必填	說明
handoffPrompt	string	否	
handoffLlm	string (uuid)	否	
handoffContextMessageLimit	integer	否	
handoffMessage	string	否	
queuingMessage	string	否	
assignedMessage	string	否	
enablePendingReplyMessage	boolean	否	Send a placeholder message to the user while the AI is processing.
pendingReplyMessage	string	否	
pendingReplyInitialDelaySeconds	integer	否	Delay before sending the first pending reply, so a fast AI response can pre-empt it.
pendingReplyIntervalSeconds	integer	否	Interval to repeat the pending reply while the AI is still processing.
enablePendingReplyCleanup	boolean	否	Delete pending reply messages after the AI reply is sent. Only effective on platforms that support message deletion (Teams, Telegram, Slack).
enableAnalysis	boolean	否	
analysisLlm	string (uuid)	否	
analysisPrompt	string	否	
analysisContextMessageLimit	integer	否	
enableServiceHours	boolean	否	
serviceHoursTimezone	string	否	
offlineBehavior	string (enum: show_message, leave_message)	否	`show_message` : Show Message ; `leave_message` : Leave Message;
offlineMessage	string	否	
serviceHoursSchedules	array[ServiceHoursSchedule]	否	
dispatchMode	object	否	Auto dispatch assigns transferred conversations to an agent automatically. Claim (handover) leaves them unassigned for online agents to pick up themselves; timeout reassignment does not apply and the ...
assignmentRoutingModel	string (enum: round_robin, least_active)	否	`round_robin` : Round Robin ; `least_active` : Least Active;
assignmentMaxConcurrent	integer	否	

欄位	類型	必填	說明
assignmentQueueTimeout	integer	否	Queue timeout in seconds
queueTimeoutMessage	string	否	
maxQueueSize	integer	否	
queueFullMessage	string	否	
assignmentTargetMembers	array[string]	否	
enableTagRouting	boolean	否	
enableReassignOnTimeout	boolean	否	When on, a queued or assigned-but-unanswered conversation that times out is reassigned to the next available agent (skipping already-tried agents) instead of returning straight to the AI; it only retu...
enableQueueReminder	boolean	否	Reply with a throttled waiting reminder when the contact sends messages while queued.
queueReminderMessage	string	否	
queueReminderCooldown	integer	否	Minimum seconds between queue reminders in one conversation
enableQueueCancel	boolean	否	Allow the contact to cancel a queued handoff and return to the AI by themselves.
queueCancelButtonText	string	否	Label of the cancel quick-reply button. Its text also counts as a cancel keyword, so tapping the button always cancels even when the keyword list changes.
queueCancelKeywords	object	否	Messages matching one of these exactly (after stripping surrounding whitespace) cancel the queued handoff. Empty means no keyword matching (the cancel button text still matches); the serializer requir...
queueCancelMessage	string	否	Sent to the contact right after they cancel the queued handoff.
enableAgentReplyTimeout	boolean	否	When on, a conversation served by a human agent returns to the AI once a contact message has gone unanswered by any agent for the configured seconds; the AI then answers the last unanswered message. A...
agentReplyTimeout	integer	否	Seconds (60-86400) a contact message may go unanswered by a human agent before the AI takes over

欄位	類型	必填	說明
agentReplyTimeoutMessage	string	否	Sent to the contact when the conversation returns to the AI; leave empty to send none.
enableReturnToPreviousAssignee	boolean	否	When on, a resolved conversation the contact writes to again within the configured hours reopens assigned to the agent who held it instead of to the AI. It still reopens to the AI when that agent is o...
returnToPreviousAssigneeHours	integer	否	Hours (1-720), counted from when the conversation was resolved, during which a returning contact goes back to the agent who held it
copilotEnabled	boolean	否	
copilotTriggerMode	string (enum: manual, every_incoming)	否	`manual` : Manual ; `every_incoming` : Every Incoming;
quotaExceededMessage	string	否	Custom message sent to the visitor when the inbox credit quota is exhausted. Used as the fallback when `quota_exceeded_message_by_locale` has no match for the conversation locale. Empty means the syst...
quotaExceededMessageByLocale	object	否	Locale-keyed quota-exceeded messages. A dict mapping normalized locale codes from CHAT_LANGUAGES (e.g. "en", "zh-hant", "ja") to a message string. Selected by the conversation locale; falls back to `q...

請求結構範例

```
{
  "groups"?: [ // 可存取此收件匣的群組列表 (非必填)
    {
      "id": string (uuid)
    }
  ]
  "channelType"?: string (enum: line, telegram, teams, web, messenger, instagram, email, whatsapp,
slack, team_plus, line_works, viber) // * `line` - LINE
* `telegram` - Telegram
* `teams` - Teams
* `web` - Web
* `messenger` - Messenger
* `instagram` - Instagram
* `email` - Email
* `whatsapp` - WhatsApp
* `slack` - Slack
* `team_plus` - Team+
* `line_works` - LINE WORKS
* `viber` - Viber (非必填)
```

```
  "name"?: string // 非必填
  "autoReplySchedules"?: [ // 非必填
    {
      "isEnabled"?: boolean // 非必填
      "timeSlots"?: [ // 非必填
        array[string]
      ]
    }
  ]
  "channel"?: // 可能有不同的類型 (非必填)
  {
    "avatar"?: string (uri) // 非必填
    "logo"?: string (uri) // 非必填
    "description"?: string // 非必填
    "cover"?: string (uri) // 非必填
    "backUrl"?: string // 非必填
    "isActive"?: boolean // 非必填
    "theme": {
    {
      "primaryColor"?: string // 非必填
      "navbarTextColor"?: string // 非必填
      "conversationBackgroundColor"?: string // 非必填
      "chatbotMessageTextColor"?: string // 非必填
      "userMessageTextColor"?: string // 非必填
      "chatbotMessageBackgroundColor"?: string // 非必填
      "userMessageBackgroundColor"?: string // 非必填
      "chatbotMessageBackgroundShadowEnabled"?: boolean // 非必填
      "userMessageBackgroundShadowEnabled"?: boolean // 非必填
      "chatbotMessageGradientEnabled"?: boolean // 非必填
      "userMessageGradientEnabled"?: boolean // 非必填
    }
    }
    "darkTheme": {
    {
      "primaryColor"?: string // 非必填
      "navbarTextColor"?: string // 非必填
      "conversationBackgroundColor"?: string // 非必填
      "chatbotMessageTextColor"?: string // 非必填
      "userMessageTextColor"?: string // 非必填
      "chatbotMessageBackgroundColor"?: string // 非必填
      "userMessageBackgroundColor"?: string // 非必填
      "chatbotMessageBackgroundShadowEnabled"?: boolean // 非必填
      "userMessageBackgroundShadowEnabled"?: boolean // 非必填
      "chatbotMessageGradientEnabled"?: boolean // 非必填
      "userMessageGradientEnabled"?: boolean // 非必填
    }
    }
    "enableFileUpload"?: boolean // 非必填
    "enableDisplayCitations"?: boolean // 非必填
    "toolDisplayMode"?: string (enum: full, compact, hidden) // * `full` - Full
* `compact` - Compact
* `hidden` - Hidden (非必填)
    "enableAskOptionButtons"?: boolean // 開啟後 ask_user_question 選項以按鈕列浮在輸入框上方（輸入框保持可用）；關閉則維持現行覆蓋式面板。灰度開關，可隨時關閉回退。 (非必填)
    "enableConversationHandoff"?: boolean // 開啟後此對話平台的 webchat 顯示交接 UI（提示條、摘要卡、接續按鈕）並註冊交接工具；仍受系統設定的全域交接開關管制（全域關＝一律關）。MaiGPT 免此開關恆顯示。底部的上下文使用量百分比條另由「顯示上下文使用量」控制。預設關閉，客戶對外 webchat 不會看到任何交接 UI；灰度開關，關閉即回退、不需退版。 (非必填)
    "enableDisplayContextUsage"?: boolean // 開啟後此對話平台的 webchat 在輸入框下方顯示上下文使用量百分比條。與對話交接互相獨立：不受交接開關（含全域交接開關）影響，也不影響交接提示條。MaiGPT 免此開關恆顯示。預設關閉；關閉即回退、不需退版。 (非必填)
```

```
    "enableDisplayThinking"?: boolean // 非必填
    "enableUserThinkingControl"?: boolean // 非必填
    "enableDisplayQueryMetadata"?: boolean // 非必填
    "enableDisplayHookMarkers"?: boolean // 非必填
    "hookMarkerTextInputModify"?: string // 非必填
    "hookMarkerTextOutputModify"?: string // 非必填
    "hookMarkerTextInputBlock"?: string // 非必填
    "hookMarkerTextOutputBlock"?: string // 非必填
    "enableShareConversation"?: boolean // 非必填
    "enableLocation"?: boolean // 非必填
    "enableShowPoweredBy"?: boolean // 非必填
    "poweredByLogo"?: string (uri) // 非必填
    "enableAnonymous"?: boolean // 非必填
    "enableDisplayPreviousConversation"?: boolean // 非必填
    "enableDisplayConversationHistory"?: boolean // 非必填
    "enableConversationTimer"?: boolean // 非必填
    "conversationTimerDuration"?: integer // 計時器逾時時長，範圍 3-60 分鐘 (非必填)
    "enableAutoNewConversationOnTimeout"?: boolean // 非必填
    "enableSatisfactionSurvey"?: boolean // 非必填
    "satisfactionSurveyDelayMinutes"?: integer // 最後一則 AI 回覆後幾分鐘彈出問卷，範圍 1-60 分鐘 (非必填)
    "satisfactionSurveyPrompt"?: string // 自訂問卷標題文字，留空則使用前端多語系預設文字 (非必填)
    "enableThemeModeToggle"?: boolean // 非必填
    "enableDisplayFontSizeSwitch"?: boolean // 非必填
    "defaultThemeMode"?:  // 非必填
    {
    }
    "enableDownloadCitations"?: boolean // 非必填
    "customDomain"?:  // 非必填
    {
      "domain": string
    }
    "enableDisplayChatbotAvatar"?: boolean // 非必填
    "enableDisplayChatbotName"?: boolean // 非必填
    "buttonIcon"?: string (uri) // 非必填
    "conversationStartersDisplayCount"?: integer // 非必填
    "includeGreetingInContext"?: boolean // When enabled, the conversation greeting and the numbered
conversation starters (in configured order, unshuffled and untruncated) are injected into the LLM
context so the agent can resolve short replies like "1" to the matching starter option. (非必填)
    "preChatFormEnabled"?: boolean // 非必填
    "preChatFormFields"?: object // 非必填
    "preChatFormTitle"?: object // 非必填
    "preChatFormSubtitle"?: object // 非必填
    "loadingDisplayMode"?:  // Waiting-experience style. `narrative` shows per-stage copy;
`brand_animation` plays the uploaded asset and hides every system narration line. Defaults to
`narrative`, which with no copy configured behaves exactly as before this field existed.

* `narrative` - Narrative copy
* `brand_animation` - Brand animation (非必填)
    {
    }
    "loadingStageCopyByLocale"?: object // Locale-keyed per-stage waiting copy, shaped {locale:
{stage: text}} where stage is one of LoadingStage. An absent locale or stage falls back to the built-
in copy, so a partially filled dict is valid and never blocks a reply. (非必填)
    "loadingLongWaitCopyByLocale"?: object // Locale-keyed line shown once the wait exceeds
`loading_long_wait_threshold_seconds`, shaped {locale: text}. Written in the brand character voice
for the animation mode, but applies to both modes. Empty means no long-wait line is shown. (非必填)
    "loadingLongWaitThresholdSeconds"?: integer // How long a single reply must be pending before the
long-wait copy appears. (非必填)
    "loadingAnimationUseSharedAsset"?: boolean // True (default) means every stage plays
`loading_animation_shared_asset_url`, so the admin only uploads once. False expands per-stage assets,
```

```
each falling back to the shared asset when its own slot is empty. (非必填)
    "loadingAnimationSharedAssetUrl"?: string (uri) // 非必填
    "loadingAnimationAssetUrlsByStage"?: object // Shaped {stage: url} keyed by LoadingStage. Only
consulted when `loading_animation_use_shared_asset` is False; a missing stage falls back to the
shared asset. (非必填)
    "loadingTypingShowCopy"?: boolean // Only affects the first "typing" stage. True (default, the
pre-existing behavior) shows the typing-stage copy next to the pre-first-char animation/dot; False
plays only the animation with no text line. Thinking / analyzing / long-wait stages are unaffected.
(非必填)
    "toolCardRunningIconUrl"?: string (uri) // 非必填
    "toolCardCompletedIconUrl"?: string (uri) // 非必填
    "greetings"?: [ // Default greeting messages shown as the AI first message when a new
conversation starts. One message is randomly selected per conversation. Used as the fallback when
`greetings_by_locale` has no match for the request locale. (非必填)
      string
    ]
    "greetingsByLocale"?: object // Locale-keyed greetings. A dict mapping locale codes to a list of
greeting strings (e.g. keys like "en", "zh-TW", "ja"). Selected by the conversation request Accept-
Language header; falls back to `greetings` when no locale matches. (非必填)
    "voiceGreetings"?: [ // Greeting messages spoken aloud when a voice session starts. One message
is randomly selected per session. The spoken greeting is ephemeral and NOT written back to
conversation history. Used as the fallback when `voice_greetings_by_locale` has no match for the
request locale. (非必填)
      string
    ]
    "voiceGreetingsByLocale"?: object // Locale-keyed voice greetings. A dict mapping locale codes to
a list of greeting strings. Selected by the Accept-Language header; falls back to `voice_greetings`
when no locale matches. (非必填)
    "conversationStarters"?: [ // Default suggested questions shown to the end-user as clickable
prompts at the start of a conversation. Used as the fallback when `conversation_starters_by_locale`
has no match for the request locale. (非必填)
      string
    ]
    "conversationStartersByLocale"?: object // Locale-keyed conversation starters. A dict mapping
locale codes to a list of starter strings (e.g. keys like "en", "zh-TW", "ja"). Selected by the
Accept-Language header; falls back to `conversation_starters` when no locale matches. (非必填)
    "allowedEmbedOrigins"?: [ // Origins allowed to embed this web chat and call the SDK contact-
setup endpoint. Each entry is either an exact origin (scheme://host[:port], e.g. https://example.com)
or a wildcard (*.example.com) that matches example.com and all of its subdomains on any scheme/port.
An empty list means no restriction. Validated against the embedding page origin forwarded by the web
chat frontend; bounds unauthorized-domain embedding. Browser-level enforcement (CSP frame-ancestors
on the entry page) additionally requires an AWS/CloudFront deployment; on GCP storage the allowlist
is enforced by the API alone. WARNING: leave empty until the web chat frontend forwards the embedding
origin, otherwise setup calls fall back to the web chat host origin and every request is rejected. (非
必填)
      string
    ]
  }
  "organization"?: string (uuid) // 非必填
  "signAuth"?:  // 非必填
  {
    "signSource": string (uuid)
    "signParams": {
    {
      "keycloak":
      {
        "clientId": string
        "url": string
        "realm": string
      }
```

```
      "line":
      {
        "liffId": string
      }
      "ad":
      {
        "saml": string
      }
      "google"?:  // 非必填
      {
        "enabled": boolean
      }
    }
    }
    "sourceIdAccessEnabled"?: boolean // When enabled, embedded visitors presenting a Source ID (verified per the verify mode below) may chat without going through the login flow. Disabled keeps every existing behavior unchanged. (非必填)
    "sourceIdVerifyMode"?:  // "Require signature verification": the embedding site must send an HMAC signature computed on its backend. "Source ID only": anyone knowing a Source ID can act as that contact; suitable only for testing or closed networks.

* `signature` - Require signature verification
* `raw` - Source ID only (非必填)
    {
    }
    "sourceIdSignatureTtlMinutes"?:  // How long a signature can be used to obtain the contact identity. Not a session lifetime: once exchanged, the session follows the existing WebChat mechanism.

* `1` - 1
* `5` - 5
* `15` - 15 (非必填)
    {
    }
    "keycloakTokenPassthrough"?: boolean // When enabled, the Keycloak access token a visitor logged in with is forwarded as the Authorization header when the AI calls MCP and API tools on their behalf, so tools do not require a separate per-tool login. Only for the Keycloak sign source. Never overrides an Authorization header a tool already resolves from its own credentials. The visitor identity is the organization member bound to the conversation at login, never the contact Source ID. (非必填)
    "keycloakTokenPassthroughAllowedHosts"?: [ // Hostnames (or "*.example.com" wildcards) of the tools the visitor Keycloak token may be sent to (非必填)
      string
    ]
  }
  "enableTimeAwareResponse"?: boolean // Enable time aware responses for this inbox (非必填)
  "defaultTimezone"?: string // Default timezone for this inbox (e.g., Asia/Taipei, America/New_York) (非必填)
  "enableSenderNameAwareResponse"?: boolean // Enable sender name aware responses for this inbox (非必填)
  "enableGpsAwareResponse"?: boolean // Enable GPS aware responses for this inbox (非必填)
  "enableOcr"?: boolean // Enable OCR parser, prioritize OCR-enabled parsers when uploading attachments (非必填)
  "enableAgentAttachmentDecision"?: boolean // Kill switch for AGENT-mode attachment handling. When False (default), AGENT-mode chatbots skip auto-embedding on upload and let the agent handle attachments at runtime via ParseAttachmentContentTool / IngestAttachmentTool. When True, AGENT-mode chatbots fall back to auto-embedding chat attachments into the knowledge base on upload, same as non-AGENT modes. Has no effect on non-AGENT chatbot modes (they always auto-embed). (非必填)
  "enableStreamMessage"?: boolean // 非必填
  "enableHumanHandoff"?: boolean // 非必填
  "handoffPrompt"?: string // 非必填
  "handoffLlm"?: string (uuid) // 非必填
```

```
  "handoffContextMessageLimit"?: integer // 非必填
  "handoffMessage"?: string // 非必填
  "queuingMessage"?: string // 非必填
  "assignedMessage"?: string // 非必填
  "enablePendingReplyMessage"?: boolean // Send a placeholder message to the user while the AI is
processing. (非必填)
  "pendingReplyMessage"?: string // 非必填
  "pendingReplyInitialDelaySeconds"?: integer // Delay before sending the first pending reply, so a
fast AI response can pre-empt it. (非必填)
  "pendingReplyIntervalSeconds"?: integer // Interval to repeat the pending reply while the AI is
still processing. (非必填)
  "enablePendingReplyCleanup"?: boolean // Delete pending reply messages after the AI reply is sent.
Only effective on platforms that support message deletion (Teams, Telegram, Slack). (非必填)
  "enableAnalysis"?: boolean // 非必填
  "analysisLlm"?: string (uuid) // 非必填
  "analysisPrompt"?: string // 非必填
  "analysisContextMessageLimit"?: integer // 非必填
  "enableServiceHours"?: boolean // 非必填
  "serviceHoursTimezone"?: string // 非必填
  "offlineBehavior"?: string (enum: show_message, leave_message) // * `show_message` - Show Message
* `leave_message` - Leave Message (非必填)
  "offlineMessage"?: string // 非必填
  "serviceHoursSchedules"?: [ // 非必填
    {
      "weekday": integer
      "startTime": string (time)
      "endTime": string (time)
      "isEnabled"?: boolean // 非必填
    }
  ]
  "dispatchMode"?:  // Auto dispatch assigns transferred conversations to an agent automatically.
Claim (handover) leaves them unassigned for online agents to pick up themselves; timeout reassignment
does not apply and the queue timeout may be set to "no timeout".

* `auto` - Auto Dispatch
* `handover` - Claim (Handover) (非必填)
  {
  }
  "assignmentRoutingModel"?: string (enum: round_robin, least_active) // * `round_robin` - Round
Robin
* `least_active` - Least Active (非必填)
  "assignmentMaxConcurrent"?: integer // 非必填
  "assignmentQueueTimeout"?: integer // Queue timeout in seconds (非必填)
  "queueTimeoutMessage"?: string // 非必填
  "maxQueueSize"?: integer // 非必填
  "queueFullMessage"?: string // 非必填
  "assignmentTargetMembers"?: [ // 非必填
    string (uuid)
  ]
  "enableTagRouting"?: boolean // 非必填
  "enableReassignOnTimeout"?: boolean // When on, a queued or assigned-but-unanswered conversation
that times out is reassigned to the next available agent (skipping already-tried agents) instead of
returning straight to the AI; it only returns to the AI once no agent is left to try. (非必填)
  "enableQueueReminder"?: boolean // Reply with a throttled waiting reminder when the contact sends
messages while queued. (非必填)
  "queueReminderMessage"?: string // 非必填
  "queueReminderCooldown"?: integer // Minimum seconds between queue reminders in one conversation (非
必填)
  "enableQueueCancel"?: boolean // Allow the contact to cancel a queued handoff and return to the AI
by themselves. (非必填)
```

```
  "queueCancelButtonText"?: string // Label of the cancel quick-reply button. Its text also counts as a cancel keyword, so tapping the button always cancels even when the keyword list changes. (非必填)
  "queueCancelKeywords"?: object // Messages matching one of these exactly (after stripping surrounding whitespace) cancel the queued handoff. Empty means no keyword matching (the cancel button text still matches); the serializer requires at least one keyword while queue cancel is enabled. (非必填)
  "queueCancelMessage"?: string // Sent to the contact right after they cancel the queued handoff. (非必填)
  "enableAgentReplyTimeout"?: boolean // When on, a conversation served by a human agent returns to the AI once a contact message has gone unanswered by any agent for the configured seconds; the AI then answers the last unanswered message. Auto-dispatched conversations the agent has not answered yet are left to timeout reassignment while that is enabled. (非必填)
  "agentReplyTimeout"?: integer // Seconds (60-86400) a contact message may go unanswered by a human agent before the AI takes over (非必填)
  "agentReplyTimeoutMessage"?: string // Sent to the contact when the conversation returns to the AI; leave empty to send none. (非必填)
  "enableReturnToPreviousAssignee"?: boolean // When on, a resolved conversation the contact writes to again within the configured hours reopens assigned to the agent who held it instead of to the AI. It still reopens to the AI when that agent is offline, paused, off duty, no longer an active member with access to this inbox, or the inbox is outside its service hours. (非必填)
  "returnToPreviousAssigneeHours"?: integer // Hours (1-720), counted from when the conversation was resolved, during which a returning contact goes back to the agent who held it (非必填)
  "copilotEnabled"?: boolean // 非必填
  "copilotTriggerMode"?: string (enum: manual, every_incoming) // * `manual` - Manual * `every_incoming` - Every Incoming (非必填)
  "quotaExceededMessage"?: string // Custom message sent to the visitor when the inbox credit quota is exhausted. Used as the fallback when `quota_exceeded_message_by_locale` has no match for the conversation locale. Empty means the system default message is used. (非必填)
  "quotaExceededMessageByLocale"?: object // Locale-keyed quota-exceeded messages. A dict mapping normalized locale codes from CHAT_LANGUAGES (e.g. "en", "zh-hant", "ja") to a message string. Selected by the conversation locale; falls back to `quota_exceeded_message`. (非必填)
}
```

請求範例值

```
{
  "chatbot": {
    "id": "80f3170d-eed7-4651-a8da-6b7e6bdbef8b"
  },
  "groups": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000"
    }
  ],
  "name": "更新後的名稱"
}
```

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X PATCH "https://api.maiagent.ai/api/v1/inboxes/550e8400-e29b-41d4-a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "chatbot": {
      "id": "80f3170d-eed7-4651-a8da-6b7e6bdbef8b"
    },
    "groups": [
      {
        "id": "550e8400-e29b-41d4-a716-446655440000"
      }
    ],
    "name": "更新後的名稱"
  }'

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// 請求內容 (payload)
const data = {
    "chatbot": {
      "id": "80f3170d-eed7-4651-a8da-6b7e6bdbef8b"
    },
    "groups": [
      {
        "id": "550e8400-e29b-41d4-a716-446655440000"
      }
    ],
    "name": "更新後的名稱"
  };

axios.patch("https://api.maiagent.ai/api/v1/inboxes/550e8400-e29b-41d4-a716-446655440000/",
data, config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/inboxes/550e8400-e29b-41d4-a716-446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# 請求內容 (payload)
data = {
    "chatbot": {
        "id": "80f3170d-eed7-4651-a8da-6b7e6bdbef8b"
    },
    "groups": [
        {
            "id": "550e8400-e29b-41d4-a716-446655440000"
        }
    ],
    "name": "更新後的名稱"
}

response = requests.patch(url, json=data, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->patch("https://api.maiagent.ai/api/v1/inboxes/550e8400-e29b-41d4-a716-446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'chatbot' => [
                'id' => '80f3170d-eed7-4651-a8da-6b7e6bdbef8b'
            ],
            'groups' => [
                [
                    'id' => '550e8400-e29b-41d4-a716-446655440000'
                ]
            ],
            'name' => '更新後的名稱'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
{
  "id": string (uuid)
  "name": string
  "channelType": string (enum: line, telegram, teams, web, messenger, instagram, email, whatsapp, slack, team_plus, line_works, viber) // * `line` - LINE
* `telegram` - Telegram
* `teams` - Teams
```

```
* `web` - Web
* `messenger` - Messenger
* `instagram` - Instagram
* `email` - Email
* `whatsapp` - WhatsApp
* `slack` - Slack
* `team_plus` - Team+
* `line_works` - LINE WORKS
* `viber` - Viber
  "unreadConversationsCount"?: integer // 非必填
  "signAuth"?:  // 非必填
  {
    "id": string (uuid)
    "signSource": string (uuid)
    "signParams": {
    {
      "keycloak":
      {
        "clientId": string
        "url": string
        "realm": string
      }
      "line":
      {
        "liffId": string
      }
      "ad":
      {
        "saml": string
      }
      "google"?:  // 非必填
      {
        "enabled": boolean
      }
    }
    }
    "sourceIdAccessEnabled"?: boolean // When enabled, embedded visitors presenting a Source ID (verified per the verify mode below) may chat without going through the login flow. Disabled keeps every existing behavior unchanged. (非必填)
    "sourceIdVerifyMode"?:  // "Require signature verification": the embedding site must send an HMAC signature computed on its backend. "Source ID only": anyone knowing a Source ID can act as that contact; suitable only for testing or closed networks.

* `signature` - Require signature verification
* `raw` - Source ID only (非必填)
    {
    }
    "sourceIdSignatureTtlMinutes"?:  // How long a signature can be used to obtain the contact identity. Not a session lifetime: once exchanged, the session follows the existing WebChat mechanism.

* `1` - 1
* `5` - 5
* `15` - 15 (非必填)
    {
    }
    "keycloakTokenPassthrough"?: boolean // When enabled, the Keycloak access token a visitor logged in with is forwarded as the Authorization header when the AI calls MCP and API tools on their behalf, so tools do not require a separate per-tool login. Only for the Keycloak sign source. Never overrides an Authorization header a tool already resolves from its own credentials. The visitor identity is the organization member bound to the conversation at login, never the contact Source ID. (非必填)
```

```
    "keycloakTokenPassthroughAllowedHosts"?: [ // Hostnames (or "*.example.com" wildcards) of the
tools the visitor Keycloak token may be sent to (非必填)
      string
    ]
  }
  "enableAnalysis"?: boolean // 非必填
}
```

回應範例值


```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "name": "回應字串",
  "channelType": "line",
  "unreadConversationsCount": 456,
  "signAuth": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "signSource": "550e8400-e29b-41d4-a716-446655440000",
    "signParams": {
      "keycloak": {
        "clientId": "回應字串",
        "url": "回應字串",
        "realm": "回應字串"
      },
      "line": {
        "liffId": "回應字串"
      },
      "ad": {
        "saml": "回應字串"
      },
      "google": {
        "enabled": false
      }
    },
    "sourceIdAccessEnabled": false,
    "sourceIdVerifyMode": {},
    "sourceIdSignatureTtlMinutes": {},
    "keycloakTokenPassthrough": false,
    "keycloakTokenPassthroughAllowedHosts": [
      "回應字串"
    ]
  },
  "enableAnalysis": false
}
```


刪除對話平台

DELETE `/api/v1/inboxes/{id}`

參數

參數名稱	必填	類型	說明
`id`	V	string	A UUID string identifying this Inbox.

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X DELETE "https://api.maiagent.ai/api/v1/inboxes/550e8400-e29b-41d4-a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

// 請求內容 (payload)
const data = null;

axios.delete("https://api.maiagent.ai/api/v1/inboxes/550e8400-e29b-41d4-a716-446655440000/",
data, config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/inboxes/550e8400-e29b-41d4-a716-446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.delete(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->delete("https://api.maiagent.ai/api/v1/inboxes/550e8400-e29b-41d4-a716-446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼	說明
204	No response body

列出對話平台的 Webhook

GET `/api/v1/inboxes/{inboxPk}/webhooks/`

參數

參數名稱	必填	類型	說明
`inboxPk`	V	string	
`page`	X	integer	A page number within the paginated result set.

pageSize	X	integer	Number of results to return per page.

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/inboxes/550e8400-e29b-41d4-a716-
446655440000/webhooks/?page=1&pageSize=1"

  -H "Authorization: Api-Key YOUR_API_KEY"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/inboxes/550e8400-e29b-41d4-a716-
446655440000/webhooks/?page=1&pageSize=1", config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/inboxes/550e8400-e29b-41d4-a716-446655440000/webhooks/?
page=1&pageSize=1"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->get("https://api.maiagent.ai/api/v1/inboxes/550e8400-e29b-41d4-a716-
446655440000/webhooks/?page=1&pageSize=1", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
{
  "count": integer
  "next"?: string (uri) // 非必填
  "previous"?: string (uri) // 非必填
  "results": [
    {
      "id": string (uuid)
      "inbox": string (uuid)
      "name": string // Webhook configuration name for identification
      "direction":  // When to trigger: incoming (user messages) or outgoing (bot replies)

* `incoming` - Incoming
* `outgoing` - Outgoing
* `receive` - Receive
      {
      }
      "directionLabel": string
      "isEnabled"?: boolean // 非必填
      "url": string (uri)
      "method"?:  // 非必填
      {
      }
      "headersMasked": object
      "templatePreset"?: string (enum: maiagent_standard, genesys_cloud, custom) // *
`maiagent_standard` - MaiAgent Standard
* `genesys_cloud` - Genesys Cloud
* `custom` - Custom (非必填)
      "templatePresetLabel": string
      "customTemplate"?: string // Jinja2 template for custom payload format. Required when
template_preset is "custom". (非必填)
      "payloadPreset"?: // 可能有不同的類型 (非必填)
      string (enum: genesys_cloud) // Preset for parsing incoming webhook payloads (used with
direction=receive)

* `genesys_cloud` - Genesys Cloud (非必填)
      "payloadPresetLabel": string
      "receiveUrl": string
      "createdAt": string (timestamp)
      "updatedAt": string (timestamp)
    }
  ]
}
```

回應範例值

```
{
  "count": 123,
  "next": "http://api.example.org/accounts/?page=4",
  "previous": "http://api.example.org/accounts/?page=2",
```

```
  "results": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "inbox": "550e8400-e29b-41d4-a716-446655440000",
      "name": "回應字串",
      "direction": {},
      "directionLabel": "回應字串",
      "isEnabled": false,
      "url": "https://example.com/file.jpg",
      "method": {},
      "headersMasked": {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "name": "回應範例名稱",
        "description": "回應範例描述"
      },
      "templatePreset": "maiagent_standard",
      "templatePresetLabel": "回應字串",
      "customTemplate": "回應字串",
      "payloadPreset": "genesys_cloud",
      "payloadPresetLabel": "回應字串",
      "receiveUrl": "回應字串",
      "createdAt": "回應字串",
      "updatedAt": "回應字串"
    }
  ]
}
```


建立 Webhook

POST `/api/v1/inboxes/{inboxPk}/webhooks/`

direction 為 incoming（使用者訊息進入時觸發）或 outgoing（Agent 回覆時觸發）；template_preset 選 maiagent_standard 使用 MaiAgent 標準 payload。

參數

參數名稱	必填	類型	說明
inboxPk	V	string	

請求內容

請求參數

欄位	類型	必填	說明
name	string	是	Webhook configuration name for identification
direction	object	是	When to trigger: incoming (user messages) or outgoing (bot replies) `incoming` : Incoming ; `outgoing` : Outgoing ; `receive` : Receive;
isEnabled	boolean	否	
url	string (uri)	否	
method	object	否	
headers	object	否	Custom HTTP headers as JSON object
templatePreset	string (enum: maiagent_standard, genesys_cloud, custom)	否	`maiagent_standard` : MaiAgent Standard ; `genesys_cloud` : Genesys Cloud ; `custom` : Custom;
customTemplate	string	否	Jinja2 template for custom payload format. Required when template_preset is "custom".
secretToken	string	否	Secret token for webhook signature verification
payloadPreset	object	否	Preset for parsing incoming webhook payloads (used with direction=receive) `genesys_cloud` : Genesys Cloud;

請求結構範例

```
{
  "name": string // Webhook configuration name for identification
  "direction":  // When to trigger: incoming (user messages) or outgoing (bot replies)

* `incoming` - Incoming
* `outgoing` - Outgoing
* `receive` - Receive
  {
  }
  "isEnabled"?: boolean // 非必填
  "url"?: string (uri) // 非必填
  "method"?:  // 非必填
  {
  }
  "headers"?: object // Custom HTTP headers as JSON object (非必填)
  "templatePreset"?: string (enum: maiagent_standard, genesys_cloud, custom) // * `maiagent_standard`
- MaiAgent Standard
* `genesys_cloud` - Genesys Cloud
* `custom` - Custom (非必填)
  "customTemplate"?: string // Jinja2 template for custom payload format. Required when
template_preset is "custom". (非必填)
  "secretToken"?: string // Secret token for webhook signature verification (非必填)
  "payloadPreset"?: // 可能有不同的類型 (非必填)
  string (enum: genesys_cloud) // Preset for parsing incoming webhook payloads (used with
direction=receive)

* `genesys_cloud` - Genesys Cloud (非必填)
}
```

請求範例值

```
{
  "name": "範例名稱",
  "direction": {},
  "isEnabled": true,
  "url": "https://example.com/file.jpg",
  "method": {},
  "headers": null,
  "templatePreset": "maiagent_standard",
  "customTemplate": "範例字串",
  "secretToken": "範例字串",
  "payloadPreset": null
}
```

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X POST "https://api.maiagent.ai/api/v1/inboxes/550e8400-e29b-41d4-a716-
446655440000/webhooks/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "name": "範例名稱",
    "direction": {},
    "isEnabled": true,
    "url": "https://example.com/file.jpg",
    "method": {},
    "headers": null,
    "templatePreset": "maiagent_standard",
    "customTemplate": "範例字串",
    "secretToken": "範例字串",
    "payloadPreset": null
  }'

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// 請求內容 (payload)
const data = {
    "name": "範例名稱",
    "direction": {},
    "isEnabled": true,
    "url": "https://example.com/file.jpg",
    "method": {},
    "headers": null,
    "templatePreset": "maiagent_standard",
    "customTemplate": "範例字串",
    "secretToken": "範例字串",
    "payloadPreset": null
  };

axios.post("https://api.maiagent.ai/api/v1/inboxes/550e8400-e29b-41d4-a716-
446655440000/webhooks/", data, config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```python
import requests

url = "https://api.maiagent.ai/api/v1/inboxes/550e8400-e29b-41d4-a716-446655440000/webhooks/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# 請求內容 (payload)
data = {
    "name": "範例名稱",
    "direction": {},
    "isEnabled": True,
    "url": "https://example.com/file.jpg",
    "method": {},
    "headers": None,
    "templatePreset": "maiagent_standard",
    "customTemplate": "範例字串",
    "secretToken": "範例字串",
    "payloadPreset": None
}

response = requests.post(url, json=data, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->post("https://api.maiagent.ai/api/v1/inboxes/550e8400-e29b-41d4-a716-446655440000/webhooks/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'name' => '範例名稱',
            'direction' => new \stdClass(),
            'isEnabled' => true,
            'url' => 'https://example.com/file.jpg',
            'method' => new \stdClass(),
            'headers' => null,
            'templatePreset' => 'maiagent_standard',
            'customTemplate' => '範例字串',
            'secretToken' => '範例字串',
            'payloadPreset' => null
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 201

回應結構範例

```
{
  "id": string (uuid)
  "inbox": string (uuid)
  "name": string // Webhook configuration name for identification
  "direction":  // When to trigger: incoming (user messages) or outgoing (bot replies)
```

```
* `incoming` - Incoming
* `outgoing` - Outgoing
* `receive` - Receive
  {
  }
  "directionLabel": string
  "isEnabled"?: boolean // 非必填
  "url": string (uri)
  "method"?:  // 非必填
  {
  }
  "headersMasked": object
  "templatePreset"?: string (enum: maiagent_standard, genesys_cloud, custom) // * `maiagent_standard`
- MaiAgent Standard
* `genesys_cloud` - Genesys Cloud
* `custom` - Custom (非必填)
  "templatePresetLabel": string
  "customTemplate"?: string // Jinja2 template for custom payload format. Required when
template_preset is "custom". (非必填)
  "payloadPreset"?: // 可能有不同的類型 (非必填)
  string (enum: genesys_cloud) // Preset for parsing incoming webhook payloads (used with
direction=receive)

* `genesys_cloud` - Genesys Cloud (非必填)
  "payloadPresetLabel": string
  "receiveUrl": string
  "createdAt": string (timestamp)
  "updatedAt": string (timestamp)
}
```

回應範例值

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "inbox": "550e8400-e29b-41d4-a716-446655440000",
  "name": "回應字串",
  "direction": {},
  "directionLabel": "回應字串",
  "isEnabled": false,
  "url": "https://example.com/file.jpg",
  "method": {},
  "headersMasked": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應範例名稱",
    "description": "回應範例描述"
  },
  "templatePreset": "maiagent_standard",
  "templatePresetLabel": "回應字串",
  "customTemplate": "回應字串",
  "payloadPreset": "genesys_cloud",
  "payloadPresetLabel": "回應字串",
  "receiveUrl": "回應字串",
  "createdAt": "回應字串",
  "updatedAt": "回應字串"
}
```

取得特定 Webhook

GET `/api/v1/inboxes/{inboxPk}/webhooks/{id}`

參數

參數名稱	必填	類型	說明
`id`	V	string	A UUID string identifying this Inbox Webhook.
`inboxPk`	V	string	

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/inboxes/550e8400-e29b-41d4-a716-
446655440000/webhooks/550e8400-e29b-41d4-a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/inboxes/550e8400-e29b-41d4-a716-
446655440000/webhooks/550e8400-e29b-41d4-a716-446655440000/", config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/inboxes/550e8400-e29b-41d4-a716-
446655440000/webhooks/550e8400-e29b-41d4-a716-446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->get("https://api.maiagent.ai/api/v1/inboxes/550e8400-e29b-41d4-a716-
446655440000/webhooks/550e8400-e29b-41d4-a716-446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
{
  "id": string (uuid)
  "inbox": string (uuid)
  "name": string // Webhook configuration name for identification
  "direction":  // When to trigger: incoming (user messages) or outgoing (bot replies)

* `incoming` - Incoming
* `outgoing` - Outgoing
* `receive` - Receive
  {
  }
  "directionLabel": string
  "isEnabled"?: boolean // 非必填
  "url": string (uri)
  "method"?:  // 非必填
  {
  }
  "headersMasked": object
  "templatePreset"?: string (enum: maiagent_standard, genesys_cloud, custom) // * `maiagent_standard`
```

```
- MaiAgent Standard
* `genesys_cloud` - Genesys Cloud
* `custom` - Custom (非必填)
  "templatePresetLabel": string
  "customTemplate"?: string // Jinja2 template for custom payload format. Required when
template_preset is "custom". (非必填)
  "payloadPreset"?: // 可能有不同的類型 (非必填)
  string (enum: genesys_cloud) // Preset for parsing incoming webhook payloads (used with
direction=receive)

* `genesys_cloud` - Genesys Cloud (非必填)
  "payloadPresetLabel": string
  "receiveUrl": string
  "createdAt": string (timestamp)
  "updatedAt": string (timestamp)
}
```

回應範例值

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "inbox": "550e8400-e29b-41d4-a716-446655440000",
  "name": "回應字串",
  "direction": {},
  "directionLabel": "回應字串",
  "isEnabled": false,
  "url": "https://example.com/file.jpg",
  "method": {},
  "headersMasked": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應範例名稱",
    "description": "回應範例描述"
  },
  "templatePreset": "maiagent_standard",
  "templatePresetLabel": "回應字串",
  "customTemplate": "回應字串",
  "payloadPreset": "genesys_cloud",
  "payloadPresetLabel": "回應字串",
  "receiveUrl": "回應字串",
  "createdAt": "回應字串",
  "updatedAt": "回應字串"
}
```

更新 Webhook

PUT `/api/v1/inboxes/{inboxPk}/webhooks/{id}`

參數

參數名稱	必填	類型	說明
`id`	V	string	A UUID string identifying this Inbox Webhook.
`inboxPk`	V	string	

請求內容

請求參數

欄位	類型	必填	說明
name	string	是	Webhook configuration name for identification
direction	object	是	When to trigger: incoming (user messages) or outgoing (bot replies) `incoming` : Incoming ; `outgoing` : Outgoing ; `receive` : Receive;
isEnabled	boolean	否	
url	string (uri)	否	
method	object	否	
headers	object	否	Custom HTTP headers as JSON object
templatePreset	string (enum: maiagent_standard, genesys_cloud, custom)	否	`maiagent_standard` : MaiAgent Standard ; `genesys_cloud` : Genesys Cloud ; `custom` : Custom;
customTemplate	string	否	Jinja2 template for custom payload format. Required when template_preset is "custom".
secretToken	string	否	Secret token for webhook signature verification
payloadPreset	object	否	Preset for parsing incoming webhook payloads (used with direction=receive) `genesys_cloud` : Genesys Cloud;

請求結構範例

```
{
  "name": string // Webhook configuration name for identification
  "direction":  // When to trigger: incoming (user messages) or outgoing (bot replies)

* `incoming` - Incoming
* `outgoing` - Outgoing
* `receive` - Receive
  {
  }
  "isEnabled"?: boolean // 非必填
  "url"?: string (uri) // 非必填
  "method"?:  // 非必填
  {
  }
  "headers"?: object // Custom HTTP headers as JSON object (非必填)
  "templatePreset"?: string (enum: maiagent_standard, genesys_cloud, custom) // * `maiagent_standard`
```

```
- MaiAgent Standard
* `genesys_cloud` - Genesys Cloud
* `custom` - Custom (非必填)
  "customTemplate"?: string // Jinja2 template for custom payload format. Required when
template_preset is "custom". (非必填)
  "secretToken"?: string // Secret token for webhook signature verification (非必填)
  "payloadPreset"?: // 可能有不同的類型 (非必填)
  string (enum: genesys_cloud) // Preset for parsing incoming webhook payloads (used with
direction=receive)

* `genesys_cloud` - Genesys Cloud (非必填)
}
```

請求範例值

```
{
  "name": "範例名稱",
  "direction": {},
  "isEnabled": true,
  "url": "https://example.com/file.jpg",
  "method": {},
  "headers": null,
  "templatePreset": "maiagent_standard",
  "customTemplate": "範例字串",
  "secretToken": "範例字串",
  "payloadPreset": null
}
```

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X PUT "https://api.maiagent.ai/api/v1/inboxes/550e8400-e29b-41d4-a716-
446655440000/webhooks/550e8400-e29b-41d4-a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "name": "範例名稱",
    "direction": {},
    "isEnabled": true,
    "url": "https://example.com/file.jpg",
    "method": {},
    "headers": null,
    "templatePreset": "maiagent_standard",
    "customTemplate": "範例字串",
    "secretToken": "範例字串",
    "payloadPreset": null
  }'

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// 請求內容 (payload)
const data = {
    "name": "範例名稱",
    "direction": {},
    "isEnabled": true,
    "url": "https://example.com/file.jpg",
    "method": {},
    "headers": null,
    "templatePreset": "maiagent_standard",
    "customTemplate": "範例字串",
    "secretToken": "範例字串",
    "payloadPreset": null
  };

axios.put("https://api.maiagent.ai/api/v1/inboxes/550e8400-e29b-41d4-a716-
446655440000/webhooks/550e8400-e29b-41d4-a716-446655440000/", data, config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/inboxes/550e8400-e29b-41d4-a716-
446655440000/webhooks/550e8400-e29b-41d4-a716-446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# 請求內容 (payload)
data = {
    "name": "範例名稱",
    "direction": {},
    "isEnabled": True,
    "url": "https://example.com/file.jpg",
    "method": {},
    "headers": None,
    "templatePreset": "maiagent_standard",
    "customTemplate": "範例字串",
    "secretToken": "範例字串",
    "payloadPreset": None
}

response = requests.put(url, json=data, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->put("https://api.maiagent.ai/api/v1/inboxes/550e8400-e29b-41d4-a716-
446655440000/webhooks/550e8400-e29b-41d4-a716-446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'name' => '範例名稱',
            'direction' => new \stdClass(),
            'isEnabled' => true,
            'url' => 'https://example.com/file.jpg',
            'method' => new \stdClass(),
            'headers' => null,
            'templatePreset' => 'maiagent_standard',
            'customTemplate' => '範例字串',
            'secretToken' => '範例字串',
            'payloadPreset' => null
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
{
  "id": string (uuid)
  "inbox": string (uuid)
  "name": string // Webhook configuration name for identification
  "direction":  // When to trigger: incoming (user messages) or outgoing (bot replies)
```

```
* `incoming` - Incoming
* `outgoing` - Outgoing
* `receive` - Receive
  {
  }
  "directionLabel": string
  "isEnabled"?: boolean // 非必填
  "url": string (uri)
  "method"?:  // 非必填
  {
  }
  "headersMasked": object
  "templatePreset"?: string (enum: maiagent_standard, genesys_cloud, custom) // * `maiagent_standard`
- MaiAgent Standard
* `genesys_cloud` - Genesys Cloud
* `custom` - Custom (非必填)
  "templatePresetLabel": string
  "customTemplate"?: string // Jinja2 template for custom payload format. Required when
template_preset is "custom". (非必填)
  "payloadPreset"?: // 可能有不同的類型 (非必填)
  string (enum: genesys_cloud) // Preset for parsing incoming webhook payloads (used with
direction=receive)

* `genesys_cloud` - Genesys Cloud (非必填)
  "payloadPresetLabel": string
  "receiveUrl": string
  "createdAt": string (timestamp)
  "updatedAt": string (timestamp)
}
```

回應範例值

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "inbox": "550e8400-e29b-41d4-a716-446655440000",
  "name": "回應字串",
  "direction": {},
  "directionLabel": "回應字串",
  "isEnabled": false,
  "url": "https://example.com/file.jpg",
  "method": {},
  "headersMasked": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應範例名稱",
    "description": "回應範例描述"
  },
  "templatePreset": "maiagent_standard",
  "templatePresetLabel": "回應字串",
  "customTemplate": "回應字串",
  "payloadPreset": "genesys_cloud",
  "payloadPresetLabel": "回應字串",
  "receiveUrl": "回應字串",
  "createdAt": "回應字串",
  "updatedAt": "回應字串"
}
```

部分更新 Webhook

PATCH `/api/v1/inboxes/{inboxPk}/webhooks/{id}`

參數

參數名稱	必填	類型	說明
`id`	V	string	A UUID string identifying this Inbox Webhook.
`inboxPk`	V	string	

請求內容

請求參數

欄位	類型	必填	說明
name	string	否	Webhook configuration name for identification
direction	object	否	When to trigger: incoming (user messages) or outgoing (bot replies) `incoming` : Incoming ; `outgoing` : Outgoing ; `receive` : Receive;
isEnabled	boolean	否	
url	string (uri)	否	
method	object	否	
headers	object	否	Custom HTTP headers as JSON object
templatePreset	string (enum: maiagent_standard, genesys_cloud, custom)	否	`maiagent_standard` : MaiAgent Standard ; `genesys_cloud` : Genesys Cloud ; `custom` : Custom;
customTemplate	string	否	Jinja2 template for custom payload format. Required when template_preset is "custom".
secretToken	string	否	Secret token for webhook signature verification
payloadPreset	object	否	Preset for parsing incoming webhook payloads (used with direction=receive) `genesys_cloud` : Genesys Cloud;

請求結構範例

```
{
  "name"?: string // Webhook configuration name for identification (非必填)
  "direction"?:  // When to trigger: incoming (user messages) or outgoing (bot replies)
```

```
* `incoming` - Incoming
* `outgoing` - Outgoing
* `receive` - Receive (非必填)
  {
  }
  "isEnabled"?: boolean // 非必填
  "url"?: string (uri) // 非必填
  "method"?:  // 非必填
  {
  }
  "headers"?: object // Custom HTTP headers as JSON object (非必填)
  "templatePreset"?: string (enum: maiagent_standard, genesys_cloud, custom) // * `maiagent_standard`
- MaiAgent Standard
* `genesys_cloud` - Genesys Cloud
* `custom` - Custom (非必填)
  "customTemplate"?: string // Jinja2 template for custom payload format. Required when
template_preset is "custom". (非必填)
  "secretToken"?: string // Secret token for webhook signature verification (非必填)
  "payloadPreset"?: // 可能有不同的類型 (非必填)
  string (enum: genesys_cloud) // Preset for parsing incoming webhook payloads (used with
direction=receive)

* `genesys_cloud` - Genesys Cloud (非必填)
}
```

請求範例值

```
{
  "name": "範例名稱",
  "direction": {},
  "isEnabled": true,
  "url": "https://example.com/file.jpg",
  "method": {},
  "headers": null,
  "templatePreset": "maiagent_standard",
  "customTemplate": "範例字串",
  "secretToken": "範例字串",
  "payloadPreset": null
}
```

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X PATCH "https://api.maiagent.ai/api/v1/inboxes/550e8400-e29b-41d4-a716-
446655440000/webhooks/550e8400-e29b-41d4-a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "name": "範例名稱",
    "direction": {},
    "isEnabled": true,
    "url": "https://example.com/file.jpg",
    "method": {},
    "headers": null,
    "templatePreset": "maiagent_standard",
    "customTemplate": "範例字串",
    "secretToken": "範例字串",
    "payloadPreset": null
  }'

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// 請求內容 (payload)
const data = {
    "name": "範例名稱",
    "direction": {},
    "isEnabled": true,
    "url": "https://example.com/file.jpg",
    "method": {},
    "headers": null,
    "templatePreset": "maiagent_standard",
    "customTemplate": "範例字串",
    "secretToken": "範例字串",
    "payloadPreset": null
  };

axios.patch("https://api.maiagent.ai/api/v1/inboxes/550e8400-e29b-41d4-a716-
446655440000/webhooks/550e8400-e29b-41d4-a716-446655440000/", data, config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/inboxes/550e8400-e29b-41d4-a716-
446655440000/webhooks/550e8400-e29b-41d4-a716-446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# 請求內容 (payload)
data = {
    "name": "範例名稱",
    "direction": {},
    "isEnabled": True,
    "url": "https://example.com/file.jpg",
    "method": {},
    "headers": None,
    "templatePreset": "maiagent_standard",
    "customTemplate": "範例字串",
    "secretToken": "範例字串",
    "payloadPreset": None
}

response = requests.patch(url, json=data, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->patch("https://api.maiagent.ai/api/v1/inboxes/550e8400-e29b-41d4-a716-446655440000/webhooks/550e8400-e29b-41d4-a716-446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'name' => '範例名稱',
            'direction' => new \stdClass(),
            'isEnabled' => true,
            'url' => 'https://example.com/file.jpg',
            'method' => new \stdClass(),
            'headers' => null,
            'templatePreset' => 'maiagent_standard',
            'customTemplate' => '範例字串',
            'secretToken' => '範例字串',
            'payloadPreset' => null
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
{
  "id": string (uuid)
  "inbox": string (uuid)
  "name": string // Webhook configuration name for identification
  "direction":  // When to trigger: incoming (user messages) or outgoing (bot replies)
```

```
* `incoming` - Incoming
* `outgoing` - Outgoing
* `receive` - Receive
  {
  }
  "directionLabel": string
  "isEnabled"?: boolean // 非必填
  "url": string (uri)
  "method"?:  // 非必填
  {
  }
  "headersMasked": object
  "templatePreset"?: string (enum: maiagent_standard, genesys_cloud, custom) // * `maiagent_standard`
- MaiAgent Standard
* `genesys_cloud` - Genesys Cloud
* `custom` - Custom (非必填)
  "templatePresetLabel": string
  "customTemplate"?: string // Jinja2 template for custom payload format. Required when
template_preset is "custom". (非必填)
  "payloadPreset"?: // 可能有不同的類型 (非必填)
  string (enum: genesys_cloud) // Preset for parsing incoming webhook payloads (used with
direction=receive)

* `genesys_cloud` - Genesys Cloud (非必填)
  "payloadPresetLabel": string
  "receiveUrl": string
  "createdAt": string (timestamp)
  "updatedAt": string (timestamp)
}
```

回應範例值

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "inbox": "550e8400-e29b-41d4-a716-446655440000",
  "name": "回應字串",
  "direction": {},
  "directionLabel": "回應字串",
  "isEnabled": false,
  "url": "https://example.com/file.jpg",
  "method": {},
  "headersMasked": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應範例名稱",
    "description": "回應範例描述"
  },
  "templatePreset": "maiagent_standard",
  "templatePresetLabel": "回應字串",
  "customTemplate": "回應字串",
  "payloadPreset": "genesys_cloud",
  "payloadPresetLabel": "回應字串",
  "receiveUrl": "回應字串",
  "createdAt": "回應字串",
  "updatedAt": "回應字串"
}
```

刪除 Webhook

DELETE `/api/v1/inboxes/{inboxPk}/webhooks/{id}`

參數

參數名稱	必填	類型	說明
`id`	V	string	A UUID string identifying this Inbox Webhook.
`inboxPk`	V	string	

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X DELETE "https://api.maiagent.ai/api/v1/inboxes/550e8400-e29b-41d4-a716-
446655440000/webhooks/550e8400-e29b-41d4-a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

// 請求內容 (payload)
const data = null;

axios.delete("https://api.maiagent.ai/api/v1/inboxes/550e8400-e29b-41d4-a716-
446655440000/webhooks/550e8400-e29b-41d4-a716-446655440000/", data, config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/inboxes/550e8400-e29b-41d4-a716-
446655440000/webhooks/550e8400-e29b-41d4-a716-446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.delete(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->delete("https://api.maiagent.ai/api/v1/inboxes/550e8400-e29b-41d4-a716-446655440000/webhooks/550e8400-e29b-41d4-a716-446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼	說明
204	No response body

呼叫 API 示例 (Shell)

目錄

1. 建立工具
2. 列出工具
3. 取得特定工具
4. 更新工具
5. 部分更新工具
6. 刪除工具
7. 列出可用工具
8. 建立連接器
9. 列出連接器
10. 取得特定連接器
11. 更新連接器
12. 部分更新連接器
13. 刪除連接器
14. 列出連接器授權成員
15. 移除連接器授權成員
16. 列出 MCP 工具登錄
17. 取得特定 MCP 工具登錄
18. 列出組織自架的 MCP Server
19. 新增自架 MCP Server
20. 取得特定自架 MCP Server
21. 部分更新自架 MCP Server
22. 刪除自架 MCP Server
23. 測試 MCP Server 連線
24. 取得工具執行紀錄列表
25. 取得特定工具執行紀錄
26. 取得執行紀錄的 AI 助理過濾選項
27. 取得執行紀錄的工具過濾選項
28. 取得特定工具的執行紀錄列表
29. 取得特定工具的特定執行紀錄
30. 取得特定工具執行紀錄的 AI 助理過濾選項
31. 取得特定工具執行紀錄的工具過濾選項

呼叫 API 示例 (Shell)

建立工具

`POST` `/api/v1/tools/`

請求內容

請求參數

欄位	類型	必填	說明
name	object	否	Tool name may only contain letters, digits, underscores (_) and hyphens (-). Not required for MCP tools; for API tools it is the tool name given to the LLM.
displayName	string	是	A name with any characters, used by users for configuration and management.
description	string	否	Tool description shown to users. Not required for MCP tools.
prompt	string	否	Tool description/prompt given to the LLM. If empty, the description field is used. Not required for MCP tools.

欄位	類型	必填	說明
toolType	string (enum: api, function, mcp, desktop, flex, quick_reply, quick_menu)	否	`api` : API ; `function` : Function ; `mcp` : MCP ; `desktop` : Desktop ; `flex` : Flex Message ; `quick_reply` : Quick Reply ; `quick_menu` : Quick Menu;
apiUrl	string	否	
httpMethod	object	否	
rawHeaders	object	否	
sensitiveHeaders	array[string]	否	
rawQueryParams	object	否	Query string parameters appended to every request of this API tool. Values support the same {{variable}} template rendering as raw_headers. On key collision with LLM-generated arguments, these values ...
rawParametersSchema	object	否	
functionCode	string	否	
mcpUrl	string	否	
mcpRegistry	string (uuid)	否	Registry backing this MCP tool. Null for manual-URL MCP tools.
mcpAllowedTools	object	否	
rawMcpHeader	object	否	Default headers used when the Contact has no matching MCP Credential.
authSubject	object	否	Shared uses the tool level token plus per contact credentials; contact requires per contact

欄位	類型	必填	說明
			authentication only; caller mints a short-lived token for the conversation-bound member (falls back to per c...
flexTemplateJson	object	否	FlexMessage JSON template. Required for FLEX_MESSAGE tools. Stores the full LINE FlexMessage JSON structure (bubble / carousel / box / text / image / button etc.).
flexSchema	object	否	AI dynamic field schema for FlexMessage. JSON object whose keys are field paths parsed from flex_template_json (e.g. text / image url / button label / button uri / button message). Each value may be e...
quickReplyConfig	object	否	Authoring config for QUICK_REPLY tools. Structured JSON describing the chip buttons: static list or dynamic (LLM-generated) mode, each field either a fixed value or an LLM prompt.
quickMenuConfig	object	否	Authoring config for QUICK_MENU tools. Structured JSON describing the persistent input-bar menu rendered by the web chat only: layout (grid / list), default open state, and 2-6 items each carrying a d...

欄位	類型	必填	說明
category	string (enum: knowledge_base, web_search, web_fetch, code_execution, file_processing, image_video_generation, database_query, third_party_integration, browser_operation, agent_collaboration, other)	否	`knowledge_base`：Knowledge base retrieval；`web_search`：Web search；`web_fetch`：Web page fetch；`code_execution`：Code execution；`file_processing`：File processing；`image_video_generation`：...
displayCopyByLocale	object	否	
outputRenderTemplateByLocale	object	否	
toolDisplayMode	object	否	
groups	array[IdName]	否	Groups this tool is assigned to. Non-owner members must pick at least one group they belong to.

請求結構範例

```
{
  "name"?: // 可能有不同的類型 (非必填)
  string // Tool name may only contain letters, digits, underscores (_) and hyphens (-). Not required for MCP tools; for API tools it is the tool name given to the LLM. (非必填)
  "displayName": string // A name with any characters, used by users for configuration and management.
  "description"?: string // Tool description shown to users. Not required for MCP tools. (非必填)
  "prompt"?: string // Tool description/prompt given to the LLM. If empty, the description field is used. Not required for MCP tools. (非必填)
  "toolType"?: string (enum: api, function, mcp, desktop, flex, quick_reply, quick_menu) // * `api` - API
* `function` - Function
* `mcp` - MCP
* `desktop` - Desktop
* `flex` - Flex Message
```

```
* `quick_reply` - Quick Reply
* `quick_menu` - Quick Menu (非必填)
  "apiUrl"?: string // 非必填
  "httpMethod"?: // 可能有不同的類型 (非必填)
  string (enum: get, post, put, delete, patch) // 非必填
  "rawHeaders"?: object // 非必填
  "sensitiveHeaders"?: [ // 非必填
    string
  ]
  "rawQueryParams"?: object // Query string parameters appended to every request of this API tool. Values support the same {{variable}} template rendering as raw_headers. On key collision with LLM-generated arguments, these values win — use this field for API keys that must travel in the query string. (非必填)
  "rawParametersSchema"?: object // 非必填
  "functionCode"?: string // 非必填
  "mcpUrl"?: string // 非必填
  "mcpRegistry"?: string (uuid) // Registry backing this MCP tool. Null for manual-URL MCP tools. (非必填)
  "mcpAllowedTools"?: object // 非必填
  "rawMcpHeader"?: object // Default headers used when the Contact has no matching MCP Credential. (非必填)
  "authSubject"?:  // Shared uses the tool level token plus per contact credentials; contact requires per contact authentication only; caller mints a short-lived token for the conversation-bound member (falls back to per contact credentials when the conversation has no bound member). MCP tools only.

* `shared` - Shared
* `contact` - Contact
* `caller` - Caller (非必填)
  {
  }
  "flexTemplateJson"?: object // FlexMessage JSON template. Required for FLEX_MESSAGE tools. Stores the full LINE FlexMessage JSON structure (bubble / carousel / box / text / image / button etc.). (非必填)
  "flexSchema"?: object // AI dynamic field schema for FlexMessage. JSON object whose keys are field paths parsed from flex_template_json (e.g. text / image url / button label / button uri / button message). Each value may be either a plain string (the AI prompt) or an object carrying additional metadata such as a field tag, e.g. {"prompt": "...", "tag": "title"}. Empty values fall back to the template default. (非必填)
  "quickReplyConfig"?: object // Authoring config for QUICK_REPLY tools. Structured JSON describing the chip buttons: static list or dynamic (LLM-generated) mode, each field either a fixed value or an LLM prompt. (非必填)
  "quickMenuConfig"?: object // Authoring config for QUICK_MENU tools.
```

```
Structured JSON describing the persistent input-bar menu rendered by the
web chat only: layout (grid / list), default open state, and 2-6 items each
carrying a display label plus an action payload (send prompt / prefill text
/ open http(s) link). (非必填)
  "category"?: string (enum: knowledge_base, web_search, web_fetch,
code_execution, file_processing, image_video_generation, database_query,
third_party_integration, browser_operation, agent_collaboration, other) //
* `knowledge_base` - Knowledge base retrieval
* `web_search` - Web search
* `web_fetch` - Web page fetch
* `code_execution` - Code execution
* `file_processing` - File processing
* `image_video_generation` - Image/video generation
* `database_query` - Database query
* `third_party_integration` - Third-party integration
* `browser_operation` - Browser operation
* `agent_collaboration` - Agent collaboration
* `other` - Other (catch-all) (非必填)
  "displayCopyByLocale"?: object // 非必填
  "outputRenderTemplateByLocale"?: object // 非必填
  "toolDisplayMode"?: // 可能有不同的類型 (非必填)
  string (enum: full, compact, hidden) // 非必填
  "groups"?: [ // Groups this tool is assigned to. Non-owner members must
pick at least one group they belong to. (非必填)
    {
      "id": string (uuid)
    }
  ]
}
```

請求範例值

```
{
  "name": null,
  "displayName": "範例字串",
  "description": "範例字串",
  "prompt": "範例字串",
  "toolType": "api",
  "apiUrl": "範例字串",
  "httpMethod": null,
  "rawHeaders": null,
  "sensitiveHeaders": [
    "範例字串"
  ],
```

```
  "rawQueryParams": null,
  "rawParametersSchema": null,
  "functionCode": "範例字串",
  "mcpUrl": "範例字串",
  "mcpRegistry": "550e8400-e29b-41d4-a716-446655440000",
  "mcpAllowedTools": null,
  "rawMcpHeader": null,
  "authSubject": {},
  "flexTemplateJson": null,
  "flexSchema": null,
  "quickReplyConfig": null,
  "quickMenuConfig": null,
  "category": "knowledge_base",
  "displayCopyByLocale": null,
  "outputRenderTemplateByLocale": null,
  "toolDisplayMode": null,
  "groups": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000"
    }
  ]
}
```


程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X POST "https://api.maiagent.ai/api/v1/tools/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "name": null,
    "displayName": "範例字串",
    "description": "範例字串",
    "prompt": "範例字串",
    "toolType": "api",
    "apiUrl": "範例字串",
    "httpMethod": null,
    "rawHeaders": null,
    "sensitiveHeaders": [
      "範例字串"
    ],
    "rawQueryParams": null,
    "rawParametersSchema": null,
    "functionCode": "範例字串",
    "mcpUrl": "範例字串",
    "mcpRegistry": "550e8400-e29b-41d4-a716-446655440000",
    "mcpAllowedTools": null,
    "rawMcpHeader": null,
    "authSubject": {},
    "flexTemplateJson": null,
    "flexSchema": null,
    "quickReplyConfig": null,
    "quickMenuConfig": null,
    "category": "knowledge_base",
    "displayCopyByLocale": null,
    "outputRenderTemplateByLocale": null,
    "toolDisplayMode": null,
    "groups": [
      {
        "id": "550e8400-e29b-41d4-a716-446655440000"
      }
    ]
  }'
```

```
# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// 請求內容 (payload)
const data = {
    "name": null,
    "displayName": "範例字串",
    "description": "範例字串",
    "prompt": "範例字串",
    "toolType": "api",
    "apiUrl": "範例字串",
    "httpMethod": null,
    "rawHeaders": null,
    "sensitiveHeaders": [
      "範例字串"
    ],
    "rawQueryParams": null,
    "rawParametersSchema": null,
    "functionCode": "範例字串",
    "mcpUrl": "範例字串",
    "mcpRegistry": "550e8400-e29b-41d4-a716-446655440000",
    "mcpAllowedTools": null,
    "rawMcpHeader": null,
    "authSubject": {},
    "flexTemplateJson": null,
    "flexSchema": null,
    "quickReplyConfig": null,
    "quickMenuConfig": null,
    "category": "knowledge_base",
    "displayCopyByLocale": null,
    "outputRenderTemplateByLocale": null,
    "toolDisplayMode": null,
    "groups": [
      {
```

```
        "id": "550e8400-e29b-41d4-a716-446655440000"
      }
    ]
  };

axios.post("https://api.maiagent.ai/api/v1/tools/", data, config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/tools/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# 請求內容 (payload)
data = {
    "name": None,
    "displayName": "範例字串",
    "description": "範例字串",
    "prompt": "範例字串",
    "toolType": "api",
    "apiUrl": "範例字串",
    "httpMethod": None,
    "rawHeaders": None,
    "sensitiveHeaders": [
        "範例字串"
    ],
    "rawQueryParams": None,
    "rawParametersSchema": None,
    "functionCode": "範例字串",
    "mcpUrl": "範例字串",
    "mcpRegistry": "550e8400-e29b-41d4-a716-446655440000",
    "mcpAllowedTools": None,
    "rawMcpHeader": None,
    "authSubject": {},
    "flexTemplateJson": None,
    "flexSchema": None,
    "quickReplyConfig": None,
    "quickMenuConfig": None,
    "category": "knowledge_base",
    "displayCopyByLocale": None,
    "outputRenderTemplateByLocale": None,
    "toolDisplayMode": None,
    "groups": [
        {
            "id": "550e8400-e29b-41d4-a716-446655440000"
        }
```

```
    ]
}

response = requests.post(url, json=data, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->post("https://api.maiagent.ai/api/v1/tools/",
[
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'name' => null,
            'displayName' => '範例字串',
            'description' => '範例字串',
            'prompt' => '範例字串',
            'toolType' => 'api',
            'apiUrl' => '範例字串',
            'httpMethod' => null,
            'rawHeaders' => null,
            'sensitiveHeaders' => [
                '範例字串'
            ],
            'rawQueryParams' => null,
            'rawParametersSchema' => null,
            'functionCode' => '範例字串',
            'mcpUrl' => '範例字串',
            'mcpRegistry' => '550e8400-e29b-41d4-a716-446655440000',
            'mcpAllowedTools' => null,
            'rawMcpHeader' => null,
            'authSubject' => new \stdClass(),
            'flexTemplateJson' => null,
            'flexSchema' => null,
            'quickReplyConfig' => null,
            'quickMenuConfig' => null,
            'category' => 'knowledge_base',
            'displayCopyByLocale' => null,
            'outputRenderTemplateByLocale' => null,
            'toolDisplayMode' => null,
            'groups' => [
```

```
                [
                    'id' => '550e8400-e29b-41d4-a716-446655440000'
                ]
            ]
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 201

回應結構範例

```
{
  "id": string (uuid)
  "name"?: // 可能有不同的類型 (非必填)
  string // Tool name may only contain letters, digits, underscores (_) and
hyphens (-). Not required for MCP tools; for API tools it is the tool name
given to the LLM. (非必填)
  "displayName": string // A name with any characters, used by users for
configuration and management.
  "description"?: string // Tool description shown to users. Not required
for MCP tools. (非必填)
  "prompt"?: string // Tool description/prompt given to the LLM. If empty,
the description field is used. Not required for MCP tools. (非必填)
  "toolType"?: string (enum: api, function, mcp, desktop, flex,
quick_reply, quick_menu) // * `api` - API
* `function` - Function
* `mcp` - MCP
```

```
* `desktop` - Desktop
* `flex` - Flex Message
* `quick_reply` - Quick Reply
* `quick_menu` - Quick Menu (非必填)
  "apiUrl"?: string // 非必填
  "httpMethod"?: // 可能有不同的類型 (非必填)
  string (enum: get, post, put, delete, patch) // 非必填
  "rawHeaders"?: object // 非必填
  "rawHeadersMasked": object
  "sensitiveHeaders"?: [ // 非必填
    string
  ]
  "globalSensitiveHeaders": [ // Expose platform defaults as read-only
authoring guidance.
    string
  ]
  "rawQueryParams"?: object // Query string parameters appended to every
request of this API tool. Values support the same {{variable}} template
rendering as raw_headers. On key collision with LLM-generated arguments,
these values win — use this field for API keys that must travel in the
query string. (非必填)
  "rawQueryParamsMasked": object
  "rawParametersSchema"?: object // 非必填
  "functionCode"?: string // 非必填
  "organization": string (uuid)
  "createdBy": string (uuid)
  "isGlobal": boolean // If set as global tool, all organizations can use
this tool
  "mcpUrl"?: string // 非必填
  "mcpRegistry"?: string (uuid) // Registry backing this MCP tool. Null for
manual-URL MCP tools. (非必填)
  "mcpAllowedTools"?: object // 非必填
  "rawMcpHeader"?: object // Default headers used when the Contact has no
matching MCP Credential. (非必填)
  "rawMcpHeaderMasked": object
  "authSubject"?:  // Shared uses the tool level token plus per contact
credentials; contact requires per contact authentication only; caller mints
a short-lived token for the conversation-bound member (falls back to per
contact credentials when the conversation has no bound member). MCP tools
only.

* `shared` - Shared
* `contact` - Contact
* `caller` - Caller (非必填)
  {
  }
```

```
  "flexTemplateJson"?: object // FlexMessage JSON template. Required for
FLEX_MESSAGE tools. Stores the full LINE FlexMessage JSON structure (bubble
/ carousel / box / text / image / button etc.). (非必填)
  "flexSchema"?: object // AI dynamic field schema for FlexMessage. JSON
object whose keys are field paths parsed from flex_template_json (e.g. text
/ image url / button label / button uri / button message). Each value may
be either a plain string (the AI prompt) or an object carrying additional
metadata such as a field tag, e.g. {"prompt": "...", "tag": "title"}. Empty
values fall back to the template default. (非必填)
  "quickReplyConfig"?: object // Authoring config for QUICK_REPLY tools.
Structured JSON describing the chip buttons: static list or dynamic (LLM-
generated) mode, each field either a fixed value or an LLM prompt. (非必填)
  "quickMenuConfig"?: object // Authoring config for QUICK_MENU tools.
Structured JSON describing the persistent input-bar menu rendered by the
web chat only: layout (grid / list), default open state, and 2-6 items each
carrying a display label plus an action payload (send prompt / prefill text
/ open http(s) link). (非必填)
  "category"?: string (enum: knowledge_base, web_search, web_fetch,
code_execution, file_processing, image_video_generation, database_query,
third_party_integration, browser_operation, agent_collaboration, other) //
* `knowledge_base` - Knowledge base retrieval
* `web_search` - Web search
* `web_fetch` - Web page fetch
* `code_execution` - Code execution
* `file_processing` - File processing
* `image_video_generation` - Image/video generation
* `database_query` - Database query
* `third_party_integration` - Third-party integration
* `browser_operation` - Browser operation
* `agent_collaboration` - Agent collaboration
* `other` - Other (catch-all) (非必填)
  "displayCopyByLocale"?: object // 非必填
  "outputRenderTemplateByLocale"?: object // 非必填
  "toolDisplayMode"?: // 可能有不同的類型 (非必填)
  string (enum: full, compact, hidden) // 非必填
  "groups"?: [ // Groups this tool is assigned to. Non-owner members must
pick at least one group they belong to. (非必填)
    {
      "id": string (uuid)
      "name": string
    }
  ]
  "createdAt": string (timestamp)
  "updatedAt": string (timestamp)
  "canUpdate": boolean // Return whether the current user can update this
resource.
```

```
  "canDelete": boolean // Return whether the current user can delete this
resource.
}
```

回應範例值

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "name": "回應字串",
  "displayName": "回應字串",
  "description": "回應字串",
  "prompt": "回應字串",
  "toolType": "api",
  "apiUrl": "回應字串",
  "httpMethod": "get",
  "rawHeaders": null,
  "rawHeadersMasked": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應範例名稱",
    "description": "回應範例描述"
  },
  "sensitiveHeaders": [
    "回應字串"
  ],
  "globalSensitiveHeaders": [
    "回應字串"
  ],
  "rawQueryParams": null,
  "rawQueryParamsMasked": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應範例名稱",
    "description": "回應範例描述"
  },
  "rawParametersSchema": null,
  "functionCode": "回應字串",
  "organization": "550e8400-e29b-41d4-a716-446655440000",
  "createdBy": "550e8400-e29b-41d4-a716-446655440000",
  "isGlobal": false,
  "mcpUrl": "回應字串",
  "mcpRegistry": "550e8400-e29b-41d4-a716-446655440000",
  "mcpAllowedTools": null,
  "rawMcpHeader": null,
  "rawMcpHeaderMasked": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
```

```
      "name": "回應範例名稱",
      "description": "回應範例描述"
    },
    "authSubject": {},
    "flexTemplateJson": null,
    "flexSchema": null,
    "quickReplyConfig": null,
    "quickMenuConfig": null,
    "category": "knowledge_base",
    "displayCopyByLocale": null,
    "outputRenderTemplateByLocale": null,
    "toolDisplayMode": "full",
    "groups": [
      {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "name": "回應字串"
      }
    ],
    "createdAt": "回應字串",
    "updatedAt": "回應字串",
    "canUpdate": false,
    "canDelete": false
  }
```


列出工具

GET `/api/v1/tools/`

參數

參數名稱	必填	類型	說明
`clientPlatform`	X	string	呼叫端平台。傳入 "desktop" 時會包含 desktop 類型工具，其餘值或未傳入則預設排除 desktop 工具

`isGlobal`	X	boolean	設定為 "true" 以獲取全域工具，否則獲取組織工具
`page`	X	integer	A page number within the paginated result set.
`pageSize`	X	integer	Number of results to return per page.
`toolType`	X	string	過濾工具類型：api, function, mcp, desktop

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/tools/?
clientPlatform=desktop&isGlobal=true&page=1&pageSize=1&toolType=api"

  -H "Authorization: Api-Key YOUR_API_KEY"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/tools/?
clientPlatform=desktop&isGlobal=true&page=1&pageSize=1&toolType=api",
config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/tools/?
clientPlatform=desktop&isGlobal=true&page=1&pageSize=1&toolType=api"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->get("https://api.maiagent.ai/api/v1/tools/?
clientPlatform=desktop&isGlobal=true&page=1&pageSize=1&toolType=api",
[
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
{
  "count": integer
  "next"?: string (uri) // 非必填
  "previous"?: string (uri) // 非必填
```

```
  "results": [
    {
      "id": string (uuid)
      "name"?: // 可能有不同的類型 (非必填)
      string // Tool name may only contain letters, digits, underscores (_) and hyphens (-). Not required for MCP tools; for API tools it is the tool name given to the LLM. (非必填)
      "displayName": string // A name with any characters, used by users for configuration and management.
      "description"?: string // Tool description shown to users. Not required for MCP tools. (非必填)
      "prompt"?: string // Tool description/prompt given to the LLM. If empty, the description field is used. Not required for MCP tools. (非必填)
      "toolType"?: string (enum: api, function, mcp, desktop, flex, quick_reply, quick_menu) // * `api` - API
* `function` - Function
* `mcp` - MCP
* `desktop` - Desktop
* `flex` - Flex Message
* `quick_reply` - Quick Reply
* `quick_menu` - Quick Menu (非必填)
      "apiUrl"?: string // 非必填
      "httpMethod"?: // 可能有不同的類型 (非必填)
      string (enum: get, post, put, delete, patch) // 非必填
      "rawHeaders"?: object // 非必填
      "rawHeadersMasked": object
      "sensitiveHeaders"?: [ // 非必填
        string
      ]
      "globalSensitiveHeaders": [ // Expose platform defaults as read-only authoring guidance.
        string
      ]
      "rawQueryParams"?: object // Query string parameters appended to every request of this API tool. Values support the same {{variable}} template rendering as raw_headers. On key collision with LLM-generated arguments, these values win — use this field for API keys that must travel in the query string. (非必填)
      "rawQueryParamsMasked": object
      "rawParametersSchema"?: object // 非必填
      "functionCode"?: string // 非必填
      "organization": string (uuid)
      "createdBy": string (uuid)
      "isGlobal": boolean // If set as global tool, all organizations can use this tool
      "mcpUrl"?: string // 非必填
```

"mcpRegistry"?: string (uuid) // Registry backing this MCP tool. Null for manual-URL MCP tools. (非必填)
"mcpAllowedTools"?: object // 非必填
"rawMcpHeader"?: object // Default headers used when the Contact has no matching MCP Credential. (非必填)
"rawMcpHeaderMasked": object
"authSubject"?: // Shared uses the tool level token plus per contact credentials; contact requires per contact authentication only; caller mints a short-lived token for the conversation-bound member (falls back to per contact credentials when the conversation has no bound member). MCP tools only.

* `shared` - Shared
* `contact` - Contact
* `caller` - Caller (非必填)
{
}
"flexTemplateJson"?: object // FlexMessage JSON template. Required for FLEX_MESSAGE tools. Stores the full LINE FlexMessage JSON structure (bubble / carousel / box / text / image / button etc.). (非必填)
"flexSchema"?: object // AI dynamic field schema for FlexMessage. JSON object whose keys are field paths parsed from flex_template_json (e.g. text / image url / button label / button uri / button message). Each value may be either a plain string (the AI prompt) or an object carrying additional metadata such as a field tag, e.g. {"prompt": "...", "tag": "title"}. Empty values fall back to the template default. (非必填)
"quickReplyConfig"?: object // Authoring config for QUICK_REPLY tools. Structured JSON describing the chip buttons: static list or dynamic (LLM-generated) mode, each field either a fixed value or an LLM prompt. (非必填)
"quickMenuConfig"?: object // Authoring config for QUICK_MENU tools. Structured JSON describing the persistent input-bar menu rendered by the web chat only: layout (grid / list), default open state, and 2-6 items each carrying a display label plus an action payload (send prompt / prefill text / open http(s) link). (非必填)
"category"?: string (enum: knowledge_base, web_search, web_fetch, code_execution, file_processing, image_video_generation, database_query, third_party_integration, browser_operation, agent_collaboration, other) //
* `knowledge_base` - Knowledge base retrieval
* `web_search` - Web search
* `web_fetch` - Web page fetch
* `code_execution` - Code execution
* `file_processing` - File processing
* `image_video_generation` - Image/video generation
* `database_query` - Database query
* `third_party_integration` - Third-party integration

```
* `browser_operation` - Browser operation
* `agent_collaboration` - Agent collaboration
* `other` - Other (catch-all) (非必填)
      "displayCopyByLocale"?: object // 非必填
      "outputRenderTemplateByLocale"?: object // 非必填
      "toolDisplayMode"?: // 可能有不同的類型 (非必填)
      string (enum: full, compact, hidden) // 非必填
      "groups"?: [ // Groups this tool is assigned to. Non-owner members
must pick at least one group they belong to. (非必填)
        {
          "id": string (uuid)
          "name": string
        }
      ]
      "createdAt": string (timestamp)
      "updatedAt": string (timestamp)
      "canUpdate": boolean // Return whether the current user can update
this resource.
      "canDelete": boolean // Return whether the current user can delete
this resource.
    }
  ]
}
```

回應範例值

```
{
  "count": 123,
  "next": "http://api.example.org/accounts/?page=4",
  "previous": "http://api.example.org/accounts/?page=2",
  "results": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "回應字串",
      "displayName": "回應字串",
      "description": "回應字串",
      "prompt": "回應字串",
      "toolType": "api",
      "apiUrl": "回應字串",
      "httpMethod": "get",
      "rawHeaders": null,
      "rawHeadersMasked": {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "name": "回應範例名稱",
```

```
      "description": "回應範例描述"
    },
    "sensitiveHeaders": [
      "回應字串"
    ],
    "globalSensitiveHeaders": [
      "回應字串"
    ],
    "rawQueryParams": null,
    "rawQueryParamsMasked": {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "回應範例名稱",
      "description": "回應範例描述"
    },
    "rawParametersSchema": null,
    "functionCode": "回應字串",
    "organization": "550e8400-e29b-41d4-a716-446655440000",
    "createdBy": "550e8400-e29b-41d4-a716-446655440000",
    "isGlobal": false,
    "mcpUrl": "回應字串",
    "mcpRegistry": "550e8400-e29b-41d4-a716-446655440000",
    "mcpAllowedTools": null,
    "rawMcpHeader": null,
    "rawMcpHeaderMasked": {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "回應範例名稱",
      "description": "回應範例描述"
    },
    "authSubject": {},
    "flexTemplateJson": null,
    "flexSchema": null,
    "quickReplyConfig": null,
    "quickMenuConfig": null,
    "category": "knowledge_base",
    "displayCopyByLocale": null,
    "outputRenderTemplateByLocale": null,
    "toolDisplayMode": "full",
    "groups": [
      {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "name": "回應字串"
      }
    ],
    "createdAt": "回應字串",
    "updatedAt": "回應字串",
    "canUpdate": false,
```

```
      "canDelete": false
    }
  ]
}
```


取得特定工具

GET `/api/v1/tools/{id}`

參數

參數名稱	必填	類型	說明
id	V	string	A UUID string identifying this Tool.

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/tools/550e8400-e29b-41d4-a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/tools/550e8400-e29b-41d4-
a716-446655440000/", config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/tools/550e8400-e29b-41d4-a716-446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/tools/550e8400-e29b-41d4-a716-
446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
{
  "id": string (uuid)
  "name"?: // 可能有不同的類型 (非必填)
  string // Tool name may only contain letters, digits, underscores (_) and
```

```
hyphens (-). Not required for MCP tools; for API tools it is the tool name
given to the LLM. (非必填)
  "displayName": string // A name with any characters, used by users for
configuration and management.
  "description"?: string // Tool description shown to users. Not required
for MCP tools. (非必填)
  "prompt"?: string // Tool description/prompt given to the LLM. If empty,
the description field is used. Not required for MCP tools. (非必填)
  "toolType"?: string (enum: api, function, mcp, desktop, flex,
quick_reply, quick_menu) // * `api` - API
* `function` - Function
* `mcp` - MCP
* `desktop` - Desktop
* `flex` - Flex Message
* `quick_reply` - Quick Reply
* `quick_menu` - Quick Menu (非必填)
  "apiUrl"?: string // 非必填
  "httpMethod"?: // 可能有不同的類型 (非必填)
  string (enum: get, post, put, delete, patch) // 非必填
  "rawHeaders"?: object // 非必填
  "rawHeadersMasked": object
  "sensitiveHeaders"?: [ // 非必填
    string
  ]
  "globalSensitiveHeaders": [ // Expose platform defaults as read-only
authoring guidance.
    string
  ]
  "rawQueryParams"?: object // Query string parameters appended to every
request of this API tool. Values support the same {{variable}} template
rendering as raw_headers. On key collision with LLM-generated arguments,
these values win — use this field for API keys that must travel in the
query string. (非必填)
  "rawQueryParamsMasked": object
  "rawParametersSchema"?: object // 非必填
  "functionCode"?: string // 非必填
  "organization": string (uuid)
  "createdBy": string (uuid)
  "isGlobal": boolean // If set as global tool, all organizations can use
this tool
  "mcpUrl"?: string // 非必填
  "mcpRegistry"?: string (uuid) // Registry backing this MCP tool. Null for
manual-URL MCP tools. (非必填)
  "mcpAllowedTools"?: object // 非必填
  "rawMcpHeader"?: object // Default headers used when the Contact has no
matching MCP Credential. (非必填)
```

```
  "rawMcpHeaderMasked": object
  "authSubject"?:  // Shared uses the tool level token plus per contact
credentials; contact requires per contact authentication only; caller mints
a short-lived token for the conversation-bound member (falls back to per
contact credentials when the conversation has no bound member). MCP tools
only.

* `shared` - Shared
* `contact` - Contact
* `caller` - Caller (非必填)
  {
  }
  "flexTemplateJson"?: object // FlexMessage JSON template. Required for
FLEX_MESSAGE tools. Stores the full LINE FlexMessage JSON structure (bubble
/ carousel / box / text / image / button etc.). (非必填)
  "flexSchema"?: object // AI dynamic field schema for FlexMessage. JSON
object whose keys are field paths parsed from flex_template_json (e.g. text
/ image url / button label / button uri / button message). Each value may
be either a plain string (the AI prompt) or an object carrying additional
metadata such as a field tag, e.g. {"prompt": "...", "tag": "title"}. Empty
values fall back to the template default. (非必填)
  "quickReplyConfig"?: object // Authoring config for QUICK_REPLY tools.
Structured JSON describing the chip buttons: static list or dynamic (LLM-
generated) mode, each field either a fixed value or an LLM prompt. (非必填)
  "quickMenuConfig"?: object // Authoring config for QUICK_MENU tools.
Structured JSON describing the persistent input-bar menu rendered by the
web chat only: layout (grid / list), default open state, and 2-6 items each
carrying a display label plus an action payload (send prompt / prefill text
/ open http(s) link). (非必填)
  "category"?: string (enum: knowledge_base, web_search, web_fetch,
code_execution, file_processing, image_video_generation, database_query,
third_party_integration, browser_operation, agent_collaboration, other) //
* `knowledge_base` - Knowledge base retrieval
* `web_search` - Web search
* `web_fetch` - Web page fetch
* `code_execution` - Code execution
* `file_processing` - File processing
* `image_video_generation` - Image/video generation
* `database_query` - Database query
* `third_party_integration` - Third-party integration
* `browser_operation` - Browser operation
* `agent_collaboration` - Agent collaboration
* `other` - Other (catch-all) (非必填)
  "displayCopyByLocale"?: object // 非必填
  "outputRenderTemplateByLocale"?: object // 非必填
  "toolDisplayMode"?: // 可能有不同的類型 (非必填)
```

```
  string (enum: full, compact, hidden) // 非必填
  "groups"?: [ // Groups this tool is assigned to. Non-owner members must
pick at least one group they belong to. (非必填)
    {
      "id": string (uuid)
      "name": string
    }
  ]
  "createdAt": string (timestamp)
  "updatedAt": string (timestamp)
  "canUpdate": boolean // Return whether the current user can update this
resource.
  "canDelete": boolean // Return whether the current user can delete this
resource.
}
```

回應範例值

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "name": "回應字串",
  "displayName": "回應字串",
  "description": "回應字串",
  "prompt": "回應字串",
  "toolType": "api",
  "apiUrl": "回應字串",
  "httpMethod": "get",
  "rawHeaders": null,
  "rawHeadersMasked": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應範例名稱",
    "description": "回應範例描述"
  },
  "sensitiveHeaders": [
    "回應字串"
  ],
  "globalSensitiveHeaders": [
    "回應字串"
  ],
  "rawQueryParams": null,
  "rawQueryParamsMasked": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應範例名稱",
    "description": "回應範例描述"
```

```
  },
  "rawParametersSchema": null,
  "functionCode": "回應字串",
  "organization": "550e8400-e29b-41d4-a716-446655440000",
  "createdBy": "550e8400-e29b-41d4-a716-446655440000",
  "isGlobal": false,
  "mcpUrl": "回應字串",
  "mcpRegistry": "550e8400-e29b-41d4-a716-446655440000",
  "mcpAllowedTools": null,
  "rawMcpHeader": null,
  "rawMcpHeaderMasked": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應範例名稱",
    "description": "回應範例描述"
  },
  "authSubject": {},
  "flexTemplateJson": null,
  "flexSchema": null,
  "quickReplyConfig": null,
  "quickMenuConfig": null,
  "category": "knowledge_base",
  "displayCopyByLocale": null,
  "outputRenderTemplateByLocale": null,
  "toolDisplayMode": "full",
  "groups": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "回應字串"
    }
  ],
  "createdAt": "回應字串",
  "updatedAt": "回應字串",
  "canUpdate": false,
  "canDelete": false
}
```


更新工具

`PUT` `/api/v1/tools/{id}`

參數

參數名稱	必填	類型	說明
`id`	V	string	A UUID string identifying this Tool.

請求內容

請求參數

欄位	類型	必填	說明
name	object	否	Tool name may only contain letters, digits, underscores (_) and hyphens (-). Not required for MCP tools; for API tools it is the tool name given to the LLM.
displayName	string	是	A name with any characters, used by users for configuration and management.
description	string	否	Tool description shown to users. Not required for MCP tools.
prompt	string	否	Tool description/prompt given to the LLM. If empty, the description field is used. Not required for MCP tools.
toolType	string (enum: api, function, mcp, desktop, flex, quick_reply, quick_menu)	否	`api` : API ; `function` : Function ; `mcp` : MCP ; `desktop` : Desktop ; `flex` : Flex Message ; `quick_reply` : Quick

欄位	類型	必填	說明
			Reply ; `quick_menu` : Quick Menu;
apiUrl	string	否	
httpMethod	object	否	
rawHeaders	object	否	
sensitiveHeaders	array[string]	否	
rawQueryParams	object	否	Query string parameters appended to every request of this API tool. Values support the same {{variable}} template rendering as raw_headers. On key collision with LLM-generated arguments, these values ...
rawParametersSchema	object	否	
functionCode	string	否	
mcpUrl	string	否	
mcpRegistry	string (uuid)	否	Registry backing this MCP tool. Null for manual-URL MCP tools.
mcpAllowedTools	object	否	
rawMcpHeader	object	否	Default headers used when the Contact has no matching MCP Credential.
authSubject	object	否	Shared uses the tool level token plus per contact credentials; contact requires per contact authentication only; caller mints a short-lived token for the conversation-bound member (falls back to per c...

欄位	類型	必填	說明
flexTemplateJson	object	否	FlexMessage JSON template. Required for FLEX_MESSAGE tools. Stores the full LINE FlexMessage JSON structure (bubble / carousel / box / text / image / button etc.).
flexSchema	object	否	AI dynamic field schema for FlexMessage. JSON object whose keys are field paths parsed from flex_template_json (e.g. text / image url / button label / button uri / button message). Each value may be e...
quickReplyConfig	object	否	Authoring config for QUICK_REPLY tools. Structured JSON describing the chip buttons: static list or dynamic (LLM-generated) mode, each field either a fixed value or an LLM prompt.
quickMenuConfig	object	否	Authoring config for QUICK_MENU tools. Structured JSON describing the persistent input-bar menu rendered by the web chat only: layout (grid / list), default open state, and 2-6 items each carrying a d...
category	string (enum: knowledge_base, web_search, web_fetch, code_execution, file_processing,	否	`knowledge_base` : Knowledge base retrieval ; `web_search` : Web search ; `web_fetch` : Web page fetch ; `code_execution` :

欄位	類型	必填	說明
	image_video_generation, database_query, third_party_integration, browser_operation, agent_collaboration, other)		Code execution ; `file_processing` : File processing ; `image_video_generation` : ...
displayCopyByLocale	object	否	
outputRenderTemplateByLocale	object	否	
toolDisplayMode	object	否	
groups	array[IdName]	否	Groups this tool is assigned to. Non-owner members must pick at least one group they belong to.

請求結構範例

```
{
  "name"?: // 可能有不同的類型 (非必填)
  string // Tool name may only contain letters, digits, underscores (_) and hyphens (-). Not required for MCP tools; for API tools it is the tool name given to the LLM. (非必填)
  "displayName": string // A name with any characters, used by users for configuration and management.
  "description"?: string // Tool description shown to users. Not required for MCP tools. (非必填)
  "prompt"?: string // Tool description/prompt given to the LLM. If empty, the description field is used. Not required for MCP tools. (非必填)
  "toolType"?: string (enum: api, function, mcp, desktop, flex, quick_reply, quick_menu) // * `api` - API
* `function` - Function
* `mcp` - MCP
* `desktop` - Desktop
* `flex` - Flex Message
* `quick_reply` - Quick Reply
* `quick_menu` - Quick Menu (非必填)
  "apiUrl"?: string // 非必填
  "httpMethod"?: // 可能有不同的類型 (非必填)
  string (enum: get, post, put, delete, patch) // 非必填
```

```
  "rawHeaders"?: object // 非必填
  "sensitiveHeaders"?: [ // 非必填
    string
  ]
  "rawQueryParams"?: object // Query string parameters appended to every request of this API tool. Values support the same {{variable}} template rendering as raw_headers. On key collision with LLM-generated arguments, these values win — use this field for API keys that must travel in the query string. (非必填)
  "rawParametersSchema"?: object // 非必填
  "functionCode"?: string // 非必填
  "mcpUrl"?: string // 非必填
  "mcpRegistry"?: string (uuid) // Registry backing this MCP tool. Null for manual-URL MCP tools. (非必填)
  "mcpAllowedTools"?: object // 非必填
  "rawMcpHeader"?: object // Default headers used when the Contact has no matching MCP Credential. (非必填)
  "authSubject"?:  // Shared uses the tool level token plus per contact credentials; contact requires per contact authentication only; caller mints a short-lived token for the conversation-bound member (falls back to per contact credentials when the conversation has no bound member). MCP tools only.

* `shared` - Shared
* `contact` - Contact
* `caller` - Caller (非必填)
  {
  }
  "flexTemplateJson"?: object // FlexMessage JSON template. Required for FLEX_MESSAGE tools. Stores the full LINE FlexMessage JSON structure (bubble / carousel / box / text / image / button etc.). (非必填)
  "flexSchema"?: object // AI dynamic field schema for FlexMessage. JSON object whose keys are field paths parsed from flex_template_json (e.g. text / image url / button label / button uri / button message). Each value may be either a plain string (the AI prompt) or an object carrying additional metadata such as a field tag, e.g. {"prompt": "...", "tag": "title"}. Empty values fall back to the template default. (非必填)
  "quickReplyConfig"?: object // Authoring config for QUICK_REPLY tools. Structured JSON describing the chip buttons: static list or dynamic (LLM-generated) mode, each field either a fixed value or an LLM prompt. (非必填)
  "quickMenuConfig"?: object // Authoring config for QUICK_MENU tools. Structured JSON describing the persistent input-bar menu rendered by the web chat only: layout (grid / list), default open state, and 2-6 items each carrying a display label plus an action payload (send prompt / prefill text / open http(s) link). (非必填)
  "category"?: string (enum: knowledge_base, web_search, web_fetch,
```

```
code_execution, file_processing, image_video_generation, database_query,
third_party_integration, browser_operation, agent_collaboration, other) //
* `knowledge_base` - Knowledge base retrieval
* `web_search` - Web search
* `web_fetch` - Web page fetch
* `code_execution` - Code execution
* `file_processing` - File processing
* `image_video_generation` - Image/video generation
* `database_query` - Database query
* `third_party_integration` - Third-party integration
* `browser_operation` - Browser operation
* `agent_collaboration` - Agent collaboration
* `other` - Other (catch-all) (非必填)
  "displayCopyByLocale"?: object // 非必填
  "outputRenderTemplateByLocale"?: object // 非必填
  "toolDisplayMode"?: // 可能有不同的類型 (非必填)
  string (enum: full, compact, hidden) // 非必填
  "groups"?: [ // Groups this tool is assigned to. Non-owner members must
pick at least one group they belong to. (非必填)
    {
      "id": string (uuid)
    }
  ]
}
```

請求範例值

```
{
  "name": null,
  "displayName": "範例字串",
  "description": "範例字串",
  "prompt": "範例字串",
  "toolType": "api",
  "apiUrl": "範例字串",
  "httpMethod": null,
  "rawHeaders": null,
  "sensitiveHeaders": [
    "範例字串"
  ],
  "rawQueryParams": null,
  "rawParametersSchema": null,
  "functionCode": "範例字串",
  "mcpUrl": "範例字串",
  "mcpRegistry": "550e8400-e29b-41d4-a716-446655440000",
```

```
  "mcpAllowedTools": null,
  "rawMcpHeader": null,
  "authSubject": {},
  "flexTemplateJson": null,
  "flexSchema": null,
  "quickReplyConfig": null,
  "quickMenuConfig": null,
  "category": "knowledge_base",
  "displayCopyByLocale": null,
  "outputRenderTemplateByLocale": null,
  "toolDisplayMode": null,
  "groups": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000"
    }
  ]
}
```

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X PUT "https://api.maiagent.ai/api/v1/tools/550e8400-e29b-41d4-
a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "name": null,
    "displayName": "範例字串",
    "description": "範例字串",
    "prompt": "範例字串",
    "toolType": "api",
    "apiUrl": "範例字串",
    "httpMethod": null,
    "rawHeaders": null,
    "sensitiveHeaders": [
      "範例字串"
    ],
    "rawQueryParams": null,
    "rawParametersSchema": null,
    "functionCode": "範例字串",
    "mcpUrl": "範例字串",
    "mcpRegistry": "550e8400-e29b-41d4-a716-446655440000",
    "mcpAllowedTools": null,
    "rawMcpHeader": null,
    "authSubject": {},
    "flexTemplateJson": null,
    "flexSchema": null,
    "quickReplyConfig": null,
    "quickMenuConfig": null,
    "category": "knowledge_base",
    "displayCopyByLocale": null,
    "outputRenderTemplateByLocale": null,
    "toolDisplayMode": null,
    "groups": [
      {
        "id": "550e8400-e29b-41d4-a716-446655440000"
      }
    ]
```

```
  }'

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// 請求內容 (payload)
const data = {
    "name": null,
    "displayName": "範例字串",
    "description": "範例字串",
    "prompt": "範例字串",
    "toolType": "api",
    "apiUrl": "範例字串",
    "httpMethod": null,
    "rawHeaders": null,
    "sensitiveHeaders": [
      "範例字串"
    ],
    "rawQueryParams": null,
    "rawParametersSchema": null,
    "functionCode": "範例字串",
    "mcpUrl": "範例字串",
    "mcpRegistry": "550e8400-e29b-41d4-a716-446655440000",
    "mcpAllowedTools": null,
    "rawMcpHeader": null,
    "authSubject": {},
    "flexTemplateJson": null,
    "flexSchema": null,
    "quickReplyConfig": null,
    "quickMenuConfig": null,
    "category": "knowledge_base",
    "displayCopyByLocale": null,
    "outputRenderTemplateByLocale": null,
    "toolDisplayMode": null,
    "groups": [
      {
```

```
        "id": "550e8400-e29b-41d4-a716-446655440000"
      }
    ]
  };

axios.put("https://api.maiagent.ai/api/v1/tools/550e8400-e29b-41d4-
a716-446655440000/", data, config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/tools/550e8400-e29b-41d4-a716-
446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# 請求內容 (payload)
data = {
    "name": None,
    "displayName": "範例字串",
    "description": "範例字串",
    "prompt": "範例字串",
    "toolType": "api",
    "apiUrl": "範例字串",
    "httpMethod": None,
    "rawHeaders": None,
    "sensitiveHeaders": [
        "範例字串"
    ],
    "rawQueryParams": None,
    "rawParametersSchema": None,
    "functionCode": "範例字串",
    "mcpUrl": "範例字串",
    "mcpRegistry": "550e8400-e29b-41d4-a716-446655440000",
    "mcpAllowedTools": None,
    "rawMcpHeader": None,
    "authSubject": {},
    "flexTemplateJson": None,
    "flexSchema": None,
    "quickReplyConfig": None,
    "quickMenuConfig": None,
    "category": "knowledge_base",
    "displayCopyByLocale": None,
    "outputRenderTemplateByLocale": None,
    "toolDisplayMode": None,
    "groups": [
        {
            "id": "550e8400-e29b-41d4-a716-446655440000"
```

```
        }
    ]
}

response = requests.put(url, json=data, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>put("https://api.maiagent.ai/api/v1/tools/550e8400-e29b-41d4-a716-
446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'name' => null,
            'displayName' => '範例字串',
            'description' => '範例字串',
            'prompt' => '範例字串',
            'toolType' => 'api',
            'apiUrl' => '範例字串',
            'httpMethod' => null,
            'rawHeaders' => null,
            'sensitiveHeaders' => [
                '範例字串'
            ],
            'rawQueryParams' => null,
            'rawParametersSchema' => null,
            'functionCode' => '範例字串',
            'mcpUrl' => '範例字串',
            'mcpRegistry' => '550e8400-e29b-41d4-a716-446655440000',
            'mcpAllowedTools' => null,
            'rawMcpHeader' => null,
            'authSubject' => new \stdClass(),
            'flexTemplateJson' => null,
            'flexSchema' => null,
            'quickReplyConfig' => null,
            'quickMenuConfig' => null,
            'category' => 'knowledge_base',
            'displayCopyByLocale' => null,
            'outputRenderTemplateByLocale' => null,
            'toolDisplayMode' => null,
```

```
            'groups' => [
                [
                    'id' => '550e8400-e29b-41d4-a716-446655440000'
                ]
            ]
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
{
  "id": string (uuid)
  "name"?: // 可能有不同的類型 (非必填)
  string // Tool name may only contain letters, digits, underscores (_) and
hyphens (-). Not required for MCP tools; for API tools it is the tool name
given to the LLM. (非必填)
  "displayName": string // A name with any characters, used by users for
configuration and management.
  "description"?: string // Tool description shown to users. Not required
for MCP tools. (非必填)
  "prompt"?: string // Tool description/prompt given to the LLM. If empty,
the description field is used. Not required for MCP tools. (非必填)
  "toolType"?: string (enum: api, function, mcp, desktop, flex,
quick_reply, quick_menu) // * `api` - API
* `function` - Function
```

```
* `mcp` - MCP
* `desktop` - Desktop
* `flex` - Flex Message
* `quick_reply` - Quick Reply
* `quick_menu` - Quick Menu (非必填)
  "apiUrl"?: string // 非必填
  "httpMethod"?: // 可能有不同的類型 (非必填)
  string (enum: get, post, put, delete, patch) // 非必填
  "rawHeaders"?: object // 非必填
  "rawHeadersMasked": object
  "sensitiveHeaders"?: [ // 非必填
    string
  ]
  "globalSensitiveHeaders": [ // Expose platform defaults as read-only
authoring guidance.
    string
  ]
  "rawQueryParams"?: object // Query string parameters appended to every
request of this API tool. Values support the same {{variable}} template
rendering as raw_headers. On key collision with LLM-generated arguments,
these values win — use this field for API keys that must travel in the
query string. (非必填)
  "rawQueryParamsMasked": object
  "rawParametersSchema"?: object // 非必填
  "functionCode"?: string // 非必填
  "organization": string (uuid)
  "createdBy": string (uuid)
  "isGlobal": boolean // If set as global tool, all organizations can use
this tool
  "mcpUrl"?: string // 非必填
  "mcpRegistry"?: string (uuid) // Registry backing this MCP tool. Null for
manual-URL MCP tools. (非必填)
  "mcpAllowedTools"?: object // 非必填
  "rawMcpHeader"?: object // Default headers used when the Contact has no
matching MCP Credential. (非必填)
  "rawMcpHeaderMasked": object
  "authSubject"?:  // Shared uses the tool level token plus per contact
credentials; contact requires per contact authentication only; caller mints
a short-lived token for the conversation-bound member (falls back to per
contact credentials when the conversation has no bound member). MCP tools
only.

* `shared` - Shared
* `contact` - Contact
* `caller` - Caller (非必填)
  {
```

```
  }
  "flexTemplateJson"?: object // FlexMessage JSON template. Required for
FLEX_MESSAGE tools. Stores the full LINE FlexMessage JSON structure (bubble
/ carousel / box / text / image / button etc.). (非必填)
  "flexSchema"?: object // AI dynamic field schema for FlexMessage. JSON
object whose keys are field paths parsed from flex_template_json (e.g. text
/ image url / button label / button uri / button message). Each value may
be either a plain string (the AI prompt) or an object carrying additional
metadata such as a field tag, e.g. {"prompt": "...", "tag": "title"}. Empty
values fall back to the template default. (非必填)
  "quickReplyConfig"?: object // Authoring config for QUICK_REPLY tools.
Structured JSON describing the chip buttons: static list or dynamic (LLM-
generated) mode, each field either a fixed value or an LLM prompt. (非必填)
  "quickMenuConfig"?: object // Authoring config for QUICK_MENU tools.
Structured JSON describing the persistent input-bar menu rendered by the
web chat only: layout (grid / list), default open state, and 2-6 items each
carrying a display label plus an action payload (send prompt / prefill text
/ open http(s) link). (非必填)
  "category"?: string (enum: knowledge_base, web_search, web_fetch,
code_execution, file_processing, image_video_generation, database_query,
third_party_integration, browser_operation, agent_collaboration, other) //
* `knowledge_base` - Knowledge base retrieval
* `web_search` - Web search
* `web_fetch` - Web page fetch
* `code_execution` - Code execution
* `file_processing` - File processing
* `image_video_generation` - Image/video generation
* `database_query` - Database query
* `third_party_integration` - Third-party integration
* `browser_operation` - Browser operation
* `agent_collaboration` - Agent collaboration
* `other` - Other (catch-all) (非必填)
  "displayCopyByLocale"?: object // 非必填
  "outputRenderTemplateByLocale"?: object // 非必填
  "toolDisplayMode"?: // 可能有不同的類型 (非必填)
  string (enum: full, compact, hidden) // 非必填
  "groups"?: [ // Groups this tool is assigned to. Non-owner members must
pick at least one group they belong to. (非必填)
    {
      "id": string (uuid)
      "name": string
    }
  ]
  "createdAt": string (timestamp)
  "updatedAt": string (timestamp)
  "canUpdate": boolean // Return whether the current user can update this
```

```
resource.
  "canDelete": boolean // Return whether the current user can delete this
resource.
}
```

回應範例值


```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "name": "回應字串",
  "displayName": "回應字串",
  "description": "回應字串",
  "prompt": "回應字串",
  "toolType": "api",
  "apiUrl": "回應字串",
  "httpMethod": "get",
  "rawHeaders": null,
  "rawHeadersMasked": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應範例名稱",
    "description": "回應範例描述"
  },
  "sensitiveHeaders": [
    "回應字串"
  ],
  "globalSensitiveHeaders": [
    "回應字串"
  ],
  "rawQueryParams": null,
  "rawQueryParamsMasked": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應範例名稱",
    "description": "回應範例描述"
  },
  "rawParametersSchema": null,
  "functionCode": "回應字串",
  "organization": "550e8400-e29b-41d4-a716-446655440000",
  "createdBy": "550e8400-e29b-41d4-a716-446655440000",
  "isGlobal": false,
  "mcpUrl": "回應字串",
  "mcpRegistry": "550e8400-e29b-41d4-a716-446655440000",
  "mcpAllowedTools": null,
  "rawMcpHeader": null,
  "rawMcpHeaderMasked": {
```

```
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "回應範例名稱",
      "description": "回應範例描述"
    },
    "authSubject": {},
    "flexTemplateJson": null,
    "flexSchema": null,
    "quickReplyConfig": null,
    "quickMenuConfig": null,
    "category": "knowledge_base",
    "displayCopyByLocale": null,
    "outputRenderTemplateByLocale": null,
    "toolDisplayMode": "full",
    "groups": [
      {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "name": "回應字串"
      }
    ],
    "createdAt": "回應字串",
    "updatedAt": "回應字串",
    "canUpdate": false,
    "canDelete": false
  }
```


部分更新工具

`PATCH` `/api/v1/tools/{id}`

參數

參數名稱	必填	類型	說明
`id`	V	string	A UUID string identifying this Tool.

請求內容

請求參數

欄位	類型	必填	說明
name	object	否	Tool name may only contain letters, digits, underscores (_) and hyphens (-). Not required for MCP tools; for API tools it is the tool name given to the LLM.
displayName	string	否	A name with any characters, used by users for configuration and management.
description	string	否	Tool description shown to users. Not required for MCP tools.
prompt	string	否	Tool description/prompt given to the LLM. If empty, the description field is used. Not required for MCP tools.
toolType	string (enum: api, function, mcp, desktop, flex, quick_reply, quick_menu)	否	`api` : API ; `function` : Function ; `mcp` : MCP ; `desktop` : Desktop ; `flex` : Flex Message ; `quick_reply` : Quick Reply ; `quick_menu` : Quick Menu;
apiUrl	string	否	
httpMethod	object	否	
rawHeaders	object	否	
sensitiveHeaders	array[string]	否	

欄位	類型	必填	說明
rawQueryParams	object	否	Query string parameters appended to every request of this API tool. Values support the same {{variable}} template rendering as raw_headers. On key collision with LLM-generated arguments, these values ...
rawParametersSchema	object	否	
functionCode	string	否	
mcpUrl	string	否	
mcpRegistry	string (uuid)	否	Registry backing this MCP tool. Null for manual-URL MCP tools.
mcpAllowedTools	object	否	
rawMcpHeader	object	否	Default headers used when the Contact has no matching MCP Credential.
authSubject	object	否	Shared uses the tool level token plus per contact credentials; contact requires per contact authentication only; caller mints a short-lived token for the conversation-bound member (falls back to per c...
flexTemplateJson	object	否	FlexMessage JSON template. Required for FLEX_MESSAGE tools. Stores the full LINE FlexMessage JSON structure (bubble / carousel / box / text / image / button etc.).

欄位	類型	必填	說明
flexSchema	object	否	AI dynamic field schema for FlexMessage. JSON object whose keys are field paths parsed from flex_template_json (e.g. text / image url / button label / button uri / button message). Each value may be e...
quickReplyConfig	object	否	Authoring config for QUICK_REPLY tools. Structured JSON describing the chip buttons: static list or dynamic (LLM-generated) mode, each field either a fixed value or an LLM prompt.
quickMenuConfig	object	否	Authoring config for QUICK_MENU tools. Structured JSON describing the persistent input-bar menu rendered by the web chat only: layout (grid / list), default open state, and 2-6 items each carrying a d...
category	string (enum: knowledge_base, web_search, web_fetch, code_execution, file_processing, image_video_generation, database_query, third_party_integration, browser_operation, agent_collaboration, other)	否	`knowledge_base` : Knowledge base retrieval ; `web_search` : Web search ; `web_fetch` : Web page fetch ; `code_execution` : Code execution ; `file_processing` : File processing ; `image_video_generation` : ...
displayCopyByLocale	object	否	

欄位	類型	必填	說明
outputRenderTemplateByLocale	object	否	
toolDisplayMode	object	否	
groups	array[IdName]	否	Groups this tool is assigned to. Non-owner members must pick at least one group they belong to.

請求結構範例

```
{
  "name"?: // 可能有不同的類型 (非必填)
  string // Tool name may only contain letters, digits, underscores (_) and hyphens (-). Not required for MCP tools; for API tools it is the tool name given to the LLM. (非必填)
  "displayName"?: string // A name with any characters, used by users for configuration and management. (非必填)
  "description"?: string // Tool description shown to users. Not required for MCP tools. (非必填)
  "prompt"?: string // Tool description/prompt given to the LLM. If empty, the description field is used. Not required for MCP tools. (非必填)
  "toolType"?: string (enum: api, function, mcp, desktop, flex, quick_reply, quick_menu) // * `api` - API
* `function` - Function
* `mcp` - MCP
* `desktop` - Desktop
* `flex` - Flex Message
* `quick_reply` - Quick Reply
* `quick_menu` - Quick Menu (非必填)
  "apiUrl"?: string // 非必填
  "httpMethod"?: // 可能有不同的類型 (非必填)
  string (enum: get, post, put, delete, patch) // 非必填
  "rawHeaders"?: object // 非必填
  "sensitiveHeaders"?: [ // 非必填
    string
  ]
  "rawQueryParams"?: object // Query string parameters appended to every request of this API tool. Values support the same {{variable}} template rendering as raw_headers. On key collision with LLM-generated arguments, these values win — use this field for API keys that must travel in the
```

```
query string. (非必填)
  "rawParametersSchema"?: object // 非必填
  "functionCode"?: string // 非必填
  "mcpUrl"?: string // 非必填
  "mcpRegistry"?: string (uuid) // Registry backing this MCP tool. Null for
manual-URL MCP tools. (非必填)
  "mcpAllowedTools"?: object // 非必填
  "rawMcpHeader"?: object // Default headers used when the Contact has no
matching MCP Credential. (非必填)
  "authSubject"?:  // Shared uses the tool level token plus per contact
credentials; contact requires per contact authentication only; caller mints
a short-lived token for the conversation-bound member (falls back to per
contact credentials when the conversation has no bound member). MCP tools
only.

* `shared` - Shared
* `contact` - Contact
* `caller` - Caller (非必填)
  {
  }
  "flexTemplateJson"?: object // FlexMessage JSON template. Required for
FLEX_MESSAGE tools. Stores the full LINE FlexMessage JSON structure (bubble
/ carousel / box / text / image / button etc.). (非必填)
  "flexSchema"?: object // AI dynamic field schema for FlexMessage. JSON
object whose keys are field paths parsed from flex_template_json (e.g. text
/ image url / button label / button uri / button message). Each value may
be either a plain string (the AI prompt) or an object carrying additional
metadata such as a field tag, e.g. {"prompt": "...", "tag": "title"}. Empty
values fall back to the template default. (非必填)
  "quickReplyConfig"?: object // Authoring config for QUICK_REPLY tools.
Structured JSON describing the chip buttons: static list or dynamic (LLM-
generated) mode, each field either a fixed value or an LLM prompt. (非必填)
  "quickMenuConfig"?: object // Authoring config for QUICK_MENU tools.
Structured JSON describing the persistent input-bar menu rendered by the
web chat only: layout (grid / list), default open state, and 2-6 items each
carrying a display label plus an action payload (send prompt / prefill text
/ open http(s) link). (非必填)
  "category"?: string (enum: knowledge_base, web_search, web_fetch,
code_execution, file_processing, image_video_generation, database_query,
third_party_integration, browser_operation, agent_collaboration, other) //
* `knowledge_base` - Knowledge base retrieval
* `web_search` - Web search
* `web_fetch` - Web page fetch
* `code_execution` - Code execution
* `file_processing` - File processing
* `image_video_generation` - Image/video generation
```

```
* `database_query` - Database query
* `third_party_integration` - Third-party integration
* `browser_operation` - Browser operation
* `agent_collaboration` - Agent collaboration
* `other` - Other (catch-all) (非必填)
  "displayCopyByLocale"?: object // 非必填
  "outputRenderTemplateByLocale"?: object // 非必填
  "toolDisplayMode"?: // 可能有不同的類型 (非必填)
  string (enum: full, compact, hidden) // 非必填
  "groups"?: [ // Groups this tool is assigned to. Non-owner members must
pick at least one group they belong to. (非必填)
    {
      "id": string (uuid)
    }
  ]
}
```

請求範例值

```
{
  "name": null,
  "displayName": "範例字串",
  "description": "範例字串",
  "prompt": "範例字串",
  "toolType": "api",
  "apiUrl": "範例字串",
  "httpMethod": null,
  "rawHeaders": null,
  "sensitiveHeaders": [
    "範例字串"
  ],
  "rawQueryParams": null,
  "rawParametersSchema": null,
  "functionCode": "範例字串",
  "mcpUrl": "範例字串",
  "mcpRegistry": "550e8400-e29b-41d4-a716-446655440000",
  "mcpAllowedTools": null,
  "rawMcpHeader": null,
  "authSubject": {},
  "flexTemplateJson": null,
  "flexSchema": null,
  "quickReplyConfig": null,
  "quickMenuConfig": null,
  "category": "knowledge_base",
```

```
  "displayCopyByLocale": null,
  "outputRenderTemplateByLocale": null,
  "toolDisplayMode": null,
  "groups": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000"
    }
  ]
}
```

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X PATCH "https://api.maiagent.ai/api/v1/tools/550e8400-e29b-
41d4-a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "name": null,
    "displayName": "範例字串",
    "description": "範例字串",
    "prompt": "範例字串",
    "toolType": "api",
    "apiUrl": "範例字串",
    "httpMethod": null,
    "rawHeaders": null,
    "sensitiveHeaders": [
      "範例字串"
    ],
    "rawQueryParams": null,
    "rawParametersSchema": null,
    "functionCode": "範例字串",
    "mcpUrl": "範例字串",
    "mcpRegistry": "550e8400-e29b-41d4-a716-446655440000",
    "mcpAllowedTools": null,
    "rawMcpHeader": null,
    "authSubject": {},
    "flexTemplateJson": null,
    "flexSchema": null,
    "quickReplyConfig": null,
    "quickMenuConfig": null,
    "category": "knowledge_base",
    "displayCopyByLocale": null,
    "outputRenderTemplateByLocale": null,
    "toolDisplayMode": null,
    "groups": [
      {
        "id": "550e8400-e29b-41d4-a716-446655440000"
      }
    ]
```

```
  }'

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// 請求內容 (payload)
const data = {
    "name": null,
    "displayName": "範例字串",
    "description": "範例字串",
    "prompt": "範例字串",
    "toolType": "api",
    "apiUrl": "範例字串",
    "httpMethod": null,
    "rawHeaders": null,
    "sensitiveHeaders": [
      "範例字串"
    ],
    "rawQueryParams": null,
    "rawParametersSchema": null,
    "functionCode": "範例字串",
    "mcpUrl": "範例字串",
    "mcpRegistry": "550e8400-e29b-41d4-a716-446655440000",
    "mcpAllowedTools": null,
    "rawMcpHeader": null,
    "authSubject": {},
    "flexTemplateJson": null,
    "flexSchema": null,
    "quickReplyConfig": null,
    "quickMenuConfig": null,
    "category": "knowledge_base",
    "displayCopyByLocale": null,
    "outputRenderTemplateByLocale": null,
    "toolDisplayMode": null,
    "groups": [
      {
```

```
        "id": "550e8400-e29b-41d4-a716-446655440000"
      }
    ]
  };

axios.patch("https://api.maiagent.ai/api/v1/tools/550e8400-e29b-41d4-
a716-446655440000/", data, config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/tools/550e8400-e29b-41d4-a716-
446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# 請求內容 (payload)
data = {
    "name": None,
    "displayName": "範例字串",
    "description": "範例字串",
    "prompt": "範例字串",
    "toolType": "api",
    "apiUrl": "範例字串",
    "httpMethod": None,
    "rawHeaders": None,
    "sensitiveHeaders": [
        "範例字串"
    ],
    "rawQueryParams": None,
    "rawParametersSchema": None,
    "functionCode": "範例字串",
    "mcpUrl": "範例字串",
    "mcpRegistry": "550e8400-e29b-41d4-a716-446655440000",
    "mcpAllowedTools": None,
    "rawMcpHeader": None,
    "authSubject": {},
    "flexTemplateJson": None,
    "flexSchema": None,
    "quickReplyConfig": None,
    "quickMenuConfig": None,
    "category": "knowledge_base",
    "displayCopyByLocale": None,
    "outputRenderTemplateByLocale": None,
    "toolDisplayMode": None,
    "groups": [
        {
            "id": "550e8400-e29b-41d4-a716-446655440000"
```

```
        }
    ]
}

response = requests.patch(url, json=data, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>patch("https://api.maiagent.ai/api/v1/tools/550e8400-e29b-41d4-a716-
446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'name' => null,
            'displayName' => '範例字串',
            'description' => '範例字串',
            'prompt' => '範例字串',
            'toolType' => 'api',
            'apiUrl' => '範例字串',
            'httpMethod' => null,
            'rawHeaders' => null,
            'sensitiveHeaders' => [
                '範例字串'
            ],
            'rawQueryParams' => null,
            'rawParametersSchema' => null,
            'functionCode' => '範例字串',
            'mcpUrl' => '範例字串',
            'mcpRegistry' => '550e8400-e29b-41d4-a716-446655440000',
            'mcpAllowedTools' => null,
            'rawMcpHeader' => null,
            'authSubject' => new \stdClass(),
            'flexTemplateJson' => null,
            'flexSchema' => null,
            'quickReplyConfig' => null,
            'quickMenuConfig' => null,
            'category' => 'knowledge_base',
            'displayCopyByLocale' => null,
            'outputRenderTemplateByLocale' => null,
            'toolDisplayMode' => null,
```

```
            'groups' => [
                [
                    'id' => '550e8400-e29b-41d4-a716-446655440000'
                ]
            ]
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
{
  "id": string (uuid)
  "name"?: // 可能有不同的類型 (非必填)
  string // Tool name may only contain letters, digits, underscores (_) and
hyphens (-). Not required for MCP tools; for API tools it is the tool name
given to the LLM. (非必填)
  "displayName": string // A name with any characters, used by users for
configuration and management.
  "description"?: string // Tool description shown to users. Not required
for MCP tools. (非必填)
  "prompt"?: string // Tool description/prompt given to the LLM. If empty,
the description field is used. Not required for MCP tools. (非必填)
  "toolType"?: string (enum: api, function, mcp, desktop, flex,
quick_reply, quick_menu) // * `api` - API
* `function` - Function
```

```
* `mcp` - MCP
* `desktop` - Desktop
* `flex` - Flex Message
* `quick_reply` - Quick Reply
* `quick_menu` - Quick Menu (非必填)
  "apiUrl"?: string // 非必填
  "httpMethod"?: // 可能有不同的類型 (非必填)
  string (enum: get, post, put, delete, patch) // 非必填
  "rawHeaders"?: object // 非必填
  "rawHeadersMasked": object
  "sensitiveHeaders"?: [ // 非必填
    string
  ]
  "globalSensitiveHeaders": [ // Expose platform defaults as read-only
authoring guidance.
    string
  ]
  "rawQueryParams"?: object // Query string parameters appended to every
request of this API tool. Values support the same {{variable}} template
rendering as raw_headers. On key collision with LLM-generated arguments,
these values win — use this field for API keys that must travel in the
query string. (非必填)
  "rawQueryParamsMasked": object
  "rawParametersSchema"?: object // 非必填
  "functionCode"?: string // 非必填
  "organization": string (uuid)
  "createdBy": string (uuid)
  "isGlobal": boolean // If set as global tool, all organizations can use
this tool
  "mcpUrl"?: string // 非必填
  "mcpRegistry"?: string (uuid) // Registry backing this MCP tool. Null for
manual-URL MCP tools. (非必填)
  "mcpAllowedTools"?: object // 非必填
  "rawMcpHeader"?: object // Default headers used when the Contact has no
matching MCP Credential. (非必填)
  "rawMcpHeaderMasked": object
  "authSubject"?:  // Shared uses the tool level token plus per contact
credentials; contact requires per contact authentication only; caller mints
a short-lived token for the conversation-bound member (falls back to per
contact credentials when the conversation has no bound member). MCP tools
only.

* `shared` - Shared
* `contact` - Contact
* `caller` - Caller (非必填)
  {
```

```
  }
  "flexTemplateJson"?: object // FlexMessage JSON template. Required for
FLEX_MESSAGE tools. Stores the full LINE FlexMessage JSON structure (bubble
/ carousel / box / text / image / button etc.). (非必填)
  "flexSchema"?: object // AI dynamic field schema for FlexMessage. JSON
object whose keys are field paths parsed from flex_template_json (e.g. text
/ image url / button label / button uri / button message). Each value may
be either a plain string (the AI prompt) or an object carrying additional
metadata such as a field tag, e.g. {"prompt": "...", "tag": "title"}. Empty
values fall back to the template default. (非必填)
  "quickReplyConfig"?: object // Authoring config for QUICK_REPLY tools.
Structured JSON describing the chip buttons: static list or dynamic (LLM-
generated) mode, each field either a fixed value or an LLM prompt. (非必填)
  "quickMenuConfig"?: object // Authoring config for QUICK_MENU tools.
Structured JSON describing the persistent input-bar menu rendered by the
web chat only: layout (grid / list), default open state, and 2-6 items each
carrying a display label plus an action payload (send prompt / prefill text
/ open http(s) link). (非必填)
  "category"?: string (enum: knowledge_base, web_search, web_fetch,
code_execution, file_processing, image_video_generation, database_query,
third_party_integration, browser_operation, agent_collaboration, other) //
* `knowledge_base` - Knowledge base retrieval
* `web_search` - Web search
* `web_fetch` - Web page fetch
* `code_execution` - Code execution
* `file_processing` - File processing
* `image_video_generation` - Image/video generation
* `database_query` - Database query
* `third_party_integration` - Third-party integration
* `browser_operation` - Browser operation
* `agent_collaboration` - Agent collaboration
* `other` - Other (catch-all) (非必填)
  "displayCopyByLocale"?: object // 非必填
  "outputRenderTemplateByLocale"?: object // 非必填
  "toolDisplayMode"?: // 可能有不同的類型 (非必填)
  string (enum: full, compact, hidden) // 非必填
  "groups"?: [ // Groups this tool is assigned to. Non-owner members must
pick at least one group they belong to. (非必填)
    {
      "id": string (uuid)
      "name": string
    }
  ]
  "createdAt": string (timestamp)
  "updatedAt": string (timestamp)
  "canUpdate": boolean // Return whether the current user can update this
```

```
resource.
  "canDelete": boolean // Return whether the current user can delete this
resource.
}
```

回應範例值

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "name": "回應字串",
  "displayName": "回應字串",
  "description": "回應字串",
  "prompt": "回應字串",
  "toolType": "api",
  "apiUrl": "回應字串",
  "httpMethod": "get",
  "rawHeaders": null,
  "rawHeadersMasked": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應範例名稱",
    "description": "回應範例描述"
  },
  "sensitiveHeaders": [
    "回應字串"
  ],
  "globalSensitiveHeaders": [
    "回應字串"
  ],
  "rawQueryParams": null,
  "rawQueryParamsMasked": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應範例名稱",
    "description": "回應範例描述"
  },
  "rawParametersSchema": null,
  "functionCode": "回應字串",
  "organization": "550e8400-e29b-41d4-a716-446655440000",
  "createdBy": "550e8400-e29b-41d4-a716-446655440000",
  "isGlobal": false,
  "mcpUrl": "回應字串",
  "mcpRegistry": "550e8400-e29b-41d4-a716-446655440000",
  "mcpAllowedTools": null,
  "rawMcpHeader": null,
  "rawMcpHeaderMasked": {
```

```
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "回應範例名稱",
      "description": "回應範例描述"
    },
    "authSubject": {},
    "flexTemplateJson": null,
    "flexSchema": null,
    "quickReplyConfig": null,
    "quickMenuConfig": null,
    "category": "knowledge_base",
    "displayCopyByLocale": null,
    "outputRenderTemplateByLocale": null,
    "toolDisplayMode": "full",
    "groups": [
      {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "name": "回應字串"
      }
    ],
    "createdAt": "回應字串",
    "updatedAt": "回應字串",
    "canUpdate": false,
    "canDelete": false
  }
```


刪除工具

DELETE `/api/v1/tools/{id}`

參數

參數名稱	必填	類型	說明
`id`	V	string	A UUID string identifying this Tool.

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X DELETE "https://api.maiagent.ai/api/v1/tools/550e8400-e29b-
41d4-a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

// 請求內容 (payload)
const data = null;

axios.delete("https://api.maiagent.ai/api/v1/tools/550e8400-e29b-41d4-a716-446655440000/", data, config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/tools/550e8400-e29b-41d4-a716-446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.delete(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->delete("https://api.maiagent.ai/api/v1/tools/550e8400-e29b-41d4-a716-446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼	說明
204	No response body

列出可用工具

GET `/api/v1/tools/available-tools/`

參數

參數名稱	必填	類型	說明
`availableTools`	V	array	所有可用的MCP工具列表
`error`	V		取得工具失敗的原因：{code, message}；code 為 url_rejected／invalid_header／dns_error／connect_error／tls_error／auth_error／timeout_error／handshake_error／unknown_error。連線成功（含伺服器沒有工具）時為 null；已棄用的 GET 入口一律為 null
`mcpAllowedTools`	X	array	MCP 允許使用的工具列表
`mcpUrl`	V	string	MCP 伺服器 URL（必填）
`rawMcpHeader`	X		MCP Header（JSON 格式）
`toolId`	X	string	Tool ID for per-member OAuth token lookup

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/tools/available-tools/?
availableTools=example&error=example&mcpAllowedTools=example&mcpUrl=ex
ample&rawMcpHeader=example&toolId=550e8400-e29b-41d4-a716-
446655440000"

  -H "Authorization: Api-Key YOUR_API_KEY"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/tools/available-tools/?
availableTools=example&error=example&mcpAllowedTools=example&mcpUrl=ex
ample&rawMcpHeader=example&toolId=550e8400-e29b-41d4-a716-
446655440000", config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/tools/available-tools/?
availableTools=example&error=example&mcpAllowedTools=example&mcpUrl=ex
ample&rawMcpHeader=example&toolId=550e8400-e29b-41d4-a716-
446655440000"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/tools/available-tools/?
availableTools=example&error=example&mcpAllowedTools=example&mcpUrl=ex
ample&rawMcpHeader=example&toolId=550e8400-e29b-41d4-a716-
446655440000", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
{
  "mcpUrl": string // MCP 伺服器 URL（必填）
```

```
  "rawMcpHeader"?: object // MCP Header（JSON 格式） （非必填）
  "mcpAllowedTools"?: [ // MCP 允許使用的工具列表 （非必填）
    string
  ]
  "toolId"?: string (uuid) // Tool ID for per-member OAuth token lookup (非必填)
  "availableTools": [ // 所有可用的MCP工具列表
    string
  ]
  "error":  // 取得工具失敗的原因：{code, message}；code 為 url_rejected／invalid_header／dns_error／connect_error／tls_error／auth_error／timeout_error／handshake_error／unknown_error。連線成功（含伺服器沒有工具）時為 null；已棄用的 GET 入口一律為 null
  {
    "code": string // url_rejected / invalid_header / dns_error / connect_error / tls_error / auth_error / timeout_error / handshake_error / unknown_error
    "message": string // 依使用者語系翻譯好的原因，可直接顯示
  }
}
```

回應範例值

```
{
  "mcpUrl": "回應字串",
  "rawMcpHeader": null,
  "mcpAllowedTools": [
    "回應字串"
  ],
  "toolId": "550e8400-e29b-41d4-a716-446655440000",
  "availableTools": [
    "回應字串"
  ],
  "error": {
    "code": "回應字串",
    "message": "回應字串"
  }
}
```

狀態碼: 400

回應結構範例

```
{
  "detail"?: string // 非必填
}
```

回應範例值

```
{
  "detail": "回應字串"
}
```

建立連接器

POST `/api/v1/connectors/`

請求內容

請求參數

欄位	類型	必填	說明
mcpRegistryId	string (uuid)	是	
displayName	string	否	Custom display name for this connector (defaults to MCP Registry name)
description	string	否	Custom description for this connector (defaults to MCP Registry description)
defaultCategory	object	否	Org-level override of the MCP Registry default category for this connector's dynamic tools. Empty

欄位	類型	必填	說明
			= use the MCP Registry default_category. `knowledge_base` : Knowledge base retrieval ; `web_search` : We...
defaultDisplayGroupNameByLocale	object	否	Locale-keyed server-level default group headline shown in chat for this connector's dynamic MCP tools (those without an individual Tool row). Shape: {"": str}. The headline for the conversatio...
defaultToolIcon	string	否	Server-level default icon identifier (a frontend icon key, not an uploaded image) for this connector's dynamic MCP tools. Empty = frontend uses its default MCP icon. Streamed as toolIcon.
authHeaders	object	否	
allowedContextDataKeys	object	否	Allowlist of webchat contextData keys this connector may render into auth_headers through {{context_data.}}. An empty list disables the feature for this connector: the placeholder is left verbati...
exposedMcpTools	object	否	Allowlist of MCP tool names this connector exposes (to the agent and to SEP-1865 UI cards). Empty list = expose all of the server tools. Use this to limit a connector to a safe subset (e.g. read-only ...
isEnabled	boolean	否	Whether this connector is enabled for contacts in the organization

請求結構範例

```
{
  "mcpRegistryId": string (uuid)
  "displayName"?: string // Custom display name for this connector
```

```
(defaults to MCP Registry name) (非必填)
  "description"?: string // Custom description for this connector (defaults
to MCP Registry description) (非必填)
  "defaultCategory"?: // 可能有不同的類型 (非必填)
  string (enum: knowledge_base, web_search, web_fetch, code_execution,
file_processing, image_video_generation, database_query,
third_party_integration, browser_operation, agent_collaboration, other) //
Org-level override of the MCP Registry default category for this
connector's dynamic tools. Empty = use the MCP Registry default_category.

* `knowledge_base` - Knowledge base retrieval
* `web_search` - Web search
* `web_fetch` - Web page fetch
* `code_execution` - Code execution
* `file_processing` - File processing
* `image_video_generation` - Image/video generation
* `database_query` - Database query
* `third_party_integration` - Third-party integration
* `browser_operation` - Browser operation
* `agent_collaboration` - Agent collaboration
* `other` - Other (catch-all) (非必填)
  "defaultDisplayGroupNameByLocale"?: object // Locale-keyed server-level
default group headline shown in chat for this connector's dynamic MCP tools
(those without an individual Tool row). Shape: {"<locale>": str}. The
headline for the conversation locale is resolved server-side (see
whizchat.tools.services.tool_category.resolve_localized_text): requested
locale -> settings.LANGUAGE_CODE locale -> empty, then streamed verbatim as
displayGroupName. Empty = frontend falls back to its name-based heuristic.
An individual Tool row overrides this. (非必填)
  "defaultToolIcon"?: string // Server-level default icon identifier (a
frontend icon key, not an uploaded image) for this connector's dynamic MCP
tools. Empty = frontend uses its default MCP icon. Streamed as toolIcon.
(非必填)
  "authHeaders"?: object // 非必填
  "allowedContextDataKeys"?: object // Allowlist of webchat contextData
keys this connector may render into auth_headers through {{context_data.
<key>}}. An empty list disables the feature for this connector: the
placeholder is left verbatim, exactly as before the feature existed. Keys
are matched literally and are case-sensitive; at most 20 keys of letters,
digits and underscores. (非必填)
  "exposedMcpTools"?: object // Allowlist of MCP tool names this connector
exposes (to the agent and to SEP-1865 UI cards). Empty list = expose all of
the server tools. Use this to limit a connector to a safe subset (e.g.
read-only tools). (非必填)
  "isEnabled"?: boolean // Whether this connector is enabled for contacts
```

```
in the organization (非必填)
}
```

請求範例值

```
{
  "mcpRegistryId": "550e8400-e29b-41d4-a716-446655440000",
  "displayName": "範例字串",
  "description": "範例字串",
  "defaultCategory": null,
  "defaultDisplayGroupNameByLocale": null,
  "defaultToolIcon": "範例字串",
  "authHeaders": null,
  "allowedContextDataKeys": null,
  "exposedMcpTools": null,
  "isEnabled": true
}
```

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X POST "https://api.maiagent.ai/api/v1/connectors/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "mcpRegistryId": "550e8400-e29b-41d4-a716-446655440000",
    "displayName": "範例字串",
    "description": "範例字串",
    "defaultCategory": null,
    "defaultDisplayGroupNameByLocale": null,
    "defaultToolIcon": "範例字串",
    "authHeaders": null,
    "allowedContextDataKeys": null,
    "exposedMcpTools": null,
    "isEnabled": true
  }'

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// 請求內容 (payload)
const data = {
    "mcpRegistryId": "550e8400-e29b-41d4-a716-446655440000",
    "displayName": "範例字串",
    "description": "範例字串",
    "defaultCategory": null,
    "defaultDisplayGroupNameByLocale": null,
    "defaultToolIcon": "範例字串",
    "authHeaders": null,
    "allowedContextDataKeys": null,
    "exposedMcpTools": null,
    "isEnabled": true
  };

axios.post("https://api.maiagent.ai/api/v1/connectors/", data, config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/connectors/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# 請求內容 (payload)
data = {
    "mcpRegistryId": "550e8400-e29b-41d4-a716-446655440000",
    "displayName": "範例字串",
    "description": "範例字串",
    "defaultCategory": None,
    "defaultDisplayGroupNameByLocale": None,
    "defaultToolIcon": "範例字串",
    "authHeaders": None,
    "allowedContextDataKeys": None,
    "exposedMcpTools": None,
    "isEnabled": True
}

response = requests.post(url, json=data, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>post("https://api.maiagent.ai/api/v1/connectors/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'mcpRegistryId' => '550e8400-e29b-41d4-a716-446655440000',
            'displayName' => '範例字串',
            'description' => '範例字串',
            'defaultCategory' => null,
            'defaultDisplayGroupNameByLocale' => null,
            'defaultToolIcon' => '範例字串',
            'authHeaders' => null,
            'allowedContextDataKeys' => null,
            'exposedMcpTools' => null,
            'isEnabled' => true
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 201

回應結構範例

```
{
  "id": string (uuid)
  "mcpRegistry":
  {
    "id": string (uuid)
    "name": string // MCP service name (e.g., Supabase, Sentry). Only
alphanumeric, underscore and hyphen allowed.
    "displayName"?: string // Human-readable display name (defaults to name
if empty) (非必填)
    "description"?: string // Brief description of the MCP service (非必填)
    "remoteMcpUrl": string (uri) // The URL of the Remote MCP service
    "oauthServerUrl"?: // 可能有不同的類型 (非必填)
    string (uri) // Manual override for the OAuth authorization server URL.
Leave empty to auto-discover from the MCP server (RFC 9728 protected
resource metadata). Only fill in when auto-discovery fails or the server
advertises incorrect metadata. (e.g., Supabase MCP is at mcp.supabase.com
but OAuth is at api.supabase.com) (非必填)
    "logoUrl": string (uri)
    "isActive"?: boolean // Whether this MCP service is currently available
for use (非必填)
    "isGlobal"?: boolean // Global registries are maintained by the
platform and available to all organizations. (非必填)
    "authType"?:  // How to authenticate with this MCP server.

* `oauth` - OAuth 2.0
* `service_account` - Service Account
* `none` - No Authentication (非必填)
    {
    }
    "createdAt": string (timestamp)
    "updatedAt": string (timestamp)
  }
  "mcpRegistryId": string (uuid)
  "name": string
  "displayName"?: string // Custom display name for this connector
(defaults to MCP Registry name) (非必填)
  "description"?: string // Custom description for this connector (defaults
```

```
to MCP Registry description) (非必填)
  "defaultCategory"?: // 可能有不同的類型 (非必填)
  string (enum: knowledge_base, web_search, web_fetch, code_execution,
file_processing, image_video_generation, database_query,
third_party_integration, browser_operation, agent_collaboration, other) //
Org-level override of the MCP Registry default category for this
connector's dynamic tools. Empty = use the MCP Registry default_category.

* `knowledge_base` - Knowledge base retrieval
* `web_search` - Web search
* `web_fetch` - Web page fetch
* `code_execution` - Code execution
* `file_processing` - File processing
* `image_video_generation` - Image/video generation
* `database_query` - Database query
* `third_party_integration` - Third-party integration
* `browser_operation` - Browser operation
* `agent_collaboration` - Agent collaboration
* `other` - Other (catch-all) (非必填)
  "defaultDisplayGroupNameByLocale"?: object // Locale-keyed server-level
default group headline shown in chat for this connector's dynamic MCP tools
(those without an individual Tool row). Shape: {"<locale>": str}. The
headline for the conversation locale is resolved server-side (see
whizchat.tools.services.tool_category.resolve_localized_text): requested
locale -> settings.LANGUAGE_CODE locale -> empty, then streamed verbatim as
displayGroupName. Empty = frontend falls back to its name-based heuristic.
An individual Tool row overrides this. (非必填)
  "defaultToolIcon"?: string // Server-level default icon identifier (a
frontend icon key, not an uploaded image) for this connector's dynamic MCP
tools. Empty = frontend uses its default MCP icon. Streamed as toolIcon.
(非必填)
  "effectiveDescription": string
  "remoteMcpUrl": string
  "oauthServerUrl": string
  "logoUrl": string (uri)
  "authType": string
  "authHeaders"?: object // 非必填
  "authHeadersMasked": object
  "allowedContextDataKeys"?: object // Allowlist of webchat contextData
keys this connector may render into auth_headers through {{context_data.
<key>}}. An empty list disables the feature for this connector: the
placeholder is left verbatim, exactly as before the feature existed. Keys
are matched literally and are case-sensitive; at most 20 keys of letters,
digits and underscores. (非必填)
  "exposedMcpTools"?: object // Allowlist of MCP tool names this connector
exposes (to the agent and to SEP-1865 UI cards). Empty list = expose all of
```

```
the server tools. Use this to limit a connector to a safe subset (e.g.
read-only tools). (非必填)
  "isEnabled"?: boolean // Whether this connector is enabled for contacts
in the organization (非必填)
  "organization": string (uuid)
  "createdBy": string (uuid)
  "createdAt": string (timestamp)
  "updatedAt": string (timestamp)
}
```

回應範例值


```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "mcpRegistry": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應字串",
    "displayName": "回應字串",
    "description": "回應字串",
    "remoteMcpUrl": "https://example.com/file.jpg",
    "oauthServerUrl": "https://example.com/file.jpg",
    "logoUrl": "https://example.com/file.jpg",
    "isActive": false,
    "isGlobal": false,
    "authType": {},
    "createdAt": "回應字串",
    "updatedAt": "回應字串"
  },
  "mcpRegistryId": "550e8400-e29b-41d4-a716-446655440000",
  "name": "回應字串",
  "displayName": "回應字串",
  "description": "回應字串",
  "defaultCategory": "knowledge_base",
  "defaultDisplayGroupNameByLocale": null,
  "defaultToolIcon": "回應字串",
  "effectiveDescription": "回應字串",
  "remoteMcpUrl": "回應字串",
  "oauthServerUrl": "回應字串",
  "logoUrl": "https://example.com/file.jpg",
  "authType": "回應字串",
  "authHeaders": null,
  "authHeadersMasked": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應範例名稱",
```

```
    "description": "回應範例描述"
  },
  "allowedContextDataKeys": null,
  "exposedMcpTools": null,
  "isEnabled": false,
  "organization": "550e8400-e29b-41d4-a716-446655440000",
  "createdBy": "550e8400-e29b-41d4-a716-446655440000",
  "createdAt": "回應字串",
  "updatedAt": "回應字串"
}
```


列出連接器

GET `/api/v1/connectors/`

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/connectors/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/connectors/", config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```python
import requests

url = "https://api.maiagent.ai/api/v1/connectors/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/connectors/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
[
  {
    "id": string (uuid)
    "displayName"?: string // Custom display name for this connector
(defaults to MCP Registry name) (非必填)
```

```
    "mcpRegistryName": string
    "mcpRegistryId": string
    "mcpRegistryIsGlobal": boolean
    "logoUrl": string (uri)
    "defaultCategory"?: // 可能有不同的類型 (非必填)
    string (enum: knowledge_base, web_search, web_fetch, code_execution,
file_processing, image_video_generation, database_query,
third_party_integration, browser_operation, agent_collaboration, other) //
Org-level override of the MCP Registry default category for this
connector's dynamic tools. Empty = use the MCP Registry default_category.

* `knowledge_base` - Knowledge base retrieval
* `web_search` - Web search
* `web_fetch` - Web page fetch
* `code_execution` - Code execution
* `file_processing` - File processing
* `image_video_generation` - Image/video generation
* `database_query` - Database query
* `third_party_integration` - Third-party integration
* `browser_operation` - Browser operation
* `agent_collaboration` - Agent collaboration
* `other` - Other (catch-all) (非必填)
    "isEnabled"?: boolean // Whether this connector is enabled for contacts
in the organization (非必填)
    "authHeadersMasked": object
    "allowedContextDataKeys": object // Allowlist of webchat contextData
keys this connector may render into auth_headers through {{context_data.
<key>}}. An empty list disables the feature for this connector: the
placeholder is left verbatim, exactly as before the feature existed. Keys
are matched literally and are case-sensitive; at most 20 keys of letters,
digits and underscores.
    "authorizedMembersCount": integer
    "createdBy":
    {
      "id": string (uuid)
      "name": string
    }
    "createdAt": string (timestamp)
    "updatedAt": string (timestamp)
  }
]
```

回應範例值

```
```

```
[
  {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "displayName": "回應字串",
    "mcpRegistryName": "回應字串",
    "mcpRegistryId": "回應字串",
    "mcpRegistryIsGlobal": false,
    "logoUrl": "https://example.com/file.jpg",
    "defaultCategory": "knowledge_base",
    "isEnabled": false,
    "authHeadersMasked": {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "回應範例名稱",
      "description": "回應範例描述"
    },
    "allowedContextDataKeys": null,
    "authorizedMembersCount": 456,
    "createdBy": {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "回應字串"
    },
    "createdAt": "回應字串",
    "updatedAt": "回應字串"
  }
]
```


取得特定連接器

`GET` `/api/v1/connectors/{id}`

參數

參數名稱	必填	類型	說明
id	V	string	

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/connectors/550e8400-e29b-
41d4-a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/connectors/550e8400-e29b-
41d4-a716-446655440000/", config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/connectors/550e8400-e29b-41d4-
a716-446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/connectors/550e8400-e29b-41d4-
a716-446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
{
  "id": string (uuid)
  "mcpRegistry":
  {
```

```
    "id": string (uuid)
    "name": string // MCP service name (e.g., Supabase, Sentry). Only
alphanumeric, underscore and hyphen allowed.
    "displayName"?: string // Human-readable display name (defaults to name
if empty) (非必填)
    "description"?: string // Brief description of the MCP service (非必填)
    "remoteMcpUrl": string (uri) // The URL of the Remote MCP service
    "oauthServerUrl"?: // 可能有不同的類型 (非必填)
    string (uri) // Manual override for the OAuth authorization server URL.
Leave empty to auto-discover from the MCP server (RFC 9728 protected
resource metadata). Only fill in when auto-discovery fails or the server
advertises incorrect metadata. (e.g., Supabase MCP is at mcp.supabase.com
but OAuth is at api.supabase.com) (非必填)
    "logoUrl": string (uri)
    "isActive"?: boolean // Whether this MCP service is currently available
for use (非必填)
    "isGlobal"?: boolean // Global registries are maintained by the
platform and available to all organizations. (非必填)
    "authType"?:  // How to authenticate with this MCP server.

* `oauth` - OAuth 2.0
* `service_account` - Service Account
* `none` - No Authentication (非必填)
    {
    }
    "createdAt": string (timestamp)
    "updatedAt": string (timestamp)
  }
  "mcpRegistryId": string (uuid)
  "name": string
  "displayName"?: string // Custom display name for this connector
(defaults to MCP Registry name) (非必填)
  "description"?: string // Custom description for this connector (defaults
to MCP Registry description) (非必填)
  "defaultCategory"?: // 可能有不同的類型 (非必填)
  string (enum: knowledge_base, web_search, web_fetch, code_execution,
file_processing, image_video_generation, database_query,
third_party_integration, browser_operation, agent_collaboration, other) //
Org-level override of the MCP Registry default category for this
connector's dynamic tools. Empty = use the MCP Registry default_category.

* `knowledge_base` - Knowledge base retrieval
* `web_search` - Web search
* `web_fetch` - Web page fetch
* `code_execution` - Code execution
* `file_processing` - File processing
```

```
* `image_video_generation` - Image/video generation
* `database_query` - Database query
* `third_party_integration` - Third-party integration
* `browser_operation` - Browser operation
* `agent_collaboration` - Agent collaboration
* `other` - Other (catch-all) (非必填)
  "defaultDisplayGroupNameByLocale"?: object // Locale-keyed server-level
default group headline shown in chat for this connector's dynamic MCP tools
(those without an individual Tool row). Shape: {"<locale>": str}. The
headline for the conversation locale is resolved server-side (see
whizchat.tools.services.tool_category.resolve_localized_text): requested
locale -> settings.LANGUAGE_CODE locale -> empty, then streamed verbatim as
displayGroupName. Empty = frontend falls back to its name-based heuristic.
An individual Tool row overrides this. (非必填)
  "defaultToolIcon"?: string // Server-level default icon identifier (a
frontend icon key, not an uploaded image) for this connector's dynamic MCP
tools. Empty = frontend uses its default MCP icon. Streamed as toolIcon.
(非必填)
  "effectiveDescription": string
  "remoteMcpUrl": string
  "oauthServerUrl": string
  "logoUrl": string (uri)
  "authType": string
  "authHeaders"?: object // 非必填
  "authHeadersMasked": object
  "allowedContextDataKeys"?: object // Allowlist of webchat contextData
keys this connector may render into auth_headers through {{context_data.
<key>}}. An empty list disables the feature for this connector: the
placeholder is left verbatim, exactly as before the feature existed. Keys
are matched literally and are case-sensitive; at most 20 keys of letters,
digits and underscores. (非必填)
  "exposedMcpTools"?: object // Allowlist of MCP tool names this connector
exposes (to the agent and to SEP-1865 UI cards). Empty list = expose all of
the server tools. Use this to limit a connector to a safe subset (e.g.
read-only tools). (非必填)
  "isEnabled"?: boolean // Whether this connector is enabled for contacts
in the organization (非必填)
  "organization": string (uuid)
  "createdBy": string (uuid)
  "createdAt": string (timestamp)
  "updatedAt": string (timestamp)
}
```

回應範例值

```
```

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "mcpRegistry": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應字串",
    "displayName": "回應字串",
    "description": "回應字串",
    "remoteMcpUrl": "https://example.com/file.jpg",
    "oauthServerUrl": "https://example.com/file.jpg",
    "logoUrl": "https://example.com/file.jpg",
    "isActive": false,
    "isGlobal": false,
    "authType": {},
    "createdAt": "回應字串",
    "updatedAt": "回應字串"
  },
  "mcpRegistryId": "550e8400-e29b-41d4-a716-446655440000",
  "name": "回應字串",
  "displayName": "回應字串",
  "description": "回應字串",
  "defaultCategory": "knowledge_base",
  "defaultDisplayGroupNameByLocale": null,
  "defaultToolIcon": "回應字串",
  "effectiveDescription": "回應字串",
  "remoteMcpUrl": "回應字串",
  "oauthServerUrl": "回應字串",
  "logoUrl": "https://example.com/file.jpg",
  "authType": "回應字串",
  "authHeaders": null,
  "authHeadersMasked": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應範例名稱",
    "description": "回應範例描述"
  },
  "allowedContextDataKeys": null,
  "exposedMcpTools": null,
  "isEnabled": false,
  "organization": "550e8400-e29b-41d4-a716-446655440000",
  "createdBy": "550e8400-e29b-41d4-a716-446655440000",
  "createdAt": "回應字串",
  "updatedAt": "回應字串"
}
```

更新連接器

PUT `/api/v1/connectors/{id}`

參數

參數名稱	必填	類型	說明
`id`	V	string	

請求內容

請求參數

欄位	類型	必填	說明
mcpRegistryId	string (uuid)	是	
displayName	string	否	Custom display name for this connector (defaults to MCP Registry name)
description	string	否	Custom description for this connector (defaults to MCP Registry description)
defaultCategory	object	否	Org-level override of the MCP Registry default category for this connector's dynamic tools. Empty = use the MCP Registry default_category. `knowledge_base` : Knowledge base retrieval ; `web_search` : We...

欄位	類型	必填	說明
defaultDisplayGroupNameByLocale	object	否	Locale-keyed server-level default group headline shown in chat for this connector's dynamic MCP tools (those without an individual Tool row). Shape: {"": str}. The headline for the conversatio...
defaultToolIcon	string	否	Server-level default icon identifier (a frontend icon key, not an uploaded image) for this connector's dynamic MCP tools. Empty = frontend uses its default MCP icon. Streamed as toolIcon.
authHeaders	object	否	
allowedContextDataKeys	object	否	Allowlist of webchat contextData keys this connector may render into auth_headers through {{context_data.}}. An empty list disables the feature for this connector: the placeholder is left verbati...
exposedMcpTools	object	否	Allowlist of MCP tool names this connector exposes (to the agent and to SEP-1865 UI cards). Empty list = expose all of the server tools. Use this to limit a connector to a safe subset (e.g. read-only ...
isEnabled	boolean	否	Whether this connector is enabled for contacts in the organization

請求結構範例

```
{
  "mcpRegistryId": string (uuid)
  "displayName"?: string // Custom display name for this connector
(defaults to MCP Registry name) (非必填)
  "description"?: string // Custom description for this connector (defaults
to MCP Registry description) (非必填)
  "defaultCategory"?: // 可能有不同的類型 (非必填)
```

```
  string (enum: knowledge_base, web_search, web_fetch, code_execution,
file_processing, image_video_generation, database_query,
third_party_integration, browser_operation, agent_collaboration, other) //
Org-level override of the MCP Registry default category for this
connector's dynamic tools. Empty = use the MCP Registry default_category.

* `knowledge_base` - Knowledge base retrieval
* `web_search` - Web search
* `web_fetch` - Web page fetch
* `code_execution` - Code execution
* `file_processing` - File processing
* `image_video_generation` - Image/video generation
* `database_query` - Database query
* `third_party_integration` - Third-party integration
* `browser_operation` - Browser operation
* `agent_collaboration` - Agent collaboration
* `other` - Other (catch-all) (非必填)
  "defaultDisplayGroupNameByLocale"?: object // Locale-keyed server-level
default group headline shown in chat for this connector's dynamic MCP tools
(those without an individual Tool row). Shape: {"<locale>": str}. The
headline for the conversation locale is resolved server-side (see
whizchat.tools.services.tool_category.resolve_localized_text): requested
locale -> settings.LANGUAGE_CODE locale -> empty, then streamed verbatim as
displayGroupName. Empty = frontend falls back to its name-based heuristic.
An individual Tool row overrides this. (非必填)
  "defaultToolIcon"?: string // Server-level default icon identifier (a
frontend icon key, not an uploaded image) for this connector's dynamic MCP
tools. Empty = frontend uses its default MCP icon. Streamed as toolIcon.
(非必填)
  "authHeaders"?: object // 非必填
  "allowedContextDataKeys"?: object // Allowlist of webchat contextData
keys this connector may render into auth_headers through {{context_data.
<key>}}. An empty list disables the feature for this connector: the
placeholder is left verbatim, exactly as before the feature existed. Keys
are matched literally and are case-sensitive; at most 20 keys of letters,
digits and underscores. (非必填)
  "exposedMcpTools"?: object // Allowlist of MCP tool names this connector
exposes (to the agent and to SEP-1865 UI cards). Empty list = expose all of
the server tools. Use this to limit a connector to a safe subset (e.g.
read-only tools). (非必填)
  "isEnabled"?: boolean // Whether this connector is enabled for contacts
in the organization (非必填)
}
```

請求範例值

```
```

```
{
  "mcpRegistryId": "550e8400-e29b-41d4-a716-446655440000",
  "displayName": "範例字串",
  "description": "範例字串",
  "defaultCategory": null,
  "defaultDisplayGroupNameByLocale": null,
  "defaultToolIcon": "範例字串",
  "authHeaders": null,
  "allowedContextDataKeys": null,
  "exposedMcpTools": null,
  "isEnabled": true
}
```


程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X PUT "https://api.maiagent.ai/api/v1/connectors/550e8400-e29b-
41d4-a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "mcpRegistryId": "550e8400-e29b-41d4-a716-446655440000",
    "displayName": "範例字串",
    "description": "範例字串",
    "defaultCategory": null,
    "defaultDisplayGroupNameByLocale": null,
    "defaultToolIcon": "範例字串",
    "authHeaders": null,
    "allowedContextDataKeys": null,
    "exposedMcpTools": null,
    "isEnabled": true
  }'

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// 請求內容 (payload)
const data = {
    "mcpRegistryId": "550e8400-e29b-41d4-a716-446655440000",
    "displayName": "範例字串",
    "description": "範例字串",
    "defaultCategory": null,
    "defaultDisplayGroupNameByLocale": null,
    "defaultToolIcon": "範例字串",
    "authHeaders": null,
    "allowedContextDataKeys": null,
    "exposedMcpTools": null,
    "isEnabled": true
  };

axios.put("https://api.maiagent.ai/api/v1/connectors/550e8400-e29b-
41d4-a716-446655440000/", data, config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/connectors/550e8400-e29b-41d4-
a716-446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# 請求內容 (payload)
data = {
    "mcpRegistryId": "550e8400-e29b-41d4-a716-446655440000",
    "displayName": "範例字串",
    "description": "範例字串",
    "defaultCategory": None,
    "defaultDisplayGroupNameByLocale": None,
    "defaultToolIcon": "範例字串",
    "authHeaders": None,
    "allowedContextDataKeys": None,
    "exposedMcpTools": None,
    "isEnabled": True
}

response = requests.put(url, json=data, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>put("https://api.maiagent.ai/api/v1/connectors/550e8400-e29b-41d4-
a716-446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'mcpRegistryId' => '550e8400-e29b-41d4-a716-446655440000',
            'displayName' => '範例字串',
            'description' => '範例字串',
            'defaultCategory' => null,
            'defaultDisplayGroupNameByLocale' => null,
            'defaultToolIcon' => '範例字串',
            'authHeaders' => null,
            'allowedContextDataKeys' => null,
            'exposedMcpTools' => null,
            'isEnabled' => true
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
{
  "id": string (uuid)
  "mcpRegistry":
  {
    "id": string (uuid)
    "name": string // MCP service name (e.g., Supabase, Sentry). Only
alphanumeric, underscore and hyphen allowed.
    "displayName"?: string // Human-readable display name (defaults to name
if empty) (非必填)
    "description"?: string // Brief description of the MCP service (非必填)
    "remoteMcpUrl": string (uri) // The URL of the Remote MCP service
    "oauthServerUrl"?: // 可能有不同的類型 (非必填)
    string (uri) // Manual override for the OAuth authorization server URL.
Leave empty to auto-discover from the MCP server (RFC 9728 protected
resource metadata). Only fill in when auto-discovery fails or the server
advertises incorrect metadata. (e.g., Supabase MCP is at mcp.supabase.com
but OAuth is at api.supabase.com) (非必填)
    "logoUrl": string (uri)
    "isActive"?: boolean // Whether this MCP service is currently available
for use (非必填)
    "isGlobal"?: boolean // Global registries are maintained by the
platform and available to all organizations. (非必填)
    "authType"?:  // How to authenticate with this MCP server.

* `oauth` - OAuth 2.0
* `service_account` - Service Account
* `none` - No Authentication (非必填)
    {
    }
    "createdAt": string (timestamp)
    "updatedAt": string (timestamp)
  }
  "mcpRegistryId": string (uuid)
  "name": string
  "displayName"?: string // Custom display name for this connector
(defaults to MCP Registry name) (非必填)
  "description"?: string // Custom description for this connector (defaults
```

```
to MCP Registry description) (非必填)
  "defaultCategory"?: // 可能有不同的類型 (非必填)
  string (enum: knowledge_base, web_search, web_fetch, code_execution,
file_processing, image_video_generation, database_query,
third_party_integration, browser_operation, agent_collaboration, other) //
Org-level override of the MCP Registry default category for this
connector's dynamic tools. Empty = use the MCP Registry default_category.

* `knowledge_base` - Knowledge base retrieval
* `web_search` - Web search
* `web_fetch` - Web page fetch
* `code_execution` - Code execution
* `file_processing` - File processing
* `image_video_generation` - Image/video generation
* `database_query` - Database query
* `third_party_integration` - Third-party integration
* `browser_operation` - Browser operation
* `agent_collaboration` - Agent collaboration
* `other` - Other (catch-all) (非必填)
  "defaultDisplayGroupNameByLocale"?: object // Locale-keyed server-level
default group headline shown in chat for this connector's dynamic MCP tools
(those without an individual Tool row). Shape: {"<locale>": str}. The
headline for the conversation locale is resolved server-side (see
whizchat.tools.services.tool_category.resolve_localized_text): requested
locale -> settings.LANGUAGE_CODE locale -> empty, then streamed verbatim as
displayGroupName. Empty = frontend falls back to its name-based heuristic.
An individual Tool row overrides this. (非必填)
  "defaultToolIcon"?: string // Server-level default icon identifier (a
frontend icon key, not an uploaded image) for this connector's dynamic MCP
tools. Empty = frontend uses its default MCP icon. Streamed as toolIcon.
(非必填)
  "effectiveDescription": string
  "remoteMcpUrl": string
  "oauthServerUrl": string
  "logoUrl": string (uri)
  "authType": string
  "authHeaders"?: object // 非必填
  "authHeadersMasked": object
  "allowedContextDataKeys"?: object // Allowlist of webchat contextData
keys this connector may render into auth_headers through {{context_data.
<key>}}. An empty list disables the feature for this connector: the
placeholder is left verbatim, exactly as before the feature existed. Keys
are matched literally and are case-sensitive; at most 20 keys of letters,
digits and underscores. (非必填)
  "exposedMcpTools"?: object // Allowlist of MCP tool names this connector
exposes (to the agent and to SEP-1865 UI cards). Empty list = expose all of
```

```
the server tools. Use this to limit a connector to a safe subset (e.g.
read-only tools). (非必填)
  "isEnabled"?: boolean // Whether this connector is enabled for contacts
in the organization (非必填)
  "organization": string (uuid)
  "createdBy": string (uuid)
  "createdAt": string (timestamp)
  "updatedAt": string (timestamp)
}
```

回應範例值


```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "mcpRegistry": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應字串",
    "displayName": "回應字串",
    "description": "回應字串",
    "remoteMcpUrl": "https://example.com/file.jpg",
    "oauthServerUrl": "https://example.com/file.jpg",
    "logoUrl": "https://example.com/file.jpg",
    "isActive": false,
    "isGlobal": false,
    "authType": {},
    "createdAt": "回應字串",
    "updatedAt": "回應字串"
  },
  "mcpRegistryId": "550e8400-e29b-41d4-a716-446655440000",
  "name": "回應字串",
  "displayName": "回應字串",
  "description": "回應字串",
  "defaultCategory": "knowledge_base",
  "defaultDisplayGroupNameByLocale": null,
  "defaultToolIcon": "回應字串",
  "effectiveDescription": "回應字串",
  "remoteMcpUrl": "回應字串",
  "oauthServerUrl": "回應字串",
  "logoUrl": "https://example.com/file.jpg",
  "authType": "回應字串",
  "authHeaders": null,
  "authHeadersMasked": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應範例名稱",
```

```
    "description": "回應範例描述"
  },
  "allowedContextDataKeys": null,
  "exposedMcpTools": null,
  "isEnabled": false,
  "organization": "550e8400-e29b-41d4-a716-446655440000",
  "createdBy": "550e8400-e29b-41d4-a716-446655440000",
  "createdAt": "回應字串",
  "updatedAt": "回應字串"
}
```


部分更新連接器

`PATCH` `/api/v1/connectors/{id}`

參數

參數名稱	必填	類型	說明
id	V	string	

請求內容

請求參數

欄位	類型	必填	說明
mcpRegistryId	string (uuid)	否	

欄位	類型	必填	說明
displayName	string	否	Custom display name for this connector (defaults to MCP Registry name)
description	string	否	Custom description for this connector (defaults to MCP Registry description)
defaultCategory	object	否	Org-level override of the MCP Registry default category for this connector's dynamic tools. Empty = use the MCP Registry default_category. `knowledge_base` : Knowledge base retrieval ; `web_search` : We...
defaultDisplayGroupNameByLocale	object	否	Locale-keyed server-level default group headline shown in chat for this connector's dynamic MCP tools (those without an individual Tool row). Shape: {"": str}. The headline for the conversatio...
defaultToolIcon	string	否	Server-level default icon identifier (a frontend icon key, not an uploaded image) for this connector's dynamic MCP tools. Empty = frontend uses its default MCP icon. Streamed as toolIcon.
authHeaders	object	否	
allowedContextDataKeys	object	否	Allowlist of webchat contextData keys this connector may render into auth_headers through {{context_data.}}. An empty list disables the feature for this connector: the placeholder is left verbati...
exposedMcpTools	object	否	Allowlist of MCP tool names this connector exposes (to the agent and to SEP-1865 UI cards). Empty list = expose all of the server tools.

欄位	類型	必填	說明
			Use this to limit a connector to a safe subset (e.g. read-only ...
isEnabled	boolean	否	Whether this connector is enabled for contacts in the organization

請求結構範例

```
{
  "mcpRegistryId"?: string (uuid) // 非必填
  "displayName"?: string // Custom display name for this connector
(defaults to MCP Registry name) (非必填)
  "description"?: string // Custom description for this connector (defaults
to MCP Registry description) (非必填)
  "defaultCategory"?: // 可能有不同的類型 (非必填)
  string (enum: knowledge_base, web_search, web_fetch, code_execution,
file_processing, image_video_generation, database_query,
third_party_integration, browser_operation, agent_collaboration, other) //
Org-level override of the MCP Registry default category for this
connector's dynamic tools. Empty = use the MCP Registry default_category.

* `knowledge_base` - Knowledge base retrieval
* `web_search` - Web search
* `web_fetch` - Web page fetch
* `code_execution` - Code execution
* `file_processing` - File processing
* `image_video_generation` - Image/video generation
* `database_query` - Database query
* `third_party_integration` - Third-party integration
* `browser_operation` - Browser operation
* `agent_collaboration` - Agent collaboration
* `other` - Other (catch-all) (非必填)
  "defaultDisplayGroupNameByLocale"?: object // Locale-keyed server-level
default group headline shown in chat for this connector's dynamic MCP tools
(those without an individual Tool row). Shape: {"<locale>": str}. The
headline for the conversation locale is resolved server-side (see
whizchat.tools.services.tool_category.resolve_localized_text): requested
locale -> settings.LANGUAGE_CODE locale -> empty, then streamed verbatim as
displayGroupName. Empty = frontend falls back to its name-based heuristic.
An individual Tool row overrides this. (非必填)
  "defaultToolIcon"?: string // Server-level default icon identifier (a
frontend icon key, not an uploaded image) for this connector's dynamic MCP
```

```
tools. Empty = frontend uses its default MCP icon. Streamed as toolIcon.
(非必填)
  "authHeaders"?: object // 非必填
  "allowedContextDataKeys"?: object // Allowlist of webchat contextData
keys this connector may render into auth_headers through {{context_data.
<key>}}. An empty list disables the feature for this connector: the
placeholder is left verbatim, exactly as before the feature existed. Keys
are matched literally and are case-sensitive; at most 20 keys of letters,
digits and underscores. (非必填)
  "exposedMcpTools"?: object // Allowlist of MCP tool names this connector
exposes (to the agent and to SEP-1865 UI cards). Empty list = expose all of
the server tools. Use this to limit a connector to a safe subset (e.g.
read-only tools). (非必填)
  "isEnabled"?: boolean // Whether this connector is enabled for contacts
in the organization (非必填)
}
```

請求範例值

```
{
  "mcpRegistryId": "550e8400-e29b-41d4-a716-446655440000",
  "displayName": "範例字串",
  "description": "範例字串",
  "defaultCategory": null,
  "defaultDisplayGroupNameByLocale": null,
  "defaultToolIcon": "範例字串",
  "authHeaders": null,
  "allowedContextDataKeys": null,
  "exposedMcpTools": null,
  "isEnabled": true
}
```

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X PATCH "https://api.maiagent.ai/api/v1/connectors/550e8400-
e29b-41d4-a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "mcpRegistryId": "550e8400-e29b-41d4-a716-446655440000",
    "displayName": "範例字串",
    "description": "範例字串",
    "defaultCategory": null,
    "defaultDisplayGroupNameByLocale": null,
    "defaultToolIcon": "範例字串",
    "authHeaders": null,
    "allowedContextDataKeys": null,
    "exposedMcpTools": null,
    "isEnabled": true
  }'

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// 請求內容 (payload)
const data = {
    "mcpRegistryId": "550e8400-e29b-41d4-a716-446655440000",
    "displayName": "範例字串",
    "description": "範例字串",
    "defaultCategory": null,
    "defaultDisplayGroupNameByLocale": null,
    "defaultToolIcon": "範例字串",
    "authHeaders": null,
    "allowedContextDataKeys": null,
    "exposedMcpTools": null,
    "isEnabled": true
  };

axios.patch("https://api.maiagent.ai/api/v1/connectors/550e8400-e29b-
41d4-a716-446655440000/", data, config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/connectors/550e8400-e29b-41d4-
a716-446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# 請求內容 (payload)
data = {
    "mcpRegistryId": "550e8400-e29b-41d4-a716-446655440000",
    "displayName": "範例字串",
    "description": "範例字串",
    "defaultCategory": None,
    "defaultDisplayGroupNameByLocale": None,
    "defaultToolIcon": "範例字串",
    "authHeaders": None,
    "allowedContextDataKeys": None,
    "exposedMcpTools": None,
    "isEnabled": True
}

response = requests.patch(url, json=data, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->patch("https://api.maiagent.ai/api/v1/connectors/550e8400-e29b-41d4-a716-446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'mcpRegistryId' => '550e8400-e29b-41d4-a716-446655440000',
            'displayName' => '範例字串',
            'description' => '範例字串',
            'defaultCategory' => null,
            'defaultDisplayGroupNameByLocale' => null,
            'defaultToolIcon' => '範例字串',
            'authHeaders' => null,
            'allowedContextDataKeys' => null,
            'exposedMcpTools' => null,
            'isEnabled' => true
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
{
  "id": string (uuid)
  "mcpRegistry":
  {
    "id": string (uuid)
    "name": string // MCP service name (e.g., Supabase, Sentry). Only
alphanumeric, underscore and hyphen allowed.
    "displayName"?: string // Human-readable display name (defaults to name
if empty) (非必填)
    "description"?: string // Brief description of the MCP service (非必填)
    "remoteMcpUrl": string (uri) // The URL of the Remote MCP service
    "oauthServerUrl"?: // 可能有不同的類型 (非必填)
    string (uri) // Manual override for the OAuth authorization server URL.
Leave empty to auto-discover from the MCP server (RFC 9728 protected
resource metadata). Only fill in when auto-discovery fails or the server
advertises incorrect metadata. (e.g., Supabase MCP is at mcp.supabase.com
but OAuth is at api.supabase.com) (非必填)
    "logoUrl": string (uri)
    "isActive"?: boolean // Whether this MCP service is currently available
for use (非必填)
    "isGlobal"?: boolean // Global registries are maintained by the
platform and available to all organizations. (非必填)
    "authType"?:  // How to authenticate with this MCP server.

* `oauth` - OAuth 2.0
* `service_account` - Service Account
* `none` - No Authentication (非必填)
    {
    }
    "createdAt": string (timestamp)
    "updatedAt": string (timestamp)
  }
  "mcpRegistryId": string (uuid)
  "name": string
  "displayName"?: string // Custom display name for this connector
(defaults to MCP Registry name) (非必填)
  "description"?: string // Custom description for this connector (defaults
```

```
to MCP Registry description) (非必填)
  "defaultCategory"?: // 可能有不同的類型 (非必填)
  string (enum: knowledge_base, web_search, web_fetch, code_execution,
file_processing, image_video_generation, database_query,
third_party_integration, browser_operation, agent_collaboration, other) //
Org-level override of the MCP Registry default category for this
connector's dynamic tools. Empty = use the MCP Registry default_category.

* `knowledge_base` - Knowledge base retrieval
* `web_search` - Web search
* `web_fetch` - Web page fetch
* `code_execution` - Code execution
* `file_processing` - File processing
* `image_video_generation` - Image/video generation
* `database_query` - Database query
* `third_party_integration` - Third-party integration
* `browser_operation` - Browser operation
* `agent_collaboration` - Agent collaboration
* `other` - Other (catch-all) (非必填)
  "defaultDisplayGroupNameByLocale"?: object // Locale-keyed server-level
default group headline shown in chat for this connector's dynamic MCP tools
(those without an individual Tool row). Shape: {"<locale>": str}. The
headline for the conversation locale is resolved server-side (see
whizchat.tools.services.tool_category.resolve_localized_text): requested
locale -> settings.LANGUAGE_CODE locale -> empty, then streamed verbatim as
displayGroupName. Empty = frontend falls back to its name-based heuristic.
An individual Tool row overrides this. (非必填)
  "defaultToolIcon"?: string // Server-level default icon identifier (a
frontend icon key, not an uploaded image) for this connector's dynamic MCP
tools. Empty = frontend uses its default MCP icon. Streamed as toolIcon.
(非必填)
  "effectiveDescription": string
  "remoteMcpUrl": string
  "oauthServerUrl": string
  "logoUrl": string (uri)
  "authType": string
  "authHeaders"?: object // 非必填
  "authHeadersMasked": object
  "allowedContextDataKeys"?: object // Allowlist of webchat contextData
keys this connector may render into auth_headers through {{context_data.
<key>}}. An empty list disables the feature for this connector: the
placeholder is left verbatim, exactly as before the feature existed. Keys
are matched literally and are case-sensitive; at most 20 keys of letters,
digits and underscores. (非必填)
  "exposedMcpTools"?: object // Allowlist of MCP tool names this connector
exposes (to the agent and to SEP-1865 UI cards). Empty list = expose all of
```

```
the server tools. Use this to limit a connector to a safe subset (e.g.
read-only tools). (非必填)
  "isEnabled"?: boolean // Whether this connector is enabled for contacts
in the organization (非必填)
  "organization": string (uuid)
  "createdBy": string (uuid)
  "createdAt": string (timestamp)
  "updatedAt": string (timestamp)
}
```

回應範例值

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "mcpRegistry": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應字串",
    "displayName": "回應字串",
    "description": "回應字串",
    "remoteMcpUrl": "https://example.com/file.jpg",
    "oauthServerUrl": "https://example.com/file.jpg",
    "logoUrl": "https://example.com/file.jpg",
    "isActive": false,
    "isGlobal": false,
    "authType": {},
    "createdAt": "回應字串",
    "updatedAt": "回應字串"
  },
  "mcpRegistryId": "550e8400-e29b-41d4-a716-446655440000",
  "name": "回應字串",
  "displayName": "回應字串",
  "description": "回應字串",
  "defaultCategory": "knowledge_base",
  "defaultDisplayGroupNameByLocale": null,
  "defaultToolIcon": "回應字串",
  "effectiveDescription": "回應字串",
  "remoteMcpUrl": "回應字串",
  "oauthServerUrl": "回應字串",
  "logoUrl": "https://example.com/file.jpg",
  "authType": "回應字串",
  "authHeaders": null,
  "authHeadersMasked": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應範例名稱",
```

```
    "description": "回應範例描述"
  },
  "allowedContextDataKeys": null,
  "exposedMcpTools": null,
  "isEnabled": false,
  "organization": "550e8400-e29b-41d4-a716-446655440000",
  "createdBy": "550e8400-e29b-41d4-a716-446655440000",
  "createdAt": "回應字串",
  "updatedAt": "回應字串"
}
```


刪除連接器

DELETE `/api/v1/connectors/{id}`

參數

參數名稱	必填	類型	說明
`id`	V	string	

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X DELETE "https://api.maiagent.ai/api/v1/connectors/550e8400-
e29b-41d4-a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

// 請求內容 (payload)
const data = null;

axios.delete("https://api.maiagent.ai/api/v1/connectors/550e8400-e29b-41d4-a716-446655440000/", data, config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/connectors/550e8400-e29b-41d4-
a716-446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.delete(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>delete("https://api.maiagent.ai/api/v1/connectors/550e8400-e29b-41d4-
a716-446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼	說明
204	No response body

列出連接器授權成員

GET `/api/v1/connectors/{id}/authorized-members/`

參數

參數名稱	必填	類型	說明
id	V	string	

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/connectors/550e8400-e29b-41d4-a716-446655440000/authorized-members/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/connectors/550e8400-e29b-
41d4-a716-446655440000/authorized-members/", config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/connectors/550e8400-e29b-41d4-
a716-446655440000/authorized-members/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/connectors/550e8400-e29b-41d4-
a716-446655440000/authorized-members/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
{
  "id": string (uuid)
  "mcpRegistry":
  {
```

```
    "id": string (uuid)
    "name": string // MCP service name (e.g., Supabase, Sentry). Only
alphanumeric, underscore and hyphen allowed.
    "displayName"?: string // Human-readable display name (defaults to name
if empty) (非必填)
    "description"?: string // Brief description of the MCP service (非必填)
    "remoteMcpUrl": string (uri) // The URL of the Remote MCP service
    "oauthServerUrl"?: // 可能有不同的類型 (非必填)
    string (uri) // Manual override for the OAuth authorization server URL.
Leave empty to auto-discover from the MCP server (RFC 9728 protected
resource metadata). Only fill in when auto-discovery fails or the server
advertises incorrect metadata. (e.g., Supabase MCP is at mcp.supabase.com
but OAuth is at api.supabase.com) (非必填)
    "logoUrl": string (uri)
    "isActive"?: boolean // Whether this MCP service is currently available
for use (非必填)
    "isGlobal"?: boolean // Global registries are maintained by the
platform and available to all organizations. (非必填)
    "authType"?:  // How to authenticate with this MCP server.

* `oauth` - OAuth 2.0
* `service_account` - Service Account
* `none` - No Authentication (非必填)
    {
    }
    "createdAt": string (timestamp)
    "updatedAt": string (timestamp)
  }
  "mcpRegistryId": string (uuid)
  "name": string
  "displayName"?: string // Custom display name for this connector
(defaults to MCP Registry name) (非必填)
  "description"?: string // Custom description for this connector (defaults
to MCP Registry description) (非必填)
  "defaultCategory"?: // 可能有不同的類型 (非必填)
  string (enum: knowledge_base, web_search, web_fetch, code_execution,
file_processing, image_video_generation, database_query,
third_party_integration, browser_operation, agent_collaboration, other) //
Org-level override of the MCP Registry default category for this
connector's dynamic tools. Empty = use the MCP Registry default_category.

* `knowledge_base` - Knowledge base retrieval
* `web_search` - Web search
* `web_fetch` - Web page fetch
* `code_execution` - Code execution
* `file_processing` - File processing
```

```
* `image_video_generation` - Image/video generation
* `database_query` - Database query
* `third_party_integration` - Third-party integration
* `browser_operation` - Browser operation
* `agent_collaboration` - Agent collaboration
* `other` - Other (catch-all) (非必填)
  "defaultDisplayGroupNameByLocale"?: object // Locale-keyed server-level
default group headline shown in chat for this connector's dynamic MCP tools
(those without an individual Tool row). Shape: {"<locale>": str}. The
headline for the conversation locale is resolved server-side (see
whizchat.tools.services.tool_category.resolve_localized_text): requested
locale -> settings.LANGUAGE_CODE locale -> empty, then streamed verbatim as
displayGroupName. Empty = frontend falls back to its name-based heuristic.
An individual Tool row overrides this. (非必填)
  "defaultToolIcon"?: string // Server-level default icon identifier (a
frontend icon key, not an uploaded image) for this connector's dynamic MCP
tools. Empty = frontend uses its default MCP icon. Streamed as toolIcon.
(非必填)
  "effectiveDescription": string
  "remoteMcpUrl": string
  "oauthServerUrl": string
  "logoUrl": string (uri)
  "authType": string
  "authHeaders"?: object // 非必填
  "authHeadersMasked": object
  "allowedContextDataKeys"?: object // Allowlist of webchat contextData
keys this connector may render into auth_headers through {{context_data.
<key>}}. An empty list disables the feature for this connector: the
placeholder is left verbatim, exactly as before the feature existed. Keys
are matched literally and are case-sensitive; at most 20 keys of letters,
digits and underscores. (非必填)
  "exposedMcpTools"?: object // Allowlist of MCP tool names this connector
exposes (to the agent and to SEP-1865 UI cards). Empty list = expose all of
the server tools. Use this to limit a connector to a safe subset (e.g.
read-only tools). (非必填)
  "isEnabled"?: boolean // Whether this connector is enabled for contacts
in the organization (非必填)
  "organization": string (uuid)
  "createdBy": string (uuid)
  "createdAt": string (timestamp)
  "updatedAt": string (timestamp)
}
```

回應範例值

```
```

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "mcpRegistry": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應字串",
    "displayName": "回應字串",
    "description": "回應字串",
    "remoteMcpUrl": "https://example.com/file.jpg",
    "oauthServerUrl": "https://example.com/file.jpg",
    "logoUrl": "https://example.com/file.jpg",
    "isActive": false,
    "isGlobal": false,
    "authType": {},
    "createdAt": "回應字串",
    "updatedAt": "回應字串"
  },
  "mcpRegistryId": "550e8400-e29b-41d4-a716-446655440000",
  "name": "回應字串",
  "displayName": "回應字串",
  "description": "回應字串",
  "defaultCategory": "knowledge_base",
  "defaultDisplayGroupNameByLocale": null,
  "defaultToolIcon": "回應字串",
  "effectiveDescription": "回應字串",
  "remoteMcpUrl": "回應字串",
  "oauthServerUrl": "回應字串",
  "logoUrl": "https://example.com/file.jpg",
  "authType": "回應字串",
  "authHeaders": null,
  "authHeadersMasked": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應範例名稱",
    "description": "回應範例描述"
  },
  "allowedContextDataKeys": null,
  "exposedMcpTools": null,
  "isEnabled": false,
  "organization": "550e8400-e29b-41d4-a716-446655440000",
  "createdBy": "550e8400-e29b-41d4-a716-446655440000",
  "createdAt": "回應字串",
  "updatedAt": "回應字串"
}
```

移除連接器授權成員

`DELETE` `/api/v1/connectors/{id}/authorized-members/{memberId}`

參數

參數名稱	必填	類型	說明
`id`	V	string	
`memberId`	V	string	

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X DELETE "https://api.maiagent.ai/api/v1/connectors/550e8400-
e29b-41d4-a716-446655440000/authorized-members/{memberId}
"

  -H "Authorization: Api-Key YOUR_API_KEY"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

// 請求內容 (payload)
const data = null;

axios.delete("https://api.maiagent.ai/api/v1/connectors/550e8400-e29b-
41d4-a716-446655440000/authorized-members/{memberId}
", data, config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/connectors/550e8400-e29b-41d4-
a716-446655440000/authorized-members/{memberId}
"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.delete(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>delete("https://api.maiagent.ai/api/v1/connectors/550e8400-e29b-41d4-
a716-446655440000/authorized-members/{memberId}
", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼	說明
204	No response body

列出 MCP 工具登錄

GET `/api/v1/mcp/registry/`

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/mcp/registry/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/mcp/registry/", config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/mcp/registry/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/mcp/registry/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
[
  {
    "id": string (uuid)
    "name": string // MCP service name (e.g., Supabase, Sentry). Only
alphanumeric, underscore and hyphen allowed.
```

```
    "displayName"?: string // Human-readable display name (defaults to name if empty) (非必填)
    "description"?: string // Brief description of the MCP service (非必填)
    "remoteMcpUrl": string (uri) // The URL of the Remote MCP service
    "oauthServerUrl"?: // 可能有不同的類型 (非必填)
    string (uri) // Manual override for the OAuth authorization server URL. Leave empty to auto-discover from the MCP server (RFC 9728 protected resource metadata). Only fill in when auto-discovery fails or the server advertises incorrect metadata. (e.g., Supabase MCP is at mcp.supabase.com but OAuth is at api.supabase.com) (非必填)
    "logoUrl": string (uri)
    "isActive"?: boolean // Whether this MCP service is currently available for use (非必填)
    "isGlobal"?: boolean // Global registries are maintained by the platform and available to all organizations. (非必填)
    "authType"?:  // How to authenticate with this MCP server.

* `oauth` - OAuth 2.0
* `service_account` - Service Account
* `none` - No Authentication (非必填)
    {
    }
    "createdAt": string (timestamp)
    "updatedAt": string (timestamp)
  }
]
```

回應範例值

```
[
  {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應字串",
    "displayName": "回應字串",
    "description": "回應字串",
    "remoteMcpUrl": "https://example.com/file.jpg",
    "oauthServerUrl": "https://example.com/file.jpg",
    "logoUrl": "https://example.com/file.jpg",
    "isActive": false,
    "isGlobal": false,
    "authType": {},
    "createdAt": "回應字串",
    "updatedAt": "回應字串"
```

```
  }
]
```

取得特定 MCP 工具登錄

`GET` `/api/v1/mcp/registry/{id}`

參數

參數名稱	必填	類型	說明
id	V	string	

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/mcp/registry/550e8400-
e29b-41d4-a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/mcp/registry/550e8400-e29b-41d4-a716-446655440000/", config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/mcp/registry/550e8400-e29b-41d4-a716-446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/mcp/registry/550e8400-e29b-41d4-
a716-446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
{
  "id": string (uuid)
  "name": string // MCP service name (e.g., Supabase, Sentry). Only
alphanumeric, underscore and hyphen allowed.
```

```
  "displayName"?: string // Human-readable display name (defaults to name
if empty) (非必填)
  "description"?: string // Brief description of the MCP service (非必填)
  "remoteMcpUrl": string (uri) // The URL of the Remote MCP service
  "oauthServerUrl"?: // 可能有不同的類型 (非必填)
  string (uri) // Manual override for the OAuth authorization server URL.
Leave empty to auto-discover from the MCP server (RFC 9728 protected
resource metadata). Only fill in when auto-discovery fails or the server
advertises incorrect metadata. (e.g., Supabase MCP is at mcp.supabase.com
but OAuth is at api.supabase.com) (非必填)
  "logoUrl": string (uri)
  "isActive"?: boolean // Whether this MCP service is currently available
for use (非必填)
  "isGlobal"?: boolean // Global registries are maintained by the platform
and available to all organizations. (非必填)
  "authType"?:  // How to authenticate with this MCP server.

* `oauth` - OAuth 2.0
* `service_account` - Service Account
* `none` - No Authentication (非必填)
  {
  }
  "createdAt": string (timestamp)
  "updatedAt": string (timestamp)
}
```

回應範例值

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "name": "回應字串",
  "displayName": "回應字串",
  "description": "回應字串",
  "remoteMcpUrl": "https://example.com/file.jpg",
  "oauthServerUrl": "https://example.com/file.jpg",
  "logoUrl": "https://example.com/file.jpg",
  "isActive": false,
  "isGlobal": false,
  "authType": {},
  "createdAt": "回應字串",
  "updatedAt": "回應字串"
}
```

列出組織自架的 MCP Server

`GET` `/api/v1/mcp/private-registry/`

需要連接器管理權限。接入方式見技術手冊自架 MCP Server。

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/mcp/private-registry/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/mcp/private-registry/",
config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/mcp/private-registry/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/mcp/private-registry/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
[
  {
    "id": string (uuid)
    "name": string // MCP service name (e.g., Supabase, Sentry). Only
alphanumeric, underscore and hyphen allowed.
```

```
    "displayName"?: string // Human-readable display name (defaults to name if empty) (非必填)
    "description"?: string // Brief description of the MCP service (非必填)
    "remoteMcpUrl": string (uri) // The URL of the Remote MCP service
    "oauthServerUrl"?: // 可能有不同的類型 (非必填)
    string (uri) // Manual override for the OAuth authorization server URL. Leave empty to auto-discover from the MCP server (RFC 9728 protected resource metadata). Only fill in when auto-discovery fails or the server advertises incorrect metadata. (e.g., Supabase MCP is at mcp.supabase.com but OAuth is at api.supabase.com) (非必填)
    "resourceIdentifier"?: // 可能有不同的類型 (非必填)
    string (uri) // Manual override for the OAuth resource identifier (RFC 9728 / RFC 8707). Leave empty to auto-discover from the MCP server's .well-known/oauth-protected-resource endpoint. Only fill in when auto-discovery fails or the metadata is incorrect. (e.g., Asana uses https://mcp.asana.com, Supabase uses https://mcp.supabase.com/mcp) (非必填)
    "oauthClientId"?: string // Pre-registered OAuth client ID for MCP servers that do not support dynamic client registration (RFC 7591). Leave empty if the server supports dynamic registration. (非必填)
    "oauthClientSecret"?: string // Pre-registered OAuth client secret. Required only if the MCP server requires a confidential client. Leave empty for public clients (token_endpoint_auth_method=none). (非必填)
    "logoUrl"?: // 可能有不同的類型 (非必填)
    string (uri) // Logo: the uploaded storage object key (media/...) or an external URL; read back as a signed URL. (非必填)
    "authType"?:  // How to authenticate with this MCP server.

* `oauth` - OAuth 2.0
* `service_account` - Service Account
* `none` - No Authentication (非必填)
    {
    }
    "cspAllowedOrigins"?: object // Extra origins a SEP-1865 MCP App card from this server may load from (script-src/img-src/connect-src etc.), e.g. ['https://viewer.diagrams.net']. The sandboxed iframe denies all external origins by default; list only what the app genuinely needs. Empty = the host's strict default (self only). (非必填)
    "isActive": boolean // Whether this MCP service is currently available for use
    "createdAt": string (timestamp)
    "updatedAt": string (timestamp)
  }
]
```

回應範例值

```
```

```
[
  {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應字串",
    "displayName": "回應字串",
    "description": "回應字串",
    "remoteMcpUrl": "https://example.com/file.jpg",
    "oauthServerUrl": "https://example.com/file.jpg",
    "resourceIdentifier": "https://example.com/file.jpg",
    "oauthClientId": "回應字串",
    "oauthClientSecret": "回應字串",
    "logoUrl": "https://example.com/file.jpg",
    "authType": {},
    "cspAllowedOrigins": null,
    "isActive": false,
    "createdAt": "回應字串",
    "updatedAt": "回應字串"
  }
]
```


新增自架 MCP Server

POST `/api/v1/mcp/private-registry/`

請求內容

請求參數

欄位	類型	必填	說明
name	string	是	MCP service name (e.g., Supabase, Sentry). Only alphanumeric, underscore and hyphen allowed.
displayName	string	否	Human-readable display name (defaults to name if empty)

欄位	類型	必填	說明
description	string	否	Brief description of the MCP service
remoteMcpUrl	string (uri)	是	The URL of the Remote MCP service
oauthServerUrl	object	否	Manual override for the OAuth authorization server URL. Leave empty to auto-discover from the MCP server (RFC 9728 protected resource metadata). Only fill in when auto-discovery fails or the server ad...
resourceIdentifier	object	否	Manual override for the OAuth resource identifier (RFC 9728 / RFC 8707). Leave empty to auto-discover from the MCP server's .well-known/oauth-protected-resource endpoint. Only fill in when auto-discov...
oauthClientId	string	否	Pre-registered OAuth client ID for MCP servers that do not support dynamic client registration (RFC 7591). Leave empty if the server supports dynamic registration.
oauthClientSecret	string	否	Pre-registered OAuth client secret. Required only if the MCP server requires a confidential client. Leave empty for public clients (token_endpoint_auth_method=none).
logoUrl	object	否	Logo: the uploaded storage object key (media/...) or an external URL; read back as a signed URL.
authType	object	否	How to authenticate with this MCP server. `oauth` : OAuth 2.0 ; `service_account` : Service Account ; `none` : No Authentication;
cspAllowedOrigins	object	否	Extra origins a SEP-1865 MCP App card from this server may load from (script-src/img-src/connect-src etc.), e.g. ['https://viewer.diagrams.net']. The sandboxed iframe denies all external origins by de...

請求結構範例

```
{
  "name": string // MCP service name (e.g., Supabase, Sentry). Only
alphanumeric, underscore and hyphen allowed.
  "displayName"?: string // Human-readable display name (defaults to name
if empty) (非必填)
```

```
  "description"?: string // Brief description of the MCP service (非必填)
  "remoteMcpUrl": string (uri) // The URL of the Remote MCP service
  "oauthServerUrl"?: // 可能有不同的類型 (非必填)
  string (uri) // Manual override for the OAuth authorization server URL. Leave empty to auto-discover from the MCP server (RFC 9728 protected resource metadata). Only fill in when auto-discovery fails or the server advertises incorrect metadata. (e.g., Supabase MCP is at mcp.supabase.com but OAuth is at api.supabase.com) (非必填)
  "resourceIdentifier"?: // 可能有不同的類型 (非必填)
  string (uri) // Manual override for the OAuth resource identifier (RFC 9728 / RFC 8707). Leave empty to auto-discover from the MCP server's .well-known/oauth-protected-resource endpoint. Only fill in when auto-discovery fails or the metadata is incorrect. (e.g., Asana uses https://mcp.asana.com, Supabase uses https://mcp.supabase.com/mcp) (非必填)
  "oauthClientId"?: string // Pre-registered OAuth client ID for MCP servers that do not support dynamic client registration (RFC 7591). Leave empty if the server supports dynamic registration. (非必填)
  "oauthClientSecret"?: string // Pre-registered OAuth client secret. Required only if the MCP server requires a confidential client. Leave empty for public clients (token_endpoint_auth_method=none). (非必填)
  "logoUrl"?: // 可能有不同的類型 (非必填)
  string (uri) // Logo: the uploaded storage object key (media/...) or an external URL; read back as a signed URL. (非必填)
  "authType"?:  // How to authenticate with this MCP server.

* `oauth` - OAuth 2.0
* `service_account` - Service Account
* `none` - No Authentication (非必填)
  {
  }
  "cspAllowedOrigins"?: object // Extra origins a SEP-1865 MCP App card from this server may load from (script-src/img-src/connect-src etc.), e.g. ['https://viewer.diagrams.net']. The sandboxed iframe denies all external origins by default; list only what the app genuinely needs. Empty = the host's strict default (self only). (非必填)
}
```

請求範例值

```
{
  "name": "範例名稱",
  "displayName": "範例字串",
  "description": "範例字串",
  "remoteMcpUrl": "https://example.com/file.jpg",
```

```
  "oauthServerUrl": null,
  "resourceIdentifier": null,
  "oauthClientId": "範例字串",
  "oauthClientSecret": "範例字串",
  "logoUrl": null,
  "authType": {},
  "cspAllowedOrigins": null
}
```


程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X POST "https://api.maiagent.ai/api/v1/mcp/private-registry/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "name": "範例名稱",
    "displayName": "範例字串",
    "description": "範例字串",
    "remoteMcpUrl": "https://example.com/file.jpg",
    "oauthServerUrl": null,
    "resourceIdentifier": null,
    "oauthClientId": "範例字串",
    "oauthClientSecret": "範例字串",
    "logoUrl": null,
    "authType": {},
    "cspAllowedOrigins": null
  }'

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// 請求內容 (payload)
const data = {
    "name": "範例名稱",
    "displayName": "範例字串",
    "description": "範例字串",
    "remoteMcpUrl": "https://example.com/file.jpg",
    "oauthServerUrl": null,
    "resourceIdentifier": null,
    "oauthClientId": "範例字串",
    "oauthClientSecret": "範例字串",
    "logoUrl": null,
    "authType": {},
    "cspAllowedOrigins": null
  };

axios.post("https://api.maiagent.ai/api/v1/mcp/private-registry/",
data, config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/mcp/private-registry/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# 請求內容 (payload)
data = {
    "name": "範例名稱",
    "displayName": "範例字串",
    "description": "範例字串",
    "remoteMcpUrl": "https://example.com/file.jpg",
    "oauthServerUrl": None,
    "resourceIdentifier": None,
    "oauthClientId": "範例字串",
    "oauthClientSecret": "範例字串",
    "logoUrl": None,
    "authType": {},
    "cspAllowedOrigins": None
}

response = requests.post(url, json=data, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>post("https://api.maiagent.ai/api/v1/mcp/private-registry/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'name' => '範例名稱',
            'displayName' => '範例字串',
            'description' => '範例字串',
            'remoteMcpUrl' => 'https://example.com/file.jpg',
            'oauthServerUrl' => null,
            'resourceIdentifier' => null,
            'oauthClientId' => '範例字串',
            'oauthClientSecret' => '範例字串',
            'logoUrl' => null,
            'authType' => new \stdClass(),
            'cspAllowedOrigins' => null
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 201

回應結構範例

```
{
  "id": string (uuid)
  "name": string // MCP service name (e.g., Supabase, Sentry). Only
alphanumeric, underscore and hyphen allowed.
  "displayName"?: string // Human-readable display name (defaults to name
if empty) (非必填)
  "description"?: string // Brief description of the MCP service (非必填)
  "remoteMcpUrl": string (uri) // The URL of the Remote MCP service
  "oauthServerUrl"?: // 可能有不同的類型 (非必填)
  string (uri) // Manual override for the OAuth authorization server URL.
Leave empty to auto-discover from the MCP server (RFC 9728 protected
resource metadata). Only fill in when auto-discovery fails or the server
advertises incorrect metadata. (e.g., Supabase MCP is at mcp.supabase.com
but OAuth is at api.supabase.com) (非必填)
  "resourceIdentifier"?: // 可能有不同的類型 (非必填)
  string (uri) // Manual override for the OAuth resource identifier (RFC
9728 / RFC 8707). Leave empty to auto-discover from the MCP server's .well-
known/oauth-protected-resource endpoint. Only fill in when auto-discovery
fails or the metadata is incorrect. (e.g., Asana uses
https://mcp.asana.com, Supabase uses https://mcp.supabase.com/mcp) (非必填)
  "oauthClientId"?: string // Pre-registered OAuth client ID for MCP
servers that do not support dynamic client registration (RFC 7591). Leave
empty if the server supports dynamic registration. (非必填)
  "oauthClientSecret"?: string // Pre-registered OAuth client secret.
Required only if the MCP server requires a confidential client. Leave empty
for public clients (token_endpoint_auth_method=none). (非必填)
  "logoUrl"?: // 可能有不同的類型 (非必填)
  string (uri) // Logo: the uploaded storage object key (media/...) or an
external URL; read back as a signed URL. (非必填)
  "authType"?:  // How to authenticate with this MCP server.

* `oauth` - OAuth 2.0
* `service_account` - Service Account
* `none` - No Authentication (非必填)
  {
  }
  "cspAllowedOrigins"?: object // Extra origins a SEP-1865 MCP App card
```

```
from this server may load from (script-src/img-src/connect-src etc.), e.g.
['https://viewer.diagrams.net']. The sandboxed iframe denies all external
origins by default; list only what the app genuinely needs. Empty = the
host's strict default (self only). (非必填)
  "isActive": boolean // Whether this MCP service is currently available
for use
  "createdAt": string (timestamp)
  "updatedAt": string (timestamp)
}
```

回應範例值


```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "name": "回應字串",
  "displayName": "回應字串",
  "description": "回應字串",
  "remoteMcpUrl": "https://example.com/file.jpg",
  "oauthServerUrl": "https://example.com/file.jpg",
  "resourceIdentifier": "https://example.com/file.jpg",
  "oauthClientId": "回應字串",
  "oauthClientSecret": "回應字串",
  "logoUrl": "https://example.com/file.jpg",
  "authType": {},
  "cspAllowedOrigins": null,
  "isActive": false,
  "createdAt": "回應字串",
  "updatedAt": "回應字串"
}
```


取得特定自架 MCP Server

`GET` `/api/v1/mcp/private-registry/{id}`

參數

參數名稱	必填	類型	說明
id	V	string	A UUID string identifying this MCP Registry.

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/mcp/private-
registry/550e8400-e29b-41d4-a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/mcp/private-
registry/550e8400-e29b-41d4-a716-446655440000/", config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/mcp/private-registry/550e8400-e29b-41d4-a716-446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/mcp/private-registry/550e8400-
e29b-41d4-a716-446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
{
  "id": string (uuid)
  "name": string // MCP service name (e.g., Supabase, Sentry). Only
alphanumeric, underscore and hyphen allowed.
```

```
  "displayName"?: string // Human-readable display name (defaults to name
if empty) (非必填)
  "description"?: string // Brief description of the MCP service (非必填)
  "remoteMcpUrl": string (uri) // The URL of the Remote MCP service
  "oauthServerUrl"?: // 可能有不同的類型 (非必填)
  string (uri) // Manual override for the OAuth authorization server URL.
Leave empty to auto-discover from the MCP server (RFC 9728 protected
resource metadata). Only fill in when auto-discovery fails or the server
advertises incorrect metadata. (e.g., Supabase MCP is at mcp.supabase.com
but OAuth is at api.supabase.com) (非必填)
  "resourceIdentifier"?: // 可能有不同的類型 (非必填)
  string (uri) // Manual override for the OAuth resource identifier (RFC
9728 / RFC 8707). Leave empty to auto-discover from the MCP server's .well-
known/oauth-protected-resource endpoint. Only fill in when auto-discovery
fails or the metadata is incorrect. (e.g., Asana uses
https://mcp.asana.com, Supabase uses https://mcp.supabase.com/mcp) (非必填)
  "oauthClientId"?: string // Pre-registered OAuth client ID for MCP
servers that do not support dynamic client registration (RFC 7591). Leave
empty if the server supports dynamic registration. (非必填)
  "oauthClientSecret"?: string // Pre-registered OAuth client secret.
Required only if the MCP server requires a confidential client. Leave empty
for public clients (token_endpoint_auth_method=none). (非必填)
  "logoUrl"?: // 可能有不同的類型 (非必填)
  string (uri) // Logo: the uploaded storage object key (media/...) or an
external URL; read back as a signed URL. (非必填)
  "authType"?:  // How to authenticate with this MCP server.

* `oauth` - OAuth 2.0
* `service_account` - Service Account
* `none` - No Authentication (非必填)
  {
  }
  "cspAllowedOrigins"?: object // Extra origins a SEP-1865 MCP App card
from this server may load from (script-src/img-src/connect-src etc.), e.g.
['https://viewer.diagrams.net']. The sandboxed iframe denies all external
origins by default; list only what the app genuinely needs. Empty = the
host's strict default (self only). (非必填)
  "isActive": boolean // Whether this MCP service is currently available
for use
  "createdAt": string (timestamp)
  "updatedAt": string (timestamp)
}
```

回應範例值

```
```

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "name": "回應字串",
  "displayName": "回應字串",
  "description": "回應字串",
  "remoteMcpUrl": "https://example.com/file.jpg",
  "oauthServerUrl": "https://example.com/file.jpg",
  "resourceIdentifier": "https://example.com/file.jpg",
  "oauthClientId": "回應字串",
  "oauthClientSecret": "回應字串",
  "logoUrl": "https://example.com/file.jpg",
  "authType": {},
  "cspAllowedOrigins": null,
  "isActive": false,
  "createdAt": "回應字串",
  "updatedAt": "回應字串"
}
```


部分更新自架 MCP Server

PATCH `/api/v1/mcp/private-registry/{id}`

參數

參數名稱	必填	類型	說明
id	V	string	A UUID string identifying this MCP Registry.

請求內容

請求參數

欄位	類型	必填	說明
name	string	否	MCP service name (e.g., Supabase, Sentry). Only alphanumeric, underscore and hyphen allowed.
displayName	string	否	Human-readable display name (defaults to name if empty)
description	string	否	Brief description of the MCP service
remoteMcpUrl	string (uri)	否	The URL of the Remote MCP service
oauthServerUrl	object	否	Manual override for the OAuth authorization server URL. Leave empty to auto-discover from the MCP server (RFC 9728 protected resource metadata). Only fill in when auto-discovery fails or the server ad...
resourceIdentifier	object	否	Manual override for the OAuth resource identifier (RFC 9728 / RFC 8707). Leave empty to auto-discover from the MCP server's .well-known/oauth-protected-resource endpoint. Only fill in when auto-discov...
oauthClientId	string	否	Pre-registered OAuth client ID for MCP servers that do not support dynamic client registration (RFC 7591). Leave empty if the server supports dynamic registration.
oauthClientSecret	string	否	Pre-registered OAuth client secret. Required only if the MCP server requires a confidential client. Leave empty for public clients (token_endpoint_auth_method=none).
logoUrl	object	否	Logo: the uploaded storage object key (media/...) or an external URL; read back as a signed URL.
authType	object	否	How to authenticate with this MCP server. `oauth` : OAuth 2.0 ; `service_account` : Service Account ; `none` : No Authentication;
cspAllowedOrigins	object	否	Extra origins a SEP-1865 MCP App card from this server may load from (script-src/img-src/connect-src etc.), e.g. ['https://viewer.diagrams.net']. The sandboxed iframe denies all external origins by de...

請求結構範例

```
{
  "name"?: string // MCP service name (e.g., Supabase, Sentry). Only alphanumeric, underscore and hyphen allowed. (非必填)
  "displayName"?: string // Human-readable display name (defaults to name if empty) (非必填)
  "description"?: string // Brief description of the MCP service (非必填)
  "remoteMcpUrl"?: string (uri) // The URL of the Remote MCP service (非必填)
  "oauthServerUrl"?: // 可能有不同的類型 (非必填)
  string (uri) // Manual override for the OAuth authorization server URL. Leave empty to auto-discover from the MCP server (RFC 9728 protected resource metadata). Only fill in when auto-discovery fails or the server advertises incorrect metadata. (e.g., Supabase MCP is at mcp.supabase.com but OAuth is at api.supabase.com) (非必填)
  "resourceIdentifier"?: // 可能有不同的類型 (非必填)
  string (uri) // Manual override for the OAuth resource identifier (RFC 9728 / RFC 8707). Leave empty to auto-discover from the MCP server's .well-known/oauth-protected-resource endpoint. Only fill in when auto-discovery fails or the metadata is incorrect. (e.g., Asana uses https://mcp.asana.com, Supabase uses https://mcp.supabase.com/mcp) (非必填)
  "oauthClientId"?: string // Pre-registered OAuth client ID for MCP servers that do not support dynamic client registration (RFC 7591). Leave empty if the server supports dynamic registration. (非必填)
  "oauthClientSecret"?: string // Pre-registered OAuth client secret. Required only if the MCP server requires a confidential client. Leave empty for public clients (token_endpoint_auth_method=none). (非必填)
  "logoUrl"?: // 可能有不同的類型 (非必填)
  string (uri) // Logo: the uploaded storage object key (media/...) or an external URL; read back as a signed URL. (非必填)
  "authType"?:  // How to authenticate with this MCP server.

* `oauth` - OAuth 2.0
* `service_account` - Service Account
* `none` - No Authentication (非必填)
  {
  }
  "cspAllowedOrigins"?: object // Extra origins a SEP-1865 MCP App card from this server may load from (script-src/img-src/connect-src etc.), e.g. ['https://viewer.diagrams.net']. The sandboxed iframe denies all external origins by default; list only what the app genuinely needs. Empty = the host's strict default (self only). (非必填)
}
```

請求範例值

```
```

```
{
  "name": "範例名稱",
  "displayName": "範例字串",
  "description": "範例字串",
  "remoteMcpUrl": "https://example.com/file.jpg",
  "oauthServerUrl": null,
  "resourceIdentifier": null,
  "oauthClientId": "範例字串",
  "oauthClientSecret": "範例字串",
  "logoUrl": null,
  "authType": {},
  "cspAllowedOrigins": null
}
```


程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X PATCH "https://api.maiagent.ai/api/v1/mcp/private-
registry/550e8400-e29b-41d4-a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "name": "範例名稱",
    "displayName": "範例字串",
    "description": "範例字串",
    "remoteMcpUrl": "https://example.com/file.jpg",
    "oauthServerUrl": null,
    "resourceIdentifier": null,
    "oauthClientId": "範例字串",
    "oauthClientSecret": "範例字串",
    "logoUrl": null,
    "authType": {},
    "cspAllowedOrigins": null
  }'

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// 請求內容 (payload)
const data = {
    "name": "範例名稱",
    "displayName": "範例字串",
    "description": "範例字串",
    "remoteMcpUrl": "https://example.com/file.jpg",
    "oauthServerUrl": null,
    "resourceIdentifier": null,
    "oauthClientId": "範例字串",
    "oauthClientSecret": "範例字串",
    "logoUrl": null,
    "authType": {},
    "cspAllowedOrigins": null
  };

axios.patch("https://api.maiagent.ai/api/v1/mcp/private-
registry/550e8400-e29b-41d4-a716-446655440000/", data, config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/mcp/private-registry/550e8400-e29b-41d4-a716-446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# 請求內容 (payload)
data = {
    "name": "範例名稱",
    "displayName": "範例字串",
    "description": "範例字串",
    "remoteMcpUrl": "https://example.com/file.jpg",
    "oauthServerUrl": None,
    "resourceIdentifier": None,
    "oauthClientId": "範例字串",
    "oauthClientSecret": "範例字串",
    "logoUrl": None,
    "authType": {},
    "cspAllowedOrigins": None
}

response = requests.patch(url, json=data, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>patch("https://api.maiagent.ai/api/v1/mcp/private-registry/550e8400-
e29b-41d4-a716-446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'name' => '範例名稱',
            'displayName' => '範例字串',
            'description' => '範例字串',
            'remoteMcpUrl' => 'https://example.com/file.jpg',
            'oauthServerUrl' => null,
            'resourceIdentifier' => null,
            'oauthClientId' => '範例字串',
            'oauthClientSecret' => '範例字串',
            'logoUrl' => null,
            'authType' => new \stdClass(),
            'cspAllowedOrigins' => null
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
{
  "id": string (uuid)
  "name": string // MCP service name (e.g., Supabase, Sentry). Only
alphanumeric, underscore and hyphen allowed.
  "displayName"?: string // Human-readable display name (defaults to name
if empty) (非必填)
  "description"?: string // Brief description of the MCP service (非必填)
  "remoteMcpUrl": string (uri) // The URL of the Remote MCP service
  "oauthServerUrl"?: // 可能有不同的類型 (非必填)
  string (uri) // Manual override for the OAuth authorization server URL.
Leave empty to auto-discover from the MCP server (RFC 9728 protected
resource metadata). Only fill in when auto-discovery fails or the server
advertises incorrect metadata. (e.g., Supabase MCP is at mcp.supabase.com
but OAuth is at api.supabase.com) (非必填)
  "resourceIdentifier"?: // 可能有不同的類型 (非必填)
  string (uri) // Manual override for the OAuth resource identifier (RFC
9728 / RFC 8707). Leave empty to auto-discover from the MCP server's .well-
known/oauth-protected-resource endpoint. Only fill in when auto-discovery
fails or the metadata is incorrect. (e.g., Asana uses
https://mcp.asana.com, Supabase uses https://mcp.supabase.com/mcp) (非必填)
  "oauthClientId"?: string // Pre-registered OAuth client ID for MCP
servers that do not support dynamic client registration (RFC 7591). Leave
empty if the server supports dynamic registration. (非必填)
  "oauthClientSecret"?: string // Pre-registered OAuth client secret.
Required only if the MCP server requires a confidential client. Leave empty
for public clients (token_endpoint_auth_method=none). (非必填)
  "logoUrl"?: // 可能有不同的類型 (非必填)
  string (uri) // Logo: the uploaded storage object key (media/...) or an
external URL; read back as a signed URL. (非必填)
  "authType"?:  // How to authenticate with this MCP server.

* `oauth` - OAuth 2.0
* `service_account` - Service Account
* `none` - No Authentication (非必填)
  {
  }
  "cspAllowedOrigins"?: object // Extra origins a SEP-1865 MCP App card
```

```
from this server may load from (script-src/img-src/connect-src etc.), e.g.
['https://viewer.diagrams.net']. The sandboxed iframe denies all external
origins by default; list only what the app genuinely needs. Empty = the
host's strict default (self only). (非必填)
  "isActive": boolean // Whether this MCP service is currently available
for use
  "createdAt": string (timestamp)
  "updatedAt": string (timestamp)
}
```

回應範例值


```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "name": "回應字串",
  "displayName": "回應字串",
  "description": "回應字串",
  "remoteMcpUrl": "https://example.com/file.jpg",
  "oauthServerUrl": "https://example.com/file.jpg",
  "resourceIdentifier": "https://example.com/file.jpg",
  "oauthClientId": "回應字串",
  "oauthClientSecret": "回應字串",
  "logoUrl": "https://example.com/file.jpg",
  "authType": {},
  "cspAllowedOrigins": null,
  "isActive": false,
  "createdAt": "回應字串",
  "updatedAt": "回應字串"
}
```


刪除自架 MCP Server

DELETE `/api/v1/mcp/private-registry/{id}`

參數

參數名稱	必填	類型	說明
id	V	string	A UUID string identifying this MCP Registry.

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X DELETE "https://api.maiagent.ai/api/v1/mcp/private-
registry/550e8400-e29b-41d4-a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

// 請求內容 (payload)
const data = null;

axios.delete("https://api.maiagent.ai/api/v1/mcp/private-
registry/550e8400-e29b-41d4-a716-446655440000/", data, config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/mcp/private-registry/550e8400-
e29b-41d4-a716-446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.delete(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->delete("https://api.maiagent.ai/api/v1/mcp/private-registry/550e8400-e29b-41d4-a716-446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼	說明
204	No response body

測試 MCP Server 連線

POST `/api/v1/mcp/private-registry/test-connection/`

請求內容

請求參數

欄位	類型	必填	說明
name	string	是	MCP service name (e.g., Supabase, Sentry). Only alphanumeric, underscore and hyphen allowed.
displayName	string	否	Human-readable display name (defaults to name if empty)
description	string	否	Brief description of the MCP service
remoteMcpUrl	string (uri)	是	The URL of the Remote MCP service
oauthServerUrl	object	否	Manual override for the OAuth authorization server URL. Leave empty to auto-discover from the MCP server (RFC 9728 protected resource metadata). Only fill in when auto-discovery fails or the server ad...
resourceIdentifier	object	否	Manual override for the OAuth resource identifier (RFC 9728 / RFC 8707). Leave empty to auto-discover from the MCP server's .well-known/oauth-protected-resource endpoint. Only fill in when auto-discov...
oauthClientId	string	否	Pre-registered OAuth client ID for MCP servers that do not support dynamic client registration (RFC 7591). Leave empty if the server supports dynamic registration.
oauthClientSecret	string	否	Pre-registered OAuth client secret. Required only if the MCP server requires a confidential client. Leave empty for public clients (token_endpoint_auth_method=none).
logoUrl	object	否	Logo: the uploaded storage object key (media/...) or an external URL; read back as a signed URL.
authType	object	否	How to authenticate with this MCP server. `oauth` : OAuth 2.0 ; `service_account` : Service Account ;

欄位	類型	必填	說明
			`none` : No Authentication;
cspAllowedOrigins	object	否	Extra origins a SEP-1865 MCP App card from this server may load from (script-src/img-src/connect-src etc.), e.g. ['https://viewer.diagrams.net']. The sandboxed iframe denies all external origins by de...

請求結構範例

```
{
  "name": string // MCP service name (e.g., Supabase, Sentry). Only
alphanumeric, underscore and hyphen allowed.
  "displayName"?: string // Human-readable display name (defaults to name
if empty) (非必填)
  "description"?: string // Brief description of the MCP service (非必填)
  "remoteMcpUrl": string (uri) // The URL of the Remote MCP service
  "oauthServerUrl"?: // 可能有不同的類型 (非必填)
  string (uri) // Manual override for the OAuth authorization server URL.
Leave empty to auto-discover from the MCP server (RFC 9728 protected
resource metadata). Only fill in when auto-discovery fails or the server
advertises incorrect metadata. (e.g., Supabase MCP is at mcp.supabase.com
but OAuth is at api.supabase.com) (非必填)
  "resourceIdentifier"?: // 可能有不同的類型 (非必填)
  string (uri) // Manual override for the OAuth resource identifier (RFC
9728 / RFC 8707). Leave empty to auto-discover from the MCP server's .well-
known/oauth-protected-resource endpoint. Only fill in when auto-discovery
fails or the metadata is incorrect. (e.g., Asana uses
https://mcp.asana.com, Supabase uses https://mcp.supabase.com/mcp) (非必填)
  "oauthClientId"?: string // Pre-registered OAuth client ID for MCP
servers that do not support dynamic client registration (RFC 7591). Leave
empty if the server supports dynamic registration. (非必填)
  "oauthClientSecret"?: string // Pre-registered OAuth client secret.
Required only if the MCP server requires a confidential client. Leave empty
for public clients (token_endpoint_auth_method=none). (非必填)
  "logoUrl"?: // 可能有不同的類型 (非必填)
  string (uri) // Logo: the uploaded storage object key (media/...) or an
external URL; read back as a signed URL. (非必填)
  "authType"?:  // How to authenticate with this MCP server.

* `oauth` - OAuth 2.0
* `service_account` - Service Account
* `none` - No Authentication (非必填)
```

```
  {
  }
  "cspAllowedOrigins"?: object // Extra origins a SEP-1865 MCP App card
from this server may load from (script-src/img-src/connect-src etc.), e.g.
['https://viewer.diagrams.net']. The sandboxed iframe denies all external
origins by default; list only what the app genuinely needs. Empty = the
host's strict default (self only). (非必填)
}
```

請求範例值

```
{
  "name": "範例名稱",
  "displayName": "範例字串",
  "description": "範例字串",
  "remoteMcpUrl": "https://example.com/file.jpg",
  "oauthServerUrl": null,
  "resourceIdentifier": null,
  "oauthClientId": "範例字串",
  "oauthClientSecret": "範例字串",
  "logoUrl": null,
  "authType": {},
  "cspAllowedOrigins": null
}
```

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X POST "https://api.maiagent.ai/api/v1/mcp/private-
registry/test-connection/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "name": "範例名稱",
    "displayName": "範例字串",
    "description": "範例字串",
    "remoteMcpUrl": "https://example.com/file.jpg",
    "oauthServerUrl": null,
    "resourceIdentifier": null,
    "oauthClientId": "範例字串",
    "oauthClientSecret": "範例字串",
    "logoUrl": null,
    "authType": {},
    "cspAllowedOrigins": null
  }'

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// 請求內容 (payload)
const data = {
    "name": "範例名稱",
    "displayName": "範例字串",
    "description": "範例字串",
    "remoteMcpUrl": "https://example.com/file.jpg",
    "oauthServerUrl": null,
    "resourceIdentifier": null,
    "oauthClientId": "範例字串",
    "oauthClientSecret": "範例字串",
    "logoUrl": null,
    "authType": {},
    "cspAllowedOrigins": null
  };

axios.post("https://api.maiagent.ai/api/v1/mcp/private-registry/test-
connection/", data, config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/mcp/private-registry/test-
connection/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# 請求內容 (payload)
data = {
    "name": "範例名稱",
    "displayName": "範例字串",
    "description": "範例字串",
    "remoteMcpUrl": "https://example.com/file.jpg",
    "oauthServerUrl": None,
    "resourceIdentifier": None,
    "oauthClientId": "範例字串",
    "oauthClientSecret": "範例字串",
    "logoUrl": None,
    "authType": {},
    "cspAllowedOrigins": None
}

response = requests.post(url, json=data, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->post("https://api.maiagent.ai/api/v1/mcp/private-registry/test-connection/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'name' => '範例名稱',
            'displayName' => '範例字串',
            'description' => '範例字串',
            'remoteMcpUrl' => 'https://example.com/file.jpg',
            'oauthServerUrl' => null,
            'resourceIdentifier' => null,
            'oauthClientId' => '範例字串',
            'oauthClientSecret' => '範例字串',
            'logoUrl' => null,
            'authType' => new \stdClass(),
            'cspAllowedOrigins' => null
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
{
  "id": string (uuid)
  "name": string // MCP service name (e.g., Supabase, Sentry). Only
alphanumeric, underscore and hyphen allowed.
  "displayName"?: string // Human-readable display name (defaults to name
if empty) (非必填)
  "description"?: string // Brief description of the MCP service (非必填)
  "remoteMcpUrl": string (uri) // The URL of the Remote MCP service
  "oauthServerUrl"?: // 可能有不同的類型 (非必填)
  string (uri) // Manual override for the OAuth authorization server URL.
Leave empty to auto-discover from the MCP server (RFC 9728 protected
resource metadata). Only fill in when auto-discovery fails or the server
advertises incorrect metadata. (e.g., Supabase MCP is at mcp.supabase.com
but OAuth is at api.supabase.com) (非必填)
  "resourceIdentifier"?: // 可能有不同的類型 (非必填)
  string (uri) // Manual override for the OAuth resource identifier (RFC
9728 / RFC 8707). Leave empty to auto-discover from the MCP server's .well-
known/oauth-protected-resource endpoint. Only fill in when auto-discovery
fails or the metadata is incorrect. (e.g., Asana uses
https://mcp.asana.com, Supabase uses https://mcp.supabase.com/mcp) (非必填)
  "oauthClientId"?: string // Pre-registered OAuth client ID for MCP
servers that do not support dynamic client registration (RFC 7591). Leave
empty if the server supports dynamic registration. (非必填)
  "oauthClientSecret"?: string // Pre-registered OAuth client secret.
Required only if the MCP server requires a confidential client. Leave empty
for public clients (token_endpoint_auth_method=none). (非必填)
  "logoUrl"?: // 可能有不同的類型 (非必填)
  string (uri) // Logo: the uploaded storage object key (media/...) or an
external URL; read back as a signed URL. (非必填)
  "authType"?:  // How to authenticate with this MCP server.

* `oauth` - OAuth 2.0
* `service_account` - Service Account
* `none` - No Authentication (非必填)
  {
  }
  "cspAllowedOrigins"?: object // Extra origins a SEP-1865 MCP App card
```

```
from this server may load from (script-src/img-src/connect-src etc.), e.g.
['https://viewer.diagrams.net']. The sandboxed iframe denies all external
origins by default; list only what the app genuinely needs. Empty = the
host's strict default (self only). (非必填)
  "isActive": boolean // Whether this MCP service is currently available
for use
  "createdAt": string (timestamp)
  "updatedAt": string (timestamp)
}
```

回應範例值


```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "name": "回應字串",
  "displayName": "回應字串",
  "description": "回應字串",
  "remoteMcpUrl": "https://example.com/file.jpg",
  "oauthServerUrl": "https://example.com/file.jpg",
  "resourceIdentifier": "https://example.com/file.jpg",
  "oauthClientId": "回應字串",
  "oauthClientSecret": "回應字串",
  "logoUrl": "https://example.com/file.jpg",
  "authType": {},
  "cspAllowedOrigins": null,
  "isActive": false,
  "createdAt": "回應字串",
  "updatedAt": "回應字串"
}
```


取得工具執行紀錄列表

GET `/api/v1/tool-execution-records/`

參數

參數名稱	必填	類型	說明
`chatbot`	X	string	通過 AI 助理 ID 過濾
`endDate`	X	string	結束日期（包含當日），格式：YYYY-MM-DD
`page`	X	integer	A page number within the paginated result set.
`pageSize`	X	integer	Number of results to return per page.
`query`	X	string	搜尋 AI 助理名稱、工具名稱、訊息內容
`startDate`	X	string	開始日期（包含當日），格式：YYYY-MM-DD
`status`	X	string	通過執行狀態過濾：success, failure, pending, timeout
`tool`	X	string	通過工具 ID 過濾
`toolType`	X	string	通過工具類型過濾：api, function, mcp

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/tool-execution-records/?
chatbot=example&endDate=example&page=1&pageSize=1&query=example&startD
ate=example&status=failure&tool=example&toolType=api"

  -H "Authorization: Api-Key YOUR_API_KEY"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/tool-execution-records/?
chatbot=example&endDate=example&page=1&pageSize=1&query=example&startD
ate=example&status=failure&tool=example&toolType=api", config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/tool-execution-records/?
chatbot=example&endDate=example&page=1&pageSize=1&query=example&startD
ate=example&status=failure&tool=example&toolType=api"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->get("https://api.maiagent.ai/api/v1/tool-execution-records/?chatbot=example&endDate=example&page=1&pageSize=1&query=example&startDate=example&status=failure&tool=example&toolType=api", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
{
  "count": integer
  "next"?: string (uri) // 非必填
```

```
  "previous"?: string (uri) // 非必填
  "results": [
    {
      "id": string (uuid)
      "tool": object // 獲取工具資訊
      "chatbot": object // 獲取 AI 助理資訊
      "messageContent": string // 獲取訊息內容
      "status"?: string (enum: success, failure, pending, timeout) // *
`success` - Success
* `failure` - Failed
* `pending` - Processing
* `timeout` - Timeout (非必填)
      "executionTime": integer // 獲取執行時間（毫秒）
      "errorMessage"?: string // 非必填
      "retryCount"?: integer // How many times the platform auto-retried
this tool call before the final outcome (0 = the first attempt was the
final one). API tools count tenacity retries inside APIRequestService; MCP
tools count transient-error retries (read-classified tools only). Function
tools are never auto-retried. (非必填)
      "createdAt": string (timestamp)
      "source": string // Scheduled runs' tool calls are attributed via
ChatbotScheduleExecution.user_message.
    }
  ]
}
```

回應範例值

```
{
  "count": 123,
  "next": "http://api.example.org/accounts/?page=4",
  "previous": "http://api.example.org/accounts/?page=2",
  "results": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "tool": {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "name": "回應範例名稱",
        "description": "回應範例描述"
      },
      "chatbot": {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "name": "回應範例名稱",
        "description": "回應範例描述"
```

```
      },
      "messageContent": "回應字串",
      "status": "success",
      "executionTime": 456,
      "errorMessage": "回應字串",
      "retryCount": 456,
      "createdAt": "回應字串",
      "source": "回應字串"
    }
  ]
}
```


取得特定工具執行紀錄

`GET` `/api/v1/tool-execution-records/{id}`

參數

參數名稱	必填	類型	說明
`id`	V	string	A UUID string identifying this Tool Execution Record.

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/tool-execution-
records/550e8400-e29b-41d4-a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/tool-execution-
records/550e8400-e29b-41d4-a716-446655440000/", config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/tool-execution-records/550e8400-e29b-41d4-a716-446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->get("https://api.maiagent.ai/api/v1/tool-execution-records/550e8400-e29b-41d4-a716-446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
{
  "id": string (uuid)
  "tool": object // 獲取工具資訊，並包含 operated_tool_name
  "chatbot": object // 獲取 AI 助理資訊
  "message":
```

```
  {
    "id": string (uuid)
    "content": string
  }
  "inputParameters": object
  "outputResult"?: object // 非必填
  "errorMessage"?: string // 非必填
  "status"?: string (enum: success, failure, pending, timeout) // *
`success` - Success
* `failure` - Failed
* `pending` - Processing
* `timeout` - Timeout (非必填)
  "executionTime": integer // 獲取執行時間（毫秒）
  "retryCount"?: integer // How many times the platform auto-retried this
tool call before the final outcome (0 = the first attempt was the final
one). API tools count tenacity retries inside APIRequestService; MCP tools
count transient-error retries (read-classified tools only). Function tools
are never auto-retried. (非必填)
  "requestUrl"?: // 可能有不同的類型 (非必填)
  string (uri) // Final rendered URL used when calling an API tool. Null
for non-API tools. (非必填)
  "requestMethod"?: string // HTTP method (GET/POST/...) used when calling
an API tool. Null for non-API tools. (非必填)
  "requestHeaders": object // Return rendered request headers with
sensitive values masked.

Three sources are unioned, any hit masks:
``settings.TOOL_API_SENSITIVE_HEADERS``,
APICredential keys for the (contact, tool) pair, and the tool's current
``sensitive_headers``. The tool list is applied at read time against the
stored
value, so editing it changes how existing records render without rewriting
them.
  "requestBody"?: object // Final rendered body sent to the external API.
Null for non-API tools or read-only methods. (非必填)
  "createdAt": string (timestamp)
  "updatedAt": string (timestamp)
  "source": string // Scheduled runs' tool calls are attributed via
ChatbotScheduleExecution.user_message.
}
```

回應範例值

```
```

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "tool": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應範例名稱",
    "description": "回應範例描述"
  },
  "chatbot": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應範例名稱",
    "description": "回應範例描述"
  },
  "message": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "content": "回應字串"
  },
  "inputParameters": null,
  "outputResult": null,
  "errorMessage": "回應字串",
  "status": "success",
  "executionTime": 456,
  "retryCount": 456,
  "requestUrl": "https://example.com/file.jpg",
  "requestMethod": "回應字串",
  "requestHeaders": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應範例名稱",
    "description": "回應範例描述"
  },
  "requestBody": null,
  "createdAt": "回應字串",
  "updatedAt": "回應字串",
  "source": "回應字串"
}
```


取得執行紀錄的 AI 助理過濾選項

GET `/api/v1/tool-execution-records/chatbots/`

參數

參數名稱	必填	類型	說明
`chatbot`	X	string	
`endDate`	X	string	
`query`	X	string	
`startDate`	X	string	
`status`	X	string	`success`: Success ; `failure`: Failed ; `pending`: Processing ; `timeout`: Timeout;
`tool`	X	string	
`toolType`	X	string	`api`: API ; `function`: Function ; `mcp`: MCP ; `desktop`: Desktop ; `flex`: Flex Message ; `quick_reply`: Quick Reply ; `quick_menu`: Quick Menu;

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/tool-execution-
records/chatbots/?chatbot=550e8400-e29b-41d4-a716-
446655440000&endDate=example&query=example&startDate=example&status=fa
ilure&tool=550e8400-e29b-41d4-a716-446655440000&toolType=api"

  -H "Authorization: Api-Key YOUR_API_KEY"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/tool-execution-
records/chatbots/?chatbot=550e8400-e29b-41d4-a716-
446655440000&endDate=example&query=example&startDate=example&status=fa
ilure&tool=550e8400-e29b-41d4-a716-446655440000&toolType=api", config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/tool-execution-
records/chatbots/?chatbot=550e8400-e29b-41d4-a716-
446655440000&endDate=example&query=example&startDate=example&status=fa
ilure&tool=550e8400-e29b-41d4-a716-446655440000&toolType=api"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->get("https://api.maiagent.ai/api/v1/tool-execution-records/chatbots/?chatbot=550e8400-e29b-41d4-a716-446655440000&endDate=example&query=example&startDate=example&status=failure&tool=550e8400-e29b-41d4-a716-446655440000&toolType=api", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
[
  {
    "id": string (uuid)
```

```
    "name": string // Chatbot name. In Agent mode it carries semantic
meaning; in other modes it only distinguishes chatbots.
    "team":
    {
      "id": string (uuid)
      "name": string
    }
  }
]
```

回應範例值

```
[
  {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應字串",
    "team": {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "回應字串"
    }
  }
]
```

取得執行紀錄的工具過濾選項

GET `/api/v1/tool-execution-records/tools/`

參數

參數名稱	必填	類型	說明
`chatbot`	X	string	
`endDate`	X	string	

`page`	X	integer	A page number within the paginated result set.
`pageSize`	X	integer	Number of results to return per page.
`query`	X	string	
`startDate`	X	string	
`status`	X	string	`success`: Success ; `failure`: Failed ; `pending`: Processing ; `timeout`: Timeout;
`tool`	X	string	
`toolType`	X	string	`api`: API ; `function`: Function ; `mcp`: MCP ; `desktop`: Desktop ; `flex`: Flex Message ; `quick_reply`: Quick Reply ; `quick_menu`: Quick Menu;

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/tool-execution-
records/tools/?chatbot=550e8400-e29b-41d4-a716-
446655440000&endDate=example&page=1&pageSize=1&query=example&startDate
=example&status=failure&tool=550e8400-e29b-41d4-a716-
446655440000&toolType=api"

  -H "Authorization: Api-Key YOUR_API_KEY"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/tool-execution-
records/tools/?chatbot=550e8400-e29b-41d4-a716-
446655440000&endDate=example&page=1&pageSize=1&query=example&startDate
=example&status=failure&tool=550e8400-e29b-41d4-a716-
446655440000&toolType=api", config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/tool-execution-records/tools/?
chatbot=550e8400-e29b-41d4-a716-
446655440000&endDate=example&page=1&pageSize=1&query=example&startDate
=example&status=failure&tool=550e8400-e29b-41d4-a716-
446655440000&toolType=api"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->get("https://api.maiagent.ai/api/v1/tool-execution-records/tools/?chatbot=550e8400-e29b-41d4-a716-446655440000&endDate=example&page=1&pageSize=1&query=example&startDate=example&status=failure&tool=550e8400-e29b-41d4-a716-446655440000&toolType=api", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
{
  "count": integer
```

```
  "next"?: string (uri) // 非必填
  "previous"?: string (uri) // 非必填
  "results": [
    {
      "id": string (uuid)
      "displayName": string
    }
  ]
}
```

回應範例值

```
{
  "count": 123,
  "next": "http://api.example.org/accounts/?page=4",
  "previous": "http://api.example.org/accounts/?page=2",
  "results": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "displayName": "回應字串"
    }
  ]
}
```

取得特定工具的執行紀錄列表

`GET` `/api/v1/tools/{toolPk}/tool-execution-records/`

參數

參數名稱	必填	類型	說明
`toolPk`	V	string	
`chatbot`	X	string	通過 AI 助理 ID 過濾

`endDate`	X	string	結束日期（包含當日），格式：YYYY-MM-DD
`page`	X	integer	A page number within the paginated result set.
`pageSize`	X	integer	Number of results to return per page.
`query`	X	string	搜尋 AI 助理名稱、工具名稱、訊息內容
`startDate`	X	string	開始日期（包含當日），格式：YYYY-MM-DD
`status`	X	string	通過執行狀態過濾：success, failure, pending, timeout
`tool`	X	string	通過工具 ID 過濾
`toolType`	X	string	通過工具類型過濾：api, function, mcp

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/tools/550e8400-e29b-41d4-
a716-446655440000/tool-execution-records/?
chatbot=example&endDate=example&page=1&pageSize=1&query=example&startD
ate=example&status=failure&tool=example&toolType=api"

  -H "Authorization: Api-Key YOUR_API_KEY"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/tools/550e8400-e29b-41d4-
a716-446655440000/tool-execution-records/?
chatbot=example&endDate=example&page=1&pageSize=1&query=example&startD
ate=example&status=failure&tool=example&toolType=api", config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/tools/550e8400-e29b-41d4-a716-446655440000/tool-execution-records/?chatbot=example&endDate=example&page=1&pageSize=1&query=example&startDate=example&status=failure&tool=example&toolType=api"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/tools/550e8400-e29b-41d4-a716-
446655440000/tool-execution-records/?
chatbot=example&endDate=example&page=1&pageSize=1&query=example&startD
ate=example&status=failure&tool=example&toolType=api", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
{
  "count": integer
```

```
  "next"?: string (uri) // 非必填
  "previous"?: string (uri) // 非必填
  "results": [
    {
      "id": string (uuid)
      "tool": object // 獲取工具資訊
      "chatbot": object // 獲取 AI 助理資訊
      "messageContent": string // 獲取訊息內容
      "status"?: string (enum: success, failure, pending, timeout) // *
`success` - Success
* `failure` - Failed
* `pending` - Processing
* `timeout` - Timeout (非必填)
      "executionTime": integer // 獲取執行時間（毫秒）
      "errorMessage"?: string // 非必填
      "retryCount"?: integer // How many times the platform auto-retried
this tool call before the final outcome (0 = the first attempt was the
final one). API tools count tenacity retries inside APIRequestService; MCP
tools count transient-error retries (read-classified tools only). Function
tools are never auto-retried. (非必填)
      "createdAt": string (timestamp)
      "source": string // Scheduled runs' tool calls are attributed via
ChatbotScheduleExecution.user_message.
    }
  ]
}
```

回應範例值

```
{
  "count": 123,
  "next": "http://api.example.org/accounts/?page=4",
  "previous": "http://api.example.org/accounts/?page=2",
  "results": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "tool": {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "name": "回應範例名稱",
        "description": "回應範例描述"
      },
      "chatbot": {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "name": "回應範例名稱",
```

```
        "description": "回應範例描述"
      },
      "messageContent": "回應字串",
      "status": "success",
      "executionTime": 456,
      "errorMessage": "回應字串",
      "retryCount": 456,
      "createdAt": "回應字串",
      "source": "回應字串"
    }
  ]
}
```


取得特定工具的特定執行紀錄

GET `/api/v1/tools/{toolPk}/tool-execution-records/{id}`

參數

參數名稱	必填	類型	說明
`id`	V	string	A UUID string identifying this Tool Execution Record.
`toolPk`	V	string	

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/tools/550e8400-e29b-41d4-
a716-446655440000/tool-execution-records/550e8400-e29b-41d4-a716-
446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/tools/550e8400-e29b-41d4-a716-446655440000/tool-execution-records/550e8400-e29b-41d4-a716-446655440000/", config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/tools/550e8400-e29b-41d4-a716-446655440000/tool-execution-records/550e8400-e29b-41d4-a716-446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/tools/550e8400-e29b-41d4-a716-
446655440000/tool-execution-records/550e8400-e29b-41d4-a716-
446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
{
  "id": string (uuid)
  "tool": object // 獲取工具資訊，並包含 operated_tool_name
```

```
  "chatbot": object // 獲取 AI 助理資訊
  "message":
  {
    "id": string (uuid)
    "content": string
  }
  "inputParameters": object
  "outputResult"?: object // 非必填
  "errorMessage"?: string // 非必填
  "status"?: string (enum: success, failure, pending, timeout) // *
`success` - Success
* `failure` - Failed
* `pending` - Processing
* `timeout` - Timeout (非必填)
  "executionTime": integer // 獲取執行時間（毫秒）
  "retryCount"?: integer // How many times the platform auto-retried this
tool call before the final outcome (0 = the first attempt was the final
one). API tools count tenacity retries inside APIRequestService; MCP tools
count transient-error retries (read-classified tools only). Function tools
are never auto-retried. (非必填)
  "requestUrl"?: // 可能有不同的類型 (非必填)
  string (uri) // Final rendered URL used when calling an API tool. Null
for non-API tools. (非必填)
  "requestMethod"?: string // HTTP method (GET/POST/...) used when calling
an API tool. Null for non-API tools. (非必填)
  "requestHeaders": object // Return rendered request headers with
sensitive values masked.

Three sources are unioned, any hit masks:
``settings.TOOL_API_SENSITIVE_HEADERS``,
APICredential keys for the (contact, tool) pair, and the tool's current
``sensitive_headers``. The tool list is applied at read time against the
stored
value, so editing it changes how existing records render without rewriting
them.
  "requestBody"?: object // Final rendered body sent to the external API.
Null for non-API tools or read-only methods. (非必填)
  "createdAt": string (timestamp)
  "updatedAt": string (timestamp)
  "source": string // Scheduled runs' tool calls are attributed via
ChatbotScheduleExecution.user_message.
}
```

回應範例值

```
```

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "tool": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應範例名稱",
    "description": "回應範例描述"
  },
  "chatbot": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應範例名稱",
    "description": "回應範例描述"
  },
  "message": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "content": "回應字串"
  },
  "inputParameters": null,
  "outputResult": null,
  "errorMessage": "回應字串",
  "status": "success",
  "executionTime": 456,
  "retryCount": 456,
  "requestUrl": "https://example.com/file.jpg",
  "requestMethod": "回應字串",
  "requestHeaders": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應範例名稱",
    "description": "回應範例描述"
  },
  "requestBody": null,
  "createdAt": "回應字串",
  "updatedAt": "回應字串",
  "source": "回應字串"
}
```


取得特定工具執行紀錄的 AI 助理過濾選項

GET `/api/v1/tools/{toolPk}/tool-execution-records/chatbots/`

參數

參數名稱	必填	類型	說明
`toolPk`	V	string	
`chatbot`	X	string	
`endDate`	X	string	
`query`	X	string	
`startDate`	X	string	
`status`	X	string	`success`: Success ; `failure`: Failed ; `pending`: Processing ; `timeout`: Timeout;
`tool`	X	string	
`toolType`	X	string	`api`: API ; `function`: Function ; `mcp`: MCP ; `desktop`: Desktop ; `flex`: Flex Message ; `quick_reply`: Quick Reply ; `quick_menu`: Quick Menu;

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/tools/550e8400-e29b-41d4-a716-446655440000/tool-execution-records/chatbots/?chatbot=550e8400-e29b-41d4-a716-446655440000&endDate=example&query=example&startDate=example&status=failure&tool=550e8400-e29b-41d4-a716-446655440000&toolType=api"

  -H "Authorization: Api-Key YOUR_API_KEY"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/tools/550e8400-e29b-41d4-a716-446655440000/tool-execution-records/chatbots/?chatbot=550e8400-e29b-41d4-a716-446655440000&endDate=example&query=example&startDate=example&status=failure&tool=550e8400-e29b-41d4-a716-446655440000&toolType=api", config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/tools/550e8400-e29b-41d4-a716-446655440000/tool-execution-records/chatbots/?chatbot=550e8400-e29b-41d4-a716-446655440000&endDate=example&query=example&startDate=example&status=failure&tool=550e8400-e29b-41d4-a716-446655440000&toolType=api"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/tools/550e8400-e29b-41d4-a716-
446655440000/tool-execution-records/chatbots/?chatbot=550e8400-e29b-
41d4-a716-
446655440000&endDate=example&query=example&startDate=example&status=fa
ilure&tool=550e8400-e29b-41d4-a716-446655440000&toolType=api", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
[
  {
    "id": string (uuid)
    "name": string // Chatbot name. In Agent mode it carries semantic
meaning; in other modes it only distinguishes chatbots.
    "team":
    {
      "id": string (uuid)
      "name": string
    }
  }
]
```

回應範例值

```
[
  {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應字串",
    "team": {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "回應字串"
    }
  }
]
```

取得特定工具執行紀錄的工具過濾選項

GET `/api/v1/tools/{toolPk}/tool-execution-records/tools/`

參數

參數名稱	必填	類型	說明

`toolPk`	V	string	
`chatbot`	X	string	
`endDate`	X	string	
`page`	X	integer	A page number within the paginated result set.
`pageSize`	X	integer	Number of results to return per page.
`query`	X	string	
`startDate`	X	string	
`status`	X	string	`success`: Success ; `failure`: Failed ; `pending`: Processing ; `timeout`: Timeout;
`tool`	X	string	
`toolType`	X	string	`api`: API ; `function`: Function ; `mcp`: MCP ; `desktop`: Desktop ; `flex`: Flex Message ; `quick_reply`: Quick Reply ; `quick_menu`: Quick Menu;

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/tools/550e8400-e29b-41d4-a716-446655440000/tool-execution-records/tools/?chatbot=550e8400-e29b-41d4-a716-446655440000&endDate=example&page=1&pageSize=1&query=example&startDate=example&status=failure&tool=550e8400-e29b-41d4-a716-446655440000&toolType=api"

  -H "Authorization: Api-Key YOUR_API_KEY"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/tools/550e8400-e29b-41d4-
a716-446655440000/tool-execution-records/tools/?chatbot=550e8400-e29b-
41d4-a716-
446655440000&endDate=example&page=1&pageSize=1&query=example&startDate
=example&status=failure&tool=550e8400-e29b-41d4-a716-
446655440000&toolType=api", config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/tools/550e8400-e29b-41d4-a716-446655440000/tool-execution-records/tools/?chatbot=550e8400-e29b-41d4-a716-446655440000&endDate=example&page=1&pageSize=1&query=example&startDate=example&status=failure&tool=550e8400-e29b-41d4-a716-446655440000&toolType=api"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/tools/550e8400-e29b-41d4-a716-
446655440000/tool-execution-records/tools/?chatbot=550e8400-e29b-41d4-
a716-
446655440000&endDate=example&page=1&pageSize=1&query=example&startDate
=example&status=failure&tool=550e8400-e29b-41d4-a716-
446655440000&toolType=api", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
{
  "count": integer
  "next"?: string (uri) // 非必填
  "previous"?: string (uri) // 非必填
  "results": [
    {
      "id": string (uuid)
      "displayName": string
    }
  ]
}
```

回應範例值

```
{
  "count": 123,
  "next": "http://api.example.org/accounts/?page=4",
  "previous": "http://api.example.org/accounts/?page=2",
  "results": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "displayName": "回應字串"
    }
  ]
}
```

呼叫 API 示例 (Shell)

目錄

1. 上傳技能
2. 建立技能
3. 列出技能
4. 取得特定技能
5. 更新技能
6. 部分更新技能
7. 刪除技能
8. 匯出技能
9. 瀏覽技能包目錄結構
10. 重新上傳技能
11. 列出技能資源
12. 上傳技能資源
13. 刪除技能資源
14. 下載技能資源

呼叫 API 示例 (Shell)

上傳技能

`POST` `/api/v1/skills/upload/`

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X POST "https://api.maiagent.ai/api/v1/skills/upload/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -F "file=@example_file.pdf"

  -F "attached_tool_ids=範例字串"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');
const FormData = require('form-data');

// 建立FormData對象
const formData = new FormData();
// 請用實際檔案替換
formData.append('file',
* 實際檔案物件 *
, 'example_file.pdf');
formData.append('attached_tool_ids', '範例字串');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    ...formData.getHeaders()
  }
};

axios.post("https://api.maiagent.ai/api/v1/skills/upload/",
formData, config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/skills/upload/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}

# 建立檔案和表單資料
files = {
    'file': ('example_file.pdf', open('example_file.pdf', 'rb'),
'application/pdf'),
    'attached_tool_ids': (None, '範例字串')
}

response = requests.post(url, files=files, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>post("https://api.maiagent.ai/api/v1/skills/upload/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ],
        'multipart' => [
            [
                'name' => 'file',
                'contents' => fopen('example_file.pdf', 'r'),
                'filename' => 'example_file.pdf'
            ],
            [
                'name' => 'attached_tool_ids',
                'contents' => '範例字串'
            ]
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 201

回應結構範例

```
{
  "id"?: string (uuid) // 非必填
  "name"?: string // 非必填
  "description"?: string // 非必填
  "attached_tools"?: [ // 已依技能包 frontmatter 自動綁定的工具名稱 (非必填)
    string
  ]
  "missing_tools"?: [ // 技能包宣告但本組織查無同名工具、需手動補綁的工具名稱 (非必填)
    string
  ]
  "message"?: string // 非必填
}
```

回應範例值

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "name": "回應字串",
  "description": "回應字串",
  "attached_tools": [
    "回應字串"
  ],
  "missing_tools": [
    "回應字串"
  ],
  "message": "回應字串"
}
```

狀態碼: 400

回應結構範例

```
{
  "detail"?: string // 錯誤訊息 (非必填)
}
```

回應範例值

```
{
  "detail": "回應字串"
}
```

建立技能

POST `/api/v1/skills/`

請求內容

請求參數

欄位	類型	必填	說明
name	string	是	
description	string	是	
whenToUse	string	否	Describe when the LLM should trigger this skill. Max 200 characters recommended.
instructions	string	否	Markdown text with instructions for the skill
attachedToolIds	array[string]	否	
groups	array[IdName]	否	Groups this skill is assigned to. Non-owner members must pick at least one group they belong to.

欄位	類型	必填	說明
files	array[object]	否	Optional resource files to create with the skill. Each item must include path and content. content_encoding may be "text" or "base64".

請求結構範例

```
{
  "name": string
  "description": string
  "whenToUse"?: string // Describe when the LLM should trigger this skill. Max 200 characters recommended. (非必填)
  "instructions"?: string // Markdown text with instructions for the skill (非必填)
  "attachedToolIds"?: [ // 非必填
    string (uuid)
  ]
  "groups"?: [ // Groups this skill is assigned to. Non-owner members must pick at least one group they belong to. (非必填)
    {
      "id": string (uuid)
    }
  ]
  "files"?: [ // Optional resource files to create with the skill. Each item must include path and content. content_encoding may be "text" or "base64". (非必填)
    object
  ]
}
```

請求範例值

```
{
  "name": "範例名稱",
  "description": "範例字串",
  "whenToUse": "範例字串",
  "instructions": "範例字串",
  "attachedToolIds": [
    "550e8400-e29b-41d4-a716-446655440000"
  ],
  "groups": [
```

```
    {
      "id": "550e8400-e29b-41d4-a716-446655440000"
    }
  ],
  "files": [
    {}
  ]
}
```

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X POST "https://api.maiagent.ai/api/v1/skills/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "name": "範例名稱",
    "description": "範例字串",
    "whenToUse": "範例字串",
    "instructions": "範例字串",
    "attachedToolIds": [
      "550e8400-e29b-41d4-a716-446655440000"
    ],
    "groups": [
      {
        "id": "550e8400-e29b-41d4-a716-446655440000"
      }
    ],
    "files": [
      {}
    ]
  }'

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// 請求內容 (payload)
const data = {
    "name": "範例名稱",
    "description": "範例字串",
    "whenToUse": "範例字串",
    "instructions": "範例字串",
    "attachedToolIds": [
      "550e8400-e29b-41d4-a716-446655440000"
    ],
    "groups": [
      {
        "id": "550e8400-e29b-41d4-a716-446655440000"
      }
    ],
    "files": [
      {}
    ]
  };

axios.post("https://api.maiagent.ai/api/v1/skills/", data, config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/skills/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# 請求內容 (payload)
data = {
    "name": "範例名稱",
    "description": "範例字串",
    "whenToUse": "範例字串",
    "instructions": "範例字串",
    "attachedToolIds": [
        "550e8400-e29b-41d4-a716-446655440000"
    ],
    "groups": [
        {
            "id": "550e8400-e29b-41d4-a716-446655440000"
        }
    ],
    "files": [
        {}
    ]
}

response = requests.post(url, json=data, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>post("https://api.maiagent.ai/api/v1/skills/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'name' => '範例名稱',
            'description' => '範例字串',
            'whenToUse' => '範例字串',
            'instructions' => '範例字串',
            'attachedToolIds' => [
                '550e8400-e29b-41d4-a716-446655440000'
            ],
            'groups' => [
                [
                    'id' => '550e8400-e29b-41d4-a716-446655440000'
                ]
            ],
            'files' => [
                new \stdClass()
            ]
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 201

回應結構範例

```
{
  "id": string (uuid)
  "name": string
  "description": string
  "whenToUse": string // Describe when the LLM should trigger this skill.
Max 200 characters recommended.
  "instructions": string // Markdown text with instructions for the skill
  "compatibility": string // Optional environment requirements from the
Agent Skills Spec frontmatter (max 500 chars).
  "metadata": object // Optional arbitrary key-value mapping from the
Agent Skills Spec frontmatter.
  "allowedTools": object // Optional pre-approved tool list from the
Agent Skills Spec frontmatter (experimental).
  "source":  // How the skill was created: upload (.skill/.zip) or manual

* `upload` - Upload
* `manual` - Manual
  {
  }
  "skillPackagePath": string // S3 path for the uploaded .skill/.zip file
  "skillPackageName": string // Original filename of the uploaded skill
package
  "skillPackageSize": integer // Size of the uploaded skill package in
bytes
  "skillPackageUploadedAt": string (timestamp)
  "attachedTools": [
    {
      "id": string (uuid)
      "name": string
      "description": string
      "displayName": string
```

```
      "toolType": string
    }
  ]
  "resources": [
    {
      "id": string (uuid)
      "path": string // Relative path within the skill directory, e.g.
scripts/helper.py
      "filePath": string // S3 path:
skills/{organization_id}/{skill_id}/resources/
      "fileSize": integer // File size in bytes
      "mimeType": string
      "createdAt": string (timestamp)
    }
  ]
  "groups": [
    {
      "id": string (uuid)
      "name": string
    }
  ]
  "createdAt": string (timestamp)
  "updatedAt": string (timestamp)
  "lastUsedAt": string (timestamp)
  "canUpdate": boolean // Return whether the current user can update this
resource.
  "canDelete": boolean // Return whether the current user can delete this
resource.
}
```

回應範例值

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "name": "回應字串",
  "description": "回應字串",
  "whenToUse": "回應字串",
  "instructions": "回應字串",
  "compatibility": "回應字串",
  "metadata": null,
  "allowedTools": null,
  "source": {},
  "skillPackagePath": "回應字串",
  "skillPackageName": "回應字串",
```

```
  "skillPackageSize": 456,
  "skillPackageUploadedAt": "回應字串",
  "attachedTools": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "回應字串",
      "description": "回應字串",
      "displayName": "回應字串",
      "toolType": "回應字串"
    }
  ],
  "resources": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "path": "回應字串",
      "filePath": "回應字串",
      "fileSize": 456,
      "mimeType": "回應字串",
      "createdAt": "回應字串"
    }
  ],
  "groups": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "回應字串"
    }
  ],
  "createdAt": "回應字串",
  "updatedAt": "回應字串",
  "lastUsedAt": "回應字串",
  "canUpdate": false,
  "canDelete": false
}
```


列出技能

GET `/api/v1/skills/`

參數

參數名稱	必填	類型	說明
`isActive`	X	boolean	
`page`	X	integer	A page number within the paginated result set.
`pageSize`	X	integer	Number of results to return per page.
`search`	X	string	

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/skills/?
isActive=true&page=1&pageSize=1&search=example"

  -H "Authorization: Api-Key YOUR_API_KEY"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/skills/?
isActive=true&page=1&pageSize=1&search=example", config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/skills/?
isActive=true&page=1&pageSize=1&search=example"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/skills/?
isActive=true&page=1&pageSize=1&search=example", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
{
  "count": integer
  "next"?: string (uri) // 非必填
```

```
  "previous"?: string (uri) // 非必填
  "results": [
    {
      "id": string (uuid)
      "name": string
      "description": string
      "whenToUse": string // Describe when the LLM should trigger this
skill. Max 200 characters recommended.
      "source":  // How the skill was created: upload (.skill/.zip) or
manual

* `upload` - Upload
* `manual` - Manual
      {
      }
      "attachedTools": [
        {
          "id": string (uuid)
          "name": string
          "description": string
          "displayName": string
          "toolType": string
        }
      ]
      "groups": [
        {
          "id": string (uuid)
          "name": string
        }
      ]
      "createdBy": object // Show 'System' as the creator for global
skills (uploaded by platform staff).
      "createdAt": string (timestamp)
      "updatedAt": string (timestamp)
      "lastUsedAt": string (timestamp)
      "canUpdate": boolean // Return whether the current user can update
this resource.
      "canDelete": boolean // Return whether the current user can delete
this resource.
    }
  ]
}
```

回應範例值

```
{
  "count": 123,
  "next": "http://api.example.org/accounts/?page=4",
  "previous": "http://api.example.org/accounts/?page=2",
  "results": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "回應字串",
      "description": "回應字串",
      "whenToUse": "回應字串",
      "source": {},
      "attachedTools": [
        {
          "id": "550e8400-e29b-41d4-a716-446655440000",
          "name": "回應字串",
          "description": "回應字串",
          "displayName": "回應字串",
          "toolType": "回應字串"
        }
      ],
      "groups": [
        {
          "id": "550e8400-e29b-41d4-a716-446655440000",
          "name": "回應字串"
        }
      ],
      "createdBy": {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "name": "回應範例名稱",
        "description": "回應範例描述"
      },
      "createdAt": "回應字串",
      "updatedAt": "回應字串",
      "lastUsedAt": "回應字串",
      "canUpdate": false,
      "canDelete": false
    }
  ]
}
```

取得特定技能

GET `/api/v1/skills/{id}`

參數

參數名稱	必填	類型	說明
id	V	string	A UUID string identifying this Skill.

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/skills/550e8400-e29b-
41d4-a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/skills/550e8400-e29b-41d4-
a716-446655440000/", config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/skills/550e8400-e29b-41d4-
a716-446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/skills/550e8400-e29b-41d4-a716-
446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
{
  "id": string (uuid)
  "name": string
```

```
  "description": string
  "whenToUse": string // Describe when the LLM should trigger this skill.
Max 200 characters recommended.
  "instructions": string // Markdown text with instructions for the skill
  "compatibility": string // Optional environment requirements from the
Agent Skills Spec frontmatter (max 500 chars).
  "metadata": object // Optional arbitrary key-value mapping from the
Agent Skills Spec frontmatter.
  "allowedTools": object // Optional pre-approved tool list from the
Agent Skills Spec frontmatter (experimental).
  "source":  // How the skill was created: upload (.skill/.zip) or manual

* `upload` - Upload
* `manual` - Manual
  {
  }
  "skillPackagePath": string // S3 path for the uploaded .skill/.zip file
  "skillPackageName": string // Original filename of the uploaded skill
package
  "skillPackageSize": integer // Size of the uploaded skill package in
bytes
  "skillPackageUploadedAt": string (timestamp)
  "attachedTools": [
    {
      "id": string (uuid)
      "name": string
      "description": string
      "displayName": string
      "toolType": string
    }
  ]
  "resources": [
    {
      "id": string (uuid)
      "path": string // Relative path within the skill directory, e.g.
scripts/helper.py
      "filePath": string // S3 path:
skills/{organization_id}/{skill_id}/resources/
      "fileSize": integer // File size in bytes
      "mimeType": string
      "createdAt": string (timestamp)
    }
  ]
  "groups": [
    {
```

```
      "id": string (uuid)
      "name": string
    }
  ]
  "createdAt": string (timestamp)
  "updatedAt": string (timestamp)
  "lastUsedAt": string (timestamp)
  "canUpdate": boolean // Return whether the current user can update this
resource.
  "canDelete": boolean // Return whether the current user can delete this
resource.
}
```

回應範例值

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "name": "回應字串",
  "description": "回應字串",
  "whenToUse": "回應字串",
  "instructions": "回應字串",
  "compatibility": "回應字串",
  "metadata": null,
  "allowedTools": null,
  "source": {},
  "skillPackagePath": "回應字串",
  "skillPackageName": "回應字串",
  "skillPackageSize": 456,
  "skillPackageUploadedAt": "回應字串",
  "attachedTools": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "回應字串",
      "description": "回應字串",
      "displayName": "回應字串",
      "toolType": "回應字串"
    }
  ],
  "resources": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "path": "回應字串",
      "filePath": "回應字串",
      "fileSize": 456,
```

```
      "mimeType": "回應字串",
      "createdAt": "回應字串"
    }
  ],
  "groups": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "回應字串"
    }
  ],
  "createdAt": "回應字串",
  "updatedAt": "回應字串",
  "lastUsedAt": "回應字串",
  "canUpdate": false,
  "canDelete": false
}
```


更新技能

PUT `/api/v1/skills/{id}`

參數

參數名稱	必填	類型	說明
id	V	string	A UUID string identifying this Skill.

請求內容

請求參數

欄位	類型	必填	說明
name	string	是	
description	string	是	
whenToUse	string	否	Describe when the LLM should trigger this skill. Max 200 characters recommended.
instructions	string	否	Markdown text with instructions for the skill
attachedToolIds	array[string]	否	
groups	array[IdName]	否	Groups this skill is assigned to. Non-owner members must pick at least one group they belong to.

請求結構範例

```
{
  "name": string
  "description": string
  "whenToUse"?: string // Describe when the LLM should trigger this
skill. Max 200 characters recommended. (非必填)
  "instructions"?: string // Markdown text with instructions for the
skill (非必填)
  "attachedToolIds"?: [ // 非必填
    string (uuid)
  ]
  "groups"?: [ // Groups this skill is assigned to. Non-owner members
must pick at least one group they belong to. (非必填)
    {
      "id": string (uuid)
    }
  ]
}
```

請求範例值

```
{
  "name": "範例名稱",
  "description": "範例字串",
  "whenToUse": "範例字串",
```

```
  "instructions": "範例字串",
  "attachedToolIds": [
    "550e8400-e29b-41d4-a716-446655440000"
  ],
  "groups": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000"
    }
  ]
}
```

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X PUT "https://api.maiagent.ai/api/v1/skills/550e8400-e29b-
41d4-a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "name": "範例名稱",
    "description": "範例字串",
    "whenToUse": "範例字串",
    "instructions": "範例字串",
    "attachedToolIds": [
      "550e8400-e29b-41d4-a716-446655440000"
    ],
    "groups": [
      {
        "id": "550e8400-e29b-41d4-a716-446655440000"
      }
    ]
  }'

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// 請求內容 (payload)
const data = {
    "name": "範例名稱",
    "description": "範例字串",
    "whenToUse": "範例字串",
    "instructions": "範例字串",
    "attachedToolIds": [
      "550e8400-e29b-41d4-a716-446655440000"
    ],
    "groups": [
      {
        "id": "550e8400-e29b-41d4-a716-446655440000"
      }
    ]
  };

axios.put("https://api.maiagent.ai/api/v1/skills/550e8400-e29b-41d4-
a716-446655440000/", data, config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/skills/550e8400-e29b-41d4-
a716-446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# 請求內容 (payload)
data = {
    "name": "範例名稱",
    "description": "範例字串",
    "whenToUse": "範例字串",
    "instructions": "範例字串",
    "attachedToolIds": [
        "550e8400-e29b-41d4-a716-446655440000"
    ],
    "groups": [
        {
            "id": "550e8400-e29b-41d4-a716-446655440000"
        }
    ]
}

response = requests.put(url, json=data, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>put("https://api.maiagent.ai/api/v1/skills/550e8400-e29b-41d4-a716-
446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'name' => '範例名稱',
            'description' => '範例字串',
            'whenToUse' => '範例字串',
            'instructions' => '範例字串',
            'attachedToolIds' => [
                '550e8400-e29b-41d4-a716-446655440000'
            ],
            'groups' => [
                [
                    'id' => '550e8400-e29b-41d4-a716-446655440000'
                ]
            ]
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
{
  "id": string (uuid)
  "name": string
  "description": string
  "whenToUse": string // Describe when the LLM should trigger this skill.
Max 200 characters recommended.
  "instructions": string // Markdown text with instructions for the skill
  "compatibility": string // Optional environment requirements from the
Agent Skills Spec frontmatter (max 500 chars).
  "metadata": object // Optional arbitrary key-value mapping from the
Agent Skills Spec frontmatter.
  "allowedTools": object // Optional pre-approved tool list from the
Agent Skills Spec frontmatter (experimental).
  "source":  // How the skill was created: upload (.skill/.zip) or manual

* `upload` - Upload
* `manual` - Manual
  {
  }
  "skillPackagePath": string // S3 path for the uploaded .skill/.zip file
  "skillPackageName": string // Original filename of the uploaded skill
package
  "skillPackageSize": integer // Size of the uploaded skill package in
bytes
  "skillPackageUploadedAt": string (timestamp)
  "attachedTools": [
    {
      "id": string (uuid)
      "name": string
      "description": string
      "displayName": string
      "toolType": string
    }
  ]
  "resources": [
```

```
    {
      "id": string (uuid)
      "path": string // Relative path within the skill directory, e.g.
scripts/helper.py
      "filePath": string // S3 path:
skills/{organization_id}/{skill_id}/resources/
      "fileSize": integer // File size in bytes
      "mimeType": string
      "createdAt": string (timestamp)
    }
  ]
  "groups": [
    {
      "id": string (uuid)
      "name": string
    }
  ]
  "createdAt": string (timestamp)
  "updatedAt": string (timestamp)
  "lastUsedAt": string (timestamp)
  "canUpdate": boolean // Return whether the current user can update this
resource.
  "canDelete": boolean // Return whether the current user can delete this
resource.
}
```

回應範例值

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "name": "回應字串",
  "description": "回應字串",
  "whenToUse": "回應字串",
  "instructions": "回應字串",
  "compatibility": "回應字串",
  "metadata": null,
  "allowedTools": null,
  "source": {},
  "skillPackagePath": "回應字串",
  "skillPackageName": "回應字串",
  "skillPackageSize": 456,
  "skillPackageUploadedAt": "回應字串",
  "attachedTools": [
    {
```

```
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "回應字串",
      "description": "回應字串",
      "displayName": "回應字串",
      "toolType": "回應字串"
    }
  ],
  "resources": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "path": "回應字串",
      "filePath": "回應字串",
      "fileSize": 456,
      "mimeType": "回應字串",
      "createdAt": "回應字串"
    }
  ],
  "groups": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "回應字串"
    }
  ],
  "createdAt": "回應字串",
  "updatedAt": "回應字串",
  "lastUsedAt": "回應字串",
  "canUpdate": false,
  "canDelete": false
}
```


部分更新技能

`PATCH` `/api/v1/skills/{id}`

參數

參數名稱	必填	類型	說明
`id`	V	string	A UUID string identifying this Skill.

請求內容

請求參數

欄位	類型	必填	說明
name	string	否	
description	string	否	
whenToUse	string	否	Describe when the LLM should trigger this skill. Max 200 characters recommended.
instructions	string	否	Markdown text with instructions for the skill
attachedToolIds	array[string]	否	
groups	array[IdName]	否	Groups this skill is assigned to. Non-owner members must pick at least one group they belong to.

請求結構範例

```
{
  "name"?: string // 非必填
  "description"?: string // 非必填
  "whenToUse"?: string // Describe when the LLM should trigger this
skill. Max 200 characters recommended. (非必填)
  "instructions"?: string // Markdown text with instructions for the
skill (非必填)
  "attachedToolIds"?: [ // 非必填
    string (uuid)
  ]
  "groups"?: [ // Groups this skill is assigned to. Non-owner members
must pick at least one group they belong to. (非必填)
    {
      "id": string (uuid)
```

```
    }
  ]
}
```

請求範例值

```
{
  "name": "範例名稱",
  "description": "範例字串",
  "whenToUse": "範例字串",
  "instructions": "範例字串",
  "attachedToolIds": [
    "550e8400-e29b-41d4-a716-446655440000"
  ],
  "groups": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000"
    }
  ]
}
```

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X PATCH "https://api.maiagent.ai/api/v1/skills/550e8400-e29b-
41d4-a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "name": "範例名稱",
    "description": "範例字串",
    "whenToUse": "範例字串",
    "instructions": "範例字串",
    "attachedToolIds": [
      "550e8400-e29b-41d4-a716-446655440000"
    ],
    "groups": [
      {
        "id": "550e8400-e29b-41d4-a716-446655440000"
      }
    ]
  }'

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// 請求內容 (payload)
const data = {
    "name": "範例名稱",
    "description": "範例字串",
    "whenToUse": "範例字串",
    "instructions": "範例字串",
    "attachedToolIds": [
      "550e8400-e29b-41d4-a716-446655440000"
    ],
    "groups": [
      {
        "id": "550e8400-e29b-41d4-a716-446655440000"
      }
    ]
  };

axios.patch("https://api.maiagent.ai/api/v1/skills/550e8400-e29b-
41d4-a716-446655440000/", data, config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/skills/550e8400-e29b-41d4-
a716-446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# 請求內容 (payload)
data = {
    "name": "範例名稱",
    "description": "範例字串",
    "whenToUse": "範例字串",
    "instructions": "範例字串",
    "attachedToolIds": [
        "550e8400-e29b-41d4-a716-446655440000"
    ],
    "groups": [
        {
            "id": "550e8400-e29b-41d4-a716-446655440000"
        }
    ]
}

response = requests.patch(url, json=data, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>patch("https://api.maiagent.ai/api/v1/skills/550e8400-e29b-41d4-
a716-446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'name' => '範例名稱',
            'description' => '範例字串',
            'whenToUse' => '範例字串',
            'instructions' => '範例字串',
            'attachedToolIds' => [
                '550e8400-e29b-41d4-a716-446655440000'
            ],
            'groups' => [
                [
                    'id' => '550e8400-e29b-41d4-a716-446655440000'
                ]
            ]
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
{
  "id": string (uuid)
  "name": string
  "description": string
  "whenToUse": string // Describe when the LLM should trigger this skill.
Max 200 characters recommended.
  "instructions": string // Markdown text with instructions for the skill
  "compatibility": string // Optional environment requirements from the
Agent Skills Spec frontmatter (max 500 chars).
  "metadata": object // Optional arbitrary key-value mapping from the
Agent Skills Spec frontmatter.
  "allowedTools": object // Optional pre-approved tool list from the
Agent Skills Spec frontmatter (experimental).
  "source":  // How the skill was created: upload (.skill/.zip) or manual

* `upload` - Upload
* `manual` - Manual
  {
  }
  "skillPackagePath": string // S3 path for the uploaded .skill/.zip file
  "skillPackageName": string // Original filename of the uploaded skill
package
  "skillPackageSize": integer // Size of the uploaded skill package in
bytes
  "skillPackageUploadedAt": string (timestamp)
  "attachedTools": [
    {
      "id": string (uuid)
      "name": string
      "description": string
      "displayName": string
      "toolType": string
    }
  ]
  "resources": [
```

```
    {
      "id": string (uuid)
      "path": string // Relative path within the skill directory, e.g.
scripts/helper.py
      "filePath": string // S3 path:
skills/{organization_id}/{skill_id}/resources/
      "fileSize": integer // File size in bytes
      "mimeType": string
      "createdAt": string (timestamp)
    }
  ]
  "groups": [
    {
      "id": string (uuid)
      "name": string
    }
  ]
  "createdAt": string (timestamp)
  "updatedAt": string (timestamp)
  "lastUsedAt": string (timestamp)
  "canUpdate": boolean // Return whether the current user can update this
resource.
  "canDelete": boolean // Return whether the current user can delete this
resource.
}
```

回應範例值

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "name": "回應字串",
  "description": "回應字串",
  "whenToUse": "回應字串",
  "instructions": "回應字串",
  "compatibility": "回應字串",
  "metadata": null,
  "allowedTools": null,
  "source": {},
  "skillPackagePath": "回應字串",
  "skillPackageName": "回應字串",
  "skillPackageSize": 456,
  "skillPackageUploadedAt": "回應字串",
  "attachedTools": [
    {
```

```
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "回應字串",
      "description": "回應字串",
      "displayName": "回應字串",
      "toolType": "回應字串"
    }
  ],
  "resources": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "path": "回應字串",
      "filePath": "回應字串",
      "fileSize": 456,
      "mimeType": "回應字串",
      "createdAt": "回應字串"
    }
  ],
  "groups": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "回應字串"
    }
  ],
  "createdAt": "回應字串",
  "updatedAt": "回應字串",
  "lastUsedAt": "回應字串",
  "canUpdate": false,
  "canDelete": false
}
```


刪除技能

`DELETE` `/api/v1/skills/{id}`

參數

參數名稱	必填	類型	說明
`id`	V	string	A UUID string identifying this Skill.

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X DELETE "https://api.maiagent.ai/api/v1/skills/550e8400-e29b-
41d4-a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

// 請求內容 (payload)
const data = null;

axios.delete("https://api.maiagent.ai/api/v1/skills/550e8400-e29b-
41d4-a716-446655440000/", data, config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/skills/550e8400-e29b-41d4-
a716-446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.delete(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>delete("https://api.maiagent.ai/api/v1/skills/550e8400-e29b-41d4-
a716-446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼	說明
204	No response body

匯出技能

`GET` `/api/v1/skills/{id}/export/`

參數

參數名稱	必填	類型	說明
`id`	V	string	A UUID string identifying this Skill.

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/skills/550e8400-e29b-
41d4-a716-446655440000/export/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/skills/550e8400-e29b-41d4-a716-446655440000/export/", config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/skills/550e8400-e29b-41d4-
a716-446655440000/export/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/skills/550e8400-e29b-41d4-a716-
446655440000/export/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼	說明
200	.skill 檔案下載

瀏覽技能包目錄結構

`GET` `/api/v1/skills/{id}/package-structure/`

參數

參數名稱	必填	類型	說明
`id`	V	string	A UUID string identifying this Skill.
`path`	X	string	要瀏覽的目錄路徑（預設為根目錄）

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/skills/550e8400-e29b-
41d4-a716-446655440000/package-structure/?path=example"

  -H "Authorization: Api-Key YOUR_API_KEY"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/skills/550e8400-e29b-41d4-a716-446655440000/package-structure/?path=example", config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/skills/550e8400-e29b-41d4-
a716-446655440000/package-structure/?path=example"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/skills/550e8400-e29b-41d4-a716-
446655440000/package-structure/?path=example", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
{
  "package_name"?: string // 技能包檔案名稱 (非必填)
  "package_size"?: integer // 技能包大小 (bytes) (非必填)
```

```
  "uploaded_at"?: string (date-time) // 上傳時間 (非必填)
  "current_path"?: string // 目前瀏覽路徑 (非必填)
  "items"?: [ // 目錄內容（資料夾優先，依字母排序） (非必填)
    {
      "name"?: string // 檔案或資料夾名稱 (非必填)
      "type"?: string (enum: file, dir) // 項目類型 (非必填)
      "size"?: integer // 檔案大小（bytes），僅 type=file 時回傳 (非必填)
      "item_count"?: integer // 資料夾內直接子項目數量，僅 type=dir 時回傳 (非必填)
    }
  ]
}
```

回應範例值

```
{
  "package_name": "回應字串",
  "package_size": 456,
  "uploaded_at": "2025-01-01T00:00:00.000Z",
  "current_path": "回應字串",
  "items": [
    {
      "name": "回應字串",
      "type": "file",
      "size": 456,
      "item_count": 456
    }
  ]
}
```

狀態碼: 400

回應結構範例

```
{
  "detail"?: string // 錯誤訊息 (非必填)
}
```

回應範例值

```
{
  "detail": "回應字串"
}
```

重新上傳技能

POST `/api/v1/skills/{id}/reupload/`

參數

參數名稱	必填	類型	說明
id	V	string	A UUID string identifying this Skill.

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X POST "https://api.maiagent.ai/api/v1/skills/550e8400-e29b-
41d4-a716-446655440000/reupload/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -F "file=@example_file.pdf"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');
const FormData = require('form-data');

// 建立FormData對象
const formData = new FormData();
// 請用實際檔案替換
formData.append('file',
* 實際檔案物件 *
, 'example_file.pdf');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    ...formData.getHeaders()
  }
};

axios.post("https://api.maiagent.ai/api/v1/skills/550e8400-e29b-
41d4-a716-446655440000/reupload/", formData, config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/skills/550e8400-e29b-41d4-
a716-446655440000/reupload/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}

# 建立檔案和表單資料
files = {
    'file': ('example_file.pdf', open('example_file.pdf', 'rb'),
'application/pdf')
}

response = requests.post(url, files=files, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>post("https://api.maiagent.ai/api/v1/skills/550e8400-e29b-41d4-
a716-446655440000/reupload/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ],
        'multipart' => [
            [
                'name' => 'file',
                'contents' => fopen('example_file.pdf', 'r'),
                'filename' => 'example_file.pdf'
            ]
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
{
  "id"?: string (uuid) // 非必填
  "name"?: string // 非必填
  "description"?: string // 非必填
  "message"?: string // 非必填
}
```

回應範例值

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "name": "回應字串",
  "description": "回應字串",
  "message": "回應字串"
}
```

狀態碼: 400

回應結構範例

```
{
  "detail"?: string // 錯誤訊息 (非必填)
}
```

回應範例值

```
{
  "detail": "回應字串"
}
```

列出技能資源

GET `/api/v1/skills/{skillPk}/resources/`

參數

參數名稱	必填	類型	說明
`skillPk`	V	string	

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X GET
"https://api.maiagent.ai/api/v1/skills/{skillPk}/resources/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/skills/{skillPk}/resources
/", config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/skills/{skillPk}/resources/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/skills/{skillPk}/resources/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
[
  {
    "id": string (uuid)
    "path": string // Relative path within the skill directory, e.g.
```

```
scripts/helper.py
    "filePath": string // S3 path:
skills/{organization_id}/{skill_id}/resources/
    "fileSize": integer // File size in bytes
    "mimeType": string
    "createdAt": string (timestamp)
  }
]
```

回應範例值

```
[
  {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "path": "回應字串",
    "filePath": "回應字串",
    "fileSize": 456,
    "mimeType": "回應字串",
    "createdAt": "回應字串"
  }
]
```

上傳技能資源

POST `/api/v1/skills/{skillPk}/resources/`

參數

參數名稱	必填	類型	說明
skillPk	V	string	

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X POST
"https://api.maiagent.ai/api/v1/skills/{skillPk}/resources/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -F "file=@example_file.pdf"

  -F "path=範例字串"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');
const FormData = require('form-data');

// 建立FormData對象
const formData = new FormData();
// 請用實際檔案替換
formData.append('file',
* 實際檔案物件 *
, 'example_file.pdf');
formData.append('path', '範例字串');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    ...formData.getHeaders()
  }
};

axios.post("https://api.maiagent.ai/api/v1/skills/{skillPk}/resource
s/", formData, config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/skills/{skillPk}/resources/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}

# 建立檔案和表單資料
files = {
    'file': ('example_file.pdf', open('example_file.pdf', 'rb'),
'application/pdf'),
    'path': (None, '範例字串')
}

response = requests.post(url, files=files, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>post("https://api.maiagent.ai/api/v1/skills/{skillPk}/resources/",
[
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ],
        'multipart' => [
            [
                'name' => 'file',
                'contents' => fopen('example_file.pdf', 'r'),
                'filename' => 'example_file.pdf'
            ],
            [
                'name' => 'path',
                'contents' => '範例字串'
            ]
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 201

回應結構範例

```
{
  "id": string (uuid)
  "path": string // Relative path within the skill directory, e.g.
scripts/helper.py
  "filePath": string // S3 path:
skills/{organization_id}/{skill_id}/resources/
  "fileSize": integer // File size in bytes
  "mimeType": string
  "createdAt": string (timestamp)
}
```

回應範例值

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "path": "回應字串",
  "filePath": "回應字串",
  "fileSize": 456,
  "mimeType": "回應字串",
  "createdAt": "回應字串"
}
```

狀態碼: 400

回應結構範例

```
{
  "path"?: string // 路徑驗證錯誤 (非必填)
  "file"?: string // 檔案驗證錯誤 (非必填)
}
```

回應範例值

```
{
  "path": "回應字串",
  "file": "回應字串"
}
```

刪除技能資源

DELETE `/api/v1/skills/{skillPk}/resources/{id}`

參數

參數名稱	必填	類型	說明
`id`	V	string	
`skillPk`	V	string	

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X DELETE
"https://api.maiagent.ai/api/v1/skills/{skillPk}/resources/550e8400-
e29b-41d4-a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

// 請求內容 (payload)
const data = null;

axios.delete("https://api.maiagent.ai/api/v1/skills/{skillPk}/resour
ces/550e8400-e29b-41d4-a716-446655440000/", data, config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url =
"https://api.maiagent.ai/api/v1/skills/{skillPk}/resources/550e8400-
e29b-41d4-a716-446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.delete(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>delete("https://api.maiagent.ai/api/v1/skills/{skillPk}/resources/5
50e8400-e29b-41d4-a716-446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼	說明
204	No response body

下載技能資源

GET `/api/v1/skills/{skillPk}/resources/{id}/download/`

參數

參數名稱	必填	類型	說明
`id`	V	string	
`skillPk`	V	string	

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X GET
"https://api.maiagent.ai/api/v1/skills/{skillPk}/resources/550e8400-
e29b-41d4-a716-446655440000/download/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/skills/{skillPk}/resources
/550e8400-e29b-41d4-a716-446655440000/download/", config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url =
"https://api.maiagent.ai/api/v1/skills/{skillPk}/resources/550e8400-
e29b-41d4-a716-446655440000/download/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/skills/{skillPk}/resources/550e
8400-e29b-41d4-a716-446655440000/download/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼	說明
200	檔案下載

呼叫 API 示例 (Shell)

目錄

1. 列出會議記錄
2. 建立會議記錄
3. 取得特定會議記錄
4. 部分更新會議記錄
5. 刪除會議記錄
6. 匯入音檔並開始轉錄
7. 取得會議逐字稿（JSON）
8. 列出會議摘要
9. 產生會議摘要
10. 取得特定會議摘要
11. 上傳逐字稿到知識庫
12. 下載 SRT 字幕檔
13. 下載 MP3 音檔

呼叫 API 示例 (Shell)

會議記錄端點讓您的系統建立會議、匯入音檔轉錄、讀取逐字稿與摘要，並把逐字稿存入知識庫。匯入音檔前先用 `POST /api/v1/upload-presigned-url/`（`modelName` 為 `meeting-record`、`fieldName` 為 `audio`）上傳檔案，見 附件與檔案。功能說明見使用者手冊會議記錄。

列出會議記錄

`GET` `/api/v1/meeting-records/`

參數

參數名稱	必填	類型	說明
`endDate`	X		
`page`	X	integer	A page number within the paginated result set.

`pageSize`	X	integer	Number of results to return per page.
`query`	X		
`startDate`	X		
`status`	X	string	`pending`: Pending; `recording`: Recording; `processing`: Processing; `completed`: Completed; `failed`: Failed;

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/meeting-records/?
endDate=example&page=1&pageSize=1&query=example&startDate=example&st
atus=completed"

  -H "Authorization: Api-Key YOUR_API_KEY"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/meeting-records/?
endDate=example&page=1&pageSize=1&query=example&startDate=example&st
atus=completed", config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/meeting-records/?
endDate=example&page=1&pageSize=1&query=example&startDate=example&st
atus=completed"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/meeting-records/?
endDate=example&page=1&pageSize=1&query=example&startDate=example&st
atus=completed", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
{
  "count": integer
```

```
  "next"?: string (uri) // 非必填
  "previous"?: string (uri) // 非必填
  "results": [
    {
      "id": string (uuid)
      "sttContext"?: string // 非必填
      "sttContextLlmId"?: string (uuid) // 非必填
      "liveTranscriptionResult": object
      "eventContext"?: object // 非必填
      "meetingRecordSttProvider":
      {
        "id": string (uuid)
        "name": string // Display name for this STT provider
        "provider": string (enum: whisperlive, azure, deepgram,
assemblyai, bronci, alibaba, localai, openai, rap) // * `whisperlive` -
Whisperlive
* `azure` - Azure
* `deepgram` - Deepgram
* `assemblyai` - Assemblyai
* `bronci` - Bronci
* `alibaba` - Alibaba
* `localai` - Localai
* `openai` - Openai
* `rap` - Rap
        "modelName": string
      }
      "offlineTranscriptProviderDetail":
      {
        "id": string (uuid)
        "name": string // Display name for this provider
        "provider": string (enum: whisper_openai, whisper_groq,
whisper_offline, localai, azure, bronci, alibaba, rap, deepgram,
assemblyai) // * `whisper_openai` - whisper_openai
* `whisper_groq` - whisper_groq
* `whisper_offline` - whisper_offline
* `localai` - localai
* `azure` - azure
* `bronci` - bronci
* `alibaba` - alibaba
* `rap` - rap
* `deepgram` - deepgram
* `assemblyai` - assemblyai
        "modelName": string // Free-form vendor model identifier; any
string the vendor deployment accepts is valid.
      }
```

```
      "meetingRecordSttProviderId"?: string (uuid) // 非必填
      "speakerDiarizationProvider":
      {
        "id": string (uuid)
        "name": string // Display name for this provider
        "provider": string (enum: pyannoteai) // * `pyannoteai` -
pyannoteai
        "modelName": string // Free-form vendor model identifier; any
string the vendor deployment accepts is valid.
      }
      "enableTranslation"?: boolean // 非必填
      "targetLanguages"?: [ // Target language codes for live transcript
translation. (非必填)
        string
      ]
      "translationLlmId"?: string (uuid) // 非必填
      "knowledgeBaseId"?: string (uuid) // 非必填
      "audioUrl": string
      "transcriptUrl": string
      "mp3Url": string
      "backupAudioUrl": string
      "backupSyncStatus": string
      "backupUnavailableReason": string
      "backupError": object
      "backupDurationSeconds": number (double)
      "backupTotalParts": integer
      "backupTotalChunks": integer
      "backupRecordingStartedAt": string (timestamp)
      "backupLastActivityAt": string (timestamp)
      "backupFinalizedAt": string (timestamp)
      "knowledgeBase": object
      "transcriptFile": object
      "qaConfig": object // Generate qa_config for frontend to use with
chatbot completion API.
      "availableChatbots": [ // Get chatbots that have this meeting's
knowledge base (detail view only).
        object
      ]
      "createdBy":
      {
        "id": string (uuid)
        "name": string
      }
      "members": [ // The meeting's access roster, visible to anyone who
can see the meeting.
```

```
Editing (add/remove) is gated separately on the members endpoint; here
the
list is read-only context so members can see who participated and who
else
was granted view access.
        object
      ]
      "myRole": string // The requesting user's role on this meeting, or
None if not a member.
      "createdAt": string (timestamp)
      "updatedAt": string (timestamp)
      "meetingName": string
      "participants"?: object // List of meeting participants (非必填)
      "durationSeconds"?: number (double) // 非必填
      "status"?: string (enum: pending, recording, processing, completed,
failed) // * `pending` - Pending
* `recording` - Recording
* `processing` - Processing
* `completed` - Completed
* `failed` - Failed (非必填)
      "stopRequestedAt": string (timestamp) // When a user explicitly
requested to stop the recording. A finished recording without this set
ended on the server side (e.g. the client connection was lost).
      "recordingLimitReachedAt": string (timestamp) // When LiveKit ended
the egress at its maximum recording duration. The main audio file ends
here; the STT agent and the browser backup keep going until the room
closes, and the meeting completes on room end.
      "failureReason": // 可能有不同的類型
      string (enum: egress_not_started, egress_failed, finalize_timeout)
// Why the live recording ended as failed. Empty for meetings that did
not fail.

* `` - None
* `egress_not_started` - Recording did not start
* `egress_failed` - Recording failed
* `finalize_timeout` - Recording was never finalized
      "clientSurface":  // Durable client entry point captured when
recording starts. Legacy records remain unknown.

* `unknown` - Unknown
* `web` - Web
* `desktop` - Desktop
      {
      }
```

```
      "requestedSourceMode":  // Audio source mode requested by the
client when recording starts.

* `unknown` - Unknown
* `microphone` - Microphone
* `system_audio` - System Audio
* `both` - Microphone and System Audio
      {
      }
      "effectiveSourceMode":  // Server-resolved audio source mode used
for runtime and billing reconciliation.

* `unknown` - Unknown
* `microphone` - Microphone
* `system_audio` - System Audio
* `both` - Microphone and System Audio
      {
      }
      "sourceLanguages"?: object // Source languages for transcription (非
必填)
      "speakerDiarizationConfig": object // Per-meeting non-secret
speaker diarization hints, such as numSpeakers.
      "offlineAsrRequestOptions": object // Per-request ASR payload for
the offline audio import, keyed by the selected provider row
request_option_specs contract. EMPTY MEANS: no extra parameters.
      "audioProcessingSnapshot": object // Immutable audio processing
policy snapshot frozen from the platform active profile at meeting start
(via MeetingAudioProcessingProfile.to_snapshot). Downlinked to the
LiveKit Agent with this meeting client/source facts and used to correlate
per-track usage.
      "translationInputTokens"?: integer (int64) // Cumulative LLM input
tokens consumed by realtime translation. Atomically incremented per
translate() call; settled at egress completion. (非必填)
      "translationOutputTokens"?: integer (int64) // Cumulative LLM
output tokens consumed by realtime translation. (非必填)
      "deletedAt"?: string (timestamp) // 非必填
      "translationLlm"?: string (uuid) // LLM model to use for
translation when enabled (非必填)
    }
  ]
}
```

回應範例值

```
{
  "count": 123,
  "next": "http://api.example.org/accounts/?page=4",
  "previous": "http://api.example.org/accounts/?page=2",
  "results": [
    {
      "id": "a1b2c3d4-e5f6-7890-abcd-ef1234567890",
      "meeting_name": "產品規劃會議",
      "participants": [
        "張三",
        "李四",
        "王五"
      ],
      "duration_seconds": 3600.5,
      "status": "completed",
      "audio_url": "https://cdn.example.com/media/meeting-
record/a1b2c3d4-e5f6-7890-abcd-ef1234567890.ogg",
      "transcript_url": "https://cdn.example.com/media/meeting-
record/a1b2c3d4_transcript.json",
      "mp3_url": "https://cdn.example.com/media/meeting-record/a1b2c3d4-
e5f6-7890-abcd-ef1234567890_mp3.mp3",
      "source_languages": [
        "zh-TW"
      ],
      "enable_translation": true,
      "target_languages": [
        "en-US",
        "ja-JP"
      ],
      "meeting_record_stt_provider": {
        "id": "c8dc9f8a-2b5e-4a2d-8f93-1a2b3c4d5e6f",
        "provider": "deepgram",
        "model_name": "nova-2",
        "supported_languages": [
          "zh-TW",
          "en-US",
          "ja-JP"
        ],
        "config": {
          "punctuate": true,
          "diarize": true
        },
        "created_at": "2025-01-15T10:00:00Z",
        "updated_at": "2025-01-15T10:00:00Z"
```

```
      },
      "created_at": "2025-01-15T14:00:00Z",
      "updated_at": "2025-01-15T15:00:00Z"
    }
  ]
}
```

建立會議記錄

POST `/api/v1/meeting-records/`

請求內容

請求參數

欄位	類型	必填	說明
sttContext	string	否	
sttContextLlmId	string (uuid)	否	
eventContext	object	否	
meetingRecordSttProviderId	string (uuid)	否	
enableTranslation	boolean	否	
targetLanguages	array[string]	否	Target language codes for live transcript translation.
translationLlmId	string (uuid)	否	
knowledgeBaseId	string (uuid)	否	
meetingName	string	是	
participants	object	否	List of meeting participants

欄位	類型	必填	說明
durationSeconds	number (double)	否	
status	string (enum: pending, recording, processing, completed, failed)	否	`pending` : Pending ; `recording` : Recording ; `processing` : Processing ; `completed` : Completed ; `failed` : Failed;
sourceLanguages	object	否	Source languages for transcription
translationInputTokens	integer (int64)	否	Cumulative LLM input tokens consumed by realtime translation. Atomically incremented per translate() call; settled at egress completion.
translationOutputTokens	integer (int64)	否	Cumulative LLM output tokens consumed by realtime translation.
deletedAt	string (timestamp)	否	
translationLlm	string (uuid)	否	LLM model to use for translation when enabled

請求結構範例

```
{
  "sttContext"?: string // 非必填
  "sttContextLlmId"?: string (uuid) // 非必填
  "eventContext"?: object // 非必填
  "meetingRecordSttProviderId"?: string (uuid) // 非必填
  "enableTranslation"?: boolean // 非必填
  "targetLanguages"?: [ // Target language codes for live transcript
translation. (非必填)
    string
  ]
  "translationLlmId"?: string (uuid) // 非必填
  "knowledgeBaseId"?: string (uuid) // 非必填
  "meetingName": string
  "participants"?: object // List of meeting participants (非必填)
```

```
  "durationSeconds"?: number (double) // 非必填
  "status"?: string (enum: pending, recording, processing, completed,
failed) // * `pending` - Pending
* `recording` - Recording
* `processing` - Processing
* `completed` - Completed
* `failed` - Failed (非必填)
  "sourceLanguages"?: object // Source languages for transcription (非必
填)
  "translationInputTokens"?: integer (int64) // Cumulative LLM input
tokens consumed by realtime translation. Atomically incremented per
translate() call; settled at egress completion. (非必填)
  "translationOutputTokens"?: integer (int64) // Cumulative LLM output
tokens consumed by realtime translation. (非必填)
  "deletedAt"?: string (timestamp) // 非必填
  "translationLlm"?: string (uuid) // LLM model to use for translation
when enabled (非必填)
}
```

請求範例值

```
{
  "meeting_name": "產品規劃會議",
  "participants": [
    "張三",
    "李四",
    "王五"
  ],
  "source_languages": [
    "zh-TW"
  ],
  "enable_translation": true,
  "target_languages": [
    "en-US",
    "ja-JP"
  ]
}
```

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X POST "https://api.maiagent.ai/api/v1/meeting-records/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "meeting_name": "產品規劃會議",
    "participants": [
      "張三",
      "李四",
      "王五"
    ],
    "source_languages": [
      "zh-TW"
    ],
    "enable_translation": true,
    "target_languages": [
      "en-US",
      "ja-JP"
    ]
  }'

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```javascript
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// 請求內容 (payload)
const data = {
    "meeting_name": "產品規劃會議",
    "participants": [
      "張三",
      "李四",
      "王五"
    ],
    "source_languages": [
      "zh-TW"
    ],
    "enable_translation": true,
    "target_languages": [
      "en-US",
      "ja-JP"
    ]
  };

axios.post("https://api.maiagent.ai/api/v1/meeting-records/", data,
config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/meeting-records/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# 請求內容 (payload)
data = {
    "meeting_name": "產品規劃會議",
    "participants": [
        "張三",
        "李四",
        "王五"
    ],
    "source_languages": [
        "zh-TW"
    ],
    "enable_translation": True,
    "target_languages": [
        "en-US",
        "ja-JP"
    ]
}

response = requests.post(url, json=data, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>post("https://api.maiagent.ai/api/v1/meeting-records/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'meeting_name' => '產品規劃會議',
            'participants' => [
                '張三',
                '李四',
                '王五'
            ],
            'source_languages' => [
                'zh-TW'
            ],
            'enable_translation' => true,
            'target_languages' => [
                'en-US',
                'ja-JP'
            ]
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 201

回應結構範例

```
{
  "id": string (uuid)
  "sttContext"?: string // 非必填
  "sttContextLlmId"?: string (uuid) // 非必填
  "liveTranscriptionResult": object
  "eventContext"?: object // 非必填
  "meetingRecordSttProvider":
  {
    "id": string (uuid)
    "name": string // Display name for this STT provider
    "provider": string (enum: whisperlive, azure, deepgram, assemblyai,
bronci, alibaba, localai, openai, rap) // * `whisperlive` - Whisperlive
* `azure` - Azure
* `deepgram` - Deepgram
* `assemblyai` - Assemblyai
* `bronci` - Bronci
* `alibaba` - Alibaba
* `localai` - Localai
* `openai` - Openai
* `rap` - Rap
    "modelName": string
  }
  "offlineTranscriptProviderDetail":
  {
    "id": string (uuid)
    "name": string // Display name for this provider
    "provider": string (enum: whisper_openai, whisper_groq,
whisper_offline, localai, azure, bronci, alibaba, rap, deepgram,
assemblyai) // * `whisper_openai` - whisper_openai
* `whisper_groq` - whisper_groq
* `whisper_offline` - whisper_offline
```

```
* `localai` - localai
* `azure` - azure
* `bronci` - bronci
* `alibaba` - alibaba
* `rap` - rap
* `deepgram` - deepgram
* `assemblyai` - assemblyai
    "modelName": string // Free-form vendor model identifier; any string
the vendor deployment accepts is valid.
  }
  "meetingRecordSttProviderId"?: string (uuid) // 非必填
  "speakerDiarizationProvider":
  {
    "id": string (uuid)
    "name": string // Display name for this provider
    "provider": string (enum: pyannoteai) // * `pyannoteai` - pyannoteai
    "modelName": string // Free-form vendor model identifier; any string
the vendor deployment accepts is valid.
  }
  "enableTranslation"?: boolean // 非必填
  "targetLanguages"?: [ // Target language codes for live transcript
translation. (非必填)
    string
  ]
  "translationLlmId"?: string (uuid) // 非必填
  "knowledgeBaseId"?: string (uuid) // 非必填
  "audioUrl": string
  "transcriptUrl": string
  "mp3Url": string
  "backupAudioUrl": string
  "backupSyncStatus": string
  "backupUnavailableReason": string
  "backupError": object
  "backupDurationSeconds": number (double)
  "backupTotalParts": integer
  "backupTotalChunks": integer
  "backupRecordingStartedAt": string (timestamp)
  "backupLastActivityAt": string (timestamp)
  "backupFinalizedAt": string (timestamp)
  "knowledgeBase": object
  "transcriptFile": object
  "qaConfig": object // Generate qa_config for frontend to use with
chatbot completion API.
  "availableChatbots": [ // Get chatbots that have this meeting's
knowledge base (detail view only).
```

```
    object
  ]
  "createdBy":
  {
    "id": string (uuid)
    "name": string
  }
  "members": [ // The meeting's access roster, visible to anyone who can
see the meeting.

Editing (add/remove) is gated separately on the members endpoint; here
the
list is read-only context so members can see who participated and who
else
was granted view access.
    object
  ]
  "myRole": string // The requesting user's role on this meeting, or None
if not a member.
  "createdAt": string (timestamp)
  "updatedAt": string (timestamp)
  "meetingName": string
  "participants"?: object // List of meeting participants (非必填)
  "durationSeconds"?: number (double) // 非必填
  "status"?: string (enum: pending, recording, processing, completed,
failed) // * `pending` - Pending
* `recording` - Recording
* `processing` - Processing
* `completed` - Completed
* `failed` - Failed (非必填)
  "stopRequestedAt": string (timestamp) // When a user explicitly
requested to stop the recording. A finished recording without this set
ended on the server side (e.g. the client connection was lost).
  "recordingLimitReachedAt": string (timestamp) // When LiveKit ended the
egress at its maximum recording duration. The main audio file ends here;
the STT agent and the browser backup keep going until the room closes,
and the meeting completes on room end.
  "failureReason": // 可能有不同的類型
  string (enum: egress_not_started, egress_failed, finalize_timeout) //
Why the live recording ended as failed. Empty for meetings that did not
fail.

* `` - None
* `egress_not_started` - Recording did not start
* `egress_failed` - Recording failed
```

```
* `finalize_timeout` - Recording was never finalized
  "clientSurface":  // Durable client entry point captured when recording
starts. Legacy records remain unknown.

* `unknown` - Unknown
* `web` - Web
* `desktop` - Desktop
  {
  }
  "requestedSourceMode":  // Audio source mode requested by the client
when recording starts.

* `unknown` - Unknown
* `microphone` - Microphone
* `system_audio` - System Audio
* `both` - Microphone and System Audio
  {
  }
  "effectiveSourceMode":  // Server-resolved audio source mode used for
runtime and billing reconciliation.

* `unknown` - Unknown
* `microphone` - Microphone
* `system_audio` - System Audio
* `both` - Microphone and System Audio
  {
  }
  "sourceLanguages"?: object // Source languages for transcription (非必
填)
  "speakerDiarizationConfig": object // Per-meeting non-secret speaker
diarization hints, such as numSpeakers.
  "offlineAsrRequestOptions": object // Per-request ASR payload for the
offline audio import, keyed by the selected provider row
request_option_specs contract. EMPTY MEANS: no extra parameters.
  "audioProcessingSnapshot": object // Immutable audio processing policy
snapshot frozen from the platform active profile at meeting start (via
MeetingAudioProcessingProfile.to_snapshot). Downlinked to the LiveKit
Agent with this meeting client/source facts and used to correlate per-
track usage.
  "translationInputTokens"?: integer (int64) // Cumulative LLM input
tokens consumed by realtime translation. Atomically incremented per
translate() call; settled at egress completion. (非必填)
  "translationOutputTokens"?: integer (int64) // Cumulative LLM output
tokens consumed by realtime translation. (非必填)
  "deletedAt"?: string (timestamp) // 非必填
```

```
  "translationLlm"?: string (uuid) // LLM model to use for translation
when enabled (非必填)
}
```

回應範例值


```
{
  "id": "a1b2c3d4-e5f6-7890-abcd-ef1234567890",
  "meeting_name": "產品規劃會議",
  "participants": [
    "張三",
    "李四",
    "王五"
  ],
  "duration_seconds": 3600.5,
  "status": "completed",
  "audio_url": "https://cdn.example.com/media/meeting-record/a1b2c3d4-
e5f6-7890-abcd-ef1234567890.ogg",
  "transcript_url": "https://cdn.example.com/media/meeting-
record/a1b2c3d4_transcript.json",
  "mp3_url": "https://cdn.example.com/media/meeting-record/a1b2c3d4-e5f6-
7890-abcd-ef1234567890_mp3.mp3",
  "source_languages": [
    "zh-TW"
  ],
  "enable_translation": true,
  "target_languages": [
    "en-US",
    "ja-JP"
  ],
  "meeting_record_stt_provider": {
    "id": "c8dc9f8a-2b5e-4a2d-8f93-1a2b3c4d5e6f",
    "provider": "deepgram",
    "model_name": "nova-2",
    "supported_languages": [
      "zh-TW",
      "en-US",
      "ja-JP"
    ],
    "config": {
      "punctuate": true,
      "diarize": true
    },
    "created_at": "2025-01-15T10:00:00Z",
```

```
    "updated_at": "2025-01-15T10:00:00Z"
  },
  "created_at": "2025-01-15T14:00:00Z",
  "updated_at": "2025-01-15T15:00:00Z"
}
```


取得特定會議記錄

GET `/api/v1/meeting-records/{id}`

參數

參數名稱	必填	類型	說明
id	V	string	A UUID string identifying this Meeting Record.

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/meeting-
records/550e8400-e29b-41d4-a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/meeting-records/550e8400-
e29b-41d4-a716-446655440000/", config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/meeting-records/550e8400-e29b-41d4-a716-446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/meeting-records/550e8400-e29b-
41d4-a716-446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
{
  "id": string (uuid)
  "sttContext"?: string // 非必填
```

```
  "sttContextLlmId"?: string (uuid) // 非必填
  "liveTranscriptionResult": object
  "eventContext"?: object // 非必填
  "meetingRecordSttProvider":
  {
    "id": string (uuid)
    "name": string // Display name for this STT provider
    "provider": string (enum: whisperlive, azure, deepgram, assemblyai,
bronci, alibaba, localai, openai, rap) // * `whisperlive` - Whisperlive
* `azure` - Azure
* `deepgram` - Deepgram
* `assemblyai` - Assemblyai
* `bronci` - Bronci
* `alibaba` - Alibaba
* `localai` - Localai
* `openai` - Openai
* `rap` - Rap
    "modelName": string
  }
  "offlineTranscriptProviderDetail":
  {
    "id": string (uuid)
    "name": string // Display name for this provider
    "provider": string (enum: whisper_openai, whisper_groq,
whisper_offline, localai, azure, bronci, alibaba, rap, deepgram,
assemblyai) // * `whisper_openai` - whisper_openai
* `whisper_groq` - whisper_groq
* `whisper_offline` - whisper_offline
* `localai` - localai
* `azure` - azure
* `bronci` - bronci
* `alibaba` - alibaba
* `rap` - rap
* `deepgram` - deepgram
* `assemblyai` - assemblyai
    "modelName": string // Free-form vendor model identifier; any string
the vendor deployment accepts is valid.
  }
  "meetingRecordSttProviderId"?: string (uuid) // 非必填
  "speakerDiarizationProvider":
  {
    "id": string (uuid)
    "name": string // Display name for this provider
    "provider": string (enum: pyannoteai) // * `pyannoteai` - pyannoteai
    "modelName": string // Free-form vendor model identifier; any string
```

```
the vendor deployment accepts is valid.
  }
  "enableTranslation"?: boolean // 非必填
  "targetLanguages"?: [ // Target language codes for live transcript
translation. (非必填)
    string
  ]
  "translationLlmId"?: string (uuid) // 非必填
  "knowledgeBaseId"?: string (uuid) // 非必填
  "audioUrl": string
  "transcriptUrl": string
  "mp3Url": string
  "backupAudioUrl": string
  "backupSyncStatus": string
  "backupUnavailableReason": string
  "backupError": object
  "backupDurationSeconds": number (double)
  "backupTotalParts": integer
  "backupTotalChunks": integer
  "backupRecordingStartedAt": string (timestamp)
  "backupLastActivityAt": string (timestamp)
  "backupFinalizedAt": string (timestamp)
  "knowledgeBase": object
  "transcriptFile": object
  "qaConfig": object // Generate qa_config for frontend to use with
chatbot completion API.
  "availableChatbots": [ // Get chatbots that have this meeting's
knowledge base (detail view only).
    object
  ]
  "createdBy":
  {
    "id": string (uuid)
    "name": string
  }
  "members": [ // The meeting's access roster, visible to anyone who can
see the meeting.

Editing (add/remove) is gated separately on the members endpoint; here
the
list is read-only context so members can see who participated and who
else
was granted view access.
    object
  ]
```

```
  "myRole": string // The requesting user's role on this meeting, or None
if not a member.
  "createdAt": string (timestamp)
  "updatedAt": string (timestamp)
  "meetingName": string
  "participants"?: object // List of meeting participants (非必填)
  "durationSeconds"?: number (double) // 非必填
  "status"?: string (enum: pending, recording, processing, completed,
failed) // * `pending` - Pending
* `recording` - Recording
* `processing` - Processing
* `completed` - Completed
* `failed` - Failed (非必填)
  "stopRequestedAt": string (timestamp) // When a user explicitly
requested to stop the recording. A finished recording without this set
ended on the server side (e.g. the client connection was lost).
  "recordingLimitReachedAt": string (timestamp) // When LiveKit ended the
egress at its maximum recording duration. The main audio file ends here;
the STT agent and the browser backup keep going until the room closes,
and the meeting completes on room end.
  "failureReason": // 可能有不同的類型
  string (enum: egress_not_started, egress_failed, finalize_timeout) //
Why the live recording ended as failed. Empty for meetings that did not
fail.

* `` - None
* `egress_not_started` - Recording did not start
* `egress_failed` - Recording failed
* `finalize_timeout` - Recording was never finalized
  "clientSurface":  // Durable client entry point captured when recording
starts. Legacy records remain unknown.

* `unknown` - Unknown
* `web` - Web
* `desktop` - Desktop
  {
  }
  "requestedSourceMode":  // Audio source mode requested by the client
when recording starts.

* `unknown` - Unknown
* `microphone` - Microphone
* `system_audio` - System Audio
* `both` - Microphone and System Audio
  {
```

```
  }
  "effectiveSourceMode":  // Server-resolved audio source mode used for
runtime and billing reconciliation.

* `unknown` - Unknown
* `microphone` - Microphone
* `system_audio` - System Audio
* `both` - Microphone and System Audio
  {
  }
  "sourceLanguages"?: object // Source languages for transcription (非必
填)
  "speakerDiarizationConfig": object // Per-meeting non-secret speaker
diarization hints, such as numSpeakers.
  "offlineAsrRequestOptions": object // Per-request ASR payload for the
offline audio import, keyed by the selected provider row
request_option_specs contract. EMPTY MEANS: no extra parameters.
  "audioProcessingSnapshot": object // Immutable audio processing policy
snapshot frozen from the platform active profile at meeting start (via
MeetingAudioProcessingProfile.to_snapshot). Downlinked to the LiveKit
Agent with this meeting client/source facts and used to correlate per-
track usage.
  "translationInputTokens"?: integer (int64) // Cumulative LLM input
tokens consumed by realtime translation. Atomically incremented per
translate() call; settled at egress completion. (非必填)
  "translationOutputTokens"?: integer (int64) // Cumulative LLM output
tokens consumed by realtime translation. (非必填)
  "deletedAt"?: string (timestamp) // 非必填
  "translationLlm"?: string (uuid) // LLM model to use for translation
when enabled (非必填)
}
```

回應範例值

```
{
  "id": "a1b2c3d4-e5f6-7890-abcd-ef1234567890",
  "meeting_name": "產品規劃會議",
  "participants": [
    "張三",
    "李四",
    "王五"
  ],
  "duration_seconds": 3600.5,
  "status": "completed",
```

```
  "audio_url": "https://cdn.example.com/media/meeting-record/a1b2c3d4-
e5f6-7890-abcd-ef1234567890.ogg",
  "transcript_url": "https://cdn.example.com/media/meeting-
record/a1b2c3d4_transcript.json",
  "mp3_url": "https://cdn.example.com/media/meeting-record/a1b2c3d4-e5f6-
7890-abcd-ef1234567890_mp3.mp3",
  "source_languages": [
    "zh-TW"
  ],
  "enable_translation": true,
  "target_languages": [
    "en-US",
    "ja-JP"
  ],
  "meeting_record_stt_provider": {
    "id": "c8dc9f8a-2b5e-4a2d-8f93-1a2b3c4d5e6f",
    "provider": "deepgram",
    "model_name": "nova-2",
    "supported_languages": [
      "zh-TW",
      "en-US",
      "ja-JP"
    ],
    "config": {
      "punctuate": true,
      "diarize": true
    },
    "created_at": "2025-01-15T10:00:00Z",
    "updated_at": "2025-01-15T10:00:00Z"
  },
  "created_at": "2025-01-15T14:00:00Z",
  "updated_at": "2025-01-15T15:00:00Z"
}
```


部分更新會議記錄

PATCH `/api/v1/meeting-records/{id}`

參數

參數名稱	必填	類型	說明
`id`	V	string	A UUID string identifying this Meeting Record.

請求內容

請求參數

欄位	類型	必填	說明
sttContext	string	否	
sttContextLlmId	string (uuid)	否	
eventContext	object	否	
meetingRecordSttProviderId	string (uuid)	否	
enableTranslation	boolean	否	
targetLanguages	array[string]	否	Target language codes for live transcript translation.
translationLlmId	string (uuid)	否	
knowledgeBaseId	string (uuid)	否	
meetingName	string	否	
participants	object	否	List of meeting participants
durationSeconds	number (double)	否	
status	string (enum: pending, recording, processing, completed, failed)	否	`pending` : Pending ; `recording` : Recording ; `processing` : Processing ; `completed` : Completed ; `failed` : Failed;

欄位	類型	必填	說明
sourceLanguages	object	否	Source languages for transcription
translationInputTokens	integer (int64)	否	Cumulative LLM input tokens consumed by realtime translation. Atomically incremented per translate() call; settled at egress completion.
translationOutputTokens	integer (int64)	否	Cumulative LLM output tokens consumed by realtime translation.
deletedAt	string (timestamp)	否	
translationLlm	string (uuid)	否	LLM model to use for translation when enabled

請求結構範例

```
{
  "sttContext"?: string // 非必填
  "sttContextLlmId"?: string (uuid) // 非必填
  "eventContext"?: object // 非必填
  "meetingRecordSttProviderId"?: string (uuid) // 非必填
  "enableTranslation"?: boolean // 非必填
  "targetLanguages"?: [ // Target language codes for live transcript
translation. (非必填)
    string
  ]
  "translationLlmId"?: string (uuid) // 非必填
  "knowledgeBaseId"?: string (uuid) // 非必填
  "meetingName"?: string // 非必填
  "participants"?: object // List of meeting participants (非必填)
  "durationSeconds"?: number (double) // 非必填
  "status"?: string (enum: pending, recording, processing, completed,
failed) // * `pending` - Pending
* `recording` - Recording
* `processing` - Processing
* `completed` - Completed
* `failed` - Failed (非必填)
```

```
  "sourceLanguages"?: object // Source languages for transcription (非必
填)
  "translationInputTokens"?: integer (int64) // Cumulative LLM input
tokens consumed by realtime translation. Atomically incremented per
translate() call; settled at egress completion. (非必填)
  "translationOutputTokens"?: integer (int64) // Cumulative LLM output
tokens consumed by realtime translation. (非必填)
  "deletedAt"?: string (timestamp) // 非必填
  "translationLlm"?: string (uuid) // LLM model to use for translation
when enabled (非必填)
}
```

請求範例值

```
{
  "id": "a1b2c3d4-e5f6-7890-abcd-ef1234567890",
  "meeting_name": "產品規劃會議",
  "participants": [
    "張三",
    "李四",
    "王五"
  ],
  "duration_seconds": 3600.5,
  "status": "completed",
  "audio_url": "https://cdn.example.com/media/meeting-record/a1b2c3d4-
e5f6-7890-abcd-ef1234567890.ogg",
  "transcript_url": "https://cdn.example.com/media/meeting-
record/a1b2c3d4_transcript.json",
  "mp3_url": "https://cdn.example.com/media/meeting-record/a1b2c3d4-e5f6-
7890-abcd-ef1234567890_mp3.mp3",
  "source_languages": [
    "zh-TW"
  ],
  "enable_translation": true,
  "target_languages": [
    "en-US",
    "ja-JP"
  ],
  "meeting_record_stt_provider": {
    "id": "c8dc9f8a-2b5e-4a2d-8f93-1a2b3c4d5e6f",
    "provider": "deepgram",
    "model_name": "nova-2",
    "supported_languages": [
      "zh-TW",
```

```
      "en-US",
      "ja-JP"
    ],
    "config": {
      "punctuate": true,
      "diarize": true
    },
    "created_at": "2025-01-15T10:00:00Z",
    "updated_at": "2025-01-15T10:00:00Z"
  },
  "created_at": "2025-01-15T14:00:00Z",
  "updated_at": "2025-01-15T15:00:00Z"
}
```


程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X PATCH "https://api.maiagent.ai/api/v1/meeting-
records/550e8400-e29b-41d4-a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "id": "a1b2c3d4-e5f6-7890-abcd-ef1234567890",
    "meeting_name": "產品規劃會議",
    "participants": [
      "張三",
      "李四",
      "王五"
    ],
    "duration_seconds": 3600.5,
    "status": "completed",
    "audio_url": "https://cdn.example.com/media/meeting-
record/a1b2c3d4-e5f6-7890-abcd-ef1234567890.ogg",
    "transcript_url": "https://cdn.example.com/media/meeting-
record/a1b2c3d4_transcript.json",
    "mp3_url": "https://cdn.example.com/media/meeting-
record/a1b2c3d4-e5f6-7890-abcd-ef1234567890_mp3.mp3",
    "source_languages": [
      "zh-TW"
    ],
    "enable_translation": true,
    "target_languages": [
      "en-US",
      "ja-JP"
    ],
    "meeting_record_stt_provider": {
      "id": "c8dc9f8a-2b5e-4a2d-8f93-1a2b3c4d5e6f",
      "provider": "deepgram",
      "model_name": "nova-2",
      "supported_languages": [
        "zh-TW",
        "en-US",
        "ja-JP"
```

```
      ],
      "config": {
        "punctuate": true,
        "diarize": true
      },
      "created_at": "2025-01-15T10:00:00Z",
      "updated_at": "2025-01-15T10:00:00Z"
    },
    "created_at": "2025-01-15T14:00:00Z",
    "updated_at": "2025-01-15T15:00:00Z"
  }'

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// 請求內容 (payload)
const data = {
    "id": "a1b2c3d4-e5f6-7890-abcd-ef1234567890",
    "meeting_name": "產品規劃會議",
    "participants": [
      "張三",
      "李四",
      "王五"
    ],
    "duration_seconds": 3600.5,
    "status": "completed",
    "audio_url": "https://cdn.example.com/media/meeting-
record/a1b2c3d4-e5f6-7890-abcd-ef1234567890.ogg",
    "transcript_url": "https://cdn.example.com/media/meeting-
record/a1b2c3d4_transcript.json",
    "mp3_url": "https://cdn.example.com/media/meeting-
record/a1b2c3d4-e5f6-7890-abcd-ef1234567890_mp3.mp3",
    "source_languages": [
      "zh-TW"
    ],
    "enable_translation": true,
    "target_languages": [
      "en-US",
      "ja-JP"
    ],
    "meeting_record_stt_provider": {
      "id": "c8dc9f8a-2b5e-4a2d-8f93-1a2b3c4d5e6f",
      "provider": "deepgram",
      "model_name": "nova-2",
      "supported_languages": [
```

```
        "zh-TW",
        "en-US",
        "ja-JP"
      ],
      "config": {
        "punctuate": true,
        "diarize": true
      },
      "created_at": "2025-01-15T10:00:00Z",
      "updated_at": "2025-01-15T10:00:00Z"
    },
    "created_at": "2025-01-15T14:00:00Z",
    "updated_at": "2025-01-15T15:00:00Z"
  };

axios.patch("https://api.maiagent.ai/api/v1/meeting-
records/550e8400-e29b-41d4-a716-446655440000/", data, config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/meeting-records/550e8400-e29b-
41d4-a716-446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# 請求內容 (payload)
data = {
    "id": "a1b2c3d4-e5f6-7890-abcd-ef1234567890",
    "meeting_name": "產品規劃會議",
    "participants": [
        "張三",
        "李四",
        "王五"
    ],
    "duration_seconds": 3600.5,
    "status": "completed",
    "audio_url": "https://cdn.example.com/media/meeting-
record/a1b2c3d4-e5f6-7890-abcd-ef1234567890.ogg",
    "transcript_url": "https://cdn.example.com/media/meeting-
record/a1b2c3d4_transcript.json",
    "mp3_url": "https://cdn.example.com/media/meeting-
record/a1b2c3d4-e5f6-7890-abcd-ef1234567890_mp3.mp3",
    "source_languages": [
        "zh-TW"
    ],
    "enable_translation": True,
    "target_languages": [
        "en-US",
        "ja-JP"
    ],
    "meeting_record_stt_provider": {
        "id": "c8dc9f8a-2b5e-4a2d-8f93-1a2b3c4d5e6f",
        "provider": "deepgram",
        "model_name": "nova-2",
        "supported_languages": [
            "zh-TW",
```

```
            "en-US",
            "ja-JP"
        ],
        "config": {
            "punctuate": True,
            "diarize": True
        },
        "created_at": "2025-01-15T10:00:00Z",
        "updated_at": "2025-01-15T10:00:00Z"
    },
    "created_at": "2025-01-15T14:00:00Z",
    "updated_at": "2025-01-15T15:00:00Z"
}

response = requests.patch(url, json=data, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>patch("https://api.maiagent.ai/api/v1/meeting-records/550e8400-
e29b-41d4-a716-446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'id' => 'a1b2c3d4-e5f6-7890-abcd-ef1234567890',
            'meeting_name' => '產品規劃會議',
            'participants' => [
                '張三',
                '李四',
                '王五'
            ],
            'duration_seconds' => 3600.5,
            'status' => 'completed',
            'audio_url' => 'https://cdn.example.com/media/meeting-
record/a1b2c3d4-e5f6-7890-abcd-ef1234567890.ogg',
            'transcript_url' =>
'https://cdn.example.com/media/meeting-
record/a1b2c3d4_transcript.json',
            'mp3_url' => 'https://cdn.example.com/media/meeting-
record/a1b2c3d4-e5f6-7890-abcd-ef1234567890_mp3.mp3',
            'source_languages' => [
                'zh-TW'
            ],
            'enable_translation' => true,
            'target_languages' => [
                'en-US',
                'ja-JP'
            ],
            'meeting_record_stt_provider' => [
                'id' => 'c8dc9f8a-2b5e-4a2d-8f93-1a2b3c4d5e6f',
```

```
                    'provider' => 'deepgram',
                    'model_name' => 'nova-2',
                    'supported_languages' => [
                        'zh-TW',
                        'en-US',
                        'ja-JP'
                    ],
                    'config' => [
                        'punctuate' => true,
                        'diarize' => true
                    ],
                    'created_at' => '2025-01-15T10:00:00Z',
                    'updated_at' => '2025-01-15T10:00:00Z'
                ],
                'created_at' => '2025-01-15T14:00:00Z',
                'updated_at' => '2025-01-15T15:00:00Z'
            ]
        ]);

        $data = json_decode($response->getBody(), true);
        echo "成功取得回應:\n";
        print_r($data);
    } catch (Exception $e) {
        echo '請求發生錯誤: ' . $e->getMessage();
    }
    ?>
```

回應內容

狀態碼: 200

回應結構範例

```
{
  "id": string (uuid)
  "sttContext"?: string // 非必填
  "sttContextLlmId"?: string (uuid) // 非必填
```

```
  "liveTranscriptionResult": object
  "eventContext"?: object // 非必填
  "meetingRecordSttProvider":
  {
    "id": string (uuid)
    "name": string // Display name for this STT provider
    "provider": string (enum: whisperlive, azure, deepgram, assemblyai,
bronci, alibaba, localai, openai, rap) // * `whisperlive` - Whisperlive
* `azure` - Azure
* `deepgram` - Deepgram
* `assemblyai` - Assemblyai
* `bronci` - Bronci
* `alibaba` - Alibaba
* `localai` - Localai
* `openai` - Openai
* `rap` - Rap
    "modelName": string
  }
  "offlineTranscriptProviderDetail":
  {
    "id": string (uuid)
    "name": string // Display name for this provider
    "provider": string (enum: whisper_openai, whisper_groq,
whisper_offline, localai, azure, bronci, alibaba, rap, deepgram,
assemblyai) // * `whisper_openai` - whisper_openai
* `whisper_groq` - whisper_groq
* `whisper_offline` - whisper_offline
* `localai` - localai
* `azure` - azure
* `bronci` - bronci
* `alibaba` - alibaba
* `rap` - rap
* `deepgram` - deepgram
* `assemblyai` - assemblyai
    "modelName": string // Free-form vendor model identifier; any string
the vendor deployment accepts is valid.
  }
  "meetingRecordSttProviderId"?: string (uuid) // 非必填
  "speakerDiarizationProvider":
  {
    "id": string (uuid)
    "name": string // Display name for this provider
    "provider": string (enum: pyannoteai) // * `pyannoteai` - pyannoteai
    "modelName": string // Free-form vendor model identifier; any string
the vendor deployment accepts is valid.
```

```
  }
  "enableTranslation"?: boolean // 非必填
  "targetLanguages"?: [ // Target language codes for live transcript
translation. (非必填)
    string
  ]
  "translationLlmId"?: string (uuid) // 非必填
  "knowledgeBaseId"?: string (uuid) // 非必填
  "audioUrl": string
  "transcriptUrl": string
  "mp3Url": string
  "backupAudioUrl": string
  "backupSyncStatus": string
  "backupUnavailableReason": string
  "backupError": object
  "backupDurationSeconds": number (double)
  "backupTotalParts": integer
  "backupTotalChunks": integer
  "backupRecordingStartedAt": string (timestamp)
  "backupLastActivityAt": string (timestamp)
  "backupFinalizedAt": string (timestamp)
  "knowledgeBase": object
  "transcriptFile": object
  "qaConfig": object // Generate qa_config for frontend to use with
chatbot completion API.
  "availableChatbots": [ // Get chatbots that have this meeting's
knowledge base (detail view only).
    object
  ]
  "createdBy":
  {
    "id": string (uuid)
    "name": string
  }
  "members": [ // The meeting's access roster, visible to anyone who can
see the meeting.

Editing (add/remove) is gated separately on the members endpoint; here
the
list is read-only context so members can see who participated and who
else
was granted view access.
    object
  ]
  "myRole": string // The requesting user's role on this meeting, or None
```

```
if not a member.
  "createdAt": string (timestamp)
  "updatedAt": string (timestamp)
  "meetingName": string
  "participants"?: object // List of meeting participants (非必填)
  "durationSeconds"?: number (double) // 非必填
  "status"?: string (enum: pending, recording, processing, completed,
failed) // * `pending` - Pending
* `recording` - Recording
* `processing` - Processing
* `completed` - Completed
* `failed` - Failed (非必填)
  "stopRequestedAt": string (timestamp) // When a user explicitly
requested to stop the recording. A finished recording without this set
ended on the server side (e.g. the client connection was lost).
  "recordingLimitReachedAt": string (timestamp) // When LiveKit ended the
egress at its maximum recording duration. The main audio file ends here;
the STT agent and the browser backup keep going until the room closes,
and the meeting completes on room end.
  "failureReason": // 可能有不同的類型
  string (enum: egress_not_started, egress_failed, finalize_timeout) //
Why the live recording ended as failed. Empty for meetings that did not
fail.

* `` - None
* `egress_not_started` - Recording did not start
* `egress_failed` - Recording failed
* `finalize_timeout` - Recording was never finalized
  "clientSurface":  // Durable client entry point captured when recording
starts. Legacy records remain unknown.

* `unknown` - Unknown
* `web` - Web
* `desktop` - Desktop
  {
  }
  "requestedSourceMode":  // Audio source mode requested by the client
when recording starts.

* `unknown` - Unknown
* `microphone` - Microphone
* `system_audio` - System Audio
* `both` - Microphone and System Audio
  {
  }
```

```
  "effectiveSourceMode":  // Server-resolved audio source mode used for
runtime and billing reconciliation.

* `unknown` - Unknown
* `microphone` - Microphone
* `system_audio` - System Audio
* `both` - Microphone and System Audio
  {
  }
  "sourceLanguages"?: object // Source languages for transcription (非必
填)
  "speakerDiarizationConfig": object // Per-meeting non-secret speaker
diarization hints, such as numSpeakers.
  "offlineAsrRequestOptions": object // Per-request ASR payload for the
offline audio import, keyed by the selected provider row
request_option_specs contract. EMPTY MEANS: no extra parameters.
  "audioProcessingSnapshot": object // Immutable audio processing policy
snapshot frozen from the platform active profile at meeting start (via
MeetingAudioProcessingProfile.to_snapshot). Downlinked to the LiveKit
Agent with this meeting client/source facts and used to correlate per-
track usage.
  "translationInputTokens"?: integer (int64) // Cumulative LLM input
tokens consumed by realtime translation. Atomically incremented per
translate() call; settled at egress completion. (非必填)
  "translationOutputTokens"?: integer (int64) // Cumulative LLM output
tokens consumed by realtime translation. (非必填)
  "deletedAt"?: string (timestamp) // 非必填
  "translationLlm"?: string (uuid) // LLM model to use for translation
when enabled (非必填)
}
```

回應範例值

```
{
  "id": "a1b2c3d4-e5f6-7890-abcd-ef1234567890",
  "meeting_name": "產品規劃會議",
  "participants": [
    "張三",
    "李四",
    "王五"
  ],
  "duration_seconds": 3600.5,
  "status": "completed",
  "audio_url": "https://cdn.example.com/media/meeting-record/a1b2c3d4-
```

```
e5f6-7890-abcd-ef1234567890.ogg",
  "transcript_url": "https://cdn.example.com/media/meeting-
record/a1b2c3d4_transcript.json",
  "mp3_url": "https://cdn.example.com/media/meeting-record/a1b2c3d4-e5f6-
7890-abcd-ef1234567890_mp3.mp3",
  "source_languages": [
    "zh-TW"
  ],
  "enable_translation": true,
  "target_languages": [
    "en-US",
    "ja-JP"
  ],
  "meeting_record_stt_provider": {
    "id": "c8dc9f8a-2b5e-4a2d-8f93-1a2b3c4d5e6f",
    "provider": "deepgram",
    "model_name": "nova-2",
    "supported_languages": [
      "zh-TW",
      "en-US",
      "ja-JP"
    ],
    "config": {
      "punctuate": true,
      "diarize": true
    },
    "created_at": "2025-01-15T10:00:00Z",
    "updated_at": "2025-01-15T10:00:00Z"
  },
  "created_at": "2025-01-15T14:00:00Z",
  "updated_at": "2025-01-15T15:00:00Z"
}
```


刪除會議記錄

DELETE `/api/v1/meeting-records/{id}`

參數

參數名稱	必填	類型	說明
`id`	V	string	A UUID string identifying this Meeting Record.

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X DELETE "https://api.maiagent.ai/api/v1/meeting-
records/550e8400-e29b-41d4-a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

// 請求內容 (payload)
const data = null;

axios.delete("https://api.maiagent.ai/api/v1/meeting-
records/550e8400-e29b-41d4-a716-446655440000/", data, config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/meeting-records/550e8400-e29b-41d4-a716-446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.delete(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>delete("https://api.maiagent.ai/api/v1/meeting-records/550e8400-
e29b-41d4-a716-446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼	說明
204	No response body

匯入音檔並開始轉錄

`POST` `/api/v1/meeting-records/import-audio/`

以非同步方式轉錄已上傳的音檔；轉錄進度從會議記錄的狀態欄位查詢。

請求內容

請求參數

欄位	類型	必填	說明
sttContext	string	否	
sttContextLlmId	string (uuid)	否	
offlineTranscriptProviderId	string (uuid)	是	
asrOptions	object	否	Nested ASR selection shared by every ASR entry point: languages (at least one), provider payload keys governed by the provider row request_option_specs contract, and the diarization selection (source ...
meetingName	string	是	
audioFilePath	string	是	
clientSurface	object	否	Client uploading the audio. Omitting it stays unknown instead of claiming web. `unknown` : Unknown ; `web` : Web ; `desktop` : Desktop;

請求結構範例

```
{
  "sttContext"?: string // 非必填
  "sttContextLlmId"?: string (uuid) // 非必填
  "offlineTranscriptProviderId": string (uuid)
  "asrOptions"?: object // Nested ASR selection shared by every ASR entry point: languages (at least one), provider payload keys governed by the provider row request_option_specs contract, and the diarization selection (source / provider_id / options). (非必填)
  "meetingName": string
  "audioFilePath": string
  "clientSurface"?:  // Client uploading the audio. Omitting it stays unknown instead of claiming web.

* `unknown` - Unknown
* `web` - Web
* `desktop` - Desktop (非必填)
  {
  }
}
```

請求範例值

```
{
  "meeting_name": "客戶訪談錄音",
  "audio_file_path": "media/chatbot-file/2026/06/customer-interview.m4a",
  "offline_transcript_provider_id": "c8dc9f8a-2b5e-4a2d-8f93-1a2b3c4d5e6f",
  "asr_options": {
    "languages": [
      "zh-TW"
    ],
    "diarization": {
      "source": "model",
      "provider_id": "a1b2c3d4-e5f6-7890-abcd-ef1234567890"
    }
  }
}
```

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X POST "https://api.maiagent.ai/api/v1/meeting-records/import-audio/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "meeting_name": "客戶訪談錄音",
    "audio_file_path": "media/chatbot-file/2026/06/customer-interview.m4a",
    "offline_transcript_provider_id": "c8dc9f8a-2b5e-4a2d-8f93-1a2b3c4d5e6f",
    "asr_options": {
      "languages": [
        "zh-TW"
      ],
      "diarization": {
        "source": "model",
        "provider_id": "a1b2c3d4-e5f6-7890-abcd-ef1234567890"
      }
    }
  }'

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// 請求內容 (payload)
const data = {
    "meeting_name": "客戶訪談錄音",
    "audio_file_path": "media/chatbot-file/2026/06/customer-
interview.m4a",
    "offline_transcript_provider_id": "c8dc9f8a-2b5e-4a2d-8f93-
1a2b3c4d5e6f",
    "asr_options": {
      "languages": [
        "zh-TW"
      ],
      "diarization": {
        "source": "model",
        "provider_id": "a1b2c3d4-e5f6-7890-abcd-ef1234567890"
      }
    }
  };

axios.post("https://api.maiagent.ai/api/v1/meeting-records/import-
audio/", data, config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/meeting-records/import-audio/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# 請求內容 (payload)
data = {
    "meeting_name": "客戶訪談錄音",
    "audio_file_path": "media/chatbot-file/2026/06/customer-
interview.m4a",
    "offline_transcript_provider_id": "c8dc9f8a-2b5e-4a2d-8f93-
1a2b3c4d5e6f",
    "asr_options": {
        "languages": [
            "zh-TW"
        ],
        "diarization": {
            "source": "model",
            "provider_id": "a1b2c3d4-e5f6-7890-abcd-ef1234567890"
        }
    }
}

response = requests.post(url, json=data, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->post("https://api.maiagent.ai/api/v1/meeting-records/import-audio/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'meeting_name' => '客戶訪談錄音',
            'audio_file_path' => 'media/chatbot-file/2026/06/customer-interview.m4a',
            'offline_transcript_provider_id' => 'c8dc9f8a-2b5e-4a2d-8f93-1a2b3c4d5e6f',
            'asr_options' => [
                'languages' => [
                    'zh-TW'
                ],
                'diarization' => [
                    'source' => 'model',
                    'provider_id' => 'a1b2c3d4-e5f6-7890-abcd-ef1234567890'
                ]
            ]
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 202

回應結構範例

```
{
  "id": string (uuid)
  "sttContext"?: string // 非必填
  "sttContextLlmId"?: string (uuid) // 非必填
  "liveTranscriptionResult": object
  "eventContext"?: object // 非必填
  "meetingRecordSttProvider":
  {
    "id": string (uuid)
    "name": string // Display name for this STT provider
    "provider": string (enum: whisperlive, azure, deepgram, assemblyai,
bronci, alibaba, localai, openai, rap) // * `whisperlive` - Whisperlive
* `azure` - Azure
* `deepgram` - Deepgram
* `assemblyai` - Assemblyai
* `bronci` - Bronci
* `alibaba` - Alibaba
* `localai` - Localai
* `openai` - Openai
* `rap` - Rap
    "modelName": string
  }
  "offlineTranscriptProviderDetail":
  {
    "id": string (uuid)
    "name": string // Display name for this provider
    "provider": string (enum: whisper_openai, whisper_groq,
whisper_offline, localai, azure, bronci, alibaba, rap, deepgram,
assemblyai) // * `whisper_openai` - whisper_openai
* `whisper_groq` - whisper_groq
* `whisper_offline` - whisper_offline
```

```
* `localai` - localai
* `azure` - azure
* `bronci` - bronci
* `alibaba` - alibaba
* `rap` - rap
* `deepgram` - deepgram
* `assemblyai` - assemblyai
    "modelName": string // Free-form vendor model identifier; any string
the vendor deployment accepts is valid.
  }
  "meetingRecordSttProviderId"?: string (uuid) // 非必填
  "speakerDiarizationProvider":
  {
    "id": string (uuid)
    "name": string // Display name for this provider
    "provider": string (enum: pyannoteai) // * `pyannoteai` - pyannoteai
    "modelName": string // Free-form vendor model identifier; any string
the vendor deployment accepts is valid.
  }
  "enableTranslation"?: boolean // 非必填
  "targetLanguages"?: [ // Target language codes for live transcript
translation. (非必填)
    string
  ]
  "translationLlmId"?: string (uuid) // 非必填
  "knowledgeBaseId"?: string (uuid) // 非必填
  "audioUrl": string
  "transcriptUrl": string
  "mp3Url": string
  "backupAudioUrl": string
  "backupSyncStatus": string
  "backupUnavailableReason": string
  "backupError": object
  "backupDurationSeconds": number (double)
  "backupTotalParts": integer
  "backupTotalChunks": integer
  "backupRecordingStartedAt": string (timestamp)
  "backupLastActivityAt": string (timestamp)
  "backupFinalizedAt": string (timestamp)
  "knowledgeBase": object
  "transcriptFile": object
  "qaConfig": object // Generate qa_config for frontend to use with
chatbot completion API.
  "availableChatbots": [ // Get chatbots that have this meeting's
knowledge base (detail view only).
```

```
    object
  ]
  "createdBy":
  {
    "id": string (uuid)
    "name": string
  }
  "members": [ // The meeting's access roster, visible to anyone who can
see the meeting.

Editing (add/remove) is gated separately on the members endpoint; here
the
list is read-only context so members can see who participated and who
else
was granted view access.
    object
  ]
  "myRole": string // The requesting user's role on this meeting, or None
if not a member.
  "createdAt": string (timestamp)
  "updatedAt": string (timestamp)
  "meetingName": string
  "participants"?: object // List of meeting participants (非必填)
  "durationSeconds"?: number (double) // 非必填
  "status"?: string (enum: pending, recording, processing, completed,
failed) // * `pending` - Pending
* `recording` - Recording
* `processing` - Processing
* `completed` - Completed
* `failed` - Failed (非必填)
  "stopRequestedAt": string (timestamp) // When a user explicitly
requested to stop the recording. A finished recording without this set
ended on the server side (e.g. the client connection was lost).
  "recordingLimitReachedAt": string (timestamp) // When LiveKit ended the
egress at its maximum recording duration. The main audio file ends here;
the STT agent and the browser backup keep going until the room closes,
and the meeting completes on room end.
  "failureReason": // 可能有不同的類型
  string (enum: egress_not_started, egress_failed, finalize_timeout) //
Why the live recording ended as failed. Empty for meetings that did not
fail.

* `` - None
* `egress_not_started` - Recording did not start
* `egress_failed` - Recording failed
```

```
* `finalize_timeout` - Recording was never finalized
  "clientSurface":  // Durable client entry point captured when recording
starts. Legacy records remain unknown.

* `unknown` - Unknown
* `web` - Web
* `desktop` - Desktop
  {
  }
  "requestedSourceMode":  // Audio source mode requested by the client
when recording starts.

* `unknown` - Unknown
* `microphone` - Microphone
* `system_audio` - System Audio
* `both` - Microphone and System Audio
  {
  }
  "effectiveSourceMode":  // Server-resolved audio source mode used for
runtime and billing reconciliation.

* `unknown` - Unknown
* `microphone` - Microphone
* `system_audio` - System Audio
* `both` - Microphone and System Audio
  {
  }
  "sourceLanguages"?: object // Source languages for transcription (非必
填)
  "speakerDiarizationConfig": object // Per-meeting non-secret speaker
diarization hints, such as numSpeakers.
  "offlineAsrRequestOptions": object // Per-request ASR payload for the
offline audio import, keyed by the selected provider row
request_option_specs contract. EMPTY MEANS: no extra parameters.
  "audioProcessingSnapshot": object // Immutable audio processing policy
snapshot frozen from the platform active profile at meeting start (via
MeetingAudioProcessingProfile.to_snapshot). Downlinked to the LiveKit
Agent with this meeting client/source facts and used to correlate per-
track usage.
  "translationInputTokens"?: integer (int64) // Cumulative LLM input
tokens consumed by realtime translation. Atomically incremented per
translate() call; settled at egress completion. (非必填)
  "translationOutputTokens"?: integer (int64) // Cumulative LLM output
tokens consumed by realtime translation. (非必填)
  "deletedAt"?: string (timestamp) // 非必填
```

```
  "translationLlm"?: string (uuid) // LLM model to use for translation
when enabled (非必填)
}
```

回應範例值


```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "sttContext": "回應字串",
  "sttContextLlmId": "550e8400-e29b-41d4-a716-446655440000",
  "liveTranscriptionResult": null,
  "eventContext": null,
  "meetingRecordSttProvider": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應字串",
    "provider": "whisperlive",
    "modelName": "回應字串"
  },
  "offlineTranscriptProviderDetail": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應字串",
    "provider": "whisper_openai",
    "modelName": "回應字串"
  },
  "meetingRecordSttProviderId": "550e8400-e29b-41d4-a716-446655440000",
  "speakerDiarizationProvider": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應字串",
    "provider": "pyannoteai",
    "modelName": "回應字串"
  },
  "enableTranslation": false,
  "targetLanguages": [
    "回應字串"
  ],
  "translationLlmId": "550e8400-e29b-41d4-a716-446655440000",
  "knowledgeBaseId": "550e8400-e29b-41d4-a716-446655440000",
  "audioUrl": "回應字串",
  "transcriptUrl": "回應字串",
  "mp3Url": "回應字串",
  "backupAudioUrl": "回應字串",
  "backupSyncStatus": "回應字串",
  "backupUnavailableReason": "回應字串",
  "backupError": {
```

```
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應範例名稱",
    "description": "回應範例描述"
  },
  "backupDurationSeconds": 456,
  "backupTotalParts": 456,
  "backupTotalChunks": 456,
  "backupRecordingStartedAt": "回應字串",
  "backupLastActivityAt": "回應字串",
  "backupFinalizedAt": "回應字串",
  "knowledgeBase": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應範例名稱",
    "description": "回應範例描述"
  },
  "transcriptFile": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應範例名稱",
    "description": "回應範例描述"
  },
  "qaConfig": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應範例名稱",
    "description": "回應範例描述"
  },
  "availableChatbots": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "回應範例名稱",
      "description": "回應範例描述"
    }
  ],
  "createdBy": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應字串"
  },
  "members": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "回應範例名稱",
      "description": "回應範例描述"
    }
  ],
  "myRole": "回應字串",
  "createdAt": "回應字串",
```

```
  "updatedAt": "回應字串",
  "meetingName": "回應字串",
  "participants": null,
  "durationSeconds": 456,
  "status": "pending",
  "stopRequestedAt": "回應字串",
  "recordingLimitReachedAt": "回應字串",
  "failureReason": "egress_not_started",
  "clientSurface": {},
  "requestedSourceMode": {},
  "effectiveSourceMode": {},
  "sourceLanguages": null,
  "speakerDiarizationConfig": null,
  "offlineAsrRequestOptions": null,
  "audioProcessingSnapshot": null,
  "translationInputTokens": 456,
  "translationOutputTokens": 456,
  "deletedAt": "回應字串",
  "translationLlm": "550e8400-e29b-41d4-a716-446655440000"
}
```


取得會議逐字稿（JSON）

`GET` `/api/v1/meeting-records/{id}/transcript/`

參數

參數名稱	必填	類型	說明
id	V	string	A UUID string identifying this Meeting Record.

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/meeting-
records/550e8400-e29b-41d4-a716-446655440000/transcript/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/meeting-records/550e8400-
e29b-41d4-a716-446655440000/transcript/", config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/meeting-records/550e8400-e29b-41d4-a716-446655440000/transcript/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/meeting-records/550e8400-e29b-
41d4-a716-446655440000/transcript/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
object
```

回應範例值


```
[
  {
    "id": "9f4a0a46-1c67-45fc-b2d0-35b0f2bb5a2e",
    "type": "final",
    "text": "今天先確認會議摘要流程。",
    "startTime": 0,
    "endTime": 2.5,
    "language": "zh-TW"
  }
]
```


狀態碼: 400 - No response body

列出會議摘要

GET `/api/v1/meeting-records/{meetingRecordPk}/summaries/`

參數

參數名稱	必填	類型	說明
`meetingRecordPk`	V	string	
`page`	X	integer	A page number within the paginated result set.
`pageSize`	X	integer	Number of results to return per page.

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/meeting-
records/{meetingRecordPk}/summaries/?page=1&pageSize=1"

  -H "Authorization: Api-Key YOUR_API_KEY"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/meeting-
records/{meetingRecordPk}/summaries/?page=1&pageSize=1", config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/meeting-
records/{meetingRecordPk}/summaries/?page=1&pageSize=1"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/meeting-
records/{meetingRecordPk}/summaries/?page=1&pageSize=1", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
{
  "count": integer
  "next"?: string (uri) // 非必填
```

```
  "previous"?: string (uri) // 非必填
  "results": [
    {
      "id": string (uuid)
      "content"?: string // Summary content; empty while a background
generation is in progress. (非必填)
      "status":  // Manual create/edit rows stay completed; background
generations walk from pending to processing.

* `pending` - Pending
* `processing` - Processing
* `completed` - Completed
* `failed` - Failed
      {
      }
      "failureReason": string // Why the last save/generation failed, for
both AI-generated and manually-edited summaries.
      "completedSegments": integer
      "totalSegments": integer
      "transcriptOptimization": string (uuid) // Which re-transcribed
pass this summary was generated from. Null means the meeting's own
realtime transcript, which is the only other source a summary can have.
      "createdAt": string (timestamp)
      "updatedAt": string (timestamp)
    }
  ]
}
```

回應範例值

```
{
  "count": 123,
  "next": "http://api.example.org/accounts/?page=4",
  "previous": "http://api.example.org/accounts/?page=2",
  "results": [
    {
      "id": "d1e2f3a4-b5c6-7890-abcd-ef1234567890",
      "content": "本次會議主要討論了產品開發進度，團隊確認了下週的里程碑目標...",
      "created_at": "2025-01-15T14:30:00Z",
      "updated_at": "2025-01-15T14:30:00Z"
    }
```

```
    ]
}
```

產生會議摘要

`POST` `/api/v1/meeting-records/{meetingRecordPk}/summaries/generate/`

參數

參數名稱	必填	類型	說明
`meetingRecordPk`	V	string	

請求內容

請求參數

欄位	類型	必填	說明
transcriptOptimizationId	string (uuid)	否	Optional re-transcribed pass to summarize, from GET /meeting-records/{id}/transcript-optimizations/; it must be completed and belong to this meeting. Omit it to summarize the meeting's own transcript.
chatbotId	string (uuid)	否	Optional summary agent; when set, the agent generates the summary itself, reading the transcript through the transcript-reading tool.

欄位	類型	必填	說明
largeLanguageModelId	string (uuid)	否	Optional LLM override for the base (no-agent) mode; mutually exclusive with chatbot_id, whose agent always uses its own configured model.
knowledgeBaseIds	array[string]	否	Optional RBAC-filtered knowledge base ids for the base (no-agent) mode; mutually exclusive with chatbot_id, whose agent always uses its own configured knowledge bases.
customInstructions	string	否	Optional extra instructions appended to the built-in summary prompt.
clientPlatform	object	否	Client platform triggering this generation; stamped on the summary conversation. `web` : Web ; `desktop` : Desktop;

請求結構範例

```
{
  "transcriptOptimizationId"?: string (uuid) // Optional re-transcribed pass to summarize, from GET /meeting-records/{id}/transcript-optimizations/; it must be completed and belong to this meeting. Omit it to summarize the meeting's own transcript. (非必填)
  "chatbotId"?: string (uuid) // Optional summary agent; when set, the agent generates the summary itself, reading the transcript through the transcript-reading tool. (非必填)
  "largeLanguageModelId"?: string (uuid) // Optional LLM override for the base (no-agent) mode; mutually exclusive with chatbot_id, whose agent always uses its own configured model. (非必填)
  "knowledgeBaseIds"?: [ // Optional RBAC-filtered knowledge base ids for the base (no-agent) mode; mutually exclusive with chatbot_id, whose agent always uses its own configured knowledge bases. (非必填)
    string (uuid)
  ]
  "customInstructions"?: string // Optional extra instructions appended to the built-in summary prompt. (非必填)
  "clientPlatform"?:  // Client platform triggering this generation; stamped on the summary conversation.
```

```
* `web` - Web
* `desktop` - Desktop (非必填)
  {
  }
}
```

請求範例值

```
{
  "transcriptOptimizationId": "550e8400-e29b-41d4-a716-446655440000",
  "chatbotId": "550e8400-e29b-41d4-a716-446655440000",
  "largeLanguageModelId": "550e8400-e29b-41d4-a716-446655440000",
  "knowledgeBaseIds": [
    "550e8400-e29b-41d4-a716-446655440000"
  ],
  "customInstructions": "範例字串",
  "clientPlatform": {}
}
```

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X POST "https://api.maiagent.ai/api/v1/meeting-
records/{meetingRecordPk}/summaries/generate/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "transcriptOptimizationId": "550e8400-e29b-41d4-a716-
446655440000",
    "chatbotId": "550e8400-e29b-41d4-a716-446655440000",
    "largeLanguageModelId": "550e8400-e29b-41d4-a716-446655440000",
    "knowledgeBaseIds": [
      "550e8400-e29b-41d4-a716-446655440000"
    ],
    "customInstructions": "範例字串",
    "clientPlatform": {}
  }'

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// 請求內容 (payload)
const data = {
    "transcriptOptimizationId": "550e8400-e29b-41d4-a716-
446655440000",
    "chatbotId": "550e8400-e29b-41d4-a716-446655440000",
    "largeLanguageModelId": "550e8400-e29b-41d4-a716-446655440000",
    "knowledgeBaseIds": [
      "550e8400-e29b-41d4-a716-446655440000"
    ],
    "customInstructions": "範例字串",
    "clientPlatform": {}
  };

axios.post("https://api.maiagent.ai/api/v1/meeting-
records/{meetingRecordPk}/summaries/generate/", data, config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/meeting-
records/{meetingRecordPk}/summaries/generate/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# 請求內容 (payload)
data = {
    "transcriptOptimizationId": "550e8400-e29b-41d4-a716-
446655440000",
    "chatbotId": "550e8400-e29b-41d4-a716-446655440000",
    "largeLanguageModelId": "550e8400-e29b-41d4-a716-446655440000",
    "knowledgeBaseIds": [
        "550e8400-e29b-41d4-a716-446655440000"
    ],
    "customInstructions": "範例字串",
    "clientPlatform": {}
}

response = requests.post(url, json=data, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>post("https://api.maiagent.ai/api/v1/meeting-
records/{meetingRecordPk}/summaries/generate/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'transcriptOptimizationId' => '550e8400-e29b-41d4-a716-
446655440000',
            'chatbotId' => '550e8400-e29b-41d4-a716-446655440000',
            'largeLanguageModelId' => '550e8400-e29b-41d4-a716-
446655440000',
            'knowledgeBaseIds' => [
                '550e8400-e29b-41d4-a716-446655440000'
            ],
            'customInstructions' => '範例字串',
            'clientPlatform' => new \stdClass()
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
{
  "id": string (uuid)
  "content"?: string // Summary content; empty while a background
generation is in progress. (非必填)
  "status":  // Manual create/edit rows stay completed; background
generations walk from pending to processing.

* `pending` - Pending
* `processing` - Processing
* `completed` - Completed
* `failed` - Failed
  {
  }
  "failureReason": string // Why the last save/generation failed, for
both AI-generated and manually-edited summaries.
  "completedSegments": integer
  "totalSegments": integer
  "transcriptOptimization": string (uuid) // Which re-transcribed pass
this summary was generated from. Null means the meeting's own realtime
transcript, which is the only other source a summary can have.
  "createdAt": string (timestamp)
  "updatedAt": string (timestamp)
}
```

回應範例值

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "content": "回應字串",
  "status": {},
  "failureReason": "回應字串",
  "completedSegments": 456,
  "totalSegments": 456,
  "transcriptOptimization": "550e8400-e29b-41d4-a716-446655440000",
  "createdAt": "回應字串",
```

```
  "updatedAt": "回應字串"
}
```

狀態碼: 202

回應結構範例

```
{
  "id": string (uuid)
  "content"?: string // Summary content; empty while a background
generation is in progress. (非必填)
  "status":  // Manual create/edit rows stay completed; background
generations walk from pending to processing.

* `pending` - Pending
* `processing` - Processing
* `completed` - Completed
* `failed` - Failed
  {
  }
  "failureReason": string // Why the last save/generation failed, for
both AI-generated and manually-edited summaries.
  "completedSegments": integer
  "totalSegments": integer
  "transcriptOptimization": string (uuid) // Which re-transcribed pass
this summary was generated from. Null means the meeting's own realtime
transcript, which is the only other source a summary can have.
  "createdAt": string (timestamp)
  "updatedAt": string (timestamp)
}
```

回應範例值

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "content": "回應字串",
  "status": {},
  "failureReason": "回應字串",
  "completedSegments": 456,
  "totalSegments": 456,
  "transcriptOptimization": "550e8400-e29b-41d4-a716-446655440000",
  "createdAt": "回應字串",
```

```
  "updatedAt": "回應字串"
}
```

取得特定會議摘要

GET `/api/v1/meeting-records/{meetingRecordPk}/summaries/{id}`

參數

參數名稱	必填	類型	說明
`id`	V	string	
`meetingRecordPk`	V	string	

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/meeting-
records/{meetingRecordPk}/summaries/550e8400-e29b-41d4-a716-
446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/meeting-
records/{meetingRecordPk}/summaries/550e8400-e29b-41d4-a716-
446655440000/", config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/meeting-
records/{meetingRecordPk}/summaries/550e8400-e29b-41d4-a716-
446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/meeting-
records/{meetingRecordPk}/summaries/550e8400-e29b-41d4-a716-
446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
{
  "id": string (uuid)
```

```
  "content"?: string // Summary content; empty while a background
generation is in progress. (非必填)
  "status":  // Manual create/edit rows stay completed; background
generations walk from pending to processing.

* `pending` - Pending
* `processing` - Processing
* `completed` - Completed
* `failed` - Failed
  {
  }
  "failureReason": string // Why the last save/generation failed, for
both AI-generated and manually-edited summaries.
  "completedSegments": integer
  "totalSegments": integer
  "transcriptOptimization": string (uuid) // Which re-transcribed pass
this summary was generated from. Null means the meeting's own realtime
transcript, which is the only other source a summary can have.
  "createdAt": string (timestamp)
  "updatedAt": string (timestamp)
}
```

回應範例值

```
{
  "id": "d1e2f3a4-b5c6-7890-abcd-ef1234567890",
  "content": "本次會議主要討論了產品開發進度，團隊確認了下週的里程碑目標...",
  "created_at": "2025-01-15T14:30:00Z",
  "updated_at": "2025-01-15T14:30:00Z"
}
```

上傳逐字稿到知識庫

POST `/api/v1/meeting-records/{id}/upload-transcript/`

首次上傳需帶 knowledge_base_id；知識庫中的逐字稿被刪除後可再呼叫重新上傳。

參數

參數名稱	必填	類型	說明
id	V	string	A UUID string identifying this Meeting Record.

請求內容

請求參數

欄位	類型	必填	說明
knowledgeBaseId	string (uuid)	否	Knowledge base ID to upload transcript to. If not provided, uses existing knowledge base.

請求結構範例

```
{
  "knowledgeBaseId"?: string (uuid) // Knowledge base ID to upload
transcript to. If not provided, uses existing knowledge base. (非必填)
}
```

請求範例值

```
{
  "knowledge_base_id": "b1c2d3e4-f5a6-7890-abcd-ef1234567890"
}
```

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X POST "https://api.maiagent.ai/api/v1/meeting-
records/550e8400-e29b-41d4-a716-446655440000/upload-transcript/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "knowledge_base_id": "b1c2d3e4-f5a6-7890-abcd-ef1234567890"
  }'

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// 請求內容 (payload)
const data = {
    "knowledge_base_id": "b1c2d3e4-f5a6-7890-abcd-ef1234567890"
  };

axios.post("https://api.maiagent.ai/api/v1/meeting-records/550e8400-
e29b-41d4-a716-446655440000/upload-transcript/", data, config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/meeting-records/550e8400-e29b-
41d4-a716-446655440000/upload-transcript/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# 請求內容 (payload)
data = {
    "knowledge_base_id": "b1c2d3e4-f5a6-7890-abcd-ef1234567890"
}

response = requests.post(url, json=data, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>post("https://api.maiagent.ai/api/v1/meeting-records/550e8400-e29b-
41d4-a716-446655440000/upload-transcript/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'knowledge_base_id' => 'b1c2d3e4-f5a6-7890-abcd-
ef1234567890'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼	說明
202	No response body

400	No response body
404	No response body

下載 SRT 字幕檔

`GET` `/api/v1/meeting-records/{id}/download-srt/`

參數

參數名稱	必填	類型	說明
id	V	string	A UUID string identifying this Meeting Record.

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/meeting-
records/550e8400-e29b-41d4-a716-446655440000/download-srt/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/meeting-records/550e8400-e29b-41d4-a716-446655440000/download-srt/", config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/meeting-records/550e8400-e29b-41d4-a716-446655440000/download-srt/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/meeting-records/550e8400-e29b-
41d4-a716-446655440000/download-srt/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200 - SRT 字幕檔內容

回應結構範例

```
string (binary)
```

回應範例值


```
"1\n00:00:00,000 --> 00:00:05,500\nWelcome to the
meeting\n\n2\n00:00:05,500 --> 00:00:10,200\nLet's begin the discussion"
```


狀態碼: 400 - No response body

下載 MP3 音檔

GET `/api/v1/meeting-records/{id}/download-mp3/`

參數

參數名稱	必填	類型	說明
id	V	string	A UUID string identifying this Meeting Record.

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/meeting-
records/550e8400-e29b-41d4-a716-446655440000/download-mp3/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/meeting-records/550e8400-
e29b-41d4-a716-446655440000/download-mp3/", config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/meeting-records/550e8400-e29b-41d4-a716-446655440000/download-mp3/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/meeting-records/550e8400-e29b-
41d4-a716-446655440000/download-mp3/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
{
  "downloadUrl": string (uri) // Presigned download URL
  "filename": string // Suggested filename
```

```
  "expiresIn": integer // URL expiration time in seconds
}
```

回應範例值

```
{
  "download_url": "https://s3.amazonaws.com/bucket/media/meeting-
record/xxx_mp3.mp3?X-Amz-...",
  "filename": "產品規劃會議_20250115.mp3",
  "expires_in": 3600
}
```

狀態碼: 400 - No response body

呼叫 API 示例 (Shell)

目錄

1. 建立知識庫
2. 列出所有知識庫
3. 取得特定知識庫詳情
4. 搜尋特定知識庫的內容
5. 更新知識庫
6. 部分更新知識庫
7. 刪除知識庫
8. 檢查 RRF 可用性
9. 匯出標籤 Excel
10. 匯入標籤 Excel
11. 匯出元資料 Excel
12. 匯入元資料 Excel
13. 建立新標籤
14. 列出知識庫中的標籤
15. 取得特定標籤詳情
16. 更新標籤
17. 部分更新標籤
18. 刪除標籤
19. 建立元資料欄位
20. 列出元資料欄位
21. 取得特定元資料欄位
22. 更新元資料欄位
23. 上傳檔案到知識庫
24. 更新檔案元資料
25. 批量刪除檔案
26. 批量重新解析檔案
27. 列出知識庫中的檔案
28. 取得特定檔案詳情
29. 取得檔案最新失敗原因
30. 取得檔案轉錄內容
31. 更新檔案資訊
32. 部分更新檔案
33. 刪除檔案
34. 建立檔案翻譯
35. 列出檔案翻譯

36. 取得特定翻譯
37. 刪除翻譯
38. 下載翻譯檔案
39. 列出知識庫文件
40. 更新文件
41. 部分更新文件
42. 刪除文件
43. 建立新的 FAQ
44. 更新 FAQ 元資料
45. 批量刪除 FAQ
46. 列出特定知識庫的所有 FAQ
47. 取得特定 FAQ 詳情
48. 更新 FAQ
49. 部分更新 FAQ
50. 刪除 FAQ
51. 匯出 FAQ Excel（或空白範本）
52. 匯入 FAQ Excel（非同步）
53. 列出 FAQ 匯入工作
54. 取得特定 FAQ 匯入工作
55. 列出解析器
56. 取得特定解析器

呼叫 API 示例 (Shell)

建立知識庫

`POST` `/api/v1/knowledge-bases/`

請求內容

請求參數

欄位	類型	必填	說明
embeddingModel	string (uuid)	是	
rerankerModel	string (uuid)	是	
name	string	是	
description	string	否	
numberOfRetrievedChunks	integer	否	提取的參考資料數量，預設為 12，最小值為 1
enableHyde	boolean	否	啟用 HyDE，預設為 False
similarityCutoff	number (double)	否	相似度門檻，預設為 0.0，範圍為 0.0-1.0
enableRerank	boolean	否	是否啟用重新排序，預設為 True
enableRrf	boolean	否	Enable Reciprocal Rank Fusion for hybrid search. Disable this if using a custom Elasticsearch without enterprise license. If not provided, uses system default.
vectorDatabaseType	object	否	Type of vector database: elasticsearch, opensearch, oracle or synxdb. Defaults to the platform-managed engine. `elasticsearch` : Elasticsearch ; `opensearch` : OpenSearch ; `oracle` : Oracle AI Database ...
vectorDatabaseUrl	string	否	Custom vector database endpoint URL or Oracle DSN. For Elasticsearch/OpenSearch: URL format (e.g., "https://host:9200"). For Oracle: DSN format (e.g., "host:1521/service_name").
vectorDatabaseApiKey	string	否	API Key for Elasticsearch. Not used for OpenSearch.
opensearchUsername	string	否	Username for OpenSearch Basic Auth.

欄位	類型	必填	說明
opensearchPassword	string	否	Password for OpenSearch Basic Auth.
oracleUser	string	否	Oracle database username.
oraclePassword	string	否	Oracle database password.
synxdbUser	string	否	SynxDB database username.
synxdbPassword	string	否	SynxDB database password.
chatbots	array[IdName]	否	
groups	array[IdName]	否	

請求結構範例

```
{
  "embeddingModel": string (uuid)
  "rerankerModel": string (uuid)
  "name": string
  "description"?: string // 非必填
  "numberOfRetrievedChunks"?: integer // 提取的參考資料數量，預設為 12，最小值為 1 (非必填)
  "enableHyde"?: boolean // 啟用 HyDE，預設為 False (非必填)
  "similarityCutoff"?: number (double) // 相似度門檻，預設為 0.0，範圍為 0.0-1.0 (非必填)
  "enableRerank"?: boolean // 是否啟用重新排序，預設為 True (非必填)
  "enableRrf"?: boolean // Enable Reciprocal Rank Fusion for hybrid search. Disable this if using a custom Elasticsearch without enterprise license. If not provided, uses system default. (非必填)
  "vectorDatabaseType"?:  // Type of vector database: elasticsearch, opensearch, oracle or synxdb. Defaults to the platform-managed engine.

* `elasticsearch` - Elasticsearch
* `opensearch` - OpenSearch
* `oracle` - Oracle AI Database 26ai
* `synxdb` - SynxDB (非必填)
  {
  }
  "vectorDatabaseUrl"?: string // Custom vector database endpoint URL or Oracle DSN. For Elasticsearch/OpenSearch: URL format (e.g., "https://host:9200"). For Oracle: DSN format (e.g.,
```

```
"host:1521/service_name"). (非必填)
  "vectorDatabaseApiKey"?: string // API Key for Elasticsearch. Not used
for OpenSearch. (非必填)
  "opensearchUsername"?: string // Username for OpenSearch Basic Auth. (非
必填)
  "opensearchPassword"?: string // Password for OpenSearch Basic Auth. (非
必填)
  "oracleUser"?: string // Oracle database username. (非必填)
  "oraclePassword"?: string // Oracle database password. (非必填)
  "synxdbUser"?: string // SynxDB database username. (非必填)
  "synxdbPassword"?: string // SynxDB database password. (非必填)
  "chatbots"?: [ // 非必填
    {
      "id": string (uuid)
    }
  ]
  "groups"?: [ // 非必填
    {
      "id": string (uuid)
    }
  ]
}
```

請求範例值

```
{
  "embeddingModel": "550e8400-e29b-41d4-a716-446655440000",
  "rerankerModel": "550e8400-e29b-41d4-a716-446655440000",
  "name": "範例名稱",
  "description": "範例字串",
  "numberOfRetrievedChunks": 123,
  "enableHyde": true,
  "similarityCutoff": 123,
  "enableRerank": true,
  "enableRrf": true,
  "vectorDatabaseType": {},
  "vectorDatabaseUrl": "範例字串",
  "vectorDatabaseApiKey": "範例字串",
  "opensearchUsername": "範例字串",
  "opensearchPassword": "範例字串",
  "oracleUser": "範例字串",
  "oraclePassword": "範例字串",
  "synxdbUser": "範例字串",
  "synxdbPassword": "範例字串",
```

```
  "chatbots": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000"
    }
  ],
  "groups": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000"
    }
  ]
}
```

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X POST "https://api.maiagent.ai/api/v1/knowledge-bases/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "embeddingModel": "550e8400-e29b-41d4-a716-446655440000",
    "rerankerModel": "550e8400-e29b-41d4-a716-446655440000",
    "name": "範例名稱",
    "description": "範例字串",
    "numberOfRetrievedChunks": 123,
    "enableHyde": true,
    "similarityCutoff": 123,
    "enableRerank": true,
    "enableRrf": true,
    "vectorDatabaseType": {},
    "vectorDatabaseUrl": "範例字串",
    "vectorDatabaseApiKey": "範例字串",
    "opensearchUsername": "範例字串",
    "opensearchPassword": "範例字串",
    "oracleUser": "範例字串",
    "oraclePassword": "範例字串",
    "synxdbUser": "範例字串",
    "synxdbPassword": "範例字串",
    "chatbots": [
      {
        "id": "550e8400-e29b-41d4-a716-446655440000"
      }
    ],
    "groups": [
      {
        "id": "550e8400-e29b-41d4-a716-446655440000"
      }
    ]
  }'

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// 請求內容 (payload)
const data = {
    "embeddingModel": "550e8400-e29b-41d4-a716-446655440000",
    "rerankerModel": "550e8400-e29b-41d4-a716-446655440000",
    "name": "範例名稱",
    "description": "範例字串",
    "numberOfRetrievedChunks": 123,
    "enableHyde": true,
    "similarityCutoff": 123,
    "enableRerank": true,
    "enableRrf": true,
    "vectorDatabaseType": {},
    "vectorDatabaseUrl": "範例字串",
    "vectorDatabaseApiKey": "範例字串",
    "opensearchUsername": "範例字串",
    "opensearchPassword": "範例字串",
    "oracleUser": "範例字串",
    "oraclePassword": "範例字串",
    "synxdbUser": "範例字串",
    "synxdbPassword": "範例字串",
    "chatbots": [
      {
        "id": "550e8400-e29b-41d4-a716-446655440000"
      }
    ],
    "groups": [
      {
        "id": "550e8400-e29b-41d4-a716-446655440000"
      }
    ]
```

```
  };

axios.post("https://api.maiagent.ai/api/v1/knowledge-bases/", data,
config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/knowledge-bases/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# 請求內容 (payload)
data = {
    "embeddingModel": "550e8400-e29b-41d4-a716-446655440000",
    "rerankerModel": "550e8400-e29b-41d4-a716-446655440000",
    "name": "範例名稱",
    "description": "範例字串",
    "numberOfRetrievedChunks": 123,
    "enableHyde": True,
    "similarityCutoff": 123,
    "enableRerank": True,
    "enableRrf": True,
    "vectorDatabaseType": {},
    "vectorDatabaseUrl": "範例字串",
    "vectorDatabaseApiKey": "範例字串",
    "opensearchUsername": "範例字串",
    "opensearchPassword": "範例字串",
    "oracleUser": "範例字串",
    "oraclePassword": "範例字串",
    "synxdbUser": "範例字串",
    "synxdbPassword": "範例字串",
    "chatbots": [
        {
            "id": "550e8400-e29b-41d4-a716-446655440000"
        }
    ],
    "groups": [
        {
            "id": "550e8400-e29b-41d4-a716-446655440000"
        }
    ]
}
```

```
response = requests.post(url, json=data, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>post("https://api.maiagent.ai/api/v1/knowledge-bases/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'embeddingModel' => '550e8400-e29b-41d4-a716-
446655440000',
            'rerankerModel' => '550e8400-e29b-41d4-a716-
446655440000',
            'name' => '範例名稱',
            'description' => '範例字串',
            'numberOfRetrievedChunks' => 123,
            'enableHyde' => true,
            'similarityCutoff' => 123,
            'enableRerank' => true,
            'enableRrf' => true,
            'vectorDatabaseType' => new \stdClass(),
            'vectorDatabaseUrl' => '範例字串',
            'vectorDatabaseApiKey' => '範例字串',
            'opensearchUsername' => '範例字串',
            'opensearchPassword' => '範例字串',
            'oracleUser' => '範例字串',
            'oraclePassword' => '範例字串',
            'synxdbUser' => '範例字串',
            'synxdbPassword' => '範例字串',
            'chatbots' => [
                [
                    'id' => '550e8400-e29b-41d4-a716-446655440000'
                ]
            ],
            'groups' => [
                [
```

```
                    'id' => '550e8400-e29b-41d4-a716-446655440000'
                ]
            ]
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 201

回應結構範例

```
{
  "id": string (uuid)
  "createdBy":
  {
    "id": string (uuid)
    "name": string
  }
  "organization"?: string (uuid) // 非必填
  "embeddingModel": string (uuid)
  "rerankerModel": string (uuid)
  "name": string
  "description"?: string // 非必填
  "numberOfRetrievedChunks"?: integer // 提取的參考資料數量，預設為 12，最小值為 1 (非必填)
  "enableHyde"?: boolean // 啟用 HyDE，預設為 False (非必填)
  "similarityCutoff"?: number (double) // 相似度門檻，預設為 0.0，範圍為 0.0-1.0 (非必填)
```

```
  "enableRerank"?: boolean // 是否啟用重新排序，預設為 True (非必填)
  "enableRrf"?: boolean // Enable Reciprocal Rank Fusion for hybrid
search. Disable this if using a custom Elasticsearch without enterprise
license. (非必填)
  "vectorDatabaseType"?:  // Type of vector database: elasticsearch or
opensearch.

* `elasticsearch` - Elasticsearch
* `opensearch` - OpenSearch
* `oracle` - Oracle AI Database 26ai
* `synxdb` - SynxDB (非必填)
  {
  }
  "vectorDatabaseUrl"?: string // Custom vector database endpoint URL or
Oracle DSN. For Elasticsearch/OpenSearch: URL format (e.g.,
"https://host:9200"). For Oracle: DSN format (e.g.,
"host:1521/service_name"). (非必填)
  "vectorDatabaseApiKey"?: string // API Key for Elasticsearch. Not used
for OpenSearch. (非必填)
  "opensearchUsername"?: string // Username for OpenSearch Basic Auth. (非
必填)
  "opensearchPassword"?: string // Password for OpenSearch Basic Auth. (非
必填)
  "oracleUser"?: string // Oracle database username. (非必填)
  "oraclePassword"?: string // Oracle database password. (非必填)
  "synxdbUser"?: string // SynxDB database username. (非必填)
  "synxdbPassword"?: string // SynxDB database password. (非必填)
  "labels": [
    {
      "id": string (uuid)
      "name": string
    }
  ]
  "chatbots"?: [ // 非必填
    {
      "id": string (uuid)
      "name": string
    }
  ]
  "groups"?: [ // 知識庫可存取的群組列表 (非必填)
    {
      "id": string (uuid)
      "name": string
    }
  ]
```

```
  "filesCount": integer // Return count of KnowledgeBaseFile excluding
processed files, conversation attachments, and soft-deleted.
  "vectorStorageSize": integer
  "chunksCount": integer
  "canUpdate": boolean // Return whether the current user can update this
resource.
  "canDelete": boolean // Return whether the current user can delete this
resource.
  "createdAt": string (timestamp)
  "updatedAt": string (timestamp)
}
```

回應範例值

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "createdBy": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應字串"
  },
  "organization": "550e8400-e29b-41d4-a716-446655440000",
  "embeddingModel": "550e8400-e29b-41d4-a716-446655440000",
  "rerankerModel": "550e8400-e29b-41d4-a716-446655440000",
  "name": "回應字串",
  "description": "回應字串",
  "numberOfRetrievedChunks": 456,
  "enableHyde": false,
  "similarityCutoff": 456,
  "enableRerank": false,
  "enableRrf": false,
  "vectorDatabaseType": {},
  "vectorDatabaseUrl": "回應字串",
  "vectorDatabaseApiKey": "回應字串",
  "opensearchUsername": "回應字串",
  "opensearchPassword": "回應字串",
  "oracleUser": "回應字串",
  "oraclePassword": "回應字串",
  "synxdbUser": "回應字串",
  "synxdbPassword": "回應字串",
  "labels": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "回應字串"
    }
```

```
  ],
  "chatbots": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "回應字串"
    }
  ],
  "groups": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "回應字串"
    }
  ],
  "filesCount": 456,
  "vectorStorageSize": 456,
  "chunksCount": 456,
  "canUpdate": false,
  "canDelete": false,
  "createdAt": "回應字串",
  "updatedAt": "回應字串"
}
```


列出所有知識庫

GET `/api/v1/knowledge-bases/`

參數

參數名稱	必填	類型	說明
`embeddingModel`	X	string	
`page`	X	integer	A page number within the paginated result set.
`pageSize`	X	integer	Number of results to return per page.

`query`	X	string	
`rerankerModel`	X	string	

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/knowledge-bases/?
embeddingModel=550e8400-e29b-41d4-a716-
446655440000&page=1&pageSize=1&query=example&rerankerModel=550e8400-
e29b-41d4-a716-446655440000"

  -H "Authorization: Api-Key YOUR_API_KEY"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/knowledge-bases/?
embeddingModel=550e8400-e29b-41d4-a716-
446655440000&page=1&pageSize=1&query=example&rerankerModel=550e8400-
e29b-41d4-a716-446655440000", config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/knowledge-bases/?
embeddingModel=550e8400-e29b-41d4-a716-
446655440000&page=1&pageSize=1&query=example&rerankerModel=550e8400-
e29b-41d4-a716-446655440000"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/knowledge-bases/?
embeddingModel=550e8400-e29b-41d4-a716-
446655440000&page=1&pageSize=1&query=example&rerankerModel=550e8400-
e29b-41d4-a716-446655440000", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
{
  "count": integer
  "next"?: string (uri) // 非必填
  "previous"?: string (uri) // 非必填
  "results": [
    {
      "id": string (uuid)
      "createdBy":
      {
        "id": string (uuid)
        "name": string
      }
      "organization"?: string (uuid) // 非必填
      "embeddingModel": string (uuid)
      "rerankerModel": string (uuid)
      "name": string
      "description"?: string // 非必填
      "numberOfRetrievedChunks"?: integer // 提取的參考資料數量，預設為 12，最小值為 1 (非必填)
      "enableHyde"?: boolean // 啟用 HyDE，預設為 False (非必填)
      "similarityCutoff"?: number (double) // 相似度門檻，預設為 0.0，範圍為 0.0-1.0 (非必填)
      "enableRerank"?: boolean // 是否啟用重新排序，預設為 True (非必填)
      "enableRrf"?: boolean // Enable Reciprocal Rank Fusion for hybrid search. Disable this if using a custom Elasticsearch without enterprise license. (非必填)
      "vectorDatabaseType"?:  // Type of vector database: elasticsearch or opensearch.

* `elasticsearch` - Elasticsearch
* `opensearch` - OpenSearch
* `oracle` - Oracle AI Database 26ai
* `synxdb` - SynxDB (非必填)
      {
      }
      "vectorDatabaseUrl"?: string // Custom vector database endpoint URL or Oracle DSN. For Elasticsearch/OpenSearch: URL format (e.g., "https://host:9200"). For Oracle: DSN format (e.g., "host:1521/service_name"). (非必填)
      "vectorDatabaseApiKey"?: string // API Key for Elasticsearch. Not used for OpenSearch. (非必填)
      "opensearchUsername"?: string // Username for OpenSearch Basic Auth. (非必填)
      "opensearchPassword"?: string // Password for OpenSearch Basic
```

```
Auth. (非必填)
      "oracleUser"?: string // Oracle database username. (非必填)
      "oraclePassword"?: string // Oracle database password. (非必填)
      "synxdbUser"?: string // SynxDB database username. (非必填)
      "synxdbPassword"?: string // SynxDB database password. (非必填)
      "labels": [
        {
          "id": string (uuid)
          "name": string
        }
      ]
      "chatbots"?: [ // 非必填
        {
          "id": string (uuid)
          "name": string
        }
      ]
      "groups"?: [ // 知識庫可存取的群組列表 (非必填)
        {
          "id": string (uuid)
          "name": string
        }
      ]
      "filesCount": integer // Return count of KnowledgeBaseFile
excluding processed files, conversation attachments, and soft-deleted.
      "vectorStorageSize": integer
      "chunksCount": integer
      "canUpdate": boolean // Return whether the current user can update
this resource.
      "canDelete": boolean // Return whether the current user can delete
this resource.
      "createdAt": string (timestamp)
      "updatedAt": string (timestamp)
    }
  ]
}
```

回應範例值

```
{
  "count": 123,
  "next": "http://api.example.org/accounts/?page=4",
  "previous": "http://api.example.org/accounts/?page=2",
  "results": [
```

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "createdBy": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應字串"
  },
  "organization": "550e8400-e29b-41d4-a716-446655440000",
  "embeddingModel": "550e8400-e29b-41d4-a716-446655440000",
  "rerankerModel": "550e8400-e29b-41d4-a716-446655440000",
  "name": "回應字串",
  "description": "回應字串",
  "numberOfRetrievedChunks": 456,
  "enableHyde": false,
  "similarityCutoff": 456,
  "enableRerank": false,
  "enableRrf": false,
  "vectorDatabaseType": {},
  "vectorDatabaseUrl": "回應字串",
  "vectorDatabaseApiKey": "回應字串",
  "opensearchUsername": "回應字串",
  "opensearchPassword": "回應字串",
  "oracleUser": "回應字串",
  "oraclePassword": "回應字串",
  "synxdbUser": "回應字串",
  "synxdbPassword": "回應字串",
  "labels": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "回應字串"
    }
  ],
  "chatbots": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "回應字串"
    }
  ],
  "groups": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "回應字串"
    }
  ],
  "filesCount": 456,
  "vectorStorageSize": 456,
```

```
      "chunksCount": 456,
      "canUpdate": false,
      "canDelete": false,
      "createdAt": "回應字串",
      "updatedAt": "回應字串"
    }
  ]
}
```


取得特定知識庫詳情

`GET` `/api/v1/knowledge-bases/{id}`

參數

參數名稱	必填	類型	說明
id	V	string	A UUID string identifying this Knowledge Base.

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/knowledge-
bases/550e8400-e29b-41d4-a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-
e29b-41d4-a716-446655440000/", config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-e29b-41d4-a716-446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-e29b-
41d4-a716-446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
{
  "id": string (uuid)
  "createdBy":
```

```
  {
    "id": string (uuid)
    "name": string
  }
  "organization"?: string (uuid) // 非必填
  "embeddingModel": string (uuid)
  "rerankerModel": string (uuid)
  "name": string
  "description"?: string // 非必填
  "numberOfRetrievedChunks"?: integer // 提取的參考資料數量，預設為 12，最小值為 1 (非必填)
  "enableHyde"?: boolean // 啟用 HyDE，預設為 False (非必填)
  "similarityCutoff"?: number (double) // 相似度門檻，預設為 0.0，範圍為 0.0-1.0 (非必填)
  "enableRerank"?: boolean // 是否啟用重新排序，預設為 True (非必填)
  "enableRrf"?: boolean // Enable Reciprocal Rank Fusion for hybrid search. Disable this if using a custom Elasticsearch without enterprise license. (非必填)
  "vectorDatabaseType"?:  // Type of vector database: elasticsearch or opensearch.

* `elasticsearch` - Elasticsearch
* `opensearch` - OpenSearch
* `oracle` - Oracle AI Database 26ai
* `synxdb` - SynxDB (非必填)
  {
  }
  "vectorDatabaseUrl"?: string // Custom vector database endpoint URL or Oracle DSN. For Elasticsearch/OpenSearch: URL format (e.g., "https://host:9200"). For Oracle: DSN format (e.g., "host:1521/service_name"). (非必填)
  "vectorDatabaseApiKey"?: string // API Key for Elasticsearch. Not used for OpenSearch. (非必填)
  "opensearchUsername"?: string // Username for OpenSearch Basic Auth. (非必填)
  "opensearchPassword"?: string // Password for OpenSearch Basic Auth. (非必填)
  "oracleUser"?: string // Oracle database username. (非必填)
  "oraclePassword"?: string // Oracle database password. (非必填)
  "synxdbUser"?: string // SynxDB database username. (非必填)
  "synxdbPassword"?: string // SynxDB database password. (非必填)
  "labels": [
    {
      "id": string (uuid)
      "name": string
```

```
    }
  ]
  "chatbots"?: [ // 非必填
    {
      "id": string (uuid)
      "name": string
    }
  ]
  "groups"?: [ // 知識庫可存取的群組列表 (非必填)
    {
      "id": string (uuid)
      "name": string
    }
  ]
  "filesCount": integer // Return count of KnowledgeBaseFile excluding
processed files, conversation attachments, and soft-deleted.
  "vectorStorageSize": integer
  "chunksCount": integer
  "canUpdate": boolean // Return whether the current user can update this
resource.
  "canDelete": boolean // Return whether the current user can delete this
resource.
  "createdAt": string (timestamp)
  "updatedAt": string (timestamp)
}
```

回應範例值

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "createdBy": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應字串"
  },
  "organization": "550e8400-e29b-41d4-a716-446655440000",
  "embeddingModel": "550e8400-e29b-41d4-a716-446655440000",
  "rerankerModel": "550e8400-e29b-41d4-a716-446655440000",
  "name": "回應字串",
  "description": "回應字串",
  "numberOfRetrievedChunks": 456,
  "enableHyde": false,
  "similarityCutoff": 456,
  "enableRerank": false,
  "enableRrf": false,
```

```
  "vectorDatabaseType": {},
  "vectorDatabaseUrl": "回應字串",
  "vectorDatabaseApiKey": "回應字串",
  "opensearchUsername": "回應字串",
  "opensearchPassword": "回應字串",
  "oracleUser": "回應字串",
  "oraclePassword": "回應字串",
  "synxdbUser": "回應字串",
  "synxdbPassword": "回應字串",
  "labels": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "回應字串"
    }
  ],
  "chatbots": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "回應字串"
    }
  ],
  "groups": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "回應字串"
    }
  ],
  "filesCount": 456,
  "vectorStorageSize": 456,
  "chunksCount": 456,
  "canUpdate": false,
  "canDelete": false,
  "createdAt": "回應字串",
  "updatedAt": "回應字串"
}
```


搜尋特定知識庫的內容

POST `/api/v1/knowledge-bases/{id}/search/`

參數

參數名稱	必填	類型	說明
`id`	V	string	A UUID string identifying this Knowledge Base.
`embeddingModel`	X	string	
`page`	X	integer	A page number within the paginated result set.
`pageSize`	X	integer	Number of results to return per page.
`query`	X	string	
`rerankerModel`	X	string	

請求內容

請求參數

欄位	類型	必填	說明
searchMode	object	否	Search mode: hybrid (default, vector + BM25), semantic (vector only), keyword (BM25 only) `hybrid` : Hybrid (vector + BM25) ; `semantic` : Semantic (vector only) ; `keyword` : Keyword (BM25 only);
queryMetadata	object	否	查詢元數據，用於控制搜尋範圍和方式

請求結構範例

```
{
  "searchMode"?:  // Search mode: hybrid (default, vector + BM25),
semantic (vector only), keyword (BM25 only)

* `hybrid` - Hybrid (vector + BM25)
* `semantic` - Semantic (vector only)
* `keyword` - Keyword (BM25 only) (非必填)
  {
  }
  "queryMetadata"?: object // 查詢元數據，用於控制搜尋範圍和方式 (非必填)
}
```

請求範例值

```
{
  "query": "如何使用API"
}
```

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X POST "https://api.maiagent.ai/api/v1/knowledge-
bases/550e8400-e29b-41d4-a716-446655440000/search/?
embeddingModel=550e8400-e29b-41d4-a716-
446655440000&page=1&pageSize=1&query=example&rerankerModel=550e8400-
e29b-41d4-a716-446655440000"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "query": "如何使用API"
  }'

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// 請求內容 (payload)
const data = {
    "query": "如何使用API"
  };

axios.post("https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-e29b-41d4-a716-446655440000/search/?embeddingModel=550e8400-e29b-41d4-a716-446655440000&page=1&pageSize=1&query=example&rerankerModel=550e8400-e29b-41d4-a716-446655440000", data, config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-e29b-41d4-a716-446655440000/search/?embeddingModel=550e8400-e29b-41d4-a716-446655440000&page=1&pageSize=1&query=example&rerankerModel=550e8400-e29b-41d4-a716-446655440000"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# 請求內容 (payload)
data = {
    "query": "如何使用API"
}

response = requests.post(url, json=data, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->post("https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-e29b-41d4-a716-446655440000/search/?embeddingModel=550e8400-e29b-41d4-a716-446655440000&page=1&pageSize=1&query=example&rerankerModel=550e8400-e29b-41d4-a716-446655440000", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'query' => '如何使用API'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
{
  "count": integer
  "next"?: string (uri) // 非必填
  "previous"?: string (uri) // 非必填
  "results": [
    {
      "id": string (uuid)
      "charactersCount": integer
      "hitsCount": integer
      "text": string
      "updatedAt": string (timestamp)
      "filename": string
      "chatbotFile": object // 返回 ChatbotFile 的完整資訊，包含檔案 URL 和類型，以支援前端圖片預覽
      "knowledgeBaseFile": object // 與 get_chatbot_file 相同，提供向後兼容
      "pageNumber": integer // Backward-compatible alias of ``page_start``.
      "pageStart": integer
      "pageEnd": integer
      "citationTitle": string // Source title shown on the inline citation hover card.
      "citationDescription": string // Source description shown on the inline citation hover card.
      "citationQuote": string // Quoted text snippet shown on the inline citation hover card.
      "hasImage": boolean // 判斷是否包含圖片（檢查檔案類型或 text 中的 Markdown 圖片）
      "imageUrl": string // 提取圖片 URL（優先使用檔案 URL，否則從 Markdown 提取）
      "displayText": string // 返回移除圖片 Markdown 標記的完整文字
      "displayTitle": string // 返回顯示標題（fallback: citation_title -> filename）
      "highlightedText": string // Return text with matched terms wrapped in ``<mark>`` tags.

Priority:
1. ES/OpenSearch native highlight (set by retrieve_api via ``_es_highlighted_text``)
2. Python regex fallback (keyword-based, works for all backends)
      "labels": [
        {
          "id": string (uuid)
          "name": string
```

```
        }
      ]
      "rawUserDefineMetadata"?: object // Metadata keys and values
defined by the user. (非必填)
      "metadataEnabledForSearch": object // Map each user-defined
metadata key on this node to whether it was sent into the LLM.

A key reaches the LLM only when its ``MetadataKey.enabled_for_search`` is
True *and*
the node carries a value for it. Since this maps over
``raw_user_define_metadata``
(the keys the cited-documents block displays, all of which have a value),
``enabled_for_search`` alone decides the flag. The source of truth is the
node's
knowledge base ``MetadataKey`` current setting, matching the AI Search
indicator.
      "startCharIdx": integer
      "endCharIdx": integer
    }
  ]
}
```

回應範例值

```
{
  "count": 123,
  "next": "http://api.example.org/accounts/?page=4",
  "previous": "http://api.example.org/accounts/?page=2",
  "results": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "charactersCount": 456,
      "hitsCount": 456,
      "text": "回應字串",
      "updatedAt": "回應字串",
      "filename": "回應字串",
      "chatbotFile": {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "name": "回應範例名稱",
        "description": "回應範例描述"
      },
      "knowledgeBaseFile": {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "name": "回應範例名稱",
```

```
          "description": "回應範例描述"
        },
        "pageNumber": 456,
        "pageStart": 456,
        "pageEnd": 456,
        "citationTitle": "回應字串",
        "citationDescription": "回應字串",
        "citationQuote": "回應字串",
        "hasImage": false,
        "imageUrl": "回應字串",
        "displayText": "回應字串",
        "displayTitle": "回應字串",
        "highlightedText": "回應字串",
        "labels": [
          {
            "id": "550e8400-e29b-41d4-a716-446655440000",
            "name": "回應字串"
          }
        ],
        "rawUserDefineMetadata": null,
        "metadataEnabledForSearch": {
          "key1": "value1",
          "key2": "value2",
          "createdAt": "2025-01-01T00:00:00.000Z"
        },
        "startCharIdx": 456,
        "endCharIdx": 456
      }
    ]
}
```


更新知識庫

PUT `/api/v1/knowledge-bases/{id}`

參數

參數名稱	必填	類型	說明
`id`	V	string	A UUID string identifying this Knowledge Base.

請求內容

請求參數

欄位	類型	必填	說明
organization	string (uuid)	否	
embeddingModel	string (uuid)	是	
rerankerModel	string (uuid)	是	
name	string	是	
description	string	否	
numberOfRetrievedChunks	integer	否	提取的參考資料數量，預設為 12，最小值為 1
enableHyde	boolean	否	啟用 HyDE，預設為 False
similarityCutoff	number (double)	否	相似度門檻，預設為 0.0，範圍為 0.0-1.0
enableRerank	boolean	否	是否啟用重新排序，預設為 True
enableRrf	boolean	否	Enable Reciprocal Rank Fusion for hybrid search. Disable this if using a custom Elasticsearch without enterprise license.
vectorDatabaseType	object	否	Type of vector database: elasticsearch or opensearch. `elasticsearch` : Elasticsearch ; `opensearch` : OpenSearch ; `oracle` : Oracle AI Database 26ai ; `synxdb` : SynxDB;

欄位	類型	必填	說明
vectorDatabaseUrl	string	否	Custom vector database endpoint URL or Oracle DSN. For Elasticsearch/OpenSearch: URL format (e.g., "https://host:9200"). For Oracle: DSN format (e.g., "host:1521/service_name").
vectorDatabaseApiKey	string	否	API Key for Elasticsearch. Not used for OpenSearch.
opensearchUsername	string	否	Username for OpenSearch Basic Auth.
opensearchPassword	string	否	Password for OpenSearch Basic Auth.
oracleUser	string	否	Oracle database username.
oraclePassword	string	否	Oracle database password.
synxdbUser	string	否	SynxDB database username.
synxdbPassword	string	否	SynxDB database password.
chatbots	array[IdName]	否	
groups	array[IdName]	否	知識庫可存取的群組列表

請求結構範例

```
{
  "organization"?: string (uuid) // 非必填
  "embeddingModel": string (uuid)
  "rerankerModel": string (uuid)
  "name": string
  "description"?: string // 非必填
  "numberOfRetrievedChunks"?: integer // 提取的參考資料數量，預設為 12，最小值為 1 (非必填)
  "enableHyde"?: boolean // 啟用 HyDE，預設為 False (非必填)
  "similarityCutoff"?: number (double) // 相似度門檻，預設為 0.0，範圍為 0.0-1.0 (非必填)
  "enableRerank"?: boolean // 是否啟用重新排序，預設為 True (非必填)
  "enableRrf"?: boolean // Enable Reciprocal Rank Fusion for hybrid
```

```
search. Disable this if using a custom Elasticsearch without enterprise
license. (非必填)
  "vectorDatabaseType"?:  // Type of vector database: elasticsearch or
opensearch.

* `elasticsearch` - Elasticsearch
* `opensearch` - OpenSearch
* `oracle` - Oracle AI Database 26ai
* `synxdb` - SynxDB (非必填)
  {
  }
  "vectorDatabaseUrl"?: string // Custom vector database endpoint URL or
Oracle DSN. For Elasticsearch/OpenSearch: URL format (e.g.,
"https://host:9200"). For Oracle: DSN format (e.g.,
"host:1521/service_name"). (非必填)
  "vectorDatabaseApiKey"?: string // API Key for Elasticsearch. Not used
for OpenSearch. (非必填)
  "opensearchUsername"?: string // Username for OpenSearch Basic Auth. (非
必填)
  "opensearchPassword"?: string // Password for OpenSearch Basic Auth. (非
必填)
  "oracleUser"?: string // Oracle database username. (非必填)
  "oraclePassword"?: string // Oracle database password. (非必填)
  "synxdbUser"?: string // SynxDB database username. (非必填)
  "synxdbPassword"?: string // SynxDB database password. (非必填)
  "chatbots"?: [ // 非必填
    {
      "id": string (uuid)
    }
  ]
  "groups"?: [ // 知識庫可存取的群組列表 (非必填)
    {
      "id": string (uuid)
    }
  ]
}
```

請求範例值

```
{
  "organization": "550e8400-e29b-41d4-a716-446655440000",
  "embeddingModel": "550e8400-e29b-41d4-a716-446655440000",
  "rerankerModel": "550e8400-e29b-41d4-a716-446655440000",
  "name": "範例名稱",
```

```
  "description": "範例字串",
  "numberOfRetrievedChunks": 123,
  "enableHyde": true,
  "similarityCutoff": 123,
  "enableRerank": true,
  "enableRrf": true,
  "vectorDatabaseType": {},
  "vectorDatabaseUrl": "範例字串",
  "vectorDatabaseApiKey": "範例字串",
  "opensearchUsername": "範例字串",
  "opensearchPassword": "範例字串",
  "oracleUser": "範例字串",
  "oraclePassword": "範例字串",
  "synxdbUser": "範例字串",
  "synxdbPassword": "範例字串",
  "chatbots": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000"
    }
  ],
  "groups": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000"
    }
  ]
}
```


程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X PUT "https://api.maiagent.ai/api/v1/knowledge-
bases/550e8400-e29b-41d4-a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "organization": "550e8400-e29b-41d4-a716-446655440000",
    "embeddingModel": "550e8400-e29b-41d4-a716-446655440000",
    "rerankerModel": "550e8400-e29b-41d4-a716-446655440000",
    "name": "範例名稱",
    "description": "範例字串",
    "numberOfRetrievedChunks": 123,
    "enableHyde": true,
    "similarityCutoff": 123,
    "enableRerank": true,
    "enableRrf": true,
    "vectorDatabaseType": {},
    "vectorDatabaseUrl": "範例字串",
    "vectorDatabaseApiKey": "範例字串",
    "opensearchUsername": "範例字串",
    "opensearchPassword": "範例字串",
    "oracleUser": "範例字串",
    "oraclePassword": "範例字串",
    "synxdbUser": "範例字串",
    "synxdbPassword": "範例字串",
    "chatbots": [
      {
        "id": "550e8400-e29b-41d4-a716-446655440000"
      }
    ],
    "groups": [
      {
        "id": "550e8400-e29b-41d4-a716-446655440000"
      }
    ]
  }'
```

```
# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// 請求內容 (payload)
const data = {
    "organization": "550e8400-e29b-41d4-a716-446655440000",
    "embeddingModel": "550e8400-e29b-41d4-a716-446655440000",
    "rerankerModel": "550e8400-e29b-41d4-a716-446655440000",
    "name": "範例名稱",
    "description": "範例字串",
    "numberOfRetrievedChunks": 123,
    "enableHyde": true,
    "similarityCutoff": 123,
    "enableRerank": true,
    "enableRrf": true,
    "vectorDatabaseType": {},
    "vectorDatabaseUrl": "範例字串",
    "vectorDatabaseApiKey": "範例字串",
    "opensearchUsername": "範例字串",
    "opensearchPassword": "範例字串",
    "oracleUser": "範例字串",
    "oraclePassword": "範例字串",
    "synxdbUser": "範例字串",
    "synxdbPassword": "範例字串",
    "chatbots": [
      {
        "id": "550e8400-e29b-41d4-a716-446655440000"
      }
    ],
    "groups": [
      {
        "id": "550e8400-e29b-41d4-a716-446655440000"
      }
```

```
    ]
  };

axios.put("https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-
e29b-41d4-a716-446655440000/", data, config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-e29b-
41d4-a716-446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# 請求內容 (payload)
data = {
    "organization": "550e8400-e29b-41d4-a716-446655440000",
    "embeddingModel": "550e8400-e29b-41d4-a716-446655440000",
    "rerankerModel": "550e8400-e29b-41d4-a716-446655440000",
    "name": "範例名稱",
    "description": "範例字串",
    "numberOfRetrievedChunks": 123,
    "enableHyde": True,
    "similarityCutoff": 123,
    "enableRerank": True,
    "enableRrf": True,
    "vectorDatabaseType": {},
    "vectorDatabaseUrl": "範例字串",
    "vectorDatabaseApiKey": "範例字串",
    "opensearchUsername": "範例字串",
    "opensearchPassword": "範例字串",
    "oracleUser": "範例字串",
    "oraclePassword": "範例字串",
    "synxdbUser": "範例字串",
    "synxdbPassword": "範例字串",
    "chatbots": [
        {
            "id": "550e8400-e29b-41d4-a716-446655440000"
        }
    ],
    "groups": [
        {
            "id": "550e8400-e29b-41d4-a716-446655440000"
        }
    ]
```

```
}

response = requests.put(url, json=data, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>put("https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-e29b-
41d4-a716-446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'organization' => '550e8400-e29b-41d4-a716-
446655440000',
            'embeddingModel' => '550e8400-e29b-41d4-a716-
446655440000',
            'rerankerModel' => '550e8400-e29b-41d4-a716-
446655440000',
            'name' => '範例名稱',
            'description' => '範例字串',
            'numberOfRetrievedChunks' => 123,
            'enableHyde' => true,
            'similarityCutoff' => 123,
            'enableRerank' => true,
            'enableRrf' => true,
            'vectorDatabaseType' => new \stdClass(),
            'vectorDatabaseUrl' => '範例字串',
            'vectorDatabaseApiKey' => '範例字串',
            'opensearchUsername' => '範例字串',
            'opensearchPassword' => '範例字串',
            'oracleUser' => '範例字串',
            'oraclePassword' => '範例字串',
            'synxdbUser' => '範例字串',
            'synxdbPassword' => '範例字串',
            'chatbots' => [
                [
                    'id' => '550e8400-e29b-41d4-a716-446655440000'
                ]
```

```
                ],
                'groups' => [
                    [
                        'id' => '550e8400-e29b-41d4-a716-446655440000'
                    ]
                ]
            ]
        ]);

        $data = json_decode($response->getBody(), true);
        echo "成功取得回應:\n";
        print_r($data);
    } catch (Exception $e) {
        echo '請求發生錯誤: ' . $e->getMessage();
    }
    ?>
```

回應內容

狀態碼: 200

回應結構範例

```
{
  "id": string (uuid)
  "createdBy":
  {
    "id": string (uuid)
    "name": string
  }
  "organization"?: string (uuid) // 非必填
  "embeddingModel": string (uuid)
  "rerankerModel": string (uuid)
  "name": string
  "description"?: string // 非必填
  "numberOfRetrievedChunks"?: integer // 提取的參考資料數量，預設為 12，最小值為 1 (非必填)
```

```
  "enableHyde"?: boolean // 啟用 HyDE，預設為 False (非必填)
  "similarityCutoff"?: number (double) // 相似度門檻，預設為 0.0，範圍為 0.0-1.0 (非必填)
  "enableRerank"?: boolean // 是否啟用重新排序，預設為 True (非必填)
  "enableRrf"?: boolean // Enable Reciprocal Rank Fusion for hybrid search. Disable this if using a custom Elasticsearch without enterprise license. (非必填)
  "vectorDatabaseType"?:  // Type of vector database: elasticsearch or opensearch.

* `elasticsearch` - Elasticsearch
* `opensearch` - OpenSearch
* `oracle` - Oracle AI Database 26ai
* `synxdb` - SynxDB (非必填)
  {
  }
  "vectorDatabaseUrl"?: string // Custom vector database endpoint URL or Oracle DSN. For Elasticsearch/OpenSearch: URL format (e.g., "https://host:9200"). For Oracle: DSN format (e.g., "host:1521/service_name"). (非必填)
  "vectorDatabaseApiKey"?: string // API Key for Elasticsearch. Not used for OpenSearch. (非必填)
  "opensearchUsername"?: string // Username for OpenSearch Basic Auth. (非必填)
  "opensearchPassword"?: string // Password for OpenSearch Basic Auth. (非必填)
  "oracleUser"?: string // Oracle database username. (非必填)
  "oraclePassword"?: string // Oracle database password. (非必填)
  "synxdbUser"?: string // SynxDB database username. (非必填)
  "synxdbPassword"?: string // SynxDB database password. (非必填)
  "labels": [
    {
      "id": string (uuid)
      "name": string
    }
  ]
  "chatbots"?: [ // 非必填
    {
      "id": string (uuid)
      "name": string
    }
  ]
  "groups"?: [ // 知識庫可存取的群組列表 (非必填)
    {
      "id": string (uuid)
```

```
      "name": string
    }
  ]
  "filesCount": integer // Return count of KnowledgeBaseFile excluding
processed files, conversation attachments, and soft-deleted.
  "vectorStorageSize": integer
  "chunksCount": integer
  "canUpdate": boolean // Return whether the current user can update this
resource.
  "canDelete": boolean // Return whether the current user can delete this
resource.
  "createdAt": string (timestamp)
  "updatedAt": string (timestamp)
}
```

回應範例值

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "createdBy": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應字串"
  },
  "organization": "550e8400-e29b-41d4-a716-446655440000",
  "embeddingModel": "550e8400-e29b-41d4-a716-446655440000",
  "rerankerModel": "550e8400-e29b-41d4-a716-446655440000",
  "name": "回應字串",
  "description": "回應字串",
  "numberOfRetrievedChunks": 456,
  "enableHyde": false,
  "similarityCutoff": 456,
  "enableRerank": false,
  "enableRrf": false,
  "vectorDatabaseType": {},
  "vectorDatabaseUrl": "回應字串",
  "vectorDatabaseApiKey": "回應字串",
  "opensearchUsername": "回應字串",
  "opensearchPassword": "回應字串",
  "oracleUser": "回應字串",
  "oraclePassword": "回應字串",
  "synxdbUser": "回應字串",
  "synxdbPassword": "回應字串",
  "labels": [
    {
```

```
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "回應字串"
    }
  ],
  "chatbots": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "回應字串"
    }
  ],
  "groups": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "回應字串"
    }
  ],
  "filesCount": 456,
  "vectorStorageSize": 456,
  "chunksCount": 456,
  "canUpdate": false,
  "canDelete": false,
  "createdAt": "回應字串",
  "updatedAt": "回應字串"
}
```


部分更新知識庫

PATCH `/api/v1/knowledge-bases/{id}`

參數

參數名稱	必填	類型	說明
id	V	string	A UUID string identifying this Knowledge Base.

請求內容

請求參數

欄位	類型	必填	說明
organization	string (uuid)	否	
embeddingModel	string (uuid)	否	
rerankerModel	string (uuid)	否	
name	string	否	
description	string	否	
numberOfRetrievedChunks	integer	否	提取的參考資料數量，預設為 12，最小值為 1
enableHyde	boolean	否	啟用 HyDE，預設為 False
similarityCutoff	number (double)	否	相似度門檻，預設為 0.0，範圍為 0.0-1.0
enableRerank	boolean	否	是否啟用重新排序，預設為 True
enableRrf	boolean	否	Enable Reciprocal Rank Fusion for hybrid search. Disable this if using a custom Elasticsearch without enterprise license.
vectorDatabaseType	object	否	Type of vector database: elasticsearch or opensearch. `elasticsearch` : Elasticsearch ; `opensearch` : OpenSearch ; `oracle` : Oracle AI Database 26ai ; `synxdb` : SynxDB;
vectorDatabaseUrl	string	否	Custom vector database endpoint URL or Oracle DSN. For Elasticsearch/OpenSearch: URL format (e.g., "https://host:9200"). For Oracle: DSN format (e.g., "host:1521/service_name").

欄位	類型	必填	說明
vectorDatabaseApiKey	string	否	API Key for Elasticsearch. Not used for OpenSearch.
opensearchUsername	string	否	Username for OpenSearch Basic Auth.
opensearchPassword	string	否	Password for OpenSearch Basic Auth.
oracleUser	string	否	Oracle database username.
oraclePassword	string	否	Oracle database password.
synxdbUser	string	否	SynxDB database username.
synxdbPassword	string	否	SynxDB database password.
chatbots	array[IdName]	否	
groups	array[IdName]	否	知識庫可存取的群組列表

請求結構範例

```
{
  "organization"?: string (uuid) // 非必填
  "embeddingModel"?: string (uuid) // 非必填
  "rerankerModel"?: string (uuid) // 非必填
  "name"?: string // 非必填
  "description"?: string // 非必填
  "numberOfRetrievedChunks"?: integer // 提取的參考資料數量，預設為 12，最小值為 1 (非必填)
  "enableHyde"?: boolean // 啟用 HyDE，預設為 False (非必填)
  "similarityCutoff"?: number (double) // 相似度門檻，預設為 0.0，範圍為 0.0-1.0 (非必填)
  "enableRerank"?: boolean // 是否啟用重新排序，預設為 True (非必填)
  "enableRrf"?: boolean // Enable Reciprocal Rank Fusion for hybrid search. Disable this if using a custom Elasticsearch without enterprise license. (非必填)
  "vectorDatabaseType"?:  // Type of vector database: elasticsearch or opensearch.

* `elasticsearch` - Elasticsearch
* `opensearch` - OpenSearch
```

```
* `oracle` - Oracle AI Database 26ai
* `synxdb` - SynxDB (非必填)
  {
  }
  "vectorDatabaseUrl"?: string // Custom vector database endpoint URL or
Oracle DSN. For Elasticsearch/OpenSearch: URL format (e.g.,
"https://host:9200"). For Oracle: DSN format (e.g.,
"host:1521/service_name"). (非必填)
  "vectorDatabaseApiKey"?: string // API Key for Elasticsearch. Not used
for OpenSearch. (非必填)
  "opensearchUsername"?: string // Username for OpenSearch Basic Auth. (非
必填)
  "opensearchPassword"?: string // Password for OpenSearch Basic Auth. (非
必填)
  "oracleUser"?: string // Oracle database username. (非必填)
  "oraclePassword"?: string // Oracle database password. (非必填)
  "synxdbUser"?: string // SynxDB database username. (非必填)
  "synxdbPassword"?: string // SynxDB database password. (非必填)
  "chatbots"?: [ // 非必填
    {
      "id": string (uuid)
    }
  ]
  "groups"?: [ // 知識庫可存取的群組列表 (非必填)
    {
      "id": string (uuid)
    }
  ]
}
```

請求範例值

```
{
  "organization": "550e8400-e29b-41d4-a716-446655440000",
  "embeddingModel": "550e8400-e29b-41d4-a716-446655440000",
  "rerankerModel": "550e8400-e29b-41d4-a716-446655440000",
  "name": "範例名稱",
  "description": "範例字串",
  "numberOfRetrievedChunks": 123,
  "enableHyde": true,
  "similarityCutoff": 123,
  "enableRerank": true,
  "enableRrf": true,
  "vectorDatabaseType": {},
```

```
  "vectorDatabaseUrl": "範例字串",
  "vectorDatabaseApiKey": "範例字串",
  "opensearchUsername": "範例字串",
  "opensearchPassword": "範例字串",
  "oracleUser": "範例字串",
  "oraclePassword": "範例字串",
  "synxdbUser": "範例字串",
  "synxdbPassword": "範例字串",
  "chatbots": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000"
    }
  ],
  "groups": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000"
    }
  ]
}
```


程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X PATCH "https://api.maiagent.ai/api/v1/knowledge-
bases/550e8400-e29b-41d4-a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "organization": "550e8400-e29b-41d4-a716-446655440000",
    "embeddingModel": "550e8400-e29b-41d4-a716-446655440000",
    "rerankerModel": "550e8400-e29b-41d4-a716-446655440000",
    "name": "範例名稱",
    "description": "範例字串",
    "numberOfRetrievedChunks": 123,
    "enableHyde": true,
    "similarityCutoff": 123,
    "enableRerank": true,
    "enableRrf": true,
    "vectorDatabaseType": {},
    "vectorDatabaseUrl": "範例字串",
    "vectorDatabaseApiKey": "範例字串",
    "opensearchUsername": "範例字串",
    "opensearchPassword": "範例字串",
    "oracleUser": "範例字串",
    "oraclePassword": "範例字串",
    "synxdbUser": "範例字串",
    "synxdbPassword": "範例字串",
    "chatbots": [
      {
        "id": "550e8400-e29b-41d4-a716-446655440000"
      }
    ],
    "groups": [
      {
        "id": "550e8400-e29b-41d4-a716-446655440000"
      }
    ]
  }'
```

```
# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// 請求內容 (payload)
const data = {
    "organization": "550e8400-e29b-41d4-a716-446655440000",
    "embeddingModel": "550e8400-e29b-41d4-a716-446655440000",
    "rerankerModel": "550e8400-e29b-41d4-a716-446655440000",
    "name": "範例名稱",
    "description": "範例字串",
    "numberOfRetrievedChunks": 123,
    "enableHyde": true,
    "similarityCutoff": 123,
    "enableRerank": true,
    "enableRrf": true,
    "vectorDatabaseType": {},
    "vectorDatabaseUrl": "範例字串",
    "vectorDatabaseApiKey": "範例字串",
    "opensearchUsername": "範例字串",
    "opensearchPassword": "範例字串",
    "oracleUser": "範例字串",
    "oraclePassword": "範例字串",
    "synxdbUser": "範例字串",
    "synxdbPassword": "範例字串",
    "chatbots": [
      {
        "id": "550e8400-e29b-41d4-a716-446655440000"
      }
    ],
    "groups": [
      {
        "id": "550e8400-e29b-41d4-a716-446655440000"
      }
```

```
    ]
  };

axios.patch("https://api.maiagent.ai/api/v1/knowledge-
bases/550e8400-e29b-41d4-a716-446655440000/", data, config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-e29b-41d4-a716-446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# 請求內容 (payload)
data = {
    "organization": "550e8400-e29b-41d4-a716-446655440000",
    "embeddingModel": "550e8400-e29b-41d4-a716-446655440000",
    "rerankerModel": "550e8400-e29b-41d4-a716-446655440000",
    "name": "範例名稱",
    "description": "範例字串",
    "numberOfRetrievedChunks": 123,
    "enableHyde": True,
    "similarityCutoff": 123,
    "enableRerank": True,
    "enableRrf": True,
    "vectorDatabaseType": {},
    "vectorDatabaseUrl": "範例字串",
    "vectorDatabaseApiKey": "範例字串",
    "opensearchUsername": "範例字串",
    "opensearchPassword": "範例字串",
    "oracleUser": "範例字串",
    "oraclePassword": "範例字串",
    "synxdbUser": "範例字串",
    "synxdbPassword": "範例字串",
    "chatbots": [
        {
            "id": "550e8400-e29b-41d4-a716-446655440000"
        }
    ],
    "groups": [
        {
            "id": "550e8400-e29b-41d4-a716-446655440000"
        }
    ]
```

```
}

response = requests.patch(url, json=data, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>patch("https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-
e29b-41d4-a716-446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'organization' => '550e8400-e29b-41d4-a716-
446655440000',
            'embeddingModel' => '550e8400-e29b-41d4-a716-
446655440000',
            'rerankerModel' => '550e8400-e29b-41d4-a716-
446655440000',
            'name' => '範例名稱',
            'description' => '範例字串',
            'numberOfRetrievedChunks' => 123,
            'enableHyde' => true,
            'similarityCutoff' => 123,
            'enableRerank' => true,
            'enableRrf' => true,
            'vectorDatabaseType' => new \stdClass(),
            'vectorDatabaseUrl' => '範例字串',
            'vectorDatabaseApiKey' => '範例字串',
            'opensearchUsername' => '範例字串',
            'opensearchPassword' => '範例字串',
            'oracleUser' => '範例字串',
            'oraclePassword' => '範例字串',
            'synxdbUser' => '範例字串',
            'synxdbPassword' => '範例字串',
            'chatbots' => [
                [
                    'id' => '550e8400-e29b-41d4-a716-446655440000'
                ]
```

```
                ],
                'groups' => [
                    [
                        'id' => '550e8400-e29b-41d4-a716-446655440000'
                    ]
                ]
            ]
        ]);

        $data = json_decode($response->getBody(), true);
        echo "成功取得回應:\n";
        print_r($data);
    } catch (Exception $e) {
        echo '請求發生錯誤: ' . $e->getMessage();
    }
    ?>
```

回應內容

狀態碼: 200

回應結構範例

```
{
  "id": string (uuid)
  "createdBy":
  {
    "id": string (uuid)
    "name": string
  }
  "organization"?: string (uuid) // 非必填
  "embeddingModel": string (uuid)
  "rerankerModel": string (uuid)
  "name": string
  "description"?: string // 非必填
  "numberOfRetrievedChunks"?: integer // 提取的參考資料數量，預設為 12，最小值為 1 (非必填)
```

```
  "enableHyde"?: boolean // 啟用 HyDE，預設為 False (非必填)
  "similarityCutoff"?: number (double) // 相似度門檻，預設為 0.0，範圍為 0.0-1.0 (非必填)
  "enableRerank"?: boolean // 是否啟用重新排序，預設為 True (非必填)
  "enableRrf"?: boolean // Enable Reciprocal Rank Fusion for hybrid search. Disable this if using a custom Elasticsearch without enterprise license. (非必填)
  "vectorDatabaseType"?:  // Type of vector database: elasticsearch or opensearch.

* `elasticsearch` - Elasticsearch
* `opensearch` - OpenSearch
* `oracle` - Oracle AI Database 26ai
* `synxdb` - SynxDB (非必填)
  {
  }
  "vectorDatabaseUrl"?: string // Custom vector database endpoint URL or Oracle DSN. For Elasticsearch/OpenSearch: URL format (e.g., "https://host:9200"). For Oracle: DSN format (e.g., "host:1521/service_name"). (非必填)
  "vectorDatabaseApiKey"?: string // API Key for Elasticsearch. Not used for OpenSearch. (非必填)
  "opensearchUsername"?: string // Username for OpenSearch Basic Auth. (非必填)
  "opensearchPassword"?: string // Password for OpenSearch Basic Auth. (非必填)
  "oracleUser"?: string // Oracle database username. (非必填)
  "oraclePassword"?: string // Oracle database password. (非必填)
  "synxdbUser"?: string // SynxDB database username. (非必填)
  "synxdbPassword"?: string // SynxDB database password. (非必填)
  "labels": [
    {
      "id": string (uuid)
      "name": string
    }
  ]
  "chatbots"?: [ // 非必填
    {
      "id": string (uuid)
      "name": string
    }
  ]
  "groups"?: [ // 知識庫可存取的群組列表 (非必填)
    {
      "id": string (uuid)
```

```
      "name": string
    }
  ]
  "filesCount": integer // Return count of KnowledgeBaseFile excluding
processed files, conversation attachments, and soft-deleted.
  "vectorStorageSize": integer
  "chunksCount": integer
  "canUpdate": boolean // Return whether the current user can update this
resource.
  "canDelete": boolean // Return whether the current user can delete this
resource.
  "createdAt": string (timestamp)
  "updatedAt": string (timestamp)
}
```

回應範例值

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "createdBy": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應字串"
  },
  "organization": "550e8400-e29b-41d4-a716-446655440000",
  "embeddingModel": "550e8400-e29b-41d4-a716-446655440000",
  "rerankerModel": "550e8400-e29b-41d4-a716-446655440000",
  "name": "回應字串",
  "description": "回應字串",
  "numberOfRetrievedChunks": 456,
  "enableHyde": false,
  "similarityCutoff": 456,
  "enableRerank": false,
  "enableRrf": false,
  "vectorDatabaseType": {},
  "vectorDatabaseUrl": "回應字串",
  "vectorDatabaseApiKey": "回應字串",
  "opensearchUsername": "回應字串",
  "opensearchPassword": "回應字串",
  "oracleUser": "回應字串",
  "oraclePassword": "回應字串",
  "synxdbUser": "回應字串",
  "synxdbPassword": "回應字串",
  "labels": [
    {
```

```
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "回應字串"
    }
  ],
  "chatbots": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "回應字串"
    }
  ],
  "groups": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "回應字串"
    }
  ],
  "filesCount": 456,
  "vectorStorageSize": 456,
  "chunksCount": 456,
  "canUpdate": false,
  "canDelete": false,
  "createdAt": "回應字串",
  "updatedAt": "回應字串"
}
```


刪除知識庫

DELETE `/api/v1/knowledge-bases/{id}`

參數

參數名稱	必填	類型	說明
id	V	string	A UUID string identifying this Knowledge Base.

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X DELETE "https://api.maiagent.ai/api/v1/knowledge-
bases/550e8400-e29b-41d4-a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

// 請求內容 (payload)
const data = null;

axios.delete("https://api.maiagent.ai/api/v1/knowledge-
bases/550e8400-e29b-41d4-a716-446655440000/", data, config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-e29b-
41d4-a716-446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.delete(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>delete("https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-
e29b-41d4-a716-446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼	說明
204	No response body

檢查 RRF 可用性

GET `/api/v1/knowledge-bases/{id}/check-rrf-availability/`

參數

參數名稱	必填	類型	說明
`id`	V	string	A UUID string identifying this Knowledge Base.

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/knowledge-
bases/550e8400-e29b-41d4-a716-446655440000/check-rrf-availability/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-e29b-41d4-a716-446655440000/check-rrf-availability/", config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-e29b-41d4-a716-446655440000/check-rrf-availability/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-e29b-
41d4-a716-446655440000/check-rrf-availability/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
{
  "id": string (uuid)
  "createdBy":
```

```
  {
    "id": string (uuid)
    "name": string
  }
  "organization"?: string (uuid) // 非必填
  "embeddingModel": string (uuid)
  "rerankerModel": string (uuid)
  "name": string
  "description"?: string // 非必填
  "numberOfRetrievedChunks"?: integer // 提取的參考資料數量，預設為 12，最小值為 1 (非必填)
  "enableHyde"?: boolean // 啟用 HyDE，預設為 False (非必填)
  "similarityCutoff"?: number (double) // 相似度門檻，預設為 0.0，範圍為 0.0-1.0 (非必填)
  "enableRerank"?: boolean // 是否啟用重新排序，預設為 True (非必填)
  "enableRrf"?: boolean // Enable Reciprocal Rank Fusion for hybrid search. Disable this if using a custom Elasticsearch without enterprise license. (非必填)
  "vectorDatabaseType"?:  // Type of vector database: elasticsearch or opensearch.

* `elasticsearch` - Elasticsearch
* `opensearch` - OpenSearch
* `oracle` - Oracle AI Database 26ai
* `synxdb` - SynxDB (非必填)
  {
  }
  "vectorDatabaseUrl"?: string // Custom vector database endpoint URL or Oracle DSN. For Elasticsearch/OpenSearch: URL format (e.g., "https://host:9200"). For Oracle: DSN format (e.g., "host:1521/service_name"). (非必填)
  "vectorDatabaseApiKey"?: string // API Key for Elasticsearch. Not used for OpenSearch. (非必填)
  "opensearchUsername"?: string // Username for OpenSearch Basic Auth. (非必填)
  "opensearchPassword"?: string // Password for OpenSearch Basic Auth. (非必填)
  "oracleUser"?: string // Oracle database username. (非必填)
  "oraclePassword"?: string // Oracle database password. (非必填)
  "synxdbUser"?: string // SynxDB database username. (非必填)
  "synxdbPassword"?: string // SynxDB database password. (非必填)
  "labels": [
    {
      "id": string (uuid)
      "name": string
```

```
    }
  ]
  "chatbots"?: [ // 非必填
    {
      "id": string (uuid)
      "name": string
    }
  ]
  "groups"?: [ // 知識庫可存取的群組列表 (非必填)
    {
      "id": string (uuid)
      "name": string
    }
  ]
  "filesCount": integer // Return count of KnowledgeBaseFile excluding
processed files, conversation attachments, and soft-deleted.
  "vectorStorageSize": integer
  "chunksCount": integer
  "canUpdate": boolean // Return whether the current user can update this
resource.
  "canDelete": boolean // Return whether the current user can delete this
resource.
  "createdAt": string (timestamp)
  "updatedAt": string (timestamp)
}
```

回應範例值

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "createdBy": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應字串"
  },
  "organization": "550e8400-e29b-41d4-a716-446655440000",
  "embeddingModel": "550e8400-e29b-41d4-a716-446655440000",
  "rerankerModel": "550e8400-e29b-41d4-a716-446655440000",
  "name": "回應字串",
  "description": "回應字串",
  "numberOfRetrievedChunks": 456,
  "enableHyde": false,
  "similarityCutoff": 456,
  "enableRerank": false,
  "enableRrf": false,
```

```
  "vectorDatabaseType": {},
  "vectorDatabaseUrl": "回應字串",
  "vectorDatabaseApiKey": "回應字串",
  "opensearchUsername": "回應字串",
  "opensearchPassword": "回應字串",
  "oracleUser": "回應字串",
  "oraclePassword": "回應字串",
  "synxdbUser": "回應字串",
  "synxdbPassword": "回應字串",
  "labels": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "回應字串"
    }
  ],
  "chatbots": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "回應字串"
    }
  ],
  "groups": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "回應字串"
    }
  ],
  "filesCount": 456,
  "vectorStorageSize": 456,
  "chunksCount": 456,
  "canUpdate": false,
  "canDelete": false,
  "createdAt": "回應字串",
  "updatedAt": "回應字串"
}
```


匯出標籤 Excel

GET `/api/v1/knowledge-bases/{id}/export-labels-excel/`

參數

參數名稱	必填	類型	說明
`id`	V	string	A UUID string identifying this Knowledge Base.

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/knowledge-
bases/550e8400-e29b-41d4-a716-446655440000/export-labels-excel/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-e29b-41d4-a716-446655440000/export-labels-excel/", config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-e29b-41d4-a716-446655440000/export-labels-excel/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-e29b-
41d4-a716-446655440000/export-labels-excel/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼	說明
200	Excel file download

匯入標籤 Excel

POST `/api/v1/knowledge-bases/{id}/import-labels-excel/`

參數

參數名稱	必填	類型	說明
`id`	V	string	A UUID string identifying this Knowledge Base.

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X POST "https://api.maiagent.ai/api/v1/knowledge-
bases/550e8400-e29b-41d4-a716-446655440000/import-labels-excel/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -F "excelFile=@example_file.txt"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');
const FormData = require('form-data');

// 建立FormData對象
const formData = new FormData();
// 請用實際檔案替換
formData.append('excelFile',
* 實際檔案物件 *
, 'example_file.txt');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    ...formData.getHeaders()
  }
};

axios.post("https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-
e29b-41d4-a716-446655440000/import-labels-excel/", formData, config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-e29b-
41d4-a716-446655440000/import-labels-excel/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}

# 建立檔案和表單資料
files = {
    'excelFile': ('example_file.txt', open('example_file.txt',
'rb'), 'text/plain')
}

response = requests.post(url, files=files, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->post("https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-e29b-41d4-a716-446655440000/import-labels-excel/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ],
        'multipart' => [
            [
                'name' => 'excelFile',
                'contents' => fopen('example_file.txt', 'r'),
                'filename' => 'example_file.txt'
            ]
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
{
  "success"?: boolean // 非必填
  "updated_count"?: integer // 非必填
  "total_rows"?: integer // 非必填
  "errors"?: [ // 非必填
    {
      "row"?: integer // 非必填
      "file_id"?: string // 非必填
      "error"?: string // 非必填
    }
  ]
}
```

回應範例值

```
{
  "success": false,
  "updated_count": 456,
  "total_rows": 456,
  "errors": [
    {
      "row": 456,
      "file_id": "回應字串",
      "error": "回應字串"
    }
  ]
}
```

匯出元資料 Excel

GET `/api/v1/knowledge-bases/{id}/export-metadata-excel/`

參數

參數名稱	必填	類型	說明
`id`	V	string	A UUID string identifying this Knowledge Base.

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/knowledge-
bases/550e8400-e29b-41d4-a716-446655440000/export-metadata-excel/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-e29b-41d4-a716-446655440000/export-metadata-excel/", config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-e29b-41d4-a716-446655440000/export-metadata-excel/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-e29b-
41d4-a716-446655440000/export-metadata-excel/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼	說明
200	Excel 檔案下載

匯入元資料 Excel

POST `/api/v1/knowledge-bases/{id}/import-metadata-excel/`

參數

參數名稱	必填	類型	說明
id	V	string	A UUID string identifying this Knowledge Base.

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X POST "https://api.maiagent.ai/api/v1/knowledge-
bases/550e8400-e29b-41d4-a716-446655440000/import-metadata-excel/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -F "excelFile=@example_file.txt"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');
const FormData = require('form-data');

// 建立FormData對象
const formData = new FormData();
// 請用實際檔案替換
formData.append('excelFile',
* 實際檔案物件 *
, 'example_file.txt');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    ...formData.getHeaders()
  }
};

axios.post("https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-
e29b-41d4-a716-446655440000/import-metadata-excel/", formData,
config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-e29b-
41d4-a716-446655440000/import-metadata-excel/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}

# 建立檔案和表單資料
files = {
    'excelFile': ('example_file.txt', open('example_file.txt',
'rb'), 'text/plain')
}

response = requests.post(url, files=files, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>post("https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-e29b-
41d4-a716-446655440000/import-metadata-excel/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ],
        'multipart' => [
            [
                'name' => 'excelFile',
                'contents' => fopen('example_file.txt', 'r'),
                'filename' => 'example_file.txt'
            ]
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
{
  "success"?: boolean // 非必填
  "updated_count"?: integer // 非必填
  "total_rows"?: integer // 非必填
  "errors"?: [ // 非必填
    {
      "row"?: integer // 非必填
      "file_id"?: string // 非必填
      "error"?: string // 非必填
    }
  ]
}
```

回應範例值

```
{
  "success": false,
  "updated_count": 456,
  "total_rows": 456,
  "errors": [
    {
      "row": 456,
      "file_id": "回應字串",
      "error": "回應字串"
    }
  ]
}
```

建立新標籤

POST `/api/v1/knowledge-bases/{knowledgeBasePk}/labels/`

參數

參數名稱	必填	類型	說明
knowledgeBasePk	V	string	

請求內容

請求參數

欄位	類型	必填	說明
name	string	是	

請求結構範例

```
{
  "name": string
}
```

請求範例值

```
{
  "name": "範例名稱"
}
```

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X POST "https://api.maiagent.ai/api/v1/knowledge-
bases/550e8400-e29b-41d4-a716-446655440000/labels/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "name": "範例名稱"
  }'

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// 請求內容 (payload)
const data = {
    "name": "範例名稱"
  };

axios.post("https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-e29b-41d4-a716-446655440000/labels/", data, config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-e29b-
41d4-a716-446655440000/labels/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# 請求內容 (payload)
data = {
    "name": "範例名稱"
}

response = requests.post(url, json=data, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>post("https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-e29b-
41d4-a716-446655440000/labels/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'name' => '範例名稱'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 201

回應結構範例

```
{
  "id": string (uuid)
  "name"?: string // 非必填
}
```

回應範例值

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "name": "回應字串"
}
```

列出知識庫中的標籤

GET `/api/v1/knowledge-bases/{knowledgeBasePk}/labels/`

參數

參數名稱	必填	類型	說明
`knowledgeBasePk`	V	string	
`page`	X	integer	A page number within the paginated result set.
`pageSize`	X	integer	Number of results to return per page.

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/knowledge-
bases/550e8400-e29b-41d4-a716-446655440000/labels/?
page=1&pageSize=1"

  -H "Authorization: Api-Key YOUR_API_KEY"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-e29b-41d4-a716-446655440000/labels/?page=1&pageSize=1", config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-e29b-41d4-a716-446655440000/labels/?page=1&pageSize=1"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-e29b-
41d4-a716-446655440000/labels/?page=1&pageSize=1", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
{
  "count": integer
  "next"?: string (uri) // 非必填
```

```
  "previous"?: string (uri) // 非必填
  "results": [
    {
      "id": string (uuid)
      "name"?: string // 非必填
    }
  ]
}
```

回應範例值

```
{
  "count": 123,
  "next": "http://api.example.org/accounts/?page=4",
  "previous": "http://api.example.org/accounts/?page=2",
  "results": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "回應字串"
    }
  ]
}
```

取得特定標籤詳情

GET `/api/v1/knowledge-bases/{knowledgeBasePk}/labels/{id}`

參數

參數名稱	必填	類型	說明
id	V	string	A UUID string identifying this knowledge base label.

`knowledgeBasePk`	V	string

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/knowledge-
bases/550e8400-e29b-41d4-a716-446655440000/labels/550e8400-e29b-
41d4-a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-e29b-41d4-a716-446655440000/labels/550e8400-e29b-41d4-a716-446655440000/", config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-e29b-41d4-a716-446655440000/labels/550e8400-e29b-41d4-a716-446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-e29b-
41d4-a716-446655440000/labels/550e8400-e29b-41d4-a716-
446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
{
  "id": string (uuid)
```

```
  "name"?: string // 非必填
}
```

回應範例值

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "name": "回應字串"
}
```

更新標籤

PUT `/api/v1/knowledge-bases/{knowledgeBasePk}/labels/{id}`

參數

參數名稱	必填	類型	說明
`id`	V	string	A UUID string identifying this knowledge base label.
`knowledgeBasePk`	V	string	

請求內容

請求參數

欄位	類型	必填	說明
name	string	是	

請求結構範例

```
{
  "name": string
}
```

請求範例值

```
{
  "name": "範例名稱"
}
```

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X PUT "https://api.maiagent.ai/api/v1/knowledge-
bases/550e8400-e29b-41d4-a716-446655440000/labels/550e8400-e29b-
41d4-a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "name": "範例名稱"
  }'

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// 請求內容 (payload)
const data = {
    "name": "範例名稱"
  };

axios.put("https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-
e29b-41d4-a716-446655440000/labels/550e8400-e29b-41d4-a716-
446655440000/", data, config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-e29b-
41d4-a716-446655440000/labels/550e8400-e29b-41d4-a716-446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# 請求內容 (payload)
data = {
    "name": "範例名稱"
}

response = requests.put(url, json=data, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>put("https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-e29b-
41d4-a716-446655440000/labels/550e8400-e29b-41d4-a716-
446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'name' => '範例名稱'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
{
  "id": string (uuid)
  "name"?: string // 非必填
}
```

回應範例值

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "name": "回應字串"
}
```

部分更新標籤

PATCH `/api/v1/knowledge-bases/{knowledgeBasePk}/labels/{id}`

參數

參數名稱	必填	類型	說明
`id`	V	string	A UUID string identifying this knowledge base label.
`knowledgeBasePk`	V	string	

請求內容

請求參數

欄位	類型	必填	說明
name	string	否	

請求結構範例

```
{
  "name"?: string // 非必填
}
```

請求範例值

```
{
  "name": "範例名稱"
}
```

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X PATCH "https://api.maiagent.ai/api/v1/knowledge-
bases/550e8400-e29b-41d4-a716-446655440000/labels/550e8400-e29b-
41d4-a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "name": "範例名稱"
  }'

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// 請求內容 (payload)
const data = {
    "name": "範例名稱"
  };

axios.patch("https://api.maiagent.ai/api/v1/knowledge-
bases/550e8400-e29b-41d4-a716-446655440000/labels/550e8400-e29b-
41d4-a716-446655440000/", data, config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-e29b-
41d4-a716-446655440000/labels/550e8400-e29b-41d4-a716-446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# 請求內容 (payload)
data = {
    "name": "範例名稱"
}

response = requests.patch(url, json=data, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>patch("https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-
e29b-41d4-a716-446655440000/labels/550e8400-e29b-41d4-a716-
446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'name' => '範例名稱'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
{
  "id": string (uuid)
  "name"?: string // 非必填
}
```

回應範例值

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "name": "回應字串"
}
```

刪除標籤

DELETE `/api/v1/knowledge-bases/{knowledgeBasePk}/labels/{id}`

參數

參數名稱	必填	類型	說明
`id`	V	string	A UUID string identifying this knowledge base label.
`knowledgeBasePk`	V	string	

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X DELETE "https://api.maiagent.ai/api/v1/knowledge-
bases/550e8400-e29b-41d4-a716-446655440000/labels/550e8400-e29b-
41d4-a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

// 請求內容 (payload)
const data = null;

axios.delete("https://api.maiagent.ai/api/v1/knowledge-
bases/550e8400-e29b-41d4-a716-446655440000/labels/550e8400-e29b-
41d4-a716-446655440000/", data, config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-e29b-41d4-a716-446655440000/labels/550e8400-e29b-41d4-a716-446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.delete(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>delete("https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-
e29b-41d4-a716-446655440000/labels/550e8400-e29b-41d4-a716-
446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼	說明
204	No response body

建立元資料欄位

POST `/api/v1/knowledge-bases/{knowledgeBasePk}/metadata-keys/`

參數

參數名稱	必填	類型	說明
knowledgeBasePk	V	string	

請求內容

請求參數

欄位	類型	必填	說明
keyName	string	是	Metadata 的 key 名稱
description	string	否	說明此欄位的用途
isRequired	boolean	否	是否為必填欄位
defaultValue	string	否	新檔案的預設值
enabledForSearch	boolean	否	是否在檢索時使用此欄位

請求結構範例

```
{
  "keyName": string // Metadata 的 key 名稱
  "description"?: string // 說明此欄位的用途 (非必填)
  "isRequired"?: boolean // 是否為必填欄位 (非必填)
  "defaultValue"?: string // 新檔案的預設值 (非必填)
  "enabledForSearch"?: boolean // 是否在檢索時使用此欄位 (非必填)
}
```

請求範例值

```
{
  "keyName": "範例字串",
  "description": "範例字串",
  "isRequired": true,
  "defaultValue": "範例字串",
  "enabledForSearch": true
}
```

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X POST "https://api.maiagent.ai/api/v1/knowledge-
bases/550e8400-e29b-41d4-a716-446655440000/metadata-keys/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "keyName": "範例字串",
    "description": "範例字串",
    "isRequired": true,
    "defaultValue": "範例字串",
    "enabledForSearch": true
  }'

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// 請求內容 (payload)
const data = {
    "keyName": "範例字串",
    "description": "範例字串",
    "isRequired": true,
    "defaultValue": "範例字串",
    "enabledForSearch": true
  };

axios.post("https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-
e29b-41d4-a716-446655440000/metadata-keys/", data, config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-e29b-
41d4-a716-446655440000/metadata-keys/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# 請求內容 (payload)
data = {
    "keyName": "範例字串",
    "description": "範例字串",
    "isRequired": True,
    "defaultValue": "範例字串",
    "enabledForSearch": True
}

response = requests.post(url, json=data, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>post("https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-e29b-
41d4-a716-446655440000/metadata-keys/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'keyName' => '範例字串',
            'description' => '範例字串',
            'isRequired' => true,
            'defaultValue' => '範例字串',
            'enabledForSearch' => true
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 201

回應結構範例

```
{
  "id": string (uuid)
  "knowledgeBase":
  {
    "id": string (uuid)
    "name": string
  }
  "keyName": string // Metadata 的 key 名稱
  "keyType": string // 根據欄位名稱自動判斷（預設欄位或自定欄位）
  "description"?: string // 說明此欄位的用途 (非必填)
  "isRequired"?: boolean // 是否為必填欄位 (非必填)
  "defaultValue"?: string // 新檔案的預設值 (非必填)
  "enabledForSearch"?: boolean // 是否在檢索時使用此欄位 (非必填)
  "createdAt": string (timestamp)
  "updatedAt": string (timestamp)
}
```

回應範例值

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "knowledgeBase": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應字串"
  },
  "keyName": "回應字串",
  "keyType": "回應字串",
  "description": "回應字串",
  "isRequired": false,
  "defaultValue": "回應字串",
  "enabledForSearch": false,
  "createdAt": "回應字串",
  "updatedAt": "回應字串"
}
```

列出元資料欄位

`GET` `/api/v1/knowledge-bases/{knowledgeBasePk}/metadata-keys/`

參數

參數名稱	必填	類型	說明
`knowledgeBasePk`	V	string	
`page`	X	integer	A page number within the paginated result set.
`pageSize`	X	integer	Number of results to return per page.
`pagination`	X	boolean	Set to false to return all keys without pagination (defaults to true).

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/knowledge-
bases/550e8400-e29b-41d4-a716-446655440000/metadata-keys/?
page=1&pageSize=1&pagination=true"

  -H "Authorization: Api-Key YOUR_API_KEY"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-
e29b-41d4-a716-446655440000/metadata-keys/?
page=1&pageSize=1&pagination=true", config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-e29b-
41d4-a716-446655440000/metadata-keys/?
page=1&pageSize=1&pagination=true"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-e29b-
41d4-a716-446655440000/metadata-keys/?
page=1&pageSize=1&pagination=true", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
{
  "count": integer
```

```
  "next"?: string (uri) // 非必填
  "previous"?: string (uri) // 非必填
  "results": [
    {
      "id": string (uuid)
      "knowledgeBase":
      {
        "id": string (uuid)
        "name": string
      }
      "keyName": string // Metadata 的 key 名稱
      "keyType": string // 根據欄位名稱自動判斷（預設欄位或自定欄位）
      "description"?: string // 說明此欄位的用途 (非必填)
      "isRequired"?: boolean // 是否為必填欄位 (非必填)
      "defaultValue"?: string // 新檔案的預設值 (非必填)
      "enabledForSearch"?: boolean // 是否在檢索時使用此欄位 (非必填)
      "createdAt": string (timestamp)
      "updatedAt": string (timestamp)
    }
  ]
}
```

回應範例值

```
{
  "count": 123,
  "next": "http://api.example.org/accounts/?page=4",
  "previous": "http://api.example.org/accounts/?page=2",
  "results": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "knowledgeBase": {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "name": "回應字串"
      },
      "keyName": "回應字串",
      "keyType": "回應字串",
      "description": "回應字串",
      "isRequired": false,
      "defaultValue": "回應字串",
      "enabledForSearch": false,
      "createdAt": "回應字串",
      "updatedAt": "回應字串"
    }
```

```
  ]
}
```

取得特定元資料欄位

GET `/api/v1/knowledge-bases/{knowledgeBasePk}/metadata-keys/{id}`

參數

參數名稱	必填	類型	說明
`id`	V	string	A UUID string identifying this Metadata Key.
`knowledgeBasePk`	V	string	

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/knowledge-
bases/550e8400-e29b-41d4-a716-446655440000/metadata-keys/550e8400-
e29b-41d4-a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-e29b-41d4-a716-446655440000/metadata-keys/550e8400-e29b-41d4-a716-446655440000/", config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-e29b-41d4-a716-446655440000/metadata-keys/550e8400-e29b-41d4-a716-446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-e29b-
41d4-a716-446655440000/metadata-keys/550e8400-e29b-41d4-a716-
446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
{
  "id": string (uuid)
```

```
  "knowledgeBase":
  {
    "id": string (uuid)
    "name": string
  }
  "keyName": string // Metadata 的 key 名稱
  "keyType": string // 根據欄位名稱自動判斷（預設欄位或自定欄位）
  "description"?: string // 說明此欄位的用途（非必填）
  "isRequired"?: boolean // 是否為必填欄位（非必填）
  "defaultValue"?: string // 新檔案的預設值（非必填）
  "enabledForSearch"?: boolean // 是否在檢索時使用此欄位（非必填）
  "createdAt": string (timestamp)
  "updatedAt": string (timestamp)
}
```

回應範例值

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "knowledgeBase": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應字串"
  },
  "keyName": "回應字串",
  "keyType": "回應字串",
  "description": "回應字串",
  "isRequired": false,
  "defaultValue": "回應字串",
  "enabledForSearch": false,
  "createdAt": "回應字串",
  "updatedAt": "回應字串"
}
```

更新元資料欄位

PUT `/api/v1/knowledge-bases/{knowledgeBasePk}/metadata-keys/{id}`

參數

參數名稱	必填	類型	說明
`id`	V	string	A UUID string identifying this Metadata Key.
`knowledgeBasePk`	V	string	

請求內容

請求參數

欄位	類型	必填	說明
keyName	string	是	Metadata 的 key 名稱
description	string	否	說明此欄位的用途
isRequired	boolean	否	是否為必填欄位
defaultValue	string	否	新檔案的預設值
enabledForSearch	boolean	否	是否在檢索時使用此欄位

請求結構範例

```
{
  "keyName": string // Metadata 的 key 名稱
  "description"?: string // 說明此欄位的用途 (非必填)
  "isRequired"?: boolean // 是否為必填欄位 (非必填)
  "defaultValue"?: string // 新檔案的預設值 (非必填)
  "enabledForSearch"?: boolean // 是否在檢索時使用此欄位 (非必填)
}
```

請求範例值

```
{
  "keyName": "範例字串",
```

```
  "description": "範例字串",
  "isRequired": true,
  "defaultValue": "範例字串",
  "enabledForSearch": true
}
```

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X PUT "https://api.maiagent.ai/api/v1/knowledge-
bases/550e8400-e29b-41d4-a716-446655440000/metadata-keys/550e8400-
e29b-41d4-a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "keyName": "範例字串",
    "description": "範例字串",
    "isRequired": true,
    "defaultValue": "範例字串",
    "enabledForSearch": true
  }'

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// 請求內容 (payload)
const data = {
    "keyName": "範例字串",
    "description": "範例字串",
    "isRequired": true,
    "defaultValue": "範例字串",
    "enabledForSearch": true
  };

axios.put("https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-
e29b-41d4-a716-446655440000/metadata-keys/550e8400-e29b-41d4-a716-
446655440000/", data, config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-e29b-41d4-a716-446655440000/metadata-keys/550e8400-e29b-41d4-a716-446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# 請求內容 (payload)
data = {
    "keyName": "範例字串",
    "description": "範例字串",
    "isRequired": True,
    "defaultValue": "範例字串",
    "enabledForSearch": True
}

response = requests.put(url, json=data, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>put("https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-e29b-
41d4-a716-446655440000/metadata-keys/550e8400-e29b-41d4-a716-
446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'keyName' => '範例字串',
            'description' => '範例字串',
            'isRequired' => true,
            'defaultValue' => '範例字串',
            'enabledForSearch' => true
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
{
  "id": string (uuid)
  "knowledgeBase":
  {
    "id": string (uuid)
    "name": string
  }
  "keyName": string // Metadata 的 key 名稱
  "keyType": string // 根據欄位名稱自動判斷（預設欄位或自定欄位）
  "description"?: string // 說明此欄位的用途 (非必填)
  "isRequired"?: boolean // 是否為必填欄位 (非必填)
  "defaultValue"?: string // 新檔案的預設值 (非必填)
  "enabledForSearch"?: boolean // 是否在檢索時使用此欄位 (非必填)
  "createdAt": string (timestamp)
  "updatedAt": string (timestamp)
}
```

回應範例值

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "knowledgeBase": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應字串"
  },
  "keyName": "回應字串",
  "keyType": "回應字串",
  "description": "回應字串",
  "isRequired": false,
  "defaultValue": "回應字串",
  "enabledForSearch": false,
  "createdAt": "回應字串",
  "updatedAt": "回應字串"
}
```

上傳檔案到知識庫

`POST` `/api/v1/knowledge-bases/{knowledgeBasePk}/files/`

參數

參數名稱	必填	類型	說明
`knowledgeBasePk`	V	string	
`fileType`	X	string	檔案類型過濾，例如：pdf、docx、txt、xlsx 等
`knowledgeBase`	X	string	知識庫 ID
`page`	X	integer	A page number within the paginated result set.
`pageSize`	X	integer	Number of results to return per page.
`query`	X	string	搜尋關鍵字，支援空白分隔的多條件查詢。可搜尋：檔案 ID、檔案名稱、標籤名稱、Metadata value
`status`	X	string	檔案狀態過濾，可選值：initial（初始化）、processing（處理中）、done（完成）、deleting（刪除中）、deleted（已刪除）、failed（失敗） `initial`: Initial ; `processing`: Processing ; `done`: Done ; `deleting`: Deleting ; `deleted`: Deleted ; `faile...

請求內容

請求參數

欄位	類型	必填	說明
files	array[KnowledgeBaseFileCreate]	是	Supports uploading multiple files in one batch.

請求結構範例

```
{
  "files": [ // Supports uploading multiple files in one batch.
    {
      "filename": string // 檔案名稱
      "file": string (uri) // 要上傳的檔案
      "parser"?: string (uuid) // 非必填
      "labels"?: [ // 非必填
        {
          "id": string (uuid)
        }
      ]
      "rawUserDefineMetadata"?: object // 非必填
      "asrOptions"?: object // Per-file canonical transcription options (languages, prompt, diarization). Empty means no per-file options: provider defaults apply. Completely decoupled from user-defined metadata; never indexed for search. (非必填)
    }
  ]
}
```

請求範例值

```
{
  "files": [
    {
      "filename": "my-file.pdf",
      "file": "string",
      "parser": "3fa85f64-5717-4562-b3fc-2c963f66afa6",
      "labels": [
        {
          "id": "3fa85f64-5717-4562-b3fc-2c963f66afa6",
          "name": "my-label"
        }
      ],
      "rawUserDefineMetadata": {
```

```
        "key1": "value1",
        "key2": "value2"
      }
    },
    {
      "filename": "you-can-upload-multiple-files.pdf",
      "file": "string",
      "parser": "3fa85f64-5717-4562-b3fc-2c963f66afa6"
    }
  ]
}
```

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X POST "https://api.maiagent.ai/api/v1/knowledge-
bases/550e8400-e29b-41d4-a716-446655440000/files/?
fileType=example&knowledgeBase=550e8400-e29b-41d4-a716-
446655440000&page=1&pageSize=1&query=example&status=delete_failed"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "files": [
      {
        "filename": "my-file.pdf",
        "file": "string",
        "parser": "3fa85f64-5717-4562-b3fc-2c963f66afa6",
        "labels": [
          {
            "id": "3fa85f64-5717-4562-b3fc-2c963f66afa6",
            "name": "my-label"
          }
        ],
        "rawUserDefineMetadata": {
          "key1": "value1",
          "key2": "value2"
        }
      },
      {
        "filename": "you-can-upload-multiple-files.pdf",
        "file": "string",
        "parser": "3fa85f64-5717-4562-b3fc-2c963f66afa6"
      }
    ]
  }'

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// 請求內容 (payload)
const data = {
    "files": [
      {
        "filename": "my-file.pdf",
        "file": "string",
        "parser": "3fa85f64-5717-4562-b3fc-2c963f66afa6",
        "labels": [
          {
            "id": "3fa85f64-5717-4562-b3fc-2c963f66afa6",
            "name": "my-label"
          }
        ],
        "rawUserDefineMetadata": {
          "key1": "value1",
          "key2": "value2"
        }
      },
      {
        "filename": "you-can-upload-multiple-files.pdf",
        "file": "string",
        "parser": "3fa85f64-5717-4562-b3fc-2c963f66afa6"
      }
    ]
  };

axios.post("https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-
e29b-41d4-a716-446655440000/files/?
fileType=example&knowledgeBase=550e8400-e29b-41d4-a716-
446655440000&page=1&pageSize=1&query=example&status=delete_failed",
```

```
  data, config)
    .then(response => {
      console.log('成功取得回應:');
      console.log(response.data);
    })
    .catch(error => {
      console.error('請求發生錯誤:');
      console.error(error.response?.data || error.message);
    });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-e29b-
41d4-a716-446655440000/files/?
fileType=example&knowledgeBase=550e8400-e29b-41d4-a716-
446655440000&page=1&pageSize=1&query=example&status=delete_failed"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# 請求內容 (payload)
data = {
    "files": [
        {
            "filename": "my-file.pdf",
            "file": "string",
            "parser": "3fa85f64-5717-4562-b3fc-2c963f66afa6",
            "labels": [
                {
                    "id": "3fa85f64-5717-4562-b3fc-2c963f66afa6",
                    "name": "my-label"
                }
            ],
            "rawUserDefineMetadata": {
                "key1": "value1",
                "key2": "value2"
            }
        },
        {
            "filename": "you-can-upload-multiple-files.pdf",
            "file": "string",
            "parser": "3fa85f64-5717-4562-b3fc-2c963f66afa6"
        }
    ]
}

response = requests.post(url, json=data, headers=headers)
try:
    print("成功取得回應:")
```

```
        print(response.json())
    except Exception as e:
        print("請求發生錯誤:", e)
```

PHP

```
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>post("https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-e29b-
41d4-a716-446655440000/files/?
fileType=example&knowledgeBase=550e8400-e29b-41d4-a716-
446655440000&page=1&pageSize=1&query=example&status=delete_failed",
[
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'files' => [
                [
                    'filename' => 'my-file.pdf',
                    'file' => 'string',
                    'parser' => '3fa85f64-5717-4562-b3fc-
2c963f66afa6',
                    'labels' => [
                        [
                            'id' => '3fa85f64-5717-4562-b3fc-
2c963f66afa6',
                            'name' => 'my-label'
                        ]
                    ],
                    'rawUserDefineMetadata' => [
                        'key1' => 'value1',
                        'key2' => 'value2'
                    ]
                ],
                [
                    'filename' => 'you-can-upload-multiple-
files.pdf',
                    'file' => 'string',
                    'parser' => '3fa85f64-5717-4562-b3fc-
```

```
    2c963f66afa6'
                    ]
                ]
            ]
        ]);

        $data = json_decode($response->getBody(), true);
        echo "成功取得回應:\n";
        print_r($data);
    } catch (Exception $e) {
        echo '請求發生錯誤: ' . $e->getMessage();
    }
    ?>
```

回應內容

狀態碼: 201

回應結構範例

```
{
  "count": integer
  "next"?: string (uri) // 非必填
  "previous"?: string (uri) // 非必填
  "results": [
    {
      "id": string (uuid)
      "filename": string // 檔案名稱
      "file": string (uri) // 要上傳的檔案
      "fileType": string
      "knowledgeBase"?:  // 非必填
      {
        "id": string (uuid)
        "name": string
      }
      "size": integer
      "status":
```

```
      {
      }
      "parser":
      {
        "id": string (uuid)
        "name": string
        "provider":
        {
        }
        "isTimestampSttProvider": boolean
      }
      "labels"?: [ // 非必填
        {
          "id": string (uuid)
          "name": string
        }
      ]
      "rawUserDefineMetadata"?: object // 非必填
      "speakerLabels": [
        {
          "id": string (uuid)
          "originalLabel": string // Original speaker label from
diarization (e.g., SPEAKER_00)
          "customName"?: string // User-defined speaker name (e.g., John)
(非必填)
          "displayName": string
        }
      ]
      "vectorStorageSize": integer // Size of vectors for this file in
Elasticsearch (bytes)
      "chunksCount": integer // Number of chunks/nodes generated from
this file
      "waitingTime": number (double)
      "processingTime": number (double)
      "processingTimeDetails": object
      "previewUrl": string // 簡報（pptx/ppt）回傳可預覽的 pdf 衍生檔 URL（前端
用 PDF 預覽器顯示）；其餘為 None。

用與 `file` 欄位相同的 CustomizedFileFieldSerializer 產 URL，確保格式一致（含各
storage provider 的 presign/host 規則）。不可用 get_absolute_url()——它產出的
URL 格式錯誤。
      "createdAt": string (timestamp)
    }
```

```
  ]
}
```

回應範例值


```
{
  "count": 123,
  "next": "http://api.example.org/accounts/?page=4",
  "previous": "http://api.example.org/accounts/?page=2",
  "results": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "filename": "回應字串",
      "file": "https://example.com/file.jpg",
      "fileType": "回應字串",
      "knowledgeBase": {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "name": "回應字串"
      },
      "size": 456,
      "status": {},
      "parser": {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "name": "回應字串",
        "provider": {},
        "isTimestampSttProvider": false
      },
      "labels": [
        {
          "id": "550e8400-e29b-41d4-a716-446655440000",
          "name": "回應字串"
        }
      ],
      "rawUserDefineMetadata": null,
      "speakerLabels": [
        {
          "id": "550e8400-e29b-41d4-a716-446655440000",
          "originalLabel": "回應字串",
          "customName": "回應字串",
          "displayName": "回應字串"
        }
      ],
      "vectorStorageSize": 456,
      "chunksCount": 456,
```

```
        "waitingTime": 456,
        "processingTime": 456,
        "processingTimeDetails": null,
        "previewUrl": "回應字串",
        "createdAt": "回應字串"
      }
    ]
  }
```


更新檔案元資料

PATCH `/api/v1/knowledge-bases/{knowledgeBasePk}/files/{id}/update-metadata/`

參數

參數名稱	必填	類型	說明
`id`	V	string	A UUID string identifying this Knowledge Base File.
`knowledgeBasePk`	V	string	

請求內容

請求參數

欄位	類型	必填	說明
labels	array[IdName]	否	
rawUserDefineMetadata	object	否	

請求結構範例

```
{
  "labels"?: [ // 非必填
    {
      "id": string (uuid)
    }
  ]
  "rawUserDefineMetadata"?: object // 非必填
}
```

請求範例值

```
{
  "labels": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000"
    }
  ],
  "rawUserDefineMetadata": null
}
```

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X PATCH "https://api.maiagent.ai/api/v1/knowledge-
bases/550e8400-e29b-41d4-a716-446655440000/files/550e8400-e29b-41d4-
a716-446655440000/update-metadata/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "labels": [
      {
        "id": "550e8400-e29b-41d4-a716-446655440000"
      }
    ],
    "rawUserDefineMetadata": null
  }'

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// 請求內容 (payload)
const data = {
    "labels": [
      {
        "id": "550e8400-e29b-41d4-a716-446655440000"
      }
    ],
    "rawUserDefineMetadata": null
  };

axios.patch("https://api.maiagent.ai/api/v1/knowledge-
bases/550e8400-e29b-41d4-a716-446655440000/files/550e8400-e29b-41d4-
a716-446655440000/update-metadata/", data, config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-e29b-
41d4-a716-446655440000/files/550e8400-e29b-41d4-a716-
446655440000/update-metadata/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# 請求內容 (payload)
data = {
    "labels": [
        {
            "id": "550e8400-e29b-41d4-a716-446655440000"
        }
    ],
    "rawUserDefineMetadata": None
}

response = requests.patch(url, json=data, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>patch("https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-
e29b-41d4-a716-446655440000/files/550e8400-e29b-41d4-a716-
446655440000/update-metadata/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'labels' => [
                [
                    'id' => '550e8400-e29b-41d4-a716-446655440000'
                ]
            ],
            'rawUserDefineMetadata' => null
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
{
  "id": string (uuid)
  "filename": string // 檔案名稱
  "file": string (uri) // 要上傳的檔案
  "fileType": string
  "knowledgeBase"?:  // 非必填
  {
    "id": string (uuid)
    "name": string
  }
  "size": integer
  "status":
  {
  }
  "parser":
  {
    "id": string (uuid)
    "name": string
    "provider":
    {
    }
    "isTimestampSttProvider": boolean
  }
  "labels"?: [ // 非必填
    {
      "id": string (uuid)
      "name": string
    }
  ]
  "rawUserDefineMetadata"?: object // 非必填
  "speakerLabels": [
    {
      "id": string (uuid)
      "originalLabel": string // Original speaker label from diarization
(e.g., SPEAKER_00)
      "customName"?: string // User-defined speaker name (e.g., John) (非
```

```
必填)
      "displayName": string
    }
  ]
  "vectorStorageSize": integer // Size of vectors for this file in
Elasticsearch (bytes)
  "chunksCount": integer // Number of chunks/nodes generated from this
file
  "waitingTime": number (double)
  "processingTime": number (double)
  "processingTimeDetails": object
  "previewUrl": string // 簡報（pptx/ppt）回傳可預覽的 pdf 衍生檔 URL（前端用
PDF 預覽器顯示）；其餘為 None。

用與 `file` 欄位相同的 CustomizedFileFieldSerializer 產 URL，確保格式一致（含各
storage provider 的 presign/host 規則）。不可用 get_absolute_url()——它產出的
URL 格式錯誤。
  "createdAt": string (timestamp)
}
```

回應範例值

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "filename": "回應字串",
  "file": "https://example.com/file.jpg",
  "fileType": "回應字串",
  "knowledgeBase": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應字串"
  },
  "size": 456,
  "status": {},
  "parser": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應字串",
    "provider": {},
    "isTimestampSttProvider": false
  },
  "labels": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "回應字串"
    }
```

```
  ],
  "rawUserDefineMetadata": null,
  "speakerLabels": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "originalLabel": "回應字串",
      "customName": "回應字串",
      "displayName": "回應字串"
    }
  ],
  "vectorStorageSize": 456,
  "chunksCount": 456,
  "waitingTime": 456,
  "processingTime": 456,
  "processingTimeDetails": null,
  "previewUrl": "回應字串",
  "createdAt": "回應字串"
}
```


批量刪除檔案

POST `/api/v1/knowledge-bases/{knowledgeBasePk}/files/batch-delete/`

參數

參數名稱	必填	類型	說明
knowledgeBasePk	V	string	

請求內容

請求參數

欄位	類型	必填	說明
ids	array[string]	是	

請求結構範例

```
{
  "ids": [
    string (uuid)
  ]
}
```

請求範例值

```
{
  "ids": [
    "550e8400-e29b-41d4-a716-446655440000"
  ]
}
```

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X POST "https://api.maiagent.ai/api/v1/knowledge-
bases/550e8400-e29b-41d4-a716-446655440000/files/batch-delete/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "ids": [
      "550e8400-e29b-41d4-a716-446655440000"
    ]
  }'

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// 請求內容 (payload)
const data = {
    "ids": [
      "550e8400-e29b-41d4-a716-446655440000"
    ]
  };

axios.post("https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-
e29b-41d4-a716-446655440000/files/batch-delete/", data, config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-e29b-
41d4-a716-446655440000/files/batch-delete/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# 請求內容 (payload)
data = {
    "ids": [
        "550e8400-e29b-41d4-a716-446655440000"
    ]
}

response = requests.post(url, json=data, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>post("https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-e29b-
41d4-a716-446655440000/files/batch-delete/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'ids' => [
                '550e8400-e29b-41d4-a716-446655440000'
            ]
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
{
  "queued": [
    string (uuid)
  ]
  "skipped": [
    {
      "id": string (uuid)
      "reason": string (enum: deleting) // * `deleting` - deleting
    }
  ]
}
```

回應範例值

```
{
  "queued": [
    "550e8400-e29b-41d4-a716-446655440000"
  ],
  "skipped": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "reason": "deleting"
    }
  ]
}
```

批量重新解析檔案

PATCH `/api/v1/knowledge-bases/{knowledgeBasePk}/files/batch-reparse/`

參數

參數名稱	必填	類型	說明
`knowledgeBasePk`	V	string	
`fileType`	X	string	檔案類型過濾，例如：pdf、docx、txt、xlsx 等
`knowledgeBase`	X	string	知識庫 ID
`page`	X	integer	A page number within the paginated result set.
`pageSize`	X	integer	Number of results to return per page.
`query`	X	string	搜尋關鍵字，支援空白分隔的多條件查詢。可搜尋：檔案 ID、檔案名稱、標籤名稱、Metadata value
`status`	X	string	檔案狀態過濾，可選值：initial（初始化）、processing（處理中）、done（完成）、deleting（刪除中）、deleted（已刪除）、failed（失敗） `initial`: Initial ; `processing`: Processing ; `done`: Done ; `deleting`: Deleting ; `deleted`: Deleted ; `faile...

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X PATCH "https://api.maiagent.ai/api/v1/knowledge-
bases/550e8400-e29b-41d4-a716-446655440000/files/batch-reparse/?
fileType=example&knowledgeBase=550e8400-e29b-41d4-a716-
446655440000&page=1&pageSize=1&query=example&status=delete_failed"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '[]'

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// 請求內容 (payload)
const data = [];

axios.patch("https://api.maiagent.ai/api/v1/knowledge-
bases/550e8400-e29b-41d4-a716-446655440000/files/batch-reparse/?
fileType=example&knowledgeBase=550e8400-e29b-41d4-a716-
446655440000&page=1&pageSize=1&query=example&status=delete_failed",
data, config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-e29b-
41d4-a716-446655440000/files/batch-reparse/?
fileType=example&knowledgeBase=550e8400-e29b-41d4-a716-
446655440000&page=1&pageSize=1&query=example&status=delete_failed"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# 請求內容 (payload)
data = []

response = requests.patch(url, json=data, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->patch("https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-e29b-41d4-a716-446655440000/files/batch-reparse/?fileType=example&knowledgeBase=550e8400-e29b-41d4-a716-446655440000&page=1&pageSize=1&query=example&status=delete_failed", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => []
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
{
  "count": integer
  "next"?: string (uri) // 非必填
  "previous"?: string (uri) // 非必填
  "results": [
    {
      "id": string (uuid)
      "filename": string // 檔案名稱
      "file": string (uri) // 要上傳的檔案
      "fileType": string
      "knowledgeBase"?:  // 非必填
      {
        "id": string (uuid)
        "name": string
      }
      "size": integer
      "status":
      {
      }
      "parser":
      {
        "id": string (uuid)
        "name": string
        "provider":
        {
        }
        "isTimestampSttProvider": boolean
      }
      "labels"?: [ // 非必填
        {
          "id": string (uuid)
          "name": string
        }
      ]
      "rawUserDefineMetadata"?: object // 非必填
      "speakerLabels": [
        {
          "id": string (uuid)
          "originalLabel": string // Original speaker label from
diarization (e.g., SPEAKER_00)
          "customName"?: string // User-defined speaker name (e.g., John)
(非必填)
          "displayName": string
        }
```

```
      ]
      "vectorStorageSize": integer // Size of vectors for this file in
Elasticsearch (bytes)
      "chunksCount": integer // Number of chunks/nodes generated from
this file
      "waitingTime": number (double)
      "processingTime": number (double)
      "processingTimeDetails": object
      "previewUrl": string // 簡報（pptx/ppt）回傳可預覽的 pdf 衍生檔 URL（前端
用 PDF 預覽器顯示）；其餘為 None。

用與 `file` 欄位相同的 CustomizedFileFieldSerializer 產 URL，確保格式一致（含各
storage provider 的 presign/host 規則）。不可用 get_absolute_url()——它產出的
URL 格式錯誤。
      "createdAt": string (timestamp)
    }
  ]
}
```

回應範例值

```
{
  "count": 123,
  "next": "http://api.example.org/accounts/?page=4",
  "previous": "http://api.example.org/accounts/?page=2",
  "results": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "filename": "回應字串",
      "file": "https://example.com/file.jpg",
      "fileType": "回應字串",
      "knowledgeBase": {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "name": "回應字串"
      },
      "size": 456,
      "status": {},
      "parser": {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "name": "回應字串",
        "provider": {},
        "isTimestampSttProvider": false
      },
      "labels": [
```

```
        {
          "id": "550e8400-e29b-41d4-a716-446655440000",
          "name": "回應字串"
        }
      ],
      "rawUserDefineMetadata": null,
      "speakerLabels": [
        {
          "id": "550e8400-e29b-41d4-a716-446655440000",
          "originalLabel": "回應字串",
          "customName": "回應字串",
          "displayName": "回應字串"
        }
      ],
      "vectorStorageSize": 456,
      "chunksCount": 456,
      "waitingTime": 456,
      "processingTime": 456,
      "processingTimeDetails": null,
      "previewUrl": "回應字串",
      "createdAt": "回應字串"
    }
  ]
}
```


列出知識庫中的檔案

GET `/api/v1/knowledge-bases/{knowledgeBasePk}/files/`

參數

參數名稱	必填	類型	說明
knowledgeBasePk	V	string	

`fileType`	X	string	檔案類型過濾，例如：pdf、docx、txt、xlsx 等
`knowledgeBase`	X	string	知識庫 ID
`page`	X	integer	A page number within the paginated result set.
`pageSize`	X	integer	Number of results to return per page.
`query`	X	string	搜尋關鍵字，支援空白分隔的多條件查詢。可搜尋：檔案 ID、檔案名稱、標籤名稱、Metadata value
`status`	X	string	檔案狀態過濾，可選值：initial（初始化）、processing（處理中）、done（完成）、deleting（刪除中）、deleted（已刪除）、failed（失敗） `initial`: Initial ; `processing`: Processing ; `done`: Done ; `deleting`: Deleting ; `deleted`: Deleted ; `faile...

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/knowledge-
bases/550e8400-e29b-41d4-a716-446655440000/files/?
fileType=example&knowledgeBase=550e8400-e29b-41d4-a716-
446655440000&page=1&pageSize=1&query=example&status=delete_failed"

  -H "Authorization: Api-Key YOUR_API_KEY"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-e29b-41d4-a716-446655440000/files/?fileType=example&knowledgeBase=550e8400-e29b-41d4-a716-446655440000&page=1&pageSize=1&query=example&status=delete_failed", config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-e29b-41d4-a716-446655440000/files/?fileType=example&knowledgeBase=550e8400-e29b-41d4-a716-446655440000&page=1&pageSize=1&query=example&status=delete_failed"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-e29b-
41d4-a716-446655440000/files/?
fileType=example&knowledgeBase=550e8400-e29b-41d4-a716-
446655440000&page=1&pageSize=1&query=example&status=delete_failed",
[
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
{
  "count": integer
  "next"?: string (uri) // 非必填
  "previous"?: string (uri) // 非必填
  "results": [
    {
      "id": string (uuid)
      "filename": string // 檔案名稱
      "file": string (uri) // 要上傳的檔案
      "fileType": string
      "knowledgeBase"?:  // 非必填
      {
        "id": string (uuid)
        "name": string
      }
      "size": integer
      "status":
      {
      }
      "parser":
      {
        "id": string (uuid)
        "name": string
        "provider":
        {
        }
        "isTimestampSttProvider": boolean
      }
      "labels"?: [ // 非必填
        {
          "id": string (uuid)
          "name": string
        }
      ]
      "rawUserDefineMetadata"?: object // 非必填
      "speakerLabels": [
        {
          "id": string (uuid)
          "originalLabel": string // Original speaker label from
diarization (e.g., SPEAKER_00)
          "customName"?: string // User-defined speaker name (e.g., John)
(非必填)
          "displayName": string
        }
```

```
      ]
      "vectorStorageSize": integer // Size of vectors for this file in
Elasticsearch (bytes)
      "chunksCount": integer // Number of chunks/nodes generated from
this file
      "waitingTime": number (double)
      "processingTime": number (double)
      "processingTimeDetails": object
      "previewUrl": string // 簡報（pptx/ppt）回傳可預覽的 pdf 衍生檔 URL（前端
用 PDF 預覽器顯示）；其餘為 None。

用與 `file` 欄位相同的 CustomizedFileFieldSerializer 產 URL，確保格式一致（含各
storage provider 的 presign/host 規則）。不可用 get_absolute_url()——它產出的
URL 格式錯誤。
      "createdAt": string (timestamp)
    }
  ]
}
```

回應範例值

```
{
  "count": 123,
  "next": "http://api.example.org/accounts/?page=4",
  "previous": "http://api.example.org/accounts/?page=2",
  "results": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "filename": "回應字串",
      "file": "https://example.com/file.jpg",
      "fileType": "回應字串",
      "knowledgeBase": {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "name": "回應字串"
      },
      "size": 456,
      "status": {},
      "parser": {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "name": "回應字串",
        "provider": {},
        "isTimestampSttProvider": false
      },
      "labels": [
```

```
        {
          "id": "550e8400-e29b-41d4-a716-446655440000",
          "name": "回應字串"
        }
      ],
      "rawUserDefineMetadata": null,
      "speakerLabels": [
        {
          "id": "550e8400-e29b-41d4-a716-446655440000",
          "originalLabel": "回應字串",
          "customName": "回應字串",
          "displayName": "回應字串"
        }
      ],
      "vectorStorageSize": 456,
      "chunksCount": 456,
      "waitingTime": 456,
      "processingTime": 456,
      "processingTimeDetails": null,
      "previewUrl": "回應字串",
      "createdAt": "回應字串"
    }
  ]
}
```


取得特定檔案詳情

`GET` `/api/v1/knowledge-bases/{knowledgeBasePk}/files/{id}`

參數

參數名稱	必填	類型	說明
`id`	V	string	A UUID string identifying this Knowledge Base File.

`knowledgeBasePk`	V	string

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/knowledge-
bases/550e8400-e29b-41d4-a716-446655440000/files/550e8400-e29b-41d4-
a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-e29b-41d4-a716-446655440000/files/550e8400-e29b-41d4-a716-446655440000/", config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-e29b-41d4-a716-446655440000/files/550e8400-e29b-41d4-a716-446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-e29b-
41d4-a716-446655440000/files/550e8400-e29b-41d4-a716-446655440000/",
[
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
{
  "id": string (uuid)
```

```
  "filename": string // 檔案名稱
  "file": string (uri) // 要上傳的檔案
  "fileType": string
  "knowledgeBase"?:  // 非必填
  {
    "id": string (uuid)
    "name": string
  }
  "size": integer
  "status":
  {
  }
  "parser":
  {
    "id": string (uuid)
    "name": string
    "provider":
    {
    }
    "isTimestampSttProvider": boolean
  }
  "labels"?: [ // 非必填
    {
      "id": string (uuid)
      "name": string
    }
  ]
  "rawUserDefineMetadata"?: object // 非必填
  "speakerLabels": [
    {
      "id": string (uuid)
      "originalLabel": string // Original speaker label from diarization
(e.g., SPEAKER_00)
      "customName"?: string // User-defined speaker name (e.g., John) (非
必填)
      "displayName": string
    }
  ]
  "vectorStorageSize": integer // Size of vectors for this file in
Elasticsearch (bytes)
  "chunksCount": integer // Number of chunks/nodes generated from this
file
  "waitingTime": number (double)
  "processingTime": number (double)
  "processingTimeDetails": object
```

```
  "previewUrl": string // 簡報（pptx/ppt）回傳可預覽的 pdf 衍生檔 URL（前端用 PDF 預覽器顯示）；其餘為 None。

用與 `file` 欄位相同的 CustomizedFileFieldSerializer 產 URL，確保格式一致（含各 storage provider 的 presign/host 規則）。不可用 get_absolute_url()——它產出的 URL 格式錯誤。
  "createdAt": string (timestamp)
}
```

回應範例值


```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "filename": "回應字串",
  "file": "https://example.com/file.jpg",
  "fileType": "回應字串",
  "knowledgeBase": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應字串"
  },
  "size": 456,
  "status": {},
  "parser": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應字串",
    "provider": {},
    "isTimestampSttProvider": false
  },
  "labels": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "回應字串"
    }
  ],
  "rawUserDefineMetadata": null,
  "speakerLabels": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "originalLabel": "回應字串",
      "customName": "回應字串",
      "displayName": "回應字串"
    }
  ],
  "vectorStorageSize": 456,
```

```
  "chunksCount": 456,
  "waitingTime": 456,
  "processingTime": 456,
  "processingTimeDetails": null,
  "previewUrl": "回應字串",
  "createdAt": "回應字串"
}
```


取得檔案最新失敗原因

`GET` `/api/v1/knowledge-bases/{knowledgeBasePk}/files/{id}/latest-failed-reason/`

參數

參數名稱	必填	類型	說明
`id`	V	string	A UUID string identifying this Knowledge Base File.
`knowledgeBasePk`	V	string	

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/knowledge-
bases/550e8400-e29b-41d4-a716-446655440000/files/550e8400-e29b-41d4-
a716-446655440000/latest-failed-reason/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-e29b-41d4-a716-446655440000/files/550e8400-e29b-41d4-a716-446655440000/latest-failed-reason/", config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-e29b-41d4-a716-446655440000/files/550e8400-e29b-41d4-a716-446655440000/latest-failed-reason/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-e29b-
41d4-a716-446655440000/files/550e8400-e29b-41d4-a716-
446655440000/latest-failed-reason/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
{
  "id": string (uuid)
```

```
  "errorMessage": string
  "errorCode"?: string // Machine-readable code of a known failure type
(see FAILED_REASON_LOCALIZED_MESSAGES in whizchat/parsers/exceptions.py);
the serializer translates it into the request language on read. An empty
string means no translation, and error_message is shown as is. (非必填)
  "createdAt": string (timestamp)
}
```

回應範例值

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "errorMessage": "回應字串",
  "errorCode": "回應字串",
  "createdAt": "回應字串"
}
```

取得檔案轉錄內容

GET `/api/v1/knowledge-bases/{knowledgeBasePk}/files/{id}/transcription/`

參數

參數名稱	必填	類型	說明
`id`	V	string	A UUID string identifying this Knowledge Base File.
`knowledgeBasePk`	V	string	

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/knowledge-
bases/550e8400-e29b-41d4-a716-446655440000/files/550e8400-e29b-41d4-
a716-446655440000/transcription/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-e29b-41d4-a716-446655440000/files/550e8400-e29b-41d4-a716-446655440000/transcription/", config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-e29b-41d4-a716-446655440000/files/550e8400-e29b-41d4-a716-446655440000/transcription/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-e29b-
41d4-a716-446655440000/files/550e8400-e29b-41d4-a716-
446655440000/transcription/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
{
  "id": string (uuid)
```

```
  "filename": string // 檔案名稱
  "file": string (uri) // 要上傳的檔案
  "fileType": string
  "knowledgeBase"?:  // 非必填
  {
    "id": string (uuid)
    "name": string
  }
  "size": integer
  "status":
  {
  }
  "parser":
  {
    "id": string (uuid)
    "name": string
    "provider":
    {
    }
    "isTimestampSttProvider": boolean
  }
  "labels"?: [ // 非必填
    {
      "id": string (uuid)
      "name": string
    }
  ]
  "rawUserDefineMetadata"?: object // 非必填
  "speakerLabels": [
    {
      "id": string (uuid)
      "originalLabel": string // Original speaker label from diarization
(e.g., SPEAKER_00)
      "customName"?: string // User-defined speaker name (e.g., John) (非
必填)
      "displayName": string
    }
  ]
  "vectorStorageSize": integer // Size of vectors for this file in
Elasticsearch (bytes)
  "chunksCount": integer // Number of chunks/nodes generated from this
file
  "waitingTime": number (double)
  "processingTime": number (double)
  "processingTimeDetails": object
```

```
  "previewUrl": string // 簡報（pptx/ppt）回傳可預覽的 pdf 衍生檔 URL（前端用 PDF 預覽器顯示）；其餘為 None。

用與 `file` 欄位相同的 CustomizedFileFieldSerializer 產 URL，確保格式一致（含各 storage provider 的 presign/host 規則）。不可用 get_absolute_url()——它產出的 URL 格式錯誤。
  "createdAt": string (timestamp)
}
```

回應範例值


```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "filename": "回應字串",
  "file": "https://example.com/file.jpg",
  "fileType": "回應字串",
  "knowledgeBase": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應字串"
  },
  "size": 456,
  "status": {},
  "parser": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應字串",
    "provider": {},
    "isTimestampSttProvider": false
  },
  "labels": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "回應字串"
    }
  ],
  "rawUserDefineMetadata": null,
  "speakerLabels": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "originalLabel": "回應字串",
      "customName": "回應字串",
      "displayName": "回應字串"
    }
  ],
  "vectorStorageSize": 456,
```

```
  "chunksCount": 456,
  "waitingTime": 456,
  "processingTime": 456,
  "processingTimeDetails": null,
  "previewUrl": "回應字串",
  "createdAt": "回應字串"
}
```


更新檔案資訊

PUT `/api/v1/knowledge-bases/{knowledgeBasePk}/files/{id}`

參數

參數名稱	必填	類型	說明
`id`	V	string	A UUID string identifying this Knowledge Base File.
`knowledgeBasePk`	V	string	

請求內容

請求參數

欄位	類型	必填	說明
filename	string	是	檔案名稱
file	string (uri)	是	要上傳的檔案
parser	string (uuid)	否	

欄位	類型	必填	說明
labels	array[IdName]	否	
rawUserDefineMetadata	object	否	
asrOptions	object	否	Per-file canonical transcription options (languages, prompt, diarization). Empty means no per-file options: provider defaults apply. Completely decoupled from user-defined metadata; never indexed for ...

請求結構範例

```
{
  "filename": string // 檔案名稱
  "file": string (uri) // 要上傳的檔案
  "parser"?: string (uuid) // 非必填
  "labels"?: [ // 非必填
    {
      "id": string (uuid)
    }
  ]
  "rawUserDefineMetadata"?: object // 非必填
  "asrOptions"?: object // Per-file canonical transcription options
(languages, prompt, diarization). Empty means no per-file options:
provider defaults apply. Completely decoupled from user-defined metadata;
never indexed for search. (非必填)
}
```

請求範例值

```
{
  "filename": "document.pdf",
  "file": "https://example.com/file.jpg",
  "parser": "550e8400-e29b-41d4-a716-446655440000",
  "labels": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000"
    }
```

```
  ],
  "rawUserDefineMetadata": null,
  "asrOptions": null
}
```

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X PUT "https://api.maiagent.ai/api/v1/knowledge-
bases/550e8400-e29b-41d4-a716-446655440000/files/550e8400-e29b-41d4-
a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "filename": "document.pdf",
    "file": "https://example.com/file.jpg",
    "parser": "550e8400-e29b-41d4-a716-446655440000",
    "labels": [
      {
        "id": "550e8400-e29b-41d4-a716-446655440000"
      }
    ],
    "rawUserDefineMetadata": null,
    "asrOptions": null
  }'

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// 請求內容 (payload)
const data = {
    "filename": "document.pdf",
    "file": "https://example.com/file.jpg",
    "parser": "550e8400-e29b-41d4-a716-446655440000",
    "labels": [
      {
        "id": "550e8400-e29b-41d4-a716-446655440000"
      }
    ],
    "rawUserDefineMetadata": null,
    "asrOptions": null
  };

axios.put("https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-
e29b-41d4-a716-446655440000/files/550e8400-e29b-41d4-a716-
446655440000/", data, config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-e29b-
41d4-a716-446655440000/files/550e8400-e29b-41d4-a716-446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# 請求內容 (payload)
data = {
    "filename": "document.pdf",
    "file": "https://example.com/file.jpg",
    "parser": "550e8400-e29b-41d4-a716-446655440000",
    "labels": [
        {
            "id": "550e8400-e29b-41d4-a716-446655440000"
        }
    ],
    "rawUserDefineMetadata": None,
    "asrOptions": None
}

response = requests.put(url, json=data, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>put("https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-e29b-
41d4-a716-446655440000/files/550e8400-e29b-41d4-a716-446655440000/",
[
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'filename' => 'document.pdf',
            'file' => 'https://example.com/file.jpg',
            'parser' => '550e8400-e29b-41d4-a716-446655440000',
            'labels' => [
                [
                    'id' => '550e8400-e29b-41d4-a716-446655440000'
                ]
            ],
            'rawUserDefineMetadata' => null,
            'asrOptions' => null
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
{
  "id": string (uuid)
  "filename": string // 檔案名稱
  "file": string (uri) // 要上傳的檔案
  "fileType": string
  "knowledgeBase"?:  // 非必填
  {
    "id": string (uuid)
    "name": string
  }
  "size": integer
  "status":
  {
  }
  "parser":
  {
    "id": string (uuid)
    "name": string
    "provider":
    {
    }
    "isTimestampSttProvider": boolean
  }
  "labels"?: [ // 非必填
    {
      "id": string (uuid)
      "name": string
    }
  ]
  "rawUserDefineMetadata"?: object // 非必填
  "speakerLabels": [
    {
      "id": string (uuid)
      "originalLabel": string // Original speaker label from diarization
(e.g., SPEAKER_00)
```

```
      "customName"?: string // User-defined speaker name (e.g., John) (非必填)
      "displayName": string
    }
  ]
  "vectorStorageSize": integer // Size of vectors for this file in Elasticsearch (bytes)
  "chunksCount": integer // Number of chunks/nodes generated from this file
  "waitingTime": number (double)
  "processingTime": number (double)
  "processingTimeDetails": object
  "previewUrl": string // 簡報（pptx/ppt）回傳可預覽的 pdf 衍生檔 URL（前端用 PDF 預覽器顯示）；其餘為 None。

用與 `file` 欄位相同的 CustomizedFileFieldSerializer 產 URL，確保格式一致（含各 storage provider 的 presign/host 規則）。不可用 get_absolute_url()——它產出的 URL 格式錯誤。
  "createdAt": string (timestamp)
}
```

回應範例值

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "filename": "回應字串",
  "file": "https://example.com/file.jpg",
  "fileType": "回應字串",
  "knowledgeBase": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應字串"
  },
  "size": 456,
  "status": {},
  "parser": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應字串",
    "provider": {},
    "isTimestampSttProvider": false
  },
  "labels": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "回應字串"
```

```
    }
  ],
  "rawUserDefineMetadata": null,
  "speakerLabels": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "originalLabel": "回應字串",
      "customName": "回應字串",
      "displayName": "回應字串"
    }
  ],
  "vectorStorageSize": 456,
  "chunksCount": 456,
  "waitingTime": 456,
  "processingTime": 456,
  "processingTimeDetails": null,
  "previewUrl": "回應字串",
  "createdAt": "回應字串"
}
```


部分更新檔案

PATCH `/api/v1/knowledge-bases/{knowledgeBasePk}/files/{id}`

參數

參數名稱	必填	類型	說明
`id`	V	string	A UUID string identifying this Knowledge Base File.
`knowledgeBasePk`	V	string	

請求內容

請求參數

欄位	類型	必填	說明
filename	string	否	檔案名稱
file	string (uri)	否	要上傳的檔案
parser	string (uuid)	否	
labels	array[IdName]	否	
rawUserDefineMetadata	object	否	
asrOptions	object	否	Per-file canonical transcription options (languages, prompt, diarization). Empty means no per-file options: provider defaults apply. Completely decoupled from user-defined metadata; never indexed for ...

請求結構範例

```
{
  "filename"?: string // 檔案名稱 (非必填)
  "file"?: string (uri) // 要上傳的檔案 (非必填)
  "parser"?: string (uuid) // 非必填
  "labels"?: [ // 非必填
    {
      "id": string (uuid)
    }
  ]
  "rawUserDefineMetadata"?: object // 非必填
  "asrOptions"?: object // Per-file canonical transcription options
(languages, prompt, diarization). Empty means no per-file options:
provider defaults apply. Completely decoupled from user-defined metadata;
never indexed for search. (非必填)
}
```

請求範例值

```
{
  "filename": "document.pdf",
  "file": "https://example.com/file.jpg",
  "parser": "550e8400-e29b-41d4-a716-446655440000",
  "labels": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000"
    }
  ],
  "rawUserDefineMetadata": null,
  "asrOptions": null
}
```

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X PATCH "https://api.maiagent.ai/api/v1/knowledge-
bases/550e8400-e29b-41d4-a716-446655440000/files/550e8400-e29b-41d4-
a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "filename": "document.pdf",
    "file": "https://example.com/file.jpg",
    "parser": "550e8400-e29b-41d4-a716-446655440000",
    "labels": [
      {
        "id": "550e8400-e29b-41d4-a716-446655440000"
      }
    ],
    "rawUserDefineMetadata": null,
    "asrOptions": null
  }'

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// 請求內容 (payload)
const data = {
    "filename": "document.pdf",
    "file": "https://example.com/file.jpg",
    "parser": "550e8400-e29b-41d4-a716-446655440000",
    "labels": [
      {
        "id": "550e8400-e29b-41d4-a716-446655440000"
      }
    ],
    "rawUserDefineMetadata": null,
    "asrOptions": null
  };

axios.patch("https://api.maiagent.ai/api/v1/knowledge-
bases/550e8400-e29b-41d4-a716-446655440000/files/550e8400-e29b-41d4-
a716-446655440000/", data, config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-e29b-
41d4-a716-446655440000/files/550e8400-e29b-41d4-a716-446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# 請求內容 (payload)
data = {
    "filename": "document.pdf",
    "file": "https://example.com/file.jpg",
    "parser": "550e8400-e29b-41d4-a716-446655440000",
    "labels": [
        {
            "id": "550e8400-e29b-41d4-a716-446655440000"
        }
    ],
    "rawUserDefineMetadata": None,
    "asrOptions": None
}

response = requests.patch(url, json=data, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>patch("https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-
e29b-41d4-a716-446655440000/files/550e8400-e29b-41d4-a716-
446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'filename' => 'document.pdf',
            'file' => 'https://example.com/file.jpg',
            'parser' => '550e8400-e29b-41d4-a716-446655440000',
            'labels' => [
                [
                    'id' => '550e8400-e29b-41d4-a716-446655440000'
                ]
            ],
            'rawUserDefineMetadata' => null,
            'asrOptions' => null
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
{
  "id": string (uuid)
  "filename": string // 檔案名稱
  "file": string (uri) // 要上傳的檔案
  "fileType": string
  "knowledgeBase"?:  // 非必填
  {
    "id": string (uuid)
    "name": string
  }
  "size": integer
  "status":
  {
  }
  "parser":
  {
    "id": string (uuid)
    "name": string
    "provider":
    {
    }
    "isTimestampSttProvider": boolean
  }
  "labels"?: [ // 非必填
    {
      "id": string (uuid)
      "name": string
    }
  ]
  "rawUserDefineMetadata"?: object // 非必填
  "speakerLabels": [
    {
      "id": string (uuid)
      "originalLabel": string // Original speaker label from diarization
(e.g., SPEAKER_00)
```

```
      "customName"?: string // User-defined speaker name (e.g., John) (非必填)
      "displayName": string
    }
  ]
  "vectorStorageSize": integer // Size of vectors for this file in Elasticsearch (bytes)
  "chunksCount": integer // Number of chunks/nodes generated from this file
  "waitingTime": number (double)
  "processingTime": number (double)
  "processingTimeDetails": object
  "previewUrl": string // 簡報（pptx/ppt）回傳可預覽的 pdf 衍生檔 URL（前端用 PDF 預覽器顯示）；其餘為 None。

用與 `file` 欄位相同的 CustomizedFileFieldSerializer 產 URL，確保格式一致（含各 storage provider 的 presign/host 規則）。不可用 get_absolute_url()——它產出的 URL 格式錯誤。
  "createdAt": string (timestamp)
}
```

回應範例值

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "filename": "回應字串",
  "file": "https://example.com/file.jpg",
  "fileType": "回應字串",
  "knowledgeBase": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應字串"
  },
  "size": 456,
  "status": {},
  "parser": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應字串",
    "provider": {},
    "isTimestampSttProvider": false
  },
  "labels": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "回應字串"
```

```
    }
  ],
  "rawUserDefineMetadata": null,
  "speakerLabels": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "originalLabel": "回應字串",
      "customName": "回應字串",
      "displayName": "回應字串"
    }
  ],
  "vectorStorageSize": 456,
  "chunksCount": 456,
  "waitingTime": 456,
  "processingTime": 456,
  "processingTimeDetails": null,
  "previewUrl": "回應字串",
  "createdAt": "回應字串"
}
```


刪除檔案

DELETE `/api/v1/knowledge-bases/{knowledgeBasePk}/files/{id}`

參數

參數名稱	必填	類型	說明
`id`	V	string	A UUID string identifying this Knowledge Base File.
`knowledgeBasePk`	V	string	

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X DELETE "https://api.maiagent.ai/api/v1/knowledge-
bases/550e8400-e29b-41d4-a716-446655440000/files/550e8400-e29b-41d4-
a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

// 請求內容 (payload)
const data = null;

axios.delete("https://api.maiagent.ai/api/v1/knowledge-
bases/550e8400-e29b-41d4-a716-446655440000/files/550e8400-e29b-41d4-
a716-446655440000/", data, config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-e29b-41d4-a716-446655440000/files/550e8400-e29b-41d4-a716-446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.delete(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>delete("https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-
e29b-41d4-a716-446655440000/files/550e8400-e29b-41d4-a716-
446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 202

回應結構範例

```
{
  "detail": string
```

```
}
```

回應範例值

```
{
  "detail": "回應字串"
}
```

狀態碼: 204 - No response body

建立檔案翻譯

`POST` `/api/v1/knowledge-bases/{knowledgeBasePk}/files/{knowledgeBaseFilePk}/translations/`

參數

參數名稱	必填	類型	說明
`knowledgeBaseFilePk`	V	string	
`knowledgeBasePk`	V	string	

請求內容

請求參數

欄位	類型	必填	說明
sourceLanguage	string	否	
targetLanguage	string	是	

欄位	類型	必填	說明
customPrompt	string	否	
largeLanguageModelId	string (uuid)	是	

請求結構範例

```
{
  "sourceLanguage"?: string // 非必填
  "targetLanguage": string
  "customPrompt"?: string // 非必填
  "largeLanguageModelId": string (uuid)
}
```

請求範例值

```
{
  "sourceLanguage": "範例字串",
  "targetLanguage": "範例字串",
  "customPrompt": "範例字串",
  "largeLanguageModelId": "550e8400-e29b-41d4-a716-446655440000"
}
```

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X POST "https://api.maiagent.ai/api/v1/knowledge-
bases/{knowledgeBasePk}/files/{knowledgeBaseFilePk}/translations/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "sourceLanguage": "範例字串",
    "targetLanguage": "範例字串",
    "customPrompt": "範例字串",
    "largeLanguageModelId": "550e8400-e29b-41d4-a716-446655440000"
  }'

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// 請求內容 (payload)
const data = {
    "sourceLanguage": "範例字串",
    "targetLanguage": "範例字串",
    "customPrompt": "範例字串",
    "largeLanguageModelId": "550e8400-e29b-41d4-a716-446655440000"
  };

axios.post("https://api.maiagent.ai/api/v1/knowledge-
bases/{knowledgeBasePk}/files/{knowledgeBaseFilePk}/translations/",
data, config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/knowledge-
bases/{knowledgeBasePk}/files/{knowledgeBaseFilePk}/translations/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# 請求內容 (payload)
data = {
    "sourceLanguage": "範例字串",
    "targetLanguage": "範例字串",
    "customPrompt": "範例字串",
    "largeLanguageModelId": "550e8400-e29b-41d4-a716-446655440000"
}

response = requests.post(url, json=data, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->post("https://api.maiagent.ai/api/v1/knowledge-bases/{knowledgeBasePk}/files/{knowledgeBaseFilePk}/translations/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'sourceLanguage' => '範例字串',
            'targetLanguage' => '範例字串',
            'customPrompt' => '範例字串',
            'largeLanguageModelId' => '550e8400-e29b-41d4-a716-446655440000'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 201

回應結構範例

```
{
  "sourceLanguage"?: string // 非必填
  "targetLanguage": string
  "customPrompt"?: string // 非必填
  "largeLanguageModelId": string (uuid)
}
```

回應範例值

```
{
  "sourceLanguage": "回應字串",
  "targetLanguage": "回應字串",
  "customPrompt": "回應字串",
  "largeLanguageModelId": "550e8400-e29b-41d4-a716-446655440000"
}
```

列出檔案翻譯

GET `/api/v1/knowledge-bases/{knowledgeBasePk}/files/{knowledgeBaseFilePk}/translations/`

參數

參數名稱	必填	類型	說明
`knowledgeBaseFilePk`	V	string	
`knowledgeBasePk`	V	string	

`page`	X	integer	A page number within the paginated result set.
`pageSize`	X	integer	Number of results to return per page.

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/knowledge-
bases/{knowledgeBasePk}/files/{knowledgeBaseFilePk}/translations/?
page=1&pageSize=1"

  -H "Authorization: Api-Key YOUR_API_KEY"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/knowledge-
bases/{knowledgeBasePk}/files/{knowledgeBaseFilePk}/translations/?
page=1&pageSize=1", config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/knowledge-
bases/{knowledgeBasePk}/files/{knowledgeBaseFilePk}/translations/?
page=1&pageSize=1"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/knowledge-
bases/{knowledgeBasePk}/files/{knowledgeBaseFilePk}/translations/?
page=1&pageSize=1", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
{
  "count": integer
```

```
  "next"?: string (uri) // 非必填
  "previous"?: string (uri) // 非必填
  "results": [
    {
      "id": string (uuid)
      "chatbotFileId": string (uuid)
      "chatbotFileFilename": string
      "organization": string (uuid)
      "largeLanguageModel":
      {
        "id": string (uuid)
        "name": string
      }
      "sourceLanguage": string
      "targetLanguage": string
      "customPrompt": string // User-provided terminology/glossary rules
      "status":
      {
      }
      "errorMessage": string
      "translatedFileUrl": string
      "bilingualFileUrl": string
      "processDuration": string
      "processingDurationSeconds": number (double)
      "pageCount": integer
      "originalWordCount": integer
      "translatedWordCount": integer
      "inputTokensUsed": integer
      "outputTokensUsed": integer
      "totalTokensUsed": integer
      "originalFileSize": integer
      "translatedFileSize": integer
      "bilingualFileSize": integer
      "llmTranslationDuration": string // Total time spent on LLM API
calls
      "llmTranslationDurationSeconds": number (double)
      "llmCallCount": integer // Number of LLM API calls made
      "avgLlmCallDuration": number (double) // Average time per LLM call
in seconds
      "pdfParsingDuration": string // Time spent on PDF parsing and
processing
      "pdfParsingDurationSeconds": number (double)
      "fileSavingDuration": string // Time spent on saving output files
      "fileSavingDurationSeconds": number (double)
      "startedAt": string (timestamp)
```

```
      "completedAt": string (timestamp)
      "createdAt": string (timestamp)
      "updatedAt": string (timestamp)
    }
  ]
}
```

回應範例值

```
{
  "count": 123,
  "next": "http://api.example.org/accounts/?page=4",
  "previous": "http://api.example.org/accounts/?page=2",
  "results": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "chatbotFileId": "550e8400-e29b-41d4-a716-446655440000",
      "chatbotFileFilename": "回應字串",
      "organization": "550e8400-e29b-41d4-a716-446655440000",
      "largeLanguageModel": {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "name": "回應字串"
      },
      "sourceLanguage": "回應字串",
      "targetLanguage": "回應字串",
      "customPrompt": "回應字串",
      "status": {},
      "errorMessage": "回應字串",
      "translatedFileUrl": "回應字串",
      "bilingualFileUrl": "回應字串",
      "processDuration": "回應字串",
      "processingDurationSeconds": 456,
      "pageCount": 456,
      "originalWordCount": 456,
      "translatedWordCount": 456,
      "inputTokensUsed": 456,
      "outputTokensUsed": 456,
      "totalTokensUsed": 456,
      "originalFileSize": 456,
      "translatedFileSize": 456,
      "bilingualFileSize": 456,
      "llmTranslationDuration": "回應字串",
      "llmTranslationDurationSeconds": 456,
      "llmCallCount": 456,
```

```
      "avgLlmCallDuration": 456,
      "pdfParsingDuration": "回應字串",
      "pdfParsingDurationSeconds": 456,
      "fileSavingDuration": "回應字串",
      "fileSavingDurationSeconds": 456,
      "startedAt": "回應字串",
      "completedAt": "回應字串",
      "createdAt": "回應字串",
      "updatedAt": "回應字串"
    }
  ]
}
```


取得特定翻譯

`GET` `/api/v1/knowledge-bases/{knowledgeBasePk}/files/{knowledgeBaseFilePk}/translations/{id}`

參數

參數名稱	必填	類型	說明
`id`	V	string	A UUID string identifying this File Translation.
`knowledgeBaseFilePk`	V	string	
`knowledgeBasePk`	V	string	

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/knowledge-
bases/{knowledgeBasePk}/files/{knowledgeBaseFilePk}/translations/550
e8400-e29b-41d4-a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/knowledge-
bases/{knowledgeBasePk}/files/{knowledgeBaseFilePk}/translations/550
e8400-e29b-41d4-a716-446655440000/", config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/knowledge-
bases/{knowledgeBasePk}/files/{knowledgeBaseFilePk}/translations/550
e8400-e29b-41d4-a716-446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/knowledge-
bases/{knowledgeBasePk}/files/{knowledgeBaseFilePk}/translations/550
e8400-e29b-41d4-a716-446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
{
  "id": string (uuid)
```

```
  "chatbotFileId": string (uuid)
  "chatbotFileFilename": string
  "organization": string (uuid)
  "largeLanguageModel":
  {
    "id": string (uuid)
    "name": string
  }
  "sourceLanguage": string
  "targetLanguage": string
  "customPrompt": string // User-provided terminology/glossary rules
  "status":
  {
  }
  "errorMessage": string
  "translatedFileUrl": string
  "bilingualFileUrl": string
  "processDuration": string
  "processingDurationSeconds": number (double)
  "pageCount": integer
  "originalWordCount": integer
  "translatedWordCount": integer
  "inputTokensUsed": integer
  "outputTokensUsed": integer
  "totalTokensUsed": integer
  "originalFileSize": integer
  "translatedFileSize": integer
  "bilingualFileSize": integer
  "llmTranslationDuration": string // Total time spent on LLM API calls
  "llmTranslationDurationSeconds": number (double)
  "llmCallCount": integer // Number of LLM API calls made
  "avgLlmCallDuration": number (double) // Average time per LLM call in
seconds
  "pdfParsingDuration": string // Time spent on PDF parsing and
processing
  "pdfParsingDurationSeconds": number (double)
  "fileSavingDuration": string // Time spent on saving output files
  "fileSavingDurationSeconds": number (double)
  "startedAt": string (timestamp)
  "completedAt": string (timestamp)
  "createdAt": string (timestamp)
  "updatedAt": string (timestamp)
}
```

回應範例值

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "chatbotFileId": "550e8400-e29b-41d4-a716-446655440000",
  "chatbotFileFilename": "回應字串",
  "organization": "550e8400-e29b-41d4-a716-446655440000",
  "largeLanguageModel": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應字串"
  },
  "sourceLanguage": "回應字串",
  "targetLanguage": "回應字串",
  "customPrompt": "回應字串",
  "status": {},
  "errorMessage": "回應字串",
  "translatedFileUrl": "回應字串",
  "bilingualFileUrl": "回應字串",
  "processDuration": "回應字串",
  "processingDurationSeconds": 456,
  "pageCount": 456,
  "originalWordCount": 456,
  "translatedWordCount": 456,
  "inputTokensUsed": 456,
  "outputTokensUsed": 456,
  "totalTokensUsed": 456,
  "originalFileSize": 456,
  "translatedFileSize": 456,
  "bilingualFileSize": 456,
  "llmTranslationDuration": "回應字串",
  "llmTranslationDurationSeconds": 456,
  "llmCallCount": 456,
  "avgLlmCallDuration": 456,
  "pdfParsingDuration": "回應字串",
  "pdfParsingDurationSeconds": 456,
  "fileSavingDuration": "回應字串",
  "fileSavingDurationSeconds": 456,
  "startedAt": "回應字串",
  "completedAt": "回應字串",
  "createdAt": "回應字串",
  "updatedAt": "回應字串"
}
```

刪除翻譯

DELETE `/api/v1/knowledge-bases/{knowledgeBasePk}/files/{knowledgeBaseFilePk}/translations/{id}`

參數

參數名稱	必填	類型	說明
`id`	V	string	A UUID string identifying this File Translation.
`knowledgeBaseFilePk`	V	string	
`knowledgeBasePk`	V	string	

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X DELETE "https://api.maiagent.ai/api/v1/knowledge-bases/{knowledgeBasePk}/files/{knowledgeBaseFilePk}/translations/550e8400-e29b-41d4-a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

// 請求內容 (payload)
const data = null;

axios.delete("https://api.maiagent.ai/api/v1/knowledge-
bases/{knowledgeBasePk}/files/{knowledgeBaseFilePk}/translations/550
e8400-e29b-41d4-a716-446655440000/", data, config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/knowledge-
bases/{knowledgeBasePk}/files/{knowledgeBaseFilePk}/translations/550
e8400-e29b-41d4-a716-446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.delete(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>delete("https://api.maiagent.ai/api/v1/knowledge-
bases/{knowledgeBasePk}/files/{knowledgeBaseFilePk}/translations/550
e8400-e29b-41d4-a716-446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼	說明
204	No response body

下載翻譯檔案

GET `/api/v1/knowledge-bases/{knowledgeBasePk}/files/{knowledgeBaseFilePk}/translations/{id}/download/`

參數

參數名稱	必填	類型	說明
`id`	V	string	A UUID string identifying this File Translation.
`knowledgeBaseFilePk`	V	string	
`knowledgeBasePk`	V	string	

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/knowledge-bases/{knowledgeBasePk}/files/{knowledgeBaseFilePk}/translations/550e8400-e29b-41d4-a716-446655440000/download/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/knowledge-
bases/{knowledgeBasePk}/files/{knowledgeBaseFilePk}/translations/550
e8400-e29b-41d4-a716-446655440000/download/", config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/knowledge-
bases/{knowledgeBasePk}/files/{knowledgeBaseFilePk}/translations/550
e8400-e29b-41d4-a716-446655440000/download/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/knowledge-
bases/{knowledgeBasePk}/files/{knowledgeBaseFilePk}/translations/550
e8400-e29b-41d4-a716-446655440000/download/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
{
  "id": string (uuid)
```

```
  "chatbotFileId": string (uuid)
  "chatbotFileFilename": string
  "organization": string (uuid)
  "largeLanguageModel":
  {
    "id": string (uuid)
    "name": string
  }
  "sourceLanguage": string
  "targetLanguage": string
  "customPrompt": string // User-provided terminology/glossary rules
  "status":
  {
  }
  "errorMessage": string
  "translatedFileUrl": string
  "bilingualFileUrl": string
  "processDuration": string
  "processingDurationSeconds": number (double)
  "pageCount": integer
  "originalWordCount": integer
  "translatedWordCount": integer
  "inputTokensUsed": integer
  "outputTokensUsed": integer
  "totalTokensUsed": integer
  "originalFileSize": integer
  "translatedFileSize": integer
  "bilingualFileSize": integer
  "llmTranslationDuration": string // Total time spent on LLM API calls
  "llmTranslationDurationSeconds": number (double)
  "llmCallCount": integer // Number of LLM API calls made
  "avgLlmCallDuration": number (double) // Average time per LLM call in
seconds
  "pdfParsingDuration": string // Time spent on PDF parsing and
processing
  "pdfParsingDurationSeconds": number (double)
  "fileSavingDuration": string // Time spent on saving output files
  "fileSavingDurationSeconds": number (double)
  "startedAt": string (timestamp)
  "completedAt": string (timestamp)
  "createdAt": string (timestamp)
  "updatedAt": string (timestamp)
}
```

回應範例值

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "chatbotFileId": "550e8400-e29b-41d4-a716-446655440000",
  "chatbotFileFilename": "回應字串",
  "organization": "550e8400-e29b-41d4-a716-446655440000",
  "largeLanguageModel": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應字串"
  },
  "sourceLanguage": "回應字串",
  "targetLanguage": "回應字串",
  "customPrompt": "回應字串",
  "status": {},
  "errorMessage": "回應字串",
  "translatedFileUrl": "回應字串",
  "bilingualFileUrl": "回應字串",
  "processDuration": "回應字串",
  "processingDurationSeconds": 456,
  "pageCount": 456,
  "originalWordCount": 456,
  "translatedWordCount": 456,
  "inputTokensUsed": 456,
  "outputTokensUsed": 456,
  "totalTokensUsed": 456,
  "originalFileSize": 456,
  "translatedFileSize": 456,
  "bilingualFileSize": 456,
  "llmTranslationDuration": "回應字串",
  "llmTranslationDurationSeconds": 456,
  "llmCallCount": 456,
  "avgLlmCallDuration": 456,
  "pdfParsingDuration": "回應字串",
  "pdfParsingDurationSeconds": 456,
  "fileSavingDuration": "回應字串",
  "fileSavingDurationSeconds": 456,
  "startedAt": "回應字串",
  "completedAt": "回應字串",
  "createdAt": "回應字串",
  "updatedAt": "回應字串"
}
```

列出知識庫文件

`GET` `/api/v1/knowledge-bases/{knowledgeBasePk}/documents/`

參數

參數名稱	必填	類型	說明
`knowledgeBasePk`	V	string	
`chatbotFileId`	X	string	【將棄用】檔案 ID（請使用 knowledge_base_file_id）
`knowledgeBaseFileId`	X	string	知識庫檔案 ID

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/knowledge-
bases/550e8400-e29b-41d4-a716-446655440000/documents/?
chatbotFileId=example&knowledgeBaseFileId=example"

  -H "Authorization: Api-Key YOUR_API_KEY"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-
e29b-41d4-a716-446655440000/documents/?
chatbotFileId=example&knowledgeBaseFileId=example", config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-e29b-
41d4-a716-446655440000/documents/?
chatbotFileId=example&knowledgeBaseFileId=example"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-e29b-
41d4-a716-446655440000/documents/?
chatbotFileId=example&knowledgeBaseFileId=example", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
[
  {
```

```
    "id": string (uuid)
    "fileName": string
    "pageNumber"?: integer // 非必填
    "chatbotFile": string (uuid)
    "excludedEmbedMetadataKeys"?: object // List[str]: metadata keys to
exclude from the embedding. (非必填)
    "excludedLlmMetadataKeys"?: object // List[str]: metadata keys to
exclude from the LLM context. (非必填)
    "llamaIndexObjectJson"?: object // 非必填
    "metadata"?: object // 非必填
    "text": string
    "updatedAt": string (timestamp)
  }
]
```

回應範例值

```
[
  {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "fileName": "回應字串",
    "pageNumber": 456,
    "chatbotFile": "550e8400-e29b-41d4-a716-446655440000",
    "excludedEmbedMetadataKeys": null,
    "excludedLlmMetadataKeys": null,
    "llamaIndexObjectJson": null,
    "metadata": null,
    "text": "回應字串",
    "updatedAt": "回應字串"
  }
]
```

狀態碼: 404 - 知識庫檔案不存在，或不屬於目前組織

更新文件

PUT `/api/v1/knowledge-bases/{knowledgeBasePk}/documents/{id}`

參數

參數名稱	必填	類型	說明
`id`	V	string	A UUID string identifying this Chatbot Document.
`knowledgeBasePk`	V	string	

請求內容

請求參數

欄位	類型	必填	說明
fileName	string	是	
pageNumber	integer	否	
chatbotFile	string (uuid)	是	
excludedEmbedMetadataKeys	object	否	List[str]: metadata keys to exclude from the embedding.
excludedLlmMetadataKeys	object	否	List[str]: metadata keys to exclude from the LLM context.
llamaIndexObjectJson	object	否	
metadata	object	否	
text	string	是	

請求結構範例

```
{
  "fileName": string
  "pageNumber"?: integer // 非必填
  "chatbotFile": string (uuid)
```

```
  "excludedEmbedMetadataKeys"?: object // List[str]: metadata keys to
exclude from the embedding. (非必填)
  "excludedLlmMetadataKeys"?: object // List[str]: metadata keys to
exclude from the LLM context. (非必填)
  "llamaIndexObjectJson"?: object // 非必填
  "metadata"?: object // 非必填
  "text": string
}
```

請求範例值

```
{
  "fileName": "範例字串",
  "pageNumber": 123,
  "chatbotFile": "550e8400-e29b-41d4-a716-446655440000",
  "excludedEmbedMetadataKeys": null,
  "excludedLlmMetadataKeys": null,
  "llamaIndexObjectJson": null,
  "metadata": null,
  "text": "這是一個範例訊息"
}
```

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X PUT "https://api.maiagent.ai/api/v1/knowledge-
bases/550e8400-e29b-41d4-a716-446655440000/documents/550e8400-e29b-
41d4-a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "fileName": "範例字串",
    "pageNumber": 123,
    "chatbotFile": "550e8400-e29b-41d4-a716-446655440000",
    "excludedEmbedMetadataKeys": null,
    "excludedLlmMetadataKeys": null,
    "llamaIndexObjectJson": null,
    "metadata": null,
    "text": "這是一個範例訊息"
  }'

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// 請求內容 (payload)
const data = {
    "fileName": "範例字串",
    "pageNumber": 123,
    "chatbotFile": "550e8400-e29b-41d4-a716-446655440000",
    "excludedEmbedMetadataKeys": null,
    "excludedLlmMetadataKeys": null,
    "llamaIndexObjectJson": null,
    "metadata": null,
    "text": "這是一個範例訊息"
  };

axios.put("https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-
e29b-41d4-a716-446655440000/documents/550e8400-e29b-41d4-a716-
446655440000/", data, config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-e29b-
41d4-a716-446655440000/documents/550e8400-e29b-41d4-a716-
446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# 請求內容 (payload)
data = {
    "fileName": "範例字串",
    "pageNumber": 123,
    "chatbotFile": "550e8400-e29b-41d4-a716-446655440000",
    "excludedEmbedMetadataKeys": None,
    "excludedLlmMetadataKeys": None,
    "llamaIndexObjectJson": None,
    "metadata": None,
    "text": "這是一個範例訊息"
}

response = requests.put(url, json=data, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>put("https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-e29b-
41d4-a716-446655440000/documents/550e8400-e29b-41d4-a716-
446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'fileName' => '範例字串',
            'pageNumber' => 123,
            'chatbotFile' => '550e8400-e29b-41d4-a716-446655440000',
            'excludedEmbedMetadataKeys' => null,
            'excludedLlmMetadataKeys' => null,
            'llamaIndexObjectJson' => null,
            'metadata' => null,
            'text' => '這是一個範例訊息'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
{
  "id": string (uuid)
  "fileName": string
  "pageNumber"?: integer // 非必填
  "chatbotFile": string (uuid)
  "excludedEmbedMetadataKeys"?: object // List[str]: metadata keys to
exclude from the embedding. (非必填)
  "excludedLlmMetadataKeys"?: object // List[str]: metadata keys to
exclude from the LLM context. (非必填)
  "llamaIndexObjectJson"?: object // 非必填
  "metadata"?: object // 非必填
  "text": string
  "updatedAt": string (timestamp)
}
```

回應範例值

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "fileName": "回應字串",
  "pageNumber": 456,
  "chatbotFile": "550e8400-e29b-41d4-a716-446655440000",
  "excludedEmbedMetadataKeys": null,
  "excludedLlmMetadataKeys": null,
  "llamaIndexObjectJson": null,
  "metadata": null,
  "text": "回應字串",
  "updatedAt": "回應字串"
}
```

部分更新文件

PATCH `/api/v1/knowledge-bases/{knowledgeBasePk}/documents/{id}`

參數

參數名稱	必填	類型	說明
`id`	V	string	A UUID string identifying this Chatbot Document.
`knowledgeBasePk`	V	string	

請求內容

請求參數

欄位	類型	必填	說明
fileName	string	否	
pageNumber	integer	否	
chatbotFile	string (uuid)	否	
excludedEmbedMetadataKeys	object	否	List[str]: metadata keys to exclude from the embedding.
excludedLlmMetadataKeys	object	否	List[str]: metadata keys to exclude from the LLM context.
llamaIndexObjectJson	object	否	
metadata	object	否	

欄位	類型	必填	說明
text	string	否	

請求結構範例

```
{
  "fileName"?: string // 非必填
  "pageNumber"?: integer // 非必填
  "chatbotFile"?: string (uuid) // 非必填
  "excludedEmbedMetadataKeys"?: object // List[str]: metadata keys to
exclude from the embedding. (非必填)
  "excludedLlmMetadataKeys"?: object // List[str]: metadata keys to
exclude from the LLM context. (非必填)
  "llamaIndexObjectJson"?: object // 非必填
  "metadata"?: object // 非必填
  "text"?: string // 非必填
}
```

請求範例值

```
{
  "fileName": "範例字串",
  "pageNumber": 123,
  "chatbotFile": "550e8400-e29b-41d4-a716-446655440000",
  "excludedEmbedMetadataKeys": null,
  "excludedLlmMetadataKeys": null,
  "llamaIndexObjectJson": null,
  "metadata": null,
  "text": "這是一個範例訊息"
}
```

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X PATCH "https://api.maiagent.ai/api/v1/knowledge-
bases/550e8400-e29b-41d4-a716-446655440000/documents/550e8400-e29b-
41d4-a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "fileName": "範例字串",
    "pageNumber": 123,
    "chatbotFile": "550e8400-e29b-41d4-a716-446655440000",
    "excludedEmbedMetadataKeys": null,
    "excludedLlmMetadataKeys": null,
    "llamaIndexObjectJson": null,
    "metadata": null,
    "text": "這是一個範例訊息"
  }'

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// 請求內容 (payload)
const data = {
    "fileName": "範例字串",
    "pageNumber": 123,
    "chatbotFile": "550e8400-e29b-41d4-a716-446655440000",
    "excludedEmbedMetadataKeys": null,
    "excludedLlmMetadataKeys": null,
    "llamaIndexObjectJson": null,
    "metadata": null,
    "text": "這是一個範例訊息"
  };

axios.patch("https://api.maiagent.ai/api/v1/knowledge-
bases/550e8400-e29b-41d4-a716-446655440000/documents/550e8400-e29b-
41d4-a716-446655440000/", data, config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-e29b-
41d4-a716-446655440000/documents/550e8400-e29b-41d4-a716-
446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# 請求內容 (payload)
data = {
    "fileName": "範例字串",
    "pageNumber": 123,
    "chatbotFile": "550e8400-e29b-41d4-a716-446655440000",
    "excludedEmbedMetadataKeys": None,
    "excludedLlmMetadataKeys": None,
    "llamaIndexObjectJson": None,
    "metadata": None,
    "text": "這是一個範例訊息"
}

response = requests.patch(url, json=data, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>patch("https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-
e29b-41d4-a716-446655440000/documents/550e8400-e29b-41d4-a716-
446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'fileName' => '範例字串',
            'pageNumber' => 123,
            'chatbotFile' => '550e8400-e29b-41d4-a716-446655440000',
            'excludedEmbedMetadataKeys' => null,
            'excludedLlmMetadataKeys' => null,
            'llamaIndexObjectJson' => null,
            'metadata' => null,
            'text' => '這是一個範例訊息'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
{
  "id": string (uuid)
  "fileName": string
  "pageNumber"?: integer // 非必填
  "chatbotFile": string (uuid)
  "excludedEmbedMetadataKeys"?: object // List[str]: metadata keys to
exclude from the embedding. (非必填)
  "excludedLlmMetadataKeys"?: object // List[str]: metadata keys to
exclude from the LLM context. (非必填)
  "llamaIndexObjectJson"?: object // 非必填
  "metadata"?: object // 非必填
  "text": string
  "updatedAt": string (timestamp)
}
```

回應範例值

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "fileName": "回應字串",
  "pageNumber": 456,
  "chatbotFile": "550e8400-e29b-41d4-a716-446655440000",
  "excludedEmbedMetadataKeys": null,
  "excludedLlmMetadataKeys": null,
  "llamaIndexObjectJson": null,
  "metadata": null,
  "text": "回應字串",
  "updatedAt": "回應字串"
}
```

刪除文件

`DELETE` `/api/v1/knowledge-bases/{knowledgeBasePk}/documents/{id}`

參數

參數名稱	必填	類型	說明
`id`	V	string	A UUID string identifying this Chatbot Document.
`knowledgeBasePk`	V	string	

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X DELETE "https://api.maiagent.ai/api/v1/knowledge-
bases/550e8400-e29b-41d4-a716-446655440000/documents/550e8400-e29b-
41d4-a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

// 請求內容 (payload)
const data = null;

axios.delete("https://api.maiagent.ai/api/v1/knowledge-
bases/550e8400-e29b-41d4-a716-446655440000/documents/550e8400-e29b-
41d4-a716-446655440000/", data, config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-e29b-41d4-a716-446655440000/documents/550e8400-e29b-41d4-a716-446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.delete(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>delete("https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-
e29b-41d4-a716-446655440000/documents/550e8400-e29b-41d4-a716-
446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼	說明
204	No response body

建立新的 FAQ

`POST` `/api/v1/knowledge-bases/{knowledgeBasePk}/faqs/`

參數

參數名稱	必填	類型	說明
knowledgeBasePk	V	string	

請求內容

請求參數

欄位	類型	必填	說明
question	string	是	
answer	string	是	
answerMediaUrls	object	否	URLs of media files, such as images and videos, in the answer.
labels	array[IdName]	否	
rawUserDefineMetadata	object	否	

請求結構範例

```
{
  "question": string
  "answer": string
  "answerMediaUrls"?: object // URLs of media files, such as images and
videos, in the answer. (非必填)
```

```
  "labels"?: [ // 非必填
    {
      "id": string (uuid)
    }
  ]
  "rawUserDefineMetadata"?: object // 非必填
}
```

請求範例值

```
{
  "question": "範例字串",
  "answer": "範例字串",
  "answerMediaUrls": null,
  "labels": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000"
    }
  ],
  "rawUserDefineMetadata": null
}
```

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X POST "https://api.maiagent.ai/api/v1/knowledge-
bases/550e8400-e29b-41d4-a716-446655440000/faqs/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "question": "範例字串",
    "answer": "範例字串",
    "answerMediaUrls": null,
    "labels": [
      {
        "id": "550e8400-e29b-41d4-a716-446655440000"
      }
    ],
    "rawUserDefineMetadata": null
  }'

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// 請求內容 (payload)
const data = {
    "question": "範例字串",
    "answer": "範例字串",
    "answerMediaUrls": null,
    "labels": [
      {
        "id": "550e8400-e29b-41d4-a716-446655440000"
      }
    ],
    "rawUserDefineMetadata": null
  };

axios.post("https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-
e29b-41d4-a716-446655440000/faqs/", data, config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-e29b-
41d4-a716-446655440000/faqs/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# 請求內容 (payload)
data = {
    "question": "範例字串",
    "answer": "範例字串",
    "answerMediaUrls": None,
    "labels": [
        {
            "id": "550e8400-e29b-41d4-a716-446655440000"
        }
    ],
    "rawUserDefineMetadata": None
}

response = requests.post(url, json=data, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>post("https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-e29b-
41d4-a716-446655440000/faqs/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'question' => '範例字串',
            'answer' => '範例字串',
            'answerMediaUrls' => null,
            'labels' => [
                [
                    'id' => '550e8400-e29b-41d4-a716-446655440000'
                ]
            ],
            'rawUserDefineMetadata' => null
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 201

回應結構範例

```
{
  "id": string (uuid)
  "question": string
  "answer": string
  "answerMediaUrls"?: object // URLs of media files, such as images and
videos, in the answer. (非必填)
  "hitsCount": integer
  "embeddingTokensCount": integer // Number of embedding tokens used to
create this FAQ.
  "labels"?: [ // 非必填
    {
      "id": string (uuid)
      "name": string
    }
  ]
  "rawUserDefineMetadata"?: object // 非必填
  "knowledgeBase":  // Always taken from the knowledge base in the URL; a
value in the request body is ignored.
  {
    "id": string (uuid)
    "name": string
  }
}
```

回應範例值

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "question": "回應字串",
  "answer": "回應字串",
  "answerMediaUrls": null,
  "hitsCount": 456,
  "embeddingTokensCount": 456,
  "labels": [
    {
```

```
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "回應字串"
    }
  ],
  "rawUserDefineMetadata": null,
  "knowledgeBase": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應字串"
  }
}
```


更新 FAQ 元資料

`PATCH` `/api/v1/knowledge-bases/{knowledgeBasePk}/faqs/{id}/update-metadata/`

參數

參數名稱	必填	類型	說明
`id`	V	string	A UUID string identifying this FAQ.
`knowledgeBasePk`	V	string	

請求內容

請求參數

欄位	類型	必填	說明
labels	array[IdName]	否	
rawUserDefineMetadata	object	否	

請求結構範例

```
{
  "labels"?: [ // 非必填
    {
      "id": string (uuid)
    }
  ]
  "rawUserDefineMetadata"?: object // 非必填
}
```

請求範例值

```
{
  "labels": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000"
    }
  ],
  "rawUserDefineMetadata": null
}
```

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X PATCH "https://api.maiagent.ai/api/v1/knowledge-
bases/550e8400-e29b-41d4-a716-446655440000/faqs/550e8400-e29b-41d4-
a716-446655440000/update-metadata/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "labels": [
      {
        "id": "550e8400-e29b-41d4-a716-446655440000"
      }
    ],
    "rawUserDefineMetadata": null
  }'

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// 請求內容 (payload)
const data = {
    "labels": [
      {
        "id": "550e8400-e29b-41d4-a716-446655440000"
      }
    ],
    "rawUserDefineMetadata": null
  };

axios.patch("https://api.maiagent.ai/api/v1/knowledge-
bases/550e8400-e29b-41d4-a716-446655440000/faqs/550e8400-e29b-41d4-
a716-446655440000/update-metadata/", data, config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-e29b-
41d4-a716-446655440000/faqs/550e8400-e29b-41d4-a716-
446655440000/update-metadata/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# 請求內容 (payload)
data = {
    "labels": [
        {
            "id": "550e8400-e29b-41d4-a716-446655440000"
        }
    ],
    "rawUserDefineMetadata": None
}

response = requests.patch(url, json=data, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>patch("https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-
e29b-41d4-a716-446655440000/faqs/550e8400-e29b-41d4-a716-
446655440000/update-metadata/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'labels' => [
                [
                    'id' => '550e8400-e29b-41d4-a716-446655440000'
                ]
            ],
            'rawUserDefineMetadata' => null
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
{
  "id": string (uuid)
  "question": string
  "answer": string
  "answerMediaUrls"?: object // URLs of media files, such as images and
videos, in the answer. (非必填)
  "hitsCount": integer
  "embeddingTokensCount": integer // Number of embedding tokens used to
create this FAQ.
  "labels"?: [ // 非必填
    {
      "id": string (uuid)
      "name": string
    }
  ]
  "rawUserDefineMetadata"?: object // 非必填
  "knowledgeBase":  // Always taken from the knowledge base in the URL; a
value in the request body is ignored.
  {
    "id": string (uuid)
    "name": string
  }
}
```

回應範例值

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "question": "回應字串",
  "answer": "回應字串",
  "answerMediaUrls": null,
  "hitsCount": 456,
  "embeddingTokensCount": 456,
  "labels": [
    {
```

```
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "回應字串"
    }
  ],
  "rawUserDefineMetadata": null,
  "knowledgeBase": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應字串"
  }
}
```


批量刪除 FAQ

POST `/api/v1/knowledge-bases/{knowledgeBasePk}/faqs/batch-delete/`

參數

參數名稱	必填	類型	說明
knowledgeBasePk	V	string	

請求內容

請求參數

欄位	類型	必填	說明
ids	array[string]	否	

請求結構範例

```
{
  "ids"?: [ // 非必填
    string (uuid)
  ]
}
```

請求範例值

```
{
  "ids": [
    "550e8400-e29b-41d4-a716-446655440000"
  ]
}
```

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X POST "https://api.maiagent.ai/api/v1/knowledge-
bases/550e8400-e29b-41d4-a716-446655440000/faqs/batch-delete/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "ids": [
      "550e8400-e29b-41d4-a716-446655440000"
    ]
  }'

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// 請求內容 (payload)
const data = {
    "ids": [
      "550e8400-e29b-41d4-a716-446655440000"
    ]
  };

axios.post("https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-
e29b-41d4-a716-446655440000/faqs/batch-delete/", data, config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-e29b-
41d4-a716-446655440000/faqs/batch-delete/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# 請求內容 (payload)
data = {
    "ids": [
        "550e8400-e29b-41d4-a716-446655440000"
    ]
}

response = requests.post(url, json=data, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>post("https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-e29b-
41d4-a716-446655440000/faqs/batch-delete/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'ids' => [
                '550e8400-e29b-41d4-a716-446655440000'
            ]
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼	說明

204	No response body

列出特定知識庫的所有 FAQ

`GET` `/api/v1/knowledge-bases/{knowledgeBasePk}/faqs/`

參數

參數名稱	必填	類型	說明
`knowledgeBasePk`	V	string	
`page`	X	integer	A page number within the paginated result set.
`pageSize`	X	integer	Number of results to return per page.
`query`	X	string	搜尋關鍵字，支援空白分隔的多條件查詢。可搜尋：FAQ ID、問題、答案、標籤名稱、Metadata value

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/knowledge-
bases/550e8400-e29b-41d4-a716-446655440000/faqs/?
page=1&pageSize=1&query=example"

  -H "Authorization: Api-Key YOUR_API_KEY"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-e29b-41d4-a716-446655440000/faqs/?page=1&pageSize=1&query=example", config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-e29b-41d4-a716-446655440000/faqs/?page=1&pageSize=1&query=example"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-e29b-
41d4-a716-446655440000/faqs/?page=1&pageSize=1&query=example", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
{
  "count": integer
  "next"?: string (uri) // 非必填
```

```
  "previous"?: string (uri) // 非必填
  "results": [
    {
      "id": string (uuid)
      "question": string
      "answer": string
      "answerMediaUrls"?: object // URLs of media files, such as images
and videos, in the answer. (非必填)
      "hitsCount": integer
      "embeddingTokensCount": integer // Number of embedding tokens used
to create this FAQ.
      "labels"?: [ // 非必填
        {
          "id": string (uuid)
          "name": string
        }
      ]
      "rawUserDefineMetadata"?: object // 非必填
      "knowledgeBase":  // Always taken from the knowledge base in the
URL; a value in the request body is ignored.
      {
        "id": string (uuid)
        "name": string
      }
    }
  ]
}
```

回應範例值

```
{
  "count": 123,
  "next": "http://api.example.org/accounts/?page=4",
  "previous": "http://api.example.org/accounts/?page=2",
  "results": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "question": "回應字串",
      "answer": "回應字串",
      "answerMediaUrls": null,
      "hitsCount": 456,
      "embeddingTokensCount": 456,
      "labels": [
        {
```

```
          "id": "550e8400-e29b-41d4-a716-446655440000",
          "name": "回應字串"
        }
      ],
      "rawUserDefineMetadata": null,
      "knowledgeBase": {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "name": "回應字串"
      }
    }
  ]
}
```


取得特定 FAQ 詳情

`GET` `/api/v1/knowledge-bases/{knowledgeBasePk}/faqs/{id}`

參數

參數名稱	必填	類型	說明
`id`	V	string	A UUID string identifying this FAQ.
`knowledgeBasePk`	V	string	

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/knowledge-
bases/550e8400-e29b-41d4-a716-446655440000/faqs/550e8400-e29b-41d4-
a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-e29b-41d4-a716-446655440000/faqs/550e8400-e29b-41d4-a716-446655440000/", config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-e29b-41d4-a716-446655440000/faqs/550e8400-e29b-41d4-a716-446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-e29b-
41d4-a716-446655440000/faqs/550e8400-e29b-41d4-a716-446655440000/",
[
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
{
  "id": string (uuid)
```

```
  "question": string
  "answer": string
  "answerMediaUrls"?: object // URLs of media files, such as images and
videos, in the answer. (非必填)
  "hitsCount": integer
  "embeddingTokensCount": integer // Number of embedding tokens used to
create this FAQ.
  "labels"?: [ // 非必填
    {
      "id": string (uuid)
      "name": string
    }
  ]
  "rawUserDefineMetadata"?: object // 非必填
  "knowledgeBase":  // Always taken from the knowledge base in the URL; a
value in the request body is ignored.
  {
    "id": string (uuid)
    "name": string
  }
}
```

回應範例值

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "question": "回應字串",
  "answer": "回應字串",
  "answerMediaUrls": null,
  "hitsCount": 456,
  "embeddingTokensCount": 456,
  "labels": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "回應字串"
    }
  ],
  "rawUserDefineMetadata": null,
  "knowledgeBase": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應字串"
```

```
    }
  }
```

更新 FAQ

PUT `/api/v1/knowledge-bases/{knowledgeBasePk}/faqs/{id}`

參數

參數名稱	必填	類型	說明
`id`	V	string	A UUID string identifying this FAQ.
`knowledgeBasePk`	V	string	

請求內容

請求參數

欄位	類型	必填	說明
question	string	是	
answer	string	是	
answerMediaUrls	object	否	URLs of media files, such as images and videos, in the answer.
labels	array[IdName]	否	
rawUserDefineMetadata	object	否	

請求結構範例

```
{
  "question": string
  "answer": string
  "answerMediaUrls"?: object // URLs of media files, such as images and
videos, in the answer. (非必填)
  "labels"?: [ // 非必填
    {
      "id": string (uuid)
    }
  ]
  "rawUserDefineMetadata"?: object // 非必填
}
```

請求範例值

```
{
  "question": "範例字串",
  "answer": "範例字串",
  "answerMediaUrls": null,
  "labels": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000"
    }
  ],
  "rawUserDefineMetadata": null
}
```

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X PUT "https://api.maiagent.ai/api/v1/knowledge-
bases/550e8400-e29b-41d4-a716-446655440000/faqs/550e8400-e29b-41d4-
a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "question": "範例字串",
    "answer": "範例字串",
    "answerMediaUrls": null,
    "labels": [
      {
        "id": "550e8400-e29b-41d4-a716-446655440000"
      }
    ],
    "rawUserDefineMetadata": null
  }'

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// 請求內容 (payload)
const data = {
    "question": "範例字串",
    "answer": "範例字串",
    "answerMediaUrls": null,
    "labels": [
      {
        "id": "550e8400-e29b-41d4-a716-446655440000"
      }
    ],
    "rawUserDefineMetadata": null
  };

axios.put("https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-
e29b-41d4-a716-446655440000/faqs/550e8400-e29b-41d4-a716-
446655440000/", data, config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-e29b-
41d4-a716-446655440000/faqs/550e8400-e29b-41d4-a716-446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# 請求內容 (payload)
data = {
    "question": "範例字串",
    "answer": "範例字串",
    "answerMediaUrls": None,
    "labels": [
        {
            "id": "550e8400-e29b-41d4-a716-446655440000"
        }
    ],
    "rawUserDefineMetadata": None
}

response = requests.put(url, json=data, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>put("https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-e29b-
41d4-a716-446655440000/faqs/550e8400-e29b-41d4-a716-446655440000/",
[
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'question' => '範例字串',
            'answer' => '範例字串',
            'answerMediaUrls' => null,
            'labels' => [
                [
                    'id' => '550e8400-e29b-41d4-a716-446655440000'
                ]
            ],
            'rawUserDefineMetadata' => null
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
{
  "id": string (uuid)
  "question": string
  "answer": string
  "answerMediaUrls"?: object // URLs of media files, such as images and
videos, in the answer. (非必填)
  "hitsCount": integer
  "embeddingTokensCount": integer // Number of embedding tokens used to
create this FAQ.
  "labels"?: [ // 非必填
    {
      "id": string (uuid)
      "name": string
    }
  ]
  "rawUserDefineMetadata"?: object // 非必填
  "knowledgeBase":  // Always taken from the knowledge base in the URL; a
value in the request body is ignored.
  {
    "id": string (uuid)
    "name": string
  }
}
```

回應範例值

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "question": "回應字串",
  "answer": "回應字串",
  "answerMediaUrls": null,
  "hitsCount": 456,
  "embeddingTokensCount": 456,
  "labels": [
    {
```

```
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "回應字串"
    }
  ],
  "rawUserDefineMetadata": null,
  "knowledgeBase": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應字串"
  }
}
```


部分更新 FAQ

`PATCH` `/api/v1/knowledge-bases/{knowledgeBasePk}/faqs/{id}`

參數

參數名稱	必填	類型	說明
`id`	V	string	A UUID string identifying this FAQ.
`knowledgeBasePk`	V	string	

請求內容

請求參數

欄位	類型	必填	說明
question	string	否	
answer	string	否	

欄位	類型	必填	說明
answerMediaUrls	object	否	URLs of media files, such as images and videos, in the answer.
labels	array[IdName]	否	
rawUserDefineMetadata	object	否	

請求結構範例

```
{
  "question"?: string // 非必填
  "answer"?: string // 非必填
  "answerMediaUrls"?: object // URLs of media files, such as images and videos, in the answer. (非必填)
  "labels"?: [ // 非必填
    {
      "id": string (uuid)
    }
  ]
  "rawUserDefineMetadata"?: object // 非必填
}
```

請求範例值

```
{
  "question": "範例字串",
  "answer": "範例字串",
  "answerMediaUrls": null,
  "labels": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000"
    }
  ],
  "rawUserDefineMetadata": null
}
```

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X PATCH "https://api.maiagent.ai/api/v1/knowledge-
bases/550e8400-e29b-41d4-a716-446655440000/faqs/550e8400-e29b-41d4-
a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "question": "範例字串",
    "answer": "範例字串",
    "answerMediaUrls": null,
    "labels": [
      {
        "id": "550e8400-e29b-41d4-a716-446655440000"
      }
    ],
    "rawUserDefineMetadata": null
  }'

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// 請求內容 (payload)
const data = {
    "question": "範例字串",
    "answer": "範例字串",
    "answerMediaUrls": null,
    "labels": [
      {
        "id": "550e8400-e29b-41d4-a716-446655440000"
      }
    ],
    "rawUserDefineMetadata": null
  };

axios.patch("https://api.maiagent.ai/api/v1/knowledge-
bases/550e8400-e29b-41d4-a716-446655440000/faqs/550e8400-e29b-41d4-
a716-446655440000/", data, config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-e29b-41d4-a716-446655440000/faqs/550e8400-e29b-41d4-a716-446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# 請求內容 (payload)
data = {
    "question": "範例字串",
    "answer": "範例字串",
    "answerMediaUrls": None,
    "labels": [
        {
            "id": "550e8400-e29b-41d4-a716-446655440000"
        }
    ],
    "rawUserDefineMetadata": None
}

response = requests.patch(url, json=data, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>patch("https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-
e29b-41d4-a716-446655440000/faqs/550e8400-e29b-41d4-a716-
446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'question' => '範例字串',
            'answer' => '範例字串',
            'answerMediaUrls' => null,
            'labels' => [
                [
                    'id' => '550e8400-e29b-41d4-a716-446655440000'
                ]
            ],
            'rawUserDefineMetadata' => null
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
{
  "id": string (uuid)
  "question": string
  "answer": string
  "answerMediaUrls"?: object // URLs of media files, such as images and
videos, in the answer. (非必填)
  "hitsCount": integer
  "embeddingTokensCount": integer // Number of embedding tokens used to
create this FAQ.
  "labels"?: [ // 非必填
    {
      "id": string (uuid)
      "name": string
    }
  ]
  "rawUserDefineMetadata"?: object // 非必填
  "knowledgeBase":  // Always taken from the knowledge base in the URL; a
value in the request body is ignored.
  {
    "id": string (uuid)
    "name": string
  }
}
```

回應範例值

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "question": "回應字串",
  "answer": "回應字串",
  "answerMediaUrls": null,
  "hitsCount": 456,
  "embeddingTokensCount": 456,
  "labels": [
    {
```

```
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "回應字串"
    }
  ],
  "rawUserDefineMetadata": null,
  "knowledgeBase": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應字串"
  }
}
```


刪除 FAQ

DELETE `/api/v1/knowledge-bases/{knowledgeBasePk}/faqs/{id}`

參數

參數名稱	必填	類型	說明
`id`	V	string	A UUID string identifying this FAQ.
`knowledgeBasePk`	V	string	

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X DELETE "https://api.maiagent.ai/api/v1/knowledge-
bases/550e8400-e29b-41d4-a716-446655440000/faqs/550e8400-e29b-41d4-
a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

// 請求內容 (payload)
const data = null;

axios.delete("https://api.maiagent.ai/api/v1/knowledge-
bases/550e8400-e29b-41d4-a716-446655440000/faqs/550e8400-e29b-41d4-
a716-446655440000/", data, config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-e29b-41d4-a716-446655440000/faqs/550e8400-e29b-41d4-a716-446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.delete(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>delete("https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-
e29b-41d4-a716-446655440000/faqs/550e8400-e29b-41d4-a716-
446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼	說明
204	No response body

匯出 FAQ Excel（或空白範本）

`GET` `/api/v1/knowledge-bases/{id}/export-faq-excel/`

參數

參數名稱	必填	類型	說明
`id`	V	string	A UUID string identifying this Knowledge Base.

程式碼範例

Shell/Bash

```
# 呼叫 API 示例（Shell）
curl -X GET "https://api.maiagent.ai/api/v1/knowledge-
bases/550e8400-e29b-41d4-a716-446655440000/export-faq-excel/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-e29b-41d4-a716-446655440000/export-faq-excel/", config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-e29b-41d4-a716-446655440000/export-faq-excel/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-e29b-
41d4-a716-446655440000/export-faq-excel/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
{
  "id": string (uuid)
  "createdBy":
```

```
  {
    "id": string (uuid)
    "name": string
  }
  "organization"?: string (uuid) // 非必填
  "embeddingModel": string (uuid)
  "rerankerModel": string (uuid)
  "name": string
  "description"?: string // 非必填
  "numberOfRetrievedChunks"?: integer // 提取的參考資料數量，預設為 12，最小值為 1 (非必填)
  "enableHyde"?: boolean // 啟用 HyDE，預設為 False (非必填)
  "similarityCutoff"?: number (double) // 相似度門檻，預設為 0.0，範圍為 0.0-1.0 (非必填)
  "enableRerank"?: boolean // 是否啟用重新排序，預設為 True (非必填)
  "enableRrf"?: boolean // Enable Reciprocal Rank Fusion for hybrid search. Disable this if using a custom Elasticsearch without enterprise license. (非必填)
  "vectorDatabaseType"?:  // Type of vector database: elasticsearch or opensearch.

* `elasticsearch` - Elasticsearch
* `opensearch` - OpenSearch
* `oracle` - Oracle AI Database 26ai
* `synxdb` - SynxDB (非必填)
  {
  }
  "vectorDatabaseUrl"?: string // Custom vector database endpoint URL or Oracle DSN. For Elasticsearch/OpenSearch: URL format (e.g., "https://host:9200"). For Oracle: DSN format (e.g., "host:1521/service_name"). (非必填)
  "vectorDatabaseApiKey"?: string // API Key for Elasticsearch. Not used for OpenSearch. (非必填)
  "opensearchUsername"?: string // Username for OpenSearch Basic Auth. (非必填)
  "opensearchPassword"?: string // Password for OpenSearch Basic Auth. (非必填)
  "oracleUser"?: string // Oracle database username. (非必填)
  "oraclePassword"?: string // Oracle database password. (非必填)
  "synxdbUser"?: string // SynxDB database username. (非必填)
  "synxdbPassword"?: string // SynxDB database password. (非必填)
  "labels": [
    {
      "id": string (uuid)
      "name": string
```

```
    }
  ]
  "chatbots"?: [ // 非必填
    {
      "id": string (uuid)
      "name": string
    }
  ]
  "groups"?: [ // 知識庫可存取的群組列表 (非必填)
    {
      "id": string (uuid)
      "name": string
    }
  ]
  "filesCount": integer // Return count of KnowledgeBaseFile excluding
processed files, conversation attachments, and soft-deleted.
  "vectorStorageSize": integer
  "chunksCount": integer
  "canUpdate": boolean // Return whether the current user can update this
resource.
  "canDelete": boolean // Return whether the current user can delete this
resource.
  "createdAt": string (timestamp)
  "updatedAt": string (timestamp)
}
```

回應範例值

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "createdBy": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應字串"
  },
  "organization": "550e8400-e29b-41d4-a716-446655440000",
  "embeddingModel": "550e8400-e29b-41d4-a716-446655440000",
  "rerankerModel": "550e8400-e29b-41d4-a716-446655440000",
  "name": "回應字串",
  "description": "回應字串",
  "numberOfRetrievedChunks": 456,
  "enableHyde": false,
  "similarityCutoff": 456,
  "enableRerank": false,
  "enableRrf": false,
```

```
  "vectorDatabaseType": {},
  "vectorDatabaseUrl": "回應字串",
  "vectorDatabaseApiKey": "回應字串",
  "opensearchUsername": "回應字串",
  "opensearchPassword": "回應字串",
  "oracleUser": "回應字串",
  "oraclePassword": "回應字串",
  "synxdbUser": "回應字串",
  "synxdbPassword": "回應字串",
  "labels": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "回應字串"
    }
  ],
  "chatbots": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "回應字串"
    }
  ],
  "groups": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "回應字串"
    }
  ],
  "filesCount": 456,
  "vectorStorageSize": 456,
  "chunksCount": 456,
  "canUpdate": false,
  "canDelete": false,
  "createdAt": "回應字串",
  "updatedAt": "回應字串"
}
```


匯入 FAQ Excel（非同步）

POST `/api/v1/knowledge-bases/{id}/import-faq-excel/`

同一知識庫同時只能有一個匯入工作，進行中再呼叫會回 409；用下方「FAQ 匯入工作」端點查進度。

參數

參數名稱	必填	類型	說明
`id`	V	string	A UUID string identifying this Knowledge Base.

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X POST "https://api.maiagent.ai/api/v1/knowledge-
bases/550e8400-e29b-41d4-a716-446655440000/import-faq-excel/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -F "excelFile=@example_file.txt"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');
const FormData = require('form-data');

// 建立FormData對象
const formData = new FormData();
// 請用實際檔案替換
formData.append('excelFile',
* 實際檔案物件 *
, 'example_file.txt');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    ...formData.getHeaders()
  }
};

axios.post("https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-
e29b-41d4-a716-446655440000/import-faq-excel/", formData, config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-e29b-
41d4-a716-446655440000/import-faq-excel/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}

# 建立檔案和表單資料
files = {
    'excelFile': ('example_file.txt', open('example_file.txt',
'rb'), 'text/plain')
}

response = requests.post(url, files=files, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>post("https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-e29b-
41d4-a716-446655440000/import-faq-excel/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ],
        'multipart' => [
            [
                'name' => 'excelFile',
                'contents' => fopen('example_file.txt', 'r'),
                'filename' => 'example_file.txt'
            ]
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 202

回應結構範例

```
{
  "jobId": string (uuid)
  "status": string (enum: pending, processing, done, failed) // *
`pending` - Pending
* `processing` - Processing
* `done` - Done
* `failed` - Failed
}
```

回應範例值

```
{
  "jobId": "550e8400-e29b-41d4-a716-446655440000",
  "status": "pending"
}
```

狀態碼: 409

回應結構範例

```
{
  "detail": string
  "jobId": string (uuid)
}
```

回應範例值

```
{
  "detail": "回應字串",
  "jobId": "550e8400-e29b-41d4-a716-446655440000"
}
```

列出 FAQ 匯入工作

`GET` `/api/v1/knowledge-bases/{id}/faq-import-jobs/`

參數

參數名稱	必填	類型	說明
`id`	V	string	A UUID string identifying this Knowledge Base.
`embeddingModel`	X	string	
`page`	X	integer	A page number within the paginated result set.
`pageSize`	X	integer	Number of results to return per page.
`pagination`	X	boolean	Set to false to return all jobs without pagination (defaults to true).
`query`	X	string	
`rerankerModel`	X	string	

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/knowledge-
bases/550e8400-e29b-41d4-a716-446655440000/faq-import-jobs/?
embeddingModel=550e8400-e29b-41d4-a716-
446655440000&page=1&pageSize=1&pagination=true&query=example&reranke
rModel=550e8400-e29b-41d4-a716-446655440000"

  -H "Authorization: Api-Key YOUR_API_KEY"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-e29b-41d4-a716-446655440000/faq-import-jobs/?embeddingModel=550e8400-e29b-41d4-a716-446655440000&page=1&pageSize=1&pagination=true&query=example&rerankerModel=550e8400-e29b-41d4-a716-446655440000", config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-e29b-41d4-a716-446655440000/faq-import-jobs/?embeddingModel=550e8400-e29b-41d4-a716-446655440000&page=1&pageSize=1&pagination=true&query=example&rerankerModel=550e8400-e29b-41d4-a716-446655440000"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-e29b-
41d4-a716-446655440000/faq-import-jobs/?embeddingModel=550e8400-
e29b-41d4-a716-
446655440000&page=1&pageSize=1&pagination=true&query=example&reranke
rModel=550e8400-e29b-41d4-a716-446655440000", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
{
  "count": integer
  "next"?: string (uri) // 非必填
  "previous"?: string (uri) // 非必填
  "results": [
    {
      "id": string (uuid)
      "status":
      {
      }
      "totalRows": integer
      "processedRows": integer
      "createdCount": integer
      "skippedDuplicateCount": integer // Rows skipped because their
whitespace-normalized question already exists in the knowledge base or
appears earlier in the same file.
      "errors": object // Row-level parse errors and chunk-level import
errors.
      "createdAt": string (timestamp)
      "updatedAt": string (timestamp)
    }
  ]
}
```

回應範例值

```
{
  "count": 123,
  "next": "http://api.example.org/accounts/?page=4",
  "previous": "http://api.example.org/accounts/?page=2",
  "results": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "status": {},
      "totalRows": 456,
      "processedRows": 456,
      "createdCount": 456,
      "skippedDuplicateCount": 456,
      "errors": null,
      "createdAt": "回應字串",
      "updatedAt": "回應字串"
    }
```

```
  ]
}
```

取得特定 FAQ 匯入工作

GET `/api/v1/knowledge-bases/{id}/faq-import-jobs/{jobId}`

參數

參數名稱	必填	類型	說明
`id`	V	string	A UUID string identifying this Knowledge Base.
`jobId`	V	string	

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/knowledge-
bases/550e8400-e29b-41d4-a716-446655440000/faq-import-jobs/{jobId}
"

  -H "Authorization: Api-Key YOUR_API_KEY"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-
e29b-41d4-a716-446655440000/faq-import-jobs/{jobId}
", config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-e29b-
41d4-a716-446655440000/faq-import-jobs/{jobId}
"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-e29b-
41d4-a716-446655440000/faq-import-jobs/{jobId}
", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
{
  "id": string (uuid)
```

```
  "status":
  {
  }
  "totalRows": integer
  "processedRows": integer
  "createdCount": integer
  "skippedDuplicateCount": integer // Rows skipped because their
whitespace-normalized question already exists in the knowledge base or
appears earlier in the same file.
  "errors": object // Row-level parse errors and chunk-level import
errors.
  "createdAt": string (timestamp)
  "updatedAt": string (timestamp)
}
```

回應範例值

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "status": {},
  "totalRows": 456,
  "processedRows": 456,
  "createdCount": 456,
  "skippedDuplicateCount": 456,
  "errors": null,
  "createdAt": "回應字串",
  "updatedAt": "回應字串"
}
```

列出解析器

GET `/api/v1/parsers/`

上傳檔案到知識庫時 parser 欄位要填解析器的 id，由此端點取得。

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/parsers/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/parsers/", config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/parsers/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/parsers/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
[
  {
    "id": string (uuid)
    "name": string
```

```
    "provider":
    {
    }
    "order"?: integer // 非必填
    "isTimestampSttProvider": boolean
    "asrProvider": object // The provider spec, built once per provider
row per response.

The spec is platform-level, not per parser, and it is large — a
whisper-family row carries a 100-entry language catalog in its
``languages`` spec, as codes plus display names. This serializer is
nested per row in the knowledge-base file listing and in message
citations, so without memoizing, one response rebuilds the same
catalog for every row. ``self.context`` is the root serializer's shared
dict, which is also what keeps ``get_active_diarization_rows`` at one
query per response.
  }
]
```

回應範例值

```
[
  {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應字串",
    "provider": {},
    "order": 456,
    "isTimestampSttProvider": false,
    "asrProvider": {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "回應範例名稱",
      "description": "回應範例描述"
    }
  }
]
```

取得特定解析器

GET `/api/v1/parsers/{id}`

參數

參數名稱	必填	類型	說明
`id`	V	string	A UUID string identifying this 解析器.

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/parsers/550e8400-e29b-
41d4-a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/parsers/550e8400-e29b-
41d4-a716-446655440000/", config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/parsers/550e8400-e29b-41d4-
a716-446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/parsers/550e8400-e29b-41d4-
a716-446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
{
  "id": string (uuid)
  "name": string
```

```
  "provider":
  {
  }
  "order"?: integer // 非必填
  "isTimestampSttProvider": boolean
  "asrProvider": object // The provider spec, built once per provider row
per response.

The spec is platform-level, not per parser, and it is large — a
whisper-family row carries a 100-entry language catalog in its
``languages`` spec, as codes plus display names. This serializer is
nested per row in the knowledge-base file listing and in message
citations, so without memoizing, one response rebuilds the same
catalog for every row. ``self.context`` is the root serializer's shared
dict, which is also what keeps ``get_active_diarization_rows`` at one
query per response.
}
```

回應範例值

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "name": "回應字串",
  "provider": {},
  "order": 456,
  "isTimestampSttProvider": false,
  "asrProvider": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應範例名稱",
    "description": "回應範例描述"
  }
}
```

呼叫 API 示例 (Shell)

目錄

1. 取得 AI 助理的知識庫檔案列表
2. 取得 AI 助理的知識庫 FAQ 列表
3. 取得 AI 助理的所有檔案的文本節點
4. 取得 AI 助理的特定檔案的文本節點
5. 搜尋測試
6. 列出檔案類型支援的解析器

呼叫 API 示例 (Shell)

取得 AI 助理的知識庫檔案列表

`GET` `/api/v1/chatbots/{id}/knowledge-bases-files/`

參數

參數名稱	必填	類型	說明
`id`	V	string	
`createdByMember`	X	string	建立者篩選：本組織成員 id（成員名冊回傳的 id，含已停用成員），只回該成員建立的 AI 助理
`largeLanguageModel`	X	string	
`page`	X	integer	A page number within the paginated result set.
`pageSize`	X	integer	Number of results to return per page.
`query`	X	string	
`replyMode`	X	string	

`source`	X	string	`self_built`: self_built ; `built_in`: built_in ; `all`: all;

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X GET "

  -H "Authorization: Api-Key YOUR_API_KEY"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get(" config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->get(" [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
{
  "count": integer
  "next"?: string (uri) // 非必填
  "previous"?: string (uri) // 非必填
  "results": [
```

```
    {
      "id": string (uuid)
      "filename": string // 檔案名稱
      "file": string (uri) // 要上傳的檔案
      "fileType": string
      "knowledgeBase"?:  // 非必填
      {
        "id": string (uuid)
        "name": string
      }
      "size": integer
      "status":
      {
      }
      "parser":
      {
        "id": string (uuid)
        "name": string
        "provider":
        {
        }
        "isTimestampSttProvider": boolean
      }
      "labels"?: [ // 非必填
        {
          "id": string (uuid)
          "name": string
        }
      ]
      "rawUserDefineMetadata"?: object // 非必填
      "speakerLabels": [
        {
          "id": string (uuid)
          "originalLabel": string // Original speaker label from
diarization (e.g., SPEAKER_00)
          "customName"?: string // User-defined speaker name (e.g., John)
(非必填)
          "displayName": string
        }
      ]
      "vectorStorageSize": integer // Size of vectors for this file in
Elasticsearch (bytes)
      "chunksCount": integer // Number of chunks/nodes generated from
this file
      "waitingTime": number (double)
```

```
      "processingTime": number (double)
      "processingTimeDetails": object
      "previewUrl": string // 簡報（pptx/ppt）回傳可預覽的 pdf 衍生檔 URL（前端用 PDF 預覽器顯示）；其餘為 None。

用與 `file` 欄位相同的 CustomizedFileFieldSerializer 產 URL，確保格式一致（含各 storage provider 的 presign/host 規則）。不可用 get_absolute_url()——它產出的 URL 格式錯誤。
      "createdAt": string (timestamp)
    }
  ]
}
```

回應範例值

```
{
  "count": 123,
  "next": "http://api.example.org/accounts/?page=4",
  "previous": "http://api.example.org/accounts/?page=2",
  "results": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "filename": "回應字串",
      "file": "https://example.com/file.jpg",
      "fileType": "回應字串",
      "knowledgeBase": {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "name": "回應字串"
      },
      "size": 456,
      "status": {},
      "parser": {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "name": "回應字串",
        "provider": {},
        "isTimestampSttProvider": false
      },
      "labels": [
        {
          "id": "550e8400-e29b-41d4-a716-446655440000",
          "name": "回應字串"
        }
      ],
      "rawUserDefineMetadata": null,
```

```
      "speakerLabels": [
        {
          "id": "550e8400-e29b-41d4-a716-446655440000",
          "originalLabel": "回應字串",
          "customName": "回應字串",
          "displayName": "回應字串"
        }
      ],
      "vectorStorageSize": 456,
      "chunksCount": 456,
      "waitingTime": 456,
      "processingTime": 456,
      "processingTimeDetails": null,
      "previewUrl": "回應字串",
      "createdAt": "回應字串"
    }
  ]
}
```


取得 AI 助理的知識庫 FAQ 列表

GET `/api/v1/chatbots/{id}/knowledge-bases-faqs/`

參數

參數名稱	必填	類型	說明
`id`	V	string	
`createdByMember`	X	string	建立者篩選：本組織成員 id（成員名冊回傳的 id，含已停用成員），只回該成員建立的 AI 助理
`largeLanguageModel`	X	string	

`page`	X	integer	A page number within the paginated result set.
`pageSize`	X	integer	Number of results to return per page.
`query`	X	string	
`replyMode`	X	string	
`source`	X	string	`self_built`: self_built ; `built_in`: built_in ; `all`: all;

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X GET "

  -H "Authorization: Api-Key YOUR_API_KEY"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get(" config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->get(" [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
{
  "count": integer
  "next"?: string (uri) // 非必填
  "previous"?: string (uri) // 非必填
  "results": [
```

```
    {
      "id": string (uuid)
      "question": string
      "answer": string
      "answerMediaUrls"?: object // URLs of media files, such as images
and videos, in the answer. (非必填)
      "hitsCount": integer
      "embeddingTokensCount": integer // Number of embedding tokens used
to create this FAQ.
      "labels"?: [ // 非必填
        {
          "id": string (uuid)
          "name": string
        }
      ]
      "rawUserDefineMetadata"?: object // 非必填
      "knowledgeBase":  // Always taken from the knowledge base in the
URL; a value in the request body is ignored.
      {
        "id": string (uuid)
        "name": string
      }
    }
  ]
}
```

回應範例值

```
{
  "count": 123,
  "next": "http://api.example.org/accounts/?page=4",
  "previous": "http://api.example.org/accounts/?page=2",
  "results": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "question": "回應字串",
      "answer": "回應字串",
      "answerMediaUrls": null,
      "hitsCount": 456,
      "embeddingTokensCount": 456,
      "labels": [
        {
          "id": "550e8400-e29b-41d4-a716-446655440000",
          "name": "回應字串"
```

```
        }
      ],
      "rawUserDefineMetadata": null,
      "knowledgeBase": {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "name": "回應字串"
      }
    }
  ]
}
```


取得 AI 助理的所有檔案的文本節點

GET `/api/v1/chatbot-text-nodes/`

參數

參數名稱	必填	類型	說明
`chatbotFile`	X	string	【將棄用】Chatbot 檔案 ID（請使用 knowledge_base_file）
`knowledgeBaseFile`	X	string	知識庫檔案 ID（建議使用）
`page`	X	integer	A page number within the paginated result set.
`pageSize`	X	integer	Number of results to return per page.

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/chatbot-text-nodes/?
chatbotFile=example&knowledgeBaseFile=example&page=1&pageSize=1"

  -H "Authorization: Api-Key YOUR_API_KEY"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/chatbot-text-nodes/?
chatbotFile=example&knowledgeBaseFile=example&page=1&pageSize=1",
config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/chatbot-text-nodes/?
chatbotFile=example&knowledgeBaseFile=example&page=1&pageSize=1"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/chatbot-text-nodes/?
chatbotFile=example&knowledgeBaseFile=example&page=1&pageSize=1", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
{
  "count": integer
  "next"?: string (uri) // 非必填
```

```
  "previous"?: string (uri) // 非必填
  "results": [
    {
      "id": string (uuid)
      "charactersCount": integer
      "hitsCount": integer
      "text": string
      "updatedAt": string (timestamp)
      "filename": string
      "chatbotFile": object // 返回 ChatbotFile 的完整資訊，包含檔案 URL 和類型，以支援前端圖片預覽
      "knowledgeBaseFile": object // 與 get_chatbot_file 相同，提供向後兼容
      "pageNumber": integer // Backward-compatible alias of ``page_start``.
      "pageStart": integer
      "pageEnd": integer
      "citationTitle": string // Source title shown on the inline citation hover card.
      "citationDescription": string // Source description shown on the inline citation hover card.
      "citationQuote": string // Quoted text snippet shown on the inline citation hover card.
      "hasImage": boolean // 判斷是否包含圖片（檢查檔案類型或 text 中的 Markdown 圖片）
      "imageUrl": string // 提取圖片 URL（優先使用檔案 URL，否則從 Markdown 提取）
      "displayText": string // 返回移除圖片 Markdown 標記的完整文字
      "displayTitle": string // 返回顯示標題（fallback: citation_title -> filename）
      "highlightedText": string // Return text with matched terms wrapped in ``<mark>`` tags.

Priority:
1. ES/OpenSearch native highlight (set by retrieve_api via ``_es_highlighted_text``)
2. Python regex fallback (keyword-based, works for all backends)
      "labels": [
        {
          "id": string (uuid)
          "name": string
        }
      ]
      "rawUserDefineMetadata"?: object // Metadata keys and values defined by the user. (非必填)
      "metadataEnabledForSearch": object // Map each user-defined
```

```
metadata key on this node to whether it was sent into the LLM.

A key reaches the LLM only when its ``MetadataKey.enabled_for_search`` is
True *and*
the node carries a value for it. Since this maps over
``raw_user_define_metadata``
(the keys the cited-documents block displays, all of which have a value),
``enabled_for_search`` alone decides the flag. The source of truth is the
node's
knowledge base ``MetadataKey`` current setting, matching the AI Search
indicator.
      "startCharIdx": integer
      "endCharIdx": integer
    }
  ]
}
```

回應範例值

```
{
  "count": 123,
  "next": "http://api.example.org/accounts/?page=4",
  "previous": "http://api.example.org/accounts/?page=2",
  "results": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "charactersCount": 456,
      "hitsCount": 456,
      "text": "回應字串",
      "updatedAt": "回應字串",
      "filename": "回應字串",
      "chatbotFile": {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "name": "回應範例名稱",
        "description": "回應範例描述"
      },
      "knowledgeBaseFile": {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "name": "回應範例名稱",
        "description": "回應範例描述"
      },
      "pageNumber": 456,
      "pageStart": 456,
      "pageEnd": 456,
```

```
        "citationTitle": "回應字串",
        "citationDescription": "回應字串",
        "citationQuote": "回應字串",
        "hasImage": false,
        "imageUrl": "回應字串",
        "displayText": "回應字串",
        "displayTitle": "回應字串",
        "highlightedText": "回應字串",
        "labels": [
          {
            "id": "550e8400-e29b-41d4-a716-446655440000",
            "name": "回應字串"
          }
        ],
        "rawUserDefineMetadata": null,
        "metadataEnabledForSearch": {
          "key1": "value1",
          "key2": "value2",
          "createdAt": "2025-01-01T00:00:00.000Z"
        },
        "startCharIdx": 456,
        "endCharIdx": 456
      }
    ]
}
```


狀態碼: 403 - 無權讀取此檔案的文本節點：知識庫檔案需要 chatbot_knowledge_base_access 且群組已授權該知識庫；對話附件需要該助理的 chatbot_chatbot_access；收件匣檔案需要群組已授權該收件匣

狀態碼: 404 - 知識庫檔案不存在，或不屬於目前組織

取得 AI 助理的特定檔案的文本節點

GET `/api/v1/chatbot-text-nodes/{id}`

參數

參數名稱	必填	類型	說明
`id`	V	string	A UUID string identifying this ChatbotTextNode.

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/chatbot-text-
nodes/550e8400-e29b-41d4-a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/chatbot-text-
nodes/550e8400-e29b-41d4-a716-446655440000/", config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/chatbot-text-nodes/550e8400-
e29b-41d4-a716-446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/chatbot-text-nodes/550e8400-
e29b-41d4-a716-446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
{
  "id": string (uuid)
  "charactersCount": integer
```

```
  "hitsCount": integer
  "text": string
  "updatedAt": string (timestamp)
  "filename": string
  "chatbotFile": object // 返回 ChatbotFile 的完整資訊，包含檔案 URL 和類型，以支援前端圖片預覽
  "knowledgeBaseFile": object // 與 get_chatbot_file 相同，提供向後兼容
  "pageNumber": integer // Backward-compatible alias of ``page_start``.
  "pageStart": integer
  "pageEnd": integer
  "citationTitle": string // Source title shown on the inline citation hover card.
  "citationDescription": string // Source description shown on the inline citation hover card.
  "citationQuote": string // Quoted text snippet shown on the inline citation hover card.
  "hasImage": boolean // 判斷是否包含圖片（檢查檔案類型或 text 中的 Markdown 圖片）
  "imageUrl": string // 提取圖片 URL（優先使用檔案 URL，否則從 Markdown 提取）
  "displayText": string // 返回移除圖片 Markdown 標記的完整文字
  "displayTitle": string // 返回顯示標題（fallback: citation_title -> filename）
  "highlightedText": string // Return text with matched terms wrapped in ``<mark>`` tags.

Priority:
1. ES/OpenSearch native highlight (set by retrieve_api via ``_es_highlighted_text``)
2. Python regex fallback (keyword-based, works for all backends)
  "labels": [
    {
      "id": string (uuid)
      "name": string
    }
  ]
  "rawUserDefineMetadata"?: object // Metadata keys and values defined by the user. (非必填)
  "metadataEnabledForSearch": object // Map each user-defined metadata key on this node to whether it was sent into the LLM.

A key reaches the LLM only when its ``MetadataKey.enabled_for_search`` is True *and*
the node carries a value for it. Since this maps over ``raw_user_define_metadata``
(the keys the cited-documents block displays, all of which have a value),
```

```
``enabled_for_search`` alone decides the flag. The source of truth is the
node's
knowledge base ``MetadataKey`` current setting, matching the AI Search
indicator.
  "startCharIdx": integer
  "endCharIdx": integer
}
```

回應範例值


```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "charactersCount": 456,
  "hitsCount": 456,
  "text": "回應字串",
  "updatedAt": "回應字串",
  "filename": "回應字串",
  "chatbotFile": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應範例名稱",
    "description": "回應範例描述"
  },
  "knowledgeBaseFile": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應範例名稱",
    "description": "回應範例描述"
  },
  "pageNumber": 456,
  "pageStart": 456,
  "pageEnd": 456,
  "citationTitle": "回應字串",
  "citationDescription": "回應字串",
  "citationQuote": "回應字串",
  "hasImage": false,
  "imageUrl": "回應字串",
  "displayText": "回應字串",
  "displayTitle": "回應字串",
  "highlightedText": "回應字串",
  "labels": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "回應字串"
    }
  ],
```

```
  "rawUserDefineMetadata": null,
  "metadataEnabledForSearch": {
    "key1": "value1",
    "key2": "value2",
    "createdAt": "2025-01-01T00:00:00.000Z"
  },
  "startCharIdx": 456,
  "endCharIdx": 456
}
```


搜尋測試

POST `/api/v1/chatbots/{id}/search/`

參數

參數名稱	必填	類型	說明
`id`	V	string	
`createdByMember`	X	string	建立者篩選：本組織成員 id（成員名冊回傳的 id，含已停用成員），只回該成員建立的 AI 助理
`largeLanguageModel`	X	string	
`page`	X	integer	A page number within the paginated result set.
`pageSize`	X	integer	Number of results to return per page.
`query`	X	string	
`replyMode`	X	string	

`source`		X	string	`self_built`: self_built ; `built_in`: built_in ; `all`: all;

請求內容

請求參數

欄位	類型	必填	說明
queryMetadata	object	否	Not supported for chatbot-wide search; providing a value returns 400.

請求結構範例

```
{
  "queryMetadata"?: object // Not supported for chatbot-wide search;
providing a value returns 400. (非必填)
}
```

請求範例值

```
{
  "queryMetadata": null
}
```

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X POST "

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "query": "範例字串",
    "queryMetadata": null
  }'

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// 請求內容 (payload)
const data = {
    "query": "範例字串",
    "queryMetadata": null
  };

axios.post(" data, config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# 請求內容 (payload)
data = {
    "query": "範例字串",
    "queryMetadata": None
}

response = requests.post(url, json=data, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->post(" [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'query' => '範例字串',
            'queryMetadata' => null
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
{
  "count": integer
  "next"?: string (uri) // 非必填
  "previous"?: string (uri) // 非必填
  "results": [
    {
      "id": string (uuid)
      "charactersCount": integer
      "hitsCount": integer
      "text": string
      "updatedAt": string (timestamp)
      "filename": string
      "chatbotFile": object // 返回 ChatbotFile 的完整資訊，包含檔案 URL 和類型，以支援前端圖片預覽
      "knowledgeBaseFile": object // 與 get_chatbot_file 相同，提供向後兼容
      "pageNumber": integer // Backward-compatible alias of ``page_start``.
      "pageStart": integer
      "pageEnd": integer
      "citationTitle": string // Source title shown on the inline citation hover card.
      "citationDescription": string // Source description shown on the inline citation hover card.
      "citationQuote": string // Quoted text snippet shown on the inline citation hover card.
      "hasImage": boolean // 判斷是否包含圖片（檢查檔案類型或 text 中的 Markdown 圖片）
      "imageUrl": string // 提取圖片 URL（優先使用檔案 URL，否則從 Markdown 提取）
      "displayText": string // 返回移除圖片 Markdown 標記的完整文字
      "displayTitle": string // 返回顯示標題（fallback: citation_title -> filename）
      "highlightedText": string // Return text with matched terms wrapped in ``<mark>`` tags.

Priority:
1. ES/OpenSearch native highlight (set by retrieve_api via ``_es_highlighted_text``)
2. Python regex fallback (keyword-based, works for all backends)
      "labels": [
        {
          "id": string (uuid)
          "name": string
        }
```

```
      ]
      "rawUserDefineMetadata"?: object // Metadata keys and values
defined by the user. (非必填)
      "metadataEnabledForSearch": object // Map each user-defined
metadata key on this node to whether it was sent into the LLM.

A key reaches the LLM only when its ``MetadataKey.enabled_for_search`` is
True *and*
the node carries a value for it. Since this maps over
``raw_user_define_metadata``
(the keys the cited-documents block displays, all of which have a value),
``enabled_for_search`` alone decides the flag. The source of truth is the
node's
knowledge base ``MetadataKey`` current setting, matching the AI Search
indicator.
      "startCharIdx": integer
      "endCharIdx": integer
    }
  ]
}
```

回應範例值

```
{
  "count": 123,
  "next": "http://api.example.org/accounts/?page=4",
  "previous": "http://api.example.org/accounts/?page=2",
  "results": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "charactersCount": 456,
      "hitsCount": 456,
      "text": "回應字串",
      "updatedAt": "回應字串",
      "filename": "回應字串",
      "chatbotFile": {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "name": "回應範例名稱",
        "description": "回應範例描述"
      },
      "knowledgeBaseFile": {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "name": "回應範例名稱",
        "description": "回應範例描述"
```

```
      },
      "pageNumber": 456,
      "pageStart": 456,
      "pageEnd": 456,
      "citationTitle": "回應字串",
      "citationDescription": "回應字串",
      "citationQuote": "回應字串",
      "hasImage": false,
      "imageUrl": "回應字串",
      "displayText": "回應字串",
      "displayTitle": "回應字串",
      "highlightedText": "回應字串",
      "labels": [
        {
          "id": "550e8400-e29b-41d4-a716-446655440000",
          "name": "回應字串"
        }
      ],
      "rawUserDefineMetadata": null,
      "metadataEnabledForSearch": {
        "key1": "value1",
        "key2": "value2",
        "createdAt": "2025-01-01T00:00:00.000Z"
      },
      "startCharIdx": 456,
      "endCharIdx": 456
    }
  ]
}
```


列出檔案類型支援的解析器

`GET` `/api/v1/parsers/supported-file-types/`

參數

參數名稱	必填	類型	說明
knowledgeBaseId	X	string	Knowledge base ID. When provided and the knowledge base does not support multimodal embeddings, image file types will be filtered out.

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/parsers/supported-file-types/?knowledgeBaseId=example"

  -H "Authorization: Api-Key YOUR_API_KEY"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/parsers/supported-file-types/?knowledgeBaseId=example", config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/parsers/supported-file-types/?
knowledgeBaseId=example"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/parsers/supported-file-types/?
knowledgeBaseId=example", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
[
  {
    "fileType": string
```

```
    "parsers": [
      {
        "id": string (uuid)
        "name": string
        "provider":
        {
        }
        "order"?: integer // 非必填
        "isTimestampSttProvider": boolean
        "asrProvider": object // The provider spec, built once per
provider row per response.

The spec is platform-level, not per parser, and it is large — a
whisper-family row carries a 100-entry language catalog in its
``languages`` spec, as codes plus display names. This serializer is
nested per row in the knowledge-base file listing and in message
citations, so without memoizing, one response rebuilds the same
catalog for every row. ``self.context`` is the root serializer's shared
dict, which is also what keeps ``get_active_diarization_rows`` at one
query per response.
      }
    ]
    "autoDetect": boolean // Whether files of this type get parser auto-
detection after upload
(the system auto-detects a parser when the user did not choose one).
  }
]
```

回應範例值

```
[
  [
    {
      "fileType": ".pdf",
      "parsers": [
        {
          "id": "ab83f144-5026-4bce-993f-5c982cc19318",
          "name": "MaiAgent Parser",
          "provider": "maiagent",
          "order": 0,
          "isDefault": true
        },
        {
          "id": "22fdcbb5-f075-4aad-bb81-048289ca4b25",
```

```
        "name": "MaiAgent Parser (Online)",
        "provider": "llama",
        "order": 2,
        "isDefault": false
      }
    ]
  },
  {
    "fileType": ".doc",
    "parsers": [
      {
        "id": "ab83f144-5026-4bce-993f-5c982cc19318",
        "name": "MaiAgent Parser",
        "provider": "maiagent",
        "order": 0,
        "isDefault": true
      },
      {
        "id": "22fdcbb5-f075-4aad-bb81-048289ca4b25",
        "name": "MaiAgent Parser (Online)",
        "provider": "llama",
        "order": 2,
        "isDefault": false
      }
    ]
  },
  {
    "fileType": ".docx",
    "parsers": [
      {
        "id": "ab83f144-5026-4bce-993f-5c982cc19318",
        "name": "MaiAgent Parser",
        "provider": "maiagent",
        "order": 0,
        "isDefault": true
      },
      {
        "id": "22fdcbb5-f075-4aad-bb81-048289ca4b25",
        "name": "MaiAgent Parser (Online)",
        "provider": "llama",
        "order": 2,
        "isDefault": false
      }
    ]
  },
```

```
    {
      "fileType": ".ppt",
      "parsers": [
        {
          "id": "ab83f144-5026-4bce-993f-5c982cc19318",
          "name": "MaiAgent Parser",
          "provider": "maiagent",
          "order": 0,
          "isDefault": true
        },
        {
          "id": "22fdcbb5-f075-4aad-bb81-048289ca4b25",
          "name": "MaiAgent Parser (Online)",
          "provider": "llama",
          "order": 2,
          "isDefault": false
        }
      ]
    },
    {
      "fileType": ".pptx",
      "parsers": [
        {
          "id": "ab83f144-5026-4bce-993f-5c982cc19318",
          "name": "MaiAgent Parser",
          "provider": "maiagent",
          "order": 0,
          "isDefault": true
        },
        {
          "id": "22fdcbb5-f075-4aad-bb81-048289ca4b25",
          "name": "MaiAgent Parser (Online)",
          "provider": "llama",
          "order": 2,
          "isDefault": false
        }
      ]
    },
    {
      "fileType": ".xls",
      "parsers": [
        {
          "id": "ab83f144-5026-4bce-993f-5c982cc19318",
          "name": "MaiAgent Parser",
          "provider": "maiagent",
```

```
        "order": 0,
        "isDefault": true
      }
    ]
  },
  {
    "fileType": ".xlsx",
    "parsers": [
      {
        "id": "ab83f144-5026-4bce-993f-5c982cc19318",
        "name": "MaiAgent Parser",
        "provider": "maiagent",
        "order": 0,
        "isDefault": true
      }
    ]
  },
  {
    "fileType": ".csv",
    "parsers": [
      {
        "id": "ab83f144-5026-4bce-993f-5c982cc19318",
        "name": "MaiAgent Parser",
        "provider": "maiagent",
        "order": 0,
        "isDefault": true
      }
    ]
  },
  {
    "fileType": ".txt",
    "parsers": [
      {
        "id": "ab83f144-5026-4bce-993f-5c982cc19318",
        "name": "MaiAgent Parser",
        "provider": "maiagent",
        "order": 0,
        "isDefault": true
      },
      {
        "id": "22fdcbb5-f075-4aad-bb81-048289ca4b25",
        "name": "MaiAgent Parser (Online)",
        "provider": "llama",
        "order": 2,
        "isDefault": false
```

```
      }
    ]
  },
  {
    "fileType": ".md",
    "parsers": [
      {
        "id": "ab83f144-5026-4bce-993f-5c982cc19318",
        "name": "MaiAgent Parser",
        "provider": "maiagent",
        "order": 0,
        "isDefault": true
      }
    ]
  },
  {
    "fileType": ".json",
    "parsers": [
      {
        "id": "ab83f144-5026-4bce-993f-5c982cc19318",
        "name": "MaiAgent Parser",
        "provider": "maiagent",
        "order": 0,
        "isDefault": true
      }
    ]
  },
  {
    "fileType": ".jsonl",
    "parsers": [
      {
        "id": "ab83f144-5026-4bce-993f-5c982cc19318",
        "name": "MaiAgent Parser",
        "provider": "maiagent",
        "order": 0,
        "isDefault": true
      }
    ]
  },
  {
    "fileType": ".html",
    "parsers": [
      {
        "id": "22fdcbb5-f075-4aad-bb81-048289ca4b25",
        "name": "MaiAgent Parser (Online)",
```

```
        "provider": "llama",
        "order": 2,
        "isDefault": false
      }
    ]
  },
  {
    "fileType": ".mp3",
    "parsers": [
      {
        "id": "4c47e305-2eb7-4438-8d3c-d91eb0b06cc0",
        "name": "Azure Speech",
        "provider": "azure",
        "order": 1,
        "isDefault": true
      },
      {
        "id": "22fdcbb5-f075-4aad-bb81-048289ca4b25",
        "name": "MaiAgent Parser (Online)",
        "provider": "llama",
        "order": 2,
        "isDefault": false
      }
    ]
  },
  {
    "fileType": ".wav",
    "parsers": [
      {
        "id": "4c47e305-2eb7-4438-8d3c-d91eb0b06cc0",
        "name": "Azure Speech",
        "provider": "azure",
        "order": 1,
        "isDefault": true
      },
      {
        "id": "22fdcbb5-f075-4aad-bb81-048289ca4b25",
        "name": "MaiAgent Parser (Online)",
        "provider": "llama",
        "order": 2,
        "isDefault": false
      }
    ]
  },
  {
```

```
      "fileType": ".mp4",
      "parsers": [
        {
          "id": "22fdcbb5-f075-4aad-bb81-048289ca4b25",
          "name": "MaiAgent Parser (Online)",
          "provider": "llama",
          "order": 2,
          "isDefault": false
        }
      ]
    }
  ]
]
```

呼叫 API 示例 (Shell)

目錄

1. 帳號註冊
2. 更換密碼
3. 建立新組織
4. 新增成員至指定組織
5. 取得組織列表
6. 取得特定組織資訊
7. 取得當前用戶詳細資訊
8. 取得當前用戶權限
9. 取得指定組織的成員列表
10. 取得特定成員詳細資訊
11. 更新組織資訊
12. 更新當前用戶詳細資訊
13. 更新成員所屬角色
14. 列出組織的 API Key
15. 替成員簽發 API Key
16. 取得特定 API Key
17. 更新 API Key 設定
18. 撤銷 API Key
19. 查詢 API Key 所屬組織
20. 換發成員嵌入 token
21. 列出 OAuth 應用程式
22. 註冊 OAuth 應用程式
23. 取得特定 OAuth 應用程式
24. 更新 OAuth 應用程式
25. 刪除 OAuth 應用程式並撤銷其 token
26. 重新產生 client secret
27. 列出我授權過的 OAuth 應用程式
28. 撤銷我對某應用程式的授權
29. 刪除組織
30. 刪除指定成員
31. 取得成員使用統計
32. 取得成員使用統計摘要
33. 取得 AI 助理使用統計
34. 取得 AI 助理使用統計摘要
35. 列出自己的記憶

36. 建立或更新自己的記憶
37. 修改或重新啟用自己的記憶
38. 刪除自己的記憶

呼叫 API 示例 (Shell)

帳號註冊

`POST` `/api/v1/auth/registration/`

請求內容

請求參數

欄位	類型	必填	說明
email	string (email)	是	
password1	string	是	
password2	string	是	
name	string	是	
company	string	是	
referralCode	string	否	
authSource	object (含 2 個屬性: id, name)	否	
authSource.id	string (uuid)	是	

請求結構範例

```
{
  "email": string (email)
  "password1": string
  "password2": string
```

```
  "name": string
  "company": string
  "referralCode"?: string // 非必填
  "authSource"?:  // 非必填
  {
    "id": string (uuid)
  }
}
```

請求範例值

```
{
  "email": "user@example.com",
  "password1": "範例字串",
  "password2": "範例字串",
  "name": "範例名稱",
  "company": "範例字串",
  "referralCode": "範例字串",
  "authSource": {
    "id": "550e8400-e29b-41d4-a716-446655440000"
  }
}
```

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X POST "https://api.maiagent.ai/api/v1/auth/registration/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "email": "user@example.com",
    "password1": "範例字串",
    "password2": "範例字串",
    "name": "範例名稱",
    "company": "範例字串",
    "referralCode": "範例字串",
    "authSource": {
      "id": "550e8400-e29b-41d4-a716-446655440000"
    }
  }'

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// 請求內容 (payload)
const data = {
    "email": "user@example.com",
    "password1": "範例字串",
    "password2": "範例字串",
    "name": "範例名稱",
    "company": "範例字串",
    "referralCode": "範例字串",
    "authSource": {
      "id": "550e8400-e29b-41d4-a716-446655440000"
    }
  };

axios.post("https://api.maiagent.ai/api/v1/auth/registration/",
data, config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/auth/registration/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# 請求內容 (payload)
data = {
    "email": "user@example.com",
    "password1": "範例字串",
    "password2": "範例字串",
    "name": "範例名稱",
    "company": "範例字串",
    "referralCode": "範例字串",
    "authSource": {
        "id": "550e8400-e29b-41d4-a716-446655440000"
    }
}

response = requests.post(url, json=data, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>post("https://api.maiagent.ai/api/v1/auth/registration/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'email' => 'user@example.com',
            'password1' => '範例字串',
            'password2' => '範例字串',
            'name' => '範例名稱',
            'company' => '範例字串',
            'referralCode' => '範例字串',
            'authSource' => [
                'id' => '550e8400-e29b-41d4-a716-446655440000'
            ]
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 201

回應結構範例

```
{
  "email": string (email)
  "password1": string
  "password2": string
  "name": string
  "company": string
  "referralCode"?: string // 非必填
  "authSource"?:  // 非必填
  {
    "id": string (uuid)
    "name": string
  }
}
```

回應範例值

```
{
  "email": "response@example.com",
  "password1": "回應字串",
  "password2": "回應字串",
  "name": "回應字串",
  "company": "回應字串",
  "referralCode": "回應字串",
  "authSource": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應字串"
  }
}
```

更換密碼

POST `/api/v1/auth/password/change/`

請求內容

請求參數

欄位	類型	必填	說明
oldPassword	string	是	
newPassword1	string	是	
newPassword2	string	是	

請求結構範例

```
{
  "oldPassword": string
  "newPassword1": string
  "newPassword2": string
}
```

請求範例值

```
{
  "oldPassword": "範例字串",
  "newPassword1": "範例字串",
  "newPassword2": "範例字串"
}
```

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X POST "https://api.maiagent.ai/api/v1/auth/password/change/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "oldPassword": "範例字串",
    "newPassword1": "範例字串",
    "newPassword2": "範例字串"
  }'

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// 請求內容 (payload)
const data = {
    "oldPassword": "範例字串",
    "newPassword1": "範例字串",
    "newPassword2": "範例字串"
  };

axios.post("https://api.maiagent.ai/api/v1/auth/password/change/",
data, config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```python
import requests

url = "https://api.maiagent.ai/api/v1/auth/password/change/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# 請求內容 (payload)
data = {
    "oldPassword": "範例字串",
    "newPassword1": "範例字串",
    "newPassword2": "範例字串"
}

response = requests.post(url, json=data, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>post("https://api.maiagent.ai/api/v1/auth/password/change/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'oldPassword' => '範例字串',
            'newPassword1' => '範例字串',
            'newPassword2' => '範例字串'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
{
  "detail": string
}
```

回應範例值

```
{
  "detail": "回應字串"
}
```

建立新組織

POST `/api/v1/organizations/`

請求內容

請求參數

欄位	類型	必填	說明
name	string	是	組織名稱
compact_logo	string (binary)	否	簡潔版 Logo（選填，僅企業方案可用）
full_logo	string (binary)	否	完整版 Logo（選填，僅企業方案可用）

請求結構範例

```
{
  "name": string // 組織名稱
  "compact_logo"?: string (binary) // 簡潔版 Logo（選填，僅企業方案可用） (非必填)
```

```
  "full_logo"?: string (binary) // 完整版 Logo（選填，僅企業方案可用） (非必填)
}
```

請求範例值

```
{
  "name": "My Organization"
}
```

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X POST "https://api.maiagent.ai/api/v1/organizations/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "name": "My Organization"
  }'

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// 請求內容 (payload)
const data = {
    "name": "My Organization"
  };

axios.post("https://api.maiagent.ai/api/v1/organizations/", data,
config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/organizations/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# 請求內容 (payload)
data = {
    "name": "My Organization"
}

response = requests.post(url, json=data, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>post("https://api.maiagent.ai/api/v1/organizations/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'name' => 'My Organization'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 201

回應結構範例

```
{
  "id": string (uuid)
  "name": string
  "createdAt": string (timestamp)
  "compactLogo"?: string (uri) // 非必填
  "fullLogo"?: string (uri) // 非必填
  "themePrimaryColor"?: // 可能有不同的類型 (非必填)
  string // UI 主題色，用於按鈕、連結等元素的顏色（HEX 格式，如 #0960bd）；留空表示未設定，前端退階使用系統品牌主色 (非必填)
  "usageStatistics": object
  "organizationPlan": object
  "creditWallet": object // Return credit wallet with ID only.
  "maigptInboxId": string (uuid)
  "canUseCustomElasticsearch": boolean // Allow this organization to configure custom Elasticsearch endpoints for knowledge bases.
  "canUseVoiceAgent": boolean // Allow this organization to use voice agent features.
  "canUseMeetingRecords": boolean // Allow this organization to use meeting records features.
  "canUseCallCenter": boolean // Allow this organization to use call center features.
  "canUseHookSystem": boolean // Manual override to grant this organization the hook system regardless of plan. Enterprise-plan organizations get access automatically without this flag. Layered under the global Config.hook_system_enabled switch: it must also be enabled.
  "canUseAiGateway": boolean // Allow this organization to call the OpenAI-compatible `/api/v1/chat/completions` Gateway. On by default for license installs, otherwise off until a platform admin enables it.
  "canUseAgentTeams": boolean // Read-only projection of the platform-wide Agent Teams switch (Config.enable_agent_teams). Not a per-organization flag; member-level access is still governed by RBAC.
  "canUseFileLibrary": boolean // Allow this organization to use the file library. Off by default for gradual rollout.
  "canUseFileOnlineEditing": boolean // Enable online editing in the file library (P7): the text editor and upload-new-version entries. Requires can_use_file_library to also be on.
  "canUseOfficeOnlineEditing": boolean // Enable Office (xlsx/docx/pptx) online editing in the file library (P7 S9). Requires can_use_file_online_editing to also be on.
  "canUseRolePermissionGovernance": boolean // Enables both batch permission settings on the roles page and the effective permissions view on the members page. Turning it off hides both and restores the previous behavior immediately, with no redeploy; permission changes already applied are kept. Off by default for gradual rollout.
```

```
  "enableAgentMemory": boolean // Enable persistent cross-conversation memory for agents in this organization. When off, agents use only in-session memory. On by default on SaaS; license installs remain opt-in. Members can still turn it off for themselves in Profile > AI Memory.
  "hideChinaModels"?: boolean // When on, platform models whose developer is based in China (including ones added later) are not visible or usable in this organization: model menus, assistants, the API and AI Gateway all exclude them. (非必填)
  "autoActivateNewChatbotChannels"?: boolean // Initial state of the web chat and API channels of a new chatbot whose creator did not set them (duplicates, templates and API calls without the values included). When on, they start active; when off (the platform default), they start inactive until a member turns them on. The creator can still override both channels in the New Chatbot dialog or the create API. The backstage (admin) channel is always active. Changing this does not affect existing chatbots. (非必填)
  "gatewayServiceFeePercent": string (decimal) // Markup applied on top of the token price when billing MaiAgent-managed models called through the AI Gateway (/v1/chat/completions and /v1/embeddings). Managed gateway markup only; the organization's own models (BYOK / self-hosted) are billed via the AI Gateway traffic fee percent instead.
  "gatewayTrafficFeePercent": string (decimal) // Pass-through fee for calls that run on this organization's own AI Gateway models (BYOK / self-hosted): charged as the call's total tokens (input, output, and prompt-cache) x this percent in credits, with no LLM token pricing. Adjustable per organization; changes apply to new calls only.
  "platformProcessingFeePercent": string (decimal) // Surcharge on every credit consumption of this organization, billed as a separate "Platform Processing Fee" line equal to the consumed credits x this percent. 0 disables the fee. Applies to new consumption only; the percent is shown read-only on the customer pricing page.
  "platformProcessingFeeEnabled": boolean // Whether new consumption of this organization accrues the platform processing fee. The percent is exposed read-only as platform_processing_fee_percent.
  "isTrial": boolean // 是否為試用期。判定邏輯：組織只有一個試用方案且目前有效
  "expirationDays": integer // 已過期天數。正數=已過期天數，null=尚未到期或永久方案
  "showTrialBanner": boolean // 控制前端是否顯示試用/免費方案橫幅
  "agentScheduleMinIntervalSeconds": integer // 排程最小執行間隔（秒），平台設定；建立／編輯排程時前端以此提示下限，實際檢查仍在排程 API
  "noActivePlanDays": integer // Consecutive days without an active paid plan. null when cleanup is disabled.
  "cleanupRemainingDays": integer // Days remaining before organization data is permanently deleted. null when cleanup is disabled, org has an active paid plan, or no_active_plan_days is 0.
```

```
  "estimatedCleanupDate": string // ISO date when organization data will be permanently deleted. null when cleanup_remaining_days is null.
  "approvalStatus":  // Trial-eligibility review status. Only approved organizations can receive a trial plan when organization approval is enabled. Paid plan activation auto-approves the organization.

* `pending` - Pending Review
* `approved` - Approved
* `rejected` - Rejected
  {
  }
  "companyName"?: string // Applicant-reported company name collected at organization creation for approval review. (非必填)
  "taxId"?: // 可能有不同的類型 (非必填)
  string // Applicant-reported business tax ID (8 digits, optional). Stored as-is; not verified. (非必填)
  "contactPhone"?: string // Applicant-reported contact phone collected at organization creation for approval review. (非必填)
  "applicationMetadata"?: object // Extra applicant-reported key-value fields collected at organization creation. Lets the frontend collect additional review fields without a schema migration; the core review fields (company name, tax ID, contact phone) stay as named columns. (非必填)
  "invitationCode"?: string // 非必填
  "ipAllowlistEnabled": boolean // Restrict this organization to the source IPs listed in allowed_ip_cidrs. Layered under the global Config.ip_allowlist_enforcement_enabled switch: both must be enabled. Disabled by default so existing organizations keep unrestricted access.
  "allowedIpCidrs": string // Source IPs or CIDRs allowed to reach this organization, one per line (e.g. 203.0.113.0/24); commas also work. While the IP allowlist is enabled, an empty list rejects everything. A non-empty list whose entries are all invalid rejects everything rather than silently reverting to unrestricted, so a typo cannot quietly disable the protection. Matching uses the load-balancer-appended client IP.
  "enforceIpAllowlistOnAdminUi": boolean // Apply the allowlist to browser sessions: the admin console and its WebSocket connections. Only takes effect while ip_allowlist_enabled is on.
  "enforceIpAllowlistOnApiKey": boolean // Apply the allowlist to Open API (Api-Key) and AI Gateway (Bearer) requests. Only takes effect while ip_allowlist_enabled is on.
}
```

回應範例值

```
{
  "id": "5b01e0b9-0b0e-4079-8150-d12015576d2c",
  "name": "My Organization",
  "createdAt": "1748336288000",
  "compactLogo": null,
  "fullLogo": null,
  "usageStatistics": {
    "chatbotsCount": 0,
    "countableChatbotsCount": 0,
    "exemptChatbotsByMode": {},
    "canCreateChatbot": true,
    "createChatbotLimit": 1,
    "currentMonthWordsCountTotal": 1000000,
    "currentMonthUsedWordsCountTotal": 0,
    "currentMonthUsedConversationsCountTotal": 0,
    "availableUploadFilesSizeTotal": 104857600,
    "usedUploadFileSizeTotal": 0
  },
  "organizationPlan": {
    "id": "cac825e8-cb9b-4a16-b440-4ff6b2e73911",
    "planName": "免費方案",
    "planType": "free",
    "expiredAt": null
  },
  "maigptInboxId": null,
  "canUseCustomElasticsearch": false,
  "isTrial": true,
  "expirationDays": null
}
```


新增成員至指定組織

`POST` `/api/v1/organizations/{organizationPk}/members/`

參數

參數名稱	必填	類型	說明
`organizationPk`	V	string	A UUID string identifying this 組織 ID

請求內容

請求參數

欄位	類型	必填	說明
email	string (email)	是	
organization	string (uuid)	否	

請求結構範例

```
{
  "email": string (email)
  "organization"?: string (uuid) // 非必填
}
```

請求範例值

```
{
  "organization": "613c86f7-a45f-4e29-b255-29caff89de32",
  "is_owner": false
}
```

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X POST "https://api.maiagent.ai/api/v1/organizations/550e8400-
e29b-41d4-a716-446655440000/members/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "organization": "613c86f7-a45f-4e29-b255-29caff89de32",
    "is_owner": false
  }'

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// 請求內容 (payload)
const data = {
    "organization": "613c86f7-a45f-4e29-b255-29caff89de32",
    "is_owner": false
  };

axios.post("https://api.maiagent.ai/api/v1/organizations/550e8400-
e29b-41d4-a716-446655440000/members/", data, config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-
41d4-a716-446655440000/members/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# 請求內容 (payload)
data = {
    "organization": "613c86f7-a45f-4e29-b255-29caff89de32",
    "is_owner": False
}

response = requests.post(url, json=data, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>post("https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-
41d4-a716-446655440000/members/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'organization' => '613c86f7-a45f-4e29-b255-
29caff89de32',
            'is_owner' => false
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 201

回應結構範例

```
{
  "organization": string (uuid) // 組織 ID
  "is_owner": boolean // 是否為組織擁有者
}
```

回應範例值

```
{
  "organization": "613c86f7-a45f-4e29-b255-29caff89de32",
  "is_owner": false
}
```

取得組織列表

GET `/api/v1/organizations/`

參數

參數名稱	必填	類型	說明
`page`	X	integer	A page number within the paginated result set.
`pageSize`	X	integer	Number of results to return per page.
`pagination`	X	string	是否分頁 (true/false)

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/organizations/?
page=1&pageSize=1&pagination=example"

  -H "Authorization: Api-Key YOUR_API_KEY"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/organizations/?
page=1&pageSize=1&pagination=example", config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/organizations/?
page=1&pageSize=1&pagination=example"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/organizations/?
page=1&pageSize=1&pagination=example", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
{
  "count": integer
  "next"?: string (uri) // 非必填
```

```
  "previous"?: string (uri) // 非必填
  "results": [
    {
      "id": string (uuid)
      "name": string
      "createdAt": string (timestamp)
      "memberCreatedAt": string (timestamp)
      "approvalStatus": string
    }
  ]
}
```

回應範例值

```
{
  "count": 123,
  "next": "http://api.example.org/accounts/?page=4",
  "previous": "http://api.example.org/accounts/?page=2",
  "results": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "回應字串",
      "createdAt": "回應字串",
      "memberCreatedAt": "回應字串",
      "approvalStatus": "回應字串"
    }
  ]
}
```

取得特定組織資訊

GET `/api/v1/organizations/{id}`

參數

參數名稱	必填	類型	說明
id	V	string	A UUID string identifying this 組織.

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/organizations/550e8400-
e29b-41d4-a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/organizations/550e8400-
e29b-41d4-a716-446655440000/", config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-
41d4-a716-446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-
41d4-a716-446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
{
  "id": string (uuid)
  "name": string
```

```
  "createdAt": string (timestamp)
  "compactLogo"?: string (uri) // 非必填
  "fullLogo"?: string (uri) // 非必填
  "themePrimaryColor"?: // 可能有不同的類型 (非必填)
  string // UI 主題色，用於按鈕、連結等元素的顏色（HEX 格式，如 #0960bd）；留空表示未設定，前端退階使用系統品牌主色 (非必填)
  "usageStatistics": object
  "organizationPlan": object
  "creditWallet": object // Return credit wallet with ID only.
  "maigptInboxId": string (uuid)
  "canUseCustomElasticsearch": boolean // Allow this organization to configure custom Elasticsearch endpoints for knowledge bases.
  "canUseVoiceAgent": boolean // Allow this organization to use voice agent features.
  "canUseMeetingRecords": boolean // Allow this organization to use meeting records features.
  "canUseCallCenter": boolean // Allow this organization to use call center features.
  "canUseHookSystem": boolean // Manual override to grant this organization the hook system regardless of plan. Enterprise-plan organizations get access automatically without this flag. Layered under the global Config.hook_system_enabled switch: it must also be enabled.
  "canUseAiGateway": boolean // Allow this organization to call the OpenAI-compatible `/api/v1/chat/completions` Gateway. On by default for license installs, otherwise off until a platform admin enables it.
  "canUseAgentTeams": boolean // Read-only projection of the platform-wide Agent Teams switch (Config.enable_agent_teams). Not a per-organization flag; member-level access is still governed by RBAC.
  "canUseFileLibrary": boolean // Allow this organization to use the file library. Off by default for gradual rollout.
  "canUseFileOnlineEditing": boolean // Enable online editing in the file library (P7): the text editor and upload-new-version entries. Requires can_use_file_library to also be on.
  "canUseOfficeOnlineEditing": boolean // Enable Office (xlsx/docx/pptx) online editing in the file library (P7 S9). Requires can_use_file_online_editing to also be on.
  "canUseRolePermissionGovernance": boolean // Enables both batch permission settings on the roles page and the effective permissions view on the members page. Turning it off hides both and restores the previous behavior immediately, with no redeploy; permission changes already applied are kept. Off by default for gradual rollout.
  "enableAgentMemory": boolean // Enable persistent cross-conversation memory for agents in this organization. When off, agents use only in-session memory. On by default on SaaS; license installs remain opt-in. Members can still turn it off for themselves in Profile > AI Memory.
```

```
  "hideChinaModels"?: boolean // When on, platform models whose developer is based in China (including ones added later) are not visible or usable in this organization: model menus, assistants, the API and AI Gateway all exclude them. (非必填)
  "autoActivateNewChatbotChannels"?: boolean // Initial state of the web chat and API channels of a new chatbot whose creator did not set them (duplicates, templates and API calls without the values included). When on, they start active; when off (the platform default), they start inactive until a member turns them on. The creator can still override both channels in the New Chatbot dialog or the create API. The backstage (admin) channel is always active. Changing this does not affect existing chatbots. (非必填)
  "gatewayServiceFeePercent": string (decimal) // Markup applied on top of the token price when billing MaiAgent-managed models called through the AI Gateway (/v1/chat/completions and /v1/embeddings). Managed gateway markup only; the organization's own models (BYOK / self-hosted) are billed via the AI Gateway traffic fee percent instead.
  "gatewayTrafficFeePercent": string (decimal) // Pass-through fee for calls that run on this organization's own AI Gateway models (BYOK / self-hosted): charged as the call's total tokens (input, output, and prompt-cache) x this percent in credits, with no LLM token pricing. Adjustable per organization; changes apply to new calls only.
  "platformProcessingFeePercent": string (decimal) // Surcharge on every credit consumption of this organization, billed as a separate "Platform Processing Fee" line equal to the consumed credits x this percent. 0 disables the fee. Applies to new consumption only; the percent is shown read-only on the customer pricing page.
  "platformProcessingFeeEnabled": boolean // Whether new consumption of this organization accrues the platform processing fee. The percent is exposed read-only as platform_processing_fee_percent.
  "isTrial": boolean // 是否為試用期。判定邏輯：組織只有一個試用方案且目前有效
  "expirationDays": integer // 已過期天數。正數=已過期天數，null=尚未到期或永久方案
  "showTrialBanner": boolean // 控制前端是否顯示試用/免費方案橫幅
  "agentScheduleMinIntervalSeconds": integer // 排程最小執行間隔（秒），平台設定；建立／編輯排程時前端以此提示下限，實際檢查仍在排程 API
  "noActivePlanDays": integer // Consecutive days without an active paid plan. null when cleanup is disabled.
  "cleanupRemainingDays": integer // Days remaining before organization data is permanently deleted. null when cleanup is disabled, org has an active paid plan, or no_active_plan_days is 0.
  "estimatedCleanupDate": string // ISO date when organization data will be permanently deleted. null when cleanup_remaining_days is null.
  "approvalStatus":  // Trial-eligibility review status. Only approved organizations can receive a trial plan when organization approval is
```

```
enabled. Paid plan activation auto-approves the organization.

* `pending` - Pending Review
* `approved` - Approved
* `rejected` - Rejected
  {
  }
  "companyName"?: string // Applicant-reported company name collected at organization creation for approval review. (非必填)
  "taxId"?: // 可能有不同的類型 (非必填)
  string // Applicant-reported business tax ID (8 digits, optional). Stored as-is; not verified. (非必填)
  "contactPhone"?: string // Applicant-reported contact phone collected at organization creation for approval review. (非必填)
  "applicationMetadata"?: object // Extra applicant-reported key-value fields collected at organization creation. Lets the frontend collect additional review fields without a schema migration; the core review fields (company name, tax ID, contact phone) stay as named columns. (非必填)
  "invitationCode"?: string // 非必填
  "ipAllowlistEnabled": boolean // Restrict this organization to the source IPs listed in allowed_ip_cidrs. Layered under the global Config.ip_allowlist_enforcement_enabled switch: both must be enabled. Disabled by default so existing organizations keep unrestricted access.
  "allowedIpCidrs": string // Source IPs or CIDRs allowed to reach this organization, one per line (e.g. 203.0.113.0/24); commas also work. While the IP allowlist is enabled, an empty list rejects everything. A non-empty list whose entries are all invalid rejects everything rather than silently reverting to unrestricted, so a typo cannot quietly disable the protection. Matching uses the load-balancer-appended client IP.
  "enforceIpAllowlistOnAdminUi": boolean // Apply the allowlist to browser sessions: the admin console and its WebSocket connections. Only takes effect while ip_allowlist_enabled is on.
  "enforceIpAllowlistOnApiKey": boolean // Apply the allowlist to Open API (Api-Key) and AI Gateway (Bearer) requests. Only takes effect while ip_allowlist_enabled is on.
}
```

回應範例值

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "name": "回應字串",
  "createdAt": "回應字串",
```

```
  "compactLogo": "https://example.com/file.jpg",
  "fullLogo": "https://example.com/file.jpg",
  "themePrimaryColor": "回應字串",
  "usageStatistics": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應範例名稱",
    "description": "回應範例描述"
  },
  "organizationPlan": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應範例名稱",
    "description": "回應範例描述"
  },
  "creditWallet": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應範例名稱",
    "description": "回應範例描述"
  },
  "maigptInboxId": "550e8400-e29b-41d4-a716-446655440000",
  "canUseCustomElasticsearch": false,
  "canUseVoiceAgent": false,
  "canUseMeetingRecords": false,
  "canUseCallCenter": false,
  "canUseHookSystem": false,
  "canUseAiGateway": false,
  "canUseAgentTeams": false,
  "canUseFileLibrary": false,
  "canUseFileOnlineEditing": false,
  "canUseOfficeOnlineEditing": false,
  "canUseRolePermissionGovernance": false,
  "enableAgentMemory": false,
  "hideChinaModels": false,
  "autoActivateNewChatbotChannels": false,
  "gatewayServiceFeePercent": "回應字串",
  "gatewayTrafficFeePercent": "回應字串",
  "platformProcessingFeePercent": "回應字串",
  "platformProcessingFeeEnabled": false,
  "isTrial": false,
  "expirationDays": 456,
  "showTrialBanner": false,
  "agentScheduleMinIntervalSeconds": 456,
  "noActivePlanDays": 456,
  "cleanupRemainingDays": 456,
  "estimatedCleanupDate": "回應字串",
  "approvalStatus": {},
```

```
  "companyName": "回應字串",
  "taxId": "回應字串",
  "contactPhone": "回應字串",
  "applicationMetadata": null,
  "invitationCode": "回應字串",
  "ipAllowlistEnabled": false,
  "allowedIpCidrs": "回應字串",
  "enforceIpAllowlistOnAdminUi": false,
  "enforceIpAllowlistOnApiKey": false
}
```


取得當前用戶詳細資訊

GET `/api/v1/users/current/`

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/users/current/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/users/current/", config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/users/current/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/users/current/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
{
  "id": string (uuid)
  "avatar"?: string (uri) // 非必填
  "originalAvatar"?: string (uri) // 使用者上傳的頭貼原圖（長邊已限制在 2048px
```

內)，每次編輯都從這張重裁，避免在裁切結果上再裁而累積失真。本功能上線前的舊資料為空，不回填 (非必填)
  "avatarCropBox"?: object // 上次裁切框在原圖上的位置與大小（x/y/width/height，選填 rotate/scale_x/scale_y)，座標基準為被保存的原圖 (非必填)
  "name": string
  "email": string (email)
  "authSource":
  {
    "id": string (uuid)
    "name": string
  }
  "company"?: string // 非必填
  "invitationCode"?: // 可能有不同的類型 (非必填)
  string // 非必填
  "apiKeys": [// 取得使用者在指定組織中的 API 金鑰列表。

流程：
1. 從 request 中取得當前組織實例
2. 如果沒有組織實例（通常發生在第三方 SSO 登入時)，則透過使用者的認證來源
   查找該認證來源的預設組織（is_auth_source_default_organization=True)

注意：

  第三方 SSO 登入時 request 不會包含 organization_instance
  需要透過 auth_source 和 is_auth_source_default_organization 標記來定位組織

    object
  ]
  "permissions": object // 取得使用者在當前組織中的權限（巢狀父子結構)。
  "resourcePermissions": object // 取得使用者在當前組織中的資源建立權限。
  "isOwner": boolean // 判斷使用者在當前組織中是否為 Owner。
  "maigptCapabilities": object // 成員在 MaiGPT 的有效內建功能能力（角色權限解析結果)，供前端 show/hide。

無 member context（未綁組織）時解析結果為全開，與 resolver「缺資料不鎖死」一致；前端隱藏僅為體驗層，權威把關在回覆路徑的 gate。
}

回應範例值


```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
```

```
  "avatar": "https://example.com/file.jpg",
  "originalAvatar": "https://example.com/file.jpg",
  "avatarCropBox": null,
  "name": "回應字串",
  "email": "response@example.com",
  "authSource": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應字串"
  },
  "company": "回應字串",
  "invitationCode": "回應字串",
  "apiKeys": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "回應範例名稱",
      "description": "回應範例描述"
    }
  ],
  "permissions": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應範例名稱",
    "description": "回應範例描述"
  },
  "resourcePermissions": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應範例名稱",
    "description": "回應範例描述"
  },
  "isOwner": false,
  "maigptCapabilities": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應範例名稱",
    "description": "回應範例描述"
  }
}
```


取得當前用戶權限

GET `/api/v1/permissions/`

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/permissions/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/permissions/", config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/permissions/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/permissions/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
[
  {
    "id": string (uuid)
    "name": string
```

```
    "value": string
    "description": string
    "children": [
      object
    ]
  }
]
```

回應範例值

```
[
  {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應字串",
    "value": "回應字串",
    "description": "回應字串",
    "children": [
      {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "name": "回應範例名稱",
        "description": "回應範例描述"
      }
    ]
  }
]
```

取得指定組織的成員列表

GET `/api/v1/organizations/{organizationPk}/members/`

參數

參數名稱	必填	類型	說明

`organizationPk`	V	string	A UUID string identifying this 組織 ID
`group`	X	string	
`ids`	X	string	
`inbox`	X	string	
`isActive`	X	boolean	
`page`	X	integer	A page number within the paginated result set.
`pageSize`	X	integer	Number of results to return per page.
`pagination`	X	string	是否分頁 (true/false)
`query`	X	string	
`search`	X	string	
`withGroupSources`	X	boolean	為 true 時，`groups` 每個角色只列一次並多回 `sources`（這個角色被指派的方式：manual／ldap／scim／eip／cloudflare_access，去重排序；預設角色是空陣列）。只有分頁的列表支援。

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/organizations/550e8400-
e29b-41d4-a716-446655440000/members/?group=550e8400-e29b-41d4-a716-
446655440000&ids=example&inbox=550e8400-e29b-41d4-a716-
446655440000&isActive=true&page=1&pageSize=1&pagination=example&quer
y=example&search=example&withGroupSources=true"

  -H "Authorization: Api-Key YOUR_API_KEY"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/organizations/550e8400-
e29b-41d4-a716-446655440000/members/?group=550e8400-e29b-41d4-a716-
446655440000&ids=example&inbox=550e8400-e29b-41d4-a716-
446655440000&isActive=true&page=1&pageSize=1&pagination=example&quer
y=example&search=example&withGroupSources=true", config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-41d4-a716-446655440000/members/?group=550e8400-e29b-41d4-a716-446655440000&ids=example&inbox=550e8400-e29b-41d4-a716-446655440000&isActive=true&page=1&pageSize=1&pagination=example&query=example&search=example&withGroupSources=true"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-
41d4-a716-446655440000/members/?group=550e8400-e29b-41d4-a716-
446655440000&ids=example&inbox=550e8400-e29b-41d4-a716-
446655440000&isActive=true&page=1&pageSize=1&pagination=example&quer
y=example&search=example&withGroupSources=true", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
{
  "count": integer
  "next"?: string (uri) // 非必填
  "previous"?: string (uri) // 非必填
  "results": [
    {
      "id": string (uuid)
      "name": string
      "email": string
      "isActive": boolean
      "isOwner": boolean // 檢查成員是否為組織擁有者（透過 OWNER Group）

使用快取避免同一 request 內的重複查詢
快取生命週期：在 member instance 存在期間有效

優先使用 annotation 的結果（如果有的話）避免重複查詢
      "permissions": [ // Compute the permission tree once per
(organization, custom-group set) per request.

The tree depends only on the member's organization (default groups,
feature
flags, plan whitelist), the member's custom groups, and the global
``Config``,
so members sharing a group set get the same result. A large role's
``pagination=false`` listing otherwise recomputes it per row — one Redis
``Config`` fetch plus the permission walk each time (issue #8436; the
largest
prod role has 3,837 members and a single group set). The memo lives in
the
serializer context, so it never outlives the request. Rows without the
eager
loaded ``_custom_groups_cache`` (single-object paths) keep computing
directly.
        object
      ]
      "groups": [
        object
      ]
      "creditQuotaRequired"?: boolean // When True, member must have an
active quota to consume credits (非必填)
      "activeQuota": object // Return the most recent quota summary
(active first), via prefetch to avoid N+1.
      "metadata": object // Organization-scoped member attributes,
injected into LLM system prompt
```

```
      "availabilityStatus":  // Self-declared availability for auto-
assignment. Paused members are skipped by the dispatch engine but can
still be manually assigned or claim conversations. Not touched by SCIM
provisioning.

* `available` - Available
* `paused` - Paused
      {
      }
      "createdAt": string (timestamp)
    }
  ]
}
```

回應範例值

```
{
  "count": 123,
  "next": "http://api.example.org/accounts/?page=4",
  "previous": "http://api.example.org/accounts/?page=2",
  "results": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "回應字串",
      "email": "回應字串",
      "isActive": false,
      "isOwner": false,
      "permissions": [
        {
          "id": "550e8400-e29b-41d4-a716-446655440000",
          "name": "回應範例名稱",
          "description": "回應範例描述"
        }
      ],
      "groups": [
        {
          "id": "550e8400-e29b-41d4-a716-446655440000",
          "name": "回應範例名稱",
          "description": "回應範例描述"
        }
      ],
      "creditQuotaRequired": false,
      "activeQuota": {
        "id": "550e8400-e29b-41d4-a716-446655440000",
```

```
        "name": "回應範例名稱",
        "description": "回應範例描述"
      },
      "metadata": null,
      "availabilityStatus": {},
      "createdAt": "回應字串"
    }
  ]
}
```


取得特定成員詳細資訊

GET `/api/v1/organizations/{organizationPk}/members/{id}`

參數

參數名稱	必填	類型	說明
`id`	V	string	A UUID string identifying this 成員.
`organizationPk`	V	string	A UUID string identifying this 組織 ID

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-41d4-a716-446655440000/members/550e8400-e29b-41d4-a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/organizations/550e8400-
e29b-41d4-a716-446655440000/members/550e8400-e29b-41d4-a716-
446655440000/", config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-
41d4-a716-446655440000/members/550e8400-e29b-41d4-a716-
446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-
41d4-a716-446655440000/members/550e8400-e29b-41d4-a716-
446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
{
  "id": string (uuid)
```

```
  "name": string
  "email": string
  "isActive": boolean
  "isOwner": boolean // 檢查成員是否為組織擁有者（透過 OWNER Group）

使用快取避免同一 request 內的重複查詢
快取生命週期：在 member instance 存在期間有效

優先使用 annotation 的結果（如果有的話）避免重複查詢
  "permissions": [ // Compute the permission tree once per (organization,
custom-group set) per request.

The tree depends only on the member's organization (default groups,
feature
flags, plan whitelist), the member's custom groups, and the global
``Config``,
so members sharing a group set get the same result. A large role's
``pagination=false`` listing otherwise recomputes it per row — one Redis
``Config`` fetch plus the permission walk each time (issue #8436; the
largest
prod role has 3,837 members and a single group set). The memo lives in
the
serializer context, so it never outlives the request. Rows without the
eager
loaded ``_custom_groups_cache`` (single-object paths) keep computing
directly.
    object
  ]
  "groups": [
    object
  ]
  "creditQuotaRequired"?: boolean // When True, member must have an
active quota to consume credits (非必填)
  "activeQuota": object // Return the most recent quota summary (active
first), via prefetch to avoid N+1.
  "metadata": object // Organization-scoped member attributes, injected
into LLM system prompt
  "availabilityStatus":  // Self-declared availability for auto-
assignment. Paused members are skipped by the dispatch engine but can
still be manually assigned or claim conversations. Not touched by SCIM
provisioning.

* `available` - Available
* `paused` - Paused
  {
```

```
  }
  "createdAt": string (timestamp)
}
```

回應範例值

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "name": "回應字串",
  "email": "回應字串",
  "isActive": false,
  "isOwner": false,
  "permissions": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "回應範例名稱",
      "description": "回應範例描述"
    }
  ],
  "groups": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "回應範例名稱",
      "description": "回應範例描述"
    }
  ],
  "creditQuotaRequired": false,
  "activeQuota": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應範例名稱",
    "description": "回應範例描述"
  },
  "metadata": null,
  "availabilityStatus": {},
  "createdAt": "回應字串"
}
```

更新組織資訊

PUT `/api/v1/organizations/{id}`

參數

參數名稱	必填	類型	說明
`id`	V	string	A UUID string identifying this 組織.

請求內容

請求參數

欄位	類型	必填	說明
name	string	是	
compactLogo	string (uri)	否	
fullLogo	string (uri)	否	
themePrimaryColor	object	否	UI 主題色，用於按鈕、連結等元素的顏色（HEX 格式，如 #0960bd）；留空表示未設定，前端退階使用系統品牌主色
hideChinaModels	boolean	否	When on, platform models whose developer is based in China (including ones added later) are not visible or usable in this organization: model menus, assistants, the API and AI Gateway all exclude them...
autoActivateNewChatbotChannels	boolean	否	Initial state of the web chat and API channels of a new chatbot whose creator did not set them

欄位	類型	必填	說明
			(duplicates, templates and API calls without the values included). When on, they start active; when off (...
companyName	string	否	Applicant-reported company name collected at organization creation for approval review.
taxId	object	否	Applicant-reported business tax ID (8 digits, optional). Stored as-is; not verified.
contactPhone	string	否	Applicant-reported contact phone collected at organization creation for approval review.
applicationMetadata	object	否	Extra applicant-reported key-value fields collected at organization creation. Lets the frontend collect additional review fields without a schema migration; the core review fields (company name, tax I...
invitationCode	string	否	

請求結構範例

```
{
  "name": string
  "compactLogo"?: string (uri) // 非必填
  "fullLogo"?: string (uri) // 非必填
  "themePrimaryColor"?: // 可能有不同的類型 (非必填)
  string // UI 主題色，用於按鈕、連結等元素的顏色（HEX 格式，如 #0960bd）；留空表示未設定，前端退階使用系統品牌主色 (非必填)
  "hideChinaModels"?: boolean // When on, platform models whose developer is based in China (including ones added later) are not visible or usable in this organization: model menus, assistants, the API and AI Gateway all exclude them. (非必填)
  "autoActivateNewChatbotChannels"?: boolean // Initial state of the web chat and API channels of a new chatbot whose creator did not set them (duplicates, templates and API calls without the values included). When
```

```
on, they start active; when off (the platform default), they start
inactive until a member turns them on. The creator can still override
both channels in the New Chatbot dialog or the create API. The backstage
(admin) channel is always active. Changing this does not affect existing
chatbots. (非必填)
  "companyName"?: string // Applicant-reported company name collected at
organization creation for approval review. (非必填)
  "taxId"?: // 可能有不同的類型 (非必填)
  string // Applicant-reported business tax ID (8 digits, optional).
Stored as-is; not verified. (非必填)
  "contactPhone"?: string // Applicant-reported contact phone collected
at organization creation for approval review. (非必填)
  "applicationMetadata"?: object // Extra applicant-reported key-value
fields collected at organization creation. Lets the frontend collect
additional review fields without a schema migration; the core review
fields (company name, tax ID, contact phone) stay as named columns. (非必
填)
  "invitationCode"?: string // 非必填
}
```

請求範例值


```
{
  "id": "5b01e0b9-0b0e-4079-8150-d12015576d2c",
  "name": "Updated Org Name",
  "created_at": "1748336288000",
  "usage_statistics": {
    "chatbots_count": 0,
    "countable_chatbots_count": 0,
    "exempt_chatbots_by_mode": {},
    "allowed_chatbot_reply_modes": [],
    "can_create_chatbot": true,
    "create_chatbot_limit": 1,
    "current_month_words_count_total": 1000000,
    "current_month_used_words_count_total": 0,
    "current_month_used_conversations_count_total": 0,
    "available_upload_files_size_total": 104857600,
    "used_upload_file_size_total": 0
  },
  "organization_plan": {
    "id": "cac825e8-cb9b-4a16-b440-4ff6b2e73911",
    "plan_name": "免費方案",
    "expired_at": null
  },
```

```
  "is_trial": false,
  "expiration_days": null
}
```

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X PUT "https://api.maiagent.ai/api/v1/organizations/550e8400-
e29b-41d4-a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "id": "5b01e0b9-0b0e-4079-8150-d12015576d2c",
    "name": "Updated Org Name",
    "created_at": "1748336288000",
    "usage_statistics": {
      "chatbots_count": 0,
      "countable_chatbots_count": 0,
      "exempt_chatbots_by_mode": {},
      "allowed_chatbot_reply_modes": [],
      "can_create_chatbot": true,
      "create_chatbot_limit": 1,
      "current_month_words_count_total": 1000000,
      "current_month_used_words_count_total": 0,
      "current_month_used_conversations_count_total": 0,
      "available_upload_files_size_total": 104857600,
      "used_upload_file_size_total": 0
    },
    "organization_plan": {
      "id": "cac825e8-cb9b-4a16-b440-4ff6b2e73911",
      "plan_name": "免費方案",
      "expired_at": null
    },
    "is_trial": false,
    "expiration_days": null
  }'

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// 請求內容 (payload)
const data = {
    "id": "5b01e0b9-0b0e-4079-8150-d12015576d2c",
    "name": "Updated Org Name",
    "created_at": "1748336288000",
    "usage_statistics": {
      "chatbots_count": 0,
      "countable_chatbots_count": 0,
      "exempt_chatbots_by_mode": {},
      "allowed_chatbot_reply_modes": [],
      "can_create_chatbot": true,
      "create_chatbot_limit": 1,
      "current_month_words_count_total": 1000000,
      "current_month_used_words_count_total": 0,
      "current_month_used_conversations_count_total": 0,
      "available_upload_files_size_total": 104857600,
      "used_upload_file_size_total": 0
    },
    "organization_plan": {
      "id": "cac825e8-cb9b-4a16-b440-4ff6b2e73911",
      "plan_name": "免費方案",
      "expired_at": null
    },
    "is_trial": false,
    "expiration_days": null
  };

axios.put("https://api.maiagent.ai/api/v1/organizations/550e8400-
e29b-41d4-a716-446655440000/", data, config)
  .then(response => {
```

```
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.log('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-
41d4-a716-446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# 請求內容 (payload)
data = {
    "id": "5b01e0b9-0b0e-4079-8150-d12015576d2c",
    "name": "Updated Org Name",
    "created_at": "1748336288000",
    "usage_statistics": {
        "chatbots_count": 0,
        "countable_chatbots_count": 0,
        "exempt_chatbots_by_mode": {},
        "allowed_chatbot_reply_modes": [],
        "can_create_chatbot": True,
        "create_chatbot_limit": 1,
        "current_month_words_count_total": 1000000,
        "current_month_used_words_count_total": 0,
        "current_month_used_conversations_count_total": 0,
        "available_upload_files_size_total": 104857600,
        "used_upload_file_size_total": 0
    },
    "organization_plan": {
        "id": "cac825e8-cb9b-4a16-b440-4ff6b2e73911",
        "plan_name": "免費方案",
        "expired_at": None
    },
    "is_trial": False,
    "expiration_days": None
}

response = requests.put(url, json=data, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
```

```
    except Exception as e:
        print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>put("https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-
41d4-a716-446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'id' => '5b01e0b9-0b0e-4079-8150-d12015576d2c',
            'name' => 'Updated Org Name',
            'created_at' => '1748336288000',
            'usage_statistics' => [
                'chatbots_count' => 0,
                'countable_chatbots_count' => 0,
                'exempt_chatbots_by_mode' => new \stdClass(),
                'allowed_chatbot_reply_modes' => [],
                'can_create_chatbot' => true,
                'create_chatbot_limit' => 1,
                'current_month_words_count_total' => 1000000,
                'current_month_used_words_count_total' => 0,
                'current_month_used_conversations_count_total' => 0,
                'available_upload_files_size_total' => 104857600,
                'used_upload_file_size_total' => 0
            ],
            'organization_plan' => [
                'id' => 'cac825e8-cb9b-4a16-b440-4ff6b2e73911',
                'plan_name' => '免費方案',
                'expired_at' => null
            ],
            'is_trial' => false,
            'expiration_days' => null
        ]
    ]);
```

```
    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
{
  "id": string (uuid) // 組織 ID
  "name": string // 組織名稱
  "created_at": string (timestamp) // 建立時間戳記
  "usage_statistics": { // 使用統計資訊
  {
    "chatbots_count"?: integer // 聊天機器人數量 (非必填)
    "countable_chatbots_count"?: integer // 佔用建立額度的聊天機器人數量（模式不在方案白名單內的不計入） (非必填)
    "exempt_chatbots_by_mode"?: object // 不佔額度的聊天機器人數量，依使其不計入的模式分組 (非必填)
    "allowed_chatbot_reply_modes"?: [ // 方案允許建立的回覆模式白名單（空陣列表示不限制） (非必填)
      string
    ]
    "can_create_chatbot"?: boolean // 是否可以建立聊天機器人 (非必填)
    "create_chatbot_limit"?: integer // 可建立的聊天機器人數量上限（-1 表示無上限、0 表示禁止建立） (非必填)
    "current_month_words_count_total"?: integer // 本月總字數限制 (非必填)
    "current_month_used_words_count_total"?: integer // 本月已使用字數 (非必填)
    "current_month_used_conversations_count_total"?: integer // 本月已使用對話數 (非必填)
```

```
    "available_upload_files_size_total"?: integer // 可上傳檔案總大小（位元組）（非必填）
    "used_upload_file_size_total"?: integer // 已使用上傳檔案大小（位元組）（非必填）
  }
  }
  "organization_plan": { // 組織方案資訊
  {
    "id"?: string (uuid) // 方案 ID（非必填）
    "plan_name"?: string // 方案名稱（非必填）
    "expired_at"?: string (date-time) // 到期時間（非必填）
  }
  }
  "is_trial"?: boolean // 是否為試用期。判定邏輯：組織只有一個試用方案且目前有效（非必填）
  "expiration_days"?: integer // 已過期天數。正數=已過期天數，null=尚未到期或永久方案（非必填）
}
```

回應範例值

```
{
  "id": "5b01e0b9-0b0e-4079-8150-d12015576d2c",
  "name": "Updated Org Name",
  "created_at": "1748336288000",
  "usage_statistics": {
    "chatbots_count": 0,
    "countable_chatbots_count": 0,
    "exempt_chatbots_by_mode": {},
    "allowed_chatbot_reply_modes": [],
    "can_create_chatbot": true,
    "create_chatbot_limit": 1,
    "current_month_words_count_total": 1000000,
    "current_month_used_words_count_total": 0,
    "current_month_used_conversations_count_total": 0,
    "available_upload_files_size_total": 104857600,
    "used_upload_file_size_total": 0
  },
  "organization_plan": {
    "id": "cac825e8-cb9b-4a16-b440-4ff6b2e73911",
    "plan_name": "免費方案",
    "expired_at": null
  },
  "is_trial": false,
```

```
  "expiration_days": null
}
```

更新當前用戶詳細資訊

PUT `/api/v1/users/current/`

請求內容

請求參數

欄位	類型	必填	說明
avatar	string (uri)	否	
originalAvatar	string (uri)	否	使用者上傳的頭貼原圖（長邊已限制在 2048px 內），每次編輯都從這張重裁，避免在裁切結果上再裁而累積失真。本功能上線前的舊資料為空，不回填
avatarCropBox	object	否	上次裁切框在原圖上的位置與大小（x/y/width/height，選填 rotate/scale_x/scale_y），座標基準為被保存的原圖
name	string	是	
email	string (email)	是	
company	string	否	
invitationCode	object	否	

請求結構範例

```
{
  "avatar"?: string (uri) // 非必填
  "originalAvatar"?: string (uri) // 使用者上傳的頭貼原圖（長邊已限制在 2048px 內），每次編輯都從這張重裁，避免在裁切結果上再裁而累積失真。本功能上線前的舊資料為空，不回填 (非必填)
  "avatarCropBox"?: object // 上次裁切框在原圖上的位置與大小（x/y/width/height，選填 rotate/scale_x/scale_y），座標基準為被保存的原圖 (非必填)
  "name": string
  "email": string (email)
  "company"?: string // 非必填
  "invitationCode"?: // 可能有不同的類型 (非必填)
  string // 非必填
}
```

請求範例值

```
{
  "avatar": "https://example.com/file.jpg",
  "originalAvatar": "https://example.com/file.jpg",
  "avatarCropBox": null,
  "name": "範例名稱",
  "email": "user@example.com",
  "company": "範例字串",
  "invitationCode": null
}
```

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X PUT "https://api.maiagent.ai/api/v1/users/current/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');
const FormData = require('form-data');

// 建立FormData對象
const formData = new FormData();
// 添加表單欄位

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    ...formData.getHeaders()
  }
};

axios.put("https://api.maiagent.ai/api/v1/users/current/", formData,
config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/users/current/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}

# 建立檔案和表單資料
files = {
    'file': ('example.pdf', open('example.pdf', 'rb'),
'application/pdf')
}

response = requests.put(url, files=files, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>put("https://api.maiagent.ai/api/v1/users/current/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ],
        'multipart' => [
            [
                'name' => 'file',
                'contents' => fopen('example.pdf', 'r'),
                'filename' => 'example.pdf'
            ]
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
{
  "id": string (uuid)
  "avatar"?: string (uri) // 非必填
  "originalAvatar"?: string (uri) // 使用者上傳的頭貼原圖（長邊已限制在 2048px 內），每次編輯都從這張重裁，避免在裁切結果上再裁而累積失真。本功能上線前的舊資料為空，不回填 (非必填)
  "avatarCropBox"?: object // 上次裁切框在原圖上的位置與大小（x/y/width/height，選填 rotate/scale_x/scale_y），座標基準為被保存的原圖 (非必填)
  "name": string
  "email": string (email)
  "authSource":
  {
    "id": string (uuid)
    "name": string
  }
  "company"?: string // 非必填
  "invitationCode"?: // 可能有不同的類型 (非必填)
  string // 非必填
  "apiKeys": [ // 取得使用者在指定組織中的 API 金鑰列表。

流程：
1. 從 request 中取得當前組織實例
2. 如果沒有組織實例（通常發生在第三方 SSO 登入時），則透過使用者的認證來源
   查找該認證來源的預設組織（is_auth_source_default_organization=True）

注意：
<ul>
  <li>第三方 SSO 登入時 request 不會包含 organization_instance</li>
  <li>需要透過 auth_source 和 is_auth_source_default_organization 標記來定位組織</li>
</ul>
    object
  ]
  "permissions": object // 取得使用者在當前組織中的權限（巢狀父子結構）。
  "resourcePermissions": object // 取得使用者在當前組織中的資源建立權限。
  "isOwner": boolean // 判斷使用者在當前組織中是否為 Owner。
  "maigptCapabilities": object // 成員在 MaiGPT 的有效內建功能能力（角色權限解析結果），供前端 show/hide。

無 member context（未綁組織）時解析結果為全開，與 resolver「缺資料不鎖死」
```

```
一致；前端隱藏僅為體驗層，權威把關在回覆路徑的 gate。
}
```

回應範例值

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "avatar": "https://example.com/file.jpg",
  "originalAvatar": "https://example.com/file.jpg",
  "avatarCropBox": null,
  "name": "回應字串",
  "email": "response@example.com",
  "authSource": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應字串"
  },
  "company": "回應字串",
  "invitationCode": "回應字串",
  "apiKeys": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "回應範例名稱",
      "description": "回應範例描述"
    }
  ],
  "permissions": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應範例名稱",
    "description": "回應範例描述"
  },
  "resourcePermissions": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應範例名稱",
    "description": "回應範例描述"
  },
  "isOwner": false,
  "maigptCapabilities": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應範例名稱",
    "description": "回應範例描述"
```

```
  }
}
```

更新成員所屬角色

POST `/api/v1/organizations/{organizationPk}/members/{id}/update-groups/`

參數

參數名稱	必填	類型	說明
`id`	V	string	A UUID string identifying this 成員.
`organizationPk`	V	string	A UUID string identifying this 組織 ID

請求內容

請求參數

欄位	類型	必填	說明
groups	array[string]	是	

請求結構範例

```
{
  "groups": [
    string (uuid)
  ]
}
```

請求範例值

```
{
  "groups": [
    "4e368ab4-c543-48a2-bbb8-f6f5a0bf6c61",
    "5f479bc5-d654-59b3-ccc9-g7g6b1cg7d72"
  ]
}
```

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X POST "https://api.maiagent.ai/api/v1/organizations/550e8400-
e29b-41d4-a716-446655440000/members/550e8400-e29b-41d4-a716-
446655440000/update-groups/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "groups": [
      "4e368ab4-c543-48a2-bbb8-f6f5a0bf6c61",
      "5f479bc5-d654-59b3-ccc9-g7g6b1cg7d72"
    ]
  }'

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// 請求內容 (payload)
const data = {
    "groups": [
      "4e368ab4-c543-48a2-bbb8-f6f5a0bf6c61",
      "5f479bc5-d654-59b3-ccc9-g7g6b1cg7d72"
    ]
  };

axios.post("https://api.maiagent.ai/api/v1/organizations/550e8400-
e29b-41d4-a716-446655440000/members/550e8400-e29b-41d4-a716-
446655440000/update-groups/", data, config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-
41d4-a716-446655440000/members/550e8400-e29b-41d4-a716-
446655440000/update-groups/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# 請求內容 (payload)
data = {
    "groups": [
        "4e368ab4-c543-48a2-bbb8-f6f5a0bf6c61",
        "5f479bc5-d654-59b3-ccc9-g7g6b1cg7d72"
    ]
}

response = requests.post(url, json=data, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>post("https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-
41d4-a716-446655440000/members/550e8400-e29b-41d4-a716-
446655440000/update-groups/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'groups' => [
                '4e368ab4-c543-48a2-bbb8-f6f5a0bf6c61',
                '5f479bc5-d654-59b3-ccc9-g7g6b1cg7d72'
            ]
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
{
  "id": string (uuid)
  "name": string
  "email": string
  "isActive": boolean
  "isOwner": boolean // 檢查成員是否為組織擁有者（透過 OWNER Group）

使用快取避免同一 request 內的重複查詢
快取生命週期：在 member instance 存在期間有效

優先使用 annotation 的結果（如果有的話）避免重複查詢
  "permissions": [ // Compute the permission tree once per (organization,
custom-group set) per request.

The tree depends only on the member's organization (default groups,
feature
flags, plan whitelist), the member's custom groups, and the global
``Config``,
so members sharing a group set get the same result. A large role's
``pagination=false`` listing otherwise recomputes it per row — one Redis
``Config`` fetch plus the permission walk each time (issue #8436; the
largest
prod role has 3,837 members and a single group set). The memo lives in
the
serializer context, so it never outlives the request. Rows without the
eager
loaded ``_custom_groups_cache`` (single-object paths) keep computing
directly.
    object
  ]
  "groups": [
    object
  ]
  "creditQuotaRequired"?: boolean // When True, member must have an
active quota to consume credits (非必填)
  "activeQuota": object // Return the most recent quota summary (active
first), via prefetch to avoid N+1.
  "metadata": object // Organization-scoped member attributes, injected
into LLM system prompt
  "availabilityStatus":  // Self-declared availability for auto-
assignment. Paused members are skipped by the dispatch engine but can
```

```
still be manually assigned or claim conversations. Not touched by SCIM
provisioning.

* `available` - Available
* `paused` - Paused
  {
  }
  "createdAt": string (timestamp)
}
```

回應範例值

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "name": "回應字串",
  "email": "回應字串",
  "isActive": false,
  "isOwner": false,
  "permissions": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "回應範例名稱",
      "description": "回應範例描述"
    }
  ],
  "groups": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "回應範例名稱",
      "description": "回應範例描述"
    }
  ],
  "creditQuotaRequired": false,
  "activeQuota": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應範例名稱",
    "description": "回應範例描述"
  },
  "metadata": null,
  "availabilityStatus": {},
  "createdAt": "回應字串"
}
```

狀態碼: 400

回應結構範例

```
object
```

列出組織的 API Key

`GET` `/api/v1/organizations/{organizationPk}/api-keys/`

管理者視角的 API Key 管理，需要「API Key 管理權限」。成員可同時持有多把有效金鑰，可先簽新、部署後再撤舊。取得方式見 API 認證方式。

參數

參數名稱	必填	類型	說明
`organizationPk`	V	string	A UUID string identifying this 組織 ID
`page`	X	integer	A page number within the paginated result set.
`pageSize`	X	integer	Number of results to return per page.
`query`	X	string	
`source`	X	string	
`status`	X	string	

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/organizations/550e8400-
e29b-41d4-a716-446655440000/api-keys/?
page=1&pageSize=1&query=example&source=example&status=example"

  -H "Authorization: Api-Key YOUR_API_KEY"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/organizations/550e8400-
e29b-41d4-a716-446655440000/api-keys/?
page=1&pageSize=1&query=example&source=example&status=example",
config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-
41d4-a716-446655440000/api-keys/?
page=1&pageSize=1&query=example&source=example&status=example"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-
41d4-a716-446655440000/api-keys/?
page=1&pageSize=1&query=example&source=example&status=example", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
{
  "count": integer
```

```
  "next"?: string (uri) // 非必填
  "previous"?: string (uri) // 非必填
  "results": [
    {
      "id": string
      "name"?: string // A free-form name for the API key. Need not be
unique. 50 characters max. (非必填)
      "prefix": string
      "status": string
      "source": string
      "isActive"?: boolean // Reversible enable switch. A disabled key is
rejected exactly like an unknown key (generic 401, no information leak),
but keeps its secret and usage history and can be re-enabled at any time
— unlike the irreversible revoked flag. (非必填)
      "rateLimitRpm"?: integer // Max requests per minute across every
platform API this key can call. Null = unlimited. (非必填)
      "rateLimitTpm"?: integer // Max LLM tokens per minute through the
AI Gateway inference endpoints. Null = unlimited. (非必填)
      "gatewayAllowedLlmCount": integer // Size of the gateway allow-
list, when the queryset annotated it.

0 means "no restriction" (see ``api_key_allowed_llm_ids``). ``None``
on surfaces that did not annotate (login payload, PAT list) so a
missing count is never mistaken for "unrestricted".
      "expiryDate"?: string (timestamp) // Once API key expires, clients
cannot use it anymore. (非必填)
      "createdAt": string (timestamp)
      "lastUsedAt"?: string (timestamp) // 非必填
      "member": object
      "createdByName": string
      "revokedAt"?: string (timestamp) // 非必填
      "revokedByName": string
    }
  ]
}
```

回應範例值

```
{
  "count": 123,
  "next": "http://api.example.org/accounts/?page=4",
  "previous": "http://api.example.org/accounts/?page=2",
  "results": [
    {
```

```
      "id": "回應字串",
      "name": "回應字串",
      "prefix": "回應字串",
      "status": "回應字串",
      "source": "回應字串",
      "isActive": false,
      "rateLimitRpm": 456,
      "rateLimitTpm": 456,
      "gatewayAllowedLlmCount": 456,
      "expiryDate": "回應字串",
      "createdAt": "回應字串",
      "lastUsedAt": "回應字串",
      "member": {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "name": "回應範例名稱",
        "description": "回應範例描述"
      },
      "createdByName": "回應字串",
      "revokedAt": "回應字串",
      "revokedByName": "回應字串"
    }
  ]
}
```


狀態碼: 403 - 權限不足

替成員簽發 API Key

POST `/api/v1/organizations/{organizationPk}/api-keys/`

參數

參數名稱	必填	類型	說明
`organizationPk`	V	string	A UUID string identifying this 組織 ID

請求內容

請求參數

欄位	類型	必填	說明
name	string	是	
expiryDate	string (timestamp)	否	
memberId	string (uuid)	是	
isActive	boolean	否	

請求結構範例

```
{
  "name": string
  "expiryDate"?: string (timestamp) // 非必填
  "memberId": string (uuid)
  "isActive"?: boolean // 非必填
}
```

請求範例值

```
{
  "name": "My API Key",
  "member_id": "00000000-0000-0000-0000-000000000000",
  "expiry_date": "2027-12-31T23:59:59Z"
}
```

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X POST "https://api.maiagent.ai/api/v1/organizations/550e8400-
e29b-41d4-a716-446655440000/api-keys/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "name": "My API Key",
    "member_id": "00000000-0000-0000-0000-000000000000",
    "expiry_date": "2027-12-31T23:59:59Z"
  }'

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// 請求內容 (payload)
const data = {
    "name": "My API Key",
    "member_id": "00000000-0000-0000-0000-000000000000",
    "expiry_date": "2027-12-31T23:59:59Z"
  };

axios.post("https://api.maiagent.ai/api/v1/organizations/550e8400-
e29b-41d4-a716-446655440000/api-keys/", data, config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-
41d4-a716-446655440000/api-keys/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# 請求內容 (payload)
data = {
    "name": "My API Key",
    "member_id": "00000000-0000-0000-0000-000000000000",
    "expiry_date": "2027-12-31T23:59:59Z"
}

response = requests.post(url, json=data, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>post("https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-
41d4-a716-446655440000/api-keys/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'name' => 'My API Key',
            'member_id' => '00000000-0000-0000-0000-000000000000',
            'expiry_date' => '2027-12-31T23:59:59Z'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 201

回應結構範例

```
{
  "id": string
  "name"?: string // A free-form name for the API key. Need not be
unique. 50 characters max. (非必填)
  "prefix": string
  "key": string // The full API key. Shown only in this response and
never stored, so it
cannot be retrieved again.
  "status": string
  "source": string
  "isActive"?: boolean // Reversible enable switch. A disabled key is
rejected exactly like an unknown key (generic 401, no information leak),
but keeps its secret and usage history and can be re-enabled at any time
— unlike the irreversible revoked flag. (非必填)
  "expiryDate"?: string (timestamp) // Once API key expires, clients
cannot use it anymore. (非必填)
  "createdAt": string (timestamp)
}
```

回應範例值

```
{
  "id": "回應字串",
  "name": "回應字串",
  "prefix": "回應字串",
  "key": "回應字串",
  "status": "回應字串",
  "source": "回應字串",
  "isActive": false,
  "expiryDate": "回應字串",
  "createdAt": "回應字串"
}
```

狀態碼: 400 - 驗證錯誤（例如：名稱空白、到期日已過）

狀態碼: 403 - 權限不足

取得特定 API Key

`GET` `/api/v1/organizations/{organizationPk}/api-keys/{id}`

參數

參數名稱	必填	類型	說明
`id`	V	string	
`organizationPk`	V	string	A UUID string identifying this 組織 ID

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/organizations/550e8400-
e29b-41d4-a716-446655440000/api-keys/550e8400-e29b-41d4-a716-
446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-41d4-a716-446655440000/api-keys/550e8400-e29b-41d4-a716-446655440000/", config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-
41d4-a716-446655440000/api-keys/550e8400-e29b-41d4-a716-
446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-
41d4-a716-446655440000/api-keys/550e8400-e29b-41d4-a716-
446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
{
  "id": string
```

```
  "name"?: string // A free-form name for the API key. Need not be
unique. 50 characters max. (非必填)
  "prefix": string
  "status": string
  "source": string
  "isActive"?: boolean // Reversible enable switch. A disabled key is
rejected exactly like an unknown key (generic 401, no information leak),
but keeps its secret and usage history and can be re-enabled at any time
— unlike the irreversible revoked flag. (非必填)
  "rateLimitRpm"?: integer // Max requests per minute across every
platform API this key can call. Null = unlimited. (非必填)
  "rateLimitTpm"?: integer // Max LLM tokens per minute through the AI
Gateway inference endpoints. Null = unlimited. (非必填)
  "gatewayAllowedLlmCount": integer // Size of the gateway allow-list,
when the queryset annotated it.

0 means "no restriction" (see ``api_key_allowed_llm_ids``). ``None``
on surfaces that did not annotate (login payload, PAT list) so a
missing count is never mistaken for "unrestricted".
  "expiryDate"?: string (timestamp) // Once API key expires, clients
cannot use it anymore. (非必填)
  "createdAt": string (timestamp)
  "lastUsedAt"?: string (timestamp) // 非必填
  "member": object
  "createdByName": string
  "revokedAt"?: string (timestamp) // 非必填
  "revokedByName": string
  "gatewayAllowedLlmIds": [
    string (uuid)
  ]
}
```

回應範例值

```
{
  "id": "回應字串",
  "name": "回應字串",
  "prefix": "回應字串",
  "status": "回應字串",
  "source": "回應字串",
  "isActive": false,
  "rateLimitRpm": 456,
  "rateLimitTpm": 456,
  "gatewayAllowedLlmCount": 456,
```

```
  "expiryDate": "回應字串",
  "createdAt": "回應字串",
  "lastUsedAt": "回應字串",
  "member": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應範例名稱",
    "description": "回應範例描述"
  },
  "createdByName": "回應字串",
  "revokedAt": "回應字串",
  "revokedByName": "回應字串",
  "gatewayAllowedLlmIds": [
    "550e8400-e29b-41d4-a716-446655440000"
  ]
}
```


更新 API Key 設定

PATCH `/api/v1/organizations/{organizationPk}/api-keys/{id}`

可調整啟用狀態、每分鐘請求數（RPM）、到期時間；停用可逆，撤銷用 DELETE。

參數

參數名稱	必填	類型	說明
`id`	V	string	
`organizationPk`	V	string	A UUID string identifying this 組織 ID

請求內容

請求參數

欄位	類型	必填	說明
name	string	否	A free-form name for the API key. Need not be unique. 50 characters max.
isActive	boolean	否	Reversible enable switch. A disabled key is rejected exactly like an unknown key (generic 401, no information leak), but keeps its secret and usage history and can be re-enabled at any time — unlike t...
rateLimitRpm	integer	否	Max requests per minute across every platform API this key can call. Null = unlimited.
rateLimitTpm	integer	否	Max LLM tokens per minute through the AI Gateway inference endpoints. Null = unlimited.
expiryDate	string (timestamp)	否	Once API key expires, clients cannot use it anymore.
lastUsedAt	string (timestamp)	否	
revokedAt	string (timestamp)	否	

請求結構範例

```
{
  "name"?: string // A free-form name for the API key. Need not be
unique. 50 characters max. (非必填)
  "isActive"?: boolean // Reversible enable switch. A disabled key is
rejected exactly like an unknown key (generic 401, no information leak),
but keeps its secret and usage history and can be re-enabled at any time
— unlike the irreversible revoked flag. (非必填)
  "rateLimitRpm"?: integer // Max requests per minute across every
platform API this key can call. Null = unlimited. (非必填)
  "rateLimitTpm"?: integer // Max LLM tokens per minute through the AI
Gateway inference endpoints. Null = unlimited. (非必填)
  "expiryDate"?: string (timestamp) // Once API key expires, clients
cannot use it anymore. (非必填)
  "lastUsedAt"?: string (timestamp) // 非必填
  "revokedAt"?: string (timestamp) // 非必填
}
```

請求範例值

```
{
  "name": "範例名稱",
  "isActive": true,
  "rateLimitRpm": 123,
  "rateLimitTpm": 123,
  "expiryDate": "範例字串",
  "lastUsedAt": "範例字串",
  "revokedAt": "範例字串"
}
```

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X PATCH
"https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-41d4-
a716-446655440000/api-keys/550e8400-e29b-41d4-a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "name": "範例名稱",
    "isActive": true,
    "rateLimitRpm": 123,
    "rateLimitTpm": 123,
    "expiryDate": "範例字串",
    "lastUsedAt": "範例字串",
    "revokedAt": "範例字串"
  }'

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// 請求內容 (payload)
const data = {
    "name": "範例名稱",
    "isActive": true,
    "rateLimitRpm": 123,
    "rateLimitTpm": 123,
    "expiryDate": "範例字串",
    "lastUsedAt": "範例字串",
    "revokedAt": "範例字串"
  };

axios.patch("https://api.maiagent.ai/api/v1/organizations/550e8400-
e29b-41d4-a716-446655440000/api-keys/550e8400-e29b-41d4-a716-
446655440000/", data, config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-
41d4-a716-446655440000/api-keys/550e8400-e29b-41d4-a716-
446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# 請求內容 (payload)
data = {
    "name": "範例名稱",
    "isActive": True,
    "rateLimitRpm": 123,
    "rateLimitTpm": 123,
    "expiryDate": "範例字串",
    "lastUsedAt": "範例字串",
    "revokedAt": "範例字串"
}

response = requests.patch(url, json=data, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>patch("https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-
41d4-a716-446655440000/api-keys/550e8400-e29b-41d4-a716-
446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'name' => '範例名稱',
            'isActive' => true,
            'rateLimitRpm' => 123,
            'rateLimitTpm' => 123,
            'expiryDate' => '範例字串',
            'lastUsedAt' => '範例字串',
            'revokedAt' => '範例字串'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
{
  "id": string
  "name"?: string // A free-form name for the API key. Need not be
unique. 50 characters max. (非必填)
  "prefix": string
  "status": string
  "source": string
  "isActive"?: boolean // Reversible enable switch. A disabled key is
rejected exactly like an unknown key (generic 401, no information leak),
but keeps its secret and usage history and can be re-enabled at any time
— unlike the irreversible revoked flag. (非必填)
  "rateLimitRpm"?: integer // Max requests per minute across every
platform API this key can call. Null = unlimited. (非必填)
  "rateLimitTpm"?: integer // Max LLM tokens per minute through the AI
Gateway inference endpoints. Null = unlimited. (非必填)
  "gatewayAllowedLlmCount": integer // Size of the gateway allow-list,
when the queryset annotated it.

0 means "no restriction" (see ``api_key_allowed_llm_ids``). ``None``
on surfaces that did not annotate (login payload, PAT list) so a
missing count is never mistaken for "unrestricted".
  "expiryDate"?: string (timestamp) // Once API key expires, clients
cannot use it anymore. (非必填)
  "createdAt": string (timestamp)
  "lastUsedAt"?: string (timestamp) // 非必填
  "member": object
  "createdByName": string
  "revokedAt"?: string (timestamp) // 非必填
  "revokedByName": string
  "gatewayAllowedLlmIds": [
    string (uuid)
  ]
}
```

回應範例值

```
{
  "id": "回應字串",
  "name": "回應字串",
  "prefix": "回應字串",
  "status": "回應字串",
  "source": "回應字串",
  "isActive": false,
  "rateLimitRpm": 456,
  "rateLimitTpm": 456,
  "gatewayAllowedLlmCount": 456,
  "expiryDate": "回應字串",
  "createdAt": "回應字串",
  "lastUsedAt": "回應字串",
  "member": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應範例名稱",
    "description": "回應範例描述"
  },
  "createdByName": "回應字串",
  "revokedAt": "回應字串",
  "revokedByName": "回應字串",
  "gatewayAllowedLlmIds": [
    "550e8400-e29b-41d4-a716-446655440000"
  ]
}
```


撤銷 API Key

DELETE `/api/v1/organizations/{organizationPk}/api-keys/{id}`

參數

參數名稱	必填	類型	說明
id	V	string	

`organizationPk`	V	string	A UUID string identifying this 組織 ID

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X DELETE
"https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-41d4-
a716-446655440000/api-keys/550e8400-e29b-41d4-a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

// 請求內容 (payload)
const data = null;

axios.delete("https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-41d4-a716-446655440000/api-keys/550e8400-e29b-41d4-a716-446655440000/", data, config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-
41d4-a716-446655440000/api-keys/550e8400-e29b-41d4-a716-
446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.delete(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>delete("https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-
41d4-a716-446655440000/api-keys/550e8400-e29b-41d4-a716-
446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼	說明
204	API Key 撤銷成功
400	API Key 已被撤銷
403	權限不足

404 找不到 API Key

查詢 API Key 所屬組織

GET `/api/v1/users/api-key-context/`

只接受 Authorization: Api-Key，回傳金鑰綁定的組織；不計入金鑰的 RPM 額度。用途見 共通規範：確認金鑰所屬的組織。

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/users/api-key-context/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/users/api-key-context/",
config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/users/api-key-context/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/users/api-key-context/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
{
  "organizationId": string (uuid)
}
```

回應範例值

```
{
  "organizationId": "550e8400-e29b-41d4-a716-446655440000"
}
```

狀態碼: 401 - 缺少或無效的 API Key，或使用非 API Key 憑證

換發成員嵌入 token

POST `/api/v1/members/embed-tokens/`

以組織 API Key 為指定成員換發 15 分鐘效期的 token，供您的系統以成員身分嵌入 MaiGPT；只有組織擁有者或具「組織總覽」管理權限的成員持有的金鑰可呼叫。流程見技術手冊 MaiGPT 成員身分嵌入。

請求內容

請求參數

欄位	類型	必填	說明
email	string (email)	否	
memberId	string (uuid)	否	

請求結構範例

```
{
  "email"?: string (email) // 非必填
  "memberId"?: string (uuid) // 非必填
}
```

請求範例值

```
{
  "email": "user@example.com",
  "memberId": "550e8400-e29b-41d4-a716-446655440000"
}
```

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X POST "https://api.maiagent.ai/api/v1/members/embed-tokens/"
  -H "Authorization: Api-Key YOUR_API_KEY"
  -H "Content-Type: application/json"
  -d '{
    "email": "user@example.com",
    "memberId": "550e8400-e29b-41d4-a716-446655440000"
  }'

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// 請求內容 (payload)
const data = {
    "email": "user@example.com",
    "memberId": "550e8400-e29b-41d4-a716-446655440000"
  };

axios.post("https://api.maiagent.ai/api/v1/members/embed-tokens/",
data, config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```python
import requests

url = "https://api.maiagent.ai/api/v1/members/embed-tokens/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# 請求內容 (payload)
data = {
    "email": "user@example.com",
    "memberId": "550e8400-e29b-41d4-a716-446655440000"
}

response = requests.post(url, json=data, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>post("https://api.maiagent.ai/api/v1/members/embed-tokens/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'email' => 'user@example.com',
            'memberId' => '550e8400-e29b-41d4-a716-446655440000'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 201

回應結構範例

```
{
  "accessToken": string
  "organizationId": string (uuid)
  "expiresAt": string (timestamp)
  "member": {
  {
    "id": string (uuid)
    "userId": string (uuid)
    "email": string (email)
    "name": string
  }
  }
}
```

回應範例值

```
{
  "accessToken": "回應字串",
  "organizationId": "550e8400-e29b-41d4-a716-446655440000",
  "expiresAt": "回應字串",
  "member": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "userId": "550e8400-e29b-41d4-a716-446655440000",
    "email": "response@example.com",
    "name": "回應字串"
  }
}
```

狀態碼: `400` - email 與 memberId 必須且只能提供其中一個

狀態碼: `401` - 未以 Api-Key 認證

狀態碼: `403` - API Key 持有者不是組織擁有者也沒有組織管理權限

狀態碼: `404` - 指定的成員不存在、已停用或不屬於本組織

列出 OAuth 應用程式

`GET` `/api/v1/oauth/applications/`

MaiAgent 作為 OAuth 2.1 授權伺服器時，您的應用程式先在此註冊。流程見技術手冊 MaiAgent 作為 OAuth 授權伺服器。

參數

參數名稱	必填	類型	說明
`page`	X	integer	A page number within the paginated result set.
`pageSize`	X	integer	Number of results to return per page.

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/oauth/applications/?
page=1&pageSize=1"

  -H "Authorization: Api-Key YOUR_API_KEY"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/oauth/applications/?
page=1&pageSize=1", config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/oauth/applications/?
page=1&pageSize=1"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/oauth/applications/?
page=1&pageSize=1", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
{
  "count": integer
  "next"?: string (uri) // 非必填
```

```
  "previous"?: string (uri) // 非必填
  "results": [
    {
      "id": string (uuid)
      "name": string
      "clientId": string
      "clientType":
      {
      }
      "redirectUris": [
        string
      ]
      "authorizedUserCount": integer
      "createdByName": string
      "created": string (timestamp)
      "updated": string (timestamp)
    }
  ]
}
```

回應範例值

```
{
  "count": 123,
  "next": "http://api.example.org/accounts/?page=4",
  "previous": "http://api.example.org/accounts/?page=2",
  "results": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "回應字串",
      "clientId": "回應字串",
      "clientType": {},
      "redirectUris": [
        "回應字串"
      ],
      "authorizedUserCount": 456,
      "createdByName": "回應字串",
      "created": "回應字串",
      "updated": "回應字串"
    }
```

```
  ]
}
```

註冊 OAuth 應用程式

POST `/api/v1/oauth/applications/`

請求內容

請求參數

欄位	類型	必填	說明
name	string	是	
clientType	object	否	
redirectUris	array[string]	是	

請求結構範例

```
{
  "name": string
  "clientType"?:  // 非必填
  {
  }
  "redirectUris": [
    string
  ]
}
```

請求範例值

```
{
  "name": "範例名稱",
  "clientType": {},
  "redirectUris": [
    "範例字串"
  ]
}
```

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X POST "https://api.maiagent.ai/api/v1/oauth/applications/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "name": "範例名稱",
    "clientType": {},
    "redirectUris": [
      "範例字串"
    ]
  }'

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// 請求內容 (payload)
const data = {
    "name": "範例名稱",
    "clientType": {},
    "redirectUris": [
      "範例字串"
    ]
  };

axios.post("https://api.maiagent.ai/api/v1/oauth/applications/",
data, config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/oauth/applications/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# 請求內容 (payload)
data = {
    "name": "範例名稱",
    "clientType": {},
    "redirectUris": [
        "範例字串"
    ]
}

response = requests.post(url, json=data, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>post("https://api.maiagent.ai/api/v1/oauth/applications/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'name' => '範例名稱',
            'clientType' => new \stdClass(),
            'redirectUris' => [
                '範例字串'
            ]
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 201

回應結構範例

```
{
  "id": string (uuid)
  "name": string
  "clientId": string
  "clientType":
  {
  }
  "redirectUris": [
    string
  ]
  "authorizedUserCount": integer
  "createdByName": string
  "created": string (timestamp)
  "updated": string (timestamp)
  "clientSecret": string
}
```

回應範例值

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "name": "回應字串",
  "clientId": "回應字串",
  "clientType": {},
  "redirectUris": [
    "回應字串"
  ],
  "authorizedUserCount": 456,
  "createdByName": "回應字串",
  "created": "回應字串",
  "updated": "回應字串",
  "clientSecret": "回應字串"
}
```

取得特定 OAuth 應用程式

GET `/api/v1/oauth/applications/{id}`

參數

參數名稱	必填	類型	說明
`id`	V	string	A UUID string identifying this MaiAgent OAuth application.

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X GET
"https://api.maiagent.ai/api/v1/oauth/applications/550e8400-e29b-
41d4-a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/oauth/applications/550e8400-e29b-41d4-a716-446655440000/", config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/oauth/applications/550e8400-
e29b-41d4-a716-446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/oauth/applications/550e8400-
e29b-41d4-a716-446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
{
  "id": string (uuid)
  "name": string
```

```
  "clientId": string
  "clientType":
  {
  }
  "redirectUris": [
    string
  ]
  "authorizedUserCount": integer
  "createdByName": string
  "created": string (timestamp)
  "updated": string (timestamp)
}
```

回應範例值

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "name": "回應字串",
  "clientId": "回應字串",
  "clientType": {},
  "redirectUris": [
    "回應字串"
  ],
  "authorizedUserCount": 456,
  "createdByName": "回應字串",
  "created": "回應字串",
  "updated": "回應字串"
}
```

更新 OAuth 應用程式

PATCH `/api/v1/oauth/applications/{id}`

參數

參數名稱	必填	類型	說明
`id`	V	string	A UUID string identifying this MaiAgent OAuth application.

請求內容

請求參數

欄位	類型	必填	說明
name	string	否	
redirectUris	array[string]	否	

請求結構範例

```
{
  "name"?: string // 非必填
  "redirectUris"?: [ // 非必填
    string
  ]
}
```

請求範例值

```
{
  "name": "範例名稱",
  "redirectUris": [
    "範例字串"
  ]
}
```

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X PATCH
"https://api.maiagent.ai/api/v1/oauth/applications/550e8400-e29b-
41d4-a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "name": "範例名稱",
    "redirectUris": [
      "範例字串"
    ]
  }'

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// 請求內容 (payload)
const data = {
    "name": "範例名稱",
    "redirectUris": [
      "範例字串"
    ]
  };

axios.patch("https://api.maiagent.ai/api/v1/oauth/applications/550e8400-e29b-41d4-a716-446655440000/", data, config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/oauth/applications/550e8400-
e29b-41d4-a716-446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# 請求內容 (payload)
data = {
    "name": "範例名稱",
    "redirectUris": [
        "範例字串"
    ]
}

response = requests.patch(url, json=data, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>patch("https://api.maiagent.ai/api/v1/oauth/applications/550e8400-
e29b-41d4-a716-446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'name' => '範例名稱',
            'redirectUris' => [
                '範例字串'
            ]
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
{
  "id": string (uuid)
  "name": string
  "clientId": string
  "clientType":
  {
  }
  "redirectUris": [
    string
  ]
  "authorizedUserCount": integer
  "createdByName": string
  "created": string (timestamp)
  "updated": string (timestamp)
}
```

回應範例值

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "name": "回應字串",
  "clientId": "回應字串",
  "clientType": {},
  "redirectUris": [
    "回應字串"
  ],
  "authorizedUserCount": 456,
  "createdByName": "回應字串",
  "created": "回應字串",
  "updated": "回應字串"
}
```

刪除 OAuth 應用程式並撤銷其 token

DELETE `/api/v1/oauth/applications/{id}`

參數

參數名稱	必填	類型	說明
`id`	V	string	A UUID string identifying this MaiAgent OAuth application.

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X DELETE
"https://api.maiagent.ai/api/v1/oauth/applications/550e8400-e29b-
41d4-a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

// 請求內容 (payload)
const data = null;

axios.delete("https://api.maiagent.ai/api/v1/oauth/applications/550e
8400-e29b-41d4-a716-446655440000/", data, config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/oauth/applications/550e8400-
e29b-41d4-a716-446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.delete(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>delete("https://api.maiagent.ai/api/v1/oauth/applications/550e8400-
e29b-41d4-a716-446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼	說明
204	No response body

重新產生 client secret

POST `/api/v1/oauth/applications/{id}/regenerate-secret/`

參數

參數名稱	必填	類型	說明
`id`	V	string	A UUID string identifying this MaiAgent OAuth application.

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X POST
"https://api.maiagent.ai/api/v1/oauth/applications/550e8400-e29b-
41d4-a716-446655440000/regenerate-secret/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

// 請求內容 (payload)
const data = null;

axios.post("https://api.maiagent.ai/api/v1/oauth/applications/550e84
00-e29b-41d4-a716-446655440000/regenerate-secret/", data, config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/oauth/applications/550e8400-
e29b-41d4-a716-446655440000/regenerate-secret/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.post(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>post("https://api.maiagent.ai/api/v1/oauth/applications/550e8400-
e29b-41d4-a716-446655440000/regenerate-secret/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
{
  "id": string (uuid)
  "name": string
```

```
  "clientId": string
  "clientType":
  {
  }
  "redirectUris": [
    string
  ]
  "authorizedUserCount": integer
  "createdByName": string
  "created": string (timestamp)
  "updated": string (timestamp)
  "clientSecret": string
}
```

回應範例值

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "name": "回應字串",
  "clientId": "回應字串",
  "clientType": {},
  "redirectUris": [
    "回應字串"
  ],
  "authorizedUserCount": 456,
  "createdByName": "回應字串",
  "created": "回應字串",
  "updated": "回應字串",
  "clientSecret": "回應字串"
}
```

列出我授權過的 OAuth 應用程式

GET `/api/v1/oauth/authorized-applications/`

參數

參數名稱	必填	類型	說明
`page`	X	integer	A page number within the paginated result set.
`pageSize`	X	integer	Number of results to return per page.

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/oauth/authorized-
applications/?page=1&pageSize=1"

  -H "Authorization: Api-Key YOUR_API_KEY"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/oauth/authorized-
applications/?page=1&pageSize=1", config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/oauth/authorized-
applications/?page=1&pageSize=1"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/oauth/authorized-applications/?
page=1&pageSize=1", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
{
  "count": integer
  "next"?: string (uri) // 非必填
```

```
  "previous"?: string (uri) // 非必填
  "results": [
    {
      "id": string (uuid)
      "name": string
      "organization": string (uuid)
      "organizationName": string
      "tokenCount": integer
      "lastAuthorizedAt": string (timestamp)
      "latestExpiresAt": string (timestamp)
    }
  ]
}
```

回應範例值


```
{
  "count": 123,
  "next": "http://api.example.org/accounts/?page=4",
  "previous": "http://api.example.org/accounts/?page=2",
  "results": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "回應字串",
      "organization": "550e8400-e29b-41d4-a716-446655440000",
      "organizationName": "回應字串",
      "tokenCount": 456,
      "lastAuthorizedAt": "回應字串",
      "latestExpiresAt": "回應字串"
    }
  ]
}
```


撤銷我對某應用程式的授權

DELETE `/api/v1/oauth/authorized-applications/{id}`

參數

參數名稱	必填	類型	說明
id	V	string	

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X DELETE "https://api.maiagent.ai/api/v1/oauth/authorized-
applications/550e8400-e29b-41d4-a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

// 請求內容 (payload)
const data = null;

axios.delete("https://api.maiagent.ai/api/v1/oauth/authorized-
applications/550e8400-e29b-41d4-a716-446655440000/", data, config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/oauth/authorized-
applications/550e8400-e29b-41d4-a716-446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.delete(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>delete("https://api.maiagent.ai/api/v1/oauth/authorized-
applications/550e8400-e29b-41d4-a716-446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼	說明
204	No response body

刪除組織

DELETE `/api/v1/organizations/{id}`

參數

參數名稱	必填	類型	說明
id	V	string	A UUID string identifying this 組織.

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X DELETE
"https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-41d4-
a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

// 請求內容 (payload)
const data = null;

axios.delete("https://api.maiagent.ai/api/v1/organizations/550e8400-
e29b-41d4-a716-446655440000/", data, config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-
41d4-a716-446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.delete(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>delete("https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-
41d4-a716-446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼	說明
204	No response body

刪除指定成員

`DELETE` `/api/v1/organizations/{organizationPk}/members/{id}`

參數

參數名稱	必填	類型	說明
`id`	V	string	A UUID string identifying this 成員.
`organizationPk`	V	string	A UUID string identifying this 組織 ID

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X DELETE
"https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-41d4-
a716-446655440000/members/550e8400-e29b-41d4-a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

// 請求內容 (payload)
const data = null;

axios.delete("https://api.maiagent.ai/api/v1/organizations/550e8400-
e29b-41d4-a716-446655440000/members/550e8400-e29b-41d4-a716-
446655440000/", data, config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-41d4-a716-446655440000/members/550e8400-e29b-41d4-a716-446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.delete(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>delete("https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-
41d4-a716-446655440000/members/550e8400-e29b-41d4-a716-
446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼	說明
204	No response body

取得成員使用統計

`GET` `/api/v1/organizations/{organizationPk}/usage-statistics/members/`

參數

參數名稱	必填	類型	說明
`organizationPk`	V	string	A UUID string identifying this 組織 ID
`chatbot`	X	string	篩選特定 AI 助理 ID
`chatbotId`	X	string	
`endDate`	X	string	結束日期，格式: YYYY-MM-DD
`includeTime`	X	boolean	是否返回只按時間聚合的時間序列資料，用於趨勢圖表（true/false）。設為 true 時，回應不包含實體資訊，只有時間欄位和統計數值，且不分頁。
`memberId`	X	string	
`page`	X	integer	頁碼
`pageSize`	X	integer	每頁筆數
`search`	X	string	搜尋成員 ID、名稱或 Email
`sortBy`	X	string	排序欄位
`sortOrder`	X	string	排序方式 (asc/desc)
`startDate`	V	string	開始日期，格式: YYYY-MM-DD
`timeGranularity`	X	string	時間粒度 (hour/day/month)

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/organizations/550e8400-
e29b-41d4-a716-446655440000/usage-statistics/members/?
chatbot=example&chatbotId=550e8400-e29b-41d4-a716-
446655440000&endDate=example&includeTime=true&memberId=550e8400-
e29b-41d4-a716-
446655440000&page=1&pageSize=1&search=example&sortBy=conversations_c
ount&sortOrder=asc&startDate=example&timeGranularity=day"

  -H "Authorization: Api-Key YOUR_API_KEY"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/organizations/550e8400-
e29b-41d4-a716-446655440000/usage-statistics/members/?
chatbot=example&chatbotId=550e8400-e29b-41d4-a716-
446655440000&endDate=example&includeTime=true&memberId=550e8400-
e29b-41d4-a716-
446655440000&page=1&pageSize=1&search=example&sortBy=conversations_c
ount&sortOrder=asc&startDate=example&timeGranularity=day", config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-
41d4-a716-446655440000/usage-statistics/members/?
chatbot=example&chatbotId=550e8400-e29b-41d4-a716-
446655440000&endDate=example&includeTime=true&memberId=550e8400-
e29b-41d4-a716-
446655440000&page=1&pageSize=1&search=example&sortBy=conversations_c
ount&sortOrder=asc&startDate=example&timeGranularity=day"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-
41d4-a716-446655440000/usage-statistics/members/?
chatbot=example&chatbotId=550e8400-e29b-41d4-a716-
446655440000&endDate=example&includeTime=true&memberId=550e8400-
e29b-41d4-a716-
446655440000&page=1&pageSize=1&search=example&sortBy=conversations_c
ount&sortOrder=asc&startDate=example&timeGranularity=day", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
{
  "count": integer
  "next"?: string (uri) // 非必填
  "previous"?: string (uri) // 非必填
  "results": [
    {
      "count"?: integer // 結果數量 (非必填)
      "results"?: [ // 非必填
        {
          "member"?: { // 非必填
          {
            "id"?: string (uuid) // 成員 ID (非必填)
            "name"?: string // 成員名稱 (非必填)
            "email"?: string // 成員電子郵件 (非必填)
          }
          }
          "datetime"?: string (date-time) // 時間戳（僅 include_time=true
且 time_granularity=hour 時出現） (非必填)
          "period"?: string (date) // 日期（僅 include_time=true 且
time_granularity=day/month 時出現） (非必填)
          "input_characters_count"?: integer // 輸入字元數 (非必填)
          "output_characters_count"?: integer // 輸出字元數 (非必填)
          "input_token_usage"?: integer // 輸入 Token 數 (非必填)
          "output_token_usage"?: integer // 輸出 Token 數 (非必填)
          "messages_count"?: integer // 訊息數 (非必填)
          "conversations_count"?: integer // 對話數 (非必填)
          "total_characters_count"?: integer // 總字元數 (非必填)
          "total_token_usage"?: integer // 總 Token 數 (非必填)
        }
      ]
    }
  ]
}
```

回應範例值

```
{
  "count": 123,
  "next": "http://api.example.org/accounts/?page=4",
  "previous": "http://api.example.org/accounts/?page=2",
  "results": [
    {
      "count": 2,
```

```
      "results": [
        {
          "member": {
            "id": "3a245511-d5e0-4e06-9dc6-1106915b9a8a",
            "name": "王小明",
            "email": "wang@example.com"
          },
          "input_characters_count": 10000,
          "output_characters_count": 15000,
          "input_token_usage": 2500,
          "output_token_usage": 3750,
          "messages_count": 100,
          "conversations_count": 50,
          "total_characters_count": 25000,
          "total_token_usage": 6250
        }
      ]
    }
  ]
}
```


取得成員使用統計摘要

GET `/api/v1/organizations/{organizationPk}/usage-statistics/members/summary/`

參數

參數名稱	必填	類型	說明
`organizationPk`	V	string	A UUID string identifying this 組織 ID
`endDate`	X	string	結束日期，格式: YYYY-MM-DD
`startDate`	V	string	開始日期，格式: YYYY-MM-DD

`timeGranularity`	X	string	時間粒度 (hour/day/month)

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-41d4-a716-446655440000/usage-statistics/members/summary/?endDate=example&startDate=example&timeGranularity=day"

  -H "Authorization: Api-Key YOUR_API_KEY"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/organizations/550e8400-
e29b-41d4-a716-446655440000/usage-statistics/members/summary/?
endDate=example&startDate=example&timeGranularity=day", config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-
41d4-a716-446655440000/usage-statistics/members/summary/?
endDate=example&startDate=example&timeGranularity=day"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-
41d4-a716-446655440000/usage-statistics/members/summary/?
endDate=example&startDate=example&timeGranularity=day", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
{
  "total_input_characters"?: integer // 總輸入字元數 (非必填)
```

```
  "total_output_characters"?: integer // 總輸出字元數 (非必填)
  "total_characters"?: integer // 總字元數 (非必填)
  "total_input_tokens"?: integer // 總輸入 Token 數 (非必填)
  "total_output_tokens"?: integer // 總輸出 Token 數 (非必填)
  "total_tokens"?: integer // 總 Token 數 (非必填)
  "total_messages"?: integer // 總訊息數 (非必填)
  "total_conversations"?: integer // 總對話數 (非必填)
  "chatbot_scope"?: string (enum: organization, accessible_chatbots) // 呼叫者的用量統計範圍：organization＝全組織；accessible_chatbots＝僅所屬角色被授權的 AI 助理 (非必填)
  "total_members"?: integer // 總成員數 (非必填)
}
```

回應範例值

```
{
  "total_input_characters": 456,
  "total_output_characters": 456,
  "total_characters": 456,
  "total_input_tokens": 456,
  "total_output_tokens": 456,
  "total_tokens": 456,
  "total_messages": 456,
  "total_conversations": 456,
  "chatbot_scope": "organization",
  "total_members": 456
}
```

取得 AI 助理使用統計

GET `/api/v1/organizations/{organizationPk}/usage-statistics/chatbots/`

參數

參數名稱	必填	類型	說明
`organizationPk`	V	string	A UUID string identifying this 組織 ID
`chatbotId`	X	string	
`endDate`	X	string	結束日期，格式: YYYY-MM-DD
`includeTime`	X	boolean	是否返回只按時間聚合的時間序列資料，用於趨勢圖表（true/false）。設為 true 時，回應不包含實體資訊，只有時間欄位和統計數值，且不分頁。
`page`	X	integer	頁碼
`pageSize`	X	integer	每頁筆數
`search`	X	string	搜尋 AI 助理 ID 或名稱
`sortBy`	X	string	排序欄位
`sortOrder`	X	string	排序方式 (asc/desc)
`startDate`	V	string	開始日期，格式: YYYY-MM-DD
`timeGranularity`	X	string	時間粒度 (hour/day/month)

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/organizations/550e8400-
e29b-41d4-a716-446655440000/usage-statistics/chatbots/?
chatbotId=550e8400-e29b-41d4-a716-
446655440000&endDate=example&includeTime=true&page=1&pageSize=1&sear
ch=example&sortBy=conversations_count&sortOrder=asc&startDate=exampl
e&timeGranularity=day"

  -H "Authorization: Api-Key YOUR_API_KEY"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/organizations/550e8400-
e29b-41d4-a716-446655440000/usage-statistics/chatbots/?
chatbotId=550e8400-e29b-41d4-a716-
446655440000&endDate=example&includeTime=true&page=1&pageSize=1&sear
ch=example&sortBy=conversations_count&sortOrder=asc&startDate=exampl
e&timeGranularity=day", config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-41d4-a716-446655440000/usage-statistics/chatbots/?chatbotId=550e8400-e29b-41d4-a716-446655440000&endDate=example&includeTime=true&page=1&pageSize=1&search=example&sortBy=conversations_count&sortOrder=asc&startDate=example&timeGranularity=day"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-
41d4-a716-446655440000/usage-statistics/chatbots/?
chatbotId=550e8400-e29b-41d4-a716-
446655440000&endDate=example&includeTime=true&page=1&pageSize=1&sear
ch=example&sortBy=conversations_count&sortOrder=asc&startDate=exampl
e&timeGranularity=day", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
{
  "count": integer
  "next"?: string (uri) // 非必填
  "previous"?: string (uri) // 非必填
  "results": [
    {
      "count"?: integer // 結果數量 (非必填)
      "results"?: [ // 非必填
        {
          "chatbot"?: { // 非必填
          {
            "id"?: string (uuid) // AI 助理 ID (非必填)
            "name"?: string // AI 助理名稱 (非必填)
          }
          }
          "datetime"?: string (date-time) // 時間戳（僅 include_time=true 且 time_granularity=hour 時出現） (非必填)
          "period"?: string (date) // 日期（僅 include_time=true 且 time_granularity=day/month 時出現） (非必填)
          "input_characters_count"?: integer // 輸入字元數 (非必填)
          "output_characters_count"?: integer // 輸出字元數 (非必填)
          "input_token_usage"?: integer // 輸入 Token 數 (非必填)
          "output_token_usage"?: integer // 輸出 Token 數 (非必填)
          "messages_count"?: integer // 訊息數 (非必填)
          "conversations_count"?: integer // 對話數 (非必填)
          "total_characters_count"?: integer // 總字元數 (非必填)
          "total_token_usage"?: integer // 總 Token 數 (非必填)
        }
      ]
    }
  ]
}
```

回應範例值

```
{
  "count": 123,
  "next": "http://api.example.org/accounts/?page=4",
  "previous": "http://api.example.org/accounts/?page=2",
  "results": [
    {
      "count": 2,
      "results": [
```

```
        {
          "chatbot": {
            "id": "5b646600-f6e0-4f07-aec7-0207a26c0a9b",
            "name": "客服助理"
          },
          "input_characters_count": 10000,
          "output_characters_count": 15000,
          "input_token_usage": 2500,
          "output_token_usage": 3750,
          "messages_count": 100,
          "conversations_count": 50,
          "total_characters_count": 25000,
          "total_token_usage": 6250
        }
      ]
    }
  ]
}
```


取得 AI 助理使用統計摘要

GET `/api/v1/organizations/{organizationPk}/usage-statistics/chatbots/summary/`

參數

參數名稱	必填	類型	說明
`organizationPk`	V	string	A UUID string identifying this 組織 ID
`endDate`	X	string	結束日期，格式: YYYY-MM-DD
`startDate`	V	string	開始日期，格式: YYYY-MM-DD
`timeGranularity`	X	string	時間粒度 (hour/day/month)

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/organizations/550e8400-
e29b-41d4-a716-446655440000/usage-statistics/chatbots/summary/?
endDate=example&startDate=example&timeGranularity=day"

  -H "Authorization: Api-Key YOUR_API_KEY"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/organizations/550e8400-
e29b-41d4-a716-446655440000/usage-statistics/chatbots/summary/?
endDate=example&startDate=example&timeGranularity=day", config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-
41d4-a716-446655440000/usage-statistics/chatbots/summary/?
endDate=example&startDate=example&timeGranularity=day"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-
41d4-a716-446655440000/usage-statistics/chatbots/summary/?
endDate=example&startDate=example&timeGranularity=day", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
{
  "total_input_characters"?: integer // 總輸入字元數 (非必填)
```

```
  "total_output_characters"?: integer // 總輸出字元數 (非必填)
  "total_characters"?: integer // 總字元數 (非必填)
  "total_input_tokens"?: integer // 總輸入 Token 數 (非必填)
  "total_output_tokens"?: integer // 總輸出 Token 數 (非必填)
  "total_tokens"?: integer // 總 Token 數 (非必填)
  "total_messages"?: integer // 總訊息數 (非必填)
  "total_conversations"?: integer // 總對話數 (非必填)
  "chatbot_scope"?: string (enum: organization, accessible_chatbots) // 呼叫者的用量統計範圍：organization＝全組織；accessible_chatbots＝僅所屬角色被授權的 AI 助理 (非必填)
  "total_chatbots"?: integer // 總 AI 助理數 (非必填)
}
```

回應範例值

```
{
  "total_input_characters": 456,
  "total_output_characters": 456,
  "total_characters": 456,
  "total_input_tokens": 456,
  "total_output_tokens": 456,
  "total_tokens": 456,
  "total_messages": 456,
  "total_conversations": 456,
  "chatbot_scope": "organization",
  "total_chatbots": 456
}
```

列出自己的記憶

GET `/api/v1/me/memories/`

請帶 X-Organization-Id 標頭指定要操作的組織，以 API 金鑰呼叫時也要帶。可用 status（active／expired）、kind（fact／preference／instruction）查詢參數篩選；待確認或被拒絕的記憶不會列出。行為說明見技術手冊成員記憶管理 API。

參數

參數名稱	必填	類型	說明
`kind`	X	string	`fact`: Fact ; `preference`: Preference ; `instruction`: Instruction ; `summary`: Summary ; `profile`: Profile;
`page`	X	integer	A page number within the paginated result set.
`pageSize`	X	integer	Number of results to return per page.
`status`	X	string	`pending`: Pending ; `active`: Active ; `rejected`: Rejected ; `expired`: Expired;

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/me/memories/?
kind=fact&page=1&pageSize=1&status=active"

  -H "Authorization: Api-Key YOUR_API_KEY"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/me/memories/?
kind=fact&page=1&pageSize=1&status=active", config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/me/memories/?
kind=fact&page=1&pageSize=1&status=active"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/me/memories/?
kind=fact&page=1&pageSize=1&status=active", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
{
  "count": integer
  "next"?: string (uri) // 非必填
```

```
  "previous"?: string (uri) // 非必填
  "results": [
    {
      "id": string (uuid)
      "topic": string // LLM-assigned topic slug for grouping related
memories (e.g. "language_preferences", "role", "communication_style").
Null means legacy memory without topic grouping.
      "category": // 可能有不同的類型
      string (enum: personal_info, work_role, projects, communication,
response_format, tools_tech, interests, health_lifestyle, schedule_plans,
other) // Fixed category shown to users. Null means legacy memory without
a category.

* `personal_info` - Personal Info
* `work_role` - Work and Role
* `projects` - Projects and Work
* `communication` - Communication Preferences
* `response_format` - Response Format Preferences
* `tools_tech` - Tools and Technology
* `interests` - Interests and Hobbies
* `health_lifestyle` - Health and Lifestyle
* `schedule_plans` - Schedule and Plans
* `other` - Other
      "categoryDisplay": string // Translated category name.
      "summary": string // One-line summary of the memory topic.
      "details": object // Concrete facts for this topic, stored as a
list of strings.
      "kind":
      {
      }
      "source":  // How this memory was created: user explicitly stated,
agent extracted, or manually added.

* `user_stated` - User Stated
* `agent_extracted` - Agent Extracted
* `agent_stated` - Agent Stated
* `user_manual` - User Manual
      {
      }
      "requestedByUser": boolean // True when the user explicitly asked
the agent to remember this. Only affects the UI label (S12), not LRU
eviction priority (S6).
      "status":
      {
      }
```

```
      "createdAt": string (timestamp)
      "updatedAt": string (timestamp)
    }
  ]
}
```

回應範例值

```
{
  "count": 123,
  "next": "http://api.example.org/accounts/?page=4",
  "previous": "http://api.example.org/accounts/?page=2",
  "results": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "topic": "回應字串",
      "category": "personal_info",
      "categoryDisplay": "回應字串",
      "summary": "回應字串",
      "details": null,
      "kind": {},
      "source": {},
      "requestedByUser": false,
      "status": {},
      "createdAt": "回應字串",
      "updatedAt": "回應字串"
    }
  ]
}
```

建立或更新自己的記憶

POST `/api/v1/me/memories/`

請帶 X-Organization-Id 標頭指定要操作的組織，以 API 金鑰呼叫時也要帶。請求欄位：topic（必填，最多 100 字元，只能用小寫英文字母、數字與中間的底線）、summary（必填，最多 500 字元）、details（必

填，字串陣列，最多 20 項、每項最多 500 字元）、kind（fact／preference／instruction，預設 fact）。同一成員已有相同 topic 的啟用中記憶時更新該筆並回 200，新建回 201。

請求內容

請求參數

欄位	類型	必填	說明
topic	string	是	
category	string (enum: personal_info, work_role, projects, communication, response_format, tools_tech, interests, health_lifestyle, schedule_plans, other)	否	`personal_info` : Personal Info ; `work_role` : Work and Role ; `projects` : Projects and Work ; `communication` : Communication Preferences ; `response_format` : Response Format Preferences ; `tools_tech` ...
summary	string	是	
details	array[string]	是	
kind	object	否	

請求結構範例

```
{
  "topic": string
  "category"?: string (enum: personal_info, work_role, projects,
communication, response_format, tools_tech, interests, health_lifestyle,
schedule_plans, other) // * `personal_info` - Personal Info
* `work_role` - Work and Role
* `projects` - Projects and Work
* `communication` - Communication Preferences
* `response_format` - Response Format Preferences
* `tools_tech` - Tools and Technology
* `interests` - Interests and Hobbies
* `health_lifestyle` - Health and Lifestyle
* `schedule_plans` - Schedule and Plans
* `other` - Other (非必填)
  "summary": string
```

```
  "details": [
    string
  ]
  "kind"?:  // 非必填
  {
  }
}
```

請求範例值

```
{
  "topic": "範例字串",
  "category": "personal_info",
  "summary": "範例字串",
  "details": [
    "範例字串"
  ],
  "kind": {}
}
```

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X POST "https://api.maiagent.ai/api/v1/me/memories/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "topic": "範例字串",
    "category": "personal_info",
    "summary": "範例字串",
    "details": [
      "範例字串"
    ],
    "kind": {}
  }'

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// 請求內容 (payload)
const data = {
    "topic": "範例字串",
    "category": "personal_info",
    "summary": "範例字串",
    "details": [
      "範例字串"
    ],
    "kind": {}
  };

axios.post("https://api.maiagent.ai/api/v1/me/memories/", data,
config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/me/memories/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# 請求內容 (payload)
data = {
    "topic": "範例字串",
    "category": "personal_info",
    "summary": "範例字串",
    "details": [
        "範例字串"
    ],
    "kind": {}
}

response = requests.post(url, json=data, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>post("https://api.maiagent.ai/api/v1/me/memories/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'topic' => '範例字串',
            'category' => 'personal_info',
            'summary' => '範例字串',
            'details' => [
                '範例字串'
            ],
            'kind' => new \stdClass()
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
{
  "id": string (uuid)
  "topic": string // LLM-assigned topic slug for grouping related
memories (e.g. "language_preferences", "role", "communication_style").
Null means legacy memory without topic grouping.
  "category": // 可能有不同的類型
  string (enum: personal_info, work_role, projects, communication,
response_format, tools_tech, interests, health_lifestyle, schedule_plans,
other) // Fixed category shown to users. Null means legacy memory without
a category.

* `personal_info` - Personal Info
* `work_role` - Work and Role
* `projects` - Projects and Work
* `communication` - Communication Preferences
* `response_format` - Response Format Preferences
* `tools_tech` - Tools and Technology
* `interests` - Interests and Hobbies
* `health_lifestyle` - Health and Lifestyle
* `schedule_plans` - Schedule and Plans
* `other` - Other
  "categoryDisplay": string // Translated category name.
  "summary": string // One-line summary of the memory topic.
  "details": object // Concrete facts for this topic, stored as a list of
strings.
  "kind":
  {
  }
  "source":  // How this memory was created: user explicitly stated,
agent extracted, or manually added.

* `user_stated` - User Stated
* `agent_extracted` - Agent Extracted
* `agent_stated` - Agent Stated
* `user_manual` - User Manual
  {
  }
  "requestedByUser": boolean // True when the user explicitly asked the
agent to remember this. Only affects the UI label (S12), not LRU eviction
priority (S6).
  "status":
```

```
  {
  }
  "createdAt": string (timestamp)
  "updatedAt": string (timestamp)
}
```

回應範例值

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "topic": "回應字串",
  "category": "personal_info",
  "categoryDisplay": "回應字串",
  "summary": "回應字串",
  "details": null,
  "kind": {},
  "source": {},
  "requestedByUser": false,
  "status": {},
  "createdAt": "回應字串",
  "updatedAt": "回應字串"
}
```

狀態碼: 201

回應結構範例

```
{
  "id": string (uuid)
  "topic": string // LLM-assigned topic slug for grouping related
memories (e.g. "language_preferences", "role", "communication_style").
Null means legacy memory without topic grouping.
  "category": // 可能有不同的類型
  string (enum: personal_info, work_role, projects, communication,
response_format, tools_tech, interests, health_lifestyle, schedule_plans,
other) // Fixed category shown to users. Null means legacy memory without
a category.

* `personal_info` - Personal Info
* `work_role` - Work and Role
* `projects` - Projects and Work
* `communication` - Communication Preferences
```

```
* `response_format` - Response Format Preferences
* `tools_tech` - Tools and Technology
* `interests` - Interests and Hobbies
* `health_lifestyle` - Health and Lifestyle
* `schedule_plans` - Schedule and Plans
* `other` - Other
  "categoryDisplay": string // Translated category name.
  "summary": string // One-line summary of the memory topic.
  "details": object // Concrete facts for this topic, stored as a list of
strings.
  "kind":
  {
  }
  "source":  // How this memory was created: user explicitly stated,
agent extracted, or manually added.

* `user_stated` - User Stated
* `agent_extracted` - Agent Extracted
* `agent_stated` - Agent Stated
* `user_manual` - User Manual
  {
  }
  "requestedByUser": boolean // True when the user explicitly asked the
agent to remember this. Only affects the UI label (S12), not LRU eviction
priority (S6).
  "status":
  {
  }
  "createdAt": string (timestamp)
  "updatedAt": string (timestamp)
}
```

回應範例值

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "topic": "回應字串",
  "category": "personal_info",
  "categoryDisplay": "回應字串",
  "summary": "回應字串",
  "details": null,
  "kind": {},
  "source": {},
  "requestedByUser": false,
```

```
  "status": {},
  "createdAt": "回應字串",
  "updatedAt": "回應字串"
}
```

修改或重新啟用自己的記憶

PATCH `/api/v1/me/memories/{id}`

請帶 X-Organization-Id 標頭指定要操作的組織，以 API 金鑰呼叫時也要帶。可帶 topic、summary、details（限制同建立）修改內容，或帶 status（active／expired）停用或重新啟用；至少要帶其中一個欄位。

參數

參數名稱	必填	類型	說明
id	V	string	A UUID string identifying this Memory Entry.

請求內容

請求參數

欄位	類型	必填	說明
topic	string	否	

欄位	類型	必填	說明
category	string (enum: personal_info, work_role, projects, communication, response_format, tools_tech, interests, health_lifestyle, schedule_plans, other)	否	`personal_info` : Personal Info ; `work_role` : Work and Role ; `projects` : Projects and Work ; `communication` : Communication Preferences ; `response_format` : Response Format Preferences ; `tools_tech` ...
summary	string	否	
details	array[string]	否	
status	string (enum: active, expired)	否	`active` : active ; `expired` : expired;

請求結構範例

```
{
  "topic"?: string // 非必填
  "category"?: string (enum: personal_info, work_role, projects,
communication, response_format, tools_tech, interests, health_lifestyle,
schedule_plans, other) // * `personal_info` - Personal Info
* `work_role` - Work and Role
* `projects` - Projects and Work
* `communication` - Communication Preferences
* `response_format` - Response Format Preferences
* `tools_tech` - Tools and Technology
* `interests` - Interests and Hobbies
* `health_lifestyle` - Health and Lifestyle
* `schedule_plans` - Schedule and Plans
* `other` - Other (非必填)
  "summary"?: string // 非必填
  "details"?: [ // 非必填
    string
  ]
  "status"?: string (enum: active, expired) // * `active` - active
* `expired` - expired (非必填)
}
```

請求範例值

```
{
  "topic": "範例字串",
  "category": "personal_info",
  "summary": "範例字串",
  "details": [
    "範例字串"
  ],
  "status": "active"
}
```

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X PATCH "https://api.maiagent.ai/api/v1/me/memories/550e8400-
e29b-41d4-a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "topic": "範例字串",
    "category": "personal_info",
    "summary": "範例字串",
    "details": [
      "範例字串"
    ],
    "status": "active"
  }'

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// 請求內容 (payload)
const data = {
    "topic": "範例字串",
    "category": "personal_info",
    "summary": "範例字串",
    "details": [
      "範例字串"
    ],
    "status": "active"
  };

axios.patch("https://api.maiagent.ai/api/v1/me/memories/550e8400-
e29b-41d4-a716-446655440000/", data, config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/me/memories/550e8400-e29b-
41d4-a716-446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# 請求內容 (payload)
data = {
    "topic": "範例字串",
    "category": "personal_info",
    "summary": "範例字串",
    "details": [
        "範例字串"
    ],
    "status": "active"
}

response = requests.patch(url, json=data, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>patch("https://api.maiagent.ai/api/v1/me/memories/550e8400-e29b-
41d4-a716-446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'topic' => '範例字串',
            'category' => 'personal_info',
            'summary' => '範例字串',
            'details' => [
                '範例字串'
            ],
            'status' => 'active'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
{
  "id": string (uuid)
  "topic": string // LLM-assigned topic slug for grouping related
memories (e.g. "language_preferences", "role", "communication_style").
Null means legacy memory without topic grouping.
  "category": // 可能有不同的類型
  string (enum: personal_info, work_role, projects, communication,
response_format, tools_tech, interests, health_lifestyle, schedule_plans,
other) // Fixed category shown to users. Null means legacy memory without
a category.

* `personal_info` - Personal Info
* `work_role` - Work and Role
* `projects` - Projects and Work
* `communication` - Communication Preferences
* `response_format` - Response Format Preferences
* `tools_tech` - Tools and Technology
* `interests` - Interests and Hobbies
* `health_lifestyle` - Health and Lifestyle
* `schedule_plans` - Schedule and Plans
* `other` - Other
  "categoryDisplay": string // Translated category name.
  "summary": string // One-line summary of the memory topic.
  "details": object // Concrete facts for this topic, stored as a list of
strings.
  "kind":
  {
  }
  "source":  // How this memory was created: user explicitly stated,
agent extracted, or manually added.

* `user_stated` - User Stated
* `agent_extracted` - Agent Extracted
* `agent_stated` - Agent Stated
* `user_manual` - User Manual
  {
```

```
  }
  "requestedByUser": boolean // True when the user explicitly asked the
agent to remember this. Only affects the UI label (S12), not LRU eviction
priority (S6).
  "status":
  {
  }
  "createdAt": string (timestamp)
  "updatedAt": string (timestamp)
}
```

回應範例值

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "topic": "回應字串",
  "category": "personal_info",
  "categoryDisplay": "回應字串",
  "summary": "回應字串",
  "details": null,
  "kind": {},
  "source": {},
  "requestedByUser": false,
  "status": {},
  "createdAt": "回應字串",
  "updatedAt": "回應字串"
}
```

刪除自己的記憶

DELETE `/api/v1/me/memories/{id}`

請帶 X-Organization-Id 標頭指定要操作的組織，以 API 金鑰呼叫時也要帶。

參數

參數名稱	必填	類型	說明
`id`	V	string	A UUID string identifying this Memory Entry.

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X DELETE "https://api.maiagent.ai/api/v1/me/memories/550e8400-
e29b-41d4-a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

// 請求內容 (payload)
const data = null;

axios.delete("https://api.maiagent.ai/api/v1/me/memories/550e8400-
e29b-41d4-a716-446655440000/", data, config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/me/memories/550e8400-e29b-
41d4-a716-446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.delete(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>delete("https://api.maiagent.ai/api/v1/me/memories/550e8400-e29b-
41d4-a716-446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼	說明
204	No response body

呼叫 API 示例 (Shell)

目錄

1. 列出聯絡人
2. 建立聯絡人
3. 取得聯絡人詳情
4. 更新聯絡人
5. 部分更新聯絡人
6. 刪除聯絡人
7. 取得聯絡人的對話列表
8. 取得聯絡人最新對話
9. 群發訊息
10. 為聯絡人建立 API 憑證
11. 更新聯絡人的 API 憑證
12. 刪除聯絡人的 API 憑證
13. 為聯絡人建立 MCP 憑證
14. 更新聯絡人的 MCP 憑證
15. 刪除聯絡人的 MCP 憑證
16. 下載聯絡人批次匯入範本
17. 批次匯入聯絡人

呼叫 API 示例 (Shell)

列出聯絡人

`GET` `/api/v1/contacts/`

參數

參數名稱	必填	類型	說明
`channels`	X	array	Multiple values may be separated by commas.

`inbox`	X	string	Deprecated: Use inboxes instead
`inboxes`	X	string	對話平台 ID (用於過濾特定 inbox 的聯絡人)
`page`	X	integer	A page number within the paginated result set.
`pageSize`	X	integer	Number of results to return per page.
`query`	X	string	姓名或來源ID搜尋
`search`	X	string	全文搜尋
`tags`	X	array	Multiple values may be separated by commas.

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/contacts/?
channels=example&inbox=550e8400-e29b-41d4-a716-
446655440000&inboxes=example&page=1&pageSize=1&query=example&search=
example&tags=example"

  -H "Authorization: Api-Key YOUR_API_KEY"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/contacts/?
channels=example&inbox=550e8400-e29b-41d4-a716-
446655440000&inboxes=example&page=1&pageSize=1&query=example&search=
example&tags=example", config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/contacts/?
channels=example&inbox=550e8400-e29b-41d4-a716-
446655440000&inboxes=example&page=1&pageSize=1&query=example&search=
example&tags=example"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/contacts/?
channels=example&inbox=550e8400-e29b-41d4-a716-
446655440000&inboxes=example&page=1&pageSize=1&query=example&search=
example&tags=example", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
{
  "count": integer
  "next"?: string (uri) // 非必填
  "previous"?: string (uri) // 非必填
  "results": [
    {
      "id": string (uuid)
      "inboxes"?: [ // 非必填
        {
          "id": string (uuid)
          "name": string
        }
      ]
      "inbox"?:  // 向前相容欄位：單一 inbox，若同時提供 inboxes 則忽略此欄位 (非必填)
      {
        "id": string (uuid)
        "name": string
      }
      "name": string
      "avatar"?: // 可能有不同的類型 (非必填)
      string (uri) // 聯絡人頭像 URL，支援完整 URL 或相對路徑 (非必填)
      "phoneNumber"?: string // 非必填
      "email"?: // 可能有不同的類型 (非必填)
      string (email) // 非必填
      "sourceId"?: string // 非必填
      "queryMetadata"?: { // 查詢元資料，控制可查詢的知識範圍；詳見各端點說明 (非必填)
      {
        "knowledgeBases"?: [ // 可查詢的知識庫清單；空陣列或 null＝全部不可查（無權限），未提供＝不限制 (非必填)
          {
            "knowledgeBaseId": string (uuid) // 知識庫 ID
            "chatbotFileIds"?: [ // 檔案 ID 清單（依 hasUserSelectedAll 決定為排除或僅選取） (非必填)
              string (uuid)
            ]
            "knowledgeBaseFileIds"?: [ // 檔案 ID 清單（chatbotFileIds 的新名稱；兩者皆提供時以本欄位為準） (非必填)
              string (uuid)
            ]
            "faqIds"?: [ // FAQ ID 清單（依 hasUserSelectedAll 決定為排除或僅選取） (非必填)
              string (uuid)
```

```
            ]
            "hasUserSelectedAll"?: boolean // true＝選取知識庫全部內容並排除清單中的項目；false＝僅選取清單中的項目 (非必填)
          }
        ]
        "labelRelations"?: { // 標籤過濾條件；conditions 為空陣列＝不做標籤過濾（並非無權限）。必須與 knowledgeBases 一併提供—單獨提供時知識庫檢索不會套用標籤過濾（等同不限制） (非必填)
        {
          "operator": string (enum: AND, OR) // 標籤條件的組合方式
          "conditions"?: [ // 標籤條件清單，支援巢狀 operator/conditions 組合 (非必填)
            object
          ]
        }
        }
      }
      }
      "metadata"?: object // Custom customer information shown in the customer panel of the conversation page (非必填)
      "mcpCredentials": [ // 聯絡人的 MCP 認證憑證列表
        object
      ]
      "apiCredentials": [ // 聯絡人的 API 認證憑證列表
        object
      ]
      "contactConnectors": [ // 聯絡人的 Connector OAuth 授權列表（不含 token 本體）
        object
      ]
      "tags": [
        {
          "id": string (uuid)
          "name": string
          "createdAt": string (timestamp)
          "updatedAt": string (timestamp)
        }
      ]
      "preChatFieldIndex": object // 來自此 Contact 所屬 inboxes 的 pre-chat form 欄位設定，mapping {field_id: {label: {locale: text}}}，前端用來把 metadata 的 UUID key 解析成顯示名稱
      "createdAt": string (timestamp)
      "updatedAt": string (timestamp)
    }
```

```
  ]
}
```

回應範例值

```
{
  "count": 123,
  "next": "http://api.example.org/accounts/?page=4",
  "previous": "http://api.example.org/accounts/?page=2",
  "results": [
    [
      {
        "id": "user1_uuid",
        "inboxes": [
          {
            "id": "inbox_uuid",
            "name": "inbox_name"
          }
        ],
        "name": "user1",
        "avatar": "",
        "sourceId": null,
        "queryMetadata": null,
        "createdAt": "1751875361000",
        "updatedAt": "1751875361000"
      },
      {
        "id": "user2_uuid",
        "inboxes": [
          {
            "id": "inbox_uuid",
            "name": "inbox_name"
          }
        ],
        "name": "user2",
        "avatar": "avatar_url",
        "sourceId": "self defined source id",
        "queryMetadata": {
          "knowledgeBases": [
            {
              "knowledgeBaseId": "5f8c6a99-5515-43aa-8e83-fdeea327a3a2",
              "hasUserSelectedAll": true
            }
          ],
```

```
          "labelRelations": {
            "operator": "OR",
            "conditions": [
              {
                "labelId": "957998f9-1824-4872-becd-b7f8a7962896"
              }
            ]
          }
        },
        "createdAt": "1751875400000",
        "updatedAt": "1751875400000"
      }
    ]
  ]
}
```


建立聯絡人

POST `/api/v1/contacts/`

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X POST "https://api.maiagent.ai/api/v1/contacts/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "inboxes": [
      {
        "id": "inbox_uuid"
      }
    ],
    "name": "user1",
    "avatar": "",
    "phoneNumber": 912345678,
    "email": "user1@example.com",
    "sourceId": "self defined source id",
    "queryMetadata": {
      "knowledgeBases": [
        {
          "knowledgeBaseId": "5f8c6a99-5515-43aa-8e83-fdeea327a3a2",
          "hasUserSelectedAll": true
        }
      ],
      "labelRelations": {
        "operator": "OR",
        "conditions": [
          {
            "labelId": "957998f9-1824-4872-becd-b7f8a7962896"
          }
        ]
      }
    },
    "metadata": [
      {
        "key": "客戶等級",
        "value": "VIP"
      },
      {
```

```
        "key": "偏好語言",
        "value": "繁體中文"
      }
    ]
  }'

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// 請求內容 (payload)
const data = {
    "inboxes": [
      {
        "id": "inbox_uuid"
      }
    ],
    "name": "user1",
    "avatar": "",
    "phoneNumber": 912345678,
    "email": "user1@example.com",
    "sourceId": "self defined source id",
    "queryMetadata": {
      "knowledgeBases": [
        {
          "knowledgeBaseId": "5f8c6a99-5515-43aa-8e83-fdeea327a3a2",
          "hasUserSelectedAll": true
        }
      ],
      "labelRelations": {
        "operator": "OR",
        "conditions": [
          {
            "labelId": "957998f9-1824-4872-becd-b7f8a7962896"
          }
        ]
      }
    },
    "metadata": [
      {
```

```
        "key": "客戶等級",
        "value": "VIP"
      },
      {
        "key": "偏好語言",
        "value": "繁體中文"
      }
    ]
  };

axios.post("https://api.maiagent.ai/api/v1/contacts/", data, config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/contacts/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# 請求內容 (payload)
data = {
    "inboxes": [
        {
            "id": "inbox_uuid"
        }
    ],
    "name": "user1",
    "avatar": "",
    "phoneNumber": 912345678,
    "email": "user1@example.com",
    "sourceId": "self defined source id",
    "queryMetadata": {
        "knowledgeBases": [
            {
                "knowledgeBaseId": "5f8c6a99-5515-43aa-8e83-
fdeea327a3a2",
                "hasUserSelectedAll": True
            }
        ],
        "labelRelations": {
            "operator": "OR",
            "conditions": [
                {
                    "labelId": "957998f9-1824-4872-becd-
b7f8a7962896"
                }
            ]
        }
    },
    "metadata": [
        {
```

```
            "key": "客戶等級",
            "value": "VIP"
        },
        {
            "key": "偏好語言",
            "value": "繁體中文"
        }
    ]
}

response = requests.post(url, json=data, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>post("https://api.maiagent.ai/api/v1/contacts/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'inboxes' => [
                [
                    'id' => 'inbox_uuid'
                ]
            ],
            'name' => 'user1',
            'avatar' => '',
            'phoneNumber' => 912345678,
            'email' => 'user1@example.com',
            'sourceId' => 'self defined source id',
            'queryMetadata' => [
                'knowledgeBases' => [
                    [
                        'knowledgeBaseId' => '5f8c6a99-5515-43aa-
8e83-fdeea327a3a2',
                        'hasUserSelectedAll' => true
                    ]
                ],
                'labelRelations' => [
                    'operator' => 'OR',
                    'conditions' => [
                        [
                            'labelId' => '957998f9-1824-4872-becd-
b7f8a7962896'
                        ]
                    ]
                ]
```

```
                ],
                'metadata' => [
                    [
                        'key' => '客戶等級',
                        'value' => 'VIP'
                    ],
                    [
                        'key' => '偏好語言',
                        'value' => '繁體中文'
                    ]
                ]
            ]
        ]);

        $data = json_decode($response->getBody(), true);
        echo "成功取得回應:\n";
        print_r($data);
    } catch (Exception $e) {
        echo '請求發生錯誤: ' . $e->getMessage();
    }
    ?>
```

回應內容

狀態碼: 201

回應結構範例

```
{
  "id": string (uuid)
  "inboxes"?: [ // 非必填
    {
      "id": string (uuid)
      "name": string
    }
  ]
  "inbox"?:  // 向前相容欄位：單一 inbox，若同時提供 inboxes 則忽略此欄位 (非必
```

```
填)
  {
    "id": string (uuid)
    "name": string
  }
  "name": string
  "avatar"?: // 可能有不同的類型 (非必填)
  string (uri) // 聯絡人頭像 URL，支援完整 URL 或相對路徑 (非必填)
  "phoneNumber"?: string // 非必填
  "email"?: // 可能有不同的類型 (非必填)
  string (email) // 非必填
  "sourceId"?: string // 非必填
  "queryMetadata"?: { // 查詢元資料，控制可查詢的知識範圍；詳見各端點說明 (非必填)
  {
    "knowledgeBases"?: [ // 可查詢的知識庫清單；空陣列或 null＝全部不可查（無權限），未提供＝不限制 (非必填)
      {
        "knowledgeBaseId": string (uuid) // 知識庫 ID
        "chatbotFileIds"?: [ // 檔案 ID 清單（依 hasUserSelectedAll 決定為排除或僅選取） (非必填)
          string (uuid)
        ]
        "knowledgeBaseFileIds"?: [ // 檔案 ID 清單（chatbotFileIds 的新名稱；兩者皆提供時以本欄位為準） (非必填)
          string (uuid)
        ]
        "faqIds"?: [ // FAQ ID 清單（依 hasUserSelectedAll 決定為排除或僅選取） (非必填)
          string (uuid)
        ]
        "hasUserSelectedAll"?: boolean // true＝選取知識庫全部內容並排除清單中的項目；false＝僅選取清單中的項目 (非必填)
      }
    ]
    "labelRelations"?: { // 標籤過濾條件；conditions 為空陣列＝不做標籤過濾（並非無權限）。必須與 knowledgeBases 一併提供—單獨提供時知識庫檢索不會套用標籤過濾（等同不限制） (非必填)
    {
      "operator": string (enum: AND, OR) // 標籤條件的組合方式
      "conditions"?: [ // 標籤條件清單，支援巢狀 operator/conditions 組合 (非必填)
        object
      ]
    }
    }
```

```
  }
  }
  "metadata"?: object // Custom customer information shown in the
customer panel of the conversation page (非必填)
  "mcpCredentials": [ // 聯絡人的 MCP 認證憑證列表
    object
  ]
  "apiCredentials": [ // 聯絡人的 API 認證憑證列表
    object
  ]
  "contactConnectors": [ // 聯絡人的 Connector OAuth 授權列表（不含 token 本
體）
    object
  ]
  "tags": [
    {
      "id": string (uuid)
      "name": string
      "createdAt": string (timestamp)
      "updatedAt": string (timestamp)
    }
  ]
  "preChatFieldIndex": object // 來自此 Contact 所屬 inboxes 的 pre-chat
form 欄位設定，mapping {field_id: {label: {locale: text}}}，前端用來把
metadata 的 UUID key 解析成顯示名稱
  "createdAt": string (timestamp)
  "updatedAt": string (timestamp)
}
```

回應範例值

```
{
  "id": "user1_uuid",
  "inboxes": [
    {
      "id": "inbox_uuid",
      "name": "inbox_name"
    }
  ],
  "name": "user1",
  "avatar": "",
  "phoneNumber": 912345678,
  "email": "user1@example.com",
  "sourceId": null,
```

```
  "queryMetadata": null,
  "createdAt": "1751875361000",
  "updatedAt": "1751875361000"
}
```


取得聯絡人詳情

GET `/api/v1/contacts/{id}`

參數

參數名稱	必填	類型	說明
id	V	string	A UUID string identifying this Contact.

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/contacts/550e8400-e29b-
41d4-a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/contacts/550e8400-e29b-
41d4-a716-446655440000/", config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/contacts/550e8400-e29b-41d4-
a716-446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/contacts/550e8400-e29b-41d4-
a716-446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
{
  "id": string (uuid)
  "inboxes"?: [ // 非必填
```

```
    {
      "id": string (uuid)
      "name": string
    }
  ]
  "inbox"?:  // 向前相容欄位：單一 inbox，若同時提供 inboxes 則忽略此欄位 (非必填)
  {
    "id": string (uuid)
    "name": string
  }
  "name": string
  "avatar"?: // 可能有不同的類型 (非必填)
  string (uri) // 聯絡人頭像 URL，支援完整 URL 或相對路徑 (非必填)
  "phoneNumber"?: string // 非必填
  "email"?: // 可能有不同的類型 (非必填)
  string (email) // 非必填
  "sourceId"?: string // 非必填
  "queryMetadata"?: { // 查詢元資料，控制可查詢的知識範圍；詳見各端點說明 (非必填)
  {
    "knowledgeBases"?: [ // 可查詢的知識庫清單；空陣列或 null＝全部不可查（無權限），未提供＝不限制 (非必填)
      {
        "knowledgeBaseId": string (uuid) // 知識庫 ID
        "chatbotFileIds"?: [ // 檔案 ID 清單（依 hasUserSelectedAll 決定為排除或僅選取） (非必填)
          string (uuid)
        ]
        "knowledgeBaseFileIds"?: [ // 檔案 ID 清單（chatbotFileIds 的新名稱；兩者皆提供時以本欄位為準） (非必填)
          string (uuid)
        ]
        "faqIds"?: [ // FAQ ID 清單（依 hasUserSelectedAll 決定為排除或僅選取） (非必填)
          string (uuid)
        ]
        "hasUserSelectedAll"?: boolean // true＝選取知識庫全部內容並排除清單中的項目；false＝僅選取清單中的項目 (非必填)
      }
    ]
    "labelRelations"?: { // 標籤過濾條件；conditions 為空陣列＝不做標籤過濾（並非無權限）。必須與 knowledgeBases 一併提供——單獨提供時知識庫檢索不會套用標籤過濾（等同不限制） (非必填)
    {
      "operator": string (enum: AND, OR) // 標籤條件的組合方式
```

```
      "conditions"?: [ // 標籤條件清單，支援巢狀 operator/conditions 組合 (非必填)
        object
      ]
    }
    }
  }
  }
  "metadata"?: object // Custom customer information shown in the customer panel of the conversation page (非必填)
  "mcpCredentials": [ // 聯絡人的 MCP 認證憑證列表
    object
  ]
  "apiCredentials": [ // 聯絡人的 API 認證憑證列表
    object
  ]
  "contactConnectors": [ // 聯絡人的 Connector OAuth 授權列表（不含 token 本體）
    object
  ]
  "tags": [
    {
      "id": string (uuid)
      "name": string
      "createdAt": string (timestamp)
      "updatedAt": string (timestamp)
    }
  ]
  "preChatFieldIndex": object // 來自此 Contact 所屬 inboxes 的 pre-chat form 欄位設定，mapping {field_id: {label: {locale: text}}}，前端用來把 metadata 的 UUID key 解析成顯示名稱
  "createdAt": string (timestamp)
  "updatedAt": string (timestamp)
}
```

回應範例值

```
{
  "id": "user1_uuid",
  "inboxes": [
    {
      "id": "inbox_uuid",
      "name": "inbox_name"
    }
```

```
  ],
  "name": "user1",
  "avatar": "",
  "phoneNumber": 912345678,
  "email": "user1@example.com",
  "sourceId": null,
  "queryMetadata": null,
  "createdAt": "1751875361000",
  "updatedAt": "1751875361000"
}
```


更新聯絡人

PUT `/api/v1/contacts/{id}`

參數

參數名稱	必填	類型	說明
id	V	string	A UUID string identifying this Contact.

請求內容

請求參數

欄位	類型	必填	說明
name	string	否	聯絡人姓名
inboxes	array[object]	否	對話平台列表（新版格式）

欄位	類型	必填	說明
inbox	object	否	單一對話平台（舊版格式，向前相容）
inbox.id	string (uuid)	是	對話平台 ID
avatar	string	否	頭像URL
phoneNumber	string	否	聯絡人電話號碼
email	string (email)	否	聯絡人電子信箱
sourceId	string	否	來源ID
queryMetadata	object	否	查詢元資料（Query Metadata），控制可查詢的知識範圍。未提供或 null＝未設定（不限制）；空物件 {}＝視同不限制（全選），並非無權限；knowledgeBases 為空陣列或 null＝全部不可查（無權限）；labelRelations.conditions 為空陣列＝不做標籤過濾（並非無權限）。詳見本端點說明。
queryMetadata.knowledgeBases	array[object]	否	可查詢的知識庫清單；空陣列或 null＝全部不可查（無權限），未提供＝不限制
queryMetadata.labelRelations	object	否	標籤過濾條件；conditions 為空陣列＝不做標籤過濾（並非無權限）。必須與 knowledgeBases 一併提供——單獨提供時知識庫檢索不會套用標籤過濾（等同不限制）
queryMetadata.labelRelations.operator	string (enum: AND,	是	標籤條件的組合方式

欄位	類型	必填	說明
	OR)		
queryMetadata.labelRelations.conditions	array[any]	否	標籤條件清單，支援巢狀 operator/conditions 組合
metadata	array[object]	否	自訂聯絡人屬性列表

請求結構範例

```
{
  "name"?: string // 聯絡人姓名 (非必填)
  "inboxes"?: [ // 對話平台列表（新版格式） (非必填)
    {
      "id": string (uuid) // 對話平台 ID
    }
  ]
  "inbox"?: { // 單一對話平台（舊版格式，向前相容） (非必填)
  {
    "id": string (uuid) // 對話平台 ID
  }
  }
  "avatar"?: string // 頭像URL (非必填)
  "phoneNumber"?: string // 聯絡人電話號碼 (非必填)
  "email"?: string (email) // 聯絡人電子信箱 (非必填)
  "sourceId"?: string // 來源ID (非必填)
  "queryMetadata"?: { // 查詢元資料（Query Metadata），控制可查詢的知識範圍。未提供或 null＝未設定（不限制）；空物件 {}＝視同不限制（全選），並非無權限；knowledgeBases 為空陣列或 null＝全部不可查（無權限）；labelRelations.conditions 為空陣列＝不做標籤過濾（並非無權限）。詳見本端點說明。 (非必填)
  {
    "knowledgeBases"?: [ // 可查詢的知識庫清單；空陣列或 null＝全部不可查（無權限），未提供＝不限制 (非必填)
      {
        "knowledgeBaseId": string (uuid) // 知識庫 ID
        "chatbotFileIds"?: [ // 檔案 ID 清單（依 hasUserSelectedAll 決定為排除或僅選取） (非必填)
          string (uuid)
        ]
        "knowledgeBaseFileIds"?: [ // 檔案 ID 清單（chatbotFileIds 的新名稱；兩者皆提供時以本欄位為準） (非必填)
          string (uuid)
        ]
```

```
        "faqIds"?: [ // FAQ ID 清單（依 hasUserSelectedAll 決定為排除或僅選取）（非必填）
          string (uuid)
        ]
        "hasUserSelectedAll"?: boolean // true＝選取知識庫全部內容並排除清單中的項目；false＝僅選取清單中的項目 (非必填)
      }
    ]
    "labelRelations"?: { // 標籤過濾條件；conditions 為空陣列＝不做標籤過濾（並非無權限）。必須與 knowledgeBases 一併提供—單獨提供時知識庫檢索不會套用標籤過濾（等同不限制） (非必填)
    {
      "operator": string (enum: AND, OR) // 標籤條件的組合方式
      "conditions"?: [ // 標籤條件清單，支援巢狀 operator/conditions 組合 (非必填)
        object
      ]
    }
    }
  }
  }
  "metadata"?: [ // 自訂聯絡人屬性列表 (非必填)
    {
      "key": string // 屬性名稱
      "value": string // 屬性值
      "updatedAt"?: string // 更新時間（ISO 格式，可選，未提供則自動填入） (非必填)
    }
  ]
}
```

請求範例值

```
{
  "inboxes": [
    {
      "id": "new_inbox_uuid"
    }
  ],
  "name": "updated_user_name",
  "avatar": "updated_avatar_url",
  "phoneNumber": 987654321,
  "email": "updated@example.com",
  "sourceId": "updated_source_id",
```

```
  "queryMetadata": {
    "knowledgeBases": []
  },
  "metadata": [
    {
      "key": "客戶等級",
      "value": "VVIP"
    },
    {
      "key": "偏好語言",
      "value": "日本語"
    }
  ]
}
```

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X PUT "https://api.maiagent.ai/api/v1/contacts/550e8400-e29b-
41d4-a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "inboxes": [
      {
        "id": "new_inbox_uuid"
      }
    ],
    "name": "updated_user_name",
    "avatar": "updated_avatar_url",
    "phoneNumber": 987654321,
    "email": "updated@example.com",
    "sourceId": "updated_source_id",
    "queryMetadata": {
      "knowledgeBases": []
    },
    "metadata": [
      {
        "key": "客戶等級",
        "value": "VVIP"
      },
      {
        "key": "偏好語言",
        "value": "日本語"
      }
    ]
  }'

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// 請求內容 (payload)
const data = {
    "inboxes": [
      {
        "id": "new_inbox_uuid"
      }
    ],
    "name": "updated_user_name",
    "avatar": "updated_avatar_url",
    "phoneNumber": 987654321,
    "email": "updated@example.com",
    "sourceId": "updated_source_id",
    "queryMetadata": {
      "knowledgeBases": []
    },
    "metadata": [
      {
        "key": "客戶等級",
        "value": "VVIP"
      },
      {
        "key": "偏好語言",
        "value": "日本語"
      }
    ]
  };

axios.put("https://api.maiagent.ai/api/v1/contacts/550e8400-e29b-
41d4-a716-446655440000/", data, config)
  .then(response => {
```

```
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.log('請求發生錯誤:');
    console.log(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/contacts/550e8400-e29b-41d4-
a716-446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# 請求內容 (payload)
data = {
    "inboxes": [
        {
            "id": "new_inbox_uuid"
        }
    ],
    "name": "updated_user_name",
    "avatar": "updated_avatar_url",
    "phoneNumber": 987654321,
    "email": "updated@example.com",
    "sourceId": "updated_source_id",
    "queryMetadata": {
        "knowledgeBases": []
    },
    "metadata": [
        {
            "key": "客戶等級",
            "value": "VVIP"
        },
        {
            "key": "偏好語言",
            "value": "日本語"
        }
    ]
}

response = requests.put(url, json=data, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
```

```
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>put("https://api.maiagent.ai/api/v1/contacts/550e8400-e29b-41d4-
a716-446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'inboxes' => [
                [
                    'id' => 'new_inbox_uuid'
                ]
            ],
            'name' => 'updated_user_name',
            'avatar' => 'updated_avatar_url',
            'phoneNumber' => 987654321,
            'email' => 'updated@example.com',
            'sourceId' => 'updated_source_id',
            'queryMetadata' => [
                'knowledgeBases' => []
            ],
            'metadata' => [
                [
                    'key' => '客戶等級',
                    'value' => 'VVIP'
                ],
                [
                    'key' => '偏好語言',
                    'value' => '日本語'
                ]
            ]
        ]
    ]);
```

```
        $data = json_decode($response->getBody(), true);
        echo "成功取得回應:\n";
        print_r($data);
    } catch (Exception $e) {
        echo '請求發生錯誤: ' . $e->getMessage();
    }
    ?>
```

回應內容

狀態碼: 200

回應結構範例

```
{
  "id": string (uuid)
  "inboxes"?: [ // 非必填
    {
      "id": string (uuid)
      "name": string
    }
  ]
  "inbox"?:  // 向前相容欄位：單一 inbox，若同時提供 inboxes 則忽略此欄位 (非必填)
  {
    "id": string (uuid)
    "name": string
  }
  "name": string
  "avatar"?: // 可能有不同的類型 (非必填)
  string (uri) // 聯絡人頭像 URL，支援完整 URL 或相對路徑 (非必填)
  "phoneNumber"?: string // 非必填
  "email"?: // 可能有不同的類型 (非必填)
  string (email) // 非必填
  "sourceId"?: string // 非必填
  "queryMetadata"?: { // 查詢元資料，控制可查詢的知識範圍；詳見各端點說明 (非必填)
  {
```

```
    "knowledgeBases"?: [ // 可查詢的知識庫清單；空陣列或 null＝全部不可查（無權限），未提供＝不限制 (非必填)
      {
        "knowledgeBaseId": string (uuid) // 知識庫 ID
        "chatbotFileIds"?: [ // 檔案 ID 清單（依 hasUserSelectedAll 決定為排除或僅選取） (非必填)
          string (uuid)
        ]
        "knowledgeBaseFileIds"?: [ // 檔案 ID 清單（chatbotFileIds 的新名稱；兩者皆提供時以本欄位為準） (非必填)
          string (uuid)
        ]
        "faqIds"?: [ // FAQ ID 清單（依 hasUserSelectedAll 決定為排除或僅選取） (非必填)
          string (uuid)
        ]
        "hasUserSelectedAll"?: boolean // true＝選取知識庫全部內容並排除清單中的項目；false＝僅選取清單中的項目 (非必填)
      }
    ]
    "labelRelations"?: { // 標籤過濾條件；conditions 為空陣列＝不做標籤過濾（並非無權限）。必須與 knowledgeBases 一併提供—單獨提供時知識庫檢索不會套用標籤過濾（等同不限制） (非必填)
    {
      "operator": string (enum: AND, OR) // 標籤條件的組合方式
      "conditions"?: [ // 標籤條件清單，支援巢狀 operator/conditions 組合 (非必填)
        object
      ]
    }
    }
  }
  }
  "metadata"?: object // Custom customer information shown in the customer panel of the conversation page (非必填)
  "mcpCredentials": [ // 聯絡人的 MCP 認證憑證列表
    object
  ]
  "apiCredentials": [ // 聯絡人的 API 認證憑證列表
    object
  ]
  "contactConnectors": [ // 聯絡人的 Connector OAuth 授權列表（不含 token 本體）
    object
  ]
```

```
  "tags": [
    {
      "id": string (uuid)
      "name": string
      "createdAt": string (timestamp)
      "updatedAt": string (timestamp)
    }
  ]
  "preChatFieldIndex": object // 來自此 Contact 所屬 inboxes 的 pre-chat form 欄位設定，mapping {field_id: {label: {locale: text}}}，前端用來把 metadata 的 UUID key 解析成顯示名稱
  "createdAt": string (timestamp)
  "updatedAt": string (timestamp)
}
```

回應範例值

```
{
  "id": "user1_uuid",
  "inboxes": [
    {
      "id": "inbox_uuid",
      "name": "inbox_name"
    }
  ],
  "name": "user1",
  "avatar": "",
  "phoneNumber": 912345678,
  "email": "user1@example.com",
  "sourceId": null,
  "queryMetadata": null,
  "createdAt": "1751875361000",
  "updatedAt": "1751875361000"
}
```

部分更新聯絡人

PATCH `/api/v1/contacts/{id}`

參數

參數名稱	必填	類型	說明
`id`	V	string	A UUID string identifying this Contact.

請求內容

請求參數

欄位	類型	必填	說明
name	string	否	聯絡人姓名
inboxes	array[object]	否	對話平台列表（新版格式）
inbox	object	否	單一對話平台（舊版格式，向前相容）
inbox.id	string (uuid)	是	對話平台 ID
avatar	string	否	頭像URL
phoneNumber	string	否	聯絡人電話號碼
email	string (email)	否	聯絡人電子信箱
sourceId	string	否	來源ID
queryMetadata	object	否	查詢元資料（Query Metadata），控制可查詢的知識範圍。未提供或 null＝未設定（不限制）；空物件 {}＝視同不限制（全選），並非無權限；knowledgeBases 為空陣

欄位	類型	必填	說明
			列或 null＝全部不可查（無權限）；labelRelations.conditions 為空陣列＝不做標籤過濾（並非無權限）。詳見本端點說明。
queryMetadata.knowledgeBases	array[object]	否	可查詢的知識庫清單；空陣列或 null＝全部不可查（無權限），未提供＝不限制
queryMetadata.labelRelations	object	否	標籤過濾條件；conditions 為空陣列＝不做標籤過濾（並非無權限）。必須與 knowledgeBases 一併提供——單獨提供時知識庫檢索不會套用標籤過濾（等同不限制）
queryMetadata.labelRelations.operator	string (enum: AND, OR)	是	標籤條件的組合方式
queryMetadata.labelRelations.conditions	array[any]	否	標籤條件清單，支援巢狀 operator/conditions 組合
metadata	array[object]	否	自訂聯絡人屬性列表

請求結構範例

```
{
  "name"?: string // 聯絡人姓名（非必填）
  "inboxes"?: [ // 對話平台列表（新版格式）（非必填）
    {
      "id": string (uuid) // 對話平台 ID
    }
  ]
  "inbox"?: { // 單一對話平台（舊版格式，向前相容）（非必填）
  {
    "id": string (uuid) // 對話平台 ID
  }
```

```
  }
  "avatar"?: string // 頭像URL (非必填)
  "phoneNumber"?: string // 聯絡人電話號碼 (非必填)
  "email"?: string (email) // 聯絡人電子信箱 (非必填)
  "sourceId"?: string // 來源ID (非必填)
  "queryMetadata"?: { // 查詢元資料（Query Metadata），控制可查詢的知識範圍。未提供或 null＝未設定（不限制）；空物件 {}＝視同不限制（全選），並非無權限；knowledgeBases 為空陣列或 null＝全部不可查（無權限）；labelRelations.conditions 為空陣列＝不做標籤過濾（並非無權限）。詳見本端點說明。 (非必填)
  {
    "knowledgeBases"?: [ // 可查詢的知識庫清單；空陣列或 null＝全部不可查（無權限），未提供＝不限制 (非必填)
      {
        "knowledgeBaseId": string (uuid) // 知識庫 ID
        "chatbotFileIds"?: [ // 檔案 ID 清單（依 hasUserSelectedAll 決定為排除或僅選取） (非必填)
          string (uuid)
        ]
        "knowledgeBaseFileIds"?: [ // 檔案 ID 清單（chatbotFileIds 的新名稱；兩者皆提供時以本欄位為準） (非必填)
          string (uuid)
        ]
        "faqIds"?: [ // FAQ ID 清單（依 hasUserSelectedAll 決定為排除或僅選取） (非必填)
          string (uuid)
        ]
        "hasUserSelectedAll"?: boolean // true＝選取知識庫全部內容並排除清單中的項目；false＝僅選取清單中的項目 (非必填)
      }
    ]
    "labelRelations"?: { // 標籤過濾條件；conditions 為空陣列＝不做標籤過濾（並非無權限）。必須與 knowledgeBases 一併提供—單獨提供時知識庫檢索不會套用標籤過濾（等同不限制） (非必填)
    {
      "operator": string (enum: AND, OR) // 標籤條件的組合方式
      "conditions"?: [ // 標籤條件清單，支援巢狀 operator/conditions 組合 (非必填)
        object
      ]
    }
    }
  }
  }
  "metadata"?: [ // 自訂聯絡人屬性列表 (非必填)
    {
```

```
      "key": string // 屬性名稱
      "value": string // 屬性值
      "updatedAt"?: string // 更新時間（ISO 格式，可選，未提供則自動填入）（非必
填）
    }
  ]
}
```

請求範例值

```
{
  "inboxes": [
    {
      "id": "new_inbox_uuid"
    }
  ],
  "name": "updated_user_name",
  "avatar": "updated_avatar_url",
  "phoneNumber": 987654321,
  "email": "updated@example.com",
  "sourceId": "updated_source_id",
  "queryMetadata": {
    "knowledgeBases": []
  },
  "metadata": [
    {
      "key": "客戶等級",
      "value": "VVIP"
    },
    {
      "key": "偏好語言",
      "value": "日本語"
    }
  ]
}
```

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X PATCH "https://api.maiagent.ai/api/v1/contacts/550e8400-
e29b-41d4-a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "inboxes": [
      {
        "id": "new_inbox_uuid"
      }
    ],
    "name": "updated_user_name",
    "avatar": "updated_avatar_url",
    "phoneNumber": 987654321,
    "email": "updated@example.com",
    "sourceId": "updated_source_id",
    "queryMetadata": {
      "knowledgeBases": []
    },
    "metadata": [
      {
        "key": "客戶等級",
        "value": "VVIP"
      },
      {
        "key": "偏好語言",
        "value": "日本語"
      }
    ]
  }'

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// 請求內容 (payload)
const data = {
    "inboxes": [
      {
        "id": "new_inbox_uuid"
      }
    ],
    "name": "updated_user_name",
    "avatar": "updated_avatar_url",
    "phoneNumber": 987654321,
    "email": "updated@example.com",
    "sourceId": "updated_source_id",
    "queryMetadata": {
      "knowledgeBases": []
    },
    "metadata": [
      {
        "key": "客戶等級",
        "value": "VVIP"
      },
      {
        "key": "偏好語言",
        "value": "日本語"
      }
    ]
  };

axios.patch("https://api.maiagent.ai/api/v1/contacts/550e8400-e29b-
41d4-a716-446655440000/", data, config)
  .then(response => {
```

```
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.log('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/contacts/550e8400-e29b-41d4-
a716-446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# 請求內容 (payload)
data = {
    "inboxes": [
        {
            "id": "new_inbox_uuid"
        }
    ],
    "name": "updated_user_name",
    "avatar": "updated_avatar_url",
    "phoneNumber": 987654321,
    "email": "updated@example.com",
    "sourceId": "updated_source_id",
    "queryMetadata": {
        "knowledgeBases": []
    },
    "metadata": [
        {
            "key": "客戶等級",
            "value": "VVIP"
        },
        {
            "key": "偏好語言",
            "value": "日本語"
        }
    ]
}

response = requests.patch(url, json=data, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
```

```
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>patch("https://api.maiagent.ai/api/v1/contacts/550e8400-e29b-41d4-
a716-446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'inboxes' => [
                [
                    'id' => 'new_inbox_uuid'
                ]
            ],
            'name' => 'updated_user_name',
            'avatar' => 'updated_avatar_url',
            'phoneNumber' => 987654321,
            'email' => 'updated@example.com',
            'sourceId' => 'updated_source_id',
            'queryMetadata' => [
                'knowledgeBases' => []
            ],
            'metadata' => [
                [
                    'key' => '客戶等級',
                    'value' => 'VVIP'
                ],
                [
                    'key' => '偏好語言',
                    'value' => '日本語'
                ]
            ]
        ]
    ]);
```

```
    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
{
  "id": string (uuid)
  "inboxes"?: [ // 非必填
    {
      "id": string (uuid)
      "name": string
    }
  ]
  "inbox"?:  // 向前相容欄位：單一 inbox，若同時提供 inboxes 則忽略此欄位 (非必填)
  {
    "id": string (uuid)
    "name": string
  }
  "name": string
  "avatar"?: // 可能有不同的類型 (非必填)
  string (uri) // 聯絡人頭像 URL，支援完整 URL 或相對路徑 (非必填)
  "phoneNumber"?: string // 非必填
  "email"?: // 可能有不同的類型 (非必填)
  string (email) // 非必填
  "sourceId"?: string // 非必填
  "queryMetadata"?: { // 查詢元資料，控制可查詢的知識範圍；詳見各端點說明 (非必填)
  {
```

```
    "knowledgeBases"?: [ // 可查詢的知識庫清單；空陣列或 null＝全部不可查（無權限），未提供＝不限制 (非必填)
      {
        "knowledgeBaseId": string (uuid) // 知識庫 ID
        "chatbotFileIds"?: [ // 檔案 ID 清單（依 hasUserSelectedAll 決定為排除或僅選取） (非必填)
          string (uuid)
        ]
        "knowledgeBaseFileIds"?: [ // 檔案 ID 清單（chatbotFileIds 的新名稱；兩者皆提供時以本欄位為準） (非必填)
          string (uuid)
        ]
        "faqIds"?: [ // FAQ ID 清單（依 hasUserSelectedAll 決定為排除或僅選取） (非必填)
          string (uuid)
        ]
        "hasUserSelectedAll"?: boolean // true＝選取知識庫全部內容並排除清單中的項目；false＝僅選取清單中的項目 (非必填)
      }
    ]
    "labelRelations"?: { // 標籤過濾條件；conditions 為空陣列＝不做標籤過濾（並非無權限）。必須與 knowledgeBases 一併提供—單獨提供時知識庫檢索不會套用標籤過濾（等同不限制） (非必填)
    {
      "operator": string (enum: AND, OR) // 標籤條件的組合方式
      "conditions"?: [ // 標籤條件清單，支援巢狀 operator/conditions 組合 (非必填)
        object
      ]
    }
    }
  }
  }
  "metadata"?: object // Custom customer information shown in the customer panel of the conversation page (非必填)
  "mcpCredentials": [ // 聯絡人的 MCP 認證憑證列表
    object
  ]
  "apiCredentials": [ // 聯絡人的 API 認證憑證列表
    object
  ]
  "contactConnectors": [ // 聯絡人的 Connector OAuth 授權列表（不含 token 本體）
    object
  ]
```

```
  "tags": [
    {
      "id": string (uuid)
      "name": string
      "createdAt": string (timestamp)
      "updatedAt": string (timestamp)
    }
  ]
  "preChatFieldIndex": object // 來自此 Contact 所屬 inboxes 的 pre-chat form 欄位設定，mapping {field_id: {label: {locale: text}}}，前端用來把 metadata 的 UUID key 解析成顯示名稱
  "createdAt": string (timestamp)
  "updatedAt": string (timestamp)
}
```

回應範例值

```
{
  "id": "user1_uuid",
  "inboxes": [
    {
      "id": "inbox_uuid",
      "name": "inbox_name"
    }
  ],
  "name": "user1",
  "avatar": "",
  "phoneNumber": 912345678,
  "email": "user1@example.com",
  "sourceId": null,
  "queryMetadata": null,
  "createdAt": "1751875361000",
  "updatedAt": "1751875361000"
}
```

刪除聯絡人

DELETE `/api/v1/contacts/{id}`

參數

參數名稱	必填	類型	說明
`id`	V	string	A UUID string identifying this Contact.

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X DELETE "https://api.maiagent.ai/api/v1/contacts/550e8400-
e29b-41d4-a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

// 請求內容 (payload)
const data = null;

axios.delete("https://api.maiagent.ai/api/v1/contacts/550e8400-e29b-
41d4-a716-446655440000/", data, config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/contacts/550e8400-e29b-41d4-
a716-446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.delete(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>delete("https://api.maiagent.ai/api/v1/contacts/550e8400-e29b-41d4-
a716-446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼	說明
204	No response body
400	聯絡人還有關聯的對話，無法刪除

取得聯絡人的對話列表

`GET` `/api/v1/contacts/{id}/conversations/`

參數

參數名稱	必填	類型	說明
`id`	V	string	A UUID string identifying this Contact.
`channels`	X	array	Multiple values may be separated by commas.
`inbox`	X	string	按單一 inbox ID 過濾（UUID 格式）
`inboxes`	X	string	按多個 inbox IDs 過濾（逗號分隔，如：uuid1,uuid2 或使用多個 inboxes 參數）
`keyword`	X	string	搜尋對話中的訊息內容（不區分大小寫）
`page`	X	integer	A page number within the paginated result set.
`pageSize`	X	integer	Number of results to return per page.
`query`	X	string	
`tags`	X	array	Multiple values may be separated by commas.

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/contacts/550e8400-e29b-
41d4-a716-446655440000/conversations/?
channels=example&inbox=example&inboxes=example&keyword=example&page=
1&pageSize=1&query=example&tags=example"

  -H "Authorization: Api-Key YOUR_API_KEY"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/contacts/550e8400-e29b-
41d4-a716-446655440000/conversations/?
channels=example&inbox=example&inboxes=example&keyword=example&page=
1&pageSize=1&query=example&tags=example", config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/contacts/550e8400-e29b-41d4-
a716-446655440000/conversations/?
channels=example&inbox=example&inboxes=example&keyword=example&page=
1&pageSize=1&query=example&tags=example"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/contacts/550e8400-e29b-41d4-
a716-446655440000/conversations/?
channels=example&inbox=example&inboxes=example&keyword=example&page=
1&pageSize=1&query=example&tags=example", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
{
  "count": integer
  "next"?: string (uri) // 非必填
  "previous"?: string (uri) // 非必填
  "results": [
    {
      "id": string (uuid)
      "contact": { // 輕量級 Contact Serializer，用於 Conversation List
view

只包含 List view 必要的欄位，移除 inboxes、mcp_credentials 和 api_credentials
以避免 N+1 查詢問題。email / phone_number / metadata 為 Contact 自身的純量欄
位，
前端對話側欄需要顯示，無 N+1 成本。
      {
        "id": string (uuid)
        "name": string
        "avatar"?: string // Stores our own media as a relative storage
key, or an external CDN URL as-is. (非必填)
        "email"?: // 可能有不同的類型 (非必填)
        string (email) // 非必填
        "phoneNumber"?: string // 非必填
        "metadata"?: object // Custom customer information shown in the
customer panel of the conversation page (非必填)
        "sourceId"?: string // 非必填
        "tags": [
          {
            "id": string (uuid)
            "name": string
          }
        ]
      }
      }
      "inbox": { // Inbox summary embedded in a conversation payload.

``unread_conversations_count`` stays here because it is part of the
documented REST conversation API. It is an org-wide denormalized
counter, so WS emit paths must run the payload through
:func:`strip_org_wide_unread_count` before broadcasting it to rooms
that include members without ``GroupInbox.can_view_conversations``.
      {
        "id": string (uuid)
        "name": string
        "channelType": string (enum: line, telegram, teams, web,
```

```
messenger, instagram, email, whatsapp, slack, team_plus, line_works,
viber) // * `line` - LINE
* `telegram` - Telegram
* `teams` - Teams
* `web` - Web
* `messenger` - Messenger
* `instagram` - Instagram
* `email` - Email
* `whatsapp` - WhatsApp
* `slack` - Slack
* `team_plus` - Team+
* `line_works` - LINE WORKS
* `viber` - Viber
        "unreadConversationsCount"?: integer // 非必填
        "signAuth"?:  // 非必填
        {
          "id": string (uuid)
          "signSource": string (uuid)
          "signParams": {
          {
            "keycloak":
            {
              "clientId": string
              "url": string
              "realm": string
            }
            "line":
            {
              "liffId": string
            }
            "ad":
            {
              "saml": string
            }
            "google"?:  // 非必填
            {
              "enabled": boolean
            }
          }
          }
          "sourceIdAccessEnabled"?: boolean // When enabled, embedded
visitors presenting a Source ID (verified per the verify mode below) may
chat without going through the login flow. Disabled keeps every existing
behavior unchanged. (非必填)
          "sourceIdVerifyMode"?:  // "Require signature verification":
```

```
the embedding site must send an HMAC signature computed on its backend.
"Source ID only": anyone knowing a Source ID can act as that contact;
suitable only for testing or closed networks.

* `signature` - Require signature verification
* `raw` - Source ID only (非必填)
          {
          }
          "sourceIdSignatureTtlMinutes"?:  // How long a signature can be
used to obtain the contact identity. Not a session lifetime: once
exchanged, the session follows the existing WebChat mechanism.

* `1` - 1
* `5` - 5
* `15` - 15 (非必填)
          {
          }
          "keycloakTokenPassthrough"?: boolean // When enabled, the
Keycloak access token a visitor logged in with is forwarded as the
Authorization header when the AI calls MCP and API tools on their behalf,
so tools do not require a separate per-tool login. Only for the Keycloak
sign source. Never overrides an Authorization header a tool already
resolves from its own credentials. The visitor identity is the
organization member bound to the conversation at login, never the contact
Source ID. (非必填)
          "keycloakTokenPassthroughAllowedHosts"?: [ // Hostnames (or
"*.example.com" wildcards) of the tools the visitor Keycloak token may be
sent to (非必填)
            string
          ]
        }
        "enableAnalysis"?: boolean // 非必填
      }
      }
      "chatbot": object // Chatbot (Agent) summary from the
conversation's inbox, already eager-loaded.

``is_maigpt`` lets the client tell the default MaiGPT agent apart (icon,
feature
gate) without comparing against the organization's ``maigpt_inbox`` id;
``file_workspace_mode`` is the effective P6 mode (MaiGPT, blueprint and
the
organization's file-library switch already applied).
      "title": string
      "lastMessage"?: { // 非必填
```

```
      {
        "id": string (uuid)
        "type"?: string // 非必填
        "content"?: string // 非必填
        "createdAt": string (timestamp)
      }
      }
      "callRecord":
      {
        "id": string (uuid)
        "status"?: string (enum: initiated, ringing, in-progress,
completed, failed, busy, no-answer, canceled) // * `initiated` -
Initiated
* `ringing` - Ringing
* `in-progress` - In Progress
* `completed` - Completed
* `failed` - Failed
* `busy` - Busy
* `no-answer` - No Answer
* `canceled` - Canceled (非必填)
        "direction": string (enum: inbound, outbound) // * `inbound` -
Inbound
* `outbound` - Outbound
        "isActive": boolean
        "canHangup": boolean
      }
      "lastMessageCreatedAt": string (timestamp)
      "unreadMessagesCount": integer
      "autoReplyEnabled": boolean
      "isAutoReplyNow": boolean
      "willAiReplyNow": boolean // Whether a text message arriving
through the inbox gets an AI reply right now.

The messaging channels are gated by ``is_auto_reply_now`` (auto reply on
and inside the
inbox auto-reply schedule) and by the inbox having a chatbot. The
chatbot's API web chat
is answered by the completions endpoint, which ignores the schedule, so
there the
conversation switch alone decides. The channel is only looked up for a
web inbox outside
its schedule.

Surfaces that ignore the schedule on any inbox answer from their own rule
instead: the
```

```
completions endpoint continuing an existing conversation
(``completions_progress_status``)
and voice turns, which the voice agent answers.
      "lastReadAt": string (timestamp)
      "createdAt": string (timestamp)
      "isGroupChat": boolean
      "enableGroupMention"?: boolean // 非必填
      "queryMetadata"?: { // 查詢元資料，控制可查詢的知識範圍；詳見各端點說明 (非
必填)
      {
        "knowledgeBases"?: [ // 可查詢的知識庫清單；空陣列或 null＝全部不可查（無
權限），未提供＝不限制 (非必填)
          {
            "knowledgeBaseId": string (uuid) // 知識庫 ID
            "chatbotFileIds"?: [ // 檔案 ID 清單（依 hasUserSelectedAll 決定
為排除或僅選取） (非必填)
              string (uuid)
            ]
            "knowledgeBaseFileIds"?: [ // 檔案 ID 清單（chatbotFileIds 的新
名稱；兩者皆提供時以本欄位為準） (非必填)
              string (uuid)
            ]
            "faqIds"?: [ // FAQ ID 清單（依 hasUserSelectedAll 決定為排除或僅
選取） (非必填)
              string (uuid)
            ]
            "hasUserSelectedAll"?: boolean // true＝選取知識庫全部內容並排除清
單中的項目；false＝僅選取清單中的項目 (非必填)
          }
        ]
        "labelRelations"?: { // 標籤過濾條件；conditions 為空陣列＝不做標籤過濾
（並非無權限）。必須與 knowledgeBases 一併提供——單獨提供時知識庫檢索不會套用標籤過濾
（等同不限制） (非必填)
        {
          "operator": string (enum: AND, OR) // 標籤條件的組合方式
          "conditions"?: [ // 標籤條件清單，支援巢狀 operator/conditions 組合
(非必填)
            object
          ]
        }
        }
      }
      }
      "toolMask"?: object // Enabled/disabled state per tool: {tool_id:
bool} (非必填)
```

```
      "connectorMask"?: object // Enabled/disabled state per connector:
{connector_id: bool} (非必填)
      "thinkingConfig"?: object // None = not set (inherit the chatbot
setting); otherwise {"reasoning_effort": <level>} (非必填)
      "thinkingConfigSchema": { // 此模型的思考設定表單；null 表示此模型沒有思考
設定
      {
        "type"?: string // 表單類型，固定為 reasoning_effort (非必填)
        "fields"?: object // reasoning_effort 欄位：options 列出此模型接受的
思考等級（由弱到強），default 固定為 null (非必填)
        "canDisable"?: boolean // 此模型能否關閉思考；true 時 options 含 off
(非必填)
        "unsetBehavior"?: string (enum: off, model_default) // 對話與助理都
沒設思考等級時的實際行為：off＝不思考（最快）；model_default＝模型自行思考，或平台預設
等級會開啟思考 (非必填)
        "unsetLevel"?: string // 沒設等級時平台實際送出的等級；null 表示不送思考
參數，交給模型自身預設 (非必填)
      }
      }
      "effectiveThinkingConfig": object // The level the next reply sends
on this conversation's model, after gating and clamping.

The stored choice resolves conversation > chatbot > the LLM row's default
level; None means
the model sends no thinking parameter, so the provider default applies.
      "llm": string (uuid) // The model the next reply runs on: the
conversation's pin, else its assistant's current model.

TC-0205: returning the stored ``conversation.llm`` would show a model an
unpinned conversation no
longer uses once its assistant switches model, while
``thinking_config_schema`` already follows the
effective model. Read-only: displaying it never marks the conversation as
explicitly selected;
only the update-llm endpoint does.
      "deepResearchStatus":  // Status of deep research for this
conversation

* `not_used` - Not Used
* `started` - Started
* `running` - Running
* `completed` - Completed
* `failed` - Failed
      {
      }
```

```
      "deepResearchOutputFormat": // 可能有不同的類型
      string (enum: canvas, chat, file) // Chosen delivery form for the
finished report. Set only when the user clicks a format in the pre-
research choice card; reset to NULL each time Deep Research is
(re-)armed. NULL means no explicit choice (or a plan-skipping request)
and falls back to Canvas at render time, but stays distinct from an
explicit canvas pick so the frontend can lock the card only after a real
selection. To roll back to fixed-Canvas behavior, force this to
NULL/canvas — no redeploy needed.

* `canvas` - Canvas
* `chat` - Chat reply
* `file` - Downloadable file
      "ipAddress": string
      "ipCountryCode": string
      "ipRecordedAt": string (timestamp)
      "assignee":
      {
        "id": string (uuid)
        "name": string
        "userId": string (uuid)
      }
      "status"?: string (enum: open, resolved, queued) // * `open` - Open
* `resolved` - Resolved
* `queued` - Queued (非必填)
      "tags": [
        {
          "id": string (uuid)
          "name": string
          "memberIds"?: [ // 非必填
            string (uuid)
          ]
        }
      ]
      "progressStatus": string
      "firstResponseAt"?: string (timestamp) // 非必填
      "queuedAt"?: string (timestamp) // 非必填
      "assignedAt"?: string (timestamp) // 非必填
      "transferReason"?: string // 非必填
      "satisfactionScore": integer // Conversation satisfaction rating on
a 5-point scale (1=very dissatisfied, 5=very satisfied)
      "satisfactionComment": string
      "satisfactionSubmittedAt": string (timestamp)
      "latestAnalysisSummary": string // The conversation's current
analysis summary (its active summary revision).
```

```
Reads the `latest_analysis_summary` annotation added by
`setup_eager_loading`
to avoid an N+1 query. All read paths (list / retrieve / create) eager-
load,
so the annotation is present; it falls back to '' only for instances
built
outside `setup_eager_loading`.
      "clientPlatform":  // Client platform that created this
conversation (web, desktop)

* `web` - Web
* `desktop` - Desktop
      {
      }
      "workingDirectory": string // Absolute path of the local folder
bound to a desktop conversation. Only set for desktop conversations; null
for web conversations.
      "slideProjectId": string
      "matchedField": string // Cached per instance:
``get_matched_message_id`` / ``get_matched_snippet``
both read this, so resolving it once avoids recomputing the keyword and
title-match logic three times per serialized conversation.
      "matchedSnippet": string // Keyword-centred excerpt of the matched
message, with ellipses.

Reads the ``matched_message_content`` annotation added by
``ConversationViewSet._annotate_keyword_match``; no extra query.
      "matchedMessageId": string
      "pinnedAt": string (timestamp) // When the conversation was pinned.
Null means unpinned.
      "folder": string (uuid) // The user-defined sidebar folder this
conversation is grouped into. Null means unclassified (shown under the
time groups). Deleting the folder resets this to null without deleting
the conversation.
      "hasActiveBrowserSession": boolean // Whether a browser_use session
snapshot exists to resume.

Lets the frontend know it should proactively re-request the browser
panel (emit ``browser:start``) after a page reload, instead of only
ever showing the panel when a live ``browser:frame`` push happens to
arrive first.
      "callerOrganizationId": string // Bound caller organization
(stamped at conversation start); null when unbound
      "handoff": object // 交接資訊：enabled=平台開關；接續對話帶
```

```
source_conversation_id/source_title；被交接的原對話帶
continued_to_conversation_id/continued_to_title 與
latest_summary_message_id
      "displayContextUsage": boolean // 是否顯示上下文使用量百分比條（對話平台開
關，MaiGPT 恆為 true；與交接開關互相獨立）
    }
  ]
}
```

回應範例值


```
{
  "count": 123,
  "next": "http://api.example.org/accounts/?page=4",
  "previous": "http://api.example.org/accounts/?page=2",
  "results": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "contact": {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "name": "回應字串",
        "avatar": "回應字串",
        "email": "response@example.com",
        "phoneNumber": "回應字串",
        "metadata": null,
        "sourceId": "回應字串",
        "tags": [
          {
            "id": "550e8400-e29b-41d4-a716-446655440000",
            "name": "回應字串"
          }
        ]
      },
      "inbox": {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "name": "回應字串",
        "channelType": "line",
        "unreadConversationsCount": 456,
        "signAuth": {
          "id": "550e8400-e29b-41d4-a716-446655440000",
          "signSource": "550e8400-e29b-41d4-a716-446655440000",
          "signParams": {
            "keycloak": {
              "clientId": "回應字串",
```

```
            "url": "回應字串",
            "realm": "回應字串"
          },
          "line": {
            "liffId": "回應字串"
          },
          "ad": {
            "saml": "回應字串"
          },
          "google": {
            "enabled": false
          }
        },
        "sourceIdAccessEnabled": false,
        "sourceIdVerifyMode": {},
        "sourceIdSignatureTtlMinutes": {},
        "keycloakTokenPassthrough": false,
        "keycloakTokenPassthroughAllowedHosts": [
          "回應字串"
        ]
      },
      "enableAnalysis": false
    },
    "chatbot": {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "回應範例名稱",
      "description": "回應範例描述"
    },
    "title": "回應字串",
    "lastMessage": {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "type": "回應字串",
      "content": "回應字串",
      "createdAt": "回應字串"
    },
    "callRecord": {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "status": "initiated",
      "direction": "inbound",
      "isActive": false,
      "canHangup": false
    },
    "lastMessageCreatedAt": "回應字串",
    "unreadMessagesCount": 456,
    "autoReplyEnabled": false,
```

```
      "isAutoReplyNow": false,
      "willAiReplyNow": false,
      "lastReadAt": "回應字串",
      "createdAt": "回應字串",
      "isGroupChat": false,
      "enableGroupMention": false,
      "queryMetadata": {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "name": "回應範例名稱",
        "description": "回應範例描述"
      },
      "toolMask": null,
      "connectorMask": null,
      "thinkingConfig": null,
      "thinkingConfigSchema": {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "name": "回應範例名稱",
        "description": "回應範例描述"
      },
      "effectiveThinkingConfig": {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "name": "回應範例名稱",
        "description": "回應範例描述"
      },
      "llm": "550e8400-e29b-41d4-a716-446655440000",
      "deepResearchStatus": {},
      "deepResearchOutputFormat": "canvas",
      "ipAddress": "回應字串",
      "ipCountryCode": "回應字串",
      "ipRecordedAt": "回應字串",
      "assignee": {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "name": "回應字串",
        "userId": "550e8400-e29b-41d4-a716-446655440000"
      },
      "status": "open",
      "tags": [
        {
          "id": "550e8400-e29b-41d4-a716-446655440000",
          "name": "回應字串",
          "memberIds": [
            "550e8400-e29b-41d4-a716-446655440000"
          ]
        }
      ],
```

```
      "progressStatus": "回應字串",
      "firstResponseAt": "回應字串",
      "queuedAt": "回應字串",
      "assignedAt": "回應字串",
      "transferReason": "回應字串",
      "satisfactionScore": 456,
      "satisfactionComment": "回應字串",
      "satisfactionSubmittedAt": "回應字串",
      "latestAnalysisSummary": "回應字串",
      "clientPlatform": {},
      "workingDirectory": "回應字串",
      "slideProjectId": "回應字串",
      "matchedField": "回應字串",
      "matchedSnippet": "回應字串",
      "matchedMessageId": "回應字串",
      "pinnedAt": "回應字串",
      "folder": "550e8400-e29b-41d4-a716-446655440000",
      "hasActiveBrowserSession": false,
      "callerOrganizationId": "回應字串",
      "handoff": {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "name": "回應範例名稱",
        "description": "回應範例描述"
      },
      "displayContextUsage": false
    }
  ]
}
```


取得聯絡人最新對話

`GET` `/api/v1/contacts/{id}/conversations/latest/`

參數

參數名稱	必填	類型	說明

`id`	V	string	A UUID string identifying this Contact.
`inbox`	X	string	按單一 inbox ID 過濾（UUID 格式）
`inboxes`	X	string	按多個 inbox IDs 過濾（逗號分隔，如：uuid1,uuid2 或使用多個 inboxes 參數）
`keyword`	X	string	搜尋對話中的訊息內容（不區分大小寫）

程式碼範例

Shell/Bash

```
# 呼叫 API 示例（Shell）
curl -X GET "https://api.maiagent.ai/api/v1/contacts/550e8400-e29b-
41d4-a716-446655440000/conversations/latest/?
inbox=example&inboxes=example&keyword=example"

  -H "Authorization: Api-Key YOUR_API_KEY"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/contacts/550e8400-e29b-
41d4-a716-446655440000/conversations/latest/?
inbox=example&inboxes=example&keyword=example", config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/contacts/550e8400-e29b-41d4-
a716-446655440000/conversations/latest/?
inbox=example&inboxes=example&keyword=example"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/contacts/550e8400-e29b-41d4-
a716-446655440000/conversations/latest/?
inbox=example&inboxes=example&keyword=example", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
{
  "id": string (uuid)
```

```
  "contact": { // 輕量級 Contact Serializer，用於 Conversation List view

只包含 List view 必要的欄位，移除 inboxes、mcp_credentials 和 api_credentials
以避免 N+1 查詢問題。email / phone_number / metadata 為 Contact 自身的純量欄
位，
前端對話側欄需要顯示，無 N+1 成本。
  {
    "id": string (uuid)
    "name": string
    "avatar"?: string // Stores our own media as a relative storage key,
or an external CDN URL as-is. (非必填)
    "email"?: // 可能有不同的類型 (非必填)
    string (email) // 非必填
    "phoneNumber"?: string // 非必填
    "metadata"?: object // Custom customer information shown in the
customer panel of the conversation page (非必填)
    "sourceId"?: string // 非必填
    "tags": [
      {
        "id": string (uuid)
        "name": string
      }
    ]
  }
  }
  "inbox": { // Inbox summary embedded in a conversation payload.

``unread_conversations_count`` stays here because it is part of the
documented REST conversation API. It is an org-wide denormalized
counter, so WS emit paths must run the payload through
:func:`strip_org_wide_unread_count` before broadcasting it to rooms
that include members without ``GroupInbox.can_view_conversations``.
  {
    "id": string (uuid)
    "name": string
    "channelType": string (enum: line, telegram, teams, web, messenger,
instagram, email, whatsapp, slack, team_plus, line_works, viber) // *
`line` - LINE
* `telegram` - Telegram
* `teams` - Teams
* `web` - Web
* `messenger` - Messenger
* `instagram` - Instagram
* `email` - Email
* `whatsapp` - WhatsApp
```

```
* `slack` - Slack
* `team_plus` - Team+
* `line_works` - LINE WORKS
* `viber` - Viber
    "unreadConversationsCount"?: integer // 非必填
    "signAuth"?:  // 非必填
    {
      "id": string (uuid)
      "signSource": string (uuid)
      "signParams": {
      {
        "keycloak":
        {
          "clientId": string
          "url": string
          "realm": string
        }
        "line":
        {
          "liffId": string
        }
        "ad":
        {
          "saml": string
        }
        "google"?:  // 非必填
        {
          "enabled": boolean
        }
      }
      }
      "sourceIdAccessEnabled"?: boolean // When enabled, embedded
visitors presenting a Source ID (verified per the verify mode below) may
chat without going through the login flow. Disabled keeps every existing
behavior unchanged. (非必填)
      "sourceIdVerifyMode"?:  // "Require signature verification": the
embedding site must send an HMAC signature computed on its backend.
"Source ID only": anyone knowing a Source ID can act as that contact;
suitable only for testing or closed networks.

* `signature` - Require signature verification
* `raw` - Source ID only (非必填)
      {
      }
      "sourceIdSignatureTtlMinutes"?:  // How long a signature can be
```

```
used to obtain the contact identity. Not a session lifetime: once
exchanged, the session follows the existing WebChat mechanism.

* `1` - 1
* `5` - 5
* `15` - 15 (非必填)
      {
      }
      "keycloakTokenPassthrough"?: boolean // When enabled, the Keycloak
access token a visitor logged in with is forwarded as the Authorization
header when the AI calls MCP and API tools on their behalf, so tools do
not require a separate per-tool login. Only for the Keycloak sign source.
Never overrides an Authorization header a tool already resolves from its
own credentials. The visitor identity is the organization member bound to
the conversation at login, never the contact Source ID. (非必填)
      "keycloakTokenPassthroughAllowedHosts"?: [ // Hostnames (or
"*.example.com" wildcards) of the tools the visitor Keycloak token may be
sent to (非必填)
        string
      ]
    }
    "enableAnalysis"?: boolean // 非必填
  }
  }
  "chatbot": object // Chatbot (Agent) summary from the conversation's
inbox, already eager-loaded.

``is_maigpt`` lets the client tell the default MaiGPT agent apart (icon,
feature
gate) without comparing against the organization's ``maigpt_inbox`` id;
``file_workspace_mode`` is the effective P6 mode (MaiGPT, blueprint and
the
organization's file-library switch already applied).
  "title": string
  "lastMessage"?: { // 非必填
  {
    "id": string (uuid)
    "type"?: string // 非必填
    "content"?: string // 非必填
    "createdAt": string (timestamp)
  }
  }
  "callRecord":
  {
    "id": string (uuid)
```

```
    "status"?: string (enum: initiated, ringing, in-progress, completed,
failed, busy, no-answer, canceled) // * `initiated` - Initiated
* `ringing` - Ringing
* `in-progress` - In Progress
* `completed` - Completed
* `failed` - Failed
* `busy` - Busy
* `no-answer` - No Answer
* `canceled` - Canceled (非必填)
    "direction": string (enum: inbound, outbound) // * `inbound` -
Inbound
* `outbound` - Outbound
    "isActive": boolean
    "canHangup": boolean
  }
  "lastMessageCreatedAt": string (timestamp)
  "unreadMessagesCount": integer
  "autoReplyEnabled": boolean
  "isAutoReplyNow": boolean
  "willAiReplyNow": boolean // Whether a text message arriving through
the inbox gets an AI reply right now.

The messaging channels are gated by ``is_auto_reply_now`` (auto reply on
and inside the
inbox auto-reply schedule) and by the inbox having a chatbot. The
chatbot's API web chat
is answered by the completions endpoint, which ignores the schedule, so
there the
conversation switch alone decides. The channel is only looked up for a
web inbox outside
its schedule.

Surfaces that ignore the schedule on any inbox answer from their own rule
instead: the
completions endpoint continuing an existing conversation
(``completions_progress_status``)
and voice turns, which the voice agent answers.
  "lastReadAt": string (timestamp)
  "createdAt": string (timestamp)
  "isGroupChat": boolean
  "enableGroupMention"?: boolean // 非必填
  "queryMetadata"?: { // 查詢元資料，控制可查詢的知識範圍；詳見各端點說明 (非必填)
  {
    "knowledgeBases"?: [ // 可查詢的知識庫清單；空陣列或 null＝全部不可查（無權
限），未提供＝不限制 (非必填)
```

```
      {
        "knowledgeBaseId": string (uuid) // 知識庫 ID
        "chatbotFileIds"?: [ // 檔案 ID 清單（依 hasUserSelectedAll 決定為排除或僅選取）（非必填）
          string (uuid)
        ]
        "knowledgeBaseFileIds"?: [ // 檔案 ID 清單（chatbotFileIds 的新名稱；兩者皆提供時以本欄位為準）（非必填）
          string (uuid)
        ]
        "faqIds"?: [ // FAQ ID 清單（依 hasUserSelectedAll 決定為排除或僅選取）（非必填）
          string (uuid)
        ]
        "hasUserSelectedAll"?: boolean // true＝選取知識庫全部內容並排除清單中的項目；false＝僅選取清單中的項目（非必填）
      }
    ]
    "labelRelations"?: { // 標籤過濾條件；conditions 為空陣列＝不做標籤過濾（並非無權限）。必須與 knowledgeBases 一併提供—單獨提供時知識庫檢索不會套用標籤過濾（等同不限制）（非必填）
    {
      "operator": string (enum: AND, OR) // 標籤條件的組合方式
      "conditions"?: [ // 標籤條件清單，支援巢狀 operator/conditions 組合（非必填）
        object
      ]
    }
    }
  }
  }
  "toolMask"?: object // Enabled/disabled state per tool: {tool_id: bool} (非必填)
  "connectorMask"?: object // Enabled/disabled state per connector: {connector_id: bool} (非必填)
  "thinkingConfig"?: object // None = not set (inherit the chatbot setting); otherwise {"reasoning_effort": <level>} (非必填)
  "thinkingConfigSchema": { // 此模型的思考設定表單；null 表示此模型沒有思考設定
  {
    "type"?: string // 表單類型，固定為 reasoning_effort (非必填)
    "fields"?: object // reasoning_effort 欄位：options 列出此模型接受的思考等級（由弱到強），default 固定為 null (非必填)
    "canDisable"?: boolean // 此模型能否關閉思考；true 時 options 含 off (非必填)
    "unsetBehavior"?: string (enum: off, model_default) // 對話與助理都沒設
```

```
思考等級時的實際行為：off＝不思考（最快）；model_default＝模型自行思考，或平台預設等級會開啟思考 (非必填)
    "unsetLevel"?: string // 沒設等級時平台實際送出的等級；null 表示不送思考參數，交給模型自身預設 (非必填)
  }
  }
  "effectiveThinkingConfig": object // The level the next reply sends on this conversation's model, after gating and clamping.

The stored choice resolves conversation > chatbot > the LLM row's default level; None means
the model sends no thinking parameter, so the provider default applies.
  "llm": string (uuid) // The model the next reply runs on: the conversation's pin, else its assistant's current model.

TC-0205: returning the stored ``conversation.llm`` would show a model an unpinned conversation no
longer uses once its assistant switches model, while
``thinking_config_schema`` already follows the
effective model. Read-only: displaying it never marks the conversation as explicitly selected;
only the update-llm endpoint does.
  "deepResearchStatus":  // Status of deep research for this conversation

* `not_used` - Not Used
* `started` - Started
* `running` - Running
* `completed` - Completed
* `failed` - Failed
  {
  }
  "deepResearchOutputFormat": // 可能有不同的類型
  string (enum: canvas, chat, file) // Chosen delivery form for the finished report. Set only when the user clicks a format in the pre-research choice card; reset to NULL each time Deep Research is (re-)armed. NULL means no explicit choice (or a plan-skipping request) and falls back to Canvas at render time, but stays distinct from an explicit canvas pick so the frontend can lock the card only after a real selection. To roll back to fixed-Canvas behavior, force this to NULL/canvas — no redeploy needed.

* `canvas` - Canvas
* `chat` - Chat reply
* `file` - Downloadable file
  "ipAddress": string
```

```
  "ipCountryCode": string
  "ipRecordedAt": string (timestamp)
  "assignee":
  {
    "id": string (uuid)
    "name": string
    "userId": string (uuid)
  }
  "status"?: string (enum: open, resolved, queued) // * `open` - Open
* `resolved` - Resolved
* `queued` - Queued (非必填)
  "tags": [
    {
      "id": string (uuid)
      "name": string
      "memberIds"?: [ // 非必填
        string (uuid)
      ]
    }
  ]
  "progressStatus": string
  "firstResponseAt"?: string (timestamp) // 非必填
  "queuedAt"?: string (timestamp) // 非必填
  "assignedAt"?: string (timestamp) // 非必填
  "transferReason"?: string // 非必填
  "satisfactionScore": integer // Conversation satisfaction rating on a
5-point scale (1=very dissatisfied, 5=very satisfied)
  "satisfactionComment": string
  "satisfactionSubmittedAt": string (timestamp)
  "latestAnalysisSummary": string // The conversation's current analysis
summary (its active summary revision).

Reads the `latest_analysis_summary` annotation added by
`setup_eager_loading`
to avoid an N+1 query. All read paths (list / retrieve / create) eager-
load,
so the annotation is present; it falls back to '' only for instances
built
outside `setup_eager_loading`.
  "clientPlatform":  // Client platform that created this conversation
(web, desktop)

* `web` - Web
* `desktop` - Desktop
  {
```

```
  }
  "workingDirectory": string // Absolute path of the local folder bound
to a desktop conversation. Only set for desktop conversations; null for
web conversations.
  "slideProjectId": string
  "matchedField": string // Cached per instance:
``get_matched_message_id`` / ``get_matched_snippet``
both read this, so resolving it once avoids recomputing the keyword and
title-match logic three times per serialized conversation.
  "matchedSnippet": string // Keyword-centred excerpt of the matched
message, with ellipses.

Reads the ``matched_message_content`` annotation added by
``ConversationViewSet._annotate_keyword_match``; no extra query.
  "matchedMessageId": string
  "pinnedAt": string (timestamp) // When the conversation was pinned.
Null means unpinned.
  "folder": string (uuid) // The user-defined sidebar folder this
conversation is grouped into. Null means unclassified (shown under the
time groups). Deleting the folder resets this to null without deleting
the conversation.
  "hasActiveBrowserSession": boolean // Whether a browser_use session
snapshot exists to resume.

Lets the frontend know it should proactively re-request the browser
panel (emit ``browser:start``) after a page reload, instead of only
ever showing the panel when a live ``browser:frame`` push happens to
arrive first.
  "callerOrganizationId": string // Bound caller organization (stamped at
conversation start); null when unbound
  "handoff": object // 交接資訊：enabled=平台開關；接續對話帶
source_conversation_id/source_title；被交接的原對話帶
continued_to_conversation_id/continued_to_title 與
latest_summary_message_id
  "displayContextUsage": boolean // 是否顯示上下文使用量百分比條（對話平台開關，
MaiGPT 恆為 true；與交接開關互相獨立）
}
```

回應範例值

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "contact": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
```

```
    "name": "回應字串",
    "avatar": "回應字串",
    "email": "response@example.com",
    "phoneNumber": "回應字串",
    "metadata": null,
    "sourceId": "回應字串",
    "tags": [
      {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "name": "回應字串"
      }
    ]
  },
  "inbox": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應字串",
    "channelType": "line",
    "unreadConversationsCount": 456,
    "signAuth": {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "signSource": "550e8400-e29b-41d4-a716-446655440000",
      "signParams": {
        "keycloak": {
          "clientId": "回應字串",
          "url": "回應字串",
          "realm": "回應字串"
        },
        "line": {
          "liffId": "回應字串"
        },
        "ad": {
          "saml": "回應字串"
        },
        "google": {
          "enabled": false
        }
      },
      "sourceIdAccessEnabled": false,
      "sourceIdVerifyMode": {},
      "sourceIdSignatureTtlMinutes": {},
      "keycloakTokenPassthrough": false,
      "keycloakTokenPassthroughAllowedHosts": [
        "回應字串"
      ]
    },
```

```
    "enableAnalysis": false
  },
  "chatbot": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應範例名稱",
    "description": "回應範例描述"
  },
  "title": "回應字串",
  "lastMessage": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "type": "回應字串",
    "content": "回應字串",
    "createdAt": "回應字串"
  },
  "callRecord": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "status": "initiated",
    "direction": "inbound",
    "isActive": false,
    "canHangup": false
  },
  "lastMessageCreatedAt": "回應字串",
  "unreadMessagesCount": 456,
  "autoReplyEnabled": false,
  "isAutoReplyNow": false,
  "willAiReplyNow": false,
  "lastReadAt": "回應字串",
  "createdAt": "回應字串",
  "isGroupChat": false,
  "enableGroupMention": false,
  "queryMetadata": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應範例名稱",
    "description": "回應範例描述"
  },
  "toolMask": null,
  "connectorMask": null,
  "thinkingConfig": null,
  "thinkingConfigSchema": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應範例名稱",
    "description": "回應範例描述"
  },
  "effectiveThinkingConfig": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
```

```
    "name": "回應範例名稱",
    "description": "回應範例描述"
  },
  "llm": "550e8400-e29b-41d4-a716-446655440000",
  "deepResearchStatus": {},
  "deepResearchOutputFormat": "canvas",
  "ipAddress": "回應字串",
  "ipCountryCode": "回應字串",
  "ipRecordedAt": "回應字串",
  "assignee": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應字串",
    "userId": "550e8400-e29b-41d4-a716-446655440000"
  },
  "status": "open",
  "tags": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "回應字串",
      "memberIds": [
        "550e8400-e29b-41d4-a716-446655440000"
      ]
    }
  ],
  "progressStatus": "回應字串",
  "firstResponseAt": "回應字串",
  "queuedAt": "回應字串",
  "assignedAt": "回應字串",
  "transferReason": "回應字串",
  "satisfactionScore": 456,
  "satisfactionComment": "回應字串",
  "satisfactionSubmittedAt": "回應字串",
  "latestAnalysisSummary": "回應字串",
  "clientPlatform": {},
  "workingDirectory": "回應字串",
  "slideProjectId": "回應字串",
  "matchedField": "回應字串",
  "matchedSnippet": "回應字串",
  "matchedMessageId": "回應字串",
  "pinnedAt": "回應字串",
  "folder": "550e8400-e29b-41d4-a716-446655440000",
  "hasActiveBrowserSession": false,
  "callerOrganizationId": "回應字串",
  "handoff": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
```

```
    "name": "回應範例名稱",
    "description": "回應範例描述"
  },
  "displayContextUsage": false
}
```

狀態碼: 404 - No response body

群發訊息

POST `/api/v1/contacts/broadcast-message/`

請求內容

請求參數

欄位	類型	必填	說明
contactIds	array[string]	否	[正向指定模式] 要發送訊息的 contact ID 列表
inboxId	string (uuid)	否	[反向排除/全部發送模式] Inbox ID，會發送給該 inbox 下的所有 contacts
excludeContactIds	array[string]	否	[反向排除模式] 要排除的 contact ID 列表，需配合 inbox_id 使用
message	string	是	要發送的訊息內容

請求結構範例

```
{
  "contactIds"?: [ // [正向指定模式] 要發送訊息的 contact ID 列表 (非必填)
    string (uuid)
  ]
  "inboxId"?: string (uuid) // [反向排除/全部發送模式] Inbox ID，會發送給該
```

```
inbox 下的所有 contacts (非必填)
  "excludeContactIds"?: [ // [反向排除模式] 要排除的 contact ID 列表，需配合
inbox_id 使用 (非必填)
    string (uuid)
  ]
  "message": string // 要發送的訊息內容
}
```

請求範例值

```
{
  "contactIds": [
    "550e8400-e29b-41d4-a716-446655440000"
  ],
  "inboxId": "550e8400-e29b-41d4-a716-446655440000",
  "excludeContactIds": [
    "550e8400-e29b-41d4-a716-446655440000"
  ],
  "message": "這是一個範例訊息"
}
```

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X POST "https://api.maiagent.ai/api/v1/contacts/broadcast-
message/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "contactIds": [
      "550e8400-e29b-41d4-a716-446655440000"
    ],
    "inboxId": "550e8400-e29b-41d4-a716-446655440000",
    "excludeContactIds": [
      "550e8400-e29b-41d4-a716-446655440000"
    ],
    "message": "這是一個範例訊息"
  }'

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// 請求內容 (payload)
const data = {
    "contactIds": [
      "550e8400-e29b-41d4-a716-446655440000"
    ],
    "inboxId": "550e8400-e29b-41d4-a716-446655440000",
    "excludeContactIds": [
      "550e8400-e29b-41d4-a716-446655440000"
    ],
    "message": "這是一個範例訊息"
  };

axios.post("https://api.maiagent.ai/api/v1/contacts/broadcast-
message/", data, config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/contacts/broadcast-message/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# 請求內容 (payload)
data = {
    "contactIds": [
        "550e8400-e29b-41d4-a716-446655440000"
    ],
    "inboxId": "550e8400-e29b-41d4-a716-446655440000",
    "excludeContactIds": [
        "550e8400-e29b-41d4-a716-446655440000"
    ],
    "message": "這是一個範例訊息"
}

response = requests.post(url, json=data, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>post("https://api.maiagent.ai/api/v1/contacts/broadcast-message/",
[
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'contactIds' => [
                '550e8400-e29b-41d4-a716-446655440000'
            ],
            'inboxId' => '550e8400-e29b-41d4-a716-446655440000',
            'excludeContactIds' => [
                '550e8400-e29b-41d4-a716-446655440000'
            ],
            'message' => '這是一個範例訊息'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
{
  "results"?: [ // 非必填
    {
      "contactId"?: string (uuid) // 非必填
      "conversationId"?: string (uuid) // 非必填
      "messageId"?: string (uuid) // 非必填
      "status"?: string // 非必填
    }
  ]
  "errors"?: [ // 非必填
    {
      "contactId"?: string (uuid) // 非必填
      "error"?: string // 非必填
    }
  ]
  "totalContacts"?: integer // 非必填
  "successCount"?: integer // 非必填
  "errorCount"?: integer // 非必填
}
```

回應範例值

```
{
  "results": [
    {
      "contactId": "550e8400-e29b-41d4-a716-446655440000",
      "conversationId": "550e8400-e29b-41d4-a716-446655440000",
      "messageId": "550e8400-e29b-41d4-a716-446655440000",
      "status": "success"
    }
  ],
  "errors": [
    {
      "contactId": "550e8400-e29b-41d4-a716-446655440000",
      "error": "回應字串"
```

```
    }
  ],
  "totalContacts": 456,
  "successCount": 456,
  "errorCount": 456
}
```

為聯絡人建立 API 憑證

POST `/api/v1/contacts/{id}/api-credentials/`

讓 Agent 以該聯絡人的身分呼叫您的 API 工具。流程見技術手冊聯絡人憑證同步。

參數

參數名稱	必填	類型	說明
`id`	V	string	A UUID string identifying this Contact.

請求內容

請求參數

欄位	類型	必填	說明
tool	string (uuid)	是	API 工具的 ID
headers	object	否	認證標頭字典

請求結構範例

```
{
  "tool": string (uuid) // API 工具的 ID
  "headers"?: object // 認證標頭字典 (非必填)
}
```

請求範例值

```
{
  "tool": "550e8400-e29b-41d4-a716-446655440000",
  "headers": {}
}
```

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X POST "https://api.maiagent.ai/api/v1/contacts/550e8400-e29b-41d4-a716-446655440000/api-credentials/"
  -H "Authorization: Api-Key YOUR_API_KEY"
  -H "Content-Type: application/json"
  -d '{
    "tool": "550e8400-e29b-41d4-a716-446655440000",
    "headers": {}
  }'

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// 請求內容 (payload)
const data = {
    "tool": "550e8400-e29b-41d4-a716-446655440000",
    "headers": {}
  };

axios.post("https://api.maiagent.ai/api/v1/contacts/550e8400-e29b-
41d4-a716-446655440000/api-credentials/", data, config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/contacts/550e8400-e29b-41d4-
a716-446655440000/api-credentials/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# 請求內容 (payload)
data = {
    "tool": "550e8400-e29b-41d4-a716-446655440000",
    "headers": {}
}

response = requests.post(url, json=data, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>post("https://api.maiagent.ai/api/v1/contacts/550e8400-e29b-41d4-
a716-446655440000/api-credentials/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'tool' => '550e8400-e29b-41d4-a716-446655440000',
            'headers' => new \stdClass()
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 201

回應結構範例

```
{
  "id": string (uuid)
  "inboxes"?: [ // 非必填
    {
      "id": string (uuid)
      "name": string
    }
  ]
  "inbox"?:  // 向前相容欄位：單一 inbox，若同時提供 inboxes 則忽略此欄位 (非必填)
  {
    "id": string (uuid)
    "name": string
  }
  "name": string
  "avatar"?: // 可能有不同的類型 (非必填)
  string (uri) // 聯絡人頭像 URL，支援完整 URL 或相對路徑 (非必填)
  "phoneNumber"?: string // 非必填
  "email"?: // 可能有不同的類型 (非必填)
  string (email) // 非必填
  "sourceId"?: string // 非必填
  "queryMetadata"?: { // 查詢元資料，控制可查詢的知識範圍；詳見各端點說明 (非必填)
  {
    "knowledgeBases"?: [ // 可查詢的知識庫清單；空陣列或 null＝全部不可查（無權限），未提供＝不限制 (非必填)
      {
        "knowledgeBaseId": string (uuid) // 知識庫 ID
        "chatbotFileIds"?: [ // 檔案 ID 清單（依 hasUserSelectedAll 決定為排除或僅選取） (非必填)
          string (uuid)
        ]
        "knowledgeBaseFileIds"?: [ // 檔案 ID 清單（chatbotFileIds 的新名稱；兩者皆提供時以本欄位為準） (非必填)
          string (uuid)
        ]
        "faqIds"?: [ // FAQ ID 清單（依 hasUserSelectedAll 決定為排除或僅選取） (非必填)
          string (uuid)
        ]
        "hasUserSelectedAll"?: boolean // true＝選取知識庫全部內容並排除清單中的項目；false＝僅選取清單中的項目 (非必填)
      }
    ]
    "labelRelations"?: { // 標籤過濾條件；conditions 為空陣列＝不做標籤過濾（並
```

```
非無權限)。必須與 knowledgeBases 一併提供—單獨提供時知識庫檢索不會套用標籤過濾（等同不限制） (非必填)
    {
      "operator": string (enum: AND, OR) // 標籤條件的組合方式
      "conditions"?: [ // 標籤條件清單，支援巢狀 operator/conditions 組合 (非必填)
        object
      ]
    }
    }
  }
  }
  "metadata"?: object // Custom customer information shown in the customer panel of the conversation page (非必填)
  "mcpCredentials": [ // 聯絡人的 MCP 認證憑證列表
    object
  ]
  "apiCredentials": [ // 聯絡人的 API 認證憑證列表
    object
  ]
  "contactConnectors": [ // 聯絡人的 Connector OAuth 授權列表（不含 token 本體）
    object
  ]
  "tags": [
    {
      "id": string (uuid)
      "name": string
      "createdAt": string (timestamp)
      "updatedAt": string (timestamp)
    }
  ]
  "preChatFieldIndex": object // 來自此 Contact 所屬 inboxes 的 pre-chat form 欄位設定，mapping {field_id: {label: {locale: text}}}，前端用來把 metadata 的 UUID key 解析成顯示名稱
  "createdAt": string (timestamp)
  "updatedAt": string (timestamp)
}
```

回應範例值

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "inboxes": [
```

```
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "回應字串"
    }
  ],
  "inbox": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應字串"
  },
  "name": "回應字串",
  "avatar": "https://example.com/file.jpg",
  "phoneNumber": "回應字串",
  "email": "response@example.com",
  "sourceId": "回應字串",
  "queryMetadata": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應範例名稱",
    "description": "回應範例描述"
  },
  "metadata": null,
  "mcpCredentials": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "回應範例名稱",
      "description": "回應範例描述"
    }
  ],
  "apiCredentials": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "回應範例名稱",
      "description": "回應範例描述"
    }
  ],
  "contactConnectors": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "回應範例名稱",
      "description": "回應範例描述"
    }
  ],
  "tags": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "回應字串",
```

```
      "createdAt": "回應字串",
      "updatedAt": "回應字串"
    }
  ],
  "preChatFieldIndex": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應範例名稱",
    "description": "回應範例描述"
  },
  "createdAt": "回應字串",
  "updatedAt": "回應字串"
}
```


狀態碼: 400 - No response body

更新聯絡人的 API 憑證

PATCH `/api/v1/contacts/{id}/api-credentials/{credentialId}`

參數

參數名稱	必填	類型	說明
`credentialId`	V	string	
`id`	V	string	A UUID string identifying this Contact.

請求內容

請求參數

欄位	類型	必填	說明
headers	object	否	認證標頭字典

請求結構範例

```
{
  "headers"?: object // 認證標頭字典 (非必填)
}
```

請求範例值

```
{
  "headers": {}
}
```

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X PATCH "https://api.maiagent.ai/api/v1/contacts/550e8400-
e29b-41d4-a716-446655440000/api-credentials/{credentialId}
"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "headers": {}
  }'

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// 請求內容 (payload)
const data = {
    "headers": {}
  };

axios.patch("https://api.maiagent.ai/api/v1/contacts/550e8400-e29b-
41d4-a716-446655440000/api-credentials/{credentialId}
", data, config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/contacts/550e8400-e29b-41d4-
a716-446655440000/api-credentials/{credentialId}
"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# 請求內容 (payload)
data = {
    "headers": {}
}

response = requests.patch(url, json=data, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>patch("https://api.maiagent.ai/api/v1/contacts/550e8400-e29b-41d4-
a716-446655440000/api-credentials/{credentialId}
", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'headers' => new \stdClass()
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
{
  "id": string (uuid)
  "inboxes"?: [ // 非必填
    {
      "id": string (uuid)
      "name": string
    }
  ]
  "inbox"?:  // 向前相容欄位：單一 inbox，若同時提供 inboxes 則忽略此欄位 (非必填)
  {
    "id": string (uuid)
    "name": string
  }
  "name": string
  "avatar"?: // 可能有不同的類型 (非必填)
  string (uri) // 聯絡人頭像 URL，支援完整 URL 或相對路徑 (非必填)
  "phoneNumber"?: string // 非必填
  "email"?: // 可能有不同的類型 (非必填)
  string (email) // 非必填
  "sourceId"?: string // 非必填
  "queryMetadata"?: { // 查詢元資料，控制可查詢的知識範圍；詳見各端點說明 (非必填)
  {
    "knowledgeBases"?: [ // 可查詢的知識庫清單；空陣列或 null＝全部不可查（無權限），未提供＝不限制 (非必填)
      {
        "knowledgeBaseId": string (uuid) // 知識庫 ID
        "chatbotFileIds"?: [ // 檔案 ID 清單（依 hasUserSelectedAll 決定為排除或僅選取） (非必填)
          string (uuid)
        ]
        "knowledgeBaseFileIds"?: [ // 檔案 ID 清單（chatbotFileIds 的新名稱；兩者皆提供時以本欄位為準） (非必填)
          string (uuid)
        ]
        "faqIds"?: [ // FAQ ID 清單（依 hasUserSelectedAll 決定為排除或僅選取） (非必填)
          string (uuid)
        ]
        "hasUserSelectedAll"?: boolean // true＝選取知識庫全部內容並排除清單中的項目；false＝僅選取清單中的項目 (非必填)
      }
    ]
    "labelRelations"?: { // 標籤過濾條件；conditions 為空陣列＝不做標籤過濾（並
```

```
非無權限)。必須與 knowledgeBases 一併提供—單獨提供時知識庫檢索不會套用標籤過濾（等同不限制） (非必填)
    {
      "operator": string (enum: AND, OR) // 標籤條件的組合方式
      "conditions"?: [ // 標籤條件清單，支援巢狀 operator/conditions 組合 (非必填)
        object
      ]
    }
    }
  }
  }
  "metadata"?: object // Custom customer information shown in the customer panel of the conversation page (非必填)
  "mcpCredentials": [ // 聯絡人的 MCP 認證憑證列表
    object
  ]
  "apiCredentials": [ // 聯絡人的 API 認證憑證列表
    object
  ]
  "contactConnectors": [ // 聯絡人的 Connector OAuth 授權列表（不含 token 本體）
    object
  ]
  "tags": [
    {
      "id": string (uuid)
      "name": string
      "createdAt": string (timestamp)
      "updatedAt": string (timestamp)
    }
  ]
  "preChatFieldIndex": object // 來自此 Contact 所屬 inboxes 的 pre-chat form 欄位設定，mapping {field_id: {label: {locale: text}}}，前端用來把 metadata 的 UUID key 解析成顯示名稱
  "createdAt": string (timestamp)
  "updatedAt": string (timestamp)
}
```

回應範例值

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "inboxes": [
```

```
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "回應字串"
    }
  ],
  "inbox": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應字串"
  },
  "name": "回應字串",
  "avatar": "https://example.com/file.jpg",
  "phoneNumber": "回應字串",
  "email": "response@example.com",
  "sourceId": "回應字串",
  "queryMetadata": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應範例名稱",
    "description": "回應範例描述"
  },
  "metadata": null,
  "mcpCredentials": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "回應範例名稱",
      "description": "回應範例描述"
    }
  ],
  "apiCredentials": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "回應範例名稱",
      "description": "回應範例描述"
    }
  ],
  "contactConnectors": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "回應範例名稱",
      "description": "回應範例描述"
    }
  ],
  "tags": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "回應字串",
```

```
      "createdAt": "回應字串",
      "updatedAt": "回應字串"
    }
  ],
  "preChatFieldIndex": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應範例名稱",
    "description": "回應範例描述"
  },
  "createdAt": "回應字串",
  "updatedAt": "回應字串"
}
```


狀態碼: 404 - No response body

刪除聯絡人的 API 憑證

`DELETE` `/api/v1/contacts/{id}/api-credentials/{credentialId}`

參數

參數名稱	必填	類型	說明
`credentialId`	V	string	
`id`	V	string	A UUID string identifying this Contact.

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X DELETE "https://api.maiagent.ai/api/v1/contacts/550e8400-
e29b-41d4-a716-446655440000/api-credentials/{credentialId}
"

  -H "Authorization: Api-Key YOUR_API_KEY"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

// 請求內容 (payload)
const data = null;

axios.delete("https://api.maiagent.ai/api/v1/contacts/550e8400-e29b-
41d4-a716-446655440000/api-credentials/{credentialId}
", data, config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/contacts/550e8400-e29b-41d4-
a716-446655440000/api-credentials/{credentialId}
"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.delete(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>delete("https://api.maiagent.ai/api/v1/contacts/550e8400-e29b-41d4-
a716-446655440000/api-credentials/{credentialId}
", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼	說明
204	No response body
404	No response body

為聯絡人建立 MCP 憑證

`POST` `/api/v1/contacts/{id}/mcp-credentials/`

參數

參數名稱	必填	類型	說明
`id`	V	string	A UUID string identifying this Contact.

請求內容

請求參數

欄位	類型	必填	說明
tool	string (uuid)	是	MCP 工具的 ID
headers	object	否	認證標頭字典

請求結構範例

```
{
  "tool": string (uuid) // MCP 工具的 ID
  "headers"?: object // 認證標頭字典 (非必填)
}
```

請求範例值

```
{
  "tool": "550e8400-e29b-41d4-a716-446655440000",
```

```
  "headers": {}
}
```

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X POST "https://api.maiagent.ai/api/v1/contacts/550e8400-e29b-
41d4-a716-446655440000/mcp-credentials/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "tool": "550e8400-e29b-41d4-a716-446655440000",
    "headers": {}
  }'

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// 請求內容 (payload)
const data = {
    "tool": "550e8400-e29b-41d4-a716-446655440000",
    "headers": {}
  };

axios.post("https://api.maiagent.ai/api/v1/contacts/550e8400-e29b-
41d4-a716-446655440000/mcp-credentials/", data, config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/contacts/550e8400-e29b-41d4-
a716-446655440000/mcp-credentials/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# 請求內容 (payload)
data = {
    "tool": "550e8400-e29b-41d4-a716-446655440000",
    "headers": {}
}

response = requests.post(url, json=data, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>post("https://api.maiagent.ai/api/v1/contacts/550e8400-e29b-41d4-
a716-446655440000/mcp-credentials/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'tool' => '550e8400-e29b-41d4-a716-446655440000',
            'headers' => new \stdClass()
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 201

回應結構範例

```
{
  "id": string (uuid)
  "inboxes"?: [ // 非必填
    {
      "id": string (uuid)
      "name": string
    }
  ]
  "inbox"?:  // 向前相容欄位：單一 inbox，若同時提供 inboxes 則忽略此欄位 (非必填)
  {
    "id": string (uuid)
    "name": string
  }
  "name": string
  "avatar"?: // 可能有不同的類型 (非必填)
  string (uri) // 聯絡人頭像 URL，支援完整 URL 或相對路徑 (非必填)
  "phoneNumber"?: string // 非必填
  "email"?: // 可能有不同的類型 (非必填)
  string (email) // 非必填
  "sourceId"?: string // 非必填
  "queryMetadata"?: { // 查詢元資料，控制可查詢的知識範圍；詳見各端點說明 (非必填)
  {
    "knowledgeBases"?: [ // 可查詢的知識庫清單；空陣列或 null＝全部不可查（無權限），未提供＝不限制 (非必填)
      {
        "knowledgeBaseId": string (uuid) // 知識庫 ID
        "chatbotFileIds"?: [ // 檔案 ID 清單（依 hasUserSelectedAll 決定為排除或僅選取） (非必填)
          string (uuid)
        ]
        "knowledgeBaseFileIds"?: [ // 檔案 ID 清單（chatbotFileIds 的新名稱；兩者皆提供時以本欄位為準） (非必填)
          string (uuid)
        ]
        "faqIds"?: [ // FAQ ID 清單（依 hasUserSelectedAll 決定為排除或僅選取） (非必填)
          string (uuid)
        ]
        "hasUserSelectedAll"?: boolean // true＝選取知識庫全部內容並排除清單中的項目；false＝僅選取清單中的項目 (非必填)
      }
    ]
    "labelRelations"?: { // 標籤過濾條件；conditions 為空陣列＝不做標籤過濾（並
```

```
非無權限)。必須與 knowledgeBases 一併提供—單獨提供時知識庫檢索不會套用標籤過濾（等同不限制） (非必填)
    {
      "operator": string (enum: AND, OR) // 標籤條件的組合方式
      "conditions"?: [ // 標籤條件清單，支援巢狀 operator/conditions 組合 (非必填)
        object
      ]
    }
    }
  }
  }
  "metadata"?: object // Custom customer information shown in the customer panel of the conversation page (非必填)
  "mcpCredentials": [ // 聯絡人的 MCP 認證憑證列表
    object
  ]
  "apiCredentials": [ // 聯絡人的 API 認證憑證列表
    object
  ]
  "contactConnectors": [ // 聯絡人的 Connector OAuth 授權列表（不含 token 本體）
    object
  ]
  "tags": [
    {
      "id": string (uuid)
      "name": string
      "createdAt": string (timestamp)
      "updatedAt": string (timestamp)
    }
  ]
  "preChatFieldIndex": object // 來自此 Contact 所屬 inboxes 的 pre-chat form 欄位設定，mapping {field_id: {label: {locale: text}}}，前端用來把 metadata 的 UUID key 解析成顯示名稱
  "createdAt": string (timestamp)
  "updatedAt": string (timestamp)
}
```

回應範例值

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "inboxes": [
```

```
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "回應字串"
    }
  ],
  "inbox": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應字串"
  },
  "name": "回應字串",
  "avatar": "https://example.com/file.jpg",
  "phoneNumber": "回應字串",
  "email": "response@example.com",
  "sourceId": "回應字串",
  "queryMetadata": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應範例名稱",
    "description": "回應範例描述"
  },
  "metadata": null,
  "mcpCredentials": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "回應範例名稱",
      "description": "回應範例描述"
    }
  ],
  "apiCredentials": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "回應範例名稱",
      "description": "回應範例描述"
    }
  ],
  "contactConnectors": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "回應範例名稱",
      "description": "回應範例描述"
    }
  ],
  "tags": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "回應字串",
```

```
      "createdAt": "回應字串",
      "updatedAt": "回應字串"
    }
  ],
  "preChatFieldIndex": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應範例名稱",
    "description": "回應範例描述"
  },
  "createdAt": "回應字串",
  "updatedAt": "回應字串"
}
```


狀態碼: 400 - No response body

更新聯絡人的 MCP 憑證

`PATCH` `/api/v1/contacts/{id}/mcp-credentials/{credentialId}`

參數

參數名稱	必填	類型	說明
`credentialId`	V	string	
`id`	V	string	A UUID string identifying this Contact.

請求內容

請求參數

欄位	類型	必填	說明
headers	object	否	認證標頭字典

請求結構範例

```
{
  "headers"?: object // 認證標頭字典 (非必填)
}
```

請求範例值

```
{
  "headers": {}
}
```

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X PATCH "https://api.maiagent.ai/api/v1/contacts/550e8400-
e29b-41d4-a716-446655440000/mcp-credentials/{credentialId}
"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "headers": {}
  }'

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// 請求內容 (payload)
const data = {
    "headers": {}
  };

axios.patch("https://api.maiagent.ai/api/v1/contacts/550e8400-e29b-
41d4-a716-446655440000/mcp-credentials/{credentialId}
", data, config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/contacts/550e8400-e29b-41d4-
a716-446655440000/mcp-credentials/{credentialId}
"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# 請求內容 (payload)
data = {
    "headers": {}
}

response = requests.patch(url, json=data, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>patch("https://api.maiagent.ai/api/v1/contacts/550e8400-e29b-41d4-
a716-446655440000/mcp-credentials/{credentialId}
", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'headers' => new \stdClass()
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
{
  "id": string (uuid)
  "inboxes"?: [ // 非必填
    {
      "id": string (uuid)
      "name": string
    }
  ]
  "inbox"?:  // 向前相容欄位：單一 inbox，若同時提供 inboxes 則忽略此欄位 (非必填)
  {
    "id": string (uuid)
    "name": string
  }
  "name": string
  "avatar"?: // 可能有不同的類型 (非必填)
  string (uri) // 聯絡人頭像 URL，支援完整 URL 或相對路徑 (非必填)
  "phoneNumber"?: string // 非必填
  "email"?: // 可能有不同的類型 (非必填)
  string (email) // 非必填
  "sourceId"?: string // 非必填
  "queryMetadata"?: { // 查詢元資料，控制可查詢的知識範圍；詳見各端點說明 (非必填)
  {
    "knowledgeBases"?: [ // 可查詢的知識庫清單；空陣列或 null＝全部不可查（無權限），未提供＝不限制 (非必填)
      {
        "knowledgeBaseId": string (uuid) // 知識庫 ID
        "chatbotFileIds"?: [ // 檔案 ID 清單（依 hasUserSelectedAll 決定為排除或僅選取） (非必填)
          string (uuid)
        ]
        "knowledgeBaseFileIds"?: [ // 檔案 ID 清單（chatbotFileIds 的新名稱；兩者皆提供時以本欄位為準） (非必填)
          string (uuid)
        ]
        "faqIds"?: [ // FAQ ID 清單（依 hasUserSelectedAll 決定為排除或僅選取） (非必填)
          string (uuid)
        ]
        "hasUserSelectedAll"?: boolean // true＝選取知識庫全部內容並排除清單中的項目；false＝僅選取清單中的項目 (非必填)
      }
    ]
    "labelRelations"?: { // 標籤過濾條件；conditions 為空陣列＝不做標籤過濾（並
```

```
非無權限)。必須與 knowledgeBases 一併提供—單獨提供時知識庫檢索不會套用標籤過濾（等同不限制） (非必填)
    {
      "operator": string (enum: AND, OR) // 標籤條件的組合方式
      "conditions"?: [ // 標籤條件清單，支援巢狀 operator/conditions 組合 (非必填)
        object
      ]
    }
    }
  }
  }
  "metadata"?: object // Custom customer information shown in the customer panel of the conversation page (非必填)
  "mcpCredentials": [ // 聯絡人的 MCP 認證憑證列表
    object
  ]
  "apiCredentials": [ // 聯絡人的 API 認證憑證列表
    object
  ]
  "contactConnectors": [ // 聯絡人的 Connector OAuth 授權列表（不含 token 本體）
    object
  ]
  "tags": [
    {
      "id": string (uuid)
      "name": string
      "createdAt": string (timestamp)
      "updatedAt": string (timestamp)
    }
  ]
  "preChatFieldIndex": object // 來自此 Contact 所屬 inboxes 的 pre-chat form 欄位設定，mapping {field_id: {label: {locale: text}}}，前端用來把 metadata 的 UUID key 解析成顯示名稱
  "createdAt": string (timestamp)
  "updatedAt": string (timestamp)
}
```

回應範例值

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "inboxes": [
```

```
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "回應字串"
    }
  ],
  "inbox": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應字串"
  },
  "name": "回應字串",
  "avatar": "https://example.com/file.jpg",
  "phoneNumber": "回應字串",
  "email": "response@example.com",
  "sourceId": "回應字串",
  "queryMetadata": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應範例名稱",
    "description": "回應範例描述"
  },
  "metadata": null,
  "mcpCredentials": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "回應範例名稱",
      "description": "回應範例描述"
    }
  ],
  "apiCredentials": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "回應範例名稱",
      "description": "回應範例描述"
    }
  ],
  "contactConnectors": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "回應範例名稱",
      "description": "回應範例描述"
    }
  ],
  "tags": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "回應字串",
```

```
      "createdAt": "回應字串",
      "updatedAt": "回應字串"
    }
  ],
  "preChatFieldIndex": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應範例名稱",
    "description": "回應範例描述"
  },
  "createdAt": "回應字串",
  "updatedAt": "回應字串"
}
```


狀態碼: 404 - No response body

刪除聯絡人的 MCP 憑證

`DELETE` `/api/v1/contacts/{id}/mcp-credentials/{credentialId}`

參數

參數名稱	必填	類型	說明
`credentialId`	V	string	
`id`	V	string	A UUID string identifying this Contact.

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X DELETE "https://api.maiagent.ai/api/v1/contacts/550e8400-
e29b-41d4-a716-446655440000/mcp-credentials/{credentialId}
"

  -H "Authorization: Api-Key YOUR_API_KEY"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

// 請求內容 (payload)
const data = null;

axios.delete("https://api.maiagent.ai/api/v1/contacts/550e8400-e29b-
41d4-a716-446655440000/mcp-credentials/{credentialId}
", data, config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/contacts/550e8400-e29b-41d4-
a716-446655440000/mcp-credentials/{credentialId}
"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.delete(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>delete("https://api.maiagent.ai/api/v1/contacts/550e8400-e29b-41d4-
a716-446655440000/mcp-credentials/{credentialId}
", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼	說明
204	No response body
404	No response body

下載聯絡人批次匯入範本

GET `/api/v1/contacts/bulk-import-template/`

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/contacts/bulk-import-
template/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/contacts/bulk-import-
template/", config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/contacts/bulk-import-
template/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/contacts/bulk-import-
template/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
{
  "id": string (uuid)
  "inboxes"?: [ // 非必填
```

```
    {
      "id": string (uuid)
      "name": string
    }
  ]
  "inbox"?:  // 向前相容欄位：單一 inbox，若同時提供 inboxes 則忽略此欄位 (非必填)
  {
    "id": string (uuid)
    "name": string
  }
  "name": string
  "avatar"?: // 可能有不同的類型 (非必填)
  string (uri) // 聯絡人頭像 URL，支援完整 URL 或相對路徑 (非必填)
  "phoneNumber"?: string // 非必填
  "email"?: // 可能有不同的類型 (非必填)
  string (email) // 非必填
  "sourceId"?: string // 非必填
  "queryMetadata"?: { // 查詢元資料，控制可查詢的知識範圍；詳見各端點說明 (非必填)
  {
    "knowledgeBases"?: [ // 可查詢的知識庫清單；空陣列或 null＝全部不可查（無權限），未提供＝不限制 (非必填)
      {
        "knowledgeBaseId": string (uuid) // 知識庫 ID
        "chatbotFileIds"?: [ // 檔案 ID 清單（依 hasUserSelectedAll 決定為排除或僅選取） (非必填)
          string (uuid)
        ]
        "knowledgeBaseFileIds"?: [ // 檔案 ID 清單（chatbotFileIds 的新名稱；兩者皆提供時以本欄位為準） (非必填)
          string (uuid)
        ]
        "faqIds"?: [ // FAQ ID 清單（依 hasUserSelectedAll 決定為排除或僅選取） (非必填)
          string (uuid)
        ]
        "hasUserSelectedAll"?: boolean // true＝選取知識庫全部內容並排除清單中的項目；false＝僅選取清單中的項目 (非必填)
      }
    ]
    "labelRelations"?: { // 標籤過濾條件；conditions 為空陣列＝不做標籤過濾（並非無權限）。必須與 knowledgeBases 一併提供——單獨提供時知識庫檢索不會套用標籤過濾（等同不限制） (非必填)
    {
      "operator": string (enum: AND, OR) // 標籤條件的組合方式
```

```
      "conditions"?: [ // 標籤條件清單，支援巢狀 operator/conditions 組合 (非必填)
        object
      ]
    }
    }
  }
  }
  "metadata"?: object // Custom customer information shown in the customer panel of the conversation page (非必填)
  "mcpCredentials": [ // 聯絡人的 MCP 認證憑證列表
    object
  ]
  "apiCredentials": [ // 聯絡人的 API 認證憑證列表
    object
  ]
  "contactConnectors": [ // 聯絡人的 Connector OAuth 授權列表（不含 token 本體）
    object
  ]
  "tags": [
    {
      "id": string (uuid)
      "name": string
      "createdAt": string (timestamp)
      "updatedAt": string (timestamp)
    }
  ]
  "preChatFieldIndex": object // 來自此 Contact 所屬 inboxes 的 pre-chat form 欄位設定，mapping {field_id: {label: {locale: text}}}，前端用來把 metadata 的 UUID key 解析成顯示名稱
  "createdAt": string (timestamp)
  "updatedAt": string (timestamp)
}
```

回應範例值

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "inboxes": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "回應字串"
    }
```

```
  ],
  "inbox": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應字串"
  },
  "name": "回應字串",
  "avatar": "https://example.com/file.jpg",
  "phoneNumber": "回應字串",
  "email": "response@example.com",
  "sourceId": "回應字串",
  "queryMetadata": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應範例名稱",
    "description": "回應範例描述"
  },
  "metadata": null,
  "mcpCredentials": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "回應範例名稱",
      "description": "回應範例描述"
    }
  ],
  "apiCredentials": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "回應範例名稱",
      "description": "回應範例描述"
    }
  ],
  "contactConnectors": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "回應範例名稱",
      "description": "回應範例描述"
    }
  ],
  "tags": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "回應字串",
      "createdAt": "回應字串",
      "updatedAt": "回應字串"
    }
  ],
```

```
  "preChatFieldIndex": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應範例名稱",
    "description": "回應範例描述"
  },
  "createdAt": "回應字串",
  "updatedAt": "回應字串"
}
```


批次匯入聯絡人

POST `/api/v1/contacts/bulk-import/`

上傳依範本填寫的 Excel；帶 dry_run=true 只回報將建立／更新的筆數而不寫入（回 200 而非 201）。

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X POST "https://api.maiagent.ai/api/v1/contacts/bulk-import/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');
const FormData = require('form-data');

// 建立FormData對象
const formData = new FormData();
// 添加表單欄位

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    ...formData.getHeaders()
  }
};

axios.post("https://api.maiagent.ai/api/v1/contacts/bulk-import/",
formData, config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/contacts/bulk-import/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}

# 建立檔案和表單資料
files = {
    'file': ('example.pdf', open('example.pdf', 'rb'),
'application/pdf')
}

response = requests.post(url, files=files, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>post("https://api.maiagent.ai/api/v1/contacts/bulk-import/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ],
        'multipart' => [
            [
                'name' => 'file',
                'contents' => fopen('example.pdf', 'r'),
                'filename' => 'example.pdf'
            ]
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
{
  "id": string (uuid)
  "inboxes"?: [ // 非必填
    {
      "id": string (uuid)
      "name": string
    }
  ]
  "inbox"?:  // 向前相容欄位：單一 inbox，若同時提供 inboxes 則忽略此欄位 (非必填)
  {
    "id": string (uuid)
    "name": string
  }
  "name": string
  "avatar"?: // 可能有不同的類型 (非必填)
  string (uri) // 聯絡人頭像 URL，支援完整 URL 或相對路徑 (非必填)
  "phoneNumber"?: string // 非必填
  "email"?: // 可能有不同的類型 (非必填)
  string (email) // 非必填
  "sourceId"?: string // 非必填
  "queryMetadata"?: { // 查詢元資料，控制可查詢的知識範圍；詳見各端點說明 (非必填)
  {
    "knowledgeBases"?: [ // 可查詢的知識庫清單；空陣列或 null＝全部不可查（無權限），未提供＝不限制 (非必填)
      {
        "knowledgeBaseId": string (uuid) // 知識庫 ID
        "chatbotFileIds"?: [ // 檔案 ID 清單（依 hasUserSelectedAll 決定為排除或僅選取） (非必填)
          string (uuid)
        ]
        "knowledgeBaseFileIds"?: [ // 檔案 ID 清單（chatbotFileIds 的新名稱；兩者皆提供時以本欄位為準） (非必填)
          string (uuid)
        ]
        "faqIds"?: [ // FAQ ID 清單（依 hasUserSelectedAll 決定為排除或僅選取） (非必填)
          string (uuid)
        ]
        "hasUserSelectedAll"?: boolean // true＝選取知識庫全部內容並排除清單中的項目；false＝僅選取清單中的項目 (非必填)
      }
    ]
```

```
    "labelRelations"?: { // 標籤過濾條件；conditions 為空陣列＝不做標籤過濾（並非無權限）。必須與 knowledgeBases 一併提供—單獨提供時知識庫檢索不會套用標籤過濾（等同不限制） (非必填)
    {
      "operator": string (enum: AND, OR) // 標籤條件的組合方式
      "conditions"?: [ // 標籤條件清單，支援巢狀 operator/conditions 組合 (非必填)
        object
      ]
    }
    }
  }
  }
  "metadata"?: object // Custom customer information shown in the customer panel of the conversation page (非必填)
  "mcpCredentials": [ // 聯絡人的 MCP 認證憑證列表
    object
  ]
  "apiCredentials": [ // 聯絡人的 API 認證憑證列表
    object
  ]
  "contactConnectors": [ // 聯絡人的 Connector OAuth 授權列表（不含 token 本體）
    object
  ]
  "tags": [
    {
      "id": string (uuid)
      "name": string
      "createdAt": string (timestamp)
      "updatedAt": string (timestamp)
    }
  ]
  "preChatFieldIndex": object // 來自此 Contact 所屬 inboxes 的 pre-chat form 欄位設定，mapping {field_id: {label: {locale: text}}}，前端用來把 metadata 的 UUID key 解析成顯示名稱
  "createdAt": string (timestamp)
  "updatedAt": string (timestamp)
}
```

回應範例值

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
```

```
  "inboxes": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "回應字串"
    }
  ],
  "inbox": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應字串"
  },
  "name": "回應字串",
  "avatar": "https://example.com/file.jpg",
  "phoneNumber": "回應字串",
  "email": "response@example.com",
  "sourceId": "回應字串",
  "queryMetadata": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應範例名稱",
    "description": "回應範例描述"
  },
  "metadata": null,
  "mcpCredentials": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "回應範例名稱",
      "description": "回應範例描述"
    }
  ],
  "apiCredentials": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "回應範例名稱",
      "description": "回應範例描述"
    }
  ],
  "contactConnectors": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "回應範例名稱",
      "description": "回應範例描述"
    }
  ],
  "tags": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
```

```
      "name": "回應字串",
      "createdAt": "回應字串",
      "updatedAt": "回應字串"
    }
  ],
  "preChatFieldIndex": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應範例名稱",
    "description": "回應範例描述"
  },
  "createdAt": "回應字串",
  "updatedAt": "回應字串"
}
```

呼叫 API 示例 (Shell)

目錄

1. 建立角色
2. 批量新增角色成員
3. 批量分配 AI 助理給角色
4. 批量分配收件匣給角色
5. 批量分配知識庫給角色
6. 批量分配資料庫給角色
7. 列出權限清單
8. 取得角色列表
9. 取得角色的詳情
10. 取得角色成員列表
11. 查看特定角色成員
12. 取得角色的 AI 助理列表
13. 取得角色的收件匣列表
14. 取得角色的知識庫列表
15. 取得角色的資料庫列表
16. 更新角色權限
17. 部分更新角色權限
18. 刪除角色
19. 移除角色成員
20. 移除角色裡的 AI 助理
21. 移除角色裡的收件匣
22. 移除角色裡的知識庫
23. 移除角色裡的資料庫

呼叫 API 示例 (Shell)

建立角色

`POST` `/api/v1/organizations/{organizationPk}/groups/`

參數

參數名稱	必填	類型	說明
`organizationPk`	V	string	A UUID string identifying this 組織 ID

請求內容

請求參數

欄位	類型	必填	說明
name	string	是	
organization	string (uuid)	否	
permissions	array[string]	是	
canCreateChatbot	boolean	否	
canCreateKnowledgeBase	boolean	否	
canCreateInbox	boolean	否	
canCreateDatabase	boolean	否	
canCreateTool	boolean	否	
canCreateAgentUiTool	boolean	否	
canCreateSkill	boolean	否	
maigptCanCodeInterpreter	boolean	否	Whether members of this role may use the code interpreter built-in tool in MaiGPT.
maigptCanRag	boolean	否	Whether members of this role may use the knowledge base RAG built-in tool in MaiGPT.
maigptCanDeepResearch	boolean	否	Whether members of this role may use Deep Research in MaiGPT. Deep

欄位	類型	必填	說明
			Research reaches the public internet through its own built-in search, so a role that revokes the official web-search tools needs this...
maigptCanBrowserTool	boolean	否	Whether members of this role may use the browser built-in tool in MaiGPT.
maigptAllLlms	boolean	否	Whether members of this role may use every organization-available LLM in MaiGPT. Off = only the bound LLMs; an empty binding then means none.
maigptAllTools	boolean	否	Whether members of this role may call every official (global) tool in MaiGPT. Off = only the bound tools; an empty binding then means none.
maigptAllConnectors	boolean	否	Whether members of this role may call every official (global) MCP connector in MaiGPT. Off = only the bound connectors; an empty binding then means none.
maigptAllSkills	boolean	否	Whether members of this role may use every official (global) skill in MaiGPT. Off = only the bound skills; an empty binding then means none.
usageStatisticsScope	object	否	What this role's usage statistics permission shows: the whole organization, or only the AI assistants granted to the member's roles. A member with any organization-wide granting role sees the whole or...
allowedLlms	array[string]	否	
allowedTools	array[string]	否	
allowedConnectors	array[string]	否	
allowedSkills	array[string]	否	

請求結構範例

```
{
  "name": string
  "organization"?: string (uuid) // 非必填
  "permissions": [
    string (uuid)
  ]
  "canCreateChatbot"?: boolean // 非必填
  "canCreateKnowledgeBase"?: boolean // 非必填
  "canCreateInbox"?: boolean // 非必填
  "canCreateDatabase"?: boolean // 非必填
  "canCreateTool"?: boolean // 非必填
  "canCreateAgentUiTool"?: boolean // 非必填
  "canCreateSkill"?: boolean // 非必填
  "maigptCanCodeInterpreter"?: boolean // Whether members of this role may use the code interpreter built-in tool in MaiGPT. (非必填)
  "maigptCanRag"?: boolean // Whether members of this role may use the knowledge base RAG built-in tool in MaiGPT. (非必填)
  "maigptCanDeepResearch"?: boolean // Whether members of this role may use Deep Research in MaiGPT. Deep Research reaches the public internet through its own built-in search, so a role that revokes the official web-search tools needs this switch too. (非必填)
  "maigptCanBrowserTool"?: boolean // Whether members of this role may use the browser built-in tool in MaiGPT. (非必填)
  "maigptAllLlms"?: boolean // Whether members of this role may use every organization-available LLM in MaiGPT. Off = only the bound LLMs; an empty binding then means none. (非必填)
  "maigptAllTools"?: boolean // Whether members of this role may call every official (global) tool in MaiGPT. Off = only the bound tools; an empty binding then means none. (非必填)
  "maigptAllConnectors"?: boolean // Whether members of this role may call every official (global) MCP connector in MaiGPT. Off = only the bound connectors; an empty binding then means none. (非必填)
  "maigptAllSkills"?: boolean // Whether members of this role may use every official (global) skill in MaiGPT. Off = only the bound skills; an empty binding then means none. (非必填)
  "usageStatisticsScope"?:  // What this role's usage statistics permission shows: the whole organization, or only the AI assistants granted to the member's roles. A member with any organization-wide granting role sees the whole organization.

* `organization` - Organization-wide
* `accessible_chatbots` - Authorized AI assistants only (非必填)
  {
```

```
  }
  "allowedLlms"?: [ // 非必填
    string (uuid)
  ]
  "allowedTools"?: [ // 非必填
    string (uuid)
  ]
  "allowedConnectors"?: [ // 非必填
    string (uuid)
  ]
  "allowedSkills"?: [ // 非必填
    string (uuid)
  ]
}
```

請求範例值

```
{
  "name": "範例名稱",
  "organization": "550e8400-e29b-41d4-a716-446655440000",
  "permissions": [
    "550e8400-e29b-41d4-a716-446655440000"
  ],
  "canCreateChatbot": true,
  "canCreateKnowledgeBase": true,
  "canCreateInbox": true,
  "canCreateDatabase": true,
  "canCreateTool": true,
  "canCreateAgentUiTool": true,
  "canCreateSkill": true,
  "maigptCanCodeInterpreter": true,
  "maigptCanRag": true,
  "maigptCanDeepResearch": true,
  "maigptCanBrowserTool": true,
  "maigptAllLlms": true,
  "maigptAllTools": true,
  "maigptAllConnectors": true,
  "maigptAllSkills": true,
  "usageStatisticsScope": {},
  "allowedLlms": [
    "550e8400-e29b-41d4-a716-446655440000"
  ],
  "allowedTools": [
    "550e8400-e29b-41d4-a716-446655440000"
```

```
  ],
  "allowedConnectors": [
    "550e8400-e29b-41d4-a716-446655440000"
  ],
  "allowedSkills": [
    "550e8400-e29b-41d4-a716-446655440000"
  ]
}
```

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X POST "https://api.maiagent.ai/api/v1/organizations/550e8400-
e29b-41d4-a716-446655440000/groups/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "name": "範例名稱",
    "organization": "550e8400-e29b-41d4-a716-446655440000",
    "permissions": [
      "550e8400-e29b-41d4-a716-446655440000"
    ],
    "canCreateChatbot": true,
    "canCreateKnowledgeBase": true,
    "canCreateInbox": true,
    "canCreateDatabase": true,
    "canCreateTool": true,
    "canCreateAgentUiTool": true,
    "canCreateSkill": true,
    "maigptCanCodeInterpreter": true,
    "maigptCanRag": true,
    "maigptCanDeepResearch": true,
    "maigptCanBrowserTool": true,
    "maigptAllLlms": true,
    "maigptAllTools": true,
    "maigptAllConnectors": true,
    "maigptAllSkills": true,
    "usageStatisticsScope": {},
    "allowedLlms": [
      "550e8400-e29b-41d4-a716-446655440000"
    ],
    "allowedTools": [
      "550e8400-e29b-41d4-a716-446655440000"
    ],
    "allowedConnectors": [
      "550e8400-e29b-41d4-a716-446655440000"
    ],
    "allowedSkills": [
```

```
      "550e8400-e29b-41d4-a716-446655440000"
    ]
  }'

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// 請求內容 (payload)
const data = {
    "name": "範例名稱",
    "organization": "550e8400-e29b-41d4-a716-446655440000",
    "permissions": [
      "550e8400-e29b-41d4-a716-446655440000"
    ],
    "canCreateChatbot": true,
    "canCreateKnowledgeBase": true,
    "canCreateInbox": true,
    "canCreateDatabase": true,
    "canCreateTool": true,
    "canCreateAgentUiTool": true,
    "canCreateSkill": true,
    "maigptCanCodeInterpreter": true,
    "maigptCanRag": true,
    "maigptCanDeepResearch": true,
    "maigptCanBrowserTool": true,
    "maigptAllLlms": true,
    "maigptAllTools": true,
    "maigptAllConnectors": true,
    "maigptAllSkills": true,
    "usageStatisticsScope": {},
    "allowedLlms": [
      "550e8400-e29b-41d4-a716-446655440000"
    ],
    "allowedTools": [
      "550e8400-e29b-41d4-a716-446655440000"
    ],
    "allowedConnectors": [
```

```
      "550e8400-e29b-41d4-a716-446655440000"
    ],
    "allowedSkills": [
      "550e8400-e29b-41d4-a716-446655440000"
    ]
  };

axios.post("https://api.maiagent.ai/api/v1/organizations/550e8400-
e29b-41d4-a716-446655440000/groups/", data, config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-
41d4-a716-446655440000/groups/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# 請求內容 (payload)
data = {
    "name": "範例名稱",
    "organization": "550e8400-e29b-41d4-a716-446655440000",
    "permissions": [
        "550e8400-e29b-41d4-a716-446655440000"
    ],
    "canCreateChatbot": True,
    "canCreateKnowledgeBase": True,
    "canCreateInbox": True,
    "canCreateDatabase": True,
    "canCreateTool": True,
    "canCreateAgentUiTool": True,
    "canCreateSkill": True,
    "maigptCanCodeInterpreter": True,
    "maigptCanRag": True,
    "maigptCanDeepResearch": True,
    "maigptCanBrowserTool": True,
    "maigptAllLlms": True,
    "maigptAllTools": True,
    "maigptAllConnectors": True,
    "maigptAllSkills": True,
    "usageStatisticsScope": {},
    "allowedLlms": [
        "550e8400-e29b-41d4-a716-446655440000"
    ],
    "allowedTools": [
        "550e8400-e29b-41d4-a716-446655440000"
    ],
    "allowedConnectors": [
        "550e8400-e29b-41d4-a716-446655440000"
```

```
    ],
    "allowedSkills": [
        "550e8400-e29b-41d4-a716-446655440000"
    ]
}

response = requests.post(url, json=data, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>post("https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-
41d4-a716-446655440000/groups/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'name' => '範例名稱',
            'organization' => '550e8400-e29b-41d4-a716-
446655440000',
            'permissions' => [
                '550e8400-e29b-41d4-a716-446655440000'
            ],
            'canCreateChatbot' => true,
            'canCreateKnowledgeBase' => true,
            'canCreateInbox' => true,
            'canCreateDatabase' => true,
            'canCreateTool' => true,
            'canCreateAgentUiTool' => true,
            'canCreateSkill' => true,
            'maigptCanCodeInterpreter' => true,
            'maigptCanRag' => true,
            'maigptCanDeepResearch' => true,
            'maigptCanBrowserTool' => true,
            'maigptAllLlms' => true,
            'maigptAllTools' => true,
            'maigptAllConnectors' => true,
            'maigptAllSkills' => true,
            'usageStatisticsScope' => new \stdClass(),
            'allowedLlms' => [
                '550e8400-e29b-41d4-a716-446655440000'
            ],
            'allowedTools' => [
```

```
                    '550e8400-e29b-41d4-a716-446655440000'
                ],
                'allowedConnectors' => [
                    '550e8400-e29b-41d4-a716-446655440000'
                ],
                'allowedSkills' => [
                    '550e8400-e29b-41d4-a716-446655440000'
                ]
            ]
        ]);

        $data = json_decode($response->getBody(), true);
        echo "成功取得回應:\n";
        print_r($data);
    } catch (Exception $e) {
        echo '請求發生錯誤: ' . $e->getMessage();
    }
    ?>
```

回應內容

狀態碼: 201

回應結構範例

```
{
  "id": string (uuid)
  "name": string
  "type":
  {
  }
  "permissions": [
    object
  ]
  "membersPreview": [
    string
  ]
```

```
  "membersCount": integer // 返回剩餘成員數量（扣除列表顯示的 3 人後），用於前端 +N badge 顯示

與資源 count 不同：
<ul>
  <li>members_count: 返回 total - 3（用於 +N badge），None 表示總數 <= 3</li>
  <li>chatbots_count/knowledge_bases_count/inboxes_count: 返回總數量</li>
</ul>
  "chatbotsCount": integer
  "chatbotsPreview": [
    string
  ]
  "knowledgeBasesCount": integer
  "knowledgeBasesPreview": [
    string
  ]
  "inboxesCount": integer
  "inboxesPreview": [
    string
  ]
  "databasesCount": integer
  "databasesPreview": [
    string
  ]
  "canCreateChatbot"?: boolean // 非必填
  "canCreateKnowledgeBase"?: boolean // 非必填
  "canCreateInbox"?: boolean // 非必填
  "canCreateDatabase"?: boolean // 非必填
  "canCreateTool"?: boolean // 非必填
  "canCreateAgentUiTool"?: boolean // 非必填
  "canCreateSkill"?: boolean // 非必填
  "maigptCanCodeInterpreter"?: boolean // Whether members of this role may use the code interpreter built-in tool in MaiGPT. (非必填)
  "maigptCanRag"?: boolean // Whether members of this role may use the knowledge base RAG built-in tool in MaiGPT. (非必填)
  "maigptCanDeepResearch"?: boolean // Whether members of this role may use Deep Research in MaiGPT. Deep Research reaches the public internet through its own built-in search, so a role that revokes the official web-search tools needs this switch too. (非必填)
  "maigptCanBrowserTool"?: boolean // Whether members of this role may use the browser built-in tool in MaiGPT. (非必填)
  "maigptAllLlms"?: boolean // Whether members of this role may use every organization-available LLM in MaiGPT. Off = only the bound LLMs; an empty binding then means none. (非必填)
  "maigptAllTools"?: boolean // Whether members of this role may call
```

```
every official (global) tool in MaiGPT. Off = only the bound tools; an
empty binding then means none. (非必填)
  "maigptAllConnectors"?: boolean // Whether members of this role may
call every official (global) MCP connector in MaiGPT. Off = only the
bound connectors; an empty binding then means none. (非必填)
  "maigptAllSkills"?: boolean // Whether members of this role may use
every official (global) skill in MaiGPT. Off = only the bound skills; an
empty binding then means none. (非必填)
  "usageStatisticsScope"?:  // What this role's usage statistics
permission shows: the whole organization, or only the AI assistants
granted to the member's roles. A member with any organization-wide
granting role sees the whole organization.

* `organization` - Organization-wide
* `accessible_chatbots` - Authorized AI assistants only (非必填)
  {
  }
  "createdAt": string (timestamp)
}
```

回應範例值

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "name": "回應字串",
  "type": {},
  "permissions": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "回應範例名稱",
      "description": "回應範例描述"
    }
  ],
  "membersPreview": [
    "回應字串"
  ],
  "membersCount": 456,
  "chatbotsCount": 456,
  "chatbotsPreview": [
    "回應字串"
  ],
  "knowledgeBasesCount": 456,
  "knowledgeBasesPreview": [
    "回應字串"
```

```
  ],
  "inboxesCount": 456,
  "inboxesPreview": [
    "回應字串"
  ],
  "databasesCount": 456,
  "databasesPreview": [
    "回應字串"
  ],
  "canCreateChatbot": false,
  "canCreateKnowledgeBase": false,
  "canCreateInbox": false,
  "canCreateDatabase": false,
  "canCreateTool": false,
  "canCreateAgentUiTool": false,
  "canCreateSkill": false,
  "maigptCanCodeInterpreter": false,
  "maigptCanRag": false,
  "maigptCanDeepResearch": false,
  "maigptCanBrowserTool": false,
  "maigptAllLlms": false,
  "maigptAllTools": false,
  "maigptAllConnectors": false,
  "maigptAllSkills": false,
  "usageStatisticsScope": {},
  "createdAt": "回應字串"
}
```


批量新增角色成員

POST `/api/v1/organizations/{organizationPk}/groups/{groupPk}/group-members/bulk-create/`

參數

參數名稱	必填	類型	說明

`groupPk`	V	string	
`organizationPk`	V	string	A UUID string identifying this 組織 ID

請求內容

請求參數

欄位	類型	必填	說明
members	array[string]	是	

請求結構範例

```
{
  "members": [
    string (uuid)
  ]
}
```

請求範例值

```
{
  "members": [
    "550e8400-e29b-41d4-a716-446655440000"
  ]
}
```

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X POST "https://api.maiagent.ai/api/v1/organizations/550e8400-
e29b-41d4-a716-446655440000/groups/550e8400-e29b-41d4-a716-
446655440000/group-members/bulk-create/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "members": [
      "550e8400-e29b-41d4-a716-446655440000"
    ]
  }'

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// 請求內容 (payload)
const data = {
    "members": [
      "550e8400-e29b-41d4-a716-446655440000"
    ]
  };

axios.post("https://api.maiagent.ai/api/v1/organizations/550e8400-
e29b-41d4-a716-446655440000/groups/550e8400-e29b-41d4-a716-
446655440000/group-members/bulk-create/", data, config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-
41d4-a716-446655440000/groups/550e8400-e29b-41d4-a716-
446655440000/group-members/bulk-create/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# 請求內容 (payload)
data = {
    "members": [
        "550e8400-e29b-41d4-a716-446655440000"
    ]
}

response = requests.post(url, json=data, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->post("https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-41d4-a716-446655440000/groups/550e8400-e29b-41d4-a716-446655440000/group-members/bulk-create/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'members' => [
                '550e8400-e29b-41d4-a716-446655440000'
            ]
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 201

回應結構範例

```
[
  {
    "id"?: string (uuid) // 角色成員 ID (非必填)
    "member"?: { // 非必填
    {
      "id"?: string (uuid) // 成員 ID (非必填)
      "name"?: string // 成員姓名 (非必填)
      "email"?: string (email) // 成員電子郵件 (非必填)
      "organization"?: { // 非必填
      {
        "id"?: string (uuid) // 組織 ID (非必填)
        "name"?: string // 組織名稱 (非必填)
        "createdAt"?: string // 組織建立時間戳 (非必填)
        "usageStatistics"?: { // 非必填
        {
          "chatbotsCount"?: integer // 聊天機器人數量 (非必填)
          "countableChatbotsCount"?: integer // 佔用建立額度的聊天機器人數量（模式不在方案白名單內的不計入） (非必填)
          "exemptChatbotsByMode"?: object // 不佔額度的聊天機器人數量，依使其不計入的模式分組 (非必填)
          "canCreateChatbot"?: boolean // 是否可以創建聊天機器人 (非必填)
          "createChatbotLimit"?: integer // 可建立的聊天機器人數量上限（-1 表示無上限、0 表示禁止建立） (非必填)
          "currentMonthWordsCountTotal"?: integer // 當月總字數限制 (非必填)
          "currentMonthUsedWordsCountTotal"?: integer // 當月已使用字數 (非必填)
          "currentMonthUsedConversationsCountTotal"?: integer // 當月已使用對話數 (非必填)
          "availableUploadFilesSizeTotal"?: integer // 可上傳檔案總大小 (非必填)
          "usedUploadFileSizeTotal"?: integer // 已使用上傳檔案大小 (非必填)
        }
        }
        "organizationPlan"?: { // 非必填
        {
          "id"?: string (uuid) // 方案 ID (非必填)
          "planName"?: string // 方案名稱 (非必填)
          "expiredAt"?: string // 方案到期時間 (非必填)
        }
        }
      }
      }
      "isOwner"?: boolean // 是否為組織擁有者 (非必填)
```

```
      "permissions"?: { // 非必填
      {
        "hasOrganizationAccessPermission"?: boolean // 是否有組織存取權限 (非必填)
        "hasChatAccessPermission"?: boolean // 是否有聊天存取權限 (非必填)
        "hasConversationAccessPermission"?: boolean // 是否有對話存取權限 (非必填)
        "hasChatbotAccessPermission"?: boolean // 是否有聊天機器人存取權限 (非必填)
      }
      }
      "createdAt"?: string // 成員建立時間戳 (非必填)
    }
    }
    "createdAt"?: string // 角色成員建立時間戳 (非必填)
  }
]
```

回應範例值

```
[
  {
    "id": "c1e54f04-01fc-45e9-b40c-9d8b37bd0ac0",
    "member": {
      "id": "af4e472d-3f9b-446b-bab8-05de4112d086",
      "name": "h",
      "email": "h@gmail.com",
      "organization": {
        "id": "670e3d30-9d24-47b4-b2cc-6bf224b2f3bb",
        "name": "Updated Org Name",
        "createdAt": "1745288290000",
        "usageStatistics": {
          "chatbotsCount": 1,
          "countableChatbotsCount": 1,
          "exemptChatbotsByMode": {},
          "canCreateChatbot": false,
          "createChatbotLimit": 1,
          "currentMonthWordsCountTotal": 1000000,
          "currentMonthUsedWordsCountTotal": 0,
          "currentMonthUsedConversationsCountTotal": 0,
          "availableUploadFilesSizeTotal": 104857600,
          "usedUploadFileSizeTotal": 0
        },
        "organizationPlan": {
```

```
          "id": "16136181-ae0d-4b3f-aaeb-9a6ed251459f",
          "planName": "免費方案",
          "expiredAt": null
        }
      },
      "isOwner": false,
      "permissions": {
        "hasMaigptAccessPermission": false,
        "hasChatbotAccessPermission": false,
        "hasAgentopsAccessPermission": false,
        "hasConversationAccessPermission": false,
        "hasChatAccessPermission": false,
        "hasDeveloperAccessPermission": false,
        "hasOrganizationAccessPermission": true
      },
      "createdAt": "1748335331000"
    },
    "createdAt": "1748341252000"
  }
]
```


批量分配 AI 助理給角色

POST `/api/v1/organizations/{organizationPk}/groups/{groupPk}/group-chatbots/bulk-create/`

參數

參數名稱	必填	類型	說明
`groupPk`	V	string	
`organizationPk`	V	string	A UUID string identifying this 組織 ID
`page`	X	integer	A page number within the paginated result set.

`pageSize`	X	integer	Number of results to return per page.
`query`	X	string	
`search`	X	string	

請求內容

請求參數

欄位	類型	必填	說明
chatbots	array[string]	是	

請求結構範例

```
{
  "chatbots": [
    string (uuid)
  ]
}
```

請求範例值

```
{
  "chatbots": [
    "550e8400-e29b-41d4-a716-446655440000"
  ]
}
```

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X POST "https://api.maiagent.ai/api/v1/organizations/550e8400-
e29b-41d4-a716-446655440000/groups/550e8400-e29b-41d4-a716-
446655440000/group-chatbots/bulk-create/?
page=1&pageSize=1&query=example&search=example"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "chatbots": [
      "550e8400-e29b-41d4-a716-446655440000"
    ]
  }'

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// 請求內容 (payload)
const data = {
    "chatbots": [
      "550e8400-e29b-41d4-a716-446655440000"
    ]
  };

axios.post("https://api.maiagent.ai/api/v1/organizations/550e8400-
e29b-41d4-a716-446655440000/groups/550e8400-e29b-41d4-a716-
446655440000/group-chatbots/bulk-create/?
page=1&pageSize=1&query=example&search=example", data, config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-
41d4-a716-446655440000/groups/550e8400-e29b-41d4-a716-
446655440000/group-chatbots/bulk-create/?
page=1&pageSize=1&query=example&search=example"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# 請求內容 (payload)
data = {
    "chatbots": [
        "550e8400-e29b-41d4-a716-446655440000"
    ]
}

response = requests.post(url, json=data, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>post("https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-
41d4-a716-446655440000/groups/550e8400-e29b-41d4-a716-
446655440000/group-chatbots/bulk-create/?
page=1&pageSize=1&query=example&search=example", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'chatbots' => [
                '550e8400-e29b-41d4-a716-446655440000'
            ]
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 201

回應結構範例

```
{
  "count": integer
  "next"?: string (uri) // 非必填
  "previous"?: string (uri) // 非必填
  "results": [
    {
      "id": string (uuid)
      "group": string (uuid)
      "chatbot":
      {
        "id": string (uuid)
        "name": string // Chatbot name. In Agent mode it carries semantic meaning; in other modes it only distinguishes chatbots.
        "largeLanguageModel": string (uuid) // 機器人使用的大型語言模型，用於生成回答（含組織自建的 AI Gateway 模型）
        "llm":  // 綁定模型的 id、name 與退役資訊，直接讀取 FK，即使該模型已被組織停用仍會回傳
        {
          "id": string (uuid)
          "name": string
          "retiresAt": string (date) // 供應商退役日；到期後每日排程會把助理換到 replacement 並停用此模型。null 表示未排定退役
          "replacement":  // 退役後接手的模型（id 與 name）；null 表示未指定，到期時不會自動搬移
          {
            "id": string (uuid)
            "name": string
          }
        }
        "embeddingModel"?: string (uuid) // 用於向量化文本的嵌入模型，非必填項目 (非必填)
        "rerankerModel"?: string (uuid) // 用於重新排序的模型，非必填項目 (非必填)
        "instructions"?: string // Role instructions describing the chatbot's role and behavior. (非必填)
        "knowledgeBases"?: [ // 機器人可存取的知識庫列表 (非必填)
          {
            "id": string (uuid)
            "name": string
          }
        ]
```

```
        "databases"?: [ // 機器人可存取的 SQL 資料庫列表（用於 Text-to-SQL 功能）（非必填）
          {
            "id": string (uuid)
            "name": string
          }
        ]
        "updatedAt": string (timestamp)
        "organization"?: string (uuid) // 機器人所屬的組織，如果為空則為個人機器人（非必填）
        "replyMode"?:  // 回覆模式：一般回覆或串流回覆

* `normal` - 正常
* `template` - 模板
* `hybrid` - 混合
* `agent` - 代理（非必填）
        {
        }
        "template"?: string // Template used by Template and Hybrid modes. (非必填)
        "unanswerableTemplate"?: string // Template used by Template and Hybrid modes when the question cannot be answered. (非必填)
        "totalWordsCount"?: integer (int64) // Accumulated total word count used. (非必填)
        "outputMode"?:  // 輸出模式：文字、表格或自定義格式

* `text` - 文字
* `json_schema` - JSON Schema（非必填）
        {
        }
        "rawOutputFormat"?: object // 自定義輸出格式的JSON結構定義（非必填）
        "groups"?: [ // 機器人可存取的群組列表（非必填）
          {
            "id": string (uuid)
            "name": string
          }
        ]
        "tools"?: [ // 機器人可使用的工具列表（非必填）
          {
            "id": string (uuid)
            "name": string
            "description": string
            "displayName": string
            "toolType": string
          }
```

```
        ]
        "skills"?: [ // 機器人關聯的技能列表 (非必填)
          {
            "id": string (uuid)
            "name": string
            "description": string
          }
        ]
        "connectors"?: [ // Connectors associated with this chatbot,
gating per-contact OAuth authorization (非必填)
          {
            "id": string (uuid)
            "name": string
          }
        ]
        "agentMode"?:  // 代理模式：一般、SQL或工作流程模式

* `normal` - 正常
* `canvas` - 畫布
* `team` - 團隊 (非必填)
        {
        }
        "numberOfRetrievedChunks"?: integer // 提取的參考資料數量，預設為 12，
最小值為 1 (非必填)
        "defaultLabelRelations"?: object // 助理層級的預設知識庫標籤過濾條件，
格式同 query_metadata.label_relations；null 表示不過濾。僅在呼叫端未帶
query_metadata 時作為最低優先序兜底套用。 (非必填)
        "useFullRetrievalRange"?: boolean // 啟用後忽略 LLM 的 top_k 截斷，回
傳完整 reranker 結果 (非必填)
        "enableEvaluation"?: boolean // 非必填
        "enableInlineCitations"?: boolean // Enables inline citations,
inserting citation markers such as [1][2] into responses. (非必填)
        "enableCodeInterpreter"?: boolean // When enabled, provides the
Code Interpreter tool to run code in an isolated container. (非必填)
        "enableBrowserTool"?: boolean // Enable browser automation tool
for web tasks (非必填)
        "enableImageSearch"?: boolean // Provide the image_search tool
when any attached knowledge base uses a multimodal embedding model.
Disable to remove the tool entirely. (非必填)
        "enableClaudeStreamRetry"?: boolean // When a Claude streaming
call stalls (first-chunk or mid-stream), abort and re-issue the call once
in non-streaming mode. Mid-stream retries send a reset signal so the
client discards any partial output already rendered. Each retry incurs a
second billing for the same prompt. (非必填)
        "customMaxLlmOutputTokens"?: integer // 自訂最大 LLM 輸出 token 數，
```

```
最小值為 512 (非必填)
        "voiceConfig"?: { // 非必填
        {
          "enabled"?: boolean // Whether this chatbot can be used as a
voice agent. Checked by every conversation platform (WebChat, SIP phone,
admin/marketplace voice test) instead of a per-platform toggle. (非必填)
          "voiceAgentType"?: string (uuid) // Voice agent mode type. (非必
填)
          "sttProvider"?: string (uuid) // Speech-to-Text service
provider. (非必填)
          "sttConfig"?: object // STT configuration parameters (JSON). (非
必填)
          "ttsProvider"?: string (uuid) // Text-to-Speech service
provider. (非必填)
          "ttsConfig"?: object // TTS configuration parameters (JSON). (非
必填)
          "realtimeProvider"?: string (uuid) // Realtime end-to-end voice
model provider. (非必填)
          "realtimeConfig"?: object // Realtime configuration parameters
(JSON). (非必填)
          "realtimeInstructions"?: string // Prompt dedicated to the
realtime voice session; falls back to chatbot instructions when empty (非
必填)
          "turnHandling"?: object // Turn-taking and interruption
settings for the voice agent. (非必填)
          "enableVoiceReply"?: boolean // When disabled, the voice agent
replies in text only and does not speak (非必填)
        }
        }
        "thinkingConfig"?: object // 思考等級：null（模型預設）或
{"reasoning_effort": "off|minimal|low|medium|high|xhigh|max"} (非必填)
        "enableToolSearching"?: boolean // 啟用動態工具搜尋功能，允許 agent 透
過 tool_searching_tool 動態發現和加載工具 (非必填)
        "maxAgentIterations"?: integer // Maximum number of iterations
for AgentWorkflow (1-100, default: 20) (非必填)
        "agentTimeoutSeconds"?: integer // Timeout in seconds for
AgentWorkflow execution (30-1200, default: 600) (非必填)
        "agentTimeoutMessage"?: string // Custom user-facing message
shown when AgentWorkflow times out (max 500 chars). Leave empty to use
the system default. (非必填)
        "requireTextWithFlexCards"?: boolean // When enabled, a turn that
would end with only Flex Message cards and no text for the user is re-
issued to the LLM once, asking it to write the text first and then send
the card. Each retry incurs a second billing for the same prompt. (非必填)
        "isMultimodalLlm": boolean // Whether the chatbot LLM supports
```

multimodal (read-only)
        "enableSizeBasedToolResultTruncation"?: boolean // When enabled, tool results exceeding the character threshold are kept as head+tail (with the identifiers found in the cut part) when written to conversation history; knowledge base, SQL and conversation search results keep their 100-character cut either way. Reduces memory bloat from large tool outputs (code interpreter bash stdout, web search results, etc.). (非必填)
        "toolResultMaxChars"?: integer // Character threshold for size-based tool result truncation (500-50000). Only effective when enable_size_based_tool_result_truncation is True. (非必填)
        "enableVectorMemory"?: boolean // When enabled, archived messages are vectorized and processed by fact extraction for semantic retrieval (existing behavior). When disabled, archived messages are discarded and only the active chat history window is used for multi-turn context. (非必填)
        "longTermMemoryTopK"?: integer // 長期記憶每次檢索取回的記憶節點數（向量檢索的 similarity_top_k），預設為 10，範圍 1–50 (非必填)
        "enableCrossConversationSearch"?: boolean // When enabled, the conversation history tools also reach this contact's other conversations in the same inbox, within the lookback window. When disabled, they only reach the current conversation. (非必填)
        "crossConversationLookbackDays"?: integer // How far back cross-conversation search may reach, measured from each conversation's last message (1-365 days). Leave empty to fall back to 90 days. Only effective when enable_cross_conversation_search is True. (非必填)
        "useGatewayFallback"?: boolean // When enabled, use the fallback group instead of the single LLM (非必填)
        "gatewayFallbackGroup"?: string (uuid) // 非必填
        "enableSearchMessagesTool"?: boolean // Allow the AI to search past messages in the current conversation. (非必填)
        "enableGetMessageContextTool"?: boolean // Allow the AI to retrieve messages surrounding a specific message for context. (非必填)
        "enableReadAttachmentFullTextTool"?: boolean // Allow the AI to read the full text of plain-text attachments. AGENT mode only. (非必填)
        "enableParseAttachmentContentTool"?: boolean // Allow the AI to parse PDF, Office, audio, and other attachments. AGENT mode only. (非必填)
        "enableListAvailableParsersTool"?: boolean // Allow the AI to list available parsers and their capabilities. AGENT mode only. (非必填)
        "enableGetDownloadLinkTool"?: boolean // Allow the AI to generate shareable download links for produced content. AGENT mode only. (非必填)
        "isLocked": boolean // Locked instance: config follows the official version; only the dedicated KB can be modified
        "sourceBuildInAgent": string (uuid) // Points to the official Build-in Agent blueprint when instantiated by a rental
        "canUpdate": boolean // Return whether the current user can

```
update this resource.
        "canDelete": boolean // Return whether the current user can
delete this resource.
        "team":
        {
          "id": string (uuid)
          "name": string
        }
        "webChatIsActive"?: boolean // Optional, create only. Whether the
web widget channel starts active. Omitted or null: follows the
organization's default for new chatbot channels (inactive unless a
platform admin turned it on). Ignored on update; change an existing
channel from its channel settings instead. (非必填)
        "apiIsActive"?: boolean // Optional, create only. Whether the API
channel starts active. Omitted or null: follows the organization's
default for new chatbot channels (inactive unless a platform admin turned
it on). Ignored on update; change an existing channel from its channel
settings instead. The backstage (admin) channel always starts active and
cannot be set here. (非必填)
        "fileWorkspaceMode"?:  // File workspace mode in Work internal
conversations: none, bound or user_mount.

* `none` - None
* `bound` - Bound workspace
* `user_mount` - User mount (非必填)
        {
        }
        "fileWorkspaceFolder"?: string (uuid) // The bound workspace
(folder id); required when the mode is bound, cleared otherwise. (非必填)
        "fileWorkspaceStatus": object // Read-only. {"folder": {"id",
"name"} | null, "state": "ok" | "missing" | "builder_lost_edit" | null}
        "fileWorkspaceAvailable": boolean // Read-only. Whether the
organization has the file library and this agent can configure a file
workspace.
      }
      "canRead"?: boolean // 非必填
      "canUpdate"?: boolean // 非必填
      "canDelete"?: boolean // 非必填
      "createdAt": string (timestamp)
    }
  ]
}
```

回應範例值

```
{
  "count": 123,
  "next": "http://api.example.org/accounts/?page=4",
  "previous": "http://api.example.org/accounts/?page=2",
  "results": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "group": "550e8400-e29b-41d4-a716-446655440000",
      "chatbot": {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "name": "回應字串",
        "largeLanguageModel": "550e8400-e29b-41d4-a716-446655440000",
        "llm": {
          "id": "550e8400-e29b-41d4-a716-446655440000",
          "name": "回應字串",
          "retiresAt": "回應字串",
          "replacement": {
            "id": "550e8400-e29b-41d4-a716-446655440000",
            "name": "回應字串"
          }
        },
        "embeddingModel": "550e8400-e29b-41d4-a716-446655440000",
        "rerankerModel": "550e8400-e29b-41d4-a716-446655440000",
        "instructions": "回應字串",
        "knowledgeBases": [
          {
            "id": "550e8400-e29b-41d4-a716-446655440000",
            "name": "回應字串"
          }
        ],
        "databases": [
          {
            "id": "550e8400-e29b-41d4-a716-446655440000",
            "name": "回應字串"
          }
        ],
        "updatedAt": "回應字串",
        "organization": "550e8400-e29b-41d4-a716-446655440000",
        "replyMode": {},
        "template": "回應字串",
        "unanswerableTemplate": "回應字串",
        "totalWordsCount": 456,
        "outputMode": {},
        "rawOutputFormat": null,
```

```
        "groups": [
          {
            "id": "550e8400-e29b-41d4-a716-446655440000",
            "name": "回應字串"
          }
        ],
        "tools": [
          {
            "id": "550e8400-e29b-41d4-a716-446655440000",
            "name": "回應字串",
            "description": "回應字串",
            "displayName": "回應字串",
            "toolType": "回應字串"
          }
        ],
        "skills": [
          {
            "id": "550e8400-e29b-41d4-a716-446655440000",
            "name": "回應字串",
            "description": "回應字串"
          }
        ],
        "connectors": [
          {
            "id": "550e8400-e29b-41d4-a716-446655440000",
            "name": "回應字串"
          }
        ],
        "agentMode": {},
        "numberOfRetrievedChunks": 456,
        "defaultLabelRelations": null,
        "useFullRetrievalRange": false,
        "enableEvaluation": false,
        "enableInlineCitations": false,
        "enableCodeInterpreter": false,
        "enableBrowserTool": false,
        "enableImageSearch": false,
        "enableClaudeStreamRetry": false,
        "customMaxLlmOutputTokens": 456,
        "voiceConfig": {
          "enabled": false,
          "voiceAgentType": "550e8400-e29b-41d4-a716-446655440000",
          "sttProvider": "550e8400-e29b-41d4-a716-446655440000",
          "sttConfig": null,
          "ttsProvider": "550e8400-e29b-41d4-a716-446655440000",
```

```
    "ttsConfig": null,
    "realtimeProvider": "550e8400-e29b-41d4-a716-446655440000",
    "realtimeConfig": null,
    "realtimeInstructions": "回應字串",
    "turnHandling": null,
    "enableVoiceReply": false
  },
  "thinkingConfig": null,
  "enableToolSearching": false,
  "maxAgentIterations": 456,
  "agentTimeoutSeconds": 456,
  "agentTimeoutMessage": "回應字串",
  "requireTextWithFlexCards": false,
  "isMultimodalLlm": false,
  "enableSizeBasedToolResultTruncation": false,
  "toolResultMaxChars": 456,
  "enableVectorMemory": false,
  "longTermMemoryTopK": 456,
  "enableCrossConversationSearch": false,
  "crossConversationLookbackDays": 456,
  "useGatewayFallback": false,
  "gatewayFallbackGroup": "550e8400-e29b-41d4-a716-446655440000",
  "enableSearchMessagesTool": false,
  "enableGetMessageContextTool": false,
  "enableReadAttachmentFullTextTool": false,
  "enableParseAttachmentContentTool": false,
  "enableListAvailableParsersTool": false,
  "enableGetDownloadLinkTool": false,
  "isLocked": false,
  "sourceBuildInAgent": "550e8400-e29b-41d4-a716-446655440000",
  "canUpdate": false,
  "canDelete": false,
  "team": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應字串"
  },
  "webChatIsActive": false,
  "apiIsActive": false,
  "fileWorkspaceMode": {},
  "fileWorkspaceFolder": "550e8400-e29b-41d4-a716-446655440000",
  "fileWorkspaceStatus": {
    "name": "example.pdf",
    "content": "base64encoded_content",
    "contentType": "application/pdf"
  },
```

```
        "fileWorkspaceAvailable": false
      },
      "canRead": false,
      "canUpdate": false,
      "canDelete": false,
      "createdAt": "回應字串"
    }
  ]
}
```


批量分配收件匣給角色

POST `/api/v1/organizations/{organizationPk}/groups/{groupPk}/group-inboxes/bulk-create/`

參數

參數名稱	必填	類型	說明
`groupPk`	V	string	
`organizationPk`	V	string	A UUID string identifying this 組織 ID

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X POST "https://api.maiagent.ai/api/v1/organizations/550e8400-
e29b-41d4-a716-446655440000/groups/550e8400-e29b-41d4-a716-
446655440000/group-inboxes/bulk-create/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

// 請求內容 (payload)
const data = null;

axios.post("https://api.maiagent.ai/api/v1/organizations/550e8400-
e29b-41d4-a716-446655440000/groups/550e8400-e29b-41d4-a716-
446655440000/group-inboxes/bulk-create/", data, config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-41d4-a716-446655440000/groups/550e8400-e29b-41d4-a716-446655440000/group-inboxes/bulk-create/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.post(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>post("https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-
41d4-a716-446655440000/groups/550e8400-e29b-41d4-a716-
446655440000/group-inboxes/bulk-create/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼	說明
200	No response body

批量分配知識庫給角色

POST `/api/v1/organizations/{organizationPk}/groups/{groupPk}/group-knowledge-bases/bulk-create/`

參數

參數名稱	必填	類型	說明
`groupPk`	V	string	
`organizationPk`	V	string	A UUID string identifying this 組織 ID
`page`	X	integer	A page number within the paginated result set.
`pageSize`	X	integer	Number of results to return per page.
`query`	X	string	
`search`	X	string	

請求內容

請求參數

欄位	類型	必填	說明
knowledgeBases	array[string]	是	

請求結構範例

```
{
  "knowledgeBases": [
    string (uuid)
```

```
  ]
}
```

請求範例值

```
{
  "knowledgeBases": [
    "550e8400-e29b-41d4-a716-446655440000"
  ]
}
```

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X POST "https://api.maiagent.ai/api/v1/organizations/550e8400-
e29b-41d4-a716-446655440000/groups/550e8400-e29b-41d4-a716-
446655440000/group-knowledge-bases/bulk-create/?
page=1&pageSize=1&query=example&search=example"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "knowledgeBases": [
      "550e8400-e29b-41d4-a716-446655440000"
    ]
  }'

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// 請求內容 (payload)
const data = {
    "knowledgeBases": [
      "550e8400-e29b-41d4-a716-446655440000"
    ]
  };

axios.post("https://api.maiagent.ai/api/v1/organizations/550e8400-
e29b-41d4-a716-446655440000/groups/550e8400-e29b-41d4-a716-
446655440000/group-knowledge-bases/bulk-create/?
page=1&pageSize=1&query=example&search=example", data, config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-
41d4-a716-446655440000/groups/550e8400-e29b-41d4-a716-
446655440000/group-knowledge-bases/bulk-create/?
page=1&pageSize=1&query=example&search=example"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# 請求內容 (payload)
data = {
    "knowledgeBases": [
        "550e8400-e29b-41d4-a716-446655440000"
    ]
}

response = requests.post(url, json=data, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>post("https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-
41d4-a716-446655440000/groups/550e8400-e29b-41d4-a716-
446655440000/group-knowledge-bases/bulk-create/?
page=1&pageSize=1&query=example&search=example", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'knowledgeBases' => [
                '550e8400-e29b-41d4-a716-446655440000'
            ]
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 201

回應結構範例

```
{
  "count": integer
  "next"?: string (uri) // 非必填
  "previous"?: string (uri) // 非必填
  "results": [
    {
      "id": string (uuid)
      "group": string (uuid)
      "knowledgeBase":
      {
        "id": string (uuid)
        "createdBy":
        {
          "id": string (uuid)
          "name": string
        }
        "organization"?: string (uuid) // 非必填
        "embeddingModel": string (uuid)
        "rerankerModel": string (uuid)
        "name": string
        "description"?: string // 非必填
        "numberOfRetrievedChunks"?: integer // 提取的參考資料數量，預設為 12，
最小值為 1 (非必填)
        "enableHyde"?: boolean // 啟用 HyDE，預設為 False (非必填)
        "similarityCutoff"?: number (double) // 相似度門檻，預設為 0.0，範圍為
0.0-1.0 (非必填)
        "enableRerank"?: boolean // 是否啟用重新排序，預設為 True (非必填)
        "enableRrf"?: boolean // Enable Reciprocal Rank Fusion for hybrid
search. Disable this if using a custom Elasticsearch without enterprise
license. (非必填)
        "vectorDatabaseType"?:  // Type of vector database: elasticsearch
or opensearch.

* `elasticsearch` - Elasticsearch
* `opensearch` - OpenSearch
* `oracle` - Oracle AI Database 26ai
* `synxdb` - SynxDB (非必填)
        {
        }
        "vectorDatabaseUrl"?: string // Custom vector database endpoint
URL or Oracle DSN. For Elasticsearch/OpenSearch: URL format (e.g.,
```

```
"https://host:9200"). For Oracle: DSN format (e.g.,
"host:1521/service_name"). (非必填)
        "vectorDatabaseApiKey"?: string // API Key for Elasticsearch. Not
used for OpenSearch. (非必填)
        "opensearchUsername"?: string // Username for OpenSearch Basic
Auth. (非必填)
        "opensearchPassword"?: string // Password for OpenSearch Basic
Auth. (非必填)
        "oracleUser"?: string // Oracle database username. (非必填)
        "oraclePassword"?: string // Oracle database password. (非必填)
        "synxdbUser"?: string // SynxDB database username. (非必填)
        "synxdbPassword"?: string // SynxDB database password. (非必填)
        "labels": [
          {
            "id": string (uuid)
            "name": string
          }
        ]
        "chatbots"?: [ // 非必填
          {
            "id": string (uuid)
            "name": string
          }
        ]
        "groups"?: [ // 知識庫可存取的群組列表 (非必填)
          {
            "id": string (uuid)
            "name": string
          }
        ]
        "filesCount": integer // Return count of KnowledgeBaseFile
excluding processed files, conversation attachments, and soft-deleted.
        "vectorStorageSize": integer
        "chunksCount": integer
        "canUpdate": boolean // Return whether the current user can
update this resource.
        "canDelete": boolean // Return whether the current user can
delete this resource.
        "createdAt": string (timestamp)
        "updatedAt": string (timestamp)
      }
      "canRead"?: boolean // 非必填
      "canUpdate"?: boolean // 非必填
      "canDelete"?: boolean // 非必填
      "createdAt": string (timestamp)
```

```
    }
  ]
}
```

回應範例值


```
{
  "count": 123,
  "next": "http://api.example.org/accounts/?page=4",
  "previous": "http://api.example.org/accounts/?page=2",
  "results": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "group": "550e8400-e29b-41d4-a716-446655440000",
      "knowledgeBase": {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "createdBy": {
          "id": "550e8400-e29b-41d4-a716-446655440000",
          "name": "回應字串"
        },
        "organization": "550e8400-e29b-41d4-a716-446655440000",
        "embeddingModel": "550e8400-e29b-41d4-a716-446655440000",
        "rerankerModel": "550e8400-e29b-41d4-a716-446655440000",
        "name": "回應字串",
        "description": "回應字串",
        "numberOfRetrievedChunks": 456,
        "enableHyde": false,
        "similarityCutoff": 456,
        "enableRerank": false,
        "enableRrf": false,
        "vectorDatabaseType": {},
        "vectorDatabaseUrl": "回應字串",
        "vectorDatabaseApiKey": "回應字串",
        "opensearchUsername": "回應字串",
        "opensearchPassword": "回應字串",
        "oracleUser": "回應字串",
        "oraclePassword": "回應字串",
        "synxdbUser": "回應字串",
        "synxdbPassword": "回應字串",
        "labels": [
          {
            "id": "550e8400-e29b-41d4-a716-446655440000",
            "name": "回應字串"
          }
```

```
        ],
        "chatbots": [
          {
            "id": "550e8400-e29b-41d4-a716-446655440000",
            "name": "回應字串"
          }
        ],
        "groups": [
          {
            "id": "550e8400-e29b-41d4-a716-446655440000",
            "name": "回應字串"
          }
        ],
        "filesCount": 456,
        "vectorStorageSize": 456,
        "chunksCount": 456,
        "canUpdate": false,
        "canDelete": false,
        "createdAt": "回應字串",
        "updatedAt": "回應字串"
      },
      "canRead": false,
      "canUpdate": false,
      "canDelete": false,
      "createdAt": "回應字串"
    }
  ]
}
```


批量分配資料庫給角色

`POST` `/api/v1/organizations/{organizationPk}/groups/{groupPk}/group-databases/bulk-create/`

參數

參數名稱	必填	類型	說明
`groupPk`	V	string	
`organizationPk`	V	string	A UUID string identifying this 組織 ID
`page`	X	integer	A page number within the paginated result set.
`pageSize`	X	integer	Number of results to return per page.
`query`	X	string	
`search`	X	string	

請求內容

請求參數

欄位	類型	必填	說明
databases	array[string]	是	

請求結構範例

```
{
  "databases": [
    string (uuid)
  ]
}
```

請求範例值

```
{
  "databases": [
    "550e8400-e29b-41d4-a716-446655440000"
```

```
  ]
}
```

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X POST "https://api.maiagent.ai/api/v1/organizations/550e8400-
e29b-41d4-a716-446655440000/groups/550e8400-e29b-41d4-a716-
446655440000/group-databases/bulk-create/?
page=1&pageSize=1&query=example&search=example"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "databases": [
      "550e8400-e29b-41d4-a716-446655440000"
    ]
  }'

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// 請求內容 (payload)
const data = {
    "databases": [
      "550e8400-e29b-41d4-a716-446655440000"
    ]
  };

axios.post("https://api.maiagent.ai/api/v1/organizations/550e8400-
e29b-41d4-a716-446655440000/groups/550e8400-e29b-41d4-a716-
446655440000/group-databases/bulk-create/?
page=1&pageSize=1&query=example&search=example", data, config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-
41d4-a716-446655440000/groups/550e8400-e29b-41d4-a716-
446655440000/group-databases/bulk-create/?
page=1&pageSize=1&query=example&search=example"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# 請求內容 (payload)
data = {
    "databases": [
        "550e8400-e29b-41d4-a716-446655440000"
    ]
}

response = requests.post(url, json=data, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>post("https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-
41d4-a716-446655440000/groups/550e8400-e29b-41d4-a716-
446655440000/group-databases/bulk-create/?
page=1&pageSize=1&query=example&search=example", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'databases' => [
                '550e8400-e29b-41d4-a716-446655440000'
            ]
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 201

回應結構範例

```
{
  "count": integer
  "next"?: string (uri) // 非必填
  "previous"?: string (uri) // 非必填
  "results": [
    {
      "id": string (uuid)
      "group": string (uuid)
      "database":
      {
        "id": string (uuid)
        "name": string // Display name for this database connection
        "description": string // Description of the database and its
purpose
        "databaseType":  // Type of database: PostgreSQL, MySQL, MSSQL,
Oracle, SynxDB, or MaiAgent

* `postgresql` - PostgreSQL
* `mysql` - MySQL
* `maiagent` - MaiAgent
* `oracle` - Oracle
* `mssql` - MSSQL
* `synxdb` - SynxDB
        {
        }
        "includeTables": object // Optional list of tables to include.
Format: {"tables": ["table1", "table2"]}. For MaiAgent type, this is
auto-populated from uploaded files.
        "isActive": boolean // When disabled, this database will not be
used in Text-to-SQL queries
        "status":
        {
        }
        "deletedAt": string (timestamp)
        "tables": [
          {
            "id": string (uuid)
            "tableName": string // Name of the table in the database
            "sheetName": string // Name of the source worksheet/sheet
this table was created from. Empty for tables created before this field
was added.
```

```
            "description"?: string // Description of the table and its
data for better Text-to-SQL understanding (非必填)
            "status":
            {
            }
            "errorMessage": string // Error details if table creation or
deletion failed
            "sourceFile":
            {
              "id": string (uuid)
              "name": string
              "isFromKnowledgeBase": boolean // Determine if the source
file originated from a knowledge base upload.

Returns True if the file was uploaded via knowledge base,
False if uploaded directly to the database.
            }
            "columns": [
              {
                "id": string (uuid)
                "columnName": string
                "columnType"?: string // Data type of the column (e.g.,
VARCHAR, INTEGER, TIMESTAMP) (非必填)
                "description"?: string // Description of the column for
better Text-to-SQL understanding (非必填)
                "isPrimaryKey"?: boolean // 非必填
                "isNullable"?: boolean // 非必填
                "createdAt": string (timestamp)
                "updatedAt": string (timestamp)
              }
            ]
            "createdAt": string (timestamp)
            "updatedAt": string (timestamp)
          }
        ]
        "chatbots": [
          {
            "id": string (uuid)
            "name": string
          }
        ]
        "groups": [
          {
            "id": string (uuid)
            "name": string
```

```
          }
        ]
        "createdAt": string (timestamp)
        "updatedAt": string (timestamp)
      }
      "canRead"?: boolean // 非必填
      "canUpdate"?: boolean // 非必填
      "canDelete"?: boolean // 非必填
      "createdAt": string (timestamp)
    }
  ]
}
```

回應範例值

```
{
  "count": 123,
  "next": "http://api.example.org/accounts/?page=4",
  "previous": "http://api.example.org/accounts/?page=2",
  "results": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "group": "550e8400-e29b-41d4-a716-446655440000",
      "database": {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "name": "回應字串",
        "description": "回應字串",
        "databaseType": {},
        "includeTables": null,
        "isActive": false,
        "status": {},
        "deletedAt": "回應字串",
        "tables": [
          {
            "id": "550e8400-e29b-41d4-a716-446655440000",
            "tableName": "回應字串",
            "sheetName": "回應字串",
            "description": "回應字串",
            "status": {},
            "errorMessage": "回應字串",
            "sourceFile": {
              "id": "550e8400-e29b-41d4-a716-446655440000",
              "name": "回應字串",
              "isFromKnowledgeBase": false
```

```
            },
            "columns": [
              {
                "id": "550e8400-e29b-41d4-a716-446655440000",
                "columnName": "回應字串",
                "columnType": "回應字串",
                "description": "回應字串",
                "isPrimaryKey": false,
                "isNullable": false,
                "createdAt": "回應字串",
                "updatedAt": "回應字串"
              }
            ],
            "createdAt": "回應字串",
            "updatedAt": "回應字串"
          }
        ],
        "chatbots": [
          {
            "id": "550e8400-e29b-41d4-a716-446655440000",
            "name": "回應字串"
          }
        ],
        "groups": [
          {
            "id": "550e8400-e29b-41d4-a716-446655440000",
            "name": "回應字串"
          }
        ],
        "createdAt": "回應字串",
        "updatedAt": "回應字串"
      },
      "canRead": false,
      "canUpdate": false,
      "canDelete": false,
      "createdAt": "回應字串"
    }
  ]
}
```

列出權限清單

GET `/api/v1/permissions/`

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/permissions/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/permissions/", config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/permissions/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/permissions/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
[
  {
    "id": string (uuid)
    "name": string
```

```
    "value": string
    "description": string
    "children": [
      object
    ]
  }
]
```

回應範例值

```
[
  {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應字串",
    "value": "回應字串",
    "description": "回應字串",
    "children": [
      {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "name": "回應範例名稱",
        "description": "回應範例描述"
      }
    ]
  }
]
```

取得角色列表

GET `/api/v1/organizations/{organizationPk}/groups/`

參數

參數名稱	必填	類型	說明

`organizationPk`	V	string	A UUID string identifying this 組織 ID
`page`	X	integer	A page number within the paginated result set.
`pageSize`	X	integer	Number of results to return per page.
`query`	X	string	
`search`	X	string	
`type`	X	string	`owner`: 擁有者 ; `default`: 預設角色 ; `custom`: 自訂角色;

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/organizations/550e8400-
e29b-41d4-a716-446655440000/groups/?
page=1&pageSize=1&query=example&search=example&type=custom"

  -H "Authorization: Api-Key YOUR_API_KEY"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/organizations/550e8400-
e29b-41d4-a716-446655440000/groups/?
page=1&pageSize=1&query=example&search=example&type=custom", config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-
41d4-a716-446655440000/groups/?
page=1&pageSize=1&query=example&search=example&type=custom"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-
41d4-a716-446655440000/groups/?
page=1&pageSize=1&query=example&search=example&type=custom", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
{
  "count": integer
```

```
  "next"?: string (uri) // 非必填
  "previous"?: string (uri) // 非必填
  "results": [
    {
      "id": string (uuid)
      "name": string
      "type":
      {
      }
      "permissions": [
        object
      ]
      "membersPreview": [
        string
      ]
      "membersCount": integer // 返回剩餘成員數量（扣除列表顯示的 3 人後），用於前端 +N badge 顯示

與資源 count 不同：
<ul>
  <li>members_count: 返回 total - 3（用於 +N badge），None 表示總數 <= 3</li>
  <li>chatbots_count/knowledge_bases_count/inboxes_count: 返回總數量</li>
</ul>
      "chatbotsCount": integer
      "chatbotsPreview": [
        string
      ]
      "knowledgeBasesCount": integer
      "knowledgeBasesPreview": [
        string
      ]
      "inboxesCount": integer
      "inboxesPreview": [
        string
      ]
      "databasesCount": integer
      "databasesPreview": [
        string
      ]
      "canCreateChatbot"?: boolean // 非必填
      "canCreateKnowledgeBase"?: boolean // 非必填
      "canCreateInbox"?: boolean // 非必填
      "canCreateDatabase"?: boolean // 非必填
      "canCreateTool"?: boolean // 非必填
      "canCreateAgentUiTool"?: boolean // 非必填
```

```
      "canCreateSkill"?: boolean // 非必填
      "maigptCanCodeInterpreter"?: boolean // Whether members of this
role may use the code interpreter built-in tool in MaiGPT. (非必填)
      "maigptCanRag"?: boolean // Whether members of this role may use
the knowledge base RAG built-in tool in MaiGPT. (非必填)
      "maigptCanDeepResearch"?: boolean // Whether members of this role
may use Deep Research in MaiGPT. Deep Research reaches the public
internet through its own built-in search, so a role that revokes the
official web-search tools needs this switch too. (非必填)
      "maigptCanBrowserTool"?: boolean // Whether members of this role
may use the browser built-in tool in MaiGPT. (非必填)
      "maigptAllLlms"?: boolean // Whether members of this role may use
every organization-available LLM in MaiGPT. Off = only the bound LLMs; an
empty binding then means none. (非必填)
      "maigptAllTools"?: boolean // Whether members of this role may call
every official (global) tool in MaiGPT. Off = only the bound tools; an
empty binding then means none. (非必填)
      "maigptAllConnectors"?: boolean // Whether members of this role may
call every official (global) MCP connector in MaiGPT. Off = only the
bound connectors; an empty binding then means none. (非必填)
      "maigptAllSkills"?: boolean // Whether members of this role may use
every official (global) skill in MaiGPT. Off = only the bound skills; an
empty binding then means none. (非必填)
      "usageStatisticsScope"?:  // What this role's usage statistics
permission shows: the whole organization, or only the AI assistants
granted to the member's roles. A member with any organization-wide
granting role sees the whole organization.

* `organization` - Organization-wide
* `accessible_chatbots` - Authorized AI assistants only (非必填)
      {
      }
      "createdAt": string (timestamp)
    }
  ]
}
```

回應範例值

```
{
  "count": 123,
  "next": "http://api.example.org/accounts/?page=4",
  "previous": "http://api.example.org/accounts/?page=2",
  "results": [
```

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "name": "回應字串",
  "type": {},
  "permissions": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "回應範例名稱",
      "description": "回應範例描述"
    }
  ],
  "membersPreview": [
    "回應字串"
  ],
  "membersCount": 456,
  "chatbotsCount": 456,
  "chatbotsPreview": [
    "回應字串"
  ],
  "knowledgeBasesCount": 456,
  "knowledgeBasesPreview": [
    "回應字串"
  ],
  "inboxesCount": 456,
  "inboxesPreview": [
    "回應字串"
  ],
  "databasesCount": 456,
  "databasesPreview": [
    "回應字串"
  ],
  "canCreateChatbot": false,
  "canCreateKnowledgeBase": false,
  "canCreateInbox": false,
  "canCreateDatabase": false,
  "canCreateTool": false,
  "canCreateAgentUiTool": false,
  "canCreateSkill": false,
  "maigptCanCodeInterpreter": false,
  "maigptCanRag": false,
  "maigptCanDeepResearch": false,
  "maigptCanBrowserTool": false,
  "maigptAllLlms": false,
  "maigptAllTools": false,
  "maigptAllConnectors": false,
```

```
        "maigptAllSkills": false,
        "usageStatisticsScope": {},
        "createdAt": "回應字串"
      }
    ]
}
```


取得角色的詳情

GET `/api/v1/organizations/{organizationPk}/groups/{id}`

參數

參數名稱	必填	類型	說明
`id`	V	string	A UUID string identifying this Group.
`organizationPk`	V	string	A UUID string identifying this 組織 ID

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/organizations/550e8400-
e29b-41d4-a716-446655440000/groups/550e8400-e29b-41d4-a716-
446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/organizations/550e8400-
e29b-41d4-a716-446655440000/groups/550e8400-e29b-41d4-a716-
446655440000/", config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-
41d4-a716-446655440000/groups/550e8400-e29b-41d4-a716-446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-
41d4-a716-446655440000/groups/550e8400-e29b-41d4-a716-
446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
{
  "id": string (uuid)
```

```
  "name": string
  "type":
  {
  }
  "permissions": [
    object
  ]
  "membersPreview": [
    string
  ]
  "membersCount": integer // 返回剩餘成員數量（扣除列表顯示的 3 人後），用於前端 +N badge 顯示

與資源 count 不同：
<ul>
  <li>members_count: 返回 total - 3（用於 +N badge），None 表示總數 <= 3</li>
  <li>chatbots_count/knowledge_bases_count/inboxes_count: 返回總數量</li>
</ul>
  "chatbotsCount": integer
  "chatbotsPreview": [
    string
  ]
  "knowledgeBasesCount": integer
  "knowledgeBasesPreview": [
    string
  ]
  "inboxesCount": integer
  "inboxesPreview": [
    string
  ]
  "databasesCount": integer
  "databasesPreview": [
    string
  ]
  "canCreateChatbot"?: boolean // 非必填
  "canCreateKnowledgeBase"?: boolean // 非必填
  "canCreateInbox"?: boolean // 非必填
  "canCreateDatabase"?: boolean // 非必填
  "canCreateTool"?: boolean // 非必填
  "canCreateAgentUiTool"?: boolean // 非必填
  "canCreateSkill"?: boolean // 非必填
  "maigptCanCodeInterpreter"?: boolean // Whether members of this role may use the code interpreter built-in tool in MaiGPT. (非必填)
  "maigptCanRag"?: boolean // Whether members of this role may use the knowledge base RAG built-in tool in MaiGPT. (非必填)
```

```
  "maigptCanDeepResearch"?: boolean // Whether members of this role may use Deep Research in MaiGPT. Deep Research reaches the public internet through its own built-in search, so a role that revokes the official web-search tools needs this switch too. (非必填)
  "maigptCanBrowserTool"?: boolean // Whether members of this role may use the browser built-in tool in MaiGPT. (非必填)
  "maigptAllLlms"?: boolean // Whether members of this role may use every organization-available LLM in MaiGPT. Off = only the bound LLMs; an empty binding then means none. (非必填)
  "maigptAllTools"?: boolean // Whether members of this role may call every official (global) tool in MaiGPT. Off = only the bound tools; an empty binding then means none. (非必填)
  "maigptAllConnectors"?: boolean // Whether members of this role may call every official (global) MCP connector in MaiGPT. Off = only the bound connectors; an empty binding then means none. (非必填)
  "maigptAllSkills"?: boolean // Whether members of this role may use every official (global) skill in MaiGPT. Off = only the bound skills; an empty binding then means none. (非必填)
  "usageStatisticsScope"?:  // What this role's usage statistics permission shows: the whole organization, or only the AI assistants granted to the member's roles. A member with any organization-wide granting role sees the whole organization.

* `organization` - Organization-wide
* `accessible_chatbots` - Authorized AI assistants only (非必填)
  {
  }
  "createdAt": string (timestamp)
}
```

回應範例值

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "name": "回應字串",
  "type": {},
  "permissions": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "回應範例名稱",
      "description": "回應範例描述"
    }
  ],
  "membersPreview": [
```

```
    "回應字串"
  ],
  "membersCount": 456,
  "chatbotsCount": 456,
  "chatbotsPreview": [
    "回應字串"
  ],
  "knowledgeBasesCount": 456,
  "knowledgeBasesPreview": [
    "回應字串"
  ],
  "inboxesCount": 456,
  "inboxesPreview": [
    "回應字串"
  ],
  "databasesCount": 456,
  "databasesPreview": [
    "回應字串"
  ],
  "canCreateChatbot": false,
  "canCreateKnowledgeBase": false,
  "canCreateInbox": false,
  "canCreateDatabase": false,
  "canCreateTool": false,
  "canCreateAgentUiTool": false,
  "canCreateSkill": false,
  "maigptCanCodeInterpreter": false,
  "maigptCanRag": false,
  "maigptCanDeepResearch": false,
  "maigptCanBrowserTool": false,
  "maigptAllLlms": false,
  "maigptAllTools": false,
  "maigptAllConnectors": false,
  "maigptAllSkills": false,
  "usageStatisticsScope": {},
  "createdAt": "回應字串"
}
```


取得角色成員列表

GET `/api/v1/organizations/{organizationPk}/groups/{groupPk}/group-members/`

參數

參數名稱	必填	類型	說明
`groupPk`	V	string	
`organizationPk`	V	string	A UUID string identifying this 組織 ID
`page`	X	integer	A page number within the paginated result set.
`pageSize`	X	integer	Number of results to return per page.
`query`	X	string	
`search`	X	string	

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/organizations/550e8400-
e29b-41d4-a716-446655440000/groups/550e8400-e29b-41d4-a716-
446655440000/group-members/?
page=1&pageSize=1&query=example&search=example"

  -H "Authorization: Api-Key YOUR_API_KEY"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/organizations/550e8400-
e29b-41d4-a716-446655440000/groups/550e8400-e29b-41d4-a716-
446655440000/group-members/?
page=1&pageSize=1&query=example&search=example", config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-
41d4-a716-446655440000/groups/550e8400-e29b-41d4-a716-
446655440000/group-members/?
page=1&pageSize=1&query=example&search=example"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-
41d4-a716-446655440000/groups/550e8400-e29b-41d4-a716-
446655440000/group-members/?
page=1&pageSize=1&query=example&search=example", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
{
  "count": integer
  "next"?: string (uri) // 非必填
  "previous"?: string (uri) // 非必填
  "results": [
    {
      "id": string (uuid)
      "member": {
      {
        "id": string (uuid)
        "name": string
        "email": string
        "isActive": boolean
        "isOwner": boolean // 檢查成員是否為組織擁有者（透過 OWNER Group）

使用快取避免同一 request 內的重複查詢
快取生命週期：在 member instance 存在期間有效

優先使用 annotation 的結果（如果有的話）避免重複查詢
        "permissions": [ // Compute the permission tree once per
(organization, custom-group set) per request.

The tree depends only on the member's organization (default groups,
feature
flags, plan whitelist), the member's custom groups, and the global
``Config``,
so members sharing a group set get the same result. A large role's
``pagination=false`` listing otherwise recomputes it per row — one Redis
``Config`` fetch plus the permission walk each time (issue #8436; the
largest
prod role has 3,837 members and a single group set). The memo lives in
the
serializer context, so it never outlives the request. Rows without the
eager
loaded ``_custom_groups_cache`` (single-object paths) keep computing
directly.
          object
        ]
        "groups": [
          object
        ]
        "creditQuotaRequired"?: boolean // When True, member must have an
active quota to consume credits (非必填)
        "activeQuota": object // Return the most recent quota summary
```

```
(active first), via prefetch to avoid N+1.
        "metadata": object // Organization-scoped member attributes,
injected into LLM system prompt
        "availabilityStatus":  // Self-declared availability for auto-
assignment. Paused members are skipped by the dispatch engine but can
still be manually assigned or claim conversations. Not touched by SCIM
provisioning.

* `available` - Available
* `paused` - Paused
        {
        }
        "createdAt": string (timestamp)
      }
      }
      "createdAt": string (timestamp)
    }
  ]
}
```

回應範例值

```
{
  "count": 123,
  "next": "http://api.example.org/accounts/?page=4",
  "previous": "http://api.example.org/accounts/?page=2",
  "results": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "member": {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "name": "回應字串",
        "email": "回應字串",
        "isActive": false,
        "isOwner": false,
        "permissions": [
          {
            "id": "550e8400-e29b-41d4-a716-446655440000",
            "name": "回應範例名稱",
            "description": "回應範例描述"
          }
        ],
        "groups": [
          {
```

```
            "id": "550e8400-e29b-41d4-a716-446655440000",
            "name": "回應範例名稱",
            "description": "回應範例描述"
          }
        ],
        "creditQuotaRequired": false,
        "activeQuota": {
          "id": "550e8400-e29b-41d4-a716-446655440000",
          "name": "回應範例名稱",
          "description": "回應範例描述"
        },
        "metadata": null,
        "availabilityStatus": {},
        "createdAt": "回應字串"
      },
      "createdAt": "回應字串"
    }
  ]
}
```


查看特定角色成員

`GET` `/api/v1/organizations/{organizationPk}/groups/{groupPk}/group-members/{id}`

參數

參數名稱	必填	類型	說明
`groupPk`	V	string	
`id`	V	string	A UUID string identifying this Group Member.
`organizationPk`	V	string	A UUID string identifying this 組織 ID

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/organizations/550e8400-
e29b-41d4-a716-446655440000/groups/550e8400-e29b-41d4-a716-
446655440000/group-members/550e8400-e29b-41d4-a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/organizations/550e8400-
e29b-41d4-a716-446655440000/groups/550e8400-e29b-41d4-a716-
446655440000/group-members/550e8400-e29b-41d4-a716-446655440000/",
config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-
41d4-a716-446655440000/groups/550e8400-e29b-41d4-a716-
446655440000/group-members/550e8400-e29b-41d4-a716-446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-
41d4-a716-446655440000/groups/550e8400-e29b-41d4-a716-
446655440000/group-members/550e8400-e29b-41d4-a716-446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
{
  "id": string (uuid)
```

```
  "member": {
  {
    "id": string (uuid)
    "name": string
    "email": string
    "isActive": boolean
    "isOwner": boolean // 檢查成員是否為組織擁有者（透過 OWNER Group）

使用快取避免同一 request 內的重複查詢
快取生命週期：在 member instance 存在期間有效

優先使用 annotation 的結果（如果有的話）避免重複查詢
    "permissions": [ // Compute the permission tree once per
(organization, custom-group set) per request.

The tree depends only on the member's organization (default groups,
feature
flags, plan whitelist), the member's custom groups, and the global
``Config``,
so members sharing a group set get the same result. A large role's
``pagination=false`` listing otherwise recomputes it per row — one Redis
``Config`` fetch plus the permission walk each time (issue #8436; the
largest
prod role has 3,837 members and a single group set). The memo lives in
the
serializer context, so it never outlives the request. Rows without the
eager
loaded ``_custom_groups_cache`` (single-object paths) keep computing
directly.
      object
    ]
    "groups": [
      object
    ]
    "creditQuotaRequired"?: boolean // When True, member must have an
active quota to consume credits (非必填)
    "activeQuota": object // Return the most recent quota summary (active
first), via prefetch to avoid N+1.
    "metadata": object // Organization-scoped member attributes, injected
into LLM system prompt
    "availabilityStatus":  // Self-declared availability for auto-
assignment. Paused members are skipped by the dispatch engine but can
still be manually assigned or claim conversations. Not touched by SCIM
provisioning.
```

```
* `available` - Available
* `paused` - Paused
    {
    }
    "createdAt": string (timestamp)
  }
  }
  "createdAt": string (timestamp)
}
```

回應範例值

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "member": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應字串",
    "email": "回應字串",
    "isActive": false,
    "isOwner": false,
    "permissions": [
      {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "name": "回應範例名稱",
        "description": "回應範例描述"
      }
    ],
    "groups": [
      {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "name": "回應範例名稱",
        "description": "回應範例描述"
      }
    ],
    "creditQuotaRequired": false,
    "activeQuota": {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "回應範例名稱",
      "description": "回應範例描述"
    },
    "metadata": null,
    "availabilityStatus": {},
    "createdAt": "回應字串"
  },
```

```
  "createdAt": "回應字串"
}
```

取得角色的 AI 助理列表

GET `/api/v1/organizations/{organizationPk}/groups/{groupPk}/group-chatbots/`

參數

參數名稱	必填	類型	說明
`groupPk`	V	string	
`organizationPk`	V	string	A UUID string identifying this 組織 ID
`page`	X	integer	A page number within the paginated result set.
`pageSize`	X	integer	Number of results to return per page.
`query`	X	string	
`search`	X	string	

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/organizations/550e8400-
e29b-41d4-a716-446655440000/groups/550e8400-e29b-41d4-a716-
446655440000/group-chatbots/?
page=1&pageSize=1&query=example&search=example"

  -H "Authorization: Api-Key YOUR_API_KEY"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/organizations/550e8400-
e29b-41d4-a716-446655440000/groups/550e8400-e29b-41d4-a716-
446655440000/group-chatbots/?
page=1&pageSize=1&query=example&search=example", config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-
41d4-a716-446655440000/groups/550e8400-e29b-41d4-a716-
446655440000/group-chatbots/?
page=1&pageSize=1&query=example&search=example"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-
41d4-a716-446655440000/groups/550e8400-e29b-41d4-a716-
446655440000/group-chatbots/?
page=1&pageSize=1&query=example&search=example", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
{
  "count": integer
  "next"?: string (uri) // 非必填
  "previous"?: string (uri) // 非必填
  "results": [
    {
      "id": string (uuid)
      "group": string (uuid)
      "chatbot":
      {
        "id": string (uuid)
        "name": string // Chatbot name. In Agent mode it carries semantic meaning; in other modes it only distinguishes chatbots.
        "largeLanguageModel": string (uuid) // 機器人使用的大型語言模型，用於生成回答（含組織自建的 AI Gateway 模型）
        "llm":  // 綁定模型的 id、name 與退役資訊，直接讀取 FK，即使該模型已被組織停用仍會回傳
        {
          "id": string (uuid)
          "name": string
          "retiresAt": string (date) // 供應商退役日；到期後每日排程會把助理換到 replacement 並停用此模型。null 表示未排定退役
          "replacement":  // 退役後接手的模型（id 與 name）；null 表示未指定，到期時不會自動搬移
          {
            "id": string (uuid)
            "name": string
          }
        }
        "embeddingModel"?: string (uuid) // 用於向量化文本的嵌入模型，非必填項目 (非必填)
        "rerankerModel"?: string (uuid) // 用於重新排序的模型，非必填項目 (非必填)
        "instructions"?: string // Role instructions describing the chatbot's role and behavior. (非必填)
        "knowledgeBases"?: [ // 機器人可存取的知識庫列表 (非必填)
          {
            "id": string (uuid)
            "name": string
          }
        ]
        "databases"?: [ // 機器人可存取的 SQL 資料庫列表（用於 Text-to-SQL 功能） (非必填)
          {
```

```
            "id": string (uuid)
            "name": string
          }
        ]
        "updatedAt": string (timestamp)
        "organization"?: string (uuid) // 機器人所屬的組織，如果為空則為個人機器人 (非必填)
        "replyMode"?:  // 回覆模式：一般回覆或串流回覆

* `normal` - 正常
* `template` - 模板
* `hybrid` - 混合
* `agent` - 代理 (非必填)
        {
        }
        "template"?: string // Template used by Template and Hybrid modes. (非必填)
        "unanswerableTemplate"?: string // Template used by Template and Hybrid modes when the question cannot be answered. (非必填)
        "totalWordsCount"?: integer (int64) // Accumulated total word count used. (非必填)
        "outputMode"?:  // 輸出模式：文字、表格或自定義格式

* `text` - 文字
* `json_schema` - JSON Schema (非必填)
        {
        }
        "rawOutputFormat"?: object // 自定義輸出格式的JSON結構定義 (非必填)
        "groups"?: [ // 機器人可存取的群組列表 (非必填)
          {
            "id": string (uuid)
            "name": string
          }
        ]
        "tools"?: [ // 機器人可使用的工具列表 (非必填)
          {
            "id": string (uuid)
            "name": string
            "description": string
            "displayName": string
            "toolType": string
          }
        ]
        "skills"?: [ // 機器人關聯的技能列表 (非必填)
          {
```

```
            "id": string (uuid)
            "name": string
            "description": string
          }
        ]
        "connectors"?: [ // Connectors associated with this chatbot,
gating per-contact OAuth authorization (非必填)
          {
            "id": string (uuid)
            "name": string
          }
        ]
        "agentMode"?:  // 代理模式：一般、SQL或工作流程模式

* `normal` - 正常
* `canvas` - 畫布
* `team` - 團隊 (非必填)
        {
        }
        "numberOfRetrievedChunks"?: integer // 提取的參考資料數量，預設為 12，
最小值為 1 (非必填)
        "defaultLabelRelations"?: object // 助理層級的預設知識庫標籤過濾條件，
格式同 query_metadata.label_relations；null 表示不過濾。僅在呼叫端未帶
query_metadata 時作為最低優先序兜底套用。 (非必填)
        "useFullRetrievalRange"?: boolean // 啟用後忽略 LLM 的 top_k 截斷，回
傳完整 reranker 結果 (非必填)
        "enableEvaluation"?: boolean // 非必填
        "enableInlineCitations"?: boolean // Enables inline citations,
inserting citation markers such as [1][2] into responses. (非必填)
        "enableCodeInterpreter"?: boolean // When enabled, provides the
Code Interpreter tool to run code in an isolated container. (非必填)
        "enableBrowserTool"?: boolean // Enable browser automation tool
for web tasks (非必填)
        "enableImageSearch"?: boolean // Provide the image_search tool
when any attached knowledge base uses a multimodal embedding model.
Disable to remove the tool entirely. (非必填)
        "enableClaudeStreamRetry"?: boolean // When a Claude streaming
call stalls (first-chunk or mid-stream), abort and re-issue the call once
in non-streaming mode. Mid-stream retries send a reset signal so the
client discards any partial output already rendered. Each retry incurs a
second billing for the same prompt. (非必填)
        "customMaxLlmOutputTokens"?: integer // 自訂最大 LLM 輸出 token 數，
最小值為 512 (非必填)
        "voiceConfig"?: { // 非必填
        {
```

```
          "enabled"?: boolean // Whether this chatbot can be used as a
voice agent. Checked by every conversation platform (WebChat, SIP phone,
admin/marketplace voice test) instead of a per-platform toggle. (非必填)
          "voiceAgentType"?: string (uuid) // Voice agent mode type. (非必
填)
          "sttProvider"?: string (uuid) // Speech-to-Text service
provider. (非必填)
          "sttConfig"?: object // STT configuration parameters (JSON). (非
必填)
          "ttsProvider"?: string (uuid) // Text-to-Speech service
provider. (非必填)
          "ttsConfig"?: object // TTS configuration parameters (JSON). (非
必填)
          "realtimeProvider"?: string (uuid) // Realtime end-to-end voice
model provider. (非必填)
          "realtimeConfig"?: object // Realtime configuration parameters
(JSON). (非必填)
          "realtimeInstructions"?: string // Prompt dedicated to the
realtime voice session; falls back to chatbot instructions when empty (非
必填)
          "turnHandling"?: object // Turn-taking and interruption
settings for the voice agent. (非必填)
          "enableVoiceReply"?: boolean // When disabled, the voice agent
replies in text only and does not speak (非必填)
        }
        }
        "thinkingConfig"?: object // 思考等級：null（模型預設）或
{"reasoning_effort": "off|minimal|low|medium|high|xhigh|max"} (非必填)
        "enableToolSearching"?: boolean // 啟用動態工具搜尋功能，允許 agent 透
過 tool_searching_tool 動態發現和加載工具 (非必填)
        "maxAgentIterations"?: integer // Maximum number of iterations
for AgentWorkflow (1-100, default: 20) (非必填)
        "agentTimeoutSeconds"?: integer // Timeout in seconds for
AgentWorkflow execution (30-1200, default: 600) (非必填)
        "agentTimeoutMessage"?: string // Custom user-facing message
shown when AgentWorkflow times out (max 500 chars). Leave empty to use
the system default. (非必填)
        "requireTextWithFlexCards"?: boolean // When enabled, a turn that
would end with only Flex Message cards and no text for the user is re-
issued to the LLM once, asking it to write the text first and then send
the card. Each retry incurs a second billing for the same prompt. (非必填)
        "isMultimodalLlm": boolean // Whether the chatbot LLM supports
multimodal (read-only)
        "enableSizeBasedToolResultTruncation"?: boolean // When enabled,
tool results exceeding the character threshold are kept as head+tail
```

```
(with the identifiers found in the cut part) when written to conversation history; knowledge base, SQL and conversation search results keep their 100-character cut either way. Reduces memory bloat from large tool outputs (code interpreter bash stdout, web search results, etc.). (非必填)
        "toolResultMaxChars"?: integer // Character threshold for size-based tool result truncation (500-50000). Only effective when enable_size_based_tool_result_truncation is True. (非必填)
        "enableVectorMemory"?: boolean // When enabled, archived messages are vectorized and processed by fact extraction for semantic retrieval (existing behavior). When disabled, archived messages are discarded and only the active chat history window is used for multi-turn context. (非必填)
        "longTermMemoryTopK"?: integer // 長期記憶每次檢索取回的記憶節點數（向量檢索的 similarity_top_k），預設為 10，範圍 1–50 (非必填)
        "enableCrossConversationSearch"?: boolean // When enabled, the conversation history tools also reach this contact's other conversations in the same inbox, within the lookback window. When disabled, they only reach the current conversation. (非必填)
        "crossConversationLookbackDays"?: integer // How far back cross-conversation search may reach, measured from each conversation's last message (1-365 days). Leave empty to fall back to 90 days. Only effective when enable_cross_conversation_search is True. (非必填)
        "useGatewayFallback"?: boolean // When enabled, use the fallback group instead of the single LLM (非必填)
        "gatewayFallbackGroup"?: string (uuid) // 非必填
        "enableSearchMessagesTool"?: boolean // Allow the AI to search past messages in the current conversation. (非必填)
        "enableGetMessageContextTool"?: boolean // Allow the AI to retrieve messages surrounding a specific message for context. (非必填)
        "enableReadAttachmentFullTextTool"?: boolean // Allow the AI to read the full text of plain-text attachments. AGENT mode only. (非必填)
        "enableParseAttachmentContentTool"?: boolean // Allow the AI to parse PDF, Office, audio, and other attachments. AGENT mode only. (非必填)
        "enableListAvailableParsersTool"?: boolean // Allow the AI to list available parsers and their capabilities. AGENT mode only. (非必填)
        "enableGetDownloadLinkTool"?: boolean // Allow the AI to generate shareable download links for produced content. AGENT mode only. (非必填)
        "isLocked": boolean // Locked instance: config follows the official version; only the dedicated KB can be modified
        "sourceBuildInAgent": string (uuid) // Points to the official Build-in Agent blueprint when instantiated by a rental
        "canUpdate": boolean // Return whether the current user can update this resource.
        "canDelete": boolean // Return whether the current user can delete this resource.
```

```
        "team":
        {
          "id": string (uuid)
          "name": string
        }
        "webChatIsActive"?: boolean // Optional, create only. Whether the
web widget channel starts active. Omitted or null: follows the
organization's default for new chatbot channels (inactive unless a
platform admin turned it on). Ignored on update; change an existing
channel from its channel settings instead. (非必填)
        "apiIsActive"?: boolean // Optional, create only. Whether the API
channel starts active. Omitted or null: follows the organization's
default for new chatbot channels (inactive unless a platform admin turned
it on). Ignored on update; change an existing channel from its channel
settings instead. The backstage (admin) channel always starts active and
cannot be set here. (非必填)
        "fileWorkspaceMode"?:  // File workspace mode in Work internal
conversations: none, bound or user_mount.

* `none` - None
* `bound` - Bound workspace
* `user_mount` - User mount (非必填)
        {
        }
        "fileWorkspaceFolder"?: string (uuid) // The bound workspace
(folder id); required when the mode is bound, cleared otherwise. (非必填)
        "fileWorkspaceStatus": object // Read-only. {"folder": {"id",
"name"} | null, "state": "ok" | "missing" | "builder_lost_edit" | null}
        "fileWorkspaceAvailable": boolean // Read-only. Whether the
organization has the file library and this agent can configure a file
workspace.
      }
      "canRead"?: boolean // 非必填
      "canUpdate"?: boolean // 非必填
      "canDelete"?: boolean // 非必填
      "createdAt": string (timestamp)
    }
  ]
}
```

回應範例值

```
{
  "count": 123,
```

```
  "next": "http://api.example.org/accounts/?page=4",
  "previous": "http://api.example.org/accounts/?page=2",
  "results": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "group": "550e8400-e29b-41d4-a716-446655440000",
      "chatbot": {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "name": "回應字串",
        "largeLanguageModel": "550e8400-e29b-41d4-a716-446655440000",
        "llm": {
          "id": "550e8400-e29b-41d4-a716-446655440000",
          "name": "回應字串",
          "retiresAt": "回應字串",
          "replacement": {
            "id": "550e8400-e29b-41d4-a716-446655440000",
            "name": "回應字串"
          }
        },
        "embeddingModel": "550e8400-e29b-41d4-a716-446655440000",
        "rerankerModel": "550e8400-e29b-41d4-a716-446655440000",
        "instructions": "回應字串",
        "knowledgeBases": [
          {
            "id": "550e8400-e29b-41d4-a716-446655440000",
            "name": "回應字串"
          }
        ],
        "databases": [
          {
            "id": "550e8400-e29b-41d4-a716-446655440000",
            "name": "回應字串"
          }
        ],
        "updatedAt": "回應字串",
        "organization": "550e8400-e29b-41d4-a716-446655440000",
        "replyMode": {},
        "template": "回應字串",
        "unanswerableTemplate": "回應字串",
        "totalWordsCount": 456,
        "outputMode": {},
        "rawOutputFormat": null,
        "groups": [
          {
            "id": "550e8400-e29b-41d4-a716-446655440000",
```

```
      "name": "回應字串"
    }
  ],
  "tools": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "回應字串",
      "description": "回應字串",
      "displayName": "回應字串",
      "toolType": "回應字串"
    }
  ],
  "skills": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "回應字串",
      "description": "回應字串"
    }
  ],
  "connectors": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "回應字串"
    }
  ],
  "agentMode": {},
  "numberOfRetrievedChunks": 456,
  "defaultLabelRelations": null,
  "useFullRetrievalRange": false,
  "enableEvaluation": false,
  "enableInlineCitations": false,
  "enableCodeInterpreter": false,
  "enableBrowserTool": false,
  "enableImageSearch": false,
  "enableClaudeStreamRetry": false,
  "customMaxLlmOutputTokens": 456,
  "voiceConfig": {
    "enabled": false,
    "voiceAgentType": "550e8400-e29b-41d4-a716-446655440000",
    "sttProvider": "550e8400-e29b-41d4-a716-446655440000",
    "sttConfig": null,
    "ttsProvider": "550e8400-e29b-41d4-a716-446655440000",
    "ttsConfig": null,
    "realtimeProvider": "550e8400-e29b-41d4-a716-446655440000",
    "realtimeConfig": null,
```

```
          "realtimeInstructions": "回應字串",
          "turnHandling": null,
          "enableVoiceReply": false
        },
        "thinkingConfig": null,
        "enableToolSearching": false,
        "maxAgentIterations": 456,
        "agentTimeoutSeconds": 456,
        "agentTimeoutMessage": "回應字串",
        "requireTextWithFlexCards": false,
        "isMultimodalLlm": false,
        "enableSizeBasedToolResultTruncation": false,
        "toolResultMaxChars": 456,
        "enableVectorMemory": false,
        "longTermMemoryTopK": 456,
        "enableCrossConversationSearch": false,
        "crossConversationLookbackDays": 456,
        "useGatewayFallback": false,
        "gatewayFallbackGroup": "550e8400-e29b-41d4-a716-446655440000",
        "enableSearchMessagesTool": false,
        "enableGetMessageContextTool": false,
        "enableReadAttachmentFullTextTool": false,
        "enableParseAttachmentContentTool": false,
        "enableListAvailableParsersTool": false,
        "enableGetDownloadLinkTool": false,
        "isLocked": false,
        "sourceBuildInAgent": "550e8400-e29b-41d4-a716-446655440000",
        "canUpdate": false,
        "canDelete": false,
        "team": {
          "id": "550e8400-e29b-41d4-a716-446655440000",
          "name": "回應字串"
        },
        "webChatIsActive": false,
        "apiIsActive": false,
        "fileWorkspaceMode": {},
        "fileWorkspaceFolder": "550e8400-e29b-41d4-a716-446655440000",
        "fileWorkspaceStatus": {
          "name": "example.pdf",
          "content": "base64encoded_content",
          "contentType": "application/pdf"
        },
        "fileWorkspaceAvailable": false
      },
      "canRead": false,
```

```
        "canUpdate": false,
        "canDelete": false,
        "createdAt": "回應字串"
      }
    ]
}
```


取得角色的收件匣列表

GET `/api/v1/organizations/{organizationPk}/groups/{groupPk}/group-inboxes/`

參數

參數名稱	必填	類型	說明
`groupPk`	V	string	
`organizationPk`	V	string	A UUID string identifying this 組織 ID
`channelType`	X	string	`line`: LINE ; `telegram`: Telegram ; `teams`: Teams ; `web`: Web ; `messenger`: Messenger ; `instagram`: Instagram ; `email`: Email ; `whatsapp`: WhatsApp ; `slack`: Slack ; `team_plus`: Team+ ; `lin...
`chatbot`	X	string	
`isActive`	X	boolean	
`page`	X	integer	A page number within the paginated result set.
`pageSize`	X	integer	Number of results to return per page.
`query`	X	string	

search	X	string	

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-41d4-a716-446655440000/groups/550e8400-e29b-41d4-a716-446655440000/group-inboxes/?channelType=email&chatbot=550e8400-e29b-41d4-a716-446655440000&isActive=true&page=1&pageSize=1&query=example&search=example"

  -H "Authorization: Api-Key YOUR_API_KEY"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-41d4-a716-446655440000/groups/550e8400-e29b-41d4-a716-446655440000/group-inboxes/?channelType=email&chatbot=550e8400-e29b-41d4-a716-446655440000&isActive=true&page=1&pageSize=1&query=example&search=example", config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-41d4-a716-446655440000/groups/550e8400-e29b-41d4-a716-446655440000/group-inboxes/?channelType=email&chatbot=550e8400-e29b-41d4-a716-446655440000&isActive=true&page=1&pageSize=1&query=example&search=example"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-
41d4-a716-446655440000/groups/550e8400-e29b-41d4-a716-
446655440000/group-inboxes/?channelType=email&chatbot=550e8400-e29b-
41d4-a716-
446655440000&isActive=true&page=1&pageSize=1&query=example&search=ex
ample", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
{
  "count": integer
  "next"?: string (uri) // 非必填
  "previous"?: string (uri) // 非必填
  "results": [
    {
      "id": string (uuid)
      "group": string (uuid)
      "inbox":
      {
        "id": string (uuid)
        "channelType": string (enum: line, telegram, teams, web,
messenger, instagram, email, whatsapp, slack, team_plus, line_works,
viber) // * `line` - LINE
* `telegram` - Telegram
* `teams` - Teams
* `web` - Web
* `messenger` - Messenger
* `instagram` - Instagram
* `email` - Email
* `whatsapp` - WhatsApp
* `slack` - Slack
* `team_plus` - Team+
* `line_works` - LINE WORKS
* `viber` - Viber
        "name": string
        "unreadConversationsCount": integer
        "accessType": string
      }
      "canRead"?: boolean // 非必填
      "canUpdate"?: boolean // 非必填
      "canDelete"?: boolean // 非必填
      "canViewConversations"?: boolean // Whether group members can
browse all conversations of this inbox in the conversations page.
Independent from can_read, which controls using the inbox for chatting.
(非必填)
      "createdAt": string (timestamp)
    }
  ]
}
```

回應範例值

```
{
  "count": 123,
  "next": "http://api.example.org/accounts/?page=4",
  "previous": "http://api.example.org/accounts/?page=2",
  "results": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "group": "550e8400-e29b-41d4-a716-446655440000",
      "inbox": {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "channelType": "line",
        "name": "回應字串",
        "unreadConversationsCount": 456,
        "accessType": "回應字串"
      },
      "canRead": false,
      "canUpdate": false,
      "canDelete": false,
      "canViewConversations": false,
      "createdAt": "回應字串"
    }
  ]
}
```


取得角色的知識庫列表

`GET` `/api/v1/organizations/{organizationPk}/groups/{groupPk}/group-knowledge-bases/`

參數

參數名稱	必填	類型	說明
groupPk	V	string	

`organizationPk`	V	string	A UUID string identifying this 組織 ID
`page`	X	integer	A page number within the paginated result set.
`pageSize`	X	integer	Number of results to return per page.
`query`	X	string	
`search`	X	string	

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/organizations/550e8400-
e29b-41d4-a716-446655440000/groups/550e8400-e29b-41d4-a716-
446655440000/group-knowledge-bases/?
page=1&pageSize=1&query=example&search=example"

  -H "Authorization: Api-Key YOUR_API_KEY"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/organizations/550e8400-
e29b-41d4-a716-446655440000/groups/550e8400-e29b-41d4-a716-
446655440000/group-knowledge-bases/?
page=1&pageSize=1&query=example&search=example", config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-
41d4-a716-446655440000/groups/550e8400-e29b-41d4-a716-
446655440000/group-knowledge-bases/?
page=1&pageSize=1&query=example&search=example"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-
41d4-a716-446655440000/groups/550e8400-e29b-41d4-a716-
446655440000/group-knowledge-bases/?
page=1&pageSize=1&query=example&search=example", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
{
  "count": integer
  "next"?: string (uri) // 非必填
  "previous"?: string (uri) // 非必填
  "results": [
    {
      "id": string (uuid)
      "group": string (uuid)
      "knowledgeBase":
      {
        "id": string (uuid)
        "createdBy":
        {
          "id": string (uuid)
          "name": string
        }
        "organization"?: string (uuid) // 非必填
        "embeddingModel": string (uuid)
        "rerankerModel": string (uuid)
        "name": string
        "description"?: string // 非必填
        "numberOfRetrievedChunks"?: integer // 提取的參考資料數量，預設為 12，
最小值為 1 (非必填)
        "enableHyde"?: boolean // 啟用 HyDE，預設為 False (非必填)
        "similarityCutoff"?: number (double) // 相似度門檻，預設為 0.0，範圍為
0.0-1.0 (非必填)
        "enableRerank"?: boolean // 是否啟用重新排序，預設為 True (非必填)
        "enableRrf"?: boolean // Enable Reciprocal Rank Fusion for hybrid
search. Disable this if using a custom Elasticsearch without enterprise
license. (非必填)
        "vectorDatabaseType"?:  // Type of vector database: elasticsearch
or opensearch.

* `elasticsearch` - Elasticsearch
* `opensearch` - OpenSearch
* `oracle` - Oracle AI Database 26ai
* `synxdb` - SynxDB (非必填)
        {
        }
        "vectorDatabaseUrl"?: string // Custom vector database endpoint
URL or Oracle DSN. For Elasticsearch/OpenSearch: URL format (e.g.,
"https://host:9200"). For Oracle: DSN format (e.g.,
"host:1521/service_name"). (非必填)
        "vectorDatabaseApiKey"?: string // API Key for Elasticsearch. Not
```

```
used for OpenSearch. (非必填)
        "opensearchUsername"?: string // Username for OpenSearch Basic
Auth. (非必填)
        "opensearchPassword"?: string // Password for OpenSearch Basic
Auth. (非必填)
        "oracleUser"?: string // Oracle database username. (非必填)
        "oraclePassword"?: string // Oracle database password. (非必填)
        "synxdbUser"?: string // SynxDB database username. (非必填)
        "synxdbPassword"?: string // SynxDB database password. (非必填)
        "labels": [
          {
            "id": string (uuid)
            "name": string
          }
        ]
        "chatbots"?: [ // 非必填
          {
            "id": string (uuid)
            "name": string
          }
        ]
        "groups"?: [ // 知識庫可存取的群組列表 (非必填)
          {
            "id": string (uuid)
            "name": string
          }
        ]
        "filesCount": integer // Return count of KnowledgeBaseFile
excluding processed files, conversation attachments, and soft-deleted.
        "vectorStorageSize": integer
        "chunksCount": integer
        "canUpdate": boolean // Return whether the current user can
update this resource.
        "canDelete": boolean // Return whether the current user can
delete this resource.
        "createdAt": string (timestamp)
        "updatedAt": string (timestamp)
      }
      "canRead"?: boolean // 非必填
      "canUpdate"?: boolean // 非必填
      "canDelete"?: boolean // 非必填
      "createdAt": string (timestamp)
    }
```

```
  ]
}
```

回應範例值


```
{
  "count": 123,
  "next": "http://api.example.org/accounts/?page=4",
  "previous": "http://api.example.org/accounts/?page=2",
  "results": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "group": "550e8400-e29b-41d4-a716-446655440000",
      "knowledgeBase": {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "createdBy": {
          "id": "550e8400-e29b-41d4-a716-446655440000",
          "name": "回應字串"
        },
        "organization": "550e8400-e29b-41d4-a716-446655440000",
        "embeddingModel": "550e8400-e29b-41d4-a716-446655440000",
        "rerankerModel": "550e8400-e29b-41d4-a716-446655440000",
        "name": "回應字串",
        "description": "回應字串",
        "numberOfRetrievedChunks": 456,
        "enableHyde": false,
        "similarityCutoff": 456,
        "enableRerank": false,
        "enableRrf": false,
        "vectorDatabaseType": {},
        "vectorDatabaseUrl": "回應字串",
        "vectorDatabaseApiKey": "回應字串",
        "opensearchUsername": "回應字串",
        "opensearchPassword": "回應字串",
        "oracleUser": "回應字串",
        "oraclePassword": "回應字串",
        "synxdbUser": "回應字串",
        "synxdbPassword": "回應字串",
        "labels": [
          {
            "id": "550e8400-e29b-41d4-a716-446655440000",
            "name": "回應字串"
          }
        ],
```

```
        "chatbots": [
          {
            "id": "550e8400-e29b-41d4-a716-446655440000",
            "name": "回應字串"
          }
        ],
        "groups": [
          {
            "id": "550e8400-e29b-41d4-a716-446655440000",
            "name": "回應字串"
          }
        ],
        "filesCount": 456,
        "vectorStorageSize": 456,
        "chunksCount": 456,
        "canUpdate": false,
        "canDelete": false,
        "createdAt": "回應字串",
        "updatedAt": "回應字串"
      },
      "canRead": false,
      "canUpdate": false,
      "canDelete": false,
      "createdAt": "回應字串"
    }
  ]
}
```


取得角色的資料庫列表

`GET` `/api/v1/organizations/{organizationPk}/groups/{groupPk}/group-databases/`

參數

參數名稱	必填	類型	說明

`groupPk`	V	string	
`organizationPk`	V	string	A UUID string identifying this 組織 ID
`page`	X	integer	A page number within the paginated result set.
`pageSize`	X	integer	Number of results to return per page.
`query`	X	string	
`search`	X	string	

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/organizations/550e8400-
e29b-41d4-a716-446655440000/groups/550e8400-e29b-41d4-a716-
446655440000/group-databases/?
page=1&pageSize=1&query=example&search=example"

  -H "Authorization: Api-Key YOUR_API_KEY"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/organizations/550e8400-
e29b-41d4-a716-446655440000/groups/550e8400-e29b-41d4-a716-
446655440000/group-databases/?
page=1&pageSize=1&query=example&search=example", config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-
41d4-a716-446655440000/groups/550e8400-e29b-41d4-a716-
446655440000/group-databases/?
page=1&pageSize=1&query=example&search=example"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-
41d4-a716-446655440000/groups/550e8400-e29b-41d4-a716-
446655440000/group-databases/?
page=1&pageSize=1&query=example&search=example", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
{
  "count": integer
  "next"?: string (uri) // 非必填
  "previous"?: string (uri) // 非必填
  "results": [
    {
      "id": string (uuid)
      "group": string (uuid)
      "database":
      {
        "id": string (uuid)
        "name": string // Display name for this database connection
        "description": string // Description of the database and its
purpose
        "databaseType":  // Type of database: PostgreSQL, MySQL, MSSQL,
Oracle, SynxDB, or MaiAgent

* `postgresql` - PostgreSQL
* `mysql` - MySQL
* `maiagent` - MaiAgent
* `oracle` - Oracle
* `mssql` - MSSQL
* `synxdb` - SynxDB
        {
        }
        "includeTables": object // Optional list of tables to include.
Format: {"tables": ["table1", "table2"]}. For MaiAgent type, this is
auto-populated from uploaded files.
        "isActive": boolean // When disabled, this database will not be
used in Text-to-SQL queries
        "status":
        {
        }
        "deletedAt": string (timestamp)
        "tables": [
          {
            "id": string (uuid)
            "tableName": string // Name of the table in the database
            "sheetName": string // Name of the source worksheet/sheet
this table was created from. Empty for tables created before this field
was added.
            "description"?: string // Description of the table and its
data for better Text-to-SQL understanding (非必填)
            "status":
```

```
            {
            }
            "errorMessage": string // Error details if table creation or
deletion failed
            "sourceFile":
            {
              "id": string (uuid)
              "name": string
              "isFromKnowledgeBase": boolean // Determine if the source
file originated from a knowledge base upload.

Returns True if the file was uploaded via knowledge base,
False if uploaded directly to the database.
            }
            "columns": [
              {
                "id": string (uuid)
                "columnName": string
                "columnType"?: string // Data type of the column (e.g.,
VARCHAR, INTEGER, TIMESTAMP) (非必填)
                "description"?: string // Description of the column for
better Text-to-SQL understanding (非必填)
                "isPrimaryKey"?: boolean // 非必填
                "isNullable"?: boolean // 非必填
                "createdAt": string (timestamp)
                "updatedAt": string (timestamp)
              }
            ]
            "createdAt": string (timestamp)
            "updatedAt": string (timestamp)
          }
        ]
        "chatbots": [
          {
            "id": string (uuid)
            "name": string
          }
        ]
        "groups": [
          {
            "id": string (uuid)
            "name": string
          }
        ]
        "createdAt": string (timestamp)
```

```
        "updatedAt": string (timestamp)
      }
      "canRead"?: boolean // 非必填
      "canUpdate"?: boolean // 非必填
      "canDelete"?: boolean // 非必填
      "createdAt": string (timestamp)
    }
  ]
}
```

回應範例值

```
{
  "count": 123,
  "next": "http://api.example.org/accounts/?page=4",
  "previous": "http://api.example.org/accounts/?page=2",
  "results": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "group": "550e8400-e29b-41d4-a716-446655440000",
      "database": {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "name": "回應字串",
        "description": "回應字串",
        "databaseType": {},
        "includeTables": null,
        "isActive": false,
        "status": {},
        "deletedAt": "回應字串",
        "tables": [
          {
            "id": "550e8400-e29b-41d4-a716-446655440000",
            "tableName": "回應字串",
            "sheetName": "回應字串",
            "description": "回應字串",
            "status": {},
            "errorMessage": "回應字串",
            "sourceFile": {
              "id": "550e8400-e29b-41d4-a716-446655440000",
              "name": "回應字串",
              "isFromKnowledgeBase": false
            },
            "columns": [
              {
```

```
                "id": "550e8400-e29b-41d4-a716-446655440000",
                "columnName": "回應字串",
                "columnType": "回應字串",
                "description": "回應字串",
                "isPrimaryKey": false,
                "isNullable": false,
                "createdAt": "回應字串",
                "updatedAt": "回應字串"
              }
            ],
            "createdAt": "回應字串",
            "updatedAt": "回應字串"
          }
        ],
        "chatbots": [
          {
            "id": "550e8400-e29b-41d4-a716-446655440000",
            "name": "回應字串"
          }
        ],
        "groups": [
          {
            "id": "550e8400-e29b-41d4-a716-446655440000",
            "name": "回應字串"
          }
        ],
        "createdAt": "回應字串",
        "updatedAt": "回應字串"
      },
      "canRead": false,
      "canUpdate": false,
      "canDelete": false,
      "createdAt": "回應字串"
    }
  ]
}
```


更新角色權限

PUT `/api/v1/organizations/{organizationPk}/groups/{id}`

參數

參數名稱	必填	類型	說明
`id`	V	string	A UUID string identifying this Group.
`organizationPk`	V	string	A UUID string identifying this 組織 ID

請求內容

請求參數

欄位	類型	必填	說明
name	string	是	
organization	string (uuid)	否	
permissions	array[string]	是	
canCreateChatbot	boolean	否	
canCreateKnowledgeBase	boolean	否	
canCreateInbox	boolean	否	
canCreateDatabase	boolean	否	
canCreateTool	boolean	否	
canCreateAgentUiTool	boolean	否	
canCreateSkill	boolean	否	
maigptCanCodeInterpreter	boolean	否	Whether members of this role may use the code interpreter built-in tool in MaiGPT.

欄位	類型	必填	說明
maigptCanRag	boolean	否	Whether members of this role may use the knowledge base RAG built-in tool in MaiGPT.
maigptCanDeepResearch	boolean	否	Whether members of this role may use Deep Research in MaiGPT. Deep Research reaches the public internet through its own built-in search, so a role that revokes the official web-search tools needs this...
maigptCanBrowserTool	boolean	否	Whether members of this role may use the browser built-in tool in MaiGPT.
maigptAllLlms	boolean	否	Whether members of this role may use every organization-available LLM in MaiGPT. Off = only the bound LLMs; an empty binding then means none.
maigptAllTools	boolean	否	Whether members of this role may call every official (global) tool in MaiGPT. Off = only the bound tools; an empty binding then means none.
maigptAllConnectors	boolean	否	Whether members of this role may call every official (global) MCP connector in MaiGPT. Off = only the bound connectors; an empty binding then means none.
maigptAllSkills	boolean	否	Whether members of this role may use every official (global) skill in MaiGPT. Off = only the bound skills; an empty binding then means none.
usageStatisticsScope	object	否	What this role's usage statistics permission shows: the whole organization, or only the AI assistants granted to the member's roles. A member with any organization-wide granting role sees the whole or...
allowedLlms	array[string]	否	

欄位	類型	必填	說明
allowedTools	array[string]	否	
allowedConnectors	array[string]	否	
allowedSkills	array[string]	否	

請求結構範例

```
{
  "name": string
  "organization"?: string (uuid) // 非必填
  "permissions": [
    string (uuid)
  ]
  "canCreateChatbot"?: boolean // 非必填
  "canCreateKnowledgeBase"?: boolean // 非必填
  "canCreateInbox"?: boolean // 非必填
  "canCreateDatabase"?: boolean // 非必填
  "canCreateTool"?: boolean // 非必填
  "canCreateAgentUiTool"?: boolean // 非必填
  "canCreateSkill"?: boolean // 非必填
  "maigptCanCodeInterpreter"?: boolean // Whether members of this role may use the code interpreter built-in tool in MaiGPT. (非必填)
  "maigptCanRag"?: boolean // Whether members of this role may use the knowledge base RAG built-in tool in MaiGPT. (非必填)
  "maigptCanDeepResearch"?: boolean // Whether members of this role may use Deep Research in MaiGPT. Deep Research reaches the public internet through its own built-in search, so a role that revokes the official web-search tools needs this switch too. (非必填)
  "maigptCanBrowserTool"?: boolean // Whether members of this role may use the browser built-in tool in MaiGPT. (非必填)
  "maigptAllLlms"?: boolean // Whether members of this role may use every organization-available LLM in MaiGPT. Off = only the bound LLMs; an empty binding then means none. (非必填)
  "maigptAllTools"?: boolean // Whether members of this role may call every official (global) tool in MaiGPT. Off = only the bound tools; an empty binding then means none. (非必填)
  "maigptAllConnectors"?: boolean // Whether members of this role may call every official (global) MCP connector in MaiGPT. Off = only the bound connectors; an empty binding then means none. (非必填)
  "maigptAllSkills"?: boolean // Whether members of this role may use every official (global) skill in MaiGPT. Off = only the bound skills; an
```

```
empty binding then means none. (非必填)
  "usageStatisticsScope"?:  // What this role's usage statistics
permission shows: the whole organization, or only the AI assistants
granted to the member's roles. A member with any organization-wide
granting role sees the whole organization.

* `organization` - Organization-wide
* `accessible_chatbots` - Authorized AI assistants only (非必填)
  {
  }
  "allowedLlms"?: [ // 非必填
    string (uuid)
  ]
  "allowedTools"?: [ // 非必填
    string (uuid)
  ]
  "allowedConnectors"?: [ // 非必填
    string (uuid)
  ]
  "allowedSkills"?: [ // 非必填
    string (uuid)
  ]
}
```

請求範例值

```
{
  "name": "範例名稱",
  "organization": "550e8400-e29b-41d4-a716-446655440000",
  "permissions": [
    "550e8400-e29b-41d4-a716-446655440000"
  ],
  "canCreateChatbot": true,
  "canCreateKnowledgeBase": true,
  "canCreateInbox": true,
  "canCreateDatabase": true,
  "canCreateTool": true,
  "canCreateAgentUiTool": true,
  "canCreateSkill": true,
  "maigptCanCodeInterpreter": true,
  "maigptCanRag": true,
  "maigptCanDeepResearch": true,
  "maigptCanBrowserTool": true,
  "maigptAllLlms": true,
```

```
  "maigptAllTools": true,
  "maigptAllConnectors": true,
  "maigptAllSkills": true,
  "usageStatisticsScope": {},
  "allowedLlms": [
    "550e8400-e29b-41d4-a716-446655440000"
  ],
  "allowedTools": [
    "550e8400-e29b-41d4-a716-446655440000"
  ],
  "allowedConnectors": [
    "550e8400-e29b-41d4-a716-446655440000"
  ],
  "allowedSkills": [
    "550e8400-e29b-41d4-a716-446655440000"
  ]
}
```


程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X PUT "https://api.maiagent.ai/api/v1/organizations/550e8400-
e29b-41d4-a716-446655440000/groups/550e8400-e29b-41d4-a716-
446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "name": "範例名稱",
    "organization": "550e8400-e29b-41d4-a716-446655440000",
    "permissions": [
      "550e8400-e29b-41d4-a716-446655440000"
    ],
    "canCreateChatbot": true,
    "canCreateKnowledgeBase": true,
    "canCreateInbox": true,
    "canCreateDatabase": true,
    "canCreateTool": true,
    "canCreateAgentUiTool": true,
    "canCreateSkill": true,
    "maigptCanCodeInterpreter": true,
    "maigptCanRag": true,
    "maigptCanDeepResearch": true,
    "maigptCanBrowserTool": true,
    "maigptAllLlms": true,
    "maigptAllTools": true,
    "maigptAllConnectors": true,
    "maigptAllSkills": true,
    "usageStatisticsScope": {},
    "allowedLlms": [
      "550e8400-e29b-41d4-a716-446655440000"
    ],
    "allowedTools": [
      "550e8400-e29b-41d4-a716-446655440000"
    ],
    "allowedConnectors": [
      "550e8400-e29b-41d4-a716-446655440000"
    ],
```

```
    "allowedSkills": [
      "550e8400-e29b-41d4-a716-446655440000"
    ]
  }'

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// 請求內容 (payload)
const data = {
    "name": "範例名稱",
    "organization": "550e8400-e29b-41d4-a716-446655440000",
    "permissions": [
      "550e8400-e29b-41d4-a716-446655440000"
    ],
    "canCreateChatbot": true,
    "canCreateKnowledgeBase": true,
    "canCreateInbox": true,
    "canCreateDatabase": true,
    "canCreateTool": true,
    "canCreateAgentUiTool": true,
    "canCreateSkill": true,
    "maigptCanCodeInterpreter": true,
    "maigptCanRag": true,
    "maigptCanDeepResearch": true,
    "maigptCanBrowserTool": true,
    "maigptAllLlms": true,
    "maigptAllTools": true,
    "maigptAllConnectors": true,
    "maigptAllSkills": true,
    "usageStatisticsScope": {},
    "allowedLlms": [
      "550e8400-e29b-41d4-a716-446655440000"
    ],
    "allowedTools": [
      "550e8400-e29b-41d4-a716-446655440000"
    ],
    "allowedConnectors": [
```

```
      "550e8400-e29b-41d4-a716-446655440000"
    ],
    "allowedSkills": [
      "550e8400-e29b-41d4-a716-446655440000"
    ]
  };

axios.put("https://api.maiagent.ai/api/v1/organizations/550e8400-
e29b-41d4-a716-446655440000/groups/550e8400-e29b-41d4-a716-
446655440000/", data, config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-
41d4-a716-446655440000/groups/550e8400-e29b-41d4-a716-446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# 請求內容 (payload)
data = {
    "name": "範例名稱",
    "organization": "550e8400-e29b-41d4-a716-446655440000",
    "permissions": [
        "550e8400-e29b-41d4-a716-446655440000"
    ],
    "canCreateChatbot": True,
    "canCreateKnowledgeBase": True,
    "canCreateInbox": True,
    "canCreateDatabase": True,
    "canCreateTool": True,
    "canCreateAgentUiTool": True,
    "canCreateSkill": True,
    "maigptCanCodeInterpreter": True,
    "maigptCanRag": True,
    "maigptCanDeepResearch": True,
    "maigptCanBrowserTool": True,
    "maigptAllLlms": True,
    "maigptAllTools": True,
    "maigptAllConnectors": True,
    "maigptAllSkills": True,
    "usageStatisticsScope": {},
    "allowedLlms": [
        "550e8400-e29b-41d4-a716-446655440000"
    ],
    "allowedTools": [
        "550e8400-e29b-41d4-a716-446655440000"
    ],
    "allowedConnectors": [
        "550e8400-e29b-41d4-a716-446655440000"
```

```
    ],
    "allowedSkills": [
        "550e8400-e29b-41d4-a716-446655440000"
    ]
}

response = requests.put(url, json=data, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>put("https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-
41d4-a716-446655440000/groups/550e8400-e29b-41d4-a716-
446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'name' => '範例名稱',
            'organization' => '550e8400-e29b-41d4-a716-
446655440000',
            'permissions' => [
                '550e8400-e29b-41d4-a716-446655440000'
            ],
            'canCreateChatbot' => true,
            'canCreateKnowledgeBase' => true,
            'canCreateInbox' => true,
            'canCreateDatabase' => true,
            'canCreateTool' => true,
            'canCreateAgentUiTool' => true,
            'canCreateSkill' => true,
            'maigptCanCodeInterpreter' => true,
            'maigptCanRag' => true,
            'maigptCanDeepResearch' => true,
            'maigptCanBrowserTool' => true,
            'maigptAllLlms' => true,
            'maigptAllTools' => true,
            'maigptAllConnectors' => true,
            'maigptAllSkills' => true,
            'usageStatisticsScope' => new \stdClass(),
            'allowedLlms' => [
                '550e8400-e29b-41d4-a716-446655440000'
            ],
```

```
                'allowedTools' => [
                    '550e8400-e29b-41d4-a716-446655440000'
                ],
                'allowedConnectors' => [
                    '550e8400-e29b-41d4-a716-446655440000'
                ],
                'allowedSkills' => [
                    '550e8400-e29b-41d4-a716-446655440000'
                ]
            ]
        ]);

        $data = json_decode($response->getBody(), true);
        echo "成功取得回應:\n";
        print_r($data);
    } catch (Exception $e) {
        echo '請求發生錯誤: ' . $e->getMessage();
    }
    ?>
```

回應內容

狀態碼: 200

回應結構範例

```
{
  "id": string (uuid)
  "name": string
  "type":
  {
  }
  "permissions": [
    object
  ]
  "membersPreview": [
    string
```

```
  ]
  "membersCount": integer // 返回剩餘成員數量（扣除列表顯示的 3 人後），用於前端 +N badge 顯示

與資源 count 不同：
<ul>
  <li>members_count: 返回 total - 3（用於 +N badge），None 表示總數 <= 3</li>
  <li>chatbots_count/knowledge_bases_count/inboxes_count: 返回總數量</li>
</ul>
  "chatbotsCount": integer
  "chatbotsPreview": [
    string
  ]
  "knowledgeBasesCount": integer
  "knowledgeBasesPreview": [
    string
  ]
  "inboxesCount": integer
  "inboxesPreview": [
    string
  ]
  "databasesCount": integer
  "databasesPreview": [
    string
  ]
  "canCreateChatbot"?: boolean // 非必填
  "canCreateKnowledgeBase"?: boolean // 非必填
  "canCreateInbox"?: boolean // 非必填
  "canCreateDatabase"?: boolean // 非必填
  "canCreateTool"?: boolean // 非必填
  "canCreateAgentUiTool"?: boolean // 非必填
  "canCreateSkill"?: boolean // 非必填
  "maigptCanCodeInterpreter"?: boolean // Whether members of this role may use the code interpreter built-in tool in MaiGPT. (非必填)
  "maigptCanRag"?: boolean // Whether members of this role may use the knowledge base RAG built-in tool in MaiGPT. (非必填)
  "maigptCanDeepResearch"?: boolean // Whether members of this role may use Deep Research in MaiGPT. Deep Research reaches the public internet through its own built-in search, so a role that revokes the official web-search tools needs this switch too. (非必填)
  "maigptCanBrowserTool"?: boolean // Whether members of this role may use the browser built-in tool in MaiGPT. (非必填)
  "maigptAllLlms"?: boolean // Whether members of this role may use every organization-available LLM in MaiGPT. Off = only the bound LLMs; an empty binding then means none. (非必填)
```

```
  "maigptAllTools"?: boolean // Whether members of this role may call
every official (global) tool in MaiGPT. Off = only the bound tools; an
empty binding then means none. (非必填)
  "maigptAllConnectors"?: boolean // Whether members of this role may
call every official (global) MCP connector in MaiGPT. Off = only the
bound connectors; an empty binding then means none. (非必填)
  "maigptAllSkills"?: boolean // Whether members of this role may use
every official (global) skill in MaiGPT. Off = only the bound skills; an
empty binding then means none. (非必填)
  "usageStatisticsScope"?:  // What this role's usage statistics
permission shows: the whole organization, or only the AI assistants
granted to the member's roles. A member with any organization-wide
granting role sees the whole organization.

* `organization` - Organization-wide
* `accessible_chatbots` - Authorized AI assistants only (非必填)
  {
  }
  "createdAt": string (timestamp)
}
```

回應範例值

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "name": "回應字串",
  "type": {},
  "permissions": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "回應範例名稱",
      "description": "回應範例描述"
    }
  ],
  "membersPreview": [
    "回應字串"
  ],
  "membersCount": 456,
  "chatbotsCount": 456,
  "chatbotsPreview": [
    "回應字串"
  ],
  "knowledgeBasesCount": 456,
  "knowledgeBasesPreview": [
```

```
    "回應字串"
  ],
  "inboxesCount": 456,
  "inboxesPreview": [
    "回應字串"
  ],
  "databasesCount": 456,
  "databasesPreview": [
    "回應字串"
  ],
  "canCreateChatbot": false,
  "canCreateKnowledgeBase": false,
  "canCreateInbox": false,
  "canCreateDatabase": false,
  "canCreateTool": false,
  "canCreateAgentUiTool": false,
  "canCreateSkill": false,
  "maigptCanCodeInterpreter": false,
  "maigptCanRag": false,
  "maigptCanDeepResearch": false,
  "maigptCanBrowserTool": false,
  "maigptAllLlms": false,
  "maigptAllTools": false,
  "maigptAllConnectors": false,
  "maigptAllSkills": false,
  "usageStatisticsScope": {},
  "createdAt": "回應字串"
}
```


部分更新角色權限

PATCH `/api/v1/organizations/{organizationPk}/groups/{id}`

參數

參數名稱	必填	類型	說明

`id`	V	string	A UUID string identifying this Group.
`organizationPk`	V	string	A UUID string identifying this 組織 ID

請求內容

請求參數

欄位	類型	必填	說明
name	string	否	
organization	string (uuid)	否	
permissions	array[string]	否	
canCreateChatbot	boolean	否	
canCreateKnowledgeBase	boolean	否	
canCreateInbox	boolean	否	
canCreateDatabase	boolean	否	
canCreateTool	boolean	否	
canCreateAgentUiTool	boolean	否	
canCreateSkill	boolean	否	
maigptCanCodeInterpreter	boolean	否	Whether members of this role may use the code interpreter built-in tool in MaiGPT.
maigptCanRag	boolean	否	Whether members of this role may use the knowledge base RAG built-in tool in MaiGPT.

欄位	類型	必填	說明
maigptCanDeepResearch	boolean	否	Whether members of this role may use Deep Research in MaiGPT. Deep Research reaches the public internet through its own built-in search, so a role that revokes the official web-search tools needs this...
maigptCanBrowserTool	boolean	否	Whether members of this role may use the browser built-in tool in MaiGPT.
maigptAllLlms	boolean	否	Whether members of this role may use every organization-available LLM in MaiGPT. Off = only the bound LLMs; an empty binding then means none.
maigptAllTools	boolean	否	Whether members of this role may call every official (global) tool in MaiGPT. Off = only the bound tools; an empty binding then means none.
maigptAllConnectors	boolean	否	Whether members of this role may call every official (global) MCP connector in MaiGPT. Off = only the bound connectors; an empty binding then means none.
maigptAllSkills	boolean	否	Whether members of this role may use every official (global) skill in MaiGPT. Off = only the bound skills; an empty binding then means none.
usageStatisticsScope	object	否	What this role's usage statistics permission shows: the whole organization, or only the AI assistants granted to the member's roles. A member with any organization-wide granting role sees the whole or...
allowedLlms	array[string]	否	
allowedTools	array[string]	否	
allowedConnectors	array[string]	否	

欄位	類型	必填	說明
allowedSkills	array[string]	否	

請求結構範例

```
{
  "name"?: string // 非必填
  "organization"?: string (uuid) // 非必填
  "permissions"?: [ // 非必填
    string (uuid)
  ]
  "canCreateChatbot"?: boolean // 非必填
  "canCreateKnowledgeBase"?: boolean // 非必填
  "canCreateInbox"?: boolean // 非必填
  "canCreateDatabase"?: boolean // 非必填
  "canCreateTool"?: boolean // 非必填
  "canCreateAgentUiTool"?: boolean // 非必填
  "canCreateSkill"?: boolean // 非必填
  "maigptCanCodeInterpreter"?: boolean // Whether members of this role may use the code interpreter built-in tool in MaiGPT. (非必填)
  "maigptCanRag"?: boolean // Whether members of this role may use the knowledge base RAG built-in tool in MaiGPT. (非必填)
  "maigptCanDeepResearch"?: boolean // Whether members of this role may use Deep Research in MaiGPT. Deep Research reaches the public internet through its own built-in search, so a role that revokes the official web-search tools needs this switch too. (非必填)
  "maigptCanBrowserTool"?: boolean // Whether members of this role may use the browser built-in tool in MaiGPT. (非必填)
  "maigptAllLlms"?: boolean // Whether members of this role may use every organization-available LLM in MaiGPT. Off = only the bound LLMs; an empty binding then means none. (非必填)
  "maigptAllTools"?: boolean // Whether members of this role may call every official (global) tool in MaiGPT. Off = only the bound tools; an empty binding then means none. (非必填)
  "maigptAllConnectors"?: boolean // Whether members of this role may call every official (global) MCP connector in MaiGPT. Off = only the bound connectors; an empty binding then means none. (非必填)
  "maigptAllSkills"?: boolean // Whether members of this role may use every official (global) skill in MaiGPT. Off = only the bound skills; an empty binding then means none. (非必填)
  "usageStatisticsScope"?:  // What this role's usage statistics permission shows: the whole organization, or only the AI assistants
```

```
granted to the member's roles. A member with any organization-wide
granting role sees the whole organization.

* `organization` - Organization-wide
* `accessible_chatbots` - Authorized AI assistants only (非必填)
  {
  }
  "allowedLlms"?: [ // 非必填
    string (uuid)
  ]
  "allowedTools"?: [ // 非必填
    string (uuid)
  ]
  "allowedConnectors"?: [ // 非必填
    string (uuid)
  ]
  "allowedSkills"?: [ // 非必填
    string (uuid)
  ]
}
```

請求範例值

```
{
  "name": "範例名稱",
  "organization": "550e8400-e29b-41d4-a716-446655440000",
  "permissions": [
    "550e8400-e29b-41d4-a716-446655440000"
  ],
  "canCreateChatbot": true,
  "canCreateKnowledgeBase": true,
  "canCreateInbox": true,
  "canCreateDatabase": true,
  "canCreateTool": true,
  "canCreateAgentUiTool": true,
  "canCreateSkill": true,
  "maigptCanCodeInterpreter": true,
  "maigptCanRag": true,
  "maigptCanDeepResearch": true,
  "maigptCanBrowserTool": true,
  "maigptAllLlms": true,
  "maigptAllTools": true,
  "maigptAllConnectors": true,
  "maigptAllSkills": true,
```

```
  "usageStatisticsScope": {},
  "allowedLlms": [
    "550e8400-e29b-41d4-a716-446655440000"
  ],
  "allowedTools": [
    "550e8400-e29b-41d4-a716-446655440000"
  ],
  "allowedConnectors": [
    "550e8400-e29b-41d4-a716-446655440000"
  ],
  "allowedSkills": [
    "550e8400-e29b-41d4-a716-446655440000"
  ]
}
```

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X PATCH
"https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-41d4-
a716-446655440000/groups/550e8400-e29b-41d4-a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "name": "範例名稱",
    "organization": "550e8400-e29b-41d4-a716-446655440000",
    "permissions": [
      "550e8400-e29b-41d4-a716-446655440000"
    ],
    "canCreateChatbot": true,
    "canCreateKnowledgeBase": true,
    "canCreateInbox": true,
    "canCreateDatabase": true,
    "canCreateTool": true,
    "canCreateAgentUiTool": true,
    "canCreateSkill": true,
    "maigptCanCodeInterpreter": true,
    "maigptCanRag": true,
    "maigptCanDeepResearch": true,
    "maigptCanBrowserTool": true,
    "maigptAllLlms": true,
    "maigptAllTools": true,
    "maigptAllConnectors": true,
    "maigptAllSkills": true,
    "usageStatisticsScope": {},
    "allowedLlms": [
      "550e8400-e29b-41d4-a716-446655440000"
    ],
    "allowedTools": [
      "550e8400-e29b-41d4-a716-446655440000"
    ],
    "allowedConnectors": [
      "550e8400-e29b-41d4-a716-446655440000"
    ],
```

```
    "allowedSkills": [
      "550e8400-e29b-41d4-a716-446655440000"
    ]
  }'

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// 請求內容 (payload)
const data = {
    "name": "範例名稱",
    "organization": "550e8400-e29b-41d4-a716-446655440000",
    "permissions": [
      "550e8400-e29b-41d4-a716-446655440000"
    ],
    "canCreateChatbot": true,
    "canCreateKnowledgeBase": true,
    "canCreateInbox": true,
    "canCreateDatabase": true,
    "canCreateTool": true,
    "canCreateAgentUiTool": true,
    "canCreateSkill": true,
    "maigptCanCodeInterpreter": true,
    "maigptCanRag": true,
    "maigptCanDeepResearch": true,
    "maigptCanBrowserTool": true,
    "maigptAllLlms": true,
    "maigptAllTools": true,
    "maigptAllConnectors": true,
    "maigptAllSkills": true,
    "usageStatisticsScope": {},
    "allowedLlms": [
      "550e8400-e29b-41d4-a716-446655440000"
    ],
    "allowedTools": [
      "550e8400-e29b-41d4-a716-446655440000"
    ],
    "allowedConnectors": [
```

```
      "550e8400-e29b-41d4-a716-446655440000"
    ],
    "allowedSkills": [
      "550e8400-e29b-41d4-a716-446655440000"
    ]
  };

axios.patch("https://api.maiagent.ai/api/v1/organizations/550e8400-
e29b-41d4-a716-446655440000/groups/550e8400-e29b-41d4-a716-
446655440000/", data, config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-
41d4-a716-446655440000/groups/550e8400-e29b-41d4-a716-446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# 請求內容 (payload)
data = {
    "name": "範例名稱",
    "organization": "550e8400-e29b-41d4-a716-446655440000",
    "permissions": [
        "550e8400-e29b-41d4-a716-446655440000"
    ],
    "canCreateChatbot": True,
    "canCreateKnowledgeBase": True,
    "canCreateInbox": True,
    "canCreateDatabase": True,
    "canCreateTool": True,
    "canCreateAgentUiTool": True,
    "canCreateSkill": True,
    "maigptCanCodeInterpreter": True,
    "maigptCanRag": True,
    "maigptCanDeepResearch": True,
    "maigptCanBrowserTool": True,
    "maigptAllLlms": True,
    "maigptAllTools": True,
    "maigptAllConnectors": True,
    "maigptAllSkills": True,
    "usageStatisticsScope": {},
    "allowedLlms": [
        "550e8400-e29b-41d4-a716-446655440000"
    ],
    "allowedTools": [
        "550e8400-e29b-41d4-a716-446655440000"
    ],
    "allowedConnectors": [
        "550e8400-e29b-41d4-a716-446655440000"
```

```
    ],
    "allowedSkills": [
        "550e8400-e29b-41d4-a716-446655440000"
    ]
}

response = requests.patch(url, json=data, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>patch("https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-
41d4-a716-446655440000/groups/550e8400-e29b-41d4-a716-
446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'name' => '範例名稱',
            'organization' => '550e8400-e29b-41d4-a716-
446655440000',
            'permissions' => [
                '550e8400-e29b-41d4-a716-446655440000'
            ],
            'canCreateChatbot' => true,
            'canCreateKnowledgeBase' => true,
            'canCreateInbox' => true,
            'canCreateDatabase' => true,
            'canCreateTool' => true,
            'canCreateAgentUiTool' => true,
            'canCreateSkill' => true,
            'maigptCanCodeInterpreter' => true,
            'maigptCanRag' => true,
            'maigptCanDeepResearch' => true,
            'maigptCanBrowserTool' => true,
            'maigptAllLlms' => true,
            'maigptAllTools' => true,
            'maigptAllConnectors' => true,
            'maigptAllSkills' => true,
            'usageStatisticsScope' => new \stdClass(),
            'allowedLlms' => [
                '550e8400-e29b-41d4-a716-446655440000'
            ],
```

```
                'allowedTools' => [
                    '550e8400-e29b-41d4-a716-446655440000'
                ],
                'allowedConnectors' => [
                    '550e8400-e29b-41d4-a716-446655440000'
                ],
                'allowedSkills' => [
                    '550e8400-e29b-41d4-a716-446655440000'
                ]
            ]
        ]);

        $data = json_decode($response->getBody(), true);
        echo "成功取得回應:\n";
        print_r($data);
    } catch (Exception $e) {
        echo '請求發生錯誤: ' . $e->getMessage();
    }
    ?>
```

回應內容

狀態碼: 200

回應結構範例

```
{
  "id": string (uuid)
  "name": string
  "type":
  {
  }
  "permissions": [
    object
  ]
  "membersPreview": [
    string
```

```
  ]
  "membersCount": integer // 返回剩餘成員數量（扣除列表顯示的 3 人後），用於前端 +N badge 顯示

與資源 count 不同：
<ul>
  <li>members_count: 返回 total - 3（用於 +N badge），None 表示總數 <= 3</li>
  <li>chatbots_count/knowledge_bases_count/inboxes_count: 返回總數量</li>
</ul>
  "chatbotsCount": integer
  "chatbotsPreview": [
    string
  ]
  "knowledgeBasesCount": integer
  "knowledgeBasesPreview": [
    string
  ]
  "inboxesCount": integer
  "inboxesPreview": [
    string
  ]
  "databasesCount": integer
  "databasesPreview": [
    string
  ]
  "canCreateChatbot"?: boolean // 非必填
  "canCreateKnowledgeBase"?: boolean // 非必填
  "canCreateInbox"?: boolean // 非必填
  "canCreateDatabase"?: boolean // 非必填
  "canCreateTool"?: boolean // 非必填
  "canCreateAgentUiTool"?: boolean // 非必填
  "canCreateSkill"?: boolean // 非必填
  "maigptCanCodeInterpreter"?: boolean // Whether members of this role may use the code interpreter built-in tool in MaiGPT. (非必填)
  "maigptCanRag"?: boolean // Whether members of this role may use the knowledge base RAG built-in tool in MaiGPT. (非必填)
  "maigptCanDeepResearch"?: boolean // Whether members of this role may use Deep Research in MaiGPT. Deep Research reaches the public internet through its own built-in search, so a role that revokes the official web-search tools needs this switch too. (非必填)
  "maigptCanBrowserTool"?: boolean // Whether members of this role may use the browser built-in tool in MaiGPT. (非必填)
  "maigptAllLlms"?: boolean // Whether members of this role may use every organization-available LLM in MaiGPT. Off = only the bound LLMs; an empty binding then means none. (非必填)
```

```
  "maigptAllTools"?: boolean // Whether members of this role may call
every official (global) tool in MaiGPT. Off = only the bound tools; an
empty binding then means none. (非必填)
  "maigptAllConnectors"?: boolean // Whether members of this role may
call every official (global) MCP connector in MaiGPT. Off = only the
bound connectors; an empty binding then means none. (非必填)
  "maigptAllSkills"?: boolean // Whether members of this role may use
every official (global) skill in MaiGPT. Off = only the bound skills; an
empty binding then means none. (非必填)
  "usageStatisticsScope"?:  // What this role's usage statistics
permission shows: the whole organization, or only the AI assistants
granted to the member's roles. A member with any organization-wide
granting role sees the whole organization.

* `organization` - Organization-wide
* `accessible_chatbots` - Authorized AI assistants only (非必填)
  {
  }
  "createdAt": string (timestamp)
}
```

回應範例值

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "name": "回應字串",
  "type": {},
  "permissions": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "回應範例名稱",
      "description": "回應範例描述"
    }
  ],
  "membersPreview": [
    "回應字串"
  ],
  "membersCount": 456,
  "chatbotsCount": 456,
  "chatbotsPreview": [
    "回應字串"
  ],
  "knowledgeBasesCount": 456,
  "knowledgeBasesPreview": [
```

```
      "回應字串"
    ],
    "inboxesCount": 456,
    "inboxesPreview": [
      "回應字串"
    ],
    "databasesCount": 456,
    "databasesPreview": [
      "回應字串"
    ],
    "canCreateChatbot": false,
    "canCreateKnowledgeBase": false,
    "canCreateInbox": false,
    "canCreateDatabase": false,
    "canCreateTool": false,
    "canCreateAgentUiTool": false,
    "canCreateSkill": false,
    "maigptCanCodeInterpreter": false,
    "maigptCanRag": false,
    "maigptCanDeepResearch": false,
    "maigptCanBrowserTool": false,
    "maigptAllLlms": false,
    "maigptAllTools": false,
    "maigptAllConnectors": false,
    "maigptAllSkills": false,
    "usageStatisticsScope": {},
    "createdAt": "回應字串"
  }
```


刪除角色

DELETE `/api/v1/organizations/{organizationPk}/groups/{id}`

參數

參數名稱	必填	類型	說明

`id`	V	string	A UUID string identifying this Group.
`organizationPk`	V	string	A UUID string identifying this 組織 ID

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X DELETE
"https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-41d4-
a716-446655440000/groups/550e8400-e29b-41d4-a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

// 請求內容 (payload)
const data = null;

axios.delete("https://api.maiagent.ai/api/v1/organizations/550e8400-
e29b-41d4-a716-446655440000/groups/550e8400-e29b-41d4-a716-
446655440000/", data, config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-
41d4-a716-446655440000/groups/550e8400-e29b-41d4-a716-446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.delete(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>delete("https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-
41d4-a716-446655440000/groups/550e8400-e29b-41d4-a716-
446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼	說明
204	No response body

移除角色成員

DELETE `/api/v1/organizations/{organizationPk}/groups/{groupPk}/group-members/{id}`

參數

參數名稱	必填	類型	說明
`groupPk`	V	string	
`id`	V	string	A UUID string identifying this Group Member.
`organizationPk`	V	string	A UUID string identifying this 組織 ID

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X DELETE
"https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-41d4-
a716-446655440000/groups/550e8400-e29b-41d4-a716-446655440000/group-
members/550e8400-e29b-41d4-a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

// 請求內容 (payload)
const data = null;

axios.delete("https://api.maiagent.ai/api/v1/organizations/550e8400-
e29b-41d4-a716-446655440000/groups/550e8400-e29b-41d4-a716-
446655440000/group-members/550e8400-e29b-41d4-a716-446655440000/",
data, config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-41d4-a716-446655440000/groups/550e8400-e29b-41d4-a716-446655440000/group-members/550e8400-e29b-41d4-a716-446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.delete(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>delete("https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-
41d4-a716-446655440000/groups/550e8400-e29b-41d4-a716-
446655440000/group-members/550e8400-e29b-41d4-a716-446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼	說明
204	No response body

移除角色裡的 AI 助理

DELETE `/api/v1/organizations/{organizationPk}/groups/{groupPk}/group-chatbots/{id}`

參數

參數名稱	必填	類型	說明
`groupPk`	V	string	
`id`	V	string	A UUID string identifying this Group Chatbot.
`organizationPk`	V	string	A UUID string identifying this 組織 ID

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X DELETE
"https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-41d4-
a716-446655440000/groups/550e8400-e29b-41d4-a716-446655440000/group-
chatbots/550e8400-e29b-41d4-a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

// 請求內容 (payload)
const data = null;

axios.delete("https://api.maiagent.ai/api/v1/organizations/550e8400-
e29b-41d4-a716-446655440000/groups/550e8400-e29b-41d4-a716-
446655440000/group-chatbots/550e8400-e29b-41d4-a716-446655440000/",
data, config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-
41d4-a716-446655440000/groups/550e8400-e29b-41d4-a716-
446655440000/group-chatbots/550e8400-e29b-41d4-a716-446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.delete(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>delete("https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-
41d4-a716-446655440000/groups/550e8400-e29b-41d4-a716-
446655440000/group-chatbots/550e8400-e29b-41d4-a716-446655440000/",
[
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼	說明
204	No response body

移除角色裡的收件匣

DELETE `/api/v1/organizations/{organizationPk}/groups/{groupPk}/group-inboxes/{id}`

參數

參數名稱	必填	類型	說明
`groupPk`	V	string	
`id`	V	string	A UUID string identifying this Group Inbox.
`organizationPk`	V	string	A UUID string identifying this 組織 ID

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X DELETE
"https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-41d4-
a716-446655440000/groups/550e8400-e29b-41d4-a716-446655440000/group-
inboxes/550e8400-e29b-41d4-a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

// 請求內容 (payload)
const data = null;

axios.delete("https://api.maiagent.ai/api/v1/organizations/550e8400-
e29b-41d4-a716-446655440000/groups/550e8400-e29b-41d4-a716-
446655440000/group-inboxes/550e8400-e29b-41d4-a716-446655440000/",
data, config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-41d4-a716-446655440000/groups/550e8400-e29b-41d4-a716-446655440000/group-inboxes/550e8400-e29b-41d4-a716-446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.delete(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>delete("https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-
41d4-a716-446655440000/groups/550e8400-e29b-41d4-a716-
446655440000/group-inboxes/550e8400-e29b-41d4-a716-446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼	說明
204	No response body

移除角色裡的知識庫

`DELETE` `/api/v1/organizations/{organizationPk}/groups/{groupPk}/group-knowledge-bases/{id}`

參數

參數名稱	必填	類型	說明
`groupPk`	V	string	
`id`	V	string	A UUID string identifying this Group KnowledgeBase.
`organizationPk`	V	string	A UUID string identifying this 組織 ID

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X DELETE
"https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-41d4-
a716-446655440000/groups/550e8400-e29b-41d4-a716-446655440000/group-
knowledge-bases/550e8400-e29b-41d4-a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

// 請求內容 (payload)
const data = null;

axios.delete("https://api.maiagent.ai/api/v1/organizations/550e8400-
e29b-41d4-a716-446655440000/groups/550e8400-e29b-41d4-a716-
446655440000/group-knowledge-bases/550e8400-e29b-41d4-a716-
446655440000/", data, config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-
41d4-a716-446655440000/groups/550e8400-e29b-41d4-a716-
446655440000/group-knowledge-bases/550e8400-e29b-41d4-a716-
446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.delete(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>delete("https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-
41d4-a716-446655440000/groups/550e8400-e29b-41d4-a716-
446655440000/group-knowledge-bases/550e8400-e29b-41d4-a716-
446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼	說明
204	No response body

移除角色裡的資料庫

DELETE `/api/v1/organizations/{organizationPk}/groups/{groupPk}/group-databases/{id}`

參數

參數名稱	必填	類型	說明
`groupPk`	V	string	
`id`	V	string	A UUID string identifying this Group Database.
`organizationPk`	V	string	A UUID string identifying this 組織 ID

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X DELETE
"https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-41d4-
a716-446655440000/groups/550e8400-e29b-41d4-a716-446655440000/group-
databases/550e8400-e29b-41d4-a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

// 請求內容 (payload)
const data = null;

axios.delete("https://api.maiagent.ai/api/v1/organizations/550e8400-
e29b-41d4-a716-446655440000/groups/550e8400-e29b-41d4-a716-
446655440000/group-databases/550e8400-e29b-41d4-a716-446655440000/",
data, config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-
41d4-a716-446655440000/groups/550e8400-e29b-41d4-a716-
446655440000/group-databases/550e8400-e29b-41d4-a716-446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.delete(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>delete("https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-
41d4-a716-446655440000/groups/550e8400-e29b-41d4-a716-
446655440000/group-databases/550e8400-e29b-41d4-a716-446655440000/",
[
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼	說明
204	No response body

呼叫 API 示例 (Shell)

目錄

1. 列出測試集
2. 建立空白測試集
3. 上傳 CSV 或 Excel 建立測試集
4. 從知識庫檔案生成測試集
5. 列出可生成測試案例的知識庫檔案
6. 取得特定測試集
7. 取得測試集與單輪測試案例
8. 更新測試集
9. 部分更新測試集
10. 刪除測試集
11. 列出單輪測試案例
12. 建立單輪測試案例
13. 上傳 CSV 或 Excel 加入測試案例
14. 從知識庫檔案生成單輪測試案例
15. 列出測試案例生成任務
16. 查詢測試案例生成任務進度
17. 更新單輪測試案例
18. 部分更新單輪測試案例
19. 刪除單輪測試案例
20. 批次刪除單輪測試案例
21. 列出多輪測試案例
22. 建立多輪測試案例
23. 從知識庫檔案生成多輪測試案例
24. 取得特定多輪測試案例
25. 更新多輪測試案例
26. 部分更新多輪測試案例
27. 刪除多輪測試案例
28. 列出可用的評估模型
29. 執行單輪評估
30. 執行多輪評估
31. 列出評估
32. 取得評估結果
33. 取得單輪評估的逐題結果
34. 取得多輪評估的逐對話結果
35. 取消執行中的評估

36. 繼續未完成的評估
37. 匯出評估報表
38. 查詢最新匯出狀態
39. 列出匯出紀錄
40. 編輯評估名稱與描述
41. 刪除評估

呼叫 API 示例 (Shell)

評估與測試集端點對應後台 AgentOps 的「測試集」與「自動化測試」，讓您從自己的系統批次測試 Agent。完整流程是：

1. **建立測試集**：用 `POST /api/v1/dataset/` 建立空白測試集，或用 `POST /api/v1/dataset/upload/` 上傳 CSV／Excel 一次建好。
2. **加入測試案例**：單輪問答用 `/api/v1/test-case/`（逐筆建立、上傳檔案或從知識庫檔案生成），多輪對話情境用 `/api/v1/multi-turn-test-case/`。從知識庫檔案生成在背景執行，回應 `202` 與 `jobId`，再用 查詢測試案例生成任務進度 追蹤。
3. **執行評估**：用 `POST /api/v1/evaluations/evaluate/`（單輪）或 `POST /api/v1/evaluations/multi-turn-evaluate/`（多輪）指定測試集與 Agent，回應 `202` 與 `evaluationId`。
4. **讀取結果與匯出**：輪詢 `GET /api/v1/evaluations/{id}/`，`status` 變成 `completed`、`partial_completed` 或 `failed` 即結束；單輪的逐題結果在 `details`，多輪的逐對話結果在 `multi-turn-results`。已完成的單輪評估可以用 `export` 匯出 Excel 報表，再從 `export-status` 取得下載網址。

所需權限：API Key 以建立它的成員身分呼叫。`/dataset/`、`/test-case/`、`/multi-turn-test-case/` 的列表與所有寫入操作需要角色具備「測試集權限」，`/evaluations/` 的列表與所有寫入操作需要「自動化測試權限」（角色權限中的 AgentOps 權限；擁有者一律具備），權限不足回 `403`。擁有者以外的成員只看得到、也只能評估自己角色可使用的 Agent。

Credit：從知識庫檔案生成測試案例，依實際生成的題數扣計價項目 `agentops_test_gen`；執行評估在結束時依完成的測試案例數扣 `agentops_test_run` 與 `agentops_deepeval`，評分用的評估模型呼叫另依該模型的用量計費。送出生成或評估前，系統會先檢查組織 Credit 與額度，不足回 `402`。手動建立、上傳檔案與讀取結果不扣 Credit；各項單價見 列出計價項目。

功能與後台操作見使用者手冊測試集管理與自動評估與 Agent 監控。

列出測試集

`GET` `/api/v1/dataset/`

參數

參數名稱	必填	類型	說明
`isActive`	X	boolean	只列出啟用（true）或停用（false）的資料集
`ordering`	X	string	排序欄位：created_at 或 updated_at，前面加 - 為由新到舊（例：-updated_at）；未指定時依建立時間由新到舊
`page`	X	integer	頁碼，從 1 開始；超過最後一頁回 404
`pageSize`	X	integer	每頁筆數，預設 20、上限 100（超過以 100 計）
`query`	X	string	關鍵字，比對資料集名稱、描述或 ID（部分符合）
`search`	X	string	關鍵字，比對資料集名稱或描述（部分符合、不分大小寫；以空白分隔多個關鍵字時須全部符合）

程式碼範例

Shell/Bash

```
# 呼叫 API 示例（Shell）
curl -X GET "https://api.maiagent.ai/api/v1/dataset/?
isActive=true&ordering=example&page=1&pageSize=1&query=example&searc
h=example"

  -H "Authorization: Api-Key YOUR_API_KEY"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/dataset/?
isActive=true&ordering=example&page=1&pageSize=1&query=example&searc
h=example", config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/dataset/?
isActive=true&ordering=example&page=1&pageSize=1&query=example&searc
h=example"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/dataset/?
isActive=true&ordering=example&page=1&pageSize=1&query=example&searc
h=example", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
{
  "count": integer
```

```
  "next"?: string (uri) // 非必填
  "previous"?: string (uri) // 非必填
  "results": [
    {
      "id": string (uuid)
      "name": string
      "description"?: string // 非必填
      "organization":
      {
        "id": string (uuid)
        "name": string
      }
      "createdBy":
      {
        "id": string (uuid)
        "name": string
      }
      "isActive"?: boolean // 非必填
      "singleTurnTestCaseCount": integer
      "multiTurnTestCaseCount": integer
      "createdAt": string (timestamp)
      "updatedAt": string (timestamp)
    }
  ]
}
```

回應範例值

```
{
  "count": 123,
  "next": "http://api.example.org/accounts/?page=4",
  "previous": "http://api.example.org/accounts/?page=2",
  "results": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "回應字串",
      "description": "回應字串",
      "organization": {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "name": "回應字串"
      },
      "createdBy": {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "name": "回應字串"
```

```
      },
      "isActive": false,
      "singleTurnTestCaseCount": 456,
      "multiTurnTestCaseCount": 456,
      "createdAt": "回應字串",
      "updatedAt": "回應字串"
    }
  ]
}
```

建立空白測試集

POST `/api/v1/dataset/`

測試集名稱在組織內不可重複，重複時回 400。

請求內容

請求參數

欄位	類型	必填	說明
name	string	是	
description	string	否	

請求結構範例

```
{
  "name": string
  "description"?: string // 非必填
}
```

請求範例值

```
{
  "name": "範例名稱",
  "description": "範例字串"
}
```

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X POST "https://api.maiagent.ai/api/v1/dataset/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "name": "範例名稱",
    "description": "範例字串"
  }'

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// 請求內容 (payload)
const data = {
    "name": "範例名稱",
    "description": "範例字串"
  };

axios.post("https://api.maiagent.ai/api/v1/dataset/", data, config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/dataset/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# 請求內容 (payload)
data = {
    "name": "範例名稱",
    "description": "範例字串"
}

response = requests.post(url, json=data, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>post("https://api.maiagent.ai/api/v1/dataset/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'name' => '範例名稱',
            'description' => '範例字串'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 201

回應結構範例

```
{
  "id": string (uuid)
  "name": string
  "description"?: string // 非必填
  "organization":
  {
    "id": string (uuid)
    "name": string
  }
  "createdBy":
  {
    "id": string (uuid)
    "name": string
  }
  "isActive"?: boolean // 非必填
  "singleTurnTestCaseCount": integer
  "multiTurnTestCaseCount": integer
  "createdAt": string (timestamp)
  "updatedAt": string (timestamp)
}
```

回應範例值

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "name": "回應字串",
  "description": "回應字串",
  "organization": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應字串"
  },
  "createdBy": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應字串"
  },
  "isActive": false,
  "singleTurnTestCaseCount": 456,
  "multiTurnTestCaseCount": 456,
  "createdAt": "回應字串",
```

```
  "updatedAt": "回應字串"
}
```

上傳 CSV 或 Excel 建立測試集

POST `/api/v1/dataset/upload/`

以 multipart/form-data 上傳：file 與 name 必填，description 選填。檔案格式同 上傳 CSV 或 Excel 加入測試案例；測試集名稱在組織內不可重複。

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X POST "https://api.maiagent.ai/api/v1/dataset/upload/"
  -H "Authorization: Api-Key YOUR_API_KEY"
  -F "file=@example_file.csv"
  -F "name=範例字串"
  -F "description=範例字串"
# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');
const FormData = require('form-data');

// 建立FormData對象
const formData = new FormData();
// 請用實際檔案替換
formData.append('file',
* 實際檔案物件 *
, 'example_file.csv');
formData.append('name', '範例字串');
formData.append('description', '範例字串');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    ...formData.getHeaders()
  }
};

axios.post("https://api.maiagent.ai/api/v1/dataset/upload/",
formData, config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/dataset/upload/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}

# 建立檔案和表單資料
files = {
    'file': ('example_file.csv', open('example_file.csv', 'rb'),
'text/csv'),
    'name': (None, '範例字串'),
    'description': (None, '範例字串')
}

response = requests.post(url, files=files, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>post("https://api.maiagent.ai/api/v1/dataset/upload/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ],
        'multipart' => [
            [
                'name' => 'file',
                'contents' => fopen('example_file.csv', 'r'),
                'filename' => 'example_file.csv'
            ],
            [
                'name' => 'name',
                'contents' => '範例字串'
            ],
            [
                'name' => 'description',
                'contents' => '範例字串'
            ]
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 201

回應結構範例

```
{
  "id": string (uuid)
  "name": string
  "description"?: string // 非必填
  "organization":
  {
    "id": string (uuid)
    "name": string
  }
  "createdBy":
  {
    "id": string (uuid)
    "name": string
  }
  "isActive"?: boolean // 非必填
  "singleTurnTestCaseCount": integer
  "multiTurnTestCaseCount": integer
  "createdAt": string (timestamp)
  "updatedAt": string (timestamp)
}
```

回應範例值

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "name": "回應字串",
  "description": "回應字串",
  "organization": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應字串"
  },
  "createdBy": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
```

```
    "name": "回應字串"
  },
  "isActive": false,
  "singleTurnTestCaseCount": 456,
  "multiTurnTestCaseCount": 456,
  "createdAt": "回應字串",
  "updatedAt": "回應字串"
}
```


從知識庫檔案生成測試集

POST `/api/v1/dataset/generate-from-file/`

以單一知識庫檔案（knowledgeBaseFileId）建立新測試集並生成單輪測試案例，numTestCases 為 1～50（預設 10）。生成在背景執行，實際回應是 202 與 taskId，不含測試集 ID，也沒有進度可查；完成後新測試集會出現在列表中。需要追蹤進度時，請先建立空白測試集，再用 從知識庫檔案生成單輪測試案例。Credit：送出前檢查組織 Credit，不足回 402；依實際生成的題數扣 agentops_test_gen。

請求內容

請求參數

欄位	類型	必填	說明
name	string	是	
description	string	否	
chatbotFileId	string (uuid)	否	
knowledgeBaseFileId	string (uuid)	否	
numTestCases	integer	否	

請求結構範例

```
{
  "name": string
  "description"?: string // 非必填
  "chatbotFileId"?: string (uuid) // 非必填
  "knowledgeBaseFileId"?: string (uuid) // 非必填
  "numTestCases"?: integer // 非必填
}
```

請求範例值

```
{
  "name": "範例名稱",
  "description": "範例字串",
  "chatbotFileId": "550e8400-e29b-41d4-a716-446655440000",
  "knowledgeBaseFileId": "550e8400-e29b-41d4-a716-446655440000",
  "numTestCases": 123
}
```

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X POST "https://api.maiagent.ai/api/v1/dataset/generate-from-
file/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "name": "範例名稱",
    "description": "範例字串",
    "chatbotFileId": "550e8400-e29b-41d4-a716-446655440000",
    "knowledgeBaseFileId": "550e8400-e29b-41d4-a716-446655440000",
    "numTestCases": 123
  }'

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// 請求內容 (payload)
const data = {
    "name": "範例名稱",
    "description": "範例字串",
    "chatbotFileId": "550e8400-e29b-41d4-a716-446655440000",
    "knowledgeBaseFileId": "550e8400-e29b-41d4-a716-446655440000",
    "numTestCases": 123
  };

axios.post("https://api.maiagent.ai/api/v1/dataset/generate-from-
file/", data, config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/dataset/generate-from-file/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# 請求內容 (payload)
data = {
    "name": "範例名稱",
    "description": "範例字串",
    "chatbotFileId": "550e8400-e29b-41d4-a716-446655440000",
    "knowledgeBaseFileId": "550e8400-e29b-41d4-a716-446655440000",
    "numTestCases": 123
}

response = requests.post(url, json=data, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>post("https://api.maiagent.ai/api/v1/dataset/generate-from-file/",
[
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'name' => '範例名稱',
            'description' => '範例字串',
            'chatbotFileId' => '550e8400-e29b-41d4-a716-
446655440000',
            'knowledgeBaseFileId' => '550e8400-e29b-41d4-a716-
446655440000',
            'numTestCases' => 123
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 202

回應結構範例

```
{
  "status": string (enum: accepted) // * `accepted` - 固定為 accepted，表示已受理並排入背景執行
  "message": string // 受理說明
  "taskId": string // 背景任務 ID
}
```

回應範例值

```
{
  "status": "accepted",
  "message": "回應字串",
  "taskId": "回應字串"
}
```

列出可生成測試案例的知識庫檔案

GET `/api/v1/dataset/knowledge-base-files/`

依知識庫分組，只列出處理完成、類型為 txt、docx、pdf、md、markdown、mdx 的檔案。pageSize 是每個知識庫最多回傳的檔案數（預設 5，上限 100），search 依檔名篩選。

參數

參數名稱	必填	類型	說明

`pageSize`	X	integer	每個知識庫最多回傳的檔案數（預設 5，上限 100）
`search`	X	string	依檔名篩選（部分符合，不分大小寫）

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/dataset/knowledge-base-files/?pageSize=1&search=example"

  -H "Authorization: Api-Key YOUR_API_KEY"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/dataset/knowledge-base-files/?pageSize=1&search=example", config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/dataset/knowledge-base-files/?
pageSize=1&search=example"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/dataset/knowledge-base-files/?
pageSize=1&search=example", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
{
  "knowledgeBases": [ // 有可用檔案的知識庫，依名稱排序；沒有可用檔案的知識庫不列出
    {
```

```
      "id": string (uuid)
      "name": string
      "files":
      {
        "count": integer // 此知識庫符合條件的檔案總數
        "results": [ // 最新的 page_size 個檔案
          {
            "id": string (uuid)
            "filename": string
            "fileType": string
            "size": integer
            "knowledgeBase":
            {
              "id": string (uuid)
              "name": string
            }
          }
        ]
      }
    }
  ]
}
```

回應範例值

```
{
  "knowledgeBases": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "回應字串",
      "files": {
        "count": 456,
        "results": [
          {
            "id": "550e8400-e29b-41d4-a716-446655440000",
            "filename": "回應字串",
            "fileType": "回應字串",
            "size": 456,
            "knowledgeBase": {
              "id": "550e8400-e29b-41d4-a716-446655440000",
              "name": "回應字串"
            }
          }
        ]
```

```
      }
    }
  ]
}
```

取得特定測試集

GET `/api/v1/dataset/{id}`

參數

參數名稱	必填	類型	說明
id	V	string	資料集 ID

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/dataset/550e8400-e29b-
41d4-a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/dataset/550e8400-e29b-
41d4-a716-446655440000/", config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/dataset/550e8400-e29b-41d4-
a716-446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/dataset/550e8400-e29b-41d4-
a716-446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
{
  "id": string (uuid)
  "name": string
```

```
  "description"?: string // 非必填
  "organization":
  {
    "id": string (uuid)
    "name": string
  }
  "createdBy":
  {
    "id": string (uuid)
    "name": string
  }
  "isActive"?: boolean // 非必填
  "singleTurnTestCaseCount": integer
  "multiTurnTestCaseCount": integer
  "createdAt": string (timestamp)
  "updatedAt": string (timestamp)
}
```

回應範例值

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "name": "回應字串",
  "description": "回應字串",
  "organization": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應字串"
  },
  "createdBy": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應字串"
  },
  "isActive": false,
  "singleTurnTestCaseCount": 456,
  "multiTurnTestCaseCount": 456,
  "createdAt": "回應字串",
  "updatedAt": "回應字串"
}
```

取得測試集與單輪測試案例

GET `/api/v1/dataset/{id}/details/`

回應在測試集欄位之外另含 testCases 陣列，只包含單輪測試案例；多輪測試案例請用 GET /api/v1/multi-turn-test-case/?datasetId={id}。

參數

參數名稱	必填	類型	說明
`id`	V	string	資料集 ID

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/dataset/550e8400-e29b-41d4-a716-446655440000/details/"
  -H "Authorization: Api-Key YOUR_API_KEY"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/dataset/550e8400-e29b-
41d4-a716-446655440000/details/", config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/dataset/550e8400-e29b-41d4-
a716-446655440000/details/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/dataset/550e8400-e29b-41d4-
a716-446655440000/details/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
{
  "id": string (uuid)
  "name": string
```

```
  "description"?: string // 非必填
  "organization":
  {
    "id": string (uuid)
    "name": string
  }
  "createdBy":
  {
    "id": string (uuid)
    "name": string
  }
  "isActive"?: boolean // 非必填
  "singleTurnTestCaseCount": integer
  "multiTurnTestCaseCount": integer
  "createdAt": string (timestamp)
  "updatedAt": string (timestamp)
  "testCases": [ // 此測試集的全部單輪測試案例，依建立時間由舊到新；沒有測試案例時為空陣列
    {
      "id": string (uuid)
      "dataset":
      {
        "id": string (uuid)
        "name": string
      }
      "question": string
      "groundTruth"?: string // 非必填
      "status"?: string (enum: active, inactive, pending) // * `active` - Active
* `inactive` - Inactive
* `pending` - Pending Review (非必填)
      "creationMethod"?: string (enum: manual, file, generate) // * `manual` - Manual
* `file` - File import
* `generate` - Generated (非必填)
      "sourceFile"?: string // Name of the CSV, Excel or knowledge base file this test case came from (非必填)
      "flaky"?: boolean // Flaky test cases still run and keep their results, but are excluded from the pass rate. (非必填)
      "createdAt": string (timestamp)
      "updatedAt": string (timestamp)
    }
  ]
}
```

回應範例值


```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "name": "回應字串",
  "description": "回應字串",
  "organization": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應字串"
  },
  "createdBy": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應字串"
  },
  "isActive": false,
  "singleTurnTestCaseCount": 456,
  "multiTurnTestCaseCount": 456,
  "createdAt": "回應字串",
  "updatedAt": "回應字串",
  "testCases": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "dataset": {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "name": "回應字串"
      },
      "question": "回應字串",
      "groundTruth": "回應字串",
      "status": "active",
      "creationMethod": "manual",
      "sourceFile": "回應字串",
      "flaky": false,
      "createdAt": "回應字串",
      "updatedAt": "回應字串"
    }
  ]
}
```


更新測試集

PUT `/api/v1/dataset/{id}`

參數

參數名稱	必填	類型	說明
id	V	string	資料集 ID

請求內容

請求參數

欄位	類型	必填	說明
name	string	是	
description	string	否	
isActive	boolean	否	

請求結構範例

```
{
  "name": string
  "description"?: string // 非必填
  "isActive"?: boolean // 非必填
}
```

請求範例值

```
{
  "name": "範例名稱",
  "description": "範例字串",
```

```
  "isActive": true
}
```

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X PUT "https://api.maiagent.ai/api/v1/dataset/550e8400-e29b-
41d4-a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "name": "範例名稱",
    "description": "範例字串",
    "isActive": true
  }'

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// 請求內容 (payload)
const data = {
    "name": "範例名稱",
    "description": "範例字串",
    "isActive": true
  };

axios.put("https://api.maiagent.ai/api/v1/dataset/550e8400-e29b-
41d4-a716-446655440000/", data, config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/dataset/550e8400-e29b-41d4-
a716-446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# 請求內容 (payload)
data = {
    "name": "範例名稱",
    "description": "範例字串",
    "isActive": True
}

response = requests.put(url, json=data, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>put("https://api.maiagent.ai/api/v1/dataset/550e8400-e29b-41d4-
a716-446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'name' => '範例名稱',
            'description' => '範例字串',
            'isActive' => true
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
{
  "id": string (uuid)
  "name": string
  "description"?: string // 非必填
  "organization":
  {
    "id": string (uuid)
    "name": string
  }
  "createdBy":
  {
    "id": string (uuid)
    "name": string
  }
  "isActive"?: boolean // 非必填
  "singleTurnTestCaseCount": integer
  "multiTurnTestCaseCount": integer
  "createdAt": string (timestamp)
  "updatedAt": string (timestamp)
}
```

回應範例值

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "name": "回應字串",
  "description": "回應字串",
  "organization": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應字串"
  },
  "createdBy": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應字串"
  },
  "isActive": false,
  "singleTurnTestCaseCount": 456,
  "multiTurnTestCaseCount": 456,
  "createdAt": "回應字串",
```

```
  "updatedAt": "回應字串"
}
```

部分更新測試集

PATCH `/api/v1/dataset/{id}`

參數

參數名稱	必填	類型	說明
id	V	string	資料集 ID

請求內容

請求參數

欄位	類型	必填	說明
name	string	否	
description	string	否	
isActive	boolean	否	

請求結構範例

```
{
  "name"?: string // 非必填
  "description"?: string // 非必填
  "isActive"?: boolean // 非必填
}
```

請求範例值

```
{
  "name": "範例名稱",
  "description": "範例字串",
  "isActive": true
}
```

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X PATCH "https://api.maiagent.ai/api/v1/dataset/550e8400-e29b-
41d4-a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "name": "範例名稱",
    "description": "範例字串",
    "isActive": true
  }'

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// 請求內容 (payload)
const data = {
    "name": "範例名稱",
    "description": "範例字串",
    "isActive": true
  };

axios.patch("https://api.maiagent.ai/api/v1/dataset/550e8400-e29b-
41d4-a716-446655440000/", data, config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/dataset/550e8400-e29b-41d4-
a716-446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# 請求內容 (payload)
data = {
    "name": "範例名稱",
    "description": "範例字串",
    "isActive": True
}

response = requests.patch(url, json=data, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->patch("https://api.maiagent.ai/api/v1/dataset/550e8400-e29b-41d4-a716-446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'name' => '範例名稱',
            'description' => '範例字串',
            'isActive' => true
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
{
  "id": string (uuid)
  "name": string
  "description"?: string // 非必填
  "organization":
  {
    "id": string (uuid)
    "name": string
  }
  "createdBy":
  {
    "id": string (uuid)
    "name": string
  }
  "isActive"?: boolean // 非必填
  "singleTurnTestCaseCount": integer
  "multiTurnTestCaseCount": integer
  "createdAt": string (timestamp)
  "updatedAt": string (timestamp)
}
```

回應範例值

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "name": "回應字串",
  "description": "回應字串",
  "organization": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應字串"
  },
  "createdBy": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應字串"
  },
  "isActive": false,
  "singleTurnTestCaseCount": 456,
  "multiTurnTestCaseCount": 456,
  "createdAt": "回應字串",
```

```
  "updatedAt": "回應字串"
}
```

刪除測試集

DELETE `/api/v1/dataset/{id}`

刪除後無法復原，會一併刪除測試集內的所有測試案例，以及用這個測試集執行過的評估與結果。

參數

參數名稱	必填	類型	說明
id	V	string	資料集 ID

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X DELETE "https://api.maiagent.ai/api/v1/dataset/550e8400-
e29b-41d4-a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

// 請求內容 (payload)
const data = null;

axios.delete("https://api.maiagent.ai/api/v1/dataset/550e8400-e29b-
41d4-a716-446655440000/", data, config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/dataset/550e8400-e29b-41d4-
a716-446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.delete(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>delete("https://api.maiagent.ai/api/v1/dataset/550e8400-e29b-41d4-
a716-446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼	說明
204	No response body

列出單輪測試案例

`GET` `/api/v1/test-case/`

用 datasetId 篩選單一測試集，也可依 status、creationMethod（manual、file、generate）篩選。

參數

參數名稱	必填	類型	說明
`creationMethod`	X	string	只列出以此方式建立的測試案例。可用值：`manual`: Manual ; `file`: File import ; `generate`: Generated;
`datasetId`	X	string	只列出此資料集的測試案例
`ordering`	X	string	排序欄位：created_at 或 updated_at，前面加 - 為由新到舊（例：-updated_at）；未指定時依建立時間由新到舊
`page`	X	integer	頁碼，從 1 開始；超過最後一頁回 404
`pageSize`	X	integer	每頁筆數，預設 20、上限 100（超過以 100 計）
`query`	X	string	關鍵字，比對問題、標準答案或 ID（部分符合）
`search`	X	string	關鍵字，比對問題或標準答案（部分符合、不分大小寫；以空白分隔多個關鍵字時須全部符合）
`status`	X	string	只列出此狀態的測試案例。可用值：`active`: Active ; `inactive`: Inactive ; `pending`: Pending Review;

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/test-case/?
creationMethod=file&datasetId=550e8400-e29b-41d4-a716-
446655440000&ordering=example&page=1&pageSize=1&query=example&search
=example&status=active"

  -H "Authorization: Api-Key YOUR_API_KEY"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/test-case/?
creationMethod=file&datasetId=550e8400-e29b-41d4-a716-
446655440000&ordering=example&page=1&pageSize=1&query=example&search
=example&status=active", config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/test-case/?
creationMethod=file&datasetId=550e8400-e29b-41d4-a716-
446655440000&ordering=example&page=1&pageSize=1&query=example&search
=example&status=active"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->get("https://api.maiagent.ai/api/v1/test-case/?creationMethod=file&datasetId=550e8400-e29b-41d4-a716-446655440000&ordering=example&page=1&pageSize=1&query=example&search=example&status=active", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
{
  "count": integer
```

```
  "next"?: string (uri) // 非必填
  "previous"?: string (uri) // 非必填
  "results": [
    {
      "id": string (uuid)
      "dataset":
      {
        "id": string (uuid)
        "name": string
      }
      "question": string
      "groundTruth"?: string // 非必填
      "status"?: string (enum: active, inactive, pending) // * `active` -
Active
* `inactive` - Inactive
* `pending` - Pending Review (非必填)
      "creationMethod"?: string (enum: manual, file, generate) // *
`manual` - Manual
* `file` - File import
* `generate` - Generated (非必填)
      "sourceFile"?: string // Name of the CSV, Excel or knowledge base
file this test case came from (非必填)
      "flaky"?: boolean // Flaky test cases still run and keep their
results, but are excluded from the pass rate. (非必填)
      "createdAt": string (timestamp)
      "updatedAt": string (timestamp)
    }
  ]
}
```

回應範例值

```
{
  "count": 123,
  "next": "http://api.example.org/accounts/?page=4",
  "previous": "http://api.example.org/accounts/?page=2",
  "results": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "dataset": {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "name": "回應字串"
      },
      "question": "回應字串",
```

```
      "groundTruth": "回應字串",
      "status": "active",
      "creationMethod": "manual",
      "sourceFile": "回應字串",
      "flaky": false,
      "createdAt": "回應字串",
      "updatedAt": "回應字串"
    }
  ]
}
```

建立單輪測試案例

POST `/api/v1/test-case/`

datasetId、question、groundTruth 必填。status 預設 active；評估只會執行 active 的測試案例。

請求內容

請求參數

欄位	類型	必填	說明
datasetId	string (uuid)	是	
question	string	是	
groundTruth	string	是	
status	string	否	
flaky	boolean	否	

請求結構範例

```
{
  "datasetId": string (uuid)
```

```
  "question": string
  "groundTruth": string
  "status"?: string // 非必填
  "flaky"?: boolean // 非必填
}
```

請求範例值

```
{
  "datasetId": "550e8400-e29b-41d4-a716-446655440000",
  "question": "範例字串",
  "groundTruth": "範例字串",
  "status": "範例字串",
  "flaky": true
}
```

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X POST "https://api.maiagent.ai/api/v1/test-case/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "datasetId": "550e8400-e29b-41d4-a716-446655440000",
    "question": "範例字串",
    "groundTruth": "範例字串",
    "status": "範例字串",
    "flaky": true
  }'

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// 請求內容 (payload)
const data = {
    "datasetId": "550e8400-e29b-41d4-a716-446655440000",
    "question": "範例字串",
    "groundTruth": "範例字串",
    "status": "範例字串",
    "flaky": true
  };

axios.post("https://api.maiagent.ai/api/v1/test-case/", data,
config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/test-case/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# 請求內容 (payload)
data = {
    "datasetId": "550e8400-e29b-41d4-a716-446655440000",
    "question": "範例字串",
    "groundTruth": "範例字串",
    "status": "範例字串",
    "flaky": True
}

response = requests.post(url, json=data, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->post("https://api.maiagent.ai/api/v1/test-case/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'datasetId' => '550e8400-e29b-41d4-a716-446655440000',
            'question' => '範例字串',
            'groundTruth' => '範例字串',
            'status' => '範例字串',
            'flaky' => true
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 201

回應結構範例

```
{
  "id": string (uuid)
  "dataset":
  {
    "id": string (uuid)
    "name": string
  }
  "question": string
  "groundTruth"?: string // 非必填
  "status"?: string (enum: active, inactive, pending) // * `active` -
Active
* `inactive` - Inactive
* `pending` - Pending Review (非必填)
  "creationMethod"?: string (enum: manual, file, generate) // * `manual`
- Manual
* `file` - File import
* `generate` - Generated (非必填)
  "sourceFile"?: string // Name of the CSV, Excel or knowledge base file
this test case came from (非必填)
  "flaky"?: boolean // Flaky test cases still run and keep their results,
but are excluded from the pass rate. (非必填)
  "createdAt": string (timestamp)
  "updatedAt": string (timestamp)
}
```

回應範例值

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "dataset": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應字串"
  },
  "question": "回應字串",
  "groundTruth": "回應字串",
  "status": "active",
  "creationMethod": "manual",
  "sourceFile": "回應字串",
  "flaky": false,
  "createdAt": "回應字串",
```

```
  "updatedAt": "回應字串"
}
```

上傳 CSV 或 Excel 加入測試案例

POST `/api/v1/test-case/upload/`

以 multipart/form-data 上傳，file 與 dataset_id 都必填。檔案為 .csv、.xlsx 或 .xls，標題列須有 question 與 ground_truth 兩欄，每一列新增一筆單輪測試案例；CSV 請用 UTF-8 編碼。回應是新增測試案例的陣列。

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X POST "https://api.maiagent.ai/api/v1/test-case/upload/"
  -H "Authorization: Api-Key YOUR_API_KEY"
  -F "file=@example_file.csv"
  -F "dataset_id=550e8400-e29b-41d4-a716-446655440000"
# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');
const FormData = require('form-data');

// 建立FormData對象
const formData = new FormData();
// 請用實際檔案替換
formData.append('file',
* 實際檔案物件 *
, 'example_file.csv');
formData.append('dataset_id', '550e8400-e29b-41d4-a716-
446655440000');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    ...formData.getHeaders()
  }
};

axios.post("https://api.maiagent.ai/api/v1/test-case/upload/",
formData, config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/test-case/upload/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}

# 建立檔案和表單資料
files = {
    'file': ('example_file.csv', open('example_file.csv', 'rb'),
'text/csv'),
    'dataset_id': (None, '550e8400-e29b-41d4-a716-446655440000')
}

response = requests.post(url, files=files, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->post("https://api.maiagent.ai/api/v1/test-case/upload/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ],
        'multipart' => [
            [
                'name' => 'file',
                'contents' => fopen('example_file.csv', 'r'),
                'filename' => 'example_file.csv'
            ],
            [
                'name' => 'dataset_id',
                'contents' => '550e8400-e29b-41d4-a716-446655440000'
            ]
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 201

回應結構範例

```
[
  {
    "id": string (uuid)
    "dataset":
    {
      "id": string (uuid)
      "name": string
    }
    "question": string
    "groundTruth"?: string // 非必填
    "status"?: string (enum: active, inactive, pending) // * `active` -
Active
* `inactive` - Inactive
* `pending` - Pending Review (非必填)
    "creationMethod"?: string (enum: manual, file, generate) // *
`manual` - Manual
* `file` - File import
* `generate` - Generated (非必填)
    "sourceFile"?: string // Name of the CSV, Excel or knowledge base
file this test case came from (非必填)
    "flaky"?: boolean // Flaky test cases still run and keep their
results, but are excluded from the pass rate. (非必填)
    "createdAt": string (timestamp)
    "updatedAt": string (timestamp)
  }
]
```

回應範例值

```
[
  {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "dataset": {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "回應字串"
```

```
    },
    "question": "回應字串",
    "groundTruth": "回應字串",
    "status": "active",
    "creationMethod": "manual",
    "sourceFile": "回應字串",
    "flaky": false,
    "createdAt": "回應字串",
    "updatedAt": "回應字串"
  }
]
```

從知識庫檔案生成單輪測試案例

POST `/api/v1/test-case/generate-from-file/`

用 knowledgeBaseIds（展開為知識庫內處理完成、類型支援的所有檔案）或 knowledgeBaseFileIds 指定來源，兩者可合用；支援 txt、docx、pdf、md、markdown、mdx。numTestCases 是這次要生成的總題數（預設 10），檔案數或題數超過平台上限時回 400，訊息會寫出上限。生成在背景執行，回應 202 與 jobId；同一個測試集已有生成任務在進行時，回傳該任務的 jobId，不會重複建立。Credit：送出前檢查組織 Credit，不足回 402；依實際生成的題數扣 agentops_test_gen。

請求內容

請求參數

欄位	類型	必填	說明
chatbotFileIds	array[string]	否	List of KnowledgeBaseFile IDs to generate test cases from (deprecated)
knowledgeBaseFileIds	array[string]	否	List of KnowledgeBaseFile IDs to generate test cases from
knowledgeBaseIds	array[string]	否	List of KnowledgeBase IDs to generate test cases from all their files

欄位	類型	必填	說明
datasetId	string (uuid)	是	
numTestCases	integer	否	

請求結構範例

```
{
  "chatbotFileIds"?: [ // List of KnowledgeBaseFile IDs to generate test cases from (deprecated) (非必填)
    string (uuid)
  ]
  "knowledgeBaseFileIds"?: [ // List of KnowledgeBaseFile IDs to generate test cases from (非必填)
    string (uuid)
  ]
  "knowledgeBaseIds"?: [ // List of KnowledgeBase IDs to generate test cases from all their files (非必填)
    string (uuid)
  ]
  "datasetId": string (uuid)
  "numTestCases"?: integer // 非必填
}
```

請求範例值

```
{
  "chatbotFileIds": [
    "550e8400-e29b-41d4-a716-446655440000"
  ],
  "knowledgeBaseFileIds": [
    "550e8400-e29b-41d4-a716-446655440000"
  ],
  "knowledgeBaseIds": [
    "550e8400-e29b-41d4-a716-446655440000"
  ],
  "datasetId": "550e8400-e29b-41d4-a716-446655440000",
```

```
  "numTestCases": 123
}
```

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X POST "https://api.maiagent.ai/api/v1/test-case/generate-
from-file/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "chatbotFileIds": [
      "550e8400-e29b-41d4-a716-446655440000"
    ],
    "knowledgeBaseFileIds": [
      "550e8400-e29b-41d4-a716-446655440000"
    ],
    "knowledgeBaseIds": [
      "550e8400-e29b-41d4-a716-446655440000"
    ],
    "datasetId": "550e8400-e29b-41d4-a716-446655440000",
    "numTestCases": 123
  }'

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// 請求內容 (payload)
const data = {
    "chatbotFileIds": [
      "550e8400-e29b-41d4-a716-446655440000"
    ],
    "knowledgeBaseFileIds": [
      "550e8400-e29b-41d4-a716-446655440000"
    ],
    "knowledgeBaseIds": [
      "550e8400-e29b-41d4-a716-446655440000"
    ],
    "datasetId": "550e8400-e29b-41d4-a716-446655440000",
    "numTestCases": 123
  };

axios.post("https://api.maiagent.ai/api/v1/test-case/generate-from-
file/", data, config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/test-case/generate-from-file/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# 請求內容 (payload)
data = {
    "chatbotFileIds": [
        "550e8400-e29b-41d4-a716-446655440000"
    ],
    "knowledgeBaseFileIds": [
        "550e8400-e29b-41d4-a716-446655440000"
    ],
    "knowledgeBaseIds": [
        "550e8400-e29b-41d4-a716-446655440000"
    ],
    "datasetId": "550e8400-e29b-41d4-a716-446655440000",
    "numTestCases": 123
}

response = requests.post(url, json=data, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->post("https://api.maiagent.ai/api/v1/test-case/generate-from-file/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'chatbotFileIds' => [
                '550e8400-e29b-41d4-a716-446655440000'
            ],
            'knowledgeBaseFileIds' => [
                '550e8400-e29b-41d4-a716-446655440000'
            ],
            'knowledgeBaseIds' => [
                '550e8400-e29b-41d4-a716-446655440000'
            ],
            'datasetId' => '550e8400-e29b-41d4-a716-446655440000',
            'numTestCases' => 123
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 202

回應結構範例

```
{
  "status": string (enum: accepted) // * `accepted` - 固定為 accepted，表示已受理並排入背景執行
  "message": string // 受理說明
  "jobId": string (uuid) // 生成任務 ID，可用 GET /api/v1/test-case/generation-jobs/{jobId}/ 查詢進度；同一測試集已有進行中的生成任務時，回傳的是該任務
  "taskId": string // 背景任務 ID
}
```

回應範例值

```
{
  "status": "accepted",
  "message": "回應字串",
  "jobId": "550e8400-e29b-41d4-a716-446655440000",
  "taskId": "回應字串"
}
```

列出測試案例生成任務

GET `/api/v1/test-case/generation-jobs/`

列出組織的單輪與多輪生成任務，新到舊排序，可用 datasetId 與 status 篩選。

參數

參數名稱	必填	類型	說明
`datasetId`	X	string	只列出此資料集的生成任務
`page`	X	integer	頁碼，從 1 開始；超過最後一頁回 404
`pageSize`	X	integer	每頁筆數，預設 20、上限 100（超過以 100 計）
`status`	X	string	依狀態過濾：pending running completed partial_completed failed

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/test-case/generation-
jobs/?datasetId=example&page=1&pageSize=1&status=example"

  -H "Authorization: Api-Key YOUR_API_KEY"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/test-case/generation-
jobs/?datasetId=example&page=1&pageSize=1&status=example", config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/test-case/generation-jobs/?
datasetId=example&page=1&pageSize=1&status=example"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->get("https://api.maiagent.ai/api/v1/test-case/generation-jobs/?datasetId=example&page=1&pageSize=1&status=example", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
{
  "count": integer
  "next"?: string (uri) // 非必填
```

```
  "previous"?: string (uri) // 非必填
  "results": [
    {
      "id": string (uuid)
      "dataset":
      {
        "id": string (uuid)
        "name": string
      }
      "status"?: string (enum: pending, running, completed,
partial_completed, failed) // * `pending` - Pending
* `running` - Generating
* `completed` - Completed
* `partial_completed` - Partially completed
* `failed` - Generation failed (非必填)
      "jobType"?:  // Single-turn Q&A test data or multi-turn
conversation test data

* `single_turn` - Single turn
* `multi_turn` - Multi turn (非必填)
      {
      }
      "requestedNumTestCases"?: integer // 非必填
      "totalFiles"?: integer // 非必填
      "processedFiles"?: integer // 非必填
      "generatedCount"?: integer // 非必填
      "progressPercentage": number (double)
      "errorMessage"?: string // Error message recorded when the whole
batch fails (非必填)
      "fileResults"?: object // Result for each file, such as
[{'file_id', 'filename', 'status', 'generated', 'error'}] (非必填)
      "startedAt"?: string (timestamp) // 非必填
      "completedAt"?: string (timestamp) // 非必填
      "createdAt": string (timestamp)
      "updatedAt": string (timestamp)
    }
  ]
}
```

回應範例值

```
{
  "count": 123,
  "next": "http://api.example.org/accounts/?page=4",
```

```
  "previous": "http://api.example.org/accounts/?page=2",
  "results": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "dataset": {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "name": "回應字串"
      },
      "status": "pending",
      "jobType": {},
      "requestedNumTestCases": 456,
      "totalFiles": 456,
      "processedFiles": 456,
      "generatedCount": 456,
      "progressPercentage": 456,
      "errorMessage": "回應字串",
      "fileResults": null,
      "startedAt": "回應字串",
      "completedAt": "回應字串",
      "createdAt": "回應字串",
      "updatedAt": "回應字串"
    }
  ]
}
```


查詢測試案例生成任務進度

`GET` `/api/v1/test-case/generation-jobs/{jobId}`

status 為 pending、running、completed、partial_completed 或 failed；generatedCount 是已生成的題數，fileResults 列出每個檔案的結果與失敗原因。單輪與多輪的生成任務都用這個端點查詢，以 jobType 區分。

參數

參數名稱	必填	類型	說明

`jobId`	V	string	生成任務 ID，即「從知識庫檔案生成測試案例」回應的 jobId

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/test-case/generation-jobs/550e8400-e29b-41d4-a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/test-case/generation-
jobs/550e8400-e29b-41d4-a716-446655440000/", config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/test-case/generation-
jobs/550e8400-e29b-41d4-a716-446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->get("https://api.maiagent.ai/api/v1/test-case/generation-jobs/550e8400-e29b-41d4-a716-446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
{
  "id": string (uuid)
  "dataset":
  {
```

```
    "id": string (uuid)
    "name": string
  }
  "status"?: string (enum: pending, running, completed,
partial_completed, failed) // * `pending` - Pending
* `running` - Generating
* `completed` - Completed
* `partial_completed` - Partially completed
* `failed` - Generation failed (非必填)
  "jobType"?:  // Single-turn Q&A test data or multi-turn conversation
test data

* `single_turn` - Single turn
* `multi_turn` - Multi turn (非必填)
  {
  }
  "requestedNumTestCases"?: integer // 非必填
  "totalFiles"?: integer // 非必填
  "processedFiles"?: integer // 非必填
  "generatedCount"?: integer // 非必填
  "progressPercentage": number (double)
  "errorMessage"?: string // Error message recorded when the whole batch
fails (非必填)
  "fileResults"?: object // Result for each file, such as [{'file_id',
'filename', 'status', 'generated', 'error'}] (非必填)
  "startedAt"?: string (timestamp) // 非必填
  "completedAt"?: string (timestamp) // 非必填
  "createdAt": string (timestamp)
  "updatedAt": string (timestamp)
}
```

回應範例值

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "dataset": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應字串"
  },
  "status": "pending",
  "jobType": {},
  "requestedNumTestCases": 456,
  "totalFiles": 456,
  "processedFiles": 456,
```

```
  "generatedCount": 456,
  "progressPercentage": 456,
  "errorMessage": "回應字串",
  "fileResults": null,
  "startedAt": "回應字串",
  "completedAt": "回應字串",
  "createdAt": "回應字串",
  "updatedAt": "回應字串"
}
```


更新單輪測試案例

PUT `/api/v1/test-case/{id}`

參數

參數名稱	必填	類型	說明
`id`	V	string	測試案例 ID

請求內容

請求參數

欄位	類型	必填	說明
question	string	是	
groundTruth	string	否	
status	string (enum: active, inactive, pending)	否	`active` : Active ; `inactive` : Inactive ; `pending` : Pending Review;

欄位	類型	必填	說明
flaky	boolean	否	Flaky test cases still run and keep their results, but are excluded from the pass rate.

請求結構範例

```
{
  "question": string
  "groundTruth"?: string // 非必填
  "status"?: string (enum: active, inactive, pending) // * `active` - Active
* `inactive` - Inactive
* `pending` - Pending Review (非必填)
  "flaky"?: boolean // Flaky test cases still run and keep their results, but are excluded from the pass rate. (非必填)
}
```

請求範例值

```
{
  "question": "範例字串",
  "groundTruth": "範例字串",
  "status": "active",
  "flaky": true
}
```

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X PUT "https://api.maiagent.ai/api/v1/test-case/550e8400-e29b-
41d4-a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "question": "範例字串",
    "groundTruth": "範例字串",
    "status": "active",
    "flaky": true
  }'

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// 請求內容 (payload)
const data = {
    "question": "範例字串",
    "groundTruth": "範例字串",
    "status": "active",
    "flaky": true
  };

axios.put("https://api.maiagent.ai/api/v1/test-case/550e8400-e29b-
41d4-a716-446655440000/", data, config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/test-case/550e8400-e29b-41d4-
a716-446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# 請求內容 (payload)
data = {
    "question": "範例字串",
    "groundTruth": "範例字串",
    "status": "active",
    "flaky": True
}

response = requests.put(url, json=data, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->put("https://api.maiagent.ai/api/v1/test-case/550e8400-e29b-41d4-a716-446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'question' => '範例字串',
            'groundTruth' => '範例字串',
            'status' => 'active',
            'flaky' => true
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
{
  "id": string (uuid)
  "dataset":
  {
    "id": string (uuid)
    "name": string
  }
  "question": string
  "groundTruth"?: string // 非必填
  "status"?: string (enum: active, inactive, pending) // * `active` -
Active
* `inactive` - Inactive
* `pending` - Pending Review (非必填)
  "creationMethod"?: string (enum: manual, file, generate) // * `manual`
- Manual
* `file` - File import
* `generate` - Generated (非必填)
  "sourceFile"?: string // Name of the CSV, Excel or knowledge base file
this test case came from (非必填)
  "flaky"?: boolean // Flaky test cases still run and keep their results,
but are excluded from the pass rate. (非必填)
  "createdAt": string (timestamp)
  "updatedAt": string (timestamp)
}
```

回應範例值

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "dataset": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應字串"
  },
  "question": "回應字串",
  "groundTruth": "回應字串",
  "status": "active",
  "creationMethod": "manual",
  "sourceFile": "回應字串",
  "flaky": false,
  "createdAt": "回應字串",
```

```
  "updatedAt": "回應字串"
}
```

部分更新單輪測試案例

PATCH `/api/v1/test-case/{id}`

想暫時不測某一題時，把 status 改成 inactive，評估會略過它，過往的評估結果也會保留。

參數

參數名稱	必填	類型	說明
`id`	V	string	測試案例 ID

請求內容

請求參數

欄位	類型	必填	說明
question	string	否	
groundTruth	string	否	
status	string (enum: active, inactive, pending)	否	`active` : Active ; `inactive` : Inactive ; `pending` : Pending Review;
flaky	boolean	否	Flaky test cases still run and keep their results, but are excluded from the pass rate.

請求結構範例

```
{
  "question"?: string // 非必填
  "groundTruth"?: string // 非必填
  "status"?: string (enum: active, inactive, pending) // * `active` -
Active
* `inactive` - Inactive
* `pending` - Pending Review (非必填)
  "flaky"?: boolean // Flaky test cases still run and keep their results,
but are excluded from the pass rate. (非必填)
}
```

請求範例值

```
{
  "question": "範例字串",
  "groundTruth": "範例字串",
  "status": "active",
  "flaky": true
}
```

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X PATCH "https://api.maiagent.ai/api/v1/test-case/550e8400-
e29b-41d4-a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "question": "範例字串",
    "groundTruth": "範例字串",
    "status": "active",
    "flaky": true
  }'

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// 請求內容 (payload)
const data = {
    "question": "範例字串",
    "groundTruth": "範例字串",
    "status": "active",
    "flaky": true
  };

axios.patch("https://api.maiagent.ai/api/v1/test-case/550e8400-e29b-41d4-a716-446655440000/", data, config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/test-case/550e8400-e29b-41d4-
a716-446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# 請求內容 (payload)
data = {
    "question": "範例字串",
    "groundTruth": "範例字串",
    "status": "active",
    "flaky": True
}

response = requests.patch(url, json=data, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->patch("https://api.maiagent.ai/api/v1/test-case/550e8400-e29b-41d4-a716-446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'question' => '範例字串',
            'groundTruth' => '範例字串',
            'status' => 'active',
            'flaky' => true
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
{
  "id": string (uuid)
  "dataset":
  {
    "id": string (uuid)
    "name": string
  }
  "question": string
  "groundTruth"?: string // 非必填
  "status"?: string (enum: active, inactive, pending) // * `active` -
Active
* `inactive` - Inactive
* `pending` - Pending Review (非必填)
  "creationMethod"?: string (enum: manual, file, generate) // * `manual`
- Manual
* `file` - File import
* `generate` - Generated (非必填)
  "sourceFile"?: string // Name of the CSV, Excel or knowledge base file
this test case came from (非必填)
  "flaky"?: boolean // Flaky test cases still run and keep their results,
but are excluded from the pass rate. (非必填)
  "createdAt": string (timestamp)
  "updatedAt": string (timestamp)
}
```

回應範例值

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "dataset": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應字串"
  },
  "question": "回應字串",
  "groundTruth": "回應字串",
  "status": "active",
  "creationMethod": "manual",
  "sourceFile": "回應字串",
  "flaky": false,
  "createdAt": "回應字串",
```

```
  "updatedAt": "回應字串"
}
```

刪除單輪測試案例

DELETE `/api/v1/test-case/{id}`

會一併刪除這筆測試案例在過往評估中的逐題結果；只想暫停測試請改用 status。

參數

參數名稱	必填	類型	說明
id	V	string	測試案例 ID

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X DELETE "https://api.maiagent.ai/api/v1/test-case/550e8400-
e29b-41d4-a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

// 請求內容 (payload)
const data = null;

axios.delete("https://api.maiagent.ai/api/v1/test-case/550e8400-
e29b-41d4-a716-446655440000/", data, config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/test-case/550e8400-e29b-41d4-
a716-446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.delete(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>delete("https://api.maiagent.ai/api/v1/test-case/550e8400-e29b-
41d4-a716-446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼	說明
204	No response body

批次刪除單輪測試案例

`POST` `/api/v1/test-case/bulk-delete/`

以 testCaseIds 傳入要刪除的測試案例 ID 陣列，成功回 204。刪除的影響同 刪除單輪測試案例。

請求內容

請求參數

欄位	類型	必填	說明
test_case_ids	array[string]	是	要刪除的測試案例 ID 列表

請求結構範例

```
{
  "test_case_ids": [ // 要刪除的測試案例 ID 列表
    string (uuid)
  ]
}
```

請求範例值

```
{
  "test_case_ids": [
    "550e8400-e29b-41d4-a716-446655440000"
  ]
}
```

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X POST "https://api.maiagent.ai/api/v1/test-case/bulk-delete/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "test_case_ids": [
      "550e8400-e29b-41d4-a716-446655440000"
    ]
  }'

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// 請求內容 (payload)
const data = {
    "test_case_ids": [
      "550e8400-e29b-41d4-a716-446655440000"
    ]
  };

axios.post("https://api.maiagent.ai/api/v1/test-case/bulk-delete/",
data, config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/test-case/bulk-delete/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# 請求內容 (payload)
data = {
    "test_case_ids": [
        "550e8400-e29b-41d4-a716-446655440000"
    ]
}

response = requests.post(url, json=data, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->post("https://api.maiagent.ai/api/v1/test-case/bulk-delete/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'test_case_ids' => [
                '550e8400-e29b-41d4-a716-446655440000'
            ]
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼	說明

204	No response body

列出多輪測試案例

GET `/api/v1/multi-turn-test-case/`

用 datasetId 篩選單一測試集。

參數

參數名稱	必填	類型	說明
`dataset`	X	string	同 datasetId，只列出此資料集的多輪對話測試案例
`datasetId`	X	string	只列出此資料集的多輪對話測試案例
`ordering`	X	string	排序欄位：created_at 或 updated_at，前面加 - 為由新到舊（例：-updated_at）；未指定時依建立時間由新到舊
`page`	X	integer	頁碼，從 1 開始；超過最後一頁回 404
`pageSize`	X	integer	每頁筆數，預設 20、上限 100（超過以 100 計）
`search`	X	string	關鍵字，比對情境（scenario）或預期結果（expected_outcome）（部分符合、不分大小寫；以空白分隔多個關鍵字時須全部符合）
`status`	X	string	只列出此狀態的多輪對話測試案例。可用值：`active`: Active ; `inactive`: Inactive;

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/multi-turn-test-case/?
dataset=550e8400-e29b-41d4-a716-446655440000&datasetId=550e8400-
e29b-41d4-a716-
446655440000&ordering=example&page=1&pageSize=1&search=example&statu
s=active"

  -H "Authorization: Api-Key YOUR_API_KEY"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/multi-turn-test-case/?
dataset=550e8400-e29b-41d4-a716-446655440000&datasetId=550e8400-
e29b-41d4-a716-
446655440000&ordering=example&page=1&pageSize=1&search=example&statu
s=active", config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/multi-turn-test-case/?
dataset=550e8400-e29b-41d4-a716-446655440000&datasetId=550e8400-
e29b-41d4-a716-
446655440000&ordering=example&page=1&pageSize=1&search=example&statu
s=active"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->get("https://api.maiagent.ai/api/v1/multi-turn-test-case/?dataset=550e8400-e29b-41d4-a716-446655440000&datasetId=550e8400-e29b-41d4-a716-446655440000&ordering=example&page=1&pageSize=1&search=example&status=active", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
{
  "count": integer
  "next"?: string (uri) // 非必填
  "previous"?: string (uri) // 非必填
  "results": [
    {
      "id": string (uuid)
      "dataset":
      {
        "id": string (uuid)
        "name": string
      }
      "scenario": string // Task scenario the simulated user should
accomplish
      "expectedOutcome": string // Outcome a successful conversation
should reach, also used as the simulation stop condition
      "userDescription"?: string // Persona of the simulated user, such
as tone, background and level of expertise (非必填)
      "status"?: string (enum: active, inactive) // * `active` - Active
* `inactive` - Inactive (非必填)
      "creationMethod":
      {
      }
      "sourceFile": string // Name of the knowledge base file this multi-
turn test case was generated from
      "flaky"?: boolean // Flaky test cases still run and keep their
results, but are excluded from the pass rate. (非必填)
      "createdAt": string (timestamp)
      "updatedAt": string (timestamp)
    }
  ]
}
```

回應範例值

```
{
  "count": 123,
  "next": "http://api.example.org/accounts/?page=4",
  "previous": "http://api.example.org/accounts/?page=2",
  "results": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "dataset": {
```

```
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "name": "回應字串"
      },
      "scenario": "回應字串",
      "expectedOutcome": "回應字串",
      "userDescription": "回應字串",
      "status": "active",
      "creationMethod": {},
      "sourceFile": "回應字串",
      "flaky": false,
      "createdAt": "回應字串",
      "updatedAt": "回應字串"
    }
  ]
}
```


建立多輪測試案例

POST `/api/v1/multi-turn-test-case/`

datasetId、scenario（模擬使用者要完成的任務情境）、expectedOutcome（對話成功時應達成的結果，也是模擬對話的結束條件）必填；userDescription 選填，描述模擬使用者的語氣、背景與專業程度。

請求內容

請求參數

欄位	類型	必填	說明
datasetId	string (uuid)	是	
scenario	string	是	
expectedOutcome	string	是	
userDescription	string	否	

欄位	類型	必填	說明
status	object	否	
flaky	boolean	否	

請求結構範例

```
{
  "datasetId": string (uuid)
  "scenario": string
  "expectedOutcome": string
  "userDescription"?: string // 非必填
  "status"?:  // 非必填
  {
  }
  "flaky"?: boolean // 非必填
}
```

請求範例值

```
{
  "datasetId": "550e8400-e29b-41d4-a716-446655440000",
  "scenario": "範例字串",
  "expectedOutcome": "範例字串",
  "userDescription": "範例字串",
  "status": {},
  "flaky": true
}
```

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X POST "https://api.maiagent.ai/api/v1/multi-turn-test-case/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "datasetId": "550e8400-e29b-41d4-a716-446655440000",
    "scenario": "範例字串",
    "expectedOutcome": "範例字串",
    "userDescription": "範例字串",
    "status": {},
    "flaky": true
  }'

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// 請求內容 (payload)
const data = {
    "datasetId": "550e8400-e29b-41d4-a716-446655440000",
    "scenario": "範例字串",
    "expectedOutcome": "範例字串",
    "userDescription": "範例字串",
    "status": {},
    "flaky": true
  };

axios.post("https://api.maiagent.ai/api/v1/multi-turn-test-case/",
data, config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/multi-turn-test-case/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# 請求內容 (payload)
data = {
    "datasetId": "550e8400-e29b-41d4-a716-446655440000",
    "scenario": "範例字串",
    "expectedOutcome": "範例字串",
    "userDescription": "範例字串",
    "status": {},
    "flaky": True
}

response = requests.post(url, json=data, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->post("https://api.maiagent.ai/api/v1/multi-turn-test-case/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'datasetId' => '550e8400-e29b-41d4-a716-446655440000',
            'scenario' => '範例字串',
            'expectedOutcome' => '範例字串',
            'userDescription' => '範例字串',
            'status' => new \stdClass(),
            'flaky' => true
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 201

回應結構範例

```
{
  "id": string (uuid)
  "dataset":
  {
    "id": string (uuid)
    "name": string
  }
  "scenario": string // Task scenario the simulated user should
accomplish
  "expectedOutcome": string // Outcome a successful conversation should
reach, also used as the simulation stop condition
  "userDescription"?: string // Persona of the simulated user, such as
tone, background and level of expertise (非必填)
  "status"?: string (enum: active, inactive) // * `active` - Active
* `inactive` - Inactive (非必填)
  "creationMethod":
  {
  }
  "sourceFile": string // Name of the knowledge base file this multi-turn
test case was generated from
  "flaky"?: boolean // Flaky test cases still run and keep their results,
but are excluded from the pass rate. (非必填)
  "createdAt": string (timestamp)
  "updatedAt": string (timestamp)
}
```

回應範例值

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "dataset": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應字串"
  },
  "scenario": "回應字串",
  "expectedOutcome": "回應字串",
  "userDescription": "回應字串",
  "status": "active",
  "creationMethod": {},
```

```
  "sourceFile": "回應字串",
  "flaky": false,
  "createdAt": "回應字串",
  "updatedAt": "回應字串"
}
```

從知識庫檔案生成多輪測試案例

POST `/api/v1/multi-turn-test-case/generate-from-file/`

用 knowledgeBaseFileIds 指定來源檔案，numTestCases 預設 5、最多 20。生成在背景執行，回應 202 與 jobId，用 查詢測試案例生成任務進度 追蹤。Credit：同單輪生成，依實際生成的題數扣 agentops_test_gen。

請求內容

請求參數

欄位	類型	必填	說明
datasetId	string (uuid)	是	
knowledgeBaseFileIds	array[string]	是	List of KnowledgeBaseFile IDs to generate multi-turn test cases from
numTestCases	integer	否	

請求結構範例

```
{
  "datasetId": string (uuid)
  "knowledgeBaseFileIds": [ // List of KnowledgeBaseFile IDs to generate
multi-turn test cases from
    string (uuid)
  ]
```

```
  "numTestCases"?: integer // 非必填
}
```

請求範例值

```
{
  "datasetId": "550e8400-e29b-41d4-a716-446655440000",
  "knowledgeBaseFileIds": [
    "550e8400-e29b-41d4-a716-446655440000"
  ],
  "numTestCases": 123
}
```

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X POST "https://api.maiagent.ai/api/v1/multi-turn-test-
case/generate-from-file/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "datasetId": "550e8400-e29b-41d4-a716-446655440000",
    "knowledgeBaseFileIds": [
      "550e8400-e29b-41d4-a716-446655440000"
    ],
    "numTestCases": 123
  }'

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// 請求內容 (payload)
const data = {
    "datasetId": "550e8400-e29b-41d4-a716-446655440000",
    "knowledgeBaseFileIds": [
      "550e8400-e29b-41d4-a716-446655440000"
    ],
    "numTestCases": 123
  };

axios.post("https://api.maiagent.ai/api/v1/multi-turn-test-
case/generate-from-file/", data, config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/multi-turn-test-case/generate-
from-file/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# 請求內容 (payload)
data = {
    "datasetId": "550e8400-e29b-41d4-a716-446655440000",
    "knowledgeBaseFileIds": [
        "550e8400-e29b-41d4-a716-446655440000"
    ],
    "numTestCases": 123
}

response = requests.post(url, json=data, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->post("https://api.maiagent.ai/api/v1/multi-turn-test-case/generate-from-file/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'datasetId' => '550e8400-e29b-41d4-a716-446655440000',
            'knowledgeBaseFileIds' => [
                '550e8400-e29b-41d4-a716-446655440000'
            ],
            'numTestCases' => 123
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 202

回應結構範例

```
{
  "status": string (enum: accepted) // * `accepted` - 固定為 accepted，表示已受理並排入背景執行
  "message": string // 受理說明
  "jobId": string (uuid) // 生成任務 ID，可用 GET /api/v1/test-case/generation-jobs/{jobId}/ 查詢進度；同一測試集已有進行中的生成任務時，回傳的是該任務
  "taskId": string // 背景任務 ID
}
```

回應範例值

```
{
  "status": "accepted",
  "message": "回應字串",
  "jobId": "550e8400-e29b-41d4-a716-446655440000",
  "taskId": "回應字串"
}
```

取得特定多輪測試案例

GET `/api/v1/multi-turn-test-case/{id}`

參數

參數名稱	必填	類型	說明
id	V	string	多輪對話測試案例 ID

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/multi-turn-test-
case/550e8400-e29b-41d4-a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/multi-turn-test-
case/550e8400-e29b-41d4-a716-446655440000/", config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/multi-turn-test-case/550e8400-e29b-41d4-a716-446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->get("https://api.maiagent.ai/api/v1/multi-turn-test-case/550e8400-e29b-41d4-a716-446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
{
  "id": string (uuid)
  "dataset":
  {
```

```
    "id": string (uuid)
    "name": string
  }
  "scenario": string // Task scenario the simulated user should
accomplish
  "expectedOutcome": string // Outcome a successful conversation should
reach, also used as the simulation stop condition
  "userDescription"?: string // Persona of the simulated user, such as
tone, background and level of expertise (非必填)
  "status"?: string (enum: active, inactive) // * `active` - Active
* `inactive` - Inactive (非必填)
  "creationMethod":
  {
  }
  "sourceFile": string // Name of the knowledge base file this multi-turn
test case was generated from
  "flaky"?: boolean // Flaky test cases still run and keep their results,
but are excluded from the pass rate. (非必填)
  "createdAt": string (timestamp)
  "updatedAt": string (timestamp)
}
```

回應範例值

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "dataset": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應字串"
  },
  "scenario": "回應字串",
  "expectedOutcome": "回應字串",
  "userDescription": "回應字串",
  "status": "active",
  "creationMethod": {},
  "sourceFile": "回應字串",
  "flaky": false,
  "createdAt": "回應字串",
  "updatedAt": "回應字串"
}
```

更新多輪測試案例

PUT `/api/v1/multi-turn-test-case/{id}`

參數

參數名稱	必填	類型	說明
`id`	V	string	多輪對話測試案例 ID

請求內容

請求參數

欄位	類型	必填	說明
scenario	string	是	Task scenario the simulated user should accomplish
expectedOutcome	string	是	Outcome a successful conversation should reach, also used as the simulation stop condition
userDescription	string	否	Persona of the simulated user, such as tone, background and level of expertise
status	string (enum: active, inactive)	否	`active` : Active ; `inactive` : Inactive;
flaky	boolean	否	Flaky test cases still run and keep their results, but are excluded from the pass rate.

請求結構範例

```
{
  "scenario": string // Task scenario the simulated user should
accomplish
  "expectedOutcome": string // Outcome a successful conversation should
reach, also used as the simulation stop condition
  "userDescription"?: string // Persona of the simulated user, such as
tone, background and level of expertise (非必填)
  "status"?: string (enum: active, inactive) // * `active` - Active
* `inactive` - Inactive (非必填)
  "flaky"?: boolean // Flaky test cases still run and keep their results,
but are excluded from the pass rate. (非必填)
}
```

請求範例值

```
{
  "scenario": "範例字串",
  "expectedOutcome": "範例字串",
  "userDescription": "範例字串",
  "status": "active",
  "flaky": true
}
```

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X PUT "https://api.maiagent.ai/api/v1/multi-turn-test-
case/550e8400-e29b-41d4-a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "scenario": "範例字串",
    "expectedOutcome": "範例字串",
    "userDescription": "範例字串",
    "status": "active",
    "flaky": true
  }'

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// 請求內容 (payload)
const data = {
    "scenario": "範例字串",
    "expectedOutcome": "範例字串",
    "userDescription": "範例字串",
    "status": "active",
    "flaky": true
  };

axios.put("https://api.maiagent.ai/api/v1/multi-turn-test-
case/550e8400-e29b-41d4-a716-446655440000/", data, config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/multi-turn-test-case/550e8400-
e29b-41d4-a716-446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# 請求內容 (payload)
data = {
    "scenario": "範例字串",
    "expectedOutcome": "範例字串",
    "userDescription": "範例字串",
    "status": "active",
    "flaky": True
}

response = requests.put(url, json=data, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->put("https://api.maiagent.ai/api/v1/multi-turn-test-case/550e8400-e29b-41d4-a716-446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'scenario' => '範例字串',
            'expectedOutcome' => '範例字串',
            'userDescription' => '範例字串',
            'status' => 'active',
            'flaky' => true
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
{
  "id": string (uuid)
  "dataset":
  {
    "id": string (uuid)
    "name": string
  }
  "scenario": string // Task scenario the simulated user should
accomplish
  "expectedOutcome": string // Outcome a successful conversation should
reach, also used as the simulation stop condition
  "userDescription"?: string // Persona of the simulated user, such as
tone, background and level of expertise (非必填)
  "status"?: string (enum: active, inactive) // * `active` - Active
* `inactive` - Inactive (非必填)
  "creationMethod":
  {
  }
  "sourceFile": string // Name of the knowledge base file this multi-turn
test case was generated from
  "flaky"?: boolean // Flaky test cases still run and keep their results,
but are excluded from the pass rate. (非必填)
  "createdAt": string (timestamp)
  "updatedAt": string (timestamp)
}
```

回應範例值

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "dataset": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應字串"
  },
  "scenario": "回應字串",
  "expectedOutcome": "回應字串",
  "userDescription": "回應字串",
  "status": "active",
  "creationMethod": {},
  "sourceFile": "回應字串",
  "flaky": false,
```

```
  "createdAt": "回應字串",
  "updatedAt": "回應字串"
}
```

部分更新多輪測試案例

PATCH `/api/v1/multi-turn-test-case/{id}`

參數

參數名稱	必填	類型	說明
`id`	V	string	多輪對話測試案例 ID

請求內容

請求參數

欄位	類型	必填	說明
scenario	string	否	Task scenario the simulated user should accomplish
expectedOutcome	string	否	Outcome a successful conversation should reach, also used as the simulation stop condition
userDescription	string	否	Persona of the simulated user, such as tone, background and level of expertise
status	string (enum: active, inactive)	否	`active` : Active ; `inactive` : Inactive;

欄位	類型	必填	說明
flaky	boolean	否	Flaky test cases still run and keep their results, but are excluded from the pass rate.

請求結構範例

```
{
  "scenario"?: string // Task scenario the simulated user should accomplish (非必填)
  "expectedOutcome"?: string // Outcome a successful conversation should reach, also used as the simulation stop condition (非必填)
  "userDescription"?: string // Persona of the simulated user, such as tone, background and level of expertise (非必填)
  "status"?: string (enum: active, inactive) // * `active` - Active * `inactive` - Inactive (非必填)
  "flaky"?: boolean // Flaky test cases still run and keep their results, but are excluded from the pass rate. (非必填)
}
```

請求範例值

```
{
  "scenario": "範例字串",
  "expectedOutcome": "範例字串",
  "userDescription": "範例字串",
  "status": "active",
  "flaky": true
}
```

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X PATCH "https://api.maiagent.ai/api/v1/multi-turn-test-
case/550e8400-e29b-41d4-a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "scenario": "範例字串",
    "expectedOutcome": "範例字串",
    "userDescription": "範例字串",
    "status": "active",
    "flaky": true
  }'

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// 請求內容 (payload)
const data = {
    "scenario": "範例字串",
    "expectedOutcome": "範例字串",
    "userDescription": "範例字串",
    "status": "active",
    "flaky": true
  };

axios.patch("https://api.maiagent.ai/api/v1/multi-turn-test-
case/550e8400-e29b-41d4-a716-446655440000/", data, config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/multi-turn-test-case/550e8400-
e29b-41d4-a716-446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# 請求內容 (payload)
data = {
    "scenario": "範例字串",
    "expectedOutcome": "範例字串",
    "userDescription": "範例字串",
    "status": "active",
    "flaky": True
}

response = requests.patch(url, json=data, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>patch("https://api.maiagent.ai/api/v1/multi-turn-test-
case/550e8400-e29b-41d4-a716-446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'scenario' => '範例字串',
            'expectedOutcome' => '範例字串',
            'userDescription' => '範例字串',
            'status' => 'active',
            'flaky' => true
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
{
  "id": string (uuid)
  "dataset":
  {
    "id": string (uuid)
    "name": string
  }
  "scenario": string // Task scenario the simulated user should
accomplish
  "expectedOutcome": string // Outcome a successful conversation should
reach, also used as the simulation stop condition
  "userDescription"?: string // Persona of the simulated user, such as
tone, background and level of expertise (非必填)
  "status"?: string (enum: active, inactive) // * `active` - Active
* `inactive` - Inactive (非必填)
  "creationMethod":
  {
  }
  "sourceFile": string // Name of the knowledge base file this multi-turn
test case was generated from
  "flaky"?: boolean // Flaky test cases still run and keep their results,
but are excluded from the pass rate. (非必填)
  "createdAt": string (timestamp)
  "updatedAt": string (timestamp)
}
```

回應範例值

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "dataset": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應字串"
  },
  "scenario": "回應字串",
  "expectedOutcome": "回應字串",
  "userDescription": "回應字串",
  "status": "active",
  "creationMethod": {},
```

```
  "sourceFile": "回應字串",
  "flaky": false,
  "createdAt": "回應字串",
  "updatedAt": "回應字串"
}
```

刪除多輪測試案例

DELETE `/api/v1/multi-turn-test-case/{id}`

參數

參數名稱	必填	類型	說明
`id`	V	string	多輪對話測試案例 ID

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X DELETE "https://api.maiagent.ai/api/v1/multi-turn-test-
case/550e8400-e29b-41d4-a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

// 請求內容 (payload)
const data = null;

axios.delete("https://api.maiagent.ai/api/v1/multi-turn-test-
case/550e8400-e29b-41d4-a716-446655440000/", data, config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/multi-turn-test-case/550e8400-
e29b-41d4-a716-446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.delete(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>delete("https://api.maiagent.ai/api/v1/multi-turn-test-
case/550e8400-e29b-41d4-a716-446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼	說明
204	No response body

列出可用的評估模型

GET `/api/v1/evaluations/evaluation-llms/`

isDefault 為 true 的模型，是執行評估時沒有指定 evaluationLlmId 所使用的預設評估模型。

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/evaluations/evaluation-
llms/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/evaluations/evaluation-
llms/", config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/evaluations/evaluation-llms/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/evaluations/evaluation-llms/",
[
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
[
  {
    "id": string (uuid)
```

```
    "name": string
    "value": string
    "provider": string
    "isDefault": boolean
  }
]
```

回應範例值

```
[
  {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應字串",
    "value": "回應字串",
    "provider": "回應字串",
    "isDefault": false
  }
]
```

執行單輪評估

POST `/api/v1/evaluations/evaluate/`

datasetId 與 chatbotId 必填；evaluationLlmId 省略時使用預設評估模型。metricConfig 以布林值開關內建指標，customMetrics 最多 10 個自訂指標。只評估狀態為 active 的測試案例。評估在背景執行，回應 202 與 evaluationId。Credit：送出前檢查組織 Credit，不足回 402；評估結束時依完成的測試案例數扣 agentops_test_run 與 agentops_deepeval，評估模型的呼叫另計。

請求內容

請求參數

欄位	類型	必填	說明
datasetId	string (uuid)	是	

欄位	類型	必填	說明
chatbotId	string (uuid)	是	
evaluationLlmId	string (uuid)	否	
name	string	否	
description	string	否	
metricConfig	object	否	
customMetrics	array[DatasetEvaluationCustomMetric]	否	

請求結構範例

```
{
  "datasetId": string (uuid)
  "chatbotId": string (uuid)
  "evaluationLlmId"?: string (uuid) // 非必填
  "name"?: string // 非必填
  "description"?: string // 非必填
  "metricConfig"?: object // 非必填
  "customMetrics"?: [ // 非必填
    {
      "name": string
      "criteria"?: string // 非必填
      "evaluationSteps"?: [ // 非必填
        string
      ]
      "threshold"?: number (double) // 非必填
    }
  ]
}
```

請求範例值

```
{
  "dataset_id": "3fa85f64-5717-4562-b3fc-2c963f66afa6",
  "chatbot_id": "3fa85f64-5717-4562-b3fc-2c963f66afa6",
  "evaluation_llm_id": "3fa85f64-5717-4562-b3fc-2c963f66afa6",
  "name": "Evaluation Name",
  "description": "Evaluation Description",
  "metric_config": {
```

```
    "ground_truth": true,
    "task_completion": false,
    "tool_correctness": false,
    "guardrail": true,
    "summarize": false,
    "hallucination": true
  },
  "custom_metrics": [
    {
      "name": "Support Tone",
      "criteria": "The answer should be polite, empathetic, and
professional in tone.",
      "threshold": 0.6
    }
  ]
}
```

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X POST "https://api.maiagent.ai/api/v1/evaluations/evaluate/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "dataset_id": "3fa85f64-5717-4562-b3fc-2c963f66afa6",
    "chatbot_id": "3fa85f64-5717-4562-b3fc-2c963f66afa6",
    "evaluation_llm_id": "3fa85f64-5717-4562-b3fc-2c963f66afa6",
    "name": "Evaluation Name",
    "description": "Evaluation Description",
    "metric_config": {
      "ground_truth": true,
      "task_completion": false,
      "tool_correctness": false,
      "guardrail": true,
      "summarize": false,
      "hallucination": true
    },
    "custom_metrics": [
      {
        "name": "Support Tone",
        "criteria": "The answer should be polite, empathetic, and
professional in tone.",
        "threshold": 0.6
      }
    ]
  }'

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// 請求內容 (payload)
const data = {
    "dataset_id": "3fa85f64-5717-4562-b3fc-2c963f66afa6",
    "chatbot_id": "3fa85f64-5717-4562-b3fc-2c963f66afa6",
    "evaluation_llm_id": "3fa85f64-5717-4562-b3fc-2c963f66afa6",
    "name": "Evaluation Name",
    "description": "Evaluation Description",
    "metric_config": {
      "ground_truth": true,
      "task_completion": false,
      "tool_correctness": false,
      "guardrail": true,
      "summarize": false,
      "hallucination": true
    },
    "custom_metrics": [
      {
        "name": "Support Tone",
        "criteria": "The answer should be polite, empathetic, and
professional in tone.",
        "threshold": 0.6
      }
    ]
  };

axios.post("https://api.maiagent.ai/api/v1/evaluations/evaluate/",
data, config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
```

```
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/evaluations/evaluate/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# 請求內容 (payload)
data = {
    "dataset_id": "3fa85f64-5717-4562-b3fc-2c963f66afa6",
    "chatbot_id": "3fa85f64-5717-4562-b3fc-2c963f66afa6",
    "evaluation_llm_id": "3fa85f64-5717-4562-b3fc-2c963f66afa6",
    "name": "Evaluation Name",
    "description": "Evaluation Description",
    "metric_config": {
        "ground_truth": True,
        "task_completion": False,
        "tool_correctness": False,
        "guardrail": True,
        "summarize": False,
        "hallucination": True
    },
    "custom_metrics": [
        {
            "name": "Support Tone",
            "criteria": "The answer should be polite, empathetic,
and professional in tone.",
            "threshold": 0.6
        }
    ]
}

response = requests.post(url, json=data, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>post("https://api.maiagent.ai/api/v1/evaluations/evaluate/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'dataset_id' => '3fa85f64-5717-4562-b3fc-2c963f66afa6',
            'chatbot_id' => '3fa85f64-5717-4562-b3fc-2c963f66afa6',
            'evaluation_llm_id' => '3fa85f64-5717-4562-b3fc-
2c963f66afa6',
            'name' => 'Evaluation Name',
            'description' => 'Evaluation Description',
            'metric_config' => [
                'ground_truth' => true,
                'task_completion' => false,
                'tool_correctness' => false,
                'guardrail' => true,
                'summarize' => false,
                'hallucination' => true
            ],
            'custom_metrics' => [
                [
                    'name' => 'Support Tone',
                    'criteria' => 'The answer should be polite,
empathetic, and professional in tone.',
                    'threshold' => 0.6
                ]
            ]
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
```

```
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 202

回應結構範例

```
{
  "status": string (enum: accepted) // * `accepted` - 固定為 accepted，表示已受理並排入背景執行
  "message": string // 受理說明
  "evaluationId": string (uuid) // 評估 ID，可用 GET /api/v1/evaluations/{id}/ 輪詢 status 直到結束
}
```

回應範例值

```
{
  "status": "accepted",
  "message": "回應字串",
  "evaluationId": "550e8400-e29b-41d4-a716-446655440000"
}
```

執行多輪評估

`POST` `/api/v1/evaluations/multi-turn-evaluate/`

以測試集內的多輪測試案例模擬使用者與 Agent 對話後評分。maxTurns 是模擬使用者最多發話的輪數（2～10，預設 6），language 是模擬使用者的語言（Traditional Chinese、Simplified Chinese、English、Japanese、Korean，預設 Traditional Chinese）。測試集沒有任何 active 的多輪測試案例時回 400。回應與 Credit 同 執行單輪評估。

請求內容

請求參數

欄位	類型	必填	說明
datasetId	string (uuid)	是	
chatbotId	string (uuid)	是	
evaluationLlmId	string (uuid)	否	
name	string	否	
description	string	否	
maxTurns	integer	否	
minTurns	integer	否	
turnFaithfulness	boolean	否	
turnRelevancy	boolean	否	
conversationCompleteness	boolean	否	
language	object	否	
customMetrics	array[MultiTurnCustomMetric]	否	

請求結構範例

```
{
  "datasetId": string (uuid)
  "chatbotId": string (uuid)
  "evaluationLlmId"?: string (uuid) // 非必填
  "name"?: string // 非必填
```

```
  "description"?: string // 非必填
  "maxTurns"?: integer // 非必填
  "minTurns"?: integer // 非必填
  "turnFaithfulness"?: boolean // 非必填
  "turnRelevancy"?: boolean // 非必填
  "conversationCompleteness"?: boolean // 非必填
  "language"?:  // 非必填
  {
  }
  "customMetrics"?: [ // 非必填
    {
      "name": string
      "criteria"?: string // 非必填
      "evaluationSteps"?: [ // 非必填
        string
      ]
      "threshold"?: number (double) // 非必填
    }
  ]
}
```

請求範例值

```
{
  "dataset_id": "3fa85f64-5717-4562-b3fc-2c963f66afa6",
  "chatbot_id": "3fa85f64-5717-4562-b3fc-2c963f66afa6",
  "max_turns": 6,
  "min_turns": 2,
  "custom_metrics": [
    {
      "name": "Identity Check",
      "criteria": "The assistant confirms the user identity before
sharing account details.",
      "threshold": 0.6
    }
  ]
}
```

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X POST "https://api.maiagent.ai/api/v1/evaluations/multi-turn-evaluate/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "dataset_id": "3fa85f64-5717-4562-b3fc-2c963f66afa6",
    "chatbot_id": "3fa85f64-5717-4562-b3fc-2c963f66afa6",
    "max_turns": 6,
    "min_turns": 2,
    "custom_metrics": [
      {
        "name": "Identity Check",
        "criteria": "The assistant confirms the user identity before sharing account details.",
        "threshold": 0.6
      }
    ]
  }'

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// 請求內容 (payload)
const data = {
    "dataset_id": "3fa85f64-5717-4562-b3fc-2c963f66afa6",
    "chatbot_id": "3fa85f64-5717-4562-b3fc-2c963f66afa6",
    "max_turns": 6,
    "min_turns": 2,
    "custom_metrics": [
      {
        "name": "Identity Check",
        "criteria": "The assistant confirms the user identity before
sharing account details.",
        "threshold": 0.6
      }
    ]
  };

axios.post("https://api.maiagent.ai/api/v1/evaluations/multi-turn-
evaluate/", data, config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/evaluations/multi-turn-
evaluate/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# 請求內容 (payload)
data = {
    "dataset_id": "3fa85f64-5717-4562-b3fc-2c963f66afa6",
    "chatbot_id": "3fa85f64-5717-4562-b3fc-2c963f66afa6",
    "max_turns": 6,
    "min_turns": 2,
    "custom_metrics": [
        {
            "name": "Identity Check",
            "criteria": "The assistant confirms the user identity
before sharing account details.",
            "threshold": 0.6
        }
    ]
}

response = requests.post(url, json=data, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>post("https://api.maiagent.ai/api/v1/evaluations/multi-turn-
evaluate/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'dataset_id' => '3fa85f64-5717-4562-b3fc-2c963f66afa6',
            'chatbot_id' => '3fa85f64-5717-4562-b3fc-2c963f66afa6',
            'max_turns' => 6,
            'min_turns' => 2,
            'custom_metrics' => [
                [
                    'name' => 'Identity Check',
                    'criteria' => 'The assistant confirms the user
identity before sharing account details.',
                    'threshold' => 0.6
                ]
            ]
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 202

回應結構範例

```
{
  "status": string (enum: accepted) // * `accepted` - 固定為 accepted，表示已受理並排入背景執行
  "message": string // 受理說明
  "evaluationId": string (uuid) // 評估 ID，可用 GET /api/v1/evaluations/{id}/ 輪詢 status 直到結束
}
```

回應範例值

```
{
  "status": "accepted",
  "message": "回應字串",
  "evaluationId": "550e8400-e29b-41d4-a716-446655440000"
}
```

列出評估

`GET` `/api/v1/evaluations/`

可用 datasetId、chatbotId、status 篩選。

參數

參數名稱	必填	類型	說明
`chatbotId`	X	string	只列出評估此 AI 助理的評估
`datasetId`	X	string	只列出使用此資料集的評估
`ordering`	X	string	排序欄位：created_at 或 updated_at，前面加 - 為由新到舊（例：-updated_at）；未指定時依建立時間由新到舊
`page`	X	integer	頁碼，從 1 開始；超過最後一頁回 404
`pageSize`	X	integer	每頁筆數，預設 20、上限 100（超過以 100 計）
`query`	X	string	關鍵字，比對評估名稱、描述或 ID（部分符合）
`search`	X	string	關鍵字，比對評估名稱、資料集名稱或 AI 助理名稱（部分符合、不分大小寫；以空白分隔多個關鍵字時須全部符合）
`status`	X	string	只列出此狀態的評估。可用值： `pending`: Pending evaluation ; `running`: Evaluating ; `stopping`: Stopping ; `completed`: Completed ; `partial_completed`: Partially completed ; `failed`: Evaluation failed;

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/evaluations/?
chatbotId=550e8400-e29b-41d4-a716-446655440000&datasetId=550e8400-
e29b-41d4-a716-
446655440000&ordering=example&page=1&pageSize=1&query=example&search
=example&status=completed"

  -H "Authorization: Api-Key YOUR_API_KEY"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/evaluations/?
chatbotId=550e8400-e29b-41d4-a716-446655440000&datasetId=550e8400-
e29b-41d4-a716-
446655440000&ordering=example&page=1&pageSize=1&query=example&search
=example&status=completed", config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/evaluations/?
chatbotId=550e8400-e29b-41d4-a716-446655440000&datasetId=550e8400-
e29b-41d4-a716-
446655440000&ordering=example&page=1&pageSize=1&query=example&search
=example&status=completed"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/evaluations/?
chatbotId=550e8400-e29b-41d4-a716-446655440000&datasetId=550e8400-
e29b-41d4-a716-
446655440000&ordering=example&page=1&pageSize=1&query=example&search
=example&status=completed", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
{
  "count": integer
  "next"?: string (uri) // 非必填
  "previous"?: string (uri) // 非必填
  "results": [
    {
      "id": string (uuid)
      "name": string
      "description": string
      "chatbot":
      {
        "id": string (uuid)
        "name": string
      }
      "dataset":
      {
        "id": string (uuid)
        "name": string
      }
      "organization":
      {
        "id": string (uuid)
        "name": string
      }
      "evaluationLlm":
      {
        "id": string (uuid)
        "name": string
      }
      "status":
      {
      }
      "startedAt": string (timestamp)
      "completedAt": string (timestamp)
      "totalTestCases": integer
      "completedTestCases": integer
      "passedTestCases": integer // Number of test cases that passed
      "metricScores": object // Detailed score per evaluation metric,
such as ground_truth, task_completion and tool_correctness
      "evaluationConfig": object
      "progressPercentage": number (double)
      "overallScore": number (double)
      "passRate": number (double)
      "averageExecutionTimeMs": integer
```

```
      "totalExecutionTimeMs": integer
      "chatbotConfig": string
      "createdAt": string (timestamp)
      "updatedAt": string (timestamp)
      "insights":
      {
        "summary": string
        "metricStats"?: object // 非必填
        "recommendations"?: object // 非必填
      }
    }
  ]
}
```

回應範例值

```
{
  "count": 123,
  "next": "http://api.example.org/accounts/?page=4",
  "previous": "http://api.example.org/accounts/?page=2",
  "results": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "回應字串",
      "description": "回應字串",
      "chatbot": {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "name": "回應字串"
      },
      "dataset": {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "name": "回應字串"
      },
      "organization": {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "name": "回應字串"
      },
      "evaluationLlm": {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "name": "回應字串"
      },
      "status": {},
      "startedAt": "回應字串",
      "completedAt": "回應字串",
```

```
        "totalTestCases": 456,
        "completedTestCases": 456,
        "passedTestCases": 456,
        "metricScores": null,
        "evaluationConfig": null,
        "progressPercentage": 456,
        "overallScore": 456,
        "passRate": 456,
        "averageExecutionTimeMs": 456,
        "totalExecutionTimeMs": 456,
        "chatbotConfig": "回應字串",
        "createdAt": "回應字串",
        "updatedAt": "回應字串",
        "insights": {
          "summary": "回應字串",
          "metricStats": null,
          "recommendations": null
        }
      }
    ]
}
```


取得評估結果

`GET` `/api/v1/evaluations/{id}`

status 為 pending、running、stopping、completed、partial_completed 或 failed；執行中看 progressPercentage，結束後看 passRate、overallScore 與各指標的 metricScores。沒有任何測試案例完成時結束為 failed。

參數

參數名稱	必填	類型	說明
id	V	string	評估 ID

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/evaluations/550e8400-
e29b-41d4-a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/evaluations/550e8400-e29b-41d4-a716-446655440000/", config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/evaluations/550e8400-e29b-
41d4-a716-446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/evaluations/550e8400-e29b-41d4-
a716-446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
{
  "id": string (uuid)
  "name": string
```

```
  "description": string
  "chatbot":
  {
    "id": string (uuid)
    "name": string
  }
  "dataset":
  {
    "id": string (uuid)
    "name": string
  }
  "organization":
  {
    "id": string (uuid)
    "name": string
  }
  "evaluationLlm":
  {
    "id": string (uuid)
    "name": string
  }
  "status":
  {
  }
  "startedAt": string (timestamp)
  "completedAt": string (timestamp)
  "totalTestCases": integer
  "completedTestCases": integer
  "passedTestCases": integer // Number of test cases that passed
  "metricScores": object // Detailed score per evaluation metric, such as
ground_truth, task_completion and tool_correctness
  "evaluationConfig": object
  "progressPercentage": number (double)
  "overallScore": number (double)
  "passRate": number (double)
  "averageExecutionTimeMs": integer
  "totalExecutionTimeMs": integer
  "chatbotConfig": string
  "createdAt": string (timestamp)
  "updatedAt": string (timestamp)
  "insights":
  {
    "summary": string
    "metricStats"?: object // 非必填
    "recommendations"?: object // 非必填
```

```
  }
}
```

回應範例值


```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "name": "回應字串",
  "description": "回應字串",
  "chatbot": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應字串"
  },
  "dataset": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應字串"
  },
  "organization": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應字串"
  },
  "evaluationLlm": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應字串"
  },
  "status": {},
  "startedAt": "回應字串",
  "completedAt": "回應字串",
  "totalTestCases": 456,
  "completedTestCases": 456,
  "passedTestCases": 456,
  "metricScores": null,
  "evaluationConfig": null,
  "progressPercentage": 456,
  "overallScore": 456,
  "passRate": 456,
  "averageExecutionTimeMs": 456,
  "totalExecutionTimeMs": 456,
  "chatbotConfig": "回應字串",
  "createdAt": "回應字串",
  "updatedAt": "回應字串",
  "insights": {
    "summary": "回應字串",
    "metricStats": null,
```

```
    "recommendations": null
  }
}
```

取得單輪評估的逐題結果

GET `/api/v1/evaluations/{id}/details/`

只適用單輪評估，多輪評估回 400。回應是所有測試案例結果的陣列，不分頁。

參數

參數名稱	必填	類型	說明
`id`	V	string	評估 ID

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/evaluations/550e8400-
e29b-41d4-a716-446655440000/details/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/evaluations/550e8400-e29b-
41d4-a716-446655440000/details/", config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/evaluations/550e8400-e29b-
41d4-a716-446655440000/details/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/evaluations/550e8400-e29b-41d4-
a716-446655440000/details/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
[
  {
    "id": string (uuid)
```

```
    "datasetEvaluation":
    {
      "id": string (uuid)
      "name": string
    }
    "testCase":
    {
      "id": string (uuid)
      "dataset":
      {
        "id": string (uuid)
        "name": string
      }
      "question": string
      "groundTruth"?: string // 非必填
      "status"?: string (enum: active, inactive, pending) // * `active` -
Active
* `inactive` - Inactive
* `pending` - Pending Review (非必填)
      "creationMethod"?: string (enum: manual, file, generate) // *
`manual` - Manual
* `file` - File import
* `generate` - Generated (非必填)
      "sourceFile"?: string // Name of the CSV, Excel or knowledge base
file this test case came from (非必填)
      "flaky"?: boolean // Flaky test cases still run and keep their
results, but are excluded from the pass rate. (非必填)
      "createdAt": string (timestamp)
      "updatedAt": string (timestamp)
    }
    "status":
    {
    }
    "chatbotResponse": string
    "context": [ // Enrich each context item with is_deleted status for
referenced knowledge base files.
      object
    ]
    "metricScores": object
    "executionTimeMs": integer
    "executionTimeSeconds": number (double)
    "passed": boolean
    "errorMessage": string // Error message recorded when the evaluation
fails
    "startedAt": string (timestamp)
```

```
    "completedAt": string (timestamp)
    "retryCount": integer // Number of times this test case has been
retried
    "lastAttemptAt": string (timestamp) // Time of the last evaluation
attempt
    "createdAt": string (timestamp)
    "updatedAt": string (timestamp)
  }
]
```

回應範例值

```
[
  {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "datasetEvaluation": {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "回應字串"
    },
    "testCase": {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "dataset": {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "name": "回應字串"
      },
      "question": "回應字串",
      "groundTruth": "回應字串",
      "status": "active",
      "creationMethod": "manual",
      "sourceFile": "回應字串",
      "flaky": false,
      "createdAt": "回應字串",
      "updatedAt": "回應字串"
    },
    "status": {},
    "chatbotResponse": "回應字串",
    "context": [
      {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "name": "回應範例名稱",
        "description": "回應範例描述"
      }
    ],
    "metricScores": null,
```

```
    "executionTimeMs": 456,
    "executionTimeSeconds": 456,
    "passed": false,
    "errorMessage": "回應字串",
    "startedAt": "回應字串",
    "completedAt": "回應字串",
    "retryCount": 456,
    "lastAttemptAt": "回應字串",
    "createdAt": "回應字串",
    "updatedAt": "回應字串"
  }
]
```


取得多輪評估的逐對話結果

`GET` `/api/v1/evaluations/{id}/multi-turn-results/`

只適用多輪評估，單輪評估回 400。回應分頁。

參數

參數名稱	必填	類型	說明
`id`	V	string	評估 ID
`page`	X	integer	頁碼，從 1 開始；超過最後一頁回 404
`pageSize`	X	integer	每頁筆數，預設 20、上限 100（超過以 100 計）

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/evaluations/550e8400-
e29b-41d4-a716-446655440000/multi-turn-results/?page=1&pageSize=1"

  -H "Authorization: Api-Key YOUR_API_KEY"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/evaluations/550e8400-e29b-
41d4-a716-446655440000/multi-turn-results/?page=1&pageSize=1",
config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/evaluations/550e8400-e29b-
41d4-a716-446655440000/multi-turn-results/?page=1&pageSize=1"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/evaluations/550e8400-e29b-41d4-
a716-446655440000/multi-turn-results/?page=1&pageSize=1", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
{
  "count": integer
  "next"?: string (uri) // 非必填
```

```
  "previous"?: string (uri) // 非必填
  "results": [
    {
      "id": string (uuid)
      "multiTurnTestCase": string (uuid)
      "scenario": string
      "expectedOutcome": string
      "flaky": boolean
      "status":
      {
      }
      "turns": object // The whole simulated conversation; each turn is
{role, content, retrieval_context}
      "metricScores": object
      "passed": boolean
      "errorMessage": string
      "startedAt": string (timestamp)
      "completedAt": string (timestamp)
      "createdAt": string (timestamp)
    }
  ]
}
```

回應範例值

```
{
  "count": 123,
  "next": "http://api.example.org/accounts/?page=4",
  "previous": "http://api.example.org/accounts/?page=2",
  "results": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "multiTurnTestCase": "550e8400-e29b-41d4-a716-446655440000",
      "scenario": "回應字串",
      "expectedOutcome": "回應字串",
      "flaky": false,
      "status": {},
      "turns": null,
      "metricScores": null,
      "passed": false,
      "errorMessage": "回應字串",
      "startedAt": "回應字串",
      "completedAt": "回應字串",
      "createdAt": "回應字串"
```

```
    }
  ]
}
```

取消執行中的評估

POST `/api/v1/evaluations/{id}/cancel/`

只能取消 status 為 running 的評估，否則回 400。取消後 status 先變成 stopping，停止後結束為 partial_completed，保留已算好的分數，已完成的測試案例照常扣 Credit；之後可以用 繼續未完成的評估 補跑。

參數

參數名稱	必填	類型	說明
`id`	V	string	評估 ID

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X POST "https://api.maiagent.ai/api/v1/evaluations/550e8400-
e29b-41d4-a716-446655440000/cancel/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

// 請求內容 (payload)
const data = null;

axios.post("https://api.maiagent.ai/api/v1/evaluations/550e8400-
e29b-41d4-a716-446655440000/cancel/", data, config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/evaluations/550e8400-e29b-
41d4-a716-446655440000/cancel/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.post(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>post("https://api.maiagent.ai/api/v1/evaluations/550e8400-e29b-
41d4-a716-446655440000/cancel/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
{
  "id": string (uuid)
  "name": string
```

```
  "description": string
  "chatbot":
  {
    "id": string (uuid)
    "name": string
  }
  "dataset":
  {
    "id": string (uuid)
    "name": string
  }
  "organization":
  {
    "id": string (uuid)
    "name": string
  }
  "evaluationLlm":
  {
    "id": string (uuid)
    "name": string
  }
  "status":
  {
  }
  "startedAt": string (timestamp)
  "completedAt": string (timestamp)
  "totalTestCases": integer
  "completedTestCases": integer
  "passedTestCases": integer // Number of test cases that passed
  "metricScores": object // Detailed score per evaluation metric, such as
ground_truth, task_completion and tool_correctness
  "evaluationConfig": object
  "progressPercentage": number (double)
  "overallScore": number (double)
  "passRate": number (double)
  "averageExecutionTimeMs": integer
  "totalExecutionTimeMs": integer
  "chatbotConfig": string
  "createdAt": string (timestamp)
  "updatedAt": string (timestamp)
  "insights":
  {
    "summary": string
    "metricStats"?: object // 非必填
    "recommendations"?: object // 非必填
```

```
  }
}
```

回應範例值


```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "name": "回應字串",
  "description": "回應字串",
  "chatbot": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應字串"
  },
  "dataset": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應字串"
  },
  "organization": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應字串"
  },
  "evaluationLlm": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應字串"
  },
  "status": {},
  "startedAt": "回應字串",
  "completedAt": "回應字串",
  "totalTestCases": 456,
  "completedTestCases": 456,
  "passedTestCases": 456,
  "metricScores": null,
  "evaluationConfig": null,
  "progressPercentage": 456,
  "overallScore": 456,
  "passRate": 456,
  "averageExecutionTimeMs": 456,
  "totalExecutionTimeMs": 456,
  "chatbotConfig": "回應字串",
  "createdAt": "回應字串",
  "updatedAt": "回應字串",
  "insights": {
    "summary": "回應字串",
    "metricStats": null,
```

```
    "recommendations": null
  }
}
```

繼續未完成的評估

POST `/api/v1/evaluations/{id}/resume/`

只能繼續 status 為 partial_completed 的評估，否則回 400。重跑失敗與尚未執行的測試案例並保留已完成的結果，回應 202；只對先前未計費的完成案例扣 Credit。

參數

參數名稱	必填	類型	說明
`id`	V	string	評估 ID

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X POST "https://api.maiagent.ai/api/v1/evaluations/550e8400-
e29b-41d4-a716-446655440000/resume/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

// 請求內容 (payload)
const data = null;

axios.post("https://api.maiagent.ai/api/v1/evaluations/550e8400-
e29b-41d4-a716-446655440000/resume/", data, config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/evaluations/550e8400-e29b-
41d4-a716-446655440000/resume/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.post(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>post("https://api.maiagent.ai/api/v1/evaluations/550e8400-e29b-
41d4-a716-446655440000/resume/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 202

回應結構範例

```
{
  "status": string (enum: accepted) // * `accepted` - 固定為 accepted，表示
已受理並排入背景執行
```

```
  "message": string // 受理說明
  "taskId": string // 背景任務 ID
}
```

回應範例值

```
{
  "status": "accepted",
  "message": "回應字串",
  "taskId": "回應字串"
}
```

匯出評估報表

POST `/api/v1/evaluations/{id}/export/`

只能匯出 status 為 completed 的單輪評估；多輪評估目前不支援匯出，回 400。報表在背景產生 Excel 檔，回應 201 與匯出紀錄，再用 查詢最新匯出狀態 取得下載網址。

參數

參數名稱	必填	類型	說明
`id`	V	string	評估 ID

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X POST "https://api.maiagent.ai/api/v1/evaluations/550e8400-
e29b-41d4-a716-446655440000/export/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

// 請求內容 (payload)
const data = null;

axios.post("https://api.maiagent.ai/api/v1/evaluations/550e8400-
e29b-41d4-a716-446655440000/export/", data, config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/evaluations/550e8400-e29b-
41d4-a716-446655440000/export/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.post(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>post("https://api.maiagent.ai/api/v1/evaluations/550e8400-e29b-
41d4-a716-446655440000/export/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 201

回應結構範例

```
{
  "id": string (uuid)
  "userEmail": string (email)
```

```
  "datasetEvaluationId": string (uuid)
  "datasetEvaluationName": string
  "status":
  {
  }
  "statusDisplay": string
  "fileUrl": string // 返回檔案 URL
  "fileSize": integer // File size in bytes
  "errorMessage": string
  "processingDurationSeconds": number (double) // 計算處理時長（秒）
  "createdAt": string (timestamp)
  "startedAt": string (timestamp)
  "completedAt": string (timestamp)
}
```

回應範例值

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "userEmail": "response@example.com",
  "datasetEvaluationId": "550e8400-e29b-41d4-a716-446655440000",
  "datasetEvaluationName": "回應字串",
  "status": {},
  "statusDisplay": "回應字串",
  "fileUrl": "回應字串",
  "fileSize": 456,
  "errorMessage": "回應字串",
  "processingDurationSeconds": 456,
  "createdAt": "回應字串",
  "startedAt": "回應字串",
  "completedAt": "回應字串"
}
```

查詢最新匯出狀態

GET `/api/v1/evaluations/{id}/export-status/`

回傳這筆評估最近一次的匯出紀錄：status 為 pending、processing、completed 或 failed，completed 時從 fileUrl 下載。這筆評估沒有匯出紀錄時回 404。

參數

參數名稱	必填	類型	說明
`id`	V	string	評估 ID

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/evaluations/550e8400-
e29b-41d4-a716-446655440000/export-status/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/evaluations/550e8400-e29b-41d4-a716-446655440000/export-status/", config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/evaluations/550e8400-e29b-
41d4-a716-446655440000/export-status/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/evaluations/550e8400-e29b-41d4-
a716-446655440000/export-status/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
{
  "id": string (uuid)
  "userEmail": string (email)
```

```
  "datasetEvaluationId": string (uuid)
  "datasetEvaluationName": string
  "status":
  {
  }
  "statusDisplay": string
  "fileUrl": string // 返回檔案 URL
  "fileSize": integer // File size in bytes
  "errorMessage": string
  "processingDurationSeconds": number (double) // 計算處理時長（秒）
  "createdAt": string (timestamp)
  "startedAt": string (timestamp)
  "completedAt": string (timestamp)
}
```

回應範例值

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "userEmail": "response@example.com",
  "datasetEvaluationId": "550e8400-e29b-41d4-a716-446655440000",
  "datasetEvaluationName": "回應字串",
  "status": {},
  "statusDisplay": "回應字串",
  "fileUrl": "回應字串",
  "fileSize": 456,
  "errorMessage": "回應字串",
  "processingDurationSeconds": 456,
  "createdAt": "回應字串",
  "startedAt": "回應字串",
  "completedAt": "回應字串"
}
```

列出匯出紀錄

GET `/api/v1/evaluations/{id}/exports/`

回應是這筆評估所有匯出紀錄的陣列，新到舊排序，不分頁。

參數

參數名稱	必填	類型	說明
id	V	string	評估 ID

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/evaluations/550e8400-
e29b-41d4-a716-446655440000/exports/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/evaluations/550e8400-e29b-
41d4-a716-446655440000/exports/", config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/evaluations/550e8400-e29b-
41d4-a716-446655440000/exports/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/evaluations/550e8400-e29b-41d4-
a716-446655440000/exports/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
[
  {
    "id": string (uuid)
```

```
    "userEmail": string (email)
    "datasetEvaluationId": string (uuid)
    "datasetEvaluationName": string
    "status":
    {
    }
    "statusDisplay": string
    "fileUrl": string // 返回檔案 URL
    "fileSize": integer // File size in bytes
    "processingDurationSeconds": number (double) // 計算處理時長（秒）
    "createdAt": string (timestamp)
    "startedAt": string (timestamp)
    "completedAt": string (timestamp)
  }
]
```

回應範例值

```
[
  {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "userEmail": "response@example.com",
    "datasetEvaluationId": "550e8400-e29b-41d4-a716-446655440000",
    "datasetEvaluationName": "回應字串",
    "status": {},
    "statusDisplay": "回應字串",
    "fileUrl": "回應字串",
    "fileSize": 456,
    "processingDurationSeconds": 456,
    "createdAt": "回應字串",
    "startedAt": "回應字串",
    "completedAt": "回應字串"
  }
]
```

編輯評估名稱與描述

PATCH `/api/v1/evaluations/{id}`

只接受 name 與 description，其他欄位會被忽略；任何狀態都可以編輯。

參數

參數名稱	必填	類型	說明
`id`	V	string	評估 ID

請求內容

請求參數

欄位	類型	必填	說明
name	string	否	
description	string	否	

請求結構範例

```
{
  "name"?: string // 非必填
  "description"?: string // 非必填
}
```

請求範例值

```
{
  "name": "範例名稱",
  "description": "範例字串"
}
```

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X PATCH "https://api.maiagent.ai/api/v1/evaluations/550e8400-
e29b-41d4-a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "name": "範例名稱",
    "description": "範例字串"
  }'

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// 請求內容 (payload)
const data = {
    "name": "範例名稱",
    "description": "範例字串"
  };

axios.patch("https://api.maiagent.ai/api/v1/evaluations/550e8400-
e29b-41d4-a716-446655440000/", data, config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/evaluations/550e8400-e29b-
41d4-a716-446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# 請求內容 (payload)
data = {
    "name": "範例名稱",
    "description": "範例字串"
}

response = requests.patch(url, json=data, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>patch("https://api.maiagent.ai/api/v1/evaluations/550e8400-e29b-
41d4-a716-446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'name' => '範例名稱',
            'description' => '範例字串'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
{
  "id": string (uuid)
  "name": string
  "description": string
  "chatbot":
  {
    "id": string (uuid)
    "name": string
  }
  "dataset":
  {
    "id": string (uuid)
    "name": string
  }
  "organization":
  {
    "id": string (uuid)
    "name": string
  }
  "evaluationLlm":
  {
    "id": string (uuid)
    "name": string
  }
  "status":
  {
  }
  "startedAt": string (timestamp)
  "completedAt": string (timestamp)
  "totalTestCases": integer
  "completedTestCases": integer
  "passedTestCases": integer // Number of test cases that passed
  "metricScores": object // Detailed score per evaluation metric, such as
ground_truth, task_completion and tool_correctness
  "evaluationConfig": object
  "progressPercentage": number (double)
  "overallScore": number (double)
  "passRate": number (double)
  "averageExecutionTimeMs": integer
  "totalExecutionTimeMs": integer
  "chatbotConfig": string
  "createdAt": string (timestamp)
  "updatedAt": string (timestamp)
  "insights":
```

```
  {
    "summary": string
    "metricStats"?: object // 非必填
    "recommendations"?: object // 非必填
  }
}
```

回應範例值


```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "name": "回應字串",
  "description": "回應字串",
  "chatbot": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應字串"
  },
  "dataset": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應字串"
  },
  "organization": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應字串"
  },
  "evaluationLlm": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應字串"
  },
  "status": {},
  "startedAt": "回應字串",
  "completedAt": "回應字串",
  "totalTestCases": 456,
  "completedTestCases": 456,
  "passedTestCases": 456,
  "metricScores": null,
  "evaluationConfig": null,
  "progressPercentage": 456,
  "overallScore": 456,
  "passRate": 456,
  "averageExecutionTimeMs": 456,
  "totalExecutionTimeMs": 456,
  "chatbotConfig": "回應字串",
  "createdAt": "回應字串",
```

```
  "updatedAt": "回應字串",
  "insights": {
    "summary": "回應字串",
    "metricStats": null,
    "recommendations": null
  }
}
```

刪除評估

DELETE `/api/v1/evaluations/{id}`

參數

參數名稱	必填	類型	說明
`id`	V	string	評估 ID

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X DELETE "https://api.maiagent.ai/api/v1/evaluations/550e8400-
e29b-41d4-a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

// 請求內容 (payload)
const data = null;

axios.delete("https://api.maiagent.ai/api/v1/evaluations/550e8400-
e29b-41d4-a716-446655440000/", data, config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/evaluations/550e8400-e29b-
41d4-a716-446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.delete(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>delete("https://api.maiagent.ai/api/v1/evaluations/550e8400-e29b-
41d4-a716-446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼	說明
204	No response body

呼叫 API 示例 (Shell)

目錄

1. 建立 SQL 資料庫連線
2. 列出 SQL 資料庫
3. 取得特定 SQL 資料庫
4. 更新 SQL 資料庫
5. 部分更新 SQL 資料庫
6. 刪除 SQL 資料庫
7. 測試資料庫連線
8. 上傳檔案至資料庫
9. 批量刪除 SQL 資料庫
10. 列出資料表
11. 建立資料表
12. 取得特定資料表
13. 更新資料表
14. 部分更新資料表
15. 刪除資料表
16. 批量刪除資料表
17. 列出資料欄位
18. 取得特定資料欄位
19. 更新資料欄位
20. 部分更新資料欄位
21. 測試資料庫連線（通用）
22. 列出資料庫連線字串範例
23. 取得特定連線字串範例
24. 列出 AI 助理的資料庫配置
25. 新增 AI 助理的資料庫配置
26. 取得特定資料庫配置
27. 更新資料庫配置
28. 部分更新資料庫配置
29. 刪除資料庫配置

呼叫 API 示例 (Shell)

建立 SQL 資料庫連線

`POST` `/api/v1/sql-databases/`

請求內容

請求參數

欄位	類型	必填	說明
name	string	是	Display name for this database connection
description	string	否	Description of the database and its purpose
databaseType	object	是	Type of database: PostgreSQL, MySQL, MSSQL, Oracle, SynxDB, or MaiAgent `postgresql` : PostgreSQL ; `mysql` : MySQL ; `maiagent` : MaiAgent ; `oracle` : Oracle ; `mssql` : MSSQL ; `synxdb` : SynxDB;
databaseUrl	string	否	Connection string for external databases. Not required for MaiAgent type as it uses the system default.
includeTables	object	否	Optional list of tables to include. Format: {"tables": ["table1", "table2"]}. For MaiAgent type, this is auto-populated from uploaded files.
isActive	boolean	否	When disabled, this database will not be used in Text-to-SQL queries
chatbots	array[IdName]	否	
groups	array[IdName]	否	

請求結構範例

```
{
  "name": string // Display name for this database connection
```

```
  "description"?: string // Description of the database and its purpose
(非必填)
  "databaseType":  // Type of database: PostgreSQL, MySQL, MSSQL, Oracle,
SynxDB, or MaiAgent

* `postgresql` - PostgreSQL
* `mysql` - MySQL
* `maiagent` - MaiAgent
* `oracle` - Oracle
* `mssql` - MSSQL
* `synxdb` - SynxDB
  {
  }
  "databaseUrl"?: string // Connection string for external databases. Not
required for MaiAgent type as it uses the system default. (非必填)
  "includeTables"?: object // Optional list of tables to include. Format:
{"tables": ["table1", "table2"]}. For MaiAgent type, this is auto-
populated from uploaded files. (非必填)
  "isActive"?: boolean // When disabled, this database will not be used
in Text-to-SQL queries (非必填)
  "chatbots"?: [ // 非必填
    {
      "id": string (uuid)
    }
  ]
  "groups"?: [ // 非必填
    {
      "id": string (uuid)
    }
  ]
}
```

請求範例值

```
{
  "name": "範例名稱",
  "description": "範例字串",
  "databaseType": {},
  "databaseUrl": "範例字串",
  "includeTables": null,
  "isActive": true,
  "chatbots": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000"
```

```
    }
  ],
  "groups": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000"
    }
  ]
}
```

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X POST "https://api.maiagent.ai/api/v1/sql-databases/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "name": "範例名稱",
    "description": "範例字串",
    "databaseType": {},
    "databaseUrl": "範例字串",
    "includeTables": null,
    "isActive": true,
    "chatbots": [
      {
        "id": "550e8400-e29b-41d4-a716-446655440000"
      }
    ],
    "groups": [
      {
        "id": "550e8400-e29b-41d4-a716-446655440000"
      }
    ]
  }'

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// 請求內容 (payload)
const data = {
    "name": "範例名稱",
    "description": "範例字串",
    "databaseType": {},
    "databaseUrl": "範例字串",
    "includeTables": null,
    "isActive": true,
    "chatbots": [
      {
        "id": "550e8400-e29b-41d4-a716-446655440000"
      }
    ],
    "groups": [
      {
        "id": "550e8400-e29b-41d4-a716-446655440000"
      }
    ]
  };

axios.post("https://api.maiagent.ai/api/v1/sql-databases/", data,
config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
```

```
  console.error(error.response?.data || error.message);
});
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/sql-databases/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# 請求內容 (payload)
data = {
    "name": "範例名稱",
    "description": "範例字串",
    "databaseType": {},
    "databaseUrl": "範例字串",
    "includeTables": None,
    "isActive": True,
    "chatbots": [
        {
            "id": "550e8400-e29b-41d4-a716-446655440000"
        }
    ],
    "groups": [
        {
            "id": "550e8400-e29b-41d4-a716-446655440000"
        }
    ]
}

response = requests.post(url, json=data, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->post("https://api.maiagent.ai/api/v1/sql-
databases/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'name' => '範例名稱',
            'description' => '範例字串',
            'databaseType' => new \stdClass(),
            'databaseUrl' => '範例字串',
            'includeTables' => null,
            'isActive' => true,
            'chatbots' => [
                [
                    'id' => '550e8400-e29b-41d4-a716-446655440000'
                ]
            ],
            'groups' => [
                [
                    'id' => '550e8400-e29b-41d4-a716-446655440000'
                ]
            ]
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 201

回應結構範例

```
{
  "id": string (uuid)
  "name": string // Display name for this database connection
  "description"?: string // Description of the database and its purpose
(非必填)
  "databaseType":  // Type of database: PostgreSQL, MySQL, MSSQL, Oracle,
SynxDB, or MaiAgent

* `postgresql` - PostgreSQL
* `mysql` - MySQL
* `maiagent` - MaiAgent
* `oracle` - Oracle
* `mssql` - MSSQL
* `synxdb` - SynxDB
  {
  }
  "databaseUrlMasked": string
  "includeTables"?: object // Optional list of tables to include. Format:
{"tables": ["table1", "table2"]}. For MaiAgent type, this is auto-
populated from uploaded files. (非必填)
  "isActive"?: boolean // When disabled, this database will not be used
in Text-to-SQL queries (非必填)
  "status":
  {
  }
  "deletedAt": string (timestamp)
  "tables": [
    {
      "id": string (uuid)
      "tableName": string // Name of the table in the database
      "sheetName": string // Name of the source worksheet/sheet this
```

```
table was created from. Empty for tables created before this field was
added.
      "description"?: string // Description of the table and its data for
better Text-to-SQL understanding (非必填)
      "status":
      {
      }
      "errorMessage": string // Error details if table creation or
deletion failed
      "sourceFile":
      {
        "id": string (uuid)
        "name": string
        "isFromKnowledgeBase": boolean // Determine if the source file
originated from a knowledge base upload.

Returns True if the file was uploaded via knowledge base,
False if uploaded directly to the database.
      }
      "columns": [
        {
          "id": string (uuid)
          "columnName": string
          "columnType"?: string // Data type of the column (e.g.,
VARCHAR, INTEGER, TIMESTAMP) (非必填)
          "description"?: string // Description of the column for better
Text-to-SQL understanding (非必填)
          "isPrimaryKey"?: boolean // 非必填
          "isNullable"?: boolean // 非必填
          "createdAt": string (timestamp)
          "updatedAt": string (timestamp)
        }
      ]
      "createdAt": string (timestamp)
      "updatedAt": string (timestamp)
    }
  ]
  "chatbots": [
    {
      "id": string (uuid)
      "name": string
    }
  ]
  "groups": [
    {
```

```
      "id": string (uuid)
      "name": string
    }
  ]
  "createdBy":
  {
    "id": string (uuid)
    "name": string
  }
  "canUpdate": boolean // Return whether the current user can update this
resource.
  "canDelete": boolean // Return whether the current user can delete this
resource.
  "createdAt": string (timestamp)
  "updatedAt": string (timestamp)
}
```

回應範例值

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "name": "回應字串",
  "description": "回應字串",
  "databaseType": {},
  "databaseUrlMasked": "回應字串",
  "includeTables": null,
  "isActive": false,
  "status": {},
  "deletedAt": "回應字串",
  "tables": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "tableName": "回應字串",
      "sheetName": "回應字串",
      "description": "回應字串",
      "status": {},
      "errorMessage": "回應字串",
      "sourceFile": {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "name": "回應字串",
        "isFromKnowledgeBase": false
      },
      "columns": [
        {
```

```
          "id": "550e8400-e29b-41d4-a716-446655440000",
          "columnName": "回應字串",
          "columnType": "回應字串",
          "description": "回應字串",
          "isPrimaryKey": false,
          "isNullable": false,
          "createdAt": "回應字串",
          "updatedAt": "回應字串"
        }
      ],
      "createdAt": "回應字串",
      "updatedAt": "回應字串"
    }
  ],
  "chatbots": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "回應字串"
    }
  ],
  "groups": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "回應字串"
    }
  ],
  "createdBy": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應字串"
  },
  "canUpdate": false,
  "canDelete": false,
  "createdAt": "回應字串",
  "updatedAt": "回應字串"
}
```


列出 SQL 資料庫

GET `/api/v1/sql-databases/`

參數

參數名稱	必填	類型	說明
`databaseType`	X	string	Type of database: PostgreSQL, MySQL, MSSQL, Oracle, SynxDB, or MaiAgent `postgresql`: PostgreSQL ; `mysql`: MySQL ; `maiagent`: MaiAgent ; `oracle`: Oracle ; `mssql`: MSSQL ; `synxdb`: SynxDB;
`isActive`	X	boolean	
`isExternal`	X	boolean	
`page`	X	integer	A page number within the paginated result set.
`pageSize`	X	integer	Number of results to return per page.
`pagination`	X	boolean	Set to false to return all databases without pagination (defaults to true).
`query`	X	string	

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/sql-databases/?
databaseType=maiagent&isActive=true&isExternal=true&page=1&pageSize=
1&pagination=true&query=example"

  -H "Authorization: Api-Key YOUR_API_KEY"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/sql-databases/?
databaseType=maiagent&isActive=true&isExternal=true&page=1&pageSize=
1&pagination=true&query=example", config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/sql-databases/?
databaseType=maiagent&isActive=true&isExternal=true&page=1&pageSize=
1&pagination=true&query=example"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->get("https://api.maiagent.ai/api/v1/sql-databases/?databaseType=maiagent&isActive=true&isExternal=true&page=1&pageSize=1&pagination=true&query=example", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
{
  "count": integer
```

```
  "next"?: string (uri) // 非必填
  "previous"?: string (uri) // 非必填
  "results": [
    {
      "id": string (uuid)
      "name": string // Display name for this database connection
      "description"?: string // Description of the database and its
purpose (非必填)
      "databaseType":  // Type of database: PostgreSQL, MySQL, MSSQL,
Oracle, SynxDB, or MaiAgent

* `postgresql` - PostgreSQL
* `mysql` - MySQL
* `maiagent` - MaiAgent
* `oracle` - Oracle
* `mssql` - MSSQL
* `synxdb` - SynxDB
      {
      }
      "databaseUrlMasked": string
      "includeTables"?: object // Optional list of tables to include.
Format: {"tables": ["table1", "table2"]}. For MaiAgent type, this is
auto-populated from uploaded files. (非必填)
      "isActive"?: boolean // When disabled, this database will not be
used in Text-to-SQL queries (非必填)
      "status":
      {
      }
      "deletedAt": string (timestamp)
      "tables": [
        {
          "id": string (uuid)
          "tableName": string // Name of the table in the database
        }
      ]
      "tablesCount": integer
      "chatbots": [
        {
          "id": string (uuid)
          "name": string
        }
      ]
      "groups": [
        {
          "id": string (uuid)
```

```
          "name": string
        }
      ]
      "createdBy":
      {
        "id": string (uuid)
        "name": string
      }
      "canUpdate": boolean // Return whether the current user can update
this resource.
      "canDelete": boolean // Return whether the current user can delete
this resource.
      "createdAt": string (timestamp)
      "updatedAt": string (timestamp)
    }
  ]
}
```

回應範例值

```
{
  "count": 123,
  "next": "http://api.example.org/accounts/?page=4",
  "previous": "http://api.example.org/accounts/?page=2",
  "results": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "回應字串",
      "description": "回應字串",
      "databaseType": {},
      "databaseUrlMasked": "回應字串",
      "includeTables": null,
      "isActive": false,
      "status": {},
      "deletedAt": "回應字串",
      "tables": [
        {
          "id": "550e8400-e29b-41d4-a716-446655440000",
          "tableName": "回應字串"
        }
      ],
      "tablesCount": 456,
      "chatbots": [
        {
```

```
            "id": "550e8400-e29b-41d4-a716-446655440000",
            "name": "回應字串"
          }
        ],
        "groups": [
          {
            "id": "550e8400-e29b-41d4-a716-446655440000",
            "name": "回應字串"
          }
        ],
        "createdBy": {
          "id": "550e8400-e29b-41d4-a716-446655440000",
          "name": "回應字串"
        },
        "canUpdate": false,
        "canDelete": false,
        "createdAt": "回應字串",
        "updatedAt": "回應字串"
      }
    ]
}
```


取得特定 SQL 資料庫

`GET` `/api/v1/sql-databases/{id}`

參數

參數名稱	必填	類型	說明
id	V	string	A UUID string identifying this SQL Database.

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/sql-databases/550e8400-
e29b-41d4-a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/sql-databases/550e8400-
e29b-41d4-a716-446655440000/", config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/sql-databases/550e8400-e29b-41d4-a716-446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->get("https://api.maiagent.ai/api/v1/sql-databases/550e8400-e29b-41d4-a716-446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
{
  "id": string (uuid)
  "name": string // Display name for this database connection
  "description"?: string // Description of the database and its purpose
```

```
(非必填)
  "databaseType":  // Type of database: PostgreSQL, MySQL, MSSQL, Oracle,
SynxDB, or MaiAgent

* `postgresql` - PostgreSQL
* `mysql` - MySQL
* `maiagent` - MaiAgent
* `oracle` - Oracle
* `mssql` - MSSQL
* `synxdb` - SynxDB
  {
  }
  "databaseUrlMasked": string
  "includeTables"?: object // Optional list of tables to include. Format:
{"tables": ["table1", "table2"]}. For MaiAgent type, this is auto-
populated from uploaded files. (非必填)
  "isActive"?: boolean // When disabled, this database will not be used
in Text-to-SQL queries (非必填)
  "status":
  {
  }
  "deletedAt": string (timestamp)
  "tables": [
    {
      "id": string (uuid)
      "tableName": string // Name of the table in the database
      "sheetName": string // Name of the source worksheet/sheet this
table was created from. Empty for tables created before this field was
added.
      "description"?: string // Description of the table and its data for
better Text-to-SQL understanding (非必填)
      "status":
      {
      }
      "errorMessage": string // Error details if table creation or
deletion failed
      "sourceFile":
      {
        "id": string (uuid)
        "name": string
        "isFromKnowledgeBase": boolean // Determine if the source file
originated from a knowledge base upload.

Returns True if the file was uploaded via knowledge base,
False if uploaded directly to the database.
```

```
      }
      "columns": [
        {
          "id": string (uuid)
          "columnName": string
          "columnType"?: string // Data type of the column (e.g.,
VARCHAR, INTEGER, TIMESTAMP) (非必填)
          "description"?: string // Description of the column for better
Text-to-SQL understanding (非必填)
          "isPrimaryKey"?: boolean // 非必填
          "isNullable"?: boolean // 非必填
          "createdAt": string (timestamp)
          "updatedAt": string (timestamp)
        }
      ]
      "createdAt": string (timestamp)
      "updatedAt": string (timestamp)
    }
  ]
  "chatbots": [
    {
      "id": string (uuid)
      "name": string
    }
  ]
  "groups": [
    {
      "id": string (uuid)
      "name": string
    }
  ]
  "createdBy":
  {
    "id": string (uuid)
    "name": string
  }
  "canUpdate": boolean // Return whether the current user can update this
resource.
  "canDelete": boolean // Return whether the current user can delete this
resource.
  "createdAt": string (timestamp)
  "updatedAt": string (timestamp)
}
```

回應範例值

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "name": "回應字串",
  "description": "回應字串",
  "databaseType": {},
  "databaseUrlMasked": "回應字串",
  "includeTables": null,
  "isActive": false,
  "status": {},
  "deletedAt": "回應字串",
  "tables": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "tableName": "回應字串",
      "sheetName": "回應字串",
      "description": "回應字串",
      "status": {},
      "errorMessage": "回應字串",
      "sourceFile": {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "name": "回應字串",
        "isFromKnowledgeBase": false
      },
      "columns": [
        {
          "id": "550e8400-e29b-41d4-a716-446655440000",
          "columnName": "回應字串",
          "columnType": "回應字串",
          "description": "回應字串",
          "isPrimaryKey": false,
          "isNullable": false,
          "createdAt": "回應字串",
          "updatedAt": "回應字串"
        }
      ],
      "createdAt": "回應字串",
      "updatedAt": "回應字串"
    }
  ],
  "chatbots": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "回應字串"
    }
```

```
  ],
  "groups": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "回應字串"
    }
  ],
  "createdBy": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應字串"
  },
  "canUpdate": false,
  "canDelete": false,
  "createdAt": "回應字串",
  "updatedAt": "回應字串"
}
```


更新 SQL 資料庫

PUT `/api/v1/sql-databases/{id}`

參數

參數名稱	必填	類型	說明
id	V	string	A UUID string identifying this SQL Database.

請求內容

請求參數

欄位	類型	必填	說明
name	string	是	Display name for this database connection
description	string	否	Description of the database and its purpose
databaseUrl	string	否	Connection string for external databases. Not required for MaiAgent type as it uses the system default.
includeTables	object	否	Optional list of tables to include. Format: {"tables": ["table1", "table2"]}. For MaiAgent type, this is auto-populated from uploaded files.
isActive	boolean	否	When disabled, this database will not be used in Text-to-SQL queries
chatbots	array[IdName]	否	
groups	array[IdName]	否	

請求結構範例

```
{
  "name": string // Display name for this database connection
  "description"?: string // Description of the database and its purpose (非必填)
  "databaseUrl"?: string // Connection string for external databases. Not required for MaiAgent type as it uses the system default. (非必填)
  "includeTables"?: object // Optional list of tables to include. Format: {"tables": ["table1", "table2"]}. For MaiAgent type, this is auto-populated from uploaded files. (非必填)
  "isActive"?: boolean // When disabled, this database will not be used in Text-to-SQL queries (非必填)
  "chatbots"?: [ // 非必填
    {
      "id": string (uuid)
    }
  ]
  "groups"?: [ // 非必填
    {
      "id": string (uuid)
    }
```

```
  ]
}
```

請求範例值

```
{
  "name": "範例名稱",
  "description": "範例字串",
  "databaseUrl": "範例字串",
  "includeTables": null,
  "isActive": true,
  "chatbots": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000"
    }
  ],
  "groups": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000"
    }
  ]
}
```

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X PUT "https://api.maiagent.ai/api/v1/sql-databases/550e8400-
e29b-41d4-a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "name": "範例名稱",
    "description": "範例字串",
    "databaseUrl": "範例字串",
    "includeTables": null,
    "isActive": true,
    "chatbots": [
      {
        "id": "550e8400-e29b-41d4-a716-446655440000"
      }
    ],
    "groups": [
      {
        "id": "550e8400-e29b-41d4-a716-446655440000"
      }
    ]
  }'

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// 請求內容 (payload)
const data = {
    "name": "範例名稱",
    "description": "範例字串",
    "databaseUrl": "範例字串",
    "includeTables": null,
    "isActive": true,
    "chatbots": [
      {
        "id": "550e8400-e29b-41d4-a716-446655440000"
      }
    ],
    "groups": [
      {
        "id": "550e8400-e29b-41d4-a716-446655440000"
      }
    ]
  };

axios.put("https://api.maiagent.ai/api/v1/sql-databases/550e8400-
e29b-41d4-a716-446655440000/", data, config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/sql-databases/550e8400-e29b-
41d4-a716-446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# 請求內容 (payload)
data = {
    "name": "範例名稱",
    "description": "範例字串",
    "databaseUrl": "範例字串",
    "includeTables": None,
    "isActive": True,
    "chatbots": [
        {
            "id": "550e8400-e29b-41d4-a716-446655440000"
        }
    ],
    "groups": [
        {
            "id": "550e8400-e29b-41d4-a716-446655440000"
        }
    ]
}

response = requests.put(url, json=data, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->put("https://api.maiagent.ai/api/v1/sql-databases/550e8400-e29b-41d4-a716-446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'name' => '範例名稱',
            'description' => '範例字串',
            'databaseUrl' => '範例字串',
            'includeTables' => null,
            'isActive' => true,
            'chatbots' => [
                [
                    'id' => '550e8400-e29b-41d4-a716-446655440000'
                ]
            ],
            'groups' => [
                [
                    'id' => '550e8400-e29b-41d4-a716-446655440000'
                ]
            ]
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
{
  "id": string (uuid)
  "name": string // Display name for this database connection
  "description"?: string // Description of the database and its purpose
(非必填)
  "databaseType":  // Type of database: PostgreSQL, MySQL, MSSQL, Oracle,
SynxDB, or MaiAgent

* `postgresql` - PostgreSQL
* `mysql` - MySQL
* `maiagent` - MaiAgent
* `oracle` - Oracle
* `mssql` - MSSQL
* `synxdb` - SynxDB
  {
  }
  "databaseUrlMasked": string
  "includeTables"?: object // Optional list of tables to include. Format:
{"tables": ["table1", "table2"]}. For MaiAgent type, this is auto-
populated from uploaded files. (非必填)
  "isActive"?: boolean // When disabled, this database will not be used
in Text-to-SQL queries (非必填)
  "status":
  {
  }
  "deletedAt": string (timestamp)
  "tables": [
    {
      "id": string (uuid)
      "tableName": string // Name of the table in the database
      "sheetName": string // Name of the source worksheet/sheet this
```

```
table was created from. Empty for tables created before this field was
added.
      "description"?: string // Description of the table and its data for
better Text-to-SQL understanding (非必填)
      "status":
      {
      }
      "errorMessage": string // Error details if table creation or
deletion failed
      "sourceFile":
      {
        "id": string (uuid)
        "name": string
        "isFromKnowledgeBase": boolean // Determine if the source file
originated from a knowledge base upload.

Returns True if the file was uploaded via knowledge base,
False if uploaded directly to the database.
      }
      "columns": [
        {
          "id": string (uuid)
          "columnName": string
          "columnType"?: string // Data type of the column (e.g.,
VARCHAR, INTEGER, TIMESTAMP) (非必填)
          "description"?: string // Description of the column for better
Text-to-SQL understanding (非必填)
          "isPrimaryKey"?: boolean // 非必填
          "isNullable"?: boolean // 非必填
          "createdAt": string (timestamp)
          "updatedAt": string (timestamp)
        }
      ]
      "createdAt": string (timestamp)
      "updatedAt": string (timestamp)
    }
  ]
  "chatbots": [
    {
      "id": string (uuid)
      "name": string
    }
  ]
  "groups": [
    {
```

```
      "id": string (uuid)
      "name": string
    }
  ]
  "createdBy":
  {
    "id": string (uuid)
    "name": string
  }
  "canUpdate": boolean // Return whether the current user can update this
resource.
  "canDelete": boolean // Return whether the current user can delete this
resource.
  "createdAt": string (timestamp)
  "updatedAt": string (timestamp)
}
```

回應範例值

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "name": "回應字串",
  "description": "回應字串",
  "databaseType": {},
  "databaseUrlMasked": "回應字串",
  "includeTables": null,
  "isActive": false,
  "status": {},
  "deletedAt": "回應字串",
  "tables": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "tableName": "回應字串",
      "sheetName": "回應字串",
      "description": "回應字串",
      "status": {},
      "errorMessage": "回應字串",
      "sourceFile": {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "name": "回應字串",
        "isFromKnowledgeBase": false
      },
      "columns": [
        {
```

```
          "id": "550e8400-e29b-41d4-a716-446655440000",
          "columnName": "回應字串",
          "columnType": "回應字串",
          "description": "回應字串",
          "isPrimaryKey": false,
          "isNullable": false,
          "createdAt": "回應字串",
          "updatedAt": "回應字串"
        }
      ],
      "createdAt": "回應字串",
      "updatedAt": "回應字串"
    }
  ],
  "chatbots": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "回應字串"
    }
  ],
  "groups": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "回應字串"
    }
  ],
  "createdBy": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應字串"
  },
  "canUpdate": false,
  "canDelete": false,
  "createdAt": "回應字串",
  "updatedAt": "回應字串"
}
```


部分更新 SQL 資料庫

PATCH `/api/v1/sql-databases/{id}`

參數

參數名稱	必填	類型	說明
`id`	V	string	A UUID string identifying this SQL Database.

請求內容

請求參數

欄位	類型	必填	說明
name	string	否	Display name for this database connection
description	string	否	Description of the database and its purpose
databaseUrl	string	否	Connection string for external databases. Not required for MaiAgent type as it uses the system default.
includeTables	object	否	Optional list of tables to include. Format: {"tables": ["table1", "table2"]}. For MaiAgent type, this is auto-populated from uploaded files.
isActive	boolean	否	When disabled, this database will not be used in Text-to-SQL queries
chatbots	array[IdName]	否	
groups	array[IdName]	否	

請求結構範例

```
{
  "name"?: string // Display name for this database connection (非必填)
  "description"?: string // Description of the database and its purpose
```

```
(非必填)
  "databaseUrl"?: string // Connection string for external databases. Not
required for MaiAgent type as it uses the system default. (非必填)
  "includeTables"?: object // Optional list of tables to include. Format:
{"tables": ["table1", "table2"]}. For MaiAgent type, this is auto-
populated from uploaded files. (非必填)
  "isActive"?: boolean // When disabled, this database will not be used
in Text-to-SQL queries (非必填)
  "chatbots"?: [ // 非必填
    {
      "id": string (uuid)
    }
  ]
  "groups"?: [ // 非必填
    {
      "id": string (uuid)
    }
  ]
}
```

請求範例值

```
{
  "name": "範例名稱",
  "description": "範例字串",
  "databaseUrl": "範例字串",
  "includeTables": null,
  "isActive": true,
  "chatbots": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000"
    }
  ],
  "groups": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000"
    }
  ]
}
```

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X PATCH "https://api.maiagent.ai/api/v1/sql-
databases/550e8400-e29b-41d4-a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "name": "範例名稱",
    "description": "範例字串",
    "databaseUrl": "範例字串",
    "includeTables": null,
    "isActive": true,
    "chatbots": [
      {
        "id": "550e8400-e29b-41d4-a716-446655440000"
      }
    ],
    "groups": [
      {
        "id": "550e8400-e29b-41d4-a716-446655440000"
      }
    ]
  }'

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// 請求內容 (payload)
const data = {
    "name": "範例名稱",
    "description": "範例字串",
    "databaseUrl": "範例字串",
    "includeTables": null,
    "isActive": true,
    "chatbots": [
      {
        "id": "550e8400-e29b-41d4-a716-446655440000"
      }
    ],
    "groups": [
      {
        "id": "550e8400-e29b-41d4-a716-446655440000"
      }
    ]
  };

axios.patch("https://api.maiagent.ai/api/v1/sql-databases/550e8400-
e29b-41d4-a716-446655440000/", data, config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/sql-databases/550e8400-e29b-
41d4-a716-446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# 請求內容 (payload)
data = {
    "name": "範例名稱",
    "description": "範例字串",
    "databaseUrl": "範例字串",
    "includeTables": None,
    "isActive": True,
    "chatbots": [
        {
            "id": "550e8400-e29b-41d4-a716-446655440000"
        }
    ],
    "groups": [
        {
            "id": "550e8400-e29b-41d4-a716-446655440000"
        }
    ]
}

response = requests.patch(url, json=data, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->patch("https://api.maiagent.ai/api/v1/sql-databases/550e8400-e29b-41d4-a716-446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'name' => '範例名稱',
            'description' => '範例字串',
            'databaseUrl' => '範例字串',
            'includeTables' => null,
            'isActive' => true,
            'chatbots' => [
                [
                    'id' => '550e8400-e29b-41d4-a716-446655440000'
                ]
            ],
            'groups' => [
                [
                    'id' => '550e8400-e29b-41d4-a716-446655440000'
                ]
            ]
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
{
  "id": string (uuid)
  "name": string // Display name for this database connection
  "description"?: string // Description of the database and its purpose
(非必填)
  "databaseType":  // Type of database: PostgreSQL, MySQL, MSSQL, Oracle,
SynxDB, or MaiAgent

* `postgresql` - PostgreSQL
* `mysql` - MySQL
* `maiagent` - MaiAgent
* `oracle` - Oracle
* `mssql` - MSSQL
* `synxdb` - SynxDB
  {
  }
  "databaseUrlMasked": string
  "includeTables"?: object // Optional list of tables to include. Format:
{"tables": ["table1", "table2"]}. For MaiAgent type, this is auto-
populated from uploaded files. (非必填)
  "isActive"?: boolean // When disabled, this database will not be used
in Text-to-SQL queries (非必填)
  "status":
  {
  }
  "deletedAt": string (timestamp)
  "tables": [
    {
      "id": string (uuid)
      "tableName": string // Name of the table in the database
      "sheetName": string // Name of the source worksheet/sheet this
```

```
table was created from. Empty for tables created before this field was
added.
      "description"?: string // Description of the table and its data for
better Text-to-SQL understanding (非必填)
      "status":
      {
      }
      "errorMessage": string // Error details if table creation or
deletion failed
      "sourceFile":
      {
        "id": string (uuid)
        "name": string
        "isFromKnowledgeBase": boolean // Determine if the source file
originated from a knowledge base upload.

Returns True if the file was uploaded via knowledge base,
False if uploaded directly to the database.
      }
      "columns": [
        {
          "id": string (uuid)
          "columnName": string
          "columnType"?: string // Data type of the column (e.g.,
VARCHAR, INTEGER, TIMESTAMP) (非必填)
          "description"?: string // Description of the column for better
Text-to-SQL understanding (非必填)
          "isPrimaryKey"?: boolean // 非必填
          "isNullable"?: boolean // 非必填
          "createdAt": string (timestamp)
          "updatedAt": string (timestamp)
        }
      ]
      "createdAt": string (timestamp)
      "updatedAt": string (timestamp)
    }
  ]
  "chatbots": [
    {
      "id": string (uuid)
      "name": string
    }
  ]
  "groups": [
    {
```

```
      "id": string (uuid)
      "name": string
    }
  ]
  "createdBy":
  {
    "id": string (uuid)
    "name": string
  }
  "canUpdate": boolean // Return whether the current user can update this
resource.
  "canDelete": boolean // Return whether the current user can delete this
resource.
  "createdAt": string (timestamp)
  "updatedAt": string (timestamp)
}
```

回應範例值

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "name": "回應字串",
  "description": "回應字串",
  "databaseType": {},
  "databaseUrlMasked": "回應字串",
  "includeTables": null,
  "isActive": false,
  "status": {},
  "deletedAt": "回應字串",
  "tables": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "tableName": "回應字串",
      "sheetName": "回應字串",
      "description": "回應字串",
      "status": {},
      "errorMessage": "回應字串",
      "sourceFile": {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "name": "回應字串",
        "isFromKnowledgeBase": false
      },
      "columns": [
        {
```

```
          "id": "550e8400-e29b-41d4-a716-446655440000",
          "columnName": "回應字串",
          "columnType": "回應字串",
          "description": "回應字串",
          "isPrimaryKey": false,
          "isNullable": false,
          "createdAt": "回應字串",
          "updatedAt": "回應字串"
        }
      ],
      "createdAt": "回應字串",
      "updatedAt": "回應字串"
    }
  ],
  "chatbots": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "回應字串"
    }
  ],
  "groups": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "回應字串"
    }
  ],
  "createdBy": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應字串"
  },
  "canUpdate": false,
  "canDelete": false,
  "createdAt": "回應字串",
  "updatedAt": "回應字串"
}
```


刪除 SQL 資料庫

DELETE `/api/v1/sql-databases/{id}`

參數

參數名稱	必填	類型	說明
`id`	V	string	A UUID string identifying this SQL Database.

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X DELETE "https://api.maiagent.ai/api/v1/sql-
databases/550e8400-e29b-41d4-a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

// 請求內容 (payload)
const data = null;

axios.delete("https://api.maiagent.ai/api/v1/sql-databases/550e8400-
e29b-41d4-a716-446655440000/", data, config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/sql-databases/550e8400-e29b-
41d4-a716-446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.delete(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->delete("https://api.maiagent.ai/api/v1/sql-databases/550e8400-e29b-41d4-a716-446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼	說明
204	No response body

測試資料庫連線

POST `/api/v1/sql-databases/{id}/test-connection/`

參數

參數名稱	必填	類型	說明
`id`	V	string	A UUID string identifying this SQL Database.

請求內容

請求參數

欄位	類型	必填	說明
databaseType	string (enum: postgresql, mysql, maiagent, oracle, mssql, synxdb)	是	`postgresql` : PostgreSQL ; `mysql` : MySQL ; `maiagent` : MaiAgent ; `oracle` : Oracle ; `mssql` : MSSQL ; `synxdb` : SynxDB;
databaseUrl	string	是	

請求結構範例

```
{
  "databaseType": string (enum: postgresql, mysql, maiagent, oracle,
mssql, synxdb) // * `postgresql` - PostgreSQL
* `mysql` - MySQL
* `maiagent` - MaiAgent
* `oracle` - Oracle
* `mssql` - MSSQL
* `synxdb` - SynxDB
  "databaseUrl": string
}
```

請求範例值

```
{
  "databaseType": "postgresql",
  "databaseUrl": "範例字串"
}
```

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X POST "https://api.maiagent.ai/api/v1/sql-databases/550e8400-
e29b-41d4-a716-446655440000/test-connection/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "databaseType": "postgresql",
    "databaseUrl": "範例字串"
  }'

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// 請求內容 (payload)
const data = {
    "databaseType": "postgresql",
    "databaseUrl": "範例字串"
  };

axios.post("https://api.maiagent.ai/api/v1/sql-databases/550e8400-
e29b-41d4-a716-446655440000/test-connection/", data, config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/sql-databases/550e8400-e29b-
41d4-a716-446655440000/test-connection/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# 請求內容 (payload)
data = {
    "databaseType": "postgresql",
    "databaseUrl": "範例字串"
}

response = requests.post(url, json=data, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->post("https://api.maiagent.ai/api/v1/sql-databases/550e8400-e29b-41d4-a716-446655440000/test-connection/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'databaseType' => 'postgresql',
            'databaseUrl' => '範例字串'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
{
  "success"?: boolean // 非必填
  "message"?: string // 非必填
}
```

回應範例值

```
{
  "success": false,
  "message": "回應字串"
}
```

上傳檔案至資料庫

POST `/api/v1/sql-databases/{id}/upload-files/`

參數

參數名稱	必填	類型	說明
id	V	string	A UUID string identifying this SQL Database.

請求內容

請求參數

欄位	類型	必填	說明
files	array[object]	是	

請求結構範例

```
{
  "files": [
    {
      "file": string // File path from presigned URL upload (e.g.,
media/chatbotfiles/xxx/file.csv)
      "filename": string // Original filename
      "size": integer // File size in bytes
    }
  ]
}
```

請求範例值

```
{
  "files": [
    {
      "file": "media/chatbotfiles/xxx/data.csv",
      "filename": "data.csv",
      "size": 1024
    },
    {
      "file": "media/chatbotfiles/xxx/report.xlsx",
      "filename": "report.xlsx",
      "size": 2048
    }
  ]
}
```

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X POST "https://api.maiagent.ai/api/v1/sql-databases/550e8400-
e29b-41d4-a716-446655440000/upload-files/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "files": [
      {
        "file": "media/chatbotfiles/xxx/data.csv",
        "filename": "data.csv",
        "size": 1024
      },
      {
        "file": "media/chatbotfiles/xxx/report.xlsx",
        "filename": "report.xlsx",
        "size": 2048
      }
    ]
  }'

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// 請求內容 (payload)
const data = {
    "files": [
      {
        "file": "media/chatbotfiles/xxx/data.csv",
        "filename": "data.csv",
        "size": 1024
      },
      {
        "file": "media/chatbotfiles/xxx/report.xlsx",
        "filename": "report.xlsx",
        "size": 2048
      }
    ]
  };

axios.post("https://api.maiagent.ai/api/v1/sql-databases/550e8400-
e29b-41d4-a716-446655440000/upload-files/", data, config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/sql-databases/550e8400-e29b-
41d4-a716-446655440000/upload-files/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# 請求內容 (payload)
data = {
    "files": [
        {
            "file": "media/chatbotfiles/xxx/data.csv",
            "filename": "data.csv",
            "size": 1024
        },
        {
            "file": "media/chatbotfiles/xxx/report.xlsx",
            "filename": "report.xlsx",
            "size": 2048
        }
    ]
}

response = requests.post(url, json=data, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->post("https://api.maiagent.ai/api/v1/sql-databases/550e8400-e29b-41d4-a716-446655440000/upload-files/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'files' => [
                [
                    'file' => 'media/chatbotfiles/xxx/data.csv',
                    'filename' => 'data.csv',
                    'size' => 1024
                ],
                [
                    'file' => 'media/chatbotfiles/xxx/report.xlsx',
                    'filename' => 'report.xlsx',
                    'size' => 2048
                ]
            ]
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 201

回應結構範例

```
{
  "message"?: string // 非必填
  "filesCount"?: integer // 非必填
  "fileIds"?: [ // 非必填
    string (uuid)
  ]
}
```

回應範例值

```
{
  "message": "回應字串",
  "filesCount": 456,
  "fileIds": [
    "550e8400-e29b-41d4-a716-446655440000"
  ]
}
```

批量刪除 SQL 資料庫

POST `/api/v1/sql-databases/batch-delete/`

請求內容

請求參數

欄位	類型	必填	說明
ids	array[string]	是	

請求結構範例

```
{
  "ids": [
    string (uuid)
  ]
}
```

請求範例值

```
{
  "ids": [
    "550e8400-e29b-41d4-a716-446655440000"
  ]
}
```

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X POST "https://api.maiagent.ai/api/v1/sql-databases/batch-
delete/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "ids": [
      "550e8400-e29b-41d4-a716-446655440000"
    ]
  }'

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// 請求內容 (payload)
const data = {
    "ids": [
      "550e8400-e29b-41d4-a716-446655440000"
    ]
  };

axios.post("https://api.maiagent.ai/api/v1/sql-databases/batch-
delete/", data, config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/sql-databases/batch-delete/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# 請求內容 (payload)
data = {
    "ids": [
        "550e8400-e29b-41d4-a716-446655440000"
    ]
}

response = requests.post(url, json=data, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->post("https://api.maiagent.ai/api/v1/sql-databases/batch-delete/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'ids' => [
                '550e8400-e29b-41d4-a716-446655440000'
            ]
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼	說明

204	No response body

列出資料表

GET `/api/v1/sql-databases/{sqlDatabasePk}/tables/`

參數

參數名稱	必填	類型	說明
`sqlDatabasePk`	V	string	
`page`	X	integer	A page number within the paginated result set.
`pageSize`	X	integer	Number of results to return per page.
`query`	X	string	
`status`	X	string	`pending`: Pending ; `processing`: Processing ; `success`: Success ; `failed`: Failed ; `dropping`: Dropping ; `drop_failed`: Drop Failed;

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/sql-
databases/{sqlDatabasePk}/tables/?
page=1&pageSize=1&query=example&status=drop_failed"

  -H "Authorization: Api-Key YOUR_API_KEY"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/sql-
databases/{sqlDatabasePk}/tables/?
page=1&pageSize=1&query=example&status=drop_failed", config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/sql-
databases/{sqlDatabasePk}/tables/?
page=1&pageSize=1&query=example&status=drop_failed"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->get("https://api.maiagent.ai/api/v1/sql-databases/{sqlDatabasePk}/tables/?page=1&pageSize=1&query=example&status=drop_failed", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
{
  "count": integer
  "next"?: string (uri) // 非必填
```

```
  "previous"?: string (uri) // 非必填
  "results": [
    {
      "id": string (uuid)
      "tableName": string // Name of the table in the database
      "sheetName": string // Name of the source worksheet/sheet this
table was created from. Empty for tables created before this field was
added.
      "description"?: string // Description of the table and its data for
better Text-to-SQL understanding (非必填)
      "status":
      {
      }
      "errorMessage": string // Error details if table creation or
deletion failed
      "sourceFile":
      {
        "id": string (uuid)
        "name": string
        "isFromKnowledgeBase": boolean // Determine if the source file
originated from a knowledge base upload.

Returns True if the file was uploaded via knowledge base,
False if uploaded directly to the database.
      }
      "columns": [
        {
          "id": string (uuid)
          "columnName": string
          "columnType"?: string // Data type of the column (e.g.,
VARCHAR, INTEGER, TIMESTAMP) (非必填)
          "description"?: string // Description of the column for better
Text-to-SQL understanding (非必填)
          "isPrimaryKey"?: boolean // 非必填
          "isNullable"?: boolean // 非必填
          "createdAt": string (timestamp)
          "updatedAt": string (timestamp)
        }
      ]
      "createdAt": string (timestamp)
      "updatedAt": string (timestamp)
    }
  ]
}
```

回應範例值


```
{
  "count": 123,
  "next": "http://api.example.org/accounts/?page=4",
  "previous": "http://api.example.org/accounts/?page=2",
  "results": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "tableName": "回應字串",
      "sheetName": "回應字串",
      "description": "回應字串",
      "status": {},
      "errorMessage": "回應字串",
      "sourceFile": {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "name": "回應字串",
        "isFromKnowledgeBase": false
      },
      "columns": [
        {
          "id": "550e8400-e29b-41d4-a716-446655440000",
          "columnName": "回應字串",
          "columnType": "回應字串",
          "description": "回應字串",
          "isPrimaryKey": false,
          "isNullable": false,
          "createdAt": "回應字串",
          "updatedAt": "回應字串"
        }
      ],
      "createdAt": "回應字串",
      "updatedAt": "回應字串"
    }
  ]
}
```


建立資料表

POST `/api/v1/sql-databases/{sqlDatabasePk}/tables/`

參數

參數名稱	必填	類型	說明
sqlDatabasePk	V	string	

請求內容

請求參數

欄位	類型	必填	說明
tableName	string	是	Name of the table in the database
description	string	否	Description of the table and its data for better Text-to-SQL understanding

請求結構範例

```
{
  "tableName": string // Name of the table in the database
  "description"?: string // Description of the table and its data for
better Text-to-SQL understanding (非必填)
}
```

請求範例值

```
{
  "tableName": "範例字串",
```

```
  "description": "範例字串"
}
```

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X POST "https://api.maiagent.ai/api/v1/sql-
databases/{sqlDatabasePk}/tables/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "tableName": "範例字串",
    "description": "範例字串"
  }'

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// 請求內容 (payload)
const data = {
    "tableName": "範例字串",
    "description": "範例字串"
  };

axios.post("https://api.maiagent.ai/api/v1/sql-
databases/{sqlDatabasePk}/tables/", data, config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/sql-
databases/{sqlDatabasePk}/tables/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# 請求內容 (payload)
data = {
    "tableName": "範例字串",
    "description": "範例字串"
}

response = requests.post(url, json=data, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->post("https://api.maiagent.ai/api/v1/sql-databases/{sqlDatabasePk}/tables/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'tableName' => '範例字串',
            'description' => '範例字串'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 201

回應結構範例

```
{
  "id": string (uuid)
  "tableName": string // Name of the table in the database
  "sheetName": string // Name of the source worksheet/sheet this table
was created from. Empty for tables created before this field was added.
  "description"?: string // Description of the table and its data for
better Text-to-SQL understanding (非必填)
  "status":
  {
  }
  "errorMessage": string // Error details if table creation or deletion
failed
  "sourceFile":
  {
    "id": string (uuid)
    "name": string
    "isFromKnowledgeBase": boolean // Determine if the source file
originated from a knowledge base upload.

Returns True if the file was uploaded via knowledge base,
False if uploaded directly to the database.
  }
  "columns": [
    {
      "id": string (uuid)
      "columnName": string
      "columnType"?: string // Data type of the column (e.g., VARCHAR,
INTEGER, TIMESTAMP) (非必填)
      "description"?: string // Description of the column for better
Text-to-SQL understanding (非必填)
      "isPrimaryKey"?: boolean // 非必填
      "isNullable"?: boolean // 非必填
      "createdAt": string (timestamp)
      "updatedAt": string (timestamp)
    }
  ]
  "createdAt": string (timestamp)
  "updatedAt": string (timestamp)
}
```

回應範例值

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "tableName": "回應字串",
  "sheetName": "回應字串",
  "description": "回應字串",
  "status": {},
  "errorMessage": "回應字串",
  "sourceFile": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應字串",
    "isFromKnowledgeBase": false
  },
  "columns": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "columnName": "回應字串",
      "columnType": "回應字串",
      "description": "回應字串",
      "isPrimaryKey": false,
      "isNullable": false,
      "createdAt": "回應字串",
      "updatedAt": "回應字串"
    }
  ],
  "createdAt": "回應字串",
  "updatedAt": "回應字串"
}
```


取得特定資料表

GET `/api/v1/sql-databases/{sqlDatabasePk}/tables/{id}`

參數

參數名稱	必填	類型	說明

`id`	V	string	A UUID string identifying this Database Table.
`sqlDatabasePk`	V	string	

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/sql-
databases/{sqlDatabasePk}/tables/550e8400-e29b-41d4-a716-
446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/sql-
databases/{sqlDatabasePk}/tables/550e8400-e29b-41d4-a716-
446655440000/", config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/sql-
databases/{sqlDatabasePk}/tables/550e8400-e29b-41d4-a716-
446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->get("https://api.maiagent.ai/api/v1/sql-databases/{sqlDatabasePk}/tables/550e8400-e29b-41d4-a716-446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
{
  "id": string (uuid)
  "tableName": string // Name of the table in the database
```

```
  "sheetName": string // Name of the source worksheet/sheet this table
was created from. Empty for tables created before this field was added.
  "description"?: string // Description of the table and its data for
better Text-to-SQL understanding (非必填)
  "status":
  {
  }
  "errorMessage": string // Error details if table creation or deletion
failed
  "sourceFile":
  {
    "id": string (uuid)
    "name": string
    "isFromKnowledgeBase": boolean // Determine if the source file
originated from a knowledge base upload.

Returns True if the file was uploaded via knowledge base,
False if uploaded directly to the database.
  }
  "columns": [
    {
      "id": string (uuid)
      "columnName": string
      "columnType"?: string // Data type of the column (e.g., VARCHAR,
INTEGER, TIMESTAMP) (非必填)
      "description"?: string // Description of the column for better
Text-to-SQL understanding (非必填)
      "isPrimaryKey"?: boolean // 非必填
      "isNullable"?: boolean // 非必填
      "createdAt": string (timestamp)
      "updatedAt": string (timestamp)
    }
  ]
  "createdAt": string (timestamp)
  "updatedAt": string (timestamp)
}
```

回應範例值

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "tableName": "回應字串",
  "sheetName": "回應字串",
  "description": "回應字串",
```

```
  "status": {},
  "errorMessage": "回應字串",
  "sourceFile": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應字串",
    "isFromKnowledgeBase": false
  },
  "columns": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "columnName": "回應字串",
      "columnType": "回應字串",
      "description": "回應字串",
      "isPrimaryKey": false,
      "isNullable": false,
      "createdAt": "回應字串",
      "updatedAt": "回應字串"
    }
  ],
  "createdAt": "回應字串",
  "updatedAt": "回應字串"
}
```


更新資料表

PUT `/api/v1/sql-databases/{sqlDatabasePk}/tables/{id}`

參數

參數名稱	必填	類型	說明
`id`	V	string	A UUID string identifying this Database Table.
`sqlDatabasePk`	V	string	

請求內容

請求參數

欄位	類型	必填	說明
tableName	string	是	Name of the table in the database
description	string	否	Description of the table and its data for better Text-to-SQL understanding

請求結構範例

```
{
  "tableName": string // Name of the table in the database
  "description"?: string // Description of the table and its data for
better Text-to-SQL understanding (非必填)
}
```

請求範例值

```
{
  "tableName": "範例字串",
  "description": "範例字串"
}
```

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X PUT "https://api.maiagent.ai/api/v1/sql-
databases/{sqlDatabasePk}/tables/550e8400-e29b-41d4-a716-
446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "tableName": "範例字串",
    "description": "範例字串"
  }'

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// 請求內容 (payload)
const data = {
    "tableName": "範例字串",
    "description": "範例字串"
  };

axios.put("https://api.maiagent.ai/api/v1/sql-
databases/{sqlDatabasePk}/tables/550e8400-e29b-41d4-a716-
446655440000/", data, config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/sql-
databases/{sqlDatabasePk}/tables/550e8400-e29b-41d4-a716-
446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# 請求內容 (payload)
data = {
    "tableName": "範例字串",
    "description": "範例字串"
}

response = requests.put(url, json=data, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->put("https://api.maiagent.ai/api/v1/sql-databases/{sqlDatabasePk}/tables/550e8400-e29b-41d4-a716-446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'tableName' => '範例字串',
            'description' => '範例字串'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
{
  "id": string (uuid)
  "tableName": string // Name of the table in the database
  "sheetName": string // Name of the source worksheet/sheet this table
was created from. Empty for tables created before this field was added.
  "description"?: string // Description of the table and its data for
better Text-to-SQL understanding (非必填)
  "status":
  {
  }
  "errorMessage": string // Error details if table creation or deletion
failed
  "sourceFile":
  {
    "id": string (uuid)
    "name": string
    "isFromKnowledgeBase": boolean // Determine if the source file
originated from a knowledge base upload.

Returns True if the file was uploaded via knowledge base,
False if uploaded directly to the database.
  }
  "columns": [
    {
      "id": string (uuid)
      "columnName": string
      "columnType"?: string // Data type of the column (e.g., VARCHAR,
INTEGER, TIMESTAMP) (非必填)
      "description"?: string // Description of the column for better
Text-to-SQL understanding (非必填)
      "isPrimaryKey"?: boolean // 非必填
      "isNullable"?: boolean // 非必填
      "createdAt": string (timestamp)
      "updatedAt": string (timestamp)
    }
  ]
  "createdAt": string (timestamp)
  "updatedAt": string (timestamp)
}
```

回應範例值

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "tableName": "回應字串",
  "sheetName": "回應字串",
  "description": "回應字串",
  "status": {},
  "errorMessage": "回應字串",
  "sourceFile": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應字串",
    "isFromKnowledgeBase": false
  },
  "columns": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "columnName": "回應字串",
      "columnType": "回應字串",
      "description": "回應字串",
      "isPrimaryKey": false,
      "isNullable": false,
      "createdAt": "回應字串",
      "updatedAt": "回應字串"
    }
  ],
  "createdAt": "回應字串",
  "updatedAt": "回應字串"
}
```


部分更新資料表

`PATCH` `/api/v1/sql-databases/{sqlDatabasePk}/tables/{id}`

參數

參數名稱	必填	類型	說明

`id`	V	string	A UUID string identifying this Database Table.
`sqlDatabasePk`	V	string	

請求內容

請求參數

欄位	類型	必填	說明
tableName	string	否	Name of the table in the database
description	string	否	Description of the table and its data for better Text-to-SQL understanding

請求結構範例

```
{
  "tableName"?: string // Name of the table in the database (非必填)
  "description"?: string // Description of the table and its data for
better Text-to-SQL understanding (非必填)
}
```

請求範例值

```
{
  "tableName": "範例字串",
  "description": "範例字串"
}
```

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X PATCH "https://api.maiagent.ai/api/v1/sql-
databases/{sqlDatabasePk}/tables/550e8400-e29b-41d4-a716-
446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "tableName": "範例字串",
    "description": "範例字串"
  }'

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// 請求內容 (payload)
const data = {
    "tableName": "範例字串",
    "description": "範例字串"
  };

axios.patch("https://api.maiagent.ai/api/v1/sql-
databases/{sqlDatabasePk}/tables/550e8400-e29b-41d4-a716-
446655440000/", data, config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/sql-
databases/{sqlDatabasePk}/tables/550e8400-e29b-41d4-a716-
446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# 請求內容 (payload)
data = {
    "tableName": "範例字串",
    "description": "範例字串"
}

response = requests.patch(url, json=data, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->patch("https://api.maiagent.ai/api/v1/sql-databases/{sqlDatabasePk}/tables/550e8400-e29b-41d4-a716-446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'tableName' => '範例字串',
            'description' => '範例字串'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
{
  "id": string (uuid)
  "tableName": string // Name of the table in the database
  "sheetName": string // Name of the source worksheet/sheet this table
was created from. Empty for tables created before this field was added.
  "description"?: string // Description of the table and its data for
better Text-to-SQL understanding (非必填)
  "status":
  {
  }
  "errorMessage": string // Error details if table creation or deletion
failed
  "sourceFile":
  {
    "id": string (uuid)
    "name": string
    "isFromKnowledgeBase": boolean // Determine if the source file
originated from a knowledge base upload.

Returns True if the file was uploaded via knowledge base,
False if uploaded directly to the database.
  }
  "columns": [
    {
      "id": string (uuid)
      "columnName": string
      "columnType"?: string // Data type of the column (e.g., VARCHAR,
INTEGER, TIMESTAMP) (非必填)
      "description"?: string // Description of the column for better
Text-to-SQL understanding (非必填)
      "isPrimaryKey"?: boolean // 非必填
      "isNullable"?: boolean // 非必填
      "createdAt": string (timestamp)
      "updatedAt": string (timestamp)
    }
  ]
  "createdAt": string (timestamp)
  "updatedAt": string (timestamp)
}
```

回應範例值

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "tableName": "回應字串",
  "sheetName": "回應字串",
  "description": "回應字串",
  "status": {},
  "errorMessage": "回應字串",
  "sourceFile": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "回應字串",
    "isFromKnowledgeBase": false
  },
  "columns": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "columnName": "回應字串",
      "columnType": "回應字串",
      "description": "回應字串",
      "isPrimaryKey": false,
      "isNullable": false,
      "createdAt": "回應字串",
      "updatedAt": "回應字串"
    }
  ],
  "createdAt": "回應字串",
  "updatedAt": "回應字串"
}
```


刪除資料表

`DELETE` `/api/v1/sql-databases/{sqlDatabasePk}/tables/{id}`

參數

參數名稱	必填	類型	說明

`id`	V	string	A UUID string identifying this Database Table.
`sqlDatabasePk`	V	string	

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X DELETE "https://api.maiagent.ai/api/v1/sql-
databases/{sqlDatabasePk}/tables/550e8400-e29b-41d4-a716-
446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

// 請求內容 (payload)
const data = null;

axios.delete("https://api.maiagent.ai/api/v1/sql-
databases/{sqlDatabasePk}/tables/550e8400-e29b-41d4-a716-
446655440000/", data, config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/sql-
databases/{sqlDatabasePk}/tables/550e8400-e29b-41d4-a716-
446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.delete(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->delete("https://api.maiagent.ai/api/v1/sql-databases/{sqlDatabasePk}/tables/550e8400-e29b-41d4-a716-446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼	說明
204	No response body

批量刪除資料表

`POST` `/api/v1/sql-databases/{sqlDatabasePk}/tables/batch-delete/`

參數

參數名稱	必填	類型	說明
sqlDatabasePk	V	string	

請求內容

請求參數

欄位	類型	必填	說明
ids	array[string]	是	

請求結構範例

```
{
  "ids": [
    string (uuid)
  ]
}
```

請求範例值

```
{
  "ids": [
    "550e8400-e29b-41d4-a716-446655440000"
```

```
  ]
}
```

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X POST "https://api.maiagent.ai/api/v1/sql-
databases/{sqlDatabasePk}/tables/batch-delete/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "ids": [
      "550e8400-e29b-41d4-a716-446655440000"
    ]
  }'

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// 請求內容 (payload)
const data = {
    "ids": [
      "550e8400-e29b-41d4-a716-446655440000"
    ]
  };

axios.post("https://api.maiagent.ai/api/v1/sql-
databases/{sqlDatabasePk}/tables/batch-delete/", data, config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/sql-
databases/{sqlDatabasePk}/tables/batch-delete/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# 請求內容 (payload)
data = {
    "ids": [
        "550e8400-e29b-41d4-a716-446655440000"
    ]
}

response = requests.post(url, json=data, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->post("https://api.maiagent.ai/api/v1/sql-databases/{sqlDatabasePk}/tables/batch-delete/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'ids' => [
                '550e8400-e29b-41d4-a716-446655440000'
            ]
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼	說明

204	No response body

列出資料欄位

GET `/api/v1/sql-databases/{sqlDatabasePk}/tables/{tablePk}/columns/`

參數

參數名稱	必填	類型	說明
`sqlDatabasePk`	V	string	
`tablePk`	V	string	

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/sql-
databases/{sqlDatabasePk}/tables/{tablePk}/columns/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/sql-
databases/{sqlDatabasePk}/tables/{tablePk}/columns/", config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/sql-
databases/{sqlDatabasePk}/tables/{tablePk}/columns/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->get("https://api.maiagent.ai/api/v1/sql-databases/{sqlDatabasePk}/tables/{tablePk}/columns/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
[
  {
    "id": string (uuid)
    "columnName": string
```

```
    "columnType"?: string // Data type of the column (e.g., VARCHAR,
INTEGER, TIMESTAMP) (非必填)
    "description"?: string // Description of the column for better Text-
to-SQL understanding (非必填)
    "isPrimaryKey"?: boolean // 非必填
    "isNullable"?: boolean // 非必填
    "createdAt": string (timestamp)
    "updatedAt": string (timestamp)
  }
]
```

回應範例值

```
[
  {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "columnName": "回應字串",
    "columnType": "回應字串",
    "description": "回應字串",
    "isPrimaryKey": false,
    "isNullable": false,
    "createdAt": "回應字串",
    "updatedAt": "回應字串"
  }
]
```

取得特定資料欄位

GET `/api/v1/sql-databases/{sqlDatabasePk}/tables/{tablePk}/columns/{id}`

參數

參數名稱	必填	類型	說明

`id`	V	string	A UUID string identifying this Database Table Column.
`sqlDatabasePk`	V	string	
`tablePk`	V	string	

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/sql-
databases/{sqlDatabasePk}/tables/{tablePk}/columns/550e8400-e29b-
41d4-a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/sql-
databases/{sqlDatabasePk}/tables/{tablePk}/columns/550e8400-e29b-
41d4-a716-446655440000/", config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/sql-databases/{sqlDatabasePk}/tables/{tablePk}/columns/550e8400-e29b-41d4-a716-446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->get("https://api.maiagent.ai/api/v1/sql-databases/{sqlDatabasePk}/tables/{tablePk}/columns/550e8400-e29b-41d4-a716-446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
{
  "id": string (uuid)
  "columnName": string
```

```
  "columnType"?: string // Data type of the column (e.g., VARCHAR,
INTEGER, TIMESTAMP) (非必填)
  "description"?: string // Description of the column for better Text-to-
SQL understanding (非必填)
  "isPrimaryKey"?: boolean // 非必填
  "isNullable"?: boolean // 非必填
  "createdAt": string (timestamp)
  "updatedAt": string (timestamp)
}
```

回應範例值

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "columnName": "回應字串",
  "columnType": "回應字串",
  "description": "回應字串",
  "isPrimaryKey": false,
  "isNullable": false,
  "createdAt": "回應字串",
  "updatedAt": "回應字串"
}
```

更新資料欄位

PUT `/api/v1/sql-databases/{sqlDatabasePk}/tables/{tablePk}/columns/{id}`

參數

參數名稱	必填	類型	說明
id	V	string	A UUID string identifying this Database Table Column.

`sqlDatabasePk`	V	string	
`tablePk`	V	string	

請求內容

請求參數

欄位	類型	必填	說明
columnName	string	是	
columnType	string	否	Data type of the column (e.g., VARCHAR, INTEGER, TIMESTAMP)
description	string	否	Description of the column for better Text-to-SQL understanding
isPrimaryKey	boolean	否	
isNullable	boolean	否	

請求結構範例

```
{
  "columnName": string
  "columnType"?: string // Data type of the column (e.g., VARCHAR, INTEGER, TIMESTAMP) (非必填)
  "description"?: string // Description of the column for better Text-to-SQL understanding (非必填)
  "isPrimaryKey"?: boolean // 非必填
  "isNullable"?: boolean // 非必填
}
```

請求範例值

```
{
  "columnName": "範例字串",
  "columnType": "範例字串",
```

```
  "description": "範例字串",
  "isPrimaryKey": true,
  "isNullable": true
}
```

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X PUT "https://api.maiagent.ai/api/v1/sql-
databases/{sqlDatabasePk}/tables/{tablePk}/columns/550e8400-e29b-
41d4-a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "columnName": "範例字串",
    "columnType": "範例字串",
    "description": "範例字串",
    "isPrimaryKey": true,
    "isNullable": true
  }'

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// 請求內容 (payload)
const data = {
    "columnName": "範例字串",
    "columnType": "範例字串",
    "description": "範例字串",
    "isPrimaryKey": true,
    "isNullable": true
  };

axios.put("https://api.maiagent.ai/api/v1/sql-
databases/{sqlDatabasePk}/tables/{tablePk}/columns/550e8400-e29b-
41d4-a716-446655440000/", data, config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/sql-
databases/{sqlDatabasePk}/tables/{tablePk}/columns/550e8400-e29b-
41d4-a716-446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# 請求內容 (payload)
data = {
    "columnName": "範例字串",
    "columnType": "範例字串",
    "description": "範例字串",
    "isPrimaryKey": True,
    "isNullable": True
}

response = requests.put(url, json=data, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->put("https://api.maiagent.ai/api/v1/sql-databases/{sqlDatabasePk}/tables/{tablePk}/columns/550e8400-e29b-41d4-a716-446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'columnName' => '範例字串',
            'columnType' => '範例字串',
            'description' => '範例字串',
            'isPrimaryKey' => true,
            'isNullable' => true
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
{
  "id": string (uuid)
  "columnName": string
  "columnType"?: string // Data type of the column (e.g., VARCHAR, INTEGER, TIMESTAMP) (非必填)
  "description"?: string // Description of the column for better Text-to-SQL understanding (非必填)
  "isPrimaryKey"?: boolean // 非必填
  "isNullable"?: boolean // 非必填
  "createdAt": string (timestamp)
  "updatedAt": string (timestamp)
}
```

回應範例值

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "columnName": "回應字串",
  "columnType": "回應字串",
  "description": "回應字串",
  "isPrimaryKey": false,
  "isNullable": false,
  "createdAt": "回應字串",
  "updatedAt": "回應字串"
}
```

部分更新資料欄位

PATCH `/api/v1/sql-databases/{sqlDatabasePk}/tables/{tablePk}/columns/{id}`

參數

參數名稱	必填	類型	說明
`id`	V	string	A UUID string identifying this Database Table Column.
`sqlDatabasePk`	V	string	
`tablePk`	V	string	

請求內容

請求參數

欄位	類型	必填	說明
columnName	string	否	
columnType	string	否	Data type of the column (e.g., VARCHAR, INTEGER, TIMESTAMP)
description	string	否	Description of the column for better Text-to-SQL understanding
isPrimaryKey	boolean	否	
isNullable	boolean	否	

請求結構範例

```
{
  "columnName"?: string // 非必填
  "columnType"?: string // Data type of the column (e.g., VARCHAR, INTEGER, TIMESTAMP) (非必填)
  "description"?: string // Description of the column for better Text-to-SQL understanding (非必填)
  "isPrimaryKey"?: boolean // 非必填
```

```
  "isNullable"?: boolean // 非必填
}
```

請求範例值

```
{
  "columnName": "範例字串",
  "columnType": "範例字串",
  "description": "範例字串",
  "isPrimaryKey": true,
  "isNullable": true
}
```

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X PATCH "https://api.maiagent.ai/api/v1/sql-
databases/{sqlDatabasePk}/tables/{tablePk}/columns/550e8400-e29b-
41d4-a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "columnName": "範例字串",
    "columnType": "範例字串",
    "description": "範例字串",
    "isPrimaryKey": true,
    "isNullable": true
  }'

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// 請求內容 (payload)
const data = {
    "columnName": "範例字串",
    "columnType": "範例字串",
    "description": "範例字串",
    "isPrimaryKey": true,
    "isNullable": true
  };

axios.patch("https://api.maiagent.ai/api/v1/sql-
databases/{sqlDatabasePk}/tables/{tablePk}/columns/550e8400-e29b-
41d4-a716-446655440000/", data, config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/sql-
databases/{sqlDatabasePk}/tables/{tablePk}/columns/550e8400-e29b-
41d4-a716-446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# 請求內容 (payload)
data = {
    "columnName": "範例字串",
    "columnType": "範例字串",
    "description": "範例字串",
    "isPrimaryKey": True,
    "isNullable": True
}

response = requests.patch(url, json=data, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->patch("https://api.maiagent.ai/api/v1/sql-databases/{sqlDatabasePk}/tables/{tablePk}/columns/550e8400-e29b-41d4-a716-446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'columnName' => '範例字串',
            'columnType' => '範例字串',
            'description' => '範例字串',
            'isPrimaryKey' => true,
            'isNullable' => true
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
{
  "id": string (uuid)
  "columnName": string
  "columnType"?: string // Data type of the column (e.g., VARCHAR, INTEGER, TIMESTAMP) (非必填)
  "description"?: string // Description of the column for better Text-to-SQL understanding (非必填)
  "isPrimaryKey"?: boolean // 非必填
  "isNullable"?: boolean // 非必填
  "createdAt": string (timestamp)
  "updatedAt": string (timestamp)
}
```

回應範例值

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "columnName": "回應字串",
  "columnType": "回應字串",
  "description": "回應字串",
  "isPrimaryKey": false,
  "isNullable": false,
  "createdAt": "回應字串",
  "updatedAt": "回應字串"
}
```

測試資料庫連線（通用）

POST `/api/v1/database-connection/test/`

請求內容

請求參數

欄位	類型	必填	說明
databaseType	object	是	資料庫類型（不包含 MaiAgent 內部使用類型） `postgresql` : PostgreSQL ; `mysql` : MySQL ; `oracle` : Oracle ; `mssql` : MSSQL ; `synxdb` : SynxDB;
databaseUrl	string	是	資料庫連線字串

請求結構範例

```
{
  "databaseType":  // 資料庫類型（不包含 MaiAgent 內部使用類型）

* `postgresql` - PostgreSQL
* `mysql` - MySQL
* `oracle` - Oracle
* `mssql` - MSSQL
* `synxdb` - SynxDB
  {
  }
  "databaseUrl": string // 資料庫連線字串
}
```

請求範例值

```
{
  "database_type": "postgresql",
  "database_url": "postgresql://user:password@localhost:5432/dbname"
}
```

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X POST "https://api.maiagent.ai/api/v1/database-
connection/test/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "database_type": "postgresql",
    "database_url":
"postgresql://user:password@localhost:5432/dbname"
  }'

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// 請求內容 (payload)
const data = {
    "database_type": "postgresql",
    "database_url":
"postgresql://user:password@localhost:5432/dbname"
  };

axios.post("https://api.maiagent.ai/api/v1/database-
connection/test/", data, config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/database-connection/test/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# 請求內容 (payload)
data = {
    "database_type": "postgresql",
    "database_url":
"postgresql://user:password@localhost:5432/dbname"
}

response = requests.post(url, json=data, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>post("https://api.maiagent.ai/api/v1/database-connection/test/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'database_type' => 'postgresql',
            'database_url' =>
'postgresql://user:password@localhost:5432/dbname'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
{
  "status":  // 連線狀態

* `success` - success
* `failed` - failed
  {
  }
  "responseTime"?: number (double) // 回應時間（秒） (非必填)
  "message"?: string // 成功訊息 (非必填)
  "errorMessage"?: string // 錯誤訊息 (非必填)
}
```

回應範例值

```
{
  "status": "success",
  "response_time": 0.123,
  "message": "成功連接到 PostgreSQL 資料庫"
}
```

狀態碼: 400

回應結構範例

```
{
  "detail"?: string // 非必填
}
```

回應範例值

```
{
  "status": "success",
  "response_time": 0.123,
  "message": "成功連接到 PostgreSQL 資料庫"
}
```

列出資料庫連線字串範例

GET `/api/v1/database-examples/`

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/database-examples/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/database-examples/",
config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/database-examples/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/database-examples/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
[
  {
    "databaseType"?:  // Database type option
```

```
* `postgresql` - PostgreSQL
* `mysql` - MySQL
* `maiagent` - MaiAgent
* `oracle` - Oracle
* `mssql` - MSSQL
* `synxdb` - SynxDB (非必填)
    {
    }
    "databaseTypeExample": string // For example:
postgresql://db_user:db_password@db_ip:db_port/db_name
  }
]
```

回應範例值

```
[
  {
    "databaseType": {},
    "databaseTypeExample": "回應字串"
  }
]
```

狀態碼: 401

回應結構範例

```
{
  "detail"?: string // 非必填
}
```

回應範例值

```
{
  "detail": "回應字串"
}
```

取得特定連線字串範例

GET `/api/v1/database-examples/{id}`

參數

參數名稱	必填	類型	說明
id	V	string	A UUID string identifying this Database Connection Example.

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/database-
examples/550e8400-e29b-41d4-a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/database-
examples/550e8400-e29b-41d4-a716-446655440000/", config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/database-examples/550e8400-
e29b-41d4-a716-446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/database-examples/550e8400-
e29b-41d4-a716-446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
{
  "databaseType"?:  // Database type option
```

```
* `postgresql` - PostgreSQL
* `mysql` - MySQL
* `maiagent` - MaiAgent
* `oracle` - Oracle
* `mssql` - MSSQL
* `synxdb` - SynxDB (非必填)
  {
  }
  "databaseTypeExample": string // For example:
postgresql://db_user:db_password@db_ip:db_port/db_name
}
```

回應範例值

```
{
  "databaseType": {},
  "databaseTypeExample": "回應字串"
}
```

列出 AI 助理的資料庫配置

GET `/api/v1/chatbots/{chatbotPk}/databases/`

參數

參數名稱	必填	類型	說明
`chatbotPk`	V	string	A UUID string identifying this Chatbot ID
`page`	X	integer	A page number within the paginated result set.
`pageSize`	X	integer	Number of results to return per page.

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X GET "

  -H "Authorization: Api-Key YOUR_API_KEY"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get(" config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->get(" [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
{
  "count": integer
  "next"?: string (uri) // 非必填
  "previous"?: string (uri) // 非必填
  "results": [
```

```
    {
      "id": string (uuid)
      "name": string // Display name, for example: Main Business DB,
Analytics DB.
      "databaseType":  // Database type: MySQL, PostgreSQL, MSSQL,
Oracle, SynxDB, or MaiAgent.

* `postgresql` - PostgreSQL
* `mysql` - MySQL
* `maiagent` - MaiAgent
* `oracle` - Oracle
* `mssql` - MSSQL
* `synxdb` - SynxDB
      {
      }
      "databaseUrl": string // Database connection string.
      "databaseUrlMasked": string
      "includeTables"?: object // Tables to query, formatted as
{"tables": ["table1", "table2"]}. The MaiAgent type reads them from
uploaded files automatically, so no manual setup is needed. (非必填)
      "isActive"?: boolean // When inactive, this database is not used
for Text-to-SQL queries. (非必填)
      "createdAt": string (timestamp)
      "updatedAt": string (timestamp)
    }
  ]
}
```

回應範例值

```
{
  "count": 123,
  "next": "http://api.example.org/accounts/?page=4",
  "previous": "http://api.example.org/accounts/?page=2",
  "results": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "回應字串",
      "databaseType": {},
      "databaseUrl": "回應字串",
      "databaseUrlMasked": "回應字串",
      "includeTables": null,
      "isActive": false,
      "createdAt": "回應字串",
```

```
        "updatedAt": "回應字串"
      }
    ]
}
```

新增 AI 助理的資料庫配置

POST `/api/v1/chatbots/{chatbotPk}/databases/`

參數

參數名稱	必填	類型	說明
`chatbotPk`	V	string	A UUID string identifying this Chatbot ID

請求內容

請求參數

欄位	類型	必填	說明
name	string	是	Display name, for example: Main Business DB, Analytics DB.
databaseType	object	是	Database type: MySQL, PostgreSQL, MSSQL, Oracle, SynxDB, or MaiAgent. `postgresql` : PostgreSQL ; `mysql` : MySQL ; `maiagent` : MaiAgent ; `oracle` : Oracle ; `mssql` : MSSQL ; `synxdb` : SynxDB;
databaseUrl	string	是	Database connection string.
includeTables	object	否	Tables to query, formatted as {"tables": ["table1", "table2"]}. The MaiAgent type reads them from

欄位	類型	必填	說明
			uploaded files automatically, so no manual setup is needed.
isActive	boolean	否	When inactive, this database is not used for Text-to-SQL queries.

請求結構範例

```
{
  "name": string // Display name, for example: Main Business DB, Analytics DB.
  "databaseType":  // Database type: MySQL, PostgreSQL, MSSQL, Oracle, SynxDB, or MaiAgent.

* `postgresql` - PostgreSQL
* `mysql` - MySQL
* `maiagent` - MaiAgent
* `oracle` - Oracle
* `mssql` - MSSQL
* `synxdb` - SynxDB
  {
  }
  "databaseUrl": string // Database connection string.
  "includeTables"?: object // Tables to query, formatted as {"tables": ["table1", "table2"]}. The MaiAgent type reads them from uploaded files automatically, so no manual setup is needed. (非必填)
  "isActive"?: boolean // When inactive, this database is not used for Text-to-SQL queries. (非必填)
}
```

請求範例值

```
{
  "name": "範例名稱",
  "databaseType": {},
  "databaseUrl": "範例字串",
  "includeTables": null,
```

```
  "isActive": true
}
```

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X POST "

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "name": "範例名稱",
    "databaseType": {},
    "databaseUrl": "範例字串",
    "includeTables": null,
    "isActive": true
  }'

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// 請求內容 (payload)
const data = {
    "name": "範例名稱",
    "databaseType": {},
    "databaseUrl": "範例字串",
    "includeTables": null,
    "isActive": true
  };

axios.post(" data, config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# 請求內容 (payload)
data = {
    "name": "範例名稱",
    "databaseType": {},
    "databaseUrl": "範例字串",
    "includeTables": None,
    "isActive": True
}

response = requests.post(url, json=data, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->post(" [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'name' => '範例名稱',
            'databaseType' => new \stdClass(),
            'databaseUrl' => '範例字串',
            'includeTables' => null,
            'isActive' => true
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 201

回應結構範例

```
{
  "id": string (uuid)
  "name": string // Display name, for example: Main Business DB,
Analytics DB.
  "databaseType":  // Database type: MySQL, PostgreSQL, MSSQL, Oracle,
SynxDB, or MaiAgent.

* `postgresql` - PostgreSQL
* `mysql` - MySQL
* `maiagent` - MaiAgent
* `oracle` - Oracle
* `mssql` - MSSQL
* `synxdb` - SynxDB
  {
  }
  "databaseUrl": string // Database connection string.
  "databaseUrlMasked": string
  "includeTables"?: object // Tables to query, formatted as {"tables":
["table1", "table2"]}. The MaiAgent type reads them from uploaded files
automatically, so no manual setup is needed. (非必填)
  "isActive"?: boolean // When inactive, this database is not used for
Text-to-SQL queries. (非必填)
  "createdAt": string (timestamp)
  "updatedAt": string (timestamp)
}
```

回應範例值

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "name": "回應字串",
  "databaseType": {},
  "databaseUrl": "回應字串",
  "databaseUrlMasked": "回應字串",
  "includeTables": null,
  "isActive": false,
  "createdAt": "回應字串",
  "updatedAt": "回應字串"
}
```

取得特定資料庫配置

`GET` `/api/v1/chatbots/{chatbotPk}/databases/{id}`

參數

參數名稱	必填	類型	說明
`chatbotPk`	V	string	A UUID string identifying this Chatbot ID
`id`	V	string	A UUID string identifying this Chatbot Database Configuration.

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X GET "

  -H "Authorization: Api-Key YOUR_API_KEY"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get(" config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->get(" [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
{
  "id": string (uuid)
  "name": string // Display name, for example: Main Business DB,
Analytics DB.
  "databaseType":  // Database type: MySQL, PostgreSQL, MSSQL, Oracle,
```

```
SynxDB, or MaiAgent.

* `postgresql` - PostgreSQL
* `mysql` - MySQL
* `maiagent` - MaiAgent
* `oracle` - Oracle
* `mssql` - MSSQL
* `synxdb` - SynxDB
  {
  }
  "databaseUrl": string // Database connection string.
  "databaseUrlMasked": string
  "includeTables"?: object // Tables to query, formatted as {"tables":
["table1", "table2"]}. The MaiAgent type reads them from uploaded files
automatically, so no manual setup is needed. (非必填)
  "isActive"?: boolean // When inactive, this database is not used for
Text-to-SQL queries. (非必填)
  "createdAt": string (timestamp)
  "updatedAt": string (timestamp)
}
```

回應範例值

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "name": "回應字串",
  "databaseType": {},
  "databaseUrl": "回應字串",
  "databaseUrlMasked": "回應字串",
  "includeTables": null,
  "isActive": false,
  "createdAt": "回應字串",
  "updatedAt": "回應字串"
}
```

更新資料庫配置

PUT `/api/v1/chatbots/{chatbotPk}/databases/{id}`

參數

參數名稱	必填	類型	說明
`chatbotPk`	V	string	A UUID string identifying this Chatbot ID
`id`	V	string	A UUID string identifying this Chatbot Database Configuration.

請求內容

請求參數

欄位	類型	必填	說明
name	string	是	Display name, for example: Main Business DB, Analytics DB.
databaseType	object	是	Database type: MySQL, PostgreSQL, MSSQL, Oracle, SynxDB, or MaiAgent. `postgresql` : PostgreSQL ; `mysql` : MySQL ; `maiagent` : MaiAgent ; `oracle` : Oracle ; `mssql` : MSSQL ; `synxdb` : SynxDB;
databaseUrl	string	是	Database connection string.
includeTables	object	否	Tables to query, formatted as {"tables": ["table1", "table2"]}. The MaiAgent type reads them from uploaded files automatically, so no manual setup is needed.
isActive	boolean	否	When inactive, this database is not used for Text-to-SQL queries.

請求結構範例

```
{
  "name": string // Display name, for example: Main Business DB,
Analytics DB.
  "databaseType":  // Database type: MySQL, PostgreSQL, MSSQL, Oracle,
SynxDB, or MaiAgent.

* `postgresql` - PostgreSQL
* `mysql` - MySQL
* `maiagent` - MaiAgent
* `oracle` - Oracle
* `mssql` - MSSQL
* `synxdb` - SynxDB
  {
  }
  "databaseUrl": string // Database connection string.
  "includeTables"?: object // Tables to query, formatted as {"tables":
["table1", "table2"]}. The MaiAgent type reads them from uploaded files
automatically, so no manual setup is needed. (非必填)
  "isActive"?: boolean // When inactive, this database is not used for
Text-to-SQL queries. (非必填)
}
```

請求範例值

```
{
  "name": "範例名稱",
  "databaseType": {},
  "databaseUrl": "範例字串",
  "includeTables": null,
  "isActive": true
}
```

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X PUT "

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "name": "範例名稱",
    "databaseType": {},
    "databaseUrl": "範例字串",
    "includeTables": null,
    "isActive": true
  }'

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// 請求內容 (payload)
const data = {
    "name": "範例名稱",
    "databaseType": {},
    "databaseUrl": "範例字串",
    "includeTables": null,
    "isActive": true
  };

axios.put(" data, config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# 請求內容 (payload)
data = {
    "name": "範例名稱",
    "databaseType": {},
    "databaseUrl": "範例字串",
    "includeTables": None,
    "isActive": True
}

response = requests.put(url, json=data, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->put(" [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'name' => '範例名稱',
            'databaseType' => new \stdClass(),
            'databaseUrl' => '範例字串',
            'includeTables' => null,
            'isActive' => true
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
{
  "id": string (uuid)
  "name": string // Display name, for example: Main Business DB,
Analytics DB.
  "databaseType":  // Database type: MySQL, PostgreSQL, MSSQL, Oracle,
SynxDB, or MaiAgent.

* `postgresql` - PostgreSQL
* `mysql` - MySQL
* `maiagent` - MaiAgent
* `oracle` - Oracle
* `mssql` - MSSQL
* `synxdb` - SynxDB
  {
  }
  "databaseUrl": string // Database connection string.
  "databaseUrlMasked": string
  "includeTables"?: object // Tables to query, formatted as {"tables":
["table1", "table2"]}. The MaiAgent type reads them from uploaded files
automatically, so no manual setup is needed. (非必填)
  "isActive"?: boolean // When inactive, this database is not used for
Text-to-SQL queries. (非必填)
  "createdAt": string (timestamp)
  "updatedAt": string (timestamp)
}
```

回應範例值

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "name": "回應字串",
  "databaseType": {},
  "databaseUrl": "回應字串",
  "databaseUrlMasked": "回應字串",
  "includeTables": null,
  "isActive": false,
  "createdAt": "回應字串",
  "updatedAt": "回應字串"
}
```

部分更新資料庫配置

`PATCH` `/api/v1/chatbots/{chatbotPk}/databases/{id}`

參數

參數名稱	必填	類型	說明
`chatbotPk`	V	string	A UUID string identifying this Chatbot ID
`id`	V	string	A UUID string identifying this Chatbot Database Configuration.

請求內容

請求參數

欄位	類型	必填	說明
name	string	否	Display name, for example: Main Business DB, Analytics DB.
databaseType	object	否	Database type: MySQL, PostgreSQL, MSSQL, Oracle, SynxDB, or MaiAgent. `postgresql` : PostgreSQL ; `mysql` : MySQL ; `maiagent` : MaiAgent ; `oracle` : Oracle ; `mssql` : MSSQL ; `synxdb` : SynxDB;
databaseUrl	string	否	Database connection string.
includeTables	object	否	Tables to query, formatted as {"tables": ["table1", "table2"]}. The MaiAgent type reads them from uploaded files automatically, so no manual setup is needed.

欄位	類型	必填	說明
isActive	boolean	否	When inactive, this database is not used for Text-to-SQL queries.

請求結構範例

```
{
  "name"?: string // Display name, for example: Main Business DB, Analytics DB. (非必填)
  "databaseType"?:  // Database type: MySQL, PostgreSQL, MSSQL, Oracle, SynxDB, or MaiAgent.

* `postgresql` - PostgreSQL
* `mysql` - MySQL
* `maiagent` - MaiAgent
* `oracle` - Oracle
* `mssql` - MSSQL
* `synxdb` - SynxDB (非必填)
  {
  }
  "databaseUrl"?: string // Database connection string. (非必填)
  "includeTables"?: object // Tables to query, formatted as {"tables": ["table1", "table2"]}. The MaiAgent type reads them from uploaded files automatically, so no manual setup is needed. (非必填)
  "isActive"?: boolean // When inactive, this database is not used for Text-to-SQL queries. (非必填)
}
```

請求範例值

```
{
  "name": "範例名稱",
  "databaseType": {},
  "databaseUrl": "範例字串",
  "includeTables": null,
  "isActive": true
}
```

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X PATCH "

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "name": "範例名稱",
    "databaseType": {},
    "databaseUrl": "範例字串",
    "includeTables": null,
    "isActive": true
  }'

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// 請求內容 (payload)
const data = {
    "name": "範例名稱",
    "databaseType": {},
    "databaseUrl": "範例字串",
    "includeTables": null,
    "isActive": true
  };

axios.patch(" data, config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# 請求內容 (payload)
data = {
    "name": "範例名稱",
    "databaseType": {},
    "databaseUrl": "範例字串",
    "includeTables": None,
    "isActive": True
}

response = requests.patch(url, json=data, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->patch(" [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'name' => '範例名稱',
            'databaseType' => new \stdClass(),
            'databaseUrl' => '範例字串',
            'includeTables' => null,
            'isActive' => true
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
{
  "id": string (uuid)
  "name": string // Display name, for example: Main Business DB,
Analytics DB.
  "databaseType":  // Database type: MySQL, PostgreSQL, MSSQL, Oracle,
SynxDB, or MaiAgent.

* `postgresql` - PostgreSQL
* `mysql` - MySQL
* `maiagent` - MaiAgent
* `oracle` - Oracle
* `mssql` - MSSQL
* `synxdb` - SynxDB
  {
  }
  "databaseUrl": string // Database connection string.
  "databaseUrlMasked": string
  "includeTables"?: object // Tables to query, formatted as {"tables":
["table1", "table2"]}. The MaiAgent type reads them from uploaded files
automatically, so no manual setup is needed. (非必填)
  "isActive"?: boolean // When inactive, this database is not used for
Text-to-SQL queries. (非必填)
  "createdAt": string (timestamp)
  "updatedAt": string (timestamp)
}
```

回應範例值

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "name": "回應字串",
  "databaseType": {},
  "databaseUrl": "回應字串",
  "databaseUrlMasked": "回應字串",
  "includeTables": null,
  "isActive": false,
  "createdAt": "回應字串",
  "updatedAt": "回應字串"
}
```

刪除資料庫配置

DELETE `/api/v1/chatbots/{chatbotPk}/databases/{id}`

參數

參數名稱	必填	類型	說明
`chatbotPk`	V	string	A UUID string identifying this Chatbot ID
`id`	V	string	A UUID string identifying this Chatbot Database Configuration.

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X DELETE "

  -H "Authorization: Api-Key YOUR_API_KEY"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

// 請求內容 (payload)
const data = null;

axios.delete(" data, config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.delete(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->delete(" [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼	說明
204	No response body

呼叫 API 示例 (Shell)

目錄

1. 建立新附件 (整合)
2. 取得檔案上傳用的預簽署 URL
3. Presigned 上傳附件
4. 取得特定附件
5. 建立對話附件
6. 取得允許的檔案規格
7. 列出對話附件
8. 刪除對話附件

呼叫 API 示例 (Shell)

建立新附件 (整合)

`POST` `/api/v1/attachments-upload/`

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X POST "https://api.maiagent.ai/api/v1/attachments-upload/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -F "file=@example_file.pdf"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');
const FormData = require('form-data');

// 建立FormData對象
const formData = new FormData();
// 請用實際檔案替換
formData.append('file',
* 實際檔案物件 *
, 'example_file.pdf');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    ...formData.getHeaders()
  }
};

axios.post("https://api.maiagent.ai/api/v1/attachments-upload/",
formData, config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/attachments-upload/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}

# 建立檔案和表單資料
files = {
    'file': ('example_file.pdf', open('example_file.pdf', 'rb'),
'application/pdf')
}

response = requests.post(url, files=files, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>post("https://api.maiagent.ai/api/v1/attachments-upload/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ],
        'multipart' => [
            [
                'name' => 'file',
                'contents' => fopen('example_file.pdf', 'r'),
                'filename' => 'example_file.pdf'
            ]
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 201

回應結構範例

```
{
  "id": string (uuid)
  "type"?:  // 非必填
  {
  }
  "filename": string
  "file": string (uri)
  "expiresAt": string // ISO datetime when this attachment will be auto-deleted.

For conversation-bound attachments: conversation.last_message_created_at + retention_days.
For attachments without a conversation: created_at + retention_days.
Returns None when cleanup is disabled (effective_from not set).
}
```

回應範例值

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "type": {},
  "filename": "回應字串",
  "file": "https://example.com/file.jpg",
  "expiresAt": "回應字串"
}
```

取得檔案上傳用的預簽署 URL

POST `/api/v1/upload-presigned-url/`

請求內容

請求參數

欄位	類型	必填	說明
modelName	string	是	模型名稱，例如 attachment、web-chat、faq、organization、chatbot-file、contact、meeting-record
fieldName	string	是	欄位名稱，例如 file、logo、avatar、powered-by-logo、answer、compact_logo、audio
filename	string	是	檔案名稱，例如 example.pdf
fileSize	integer	是	檔案大小（bytes）

請求結構範例

```
{
  "modelName": string // 模型名稱，例如 attachment、web-chat、faq、organization、chatbot-file、contact、meeting-record
  "fieldName": string // 欄位名稱，例如 file、logo、avatar、powered-by-logo、answer、compact_logo、audio
  "filename": string // 檔案名稱，例如 example.pdf
  "fileSize": integer // 檔案大小（bytes）
}
```

請求範例值

```
{
  "modelName": "attachment",
  "fieldName": "file",
  "filename": "example.pdf",
  "fileSize": 102400
}
```

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X POST "https://api.maiagent.ai/api/v1/upload-presigned-url/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "modelName": "attachment",
    "fieldName": "file",
    "filename": "example.pdf",
    "fileSize": 102400
  }'

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// 請求內容 (payload)
const data = {
    "modelName": "attachment",
    "fieldName": "file",
    "filename": "example.pdf",
    "fileSize": 102400
  };

axios.post("https://api.maiagent.ai/api/v1/upload-presigned-url/",
data, config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/upload-presigned-url/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# 請求內容 (payload)
data = {
    "modelName": "attachment",
    "fieldName": "file",
    "filename": "example.pdf",
    "fileSize": 102400
}

response = requests.post(url, json=data, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>post("https://api.maiagent.ai/api/v1/upload-presigned-url/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'modelName' => 'attachment',
            'fieldName' => 'file',
            'filename' => 'example.pdf',
            'fileSize' => 102400
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
{
  "url": string (uri) // 上傳目標 URL（S3／GCS 為 bucket URL；Azure 為帶 SAS 的 blob URL）
  "fields": object // POST 表單字段；Azure 只含 key
  "method"?:  // 缺席即 POST；Azure Blob 回 PUT

* `POST` - POST
* `PUT` - PUT (非必填)
  {
  }
  "headers"?: object // PUT 時必帶的請求標頭 (非必填)
}
```

回應範例值

```
{
  "url": "https://s3.example.com/bucket-name",
  "fields": {
    "key": "media/chat/attachment/filename.pdf",
    "x-amz-algorithm": "AWS4-HMAC-SHA256",
    "x-amz-credential":
"AKIAXXXXXXXXXXXXXXX/YYYYMMDD/region/s3/aws4_request",
    "x-amz-date": "YYYYMMDDTHHMMSSZ",
    "policy": "base64-encoded-policy-document",
    "x-amz-signature": "generated-signature-hash"
  }
}
```

Presigned 上傳附件

POST `/api/v1/attachments/`

請求內容

請求參數

欄位	類型	必填	說明
type	object	否	
filename	string	是	
file	string (uri)	是	

請求結構範例

```
{
  "type"?:  // 非必填
  {
  }
  "filename": string
  "file": string (uri)
}
```

請求範例值

```
{
  "type": {},
  "filename": "document.pdf",
  "file": "https://example.com/file.jpg"
}
```

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X POST "https://api.maiagent.ai/api/v1/attachments/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "type": {},
    "filename": "document.pdf",
    "file": "https://example.com/file.jpg"
  }'

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// 請求內容 (payload)
const data = {
    "type": {},
    "filename": "document.pdf",
    "file": "https://example.com/file.jpg"
  };

axios.post("https://api.maiagent.ai/api/v1/attachments/", data,
config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```python
import requests

url = "https://api.maiagent.ai/api/v1/attachments/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# 請求內容 (payload)
data = {
    "type": {},
    "filename": "document.pdf",
    "file": "https://example.com/file.jpg"
}

response = requests.post(url, json=data, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>post("https://api.maiagent.ai/api/v1/attachments/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'type' => new \stdClass(),
            'filename' => 'document.pdf',
            'file' => 'https://example.com/file.jpg'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 201

回應結構範例

```
{
  "id": string (uuid)
  "type"?:  // 非必填
  {
  }
  "filename": string
  "file": string (uri)
  "expiresAt": string // ISO datetime when this attachment will be auto-deleted.

For conversation-bound attachments: conversation.last_message_created_at + retention_days.
For attachments without a conversation: created_at + retention_days.
Returns None when cleanup is disabled (effective_from not set).
  "downloadStatus": string
}
```

回應範例值

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "type": {},
  "filename": "回應字串",
  "file": "https://example.com/file.jpg",
  "expiresAt": "回應字串",
  "downloadStatus": "回應字串"
}
```

取得特定附件

GET `/api/v1/attachments/{id}`

參數

參數名稱	必填	類型	說明
`id`	V	string	A UUID string identifying this attachment.

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/attachments/550e8400-
e29b-41d4-a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/attachments/550e8400-e29b-41d4-a716-446655440000/", config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/attachments/550e8400-e29b-
41d4-a716-446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/attachments/550e8400-e29b-41d4-
a716-446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
{
  "id": string (uuid)
  "type"?:  // 非必填
```

```
  {
  }
  "filename": string
  "file": string (uri)
  "expiresAt": string // ISO datetime when this attachment will be auto-
deleted.

For conversation-bound attachments: conversation.last_message_created_at
+ retention_days.
For attachments without a conversation: created_at + retention_days.
Returns None when cleanup is disabled (effective_from not set).
  "downloadStatus": string
}
```

回應範例值


```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "type": {},
  "filename": "回應字串",
  "file": "https://example.com/file.jpg",
  "expiresAt": "回應字串",
  "downloadStatus": "回應字串"
}
```


建立對話附件

POST `/api/v1/conversations/{conversationPk}/attachments/`

參數

參數名稱	必填	類型	說明

conversationPk	V	string	

請求內容

請求參數

欄位	類型	必填	說明
type	object	否	
filename	string	是	
file	string (uri)	是	
conversation	string (uuid)	否	

請求結構範例

```
{
  "type"?:  // 非必填
  {
  }
  "filename": string
  "file": string (uri)
  "conversation"?: string (uuid) // 非必填
}
```

請求範例值

```
{
  "type": {},
  "filename": "document.pdf",
  "file": "https://example.com/file.jpg",
  "conversation": "550e8400-e29b-41d4-a716-446655440000"
}
```

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X POST "https://api.maiagent.ai/api/v1/conversations/550e8400-
e29b-41d4-a716-446655440000/attachments/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "type": {},
    "filename": "document.pdf",
    "file": "https://example.com/file.jpg",
    "conversation": "550e8400-e29b-41d4-a716-446655440000"
  }'

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// 請求內容 (payload)
const data = {
    "type": {},
    "filename": "document.pdf",
    "file": "https://example.com/file.jpg",
    "conversation": "550e8400-e29b-41d4-a716-446655440000"
  };

axios.post("https://api.maiagent.ai/api/v1/conversations/550e8400-
e29b-41d4-a716-446655440000/attachments/", data, config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/conversations/550e8400-e29b-
41d4-a716-446655440000/attachments/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# 請求內容 (payload)
data = {
    "type": {},
    "filename": "document.pdf",
    "file": "https://example.com/file.jpg",
    "conversation": "550e8400-e29b-41d4-a716-446655440000"
}

response = requests.post(url, json=data, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>post("https://api.maiagent.ai/api/v1/conversations/550e8400-e29b-
41d4-a716-446655440000/attachments/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'type' => new \stdClass(),
            'filename' => 'document.pdf',
            'file' => 'https://example.com/file.jpg',
            'conversation' => '550e8400-e29b-41d4-a716-446655440000'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 201

回應結構範例

```
{
  "id": string (uuid)
  "type"?:  // 非必填
  {
  }
  "filename": string
  "file": string (uri)
  "expiresAt": string // ISO datetime when this attachment will be auto-deleted.

For conversation-bound attachments: conversation.last_message_created_at + retention_days.
For attachments without a conversation: created_at + retention_days.
Returns None when cleanup is disabled (effective_from not set).
  "conversation"?: string (uuid) // 非必填
}
```

回應範例值

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "type": {},
  "filename": "回應字串",
  "file": "https://example.com/file.jpg",
  "expiresAt": "回應字串",
  "conversation": "550e8400-e29b-41d4-a716-446655440000"
}
```

取得允許的檔案規格

GET `/api/v1/allowed-file-specs/`

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/allowed-file-specs/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/allowed-file-specs/",
config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/allowed-file-specs/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/allowed-file-specs/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
{
  "webChat": object
  "organization": object
  "attachment": object
```

```
  "chatbotFile": object
  "knowledgeBaseFile": object
  "batchQa": object
  "meetingRecord": object
}
```

回應範例值

```
{
  "web_chat": {
    "logo": [
      {
        "content_type": {
          ".jpg": "image/jpeg",
          ".jpeg": "image/jpeg",
          ".png": "image/png",
          ".gif": "image/gif"
        },
        "max_size": 5242880
      }
    ],
    "avatar": [
      {
        "content_type": {
          ".jpg": "image/jpeg",
          ".jpeg": "image/jpeg",
          ".png": "image/png",
          ".gif": "image/gif"
        },
        "max_size": 2097152
      }
    ],
    "cover": [
      {
        "content_type": {
          ".jpg": "image/jpeg",
          ".jpeg": "image/jpeg",
          ".png": "image/png",
          ".gif": "image/gif"
        },
        "max_size": 10485760
      }
    ],
    "powered-by-logo": [
```

```
      {
        "content_type": {
          ".jpg": "image/jpeg",
          ".jpeg": "image/jpeg",
          ".png": "image/png",
          ".gif": "image/gif"
        },
        "max_size": 5242880
      }
    ]
  },
  "organization": {
    "compact_logo": [
      {
        "content_type": {
          ".jpg": "image/jpeg",
          ".jpeg": "image/jpeg",
          ".png": "image/png",
          ".gif": "image/gif"
        },
        "max_size": 2097152
      }
    ],
    "full_logo": [
      {
        "content_type": {
          ".jpg": "image/jpeg",
          ".jpeg": "image/jpeg",
          ".png": "image/png",
          ".gif": "image/gif"
        },
        "max_size": 2097152
      }
    ]
  },
  "attachment": {
    "file": [
      {
        "content_type": {
          ".pdf": "application/pdf",
          ".doc": "application/msword",
          ".docx": "application/vnd.openxmlformats-
officedocument.wordprocessingml.document",
          ".txt": "text/plain"
        },
```

```
        "max_size": 20971520
      },
      {
        "content_type": {
          ".jpg": "image/jpeg",
          ".jpeg": "image/jpeg",
          ".png": "image/png",
          ".gif": "image/gif"
        },
        "max_size": 5242880
      }
    ]
  },
  "chatbot_file": {
    "file": [
      {
        "content_type": {
          ".pdf": "application/pdf",
          ".doc": "application/msword",
          ".docx": "application/vnd.openxmlformats-
officedocument.wordprocessingml.document",
          ".xlsx": "application/vnd.openxmlformats-
officedocument.spreadsheetml.sheet",
          ".ppt": "application/vnd.ms-powerpoint",
          ".pptx": "application/vnd.openxmlformats-
officedocument.presentationml.presentation",
          ".txt": "text/plain"
        },
        "max_size": 104857600
      }
    ]
  },
  "batch_qa": {
    "file": [
      {
        "content_type": null,
        "max_size": 104857600
      }
    ]
  },
  "faq": {
    "answer": [
      {
        "content_type": {
          ".jpg": "image/jpeg",
```

```
            ".jpeg": "image/jpeg",
            ".png": "image/png",
            ".gif": "image/gif",
            ".webp": "image/webp",
            ".tiff": "image/tiff",
            ".mp4": "video/mp4"
          },
          "max_size": 104857600
        }
      ]
    }
}
```

列出對話附件

GET `/api/v1/file-library/conversation-attachments/`

所需權限：組織已開通檔案庫，且呼叫者的角色具備任一檔案庫權限。可見範圍與 expiresAt 的計算方式見技術手冊對話附件管理 API。

參數

參數名稱	必填	類型	說明
`page`	X	integer	A page number within the paginated result set.
`pageSize`	X	integer	Number of results to return per page.

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/file-
library/conversation-attachments/?page=1&pageSize=1"

  -H "Authorization: Api-Key YOUR_API_KEY"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/file-library/conversation-
attachments/?page=1&pageSize=1", config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/file-library/conversation-
attachments/?page=1&pageSize=1"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->get("https://api.maiagent.ai/api/v1/file-library/conversation-attachments/?page=1&pageSize=1", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼: 200

回應結構範例

```
{
  "count": integer
  "next"?: string (uri) // 非必填
  "previous"?: string (uri) // 非必填
```

```
  "results": [
    {
      "id": string (uuid)
      "filename": string
      "fileSize": integer
      "type":
      {
      }
      "conversationId": string (uuid)
      "expiresAt": string
      "createdAt": string (timestamp)
    }
  ]
}
```

回應範例值

```
{
  "count": 123,
  "next": "http://api.example.org/accounts/?page=4",
  "previous": "http://api.example.org/accounts/?page=2",
  "results": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "filename": "回應字串",
      "fileSize": 456,
      "type": {},
      "conversationId": "550e8400-e29b-41d4-a716-446655440000",
      "expiresAt": "回應字串",
      "createdAt": "回應字串"
    }
  ]
}
```

刪除對話附件

DELETE `/api/v1/file-library/conversation-attachments/{id}`

所需權限：同「列出對話附件」；只能刪除呼叫者看得到的附件，其他附件回 404。刪除會一併移除沒有其他附件或檔案共用的儲存檔案。

參數

參數名稱	必填	類型	說明
`id`	V	string	

程式碼範例

Shell/Bash

```
# 呼叫 API 示例 (Shell)
curl -X DELETE "https://api.maiagent.ai/api/v1/file-
library/conversation-attachments/550e8400-e29b-41d4-a716-
446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# 請確認在執行前替換 YOUR_API_KEY 並核對請求資料。
```

JavaScript

```
const axios = require('axios');

// 設定請求標頭
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

// 請求內容 (payload)
const data = null;

axios.delete("https://api.maiagent.ai/api/v1/file-
library/conversation-attachments/550e8400-e29b-41d4-a716-
446655440000/", data, config)
  .then(response => {
    console.log('成功取得回應:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('請求發生錯誤:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/file-library/conversation-
attachments/550e8400-e29b-41d4-a716-446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.delete(url, headers=headers)
try:
    print("成功取得回應:")
    print(response.json())
except Exception as e:
    print("請求發生錯誤:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>delete("https://api.maiagent.ai/api/v1/file-library/conversation-
attachments/550e8400-e29b-41d4-a716-446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "成功取得回應:\n";
    print_r($data);
} catch (Exception $e) {
    echo '請求發生錯誤: ' . $e->getMessage();
}
?>
```

回應內容

狀態碼	說明
204	No response body