API docs

目錄

1. List available models
2. Chat completions (supports streaming and tool calls)
3. Generate text embeddings

AI Gateway provides OpenAI-compatible endpoints, allowing existing OpenAI SDKs or tools to call models through MaiAgent by changing only the URL and API key. These endpoints are available only under `/api/v1/`, and their paths do not end with `/`. Authentication uses `Authorization: Bearer` (the key is your MaiAgent API Key, but Gateway endpoints accept only the `Bearer` prefix; using the `Api-Key` prefix returns `401`). MaiAgent must enable AI Gateway for your organization. Administrators configure which models each key can call in API Key management. For full details, see the technical manual: AI Gateway: OpenAI-compatible API integration.

List available models

GET `/api/v1/models`

Returns the model IDs and pricing available to this key. For the ID rules, see Model IDs in the technical manual.

Code Examples

Shell/Bash

```
# Example API call (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/models"

  -H "Authorization: Bearer YOUR_API_KEY"

# Make sure to replace YOUR_API_KEY and verify the request data
before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Bearer YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/models", config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request failed:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/models"
headers = {
    "Authorization": "Bearer YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request failed:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/models", [
        'headers' => [
            'Authorization' => 'Bearer YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request failed: ' . $e->getMessage();
}
?>
```

Response

Status code: 200

Response Schema Example

```
{
  "object"?: string (enum: list) // optional
  "data"?: [ // optional
    {
```

```
      "id"?: string // ID to use as the model when calling (optional)
      "object"?: string (enum: model) // optional
      "created"?: integer // Unix seconds (optional)
      "owned_by"?: string // optional
      "name"?: string // optional
      "icon"?: string // optional
      "type"?: string (enum: language) // optional
      "tags"?: [ // optional
        string (enum: tool-use, multimodal, reasoning, prompt-caching,
streaming)
      ]
      "pricing"?: { // Platform models use
input/output/unit=credits_per_1k_tokens/currency; organization-owned
models use traffic_fee_percent/unit=percent_of_total_tokens/currency
(optional)
      {
        "input"?: string // optional
        "output"?: string // optional
        "traffic_fee_percent"?: string // optional
        "unit"?: string // optional
        "currency"?: string // optional
      }
      }
      "providers"?: [ // optional
        {
          "slug"?: string // optional
          "name"?: string // optional
          "icon_url"?: string // optional
          "color"?: string // optional
        }
      ]
      "context_window"?: integer // Only present when set on the model
(optional)
      "max_tokens"?: integer // Only present when set on the model
(optional)
    }
  ]
}
```

Response Example

```
{
  "object": "list",
  "data": [
```

```
    {
      "id": "response string",
      "object": "model",
      "created": 456,
      "owned_by": "response string",
      "name": "response string",
      "icon": "response string",
      "type": "language",
      "tags": [
        "tool-use"
      ],
      "pricing": {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "name": "Response example name",
        "description": "Response example description"
      },
      "providers": [
        {
          "slug": "response string",
          "name": "response string",
          "icon_url": "response string",
          "color": "response string"
        }
      ],
      "context_window": 456,
      "max_tokens": 456
    }
  ]
}
```


Chat completions (supports streaming and tool calls)

POST `/api/v1/chat/completions`

The request and response formats are the same as OpenAI chat/completions (model, messages, stream, tools, etc.); fields not listed in the platform schema also follow OpenAI. For parameters and examples, see Chat completions parameters and Minimal examples in the technical manual.

Request

Request Parameters

Field	Type	Required	Description
model	string	Yes	Model ID, taken from GET /v1/models
messages	array[object]	Yes	
stream	boolean	No	Returns text/event-stream when true
stream_options	object	No	
stream_options.include_usage	boolean	No	
temperature	number	No	
max_tokens	integer	No	
top_p	number	No	
stop	object	No	
n	integer	No	
provider	object	No	
provider.order	array[string]	No	Specifies the backend provider; currently only the first one is used
tools	array[object]	No	
tool_choice	object	No	
parallel_tool_calls	boolean	No	
response_format	object	No	type is text, json_object, or json_schema; a json_schema object is required for json_schema

Field	Type	Required	Description
reasoning_effort	string (enum: none, minimal, low, medium, high, xhigh, max)	No	

Request Schema Example

```
{
  "model": string // Model ID, taken from GET /v1/models
  "messages": [
    {
      "role": string (enum: system, user, assistant, tool)
      "content": object // Text, or an array of OpenAI multimodal content
parts
      "tool_calls"?: [ // optional
        {
          "id"?: string // optional
          "type"?: string (enum: function) // optional
          "function"?: { // optional
          {
            "name"?: string // optional
            "arguments"?: string // JSON string (optional)
          }
          }
        }
      ]
      "tool_call_id"?: string // optional
      "name"?: string // optional
    }
  ]
  "stream"?: boolean // Returns text/event-stream when true (optional)
  "stream_options"?: { // optional
  {
    "include_usage"?: boolean // optional
  }
  }
  "temperature"?: number // optional
  "max_tokens"?: integer // optional
  "top_p"?: number // optional
  "stop"?: // May be one of several types (optional)
  string // optional
  "n"?: integer // optional
```

```
  "provider"?: { // optional
  {
    "order"?: [ // Specifies the backend provider; currently only the
first one is used (optional)
      string
    ]
  }
  }
  "tools"?: [ // optional
    {
      "type": string (enum: function)
      "function": {
      {
        "name": string
        "description"?: string // optional
        "parameters"?: object // JSON Schema (optional)
        "strict"?: boolean // optional
      }
      }
    }
  ]
  "tool_choice"?: // May be one of several types (optional)
  string (enum: auto, none, required) // optional
  "parallel_tool_calls"?: boolean // optional
  "response_format"?: object // type is text, json_object, or
json_schema; a json_schema object is required for json_schema (optional)
  "reasoning_effort"?: string (enum: none, minimal, low, medium, high,
xhigh, max) // optional
}
```

Request Example

```
{
  "model": "openai/gpt-5.4-mini",
  "messages": [
    {
      "role": "user",
      "content": "Hello, please introduce yourself in one sentence."
    }
  ]
}
```

Code Examples

Shell/Bash

```
# Example API call (Shell)
curl -X POST "https://api.maiagent.ai/api/v1/chat/completions"

  -H "Authorization: Bearer YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "model": "openai/gpt-5.4-mini",
    "messages": [
      {
        "role": "user",
        "content": "Hello, please introduce yourself in one
sentence."
      }
    ]
  }'

# Make sure to replace YOUR_API_KEY and verify the request data
before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Bearer YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// Request payload
const data = {
    "model": "openai/gpt-5.4-mini",
    "messages": [
      {
        "role": "user",
        "content": "Hello, please introduce yourself in one
sentence."
      }
    ]
  };

axios.post("https://api.maiagent.ai/api/v1/chat/completions", data,
config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request failed:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/chat/completions"
headers = {
    "Authorization": "Bearer YOUR_API_KEY",
    "Content-Type": "application/json"
}

# Request payload
data = {
    "model": "openai/gpt-5.4-mini",
    "messages": [
        {
            "role": "user",
            "content": "Hello, please introduce yourself in one
sentence."
        }
    ]
}

response = requests.post(url, json=data, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request failed:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>post("https://api.maiagent.ai/api/v1/chat/completions", [
        'headers' => [
            'Authorization' => 'Bearer YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'model' => 'openai/gpt-5.4-mini',
            'messages' => [
                [
                    'role' => 'user',
                    'content' => 'Hello, please introduce yourself
in one sentence.'
                ]
            ]
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request failed: ' . $e->getMessage();
}
?>
```

Response

Status code: `200` - Returns a chat.completion object when stream=false; returns SSE when stream=true

Response Schema Example

```
{
  "id"?: string // optional
  "object"?: string (enum: chat.completion) // optional
  "created"?: integer // Unix seconds (optional)
  "model"?: string // optional
  "choices"?: [ // optional
    {
      "index"?: integer // optional
      "message"?: { // optional
      {
        "role"?: string (enum: assistant) // optional
        "content"?: string // optional
        "tool_calls"?: [ // optional
          {
            "id"?: string // optional
            "type"?: string (enum: function) // optional
            "function"?: { // optional
            {
              "name"?: string // optional
              "arguments"?: string // JSON string (optional)
            }
            }
          }
        ]
      }
      }
      "finish_reason"?: string // optional
    }
  ]
  "usage"?: { // optional
  {
    "prompt_tokens"?: integer // optional
    "completion_tokens"?: integer // optional
    "total_tokens"?: integer // optional
  }
```

```
  }
}
```

Response Example

```
{
  "id": "response string",
  "object": "chat.completion",
  "created": 456,
  "model": "response string",
  "choices": [
    {
      "index": 456,
      "message": {
        "id": "msg_550e8400e29b41d4a716446655440000",
        "content": "This is the message content of the response",
        "timestamp": "2025-01-01T00:00:00.000Z"
      },
      "finish_reason": "response string"
    }
  ],
  "usage": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Response example name",
    "description": "Response example description"
  }
}
```

Generate text embeddings

POST `/api/v1/embeddings`

The request and response formats are the same as OpenAI embeddings (model, input). For examples, see Embeddings in the technical manual.

Request

Request Parameters

Field	Type	Required	Description
model	string	Yes	
input	object	Yes	A non-empty string or an array of non-empty strings
encoding_format	string (enum: float, base64)	No	
dimensions	integer	No	
user	string	No	

Request Schema Example

```
{
  "model": string
  "input": // May be one of several types
  string // A non-empty string or an array of non-empty strings
  "encoding_format"?: string (enum: float, base64) // optional
  "dimensions"?: integer // optional
  "user"?: string // optional
}
```

Request Example

```
{
  "model": "text-embedding-3-large",
  "input": "The weather is nice today"
}
```

Code Examples

Shell/Bash

```
# Example API call (Shell)
curl -X POST "https://api.maiagent.ai/api/v1/embeddings"

  -H "Authorization: Bearer YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "model": "text-embedding-3-large",
    "input": "The weather is nice today"
  }'

# Make sure to replace YOUR_API_KEY and verify the request data
before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Bearer YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// Request payload
const data = {
    "model": "text-embedding-3-large",
    "input": "The weather is nice today"
  };

axios.post("https://api.maiagent.ai/api/v1/embeddings", data,
config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request failed:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/embeddings"
headers = {
    "Authorization": "Bearer YOUR_API_KEY",
    "Content-Type": "application/json"
}

# Request payload
data = {
    "model": "text-embedding-3-large",
    "input": "The weather is nice today"
}

response = requests.post(url, json=data, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request failed:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>post("https://api.maiagent.ai/api/v1/embeddings", [
        'headers' => [
            'Authorization' => 'Bearer YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'model' => 'text-embedding-3-large',
            'input' => 'The weather is nice today'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request failed: ' . $e->getMessage();
}
?>
```

Response

Status code: 200

Response Schema Example

```
{
  "object"?: string (enum: list) // optional
  "data"?: [ // optional
    {
      "object"?: string (enum: embedding) // optional
      "index"?: integer // optional
      "embedding"?: // May be one of several types (optional)
      array[number] // With encoding_format=float, an array of numbers;
with base64, a base64 string of little-endian float32 values (optional)
    }
  ]
  "model"?: string // optional
  "usage"?: { // optional
  {
    "prompt_tokens"?: integer // optional
    "total_tokens"?: integer // optional
  }
  }
}
```

Response Example

```
{
  "object": "list",
  "data": [
    {
      "object": "embedding",
      "index": 456,
      "embedding": [
        456
      ]
    }
  ],
  "model": "response string",
  "usage": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Response example name",
    "description": "Response example description"
  }
}
```

API call example (Shell)

目錄

1. Create a New AI Assistant
2. List Embedding Models
3. List Reranker Models
4. List Large Language Models
5. List AI Assistants
6. Retrieve an AI Assistant
7. Update AI Assistant
8. Partially Update an AI Assistant
9. Delete AI Assistant
10. Duplicate AI Assistant
11. Enable or Disable Evaluation
12. List Hooks in the Organization
13. Create a Hook from a Template
14. Retrieve a Specific Hook
15. Partially Update a Hook
16. Delete Hook
17. List Hooks Attached to an AI Assistant
18. Replace All Hooks Attached to an AI Assistant
19. List Schedules
20. Create Schedule
21. Retrieve a Specific Schedule
22. Partially Update Schedule
23. Delete a Schedule
24. Run Schedule Now
25. Enable or Disable Schedule

API call example (Shell)

Create a New AI Assistant

`POST` `/api/v1/chatbots/`

Request Body

Request Parameters

Field	Type	Required	Description
name	string	Yes	Chatbot name. In Agent mode it carries semantic meaning; in other modes it only

Field	Type	Required	Description
			distinguishes chatbots.
largeLanguageModel	string (uuid)	Yes	Large language model used by the chatbot to generate responses (including custom AI Gateway models configured by the organization); may be omitted during creation only if the organization has configured a default model in the AI assistant defaults
condenseQuestionLlm	string (uuid)	No	Question rewriting model: rewrites follow-up questions into standalone questions before retrieval in RAG reply mode; null follows the system settings (if the selected model is later blocked or disabled by the organization, this field also reads back as null and follows the system settings)
embeddingModel	string (uuid)	No	Optional embedding model used to vectorize text
rerankerModel	string (uuid)	No	Optional model used for reranking
instructions	string	No	Role instructions describing the chatbot's role and behavior.
knowledgeBases	array[IdName]	No	List of knowledge bases accessible to the chatbot
databases	array[IdName]	No	List of SQL databases accessible to the chatbot (for Text-to-SQL)
organization	string (uuid)	No	Organization the chatbot belongs to; if empty, the chatbot is personal
replyMode	object	No	Reply mode: normal or streaming replies `normal` : Normal ; `template` : Template ; `hybrid` : Hybrid ; `agent` : Agent;
template	string	No	Template used by Template and Hybrid modes.
unanswerableTemplate	string	No	Template used by Template and Hybrid modes when the question cannot be answered.
totalWordsCount	integer (int64)	No	Accumulated total word count used.
outputMode	object	No	Output mode: text, table, or custom format `text` : Text ; `json_schema` : JSON Schema;
rawOutputFormat	object	No	JSON structure definition for the custom output format
groups	array[IdName]	No	List of groups accessible to the chatbot
tools	array[ToolSummary]	No	List of tools available to the chatbot
skills	array[SkillSummary]	No	List of skills associated with the chatbot

Field	Type	Required	Description
connectors	array[IdName]	No	Connectors associated with this chatbot, gating per-contact OAuth authorization
agentMode	object	No	Agent mode: normal, SQL, or workflow mode `normal` : Normal ; `canvas` : Canvas ; `team` : Team;
numberOfRetrievedChunks	integer	No	Number of reference chunks to retrieve; defaults to 12, with a minimum of 1
defaultLabelRelations	object	No	Default knowledge base label filters at the assistant level, using the same format as query_metadata.label_relations; null means no filtering. Applied as the lowest-priority fallback only when the caller does not provide query_metadata.
useFullRetrievalRange	boolean	No	When enabled, ignores LLM top_k truncation and returns the full reranker results
enableEvaluation	boolean	No	
enableInlineCitations	boolean	No	Enables inline citations, inserting citation markers such as [1][2] into responses.
enableCodeInterpreter	boolean	No	When enabled, provides the Code Interpreter tool to run code in an isolated container.
enableBrowserTool	boolean	No	Enable browser automation tool for web tasks
enableImageSearch	boolean	No	Provide the image_search tool when any attached knowledge base uses a multimodal embedding model. Disable to remove the tool entirely.
enableClaudeStreamRetry	boolean	No	When a Claude streaming call stalls (first-chunk or mid-stream), abort and re-issue the call once in non-streaming mode. Mid-stream retries send a reset signal so the client discards any partial outpu...
customMaxLlmOutputTokens	integer	No	Custom maximum number of LLM output tokens, with a minimum of 512
voiceConfig	object	No	
voiceConfig.enabled	boolean	No	Whether this chatbot can be used as a voice agent. Checked by every conversation platform (WebChat, SIP phone, admin/marketplace voice test) instead of a per-platform toggle.
voiceConfig.voiceAgentType	string (uuid)	No	Voice agent mode type.
voiceConfig.sttProvider	string (uuid)	No	Speech-to-Text service provider.

Field	Type	Required	Description
voiceConfig.sttConfig	object	No	STT configuration parameters (JSON).
voiceConfig.ttsProvider	string (uuid)	No	Text-to-Speech service provider.
voiceConfig.ttsConfig	object	No	TTS configuration parameters (JSON).
voiceConfig.realtimeProvider	string (uuid)	No	Realtime end-to-end voice model provider.
voiceConfig.realtimeConfig	object	No	Realtime configuration parameters (JSON).
voiceConfig.realtimeInstructions	string	No	Prompt dedicated to the realtime voice session; falls back to chatbot instructions when empty
voiceConfig.turnHandling	object	No	Turn-taking and interruption settings for the voice agent.
voiceConfig.enableVoiceReply	boolean	No	When disabled, the voice agent replies in text only and does not speak
thinkingConfig	object	No	Reasoning level: null (model default) or {"reasoning_effort": "off
enableToolSearching	boolean	No	Legacy field; use tool_loading_mode instead. Writing true is equivalent to tool_loading_mode=search, and false to all; when both are provided, tool_loading_mode takes precedence. On read, returns whether the tool loading mode is anything other than loading all tools.
toolLoadingMode	object	No	Tool loading mode: auto (automatic, based on the number of available tools and the model for the current turn), all (load all), or search (dynamic search). New assistants default to auto; existing assistants that have never set this field return a value derived from the legacy toggle (on → search, off → all). `auto` : Auto ; `all` : Load all ; `search` : Dynamic search;
maxAgentIterations	integer	No	Maximum number of iterations for AgentWorkflow (1-100, default: 20)
agentTimeoutSeconds	integer	No	Timeout in seconds for AgentWorkflow execution (30-1200, default: 600)
agentTimeoutMessage	string	No	Custom user-facing message shown when AgentWorkflow times out (max 500 chars). Leave empty to use the system default.
requireTextWithFlexCards	boolean	No	When enabled, a turn that would end with only Flex Message cards and no text for the user is re-issued to the LLM once, asking it to write the text first and then send the card. Each retry incurs a se...

Field	Type	Required	Description
enableSizeBasedToolResultTruncation	boolean	No	When enabled, tool results exceeding the character threshold are kept as head+tail (with the identifiers found in the cut part) when written to conversation history; knowledge base, SQL and conversati...
toolResultMaxChars	integer	No	Character threshold for size-based tool result truncation (500-50000). Only effective when enable_size_based_tool_result_truncation is True.
enableVectorMemory	boolean	No	When enabled, archived messages are vectorized and processed by fact extraction for semantic retrieval (existing behavior). When disabled, archived messages are discarded and only the active chat hist...
longTermMemoryTopK	integer	No	Number of memory nodes returned per long-term memory retrieval (similarity_top_k for vector retrieval); defaults to 10, with a range of 1–50
enableCrossConversationSearch	boolean	No	When enabled, the conversation history tools also reach this contact's other conversations in the same inbox, within the lookback window. When disabled, they only reach the current conversation.
crossConversationLookbackDays	integer	No	How far back cross-conversation search may reach, measured from each conversation's last message (1-365 days). Leave empty to fall back to 90 days. Only effective when enable_cross_conversation_search...
useGatewayFallback	boolean	No	When enabled, use the fallback group instead of the single LLM
gatewayFallbackGroup	string (uuid)	No	
enableSearchMessagesTool	boolean	No	Allow the AI to search past messages in the current conversation.
enableGetMessageContextTool	boolean	No	Allow the AI to retrieve messages surrounding a specific message for context.
enableReadAttachmentFullTextTool	boolean	No	Allow the AI to read the full text of plain-text attachments. AGENT mode only.
enableParseAttachmentContentTool	boolean	No	Allow the AI to parse PDF, Office, audio, and other attachments. AGENT mode only.
enableListAvailableParsersTool	boolean	No	Allow the AI to list available parsers and their capabilities. AGENT mode only.

Field	Type	Required	Description
enableGetDownloadLinkTool	boolean	No	Allow the AI to generate shareable download links for produced content. AGENT mode only.
webChatIsActive	boolean	No	Optional, create only. Whether the web widget channel starts active. Omitted or null: follows the organization's default for new chatbot channels (inactive unless a platform admin turned it on). Ignor...
apiIsActive	boolean	No	Optional, create only. Whether the API channel starts active. Omitted or null: follows the organization's default for new chatbot channels (inactive unless a platform admin turned it on). Ignored on u...
fileWorkspaceMode	object	No	File workspace mode in Work internal conversations: none, bound or user_mount. `none` : None ; `bound` : Bound workspace ; `user_mount` : User mount;
fileWorkspaceFolder	string (uuid)	No	The bound workspace (folder id); required when the mode is bound, cleared otherwise.

Example Request Schema

```
{
  "name": string // Chatbot name. In Agent mode it carries semantic meaning; in other modes it only distinguishes chatbots.
  "largeLanguageModel": string (uuid) // Large language model used by the chatbot to generate responses (including custom AI Gateway models configured by the organization); may be omitted during creation only if the organization has configured a default model in the AI assistant defaults
  "condenseQuestionLlm"?: string (uuid) // Question rewriting model: rewrites follow-up questions into standalone questions before retrieval in RAG reply mode; null follows the system settings (if the selected model is later blocked or disabled by the organization, this field also reads back as null and follows the system settings) (Optional)
  "embeddingModel"?: string (uuid) // Optional embedding model used to vectorize text (Optional)
  "rerankerModel"?: string (uuid) // Optional model used for reranking (Optional)
  "instructions"?: string // Role instructions describing the chatbot's role and behavior. (Optional)
  "knowledgeBases"?: [ // List of knowledge bases accessible to the chatbot (Optional)
    {
      "id": string (uuid)
    }
  ]
  "databases"?: [ // List of SQL databases accessible to the chatbot (for Text-to-SQL) (Optional)
    {
      "id": string (uuid)
    }
```

```
  ]
  "organization"?: string (uuid) // Organization the chatbot belongs to; if empty, the chatbot
is personal (Optional)
  "replyMode"?:  // Reply mode: normal or streaming replies

* `normal` - Normal
* `template` - Template
* `hybrid` - Hybrid
* `agent` - Agent (Optional)
  {
  }
  "template"?: string // Template used by Template and Hybrid modes. (Optional)
  "unanswerableTemplate"?: string // Template used by Template and Hybrid modes when the
question cannot be answered. (Optional)
  "totalWordsCount"?: integer (int64) // Accumulated total word count used. (Optional)
  "outputMode"?:  // Output mode: text, table, or custom format

* `text` - Text
* `json_schema` - JSON Schema (Optional)
  {
  }
  "rawOutputFormat"?: object // JSON structure definition for the custom output format
(Optional)
  "groups"?: [ // List of groups accessible to the chatbot (Optional)
    {
      "id": string (uuid)
    }
  ]
  "tools"?: [ // List of tools available to the chatbot (Optional)
    {
      "id": string (uuid)
    }
  ]
  "skills"?: [ // List of skills associated with the chatbot (Optional)
    {
      "id": string (uuid)
    }
  ]
  "connectors"?: [ // Connectors associated with this chatbot, gating per-contact OAuth
authorization (Optional)
    {
      "id": string (uuid)
    }
  ]
  "agentMode"?:  // Agent mode: normal, SQL, or workflow mode

* `normal` - Normal
* `canvas` - Canvas
* `team` - Team (Optional)
  {
  }
  "numberOfRetrievedChunks"?: integer // Number of reference chunks to retrieve; defaults to
12, with a minimum of 1 (Optional)
  "defaultLabelRelations"?: object // Default knowledge base label filters at the assistant
level, using the same format as query_metadata.label_relations; null means no filtering.
Applied as the lowest-priority fallback only when the caller does not provide query_metadata.
(Optional)
```

```
  "useFullRetrievalRange"?: boolean // When enabled, ignores LLM top_k truncation and returns the full reranker results (Optional)
  "enableEvaluation"?: boolean // Optional
  "enableInlineCitations"?: boolean // Enables inline citations, inserting citation markers such as [1][2] into responses. (Optional)
  "enableCodeInterpreter"?: boolean // When enabled, provides the Code Interpreter tool to run code in an isolated container. (Optional)
  "enableBrowserTool"?: boolean // Enable browser automation tool for web tasks (Optional)
  "enableImageSearch"?: boolean // Provide the image_search tool when any attached knowledge base uses a multimodal embedding model. Disable to remove the tool entirely. (Optional)
  "enableClaudeStreamRetry"?: boolean // When a Claude streaming call stalls (first-chunk or mid-stream), abort and re-issue the call once in non-streaming mode. Mid-stream retries send a reset signal so the client discards any partial output already rendered. Each retry incurs a second billing for the same prompt. (Optional)
  "customMaxLlmOutputTokens"?: integer // Custom maximum number of LLM output tokens, with a minimum of 512 (Optional)
  "voiceConfig"?: { // Optional
  {
    "enabled"?: boolean // Whether this chatbot can be used as a voice agent. Checked by every conversation platform (WebChat, SIP phone, admin/marketplace voice test) instead of a per-platform toggle. (Optional)
    "voiceAgentType"?: string (uuid) // Voice agent mode type. (Optional)
    "sttProvider"?: string (uuid) // Speech-to-Text service provider. (Optional)
    "sttConfig"?: object // STT configuration parameters (JSON). (Optional)
    "ttsProvider"?: string (uuid) // Text-to-Speech service provider. (Optional)
    "ttsConfig"?: object // TTS configuration parameters (JSON). (Optional)
    "realtimeProvider"?: string (uuid) // Realtime end-to-end voice model provider. (Optional)
    "realtimeConfig"?: object // Realtime configuration parameters (JSON). (Optional)
    "realtimeInstructions"?: string // Prompt dedicated to the realtime voice session; falls back to chatbot instructions when empty (Optional)
    "turnHandling"?: object // Turn-taking and interruption settings for the voice agent. (Optional)
    "enableVoiceReply"?: boolean // When disabled, the voice agent replies in text only and does not speak (Optional)
  }
  }
  "thinkingConfig"?: object // Reasoning level: null (model default) or {"reasoning_effort": "off|minimal|low|medium|high|xhigh|max"} (Optional)
  "enableToolSearching"?: boolean // Legacy field; use tool_loading_mode instead. Writing true is equivalent to tool_loading_mode=search, and false to all; when both are provided, tool_loading_mode takes precedence. On read, returns whether the tool loading mode is anything other than loading all tools. (Optional)
  "toolLoadingMode"?:  // Tool loading mode: auto (automatic, based on the number of available tools and the model for the current turn), all (load all), or search (dynamic search). New assistants default to auto; existing assistants that have never set this field return a value derived from the legacy toggle (on → search, off → all).

* `auto` - Auto
* `all` - Load all
* `search` - Dynamic search (Optional)
  {
  }
  "maxAgentIterations"?: integer // Maximum number of iterations for AgentWorkflow (1-100, default: 20) (Optional)
  "agentTimeoutSeconds"?: integer // Timeout in seconds for AgentWorkflow execution (30-1200, default: 600) (Optional)
  "agentTimeoutMessage"?: string // Custom user-facing message shown when AgentWorkflow times
```

```
out (max 500 chars). Leave empty to use the system default. (Optional)
  "requireTextWithFlexCards"?: boolean // When enabled, a turn that would end with only Flex Message cards and no text for the user is re-issued to the LLM once, asking it to write the text first and then send the card. Each retry incurs a second billing for the same prompt. (Optional)
  "enableSizeBasedToolResultTruncation"?: boolean // When enabled, tool results exceeding the character threshold are kept as head+tail (with the identifiers found in the cut part) when written to conversation history; knowledge base, SQL and conversation search results keep their 100-character cut either way. Reduces memory bloat from large tool outputs (code interpreter bash stdout, web search results, etc.). (Optional)
  "toolResultMaxChars"?: integer // Character threshold for size-based tool result truncation (500-50000). Only effective when enable_size_based_tool_result_truncation is True. (Optional)
  "enableVectorMemory"?: boolean // When enabled, archived messages are vectorized and processed by fact extraction for semantic retrieval (existing behavior). When disabled, archived messages are discarded and only the active chat history window is used for multi-turn context. (Optional)
  "longTermMemoryTopK"?: integer // Number of memory nodes returned per long-term memory retrieval (similarity_top_k for vector retrieval); defaults to 10, with a range of 1–50 (Optional)
  "enableCrossConversationSearch"?: boolean // When enabled, the conversation history tools also reach this contact's other conversations in the same inbox, within the lookback window. When disabled, they only reach the current conversation. (Optional)
  "crossConversationLookbackDays"?: integer // How far back cross-conversation search may reach, measured from each conversation's last message (1-365 days). Leave empty to fall back to 90 days. Only effective when enable_cross_conversation_search is True. (Optional)
  "useGatewayFallback"?: boolean // When enabled, use the fallback group instead of the single LLM (Optional)
  "gatewayFallbackGroup"?: string (uuid) // Optional
  "enableSearchMessagesTool"?: boolean // Allow the AI to search past messages in the current conversation. (Optional)
  "enableGetMessageContextTool"?: boolean // Allow the AI to retrieve messages surrounding a specific message for context. (Optional)
  "enableReadAttachmentFullTextTool"?: boolean // Allow the AI to read the full text of plain-text attachments. AGENT mode only. (Optional)
  "enableParseAttachmentContentTool"?: boolean // Allow the AI to parse PDF, Office, audio, and other attachments. AGENT mode only. (Optional)
  "enableListAvailableParsersTool"?: boolean // Allow the AI to list available parsers and their capabilities. AGENT mode only. (Optional)
  "enableGetDownloadLinkTool"?: boolean // Allow the AI to generate shareable download links for produced content. AGENT mode only. (Optional)
  "webChatIsActive"?: boolean // Optional, create only. Whether the web widget channel starts active. Omitted or null: follows the organization's default for new chatbot channels (inactive unless a platform admin turned it on). Ignored on update; change an existing channel from its channel settings instead. (Optional)
  "apiIsActive"?: boolean // Optional, create only. Whether the API channel starts active. Omitted or null: follows the organization's default for new chatbot channels (inactive unless a platform admin turned it on). Ignored on update; change an existing channel from its channel settings instead. The backstage (admin) channel always starts active and cannot be set here. (Optional)
  "fileWorkspaceMode"?:  // File workspace mode in Work internal conversations: none, bound or user_mount.

* `none` - None
* `bound` - Bound workspace
* `user_mount` - User mount (Optional)
  {
  }
```

```
  "fileWorkspaceFolder"?: string (uuid) // The bound workspace (folder id); required when the
mode is bound, cleared otherwise. (Optional)
}
```

Example Request Values

```
{
  "name": "Example name",
  "largeLanguageModel": "550e8400-e29b-41d4-a716-446655440000",
  "condenseQuestionLlm": "550e8400-e29b-41d4-a716-446655440000",
  "embeddingModel": "550e8400-e29b-41d4-a716-446655440000",
  "rerankerModel": "550e8400-e29b-41d4-a716-446655440000",
  "instructions": "Example string",
  "knowledgeBases": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000"
    }
  ],
  "databases": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000"
    }
  ],
  "organization": "550e8400-e29b-41d4-a716-446655440000",
  "replyMode": {},
  "template": "Example string",
  "unanswerableTemplate": "Example string",
  "totalWordsCount": 123,
  "outputMode": {},
  "rawOutputFormat": null,
  "groups": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000"
    }
  ],
  "tools": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000"
    }
  ],
  "skills": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000"
    }
  ],
  "connectors": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000"
    }
  ],
  "agentMode": {},
  "numberOfRetrievedChunks": 123,
  "defaultLabelRelations": null,
  "useFullRetrievalRange": true,
  "enableEvaluation": true,
```

```
  "enableInlineCitations": true,
  "enableCodeInterpreter": true,
  "enableBrowserTool": true,
  "enableImageSearch": true,
  "enableClaudeStreamRetry": true,
  "customMaxLlmOutputTokens": 123,
  "voiceConfig": {
    "enabled": true,
    "voiceAgentType": "550e8400-e29b-41d4-a716-446655440000",
    "sttProvider": "550e8400-e29b-41d4-a716-446655440000",
    "sttConfig": null,
    "ttsProvider": "550e8400-e29b-41d4-a716-446655440000",
    "ttsConfig": null,
    "realtimeProvider": "550e8400-e29b-41d4-a716-446655440000",
    "realtimeConfig": null,
    "realtimeInstructions": "Example string",
    "turnHandling": null,
    "enableVoiceReply": true
  },
  "thinkingConfig": null,
  "enableToolSearching": true,
  "toolLoadingMode": {},
  "maxAgentIterations": 123,
  "agentTimeoutSeconds": 123,
  "agentTimeoutMessage": "Example string",
  "requireTextWithFlexCards": true,
  "enableSizeBasedToolResultTruncation": true,
  "toolResultMaxChars": 123,
  "enableVectorMemory": true,
  "longTermMemoryTopK": 123,
  "enableCrossConversationSearch": true,
  "crossConversationLookbackDays": 123,
  "useGatewayFallback": true,
  "gatewayFallbackGroup": "550e8400-e29b-41d4-a716-446655440000",
  "enableSearchMessagesTool": true,
  "enableGetMessageContextTool": true,
  "enableReadAttachmentFullTextTool": true,
  "enableParseAttachmentContentTool": true,
  "enableListAvailableParsersTool": true,
  "enableGetDownloadLinkTool": true,
  "webChatIsActive": true,
  "apiIsActive": true,
  "fileWorkspaceMode": {},
  "fileWorkspaceFolder": "550e8400-e29b-41d4-a716-446655440000"
}
```


Code Examples

Shell/Bash

```
# API call example (Shell)
curl -X POST "

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "name": "Example name",
    "largeLanguageModel": "550e8400-e29b-41d4-a716-446655440000",
    "condenseQuestionLlm": "550e8400-e29b-41d4-a716-446655440000",
    "embeddingModel": "550e8400-e29b-41d4-a716-446655440000",
    "rerankerModel": "550e8400-e29b-41d4-a716-446655440000",
    "instructions": "Example string",
    "knowledgeBases": [
      {
        "id": "550e8400-e29b-41d4-a716-446655440000"
      }
    ],
    "databases": [
      {
        "id": "550e8400-e29b-41d4-a716-446655440000"
      }
    ],
    "organization": "550e8400-e29b-41d4-a716-446655440000",
    "replyMode": {},
    "template": "Example string",
    "unanswerableTemplate": "Example string",
    "totalWordsCount": 123,
    "outputMode": {},
    "rawOutputFormat": null,
    "groups": [
      {
        "id": "550e8400-e29b-41d4-a716-446655440000"
      }
    ],
    "tools": [
      {
        "id": "550e8400-e29b-41d4-a716-446655440000"
      }
    ],
    "skills": [
      {
        "id": "550e8400-e29b-41d4-a716-446655440000"
      }
    ],
    "connectors": [
      {
        "id": "550e8400-e29b-41d4-a716-446655440000"
      }
    ],
```

```
      "agentMode": {},
      "numberOfRetrievedChunks": 123,
      "defaultLabelRelations": null,
      "useFullRetrievalRange": true,
      "enableEvaluation": true,
      "enableInlineCitations": true,
      "enableCodeInterpreter": true,
      "enableBrowserTool": true,
      "enableImageSearch": true,
      "enableClaudeStreamRetry": true,
      "customMaxLlmOutputTokens": 123,
      "voiceConfig": {
        "enabled": true,
        "voiceAgentType": "550e8400-e29b-41d4-a716-446655440000",
        "sttProvider": "550e8400-e29b-41d4-a716-446655440000",
        "sttConfig": null,
        "ttsProvider": "550e8400-e29b-41d4-a716-446655440000",
        "ttsConfig": null,
        "realtimeProvider": "550e8400-e29b-41d4-a716-446655440000",
        "realtimeConfig": null,
        "realtimeInstructions": "Example string",
        "turnHandling": null,
        "enableVoiceReply": true
      },
      "thinkingConfig": null,
      "enableToolSearching": true,
      "toolLoadingMode": {},
      "maxAgentIterations": 123,
      "agentTimeoutSeconds": 123,
      "agentTimeoutMessage": "Example string",
      "requireTextWithFlexCards": true,
      "enableSizeBasedToolResultTruncation": true,
      "toolResultMaxChars": 123,
      "enableVectorMemory": true,
      "longTermMemoryTopK": 123,
      "enableCrossConversationSearch": true,
      "crossConversationLookbackDays": 123,
      "useGatewayFallback": true,
      "gatewayFallbackGroup": "550e8400-e29b-41d4-a716-446655440000",
      "enableSearchMessagesTool": true,
      "enableGetMessageContextTool": true,
      "enableReadAttachmentFullTextTool": true,
      "enableParseAttachmentContentTool": true,
      "enableListAvailableParsersTool": true,
      "enableGetDownloadLinkTool": true,
      "webChatIsActive": true,
      "apiIsActive": true,
      "fileWorkspaceMode": {},
      "fileWorkspaceFolder": "550e8400-e29b-41d4-a716-446655440000"
    }'

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// Request body (payload)
const data = {
    "name": "Example name",
    "largeLanguageModel": "550e8400-e29b-41d4-a716-446655440000",
    "condenseQuestionLlm": "550e8400-e29b-41d4-a716-446655440000",
    "embeddingModel": "550e8400-e29b-41d4-a716-446655440000",
    "rerankerModel": "550e8400-e29b-41d4-a716-446655440000",
    "instructions": "Example string",
    "knowledgeBases": [
      {
        "id": "550e8400-e29b-41d4-a716-446655440000"
      }
    ],
    "databases": [
      {
        "id": "550e8400-e29b-41d4-a716-446655440000"
      }
    ],
    "organization": "550e8400-e29b-41d4-a716-446655440000",
    "replyMode": {},
    "template": "Example string",
    "unanswerableTemplate": "Example string",
    "totalWordsCount": 123,
    "outputMode": {},
    "rawOutputFormat": null,
    "groups": [
      {
        "id": "550e8400-e29b-41d4-a716-446655440000"
      }
    ],
    "tools": [
      {
        "id": "550e8400-e29b-41d4-a716-446655440000"
      }
    ],
    "skills": [
      {
        "id": "550e8400-e29b-41d4-a716-446655440000"
      }
    ],
    "connectors": [
```

```
        {
          "id": "550e8400-e29b-41d4-a716-446655440000"
        }
      ],
      "agentMode": {},
      "numberOfRetrievedChunks": 123,
      "defaultLabelRelations": null,
      "useFullRetrievalRange": true,
      "enableEvaluation": true,
      "enableInlineCitations": true,
      "enableCodeInterpreter": true,
      "enableBrowserTool": true,
      "enableImageSearch": true,
      "enableClaudeStreamRetry": true,
      "customMaxLlmOutputTokens": 123,
      "voiceConfig": {
        "enabled": true,
        "voiceAgentType": "550e8400-e29b-41d4-a716-446655440000",
        "sttProvider": "550e8400-e29b-41d4-a716-446655440000",
        "sttConfig": null,
        "ttsProvider": "550e8400-e29b-41d4-a716-446655440000",
        "ttsConfig": null,
        "realtimeProvider": "550e8400-e29b-41d4-a716-446655440000",
        "realtimeConfig": null,
        "realtimeInstructions": "Example string",
        "turnHandling": null,
        "enableVoiceReply": true
      },
      "thinkingConfig": null,
      "enableToolSearching": true,
      "toolLoadingMode": {},
      "maxAgentIterations": 123,
      "agentTimeoutSeconds": 123,
      "agentTimeoutMessage": "Example string",
      "requireTextWithFlexCards": true,
      "enableSizeBasedToolResultTruncation": true,
      "toolResultMaxChars": 123,
      "enableVectorMemory": true,
      "longTermMemoryTopK": 123,
      "enableCrossConversationSearch": true,
      "crossConversationLookbackDays": 123,
      "useGatewayFallback": true,
      "gatewayFallbackGroup": "550e8400-e29b-41d4-a716-446655440000",
      "enableSearchMessagesTool": true,
      "enableGetMessageContextTool": true,
      "enableReadAttachmentFullTextTool": true,
      "enableParseAttachmentContentTool": true,
      "enableListAvailableParsersTool": true,
      "enableGetDownloadLinkTool": true,
      "webChatIsActive": true,
      "apiIsActive": true,
      "fileWorkspaceMode": {},
      "fileWorkspaceFolder": "550e8400-e29b-41d4-a716-446655440000"
    };

  axios.post(" data, config)
    .then(response => {
```

```
  console.log('Response received successfully:');
  console.log(response.data);
})
.catch(error => {
  console.error('Request error:');
  console.error(error.response?.data || error.message);
});
```

Python

```
import requests

url = "
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# Request body (payload)
data = {
    "name": "Example name",
    "largeLanguageModel": "550e8400-e29b-41d4-a716-446655440000",
    "condenseQuestionLlm": "550e8400-e29b-41d4-a716-446655440000",
    "embeddingModel": "550e8400-e29b-41d4-a716-446655440000",
    "rerankerModel": "550e8400-e29b-41d4-a716-446655440000",
    "instructions": "Example string",
    "knowledgeBases": [
        {
            "id": "550e8400-e29b-41d4-a716-446655440000"
        }
    ],
    "databases": [
        {
            "id": "550e8400-e29b-41d4-a716-446655440000"
        }
    ],
    "organization": "550e8400-e29b-41d4-a716-446655440000",
    "replyMode": {},
    "template": "Example string",
    "unanswerableTemplate": "Example string",
    "totalWordsCount": 123,
    "outputMode": {},
    "rawOutputFormat": None,
    "groups": [
        {
            "id": "550e8400-e29b-41d4-a716-446655440000"
        }
    ],
    "tools": [
        {
            "id": "550e8400-e29b-41d4-a716-446655440000"
        }
    ],
    "skills": [
        {
            "id": "550e8400-e29b-41d4-a716-446655440000"
        }
    ],
    "connectors": [
        {
            "id": "550e8400-e29b-41d4-a716-446655440000"
```

```
        }
    ],
    "agentMode": {},
    "numberOfRetrievedChunks": 123,
    "defaultLabelRelations": None,
    "useFullRetrievalRange": True,
    "enableEvaluation": True,
    "enableInlineCitations": True,
    "enableCodeInterpreter": True,
    "enableBrowserTool": True,
    "enableImageSearch": True,
    "enableClaudeStreamRetry": True,
    "customMaxLlmOutputTokens": 123,
    "voiceConfig": {
        "enabled": True,
        "voiceAgentType": "550e8400-e29b-41d4-a716-446655440000",
        "sttProvider": "550e8400-e29b-41d4-a716-446655440000",
        "sttConfig": None,
        "ttsProvider": "550e8400-e29b-41d4-a716-446655440000",
        "ttsConfig": None,
        "realtimeProvider": "550e8400-e29b-41d4-a716-446655440000",
        "realtimeConfig": None,
        "realtimeInstructions": "Example string",
        "turnHandling": None,
        "enableVoiceReply": True
    },
    "thinkingConfig": None,
    "enableToolSearching": True,
    "toolLoadingMode": {},
    "maxAgentIterations": 123,
    "agentTimeoutSeconds": 123,
    "agentTimeoutMessage": "Example string",
    "requireTextWithFlexCards": True,
    "enableSizeBasedToolResultTruncation": True,
    "toolResultMaxChars": 123,
    "enableVectorMemory": True,
    "longTermMemoryTopK": 123,
    "enableCrossConversationSearch": True,
    "crossConversationLookbackDays": 123,
    "useGatewayFallback": True,
    "gatewayFallbackGroup": "550e8400-e29b-41d4-a716-446655440000",
    "enableSearchMessagesTool": True,
    "enableGetMessageContextTool": True,
    "enableReadAttachmentFullTextTool": True,
    "enableParseAttachmentContentTool": True,
    "enableListAvailableParsersTool": True,
    "enableGetDownloadLinkTool": True,
    "webChatIsActive": True,
    "apiIsActive": True,
    "fileWorkspaceMode": {},
    "fileWorkspaceFolder": "550e8400-e29b-41d4-a716-446655440000"
}

response = requests.post(url, json=data, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
```

```
    except Exception as e:
        print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->post(" [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'name' => 'Example name',
            'largeLanguageModel' => '550e8400-e29b-41d4-a716-446655440000',
            'condenseQuestionLlm' => '550e8400-e29b-41d4-a716-446655440000',
            'embeddingModel' => '550e8400-e29b-41d4-a716-446655440000',
            'rerankerModel' => '550e8400-e29b-41d4-a716-446655440000',
            'instructions' => 'Example string',
            'knowledgeBases' => [
                [
                    'id' => '550e8400-e29b-41d4-a716-446655440000'
                ]
            ],
            'databases' => [
                [
                    'id' => '550e8400-e29b-41d4-a716-446655440000'
                ]
            ],
            'organization' => '550e8400-e29b-41d4-a716-446655440000',
            'replyMode' => new \stdClass(),
            'template' => 'Example string',
            'unanswerableTemplate' => 'Example string',
            'totalWordsCount' => 123,
            'outputMode' => new \stdClass(),
            'rawOutputFormat' => null,
            'groups' => [
                [
                    'id' => '550e8400-e29b-41d4-a716-446655440000'
                ]
            ],
            'tools' => [
                [
                    'id' => '550e8400-e29b-41d4-a716-446655440000'
                ]
            ],
            'skills' => [
                [
                    'id' => '550e8400-e29b-41d4-a716-446655440000'
                ]
            ],
            'connectors' => [
```

```
                [
                    'id' => '550e8400-e29b-41d4-a716-446655440000'
                ]
            ],
            'agentMode' => new \stdClass(),
            'numberOfRetrievedChunks' => 123,
            'defaultLabelRelations' => null,
            'useFullRetrievalRange' => true,
            'enableEvaluation' => true,
            'enableInlineCitations' => true,
            'enableCodeInterpreter' => true,
            'enableBrowserTool' => true,
            'enableImageSearch' => true,
            'enableClaudeStreamRetry' => true,
            'customMaxLlmOutputTokens' => 123,
            'voiceConfig' => [
                'enabled' => true,
                'voiceAgentType' => '550e8400-e29b-41d4-a716-446655440000',
                'sttProvider' => '550e8400-e29b-41d4-a716-446655440000',
                'sttConfig' => null,
                'ttsProvider' => '550e8400-e29b-41d4-a716-446655440000',
                'ttsConfig' => null,
                'realtimeProvider' => '550e8400-e29b-41d4-a716-446655440000',
                'realtimeConfig' => null,
                'realtimeInstructions' => 'Example string',
                'turnHandling' => null,
                'enableVoiceReply' => true
            ],
            'thinkingConfig' => null,
            'enableToolSearching' => true,
            'toolLoadingMode' => new \stdClass(),
            'maxAgentIterations' => 123,
            'agentTimeoutSeconds' => 123,
            'agentTimeoutMessage' => 'Example string',
            'requireTextWithFlexCards' => true,
            'enableSizeBasedToolResultTruncation' => true,
            'toolResultMaxChars' => 123,
            'enableVectorMemory' => true,
            'longTermMemoryTopK' => 123,
            'enableCrossConversationSearch' => true,
            'crossConversationLookbackDays' => 123,
            'useGatewayFallback' => true,
            'gatewayFallbackGroup' => '550e8400-e29b-41d4-a716-446655440000',
            'enableSearchMessagesTool' => true,
            'enableGetMessageContextTool' => true,
            'enableReadAttachmentFullTextTool' => true,
            'enableParseAttachmentContentTool' => true,
            'enableListAvailableParsersTool' => true,
            'enableGetDownloadLinkTool' => true,
            'webChatIsActive' => true,
            'apiIsActive' => true,
            'fileWorkspaceMode' => new \stdClass(),
            'fileWorkspaceFolder' => '550e8400-e29b-41d4-a716-446655440000'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
```

```
        echo "Response received successfully:\n";
        print_r($data);
    } catch (Exception $e) {
        echo 'Request error: ' . $e->getMessage();
    }
    ?>
```

Response Body

Status code: 201

Example Response Schema

```
{
  "id": string (uuid)
  "name": string // Chatbot name. In Agent mode it carries semantic meaning; in other modes it only distinguishes chatbots.
  "largeLanguageModel": string (uuid) // Large language model used by the chatbot to generate responses (including custom AI Gateway models created by the organization); can be omitted on creation only if the organization has set a default model in its AI assistant defaults
  "llm":  // The bound model's id, name, and retirement information, read directly from the FK; returned even if the organization has disabled the model
  {
    "id": string (uuid)
    "name": string
    "retiresAt": string (date) // Provider retirement date; once reached, the daily scheduled job switches assistants to the replacement and disables this model. null means no retirement is scheduled
    "replacement":  // Replacement model after retirement (id and name); null means none is specified, so no automatic migration occurs on the retirement date
    {
      "id": string (uuid)
      "name": string
    }
  }
  "condenseQuestionLlm"?: string (uuid) // Question rewriting model: rewrites follow-up questions as standalone questions before retrieval in RAG reply mode; null means follow system settings (if the selected model is later blocked or disabled by the organization, null is also returned and system settings apply) (optional)
  "defaultCondenseQuestionLlm":  // Question rewriting model actually used when following system settings (id and name); null means the assistant's main model handles rewriting (read-only)
  {
    "id": string (uuid)
    "name": string
  }
  "organizationEnforcedSettings": [ // Codes of settings enforced on this assistant by the organization's AI assistant defaults (matching the keys in the AI assistant defaults API);
```

```
these fields return the enforced values, and updates with different values are rejected (read-
only; empty for official built-in Agents and MaiGPT)
    string
  ]
  "embeddingModel"?: string (uuid) // Embedding model for vectorizing text; optional (optional)
  "rerankerModel"?: string (uuid) // Model for reranking; optional (optional)
  "instructions"?: string // Role instructions describing the chatbot's role and behavior.
(optional)
  "knowledgeBases"?: [ // List of knowledge bases accessible to the chatbot (optional)
    {
      "id": string (uuid)
      "name": string
    }
  ]
  "databases"?: [ // List of SQL databases accessible to the chatbot (for Text-to-SQL)
(optional)
    {
      "id": string (uuid)
      "name": string
    }
  ]
  "updatedAt": string (timestamp)
  "organization"?: string (uuid) // Organization the chatbot belongs to; if empty, this is a
personal chatbot (optional)
  "replyMode"?:  // Reply mode: normal or streaming replies

* `normal` - Normal
* `template` - Template
* `hybrid` - Hybrid
* `agent` - Agent (optional)
  {
  }
  "template"?: string // Template used by Template and Hybrid modes. (optional)
  "unanswerableTemplate"?: string // Template used by Template and Hybrid modes when the
question cannot be answered. (optional)
  "totalWordsCount"?: integer (int64) // Accumulated total word count used. (optional)
  "outputMode"?:  // Output mode: text, table, or custom format

* `text` - Text
* `json_schema` - JSON Schema (optional)
  {
  }
  "rawOutputFormat"?: object // JSON schema definition for the custom output format (optional)
  "groups"?: [ // List of groups accessible to the chatbot (optional)
    {
      "id": string (uuid)
      "name": string
    }
  ]
  "tools"?: [ // List of tools available to the chatbot (optional)
    {
      "id": string (uuid)
      "name": string
      "description": string
      "displayName": string
      "toolType": string
    }
```

```
  ]
  "skills"?: [ // List of skills associated with the chatbot (optional)
    {
      "id": string (uuid)
      "name": string
      "description": string
    }
  ]
  "connectors"?: [ // Connectors associated with this chatbot, gating per-contact OAuth
authorization (optional)
    {
      "id": string (uuid)
      "name": string
    }
  ]
  "agentMode"?:  // Agent mode: normal, SQL, or workflow mode

* `normal` - Normal
* `canvas` - Canvas
* `team` - Team (optional)
  {
  }
  "numberOfRetrievedChunks"?: integer // Number of reference chunks retrieved; default: 12,
minimum: 1 (optional)
  "defaultLabelRelations"?: object // Assistant-level default knowledge base label filters, in
the same format as query_metadata.label_relations; null means no filtering. Applied only as the
lowest-priority fallback when the caller does not provide query_metadata. (optional)
  "useFullRetrievalRange"?: boolean // When enabled, ignores LLM top_k truncation and returns
the full reranker results (optional)
  "enableEvaluation"?: boolean // optional
  "enableInlineCitations"?: boolean // Enables inline citations, inserting citation markers
such as [1][2] into responses. (optional)
  "enableCodeInterpreter"?: boolean // When enabled, provides the Code Interpreter tool to run
code in an isolated container. (optional)
  "enableBrowserTool"?: boolean // Enable browser automation tool for web tasks (optional)
  "enableImageSearch"?: boolean // Provide the image_search tool when any attached knowledge
base uses a multimodal embedding model. Disable to remove the tool entirely. (optional)
  "enableClaudeStreamRetry"?: boolean // When a Claude streaming call stalls (first-chunk or
mid-stream), abort and re-issue the call once in non-streaming mode. Mid-stream retries send a
reset signal so the client discards any partial output already rendered. Each retry incurs a
second billing for the same prompt. (optional)
  "customMaxLlmOutputTokens"?: integer // Custom maximum number of LLM output tokens; minimum:
512 (optional)
  "voiceConfig"?: { // optional
  {
    "enabled"?: boolean // Whether this chatbot can be used as a voice agent. Checked by every
conversation platform (WebChat, SIP phone, admin/marketplace voice test) instead of a per-
platform toggle. (optional)
    "voiceAgentType"?: string (uuid) // Voice agent mode type. (optional)
    "sttProvider"?: string (uuid) // Speech-to-Text service provider. (optional)
    "sttConfig"?: object // STT configuration parameters (JSON). (optional)
    "ttsProvider"?: string (uuid) // Text-to-Speech service provider. (optional)
    "ttsConfig"?: object // TTS configuration parameters (JSON). (optional)
    "realtimeProvider"?: string (uuid) // Realtime end-to-end voice model provider. (optional)
    "realtimeConfig"?: object // Realtime configuration parameters (JSON). (optional)
    "realtimeInstructions"?: string // Prompt dedicated to the realtime voice session; falls
back to chatbot instructions when empty (optional)
```

```
    "turnHandling"?: object // Turn-taking and interruption settings for the voice agent. (optional)
    "enableVoiceReply"?: boolean // When disabled, the voice agent replies in text only and does not speak (optional)
  }
  }
  "thinkingConfig"?: object // Reasoning effort: null (model default) or {"reasoning_effort": "off|minimal|low|medium|high|xhigh|max"} (optional)
  "enableToolSearching"?: boolean // Legacy field; use tool_loading_mode instead. Writing true is equivalent to tool_loading_mode=search, and false to all; if both are provided, tool_loading_mode takes precedence. On reads, returns whether the tool loading mode is anything other than loading all tools. (optional)
  "toolLoadingMode"?:  // Tool loading mode: auto (automatically determined by the number of available tools and the model for the current turn), all (load all), or search (dynamic search). New assistants default to auto; existing assistants without an explicit setting return a value derived from the legacy toggle (on→search, off→all).

* `auto` - Auto
* `all` - Load all
* `search` - Dynamic search (Optional)
  {
  }
  "maxAgentIterations"?: integer // Maximum number of iterations for AgentWorkflow (1-100, default: 20) (Optional)
  "agentTimeoutSeconds"?: integer // Timeout in seconds for AgentWorkflow execution (30-1200, default: 600) (Optional)
  "agentTimeoutMessage"?: string // Custom user-facing message shown when AgentWorkflow times out (max 500 chars). Leave empty to use the system default. (Optional)
  "requireTextWithFlexCards"?: boolean // When enabled, a turn that would end with only Flex Message cards and no text for the user is re-issued to the LLM once, asking it to write the text first and then send the card. Each retry incurs a second billing for the same prompt. (Optional)
  "isMultimodalLlm": boolean // Whether the chatbot LLM supports multimodal (read-only)
  "enableSizeBasedToolResultTruncation"?: boolean // When enabled, tool results exceeding the character threshold are kept as head+tail (with the identifiers found in the cut part) when written to conversation history; knowledge base, SQL and conversation search results keep their 100-character cut either way. Reduces memory bloat from large tool outputs (code interpreter bash stdout, web search results, etc.). (Optional)
  "toolResultMaxChars"?: integer // Character threshold for size-based tool result truncation (500-50000). Only effective when enable_size_based_tool_result_truncation is True. (Optional)
  "enableVectorMemory"?: boolean // When enabled, archived messages are vectorized and processed by fact extraction for semantic retrieval (existing behavior). When disabled, archived messages are discarded and only the active chat history window is used for multi-turn context. (Optional)
  "longTermMemoryTopK"?: integer // Number of memory nodes retrieved per long-term memory search (similarity_top_k for vector retrieval). Default: 10; range: 1–50 (Optional)
  "enableCrossConversationSearch"?: boolean // When enabled, the conversation history tools also reach this contact's other conversations in the same inbox, within the lookback window. When disabled, they only reach the current conversation. (Optional)
  "crossConversationLookbackDays"?: integer // How far back cross-conversation search may reach, measured from each conversation's last message (1-365 days). Leave empty to fall back to 90 days. Only effective when enable_cross_conversation_search is True. (Optional)
  "useGatewayFallback"?: boolean // When enabled, use the fallback group instead of the single LLM (Optional)
  "gatewayFallbackGroup"?: string (uuid) // Optional
  "enableSearchMessagesTool"?: boolean // Allow the AI to search past messages in the current conversation. (Optional)
```

```
  "enableGetMessageContextTool"?: boolean // Allow the AI to retrieve messages surrounding a specific message for context. (Optional)
  "enableReadAttachmentFullTextTool"?: boolean // Allow the AI to read the full text of plain-text attachments. AGENT mode only. (Optional)
  "enableParseAttachmentContentTool"?: boolean // Allow the AI to parse PDF, Office, audio, and other attachments. AGENT mode only. (Optional)
  "enableListAvailableParsersTool"?: boolean // Allow the AI to list available parsers and their capabilities. AGENT mode only. (Optional)
  "enableGetDownloadLinkTool"?: boolean // Allow the AI to generate shareable download links for produced content. AGENT mode only. (Optional)
  "isLocked": boolean // Locked instance: config follows the official version; only the dedicated KB can be modified
  "sourceBuildInAgent": string (uuid) // Points to the official Build-in Agent blueprint when instantiated by a rental
  "canUpdate": boolean // Return whether the current user can update this resource.
  "canDelete": boolean // Return whether the current user can delete this resource.
  "team":
  {
    "id": string (uuid)
    "name": string
  }
  "webChatIsActive"?: boolean // Optional, create only. Whether the web widget channel starts active. Omitted or null: follows the organization's default for new chatbot channels (inactive unless a platform admin turned it on). Ignored on update; change an existing channel from its channel settings instead. (Optional)
  "apiIsActive"?: boolean // Optional, create only. Whether the API channel starts active. Omitted or null: follows the organization's default for new chatbot channels (inactive unless a platform admin turned it on). Ignored on update; change an existing channel from its channel settings instead. The backstage (admin) channel always starts active and cannot be set here. (Optional)
  "fileWorkspaceMode"?:  // File workspace mode in Work internal conversations: none, bound or user_mount.

* `none` - None
* `bound` - Bound workspace
* `user_mount` - User mount (Optional)
  {
  }
  "fileWorkspaceFolder"?: string (uuid) // The bound workspace (folder id); required when the mode is bound, cleared otherwise. (Optional)
  "fileWorkspaceStatus": object // Read-only. {"folder": {"id", "name"} | null, "state": "ok" | "missing" | "builder_lost_edit" | null}
  "fileWorkspaceAvailable": boolean // Read-only. Whether the organization has the file library and this agent can configure a file workspace.
}
```

Example Response Value

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "name": "Response string",
  "largeLanguageModel": "550e8400-e29b-41d4-a716-446655440000",
  "llm": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Response string",
```

```
    "retiresAt": "Response string",
    "replacement": {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "Response string"
    }
  },
  "condenseQuestionLlm": "550e8400-e29b-41d4-a716-446655440000",
  "defaultCondenseQuestionLlm": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Response string"
  },
  "organizationEnforcedSettings": [
    "Response string"
  ],
  "embeddingModel": "550e8400-e29b-41d4-a716-446655440000",
  "rerankerModel": "550e8400-e29b-41d4-a716-446655440000",
  "instructions": "Response string",
  "knowledgeBases": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "Response string"
    }
  ],
  "databases": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "Response string"
    }
  ],
  "updatedAt": "Response string",
  "organization": "550e8400-e29b-41d4-a716-446655440000",
  "replyMode": {},
  "template": "Response string",
  "unanswerableTemplate": "Response string",
  "totalWordsCount": 456,
  "outputMode": {},
  "rawOutputFormat": null,
  "groups": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "Response string"
    }
  ],
  "tools": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "Response string",
      "description": "Response string",
      "displayName": "Response string",
      "toolType": "Response string"
    }
  ],
  "skills": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "Response string",
      "description": "Response string"
```

```
    }
  ],
  "connectors": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "Response string"
    }
  ],
  "agentMode": {},
  "numberOfRetrievedChunks": 456,
  "defaultLabelRelations": null,
  "useFullRetrievalRange": false,
  "enableEvaluation": false,
  "enableInlineCitations": false,
  "enableCodeInterpreter": false,
  "enableBrowserTool": false,
  "enableImageSearch": false,
  "enableClaudeStreamRetry": false,
  "customMaxLlmOutputTokens": 456,
  "voiceConfig": {
    "enabled": false,
    "voiceAgentType": "550e8400-e29b-41d4-a716-446655440000",
    "sttProvider": "550e8400-e29b-41d4-a716-446655440000",
    "sttConfig": null,
    "ttsProvider": "550e8400-e29b-41d4-a716-446655440000",
    "ttsConfig": null,
    "realtimeProvider": "550e8400-e29b-41d4-a716-446655440000",
    "realtimeConfig": null,
    "realtimeInstructions": "Response string",
    "turnHandling": null,
    "enableVoiceReply": false
  },
  "thinkingConfig": null,
  "enableToolSearching": false,
  "toolLoadingMode": {},
  "maxAgentIterations": 456,
  "agentTimeoutSeconds": 456,
  "agentTimeoutMessage": "Response string",
  "requireTextWithFlexCards": false,
  "isMultimodalLlm": false,
  "enableSizeBasedToolResultTruncation": false,
  "toolResultMaxChars": 456,
  "enableVectorMemory": false,
  "longTermMemoryTopK": 456,
  "enableCrossConversationSearch": false,
  "crossConversationLookbackDays": 456,
  "useGatewayFallback": false,
  "gatewayFallbackGroup": "550e8400-e29b-41d4-a716-446655440000",
  "enableSearchMessagesTool": false,
  "enableGetMessageContextTool": false,
  "enableReadAttachmentFullTextTool": false,
  "enableParseAttachmentContentTool": false,
  "enableListAvailableParsersTool": false,
  "enableGetDownloadLinkTool": false,
  "isLocked": false,
  "sourceBuildInAgent": "550e8400-e29b-41d4-a716-446655440000",
  "canUpdate": false,
```

```
  "canDelete": false,
  "team": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Response string"
  },
  "webChatIsActive": false,
  "apiIsActive": false,
  "fileWorkspaceMode": {},
  "fileWorkspaceFolder": "550e8400-e29b-41d4-a716-446655440000",
  "fileWorkspaceStatus": {
    "name": "example.pdf",
    "content": "base64encoded_content",
    "contentType": "application/pdf"
  },
  "fileWorkspaceAvailable": false
}
```


List Embedding Models

GET `/api/v1/embedding-models/`

Code Examples

Shell/Bash

```
# API Call Example (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/embedding-models/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/embedding-models/", config)
  .then(response => {
    console.log('Response retrieved successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request failed:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/embedding-models/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("Response retrieved successfully:")
    print(response.json())
except Exception as e:
    print("Request failed:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->get("https://api.maiagent.ai/api/v1/embedding-models/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response retrieved successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request failed: ' . $e->getMessage();
}
?>
```

Response Content

Status Code: 200

Example Response Structure

```
[
  {
    "id": string (uuid)
    "name": string
    "isDefault"?: boolean // Optional
    "isMultimodal"?: boolean // Whether this embedding model supports multimodal (text + image)
embeddings (Optional)
    "icon":
    {
      "id": string (uuid)
      "name": string
      "image": string (uri)
    }
  }
]
```

Example Response Values


```
[
  {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Response string",
    "isDefault": false,
    "isMultimodal": false,
    "icon": {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "Response string",
      "image": "https://example.com/file.jpg"
    }
  }
]
```


List Reranker Models

GET `/api/v1/reranker-models/`

Code Examples

Shell/Bash

```
# API Call Example (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/reranker-models/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/reranker-models/", config)
  .then(response => {
    console.log('Response retrieved successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request failed:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/reranker-models/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("Response retrieved successfully:")
    print(response.json())
except Exception as e:
    print("Request failed:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->get("https://api.maiagent.ai/api/v1/reranker-models/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response retrieved successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request failed: ' . $e->getMessage();
}
?>
```

Response Content

Status Code: 200

Example Response Structure

```
[
  {
    "id": string (uuid)
    "name": string
    "isDefault"?: boolean // Optional
    "icon":
    {
      "id": string (uuid)
      "name": string
      "image": string (uri)
    }
  }
]
```

Example Response Values

```
[
  {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Response string",
    "isDefault": false,
    "icon": {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "Response string",
      "image": "https://example.com/file.jpg"
    }
  }
]
```


List Large Language Models

GET `/api/v1/large-language-models/`

Code Examples

Shell/Bash

```
# API call example (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/large-language-models/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/large-language-models/", config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request failed:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/large-language-models/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request failed:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->get("https://api.maiagent.ai/api/v1/large-language-models/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request failed: ' . $e->getMessage();
}
?>
```

Response

Status Code: 200

Example Response Schema

```
[
  {
    "id": string (uuid)
    "name": string
    "retiresAt": string (date) // Provider retirement date. Once reached, a daily scheduled
task switches assistants to replacement and disables this model. null means no retirement is
scheduled.
    "replacement":  // The replacement model (id and name) after retirement. null means none is
specified, so no automatic migration occurs on retirement.
    {
      "id": string (uuid)
      "name": string
    }
    "contextWindow"?: integer // Used only by OpenAILike or Ollama models; other models ignore
this value. (Optional)
    "isDefault"?: boolean // Optional
    "provider": string
```

```
    "servedBy": string // Who runs inference, which is where prompts are sent (for example
OpenRouter, AWS Bedrock); models on a customer credential show Customer credential.
    "icon":
    {
      "id": string (uuid)
      "name": string
      "image": string (uri)
    }
    "isMultiModalSupport"?: boolean // Optional
    "isFunctionalCallingAvailable": boolean // Deprecated: same value as
isToolCallingAvailable; use isToolCallingAvailable.
    "isToolCallingAvailable"?: boolean // Optional
    "isTemplateAvailable": boolean
    "isOutputFormatAvailable": boolean
    "isThinkingAvailable"?: boolean // When checked, this model shows the thinking depth
setting and requests carry thinking parameters (thinking_budget for Gemini, reasoning_effort
for OpenAI-compatible hosts). Unchecking stops sending them; saved thinking settings are kept
but have no effect. Check only for models known to support thinking parameters, otherwise the
provider returns 4xx. (Optional)
    "defaultThinkingLevel"?: // May have different types (Optional)
    string (enum: off, minimal, low, medium, high, xhigh, max) // The thinking level sent when
neither the conversation nor the assistant sets one. Empty sends no thinking parameter, so the
provider default applies. A level the model does not accept is lowered to the nearest one it
does. Takes effect only when Supports Thinking is checked.

* `off` - off
* `minimal` - minimal
* `low` - low
* `medium` - medium
* `high` - high
* `xhigh` - xhigh
* `max` - max (Optional)
    "thinkingConfigSchema": { // Thinking configuration form for this model; null means this
model has no thinking settings.
    {
      "type"?: string // Form type; always reasoning_effort. (Optional)
      "fields"?: object // reasoning_effort field: options lists the thinking levels this model
accepts, from lowest to highest; default is always null. (Optional)
      "canDisable"?: boolean // Whether thinking can be disabled for this model; when true,
options includes off. (Optional)
      "unsetBehavior"?: string (enum: off, model_default) // Actual behavior when neither the
conversation nor the assistant sets a thinking level: off = no thinking (fastest);
model_default = the model controls thinking, or the platform default level enables thinking.
(Optional)
      "unsetLevel"?: string // The level the platform actually sends when no level is set; null
means no thinking parameter is sent, leaving the model default in effect. (Optional)
    }
    }
    "replyMode": [
      string
    ]
    "outputMode": [
      string
    ]
    "agentMode": [
      string
    ]
```

```
    "maxTokens"?: integer // Optional
    "minTokens": integer
    "isCustomModel": boolean // Whether the row is organization-owned (materialized from an AI
Gateway custom model).
    "originCountry": string // ISO 3166-1 alpha-2 code of the country the model developer is
based in (e.g. US, CN, FR); null when unknown. Follows the model, not who runs inference.
    "originRegion": // May have different types
    string (enum: cn, us, other) // Origin group for labels and filters: cn / us / other; null
when unknown (no label).

* `cn` - China
* `us` - United States
* `other` - Other countries
    "originRegionDisplay": string // Translated origin group name (e.g. China / United States /
Other countries); null when unknown.
    "isCondenseQuestionAvailable": boolean // Whether an assistant can pick this model as its
question-rewrite (condense question) model; false for image-generation models, which the
chatbot condense_question_llm field rejects.
  }
]
```

Example Response Values

```
[
  {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Response string",
    "retiresAt": "Response string",
    "replacement": {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "Response string"
    },
    "contextWindow": 456,
    "isDefault": false,
    "provider": "Response string",
    "servedBy": "Response string",
    "icon": {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "Response string",
      "image": "https://example.com/file.jpg"
    },
    "isMultiModalSupport": false,
    "isFunctionalCallingAvailable": false,
    "isToolCallingAvailable": false,
    "isTemplateAvailable": false,
    "isOutputFormatAvailable": false,
    "isThinkingAvailable": false,
    "defaultThinkingLevel": "off",
    "thinkingConfigSchema": {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "Example response name",
      "description": "Example response description"
    },
    "replyMode": [
      "Response string"
```

```
    ],
    "outputMode": [
      "Response string"
    ],
    "agentMode": [
      "Response string"
    ],
    "maxTokens": 456,
    "minTokens": 456,
    "isCustomModel": false,
    "originCountry": "Response string",
    "originRegion": "cn",
    "originRegionDisplay": "Response string",
    "isCondenseQuestionAvailable": false
  }
]
```


List AI Assistants

GET `/api/v1/chatbots/`

Parameters

Parameter Name	Required	Type	Description
`createdByMember`	X	string	Creator filter: the ID of a member in this organization (the ID returned by the member directory, including disabled members). Returns only AI assistants created by that member.
`largeLanguageModel`	X	string	
`page`	X	integer	A page number within the paginated result set.
`pageSize`	X	integer	Number of results to return per page.
`pagination`	X	string	Whether to paginate (true/false)
`query`	X	string	
`replyMode`	X	string	
`source`	X	string	`self_built`: self_built ; `built_in`: built_in ; `all`: all;

Code Examples

Shell/Bash

```
# API call example (Shell)
curl -X GET "

  -H "Authorization: Api-Key YOUR_API_KEY"

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get(" config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request failed:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request failed:", e)
```

PHP

```
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->get(" [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request failed: ' . $e->getMessage();
}
?>
```

Response

Status Code: 200

Example Response Schema

```
{
  "count": integer
  "next"?: string (uri) // Optional
  "previous"?: string (uri) // Optional
  "results": [
    {
      "id": string (uuid)
      "name": string // Chatbot name. In Agent mode it carries semantic meaning; in other modes
it only distinguishes chatbots.
      "groups": [
        {
          "id": string (uuid)
          "name": string
        }
      ]
      "largeLanguageModel": { // Base LLM serializer: identification fields plus retirement
information, so the frontend can warn when the model is nearing retirement.
      {
        "id": string (uuid)
        "name": string
        "retiresAt": string (date) // Provider retirement date. Once reached, a daily scheduled
task switches assistants to replacement and disables this model. null means no retirement is
scheduled.
        "replacement":  // The replacement model (id and name) after retirement. null means
none is specified, so no automatic migration occurs on retirement.
        {
          "id": string (uuid)
          "name": string
        }
      }
      }
      "embeddingModel": {
      {
        "id": string (uuid)
        "name": string
        "isDefault"?: boolean // Optional
        "isMultimodal"?: boolean // Whether this embedding model supports multimodal (text +
image) embeddings (Optional)
        "icon":
        {
          "id": string (uuid)
          "name": string
          "image": string (uri)
        }
      }
      }
      "rerankerModel": {
      {
```

```
        "id": string (uuid)
        "name": string
        "isDefault"?: boolean // Optional
        "icon":
        {
          "id": string (uuid)
          "name": string
          "image": string (uri)
        }
      }
      }
      "knowledgeBases": [
        {
          "id": string (uuid)
          "name": string
        }
      ]
      "tools": [
        {
          "id": string (uuid)
          "name": string
          "description": string
          "displayName": string
          "toolType": string
        }
      ]
      "skills": [
        {
          "id": string (uuid)
          "name": string
          "description": string
        }
      ]
      "agentMode"?:  // Agent mode: Canvas or Normal. Canvas mode generates answers on a
canvas; Normal mode generates regular answers.

* `normal` - Normal
* `canvas` - Canvas
* `team` - Team (Optional)
      {
      }
      "replyMode"?:  // Reply mode: Normal, Template, Hybrid, or Agent.

* `normal` - Normal
* `template` - Template
* `hybrid` - Hybrid
* `agent` - Agent (Optional)
      {
      }
      "updatedAt": string (timestamp)
      "enableEvaluation"?: boolean // Optional
      "enableInlineCitations"?: boolean // Enables inline citations, inserting citation markers
such as [1][2] into responses. (Optional)
      "enableToolSearching": boolean
      "toolLoadingMode": string
      "enableCodeInterpreter"?: boolean // When enabled, provides the Code Interpreter tool to
run code in an isolated container. (Optional)
```

```
      "enableBrowserTool"?: boolean // Enable browser automation tool for web tasks (Optional)
      "enableImageSearch"?: boolean // Provide the image_search tool when any attached
knowledge base uses a multimodal embedding model. Disable to remove the tool entirely.
(Optional)
      "numberOfRetrievedChunks"?: integer // Optional
      "useFullRetrievalRange"?: boolean // When enabled, the retrieval tool ignores the top_k
set by the LLM and returns the full reranker result up to the maximum number of retrieved
chunks. Useful for knowledge bases with long tables that need a wider retrieval range.
(Optional)
      "isMultimodalLlm": boolean // Return whether the chatbot's LLM supports multimodal.
      "voiceConfig":
      {
        "enabled"?: boolean // Whether this chatbot can be used as a voice agent. Checked by
every conversation platform (WebChat, SIP phone, admin/marketplace voice test) instead of a
per-platform toggle. (Optional)
      }
      "createdBy":
      {
        "id": string (uuid)
        "name": string
      }
      "isLocked"?: boolean // Locked instance: config follows the official version; only the
dedicated KB can be modified (Optional)
      "sourceBuildInAgent"?: string (uuid) // Points to the official Build-in Agent blueprint
when instantiated by a rental (Optional)
      "canUpdate": boolean // Return whether the current user can update this resource.
      "canDelete": boolean // Return whether the current user can delete this resource.
      "team":
      {
        "id": string (uuid)
        "name": string
      }
    }
  ]
}
```

Example Response Values

```
{
  "count": 123,
  "next": "http://api.example.org/accounts/?page=4",
  "previous": "http://api.example.org/accounts/?page=2",
  "results": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "Response string",
      "groups": [
        {
          "id": "550e8400-e29b-41d4-a716-446655440000",
          "name": "Response string"
        }
      ],
      "largeLanguageModel": {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "name": "Response string",
```

```
      "retiresAt": "Response string",
      "replacement": {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "name": "Response string"
      }
    },
    "embeddingModel": {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "Response string",
      "isDefault": false,
      "isMultimodal": false,
      "icon": {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "name": "Response string",
        "image": "https://example.com/file.jpg"
      }
    },
    "rerankerModel": {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "Response string",
      "isDefault": false,
      "icon": {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "name": "Response string",
        "image": "https://example.com/file.jpg"
      }
    },
    "knowledgeBases": [
      {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "name": "Response string"
      }
    ],
    "tools": [
      {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "name": "Response string",
        "description": "Response string",
        "displayName": "Response string",
        "toolType": "Response string"
      }
    ],
    "skills": [
      {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "name": "Response string",
        "description": "Response string"
      }
    ],
    "agentMode": {},
    "replyMode": {},
    "updatedAt": "Response string",
    "enableEvaluation": false,
    "enableInlineCitations": false,
    "enableToolSearching": false,
    "toolLoadingMode": "Response string",
    "enableCodeInterpreter": false,
```

```
      "enableBrowserTool": false,
      "enableImageSearch": false,
      "numberOfRetrievedChunks": 456,
      "useFullRetrievalRange": false,
      "isMultimodalLlm": false,
      "voiceConfig": {
        "enabled": false
      },
      "createdBy": {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "name": "Response string"
      },
      "isLocked": false,
      "sourceBuildInAgent": "550e8400-e29b-41d4-a716-446655440000",
      "canUpdate": false,
      "canDelete": false,
      "team": {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "name": "Response string"
      }
    }
  ]
}
```


Retrieve an AI Assistant

GET `/api/v1/chatbots/{id}`

Parameters

Parameter Name	Required	Type	Description
`id`	V	string	

Code Examples

Shell/Bash

```
# API call example (Shell)
curl -X GET "

  -H "Authorization: Api-Key YOUR_API_KEY"

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get(" config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request failed:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request failed:", e)
```

PHP

```
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->get(" [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request failed: ' . $e->getMessage();
}
?>
```

Response

Status Code: 200

Example Response Schema

```
{
  "id": string (uuid)
  "name": string // Chatbot name. In Agent mode it carries semantic meaning; in other modes it only distinguishes chatbots.
  "largeLanguageModel": string (uuid) // Large language model used by the chatbot to generate responses (including custom AI Gateway models created by the organization); it can be omitted on creation only if the organization has configured a default model in its AI assistant defaults
  "llm":  // The bound model’s id, name, and retirement information, read directly from the foreign key; returned even if the organization has disabled the model
  {
    "id": string (uuid)
    "name": string
    "retiresAt": string (date) // Provider retirement date; once reached, a daily scheduled job switches assistants to replacement and disables this model. null means no retirement is scheduled
    "replacement":  // Replacement model after retirement (id and name); null means none is specified, so no automatic migration occurs on the retirement date
    {
      "id": string (uuid)
      "name": string
    }
  }
  "condenseQuestionLlm"?: string (uuid) // Question rewriting model: rewrites follow-up questions as standalone questions before retrieval in RAG response mode; null follows system settings (if the selected model is later blocked or disabled by the organization, this also returns null and follows system settings) (Optional)
  "defaultCondenseQuestionLlm":  // The question rewriting model actually used when following system settings (id and name); null means the assistant’s primary model rewrites questions (read-only)
  {
    "id": string (uuid)
    "name": string
  }
  "organizationEnforcedSettings": [ // Setting codes enforced for this assistant by the organization’s AI assistant defaults (matching the keys in the AI assistant defaults API); these fields return the enforced values, and updates with different values are rejected (read-only; empty for official built-in Agents and MaiGPT)
    string
  ]
  "embeddingModel"?: string (uuid) // Embedding model used to vectorize text; optional (Optional)
  "rerankerModel"?: string (uuid) // Model used for reranking; optional (Optional)
  "instructions"?: string // Role instructions describing the chatbot's role and behavior. (Optional)
  "knowledgeBases"?: [ // Knowledge bases the chatbot can access (Optional)
    {
      "id": string (uuid)
```

```
      "name": string
    }
  ]
  "databases"?: [ // SQL databases the chatbot can access (for Text-to-SQL) (Optional)
    {
      "id": string (uuid)
      "name": string
    }
  ]
  "updatedAt": string (timestamp)
  "organization"?: string (uuid) // Organization the chatbot belongs to; if empty, this is a
personal chatbot (Optional)
  "replyMode"?:  // Response mode: normal or streaming responses

* `normal` - Normal
* `template` - Template
* `hybrid` - Hybrid
* `agent` - Agent (Optional)
  {
  }
  "template"?: string // Template used by Template and Hybrid modes. (Optional)
  "unanswerableTemplate"?: string // Template used by Template and Hybrid modes when the
question cannot be answered. (Optional)
  "totalWordsCount"?: integer (int64) // Accumulated total word count used. (Optional)
  "outputMode"?:  // Output mode: text, table, or custom format

* `text` - Text
* `json_schema` - JSON Schema (Optional)
  {
  }
  "rawOutputFormat"?: object // JSON schema definition for a custom output format (Optional)
  "groups"?: [ // Groups the chatbot can access (Optional)
    {
      "id": string (uuid)
      "name": string
    }
  ]
  "tools"?: [ // Tools the chatbot can use (Optional)
    {
      "id": string (uuid)
      "name": string
      "description": string
      "displayName": string
      "toolType": string
    }
  ]
  "skills"?: [ // Skills associated with the chatbot (Optional)
    {
      "id": string (uuid)
      "name": string
      "description": string
    }
  ]
  "connectors"?: [ // Connectors associated with this chatbot, gating per-contact OAuth
authorization (Optional)
    {
      "id": string (uuid)
```

```
      "name": string
    }
  ]
  "agentMode"?:  // Agent mode: normal, SQL, or workflow mode

* `normal` - Normal
* `canvas` - Canvas
* `team` - Team (Optional)
  {
  }
  "numberOfRetrievedChunks"?: integer // Number of reference chunks retrieved; default: 12, minimum: 1 (Optional)
  "defaultLabelRelations"?: object // Assistant-level default knowledge base label filters, in the same format as query_metadata.label_relations; null means no filtering. Applied as the lowest-priority fallback only when the caller omits query_metadata. (Optional)
  "useFullRetrievalRange"?: boolean // When enabled, ignores the LLM’s top_k truncation and returns the full reranker results (Optional)
  "enableEvaluation"?: boolean // Optional
  "enableInlineCitations"?: boolean // Enables inline citations, inserting citation markers such as [1][2] into responses. (Optional)
  "enableCodeInterpreter"?: boolean // When enabled, provides the Code Interpreter tool to run code in an isolated container. (Optional)
  "enableBrowserTool"?: boolean // Enable browser automation tool for web tasks (Optional)
  "enableImageSearch"?: boolean // Provide the image_search tool when any attached knowledge base uses a multimodal embedding model. Disable to remove the tool entirely. (Optional)
  "enableClaudeStreamRetry"?: boolean // When a Claude streaming call stalls (first-chunk or mid-stream), abort and re-issue the call once in non-streaming mode. Mid-stream retries send a reset signal so the client discards any partial output already rendered. Each retry incurs a second billing for the same prompt. (Optional)
  "customMaxLlmOutputTokens"?: integer // Custom maximum number of LLM output tokens; minimum: 512 (Optional)
  "voiceConfig"?: { // Optional
  {
    "enabled"?: boolean // Whether this chatbot can be used as a voice agent. Checked by every conversation platform (WebChat, SIP phone, admin/marketplace voice test) instead of a per-platform toggle. (Optional)
    "voiceAgentType"?: string (uuid) // Voice agent mode type. (Optional)
    "sttProvider"?: string (uuid) // Speech-to-Text service provider. (Optional)
    "sttConfig"?: object // STT configuration parameters (JSON). (Optional)
    "ttsProvider"?: string (uuid) // Text-to-Speech service provider. (Optional)
    "ttsConfig"?: object // TTS configuration parameters (JSON). (Optional)
    "realtimeProvider"?: string (uuid) // Realtime end-to-end voice model provider. (Optional)
    "realtimeConfig"?: object // Realtime configuration parameters (JSON). (Optional)
    "realtimeInstructions"?: string // Prompt dedicated to the realtime voice session; falls back to chatbot instructions when empty (Optional)
    "turnHandling"?: object // Turn-taking and interruption settings for the voice agent. (Optional)
    "enableVoiceReply"?: boolean // When disabled, the voice agent replies in text only and does not speak (Optional)
  }
  }
  "thinkingConfig"?: object // Reasoning level: null (model default) or {"reasoning_effort": "off|minimal|low|medium|high|xhigh|max"} (Optional)
  "enableToolSearching"?: boolean // Legacy field; use tool_loading_mode instead. Writing true is equivalent to tool_loading_mode=search, and false to all; if both are provided, tool_loading_mode takes precedence. On read, returns whether the tool loading mode is anything other than loading all tools. (Optional)
```

```
  "toolLoadingMode"?:  // Tool loading mode: auto (selected automatically based on the number of tools available for the current turn and the model), all (load all), or search (dynamic search). New assistants default to auto; existing assistants without an explicit setting return the value derived from the legacy toggle (on → search, off → all).

* `auto` - Auto
* `all` - Load all
* `search` - Dynamic search (Optional)
  {
  }
  "maxAgentIterations"?: integer // Maximum number of iterations for AgentWorkflow (1-100, default: 20) (Optional)
  "agentTimeoutSeconds"?: integer // Timeout in seconds for AgentWorkflow execution (30-1200, default: 600) (Optional)
  "agentTimeoutMessage"?: string // Custom user-facing message shown when AgentWorkflow times out (max 500 chars). Leave empty to use the system default. (Optional)
  "requireTextWithFlexCards"?: boolean // When enabled, a turn that would end with only Flex Message cards and no text for the user is re-issued to the LLM once, asking it to write the text first and then send the card. Each retry incurs a second billing for the same prompt. (Optional)
  "isMultimodalLlm": boolean // Whether the chatbot LLM supports multimodal (read-only)
  "enableSizeBasedToolResultTruncation"?: boolean // When enabled, tool results exceeding the character threshold are kept as head+tail (with the identifiers found in the cut part) when written to conversation history; knowledge base, SQL and conversation search results keep their 100-character cut either way. Reduces memory bloat from large tool outputs (code interpreter bash stdout, web search results, etc.). (Optional)
  "toolResultMaxChars"?: integer // Character threshold for size-based tool result truncation (500-50000). Only effective when enable_size_based_tool_result_truncation is True. (Optional)
  "enableVectorMemory"?: boolean // When enabled, archived messages are vectorized and processed by fact extraction for semantic retrieval (existing behavior). When disabled, archived messages are discarded and only the active chat history window is used for multi-turn context. (Optional)
  "longTermMemoryTopK"?: integer // Number of long-term memory nodes returned per retrieval (similarity_top_k for vector retrieval); default: 10, range: 1–50 (Optional)
  "enableCrossConversationSearch"?: boolean // When enabled, the conversation history tools also reach this contact's other conversations in the same inbox, within the lookback window. When disabled, they only reach the current conversation. (Optional)
  "crossConversationLookbackDays"?: integer // How far back cross-conversation search may reach, measured from each conversation's last message (1-365 days). Leave empty to fall back to 90 days. Only effective when enable_cross_conversation_search is True. (Optional)
  "useGatewayFallback"?: boolean // When enabled, use the fallback group instead of the single LLM (Optional)
  "gatewayFallbackGroup"?: string (uuid) // Optional
  "enableSearchMessagesTool"?: boolean // Allow the AI to search past messages in the current conversation. (Optional)
  "enableGetMessageContextTool"?: boolean // Allow the AI to retrieve messages surrounding a specific message for context. (Optional)
  "enableReadAttachmentFullTextTool"?: boolean // Allow the AI to read the full text of plain-text attachments. AGENT mode only. (Optional)
  "enableParseAttachmentContentTool"?: boolean // Allow the AI to parse PDF, Office, audio, and other attachments. AGENT mode only. (Optional)
  "enableListAvailableParsersTool"?: boolean // Allow the AI to list available parsers and their capabilities. AGENT mode only. (Optional)
  "enableGetDownloadLinkTool"?: boolean // Allow the AI to generate shareable download links for produced content. AGENT mode only. (Optional)
  "isLocked": boolean // Locked instance: config follows the official version; only the dedicated KB can be modified
```

```
  "sourceBuildInAgent": string (uuid) // Points to the official Build-in Agent blueprint when
instantiated by a rental
  "canUpdate": boolean // Return whether the current user can update this resource.
  "canDelete": boolean // Return whether the current user can delete this resource.
  "team":
  {
    "id": string (uuid)
    "name": string
  }
  "webChatIsActive"?: boolean // Optional, create only. Whether the web widget channel starts
active. Omitted or null: follows the organization's default for new chatbot channels (inactive
unless a platform admin turned it on). Ignored on update; change an existing channel from its
channel settings instead. (Optional)
  "apiIsActive"?: boolean // Optional, create only. Whether the API channel starts active.
Omitted or null: follows the organization's default for new chatbot channels (inactive unless a
platform admin turned it on). Ignored on update; change an existing channel from its channel
settings instead. The backstage (admin) channel always starts active and cannot be set here.
(Optional)
  "fileWorkspaceMode"?:  // File workspace mode in Work internal conversations: none, bound or
user_mount.

* `none` - None
* `bound` - Bound workspace
* `user_mount` - User mount (Optional)
  {
  }
  "fileWorkspaceFolder"?: string (uuid) // The bound workspace (folder id); required when the
mode is bound, cleared otherwise. (Optional)
  "fileWorkspaceStatus": object // Read-only. {"folder": {"id", "name"} | null, "state": "ok" |
"missing" | "builder_lost_edit" | null}
  "fileWorkspaceAvailable": boolean // Read-only. Whether the organization has the file library
and this agent can configure a file workspace.
}
```

Example Response Values

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "name": "Response string",
  "largeLanguageModel": "550e8400-e29b-41d4-a716-446655440000",
  "llm": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Response string",
    "retiresAt": "Response string",
    "replacement": {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "Response string"
    }
  },
  "condenseQuestionLlm": "550e8400-e29b-41d4-a716-446655440000",
  "defaultCondenseQuestionLlm": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Response string"
  },
  "organizationEnforcedSettings": [
```

```
    "Response string"
  ],
  "embeddingModel": "550e8400-e29b-41d4-a716-446655440000",
  "rerankerModel": "550e8400-e29b-41d4-a716-446655440000",
  "instructions": "Response string",
  "knowledgeBases": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "Response string"
    }
  ],
  "databases": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "Response string"
    }
  ],
  "updatedAt": "Response string",
  "organization": "550e8400-e29b-41d4-a716-446655440000",
  "replyMode": {},
  "template": "Response string",
  "unanswerableTemplate": "Response string",
  "totalWordsCount": 456,
  "outputMode": {},
  "rawOutputFormat": null,
  "groups": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "Response string"
    }
  ],
  "tools": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "Response string",
      "description": "Response string",
      "displayName": "Response string",
      "toolType": "Response string"
    }
  ],
  "skills": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "Response string",
      "description": "Response string"
    }
  ],
  "connectors": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "Response string"
    }
  ],
  "agentMode": {},
  "numberOfRetrievedChunks": 456,
  "defaultLabelRelations": null,
  "useFullRetrievalRange": false,
```

```
  "enableEvaluation": false,
  "enableInlineCitations": false,
  "enableCodeInterpreter": false,
  "enableBrowserTool": false,
  "enableImageSearch": false,
  "enableClaudeStreamRetry": false,
  "customMaxLlmOutputTokens": 456,
  "voiceConfig": {
    "enabled": false,
    "voiceAgentType": "550e8400-e29b-41d4-a716-446655440000",
    "sttProvider": "550e8400-e29b-41d4-a716-446655440000",
    "sttConfig": null,
    "ttsProvider": "550e8400-e29b-41d4-a716-446655440000",
    "ttsConfig": null,
    "realtimeProvider": "550e8400-e29b-41d4-a716-446655440000",
    "realtimeConfig": null,
    "realtimeInstructions": "Response string",
    "turnHandling": null,
    "enableVoiceReply": false
  },
  "thinkingConfig": null,
  "enableToolSearching": false,
  "toolLoadingMode": {},
  "maxAgentIterations": 456,
  "agentTimeoutSeconds": 456,
  "agentTimeoutMessage": "Response string",
  "requireTextWithFlexCards": false,
  "isMultimodalLlm": false,
  "enableSizeBasedToolResultTruncation": false,
  "toolResultMaxChars": 456,
  "enableVectorMemory": false,
  "longTermMemoryTopK": 456,
  "enableCrossConversationSearch": false,
  "crossConversationLookbackDays": 456,
  "useGatewayFallback": false,
  "gatewayFallbackGroup": "550e8400-e29b-41d4-a716-446655440000",
  "enableSearchMessagesTool": false,
  "enableGetMessageContextTool": false,
  "enableReadAttachmentFullTextTool": false,
  "enableParseAttachmentContentTool": false,
  "enableListAvailableParsersTool": false,
  "enableGetDownloadLinkTool": false,
  "isLocked": false,
  "sourceBuildInAgent": "550e8400-e29b-41d4-a716-446655440000",
  "canUpdate": false,
  "canDelete": false,
  "team": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Response string"
  },
  "webChatIsActive": false,
  "apiIsActive": false,
  "fileWorkspaceMode": {},
  "fileWorkspaceFolder": "550e8400-e29b-41d4-a716-446655440000",
  "fileWorkspaceStatus": {
    "name": "example.pdf",
    "content": "base64encoded_content",
```

```
    "contentType": "application/pdf"
  },
  "fileWorkspaceAvailable": false
}
```


Update AI Assistant

PUT `/api/v1/chatbots/{id}`

Parameters

Parameter Name	Required	Type	Description
`id`	V	string	

Request Body

Request Parameters

Field	Type	Required	Description
name	string	Yes	Chatbot name. In Agent mode it carries semantic meaning; in other modes it only distinguishes chatbots.
largeLanguageModel	string (uuid)	Yes	The large language model the chatbot uses to generate responses (including custom AI Gateway models created by the organization); may be omitted on creation only if the organization has set a default model in its AI assistant defaults
condenseQuestionLlm	string (uuid)	No	Question rewriting model: rewrites follow-up questions into standalone questions before retrieval in RAG response mode; null uses the system settings (if the selected model is later blocked or disabled by the organization, reads also return null and use the system settings)
embeddingModel	string (uuid)	No	Optional embedding model for vectorizing text
rerankerModel	string (uuid)	No	Optional model for reranking

Field	Type	Required	Description
instructions	string	No	Role instructions describing the chatbot's role and behavior.
knowledgeBases	array[IdName]	No	List of knowledge bases accessible to the chatbot
databases	array[IdName]	No	List of SQL databases accessible to the chatbot (for Text-to-SQL)
organization	string (uuid)	No	The organization the chatbot belongs to; if empty, this is a personal chatbot
replyMode	object	No	Response mode: normal or streaming responses `normal` : Normal ; `template` : Template ; `hybrid` : Hybrid ; `agent` : Agent;
template	string	No	Template used by Template and Hybrid modes.
unanswerableTemplate	string	No	Template used by Template and Hybrid modes when the question cannot be answered.
totalWordsCount	integer (int64)	No	Accumulated total word count used.
outputMode	object	No	Output mode: text, table, or custom format `text` : Text ; `json_schema` : JSON Schema;
rawOutputFormat	object	No	JSON structure definition for the custom output format
groups	array[IdName]	No	List of groups accessible to the chatbot
tools	array[ToolSummary]	No	List of tools available to the chatbot
skills	array[SkillSummary]	No	List of skills associated with the chatbot
connectors	array[IdName]	No	Connectors associated with this chatbot, gating per-contact OAuth authorization
agentMode	object	No	Agent mode: normal, SQL, or workflow mode `normal` : Normal ; `canvas` : Canvas ; `team` : Team;
numberOfRetrievedChunks	integer	No	Number of retrieved reference chunks; defaults to 12, minimum 1
defaultLabelRelations	object	No	Assistant-level default knowledge base label filters, in the same format as query_metadata.label_relations; null means no filtering. Applied as the lowest-priority fallback only when the caller omits query_metadata.
useFullRetrievalRange	boolean	No	When enabled, ignores the LLM top_k truncation and returns the full reranker results

Field	Type	Required	Description
enableEvaluation	boolean	No	
enableInlineCitations	boolean	No	Enables inline citations, inserting citation markers such as [1][2] into responses.
enableCodeInterpreter	boolean	No	When enabled, provides the Code Interpreter tool to run code in an isolated container.
enableBrowserTool	boolean	No	Enable browser automation tool for web tasks
enableImageSearch	boolean	No	Provide the image_search tool when any attached knowledge base uses a multimodal embedding model. Disable to remove the tool entirely.
enableClaudeStreamRetry	boolean	No	When a Claude streaming call stalls (first-chunk or mid-stream), abort and re-issue the call once in non-streaming mode. Mid-stream retries send a reset signal so the client discards any partial outpu...
customMaxLlmOutputTokens	integer	No	Custom maximum number of LLM output tokens; minimum 512
voiceConfig	object	No	
voiceConfig.enabled	boolean	No	Whether this chatbot can be used as a voice agent. Checked by every conversation platform (WebChat, SIP phone, admin/marketplace voice test) instead of a per-platform toggle.
voiceConfig.voiceAgentType	string (uuid)	No	Voice agent mode type.
voiceConfig.sttProvider	string (uuid)	No	Speech-to-Text service provider.
voiceConfig.sttConfig	object	No	STT configuration parameters (JSON).
voiceConfig.ttsProvider	string (uuid)	No	Text-to-Speech service provider.
voiceConfig.ttsConfig	object	No	TTS configuration parameters (JSON).
voiceConfig.realtimeProvider	string (uuid)	No	Realtime end-to-end voice model provider.
voiceConfig.realtimeConfig	object	No	Realtime configuration parameters (JSON).
voiceConfig.realtimeInstructions	string	No	Prompt dedicated to the realtime voice session; falls back to chatbot instructions when empty
voiceConfig.turnHandling	object	No	Turn-taking and interruption settings for the voice agent.
voiceConfig.enableVoiceReply	boolean	No	When disabled, the voice agent replies in text only and does not speak

Field	Type	Required	Description
thinkingConfig	object	No	Reasoning level: null (model default) or {"reasoning_effort": "off
enableToolSearching	boolean	No	Legacy field; use tool_loading_mode instead. Writing true is equivalent to tool_loading_mode=search, and false to all; when both are provided, tool_loading_mode takes precedence. On read, returns whether the tool loading mode is anything other than loading all tools.
toolLoadingMode	object	No	Tool loading mode: auto (determined automatically by the number of available tools and the model for the current turn), all (load all), or search (dynamic search). New assistants default to auto; existing assistants that have never configured this return a value derived from the legacy toggle (on→search, off→all). `auto` : Auto ; `all` : Load all ; `search` : Dynamic search;
maxAgentIterations	integer	No	Maximum number of iterations for AgentWorkflow (1-100, default: 20)
agentTimeoutSeconds	integer	No	Timeout in seconds for AgentWorkflow execution (30-1200, default: 600)
agentTimeoutMessage	string	No	Custom user-facing message shown when AgentWorkflow times out (max 500 chars). Leave empty to use the system default.
requireTextWithFlexCards	boolean	No	When enabled, a turn that would end with only Flex Message cards and no text for the user is re-issued to the LLM once, asking it to write the text first and then send the card. Each retry incurs a se...
enableSizeBasedToolResultTruncation	boolean	No	When enabled, tool results exceeding the character threshold are kept as head+tail (with the identifiers found in the cut part) when written to conversation history; knowledge base, SQL and conversati...
toolResultMaxChars	integer	No	Character threshold for size-based tool result truncation (500-50000). Only effective when enable_size_based_tool_result_truncation is True.
enableVectorMemory	boolean	No	When enabled, archived messages are vectorized and processed by fact extraction for semantic retrieval (existing behavior). When disabled, archived messages are discarded and only the active chat hist...

Field	Type	Required	Description
longTermMemoryTopK	integer	No	Number of memory nodes returned per long-term memory retrieval (similarity_top_k for vector retrieval); defaults to 10, range 1–50
enableCrossConversationSearch	boolean	No	When enabled, the conversation history tools also reach this contact's other conversations in the same inbox, within the lookback window. When disabled, they only reach the current conversation.
crossConversationLookbackDays	integer	No	How far back cross-conversation search may reach, measured from each conversation's last message (1-365 days). Leave empty to fall back to 90 days. Only effective when enable_cross_conversation_search...
useGatewayFallback	boolean	No	When enabled, use the fallback group instead of the single LLM
gatewayFallbackGroup	string (uuid)	No	
enableSearchMessagesTool	boolean	No	Allow the AI to search past messages in the current conversation.
enableGetMessageContextTool	boolean	No	Allow the AI to retrieve messages surrounding a specific message for context.
enableReadAttachmentFullTextTool	boolean	No	Allow the AI to read the full text of plain-text attachments. AGENT mode only.
enableParseAttachmentContentTool	boolean	No	Allow the AI to parse PDF, Office, audio, and other attachments. AGENT mode only.
enableListAvailableParsersTool	boolean	No	Allow the AI to list available parsers and their capabilities. AGENT mode only.
enableGetDownloadLinkTool	boolean	No	Allow the AI to generate shareable download links for produced content. AGENT mode only.
webChatIsActive	boolean	No	Optional, create only. Whether the web widget channel starts active. Omitted or null: follows the organization's default for new chatbot channels (inactive unless a platform admin turned it on). Ignor...
apiIsActive	boolean	No	Optional, create only. Whether the API channel starts active. Omitted or null: follows the organization's default for new chatbot channels (inactive unless a platform admin turned it on). Ignored on u...
fileWorkspaceMode	object	No	File workspace mode in Work internal conversations: none, bound or

Field	Type	Required	Description
			user_mount. `none` : None ; `bound` : Bound workspace ; `user_mount` : User mount;
fileWorkspaceFolder	string (uuid)	No	The bound workspace (folder id); required when the mode is bound, cleared otherwise.

Request Schema Example

```
{
  "name": string // Chatbot name. In Agent mode it carries semantic meaning; in other modes it only distinguishes chatbots.
  "largeLanguageModel": string (uuid) // The large language model the chatbot uses to generate responses (including custom AI Gateway models created by the organization); may be omitted on creation only if the organization has set a default model in its AI assistant defaults
  "condenseQuestionLlm"?: string (uuid) // Question rewriting model: rewrites follow-up questions into standalone questions before retrieval in RAG response mode; null uses the system settings (if the selected model is later blocked or disabled by the organization, reads also return null and use the system settings) (Optional)
  "embeddingModel"?: string (uuid) // Optional embedding model for vectorizing text (Optional)
  "rerankerModel"?: string (uuid) // Optional model for reranking (Optional)
  "instructions"?: string // Role instructions describing the chatbot's role and behavior. (Optional)
  "knowledgeBases"?: [ // List of knowledge bases accessible to the chatbot (Optional)
    {
      "id": string (uuid)
    }
  ]
  "databases"?: [ // List of SQL databases accessible to the chatbot (for Text-to-SQL) (Optional)
    {
      "id": string (uuid)
    }
  ]
  "organization"?: string (uuid) // The organization the chatbot belongs to; if empty, this is a personal chatbot (Optional)
  "replyMode"?:  // Response mode: normal or streaming responses

* `normal` - Normal
* `template` - Template
* `hybrid` - Hybrid
* `agent` - Agent (Optional)
  {
  }
  "template"?: string // Template used by Template and Hybrid modes. (Optional)
  "unanswerableTemplate"?: string // Template used by Template and Hybrid modes when the question cannot be answered. (Optional)
  "totalWordsCount"?: integer (int64) // Accumulated total word count used. (Optional)
  "outputMode"?:  // Output mode: text, table, or custom format

* `text` - Text
* `json_schema` - JSON Schema (Optional)
  {
  }
```

```
  "rawOutputFormat"?: object // JSON structure definition for the custom output format
(Optional)
  "groups"?: [ // List of groups accessible to the chatbot (Optional)
    {
      "id": string (uuid)
    }
  ]
  "tools"?: [ // List of tools available to the chatbot (Optional)
    {
      "id": string (uuid)
    }
  ]
  "skills"?: [ // List of skills associated with the chatbot (Optional)
    {
      "id": string (uuid)
    }
  ]
  "connectors"?: [ // Connectors associated with this chatbot, gating per-contact OAuth
authorization (Optional)
    {
      "id": string (uuid)
    }
  ]
  "agentMode"?:  // Agent mode: normal, SQL, or workflow mode

* `normal` - Normal
* `canvas` - Canvas
* `team` - Team (Optional)
  {
  }
  "numberOfRetrievedChunks"?: integer // Number of retrieved reference chunks; defaults to 12,
minimum 1 (Optional)
  "defaultLabelRelations"?: object // Assistant-level default knowledge base label filters, in
the same format as query_metadata.label_relations; null means no filtering. Applied as the
lowest-priority fallback only when the caller omits query_metadata. (Optional)
  "useFullRetrievalRange"?: boolean // When enabled, ignores the LLM top_k truncation and
returns the full reranker results (Optional)
  "enableEvaluation"?: boolean // Optional
  "enableInlineCitations"?: boolean // Enables inline citations, inserting citation markers
such as [1][2] into responses. (Optional)
  "enableCodeInterpreter"?: boolean // When enabled, provides the Code Interpreter tool to run
code in an isolated container. (Optional)
  "enableBrowserTool"?: boolean // Enable browser automation tool for web tasks (Optional)
  "enableImageSearch"?: boolean // Provide the image_search tool when any attached knowledge
base uses a multimodal embedding model. Disable to remove the tool entirely. (Optional)
  "enableClaudeStreamRetry"?: boolean // When a Claude streaming call stalls (first-chunk or
mid-stream), abort and re-issue the call once in non-streaming mode. Mid-stream retries send a
reset signal so the client discards any partial output already rendered. Each retry incurs a
second billing for the same prompt. (Optional)
  "customMaxLlmOutputTokens"?: integer // Custom maximum number of LLM output tokens; minimum
512 (Optional)
  "voiceConfig"?: { // Optional
  {
    "enabled"?: boolean // Whether this chatbot can be used as a voice agent. Checked by every
conversation platform (WebChat, SIP phone, admin/marketplace voice test) instead of a per-
platform toggle. (Optional)
    "voiceAgentType"?: string (uuid) // Voice agent mode type. (Optional)
```

```
    "sttProvider"?: string (uuid) // Speech-to-Text service provider. (Optional)
    "sttConfig"?: object // STT configuration parameters (JSON). (Optional)
    "ttsProvider"?: string (uuid) // Text-to-Speech service provider. (Optional)
    "ttsConfig"?: object // TTS configuration parameters (JSON). (Optional)
    "realtimeProvider"?: string (uuid) // Realtime end-to-end voice model provider. (Optional)
    "realtimeConfig"?: object // Realtime configuration parameters (JSON). (Optional)
    "realtimeInstructions"?: string // Prompt dedicated to the realtime voice session; falls back to chatbot instructions when empty (Optional)
    "turnHandling"?: object // Turn-taking and interruption settings for the voice agent. (Optional)
    "enableVoiceReply"?: boolean // When disabled, the voice agent replies in text only and does not speak (Optional)
  }
  }
  "thinkingConfig"?: object // Reasoning level: null (model default) or {"reasoning_effort": "off|minimal|low|medium|high|xhigh|max"} (Optional)
  "enableToolSearching"?: boolean // Legacy field; use tool_loading_mode instead. Writing true is equivalent to tool_loading_mode=search, and false to all; when both are provided, tool_loading_mode takes precedence. On read, returns whether the tool loading mode is anything other than loading all tools. (Optional)
  "toolLoadingMode"?:  // Tool loading mode: auto (determined automatically by the number of available tools and the model for the current turn), all (load all), or search (dynamic search). New assistants default to auto; existing assistants that have never configured this return a value derived from the legacy toggle (on→search, off→all).

* `auto` - Auto
* `all` - Load all
* `search` - Dynamic search (Optional)
  {
  }
  "maxAgentIterations"?: integer // Maximum number of iterations for AgentWorkflow (1-100, default: 20) (Optional)
  "agentTimeoutSeconds"?: integer // Timeout in seconds for AgentWorkflow execution (30-1200, default: 600) (Optional)
  "agentTimeoutMessage"?: string // Custom user-facing message shown when AgentWorkflow times out (max 500 chars). Leave empty to use the system default. (Optional)
  "requireTextWithFlexCards"?: boolean // When enabled, a turn that would end with only Flex Message cards and no text for the user is re-issued to the LLM once, asking it to write the text first and then send the card. Each retry incurs a second billing for the same prompt. (Optional)
  "enableSizeBasedToolResultTruncation"?: boolean // When enabled, tool results exceeding the character threshold are kept as head+tail (with the identifiers found in the cut part) when written to conversation history; knowledge base, SQL and conversation search results keep their 100-character cut either way. Reduces memory bloat from large tool outputs (code interpreter bash stdout, web search results, etc.). (Optional)
  "toolResultMaxChars"?: integer // Character threshold for size-based tool result truncation (500-50000). Only effective when enable_size_based_tool_result_truncation is True. (Optional)
  "enableVectorMemory"?: boolean // When enabled, archived messages are vectorized and processed by fact extraction for semantic retrieval (existing behavior). When disabled, archived messages are discarded and only the active chat history window is used for multi-turn context. (Optional)
  "longTermMemoryTopK"?: integer // Number of memory nodes returned per long-term memory retrieval (similarity_top_k for vector retrieval); defaults to 10, range 1–50 (Optional)
  "enableCrossConversationSearch"?: boolean // When enabled, the conversation history tools also reach this contact's other conversations in the same inbox, within the lookback window. When disabled, they only reach the current conversation. (Optional)
  "crossConversationLookbackDays"?: integer // How far back cross-conversation search may
```

```
reach, measured from each conversation's last message (1-365 days). Leave empty to fall back to 90 days. Only effective when enable_cross_conversation_search is True. (Optional)
  "useGatewayFallback"?: boolean // When enabled, use the fallback group instead of the single LLM (Optional)
  "gatewayFallbackGroup"?: string (uuid) // Optional
  "enableSearchMessagesTool"?: boolean // Allow the AI to search past messages in the current conversation. (Optional)
  "enableGetMessageContextTool"?: boolean // Allow the AI to retrieve messages surrounding a specific message for context. (Optional)
  "enableReadAttachmentFullTextTool"?: boolean // Allow the AI to read the full text of plain-text attachments. AGENT mode only. (Optional)
  "enableParseAttachmentContentTool"?: boolean // Allow the AI to parse PDF, Office, audio, and other attachments. AGENT mode only. (Optional)
  "enableListAvailableParsersTool"?: boolean // Allow the AI to list available parsers and their capabilities. AGENT mode only. (Optional)
  "enableGetDownloadLinkTool"?: boolean // Allow the AI to generate shareable download links for produced content. AGENT mode only. (Optional)
  "webChatIsActive"?: boolean // Optional, create only. Whether the web widget channel starts active. Omitted or null: follows the organization's default for new chatbot channels (inactive unless a platform admin turned it on). Ignored on update; change an existing channel from its channel settings instead. (Optional)
  "apiIsActive"?: boolean // Optional, create only. Whether the API channel starts active. Omitted or null: follows the organization's default for new chatbot channels (inactive unless a platform admin turned it on). Ignored on update; change an existing channel from its channel settings instead. The backstage (admin) channel always starts active and cannot be set here. (Optional)
  "fileWorkspaceMode"?:  // File workspace mode in Work internal conversations: none, bound or user_mount.

* `none` - None
* `bound` - Bound workspace
* `user_mount` - User mount (Optional)
  {
  }
  "fileWorkspaceFolder"?: string (uuid) // The bound workspace (folder id); required when the mode is bound, cleared otherwise. (Optional)
}
```

Example Request Values

```
{
  "name": "Example name",
  "largeLanguageModel": "550e8400-e29b-41d4-a716-446655440000",
  "condenseQuestionLlm": "550e8400-e29b-41d4-a716-446655440000",
  "embeddingModel": "550e8400-e29b-41d4-a716-446655440000",
  "rerankerModel": "550e8400-e29b-41d4-a716-446655440000",
  "instructions": "Example string",
  "knowledgeBases": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000"
    }
  ],
  "databases": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000"
```

```
    }
  ],
  "organization": "550e8400-e29b-41d4-a716-446655440000",
  "replyMode": {},
  "template": "Example string",
  "unanswerableTemplate": "Example string",
  "totalWordsCount": 123,
  "outputMode": {},
  "rawOutputFormat": null,
  "groups": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000"
    }
  ],
  "tools": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000"
    }
  ],
  "skills": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000"
    }
  ],
  "connectors": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000"
    }
  ],
  "agentMode": {},
  "numberOfRetrievedChunks": 123,
  "defaultLabelRelations": null,
  "useFullRetrievalRange": true,
  "enableEvaluation": true,
  "enableInlineCitations": true,
  "enableCodeInterpreter": true,
  "enableBrowserTool": true,
  "enableImageSearch": true,
  "enableClaudeStreamRetry": true,
  "customMaxLlmOutputTokens": 123,
  "voiceConfig": {
    "enabled": true,
    "voiceAgentType": "550e8400-e29b-41d4-a716-446655440000",
    "sttProvider": "550e8400-e29b-41d4-a716-446655440000",
    "sttConfig": null,
    "ttsProvider": "550e8400-e29b-41d4-a716-446655440000",
    "ttsConfig": null,
    "realtimeProvider": "550e8400-e29b-41d4-a716-446655440000",
    "realtimeConfig": null,
    "realtimeInstructions": "Example string",
    "turnHandling": null,
    "enableVoiceReply": true
  },
  "thinkingConfig": null,
  "enableToolSearching": true,
  "toolLoadingMode": {},
  "maxAgentIterations": 123,
```

```
  "agentTimeoutSeconds": 123,
  "agentTimeoutMessage": "Example string",
  "requireTextWithFlexCards": true,
  "enableSizeBasedToolResultTruncation": true,
  "toolResultMaxChars": 123,
  "enableVectorMemory": true,
  "longTermMemoryTopK": 123,
  "enableCrossConversationSearch": true,
  "crossConversationLookbackDays": 123,
  "useGatewayFallback": true,
  "gatewayFallbackGroup": "550e8400-e29b-41d4-a716-446655440000",
  "enableSearchMessagesTool": true,
  "enableGetMessageContextTool": true,
  "enableReadAttachmentFullTextTool": true,
  "enableParseAttachmentContentTool": true,
  "enableListAvailableParsersTool": true,
  "enableGetDownloadLinkTool": true,
  "webChatIsActive": true,
  "apiIsActive": true,
  "fileWorkspaceMode": {},
  "fileWorkspaceFolder": "550e8400-e29b-41d4-a716-446655440000"
}
```


Code Examples

Shell/Bash

```
# API call example (Shell)
curl -X PUT "

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "name": "Example name",
    "largeLanguageModel": "550e8400-e29b-41d4-a716-446655440000",
    "condenseQuestionLlm": "550e8400-e29b-41d4-a716-446655440000",
    "embeddingModel": "550e8400-e29b-41d4-a716-446655440000",
    "rerankerModel": "550e8400-e29b-41d4-a716-446655440000",
    "instructions": "Example string",
    "knowledgeBases": [
      {
        "id": "550e8400-e29b-41d4-a716-446655440000"
      }
    ],
    "databases": [
      {
        "id": "550e8400-e29b-41d4-a716-446655440000"
      }
    ],
    "organization": "550e8400-e29b-41d4-a716-446655440000",
    "replyMode": {},
    "template": "Example string",
    "unanswerableTemplate": "Example string",
    "totalWordsCount": 123,
    "outputMode": {},
    "rawOutputFormat": null,
    "groups": [
      {
        "id": "550e8400-e29b-41d4-a716-446655440000"
      }
    ],
    "tools": [
      {
        "id": "550e8400-e29b-41d4-a716-446655440000"
      }
    ],
    "skills": [
      {
        "id": "550e8400-e29b-41d4-a716-446655440000"
      }
    ],
    "connectors": [
      {
        "id": "550e8400-e29b-41d4-a716-446655440000"
      }
    ],
```

```
      "agentMode": {},
      "numberOfRetrievedChunks": 123,
      "defaultLabelRelations": null,
      "useFullRetrievalRange": true,
      "enableEvaluation": true,
      "enableInlineCitations": true,
      "enableCodeInterpreter": true,
      "enableBrowserTool": true,
      "enableImageSearch": true,
      "enableClaudeStreamRetry": true,
      "customMaxLlmOutputTokens": 123,
      "voiceConfig": {
        "enabled": true,
        "voiceAgentType": "550e8400-e29b-41d4-a716-446655440000",
        "sttProvider": "550e8400-e29b-41d4-a716-446655440000",
        "sttConfig": null,
        "ttsProvider": "550e8400-e29b-41d4-a716-446655440000",
        "ttsConfig": null,
        "realtimeProvider": "550e8400-e29b-41d4-a716-446655440000",
        "realtimeConfig": null,
        "realtimeInstructions": "Example string",
        "turnHandling": null,
        "enableVoiceReply": true
      },
      "thinkingConfig": null,
      "enableToolSearching": true,
      "toolLoadingMode": {},
      "maxAgentIterations": 123,
      "agentTimeoutSeconds": 123,
      "agentTimeoutMessage": "Example string",
      "requireTextWithFlexCards": true,
      "enableSizeBasedToolResultTruncation": true,
      "toolResultMaxChars": 123,
      "enableVectorMemory": true,
      "longTermMemoryTopK": 123,
      "enableCrossConversationSearch": true,
      "crossConversationLookbackDays": 123,
      "useGatewayFallback": true,
      "gatewayFallbackGroup": "550e8400-e29b-41d4-a716-446655440000",
      "enableSearchMessagesTool": true,
      "enableGetMessageContextTool": true,
      "enableReadAttachmentFullTextTool": true,
      "enableParseAttachmentContentTool": true,
      "enableListAvailableParsersTool": true,
      "enableGetDownloadLinkTool": true,
      "webChatIsActive": true,
      "apiIsActive": true,
      "fileWorkspaceMode": {},
      "fileWorkspaceFolder": "550e8400-e29b-41d4-a716-446655440000"
    }'

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// Request body (payload)
const data = {
    "name": "Example name",
    "largeLanguageModel": "550e8400-e29b-41d4-a716-446655440000",
    "condenseQuestionLlm": "550e8400-e29b-41d4-a716-446655440000",
    "embeddingModel": "550e8400-e29b-41d4-a716-446655440000",
    "rerankerModel": "550e8400-e29b-41d4-a716-446655440000",
    "instructions": "Example string",
    "knowledgeBases": [
      {
        "id": "550e8400-e29b-41d4-a716-446655440000"
      }
    ],
    "databases": [
      {
        "id": "550e8400-e29b-41d4-a716-446655440000"
      }
    ],
    "organization": "550e8400-e29b-41d4-a716-446655440000",
    "replyMode": {},
    "template": "Example string",
    "unanswerableTemplate": "Example string",
    "totalWordsCount": 123,
    "outputMode": {},
    "rawOutputFormat": null,
    "groups": [
      {
        "id": "550e8400-e29b-41d4-a716-446655440000"
      }
    ],
    "tools": [
      {
        "id": "550e8400-e29b-41d4-a716-446655440000"
      }
    ],
    "skills": [
      {
        "id": "550e8400-e29b-41d4-a716-446655440000"
      }
    ],
    "connectors": [
```

```
        {
          "id": "550e8400-e29b-41d4-a716-446655440000"
        }
      ],
      "agentMode": {},
      "numberOfRetrievedChunks": 123,
      "defaultLabelRelations": null,
      "useFullRetrievalRange": true,
      "enableEvaluation": true,
      "enableInlineCitations": true,
      "enableCodeInterpreter": true,
      "enableBrowserTool": true,
      "enableImageSearch": true,
      "enableClaudeStreamRetry": true,
      "customMaxLlmOutputTokens": 123,
      "voiceConfig": {
        "enabled": true,
        "voiceAgentType": "550e8400-e29b-41d4-a716-446655440000",
        "sttProvider": "550e8400-e29b-41d4-a716-446655440000",
        "sttConfig": null,
        "ttsProvider": "550e8400-e29b-41d4-a716-446655440000",
        "ttsConfig": null,
        "realtimeProvider": "550e8400-e29b-41d4-a716-446655440000",
        "realtimeConfig": null,
        "realtimeInstructions": "Example string",
        "turnHandling": null,
        "enableVoiceReply": true
      },
      "thinkingConfig": null,
      "enableToolSearching": true,
      "toolLoadingMode": {},
      "maxAgentIterations": 123,
      "agentTimeoutSeconds": 123,
      "agentTimeoutMessage": "Example string",
      "requireTextWithFlexCards": true,
      "enableSizeBasedToolResultTruncation": true,
      "toolResultMaxChars": 123,
      "enableVectorMemory": true,
      "longTermMemoryTopK": 123,
      "enableCrossConversationSearch": true,
      "crossConversationLookbackDays": 123,
      "useGatewayFallback": true,
      "gatewayFallbackGroup": "550e8400-e29b-41d4-a716-446655440000",
      "enableSearchMessagesTool": true,
      "enableGetMessageContextTool": true,
      "enableReadAttachmentFullTextTool": true,
      "enableParseAttachmentContentTool": true,
      "enableListAvailableParsersTool": true,
      "enableGetDownloadLinkTool": true,
      "webChatIsActive": true,
      "apiIsActive": true,
      "fileWorkspaceMode": {},
      "fileWorkspaceFolder": "550e8400-e29b-41d4-a716-446655440000"
    };

  axios.put(" data, config)
    .then(response => {
```

```
  console.log('Response received successfully:');
  console.log(response.data);
})
.catch(error => {
  console.error('Request error:');
  console.error(error.response?.data || error.message);
});
```

Python

```
import requests

url = "
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# Request body (payload)
data = {
    "name": "Example name",
    "largeLanguageModel": "550e8400-e29b-41d4-a716-446655440000",
    "condenseQuestionLlm": "550e8400-e29b-41d4-a716-446655440000",
    "embeddingModel": "550e8400-e29b-41d4-a716-446655440000",
    "rerankerModel": "550e8400-e29b-41d4-a716-446655440000",
    "instructions": "Example string",
    "knowledgeBases": [
        {
            "id": "550e8400-e29b-41d4-a716-446655440000"
        }
    ],
    "databases": [
        {
            "id": "550e8400-e29b-41d4-a716-446655440000"
        }
    ],
    "organization": "550e8400-e29b-41d4-a716-446655440000",
    "replyMode": {},
    "template": "Example string",
    "unanswerableTemplate": "Example string",
    "totalWordsCount": 123,
    "outputMode": {},
    "rawOutputFormat": None,
    "groups": [
        {
            "id": "550e8400-e29b-41d4-a716-446655440000"
        }
    ],
    "tools": [
        {
            "id": "550e8400-e29b-41d4-a716-446655440000"
        }
    ],
    "skills": [
        {
            "id": "550e8400-e29b-41d4-a716-446655440000"
        }
    ],
    "connectors": [
        {
            "id": "550e8400-e29b-41d4-a716-446655440000"
```

```
            }
        ],
        "agentMode": {},
        "numberOfRetrievedChunks": 123,
        "defaultLabelRelations": None,
        "useFullRetrievalRange": True,
        "enableEvaluation": True,
        "enableInlineCitations": True,
        "enableCodeInterpreter": True,
        "enableBrowserTool": True,
        "enableImageSearch": True,
        "enableClaudeStreamRetry": True,
        "customMaxLlmOutputTokens": 123,
        "voiceConfig": {
            "enabled": True,
            "voiceAgentType": "550e8400-e29b-41d4-a716-446655440000",
            "sttProvider": "550e8400-e29b-41d4-a716-446655440000",
            "sttConfig": None,
            "ttsProvider": "550e8400-e29b-41d4-a716-446655440000",
            "ttsConfig": None,
            "realtimeProvider": "550e8400-e29b-41d4-a716-446655440000",
            "realtimeConfig": None,
            "realtimeInstructions": "Example string",
            "turnHandling": None,
            "enableVoiceReply": True
        },
        "thinkingConfig": None,
        "enableToolSearching": True,
        "toolLoadingMode": {},
        "maxAgentIterations": 123,
        "agentTimeoutSeconds": 123,
        "agentTimeoutMessage": "Example string",
        "requireTextWithFlexCards": True,
        "enableSizeBasedToolResultTruncation": True,
        "toolResultMaxChars": 123,
        "enableVectorMemory": True,
        "longTermMemoryTopK": 123,
        "enableCrossConversationSearch": True,
        "crossConversationLookbackDays": 123,
        "useGatewayFallback": True,
        "gatewayFallbackGroup": "550e8400-e29b-41d4-a716-446655440000",
        "enableSearchMessagesTool": True,
        "enableGetMessageContextTool": True,
        "enableReadAttachmentFullTextTool": True,
        "enableParseAttachmentContentTool": True,
        "enableListAvailableParsersTool": True,
        "enableGetDownloadLinkTool": True,
        "webChatIsActive": True,
        "apiIsActive": True,
        "fileWorkspaceMode": {},
        "fileWorkspaceFolder": "550e8400-e29b-41d4-a716-446655440000"
    }

    response = requests.put(url, json=data, headers=headers)
    try:
        print("Response received successfully:")
        print(response.json())
```

```
    except Exception as e:
        print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->put(" [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'name' => 'Example name',
            'largeLanguageModel' => '550e8400-e29b-41d4-a716-446655440000',
            'condenseQuestionLlm' => '550e8400-e29b-41d4-a716-446655440000',
            'embeddingModel' => '550e8400-e29b-41d4-a716-446655440000',
            'rerankerModel' => '550e8400-e29b-41d4-a716-446655440000',
            'instructions' => 'Example string',
            'knowledgeBases' => [
                [
                    'id' => '550e8400-e29b-41d4-a716-446655440000'
                ]
            ],
            'databases' => [
                [
                    'id' => '550e8400-e29b-41d4-a716-446655440000'
                ]
            ],
            'organization' => '550e8400-e29b-41d4-a716-446655440000',
            'replyMode' => new \stdClass(),
            'template' => 'Example string',
            'unanswerableTemplate' => 'Example string',
            'totalWordsCount' => 123,
            'outputMode' => new \stdClass(),
            'rawOutputFormat' => null,
            'groups' => [
                [
                    'id' => '550e8400-e29b-41d4-a716-446655440000'
                ]
            ],
            'tools' => [
                [
                    'id' => '550e8400-e29b-41d4-a716-446655440000'
                ]
            ],
            'skills' => [
                [
                    'id' => '550e8400-e29b-41d4-a716-446655440000'
                ]
            ],
            'connectors' => [
```

```
                [
                    'id' => '550e8400-e29b-41d4-a716-446655440000'
                ]
            ],
            'agentMode' => new \stdClass(),
            'numberOfRetrievedChunks' => 123,
            'defaultLabelRelations' => null,
            'useFullRetrievalRange' => true,
            'enableEvaluation' => true,
            'enableInlineCitations' => true,
            'enableCodeInterpreter' => true,
            'enableBrowserTool' => true,
            'enableImageSearch' => true,
            'enableClaudeStreamRetry' => true,
            'customMaxLlmOutputTokens' => 123,
            'voiceConfig' => [
                'enabled' => true,
                'voiceAgentType' => '550e8400-e29b-41d4-a716-446655440000',
                'sttProvider' => '550e8400-e29b-41d4-a716-446655440000',
                'sttConfig' => null,
                'ttsProvider' => '550e8400-e29b-41d4-a716-446655440000',
                'ttsConfig' => null,
                'realtimeProvider' => '550e8400-e29b-41d4-a716-446655440000',
                'realtimeConfig' => null,
                'realtimeInstructions' => 'Example string',
                'turnHandling' => null,
                'enableVoiceReply' => true
            ],
            'thinkingConfig' => null,
            'enableToolSearching' => true,
            'toolLoadingMode' => new \stdClass(),
            'maxAgentIterations' => 123,
            'agentTimeoutSeconds' => 123,
            'agentTimeoutMessage' => 'Example string',
            'requireTextWithFlexCards' => true,
            'enableSizeBasedToolResultTruncation' => true,
            'toolResultMaxChars' => 123,
            'enableVectorMemory' => true,
            'longTermMemoryTopK' => 123,
            'enableCrossConversationSearch' => true,
            'crossConversationLookbackDays' => 123,
            'useGatewayFallback' => true,
            'gatewayFallbackGroup' => '550e8400-e29b-41d4-a716-446655440000',
            'enableSearchMessagesTool' => true,
            'enableGetMessageContextTool' => true,
            'enableReadAttachmentFullTextTool' => true,
            'enableParseAttachmentContentTool' => true,
            'enableListAvailableParsersTool' => true,
            'enableGetDownloadLinkTool' => true,
            'webChatIsActive' => true,
            'apiIsActive' => true,
            'fileWorkspaceMode' => new \stdClass(),
            'fileWorkspaceFolder' => '550e8400-e29b-41d4-a716-446655440000'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
```

```
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response body

Status code: 200

Example response structure

```
{
  "id": string (uuid)
  "name": string // Chatbot name. In Agent mode it carries semantic meaning; in other modes it only distinguishes chatbots.
  "largeLanguageModel": string (uuid) // Large language model used by the chatbot to generate responses (including custom AI Gateway models created by the organization); it can be omitted at creation only if the organization has configured a default model in its AI assistant defaults
  "llm":  // The bound model’s id, name, and retirement information, read directly from the FK; returned even if the organization has disabled the model
  {
    "id": string (uuid)
    "name": string
    "retiresAt": string (date) // Provider retirement date; once reached, the daily scheduled job switches the assistant to the replacement and disables this model. null indicates that no retirement is scheduled
    "replacement":  // The replacement model after retirement (id and name); null indicates that none is specified and no automatic migration occurs on the retirement date
    {
      "id": string (uuid)
      "name": string
    }
  }
  "condenseQuestionLlm"?: string (uuid) // Question rewriting model: rewrites follow-up questions as standalone questions before retrieval in RAG reply mode; null uses the system setting (if the organization later blocks or disables the selected model, reads also return null and use the system setting) (Optional)
  "defaultCondenseQuestionLlm":  // The question rewriting model actually used when following the system setting (id and name); null indicates that the assistant’s primary model performs rewriting (read-only)
  {
    "id": string (uuid)
    "name": string
  }
  "organizationEnforcedSettings": [ // Codes for the settings enforced on this assistant by the
```

```
organization’s AI assistant defaults (matching the keys in the AI assistant defaults API);
reads return the enforced values, and updates with different values are rejected (read-only;
empty for official built-in Agents and MaiGPT)
    string
  ]
  "embeddingModel"?: string (uuid) // Optional embedding model for vectorizing text (Optional)
  "rerankerModel"?: string (uuid) // Optional model for reranking (Optional)
  "instructions"?: string // Role instructions describing the chatbot's role and behavior.
(Optional)
  "knowledgeBases"?: [ // List of knowledge bases accessible to the chatbot (Optional)
    {
      "id": string (uuid)
      "name": string
    }
  ]
  "databases"?: [ // List of SQL databases accessible to the chatbot (for Text-to-SQL)
(Optional)
    {
      "id": string (uuid)
      "name": string
    }
  ]
  "updatedAt": string (timestamp)
  "organization"?: string (uuid) // The organization the chatbot belongs to; if empty, it is a
personal chatbot (Optional)
  "replyMode"?:  // Reply mode: normal or streaming replies

* `normal` - Normal
* `template` - Template
* `hybrid` - Hybrid
* `agent` - Agent (Optional)
  {
  }
  "template"?: string // Template used by Template and Hybrid modes. (Optional)
  "unanswerableTemplate"?: string // Template used by Template and Hybrid modes when the
question cannot be answered. (Optional)
  "totalWordsCount"?: integer (int64) // Accumulated total word count used. (Optional)
  "outputMode"?:  // Output mode: text, table, or custom format

* `text` - Text
* `json_schema` - JSON Schema (Optional)
  {
  }
  "rawOutputFormat"?: object // JSON schema definition for the custom output format (Optional)
  "groups"?: [ // List of groups accessible to the chatbot (Optional)
    {
      "id": string (uuid)
      "name": string
    }
  ]
  "tools"?: [ // List of tools available to the chatbot (Optional)
    {
      "id": string (uuid)
      "name": string
      "description": string
      "displayName": string
      "toolType": string
```

```
    }
  ]
  "skills"?: [ // List of skills associated with the chatbot (Optional)
    {
      "id": string (uuid)
      "name": string
      "description": string
    }
  ]
  "connectors"?: [ // Connectors associated with this chatbot, gating per-contact OAuth
authorization (Optional)
    {
      "id": string (uuid)
      "name": string
    }
  ]
  "agentMode"?:  // Agent mode: normal, SQL, or workflow mode

* `normal` - Normal
* `canvas` - Canvas
* `team` - Team (Optional)
  {
  }
  "numberOfRetrievedChunks"?: integer // Number of reference chunks to retrieve; default: 12,
minimum: 1 (Optional)
  "defaultLabelRelations"?: object // Default assistant-level knowledge base label filters,
using the same format as query_metadata.label_relations; null means no filtering. Applied only
as the lowest-priority fallback when the caller does not supply query_metadata. (Optional)
  "useFullRetrievalRange"?: boolean // When enabled, ignores LLM top_k truncation and returns
the full reranker results (Optional)
  "enableEvaluation"?: boolean // Optional
  "enableInlineCitations"?: boolean // Enables inline citations, inserting citation markers
such as [1][2] into responses. (Optional)
  "enableCodeInterpreter"?: boolean // When enabled, provides the Code Interpreter tool to run
code in an isolated container. (Optional)
  "enableBrowserTool"?: boolean // Enable browser automation tool for web tasks (Optional)
  "enableImageSearch"?: boolean // Provide the image_search tool when any attached knowledge
base uses a multimodal embedding model. Disable to remove the tool entirely. (Optional)
  "enableClaudeStreamRetry"?: boolean // When a Claude streaming call stalls (first-chunk or
mid-stream), abort and re-issue the call once in non-streaming mode. Mid-stream retries send a
reset signal so the client discards any partial output already rendered. Each retry incurs a
second billing for the same prompt. (Optional)
  "customMaxLlmOutputTokens"?: integer // Custom maximum number of LLM output tokens; minimum:
512 (Optional)
  "voiceConfig"?: { // Optional
  {
    "enabled"?: boolean // Whether this chatbot can be used as a voice agent. Checked by every
conversation platform (WebChat, SIP phone, admin/marketplace voice test) instead of a per-
platform toggle. (Optional)
    "voiceAgentType"?: string (uuid) // Voice agent mode type. (Optional)
    "sttProvider"?: string (uuid) // Speech-to-Text service provider. (Optional)
    "sttConfig"?: object // STT configuration parameters (JSON). (Optional)
    "ttsProvider"?: string (uuid) // Text-to-Speech service provider. (Optional)
    "ttsConfig"?: object // TTS configuration parameters (JSON). (Optional)
    "realtimeProvider"?: string (uuid) // Realtime end-to-end voice model provider. (Optional)
    "realtimeConfig"?: object // Realtime configuration parameters (JSON). (Optional)
    "realtimeInstructions"?: string // Prompt dedicated to the realtime voice session; falls
```

```
back to chatbot instructions when empty (Optional)
    "turnHandling"?: object // Turn-taking and interruption settings for the voice agent.
(Optional)
    "enableVoiceReply"?: boolean // When disabled, the voice agent replies in text only and
does not speak (Optional)
  }
  }
  "thinkingConfig"?: object // Reasoning level: null (model default) or {"reasoning_effort":
"off|minimal|low|medium|high|xhigh|max"} (Optional)
  "enableToolSearching"?: boolean // Legacy field; use tool_loading_mode instead. Writing true
is equivalent to tool_loading_mode=search, and false to all; if both are supplied,
tool_loading_mode takes precedence. Reads return whether the tool loading mode is anything
other than loading all tools. (Optional)
  "toolLoadingMode"?:  // Tool loading mode: auto (automatically determined by the number of
available tools and the model for the current turn), all (load all), or search (dynamic
search). New assistants default to auto; existing assistants without an explicit setting return
the value derived from the legacy toggle (on → search, off → all).

* `auto` - Auto
* `all` - Load all
* `search` - Dynamic search (Optional)
  {
  }
  "maxAgentIterations"?: integer // Maximum number of iterations for AgentWorkflow (1-100,
default: 20) (Optional)
  "agentTimeoutSeconds"?: integer // Timeout in seconds for AgentWorkflow execution (30-1200,
default: 600) (Optional)
  "agentTimeoutMessage"?: string // Custom user-facing message shown when AgentWorkflow times
out (max 500 chars). Leave empty to use the system default. (Optional)
  "requireTextWithFlexCards"?: boolean // When enabled, a turn that would end with only Flex
Message cards and no text for the user is re-issued to the LLM once, asking it to write the
text first and then send the card. Each retry incurs a second billing for the same prompt.
(Optional)
  "isMultimodalLlm": boolean // Whether the chatbot LLM supports multimodal (read-only)
  "enableSizeBasedToolResultTruncation"?: boolean // When enabled, tool results exceeding the
character threshold are kept as head+tail (with the identifiers found in the cut part) when
written to conversation history; knowledge base, SQL and conversation search results keep their
100-character cut either way. Reduces memory bloat from large tool outputs (code interpreter
bash stdout, web search results, etc.). (Optional)
  "toolResultMaxChars"?: integer // Character threshold for size-based tool result truncation
(500-50000). Only effective when enable_size_based_tool_result_truncation is True. (Optional)
  "enableVectorMemory"?: boolean // When enabled, archived messages are vectorized and
processed by fact extraction for semantic retrieval (existing behavior). When disabled,
archived messages are discarded and only the active chat history window is used for multi-turn
context. (Optional)
  "longTermMemoryTopK"?: integer // Number of long-term memory nodes retrieved per search
(similarity_top_k for vector retrieval). Defaults to 10; range: 1–50 (Optional)
  "enableCrossConversationSearch"?: boolean // When enabled, the conversation history tools
also reach this contact's other conversations in the same inbox, within the lookback window.
When disabled, they only reach the current conversation. (Optional)
  "crossConversationLookbackDays"?: integer // How far back cross-conversation search may
reach, measured from each conversation's last message (1-365 days). Leave empty to fall back to
90 days. Only effective when enable_cross_conversation_search is True. (Optional)
  "useGatewayFallback"?: boolean // When enabled, use the fallback group instead of the single
LLM (Optional)
  "gatewayFallbackGroup"?: string (uuid) // Optional
  "enableSearchMessagesTool"?: boolean // Allow the AI to search past messages in the current
```

```
conversation. (Optional)
  "enableGetMessageContextTool"?: boolean // Allow the AI to retrieve messages surrounding a
specific message for context. (Optional)
  "enableReadAttachmentFullTextTool"?: boolean // Allow the AI to read the full text of plain-
text attachments. AGENT mode only. (Optional)
  "enableParseAttachmentContentTool"?: boolean // Allow the AI to parse PDF, Office, audio, and
other attachments. AGENT mode only. (Optional)
  "enableListAvailableParsersTool"?: boolean // Allow the AI to list available parsers and
their capabilities. AGENT mode only. (Optional)
  "enableGetDownloadLinkTool"?: boolean // Allow the AI to generate shareable download links
for produced content. AGENT mode only. (Optional)
  "isLocked": boolean // Locked instance: config follows the official version; only the
dedicated KB can be modified
  "sourceBuildInAgent": string (uuid) // Points to the official Build-in Agent blueprint when
instantiated by a rental
  "canUpdate": boolean // Return whether the current user can update this resource.
  "canDelete": boolean // Return whether the current user can delete this resource.
  "team":
  {
    "id": string (uuid)
    "name": string
  }
  "webChatIsActive"?: boolean // Optional, create only. Whether the web widget channel starts
active. Omitted or null: follows the organization's default for new chatbot channels (inactive
unless a platform admin turned it on). Ignored on update; change an existing channel from its
channel settings instead. (Optional)
  "apiIsActive"?: boolean // Optional, create only. Whether the API channel starts active.
Omitted or null: follows the organization's default for new chatbot channels (inactive unless a
platform admin turned it on). Ignored on update; change an existing channel from its channel
settings instead. The backstage (admin) channel always starts active and cannot be set here.
(Optional)
  "fileWorkspaceMode"?:  // File workspace mode in Work internal conversations: none, bound or
user_mount.

* `none` - None
* `bound` - Bound workspace
* `user_mount` - User mount (Optional)
  {
  }
  "fileWorkspaceFolder"?: string (uuid) // The bound workspace (folder id); required when the
mode is bound, cleared otherwise. (Optional)
  "fileWorkspaceStatus": object // Read-only. {"folder": {"id", "name"} | null, "state": "ok" |
"missing" | "builder_lost_edit" | null}
  "fileWorkspaceAvailable": boolean // Read-only. Whether the organization has the file library
and this agent can configure a file workspace.
}
```

Example Response Value

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "name": "response string",
  "largeLanguageModel": "550e8400-e29b-41d4-a716-446655440000",
  "llm": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
```

```
    "name": "response string",
    "retiresAt": "response string",
    "replacement": {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "response string"
    }
  },
  "condenseQuestionLlm": "550e8400-e29b-41d4-a716-446655440000",
  "defaultCondenseQuestionLlm": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "response string"
  },
  "organizationEnforcedSettings": [
    "response string"
  ],
  "embeddingModel": "550e8400-e29b-41d4-a716-446655440000",
  "rerankerModel": "550e8400-e29b-41d4-a716-446655440000",
  "instructions": "response string",
  "knowledgeBases": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "response string"
    }
  ],
  "databases": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "response string"
    }
  ],
  "updatedAt": "response string",
  "organization": "550e8400-e29b-41d4-a716-446655440000",
  "replyMode": {},
  "template": "response string",
  "unanswerableTemplate": "response string",
  "totalWordsCount": 456,
  "outputMode": {},
  "rawOutputFormat": null,
  "groups": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "response string"
    }
  ],
  "tools": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "response string",
      "description": "response string",
      "displayName": "response string",
      "toolType": "response string"
    }
  ],
  "skills": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "response string",
```

```
      "description": "response string"
    }
  ],
  "connectors": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "response string"
    }
  ],
  "agentMode": {},
  "numberOfRetrievedChunks": 456,
  "defaultLabelRelations": null,
  "useFullRetrievalRange": false,
  "enableEvaluation": false,
  "enableInlineCitations": false,
  "enableCodeInterpreter": false,
  "enableBrowserTool": false,
  "enableImageSearch": false,
  "enableClaudeStreamRetry": false,
  "customMaxLlmOutputTokens": 456,
  "voiceConfig": {
    "enabled": false,
    "voiceAgentType": "550e8400-e29b-41d4-a716-446655440000",
    "sttProvider": "550e8400-e29b-41d4-a716-446655440000",
    "sttConfig": null,
    "ttsProvider": "550e8400-e29b-41d4-a716-446655440000",
    "ttsConfig": null,
    "realtimeProvider": "550e8400-e29b-41d4-a716-446655440000",
    "realtimeConfig": null,
    "realtimeInstructions": "response string",
    "turnHandling": null,
    "enableVoiceReply": false
  },
  "thinkingConfig": null,
  "enableToolSearching": false,
  "toolLoadingMode": {},
  "maxAgentIterations": 456,
  "agentTimeoutSeconds": 456,
  "agentTimeoutMessage": "response string",
  "requireTextWithFlexCards": false,
  "isMultimodalLlm": false,
  "enableSizeBasedToolResultTruncation": false,
  "toolResultMaxChars": 456,
  "enableVectorMemory": false,
  "longTermMemoryTopK": 456,
  "enableCrossConversationSearch": false,
  "crossConversationLookbackDays": 456,
  "useGatewayFallback": false,
  "gatewayFallbackGroup": "550e8400-e29b-41d4-a716-446655440000",
  "enableSearchMessagesTool": false,
  "enableGetMessageContextTool": false,
  "enableReadAttachmentFullTextTool": false,
  "enableParseAttachmentContentTool": false,
  "enableListAvailableParsersTool": false,
  "enableGetDownloadLinkTool": false,
  "isLocked": false,
  "sourceBuildInAgent": "550e8400-e29b-41d4-a716-446655440000",
```

```
  "canUpdate": false,
  "canDelete": false,
  "team": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "response string"
  },
  "webChatIsActive": false,
  "apiIsActive": false,
  "fileWorkspaceMode": {},
  "fileWorkspaceFolder": "550e8400-e29b-41d4-a716-446655440000",
  "fileWorkspaceStatus": {
    "name": "example.pdf",
    "content": "base64encoded_content",
    "contentType": "application/pdf"
  },
  "fileWorkspaceAvailable": false
}
```


Partially Update an AI Assistant

`PATCH` `/api/v1/chatbots/{id}`

Parameters

Parameter Name	Required	Type	Description
id	V	string	

Request Body

Request Parameters

Field	Type	Required	Description
name	string	No	Chatbot name. In Agent mode it carries semantic meaning; in other modes it only distinguishes chatbots.
largeLanguageModel	string (uuid)	No	Large language model used by the chatbot to generate responses (including custom AI Gateway models created by the organization). Can be omitted on creation only if the organization has configured a default model in its AI assistant defaults

Field	Type	Required	Description
condenseQuestionLlm	string (uuid)	No	Question rewriting model: rewrites follow-up questions into standalone questions before retrieval in RAG reply mode. null follows the system settings (if the selected model is later blocked or disabled by the organization, this also reads back as null and follows the system settings)
embeddingModel	string (uuid)	No	Optional embedding model used to vectorize text
rerankerModel	string (uuid)	No	Optional model used for reranking
instructions	string	No	Role instructions describing the chatbot's role and behavior.
knowledgeBases	array[IdName]	No	List of knowledge bases the chatbot can access
databases	array[IdName]	No	List of SQL databases the chatbot can access (for the Text-to-SQL feature)
organization	string (uuid)	No	Organization the chatbot belongs to; if empty, this is a personal chatbot
replyMode	object	No	Reply mode: normal or streaming responses `normal` : Normal ; `template` : Template ; `hybrid` : Hybrid ; `agent` : Agent;
template	string	No	Template used by Template and Hybrid modes.
unanswerableTemplate	string	No	Template used by Template and Hybrid modes when the question cannot be answered.
totalWordsCount	integer (int64)	No	Accumulated total word count used.
outputMode	object	No	Output mode: text, table, or custom format `text` : Text ; `json_schema` : JSON Schema;
rawOutputFormat	object	No	JSON schema definition for the custom output format
groups	array[IdName]	No	List of groups the chatbot can access
tools	array[ToolSummary]	No	List of tools the chatbot can use
skills	array[SkillSummary]	No	List of skills associated with the chatbot
connectors	array[IdName]	No	Connectors associated with this chatbot, gating per-contact OAuth authorization
agentMode	object	No	Agent mode: normal, SQL, or workflow mode `normal` : Normal ; `canvas` : Canvas ; `team` : Team;

Field	Type	Required	Description
numberOfRetrievedChunks	integer	No	Number of reference chunks to retrieve. Defaults to 12; minimum: 1
defaultLabelRelations	object	No	Default assistant-level knowledge base label filters, using the same format as query_metadata.label_relations; null means no filtering. Applied as the lowest-priority fallback only when the caller does not provide query_metadata.
useFullRetrievalRange	boolean	No	When enabled, ignores LLM top_k truncation and returns the full reranker results
enableEvaluation	boolean	No	
enableInlineCitations	boolean	No	Enables inline citations, inserting citation markers such as [1][2] into responses.
enableCodeInterpreter	boolean	No	When enabled, provides the Code Interpreter tool to run code in an isolated container.
enableBrowserTool	boolean	No	Enable browser automation tool for web tasks
enableImageSearch	boolean	No	Provide the image_search tool when any attached knowledge base uses a multimodal embedding model. Disable to remove the tool entirely.
enableClaudeStreamRetry	boolean	No	When a Claude streaming call stalls (first-chunk or mid-stream), abort and re-issue the call once in non-streaming mode. Mid-stream retries send a reset signal so the client discards any partial outpu...
customMaxLlmOutputTokens	integer	No	Custom maximum number of LLM output tokens; minimum: 512
voiceConfig	object	No	
voiceConfig.enabled	boolean	No	Whether this chatbot can be used as a voice agent. Checked by every conversation platform (WebChat, SIP phone, admin/marketplace voice test) instead of a per-platform toggle.
voiceConfig.voiceAgentType	string (uuid)	No	Voice agent mode type.
voiceConfig.sttProvider	string (uuid)	No	Speech-to-Text service provider.
voiceConfig.sttConfig	object	No	STT configuration parameters (JSON).
voiceConfig.ttsProvider	string (uuid)	No	Text-to-Speech service provider.
voiceConfig.ttsConfig	object	No	TTS configuration parameters (JSON).

Field	Type	Required	Description
voiceConfig.realtimeProvider	string (uuid)	No	Realtime end-to-end voice model provider.
voiceConfig.realtimeConfig	object	No	Realtime configuration parameters (JSON).
voiceConfig.realtimeInstructions	string	No	Prompt dedicated to the realtime voice session; falls back to chatbot instructions when empty
voiceConfig.turnHandling	object	No	Turn-taking and interruption settings for the voice agent.
voiceConfig.enableVoiceReply	boolean	No	When disabled, the voice agent replies in text only and does not speak
thinkingConfig	object	No	Reasoning level: null (model default) or {"reasoning_effort": "off
enableToolSearching	boolean	No	Legacy field; use tool_loading_mode instead. Writing true is equivalent to tool_loading_mode=search, and false to all; if both are provided, tool_loading_mode takes precedence. On read, returns whether the tool loading mode is anything other than all.
toolLoadingMode	object	No	Tool loading mode: auto (automatically determined by the number of tools available in the current turn and the model), all (load all), or search (dynamic search). New assistants default to auto; existing assistants with no explicit setting return the value mapped from the legacy toggle (on→search, off→all). `auto` : Auto ; `all` : Load all ; `search` : Dynamic search;
maxAgentIterations	integer	No	Maximum number of iterations for AgentWorkflow (1-100, default: 20)
agentTimeoutSeconds	integer	No	Timeout in seconds for AgentWorkflow execution (30-1200, default: 600)
agentTimeoutMessage	string	No	Custom user-facing message shown when AgentWorkflow times out (max 500 chars). Leave empty to use the system default.
requireTextWithFlexCards	boolean	No	When enabled, a turn that would end with only Flex Message cards and no text for the user is re-issued to the LLM once, asking it to write the text first and then send the card. Each retry incurs a se...
enableSizeBasedToolResultTruncation	boolean	No	When enabled, tool results exceeding the character threshold are kept as head+tail (with the identifiers found in the cut part) when written to conversation history; knowledge base, SQL and conversati...

Field	Type	Required	Description
toolResultMaxChars	integer	No	Character threshold for size-based tool result truncation (500-50000). Only effective when enable_size_based_tool_result_truncation is True.
enableVectorMemory	boolean	No	When enabled, archived messages are vectorized and processed by fact extraction for semantic retrieval (existing behavior). When disabled, archived messages are discarded and only the active chat hist...
longTermMemoryTopK	integer	No	Number of long-term memory nodes retrieved per search (similarity_top_k for vector retrieval). Defaults to 10; range: 1–50
enableCrossConversationSearch	boolean	No	When enabled, the conversation history tools also reach this contact's other conversations in the same inbox, within the lookback window. When disabled, they only reach the current conversation.
crossConversationLookbackDays	integer	No	How far back cross-conversation search may reach, measured from each conversation's last message (1-365 days). Leave empty to fall back to 90 days. Only effective when enable_cross_conversation_search...
useGatewayFallback	boolean	No	When enabled, use the fallback group instead of the single LLM
gatewayFallbackGroup	string (uuid)	No	
enableSearchMessagesTool	boolean	No	Allow the AI to search past messages in the current conversation.
enableGetMessageContextTool	boolean	No	Allow the AI to retrieve messages surrounding a specific message for context.
enableReadAttachmentFullTextTool	boolean	No	Allow the AI to read the full text of plain-text attachments. AGENT mode only.
enableParseAttachmentContentTool	boolean	No	Allow the AI to parse PDF, Office, audio, and other attachments. AGENT mode only.
enableListAvailableParsersTool	boolean	No	Allow the AI to list available parsers and their capabilities. AGENT mode only.
enableGetDownloadLinkTool	boolean	No	Allow the AI to generate shareable download links for produced content. AGENT mode only.
webChatIsActive	boolean	No	Optional, create only. Whether the web widget channel starts active. Omitted or

Field	Type	Required	Description
			null: follows the organization's default for new chatbot channels (inactive unless a platform admin turned it on). Ignor...
apiIsActive	boolean	No	Optional, create only. Whether the API channel starts active. Omitted or null: follows the organization's default for new chatbot channels (inactive unless a platform admin turned it on). Ignored on u...
fileWorkspaceMode	object	No	File workspace mode in Work internal conversations: none, bound or user_mount. `none` : None ; `bound` : Bound workspace ; `user_mount` : User mount;
fileWorkspaceFolder	string (uuid)	No	The bound workspace (folder id); required when the mode is bound, cleared otherwise.

Example Request Schema

```
{
  "name"?: string // Chatbot name. In Agent mode it carries semantic meaning; in other modes it only distinguishes chatbots. (Optional)
  "largeLanguageModel"?: string (uuid) // Large language model used by the chatbot to generate responses (including custom AI Gateway models created by the organization). Can be omitted on creation only if the organization has configured a default model in its AI assistant defaults (Optional)
  "condenseQuestionLlm"?: string (uuid) // Question rewriting model: rewrites follow-up questions into standalone questions before retrieval in RAG reply mode. null follows the system settings (if the selected model is later blocked or disabled by the organization, this also reads back as null and follows the system settings) (Optional)
  "embeddingModel"?: string (uuid) // Optional embedding model used to vectorize text (Optional)
  "rerankerModel"?: string (uuid) // Optional model used for reranking (Optional)
  "instructions"?: string // Role instructions describing the chatbot's role and behavior. (Optional)
  "knowledgeBases"?: [ // List of knowledge bases the chatbot can access (Optional)
    {
      "id": string (uuid)
    }
  ]
  "databases"?: [ // List of SQL databases the chatbot can access (for the Text-to-SQL feature) (Optional)
    {
      "id": string (uuid)
    }
  ]
  "organization"?: string (uuid) // Organization the chatbot belongs to; if empty, this is a personal chatbot (Optional)
  "replyMode"?:  // Reply mode: normal or streaming responses

* `normal` - Normal
```

```
* `template` - Template
* `hybrid` - Hybrid
* `agent` - Agent (Optional)
  {
  }
  "template"?: string // Template used by Template and Hybrid modes. (Optional)
  "unanswerableTemplate"?: string // Template used by Template and Hybrid modes when the
question cannot be answered. (Optional)
  "totalWordsCount"?: integer (int64) // Accumulated total word count used. (Optional)
  "outputMode"?:  // Output mode: text, table, or custom format

* `text` - Text
* `json_schema` - JSON Schema (Optional)
  {
  }
  "rawOutputFormat"?: object // JSON schema definition for the custom output format (Optional)
  "groups"?: [ // List of groups the chatbot can access (Optional)
    {
      "id": string (uuid)
    }
  ]
  "tools"?: [ // List of tools the chatbot can use (Optional)
    {
      "id": string (uuid)
    }
  ]
  "skills"?: [ // List of skills associated with the chatbot (Optional)
    {
      "id": string (uuid)
    }
  ]
  "connectors"?: [ // Connectors associated with this chatbot, gating per-contact OAuth
authorization (Optional)
    {
      "id": string (uuid)
    }
  ]
  "agentMode"?:  // Agent mode: normal, SQL, or workflow mode

* `normal` - Normal
* `canvas` - Canvas
* `team` - Team (Optional)
  {
  }
  "numberOfRetrievedChunks"?: integer // Number of reference chunks to retrieve; defaults to
12, with a minimum of 1 (Optional)
  "defaultLabelRelations"?: object // Default knowledge base label filters at the assistant
level, using the same format as query_metadata.label_relations; null means no filtering.
Applied as the lowest-priority fallback only when the caller does not provide query_metadata.
(Optional)
  "useFullRetrievalRange"?: boolean // When enabled, ignores the LLM top_k truncation and
returns the complete reranker results (Optional)
  "enableEvaluation"?: boolean // Optional
  "enableInlineCitations"?: boolean // Enables inline citations, inserting citation markers
such as [1][2] into responses. (Optional)
  "enableCodeInterpreter"?: boolean // When enabled, provides the Code Interpreter tool to run
code in an isolated container. (Optional)
```

```
  "enableBrowserTool"?: boolean // Enable browser automation tool for web tasks (Optional)
  "enableImageSearch"?: boolean // Provide the image_search tool when any attached knowledge
base uses a multimodal embedding model. Disable to remove the tool entirely. (Optional)
  "enableClaudeStreamRetry"?: boolean // When a Claude streaming call stalls (first-chunk or
mid-stream), abort and re-issue the call once in non-streaming mode. Mid-stream retries send a
reset signal so the client discards any partial output already rendered. Each retry incurs a
second billing for the same prompt. (Optional)
  "customMaxLlmOutputTokens"?: integer // Custom maximum number of LLM output tokens, with a
minimum of 512 (Optional)
  "voiceConfig"?: { // Optional
  {
    "enabled"?: boolean // Whether this chatbot can be used as a voice agent. Checked by every
conversation platform (WebChat, SIP phone, admin/marketplace voice test) instead of a per-
platform toggle. (Optional)
    "voiceAgentType"?: string (uuid) // Voice agent mode type. (Optional)
    "sttProvider"?: string (uuid) // Speech-to-Text service provider. (Optional)
    "sttConfig"?: object // STT configuration parameters (JSON). (Optional)
    "ttsProvider"?: string (uuid) // Text-to-Speech service provider. (Optional)
    "ttsConfig"?: object // TTS configuration parameters (JSON). (Optional)
    "realtimeProvider"?: string (uuid) // Realtime end-to-end voice model provider. (Optional)
    "realtimeConfig"?: object // Realtime configuration parameters (JSON). (Optional)
    "realtimeInstructions"?: string // Prompt dedicated to the realtime voice session; falls
back to chatbot instructions when empty (Optional)
    "turnHandling"?: object // Turn-taking and interruption settings for the voice agent.
(Optional)
    "enableVoiceReply"?: boolean // When disabled, the voice agent replies in text only and
does not speak (Optional)
  }
  }
  "thinkingConfig"?: object // Reasoning effort: null (model default) or {"reasoning_effort":
"off|minimal|low|medium|high|xhigh|max"} (Optional)
  "enableToolSearching"?: boolean // Legacy field; use tool_loading_mode instead. Writing true
is equivalent to tool_loading_mode=search, and false is equivalent to all; if both fields are
provided, tool_loading_mode takes precedence. When read, returns whether the tool loading mode
is anything other than loading all tools. (Optional)
  "toolLoadingMode"?:  // Tool loading mode: auto (automatically determined by the number of
tools available for the current turn and the model), all (load all), or search (dynamic
search). New assistants default to auto; existing assistants that have never set this field
return a value derived from the legacy toggle (enabled → search, disabled → all).

* `auto` - Auto
* `all` - Load all
* `search` - Dynamic search (Optional)
  {
  }
  "maxAgentIterations"?: integer // Maximum number of iterations for AgentWorkflow (1-100,
default: 20) (Optional)
  "agentTimeoutSeconds"?: integer // Timeout in seconds for AgentWorkflow execution (30-1200,
default: 600) (Optional)
  "agentTimeoutMessage"?: string // Custom user-facing message shown when AgentWorkflow times
out (max 500 chars). Leave empty to use the system default. (Optional)
  "requireTextWithFlexCards"?: boolean // When enabled, a turn that would end with only Flex
Message cards and no text for the user is re-issued to the LLM once, asking it to write the
text first and then send the card. Each retry incurs a second billing for the same prompt.
(Optional)
  "enableSizeBasedToolResultTruncation"?: boolean // When enabled, tool results exceeding the
character threshold are kept as head+tail (with the identifiers found in the cut part) when
```

```
written to conversation history; knowledge base, SQL and conversation search results keep their 100-character cut either way. Reduces memory bloat from large tool outputs (code interpreter bash stdout, web search results, etc.). (Optional)
  "toolResultMaxChars"?: integer // Character threshold for size-based tool result truncation (500-50000). Only effective when enable_size_based_tool_result_truncation is True. (Optional)
  "enableVectorMemory"?: boolean // When enabled, archived messages are vectorized and processed by fact extraction for semantic retrieval (existing behavior). When disabled, archived messages are discarded and only the active chat history window is used for multi-turn context. (Optional)
  "longTermMemoryTopK"?: integer // Number of long-term memory nodes returned per retrieval (similarity_top_k for vector retrieval); defaults to 10, with a range of 1–50 (Optional)
  "enableCrossConversationSearch"?: boolean // When enabled, the conversation history tools also reach this contact's other conversations in the same inbox, within the lookback window. When disabled, they only reach the current conversation. (Optional)
  "crossConversationLookbackDays"?: integer // How far back cross-conversation search may reach, measured from each conversation's last message (1-365 days). Leave empty to fall back to 90 days. Only effective when enable_cross_conversation_search is True. (Optional)
  "useGatewayFallback"?: boolean // When enabled, use the fallback group instead of the single LLM (Optional)
  "gatewayFallbackGroup"?: string (uuid) // Optional
  "enableSearchMessagesTool"?: boolean // Allow the AI to search past messages in the current conversation. (Optional)
  "enableGetMessageContextTool"?: boolean // Allow the AI to retrieve messages surrounding a specific message for context. (Optional)
  "enableReadAttachmentFullTextTool"?: boolean // Allow the AI to read the full text of plain-text attachments. AGENT mode only. (Optional)
  "enableParseAttachmentContentTool"?: boolean // Allow the AI to parse PDF, Office, audio, and other attachments. AGENT mode only. (Optional)
  "enableListAvailableParsersTool"?: boolean // Allow the AI to list available parsers and their capabilities. AGENT mode only. (Optional)
  "enableGetDownloadLinkTool"?: boolean // Allow the AI to generate shareable download links for produced content. AGENT mode only. (Optional)
  "webChatIsActive"?: boolean // Optional, create only. Whether the web widget channel starts active. Omitted or null: follows the organization's default for new chatbot channels (inactive unless a platform admin turned it on). Ignored on update; change an existing channel from its channel settings instead. (Optional)
  "apiIsActive"?: boolean // Optional, create only. Whether the API channel starts active. Omitted or null: follows the organization's default for new chatbot channels (inactive unless a platform admin turned it on). Ignored on update; change an existing channel from its channel settings instead. The backstage (admin) channel always starts active and cannot be set here. (Optional)
  "fileWorkspaceMode"?:  // File workspace mode in Work internal conversations: none, bound or user_mount.

* `none` - None
* `bound` - Bound workspace
* `user_mount` - User mount (Optional)
  {
  }
  "fileWorkspaceFolder"?: string (uuid) // The bound workspace (folder id); required when the mode is bound, cleared otherwise. (Optional)
}
```

Example Request Values

```
{
  "name": "Example name",
  "largeLanguageModel": "550e8400-e29b-41d4-a716-446655440000",
  "condenseQuestionLlm": "550e8400-e29b-41d4-a716-446655440000",
  "embeddingModel": "550e8400-e29b-41d4-a716-446655440000",
  "rerankerModel": "550e8400-e29b-41d4-a716-446655440000",
  "instructions": "Example string",
  "knowledgeBases": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000"
    }
  ],
  "databases": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000"
    }
  ],
  "organization": "550e8400-e29b-41d4-a716-446655440000",
  "replyMode": {},
  "template": "Example string",
  "unanswerableTemplate": "Example string",
  "totalWordsCount": 123,
  "outputMode": {},
  "rawOutputFormat": null,
  "groups": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000"
    }
  ],
  "tools": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000"
    }
  ],
  "skills": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000"
    }
  ],
  "connectors": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000"
    }
  ],
  "agentMode": {},
  "numberOfRetrievedChunks": 123,
  "defaultLabelRelations": null,
  "useFullRetrievalRange": true,
  "enableEvaluation": true,
  "enableInlineCitations": true,
  "enableCodeInterpreter": true,
  "enableBrowserTool": true,
  "enableImageSearch": true,
  "enableClaudeStreamRetry": true,
  "customMaxLlmOutputTokens": 123,
  "voiceConfig": {
```

```
    "enabled": true,
    "voiceAgentType": "550e8400-e29b-41d4-a716-446655440000",
    "sttProvider": "550e8400-e29b-41d4-a716-446655440000",
    "sttConfig": null,
    "ttsProvider": "550e8400-e29b-41d4-a716-446655440000",
    "ttsConfig": null,
    "realtimeProvider": "550e8400-e29b-41d4-a716-446655440000",
    "realtimeConfig": null,
    "realtimeInstructions": "Example string",
    "turnHandling": null,
    "enableVoiceReply": true
  },
  "thinkingConfig": null,
  "enableToolSearching": true,
  "toolLoadingMode": {},
  "maxAgentIterations": 123,
  "agentTimeoutSeconds": 123,
  "agentTimeoutMessage": "Example string",
  "requireTextWithFlexCards": true,
  "enableSizeBasedToolResultTruncation": true,
  "toolResultMaxChars": 123,
  "enableVectorMemory": true,
  "longTermMemoryTopK": 123,
  "enableCrossConversationSearch": true,
  "crossConversationLookbackDays": 123,
  "useGatewayFallback": true,
  "gatewayFallbackGroup": "550e8400-e29b-41d4-a716-446655440000",
  "enableSearchMessagesTool": true,
  "enableGetMessageContextTool": true,
  "enableReadAttachmentFullTextTool": true,
  "enableParseAttachmentContentTool": true,
  "enableListAvailableParsersTool": true,
  "enableGetDownloadLinkTool": true,
  "webChatIsActive": true,
  "apiIsActive": true,
  "fileWorkspaceMode": {},
  "fileWorkspaceFolder": "550e8400-e29b-41d4-a716-446655440000"
}
```


Code Examples

Shell/Bash

```
# Example API call (Shell)
curl -X PATCH "

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "name": "Example name",
    "largeLanguageModel": "550e8400-e29b-41d4-a716-446655440000",
    "condenseQuestionLlm": "550e8400-e29b-41d4-a716-446655440000",
    "embeddingModel": "550e8400-e29b-41d4-a716-446655440000",
    "rerankerModel": "550e8400-e29b-41d4-a716-446655440000",
    "instructions": "Example string",
    "knowledgeBases": [
      {
        "id": "550e8400-e29b-41d4-a716-446655440000"
      }
    ],
    "databases": [
      {
        "id": "550e8400-e29b-41d4-a716-446655440000"
      }
    ],
    "organization": "550e8400-e29b-41d4-a716-446655440000",
    "replyMode": {},
    "template": "Example string",
    "unanswerableTemplate": "Example string",
    "totalWordsCount": 123,
    "outputMode": {},
    "rawOutputFormat": null,
    "groups": [
      {
        "id": "550e8400-e29b-41d4-a716-446655440000"
      }
    ],
    "tools": [
      {
        "id": "550e8400-e29b-41d4-a716-446655440000"
      }
    ],
    "skills": [
      {
        "id": "550e8400-e29b-41d4-a716-446655440000"
      }
    ],
    "connectors": [
      {
        "id": "550e8400-e29b-41d4-a716-446655440000"
      }
    ],
```

```
      "agentMode": {},
      "numberOfRetrievedChunks": 123,
      "defaultLabelRelations": null,
      "useFullRetrievalRange": true,
      "enableEvaluation": true,
      "enableInlineCitations": true,
      "enableCodeInterpreter": true,
      "enableBrowserTool": true,
      "enableImageSearch": true,
      "enableClaudeStreamRetry": true,
      "customMaxLlmOutputTokens": 123,
      "voiceConfig": {
        "enabled": true,
        "voiceAgentType": "550e8400-e29b-41d4-a716-446655440000",
        "sttProvider": "550e8400-e29b-41d4-a716-446655440000",
        "sttConfig": null,
        "ttsProvider": "550e8400-e29b-41d4-a716-446655440000",
        "ttsConfig": null,
        "realtimeProvider": "550e8400-e29b-41d4-a716-446655440000",
        "realtimeConfig": null,
        "realtimeInstructions": "Example string",
        "turnHandling": null,
        "enableVoiceReply": true
      },
      "thinkingConfig": null,
      "enableToolSearching": true,
      "toolLoadingMode": {},
      "maxAgentIterations": 123,
      "agentTimeoutSeconds": 123,
      "agentTimeoutMessage": "Example string",
      "requireTextWithFlexCards": true,
      "enableSizeBasedToolResultTruncation": true,
      "toolResultMaxChars": 123,
      "enableVectorMemory": true,
      "longTermMemoryTopK": 123,
      "enableCrossConversationSearch": true,
      "crossConversationLookbackDays": 123,
      "useGatewayFallback": true,
      "gatewayFallbackGroup": "550e8400-e29b-41d4-a716-446655440000",
      "enableSearchMessagesTool": true,
      "enableGetMessageContextTool": true,
      "enableReadAttachmentFullTextTool": true,
      "enableParseAttachmentContentTool": true,
      "enableListAvailableParsersTool": true,
      "enableGetDownloadLinkTool": true,
      "webChatIsActive": true,
      "apiIsActive": true,
      "fileWorkspaceMode": {},
      "fileWorkspaceFolder": "550e8400-e29b-41d4-a716-446655440000"
    }'

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// Request body (payload)
const data = {
    "name": "Example name",
    "largeLanguageModel": "550e8400-e29b-41d4-a716-446655440000",
    "condenseQuestionLlm": "550e8400-e29b-41d4-a716-446655440000",
    "embeddingModel": "550e8400-e29b-41d4-a716-446655440000",
    "rerankerModel": "550e8400-e29b-41d4-a716-446655440000",
    "instructions": "Example string",
    "knowledgeBases": [
      {
        "id": "550e8400-e29b-41d4-a716-446655440000"
      }
    ],
    "databases": [
      {
        "id": "550e8400-e29b-41d4-a716-446655440000"
      }
    ],
    "organization": "550e8400-e29b-41d4-a716-446655440000",
    "replyMode": {},
    "template": "Example string",
    "unanswerableTemplate": "Example string",
    "totalWordsCount": 123,
    "outputMode": {},
    "rawOutputFormat": null,
    "groups": [
      {
        "id": "550e8400-e29b-41d4-a716-446655440000"
      }
    ],
    "tools": [
      {
        "id": "550e8400-e29b-41d4-a716-446655440000"
      }
    ],
    "skills": [
      {
        "id": "550e8400-e29b-41d4-a716-446655440000"
      }
    ],
    "connectors": [
```

```
        {
          "id": "550e8400-e29b-41d4-a716-446655440000"
        }
      ],
      "agentMode": {},
      "numberOfRetrievedChunks": 123,
      "defaultLabelRelations": null,
      "useFullRetrievalRange": true,
      "enableEvaluation": true,
      "enableInlineCitations": true,
      "enableCodeInterpreter": true,
      "enableBrowserTool": true,
      "enableImageSearch": true,
      "enableClaudeStreamRetry": true,
      "customMaxLlmOutputTokens": 123,
      "voiceConfig": {
        "enabled": true,
        "voiceAgentType": "550e8400-e29b-41d4-a716-446655440000",
        "sttProvider": "550e8400-e29b-41d4-a716-446655440000",
        "sttConfig": null,
        "ttsProvider": "550e8400-e29b-41d4-a716-446655440000",
        "ttsConfig": null,
        "realtimeProvider": "550e8400-e29b-41d4-a716-446655440000",
        "realtimeConfig": null,
        "realtimeInstructions": "Example string",
        "turnHandling": null,
        "enableVoiceReply": true
      },
      "thinkingConfig": null,
      "enableToolSearching": true,
      "toolLoadingMode": {},
      "maxAgentIterations": 123,
      "agentTimeoutSeconds": 123,
      "agentTimeoutMessage": "Example string",
      "requireTextWithFlexCards": true,
      "enableSizeBasedToolResultTruncation": true,
      "toolResultMaxChars": 123,
      "enableVectorMemory": true,
      "longTermMemoryTopK": 123,
      "enableCrossConversationSearch": true,
      "crossConversationLookbackDays": 123,
      "useGatewayFallback": true,
      "gatewayFallbackGroup": "550e8400-e29b-41d4-a716-446655440000",
      "enableSearchMessagesTool": true,
      "enableGetMessageContextTool": true,
      "enableReadAttachmentFullTextTool": true,
      "enableParseAttachmentContentTool": true,
      "enableListAvailableParsersTool": true,
      "enableGetDownloadLinkTool": true,
      "webChatIsActive": true,
      "apiIsActive": true,
      "fileWorkspaceMode": {},
      "fileWorkspaceFolder": "550e8400-e29b-41d4-a716-446655440000"
    };

  axios.patch(" data, config)
    .then(response => {
```

```
  console.log('Response received successfully:');
  console.log(response.data);
})
.catch(error => {
  console.error('Request error:');
  console.error(error.response?.data || error.message);
});
```

Python

```
import requests

url = "
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# Request body (payload)
data = {
    "name": "Example name",
    "largeLanguageModel": "550e8400-e29b-41d4-a716-446655440000",
    "condenseQuestionLlm": "550e8400-e29b-41d4-a716-446655440000",
    "embeddingModel": "550e8400-e29b-41d4-a716-446655440000",
    "rerankerModel": "550e8400-e29b-41d4-a716-446655440000",
    "instructions": "Example string",
    "knowledgeBases": [
        {
            "id": "550e8400-e29b-41d4-a716-446655440000"
        }
    ],
    "databases": [
        {
            "id": "550e8400-e29b-41d4-a716-446655440000"
        }
    ],
    "organization": "550e8400-e29b-41d4-a716-446655440000",
    "replyMode": {},
    "template": "Example string",
    "unanswerableTemplate": "Example string",
    "totalWordsCount": 123,
    "outputMode": {},
    "rawOutputFormat": None,
    "groups": [
        {
            "id": "550e8400-e29b-41d4-a716-446655440000"
        }
    ],
    "tools": [
        {
            "id": "550e8400-e29b-41d4-a716-446655440000"
        }
    ],
    "skills": [
        {
            "id": "550e8400-e29b-41d4-a716-446655440000"
        }
    ],
    "connectors": [
        {
            "id": "550e8400-e29b-41d4-a716-446655440000"
```

```
        }
    ],
    "agentMode": {},
    "numberOfRetrievedChunks": 123,
    "defaultLabelRelations": None,
    "useFullRetrievalRange": True,
    "enableEvaluation": True,
    "enableInlineCitations": True,
    "enableCodeInterpreter": True,
    "enableBrowserTool": True,
    "enableImageSearch": True,
    "enableClaudeStreamRetry": True,
    "customMaxLlmOutputTokens": 123,
    "voiceConfig": {
        "enabled": True,
        "voiceAgentType": "550e8400-e29b-41d4-a716-446655440000",
        "sttProvider": "550e8400-e29b-41d4-a716-446655440000",
        "sttConfig": None,
        "ttsProvider": "550e8400-e29b-41d4-a716-446655440000",
        "ttsConfig": None,
        "realtimeProvider": "550e8400-e29b-41d4-a716-446655440000",
        "realtimeConfig": None,
        "realtimeInstructions": "Example string",
        "turnHandling": None,
        "enableVoiceReply": True
    },
    "thinkingConfig": None,
    "enableToolSearching": True,
    "toolLoadingMode": {},
    "maxAgentIterations": 123,
    "agentTimeoutSeconds": 123,
    "agentTimeoutMessage": "Example string",
    "requireTextWithFlexCards": True,
    "enableSizeBasedToolResultTruncation": True,
    "toolResultMaxChars": 123,
    "enableVectorMemory": True,
    "longTermMemoryTopK": 123,
    "enableCrossConversationSearch": True,
    "crossConversationLookbackDays": 123,
    "useGatewayFallback": True,
    "gatewayFallbackGroup": "550e8400-e29b-41d4-a716-446655440000",
    "enableSearchMessagesTool": True,
    "enableGetMessageContextTool": True,
    "enableReadAttachmentFullTextTool": True,
    "enableParseAttachmentContentTool": True,
    "enableListAvailableParsersTool": True,
    "enableGetDownloadLinkTool": True,
    "webChatIsActive": True,
    "apiIsActive": True,
    "fileWorkspaceMode": {},
    "fileWorkspaceFolder": "550e8400-e29b-41d4-a716-446655440000"
}

response = requests.patch(url, json=data, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
```

```
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->patch(" [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'name' => 'Example name',
            'largeLanguageModel' => '550e8400-e29b-41d4-a716-446655440000',
            'condenseQuestionLlm' => '550e8400-e29b-41d4-a716-446655440000',
            'embeddingModel' => '550e8400-e29b-41d4-a716-446655440000',
            'rerankerModel' => '550e8400-e29b-41d4-a716-446655440000',
            'instructions' => 'Example string',
            'knowledgeBases' => [
                [
                    'id' => '550e8400-e29b-41d4-a716-446655440000'
                ]
            ],
            'databases' => [
                [
                    'id' => '550e8400-e29b-41d4-a716-446655440000'
                ]
            ],
            'organization' => '550e8400-e29b-41d4-a716-446655440000',
            'replyMode' => new \stdClass(),
            'template' => 'Example string',
            'unanswerableTemplate' => 'Example string',
            'totalWordsCount' => 123,
            'outputMode' => new \stdClass(),
            'rawOutputFormat' => null,
            'groups' => [
                [
                    'id' => '550e8400-e29b-41d4-a716-446655440000'
                ]
            ],
            'tools' => [
                [
                    'id' => '550e8400-e29b-41d4-a716-446655440000'
                ]
            ],
            'skills' => [
                [
                    'id' => '550e8400-e29b-41d4-a716-446655440000'
                ]
            ],
            'connectors' => [
```

```
                [
                    'id' => '550e8400-e29b-41d4-a716-446655440000'
                ]
            ],
            'agentMode' => new \stdClass(),
            'numberOfRetrievedChunks' => 123,
            'defaultLabelRelations' => null,
            'useFullRetrievalRange' => true,
            'enableEvaluation' => true,
            'enableInlineCitations' => true,
            'enableCodeInterpreter' => true,
            'enableBrowserTool' => true,
            'enableImageSearch' => true,
            'enableClaudeStreamRetry' => true,
            'customMaxLlmOutputTokens' => 123,
            'voiceConfig' => [
                'enabled' => true,
                'voiceAgentType' => '550e8400-e29b-41d4-a716-446655440000',
                'sttProvider' => '550e8400-e29b-41d4-a716-446655440000',
                'sttConfig' => null,
                'ttsProvider' => '550e8400-e29b-41d4-a716-446655440000',
                'ttsConfig' => null,
                'realtimeProvider' => '550e8400-e29b-41d4-a716-446655440000',
                'realtimeConfig' => null,
                'realtimeInstructions' => 'Example string',
                'turnHandling' => null,
                'enableVoiceReply' => true
            ],
            'thinkingConfig' => null,
            'enableToolSearching' => true,
            'toolLoadingMode' => new \stdClass(),
            'maxAgentIterations' => 123,
            'agentTimeoutSeconds' => 123,
            'agentTimeoutMessage' => 'Example string',
            'requireTextWithFlexCards' => true,
            'enableSizeBasedToolResultTruncation' => true,
            'toolResultMaxChars' => 123,
            'enableVectorMemory' => true,
            'longTermMemoryTopK' => 123,
            'enableCrossConversationSearch' => true,
            'crossConversationLookbackDays' => 123,
            'useGatewayFallback' => true,
            'gatewayFallbackGroup' => '550e8400-e29b-41d4-a716-446655440000',
            'enableSearchMessagesTool' => true,
            'enableGetMessageContextTool' => true,
            'enableReadAttachmentFullTextTool' => true,
            'enableParseAttachmentContentTool' => true,
            'enableListAvailableParsersTool' => true,
            'enableGetDownloadLinkTool' => true,
            'webChatIsActive' => true,
            'apiIsActive' => true,
            'fileWorkspaceMode' => new \stdClass(),
            'fileWorkspaceFolder' => '550e8400-e29b-41d4-a716-446655440000'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
```

```
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response

Status code: 200

Example response schema

```
{
  "id": string (uuid)
  "name": string // Chatbot name. In Agent mode it carries semantic meaning; in other modes it only distinguishes chatbots.
  "largeLanguageModel": string (uuid) // Large language model used by the chatbot to generate answers (including organization-defined AI Gateway models); on creation, this can be omitted only if the organization has set a default model in AI assistant defaults
  "llm":  // The bound model’s id, name, and retirement information, read directly from the FK and returned even if the organization has disabled the model
  {
    "id": string (uuid)
    "name": string
    "retiresAt": string (date) // Provider retirement date; once reached, a daily scheduled task switches the assistant to the replacement and disables this model. null means no retirement is scheduled
    "replacement":  // The model taking over after retirement (id and name); null means none is specified, so no automatic migration occurs on retirement
    {
      "id": string (uuid)
      "name": string
    }
  }
  "condenseQuestionLlm"?: string (uuid) // Question rewriting model: rewrites follow-up questions into standalone questions before retrieval in RAG reply mode; null follows system settings (if the selected model is later blocked or disabled by the organization, this also returns null and follows system settings) (Optional)
  "defaultCondenseQuestionLlm":  // The question rewriting model actually used when following system settings (id and name); null means the assistant’s primary model handles rewriting (read-only)
  {
    "id": string (uuid)
    "name": string
  }
  "organizationEnforcedSettings": [ // Setting codes enforced for this assistant by the organization’s AI assistant defaults (matching the keys in the AI assistant defaults API);
```

```
these fields return the enforced values, and updates with different values are rejected (read-
only; empty for official built-in Agents and MaiGPT)
    string
  ]
  "embeddingModel"?: string (uuid) // Embedding model used to vectorize text, optional
(Optional)
  "rerankerModel"?: string (uuid) // Model used for reranking, optional (Optional)
  "instructions"?: string // Role instructions describing the chatbot's role and behavior.
(Optional)
  "knowledgeBases"?: [ // List of knowledge bases the chatbot can access (Optional)
    {
      "id": string (uuid)
      "name": string
    }
  ]
  "databases"?: [ // List of SQL databases the chatbot can access (for Text-to-SQL) (Optional)
    {
      "id": string (uuid)
      "name": string
    }
  ]
  "updatedAt": string (timestamp)
  "organization"?: string (uuid) // Organization the chatbot belongs to; if empty, this is a
personal chatbot (Optional)
  "replyMode"?:  // Reply mode: normal or streaming replies

* `normal` - Normal
* `template` - Template
* `hybrid` - Hybrid
* `agent` - Agent (Optional)
  {
  }
  "template"?: string // Template used by Template and Hybrid modes. (Optional)
  "unanswerableTemplate"?: string // Template used by Template and Hybrid modes when the
question cannot be answered. (Optional)
  "totalWordsCount"?: integer (int64) // Accumulated total word count used. (Optional)
  "outputMode"?:  // Output mode: text, table, or custom format

* `text` - Text
* `json_schema` - JSON Schema (Optional)
  {
  }
  "rawOutputFormat"?: object // JSON schema definition for the custom output format (Optional)
  "groups"?: [ // List of groups the chatbot can access (Optional)
    {
      "id": string (uuid)
      "name": string
    }
  ]
  "tools"?: [ // List of tools the chatbot can use (Optional)
    {
      "id": string (uuid)
      "name": string
      "description": string
      "displayName": string
      "toolType": string
    }
```

```
  ]
  "skills"?: [ // List of skills associated with the chatbot (Optional)
    {
      "id": string (uuid)
      "name": string
      "description": string
    }
  ]
  "connectors"?: [ // Connectors associated with this chatbot, gating per-contact OAuth
authorization (Optional)
    {
      "id": string (uuid)
      "name": string
    }
  ]
  "agentMode"?:  // Agent mode: normal, SQL, or workflow mode

* `normal` - Normal
* `canvas` - Canvas
* `team` - Team (Optional)
  {
  }
  "numberOfRetrievedChunks"?: integer // Number of reference chunks retrieved; defaults to 12,
minimum 1 (Optional)
  "defaultLabelRelations"?: object // Default knowledge base label filters at the assistant
level, in the same format as query_metadata.label_relations; null means no filtering. Applied
only as the lowest-priority fallback when the caller omits query_metadata. (Optional)
  "useFullRetrievalRange"?: boolean // When enabled, ignores the LLM’s top_k truncation and
returns the full reranker results (Optional)
  "enableEvaluation"?: boolean // Optional
  "enableInlineCitations"?: boolean // Enables inline citations, inserting citation markers
such as [1][2] into responses. (Optional)
  "enableCodeInterpreter"?: boolean // When enabled, provides the Code Interpreter tool to run
code in an isolated container. (Optional)
  "enableBrowserTool"?: boolean // Enable browser automation tool for web tasks (Optional)
  "enableImageSearch"?: boolean // Provide the image_search tool when any attached knowledge
base uses a multimodal embedding model. Disable to remove the tool entirely. (Optional)
  "enableClaudeStreamRetry"?: boolean // When a Claude streaming call stalls (first-chunk or
mid-stream), abort and re-issue the call once in non-streaming mode. Mid-stream retries send a
reset signal so the client discards any partial output already rendered. Each retry incurs a
second billing for the same prompt. (Optional)
  "customMaxLlmOutputTokens"?: integer // Custom maximum LLM output tokens, minimum 512
(Optional)
  "voiceConfig"?: { // Optional
  {
    "enabled"?: boolean // Whether this chatbot can be used as a voice agent. Checked by every
conversation platform (WebChat, SIP phone, admin/marketplace voice test) instead of a per-
platform toggle. (Optional)
    "voiceAgentType"?: string (uuid) // Voice agent mode type. (Optional)
    "sttProvider"?: string (uuid) // Speech-to-Text service provider. (Optional)
    "sttConfig"?: object // STT configuration parameters (JSON). (Optional)
    "ttsProvider"?: string (uuid) // Text-to-Speech service provider. (Optional)
    "ttsConfig"?: object // TTS configuration parameters (JSON). (Optional)
    "realtimeProvider"?: string (uuid) // Realtime end-to-end voice model provider. (Optional)
    "realtimeConfig"?: object // Realtime configuration parameters (JSON). (Optional)
    "realtimeInstructions"?: string // Prompt dedicated to the realtime voice session; falls
back to chatbot instructions when empty (Optional)
```

```
    "turnHandling"?: object // Turn-taking and interruption settings for the voice agent.
(Optional)
    "enableVoiceReply"?: boolean // When disabled, the voice agent replies in text only and
does not speak (Optional)
  }
  }
  "thinkingConfig"?: object // Thinking level: null (model default) or {"reasoning_effort":
"off|minimal|low|medium|high|xhigh|max"} (Optional)
  "enableToolSearching"?: boolean // Legacy field; use tool_loading_mode instead. Writing true
is equivalent to tool_loading_mode=search, and false to all; tool_loading_mode takes precedence
when both are provided. On read, returns whether the tool loading mode is not load all.
(Optional)
  "toolLoadingMode"?:  // Tool loading mode: auto (automatic, based on the tools available for
the current turn and the model), all (load all), or search (dynamic search). New assistants
default to auto; existing assistants that have never configured this return a value derived
from the old toggle (on → search, off → all).

* `auto` - Auto
* `all` - Load all
* `search` - Dynamic search (Optional)
  {
  }
  "maxAgentIterations"?: integer // Maximum number of iterations for AgentWorkflow (1-100,
default: 20) (Optional)
  "agentTimeoutSeconds"?: integer // Timeout in seconds for AgentWorkflow execution (30-1200,
default: 600) (Optional)
  "agentTimeoutMessage"?: string // Custom user-facing message shown when AgentWorkflow times
out (max 500 chars). Leave empty to use the system default. (Optional)
  "requireTextWithFlexCards"?: boolean // When enabled, a turn that would end with only Flex
Message cards and no text for the user is re-issued to the LLM once, asking it to write the
text first and then send the card. Each retry incurs a second billing for the same prompt.
(Optional)
  "isMultimodalLlm": boolean // Whether the chatbot LLM supports multimodal (read-only)
  "enableSizeBasedToolResultTruncation"?: boolean // When enabled, tool results exceeding the
character threshold are kept as head+tail (with the identifiers found in the cut part) when
written to conversation history; knowledge base, SQL and conversation search results keep their
100-character cut either way. Reduces memory bloat from large tool outputs (code interpreter
bash stdout, web search results, etc.). (Optional)
  "toolResultMaxChars"?: integer // Character threshold for size-based tool result truncation
(500-50000). Only effective when enable_size_based_tool_result_truncation is True. (Optional)
  "enableVectorMemory"?: boolean // When enabled, archived messages are vectorized and
processed by fact extraction for semantic retrieval (existing behavior). When disabled,
archived messages are discarded and only the active chat history window is used for multi-turn
context. (Optional)
  "longTermMemoryTopK"?: integer // Number of memory nodes retrieved from long-term memory per
query (similarity_top_k for vector retrieval); defaults to 10, range 1–50 (Optional)
  "enableCrossConversationSearch"?: boolean // When enabled, the conversation history tools
also reach this contact's other conversations in the same inbox, within the lookback window.
When disabled, they only reach the current conversation. (Optional)
  "crossConversationLookbackDays"?: integer // How far back cross-conversation search may
reach, measured from each conversation's last message (1-365 days). Leave empty to fall back to
90 days. Only effective when enable_cross_conversation_search is True. (Optional)
  "useGatewayFallback"?: boolean // When enabled, use the fallback group instead of the single
LLM (Optional)
  "gatewayFallbackGroup"?: string (uuid) // Optional
  "enableSearchMessagesTool"?: boolean // Allow the AI to search past messages in the current
conversation. (Optional)
```

```
  "enableGetMessageContextTool"?: boolean // Allow the AI to retrieve messages surrounding a specific message for context. (Optional)
  "enableReadAttachmentFullTextTool"?: boolean // Allow the AI to read the full text of plain-text attachments. AGENT mode only. (Optional)
  "enableParseAttachmentContentTool"?: boolean // Allow the AI to parse PDF, Office, audio, and other attachments. AGENT mode only. (Optional)
  "enableListAvailableParsersTool"?: boolean // Allow the AI to list available parsers and their capabilities. AGENT mode only. (Optional)
  "enableGetDownloadLinkTool"?: boolean // Allow the AI to generate shareable download links for produced content. AGENT mode only. (Optional)
  "isLocked": boolean // Locked instance: config follows the official version; only the dedicated KB can be modified
  "sourceBuildInAgent": string (uuid) // Points to the official Build-in Agent blueprint when instantiated by a rental
  "canUpdate": boolean // Return whether the current user can update this resource.
  "canDelete": boolean // Return whether the current user can delete this resource.
  "team":
  {
    "id": string (uuid)
    "name": string
  }
  "webChatIsActive"?: boolean // Optional, create only. Whether the web widget channel starts active. Omitted or null: follows the organization's default for new chatbot channels (inactive unless a platform admin turned it on). Ignored on update; change an existing channel from its channel settings instead. (Optional)
  "apiIsActive"?: boolean // Optional, create only. Whether the API channel starts active. Omitted or null: follows the organization's default for new chatbot channels (inactive unless a platform admin turned it on). Ignored on update; change an existing channel from its channel settings instead. The backstage (admin) channel always starts active and cannot be set here. (Optional)
  "fileWorkspaceMode"?:  // File workspace mode in Work internal conversations: none, bound or user_mount.

* `none` - None
* `bound` - Bound workspace
* `user_mount` - User mount (Optional)
  {
  }
  "fileWorkspaceFolder"?: string (uuid) // The bound workspace (folder id); required when the mode is bound, cleared otherwise. (Optional)
  "fileWorkspaceStatus": object // Read-only. {"folder": {"id", "name"} | null, "state": "ok" | "missing" | "builder_lost_edit" | null}
  "fileWorkspaceAvailable": boolean // Read-only. Whether the organization has the file library and this agent can configure a file workspace.
}
```

Example response values

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "name": "Response string",
  "largeLanguageModel": "550e8400-e29b-41d4-a716-446655440000",
  "llm": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Response string",
```

```
    "retiresAt": "Response string",
    "replacement": {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "Response string"
    }
  },
  "condenseQuestionLlm": "550e8400-e29b-41d4-a716-446655440000",
  "defaultCondenseQuestionLlm": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Response string"
  },
  "organizationEnforcedSettings": [
    "Response string"
  ],
  "embeddingModel": "550e8400-e29b-41d4-a716-446655440000",
  "rerankerModel": "550e8400-e29b-41d4-a716-446655440000",
  "instructions": "Response string",
  "knowledgeBases": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "Response string"
    }
  ],
  "databases": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "Response string"
    }
  ],
  "updatedAt": "Response string",
  "organization": "550e8400-e29b-41d4-a716-446655440000",
  "replyMode": {},
  "template": "Response string",
  "unanswerableTemplate": "Response string",
  "totalWordsCount": 456,
  "outputMode": {},
  "rawOutputFormat": null,
  "groups": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "Response string"
    }
  ],
  "tools": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "Response string",
      "description": "Response string",
      "displayName": "Response string",
      "toolType": "Response string"
    }
  ],
  "skills": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "Response string",
      "description": "Response string"
```

```
    }
  ],
  "connectors": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "Response string"
    }
  ],
  "agentMode": {},
  "numberOfRetrievedChunks": 456,
  "defaultLabelRelations": null,
  "useFullRetrievalRange": false,
  "enableEvaluation": false,
  "enableInlineCitations": false,
  "enableCodeInterpreter": false,
  "enableBrowserTool": false,
  "enableImageSearch": false,
  "enableClaudeStreamRetry": false,
  "customMaxLlmOutputTokens": 456,
  "voiceConfig": {
    "enabled": false,
    "voiceAgentType": "550e8400-e29b-41d4-a716-446655440000",
    "sttProvider": "550e8400-e29b-41d4-a716-446655440000",
    "sttConfig": null,
    "ttsProvider": "550e8400-e29b-41d4-a716-446655440000",
    "ttsConfig": null,
    "realtimeProvider": "550e8400-e29b-41d4-a716-446655440000",
    "realtimeConfig": null,
    "realtimeInstructions": "Response string",
    "turnHandling": null,
    "enableVoiceReply": false
  },
  "thinkingConfig": null,
  "enableToolSearching": false,
  "toolLoadingMode": {},
  "maxAgentIterations": 456,
  "agentTimeoutSeconds": 456,
  "agentTimeoutMessage": "Response string",
  "requireTextWithFlexCards": false,
  "isMultimodalLlm": false,
  "enableSizeBasedToolResultTruncation": false,
  "toolResultMaxChars": 456,
  "enableVectorMemory": false,
  "longTermMemoryTopK": 456,
  "enableCrossConversationSearch": false,
  "crossConversationLookbackDays": 456,
  "useGatewayFallback": false,
  "gatewayFallbackGroup": "550e8400-e29b-41d4-a716-446655440000",
  "enableSearchMessagesTool": false,
  "enableGetMessageContextTool": false,
  "enableReadAttachmentFullTextTool": false,
  "enableParseAttachmentContentTool": false,
  "enableListAvailableParsersTool": false,
  "enableGetDownloadLinkTool": false,
  "isLocked": false,
  "sourceBuildInAgent": "550e8400-e29b-41d4-a716-446655440000",
  "canUpdate": false,
```

```
  "canDelete": false,
  "team": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Response string"
  },
  "webChatIsActive": false,
  "apiIsActive": false,
  "fileWorkspaceMode": {},
  "fileWorkspaceFolder": "550e8400-e29b-41d4-a716-446655440000",
  "fileWorkspaceStatus": {
    "name": "example.pdf",
    "content": "base64encoded_content",
    "contentType": "application/pdf"
  },
  "fileWorkspaceAvailable": false
}
```


Delete AI Assistant

DELETE `/api/v1/chatbots/{id}`

Parameters

Parameter Name	Required	Type	Description
id	V	string	

Code Examples

Shell/Bash

```
# API call example (Shell)
curl -X DELETE "

  -H "Authorization: Api-Key YOUR_API_KEY"

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

// Request body (payload)
const data = null;

axios.delete(" data, config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.delete(url, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->delete(" [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response Body

Status Code	Description
204	No response body

Duplicate AI Assistant

POST `/api/v1/chatbots/{id}/duplicate/`

Parameters

Parameter Name	Required	Type	Description

id	V	string	

Request Body

Request Parameters

Field	Type	Required	Description
name	string	Yes	

Example Request Schema

```
{
  "name": string
}
```

Example Request Values

```
{
  "name": "Example name"
}
```

Code Examples

Shell/Bash

```
# API call example (Shell)
curl -X POST "

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "name": "Example name"
  }'

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// Request body (payload)
const data = {
    "name": "Example name"
  };

axios.post(" data, config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# Request body (payload)
data = {
    "name": "Example name"
}

response = requests.post(url, json=data, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->post(" [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'name' => 'Example name'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response Body

Status Code: 201

Example Response Schema

```
{
  "id": string (uuid)
  "name": string // Chatbot name. In Agent mode it carries semantic meaning; in other modes it
only distinguishes chatbots.
  "largeLanguageModel": string (uuid) // The large language model used by the chatbot to
generate responses (including organization-defined AI Gateway models); may be omitted on
creation only if the organization has configured a default model in its AI assistant defaults
  "llm":  // The bound model's id, name, and retirement information, read directly from the FK
and returned even if the organization has disabled the model
  {
    "id": string (uuid)
    "name": string
    "retiresAt": string (date) // Provider retirement date; once reached, the daily scheduled
```

```
job switches assistants to the replacement and disables this model. null means no retirement is
scheduled
    "replacement":  // The replacement model after retirement (id and name); null means none is
specified, so no automatic migration occurs on retirement
    {
      "id": string (uuid)
      "name": string
    }
  }
  "condenseQuestionLlm"?: string (uuid) // Question rewriting model: rewrites follow-up
questions into standalone questions before retrieval in RAG reply mode; null follows system
settings (if the selected model is later blocked or disabled by the organization, reads also
return null and follow system settings) (Optional)
  "defaultCondenseQuestionLlm":  // The question rewriting model actually used when following
system settings (id and name); null means the assistant's primary model handles rewriting
(read-only)
  {
    "id": string (uuid)
    "name": string
  }
  "organizationEnforcedSettings": [ // Setting codes enforced for this assistant by the
organization's AI assistant defaults (matching the keys in the AI assistant defaults API);
these fields return the enforced values, and updates with different values are rejected (read-
only; empty for official built-in Agents and MaiGPT)
    string
  ]
  "embeddingModel"?: string (uuid) // Embedding model used to vectorize text; optional
(Optional)
  "rerankerModel"?: string (uuid) // Model used for reranking; optional (Optional)
  "instructions"?: string // Role instructions describing the chatbot's role and behavior.
(Optional)
  "knowledgeBases"?: [ // List of knowledge bases accessible to the chatbot (Optional)
    {
      "id": string (uuid)
      "name": string
    }
  ]
  "databases"?: [ // List of SQL databases accessible to the chatbot (for Text-to-SQL)
(Optional)
    {
      "id": string (uuid)
      "name": string
    }
  ]
  "updatedAt": string (timestamp)
  "organization"?: string (uuid) // The organization the chatbot belongs to; empty for a
personal chatbot (Optional)
  "replyMode"?:  // Reply mode: normal or streaming responses

* `normal` - Normal
* `template` - Template
* `hybrid` - Hybrid
* `agent` - Agent (Optional)
  {
  }
  "template"?: string // Template used by Template and Hybrid modes. (Optional)
  "unanswerableTemplate"?: string // Template used by Template and Hybrid modes when the
```

```
question cannot be answered. (Optional)
  "totalWordsCount"?: integer (int64) // Accumulated total word count used. (Optional)
  "outputMode"?:  // Output mode: text, table, or custom format

* `text` - Text
* `json_schema` - JSON Schema (Optional)
  {
  }
  "rawOutputFormat"?: object // JSON schema definition for the custom output format (Optional)
  "groups"?: [ // List of groups accessible to the chatbot (Optional)
    {
      "id": string (uuid)
      "name": string
    }
  ]
  "tools"?: [ // List of tools available to the chatbot (Optional)
    {
      "id": string (uuid)
      "name": string
      "description": string
      "displayName": string
      "toolType": string
    }
  ]
  "skills"?: [ // List of skills associated with the chatbot (Optional)
    {
      "id": string (uuid)
      "name": string
      "description": string
    }
  ]
  "connectors"?: [ // Connectors associated with this chatbot, gating per-contact OAuth
authorization (Optional)
    {
      "id": string (uuid)
      "name": string
    }
  ]
  "agentMode"?:  // Agent mode: normal, SQL, or workflow mode

* `normal` - Normal
* `canvas` - Canvas
* `team` - Team (Optional)
  {
  }
  "numberOfRetrievedChunks"?: integer // Number of reference chunks to retrieve; defaults to
12, minimum 1 (Optional)
  "defaultLabelRelations"?: object // Assistant-level default knowledge base label filter,
using the same format as query_metadata.label_relations; null means no filtering. Applied as
the lowest-priority fallback only when the caller omits query_metadata. (Optional)
  "useFullRetrievalRange"?: boolean // When enabled, ignores LLM top_k truncation and returns
the full reranker results (Optional)
  "enableEvaluation"?: boolean // Optional
  "enableInlineCitations"?: boolean // Enables inline citations, inserting citation markers
such as [1][2] into responses. (Optional)
  "enableCodeInterpreter"?: boolean // When enabled, provides the Code Interpreter tool to run
code in an isolated container. (Optional)
```

```
  "enableBrowserTool"?: boolean // Enable browser automation tool for web tasks (Optional)
  "enableImageSearch"?: boolean // Provide the image_search tool when any attached knowledge
base uses a multimodal embedding model. Disable to remove the tool entirely. (Optional)
  "enableClaudeStreamRetry"?: boolean // When a Claude streaming call stalls (first-chunk or
mid-stream), abort and re-issue the call once in non-streaming mode. Mid-stream retries send a
reset signal so the client discards any partial output already rendered. Each retry incurs a
second billing for the same prompt. (Optional)
  "customMaxLlmOutputTokens"?: integer // Custom maximum LLM output token count; minimum 512
(Optional)
  "voiceConfig"?: { // Optional
  {
    "enabled"?: boolean // Whether this chatbot can be used as a voice agent. Checked by every
conversation platform (WebChat, SIP phone, admin/marketplace voice test) instead of a per-
platform toggle. (Optional)
    "voiceAgentType"?: string (uuid) // Voice agent mode type. (Optional)
    "sttProvider"?: string (uuid) // Speech-to-Text service provider. (Optional)
    "sttConfig"?: object // STT configuration parameters (JSON). (Optional)
    "ttsProvider"?: string (uuid) // Text-to-Speech service provider. (Optional)
    "ttsConfig"?: object // TTS configuration parameters (JSON). (Optional)
    "realtimeProvider"?: string (uuid) // Realtime end-to-end voice model provider. (Optional)
    "realtimeConfig"?: object // Realtime configuration parameters (JSON). (Optional)
    "realtimeInstructions"?: string // Prompt dedicated to the realtime voice session; falls
back to chatbot instructions when empty (Optional)
    "turnHandling"?: object // Turn-taking and interruption settings for the voice agent.
(Optional)
    "enableVoiceReply"?: boolean // When disabled, the voice agent replies in text only and
does not speak (Optional)
  }
  }
  "thinkingConfig"?: object // Reasoning level: null (model default) or {"reasoning_effort":
"off|minimal|low|medium|high|xhigh|max"} (Optional)
  "enableToolSearching"?: boolean // Legacy field; use tool_loading_mode instead. Writing true
is equivalent to tool_loading_mode=search, and false to all; if both are provided,
tool_loading_mode takes precedence. Reads return whether the tool loading mode is anything
other than loading all tools. (Optional)
  "toolLoadingMode"?:  // Tool loading mode: auto (automatic, based on the tools available in
the current turn and the model), all (load all), or search (dynamic search). New assistants
default to auto; existing assistants without this setting return a value derived from the
legacy toggle (on → search, off → all).

* `auto` - Auto
* `all` - Load all
* `search` - Dynamic search (Optional)
  {
  }
  "maxAgentIterations"?: integer // Maximum number of iterations for AgentWorkflow (1-100,
default: 20) (Optional)
  "agentTimeoutSeconds"?: integer // Timeout in seconds for AgentWorkflow execution (30-1200,
default: 600) (Optional)
  "agentTimeoutMessage"?: string // Custom user-facing message shown when AgentWorkflow times
out (max 500 chars). Leave empty to use the system default. (Optional)
  "requireTextWithFlexCards"?: boolean // When enabled, a turn that would end with only Flex
Message cards and no text for the user is re-issued to the LLM once, asking it to write the
text first and then send the card. Each retry incurs a second billing for the same prompt.
(Optional)
  "isMultimodalLlm": boolean // Whether the chatbot LLM supports multimodal (read-only)
  "enableSizeBasedToolResultTruncation"?: boolean // When enabled, tool results exceeding the
```

```
character threshold are kept as head+tail (with the identifiers found in the cut part) when written to conversation history; knowledge base, SQL and conversation search results keep their 100-character cut either way. Reduces memory bloat from large tool outputs (code interpreter bash stdout, web search results, etc.). (Optional)
  "toolResultMaxChars"?: integer // Character threshold for size-based tool result truncation (500-50000). Only effective when enable_size_based_tool_result_truncation is True. (Optional)
  "enableVectorMemory"?: boolean // When enabled, archived messages are vectorized and processed by fact extraction for semantic retrieval (existing behavior). When disabled, archived messages are discarded and only the active chat history window is used for multi-turn context. (Optional)
  "longTermMemoryTopK"?: integer // Number of long-term memory nodes returned per retrieval (similarity_top_k for vector retrieval); defaults to 10, range 1–50 (Optional)
  "enableCrossConversationSearch"?: boolean // When enabled, the conversation history tools also reach this contact's other conversations in the same inbox, within the lookback window. When disabled, they only reach the current conversation. (Optional)
  "crossConversationLookbackDays"?: integer // How far back cross-conversation search may reach, measured from each conversation's last message (1-365 days). Leave empty to fall back to 90 days. Only effective when enable_cross_conversation_search is True. (Optional)
  "useGatewayFallback"?: boolean // When enabled, use the fallback group instead of the single LLM (Optional)
  "gatewayFallbackGroup"?: string (uuid) // Optional
  "enableSearchMessagesTool"?: boolean // Allow the AI to search past messages in the current conversation. (Optional)
  "enableGetMessageContextTool"?: boolean // Allow the AI to retrieve messages surrounding a specific message for context. (Optional)
  "enableReadAttachmentFullTextTool"?: boolean // Allow the AI to read the full text of plain-text attachments. AGENT mode only. (Optional)
  "enableParseAttachmentContentTool"?: boolean // Allow the AI to parse PDF, Office, audio, and other attachments. AGENT mode only. (Optional)
  "enableListAvailableParsersTool"?: boolean // Allow the AI to list available parsers and their capabilities. AGENT mode only. (Optional)
  "enableGetDownloadLinkTool"?: boolean // Allow the AI to generate shareable download links for produced content. AGENT mode only. (Optional)
  "isLocked": boolean // Locked instance: config follows the official version; only the dedicated KB can be modified
  "sourceBuildInAgent": string (uuid) // Points to the official Build-in Agent blueprint when instantiated by a rental
  "canUpdate": boolean // Return whether the current user can update this resource.
  "canDelete": boolean // Return whether the current user can delete this resource.
  "team":
  {
    "id": string (uuid)
    "name": string
  }
  "webChatIsActive"?: boolean // Optional, create only. Whether the web widget channel starts active. Omitted or null: follows the organization's default for new chatbot channels (inactive unless a platform admin turned it on). Ignored on update; change an existing channel from its channel settings instead. (Optional)
  "apiIsActive"?: boolean // Optional, create only. Whether the API channel starts active. Omitted or null: follows the organization's default for new chatbot channels (inactive unless a platform admin turned it on). Ignored on update; change an existing channel from its channel settings instead. The backstage (admin) channel always starts active and cannot be set here. (Optional)
  "fileWorkspaceMode"?:  // File workspace mode in Work internal conversations: none, bound or user_mount.

* `none` - None
```

```
* `bound` - Bound workspace
* `user_mount` - User mount (Optional)
  {
  }
  "fileWorkspaceFolder"?: string (uuid) // The bound workspace (folder id); required when the
mode is bound, cleared otherwise. (Optional)
  "fileWorkspaceStatus": object // Read-only. {"folder": {"id", "name"} | null, "state": "ok" |
"missing" | "builder_lost_edit" | null}
  "fileWorkspaceAvailable": boolean // Read-only. Whether the organization has the file library
and this agent can configure a file workspace.
}
```

Example Response Values


```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "name": "Response string",
  "largeLanguageModel": "550e8400-e29b-41d4-a716-446655440000",
  "llm": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Response string",
    "retiresAt": "Response string",
    "replacement": {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "Response string"
    }
  },
  "condenseQuestionLlm": "550e8400-e29b-41d4-a716-446655440000",
  "defaultCondenseQuestionLlm": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Response string"
  },
  "organizationEnforcedSettings": [
    "Response string"
  ],
  "embeddingModel": "550e8400-e29b-41d4-a716-446655440000",
  "rerankerModel": "550e8400-e29b-41d4-a716-446655440000",
  "instructions": "Response string",
  "knowledgeBases": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "Response string"
    }
  ],
  "databases": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "Response string"
    }
  ],
  "updatedAt": "Response string",
  "organization": "550e8400-e29b-41d4-a716-446655440000",
  "replyMode": {},
  "template": "Response string",
  "unanswerableTemplate": "Response string",
```

```
  "totalWordsCount": 456,
  "outputMode": {},
  "rawOutputFormat": null,
  "groups": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "Response string"
    }
  ],
  "tools": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "Response string",
      "description": "Response string",
      "displayName": "Response string",
      "toolType": "Response string"
    }
  ],
  "skills": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "Response string",
      "description": "Response string"
    }
  ],
  "connectors": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "Response string"
    }
  ],
  "agentMode": {},
  "numberOfRetrievedChunks": 456,
  "defaultLabelRelations": null,
  "useFullRetrievalRange": false,
  "enableEvaluation": false,
  "enableInlineCitations": false,
  "enableCodeInterpreter": false,
  "enableBrowserTool": false,
  "enableImageSearch": false,
  "enableClaudeStreamRetry": false,
  "customMaxLlmOutputTokens": 456,
  "voiceConfig": {
    "enabled": false,
    "voiceAgentType": "550e8400-e29b-41d4-a716-446655440000",
    "sttProvider": "550e8400-e29b-41d4-a716-446655440000",
    "sttConfig": null,
    "ttsProvider": "550e8400-e29b-41d4-a716-446655440000",
    "ttsConfig": null,
    "realtimeProvider": "550e8400-e29b-41d4-a716-446655440000",
    "realtimeConfig": null,
    "realtimeInstructions": "Response string",
    "turnHandling": null,
    "enableVoiceReply": false
  },
  "thinkingConfig": null,
  "enableToolSearching": false,
```

```
  "toolLoadingMode": {},
  "maxAgentIterations": 456,
  "agentTimeoutSeconds": 456,
  "agentTimeoutMessage": "Response string",
  "requireTextWithFlexCards": false,
  "isMultimodalLlm": false,
  "enableSizeBasedToolResultTruncation": false,
  "toolResultMaxChars": 456,
  "enableVectorMemory": false,
  "longTermMemoryTopK": 456,
  "enableCrossConversationSearch": false,
  "crossConversationLookbackDays": 456,
  "useGatewayFallback": false,
  "gatewayFallbackGroup": "550e8400-e29b-41d4-a716-446655440000",
  "enableSearchMessagesTool": false,
  "enableGetMessageContextTool": false,
  "enableReadAttachmentFullTextTool": false,
  "enableParseAttachmentContentTool": false,
  "enableListAvailableParsersTool": false,
  "enableGetDownloadLinkTool": false,
  "isLocked": false,
  "sourceBuildInAgent": "550e8400-e29b-41d4-a716-446655440000",
  "canUpdate": false,
  "canDelete": false,
  "team": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Response string"
  },
  "webChatIsActive": false,
  "apiIsActive": false,
  "fileWorkspaceMode": {},
  "fileWorkspaceFolder": "550e8400-e29b-41d4-a716-446655440000",
  "fileWorkspaceStatus": {
    "name": "example.pdf",
    "content": "base64encoded_content",
    "contentType": "application/pdf"
  },
  "fileWorkspaceAvailable": false
}
```


Enable or Disable Evaluation

PATCH `/api/v1/chatbots/{id}/enable-evaluation/`

Parameters

Parameter Name	Required	Type	Description

id	V	string

Request Body

Request Parameters

Field	Type	Required	Description
enableEvaluation	boolean	No	

Example Request Schema

```
{
  "enableEvaluation"?: boolean // Optional
}
```

Example Request Values

```
{
  "enableEvaluation": true
}
```

Code Examples

Shell/Bash

```
# API call example (Shell)
curl -X PATCH "

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "enableEvaluation": true
  }'

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// Request body (payload)
const data = {
    "enableEvaluation": true
  };

axios.patch(" data, config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# Request body (payload)
data = {
    "enableEvaluation": True
}

response = requests.patch(url, json=data, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->patch(" [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'enableEvaluation' => true
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response Body

Status Code: 200

Example Response Schema

```
{
  "enableEvaluation"?: boolean // Optional
}
```

Example Response Values

```
{
  "enableEvaluation": false
}
```

List Hooks in the Organization

GET `/api/v1/hooks/`

Hooks are created from Hook templates. The template determines the trigger point and processing behavior; these cannot be specified independently when creating a Hook. Once attached to an AI assistant, a Hook runs on incoming and outgoing messages. For details, see Hook Message Interception in the user manual.

Parameters

Parameter Name	Required	Type	Description
`page`	X	integer	A page number within the paginated result set.
`pageSize`	X	integer	Number of results to return per page.
`search`	X	string	A search term.

Code Examples

Shell/Bash

```
# API Call Example (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/hooks/?page=1&pageSize=1&search=example"

  -H "Authorization: Api-Key YOUR_API_KEY"

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/hooks/?page=1&pageSize=1&search=example",
config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/hooks/?page=1&pageSize=1&search=example"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->get("https://api.maiagent.ai/api/v1/hooks/?
page=1&pageSize=1&search=example", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response Body

Status Code: 200

Example Response Schema

```
{
  "count": integer
  "next"?: string (uri) // Optional
  "previous"?: string (uri) // Optional
  "results": [
    {
      "id": string (uuid)
      "organization": string (uuid)
      "templateId": string (uuid)
      "templateName": string
      "templateTypeLabel": string
      "scope": string
      "name": string
      "description": string
      "triggerPoint": string
      "action": string
```

```
      "handlerType": string
      "config": object
      "blockMessage": string
      "enabled": boolean
      "createdBy": object
      "chatbots": [ // Attached AI assistants for the list column. Uses the prefetched
``chatbot_attachments`` (see ``HookViewSet.get_queryset``) to avoid N+1.
        object
      ]
      "canUpdate": boolean // Return whether the current user can update this resource.
      "canDelete": boolean // Return whether the current user can delete this resource.
      "createdAt": string (timestamp)
      "updatedAt": string (timestamp)
    }
  ]
}
```

Example Response Values

```
{
  "count": 123,
  "next": "http://api.example.org/accounts/?page=4",
  "previous": "http://api.example.org/accounts/?page=2",
  "results": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "organization": "550e8400-e29b-41d4-a716-446655440000",
      "templateId": "550e8400-e29b-41d4-a716-446655440000",
      "templateName": "Response string",
      "templateTypeLabel": "Response string",
      "scope": "Response string",
      "name": "Response string",
      "description": "Response string",
      "triggerPoint": "Response string",
      "action": "Response string",
      "handlerType": "Response string",
      "config": null,
      "blockMessage": "Response string",
      "enabled": false,
      "createdBy": {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "name": "Example response name",
        "description": "Example response description"
      },
      "chatbots": [
        {
          "id": "550e8400-e29b-41d4-a716-446655440000",
          "name": "Example response name",
          "description": "Example response description"
        }
      ],
      "canUpdate": false,
      "canDelete": false,
      "createdAt": "Response string",
      "updatedAt": "Response string"
```

```
    }
  ]
}
```

Create a Hook from a Template

POST `/api/v1/hooks/`

Request Body

Request Parameters

Field	Type	Required	Description
templateId	string (uuid)	Yes	
name	string	Yes	
description	string	No	
config	object	No	
blockMessage	string	No	
enabled	boolean	No	

Example Request Schema

```
{
  "templateId": string (uuid)
  "name": string
  "description"?: string // Optional
  "config"?: object // Optional
  "blockMessage"?: string // Optional
  "enabled"?: boolean // Optional
}
```

Example Request Values

```
{
  "template_id": "00000000-0000-0000-0000-000000000001",
  "name": "Customer PII Redaction",
  "description": "Mask phone numbers and emails in inbound messages.",
  "config": {
    "data": {
      "patterns": [
```

```
        "phone",
        "email"
      ],
      "mode": "mask"
    }
  },
  "block_message": "",
  "enabled": true
}
```

Code Examples

Shell/Bash

```
# API Call Example (Shell)
curl -X POST "https://api.maiagent.ai/api/v1/hooks/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "template_id": "00000000-0000-0000-0000-000000000001",
    "name": "Customer PII Redaction",
    "description": "Mask phone numbers and emails in inbound messages.",
    "config": {
      "data": {
        "patterns": [
          "phone",
          "email"
        ],
        "mode": "mask"
      }
    },
    "block_message": "",
    "enabled": true
  }'

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// Request Body (payload)
const data = {
    "template_id": "00000000-0000-0000-0000-000000000001",
    "name": "Customer PII Redaction",
    "description": "Mask phone numbers and emails in inbound messages.",
    "config": {
      "data": {
        "patterns": [
          "phone",
          "email"
        ],
        "mode": "mask"
      }
    },
    "block_message": "",
    "enabled": true
  };

axios.post("https://api.maiagent.ai/api/v1/hooks/", data, config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/hooks/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# Request Body (payload)
data = {
    "template_id": "00000000-0000-0000-0000-000000000001",
    "name": "Customer PII Redaction",
    "description": "Mask phone numbers and emails in inbound messages.",
    "config": {
        "data": {
            "patterns": [
                "phone",
                "email"
            ],
            "mode": "mask"
        }
    },
    "block_message": "",
    "enabled": True
}

response = requests.post(url, json=data, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->post("https://api.maiagent.ai/api/v1/hooks/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'template_id' => '00000000-0000-0000-0000-000000000001',
            'name' => 'Customer PII Redaction',
            'description' => 'Mask phone numbers and emails in inbound messages.',
            'config' => [
                'data' => [
                    'patterns' => [
                        'phone',
                        'email'
                    ],
                    'mode' => 'mask'
                ]
            ],
            'block_message' => '',
            'enabled' => true
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response Body

Status Code: 201

Example Response Schema

```
{
  "id": string (uuid)
  "organization": string (uuid)
  "templateId": string (uuid)
  "templateName": string
  "templateTypeLabel": string
  "scope": string
  "name": string
  "description": string
  "triggerPoint": string
  "action": string
  "handlerType": string
  "config": object
  "blockMessage": string
  "enabled": boolean
  "createdBy": object
  "chatbots": [ // Attached AI assistants for the list column. Uses the prefetched
``chatbot_attachments`` (see ``HookViewSet.get_queryset``) to avoid N+1.
    object
  ]
  "canUpdate": boolean // Return whether the current user can update this resource.
  "canDelete": boolean // Return whether the current user can delete this resource.
  "createdAt": string (timestamp)
  "updatedAt": string (timestamp)
}
```

Example Response Values

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "organization": "550e8400-e29b-41d4-a716-446655440000",
  "templateId": "550e8400-e29b-41d4-a716-446655440000",
  "templateName": "Response string",
  "templateTypeLabel": "Response string",
  "scope": "Response string",
  "name": "Response string",
  "description": "Response string",
  "triggerPoint": "Response string",
  "action": "Response string",
  "handlerType": "Response string",
  "config": null,
  "blockMessage": "Response string",
  "enabled": false,
  "createdBy": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Example response name",
    "description": "Example response description"
  },
  "chatbots": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "Example response name",
      "description": "Example response description"
    }
```

```
  ],
  "canUpdate": false,
  "canDelete": false,
  "createdAt": "Response string",
  "updatedAt": "Response string"
}
```

Retrieve a Specific Hook

GET `/api/v1/hooks/{id}`

Parameters

Parameter Name	Required	Type	Description
`id`	V	string	

Code Examples

Shell/Bash

```
# API Call Example (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/hooks/550e8400-e29b-41d4-a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/hooks/550e8400-e29b-41d4-a716-446655440000/",
config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/hooks/550e8400-e29b-41d4-a716-446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->get("https://api.maiagent.ai/api/v1/hooks/550e8400-e29b-41d4-
a716-446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response Body

Status Code: 200

Example Response Schema

```
{
  "id": string (uuid)
  "organization": string (uuid)
  "templateId": string (uuid)
  "templateName": string
  "templateTypeLabel": string
  "scope": string
  "name": string
  "description": string
  "triggerPoint": string
  "action": string
  "handlerType": string
  "config": object
  "blockMessage": string
  "enabled": boolean
  "createdBy": object
```

```
  "chatbots": [ // Attached AI assistants for the list column. Uses the prefetched
``chatbot_attachments`` (see ``HookViewSet.get_queryset``) to avoid N+1.
    object
  ]
  "canUpdate": boolean // Return whether the current user can update this resource.
  "canDelete": boolean // Return whether the current user can delete this resource.
  "createdAt": string (timestamp)
  "updatedAt": string (timestamp)
}
```

Example Response Values


```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "organization": "550e8400-e29b-41d4-a716-446655440000",
  "templateId": "550e8400-e29b-41d4-a716-446655440000",
  "templateName": "Response string",
  "templateTypeLabel": "Response string",
  "scope": "Response string",
  "name": "Response string",
  "description": "Response string",
  "triggerPoint": "Response string",
  "action": "Response string",
  "handlerType": "Response string",
  "config": null,
  "blockMessage": "Response string",
  "enabled": false,
  "createdBy": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Example response name",
    "description": "Example response description"
  },
  "chatbots": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "Example response name",
      "description": "Example response description"
    }
  ],
  "canUpdate": false,
  "canDelete": false,
  "createdAt": "Response string",
  "updatedAt": "Response string"
}
```


Partially Update a Hook

PATCH `/api/v1/hooks/{id}`

Parameters

Parameter Name	Required	Type	Description
id	V	string	

Request Body

Request Parameters

Field	Type	Required	Description
name	string	No	
description	string	No	
config	object	No	
blockMessage	string	No	
enabled	boolean	No	

Example Request Schema

```
{
  "name"?: string // Optional
  "description"?: string // Optional
  "config"?: object // Optional
  "blockMessage"?: string // Optional
  "enabled"?: boolean // Optional
}
```

Example Request Values

```
{
  "name": "Example name",
  "description": "Example string",
  "config": null,
  "blockMessage": "Example string",
  "enabled": true
}
```

Code Examples

Shell/Bash

```
# API Call Example (Shell)
curl -X PATCH "https://api.maiagent.ai/api/v1/hooks/550e8400-e29b-41d4-a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "name": "Example name",
    "description": "Example string",
    "config": null,
    "blockMessage": "Example string",
    "enabled": true
  }'

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// Request Body (payload)
const data = {
    "name": "Example name",
    "description": "Example string",
    "config": null,
    "blockMessage": "Example string",
    "enabled": true
  };

axios.patch("https://api.maiagent.ai/api/v1/hooks/550e8400-e29b-41d4-a716-446655440000/",
data, config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/hooks/550e8400-e29b-41d4-a716-446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# Request Body (payload)
data = {
    "name": "Example name",
    "description": "Example string",
    "config": None,
    "blockMessage": "Example string",
    "enabled": True
}

response = requests.patch(url, json=data, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->patch("https://api.maiagent.ai/api/v1/hooks/550e8400-e29b-41d4-a716-446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'name' => 'Example name',
            'description' => 'Example string',
            'config' => null,
            'blockMessage' => 'Example string',
            'enabled' => true
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response Body

Status Code: 200

Example Response Schema

```
{
  "id": string (uuid)
  "organization": string (uuid)
  "templateId": string (uuid)
  "templateName": string
  "templateTypeLabel": string
  "scope": string
  "name": string
```

```
  "description": string
  "triggerPoint": string
  "action": string
  "handlerType": string
  "config": object
  "blockMessage": string
  "enabled": boolean
  "createdBy": object
  "chatbots": [ // Attached AI assistants for the list column. Uses the prefetched
``chatbot_attachments`` (see ``HookViewSet.get_queryset``) to avoid N+1.
    object
  ]
  "canUpdate": boolean // Return whether the current user can update this resource.
  "canDelete": boolean // Return whether the current user can delete this resource.
  "createdAt": string (timestamp)
  "updatedAt": string (timestamp)
}
```

Example Response Values

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "organization": "550e8400-e29b-41d4-a716-446655440000",
  "templateId": "550e8400-e29b-41d4-a716-446655440000",
  "templateName": "Response string",
  "templateTypeLabel": "Response string",
  "scope": "Response string",
  "name": "Response string",
  "description": "Response string",
  "triggerPoint": "Response string",
  "action": "Response string",
  "handlerType": "Response string",
  "config": null,
  "blockMessage": "Response string",
  "enabled": false,
  "createdBy": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Example response name",
    "description": "Example response description"
  },
  "chatbots": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "Example response name",
      "description": "Example response description"
    }
  ],
  "canUpdate": false,
  "canDelete": false,
  "createdAt": "Response string",
  "updatedAt": "Response string"
}
```

Delete Hook

DELETE `/api/v1/hooks/{id}`

Parameters

Parameter Name	Required	Type	Description
`id`	V	string	

Code Examples

Shell/Bash

```
# Example API Call (Shell)
curl -X DELETE "https://api.maiagent.ai/api/v1/hooks/550e8400-e29b-41d4-a716-
446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

// Request Body (payload)
const data = null;

axios.delete("https://api.maiagent.ai/api/v1/hooks/550e8400-e29b-41d4-a716-446655440000/",
data, config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/hooks/550e8400-e29b-41d4-a716-446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.delete(url, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->delete("https://api.maiagent.ai/api/v1/hooks/550e8400-e29b-41d4-a716-446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response Body

Status Code	Description
204	No response body

List Hooks Attached to an AI Assistant

GET `/api/v1/chatbots/{chatbotId}/hooks/`

Parameters

Parameter Name	Required	Type	Description

chatbotId	V	string

Code Examples

Shell/Bash

```
# Example API Call (Shell)
curl -X GET "

  -H "Authorization: Api-Key YOUR_API_KEY"

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get(" config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->get(" [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response Body

Status Code: 200

Example Response Schema

```
{
  "results": [
    {
      "id": string (uuid)
      "name": string
      "scope": string
      "templateName": string
      "templateTypeLabel": string
      "triggerPoint": string
      "action": string
      "enabled": boolean
      "order": integer
    }
  ]
}
```

Example Response Values

```
{
  "results": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "Response string",
      "scope": "Response string",
      "templateName": "Response string",
      "templateTypeLabel": "Response string",
      "triggerPoint": "Response string",
      "action": "Response string",
      "enabled": false,
      "order": 456
    }
  ]
}
```

Replace All Hooks Attached to an AI Assistant

PUT `/api/v1/chatbots/{chatbotId}/hooks/`

Parameters

Parameter Name	Required	Type	Description
chatbotId	V	string	

Request Body

Request Parameters

Field	Type	Required	Description
hookIds	array[string]	Yes	

Example Request Schema

```
{
  "hookIds": [
    string (uuid)
  ]
}
```

Example Request Values

```
{
  "hookIds": [
    "550e8400-e29b-41d4-a716-446655440000"
  ]
}
```

Code Examples

Shell/Bash

```
# Example API Call (Shell)
curl -X PUT "

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "hookIds": [
      "550e8400-e29b-41d4-a716-446655440000"
    ]
  }'

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// Request Body (payload)
const data = {
    "hookIds": [
      "550e8400-e29b-41d4-a716-446655440000"
    ]
  };

axios.put(" data, config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# Request Body (payload)
data = {
    "hookIds": [
        "550e8400-e29b-41d4-a716-446655440000"
    ]
}

response = requests.put(url, json=data, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->put(" [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'hookIds' => [
                '550e8400-e29b-41d4-a716-446655440000'
            ]
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response Body

Status Code: 200

Example Response Schema

```
{
  "results": [
    {
      "id": string (uuid)
      "name": string
      "scope": string
      "templateName": string
      "templateTypeLabel": string
      "triggerPoint": string
      "action": string
      "enabled": boolean
```

```
      "order": integer
    }
  ]
}
```

Example Response Values

```
{
  "results": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "Response string",
      "scope": "Response string",
      "templateName": "Response string",
      "templateTypeLabel": "Response string",
      "triggerPoint": "Response string",
      "action": "Response string",
      "enabled": false,
      "order": 456
    }
  ]
}
```

List Schedules

GET `/api/v1/schedules/`

A schedule runs an instruction through an AI assistant at the specified time; the system automatically provisions a dedicated contact and conversation when the schedule is created.

Parameters

Parameter Name	Required	Type	Description
`page`	X	integer	A page number within the paginated result set.
`pageSize`	X	integer	Number of results to return per page.

Code Examples

Shell/Bash

```
# API Call Example (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/schedules/?page=1&pageSize=1"

  -H "Authorization: Api-Key YOUR_API_KEY"

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/schedules/?page=1&pageSize=1", config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```python
import requests

url = "https://api.maiagent.ai/api/v1/schedules/?page=1&pageSize=1"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->get("https://api.maiagent.ai/api/v1/schedules/?
page=1&pageSize=1", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response Body

Status Code: 200

Example Response Schema

```
{
  "count": integer
  "next"?: string (uri) // Optional
  "previous"?: string (uri) // Optional
  "results": [
    {
      "id": string (uuid)
      "name": string
      "prompt": string
      "chatbot": string (uuid)
      "chatbotName": string
      "executionMode": string (enum: in_context, isolated) // * `in_context` - In Context
* `isolated` - Isolated
      "scheduleType": string (enum: cron, interval, one_shot) // * `cron` - Cron
* `interval` - Interval
* `one_shot` - One Shot
      "cronExpression"?: string // Optional
      "intervalSeconds"?: integer // Optional
      "oneShotAt"?: string (timestamp) // Optional
      "deliveryConversationIds"?: [ // Optional
        string (uuid)
      ]
      "deliveryWebhookUrls"?: [ // Optional
        string (uri)
      ]
      "saveResultToContext"?: boolean // Optional
      "enabled"?: boolean // Optional
      "lastExecutedAt"?: string (timestamp) // Optional
      "executionCount"?: integer // Optional
      "maxExecutions"?: integer // Optional
      "endDate"?: string (date) // Last day the schedule runs, in its own timezone; the first
run due after that day turns it off. (Optional)
      "countsTowardLimit": boolean
      "createdAt": string (timestamp)
    }
  ]
}
```

Example Response Values

```
{
  "count": 123,
  "next": "http://api.example.org/accounts/?page=4",
  "previous": "http://api.example.org/accounts/?page=2",
  "results": [
    {
```

```
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "Response string",
      "prompt": "Response string",
      "chatbot": "550e8400-e29b-41d4-a716-446655440000",
      "chatbotName": "Response string",
      "executionMode": "in_context",
      "scheduleType": "cron",
      "cronExpression": "Response string",
      "intervalSeconds": 456,
      "oneShotAt": "Response string",
      "deliveryConversationIds": [
        "550e8400-e29b-41d4-a716-446655440000"
      ],
      "deliveryWebhookUrls": [
        "https://example.com/file.jpg"
      ],
      "saveResultToContext": false,
      "enabled": false,
      "lastExecutedAt": "Response string",
      "executionCount": 456,
      "maxExecutions": 456,
      "endDate": "Response string",
      "countsTowardLimit": false,
      "createdAt": "Response string"
    }
  ]
}
```


Create Schedule

POST `/api/v1/schedules/`

Request Body

Request Parameters

Field	Type	Required	Description
chatbot	string (uuid)	Yes	
name	string	Yes	
executionMode	string (enum: in_context, isolated)	Yes	`in_context` : In Context ; `isolated` : Isolated;
prompt	string	Yes	
contextVariables	object	No	

Field	Type	Required	Description
inbox	string (uuid)	Yes	
saveResultToContext	boolean	No	
deliveryConversationIds	array[string]	No	
deliveryWebhookUrls	array[string]	No	
scheduleType	string (enum: cron, interval, one_shot)	Yes	`cron` : Cron ; `interval` : Interval ; `one_shot` : One Shot;
cronExpression	string	No	
intervalSeconds	integer	No	
oneShotAt	string (timestamp)	No	
timezone	string	No	
enabled	boolean	No	
maxExecutions	integer	No	
endDate	string (date)	No	Last day the schedule runs, in its own timezone; the first run due after that day turns it off.

Example Request Schema

```
{
  "chatbot": string (uuid)
  "name": string
  "executionMode": string (enum: in_context, isolated) // * `in_context` - In Context
* `isolated` - Isolated
  "prompt": string
  "contextVariables"?: object // Optional
  "inbox": string (uuid)
  "saveResultToContext"?: boolean // Optional
  "deliveryConversationIds"?: [ // Optional
    string (uuid)
  ]
  "deliveryWebhookUrls"?: [ // Optional
    string (uri)
  ]
  "scheduleType": string (enum: cron, interval, one_shot) // * `cron` - Cron
* `interval` - Interval
* `one_shot` - One Shot
  "cronExpression"?: string // Optional
  "intervalSeconds"?: integer // Optional
  "oneShotAt"?: string (timestamp) // Optional
  "timezone"?: string // Optional
  "enabled"?: boolean // Optional
  "maxExecutions"?: integer // Optional
  "endDate"?: string (date) // Last day the schedule runs, in its own timezone; the first run
```

```
due after that day turns it off. (Optional)
}
```

Example Request Values

```
{
  "chatbot": "550e8400-e29b-41d4-a716-446655440000",
  "name": "Example name",
  "executionMode": "in_context",
  "prompt": "Example string",
  "contextVariables": null,
  "inbox": "550e8400-e29b-41d4-a716-446655440000",
  "saveResultToContext": true,
  "deliveryConversationIds": [
    "550e8400-e29b-41d4-a716-446655440000"
  ],
  "deliveryWebhookUrls": [
    "https://example.com/file.jpg"
  ],
  "scheduleType": "cron",
  "cronExpression": "Example string",
  "intervalSeconds": 123,
  "oneShotAt": "Example string",
  "timezone": "Example string",
  "enabled": true,
  "maxExecutions": 123,
  "endDate": "Example string"
}
```

Code Examples

Shell/Bash

```
# API Call Example (Shell)
curl -X POST "https://api.maiagent.ai/api/v1/schedules/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "chatbot": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Example name",
    "executionMode": "in_context",
    "prompt": "Example string",
    "contextVariables": null,
    "inbox": "550e8400-e29b-41d4-a716-446655440000",
    "saveResultToContext": true,
    "deliveryConversationIds": [
      "550e8400-e29b-41d4-a716-446655440000"
    ],
    "deliveryWebhookUrls": [
      "https://example.com/file.jpg"
    ],
    "scheduleType": "cron",
    "cronExpression": "Example string",
    "intervalSeconds": 123,
    "oneShotAt": "Example string",
    "timezone": "Example string",
    "enabled": true,
    "maxExecutions": 123,
    "endDate": "Example string"
  }'

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// Request Body (payload)
const data = {
    "chatbot": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Example name",
    "executionMode": "in_context",
    "prompt": "Example string",
    "contextVariables": null,
    "inbox": "550e8400-e29b-41d4-a716-446655440000",
    "saveResultToContext": true,
    "deliveryConversationIds": [
      "550e8400-e29b-41d4-a716-446655440000"
    ],
    "deliveryWebhookUrls": [
      "https://example.com/file.jpg"
    ],
    "scheduleType": "cron",
    "cronExpression": "Example string",
    "intervalSeconds": 123,
    "oneShotAt": "Example string",
    "timezone": "Example string",
    "enabled": true,
    "maxExecutions": 123,
    "endDate": "Example string"
  };

axios.post("https://api.maiagent.ai/api/v1/schedules/", data, config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/schedules/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# Request Body (payload)
data = {
    "chatbot": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Example name",
    "executionMode": "in_context",
    "prompt": "Example string",
    "contextVariables": None,
    "inbox": "550e8400-e29b-41d4-a716-446655440000",
    "saveResultToContext": True,
    "deliveryConversationIds": [
        "550e8400-e29b-41d4-a716-446655440000"
    ],
    "deliveryWebhookUrls": [
        "https://example.com/file.jpg"
    ],
    "scheduleType": "cron",
    "cronExpression": "Example string",
    "intervalSeconds": 123,
    "oneShotAt": "Example string",
    "timezone": "Example string",
    "enabled": True,
    "maxExecutions": 123,
    "endDate": "Example string"
}

response = requests.post(url, json=data, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->post("https://api.maiagent.ai/api/v1/schedules/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'chatbot' => '550e8400-e29b-41d4-a716-446655440000',
            'name' => 'Example name',
            'executionMode' => 'in_context',
            'prompt' => 'Example string',
            'contextVariables' => null,
            'inbox' => '550e8400-e29b-41d4-a716-446655440000',
            'saveResultToContext' => true,
            'deliveryConversationIds' => [
                '550e8400-e29b-41d4-a716-446655440000'
            ],
            'deliveryWebhookUrls' => [
                'https://example.com/file.jpg'
            ],
            'scheduleType' => 'cron',
            'cronExpression' => 'Example string',
            'intervalSeconds' => 123,
            'oneShotAt' => 'Example string',
            'timezone' => 'Example string',
            'enabled' => true,
            'maxExecutions' => 123,
            'endDate' => 'Example string'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response Body

Status Code: 201

Example Response Schema

```
{
  "id": string (uuid)
  "chatbot": string (uuid)
  "organization": string (uuid)
  "name": string
  "executionMode": string (enum: in_context, isolated) // * `in_context` - In Context
* `isolated` - Isolated
  "prompt": string
  "contextVariables"?: object // Optional
  "inbox": string (uuid)
  "saveResultToContext"?: boolean // Optional
  "dedicatedContact": string (uuid)
  "dedicatedConversation": string (uuid)
  "deliveryConversationIds"?: [ // Optional
    string (uuid)
  ]
  "deliveryWebhookUrls"?: [ // Optional
    string (uri)
  ]
  "scheduleType": string (enum: cron, interval, one_shot) // * `cron` - Cron
* `interval` - Interval
* `one_shot` - One Shot
  "cronExpression"?: string // Optional
  "intervalSeconds"?: integer // Optional
  "oneShotAt"?: string (timestamp) // Optional
  "timezone"?: string // Optional
  "periodicTask": integer
  "enabled"?: boolean // Optional
  "lastExecutedAt": string (timestamp)
  "executionCount": integer
  "maxExecutions"?: integer // Optional
  "endDate"?: string (date) // Last day the schedule runs, in its own timezone; the first run
due after that day turns it off. (Optional)
  "countsTowardLimit": boolean
  "createdAt": string (timestamp)
  "updatedAt": string (timestamp)
}
```

Example Response Values

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "chatbot": "550e8400-e29b-41d4-a716-446655440000",
  "organization": "550e8400-e29b-41d4-a716-446655440000",
  "name": "Response string",
  "executionMode": "in_context",
```

```
  "prompt": "Response string",
  "contextVariables": null,
  "inbox": "550e8400-e29b-41d4-a716-446655440000",
  "saveResultToContext": false,
  "dedicatedContact": "550e8400-e29b-41d4-a716-446655440000",
  "dedicatedConversation": "550e8400-e29b-41d4-a716-446655440000",
  "deliveryConversationIds": [
    "550e8400-e29b-41d4-a716-446655440000"
  ],
  "deliveryWebhookUrls": [
    "https://example.com/file.jpg"
  ],
  "scheduleType": "cron",
  "cronExpression": "Response string",
  "intervalSeconds": 456,
  "oneShotAt": "Response string",
  "timezone": "Response string",
  "periodicTask": 456,
  "enabled": false,
  "lastExecutedAt": "Response string",
  "executionCount": 456,
  "maxExecutions": 456,
  "endDate": "Response string",
  "countsTowardLimit": false,
  "createdAt": "Response string",
  "updatedAt": "Response string"
}
```


Retrieve a Specific Schedule

GET `/api/v1/schedules/{id}`

Parameters

Parameter Name	Required	Type	Description
`id`	V	string	A UUID string identifying this Chatbot Schedule.

Code Examples

Shell/Bash

```
# API Call Example (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/schedules/550e8400-e29b-41d4-a716-
446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/schedules/550e8400-e29b-41d4-a716-
446655440000/", config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```python
import requests

url = "https://api.maiagent.ai/api/v1/schedules/550e8400-e29b-41d4-a716-446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->get("https://api.maiagent.ai/api/v1/schedules/550e8400-e29b-41d4-
a716-446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response Body

Status Code: 200

Example Response Schema

```
{
  "id": string (uuid)
  "chatbot": string (uuid)
  "organization": string (uuid)
  "name": string
  "executionMode": string (enum: in_context, isolated) // * `in_context` - In Context
* `isolated` - Isolated
  "prompt": string
  "contextVariables"?: object // Optional
  "inbox": string (uuid)
  "saveResultToContext"?: boolean // Optional
  "dedicatedContact": string (uuid)
  "dedicatedConversation": string (uuid)
  "deliveryConversationIds"?: [ // Optional
    string (uuid)
  ]
  "deliveryWebhookUrls"?: [ // Optional
    string (uri)
  ]
  "scheduleType": string (enum: cron, interval, one_shot) // * `cron` - Cron
* `interval` - Interval
* `one_shot` - One Shot
  "cronExpression"?: string // Optional
  "intervalSeconds"?: integer // Optional
  "oneShotAt"?: string (timestamp) // Optional
  "timezone"?: string // Optional
  "periodicTask": integer
  "enabled"?: boolean // Optional
  "lastExecutedAt": string (timestamp)
  "executionCount": integer
  "maxExecutions"?: integer // Optional
  "endDate"?: string (date) // Last day the schedule runs, in its own timezone; the first run
due after that day turns it off. (Optional)
  "countsTowardLimit": boolean
  "createdAt": string (timestamp)
  "updatedAt": string (timestamp)
}
```

Example Response Values

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "chatbot": "550e8400-e29b-41d4-a716-446655440000",
  "organization": "550e8400-e29b-41d4-a716-446655440000",
  "name": "Response string",
  "executionMode": "in_context",
```

```
  "prompt": "Response string",
  "contextVariables": null,
  "inbox": "550e8400-e29b-41d4-a716-446655440000",
  "saveResultToContext": false,
  "dedicatedContact": "550e8400-e29b-41d4-a716-446655440000",
  "dedicatedConversation": "550e8400-e29b-41d4-a716-446655440000",
  "deliveryConversationIds": [
    "550e8400-e29b-41d4-a716-446655440000"
  ],
  "deliveryWebhookUrls": [
    "https://example.com/file.jpg"
  ],
  "scheduleType": "cron",
  "cronExpression": "Response string",
  "intervalSeconds": 456,
  "oneShotAt": "Response string",
  "timezone": "Response string",
  "periodicTask": 456,
  "enabled": false,
  "lastExecutedAt": "Response string",
  "executionCount": 456,
  "maxExecutions": 456,
  "endDate": "Response string",
  "countsTowardLimit": false,
  "createdAt": "Response string",
  "updatedAt": "Response string"
}
```


Partially Update Schedule

PATCH `/api/v1/schedules/{id}`

Parameters

Parameter Name	Required	Type	Description
`id`	V	string	A UUID string identifying this Chatbot Schedule.

Request Body

Request Parameters

Field	Type	Required	Description
name	string	No	
prompt	string	No	
contextVariables	object	No	
saveResultToContext	boolean	No	
deliveryConversationIds	array[string]	No	
deliveryWebhookUrls	array[string]	No	
scheduleType	string (enum: cron, interval, one_shot)	No	`cron` : Cron ; `interval` : Interval ; `one_shot` : One Shot;
cronExpression	string	No	
intervalSeconds	integer	No	
oneShotAt	string (timestamp)	No	
timezone	string	No	
enabled	boolean	No	
maxExecutions	integer	No	
endDate	string (date)	No	Last day the schedule runs, in its own timezone; the first run due after that day turns it off.

Example Request Schema

```
{
  "name"?: string // Optional
  "prompt"?: string // Optional
  "contextVariables"?: object // Optional
  "saveResultToContext"?: boolean // Optional
  "deliveryConversationIds"?: [ // Optional
    string (uuid)
  ]
  "deliveryWebhookUrls"?: [ // Optional
    string (uri)
  ]
  "scheduleType"?: string (enum: cron, interval, one_shot) // * `cron` - Cron
* `interval` - Interval
* `one_shot` - One Shot (Optional)
  "cronExpression"?: string // Optional
  "intervalSeconds"?: integer // Optional
  "oneShotAt"?: string (timestamp) // Optional
  "timezone"?: string // Optional
  "enabled"?: boolean // Optional
  "maxExecutions"?: integer // Optional
  "endDate"?: string (date) // Last day the schedule runs, in its own timezone; the first run
due after that day turns it off. (Optional)
}
```

Example Request Values


```
{
  "name": "Example name",
  "prompt": "Example string",
  "contextVariables": null,
  "saveResultToContext": true,
  "deliveryConversationIds": [
    "550e8400-e29b-41d4-a716-446655440000"
  ],
  "deliveryWebhookUrls": [
    "https://example.com/file.jpg"
  ],
  "scheduleType": "cron",
  "cronExpression": "Example string",
  "intervalSeconds": 123,
  "oneShotAt": "Example string",
  "timezone": "Example string",
  "enabled": true,
  "maxExecutions": 123,
  "endDate": "Example string"
}
```


Code Examples

Shell/Bash

```
# API call example (Shell)
curl -X PATCH "https://api.maiagent.ai/api/v1/schedules/550e8400-e29b-41d4-a716-
446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "name": "Example name",
    "prompt": "Example string",
    "contextVariables": null,
    "saveResultToContext": true,
    "deliveryConversationIds": [
      "550e8400-e29b-41d4-a716-446655440000"
    ],
    "deliveryWebhookUrls": [
      "https://example.com/file.jpg"
    ],
    "scheduleType": "cron",
    "cronExpression": "Example string",
    "intervalSeconds": 123,
    "oneShotAt": "Example string",
    "timezone": "Example string",
    "enabled": true,
    "maxExecutions": 123,
    "endDate": "Example string"
  }'

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// Request body (payload)
const data = {
    "name": "Example name",
    "prompt": "Example string",
    "contextVariables": null,
    "saveResultToContext": true,
    "deliveryConversationIds": [
      "550e8400-e29b-41d4-a716-446655440000"
    ],
    "deliveryWebhookUrls": [
      "https://example.com/file.jpg"
    ],
    "scheduleType": "cron",
    "cronExpression": "Example string",
    "intervalSeconds": 123,
    "oneShotAt": "Example string",
    "timezone": "Example string",
    "enabled": true,
    "maxExecutions": 123,
    "endDate": "Example string"
  };

axios.patch("https://api.maiagent.ai/api/v1/schedules/550e8400-e29b-41d4-a716-
446655440000/", data, config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/schedules/550e8400-e29b-41d4-a716-446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# Request body (payload)
data = {
    "name": "Example name",
    "prompt": "Example string",
    "contextVariables": None,
    "saveResultToContext": True,
    "deliveryConversationIds": [
        "550e8400-e29b-41d4-a716-446655440000"
    ],
    "deliveryWebhookUrls": [
        "https://example.com/file.jpg"
    ],
    "scheduleType": "cron",
    "cronExpression": "Example string",
    "intervalSeconds": 123,
    "oneShotAt": "Example string",
    "timezone": "Example string",
    "enabled": True,
    "maxExecutions": 123,
    "endDate": "Example string"
}

response = requests.patch(url, json=data, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->patch("https://api.maiagent.ai/api/v1/schedules/550e8400-e29b-41d4-a716-446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'name' => 'Example name',
            'prompt' => 'Example string',
            'contextVariables' => null,
            'saveResultToContext' => true,
            'deliveryConversationIds' => [
                '550e8400-e29b-41d4-a716-446655440000'
            ],
            'deliveryWebhookUrls' => [
                'https://example.com/file.jpg'
            ],
            'scheduleType' => 'cron',
            'cronExpression' => 'Example string',
            'intervalSeconds' => 123,
            'oneShotAt' => 'Example string',
            'timezone' => 'Example string',
            'enabled' => true,
            'maxExecutions' => 123,
            'endDate' => 'Example string'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response Body

Status code: 200

Example Response Schema

```
{
  "id": string (uuid)
  "chatbot": string (uuid)
  "organization": string (uuid)
  "name": string
  "executionMode":
  {
  }
  "prompt": string
  "contextVariables"?: object // Optional
  "inbox": string (uuid)
  "saveResultToContext"?: boolean // Optional
  "dedicatedContact": string (uuid)
  "dedicatedConversation": string (uuid)
  "deliveryConversationIds"?: [ // Optional
    string (uuid)
  ]
  "deliveryWebhookUrls"?: [ // Optional
    string (uri)
  ]
  "scheduleType": string (enum: cron, interval, one_shot) // * `cron` - Cron
* `interval` - Interval
* `one_shot` - One Shot
  "cronExpression"?: string // Optional
  "intervalSeconds"?: integer // Optional
  "oneShotAt"?: string (timestamp) // Optional
  "timezone"?: string // Optional
  "periodicTask": integer
  "enabled"?: boolean // Optional
  "lastExecutedAt": string (timestamp)
  "executionCount": integer
  "maxExecutions"?: integer // Optional
  "endDate"?: string (date) // Last day the schedule runs, in its own timezone; the first run
due after that day turns it off. (Optional)
  "countsTowardLimit": boolean
  "createdAt": string (timestamp)
  "updatedAt": string (timestamp)
}
```

Example Response Values

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "chatbot": "550e8400-e29b-41d4-a716-446655440000",
  "organization": "550e8400-e29b-41d4-a716-446655440000",
  "name": "Response string",
  "executionMode": {},
  "prompt": "Response string",
  "contextVariables": null,
  "inbox": "550e8400-e29b-41d4-a716-446655440000",
```

```
  "saveResultToContext": false,
  "dedicatedContact": "550e8400-e29b-41d4-a716-446655440000",
  "dedicatedConversation": "550e8400-e29b-41d4-a716-446655440000",
  "deliveryConversationIds": [
    "550e8400-e29b-41d4-a716-446655440000"
  ],
  "deliveryWebhookUrls": [
    "https://example.com/file.jpg"
  ],
  "scheduleType": "cron",
  "cronExpression": "Response string",
  "intervalSeconds": 456,
  "oneShotAt": "Response string",
  "timezone": "Response string",
  "periodicTask": 456,
  "enabled": false,
  "lastExecutedAt": "Response string",
  "executionCount": 456,
  "maxExecutions": 456,
  "endDate": "Response string",
  "countsTowardLimit": false,
  "createdAt": "Response string",
  "updatedAt": "Response string"
}
```


Delete a Schedule

DELETE `/api/v1/schedules/{id}`

Parameters

Parameter Name	Required	Type	Description
`id`	V	string	A UUID string identifying this Chatbot Schedule.

Code Examples

Shell/Bash

```
# API call example (Shell)
curl -X DELETE "https://api.maiagent.ai/api/v1/schedules/550e8400-e29b-41d4-a716-
446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

// Request Body (payload)
const data = null;

axios.delete("https://api.maiagent.ai/api/v1/schedules/550e8400-e29b-41d4-a716-
446655440000/", data, config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```python
import requests

url = "https://api.maiagent.ai/api/v1/schedules/550e8400-e29b-41d4-a716-446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.delete(url, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->delete("https://api.maiagent.ai/api/v1/schedules/550e8400-e29b-
41d4-a716-446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response Body

Status Code	Description
204	No response body

Run Schedule Now

`POST` `/api/v1/schedules/{id}/run-now/`

Parameters

Parameter Name	Required	Type	Description
`id`	V	string	A UUID string identifying this Chatbot Schedule.

Request Body

Request Parameters

Field	Type	Required	Description
chatbot	string (uuid)	Yes	
name	string	Yes	
executionMode	string (enum: in_context, isolated)	Yes	`in_context` : In Context ; `isolated` : Isolated;
prompt	string	Yes	
contextVariables	object	No	
inbox	string (uuid)	Yes	
saveResultToContext	boolean	No	
deliveryConversationIds	array[string]	No	
deliveryWebhookUrls	array[string]	No	
scheduleType	string (enum: cron, interval, one_shot)	Yes	`cron` : Cron ; `interval` : Interval ; `one_shot` : One Shot;
cronExpression	string	No	

Field	Type	Required	Description
intervalSeconds	integer	No	
oneShotAt	string (timestamp)	No	
timezone	string	No	
enabled	boolean	No	
maxExecutions	integer	No	
endDate	string (date)	No	Last day the schedule runs, in its own timezone; the first run due after that day turns it off.

Request Schema Example

```
{
  "chatbot": string (uuid)
  "name": string
  "executionMode": string (enum: in_context, isolated) // * `in_context` - In Context
* `isolated` - Isolated
  "prompt": string
  "contextVariables"?: object // Optional
  "inbox": string (uuid)
  "saveResultToContext"?: boolean // Optional
  "deliveryConversationIds"?: [ // Optional
    string (uuid)
  ]
  "deliveryWebhookUrls"?: [ // Optional
    string (uri)
  ]
  "scheduleType": string (enum: cron, interval, one_shot) // * `cron` - Cron
* `interval` - Interval
* `one_shot` - One Shot
  "cronExpression"?: string // Optional
  "intervalSeconds"?: integer // Optional
  "oneShotAt"?: string (timestamp) // Optional
  "timezone"?: string // Optional
  "enabled"?: boolean // Optional
  "maxExecutions"?: integer // Optional
  "endDate"?: string (date) // Last day the schedule runs, in its own timezone; the first run
due after that day turns it off. (Optional)
}
```

Example Request Values

```
{
  "chatbot": "550e8400-e29b-41d4-a716-446655440000",
  "name": "Example name",
  "executionMode": "in_context",
  "prompt": "Example string",
  "contextVariables": null,
  "inbox": "550e8400-e29b-41d4-a716-446655440000",
```

```
  "saveResultToContext": true,
  "deliveryConversationIds": [
    "550e8400-e29b-41d4-a716-446655440000"
  ],
  "deliveryWebhookUrls": [
    "https://example.com/file.jpg"
  ],
  "scheduleType": "cron",
  "cronExpression": "Example string",
  "intervalSeconds": 123,
  "oneShotAt": "Example string",
  "timezone": "Example string",
  "enabled": true,
  "maxExecutions": 123,
  "endDate": "Example string"
}
```


Code Examples

Shell/Bash

```
# Example API Call (Shell)
curl -X POST "https://api.maiagent.ai/api/v1/schedules/550e8400-e29b-41d4-a716-
446655440000/run-now/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "chatbot": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Example name",
    "executionMode": "in_context",
    "prompt": "Example string",
    "contextVariables": null,
    "inbox": "550e8400-e29b-41d4-a716-446655440000",
    "saveResultToContext": true,
    "deliveryConversationIds": [
      "550e8400-e29b-41d4-a716-446655440000"
    ],
    "deliveryWebhookUrls": [
      "https://example.com/file.jpg"
    ],
    "scheduleType": "cron",
    "cronExpression": "Example string",
    "intervalSeconds": 123,
    "oneShotAt": "Example string",
    "timezone": "Example string",
    "enabled": true,
    "maxExecutions": 123,
    "endDate": "Example string"
  }'

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// Request Body (payload)
const data = {
    "chatbot": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Example name",
    "executionMode": "in_context",
    "prompt": "Example string",
    "contextVariables": null,
    "inbox": "550e8400-e29b-41d4-a716-446655440000",
    "saveResultToContext": true,
    "deliveryConversationIds": [
      "550e8400-e29b-41d4-a716-446655440000"
    ],
    "deliveryWebhookUrls": [
      "https://example.com/file.jpg"
    ],
    "scheduleType": "cron",
    "cronExpression": "Example string",
    "intervalSeconds": 123,
    "oneShotAt": "Example string",
    "timezone": "Example string",
    "enabled": true,
    "maxExecutions": 123,
    "endDate": "Example string"
  };

axios.post("https://api.maiagent.ai/api/v1/schedules/550e8400-e29b-41d4-a716-
446655440000/run-now/", data, config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/schedules/550e8400-e29b-41d4-a716-446655440000/run-
now/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# Request Body (payload)
data = {
    "chatbot": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Example name",
    "executionMode": "in_context",
    "prompt": "Example string",
    "contextVariables": None,
    "inbox": "550e8400-e29b-41d4-a716-446655440000",
    "saveResultToContext": True,
    "deliveryConversationIds": [
        "550e8400-e29b-41d4-a716-446655440000"
    ],
    "deliveryWebhookUrls": [
        "https://example.com/file.jpg"
    ],
    "scheduleType": "cron",
    "cronExpression": "Example string",
    "intervalSeconds": 123,
    "oneShotAt": "Example string",
    "timezone": "Example string",
    "enabled": True,
    "maxExecutions": 123,
    "endDate": "Example string"
}

response = requests.post(url, json=data, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->post("https://api.maiagent.ai/api/v1/schedules/550e8400-e29b-41d4-a716-446655440000/run-now/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'chatbot' => '550e8400-e29b-41d4-a716-446655440000',
            'name' => 'Example name',
            'executionMode' => 'in_context',
            'prompt' => 'Example string',
            'contextVariables' => null,
            'inbox' => '550e8400-e29b-41d4-a716-446655440000',
            'saveResultToContext' => true,
            'deliveryConversationIds' => [
                '550e8400-e29b-41d4-a716-446655440000'
            ],
            'deliveryWebhookUrls' => [
                'https://example.com/file.jpg'
            ],
            'scheduleType' => 'cron',
            'cronExpression' => 'Example string',
            'intervalSeconds' => 123,
            'oneShotAt' => 'Example string',
            'timezone' => 'Example string',
            'enabled' => true,
            'maxExecutions' => 123,
            'endDate' => 'Example string'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response Body

Status Code: 202

Response Schema Example

```
{
  "status"?: string // Optional
}
```

Example Response Values

```
{
  "status": "scheduled"
}
```

Enable or Disable Schedule

POST `/api/v1/schedules/{id}/toggle/`

Parameters

Parameter Name	Required	Type	Description
`id`	V	string	A UUID string identifying this Chatbot Schedule.

Code Examples

Shell/Bash

```
# Example API Call (Shell)
curl -X POST "https://api.maiagent.ai/api/v1/schedules/550e8400-e29b-41d4-a716-
446655440000/toggle/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

// Request Body (payload)
const data = null;

axios.post("https://api.maiagent.ai/api/v1/schedules/550e8400-e29b-41d4-a716-
446655440000/toggle/", data, config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/schedules/550e8400-e29b-41d4-a716-
446655440000/toggle/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.post(url, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->post("https://api.maiagent.ai/api/v1/schedules/550e8400-e29b-
41d4-a716-446655440000/toggle/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response Body

Status Code: 200

Response Schema Example

```
{
  "id": string (uuid)
  "chatbot": string (uuid)
  "organization": string (uuid)
  "name": string
  "executionMode": string (enum: in_context, isolated) // * `in_context` - In Context
* `isolated` - Isolated
  "prompt": string
  "contextVariables"?: object // Optional
  "inbox": string (uuid)
  "saveResultToContext"?: boolean // Optional
  "dedicatedContact": string (uuid)
  "dedicatedConversation": string (uuid)
  "deliveryConversationIds"?: [ // Optional
    string (uuid)
  ]
  "deliveryWebhookUrls"?: [ // Optional
    string (uri)
  ]
  "scheduleType": string (enum: cron, interval, one_shot) // * `cron` - Cron
* `interval` - Interval
* `one_shot` - One Shot
  "cronExpression"?: string // Optional
  "intervalSeconds"?: integer // Optional
  "oneShotAt"?: string (timestamp) // Optional
  "timezone"?: string // Optional
  "periodicTask": integer
  "enabled"?: boolean // Optional
  "lastExecutedAt": string (timestamp)
  "executionCount": integer
  "maxExecutions"?: integer // Optional
  "endDate"?: string (date) // Last day the schedule runs, in its own timezone; the first run
due after that day turns it off. (Optional)
  "countsTowardLimit": boolean
  "createdAt": string (timestamp)
  "updatedAt": string (timestamp)
}
```

Example Response Values

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "chatbot": "550e8400-e29b-41d4-a716-446655440000",
  "organization": "550e8400-e29b-41d4-a716-446655440000",
  "name": "Response string",
  "executionMode": "in_context",
```

```
  "prompt": "Response string",
  "contextVariables": null,
  "inbox": "550e8400-e29b-41d4-a716-446655440000",
  "saveResultToContext": false,
  "dedicatedContact": "550e8400-e29b-41d4-a716-446655440000",
  "dedicatedConversation": "550e8400-e29b-41d4-a716-446655440000",
  "deliveryConversationIds": [
    "550e8400-e29b-41d4-a716-446655440000"
  ],
  "deliveryWebhookUrls": [
    "https://example.com/file.jpg"
  ],
  "scheduleType": "cron",
  "cronExpression": "Response string",
  "intervalSeconds": 456,
  "oneShotAt": "Response string",
  "timezone": "Response string",
  "periodicTask": 456,
  "enabled": false,
  "lastExecutedAt": "Response string",
  "executionCount": 456,
  "maxExecutions": 456,
  "endDate": "Response string",
  "countsTowardLimit": false,
  "createdAt": "Response string",
  "updatedAt": "Response string"
}
```


Status Code: 400

Response Schema Example

```
{
  "detail"?: string // Optional
}
```

Example Response Values


```
{
  "detail": "Response string"
}
```

Prerequisites

目錄

1. Query Credit Balance
2. Get Wallet Details
3. Get Wallet Balance
4. Query Expiring Credits
5. Query Top-up History
6. List Usage Transactions
7. Retrieve a Usage Transaction
8. Query Usage History
9. Query Consumption Summary
10. Query Credit Usage by Category
11. Retrieve Credit Usage for a Single Category
12. Retrieve Member Usage for a Billable Item
13. Retrieve Billable Item Usage for a Single Member
14. Retrieve Default Quota Settings for New Members
15. Update Default Quota Settings for New Members
16. List Current Member Quotas
17. List Current Role Quotas
18. List Inbox Quota Status
19. List Member Quota Settings
20. Retrieve a Member Quota Setting
21. Set a quota for a member
22. Update a member's quota settings
23. Deactivate a Member's Quota
24. List Role Quota Settings
25. Retrieve a Role Quota Setting
26. Set a quota for a role
27. Update quota settings for a role
28. Deactivate a Role's Quota Settings
29. Set Whether a Role Requires a Quota
30. Retrieve Role Member Quota Statistics
31. Distribute Quota in Bulk by Role
32. Deactivate Quota in Bulk by Role
33. List Inbox Quota Settings
34. Retrieve an Inbox Quota Setting
35. Set an inbox credit quota

36. Update an inbox credit quota
37. Disable an Inbox's Credit Quota
38. Set Whether an Inbox Requires a Credit Quota
39. Query your own quota
40. Query the quotas of your roles
41. List pricing rules
42. Retrieve a pricing rule
43. List Credit Items
44. Retrieve a Credit Item

Prerequisites

The Credit category provides queries and quota allocation for organization Credits: balances, credits nearing expiration, credit entries, consumption details and totals, usage statistics, pricing rules and pricing items, as well as quota settings for members, roles, and inboxes (list, set, update, deactivate, and specify whether a quota is required), and batch allocation or deactivation of member quotas by role.

Prerequisites

Authentication and Path Parameters

All APIs except Pricing Rules and Pricing Items require an API Key in the HTTP header:

```
Authorization: Api-Key {API_KEY}
```

The system automatically identifies the organization and member associated with the API Key. APIs starting with `/api/v1/credit/` do not require a separate organization identifier. Obtain the IDs required in paths as follows:

- `organizationPk`: Call `GET /api/v1/organizations/` and use the organization's `id` from the response.
- Wallet `id`: Call `GET /api/v1/organizations/{id}/` and use `creditWallet.id` from the response.

Rate Limits

For APIs that require an API Key, the rate limit is **the number of requests per minute configured individually for each API Key**. Organization administrators set this in the Requests per Minute (RPM) field under Organization Settings → API Keys. Calls to all APIs on the platform using the same key count toward a shared total. Keys without a configured limit are exempt. Requests exceeding the limit are rejected with HTTP 429; wait until the next minute before retrying.

Pricing Rules and Pricing Items do not require an API Key. Their rate limits are calculated separately by source IP; see the notes for each API.

How Quotas Work

Members, roles, and inboxes each have a quota layer, corresponding to the three tabs under Credits → Quota Allocation in the admin console. Each layer is tracked independently:

- **Member quota**: The usage limit for an individual member.
- **Role quota**: A shared limit for all members of a role, tracked separately from each member's individual quota. If a member belongs to multiple roles that require quotas, usage counts toward every role. Exhausting any one role's quota blocks further use.
- **Inbox quota**: The usage limit for AI replies in that inbox. Quotas cannot be set for MaiGPT inboxes.

The same rules apply to each layer:

- **Quota required**: Members, roles, and inboxes each have a Quota Required setting (response field `creditQuotaRequired`). When disabled, this layer is neither checked nor tracked, and the organization wallet is used directly. When enabled, an active quota is required. Without an active quota, use is blocked: members and roles cannot use features that consume Credits, and AI replies are paused for inboxes.
- **Setting a quota automatically enables Quota Required**. Each entity can have only one active quota at a time. Attempting to set another quota while an active one exists returns `400`; deactivate the old quota first.
- **Deactivating a quota does not disable Quota Required**: The entity remains blocked until a new quota is set or the quota requirement is removed. For roles and inboxes, use their respective Set Whether a Quota Is Required API. For members, ask an administrator to remove the requirement under Credits → Quota Allocation in the admin console, or use Batch Deactivate Quotas by Role with `removeQuotaRequirement: true` to remove it for all members of a role at once. Deactivation does not delete records. Deactivated quotas still appear in List Quota Settings with `isActive` set to `false`.
- Request fields for setting a quota: `quotaLimit` (quota limit, required), `validFrom` (start time, required), `validUntil` (expiration time, optional; must be later than `validFrom` and no later than the latest expiration date among the organization's credit entries), `resetPeriod` (usage reset interval: `none`, `daily`, `weekly`, or `monthly`; defaults to `none`), and `note` (optional note).
- **Time format**: Always use ISO 8601 strings for `validFrom` and `validUntil` in requests, such as `2026-12-31T23:59:59+08:00`. A date alone (`2026-12-31`) is interpreted as 00:00 on that date in Taiwan time. Millisecond timestamps (such as `1798732799000`) are not accepted and return `400`. Time fields in responses use 13-digit millisecond timestamps.
- **Default quota for new members**: Organizations can configure an individual quota to be assigned automatically to new members; see Get Default Quota Settings for New Members. A quota can also be specified for each invitee when sending invitations; see Invite Members to an Organization under Organizations and Members.
- IDs in paths: Obtain `memberPk` from the `id` in the List Current Member Quotas response, `groupPk` from List Current Role Quotas, and `inboxPk` from List Current Inbox Quotas. Obtain

the quota setting's own `id` from the corresponding List Quota Settings API.

Permissions and Billing Modes

The required permissions and billing mode prerequisites are listed below each API. An API Key acts as the member who created it, and permissions are determined by that member's roles. Requests are rejected with HTTP 403 in either of these cases:

- **Insufficient permissions**: The roles of the member associated with the key do not have the permission specified by the API (Credit Management, Usage Statistics, or Organization Overview). Ask an organization administrator to enable the corresponding permission for the member's role under Organization Settings → Roles.
- **The organization does not use Credit billing**: APIs marked as requiring Credit billing are available only to organizations using that billing mode. Call `GET /api/v1/organizations/{id}/` to check: these APIs are available when `organizationPlan.billingMode` is `credit`, or when the organization has no plan yet and `organizationPlan` is empty. To switch to Credit billing, contact your MaiAgent representative.

Query Credit Balance

`GET` `/api/v1/credit/wallets/`

Required permission: Credit Management. Billing mode: Unrestricted; organizations using any billing mode can call this API.

Parameters

Parameter Name	Required	Type	Description
`page`	X	integer	A page number within the paginated result set.
`pageSize`	X	integer	Number of results to return per page.

Code Examples

Shell/Bash

```
# API call example (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/credit/wallets/?
page=1&pageSize=1"

  -H "Authorization: Api-Key YOUR_API_KEY"

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/credit/wallets/?
page=1&pageSize=1", config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/credit/wallets/?
page=1&pageSize=1"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/credit/wallets/?
page=1&pageSize=1", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response Content

Status code: 200

Example Response Structure

```
{
  "count": integer
  "next"?: string (uri) // Optional
```

```
  "previous"?: string (uri) // Optional
  "results": [
    {
      "totalCredits": string (decimal)
      "autoTopup": object // Format auto-topup configuration.
      "balanceAlert": object // Format balance alert configuration.
      "nextGrant": object // Format the next grant, or None when nothing
will actually be granted.

Amount-first: a missing/zero ``amount`` always wins over any schedule
(stale ``next_grant_at`` row, Stripe period_end with zero-grant plan),
so the frontend never receives a "scheduled in X days for 0 credits"
entry — the API decides whether the block renders at all.
      "lastGrant": object // Format the most recent PLAN_GRANT topup, or
None when wallet has none.
      "consumptionHint": object // Return 7-day daily average consumption
hint, or None if insufficient data.
      "billingProvider": string // Return the organization's billing
provider so the Credit page can pick its card layout.
      "periodCreditGrant": string // Return current-period credit grant
total; None unless AWS Marketplace billed.
      "periodMeteredUsage": string // Return current-period accepted
metered usage; None unless AWS Marketplace billed.
    }
  ]
}
```

Example Response Values

```
{
  "count": 123,
  "next": "http://api.example.org/accounts/?page=4",
  "previous": "http://api.example.org/accounts/?page=2",
  "results": [
    {
      "totalCredits": "Response string",
      "autoTopup": {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "name": "Example response name",
        "description": "Example response description"
      },
      "balanceAlert": {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "name": "Example response name",
```

```
        "description": "Example response description"
      },
      "nextGrant": {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "name": "Example response name",
        "description": "Example response description"
      },
      "lastGrant": {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "name": "Example response name",
        "description": "Example response description"
      },
      "consumptionHint": {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "name": "Example response name",
        "description": "Example response description"
      },
      "billingProvider": "Response string",
      "periodCreditGrant": "Response string",
      "periodMeteredUsage": "Response string"
    }
  ]
}
```


Get Wallet Details

GET `/api/v1/credit/wallets/{id}`

Required permission: Credit Management. Billing mode: Unrestricted; organizations using any billing mode can call this API.

Parameters

Parameter Name	Required	Type	Description

id	V	string	A UUID string identifying this Credit Wallet.

Code Examples

Shell/Bash

```
# API call example (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/credit/wallets/550e8400-
e29b-41d4-a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/credit/wallets/550e8400-
e29b-41d4-a716-446655440000/", config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/credit/wallets/550e8400-e29b-
41d4-a716-446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/credit/wallets/550e8400-e29b-
41d4-a716-446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response Content

Status code: 200

Example Response Structure

```
{
  "totalCredits": string (decimal)
  "autoTopup": object // Format auto-topup configuration.
```

```
  "balanceAlert": object // Format balance alert configuration.
  "nextGrant": object // Format the next grant, or None when nothing will
actually be granted.

Amount-first: a missing/zero ``amount`` always wins over any schedule
(stale ``next_grant_at`` row, Stripe period_end with zero-grant plan),
so the frontend never receives a "scheduled in X days for 0 credits"
entry — the API decides whether the block renders at all.
  "lastGrant": object // Format the most recent PLAN_GRANT topup, or None
when wallet has none.
  "consumptionHint": object // Return 7-day daily average consumption
hint, or None if insufficient data.
  "billingProvider": string // Return the organization's billing provider
so the Credit page can pick its card layout.
  "periodCreditGrant": string // Return current-period credit grant
total; None unless AWS Marketplace billed.
  "periodMeteredUsage": string // Return current-period accepted metered
usage; None unless AWS Marketplace billed.
}
```

Example Response Values

```
{
  "totalCredits": "Response string",
  "autoTopup": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Example response name",
    "description": "Example response description"
  },
  "balanceAlert": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Example response name",
    "description": "Example response description"
  },
  "nextGrant": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Example response name",
    "description": "Example response description"
  },
  "lastGrant": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Example response name",
    "description": "Example response description"
  },
```

```
  "consumptionHint": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Example response name",
    "description": "Example response description"
  },
  "billingProvider": "Response string",
  "periodCreditGrant": "Response string",
  "periodMeteredUsage": "Response string"
}
```


Get Wallet Balance

GET `/api/v1/credit/wallets/{id}/balance/`

Required permission: Credit Management. Billing mode: Unrestricted; organizations using any billing mode can call this API.

Parameters

Parameter Name	Required	Type	Description
`id`	V	string	A UUID string identifying this Credit Wallet.

Code Examples

Shell/Bash

```
# API call example (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/credit/wallets/550e8400-
e29b-41d4-a716-446655440000/balance/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/credit/wallets/550e8400-
e29b-41d4-a716-446655440000/balance/", config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/credit/wallets/550e8400-e29b-41d4-a716-446655440000/balance/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/credit/wallets/550e8400-e29b-
41d4-a716-446655440000/balance/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response Content

Status code: 200

Example Response Structure

```
{
  "totalCredits": string (decimal)
  "autoTopup": object // Format auto-topup configuration.
```

```
  "balanceAlert": object // Format balance alert configuration.
  "nextGrant": object // Format the next grant, or None when nothing will
actually be granted.

Amount-first: a missing/zero ``amount`` always wins over any schedule
(stale ``next_grant_at`` row, Stripe period_end with zero-grant plan),
so the frontend never receives a "scheduled in X days for 0 credits"
entry — the API decides whether the block renders at all.
  "lastGrant": object // Format the most recent PLAN_GRANT topup, or None
when wallet has none.
  "consumptionHint": object // Return 7-day daily average consumption
hint, or None if insufficient data.
  "billingProvider": string // Return the organization's billing provider
so the Credit page can pick its card layout.
  "periodCreditGrant": string // Return current-period credit grant
total; None unless AWS Marketplace billed.
  "periodMeteredUsage": string // Return current-period accepted metered
usage; None unless AWS Marketplace billed.
}
```

Example Response Values

```
{
  "totalCredits": "Response string",
  "autoTopup": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Example response name",
    "description": "Example response description"
  },
  "balanceAlert": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Example response name",
    "description": "Example response description"
  },
  "nextGrant": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Example response name",
    "description": "Example response description"
  },
  "lastGrant": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Example response name",
    "description": "Example response description"
  },
```

```
  "consumptionHint": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Example response name",
    "description": "Example response description"
  },
  "billingProvider": "Response string",
  "periodCreditGrant": "Response string",
  "periodMeteredUsage": "Response string"
}
```


Query Expiring Credits

GET `/api/v1/credit/wallets/{id}/expiring-credits/`

Required permission: Credit Management. Billing mode: Unrestricted; organizations using any billing mode can call this API. Only Credits with an expiration date are listed. Credits without an expiration date are excluded, so the results do not represent the organization’ s entire balance. The days parameter specifies how many days ahead to check for expiring Credits (default: 30; pass all to list all Credits with an expiration date).

Parameters

Parameter Name	Required	Type	Description
`id`	V	string	A UUID string identifying this Credit Wallet.

Code Examples

Shell/Bash

```
# API call example (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/credit/wallets/550e8400-
e29b-41d4-a716-446655440000/expiring-credits/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/credit/wallets/550e8400-
e29b-41d4-a716-446655440000/expiring-credits/", config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/credit/wallets/550e8400-e29b-41d4-a716-446655440000/expiring-credits/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/credit/wallets/550e8400-e29b-
41d4-a716-446655440000/expiring-credits/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response Content

Status code: 200

Example Response Structure

```
{
  "totalCredits": string (decimal)
  "autoTopup": object // Format auto-topup configuration.
```

```
  "balanceAlert": object // Format balance alert configuration.
  "nextGrant": object // Format the next grant, or None when nothing will
actually be granted.

Amount-first: a missing/zero ``amount`` always wins over any schedule
(stale ``next_grant_at`` row, Stripe period_end with zero-grant plan),
so the frontend never receives a "scheduled in X days for 0 credits"
entry — the API decides whether the block renders at all.
  "lastGrant": object // Format the most recent PLAN_GRANT topup, or None
when wallet has none.
  "consumptionHint": object // Return 7-day daily average consumption
hint, or None if insufficient data.
  "billingProvider": string // Return the organization's billing provider
so the Credit page can pick its card layout.
  "periodCreditGrant": string // Return current-period credit grant
total; None unless AWS Marketplace billed.
  "periodMeteredUsage": string // Return current-period accepted metered
usage; None unless AWS Marketplace billed.
}
```

Example Response Values

```
{
  "totalCredits": "Response string",
  "autoTopup": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Example response name",
    "description": "Example response description"
  },
  "balanceAlert": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Example response name",
    "description": "Example response description"
  },
  "nextGrant": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Example response name",
    "description": "Example response description"
  },
  "lastGrant": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Example response name",
    "description": "Example response description"
  },
```

```
  "consumptionHint": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Example response name",
    "description": "Example response description"
  },
  "billingProvider": "Response string",
  "periodCreditGrant": "Response string",
  "periodMeteredUsage": "Response string"
}
```


Query Top-up History

GET `/api/v1/credit/wallets/{id}/topup-history/`

Required permission: Credit Management. Billing mode: Unrestricted; organizations using any billing mode can call this API.

Parameters

Parameter Name	Required	Type	Description
`id`	V	string	A UUID string identifying this Credit Wallet.

Code Examples

Shell/Bash

```
# API call example (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/credit/wallets/550e8400-
e29b-41d4-a716-446655440000/topup-history/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/credit/wallets/550e8400-
e29b-41d4-a716-446655440000/topup-history/", config)
  .then(response => {
    console.log('Response retrieved successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/credit/wallets/550e8400-e29b-41d4-a716-446655440000/topup-history/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("Response retrieved successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/credit/wallets/550e8400-e29b-
41d4-a716-446655440000/topup-history/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response retrieved successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response Content

Status code: 200

Example Response Structure

```
{
  "totalCredits": string (decimal)
  "autoTopup": object // Format auto-topup configuration.
```

```
  "balanceAlert": object // Format balance alert configuration.
  "nextGrant": object // Format the next grant, or None when nothing will
actually be granted.

Amount-first: a missing/zero ``amount`` always wins over any schedule
(stale ``next_grant_at`` row, Stripe period_end with zero-grant plan),
so the frontend never receives a "scheduled in X days for 0 credits"
entry — the API decides whether the block renders at all.
  "lastGrant": object // Format the most recent PLAN_GRANT topup, or None
when wallet has none.
  "consumptionHint": object // Return 7-day daily average consumption
hint, or None if insufficient data.
  "billingProvider": string // Return the organization's billing provider
so the Credit page can pick its card layout.
  "periodCreditGrant": string // Return current-period credit grant
total; None unless AWS Marketplace billed.
  "periodMeteredUsage": string // Return current-period accepted metered
usage; None unless AWS Marketplace billed.
}
```

Example Response Values

```
{
  "totalCredits": "response string",
  "autoTopup": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Example response name",
    "description": "Example response description"
  },
  "balanceAlert": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Example response name",
    "description": "Example response description"
  },
  "nextGrant": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Example response name",
    "description": "Example response description"
  },
  "lastGrant": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Example response name",
    "description": "Example response description"
  },
```

```
  "consumptionHint": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Example response name",
    "description": "Example response description"
  },
  "billingProvider": "response string",
  "periodCreditGrant": "response string",
  "periodMeteredUsage": "response string"
}
```


List Usage Transactions

GET `/api/v1/credit/transactions/`

Required permissions: Credit management permissions. Billing mode: No restrictions; organizations using any billing mode can call this endpoint.

Parameters

Parameter Name	Required	Type	Description
`page`	X	integer	A page number within the paginated result set.
`pageSize`	X	integer	Number of results to return per page.

Code Examples

Shell/Bash

```
# API call example (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/credit/transactions/?
page=1&pageSize=1"

  -H "Authorization: Api-Key YOUR_API_KEY"

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/credit/transactions/?
page=1&pageSize=1", config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/credit/transactions/?
page=1&pageSize=1"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/credit/transactions/?
page=1&pageSize=1", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response Body

Status Code: 200

Example Response Schema

```
{
  "count": integer
  "next"?: string (uri) // Optional
```

```
  "previous"?: string (uri) // Optional
  "results": [
    {
      "id": string (uuid)
      "eventDatetime": string (timestamp)
      "createdAt": string (timestamp)
      "transactionType": string
      "creditItem": object
      "amount": string (decimal)
      "balanceAfter": string (decimal)
      "quantity": string (decimal)
      "provider": string
      "modelCode": string
      "unitPriceSnapshot": string (decimal)
      "member": object
      "description": string
      "metadata": object
      "parserName": string
      "quantityUnit": string
      "targetObject": object // Return frontend deep-link target for this
transaction's GFK content.

``{kind: 'chat.message', objectId, chatbotId}`` opens the AgentOps record
modal;
``{kind: 'dataset.evaluation', objectId, isMultiTurn}`` opens the
evaluation results page.
Returns None when no GFK is attached, the content type is unsupported,
or the target no longer resolves inside this organization.
    }
  ]
}
```

Example Response Values

```
{
  "count": 123,
  "next": "http://api.example.org/accounts/?page=4",
  "previous": "http://api.example.org/accounts/?page=2",
  "results": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "eventDatetime": "response string",
      "createdAt": "response string",
      "transactionType": "response string",
```

```
      "creditItem": {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "name": "example response name",
        "description": "example response description"
      },
      "amount": "response string",
      "balanceAfter": "response string",
      "quantity": "response string",
      "provider": "response string",
      "modelCode": "response string",
      "unitPriceSnapshot": "response string",
      "member": {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "name": "example response name",
        "description": "example response description"
      },
      "description": "response string",
      "metadata": null,
      "parserName": "response string",
      "quantityUnit": "response string",
      "targetObject": {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "name": "example response name",
        "description": "example response description"
      }
    }
  ]
}
```


Retrieve a Usage Transaction

`GET` `/api/v1/credit/transactions/{id}`

Required permissions: Credit management permissions. Billing mode: No restrictions; organizations using any billing mode can call this endpoint.

Parameters

Parameter Name	Required	Type	Description
`id`	V	string	A UUID string identifying this Credit Transaction.

Code Examples

Shell/Bash

```
# API call example (Shell)
curl -X GET
"https://api.maiagent.ai/api/v1/credit/transactions/550e8400-e29b-
41d4-a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/credit/transactions/550e84
00-e29b-41d4-a716-446655440000/", config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/credit/transactions/550e8400-
e29b-41d4-a716-446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/credit/transactions/550e8400-
e29b-41d4-a716-446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response Body

Status Code: 200

Example Response Schema

```
{
  "id": string (uuid)
  "eventDatetime": string (timestamp)
```

```
  "createdAt": string (timestamp)
  "transactionType": string
  "creditItem": object
  "amount": string (decimal)
  "balanceAfter": string (decimal)
  "quantity": string (decimal)
  "provider": string
  "modelCode": string
  "unitPriceSnapshot": string (decimal)
  "member": object
  "description": string
  "metadata": object
  "parserName": string
  "quantityUnit": string
  "targetObject": object // Return frontend deep-link target for this
transaction's GFK content.

``{kind: 'chat.message', objectId, chatbotId}`` opens the AgentOps record
modal;
``{kind: 'dataset.evaluation', objectId, isMultiTurn}`` opens the
evaluation results page.
Returns None when no GFK is attached, the content type is unsupported,
or the target no longer resolves inside this organization.
}
```

Example Response Values

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "eventDatetime": "response string",
  "createdAt": "response string",
  "transactionType": "response string",
  "creditItem": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "example response name",
    "description": "example response description"
  },
  "amount": "response string",
  "balanceAfter": "response string",
  "quantity": "response string",
  "provider": "response string",
  "modelCode": "response string",
  "unitPriceSnapshot": "response string",
  "member": {
```

```
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "example response name",
    "description": "example response description"
  },
  "description": "response string",
  "metadata": null,
  "parserName": "response string",
  "quantityUnit": "response string",
  "targetObject": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "example response name",
    "description": "example response description"
  }
}
```


Query Usage History

GET `/api/v1/credit/transactions/history/`

Required permissions: Credit management permissions. Billing mode: No restrictions; organizations using any billing mode can call this endpoint.

Parameters

Parameter Name	Required	Type	Description
`category`	X	string	Credit item category (e.g. llm_token, platform_fee); agent_memory selects the AI memory lines, which llm_token then leaves out
`endDate`	X	string	End date (inclusive, whole day in the platform timezone Asia/Taipei), format: YYYY-MM-DD
`limit`	X	integer	Rows per page, capped at 100

`page`	X	integer	1-based page number
`search`	X	string	Case-insensitive match against transaction description and metadata
`startDate`	X	string	Start date (inclusive, whole day in the platform timezone Asia/Taipei), format: YYYY-MM-DD
`type`	X	string	Which rows to include: all ledger entries, consumption only, or credited only

Code Examples

Shell/Bash

```
# API call example (Shell)
curl -X GET
"https://api.maiagent.ai/api/v1/credit/transactions/history/?
category=example&endDate=example&limit=1&page=1&search=example&start
Date=example&type=all"

  -H "Authorization: Api-Key YOUR_API_KEY"

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/credit/transactions/histor
y/?
category=example&endDate=example&limit=1&page=1&search=example&start
Date=example&type=all", config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/credit/transactions/history/?
category=example&endDate=example&limit=1&page=1&search=example&start
Date=example&type=all"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/credit/transactions/history/?
category=example&endDate=example&limit=1&page=1&search=example&start
Date=example&type=all", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response Body

Status Code: 200

Example Response Schema

```
{
  "id": string (uuid)
```

```
  "eventDatetime": string (timestamp)
  "createdAt": string (timestamp)
  "transactionType": string
  "creditItem": object
  "amount": string (decimal)
  "balanceAfter": string (decimal)
  "quantity": string (decimal)
  "provider": string
  "modelCode": string
  "unitPriceSnapshot": string (decimal)
  "member": object
  "description": string
  "metadata": object
  "parserName": string
  "quantityUnit": string
  "targetObject": object // Return frontend deep-link target for this
transaction's GFK content.

``{kind: 'chat.message', objectId, chatbotId}`` opens the AgentOps record
modal;
``{kind: 'dataset.evaluation', objectId, isMultiTurn}`` opens the
evaluation results page.
Returns None when no GFK is attached, the content type is unsupported,
or the target no longer resolves inside this organization.
}
```

Example Response Values

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "eventDatetime": "response string",
  "createdAt": "response string",
  "transactionType": "response string",
  "creditItem": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "example response name",
    "description": "example response description"
  },
  "amount": "response string",
  "balanceAfter": "response string",
  "quantity": "response string",
  "provider": "response string",
  "modelCode": "response string",
  "unitPriceSnapshot": "response string",
```

```
  "member": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "example response name",
    "description": "example response description"
  },
  "description": "response string",
  "metadata": null,
  "parserName": "response string",
  "quantityUnit": "response string",
  "targetObject": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "example response name",
    "description": "example response description"
  }
}
```


Query Consumption Summary

GET `/api/v1/credit/transactions/history-summary/`

Required permission: Credit Management. Billing mode: Unrestricted; organizations using any billing mode can call this API.

Parameters

Parameter Name	Required	Type	Description
`category`	X	string	Credit item category (e.g. llm_token, platform_fee); agent_memory selects the AI memory lines, which llm_token then leaves out
`endDate`	X	string	End date (inclusive, whole day in the platform timezone Asia/Taipei), format: YYYY-MM-DD

`search`	X	string	Case-insensitive match against transaction description and metadata
`startDate`	X	string	Start date (inclusive, whole day in the platform timezone Asia/Taipei), format: YYYY-MM-DD
`type`	X	string	Which rows to include: all ledger entries, consumption only, or credited only

Code Examples

Shell/Bash

```
# API call example (Shell)
curl -X GET
"https://api.maiagent.ai/api/v1/credit/transactions/history-
summary/?
category=example&endDate=example&search=example&startDate=example&ty
pe=all"

  -H "Authorization: Api-Key YOUR_API_KEY"

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/credit/transactions/history-summary/?category=example&endDate=example&search=example&startDate=example&type=all", config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/credit/transactions/history-
summary/?
category=example&endDate=example&search=example&startDate=example&ty
pe=all"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/credit/transactions/history-
summary/?
category=example&endDate=example&search=example&startDate=example&ty
pe=all", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response Content

Status code: 200

Example Response Structure

```
{
  "consumedTotal": string (decimal)
  "creditedTotal": string (decimal)
  "count": integer
}
```

Example Response Values

```
{
  "consumedTotal": "Response string",
  "creditedTotal": "Response string",
  "count": 456
}
```

Query Credit Usage by Category

`GET` `/api/v1/organizations/{organizationPk}/usage-statistics/credit-categories/`

Required permissions: Usage statistics permission. Billing mode: The organization must use Credit billing.

Parameters

Parameter Name	Required	Type	Description
`organizationPk`	V	string	A UUID string identifying this organization ID
`endDate`	X	string	End date, format: YYYY-MM-DD
`page`	X	integer	A page number within the paginated result set.
`pageSize`	X	integer	Number of results to return per page.

`startDate`	V	string	Start date, format: YYYY-MM-DD
`timeGranularity`	X	string	Time granularity (hour/day/month)

Code Examples

Shell/Bash

```
# API Call Example (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/organizations/550e8400-
e29b-41d4-a716-446655440000/usage-statistics/credit-categories/?
endDate=example&page=1&pageSize=1&startDate=example&timeGranularity=
day"

  -H "Authorization: Api-Key YOUR_API_KEY"

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/organizations/550e8400-
e29b-41d4-a716-446655440000/usage-statistics/credit-categories/?
endDate=example&page=1&pageSize=1&startDate=example&timeGranularity=
day", config)
  .then(response => {
    console.log('Response retrieved successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request failed:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-
41d4-a716-446655440000/usage-statistics/credit-categories/?
endDate=example&page=1&pageSize=1&startDate=example&timeGranularity=
day"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("Response retrieved successfully:")
    print(response.json())
except Exception as e:
    print("Request failed:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-
41d4-a716-446655440000/usage-statistics/credit-categories/?
endDate=example&page=1&pageSize=1&startDate=example&timeGranularity=
day", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response retrieved successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request failed: ' . $e->getMessage();
}
?>
```

Response

Status Code: 200

Example Response Schema

```
{
  "count": integer
  "next"?: string (uri) // Optional
  "previous"?: string (uri) // Optional
  "results": [
    object
  ]
}
```

Example Response Values

```
{
  "count": 123,
  "next": "http://api.example.org/accounts/?page=4",
  "previous": "http://api.example.org/accounts/?page=2",
  "results": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "Example response name",
      "description": "Example response description"
    }
  ]
}
```

Retrieve Credit Usage for a Single Category

GET `/api/v1/organizations/{organizationPk}/usage-statistics/credit-categories/{id}`

Required permissions: Usage statistics permission. Billing mode: The organization must use Credit billing.

Parameters

Parameter Name	Required	Type	Description
`id`	V	string	
`organizationPk`	V	string	A UUID string identifying this organization ID
`endDate`	X	string	End date, format: YYYY-MM-DD
`startDate`	V	string	Start date, format: YYYY-MM-DD
`timeGranularity`	X	string	Time granularity (hour/day/month)

Code Examples

Shell/Bash

```
# API Call Example (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/organizations/550e8400-
e29b-41d4-a716-446655440000/usage-statistics/credit-
categories/550e8400-e29b-41d4-a716-446655440000/?
endDate=example&startDate=example&timeGranularity=day"

  -H "Authorization: Api-Key YOUR_API_KEY"

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/organizations/550e8400-
e29b-41d4-a716-446655440000/usage-statistics/credit-
categories/550e8400-e29b-41d4-a716-446655440000/?
endDate=example&startDate=example&timeGranularity=day", config)
  .then(response => {
    console.log('Response retrieved successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request failed:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-
41d4-a716-446655440000/usage-statistics/credit-categories/550e8400-
e29b-41d4-a716-446655440000/?
endDate=example&startDate=example&timeGranularity=day"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("Response retrieved successfully:")
    print(response.json())
except Exception as e:
    print("Request failed:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-
41d4-a716-446655440000/usage-statistics/credit-categories/550e8400-
e29b-41d4-a716-446655440000/?
endDate=example&startDate=example&timeGranularity=day", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response retrieved successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request failed: ' . $e->getMessage();
}
?>
```

Response

Status Code: 200

Example Response Schema

```
object
```

Example Response Values

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "name": "Example response name",
  "description": "Example response description"
}
```

Retrieve Member Usage for a Billable Item

GET `/api/v1/organizations/{organizationPk}/usage-statistics/credit-categories/{itemPk}/members/`

Required permissions: Usage statistics permission. Billing mode: The organization must use Credit billing.

Parameters

Parameter Name	Required	Type	Description
`itemPk`	V	string	
`organizationPk`	V	string	A UUID string identifying this organization ID
`endDate`	X	string	End date, format: YYYY-MM-DD
`page`	X	integer	A page number within the paginated result set.
`pageSize`	X	integer	Number of results to return per page.

`startDate`	V	string	Start date, format: YYYY-MM-DD
`timeGranularity`	X	string	Time granularity (hour/day/month)

Code Examples

Shell/Bash

```
# API Call Example (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/organizations/550e8400-
e29b-41d4-a716-446655440000/usage-statistics/credit-
categories/{itemPk}/members/?
endDate=example&page=1&pageSize=1&startDate=example&timeGranularity=
day"

  -H "Authorization: Api-Key YOUR_API_KEY"

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/organizations/550e8400-
e29b-41d4-a716-446655440000/usage-statistics/credit-
categories/{itemPk}/members/?
endDate=example&page=1&pageSize=1&startDate=example&timeGranularity=
day", config)
  .then(response => {
    console.log('Response retrieved successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request failed:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-41d4-a716-446655440000/usage-statistics/credit-categories/{itemPk}/members/?endDate=example&page=1&pageSize=1&startDate=example&timeGranularity=day"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("Response retrieved successfully:")
    print(response.json())
except Exception as e:
    print("Request failed:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-
41d4-a716-446655440000/usage-statistics/credit-
categories/{itemPk}/members/?
endDate=example&page=1&pageSize=1&startDate=example&timeGranularity=
day", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response retrieved successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request failed: ' . $e->getMessage();
}
?>
```

Response

Status Code: 200

Example Response Schema

```
{
  "count": integer
  "next"?: string (uri) // Optional
  "previous"?: string (uri) // Optional
  "results": [
    object
  ]
}
```

Example Response Values

```
{
  "count": 123,
  "next": "http://api.example.org/accounts/?page=4",
  "previous": "http://api.example.org/accounts/?page=2",
  "results": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "Example response name",
      "description": "Example response description"
    }
  ]
}
```

Retrieve Billable Item Usage for a Single Member

GET `/api/v1/organizations/{organizationPk}/usage-statistics/credit-categories/{itemPk}/members/{id}`

Required permissions: Usage statistics permission. Billing mode: The organization must use Credit billing.

Parameters

Parameter Name	Required	Type	Description
`id`	V	string	
`itemPk`	V	string	
`organizationPk`	V	string	A UUID string identifying this organization ID
`endDate`	X	string	End date, format: YYYY-MM-DD
`startDate`	V	string	Start date, format: YYYY-MM-DD
`timeGranularity`	X	string	Time granularity (hour/day/month)

Code Examples

Shell/Bash

```
# API Call Example (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/organizations/550e8400-
e29b-41d4-a716-446655440000/usage-statistics/credit-
categories/{itemPk}/members/550e8400-e29b-41d4-a716-446655440000/?
endDate=example&startDate=example&timeGranularity=day"

  -H "Authorization: Api-Key YOUR_API_KEY"

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/organizations/550e8400-
e29b-41d4-a716-446655440000/usage-statistics/credit-
categories/{itemPk}/members/550e8400-e29b-41d4-a716-446655440000/?
endDate=example&startDate=example&timeGranularity=day", config)
  .then(response => {
    console.log('Response retrieved successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request failed:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-41d4-a716-446655440000/usage-statistics/credit-categories/{itemPk}/members/550e8400-e29b-41d4-a716-446655440000/?endDate=example&startDate=example&timeGranularity=day"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("Response retrieved successfully:")
    print(response.json())
except Exception as e:
    print("Request failed:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-
41d4-a716-446655440000/usage-statistics/credit-
categories/{itemPk}/members/550e8400-e29b-41d4-a716-446655440000/?
endDate=example&startDate=example&timeGranularity=day", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response retrieved successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request failed: ' . $e->getMessage();
}
?>
```

Response

Status Code: 200

Example Response Schema

```
object
```

Example Response Values

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "name": "Example response name",
  "description": "Example response description"
}
```

Retrieve Default Quota Settings for New Members

GET `/api/v1/credit/wallets/{id}/new-member-quota-policy/`

Required permissions: Credit management permissions. Billing mode: Any. The path parameter id is the wallet ID (creditWallet.id in the GET /api/v1/organizations/{id}/ response). Response fields: newMemberQuotaEnabled (whether to allocate quotas automatically), newMemberQuotaLimit (quota limit), newMemberQuotaValidDays (number of days the quota is valid from the date the member joins; null means no expiration), newMemberQuotaResetPeriod (usage reset interval), newMemberQuotaNote (note), and requireQuotaBeforeConsumption (whether to block usage when a new member has no quota).

Parameters

Parameter Name	Required	Type	Description
`id`	V	string	A UUID string identifying this Credit Wallet.

Code Examples

Shell/Bash

```shell
# Example API Call (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/credit/wallets/550e8400-e29b-41d4-a716-446655440000/new-member-quota-policy/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```javascript
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/credit/wallets/550e8400-e29b-41d4-a716-446655440000/new-member-quota-policy/", config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/credit/wallets/550e8400-e29b-41d4-a716-446655440000/new-member-quota-policy/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/credit/wallets/550e8400-e29b-
41d4-a716-446655440000/new-member-quota-policy/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response Body

Status Code: 200

Example Response Schema

```
{
  "newMemberQuotaEnabled"?: boolean // Optional
  "newMemberQuotaLimit"?: string (decimal) // Optional
```

```
  "newMemberQuotaValidDays"?: integer // Optional
  "newMemberQuotaResetPeriod"?: string (enum: none, daily, weekly,
monthly) // * `none` - No Reset
* `daily` - Daily
* `weekly` - Weekly
* `monthly` - Monthly (Optional)
  "newMemberQuotaNote"?: string // Optional
  "requireQuotaBeforeConsumption"?: boolean // Optional
}
```

Example Response Values

```
{
  "newMemberQuotaEnabled": false,
  "newMemberQuotaLimit": "Response string",
  "newMemberQuotaValidDays": 456,
  "newMemberQuotaResetPeriod": "none",
  "newMemberQuotaNote": "Response string",
  "requireQuotaBeforeConsumption": false
}
```

Update Default Quota Settings for New Members

PATCH `/api/v1/credit/wallets/{id}/new-member-quota-policy/`

Required permissions: Credit management permissions. Billing mode: The organization must use Credit billing; otherwise, the API returns 400. Send only the fields to update. The fields are the same as those returned when retrieving the settings: newMemberQuotaLimit must not be negative and must have a value when newMemberQuotaEnabled is enabled; newMemberQuotaValidDays must be between 1 and 3650, or null. Once enabled, members who subsequently join through invitations, directory synchronization, SSO, or import automatically receive a personal quota that takes effect when they join. When a validity period is set, the expiration time cannot be later than the expiration date of the organization’ s most recently credited quota (null means no expiration). If an invitation includes creditQuota, the quota specified in the invitation takes precedence (these defaults apply if the specified quota has expired or allocation fails). When requireQuotaBeforeConsumption is enabled, new members who have not received a quota cannot use features that consume Credit until

a quota is allocated to them. Changing these settings does not affect previously allocated quotas or existing members. Response: message and config (the updated settings).

Parameters

Parameter Name	Required	Type	Description
`id`	V	string	A UUID string identifying this Credit Wallet.

Request Body

Request Parameters

Field	Type	Required	Description
newMemberQuotaEnabled	boolean	No	
newMemberQuotaLimit	string (decimal)	No	
newMemberQuotaValidDays	integer	No	
newMemberQuotaResetPeriod	string (enum: none, daily, weekly, monthly)	No	`none` : No Reset ; `daily` : Daily ; `weekly` : Weekly ; `monthly` : Monthly;
newMemberQuotaNote	string	No	
requireQuotaBeforeConsumption	boolean	No	

Example Request Schema

```
{
  "newMemberQuotaEnabled"?: boolean // Optional
  "newMemberQuotaLimit"?: string (decimal) // Optional
  "newMemberQuotaValidDays"?: integer // Optional
  "newMemberQuotaResetPeriod"?: string (enum: none, daily, weekly,
monthly) // * `none` - No Reset
```

```
* `daily` - Daily
* `weekly` - Weekly
* `monthly` - Monthly (Optional)
  "newMemberQuotaNote"?: string // Optional
  "requireQuotaBeforeConsumption"?: boolean // Optional
}
```

Example Request Values

```
{
  "newMemberQuotaEnabled": true,
  "newMemberQuotaLimit": "100",
  "newMemberQuotaValidDays": 30,
  "newMemberQuotaResetPeriod": "none",
  "requireQuotaBeforeConsumption": false
}
```

Code Examples

Shell/Bash

```
# Example API Call (Shell)
curl -X PATCH
"https://api.maiagent.ai/api/v1/credit/wallets/550e8400-e29b-41d4-
a716-446655440000/new-member-quota-policy/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "newMemberQuotaEnabled": true,
    "newMemberQuotaLimit": "100",
    "newMemberQuotaValidDays": 30,
    "newMemberQuotaResetPeriod": "none",
    "requireQuotaBeforeConsumption": false
  }'

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// Request Body (payload)
const data = {
    "newMemberQuotaEnabled": true,
    "newMemberQuotaLimit": "100",
    "newMemberQuotaValidDays": 30,
    "newMemberQuotaResetPeriod": "none",
    "requireQuotaBeforeConsumption": false
  };

axios.patch("https://api.maiagent.ai/api/v1/credit/wallets/550e8400-
e29b-41d4-a716-446655440000/new-member-quota-policy/", data, config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/credit/wallets/550e8400-e29b-
41d4-a716-446655440000/new-member-quota-policy/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# Request Body (payload)
data = {
    "newMemberQuotaEnabled": True,
    "newMemberQuotaLimit": "100",
    "newMemberQuotaValidDays": 30,
    "newMemberQuotaResetPeriod": "none",
    "requireQuotaBeforeConsumption": False
}

response = requests.patch(url, json=data, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>patch("https://api.maiagent.ai/api/v1/credit/wallets/550e8400-e29b-
41d4-a716-446655440000/new-member-quota-policy/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'newMemberQuotaEnabled' => true,
            'newMemberQuotaLimit' => '100',
            'newMemberQuotaValidDays' => 30,
            'newMemberQuotaResetPeriod' => 'none',
            'requireQuotaBeforeConsumption' => false
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response Body

Status Code: 200

Example Response Schema

```
{
  "message": string
  "config": { // Organization-level policy for new members: default
personal quota plus the consumption guardrail.
  {
    "newMemberQuotaEnabled"?: boolean // Optional
    "newMemberQuotaLimit"?: string (decimal) // Optional
    "newMemberQuotaValidDays"?: integer // Optional
    "newMemberQuotaResetPeriod"?: string (enum: none, daily, weekly,
monthly) // * `none` - No Reset
* `daily` - Daily
* `weekly` - Weekly
* `monthly` - Monthly (Optional)
    "newMemberQuotaNote"?: string // Optional
    "requireQuotaBeforeConsumption"?: boolean // Optional
  }
  }
}
```

Example Response Values

```
{
  "message": "Response string",
  "config": {
    "newMemberQuotaEnabled": false,
    "newMemberQuotaLimit": "Response string",
    "newMemberQuotaValidDays": 456,
    "newMemberQuotaResetPeriod": "none",
    "newMemberQuotaNote": "Response string",
    "requireQuotaBeforeConsumption": false
  }
}
```

Status Code: 400 - Validation failed, or the organization is not on credit billing.

List Current Member Quotas

`GET` `/api/v1/organizations/{organizationPk}/credit-quota-members/`

Required permissions: Credit management permission. Billing mode: The organization must use Credit billing.

Parameters

Parameter Name	Required	Type	Description
`organizationPk`	V	string	A UUID string identifying this organization ID
`ordering`	X	string	Sort field (default '-created_at')
`page`	X	integer	Page number
`pageSize`	X	integer	Rows per page (max 100)
`quotaStatus`	X	string	Filter by quota status
`search`	X	string	Filter by member name, email, or member ID (case-insensitive substring)

Code Examples

Shell/Bash

```
# API Call Example (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/organizations/550e8400-
e29b-41d4-a716-446655440000/credit-quota-members/?ordering=-
created_at&page=1&pageSize=1&quotaStatus=allocated&search=example"

  -H "Authorization: Api-Key YOUR_API_KEY"

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/organizations/550e8400-
e29b-41d4-a716-446655440000/credit-quota-members/?ordering=-
created_at&page=1&pageSize=1&quotaStatus=allocated&search=example",
config)
  .then(response => {
    console.log('Response retrieved successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request failed:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-41d4-a716-446655440000/credit-quota-members/?ordering=-created_at&page=1&pageSize=1&quotaStatus=allocated&search=example"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("Response retrieved successfully:")
    print(response.json())
except Exception as e:
    print("Request failed:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-
41d4-a716-446655440000/credit-quota-members/?ordering=-
created_at&page=1&pageSize=1&quotaStatus=allocated&search=example",
[
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response retrieved successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request failed: ' . $e->getMessage();
}
?>
```

Response

Status Code: 200

Example Response Schema

```
{
  "count": integer
  "next"?: string (uri) // Optional
  "previous"?: string (uri) // Optional
  "results": [
    {
      "count"?: integer // Optional
      "next"?: string (uri) // Optional
      "previous"?: string (uri) // Optional
      "results"?: [ // Optional
        {
          "id"?: string (uuid) // Optional
          "name"?: string // Optional
          "email"?: string // Optional
          "credit_quota_required"?: boolean // Optional
          "active_quota"?: { // Most recent quota summary (active first);
same shape as the members API active_quota. (Optional)
          {
            "id"?: string (uuid) // Optional
            "quota_limit"?: string // Optional
            "consumed_amount"?: string // Optional
            "remaining"?: string // Optional
            "valid_from"?: string (date-time) // Optional
            "valid_until"?: string (date-time) // Optional
            "is_active"?: boolean // Optional
            "expired_at"?: string (date-time) // Optional
            "note"?: string // Optional
          }
          }
        }
      ]
      "stats"?: { // Organization-wide member counts, unaffected by
search or quota_status filter. (Optional)
      {
        "total"?: integer // Optional
        "allocated"?: integer // Optional
        "expired"?: integer // Optional
        "unallocated"?: integer // Optional
      }
      }
    }
  ]
}
```

Example Response Values


```
{
  "count": 123,
  "next": "http://api.example.org/accounts/?page=4",
  "previous": "http://api.example.org/accounts/?page=2",
  "results": [
    {
      "count": 456,
      "next": "https://example.com/file.jpg",
      "previous": "https://example.com/file.jpg",
      "results": [
        {
          "id": "550e8400-e29b-41d4-a716-446655440000",
          "name": "Response string",
          "email": "Response string",
          "credit_quota_required": false,
          "active_quota": {
            "id": "550e8400-e29b-41d4-a716-446655440000",
            "name": "Example response name",
            "description": "Example response description"
          }
        }
      ],
      "stats": {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "name": "Example response name",
        "description": "Example response description"
      }
    }
  ]
}
```


List Current Role Quotas

`GET` `/api/v1/organizations/{organizationPk}/credit-quota-groups/`

Required permissions: Credit management permission. Billing mode: The organization must use Credit billing.

Parameters

Parameter Name	Required	Type	Description
`organizationPk`	V	string	A UUID string identifying this organization ID
`ordering`	X	string	Sort field (default '-created_at')
`page`	X	integer	Page number
`pageSize`	X	integer	Rows per page (max 100)
`quotaStatus`	X	string	Filter by quota status
`search`	X	string	Filter by group name or group ID (case-insensitive substring)

Code Examples

Shell/Bash

```
# API call example (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/organizations/550e8400-
e29b-41d4-a716-446655440000/credit-quota-groups/?ordering=-
created_at&page=1&pageSize=1&quotaStatus=allocated&search=example"

  -H "Authorization: Api-Key YOUR_API_KEY"

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/organizations/550e8400-
e29b-41d4-a716-446655440000/credit-quota-groups/?ordering=-
created_at&page=1&pageSize=1&quotaStatus=allocated&search=example",
config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request failed:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-41d4-a716-446655440000/credit-quota-groups/?ordering=-created_at&page=1&pageSize=1&quotaStatus=allocated&search=example"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request failed:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-
41d4-a716-446655440000/credit-quota-groups/?ordering=-
created_at&page=1&pageSize=1&quotaStatus=allocated&search=example",
[
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request failed: ' . $e->getMessage();
}
?>
```

Response Body

Status Code: 200

Example Response Structure

```
{
  "count": integer
  "next"?: string (uri) // Optional
  "previous"?: string (uri) // Optional
  "results": [
    {
      "count"?: integer // Optional
      "next"?: string (uri) // Optional
      "previous"?: string (uri) // Optional
      "results"?: [ // Optional
        {
          "id"?: string (uuid) // Optional
          "name"?: string // Optional
          "type"?: string (enum: owner, default, custom) // Optional
          "credit_quota_required"?: boolean // Optional
          "active_quota"?: { // Most recent quota summary (active first);
same shape as the member/inbox variants. (Optional)
          {
            "id"?: string (uuid) // Optional
            "quota_limit"?: string // Optional
            "consumed_amount"?: string // Optional
            "remaining"?: string // Optional
            "valid_from"?: string (date-time) // Optional
            "valid_until"?: string (date-time) // Optional
            "is_active"?: boolean // Optional
            "expired_at"?: string (date-time) // Optional
            "note"?: string // Optional
          }
          }
        }
      ]
      "stats"?: { // Organization-wide group counts, unaffected by search
or quota_status filter. (Optional)
      {
        "total"?: integer // Optional
        "allocated"?: integer // Optional
        "expired"?: integer // Optional
        "unallocated"?: integer // Optional
      }
      }
    }
  ]
}
```

Example Response Values


```
{
  "count": 123,
  "next": "http://api.example.org/accounts/?page=4",
  "previous": "http://api.example.org/accounts/?page=2",
  "results": [
    {
      "count": 456,
      "next": "https://example.com/file.jpg",
      "previous": "https://example.com/file.jpg",
      "results": [
        {
          "id": "550e8400-e29b-41d4-a716-446655440000",
          "name": "Response string",
          "type": "owner",
          "credit_quota_required": false,
          "active_quota": {
            "id": "550e8400-e29b-41d4-a716-446655440000",
            "name": "Example response name",
            "description": "Example response description"
          }
        }
      ],
      "stats": {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "name": "Example response name",
        "description": "Example response description"
      }
    }
  ]
}
```


List Inbox Quota Status

`GET` `/api/v1/organizations/{organizationPk}/credit-quota-inboxes/`

Required permission: Credit management permission. Billing mode: The organization must use Credit billing.

Parameters

Parameter Name	Required	Type	Description
`organizationPk`	V	string	A UUID string identifying this organization ID
`excludeBuiltIn`	X	boolean	When true, excludes data for official built-in Agents (locked instances created by renting from the Agent Marketplace), leaving only assistants created by the organization. Copies created using “Copy as Custom” count as organization-created assistants. Omitting this parameter or setting it to false applies no filtering.
`ordering`	X	string	Which field to use when ordering the results.
`page`	X	integer	A page number within the paginated result set.
`pageSize`	X	integer	Number of results to return per page.
`search`	X	string	A search term.

Code Examples

Shell/Bash

```
# API call example (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/organizations/550e8400-
e29b-41d4-a716-446655440000/credit-quota-inboxes/?
excludeBuiltIn=true&ordering=example&page=1&pageSize=1&search=exampl
e"

  -H "Authorization: Api-Key YOUR_API_KEY"

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/organizations/550e8400-
e29b-41d4-a716-446655440000/credit-quota-inboxes/?
excludeBuiltIn=true&ordering=example&page=1&pageSize=1&search=exampl
e", config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-
41d4-a716-446655440000/credit-quota-inboxes/?
excludeBuiltIn=true&ordering=example&page=1&pageSize=1&search=exampl
e"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-
41d4-a716-446655440000/credit-quota-inboxes/?
excludeBuiltIn=true&ordering=example&page=1&pageSize=1&search=exampl
e", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response Body

Status Code: 200

Example Response Schema

```
{
  "count": integer
  "next"?: string (uri) // Optional
  "previous"?: string (uri) // Optional
  "results": [
    {
      "id": string (uuid)
      "name": string
      "channelType":
      {
      }
      "channelTypeLabel": string
      "webChatAccessType": string // Sub-type for web channels (web =
public embed, admin = internal Q&A, api = completions).

A chatbot ships with three same-named web inboxes, so the frontend needs
this to tell them apart. None for non-web channels. Reads the prefetched
generic ``channel`` relation (no extra query on the list path).
      "chatbot": object
      "creditQuotaRequired": boolean // When True, this inbox must have
an active credit quota for the AI to reply
      "activeQuota": object // Return the most recent quota summary
(active first), via prefetch to avoid N+1.
      "canUpdate": boolean // Return whether the current user can update
this resource.
    }
  ]
}
```

Example Response Values

```
{
  "count": 123,
  "next": "http://api.example.org/accounts/?page=4",
  "previous": "http://api.example.org/accounts/?page=2",
  "results": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "Response string",
      "channelType": {},
      "channelTypeLabel": "Response string",
      "webChatAccessType": "Response string",
      "chatbot": {
```

```
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "name": "Example response name",
        "description": "Example response description"
      },
      "creditQuotaRequired": false,
      "activeQuota": {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "name": "Example response name",
        "description": "Example response description"
      },
      "canUpdate": false
    }
  ]
}
```


List Member Quota Settings

`GET` `/api/v1/organizations/{organizationPk}/members/{memberPk}/credit-quotas/`

Required permissions: Credit management permissions. Billing mode: The organization must use Credit billing.

Parameters

Parameter Name	Required	Type	Description
`memberPk`	V	string	
`organizationPk`	V	string	A UUID string identifying this organization ID
`page`	X	integer	A page number within the paginated result set.

`pageSize`	X	integer	Number of results to return per page.

Code Examples

Shell/Bash

```
# API call example (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/organizations/550e8400-
e29b-41d4-a716-446655440000/members/{memberPk}/credit-quotas/?
page=1&pageSize=1"

  -H "Authorization: Api-Key YOUR_API_KEY"

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/organizations/550e8400-
e29b-41d4-a716-446655440000/members/{memberPk}/credit-quotas/?
page=1&pageSize=1", config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request failed:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-
41d4-a716-446655440000/members/{memberPk}/credit-quotas/?
page=1&pageSize=1"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request failed:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-
41d4-a716-446655440000/members/{memberPk}/credit-quotas/?
page=1&pageSize=1", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request failed: ' . $e->getMessage();
}
?>
```

Response Body

Status Code: 200

Example Response Structure

```
{
  "count": integer
```

```
  "next"?: string (uri) // Optional
  "previous"?: string (uri) // Optional
  "results": [
    {
      "id": string (uuid)
      "member": object
      "quotaLimit": string (decimal) // Maximum credits this member may
consume
      "consumedAmount": string (decimal) // Credits consumed so far
(updated via F() for concurrency safety)
      "remaining": string (decimal)
      "validFrom": string (timestamp)
      "validUntil": string (timestamp) // NULL means permanent
      "resetPeriod":  // Cycle on which consumed_amount is automatically
zeroed; "none" keeps the one-shot ceiling

* `none` - No Reset
* `daily` - Daily
* `weekly` - Weekly
* `monthly` - Monthly
      {
      }
      "nextResetAt": string (timestamp) // Local-midnight boundary of the
next automatic reset; NULL when reset_period is "none"
      "isActive": boolean
      "expiredAt": string (timestamp) // Actual deactivation time (cron
or manual)
      "createdBy": object
      "note": string
      "createdAt": string (timestamp)
      "updatedAt": string (timestamp)
    }
  ]
}
```

Example Response Values

```
{
  "count": 123,
  "next": "http://api.example.org/accounts/?page=4",
  "previous": "http://api.example.org/accounts/?page=2",
  "results": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
```

```
      "member": {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "name": "Example response name",
        "description": "Example response description"
      },
      "quotaLimit": "Response string",
      "consumedAmount": "Response string",
      "remaining": "Response string",
      "validFrom": "Response string",
      "validUntil": "Response string",
      "resetPeriod": {},
      "nextResetAt": "Response string",
      "isActive": false,
      "expiredAt": "Response string",
      "createdBy": {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "name": "Example response name",
        "description": "Example response description"
      },
      "note": "Response string",
      "createdAt": "Response string",
      "updatedAt": "Response string"
    }
  ]
}
```


Retrieve a Member Quota Setting

GET `/api/v1/organizations/{organizationPk}/members/{memberPk}/credit-quotas/{id}`

Required permissions: Credit management permissions. Billing mode: The organization must use Credit billing.

Parameters

Parameter Name	Required	Type	Description
`id`	V	string	
`memberPk`	V	string	
`organizationPk`	V	string	A UUID string identifying this organization ID

Code Examples

Shell/Bash

```
# API call example (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-41d4-a716-446655440000/members/{memberPk}/credit-quotas/550e8400-e29b-41d4-a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/organizations/550e8400-
e29b-41d4-a716-446655440000/members/{memberPk}/credit-
quotas/550e8400-e29b-41d4-a716-446655440000/", config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request failed:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-41d4-a716-446655440000/members/{memberPk}/credit-quotas/550e8400-e29b-41d4-a716-446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request failed:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-
41d4-a716-446655440000/members/{memberPk}/credit-quotas/550e8400-
e29b-41d4-a716-446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request failed: ' . $e->getMessage();
}
?>
```

Response Body

Status Code: 200

Example Response Structure

```
{
  "id": string (uuid)
```

```
  "member": object
  "quotaLimit": string (decimal) // Maximum credits this member may
consume
  "consumedAmount": string (decimal) // Credits consumed so far (updated
via F() for concurrency safety)
  "remaining": string (decimal)
  "validFrom": string (timestamp)
  "validUntil": string (timestamp) // NULL means permanent
  "resetPeriod":  // Cycle on which consumed_amount is automatically
zeroed; "none" keeps the one-shot ceiling

* `none` - No Reset
* `daily` - Daily
* `weekly` - Weekly
* `monthly` - Monthly
  {
  }
  "nextResetAt": string (timestamp) // Local-midnight boundary of the
next automatic reset; NULL when reset_period is "none"
  "isActive": boolean
  "expiredAt": string (timestamp) // Actual deactivation time (cron or
manual)
  "createdBy": object
  "note": string
  "createdAt": string (timestamp)
  "updatedAt": string (timestamp)
}
```

Example Response Values


```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "member": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Example response name",
    "description": "Example response description"
  },
  "quotaLimit": "Response string",
  "consumedAmount": "Response string",
  "remaining": "Response string",
  "validFrom": "Response string",
  "validUntil": "Response string",
  "resetPeriod": {},
  "nextResetAt": "Response string",
```

```
  "isActive": false,
  "expiredAt": "Response string",
  "createdBy": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Example response name",
    "description": "Example response description"
  },
  "note": "Response string",
  "createdAt": "Response string",
  "updatedAt": "Response string"
}
```


Set a quota for a member

POST `/api/v1/organizations/{organizationPk}/members/{memberPk}/credit-quotas/`

Required permissions: Credit management permissions. Billing mode: The organization must use Credit billing. See How quotas work for the request body and rules. If the member already has an active quota, the API returns 400; deactivate it first.

Parameters

Parameter name	Required	Type	Description
`memberPk`	V	string	
`organizationPk`	V	string	A UUID string identifying this organization ID

Request body

Request parameters

Field	Type	Required	Description
quotaLimit	string (decimal)	Yes	
validFrom	string (date-time)	Yes	
validUntil	string (date-time)	No	
note	string	No	
resetPeriod	object	No	

Example request schema

```
{
  "quotaLimit": string (decimal)
  "validFrom": string (date-time)
  "validUntil"?: string (date-time) // Optional
  "note"?: string // Optional
  "resetPeriod"?:  // Optional
  {
  }
}
```

Example request values

```
{
  "quotaLimit": "500",
  "validFrom": "2026-10-16T00:00:00+08:00",
  "validUntil": "2026-12-31T23:59:59+08:00",
  "resetPeriod": "monthly",
  "note": "Q4 budget"
}
```

Code examples

Shell/Bash

```
# API call example (Shell)
curl -X POST "https://api.maiagent.ai/api/v1/organizations/550e8400-
e29b-41d4-a716-446655440000/members/{memberPk}/credit-quotas/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "quotaLimit": "500",
    "validFrom": "2026-10-16T00:00:00+08:00",
    "validUntil": "2026-12-31T23:59:59+08:00",
    "resetPeriod": "monthly",
    "note": "Q4 budget"
  }'

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// Request body (payload)
const data = {
    "quotaLimit": "500",
    "validFrom": "2026-10-16T00:00:00+08:00",
    "validUntil": "2026-12-31T23:59:59+08:00",
    "resetPeriod": "monthly",
    "note": "Q4 budget"
  };

axios.post("https://api.maiagent.ai/api/v1/organizations/550e8400-
e29b-41d4-a716-446655440000/members/{memberPk}/credit-quotas/",
data, config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request failed:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-
41d4-a716-446655440000/members/{memberPk}/credit-quotas/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# Request body (payload)
data = {
    "quotaLimit": "500",
    "validFrom": "2026-10-16T00:00:00+08:00",
    "validUntil": "2026-12-31T23:59:59+08:00",
    "resetPeriod": "monthly",
    "note": "Q4 budget"
}

response = requests.post(url, json=data, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request failed:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>post("https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-
41d4-a716-446655440000/members/{memberPk}/credit-quotas/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'quotaLimit' => '500',
            'validFrom' => '2026-10-16T00:00:00+08:00',
            'validUntil' => '2026-12-31T23:59:59+08:00',
            'resetPeriod' => 'monthly',
            'note' => 'Q4 budget'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request failed: ' . $e->getMessage();
}
?>
```

Response body

Status code: 201

Example response schema

```
{
  "id": string (uuid)
  "member": object
  "quotaLimit": string (decimal) // Maximum credits this member may
consume
  "consumedAmount": string (decimal) // Credits consumed so far (updated
via F() for concurrency safety)
  "remaining": string (decimal)
  "validFrom": string (timestamp)
  "validUntil": string (timestamp) // NULL means permanent
  "resetPeriod":  // Cycle on which consumed_amount is automatically
zeroed; "none" keeps the one-shot ceiling

* `none` - No Reset
* `daily` - Daily
* `weekly` - Weekly
* `monthly` - Monthly
  {
  }
  "nextResetAt": string (timestamp) // Local-midnight boundary of the
next automatic reset; NULL when reset_period is "none"
  "isActive": boolean
  "expiredAt": string (timestamp) // Actual deactivation time (cron or
manual)
  "createdBy": object
  "note": string
  "createdAt": string (timestamp)
  "updatedAt": string (timestamp)
}
```

Example response values

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "member": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Example response name",
    "description": "Example response description"
  },
```

```
  "quotaLimit": "Response string",
  "consumedAmount": "Response string",
  "remaining": "Response string",
  "validFrom": "Response string",
  "validUntil": "Response string",
  "resetPeriod": {},
  "nextResetAt": "Response string",
  "isActive": false,
  "expiredAt": "Response string",
  "createdBy": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Example response name",
    "description": "Example response description"
  },
  "note": "Response string",
  "createdAt": "Response string",
  "updatedAt": "Response string"
}
```


Update a member's quota settings

PATCH `/api/v1/organizations/{organizationPk}/members/{memberPk}/credit-quotas/{id}`

Required permissions: Credit management permissions. Billing mode: The organization must use Credit billing. Send only the fields to update: quotaLimit, validUntil, resetPeriod, and note (the start time cannot be changed). quotaLimit cannot be lower than the amount already consumed. Deactivated quotas cannot be updated; the API returns 400.

Parameters

Parameter name	Required	Type	Description
`id`	V	string	
`memberPk`	V	string	

`organizationPk`	V	string	A UUID string identifying this organization ID

Request body

Request parameters

Field	Type	Required	Description
quotaLimit	string (decimal)	No	
validUntil	string (date-time)	No	
note	string	No	
resetPeriod	string (enum: none, daily, weekly, monthly)	No	`none` : No Reset ; `daily` : Daily ; `weekly` : Weekly ; `monthly` : Monthly;

Example request schema

```
{
  "quotaLimit"?: string (decimal) // Optional
  "validUntil"?: string (date-time) // Optional
  "note"?: string // Optional
  "resetPeriod"?: string (enum: none, daily, weekly, monthly) // * `none`
- No Reset
* `daily` - Daily
* `weekly` - Weekly
* `monthly` - Monthly (Optional)
}
```

Example request values

```
{
  "quotaLimit": "Example string",
  "validUntil": "2025-01-01T00:00:00.000Z",
  "note": "Example string",
```

```
  "resetPeriod": "none"
}
```

Code examples

Shell/Bash

```
# API call example (Shell)
curl -X PATCH
"https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-41d4-
a716-446655440000/members/{memberPk}/credit-quotas/550e8400-e29b-
41d4-a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "quotaLimit": "Example string",
    "validUntil": "2025-01-01T00:00:00.000Z",
    "note": "Example string",
    "resetPeriod": "none"
  }'

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// Request body (payload)
const data = {
    "quotaLimit": "Example string",
    "validUntil": "2025-01-01T00:00:00.000Z",
    "note": "Example string",
    "resetPeriod": "none"
  };

axios.patch("https://api.maiagent.ai/api/v1/organizations/550e8400-
e29b-41d4-a716-446655440000/members/{memberPk}/credit-
quotas/550e8400-e29b-41d4-a716-446655440000/", data, config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request failed:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-41d4-a716-446655440000/members/{memberPk}/credit-quotas/550e8400-e29b-41d4-a716-446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# Request body (payload)
data = {
    "quotaLimit": "Example string",
    "validUntil": "2025-01-01T00:00:00.000Z",
    "note": "Example string",
    "resetPeriod": "none"
}

response = requests.patch(url, json=data, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request failed:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>patch("https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-
41d4-a716-446655440000/members/{memberPk}/credit-quotas/550e8400-
e29b-41d4-a716-446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'quotaLimit' => 'Example string',
            'validUntil' => '2025-01-01T00:00:00.000Z',
            'note' => 'Example string',
            'resetPeriod' => 'none'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request failed: ' . $e->getMessage();
}
?>
```

Response body

Status code: 200

Example response schema

```
{
  "id": string (uuid)
  "member": object
  "quotaLimit": string (decimal) // Maximum credits this member may
consume
  "consumedAmount": string (decimal) // Credits consumed so far (updated
via F() for concurrency safety)
  "remaining": string (decimal)
  "validFrom": string (timestamp)
  "validUntil": string (timestamp) // NULL means permanent
  "resetPeriod":  // Cycle on which consumed_amount is automatically
zeroed; "none" keeps the one-shot ceiling

* `none` - No Reset
* `daily` - Daily
* `weekly` - Weekly
* `monthly` - Monthly
  {
  }
  "nextResetAt": string (timestamp) // Local-midnight boundary of the
next automatic reset; NULL when reset_period is "none"
  "isActive": boolean
  "expiredAt": string (timestamp) // Actual deactivation time (cron or
manual)
  "createdBy": object
  "note": string
  "createdAt": string (timestamp)
  "updatedAt": string (timestamp)
}
```

Example response values

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "member": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Example response name",
    "description": "Example response description"
  },
```

```
  "quotaLimit": "Response string",
  "consumedAmount": "Response string",
  "remaining": "Response string",
  "validFrom": "Response string",
  "validUntil": "Response string",
  "resetPeriod": {},
  "nextResetAt": "Response string",
  "isActive": false,
  "expiredAt": "Response string",
  "createdBy": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Example response name",
    "description": "Example response description"
  },
  "note": "Response string",
  "createdAt": "Response string",
  "updatedAt": "Response string"
}
```


Deactivate a Member's Quota

DELETE `/api/v1/organizations/{organizationPk}/members/{memberPk}/credit-quotas/{id}`

Required permission: Credit management permission. Billing mode: The organization must use the Credit billing mode. Returns 204 on success. After deactivation, the member's "Quota required" setting remains on, so the member cannot use Credit-consuming features until a new quota is set or the quota restriction is removed; deactivating an already deactivated quota returns 400.

Parameters

Parameter Name	Required	Type	Description
`id`	V	string	
`memberPk`	V	string	

`organizationPk`	V	string	A UUID string identifying this Organization ID

Code Examples

Shell/Bash

```
# Example API call (Shell)
curl -X DELETE
"https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-41d4-
a716-446655440000/members/{memberPk}/credit-quotas/550e8400-e29b-
41d4-a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# Make sure to replace YOUR_API_KEY and verify the request data
before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

// Request payload
const data = null;

axios.delete("https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-41d4-a716-446655440000/members/{memberPk}/credit-quotas/550e8400-e29b-41d4-a716-446655440000/", data, config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request failed:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-
41d4-a716-446655440000/members/{memberPk}/credit-quotas/550e8400-
e29b-41d4-a716-446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.delete(url, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request failed:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>delete("https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-
41d4-a716-446655440000/members/{memberPk}/credit-quotas/550e8400-
e29b-41d4-a716-446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request failed: ' . $e->getMessage();
}
?>
```

Response

Status Code	Description
204	No response body

List Role Quota Settings

`GET` `/api/v1/organizations/{organizationPk}/groups/{groupPk}/credit-quotas/`

Required permissions: Credit management permissions. Billing mode: The organization must use Credit billing.

Parameters

Parameter Name	Required	Type	Description
`groupPk`	V	string	
`organizationPk`	V	string	A UUID string identifying this organization ID
`page`	X	integer	A page number within the paginated result set.
`pageSize`	X	integer	Number of results to return per page.

Code Examples

Shell/Bash

```
# API call example (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/organizations/550e8400-
e29b-41d4-a716-446655440000/groups/{groupPk}/credit-quotas/?
page=1&pageSize=1"

  -H "Authorization: Api-Key YOUR_API_KEY"

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/organizations/550e8400-
e29b-41d4-a716-446655440000/groups/{groupPk}/credit-quotas/?
page=1&pageSize=1", config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request failed:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-
41d4-a716-446655440000/groups/{groupPk}/credit-quotas/?
page=1&pageSize=1"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request failed:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-
41d4-a716-446655440000/groups/{groupPk}/credit-quotas/?
page=1&pageSize=1", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request failed: ' . $e->getMessage();
}
?>
```

Response Body

Status Code: 200

Response Schema Example

```
{
  "count": integer
```

```
  "next"?: string (uri) // Optional
  "previous"?: string (uri) // Optional
  "results": [
    {
      "id": string (uuid)
      "group": object
      "quotaLimit": string (decimal) // Maximum credits members of this
group may consume
      "consumedAmount": string (decimal) // Credits consumed so far
(updated via F() for concurrency safety)
      "remaining": string (decimal)
      "validFrom": string (timestamp)
      "validUntil": string (timestamp) // NULL means permanent
      "resetPeriod":  // Cycle on which consumed_amount is automatically
zeroed; "none" keeps the one-shot ceiling

* `none` - No Reset
* `daily` - Daily
* `weekly` - Weekly
* `monthly` - Monthly
      {
      }
      "nextResetAt": string (timestamp) // Local-midnight boundary of the
next automatic reset; NULL when reset_period is "none"
      "isActive": boolean
      "expiredAt": string (timestamp) // Actual deactivation time (cron
or manual)
      "createdBy": object
      "note": string
      "createdAt": string (timestamp)
      "updatedAt": string (timestamp)
    }
  ]
}
```

Example Response Values

```
{
  "count": 123,
  "next": "http://api.example.org/accounts/?page=4",
  "previous": "http://api.example.org/accounts/?page=2",
  "results": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
```

```
      "group": {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "name": "Example response name",
        "description": "Example response description"
      },
      "quotaLimit": "Response string",
      "consumedAmount": "Response string",
      "remaining": "Response string",
      "validFrom": "Response string",
      "validUntil": "Response string",
      "resetPeriod": {},
      "nextResetAt": "Response string",
      "isActive": false,
      "expiredAt": "Response string",
      "createdBy": {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "name": "Example response name",
        "description": "Example response description"
      },
      "note": "Response string",
      "createdAt": "Response string",
      "updatedAt": "Response string"
    }
  ]
}
```


Retrieve a Role Quota Setting

`GET` `/api/v1/organizations/{organizationPk}/groups/{groupPk}/credit-quotas/{id}`

Required permissions: Credit management permissions. Billing mode: The organization must use Credit billing.

Parameters

Parameter Name	Required	Type	Description
`groupPk`	V	string	
`id`	V	string	
`organizationPk`	V	string	A UUID string identifying this organization ID

Code Examples

Shell/Bash

```
# API call example (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/organizations/550e8400-
e29b-41d4-a716-446655440000/groups/{groupPk}/credit-quotas/550e8400-
e29b-41d4-a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/organizations/550e8400-
e29b-41d4-a716-446655440000/groups/{groupPk}/credit-quotas/550e8400-
e29b-41d4-a716-446655440000/", config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request failed:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-41d4-a716-446655440000/groups/{groupPk}/credit-quotas/550e8400-e29b-41d4-a716-446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request failed:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-
41d4-a716-446655440000/groups/{groupPk}/credit-quotas/550e8400-e29b-
41d4-a716-446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request failed: ' . $e->getMessage();
}
?>
```

Response Body

Status Code: 200

Response Schema Example

```
{
  "id": string (uuid)
```

```
  "group": object
  "quotaLimit": string (decimal) // Maximum credits members of this group
may consume
  "consumedAmount": string (decimal) // Credits consumed so far (updated
via F() for concurrency safety)
  "remaining": string (decimal)
  "validFrom": string (timestamp)
  "validUntil": string (timestamp) // NULL means permanent
  "resetPeriod":  // Cycle on which consumed_amount is automatically
zeroed; "none" keeps the one-shot ceiling

* `none` - No Reset
* `daily` - Daily
* `weekly` - Weekly
* `monthly` - Monthly
  {
  }
  "nextResetAt": string (timestamp) // Local-midnight boundary of the
next automatic reset; NULL when reset_period is "none"
  "isActive": boolean
  "expiredAt": string (timestamp) // Actual deactivation time (cron or
manual)
  "createdBy": object
  "note": string
  "createdAt": string (timestamp)
  "updatedAt": string (timestamp)
}
```

Example Response Values

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "group": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Example response name",
    "description": "Example response description"
  },
  "quotaLimit": "Response string",
  "consumedAmount": "Response string",
  "remaining": "Response string",
  "validFrom": "Response string",
  "validUntil": "Response string",
  "resetPeriod": {},
  "nextResetAt": "Response string",
```

```
  "isActive": false,
  "expiredAt": "Response string",
  "createdBy": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Example response name",
    "description": "Example response description"
  },
  "note": "Response string",
  "createdAt": "Response string",
  "updatedAt": "Response string"
}
```


Set a quota for a role

POST `/api/v1/organizations/{organizationPk}/groups/{groupPk}/credit-quotas/`

Required permissions: Credit management permissions. Billing mode: The organization must use Credit billing. This sets a quota shared by all members of the role; it does not allocate quotas to individual members. To assign a separate quota to each member, use Batch allocate quotas by role. See How quotas work for the request body and rules. If the role already has an active quota, the API returns 400; deactivate it first.

Parameters

Parameter name	Required	Type	Description
`groupPk`	V	string	
`organizationPk`	V	string	A UUID string identifying this organization ID

Request body

Request parameters

Field	Type	Required	Description
quotaLimit	string (decimal)	Yes	
validFrom	string (date-time)	Yes	
validUntil	string (date-time)	No	
note	string	No	
resetPeriod	object	No	

Request schema example

```
{
  "quotaLimit": string (decimal)
  "validFrom": string (date-time)
  "validUntil"?: string (date-time) // Optional
  "note"?: string // Optional
  "resetPeriod"?:  // Optional
  {
  }
}
```

Example request values

```
{
  "quotaLimit": "500",
  "validFrom": "2026-10-16T00:00:00+08:00",
  "validUntil": "2026-12-31T23:59:59+08:00",
  "resetPeriod": "monthly",
  "note": "Q4 budget"
}
```

Code examples

Shell/Bash

```
# API call example (Shell)
curl -X POST "https://api.maiagent.ai/api/v1/organizations/550e8400-
e29b-41d4-a716-446655440000/groups/{groupPk}/credit-quotas/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "quotaLimit": "500",
    "validFrom": "2026-10-16T00:00:00+08:00",
    "validUntil": "2026-12-31T23:59:59+08:00",
    "resetPeriod": "monthly",
    "note": "Q4 budget"
  }'

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// Request body (payload)
const data = {
    "quotaLimit": "500",
    "validFrom": "2026-10-16T00:00:00+08:00",
    "validUntil": "2026-12-31T23:59:59+08:00",
    "resetPeriod": "monthly",
    "note": "Q4 budget"
  };

axios.post("https://api.maiagent.ai/api/v1/organizations/550e8400-
e29b-41d4-a716-446655440000/groups/{groupPk}/credit-quotas/", data,
config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request failed:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-
41d4-a716-446655440000/groups/{groupPk}/credit-quotas/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# Request body (payload)
data = {
    "quotaLimit": "500",
    "validFrom": "2026-10-16T00:00:00+08:00",
    "validUntil": "2026-12-31T23:59:59+08:00",
    "resetPeriod": "monthly",
    "note": "Q4 budget"
}

response = requests.post(url, json=data, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request failed:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>post("https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-
41d4-a716-446655440000/groups/{groupPk}/credit-quotas/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'quotaLimit' => '500',
            'validFrom' => '2026-10-16T00:00:00+08:00',
            'validUntil' => '2026-12-31T23:59:59+08:00',
            'resetPeriod' => 'monthly',
            'note' => 'Q4 budget'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request failed: ' . $e->getMessage();
}
?>
```

Response body

Status code: 201

Response schema example

```
{
  "id": string (uuid)
  "group": object
  "quotaLimit": string (decimal) // Maximum credits members of this group
may consume
  "consumedAmount": string (decimal) // Credits consumed so far (updated
via F() for concurrency safety)
  "remaining": string (decimal)
  "validFrom": string (timestamp)
  "validUntil": string (timestamp) // NULL means permanent
  "resetPeriod":  // Cycle on which consumed_amount is automatically
zeroed; "none" keeps the one-shot ceiling

* `none` - No Reset
* `daily` - Daily
* `weekly` - Weekly
* `monthly` - Monthly
  {
  }
  "nextResetAt": string (timestamp) // Local-midnight boundary of the
next automatic reset; NULL when reset_period is "none"
  "isActive": boolean
  "expiredAt": string (timestamp) // Actual deactivation time (cron or
manual)
  "createdBy": object
  "note": string
  "createdAt": string (timestamp)
  "updatedAt": string (timestamp)
}
```

Example response values

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "group": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Example response name",
    "description": "Example response description"
  },
```

```
  "quotaLimit": "Response string",
  "consumedAmount": "Response string",
  "remaining": "Response string",
  "validFrom": "Response string",
  "validUntil": "Response string",
  "resetPeriod": {},
  "nextResetAt": "Response string",
  "isActive": false,
  "expiredAt": "Response string",
  "createdBy": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Example response name",
    "description": "Example response description"
  },
  "note": "Response string",
  "createdAt": "Response string",
  "updatedAt": "Response string"
}
```


Update quota settings for a role

PATCH `/api/v1/organizations/{organizationPk}/groups/{groupPk}/credit-quotas/{id}`

Required permissions: Credit management permissions. Billing mode: The organization must use Credit billing. Send only the fields you want to change: quotaLimit, validUntil, resetPeriod, and note (the start time cannot be changed). quotaLimit cannot be lower than the amount already consumed. Deactivated quotas cannot be updated; the API returns 400.

Parameters

Parameter name	Required	Type	Description
`groupPk`	V	string	
`id`	V	string	

`organizationPk`	V	string	A UUID string identifying this organization ID

Request body

Request parameters

Field	Type	Required	Description
quotaLimit	string (decimal)	No	
validUntil	string (date-time)	No	
note	string	No	
resetPeriod	string (enum: none, daily, weekly, monthly)	No	`none` : No Reset ; `daily` : Daily ; `weekly` : Weekly ; `monthly` : Monthly;

Request schema example

```
{
  "quotaLimit"?: string (decimal) // Optional
  "validUntil"?: string (date-time) // Optional
  "note"?: string // Optional
  "resetPeriod"?: string (enum: none, daily, weekly, monthly) // * `none`
- No Reset
* `daily` - Daily
* `weekly` - Weekly
* `monthly` - Monthly (Optional)
}
```

Example request values

```
{
  "quotaLimit": "Example string",
  "validUntil": "2025-01-01T00:00:00.000Z",
  "note": "Example string",
```

```
  "resetPeriod": "none"
}
```

Code examples

Shell/Bash

```
# API call example (Shell)
curl -X PATCH
"https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-41d4-
a716-446655440000/groups/{groupPk}/credit-quotas/550e8400-e29b-41d4-
a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "quotaLimit": "Example string",
    "validUntil": "2025-01-01T00:00:00.000Z",
    "note": "Example string",
    "resetPeriod": "none"
  }'

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// Request body (payload)
const data = {
    "quotaLimit": "Example string",
    "validUntil": "2025-01-01T00:00:00.000Z",
    "note": "Example string",
    "resetPeriod": "none"
  };

axios.patch("https://api.maiagent.ai/api/v1/organizations/550e8400-
e29b-41d4-a716-446655440000/groups/{groupPk}/credit-quotas/550e8400-
e29b-41d4-a716-446655440000/", data, config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request failed:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-41d4-a716-446655440000/groups/{groupPk}/credit-quotas/550e8400-e29b-41d4-a716-446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# Request body (payload)
data = {
    "quotaLimit": "Example string",
    "validUntil": "2025-01-01T00:00:00.000Z",
    "note": "Example string",
    "resetPeriod": "none"
}

response = requests.patch(url, json=data, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request failed:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>patch("https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-
41d4-a716-446655440000/groups/{groupPk}/credit-quotas/550e8400-e29b-
41d4-a716-446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'quotaLimit' => 'Example string',
            'validUntil' => '2025-01-01T00:00:00.000Z',
            'note' => 'Example string',
            'resetPeriod' => 'none'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request failed: ' . $e->getMessage();
}
?>
```

Response body

Status code: 200

Response schema example

```
{
  "id": string (uuid)
  "group": object
  "quotaLimit": string (decimal) // Maximum credits members of this group
may consume
  "consumedAmount": string (decimal) // Credits consumed so far (updated
via F() for concurrency safety)
  "remaining": string (decimal)
  "validFrom": string (timestamp)
  "validUntil": string (timestamp) // NULL means permanent
  "resetPeriod":  // Cycle on which consumed_amount is automatically
zeroed; "none" keeps the one-shot ceiling

* `none` - No Reset
* `daily` - Daily
* `weekly` - Weekly
* `monthly` - Monthly
  {
  }
  "nextResetAt": string (timestamp) // Local-midnight boundary of the
next automatic reset; NULL when reset_period is "none"
  "isActive": boolean
  "expiredAt": string (timestamp) // Actual deactivation time (cron or
manual)
  "createdBy": object
  "note": string
  "createdAt": string (timestamp)
  "updatedAt": string (timestamp)
}
```

Example response values

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "group": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Example response name",
    "description": "Example response description"
  },
```

```
  "quotaLimit": "Response string",
  "consumedAmount": "Response string",
  "remaining": "Response string",
  "validFrom": "Response string",
  "validUntil": "Response string",
  "resetPeriod": {},
  "nextResetAt": "Response string",
  "isActive": false,
  "expiredAt": "Response string",
  "createdBy": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Example response name",
    "description": "Example response description"
  },
  "note": "Response string",
  "createdAt": "Response string",
  "updatedAt": "Response string"
}
```


Deactivate a Role's Quota Settings

DELETE `/api/v1/organizations/{organizationPk}/groups/{groupPk}/credit-quotas/{id}`

Required permission: Credit Management. Billing mode: The organization must use the Credit billing mode. Returns 204 on success. After deactivation, the role's "quota required" setting stays on, so members of the role cannot use features that consume Credits until a new quota is set or the quota restriction is lifted. Deactivating an already deactivated quota returns 400.

Parameters

Parameter Name	Required	Type	Description
`groupPk`	V	string	
`id`	V	string	

`organizationPk`	V	string	A UUID string identifying this Organization ID

Code Examples

Shell/Bash

```
# API call example (Shell)
curl -X DELETE
"https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-41d4-
a716-446655440000/groups/{groupPk}/credit-quotas/550e8400-e29b-41d4-
a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# Make sure to replace YOUR_API_KEY and verify the request data
before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

// Request payload
const data = null;

axios.delete("https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-41d4-a716-446655440000/groups/{groupPk}/credit-quotas/550e8400-e29b-41d4-a716-446655440000/", data, config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request failed:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-
41d4-a716-446655440000/groups/{groupPk}/credit-quotas/550e8400-e29b-
41d4-a716-446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.delete(url, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request failed:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>delete("https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-
41d4-a716-446655440000/groups/{groupPk}/credit-quotas/550e8400-e29b-
41d4-a716-446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request failed: ' . $e->getMessage();
}
?>
```

Response Content

Status Code	Description
204	No response body

Set Whether a Role Requires a Quota

PATCH `/api/v1/organizations/{organizationPk}/credit-quota-groups/{id}/credit-quota-required/`

Required permission: Credit Management. Billing mode: The organization must use the Credit billing mode. The request body is {"creditQuotaRequired": true} or false, and the id in the path is the role ID. When set to false (lifting the quota restriction), the role's active quota is deactivated as well, and members use the organization wallet instead. When set to true, members of the role are blocked from using the service until a quota is set. The response shows the role's current quota status.

Parameters

Parameter Name	Required	Type	Description
`id`	V	string	A UUID string identifying this Group.
`organizationPk`	V	string	A UUID string identifying this Organization ID

Code Examples

Shell/Bash

```
# API call example (Shell)
curl -X PATCH
"https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-41d4-
a716-446655440000/credit-quota-groups/550e8400-e29b-41d4-a716-
446655440000/credit-quota-required/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{}'

# Make sure to replace YOUR_API_KEY and verify the request data
before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// Request payload
const data = {};

axios.patch("https://api.maiagent.ai/api/v1/organizations/550e8400-
e29b-41d4-a716-446655440000/credit-quota-groups/550e8400-e29b-41d4-
a716-446655440000/credit-quota-required/", data, config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request failed:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-
41d4-a716-446655440000/credit-quota-groups/550e8400-e29b-41d4-a716-
446655440000/credit-quota-required/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# Request payload
data = {}

response = requests.patch(url, json=data, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request failed:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>patch("https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-
41d4-a716-446655440000/credit-quota-groups/550e8400-e29b-41d4-a716-
446655440000/credit-quota-required/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => new \stdClass()
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request failed: ' . $e->getMessage();
}
?>
```

Response Content

Status code: 200

Example Response Structure

```
{
  "id": string (uuid)
  "name": string
  "type":
  {
  }
  "creditQuotaRequired": boolean // When True, this group must have an active credit quota for its members to consume credits
  "activeQuota": object // Return the most recent quota summary (active first), via prefetch to avoid N+1.
}
```

Example Response Values

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "name": "Response string",
  "type": {},
  "creditQuotaRequired": false,
  "activeQuota": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Response example name",
    "description": "Response example description"
  }
}
```

Retrieve Role Member Quota Statistics

`GET` `/api/v1/organizations/{organizationPk}/groups/{id}/credit-quota-stats/`

Required permissions: Credit management permissions. Billing mode: The organization must use Credit billing.

Parameters

Parameter Name	Required	Type	Description
`id`	V	string	A UUID string identifying this Group.
`organizationPk`	V	string	A UUID string identifying this organization ID

Code Examples

Shell/Bash

```
# API call example (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/organizations/550e8400-
e29b-41d4-a716-446655440000/groups/550e8400-e29b-41d4-a716-
446655440000/credit-quota-stats/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/organizations/550e8400-
e29b-41d4-a716-446655440000/groups/550e8400-e29b-41d4-a716-
446655440000/credit-quota-stats/", config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request failed:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-
41d4-a716-446655440000/groups/550e8400-e29b-41d4-a716-
446655440000/credit-quota-stats/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request failed:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-
41d4-a716-446655440000/groups/550e8400-e29b-41d4-a716-
446655440000/credit-quota-stats/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request failed: ' . $e->getMessage();
}
?>
```

Response Body

Status Code: 200

Response Schema Example

```
{
  "activeQuotaMembersCount": integer
```

```
  "quotaRequiredMembersCount": integer
}
```

Example Response Values

```
{
  "activeQuotaMembersCount": 456,
  "quotaRequiredMembersCount": 456
}
```

Distribute Quota in Bulk by Role

POST `/api/v1/organizations/{organizationPk}/groups/{id}/batch-distribute-credit-quota/`

Required permission: Credit management permission + Organization overview permission. Billing mode: The organization must be on Credit billing mode. Sets one member quota for each member in the role, with the same request body as Set a Member's Quota. Members who already have an active quota are skipped and are not modified. Response: successCount, skippedCount, skippedMemberIds, failedCount, failedMembers.

Parameters

Parameter Name	Required	Type	Description
`id`	V	string	A UUID string identifying this Group.
`organizationPk`	V	string	A UUID string identifying this Organization ID

Request

Request Parameters

Field	Type	Required	Description
name	string	Yes	
canCreateChatbot	boolean	No	
canCreateKnowledgeBase	boolean	No	
canCreateInbox	boolean	No	
canCreateDatabase	boolean	No	
canCreateTool	boolean	No	
canCreateAgentUiTool	boolean	No	
canCreateSkill	boolean	No	
maigptCanCodeInterpreter	boolean	No	Whether members of this role may use the code interpreter built-in tool in MaiGPT.
maigptCanRag	boolean	No	Whether members of this role may use the knowledge base RAG built-in tool in MaiGPT.
maigptCanDeepResearch	boolean	No	Whether members of this role may use Deep Research in MaiGPT. Deep Research reaches the public internet through its own built-in search, so a role that revokes the official web-search tools needs this...
maigptCanBrowserTool	boolean	No	Whether members of this role may use the browser built-in tool in MaiGPT.
maigptAllLlms	boolean	No	Whether members of this role may use every organization-available LLM in MaiGPT. Off = only the bound LLMs; an empty binding then means none.
maigptAllTools	boolean	No	Whether members of this role may call every official (global) tool in

Field	Type	Required	Description
			MaiGPT. Off = only the bound tools; an empty binding then means none.
maigptAllConnectors	boolean	No	Whether members of this role may call every official (global) MCP connector in MaiGPT. Off = only the bound connectors; an empty binding then means none.
maigptAllSkills	boolean	No	Whether members of this role may use every official (global) skill in MaiGPT. Off = only the bound skills; an empty binding then means none.
usageStatisticsScope	object	No	What this role's usage statistics permission shows: the whole organization, or only the AI assistants granted to the member's roles. A member with any organization-wide granting role sees the whole or...

Example Request Structure

```
{
  "name": string
  "canCreateChatbot"?: boolean // Optional
  "canCreateKnowledgeBase"?: boolean // Optional
  "canCreateInbox"?: boolean // Optional
  "canCreateDatabase"?: boolean // Optional
  "canCreateTool"?: boolean // Optional
  "canCreateAgentUiTool"?: boolean // Optional
  "canCreateSkill"?: boolean // Optional
  "maigptCanCodeInterpreter"?: boolean // Whether members of this role may use the code interpreter built-in tool in MaiGPT. (Optional)
  "maigptCanRag"?: boolean // Whether members of this role may use the knowledge base RAG built-in tool in MaiGPT. (Optional)
  "maigptCanDeepResearch"?: boolean // Whether members of this role may use Deep Research in MaiGPT. Deep Research reaches the public internet through its own built-in search, so a role that revokes the official web-search tools needs this switch too. (Optional)
```

```
  "maigptCanBrowserTool"?: boolean // Whether members of this role may
use the browser built-in tool in MaiGPT. (Optional)
  "maigptAllLlms"?: boolean // Whether members of this role may use every
organization-available LLM in MaiGPT. Off = only the bound LLMs; an empty
binding then means none. (Optional)
  "maigptAllTools"?: boolean // Whether members of this role may call
every official (global) tool in MaiGPT. Off = only the bound tools; an
empty binding then means none. (Optional)
  "maigptAllConnectors"?: boolean // Whether members of this role may
call every official (global) MCP connector in MaiGPT. Off = only the
bound connectors; an empty binding then means none. (Optional)
  "maigptAllSkills"?: boolean // Whether members of this role may use
every official (global) skill in MaiGPT. Off = only the bound skills; an
empty binding then means none. (Optional)
  "usageStatisticsScope"?:  // What this role's usage statistics
permission shows: the whole organization, or only the AI assistants
granted to the member's roles. A member with any organization-wide
granting role sees the whole organization.

* `organization` - Organization-wide
* `accessible_chatbots` - Authorized AI assistants only (Optional)
  {
  }
}
```

Example Request Values

```
{
  "name": "Example name",
  "canCreateChatbot": true,
  "canCreateKnowledgeBase": true,
  "canCreateInbox": true,
  "canCreateDatabase": true,
  "canCreateTool": true,
  "canCreateAgentUiTool": true,
  "canCreateSkill": true,
  "maigptCanCodeInterpreter": true,
  "maigptCanRag": true,
  "maigptCanDeepResearch": true,
  "maigptCanBrowserTool": true,
  "maigptAllLlms": true,
  "maigptAllTools": true,
  "maigptAllConnectors": true,
  "maigptAllSkills": true,
```

```
  "usageStatisticsScope": {}
}
```

Code Examples

Shell/Bash

```
# API call example (Shell)
curl -X POST "https://api.maiagent.ai/api/v1/organizations/550e8400-
e29b-41d4-a716-446655440000/groups/550e8400-e29b-41d4-a716-
446655440000/batch-distribute-credit-quota/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "name": "Example name",
    "canCreateChatbot": true,
    "canCreateKnowledgeBase": true,
    "canCreateInbox": true,
    "canCreateDatabase": true,
    "canCreateTool": true,
    "canCreateAgentUiTool": true,
    "canCreateSkill": true,
    "maigptCanCodeInterpreter": true,
    "maigptCanRag": true,
    "maigptCanDeepResearch": true,
    "maigptCanBrowserTool": true,
    "maigptAllLlms": true,
    "maigptAllTools": true,
    "maigptAllConnectors": true,
    "maigptAllSkills": true,
    "usageStatisticsScope": {}
  }'

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// Request payload
const data = {
    "name": "Example name",
    "canCreateChatbot": true,
    "canCreateKnowledgeBase": true,
    "canCreateInbox": true,
    "canCreateDatabase": true,
    "canCreateTool": true,
    "canCreateAgentUiTool": true,
    "canCreateSkill": true,
    "maigptCanCodeInterpreter": true,
    "maigptCanRag": true,
    "maigptCanDeepResearch": true,
    "maigptCanBrowserTool": true,
    "maigptAllLlms": true,
    "maigptAllTools": true,
    "maigptAllConnectors": true,
    "maigptAllSkills": true,
    "usageStatisticsScope": {}
  };

axios.post("https://api.maiagent.ai/api/v1/organizations/550e8400-
e29b-41d4-a716-446655440000/groups/550e8400-e29b-41d4-a716-
446655440000/batch-distribute-credit-quota/", data, config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('An error occurred while making the request:');
```

```
  console.error(error.response?.data || error.message);
});
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-
41d4-a716-446655440000/groups/550e8400-e29b-41d4-a716-
446655440000/batch-distribute-credit-quota/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# Request payload
data = {
    "name": "Example name",
    "canCreateChatbot": True,
    "canCreateKnowledgeBase": True,
    "canCreateInbox": True,
    "canCreateDatabase": True,
    "canCreateTool": True,
    "canCreateAgentUiTool": True,
    "canCreateSkill": True,
    "maigptCanCodeInterpreter": True,
    "maigptCanRag": True,
    "maigptCanDeepResearch": True,
    "maigptCanBrowserTool": True,
    "maigptAllLlms": True,
    "maigptAllTools": True,
    "maigptAllConnectors": True,
    "maigptAllSkills": True,
    "usageStatisticsScope": {}
}

response = requests.post(url, json=data, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("An error occurred while making the request:", e)
```

PHP

```
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>post("https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-
41d4-a716-446655440000/groups/550e8400-e29b-41d4-a716-
446655440000/batch-distribute-credit-quota/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'name' => 'Example name',
            'canCreateChatbot' => true,
            'canCreateKnowledgeBase' => true,
            'canCreateInbox' => true,
            'canCreateDatabase' => true,
            'canCreateTool' => true,
            'canCreateAgentUiTool' => true,
            'canCreateSkill' => true,
            'maigptCanCodeInterpreter' => true,
            'maigptCanRag' => true,
            'maigptCanDeepResearch' => true,
            'maigptCanBrowserTool' => true,
            'maigptAllLlms' => true,
            'maigptAllTools' => true,
            'maigptAllConnectors' => true,
            'maigptAllSkills' => true,
            'usageStatisticsScope' => new \stdClass()
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'An error occurred while making the request: ' . $e-
```

```
    >getMessage();
    }
    ?>
```

Response

Status code: 200

Example Response Structure

```
{
  "id": string (uuid)
  "name": string
  "type":
  {
  }
  "permissions": [
    object
  ]
  "membersPreview": [
    string
  ]
  "membersCount": integer // Returns the number of remaining members
(after subtracting the 3 shown in the list), used for the frontend +N
badge

Unlike resource counts:
<ul>
  <li>members_count: returns total - 3 (used for the +N badge); None
means the total is <= 3</li>
  <li>chatbots_count/knowledge_bases_count/inboxes_count: return the
total count</li>
</ul>
  "chatbotsCount": integer
  "chatbotsPreview": [
    string
  ]
```

```
  "knowledgeBasesCount": integer
  "knowledgeBasesPreview": [
    string
  ]
  "inboxesCount": integer
  "inboxesPreview": [
    string
  ]
  "databasesCount": integer
  "databasesPreview": [
    string
  ]
  "canCreateChatbot"?: boolean // Optional
  "canCreateKnowledgeBase"?: boolean // Optional
  "canCreateInbox"?: boolean // Optional
  "canCreateDatabase"?: boolean // Optional
  "canCreateTool"?: boolean // Optional
  "canCreateAgentUiTool"?: boolean // Optional
  "canCreateSkill"?: boolean // Optional
  "maigptCanCodeInterpreter"?: boolean // Whether members of this role
may use the code interpreter built-in tool in MaiGPT. (Optional)
  "maigptCanRag"?: boolean // Whether members of this role may use the
knowledge base RAG built-in tool in MaiGPT. (Optional)
  "maigptCanDeepResearch"?: boolean // Whether members of this role may
use Deep Research in MaiGPT. Deep Research reaches the public internet
through its own built-in search, so a role that revokes the official web-
search tools needs this switch too. (Optional)
  "maigptCanBrowserTool"?: boolean // Whether members of this role may
use the browser built-in tool in MaiGPT. (Optional)
  "maigptAllLlms"?: boolean // Whether members of this role may use every
organization-available LLM in MaiGPT. Off = only the bound LLMs; an empty
binding then means none. (Optional)
  "maigptAllTools"?: boolean // Whether members of this role may call
every official (global) tool in MaiGPT. Off = only the bound tools; an
empty binding then means none. (Optional)
  "maigptAllConnectors"?: boolean // Whether members of this role may
call every official (global) MCP connector in MaiGPT. Off = only the
bound connectors; an empty binding then means none. (Optional)
  "maigptAllSkills"?: boolean // Whether members of this role may use
every official (global) skill in MaiGPT. Off = only the bound skills; an
empty binding then means none. (Optional)
  "usageStatisticsScope"?:  // What this role's usage statistics
permission shows: the whole organization, or only the AI assistants
granted to the member's roles. A member with any organization-wide
granting role sees the whole organization.
```

```
* `organization` - Organization-wide
* `accessible_chatbots` - Authorized AI assistants only (Optional)
  {
  }
  "createdAt": string (timestamp)
}
```

Example Response Values

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "name": "Response string",
  "type": {},
  "permissions": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "Example response name",
      "description": "Example response description"
    }
  ],
  "membersPreview": [
    "Response string"
  ],
  "membersCount": 456,
  "chatbotsCount": 456,
  "chatbotsPreview": [
    "Response string"
  ],
  "knowledgeBasesCount": 456,
  "knowledgeBasesPreview": [
    "Response string"
  ],
  "inboxesCount": 456,
  "inboxesPreview": [
    "Response string"
  ],
  "databasesCount": 456,
  "databasesPreview": [
    "Response string"
  ],
  "canCreateChatbot": false,
  "canCreateKnowledgeBase": false,
  "canCreateInbox": false,
```

```
  "canCreateDatabase": false,
  "canCreateTool": false,
  "canCreateAgentUiTool": false,
  "canCreateSkill": false,
  "maigptCanCodeInterpreter": false,
  "maigptCanRag": false,
  "maigptCanDeepResearch": false,
  "maigptCanBrowserTool": false,
  "maigptAllLlms": false,
  "maigptAllTools": false,
  "maigptAllConnectors": false,
  "maigptAllSkills": false,
  "usageStatisticsScope": {},
  "createdAt": "Response string"
}
```


Deactivate Quota in Bulk by Role

POST `/api/v1/organizations/{organizationPk}/groups/{id}/batch-deactivate-credit-quota/`

Required permission: Credit management permission + Organization overview permission. Billing mode: The organization must be on Credit billing mode. Deactivates the active member quotas of all members in the role (not the role's own quota); members without an active quota are counted as skipped. The request body field removeQuotaRequirement is optional and defaults to false: only the quota is deactivated, and the member's "quota required" setting stays on, so the member cannot use the service until a quota is reassigned. When set to true, the quota requirement is also removed for all members in the role, and they use the organization wallet instead. Response: successCount, skippedCount, skippedMemberIds, failedCount, failedMembers, requirementRemovedCount. Before running, use Query Role Member Quota Statistics to confirm how many members will be affected.

Parameters

Parameter Name	Required	Type	Description
`id`	V	string	A UUID string identifying this Group.

`organizationPk`	V	string	A UUID string identifying this Organization ID

Request

Request Parameters

Field	Type	Required	Description
name	string	Yes	
canCreateChatbot	boolean	No	
canCreateKnowledgeBase	boolean	No	
canCreateInbox	boolean	No	
canCreateDatabase	boolean	No	
canCreateTool	boolean	No	
canCreateAgentUiTool	boolean	No	
canCreateSkill	boolean	No	
maigptCanCodeInterpreter	boolean	No	Whether members of this role may use the code interpreter built-in tool in MaiGPT.
maigptCanRag	boolean	No	Whether members of this role may use the knowledge base RAG built-in tool in MaiGPT.
maigptCanDeepResearch	boolean	No	Whether members of this role may use Deep Research in MaiGPT. Deep Research reaches the public internet through its own built-in search, so a role that revokes the official web-search tools needs this...
maigptCanBrowserTool	boolean	No	Whether members of this role may use the browser built-in tool in MaiGPT.

Field	Type	Required	Description
maigptAllLlms	boolean	No	Whether members of this role may use every organization-available LLM in MaiGPT. Off = only the bound LLMs; an empty binding then means none.
maigptAllTools	boolean	No	Whether members of this role may call every official (global) tool in MaiGPT. Off = only the bound tools; an empty binding then means none.
maigptAllConnectors	boolean	No	Whether members of this role may call every official (global) MCP connector in MaiGPT. Off = only the bound connectors; an empty binding then means none.
maigptAllSkills	boolean	No	Whether members of this role may use every official (global) skill in MaiGPT. Off = only the bound skills; an empty binding then means none.
usageStatisticsScope	object	No	What this role's usage statistics permission shows: the whole organization, or only the AI assistants granted to the member's roles. A member with any organization-wide granting role sees the whole or...

Example Request Structure

```
{
  "name": string
  "canCreateChatbot"?: boolean // Optional
  "canCreateKnowledgeBase"?: boolean // Optional
  "canCreateInbox"?: boolean // Optional
  "canCreateDatabase"?: boolean // Optional
  "canCreateTool"?: boolean // Optional
  "canCreateAgentUiTool"?: boolean // Optional
  "canCreateSkill"?: boolean // Optional
```

```
  "maigptCanCodeInterpreter"?: boolean // Whether members of this role
may use the code interpreter built-in tool in MaiGPT. (Optional)
  "maigptCanRag"?: boolean // Whether members of this role may use the
knowledge base RAG built-in tool in MaiGPT. (Optional)
  "maigptCanDeepResearch"?: boolean // Whether members of this role may
use Deep Research in MaiGPT. Deep Research reaches the public internet
through its own built-in search, so a role that revokes the official web-
search tools needs this switch too. (Optional)
  "maigptCanBrowserTool"?: boolean // Whether members of this role may
use the browser built-in tool in MaiGPT. (Optional)
  "maigptAllLlms"?: boolean // Whether members of this role may use every
organization-available LLM in MaiGPT. Off = only the bound LLMs; an empty
binding then means none. (Optional)
  "maigptAllTools"?: boolean // Whether members of this role may call
every official (global) tool in MaiGPT. Off = only the bound tools; an
empty binding then means none. (Optional)
  "maigptAllConnectors"?: boolean // Whether members of this role may
call every official (global) MCP connector in MaiGPT. Off = only the
bound connectors; an empty binding then means none. (Optional)
  "maigptAllSkills"?: boolean // Whether members of this role may use
every official (global) skill in MaiGPT. Off = only the bound skills; an
empty binding then means none. (Optional)
  "usageStatisticsScope"?:  // What this role's usage statistics
permission shows: the whole organization, or only the AI assistants
granted to the member's roles. A member with any organization-wide
granting role sees the whole organization.

* `organization` - Organization-wide
* `accessible_chatbots` - Authorized AI assistants only (Optional)
  {
  }
}
```

Example Request Values

```
{
  "name": "Example name",
  "canCreateChatbot": true,
  "canCreateKnowledgeBase": true,
  "canCreateInbox": true,
  "canCreateDatabase": true,
  "canCreateTool": true,
  "canCreateAgentUiTool": true,
  "canCreateSkill": true,
```

```
  "maigptCanCodeInterpreter": true,
  "maigptCanRag": true,
  "maigptCanDeepResearch": true,
  "maigptCanBrowserTool": true,
  "maigptAllLlms": true,
  "maigptAllTools": true,
  "maigptAllConnectors": true,
  "maigptAllSkills": true,
  "usageStatisticsScope": {}
}
```


Code Examples

Shell/Bash

```
# API call example (Shell)
curl -X POST "https://api.maiagent.ai/api/v1/organizations/550e8400-
e29b-41d4-a716-446655440000/groups/550e8400-e29b-41d4-a716-
446655440000/batch-deactivate-credit-quota/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "name": "Example name",
    "canCreateChatbot": true,
    "canCreateKnowledgeBase": true,
    "canCreateInbox": true,
    "canCreateDatabase": true,
    "canCreateTool": true,
    "canCreateAgentUiTool": true,
    "canCreateSkill": true,
    "maigptCanCodeInterpreter": true,
    "maigptCanRag": true,
    "maigptCanDeepResearch": true,
    "maigptCanBrowserTool": true,
    "maigptAllLlms": true,
    "maigptAllTools": true,
    "maigptAllConnectors": true,
    "maigptAllSkills": true,
    "usageStatisticsScope": {}
  }'

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// Request payload
const data = {
    "name": "Example name",
    "canCreateChatbot": true,
    "canCreateKnowledgeBase": true,
    "canCreateInbox": true,
    "canCreateDatabase": true,
    "canCreateTool": true,
    "canCreateAgentUiTool": true,
    "canCreateSkill": true,
    "maigptCanCodeInterpreter": true,
    "maigptCanRag": true,
    "maigptCanDeepResearch": true,
    "maigptCanBrowserTool": true,
    "maigptAllLlms": true,
    "maigptAllTools": true,
    "maigptAllConnectors": true,
    "maigptAllSkills": true,
    "usageStatisticsScope": {}
  };

axios.post("https://api.maiagent.ai/api/v1/organizations/550e8400-
e29b-41d4-a716-446655440000/groups/550e8400-e29b-41d4-a716-
446655440000/batch-deactivate-credit-quota/", data, config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('An error occurred while making the request:');
```

```
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-
41d4-a716-446655440000/groups/550e8400-e29b-41d4-a716-
446655440000/batch-deactivate-credit-quota/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# Request payload
data = {
    "name": "Example name",
    "canCreateChatbot": True,
    "canCreateKnowledgeBase": True,
    "canCreateInbox": True,
    "canCreateDatabase": True,
    "canCreateTool": True,
    "canCreateAgentUiTool": True,
    "canCreateSkill": True,
    "maigptCanCodeInterpreter": True,
    "maigptCanRag": True,
    "maigptCanDeepResearch": True,
    "maigptCanBrowserTool": True,
    "maigptAllLlms": True,
    "maigptAllTools": True,
    "maigptAllConnectors": True,
    "maigptAllSkills": True,
    "usageStatisticsScope": {}
}

response = requests.post(url, json=data, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("An error occurred with the request:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>post("https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-
41d4-a716-446655440000/groups/550e8400-e29b-41d4-a716-
446655440000/batch-deactivate-credit-quota/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'name' => 'Example name',
            'canCreateChatbot' => true,
            'canCreateKnowledgeBase' => true,
            'canCreateInbox' => true,
            'canCreateDatabase' => true,
            'canCreateTool' => true,
            'canCreateAgentUiTool' => true,
            'canCreateSkill' => true,
            'maigptCanCodeInterpreter' => true,
            'maigptCanRag' => true,
            'maigptCanDeepResearch' => true,
            'maigptCanBrowserTool' => true,
            'maigptAllLlms' => true,
            'maigptAllTools' => true,
            'maigptAllConnectors' => true,
            'maigptAllSkills' => true,
            'usageStatisticsScope' => new \stdClass()
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'An error occurred with the request: ' . $e->getMessage();
```

```
}
?>
```

Response Content

Status Code: 200

Example Response Structure

```
{
  "id": string (uuid)
  "name": string
  "type":
  {
  }
  "permissions": [
    object
  ]
  "membersPreview": [
    string
  ]
  "membersCount": integer // Returns the remaining number of members
(after subtracting the 3 shown in the list), used for the +N badge in the
frontend

Unlike the resource counts:
<ul>
  <li>members_count: returns total - 3 (used for the +N badge); None
means the total is <= 3</li>
  <li>chatbots_count/knowledge_bases_count/inboxes_count: return the
total count</li>
</ul>
  "chatbotsCount": integer
  "chatbotsPreview": [
    string
  ]
  "knowledgeBasesCount": integer
```

```
  "knowledgeBasesPreview": [
    string
  ]
  "inboxesCount": integer
  "inboxesPreview": [
    string
  ]
  "databasesCount": integer
  "databasesPreview": [
    string
  ]
  "canCreateChatbot"?: boolean // Optional
  "canCreateKnowledgeBase"?: boolean // Optional
  "canCreateInbox"?: boolean // Optional
  "canCreateDatabase"?: boolean // Optional
  "canCreateTool"?: boolean // Optional
  "canCreateAgentUiTool"?: boolean // Optional
  "canCreateSkill"?: boolean // Optional
  "maigptCanCodeInterpreter"?: boolean // Whether members of this role
may use the code interpreter built-in tool in MaiGPT. (Optional)
  "maigptCanRag"?: boolean // Whether members of this role may use the
knowledge base RAG built-in tool in MaiGPT. (Optional)
  "maigptCanDeepResearch"?: boolean // Whether members of this role may
use Deep Research in MaiGPT. Deep Research reaches the public internet
through its own built-in search, so a role that revokes the official web-
search tools needs this switch too. (Optional)
  "maigptCanBrowserTool"?: boolean // Whether members of this role may
use the browser built-in tool in MaiGPT. (Optional)
  "maigptAllLlms"?: boolean // Whether members of this role may use every
organization-available LLM in MaiGPT. Off = only the bound LLMs; an empty
binding then means none. (Optional)
  "maigptAllTools"?: boolean // Whether members of this role may call
every official (global) tool in MaiGPT. Off = only the bound tools; an
empty binding then means none. (Optional)
  "maigptAllConnectors"?: boolean // Whether members of this role may
call every official (global) MCP connector in MaiGPT. Off = only the
bound connectors; an empty binding then means none. (Optional)
  "maigptAllSkills"?: boolean // Whether members of this role may use
every official (global) skill in MaiGPT. Off = only the bound skills; an
empty binding then means none. (Optional)
  "usageStatisticsScope"?:  // What this role's usage statistics
permission shows: the whole organization, or only the AI assistants
granted to the member's roles. A member with any organization-wide
granting role sees the whole organization.
```

```
* `organization` - Organization-wide
* `accessible_chatbots` - Authorized AI assistants only (Optional)
  {
  }
  "createdAt": string (timestamp)
}
```

Example Response Values

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "name": "Response string",
  "type": {},
  "permissions": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "Example response name",
      "description": "Example response description"
    }
  ],
  "membersPreview": [
    "Response string"
  ],
  "membersCount": 456,
  "chatbotsCount": 456,
  "chatbotsPreview": [
    "Response string"
  ],
  "knowledgeBasesCount": 456,
  "knowledgeBasesPreview": [
    "Response string"
  ],
  "inboxesCount": 456,
  "inboxesPreview": [
    "Response string"
  ],
  "databasesCount": 456,
  "databasesPreview": [
    "Response string"
  ],
  "canCreateChatbot": false,
  "canCreateKnowledgeBase": false,
  "canCreateInbox": false,
  "canCreateDatabase": false,
```

```
  "canCreateTool": false,
  "canCreateAgentUiTool": false,
  "canCreateSkill": false,
  "maigptCanCodeInterpreter": false,
  "maigptCanRag": false,
  "maigptCanDeepResearch": false,
  "maigptCanBrowserTool": false,
  "maigptAllLlms": false,
  "maigptAllTools": false,
  "maigptAllConnectors": false,
  "maigptAllSkills": false,
  "usageStatisticsScope": {},
  "createdAt": "Response string"
}
```


List Inbox Quota Settings

GET `/api/v1/inboxes/{inboxPk}/credit-quotas/`

Required permissions: Credit management permissions. Billing mode: The organization must use Credit billing. Includes deactivated quotas, sorted from newest to oldest.

Parameters

Parameter Name	Required	Type	Description
`inboxPk`	V	string	
`page`	X	integer	A page number within the paginated result set.
`pageSize`	X	integer	Number of results to return per page.

Code Examples

Shell/Bash

```
# API call example (Shell)
curl -X GET
"https://api.maiagent.ai/api/v1/inboxes/{inboxPk}/credit-quotas/?
page=1&pageSize=1"

  -H "Authorization: Api-Key YOUR_API_KEY"

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/inboxes/{inboxPk}/credit-quotas/?page=1&pageSize=1", config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('An error occurred with the request:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/inboxes/{inboxPk}/credit-
quotas/?page=1&pageSize=1"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("An error occurred with the request:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/inboxes/{inboxPk}/credit-
quotas/?page=1&pageSize=1", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'An error occurred with the request: ' . $e->getMessage();
}
?>
```

Response Content

Status Code: 200

Example Response Structure

```
{
  "count": integer
  "next"?: string (uri) // Optional
```

```
  "previous"?: string (uri) // Optional
  "results": [
    {
      "id": string (uuid)
      "inbox": object
      "quotaLimit": string (decimal) // Maximum credits this inbox may
consume
      "consumedAmount": string (decimal) // Credits consumed so far
(updated via F() for concurrency safety)
      "remaining": string (decimal)
      "validFrom": string (timestamp)
      "validUntil": string (timestamp) // NULL means permanent
      "resetPeriod":  // Cycle on which consumed_amount is automatically
zeroed; "none" keeps the one-shot ceiling

* `none` - No Reset
* `daily` - Daily
* `weekly` - Weekly
* `monthly` - Monthly
      {
      }
      "nextResetAt": string (timestamp) // Local-midnight boundary of the
next automatic reset; NULL when reset_period is "none"
      "isActive": boolean
      "expiredAt": string (timestamp) // Actual deactivation time (cron
or manual)
      "createdBy": object
      "note": string
      "createdAt": string (timestamp)
      "updatedAt": string (timestamp)
    }
  ]
}
```

Example Response Values

```
{
  "count": 123,
  "next": "http://api.example.org/accounts/?page=4",
  "previous": "http://api.example.org/accounts/?page=2",
  "results": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "inbox": {
```

```
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "name": "Example response name",
        "description": "Example response description"
      },
      "quotaLimit": "Response string",
      "consumedAmount": "Response string",
      "remaining": "Response string",
      "validFrom": "Response string",
      "validUntil": "Response string",
      "resetPeriod": {},
      "nextResetAt": "Response string",
      "isActive": false,
      "expiredAt": "Response string",
      "createdBy": {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "name": "Example response name",
        "description": "Example response description"
      },
      "note": "Response string",
      "createdAt": "Response string",
      "updatedAt": "Response string"
    }
  ]
}
```


Retrieve an Inbox Quota Setting

`GET` `/api/v1/inboxes/{inboxPk}/credit-quotas/{id}`

Required permissions: Credit management permissions. Billing mode: The organization must use Credit billing.

Parameters

Parameter Name	Required	Type	Description

`id`	V	string	
`inboxPk`	V	string	

Code Examples

Shell/Bash

```
# API call example (Shell)
curl -X GET
"https://api.maiagent.ai/api/v1/inboxes/{inboxPk}/credit-
quotas/550e8400-e29b-41d4-a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/inboxes/{inboxPk}/credit-quotas/550e8400-e29b-41d4-a716-446655440000/", config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('An error occurred with the request:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/inboxes/{inboxPk}/credit-
quotas/550e8400-e29b-41d4-a716-446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("An error occurred with the request:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/inboxes/{inboxPk}/credit-
quotas/550e8400-e29b-41d4-a716-446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'An error occurred with the request: ' . $e->getMessage();
}
?>
```

Response Content

Status Code: 200

Example Response Structure

```
{
  "id": string (uuid)
  "inbox": object
```

```
  "quotaLimit": string (decimal) // Maximum credits this inbox may
consume
  "consumedAmount": string (decimal) // Credits consumed so far (updated
via F() for concurrency safety)
  "remaining": string (decimal)
  "validFrom": string (timestamp)
  "validUntil": string (timestamp) // NULL means permanent
  "resetPeriod":  // Cycle on which consumed_amount is automatically
zeroed; "none" keeps the one-shot ceiling

* `none` - No Reset
* `daily` - Daily
* `weekly` - Weekly
* `monthly` - Monthly
  {
  }
  "nextResetAt": string (timestamp) // Local-midnight boundary of the
next automatic reset; NULL when reset_period is "none"
  "isActive": boolean
  "expiredAt": string (timestamp) // Actual deactivation time (cron or
manual)
  "createdBy": object
  "note": string
  "createdAt": string (timestamp)
  "updatedAt": string (timestamp)
}
```

Example Response Values


```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "inbox": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Example response name",
    "description": "Example response description"
  },
  "quotaLimit": "Response string",
  "consumedAmount": "Response string",
  "remaining": "Response string",
  "validFrom": "Response string",
  "validUntil": "Response string",
  "resetPeriod": {},
  "nextResetAt": "Response string",
  "isActive": false,
```

```
  "expiredAt": "Response string",
  "createdBy": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Example response name",
    "description": "Example response description"
  },
  "note": "Response string",
  "createdAt": "Response string",
  "updatedAt": "Response string"
}
```


Set an inbox credit quota

POST `/api/v1/inboxes/{inboxPk}/credit-quotas/`

Required permission: Credit management permission. Billing mode: The organization must use Credit billing. See How quotas work for request details and rules. If the inbox already has an active quota, the API returns 400; deactivate that quota first. Quotas cannot be set for MaiGPT inboxes; the API returns 400.

Parameters

Parameter name	Required	Type	Description
`inboxPk`	V	string	

Request body

Request parameters

Field	Type	Required	Description
quotaLimit	string (decimal)	Yes	
validFrom	string (date-time)	Yes	
validUntil	string (date-time)	No	
note	string	No	
resetPeriod	object	No	

Example request schema

```
{
  "quotaLimit": string (decimal)
  "validFrom": string (date-time)
  "validUntil"?: string (date-time) // Optional
  "note"?: string // Optional
  "resetPeriod"?:  // Optional
  {
  }
}
```

Example request values

```
{
  "quotaLimit": "500",
  "validFrom": "2026-10-16T00:00:00+08:00",
  "validUntil": "2026-12-31T23:59:59+08:00",
  "resetPeriod": "monthly",
  "note": "Q4 budget"
}
```

Code examples

Shell/Bash

```
# API call example (Shell)
curl -X POST
"https://api.maiagent.ai/api/v1/inboxes/{inboxPk}/credit-quotas/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "quotaLimit": "500",
    "validFrom": "2026-10-16T00:00:00+08:00",
    "validUntil": "2026-12-31T23:59:59+08:00",
    "resetPeriod": "monthly",
    "note": "Q4 budget"
  }'

# Replace YOUR_API_KEY and verify the request data before running
this example.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// Request body (payload)
const data = {
    "quotaLimit": "500",
    "validFrom": "2026-10-16T00:00:00+08:00",
    "validUntil": "2026-12-31T23:59:59+08:00",
    "resetPeriod": "monthly",
    "note": "Q4 budget"
  };

axios.post("https://api.maiagent.ai/api/v1/inboxes/{inboxPk}/credit-quotas/", data, config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/inboxes/{inboxPk}/credit-
quotas/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# Request body (payload)
data = {
    "quotaLimit": "500",
    "validFrom": "2026-10-16T00:00:00+08:00",
    "validUntil": "2026-12-31T23:59:59+08:00",
    "resetPeriod": "monthly",
    "note": "Q4 budget"
}

response = requests.post(url, json=data, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>post("https://api.maiagent.ai/api/v1/inboxes/{inboxPk}/credit-
quotas/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'quotaLimit' => '500',
            'validFrom' => '2026-10-16T00:00:00+08:00',
            'validUntil' => '2026-12-31T23:59:59+08:00',
            'resetPeriod' => 'monthly',
            'note' => 'Q4 budget'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response body

Status code: 201

Example response schema

```
{
  "id": string (uuid)
  "inbox": object
  "quotaLimit": string (decimal) // Maximum credits this inbox may
consume
  "consumedAmount": string (decimal) // Credits consumed so far (updated
via F() for concurrency safety)
  "remaining": string (decimal)
  "validFrom": string (timestamp)
  "validUntil": string (timestamp) // NULL means permanent
  "resetPeriod":  // Cycle on which consumed_amount is automatically
zeroed; "none" keeps the one-shot ceiling

* `none` - No Reset
* `daily` - Daily
* `weekly` - Weekly
* `monthly` - Monthly
  {
  }
  "nextResetAt": string (timestamp) // Local-midnight boundary of the
next automatic reset; NULL when reset_period is "none"
  "isActive": boolean
  "expiredAt": string (timestamp) // Actual deactivation time (cron or
manual)
  "createdBy": object
  "note": string
  "createdAt": string (timestamp)
  "updatedAt": string (timestamp)
}
```

Example response values

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "inbox": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Example response name",
    "description": "Example response description"
  },
```

```
  "quotaLimit": "Response string",
  "consumedAmount": "Response string",
  "remaining": "Response string",
  "validFrom": "Response string",
  "validUntil": "Response string",
  "resetPeriod": {},
  "nextResetAt": "Response string",
  "isActive": false,
  "expiredAt": "Response string",
  "createdBy": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Example response name",
    "description": "Example response description"
  },
  "note": "Response string",
  "createdAt": "Response string",
  "updatedAt": "Response string"
}
```


Update an inbox credit quota

PATCH `/api/v1/inboxes/{inboxPk}/credit-quotas/{id}`

Required permission: Credit management permission. Billing mode: The organization must use Credit billing. Send only the fields you want to change: quotaLimit, validUntil, resetPeriod, and note (the start time cannot be changed). quotaLimit must not be less than the credits already consumed. Deactivated quotas cannot be updated; the API returns 400.

Parameters

Parameter name	Required	Type	Description
`id`	V	string	

`inboxPk`	V	string

Request body

Request parameters

Field	Type	Required	Description
quotaLimit	string (decimal)	No	
validUntil	string (date-time)	No	
note	string	No	
resetPeriod	string (enum: none, daily, weekly, monthly)	No	`none` : No Reset ; `daily` : Daily ; `weekly` : Weekly ; `monthly` : Monthly;

Example request schema

```
{
  "quotaLimit"?: string (decimal) // Optional
  "validUntil"?: string (date-time) // Optional
  "note"?: string // Optional
  "resetPeriod"?: string (enum: none, daily, weekly, monthly) // * `none`
- No Reset
* `daily` - Daily
* `weekly` - Weekly
* `monthly` - Monthly (Optional)
}
```

Example request values

```
{
  "quotaLimit": "Example string",
  "validUntil": "2025-01-01T00:00:00.000Z",
  "note": "Example string",
```

```
  "resetPeriod": "none"
}
```

Code examples

Shell/Bash

```
# API call example (Shell)
curl -X PATCH
"https://api.maiagent.ai/api/v1/inboxes/{inboxPk}/credit-
quotas/550e8400-e29b-41d4-a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "quotaLimit": "Example string",
    "validUntil": "2025-01-01T00:00:00.000Z",
    "note": "Example string",
    "resetPeriod": "none"
  }'

# Replace YOUR_API_KEY and verify the request data before running
this example.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// Request body (payload)
const data = {
    "quotaLimit": "Example string",
    "validUntil": "2025-01-01T00:00:00.000Z",
    "note": "Example string",
    "resetPeriod": "none"
  };

axios.patch("https://api.maiagent.ai/api/v1/inboxes/{inboxPk}/credit
-quotas/550e8400-e29b-41d4-a716-446655440000/", data, config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/inboxes/{inboxPk}/credit-
quotas/550e8400-e29b-41d4-a716-446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# Request body (payload)
data = {
    "quotaLimit": "Example string",
    "validUntil": "2025-01-01T00:00:00.000Z",
    "note": "Example string",
    "resetPeriod": "none"
}

response = requests.patch(url, json=data, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>patch("https://api.maiagent.ai/api/v1/inboxes/{inboxPk}/credit-
quotas/550e8400-e29b-41d4-a716-446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'quotaLimit' => 'Example string',
            'validUntil' => '2025-01-01T00:00:00.000Z',
            'note' => 'Example string',
            'resetPeriod' => 'none'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response body

Status code: 200

Example response schema

```
{
  "id": string (uuid)
  "inbox": object
  "quotaLimit": string (decimal) // Maximum credits this inbox may
consume
  "consumedAmount": string (decimal) // Credits consumed so far (updated
via F() for concurrency safety)
  "remaining": string (decimal)
  "validFrom": string (timestamp)
  "validUntil": string (timestamp) // NULL means permanent
  "resetPeriod":  // Cycle on which consumed_amount is automatically
zeroed; "none" keeps the one-shot ceiling

* `none` - No Reset
* `daily` - Daily
* `weekly` - Weekly
* `monthly` - Monthly
  {
  }
  "nextResetAt": string (timestamp) // Local-midnight boundary of the
next automatic reset; NULL when reset_period is "none"
  "isActive": boolean
  "expiredAt": string (timestamp) // Actual deactivation time (cron or
manual)
  "createdBy": object
  "note": string
  "createdAt": string (timestamp)
  "updatedAt": string (timestamp)
}
```

Example response values

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "inbox": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Example response name",
    "description": "Example response description"
  },
  "quotaLimit": "Response string",
  "consumedAmount": "Response string",
```

```
  "remaining": "Response string",
  "validFrom": "Response string",
  "validUntil": "Response string",
  "resetPeriod": {},
  "nextResetAt": "Response string",
  "isActive": false,
  "expiredAt": "Response string",
  "createdBy": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Example response name",
    "description": "Example response description"
  },
  "note": "Response string",
  "createdAt": "Response string",
  "updatedAt": "Response string"
}
```


Disable an Inbox's Credit Quota

DELETE `/api/v1/inboxes/{inboxPk}/credit-quotas/{id}`

Required permission: Credit management permission. Billing mode: The organization must use the Credit billing mode. Returns 204 on success. After deactivation, the inbox's "Requires quota" setting remains on, and AI replies stay paused until a new quota is set or the quota restriction is lifted. Deactivating an already deactivated quota returns 400.

Parameters

Parameter Name	Required	Type	Description
`id`	V	string	
`inboxPk`	V	string	

Code Examples

Shell/Bash

```
# Example API call (Shell)
curl -X DELETE
"https://api.maiagent.ai/api/v1/inboxes/{inboxPk}/credit-
quotas/550e8400-e29b-41d4-a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

// Request payload
const data = null;

axios.delete("https://api.maiagent.ai/api/v1/inboxes/{inboxPk}/credi
t-quotas/550e8400-e29b-41d4-a716-446655440000/", data, config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/inboxes/{inboxPk}/credit-
quotas/550e8400-e29b-41d4-a716-446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.delete(url, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>delete("https://api.maiagent.ai/api/v1/inboxes/{inboxPk}/credit-
quotas/550e8400-e29b-41d4-a716-446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response Content

Status code	Description
204	No response body

Set Whether an Inbox Requires a Credit Quota

`PATCH` `/api/v1/organizations/{organizationPk}/credit-quota-inboxes/{id}/credit-quota-required/`

Required permission: Credit management permission. Billing mode: The organization must use the Credit billing mode. The request body is {"creditQuotaRequired": true} or false, and the id in the path is the inbox ID. When set to false (quota restriction lifted), the active quota is deactivated as well, and AI replies use the organization wallet instead. When set to true, the inbox pauses AI replies until a quota is set. The response shows the inbox's current quota status.

Parameters

Parameter Name	Required	Type	Description
`id`	V	string	
`organizationPk`	V	string	A UUID string identifying this organization ID.

Code Examples

Shell/Bash

```
# Example API call (Shell)
curl -X PATCH
"https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-41d4-
a716-446655440000/credit-quota-inboxes/550e8400-e29b-41d4-a716-
446655440000/credit-quota-required/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{}'

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// Request payload
const data = {};

axios.patch("https://api.maiagent.ai/api/v1/organizations/550e8400-
e29b-41d4-a716-446655440000/credit-quota-inboxes/550e8400-e29b-41d4-
a716-446655440000/credit-quota-required/", data, config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-
41d4-a716-446655440000/credit-quota-inboxes/550e8400-e29b-41d4-a716-
446655440000/credit-quota-required/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# Request payload
data = {}

response = requests.patch(url, json=data, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>patch("https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-
41d4-a716-446655440000/credit-quota-inboxes/550e8400-e29b-41d4-a716-
446655440000/credit-quota-required/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => new \stdClass()
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response Content

Status code: 200

Example Response Structure

```
{
  "id": string (uuid)
  "name": string
  "channelType":
  {
  }
  "channelTypeLabel": string
  "webChatAccessType": string // Sub-type for web channels (web = public
embed, admin = internal Q&A, api = completions).

A chatbot ships with three same-named web inboxes, so the frontend needs
this to tell them apart. None for non-web channels. Reads the prefetched
generic ``channel`` relation (no extra query on the list path).
  "chatbot": object
  "creditQuotaRequired": boolean // When True, this inbox must have an
active credit quota for the AI to reply
  "activeQuota": object // Return the most recent quota summary (active
first), via prefetch to avoid N+1.
  "canUpdate": boolean // Return whether the current user can update this
resource.
}
```

Response Example Values

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "name": "Response string",
  "channelType": {},
  "channelTypeLabel": "Response string",
  "webChatAccessType": "Response string",
  "chatbot": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Sample response name",
    "description": "Sample response description"
  },
  "creditQuotaRequired": false,
  "activeQuota": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Sample response name",
    "description": "Sample response description"
  },
```

```
  "canUpdate": false
}
```

Query your own quota

GET `/api/v1/organizations/{organizationPk}/me/credit-quota/`

Required permissions: No additional permissions are required. Any organization member can query their own quota. Billing mode: The organization must use Credit billing.

Parameters

Parameter name	Required	Type	Description
`organizationPk`	V	string	A UUID string identifying this organization ID

Code examples

Shell/Bash

```
# API call example (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/organizations/550e8400-
e29b-41d4-a716-446655440000/me/credit-quota/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# Before running, replace YOUR_API_KEY and verify the request data.
```

JavaScript

```
const axios = require('axios');

// Configure request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/organizations/550e8400-
e29b-41d4-a716-446655440000/me/credit-quota/", config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-
41d4-a716-446655440000/me/credit-quota/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-
41d4-a716-446655440000/me/credit-quota/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response body

Status code	Description
200	No response body

Query the quotas of your roles

GET `/api/v1/organizations/{organizationPk}/me/group-credit-quotas/`

Required permissions: No additional permissions are required. Any organization member can query their own quota. Billing mode: The organization must use Credit billing.

Parameters

Parameter name	Required	Type	Description
`organizationPk`	V	string	A UUID string identifying this organization ID

Code examples

Shell/Bash

```
# API call example (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/organizations/550e8400-
e29b-41d4-a716-446655440000/me/group-credit-quotas/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# Before running, replace YOUR_API_KEY and verify the request data.
```

JavaScript

```
const axios = require('axios');

// Configure request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/organizations/550e8400-
e29b-41d4-a716-446655440000/me/group-credit-quotas/", config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-
41d4-a716-446655440000/me/group-credit-quotas/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-
41d4-a716-446655440000/me/group-credit-quotas/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response body

Status code	Description
200	No response body

List pricing rules

`GET` `/api/v1/credit/pricing-rules/`

No authentication required: This endpoint can be called without an API Key. Rate limit: 60 requests per minute per source IP. Exceeding the limit returns HTTP 429.

Code examples

Shell/Bash

```
# API call example (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/credit/pricing-rules/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# Before running, replace YOUR_API_KEY and verify the request data.
```

JavaScript

```
const axios = require('axios');

// Configure request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/credit/pricing-rules/",
config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/credit/pricing-rules/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/credit/pricing-rules/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response body

Status code: 200

Example response structure

```
[
  {
    "id": string (uuid)
    "creditItem": string (uuid)
```

```
    "provider": string
    "modelCode": string
    "creditPerUnit": string (decimal)
    "priority": integer // Higher priority = more specific (model-
specific=20, provider-level=10)
    "effectiveFrom": string (timestamp)
    "effectiveUntil": string (timestamp)
    "isActive": boolean
    "notes": string // Internal notes about this pricing rule
  }
]
```

Example response values

```
[
  {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "creditItem": "550e8400-e29b-41d4-a716-446655440000",
    "provider": "Response string",
    "modelCode": "Response string",
    "creditPerUnit": "Response string",
    "priority": 456,
    "effectiveFrom": "Response string",
    "effectiveUntil": "Response string",
    "isActive": false,
    "notes": "Response string"
  }
]
```

Retrieve a pricing rule

GET `/api/v1/credit/pricing-rules/{id}`

No authentication required: This endpoint can be called without an API Key. Rate limit: 60 requests per minute per source IP. Exceeding the limit returns HTTP 429.

Parameters

Parameter name	Required	Type	Description
`id`	V	string	A UUID string identifying this Credit Pricing Rule.

Code examples

Shell/Bash

```
# API call example (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/credit/pricing-
rules/550e8400-e29b-41d4-a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# Before running, replace YOUR_API_KEY and verify the request data.
```

JavaScript

```
const axios = require('axios');

// Configure request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/credit/pricing-
rules/550e8400-e29b-41d4-a716-446655440000/", config)
  .then(response => {
    console.log('Response retrieved successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request failed:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/credit/pricing-rules/550e8400-e29b-41d4-a716-446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("Response retrieved successfully:")
    print(response.json())
except Exception as e:
    print("Request failed:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/credit/pricing-rules/550e8400-
e29b-41d4-a716-446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response retrieved successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request failed: ' . $e->getMessage();
}
?>
```

Response Content

Status Code: 200

Example Response Schema

```
{
  "id": string (uuid)
  "creditItem": string (uuid)
```

```
  "provider": string
  "modelCode": string
  "creditPerUnit": string (decimal)
  "priority": integer // Higher priority = more specific (model-
specific=20, provider-level=10)
  "effectiveFrom": string (timestamp)
  "effectiveUntil": string (timestamp)
  "isActive": boolean
  "notes": string // Internal notes about this pricing rule
}
```

Example Response Values


```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "creditItem": "550e8400-e29b-41d4-a716-446655440000",
  "provider": "response string",
  "modelCode": "response string",
  "creditPerUnit": "response string",
  "priority": 456,
  "effectiveFrom": "response string",
  "effectiveUntil": "response string",
  "isActive": false,
  "notes": "response string"
}
```


List Credit Items

GET `/api/v1/credit/items/`

No login required: Call this endpoint without an API Key. Rate limit: 60 requests per minute per source IP. Exceeding this limit returns HTTP 429.

Code Examples

Shell/Bash

```
# Example API Call (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/credit/items/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/credit/items/", config)
  .then(response => {
    console.log('Response retrieved successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request failed:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/credit/items/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("Response retrieved successfully:")
    print(response.json())
except Exception as e:
    print("Request failed:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/credit/items/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response retrieved successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request failed: ' . $e->getMessage();
}
?>
```

Response Content

Status Code: 200

Example Response Schema

```
[
  {
    "id": string (uuid)
    "code": string // Unique identifier like llm_input_token
```

```
    "name": string
    "category":
    {
    }
    "unit": string // token, character, minute, etc.
    "creditPerUnit": string (decimal)
    "baseCreditPerUnit": string (decimal)
    "effectiveFrom": string (timestamp)
    "isActive": boolean
    "description": string
    "displayGroup": string // Items with the same display_group are
merged into one expandable row on the pricing page. Empty means the item
stands alone.
    "displayOrder": integer // Controls display ordering. Lower numbers
appear first.
    "attachmentRetentionDays": integer // Current Config retention
setting, so the pricing-page tooltip day count follows admin changes.
    "gatewayTrafficFeeDefaultPercent": string // System default AI
Gateway traffic-fee percent, for pricing pages without an org context.

This endpoint is AllowAny with no organization, so it can only surface
the system default ("for reference only" on the frontend); logged-in
pricing pages read the organization's actual percent from the
organization detail API instead.
  }
]
```

Example Response Values

```
[
  {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "code": "response string",
    "name": "response string",
    "category": {},
    "unit": "response string",
    "creditPerUnit": "response string",
    "baseCreditPerUnit": "response string",
    "effectiveFrom": "response string",
    "isActive": false,
    "description": "response string",
    "displayGroup": "response string",
    "displayOrder": 456,
    "attachmentRetentionDays": 456,
```

```
    "gatewayTrafficFeeDefaultPercent": "response string"
  }
]
```

Retrieve a Credit Item

GET `/api/v1/credit/items/{id}`

No login required: Call this endpoint without an API Key. Rate limit: 60 requests per minute per source IP. Exceeding this limit returns HTTP 429.

Parameters

Parameter Name	Required	Type	Description
`id`	V	string	A UUID string identifying this Credit Item.

Code Examples

Shell/Bash

```
# Example API Call (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/credit/items/550e8400-
e29b-41d4-a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/credit/items/550e8400-
e29b-41d4-a716-446655440000/", config)
  .then(response => {
    console.log('Response retrieved successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request failed:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/credit/items/550e8400-e29b-
41d4-a716-446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("Response retrieved successfully:")
    print(response.json())
except Exception as e:
    print("Request failed:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/credit/items/550e8400-e29b-
41d4-a716-446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response retrieved successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request failed: ' . $e->getMessage();
}
?>
```

Response Content

Status Code: 200

Example Response Schema

```
{
  "id": string (uuid)
  "code": string // Unique identifier like llm_input_token
```

```
  "name": string
  "category":
  {
  }
  "unit": string // token, character, minute, etc.
  "creditPerUnit": string (decimal)
  "baseCreditPerUnit": string (decimal)
  "effectiveFrom": string (timestamp)
  "isActive": boolean
  "description": string
  "displayGroup": string // Items with the same display_group are merged into one expandable row on the pricing page. Empty means the item stands alone.
  "displayOrder": integer // Controls display ordering. Lower numbers appear first.
  "attachmentRetentionDays": integer // Current Config retention setting, so the pricing-page tooltip day count follows admin changes.
  "gatewayTrafficFeeDefaultPercent": string // System default AI Gateway traffic-fee percent, for pricing pages without an org context.

This endpoint is AllowAny with no organization, so it can only surface the system default ("for reference only" on the frontend); logged-in pricing pages read the organization's actual percent from the organization detail API instead.
}
```

Example Response Values

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "code": "response string",
  "name": "response string",
  "category": {},
  "unit": "response string",
  "creditPerUnit": "response string",
  "baseCreditPerUnit": "response string",
  "effectiveFrom": "response string",
  "isActive": false,
  "description": "response string",
  "displayGroup": "response string",
  "displayOrder": 456,
  "attachmentRetentionDays": 456,
```

```
  "gatewayTrafficFeeDefaultPercent": "response string"
}
```

API Call Example (Shell)

目錄

1. Get Service Provider Configuration (for IdP Discovery)
2. List or Query Members (Supports `filter`, `startIndex`, and `count`)
3. Create Member
4. Get a Specific Member
5. Replace Member
6. Partially Update Member (Deactivate, Rename, or Change externalId)
7. Deactivate Member
8. List Groups (Mapped to MaiAgent Roles)
9. Create Group
10. Retrieve a specific group
11. Replace a group
12. Partially update a group (rename, add or remove members)
13. Delete a group

API Call Example (Shell)

SCIM 2.0 endpoints let your identity provider (Entra ID, Okta, etc.) automatically provision, update, and deactivate organization members. The base URL is https://api.maiagent.ai/api/v1/scim/{orgUuid}, with no trailing `/`. Authentication uses `Authorization: Bearer` (obtained from the identity synchronization settings in the admin console, rather than an API Key), with `Content-Type: application/scim+json` and a limit of 100 requests per minute per organization. For field mappings and deactivation semantics, see Member Provisioning in the technical manual.

Get Service Provider Configuration (for IdP Discovery)

`GET` `/api/v1/scim/{orgUuid}/ServiceProviderConfig`

Parameters

Parameter Name	Required	Type	Description
orgUuid	V	string	

Code Examples

Shell/Bash

```
# API Call Example (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/scim/550e8400-e29b-41d4-a716-446655440000/ServiceProviderConfig"

  -H "Authorization: Bearer YOUR_SCIM_TOKEN"

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set Request Headers
const config = {
  headers: {
    'Authorization': 'Bearer YOUR_SCIM_TOKEN'
  }
};

axios.get("https://api.maiagent.ai/api/v1/scim/550e8400-e29b-41d4-
a716-446655440000/ServiceProviderConfig", config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/scim/550e8400-e29b-41d4-a716-446655440000/ServiceProviderConfig"
headers = {
    "Authorization": "Bearer YOUR_SCIM_TOKEN"
}


response = requests.get(url, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/scim/550e8400-e29b-41d4-a716-
446655440000/ServiceProviderConfig", [
        'headers' => [
            'Authorization' => 'Bearer YOUR_SCIM_TOKEN'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response Content

Status Code	Description
200	No response body

List or Query Members (Supports `filter`, `startIndex`, and `count`)

GET `/api/v1/scim/{orgUuid}/Users`

Parameters

Parameter Name	Required	Type	Description
`orgUuid`	V	string	

Code Examples

Shell/Bash

```
# API Call Example (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/scim/550e8400-e29b-41d4-a716-446655440000/Users"

  -H "Authorization: Bearer YOUR_SCIM_TOKEN"

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set Request Headers
const config = {
  headers: {
    'Authorization': 'Bearer YOUR_SCIM_TOKEN'
  }
};

axios.get("https://api.maiagent.ai/api/v1/scim/550e8400-e29b-41d4-
a716-446655440000/Users", config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/scim/550e8400-e29b-41d4-a716-446655440000/Users"
headers = {
    "Authorization": "Bearer YOUR_SCIM_TOKEN"
}


response = requests.get(url, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/scim/550e8400-e29b-41d4-a716-
446655440000/Users", [
        'headers' => [
            'Authorization' => 'Bearer YOUR_SCIM_TOKEN'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response Content

Status Code	Description
200	No response body

Create Member

`POST` `/api/v1/scim/{orgUuid}/Users`

Parameters

Parameter Name	Required	Type	Description
`orgUuid`	V	string	

Code Examples

Shell/Bash

```
# API Call Example (Shell)
curl -X POST "https://api.maiagent.ai/api/v1/scim/550e8400-e29b-
41d4-a716-446655440000/Users"

  -H "Authorization: Bearer YOUR_SCIM_TOKEN"

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set Request Headers
const config = {
  headers: {
    'Authorization': 'Bearer YOUR_SCIM_TOKEN'
  }
};

// Request Body (payload)
const data = null;

axios.post("https://api.maiagent.ai/api/v1/scim/550e8400-e29b-41d4-
a716-446655440000/Users", data, config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/scim/550e8400-e29b-41d4-a716-446655440000/Users"
headers = {
    "Authorization": "Bearer YOUR_SCIM_TOKEN"
}


response = requests.post(url, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>post("https://api.maiagent.ai/api/v1/scim/550e8400-e29b-41d4-a716-
446655440000/Users", [
        'headers' => [
            'Authorization' => 'Bearer YOUR_SCIM_TOKEN'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response Content

Status Code	Description
200	No response body

Get a Specific Member

GET `/api/v1/scim/{orgUuid}/Users/{userId}`

Parameters

Parameter Name	Required	Type	Description
`orgUuid`	V	string	
`userId`	V	string	

Code Examples

Shell/Bash

```
# API Call Example (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/scim/550e8400-e29b-41d4-
a716-446655440000/Users/550e8400-e29b-41d4-a716-446655440000"

  -H "Authorization: Bearer YOUR_SCIM_TOKEN"

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set Request Headers
const config = {
  headers: {
    'Authorization': 'Bearer YOUR_SCIM_TOKEN'
  }
};

axios.get("https://api.maiagent.ai/api/v1/scim/550e8400-e29b-41d4-
a716-446655440000/Users/550e8400-e29b-41d4-a716-446655440000",
config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/scim/550e8400-e29b-41d4-a716-446655440000/Users/550e8400-e29b-41d4-a716-446655440000"
headers = {
    "Authorization": "Bearer YOUR_SCIM_TOKEN"
}


response = requests.get(url, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/scim/550e8400-e29b-41d4-a716-
446655440000/Users/550e8400-e29b-41d4-a716-446655440000", [
        'headers' => [
            'Authorization' => 'Bearer YOUR_SCIM_TOKEN'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response Content

Status Code	Description
200	No response body

Replace Member

PUT `/api/v1/scim/{orgUuid}/Users/{userId}`

Parameters

Parameter Name	Required	Type	Description
`orgUuid`	V	string	
`userId`	V	string	

Code Examples

Shell/Bash

```
# API Call Example (Shell)
curl -X PUT "https://api.maiagent.ai/api/v1/scim/550e8400-e29b-41d4-
a716-446655440000/Users/550e8400-e29b-41d4-a716-446655440000"

  -H "Authorization: Bearer YOUR_SCIM_TOKEN"

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set Request Headers
const config = {
  headers: {
    'Authorization': 'Bearer YOUR_SCIM_TOKEN'
  }
};

// Request Body (payload)
const data = null;

axios.put("https://api.maiagent.ai/api/v1/scim/550e8400-e29b-41d4-
a716-446655440000/Users/550e8400-e29b-41d4-a716-446655440000", data,
config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/scim/550e8400-e29b-41d4-a716-446655440000/Users/550e8400-e29b-41d4-a716-446655440000"
headers = {
    "Authorization": "Bearer YOUR_SCIM_TOKEN"
}


response = requests.put(url, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>put("https://api.maiagent.ai/api/v1/scim/550e8400-e29b-41d4-a716-
446655440000/Users/550e8400-e29b-41d4-a716-446655440000", [
        'headers' => [
            'Authorization' => 'Bearer YOUR_SCIM_TOKEN'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response Content

Status Code	Description
200	No response body

Partially Update Member (Deactivate, Rename, or Change externalId)

`PATCH` `/api/v1/scim/{orgUuid}/Users/{userId}`

Parameters

Parameter Name	Required	Type	Description
`orgUuid`	V	string	
`userId`	V	string	

Code Examples

Shell/Bash

```
# API Call Example (Shell)
curl -X PATCH "https://api.maiagent.ai/api/v1/scim/550e8400-e29b-
41d4-a716-446655440000/Users/550e8400-e29b-41d4-a716-446655440000"

  -H "Authorization: Bearer YOUR_SCIM_TOKEN"

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set Request Headers
const config = {
  headers: {
    'Authorization': 'Bearer YOUR_SCIM_TOKEN'
  }
};

// Request Body (payload)
const data = null;

axios.patch("https://api.maiagent.ai/api/v1/scim/550e8400-e29b-41d4-
a716-446655440000/Users/550e8400-e29b-41d4-a716-446655440000", data,
config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/scim/550e8400-e29b-41d4-a716-446655440000/Users/550e8400-e29b-41d4-a716-446655440000"
headers = {
    "Authorization": "Bearer YOUR_SCIM_TOKEN"
}


response = requests.patch(url, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>patch("https://api.maiagent.ai/api/v1/scim/550e8400-e29b-41d4-a716-
446655440000/Users/550e8400-e29b-41d4-a716-446655440000", [
        'headers' => [
            'Authorization' => 'Bearer YOUR_SCIM_TOKEN'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response Content

Status Code	Description
200	No response body

Deactivate Member

DELETE `/api/v1/scim/{orgUuid}/Users/{userId}`

Parameters

Parameter Name	Required	Type	Description
`orgUuid`	V	string	
`userId`	V	string	

Code Examples

Shell/Bash

```
# API Call Example (Shell)
curl -X DELETE "https://api.maiagent.ai/api/v1/scim/550e8400-e29b-
41d4-a716-446655440000/Users/550e8400-e29b-41d4-a716-446655440000"

  -H "Authorization: Bearer YOUR_SCIM_TOKEN"

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set Request Headers
const config = {
  headers: {
    'Authorization': 'Bearer YOUR_SCIM_TOKEN'
  }
};

// Request Body (payload)
const data = null;

axios.delete("https://api.maiagent.ai/api/v1/scim/550e8400-e29b-
41d4-a716-446655440000/Users/550e8400-e29b-41d4-a716-446655440000",
data, config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/scim/550e8400-e29b-41d4-a716-446655440000/Users/550e8400-e29b-41d4-a716-446655440000"
headers = {
    "Authorization": "Bearer YOUR_SCIM_TOKEN"
}


response = requests.delete(url, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>delete("https://api.maiagent.ai/api/v1/scim/550e8400-e29b-41d4-
a716-446655440000/Users/550e8400-e29b-41d4-a716-446655440000", [
        'headers' => [
            'Authorization' => 'Bearer YOUR_SCIM_TOKEN'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response Content

Status Code	Description
204	No response body

List Groups (Mapped to MaiAgent Roles)

GET `/api/v1/scim/{orgUuid}/Groups`

Parameters

Parameter Name	Required	Type	Description
`orgUuid`	V	string	

Code Examples

Shell/Bash

```
# API Call Example (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/scim/550e8400-e29b-41d4-
a716-446655440000/Groups"

  -H "Authorization: Bearer YOUR_SCIM_TOKEN"

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set Request Headers
const config = {
  headers: {
    'Authorization': 'Bearer YOUR_SCIM_TOKEN'
  }
};

axios.get("https://api.maiagent.ai/api/v1/scim/550e8400-e29b-41d4-
a716-446655440000/Groups", config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/scim/550e8400-e29b-41d4-a716-446655440000/Groups"
headers = {
    "Authorization": "Bearer YOUR_SCIM_TOKEN"
}


response = requests.get(url, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/scim/550e8400-e29b-41d4-a716-
446655440000/Groups", [
        'headers' => [
            'Authorization' => 'Bearer YOUR_SCIM_TOKEN'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response Content

Status Code	Description
200	No response body

Create Group

POST `/api/v1/scim/{orgUuid}/Groups`

Parameters

Parameter Name	Required	Type	Description
`orgUuid`	V	string	

Code Examples

Shell/Bash

```
# API Call Example (Shell)
curl -X POST "https://api.maiagent.ai/api/v1/scim/550e8400-e29b-
41d4-a716-446655440000/Groups"

  -H "Authorization: Bearer YOUR_SCIM_TOKEN"

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set Request Headers
const config = {
  headers: {
    'Authorization': 'Bearer YOUR_SCIM_TOKEN'
  }
};

// Request Body (payload)
const data = null;

axios.post("https://api.maiagent.ai/api/v1/scim/550e8400-e29b-41d4-
a716-446655440000/Groups", data, config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/scim/550e8400-e29b-41d4-a716-446655440000/Groups"
headers = {
    "Authorization": "Bearer YOUR_SCIM_TOKEN"
}


response = requests.post(url, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>post("https://api.maiagent.ai/api/v1/scim/550e8400-e29b-41d4-a716-
446655440000/Groups", [
        'headers' => [
            'Authorization' => 'Bearer YOUR_SCIM_TOKEN'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response body

Status code	Description
200	No response body

Retrieve a specific group

GET `/api/v1/scim/{orgUuid}/Groups/{groupId}`

Parameters

Parameter name	Required	Type	Description
`groupId`	V	string	
`orgUuid`	V	string	

Code examples

Shell/Bash

```
# API call example (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/scim/550e8400-e29b-41d4-
a716-446655440000/Groups/550e8400-e29b-41d4-a716-446655440000"

  -H "Authorization: Bearer YOUR_SCIM_TOKEN"

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Bearer YOUR_SCIM_TOKEN'
  }
};

axios.get("https://api.maiagent.ai/api/v1/scim/550e8400-e29b-41d4-
a716-446655440000/Groups/550e8400-e29b-41d4-a716-446655440000",
config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/scim/550e8400-e29b-41d4-a716-446655440000/Groups/550e8400-e29b-41d4-a716-446655440000"
headers = {
    "Authorization": "Bearer YOUR_SCIM_TOKEN"
}


response = requests.get(url, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/scim/550e8400-e29b-41d4-a716-
446655440000/Groups/550e8400-e29b-41d4-a716-446655440000", [
        'headers' => [
            'Authorization' => 'Bearer YOUR_SCIM_TOKEN'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response body

Status code	Description
200	No response body

Replace a group

PUT `/api/v1/scim/{orgUuid}/Groups/{groupId}`

Parameters

Parameter name	Required	Type	Description
`groupId`	V	string	
`orgUuid`	V	string	

Code examples

Shell/Bash

```
# API call example (Shell)
curl -X PUT "https://api.maiagent.ai/api/v1/scim/550e8400-e29b-41d4-
a716-446655440000/Groups/550e8400-e29b-41d4-a716-446655440000"

  -H "Authorization: Bearer YOUR_SCIM_TOKEN"

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Bearer YOUR_SCIM_TOKEN'
  }
};

// Request body (payload)
const data = null;

axios.put("https://api.maiagent.ai/api/v1/scim/550e8400-e29b-41d4-
a716-446655440000/Groups/550e8400-e29b-41d4-a716-446655440000",
data, config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/scim/550e8400-e29b-41d4-a716-446655440000/Groups/550e8400-e29b-41d4-a716-446655440000"
headers = {
    "Authorization": "Bearer YOUR_SCIM_TOKEN"
}


response = requests.put(url, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>put("https://api.maiagent.ai/api/v1/scim/550e8400-e29b-41d4-a716-
446655440000/Groups/550e8400-e29b-41d4-a716-446655440000", [
        'headers' => [
            'Authorization' => 'Bearer YOUR_SCIM_TOKEN'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response body

Status code	Description
200	No response body

Partially update a group (rename, add or remove members)

`PATCH` `/api/v1/scim/{orgUuid}/Groups/{groupId}`

Parameters

Parameter name	Required	Type	Description
`groupId`	V	string	
`orgUuid`	V	string	

Code examples

Shell/Bash

```
# API call example (Shell)
curl -X PATCH "https://api.maiagent.ai/api/v1/scim/550e8400-e29b-
41d4-a716-446655440000/Groups/550e8400-e29b-41d4-a716-446655440000"

  -H "Authorization: Bearer YOUR_SCIM_TOKEN"

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Bearer YOUR_SCIM_TOKEN'
  }
};

// Request body (payload)
const data = null;

axios.patch("https://api.maiagent.ai/api/v1/scim/550e8400-e29b-41d4-
a716-446655440000/Groups/550e8400-e29b-41d4-a716-446655440000",
data, config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/scim/550e8400-e29b-41d4-a716-
446655440000/Groups/550e8400-e29b-41d4-a716-446655440000"
headers = {
    "Authorization": "Bearer YOUR_SCIM_TOKEN"
}


response = requests.patch(url, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>patch("https://api.maiagent.ai/api/v1/scim/550e8400-e29b-41d4-a716-
446655440000/Groups/550e8400-e29b-41d4-a716-446655440000", [
        'headers' => [
            'Authorization' => 'Bearer YOUR_SCIM_TOKEN'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response body

Status code	Description
200	No response body

Delete a group

DELETE `/api/v1/scim/{orgUuid}/Groups/{groupId}`

Parameters

Parameter name	Required	Type	Description
`groupId`	V	string	
`orgUuid`	V	string	

Code examples

Shell/Bash

```
# API call example (Shell)
curl -X DELETE "https://api.maiagent.ai/api/v1/scim/550e8400-e29b-
41d4-a716-446655440000/Groups/550e8400-e29b-41d4-a716-446655440000"

  -H "Authorization: Bearer YOUR_SCIM_TOKEN"

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Bearer YOUR_SCIM_TOKEN'
  }
};

// Request body (payload)
const data = null;

axios.delete("https://api.maiagent.ai/api/v1/scim/550e8400-e29b-
41d4-a716-446655440000/Groups/550e8400-e29b-41d4-a716-446655440000",
data, config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/scim/550e8400-e29b-41d4-a716-446655440000/Groups/550e8400-e29b-41d4-a716-446655440000"
headers = {
    "Authorization": "Bearer YOUR_SCIM_TOKEN"
}


response = requests.delete(url, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>delete("https://api.maiagent.ai/api/v1/scim/550e8400-e29b-41d4-
a716-446655440000/Groups/550e8400-e29b-41d4-a716-446655440000", [
        'headers' => [
            'Authorization' => 'Bearer YOUR_SCIM_TOKEN'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response body

Status code	Description
204	No response body

Example API call (Shell)

目錄

1. Create Web Chat
2. List Web Chats
3. Retrieve a Specific Web Chat
4. Update Web Chat
5. Partially Update Web Chat
6. Set Up Contact Credentials
7. Get Voice Agent Token
8. Upload a Batch QA File
9. Export Batch QA to Excel
10. Get LLM Usage Statistics
11. Get AI Assistant Statistics

Example API call (Shell)

Create Web Chat

`POST` `/api/v1/web-chats/`

Request Body

Request Parameters

Field	Type	Required	Description
avatar	string (uri)	No	
logo	string (uri)	No	
description	string	No	
cover	string (uri)	No	
backUrl	string	No	
isActive	boolean	No	
theme	object	Yes	
theme.primaryColor	string	No	
theme.navbarTextColor	string	No	
theme.conversationBackgroundColor	string	No	
theme.chatbotMessageTextColor	string	No	
theme.userMessageTextColor	string	No	
theme.chatbotMessageBackgroundColor	string	No	

Field	Type	Required	Description
theme.userMessageBackgroundColor	string	No	
theme.chatbotMessageBackgroundShadowEnabled	boolean	No	
theme.userMessageBackgroundShadowEnabled	boolean	No	
theme.chatbotMessageGradientEnabled	boolean	No	
theme.userMessageGradientEnabled	boolean	No	
darkTheme	object	Yes	
darkTheme.primaryColor	string	No	
darkTheme.navbarTextColor	string	No	
darkTheme.conversationBackgroundColor	string	No	
darkTheme.chatbotMessageTextColor	string	No	
darkTheme.userMessageTextColor	string	No	
darkTheme.chatbotMessageBackgroundColor	string	No	
darkTheme.userMessageBackgroundColor	string	No	
darkTheme.chatbotMessageBackgroundShadowEnabled	boolean	No	
darkTheme.userMessageBackgroundShadowEnabled	boolean	No	
darkTheme.chatbotMessageGradientEnabled	boolean	No	
darkTheme.userMessageGradientEnabled	boolean	No	
enableFileUpload	boolean	No	
enableDisplayCitations	boolean	No	
toolDisplayMode	string (enum: full, compact, hidden)	No	`full` : Full ; `compact` : Compact ; `hidden` : Hidden;
enableAskOptionButtons	boolean	No	When enabled, ask_user_question options appear as a row of buttons above the input field, which remains usable. When disabled, the existing overlay panel is used. This gradual rollout switch can be disabled at any time to revert to the previous behavior.
enableConversationHandoff	boolean	No	When enabled, the webchat for this conversation platform displays the handoff UI (notification bar, summary card, and continuation button) and registers handoff tools. It is still governed by the global handoff switch in system settings: disabling the global switch disables handoff everywhere. MaiGPT always displays the handoff UI regardless of this switch. The context usage percentage bar at the bottom is

Field	Type	Required	Description
			controlled separately by "Display Context Usage". Disabled by default, so customer-facing webchats show no handoff UI. This gradual rollout switch can be disabled to revert immediately without rolling back the release.
enableDisplayContextUsage	boolean	No	When enabled, the webchat for this conversation platform displays a context usage percentage bar below the input field. It is independent of conversation handoff: handoff switches (including the global handoff switch) do not affect it, and it does not affect the handoff notification bar. MaiGPT always displays the context usage bar regardless of this switch. Disabled by default; disabling it reverts the behavior immediately without rolling back the release.
enableDisplayThinking	boolean	No	
enableUserThinkingControl	boolean	No	
enableDisplayQueryMetadata	boolean	No	
enableDisplayHookMarkers	boolean	No	
hookMarkerTextInputModify	string	No	
hookMarkerTextOutputModify	string	No	
hookMarkerTextInputBlock	string	No	
hookMarkerTextOutputBlock	string	No	
enableShareConversation	boolean	No	
enableLocation	boolean	No	
enableShowPoweredBy	boolean	No	
poweredByLogo	string (uri)	No	
enableAnonymous	boolean	No	
enableDisplayPreviousConversation	boolean	No	
enableDisplayConversationHistory	boolean	No	
enableConversationTimer	boolean	No	
conversationTimerDuration	integer	No	Timer timeout duration, ranging from 3-60 minutes
enableAutoNewConversationOnTimeout	boolean	No	
enableSatisfactionSurvey	boolean	No	
satisfactionSurveyDelayMinutes	integer	No	Minutes after the last AI reply before the survey appears, ranging from 1-60 minutes

Field	Type	Required	Description
satisfactionSurveyPrompt	string	No	Custom survey title text. Leave blank to use the default localized text in the frontend
enableThemeModeToggle	boolean	No	
enableDisplayFontSizeSwitch	boolean	No	
defaultThemeMode	object	No	
enableDownloadCitations	boolean	No	
customDomain	object (with 3 properties: id, domain, status)	No	
customDomain.domain	string	Yes	
enableDisplayChatbotAvatar	boolean	No	
enableDisplayChatbotName	boolean	No	
buttonIcon	string (uri)	No	
conversationStartersDisplayCount	integer	No	
preChatFormEnabled	boolean	No	
preChatFormFields	object	No	
preChatFormTitle	object	No	
preChatFormSubtitle	object	No	
loadingDisplayMode	object	No	Waiting-experience style. `narrative` shows per-stage copy; `brand_animation` plays the uploaded asset and hides every system narration line. Defaults to `narrative` , which with no copy configured beh...
loadingStageCopyByLocale	object	No	Locale-keyed per-stage waiting copy, shaped {locale: {stage: text}} where stage is one of LoadingStage. An absent locale or stage falls back to the built-in copy, so a partially filled dict is valid a...
loadingLongWaitCopyByLocale	object	No	Locale-keyed line shown once the wait exceeds `loading_long_wait_threshold_seconds` , shaped {locale: text}. Written in the brand character voice for the animation mode, but applies to both modes. Empt...
loadingLongWaitThresholdSeconds	integer	No	How long a single reply must be pending before the long-wait copy appears.
loadingAnimationUseSharedAsset	boolean	No	True (default) means every stage plays `loading_animation_shared_asset_url` ,

Field	Type	Required	Description
			so the admin only uploads once. False expands per-stage assets, each falling back to the shared asset when its own slot is ...
loadingAnimationSharedAssetUrl	string (uri)	No	
loadingAnimationAssetUrlsByStage	object	No	Shaped {stage: url} keyed by LoadingStage. Only consulted when `loading_animation_use_shared_asset` is False; a missing stage falls back to the shared asset.
loadingTypingShowCopy	boolean	No	Only affects the first "typing" stage. True (default, the pre-existing behavior) shows the typing-stage copy next to the pre-first-char animation/dot; False plays only the animation with no text line....
toolCardRunningIconUrl	string (uri)	No	
toolCardCompletedIconUrl	string (uri)	No	

Example Request Schema

```
{
  "avatar"?: string (uri) // Optional
  "logo"?: string (uri) // Optional
  "description"?: string // Optional
  "cover"?: string (uri) // Optional
  "backUrl"?: string // Optional
  "isActive"?: boolean // Optional
  "theme": {
  {
    "primaryColor"?: string // Optional
    "navbarTextColor"?: string // Optional
    "conversationBackgroundColor"?: string // Optional
    "chatbotMessageTextColor"?: string // Optional
    "userMessageTextColor"?: string // Optional
    "chatbotMessageBackgroundColor"?: string // Optional
    "userMessageBackgroundColor"?: string // Optional
    "chatbotMessageBackgroundShadowEnabled"?: boolean // Optional
    "userMessageBackgroundShadowEnabled"?: boolean // Optional
    "chatbotMessageGradientEnabled"?: boolean // Optional
    "userMessageGradientEnabled"?: boolean // Optional
  }
  }
  "darkTheme": {
  {
    "primaryColor"?: string // Optional
    "navbarTextColor"?: string // Optional
    "conversationBackgroundColor"?: string // Optional
    "chatbotMessageTextColor"?: string // Optional
    "userMessageTextColor"?: string // Optional
    "chatbotMessageBackgroundColor"?: string // Optional
    "userMessageBackgroundColor"?: string // Optional
    "chatbotMessageBackgroundShadowEnabled"?: boolean // Optional
    "userMessageBackgroundShadowEnabled"?: boolean // Optional
```

```
    "chatbotMessageGradientEnabled"?: boolean // Optional
    "userMessageGradientEnabled"?: boolean // Optional
  }
  }
  "enableFileUpload"?: boolean // Optional
  "enableDisplayCitations"?: boolean // Optional
  "toolDisplayMode"?: string (enum: full, compact, hidden) // * `full` - Full
* `compact` - Compact
* `hidden` - Hidden (Optional)
  "enableAskOptionButtons"?: boolean // When enabled, ask_user_question options appear as a row of buttons above the input field, which remains usable. When disabled, the existing overlay panel is used. This gradual rollout switch can be disabled at any time to revert to the previous behavior. (Optional)
  "enableConversationHandoff"?: boolean // When enabled, the webchat for this conversation platform displays the handoff UI (notification bar, summary card, and continuation button) and registers handoff tools. It is still governed by the global handoff switch in system settings: disabling the global switch disables handoff everywhere. MaiGPT always displays the handoff UI regardless of this switch. The context usage percentage bar at the bottom is controlled separately by "Display Context Usage". Disabled by default, so customer-facing webchats show no handoff UI. This gradual rollout switch can be disabled to revert immediately without rolling back the release. (Optional)
  "enableDisplayContextUsage"?: boolean // When enabled, the webchat for this conversation platform displays a context usage percentage bar below the input field. It is independent of conversation handoff: handoff switches (including the global handoff switch) do not affect it, and it does not affect the handoff notification bar. MaiGPT always displays the context usage bar regardless of this switch. Disabled by default; disabling it reverts the behavior immediately without rolling back the release. (Optional)
  "enableDisplayThinking"?: boolean // Optional
  "enableUserThinkingControl"?: boolean // Optional
  "enableDisplayQueryMetadata"?: boolean // Optional
  "enableDisplayHookMarkers"?: boolean // Optional
  "hookMarkerTextInputModify"?: string // Optional
  "hookMarkerTextOutputModify"?: string // Optional
  "hookMarkerTextInputBlock"?: string // Optional
  "hookMarkerTextOutputBlock"?: string // Optional
  "enableShareConversation"?: boolean // Optional
  "enableLocation"?: boolean // Optional
  "enableShowPoweredBy"?: boolean // Optional
  "poweredByLogo"?: string (uri) // Optional
  "enableAnonymous"?: boolean // Optional
  "enableDisplayPreviousConversation"?: boolean // Optional
  "enableDisplayConversationHistory"?: boolean // Optional
  "enableConversationTimer"?: boolean // Optional
  "conversationTimerDuration"?: integer // Timer timeout duration, ranging from 3-60 minutes (Optional)
  "enableAutoNewConversationOnTimeout"?: boolean // Optional
  "enableSatisfactionSurvey"?: boolean // Optional
  "satisfactionSurveyDelayMinutes"?: integer // Minutes after the last AI reply before the survey appears, ranging from 1-60 minutes (Optional)
  "satisfactionSurveyPrompt"?: string // Custom survey title text. Leave blank to use the default localized text in the frontend (Optional)
  "enableThemeModeToggle"?: boolean // Optional
  "enableDisplayFontSizeSwitch"?: boolean // Optional
  "defaultThemeMode"?:  // Optional
  {
  }
  "enableDownloadCitations"?: boolean // Optional
  "customDomain"?:  // Optional
  {
    "domain": string
  }
```

```
  "enableDisplayChatbotAvatar"?: boolean // Optional
  "enableDisplayChatbotName"?: boolean // Optional
  "buttonIcon"?: string (uri) // Optional
  "conversationStartersDisplayCount"?: integer // Optional
  "preChatFormEnabled"?: boolean // Optional
  "preChatFormFields"?: object // Optional
  "preChatFormTitle"?: object // Optional
  "preChatFormSubtitle"?: object // Optional
  "loadingDisplayMode"?:  // Waiting-experience style. `narrative` shows per-stage copy;
`brand_animation` plays the uploaded asset and hides every system narration line. Defaults to
`narrative`, which with no copy configured behaves exactly as before this field existed.

* `narrative` - Narrative copy
* `brand_animation` - Brand animation (Optional)
  {
  }
  "loadingStageCopyByLocale"?: object // Locale-keyed per-stage waiting copy, shaped {locale: {stage:
text}} where stage is one of LoadingStage. An absent locale or stage falls back to the built-in copy,
so a partially filled dict is valid and never blocks a reply. (Optional)
  "loadingLongWaitCopyByLocale"?: object // Locale-keyed line shown once the wait exceeds
`loading_long_wait_threshold_seconds`, shaped {locale: text}. Written in the brand character voice
for the animation mode, but applies to both modes. Empty means no long-wait line is shown. (Optional)
  "loadingLongWaitThresholdSeconds"?: integer // How long a single reply must be pending before the
long-wait copy appears. (Optional)
  "loadingAnimationUseSharedAsset"?: boolean // True (default) means every stage plays
`loading_animation_shared_asset_url`, so the admin only uploads once. False expands per-stage assets,
each falling back to the shared asset when its own slot is empty. (Optional)
  "loadingAnimationSharedAssetUrl"?: string (uri) // Optional
  "loadingAnimationAssetUrlsByStage"?: object // Shaped {stage: url} keyed by LoadingStage. Only
consulted when `loading_animation_use_shared_asset` is False; a missing stage falls back to the
shared asset. (Optional)
  "loadingTypingShowCopy"?: boolean // Only affects the first "typing" stage. True (default, the pre-
existing behavior) shows the typing-stage copy next to the pre-first-char animation/dot; False plays
only the animation with no text line. Thinking / analyzing / long-wait stages are unaffected.
(Optional)
  "toolCardRunningIconUrl"?: string (uri) // Optional
  "toolCardCompletedIconUrl"?: string (uri) // Optional
}
```

Example Request Values

```
{
  "avatar": "https://example.com/file.jpg",
  "logo": "https://example.com/file.jpg",
  "description": "Example string",
  "cover": "https://example.com/file.jpg",
  "backUrl": "Example string",
  "isActive": true,
  "theme": {
    "primaryColor": "Example string",
    "navbarTextColor": "Example string",
    "conversationBackgroundColor": "Example string",
    "chatbotMessageTextColor": "Example string",
    "userMessageTextColor": "Example string",
    "chatbotMessageBackgroundColor": "Example string",
    "userMessageBackgroundColor": "Example string",
    "chatbotMessageBackgroundShadowEnabled": true,
    "userMessageBackgroundShadowEnabled": true,
```

```
    "chatbotMessageGradientEnabled": true,
    "userMessageGradientEnabled": true
  },
  "darkTheme": {
    "primaryColor": "Example string",
    "navbarTextColor": "Example string",
    "conversationBackgroundColor": "Example string",
    "chatbotMessageTextColor": "Example string",
    "userMessageTextColor": "Example string",
    "chatbotMessageBackgroundColor": "Example string",
    "userMessageBackgroundColor": "Example string",
    "chatbotMessageBackgroundShadowEnabled": true,
    "userMessageBackgroundShadowEnabled": true,
    "chatbotMessageGradientEnabled": true,
    "userMessageGradientEnabled": true
  },
  "enableFileUpload": true,
  "enableDisplayCitations": true,
  "toolDisplayMode": "full",
  "enableAskOptionButtons": true,
  "enableConversationHandoff": true,
  "enableDisplayContextUsage": true,
  "enableDisplayThinking": true,
  "enableUserThinkingControl": true,
  "enableDisplayQueryMetadata": true,
  "enableDisplayHookMarkers": true,
  "hookMarkerTextInputModify": "Example string",
  "hookMarkerTextOutputModify": "Example string",
  "hookMarkerTextInputBlock": "Example string",
  "hookMarkerTextOutputBlock": "Example string",
  "enableShareConversation": true,
  "enableLocation": true,
  "enableShowPoweredBy": true,
  "poweredByLogo": "https://example.com/file.jpg",
  "enableAnonymous": true,
  "enableDisplayPreviousConversation": true,
  "enableDisplayConversationHistory": true,
  "enableConversationTimer": true,
  "conversationTimerDuration": 123,
  "enableAutoNewConversationOnTimeout": true,
  "enableSatisfactionSurvey": true,
  "satisfactionSurveyDelayMinutes": 123,
  "satisfactionSurveyPrompt": "Example string",
  "enableThemeModeToggle": true,
  "enableDisplayFontSizeSwitch": true,
  "defaultThemeMode": {},
  "enableDownloadCitations": true,
  "customDomain": {
    "domain": "Example string"
  },
  "enableDisplayChatbotAvatar": true,
  "enableDisplayChatbotName": true,
  "buttonIcon": "https://example.com/file.jpg",
  "conversationStartersDisplayCount": 123,
  "preChatFormEnabled": true,
  "preChatFormFields": null,
  "preChatFormTitle": null,
  "preChatFormSubtitle": null,
  "loadingDisplayMode": {},
  "loadingStageCopyByLocale": null,
```

```
  "loadingLongWaitCopyByLocale": null,
  "loadingLongWaitThresholdSeconds": 123,
  "loadingAnimationUseSharedAsset": true,
  "loadingAnimationSharedAssetUrl": "https://example.com/file.jpg",
  "loadingAnimationAssetUrlsByStage": null,
  "loadingTypingShowCopy": true,
  "toolCardRunningIconUrl": "https://example.com/file.jpg",
  "toolCardCompletedIconUrl": "https://example.com/file.jpg"
}
```


Code Examples

Shell/Bash

```
# Example API call (Shell)
curl -X POST "https://api.maiagent.ai/api/v1/web-chats/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "avatar": "https://example.com/file.jpg",
    "logo": "https://example.com/file.jpg",
    "description": "Example string",
    "cover": "https://example.com/file.jpg",
    "backUrl": "Example string",
    "isActive": true,
    "theme": {
      "primaryColor": "Example string",
      "navbarTextColor": "Example string",
      "conversationBackgroundColor": "Example string",
      "chatbotMessageTextColor": "Example string",
      "userMessageTextColor": "Example string",
      "chatbotMessageBackgroundColor": "Example string",
      "userMessageBackgroundColor": "Example string",
      "chatbotMessageBackgroundShadowEnabled": true,
      "userMessageBackgroundShadowEnabled": true,
      "chatbotMessageGradientEnabled": true,
      "userMessageGradientEnabled": true
    },
    "darkTheme": {
      "primaryColor": "Example string",
      "navbarTextColor": "Example string",
      "conversationBackgroundColor": "Example string",
      "chatbotMessageTextColor": "Example string",
      "userMessageTextColor": "Example string",
      "chatbotMessageBackgroundColor": "Example string",
      "userMessageBackgroundColor": "Example string",
      "chatbotMessageBackgroundShadowEnabled": true,
      "userMessageBackgroundShadowEnabled": true,
      "chatbotMessageGradientEnabled": true,
      "userMessageGradientEnabled": true
    },
    "enableFileUpload": true,
    "enableDisplayCitations": true,
    "toolDisplayMode": "full",
    "enableAskOptionButtons": true,
    "enableConversationHandoff": true,
    "enableDisplayContextUsage": true,
    "enableDisplayThinking": true,
    "enableUserThinkingControl": true,
    "enableDisplayQueryMetadata": true,
    "enableDisplayHookMarkers": true,
    "hookMarkerTextInputModify": "Example string",
    "hookMarkerTextOutputModify": "Example string",
    "hookMarkerTextInputBlock": "Example string",
    "hookMarkerTextOutputBlock": "Example string",
```

```
    "enableShareConversation": true,
    "enableLocation": true,
    "enableShowPoweredBy": true,
    "poweredByLogo": "https://example.com/file.jpg",
    "enableAnonymous": true,
    "enableDisplayPreviousConversation": true,
    "enableDisplayConversationHistory": true,
    "enableConversationTimer": true,
    "conversationTimerDuration": 123,
    "enableAutoNewConversationOnTimeout": true,
    "enableSatisfactionSurvey": true,
    "satisfactionSurveyDelayMinutes": 123,
    "satisfactionSurveyPrompt": "Example string",
    "enableThemeModeToggle": true,
    "enableDisplayFontSizeSwitch": true,
    "defaultThemeMode": {},
    "enableDownloadCitations": true,
    "customDomain": {
      "domain": "Example string"
    },
    "enableDisplayChatbotAvatar": true,
    "enableDisplayChatbotName": true,
    "buttonIcon": "https://example.com/file.jpg",
    "conversationStartersDisplayCount": 123,
    "preChatFormEnabled": true,
    "preChatFormFields": null,
    "preChatFormTitle": null,
    "preChatFormSubtitle": null,
    "loadingDisplayMode": {},
    "loadingStageCopyByLocale": null,
    "loadingLongWaitCopyByLocale": null,
    "loadingLongWaitThresholdSeconds": 123,
    "loadingAnimationUseSharedAsset": true,
    "loadingAnimationSharedAssetUrl": "https://example.com/file.jpg",
    "loadingAnimationAssetUrlsByStage": null,
    "loadingTypingShowCopy": true,
    "toolCardRunningIconUrl": "https://example.com/file.jpg",
    "toolCardCompletedIconUrl": "https://example.com/file.jpg"
  }'

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Configure request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// Request body (payload)
const data = {
    "avatar": "https://example.com/file.jpg",
    "logo": "https://example.com/file.jpg",
    "description": "Example string",
    "cover": "https://example.com/file.jpg",
    "backUrl": "Example string",
    "isActive": true,
    "theme": {
      "primaryColor": "Example string",
      "navbarTextColor": "Example string",
      "conversationBackgroundColor": "Example string",
      "chatbotMessageTextColor": "Example string",
      "userMessageTextColor": "Example string",
      "chatbotMessageBackgroundColor": "Example string",
      "userMessageBackgroundColor": "Example string",
      "chatbotMessageBackgroundShadowEnabled": true,
      "userMessageBackgroundShadowEnabled": true,
      "chatbotMessageGradientEnabled": true,
      "userMessageGradientEnabled": true
    },
    "darkTheme": {
      "primaryColor": "Example string",
      "navbarTextColor": "Example string",
      "conversationBackgroundColor": "Example string",
      "chatbotMessageTextColor": "Example string",
      "userMessageTextColor": "Example string",
      "chatbotMessageBackgroundColor": "Example string",
      "userMessageBackgroundColor": "Example string",
      "chatbotMessageBackgroundShadowEnabled": true,
      "userMessageBackgroundShadowEnabled": true,
      "chatbotMessageGradientEnabled": true,
      "userMessageGradientEnabled": true
    },
    "enableFileUpload": true,
    "enableDisplayCitations": true,
    "toolDisplayMode": "full",
    "enableAskOptionButtons": true,
    "enableConversationHandoff": true,
    "enableDisplayContextUsage": true,
    "enableDisplayThinking": true,
    "enableUserThinkingControl": true,
    "enableDisplayQueryMetadata": true,
    "enableDisplayHookMarkers": true,
```

```
    "hookMarkerTextInputModify": "Example string",
    "hookMarkerTextOutputModify": "Example string",
    "hookMarkerTextInputBlock": "Example string",
    "hookMarkerTextOutputBlock": "Example string",
    "enableShareConversation": true,
    "enableLocation": true,
    "enableShowPoweredBy": true,
    "poweredByLogo": "https://example.com/file.jpg",
    "enableAnonymous": true,
    "enableDisplayPreviousConversation": true,
    "enableDisplayConversationHistory": true,
    "enableConversationTimer": true,
    "conversationTimerDuration": 123,
    "enableAutoNewConversationOnTimeout": true,
    "enableSatisfactionSurvey": true,
    "satisfactionSurveyDelayMinutes": 123,
    "satisfactionSurveyPrompt": "Example string",
    "enableThemeModeToggle": true,
    "enableDisplayFontSizeSwitch": true,
    "defaultThemeMode": {},
    "enableDownloadCitations": true,
    "customDomain": {
      "domain": "Example string"
    },
    "enableDisplayChatbotAvatar": true,
    "enableDisplayChatbotName": true,
    "buttonIcon": "https://example.com/file.jpg",
    "conversationStartersDisplayCount": 123,
    "preChatFormEnabled": true,
    "preChatFormFields": null,
    "preChatFormTitle": null,
    "preChatFormSubtitle": null,
    "loadingDisplayMode": {},
    "loadingStageCopyByLocale": null,
    "loadingLongWaitCopyByLocale": null,
    "loadingLongWaitThresholdSeconds": 123,
    "loadingAnimationUseSharedAsset": true,
    "loadingAnimationSharedAssetUrl": "https://example.com/file.jpg",
    "loadingAnimationAssetUrlsByStage": null,
    "loadingTypingShowCopy": true,
    "toolCardRunningIconUrl": "https://example.com/file.jpg",
    "toolCardCompletedIconUrl": "https://example.com/file.jpg"
  };

axios.post("https://api.maiagent.ai/api/v1/web-chats/", data, config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/web-chats/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# Request body (payload)
data = {
    "avatar": "https://example.com/file.jpg",
    "logo": "https://example.com/file.jpg",
    "description": "Example string",
    "cover": "https://example.com/file.jpg",
    "backUrl": "Example string",
    "isActive": True,
    "theme": {
        "primaryColor": "Example string",
        "navbarTextColor": "Example string",
        "conversationBackgroundColor": "Example string",
        "chatbotMessageTextColor": "Example string",
        "userMessageTextColor": "Example string",
        "chatbotMessageBackgroundColor": "Example string",
        "userMessageBackgroundColor": "Example string",
        "chatbotMessageBackgroundShadowEnabled": True,
        "userMessageBackgroundShadowEnabled": True,
        "chatbotMessageGradientEnabled": True,
        "userMessageGradientEnabled": True
    },
    "darkTheme": {
        "primaryColor": "Example string",
        "navbarTextColor": "Example string",
        "conversationBackgroundColor": "Example string",
        "chatbotMessageTextColor": "Example string",
        "userMessageTextColor": "Example string",
        "chatbotMessageBackgroundColor": "Example string",
        "userMessageBackgroundColor": "Example string",
        "chatbotMessageBackgroundShadowEnabled": True,
        "userMessageBackgroundShadowEnabled": True,
        "chatbotMessageGradientEnabled": True,
        "userMessageGradientEnabled": True
    },
    "enableFileUpload": True,
    "enableDisplayCitations": True,
    "toolDisplayMode": "full",
    "enableAskOptionButtons": True,
    "enableConversationHandoff": True,
    "enableDisplayContextUsage": True,
    "enableDisplayThinking": True,
    "enableUserThinkingControl": True,
    "enableDisplayQueryMetadata": True,
    "enableDisplayHookMarkers": True,
    "hookMarkerTextInputModify": "Example string",
    "hookMarkerTextOutputModify": "Example string",
```

```
    "hookMarkerTextInputBlock": "Example string",
    "hookMarkerTextOutputBlock": "Example string",
    "enableShareConversation": True,
    "enableLocation": True,
    "enableShowPoweredBy": True,
    "poweredByLogo": "https://example.com/file.jpg",
    "enableAnonymous": True,
    "enableDisplayPreviousConversation": True,
    "enableDisplayConversationHistory": True,
    "enableConversationTimer": True,
    "conversationTimerDuration": 123,
    "enableAutoNewConversationOnTimeout": True,
    "enableSatisfactionSurvey": True,
    "satisfactionSurveyDelayMinutes": 123,
    "satisfactionSurveyPrompt": "Example string",
    "enableThemeModeToggle": True,
    "enableDisplayFontSizeSwitch": True,
    "defaultThemeMode": {},
    "enableDownloadCitations": True,
    "customDomain": {
        "domain": "Example string"
    },
    "enableDisplayChatbotAvatar": True,
    "enableDisplayChatbotName": True,
    "buttonIcon": "https://example.com/file.jpg",
    "conversationStartersDisplayCount": 123,
    "preChatFormEnabled": True,
    "preChatFormFields": None,
    "preChatFormTitle": None,
    "preChatFormSubtitle": None,
    "loadingDisplayMode": {},
    "loadingStageCopyByLocale": None,
    "loadingLongWaitCopyByLocale": None,
    "loadingLongWaitThresholdSeconds": 123,
    "loadingAnimationUseSharedAsset": True,
    "loadingAnimationSharedAssetUrl": "https://example.com/file.jpg",
    "loadingAnimationAssetUrlsByStage": None,
    "loadingTypingShowCopy": True,
    "toolCardRunningIconUrl": "https://example.com/file.jpg",
    "toolCardCompletedIconUrl": "https://example.com/file.jpg"
}

response = requests.post(url, json=data, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->post("https://api.maiagent.ai/api/v1/web-chats/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'avatar' => 'https://example.com/file.jpg',
            'logo' => 'https://example.com/file.jpg',
            'description' => 'Example string',
            'cover' => 'https://example.com/file.jpg',
            'backUrl' => 'Example string',
            'isActive' => true,
            'theme' => [
                'primaryColor' => 'Example string',
                'navbarTextColor' => 'Example string',
                'conversationBackgroundColor' => 'Example string',
                'chatbotMessageTextColor' => 'Example string',
                'userMessageTextColor' => 'Example string',
                'chatbotMessageBackgroundColor' => 'Example string',
                'userMessageBackgroundColor' => 'Example string',
                'chatbotMessageBackgroundShadowEnabled' => true,
                'userMessageBackgroundShadowEnabled' => true,
                'chatbotMessageGradientEnabled' => true,
                'userMessageGradientEnabled' => true
            ],
            'darkTheme' => [
                'primaryColor' => 'Example string',
                'navbarTextColor' => 'Example string',
                'conversationBackgroundColor' => 'Example string',
                'chatbotMessageTextColor' => 'Example string',
                'userMessageTextColor' => 'Example string',
                'chatbotMessageBackgroundColor' => 'Example string',
                'userMessageBackgroundColor' => 'Example string',
                'chatbotMessageBackgroundShadowEnabled' => true,
                'userMessageBackgroundShadowEnabled' => true,
                'chatbotMessageGradientEnabled' => true,
                'userMessageGradientEnabled' => true
            ],
            'enableFileUpload' => true,
            'enableDisplayCitations' => true,
            'toolDisplayMode' => 'full',
            'enableAskOptionButtons' => true,
            'enableConversationHandoff' => true,
            'enableDisplayContextUsage' => true,
            'enableDisplayThinking' => true,
            'enableUserThinkingControl' => true,
            'enableDisplayQueryMetadata' => true,
            'enableDisplayHookMarkers' => true,
```

```
            'hookMarkerTextInputModify' => 'Example string',
            'hookMarkerTextOutputModify' => 'Example string',
            'hookMarkerTextInputBlock' => 'Example string',
            'hookMarkerTextOutputBlock' => 'Example string',
            'enableShareConversation' => true,
            'enableLocation' => true,
            'enableShowPoweredBy' => true,
            'poweredByLogo' => 'https://example.com/file.jpg',
            'enableAnonymous' => true,
            'enableDisplayPreviousConversation' => true,
            'enableDisplayConversationHistory' => true,
            'enableConversationTimer' => true,
            'conversationTimerDuration' => 123,
            'enableAutoNewConversationOnTimeout' => true,
            'enableSatisfactionSurvey' => true,
            'satisfactionSurveyDelayMinutes' => 123,
            'satisfactionSurveyPrompt' => 'Example string',
            'enableThemeModeToggle' => true,
            'enableDisplayFontSizeSwitch' => true,
            'defaultThemeMode' => new \stdClass(),
            'enableDownloadCitations' => true,
            'customDomain' => [
                'domain' => 'Example string'
            ],
            'enableDisplayChatbotAvatar' => true,
            'enableDisplayChatbotName' => true,
            'buttonIcon' => 'https://example.com/file.jpg',
            'conversationStartersDisplayCount' => 123,
            'preChatFormEnabled' => true,
            'preChatFormFields' => null,
            'preChatFormTitle' => null,
            'preChatFormSubtitle' => null,
            'loadingDisplayMode' => new \stdClass(),
            'loadingStageCopyByLocale' => null,
            'loadingLongWaitCopyByLocale' => null,
            'loadingLongWaitThresholdSeconds' => 123,
            'loadingAnimationUseSharedAsset' => true,
            'loadingAnimationSharedAssetUrl' => 'https://example.com/file.jpg',
            'loadingAnimationAssetUrlsByStage' => null,
            'loadingTypingShowCopy' => true,
            'toolCardRunningIconUrl' => 'https://example.com/file.jpg',
            'toolCardCompletedIconUrl' => 'https://example.com/file.jpg'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response Content

Status code: 201

Example Response Schema

```
{
  "id": string (uuid)
  "name": string
  "avatar"?: string (uri) // Optional
  "logo"?: string (uri) // Optional
  "description"?: string // Optional
  "cover"?: string (uri) // Optional
  "backUrl"?: string // Optional
  "isActive"?: boolean // Optional
  "enableSpeech": boolean
  "displayConversationStarters": [
    string
  ]
  "theme": {
  {
    "primaryColor"?: string // Optional
    "navbarTextColor"?: string // Optional
    "conversationBackgroundColor"?: string // Optional
    "chatbotMessageTextColor"?: string // Optional
    "userMessageTextColor"?: string // Optional
    "chatbotMessageBackgroundColor"?: string // Optional
    "userMessageBackgroundColor"?: string // Optional
    "chatbotMessageBackgroundShadowEnabled"?: boolean // Optional
    "userMessageBackgroundShadowEnabled"?: boolean // Optional
    "chatbotMessageGradientEnabled"?: boolean // Optional
    "userMessageGradientEnabled"?: boolean // Optional
  }
  }
  "darkTheme": {
  {
    "primaryColor"?: string // Optional
    "navbarTextColor"?: string // Optional
    "conversationBackgroundColor"?: string // Optional
    "chatbotMessageTextColor"?: string // Optional
    "userMessageTextColor"?: string // Optional
    "chatbotMessageBackgroundColor"?: string // Optional
    "userMessageBackgroundColor"?: string // Optional
    "chatbotMessageBackgroundShadowEnabled"?: boolean // Optional
    "userMessageBackgroundShadowEnabled"?: boolean // Optional
    "chatbotMessageGradientEnabled"?: boolean // Optional
    "userMessageGradientEnabled"?: boolean // Optional
  }
  }
  "enableFileUpload"?: boolean // Optional
  "enableDisplayCitations"?: boolean // Optional
  "toolDisplayMode"?: string (enum: full, compact, hidden) // * `full` - Full
* `compact` - Compact
* `hidden` - Hidden (Optional)
  "enableAskOptionButtons"?: boolean // When enabled, ask_user_question options appear as a row of
buttons above the input field, which remains usable. When disabled, the current overlay panel is
retained. This gradual rollout toggle can be disabled at any time to revert the behavior. (Optional)
```

```
  "enableConversationHandoff"?: boolean // When enabled, this conversation platform's webchat
displays the handoff UI (notification bar, summary card, and continue button) and registers handoff
tools. It remains subject to the global handoff toggle in system settings: disabling the global
toggle disables handoff everywhere. MaiGPT always displays this UI regardless of this toggle. The
context usage percentage bar at the bottom is controlled separately by "Display context usage".
Disabled by default, so customers' public-facing webchats show no handoff UI. This gradual rollout
toggle can be disabled to revert the behavior without rolling back the release. (Optional)
  "enableDisplayContextUsage"?: boolean // When enabled, this conversation platform's webchat
displays a context usage percentage bar below the input field. This is independent of conversation
handoff: handoff toggles (including the global handoff toggle) do not affect it, and it does not
affect the handoff notification bar. MaiGPT always displays this bar regardless of this toggle.
Disabled by default; disabling it reverts the behavior without rolling back the release. (Optional)
  "enableDisplayThinking"?: boolean // Optional
  "enableUserThinkingControl"?: boolean // Optional
  "enableDisplayQueryMetadata"?: boolean // Optional
  "enableDisplayHookMarkers"?: boolean // Optional
  "hookMarkerTextInputModify"?: string // Optional
  "hookMarkerTextOutputModify"?: string // Optional
  "hookMarkerTextInputBlock"?: string // Optional
  "hookMarkerTextOutputBlock"?: string // Optional
  "enableShareConversation"?: boolean // Optional
  "enableLocation"?: boolean // Optional
  "enableShowPoweredBy"?: boolean // Optional
  "poweredByLogo"?: string (uri) // Optional
  "enableAnonymous"?: boolean // Optional
  "enableDisplayPreviousConversation"?: boolean // Optional
  "enableDisplayConversationHistory"?: boolean // Optional
  "enableConversationTimer"?: boolean // Optional
  "conversationTimerDuration"?: integer // Timer timeout duration, ranging from 3-60 minutes
(Optional)
  "enableAutoNewConversationOnTimeout"?: boolean // Optional
  "enableSatisfactionSurvey"?: boolean // Optional
  "satisfactionSurveyDelayMinutes"?: integer // Number of minutes after the last AI reply before the
survey appears, ranging from 1-60 minutes (Optional)
  "satisfactionSurveyPrompt"?: string // Custom survey title text; leave blank to use the frontend's
default localized text (Optional)
  "accessType":
  {
  }
  "enableThemeModeToggle"?: boolean // Optional
  "enableDisplayFontSizeSwitch"?: boolean // Optional
  "defaultThemeMode"?:  // Optional
  {
  }
  "enableDownloadCitations"?: boolean // Optional
  "customDomain"?:  // Optional
  {
    "id": string (uuid)
    "domain": string
    "status":
    {
    }
  }
  "enableDisplayChatbotAvatar"?: boolean // Optional
  "enableDisplayChatbotName"?: boolean // Optional
  "buttonIcon"?: string (uri) // Optional
  "enableCodeInterpreter": boolean // Read enable_code_interpreter from the inbox's chatbot.
  "voiceAgentEnabled": boolean // Whether the bound chatbot has the voice agent turned on (read-only)
  "conversationStartersDisplayCount"?: integer // Optional
  "includeGreetingInContext": boolean // When enabled, the conversation greeting and the numbered
```

```
conversation starters (in configured order, unshuffled and untruncated) are injected into the LLM
context so the agent can resolve short replies like "1" to the matching starter option.
  "tools": [ // Expose chatbot tools to SDK for the tool_mask selector.

Name resolution prefers ``display_name`` (set on MCP tools, where
``name`` is null) and falls back to ``name`` for API tools where
``display_name`` is null. Tools missing both are skipped — SDK
should never show an unnamed tool to a contact. Quick Menu tools are
static input-bar UI, never an LLM tool, so masking one is meaningless.
    object
  ]
  "preChatFormEnabled"?: boolean // Optional
  "preChatFormFields"?: object // Optional
  "preChatFormTitle"?: object // Optional
  "preChatFormSubtitle"?: object // Optional
  "loadingDisplayMode"?:  // Waiting-experience style. `narrative` shows per-stage copy;
`brand_animation` plays the uploaded asset and hides every system narration line. Defaults to
`narrative`, which with no copy configured behaves exactly as before this field existed.

* `narrative` - Narrative copy
* `brand_animation` - Brand animation (Optional)
  {
  }
  "loadingStageCopyByLocale"?: object // Locale-keyed per-stage waiting copy, shaped {locale: {stage:
text}} where stage is one of LoadingStage. An absent locale or stage falls back to the built-in copy,
so a partially filled dict is valid and never blocks a reply. (Optional)
  "loadingLongWaitCopyByLocale"?: object // Locale-keyed line shown once the wait exceeds
`loading_long_wait_threshold_seconds`, shaped {locale: text}. Written in the brand character voice
for the animation mode, but applies to both modes. Empty means no long-wait line is shown. (Optional)
  "loadingLongWaitThresholdSeconds"?: integer // How long a single reply must be pending before the
long-wait copy appears. (Optional)
  "loadingAnimationUseSharedAsset"?: boolean // True (default) means every stage plays
`loading_animation_shared_asset_url`, so the admin only uploads once. False expands per-stage assets,
each falling back to the shared asset when its own slot is empty. (Optional)
  "loadingAnimationSharedAssetUrl"?: string (uri) // Optional
  "loadingAnimationAssetUrlsByStage"?: object // Shaped {stage: url} keyed by LoadingStage. Only
consulted when `loading_animation_use_shared_asset` is False; a missing stage falls back to the
shared asset. (Optional)
  "loadingTypingShowCopy"?: boolean // Only affects the first "typing" stage. True (default, the pre-
existing behavior) shows the typing-stage copy next to the pre-first-char animation/dot; False plays
only the animation with no text line. Thinking / analyzing / long-wait stages are unaffected.
(Optional)
  "toolCardRunningIconUrl"?: string (uri) // Optional
  "toolCardCompletedIconUrl"?: string (uri) // Optional
  "inbox": object
  "quickMenu": object // Mounted Quick Menu Agent UI config for the web chat input bar; null when
absent (read-only)
}
```

Example Response Values

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "name": "Response string",
  "avatar": "https://example.com/file.jpg",
  "logo": "https://example.com/file.jpg",
  "description": "Response string",
  "cover": "https://example.com/file.jpg",
```

```
  "backUrl": "Response string",
  "isActive": false,
  "enableSpeech": false,
  "displayConversationStarters": [
    "Response string"
  ],
  "theme": {
    "primaryColor": "Response string",
    "navbarTextColor": "Response string",
    "conversationBackgroundColor": "Response string",
    "chatbotMessageTextColor": "Response string",
    "userMessageTextColor": "Response string",
    "chatbotMessageBackgroundColor": "Response string",
    "userMessageBackgroundColor": "Response string",
    "chatbotMessageBackgroundShadowEnabled": false,
    "userMessageBackgroundShadowEnabled": false,
    "chatbotMessageGradientEnabled": false,
    "userMessageGradientEnabled": false
  },
  "darkTheme": {
    "primaryColor": "Response string",
    "navbarTextColor": "Response string",
    "conversationBackgroundColor": "Response string",
    "chatbotMessageTextColor": "Response string",
    "userMessageTextColor": "Response string",
    "chatbotMessageBackgroundColor": "Response string",
    "userMessageBackgroundColor": "Response string",
    "chatbotMessageBackgroundShadowEnabled": false,
    "userMessageBackgroundShadowEnabled": false,
    "chatbotMessageGradientEnabled": false,
    "userMessageGradientEnabled": false
  },
  "enableFileUpload": false,
  "enableDisplayCitations": false,
  "toolDisplayMode": "full",
  "enableAskOptionButtons": false,
  "enableConversationHandoff": false,
  "enableDisplayContextUsage": false,
  "enableDisplayThinking": false,
  "enableUserThinkingControl": false,
  "enableDisplayQueryMetadata": false,
  "enableDisplayHookMarkers": false,
  "hookMarkerTextInputModify": "Response string",
  "hookMarkerTextOutputModify": "Response string",
  "hookMarkerTextInputBlock": "Response string",
  "hookMarkerTextOutputBlock": "Response string",
  "enableShareConversation": false,
  "enableLocation": false,
  "enableShowPoweredBy": false,
  "poweredByLogo": "https://example.com/file.jpg",
  "enableAnonymous": false,
  "enableDisplayPreviousConversation": false,
  "enableDisplayConversationHistory": false,
  "enableConversationTimer": false,
  "conversationTimerDuration": 456,
  "enableAutoNewConversationOnTimeout": false,
  "enableSatisfactionSurvey": false,
  "satisfactionSurveyDelayMinutes": 456,
  "satisfactionSurveyPrompt": "Response string",
  "accessType": {},
```

```
  "enableThemeModeToggle": false,
  "enableDisplayFontSizeSwitch": false,
  "defaultThemeMode": {},
  "enableDownloadCitations": false,
  "customDomain": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "domain": "Response string",
    "status": {}
  },
  "enableDisplayChatbotAvatar": false,
  "enableDisplayChatbotName": false,
  "buttonIcon": "https://example.com/file.jpg",
  "enableCodeInterpreter": false,
  "voiceAgentEnabled": false,
  "conversationStartersDisplayCount": 456,
  "includeGreetingInContext": false,
  "tools": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "Example response name",
      "description": "Example response description"
    }
  ],
  "preChatFormEnabled": false,
  "preChatFormFields": null,
  "preChatFormTitle": null,
  "preChatFormSubtitle": null,
  "loadingDisplayMode": {},
  "loadingStageCopyByLocale": null,
  "loadingLongWaitCopyByLocale": null,
  "loadingLongWaitThresholdSeconds": 456,
  "loadingAnimationUseSharedAsset": false,
  "loadingAnimationSharedAssetUrl": "https://example.com/file.jpg",
  "loadingAnimationAssetUrlsByStage": null,
  "loadingTypingShowCopy": false,
  "toolCardRunningIconUrl": "https://example.com/file.jpg",
  "toolCardCompletedIconUrl": "https://example.com/file.jpg",
  "inbox": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Example response name",
    "description": "Example response description"
  },
  "quickMenu": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Example response name",
    "description": "Example response description"
  }
}
```


List Web Chats

GET `/api/v1/web-chats/`

Code Examples

Shell/Bash

```
# API call example (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/web-chats/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/web-chats/", config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```python
import requests

url = "https://api.maiagent.ai/api/v1/web-chats/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->get("https://api.maiagent.ai/api/v1/web-chats/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response Content

Status Code: 200

Example Response Structure

```
[
  {
    "id": string (uuid)
    "avatar"?: string (uri) // Optional
    "name": string
  }
]
```

Example Response Values

```
[
  {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "avatar": "https://example.com/file.jpg",
    "name": "Response string"
  }
]
```

Retrieve a Specific Web Chat

GET `/api/v1/web-chats/{id}`

Parameters

Parameter Name	Required	Type	Description
`id`	V	string	A UUID string identifying this web chat.

Code Examples

Shell/Bash

```
# API call example (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/web-chats/550e8400-e29b-41d4-a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/web-chats/550e8400-e29b-41d4-a716-446655440000/",
config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```python
import requests

url = "https://api.maiagent.ai/api/v1/web-chats/550e8400-e29b-41d4-a716-446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->get("https://api.maiagent.ai/api/v1/web-chats/550e8400-e29b-41d4-a716-
446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response Content

Status Code: 200

Example Response Structure

```
{
  "id": string (uuid)
  "name": string
  "avatar"?: string (uri) // Optional
  "logo"?: string (uri) // Optional
  "description"?: string // Optional
  "cover"?: string (uri) // Optional
  "backUrl"?: string // Optional
  "isActive"?: boolean // Optional
  "enableSpeech": boolean
  "displayConversationStarters": [
    string
  ]
  "theme": {
  {
    "primaryColor"?: string // Optional
    "navbarTextColor"?: string // Optional
    "conversationBackgroundColor"?: string // Optional
    "chatbotMessageTextColor"?: string // Optional
    "userMessageTextColor"?: string // Optional
    "chatbotMessageBackgroundColor"?: string // Optional
    "userMessageBackgroundColor"?: string // Optional
    "chatbotMessageBackgroundShadowEnabled"?: boolean // Optional
    "userMessageBackgroundShadowEnabled"?: boolean // Optional
    "chatbotMessageGradientEnabled"?: boolean // Optional
    "userMessageGradientEnabled"?: boolean // Optional
  }
  }
  "darkTheme": {
  {
    "primaryColor"?: string // Optional
    "navbarTextColor"?: string // Optional
    "conversationBackgroundColor"?: string // Optional
    "chatbotMessageTextColor"?: string // Optional
    "userMessageTextColor"?: string // Optional
    "chatbotMessageBackgroundColor"?: string // Optional
    "userMessageBackgroundColor"?: string // Optional
    "chatbotMessageBackgroundShadowEnabled"?: boolean // Optional
    "userMessageBackgroundShadowEnabled"?: boolean // Optional
    "chatbotMessageGradientEnabled"?: boolean // Optional
    "userMessageGradientEnabled"?: boolean // Optional
  }
  }
  "enableFileUpload"?: boolean // Optional
  "enableDisplayCitations"?: boolean // Optional
  "toolDisplayMode"?: string (enum: full, compact, hidden) // * `full` - Full
* `compact` - Compact
* `hidden` - Hidden (Optional)
  "enableAskOptionButtons"?: boolean // When enabled, ask_user_question options appear as a row of buttons above the input field, which remains usable. When disabled, the existing overlay panel is retained. This gradual rollout switch can be disabled at any time to revert the behavior. (Optional)
  "enableConversationHandoff"?: boolean // When enabled, this conversation platform’s webchat displays the handoff UI (notification bar, summary card, and resume button) and registers handoff tools. The global handoff switch in system settings still applies: disabling it disables handoff everywhere. MaiGPT always displays this UI regardless of this switch. The context usage percentage
```

```
bar at the bottom is controlled separately by “Display context usage”. Disabled by default, so customer-facing webchats display no handoff UI. This gradual rollout switch can be disabled to revert the behavior without rolling back the release. (Optional)
  "enableDisplayContextUsage"?: boolean // When enabled, this conversation platform’s webchat displays a context usage percentage bar below the input field. This is independent of conversation handoff: handoff switches, including the global handoff switch, do not affect it, and it does not affect the handoff notification bar. MaiGPT always displays the bar regardless of this switch. Disabled by default; disabling it reverts the behavior without rolling back the release. (Optional)
  "enableDisplayThinking"?: boolean // Optional
  "enableUserThinkingControl"?: boolean // Optional
  "enableDisplayQueryMetadata"?: boolean // Optional
  "enableDisplayHookMarkers"?: boolean // Optional
  "hookMarkerTextInputModify"?: string // Optional
  "hookMarkerTextOutputModify"?: string // Optional
  "hookMarkerTextInputBlock"?: string // Optional
  "hookMarkerTextOutputBlock"?: string // Optional
  "enableShareConversation"?: boolean // Optional
  "enableLocation"?: boolean // Optional
  "enableShowPoweredBy"?: boolean // Optional
  "poweredByLogo"?: string (uri) // Optional
  "enableAnonymous"?: boolean // Optional
  "enableDisplayPreviousConversation"?: boolean // Optional
  "enableDisplayConversationHistory"?: boolean // Optional
  "enableConversationTimer"?: boolean // Optional
  "conversationTimerDuration"?: integer // Timer timeout duration, from 3 to 60 minutes (Optional)
  "enableAutoNewConversationOnTimeout"?: boolean // Optional
  "enableSatisfactionSurvey"?: boolean // Optional
  "satisfactionSurveyDelayMinutes"?: integer // Number of minutes after the last AI reply before the survey appears, from 1 to 60 minutes (Optional)
  "satisfactionSurveyPrompt"?: string // Custom survey title text; leave blank to use the frontend’s default localized text (Optional)
  "accessType":
  {
  }
  "enableThemeModeToggle"?: boolean // Optional
  "enableDisplayFontSizeSwitch"?: boolean // Optional
  "defaultThemeMode"?:  // Optional
  {
  }
  "enableDownloadCitations"?: boolean // Optional
  "customDomain"?:  // Optional
  {
    "id": string (uuid)
    "domain": string
    "status":
    {
    }
  }
  "enableDisplayChatbotAvatar"?: boolean // Optional
  "enableDisplayChatbotName"?: boolean // Optional
  "buttonIcon"?: string (uri) // Optional
  "enableCodeInterpreter": boolean // Read enable_code_interpreter from the inbox's chatbot.
  "voiceAgentEnabled": boolean // Whether the bound chatbot has the voice agent turned on (read-only)
  "conversationStartersDisplayCount"?: integer // Optional
  "includeGreetingInContext": boolean // When enabled, the conversation greeting and the numbered conversation starters (in configured order, unshuffled and untruncated) are injected into the LLM context so the agent can resolve short replies like "1" to the matching starter option.
  "tools": [ // Expose chatbot tools to SDK for the tool_mask selector.

Name resolution prefers ``display_name`` (set on MCP tools, where
```

```
``name`` is null) and falls back to ``name`` for API tools where
``display_name`` is null. Tools missing both are skipped — SDK
should never show an unnamed tool to a contact. Quick Menu tools are
static input-bar UI, never an LLM tool, so masking one is meaningless.
    object
  ]
  "preChatFormEnabled"?: boolean // Optional
  "preChatFormFields"?: object // Optional
  "preChatFormTitle"?: object // Optional
  "preChatFormSubtitle"?: object // Optional
  "loadingDisplayMode"?:  // Waiting-experience style. `narrative` shows per-stage copy;
`brand_animation` plays the uploaded asset and hides every system narration line. Defaults to
`narrative`, which with no copy configured behaves exactly as before this field existed.

* `narrative` - Narrative copy
* `brand_animation` - Brand animation (Optional)
  {
  }
  "loadingStageCopyByLocale"?: object // Locale-keyed per-stage waiting copy, shaped {locale: {stage:
text}} where stage is one of LoadingStage. An absent locale or stage falls back to the built-in copy,
so a partially filled dict is valid and never blocks a reply. (Optional)
  "loadingLongWaitCopyByLocale"?: object // Locale-keyed line shown once the wait exceeds
`loading_long_wait_threshold_seconds`, shaped {locale: text}. Written in the brand character voice
for the animation mode, but applies to both modes. Empty means no long-wait line is shown. (Optional)
  "loadingLongWaitThresholdSeconds"?: integer // How long a single reply must be pending before the
long-wait copy appears. (Optional)
  "loadingAnimationUseSharedAsset"?: boolean // True (default) means every stage plays
`loading_animation_shared_asset_url`, so the admin only uploads once. False expands per-stage assets,
each falling back to the shared asset when its own slot is empty. (Optional)
  "loadingAnimationSharedAssetUrl"?: string (uri) // Optional
  "loadingAnimationAssetUrlsByStage"?: object // Shaped {stage: url} keyed by LoadingStage. Only
consulted when `loading_animation_use_shared_asset` is False; a missing stage falls back to the
shared asset. (Optional)
  "loadingTypingShowCopy"?: boolean // Only affects the first "typing" stage. True (default, the pre-
existing behavior) shows the typing-stage copy next to the pre-first-char animation/dot; False plays
only the animation with no text line. Thinking / analyzing / long-wait stages are unaffected.
(Optional)
  "toolCardRunningIconUrl"?: string (uri) // Optional
  "toolCardCompletedIconUrl"?: string (uri) // Optional
  "inbox": object
  "quickMenu": object // Mounted Quick Menu Agent UI config for the web chat input bar; null when
absent (read-only)
}
```

Example Response Values

```
{
  "id": "123e4567-e89b-12d3-a456-426614174000",
  "name": "Test doc",
  "avatar": "https://example.com/static/images/default-chatbot-avatar.png",
  "logo": null,
  "description": "",
  "cover": null,
  "backUrl": "",
  "isActive": true,
  "enableSpeech": false,
  "displayGreeting": null,
  "displayConversationStarters": [],
```

```
  "theme": {
    "primaryColor": "#3854d8",
    "dialogColor": "#ddeaf6",
    "navbarTextColor": "#ffffff"
  },
  "enableFileUpload": true,
  "enableDisplayCitations": true,
  "enableShareConversation": false,
  "enableLocation": false,
  "enableShowPoweredBy": true,
  "poweredByLogo": null,
  "accessType": "web",
  "inbox": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Test doc",
    "signAuth": {
      "id": "6ba7b810-9dad-11d1-80b4-00c04fd430c8",
      "signSource": {
        "id": "7c9e6679-7425-40de-944b-e07fc1f90ae7",
        "accessType": "keycloak"
      },
      "signParams": {
        "keycloak": {
          "url": "example.com",
          "realm": "example",
          "clientId": "example"
        }
      }
    }
  }
}
```


Update Web Chat

PUT `/api/v1/web-chats/{id}`

Parameters

Parameter Name	Required	Type	Description
`id`	V	string	A UUID string identifying this web chat.

Request Content

Request Parameters

Field	Type	Required	Description
avatar	string (uri)	No	
logo	string (uri)	No	
description	string	No	
cover	string (uri)	No	
backUrl	string	No	
isActive	boolean	No	
theme	object	Yes	
theme.primaryColor	string	No	
theme.navbarTextColor	string	No	
theme.conversationBackgroundColor	string	No	
theme.chatbotMessageTextColor	string	No	
theme.userMessageTextColor	string	No	
theme.chatbotMessageBackgroundColor	string	No	
theme.userMessageBackgroundColor	string	No	
theme.chatbotMessageBackgroundShadowEnabled	boolean	No	
theme.userMessageBackgroundShadowEnabled	boolean	No	
theme.chatbotMessageGradientEnabled	boolean	No	
theme.userMessageGradientEnabled	boolean	No	
darkTheme	object	Yes	
darkTheme.primaryColor	string	No	
darkTheme.navbarTextColor	string	No	
darkTheme.conversationBackgroundColor	string	No	
darkTheme.chatbotMessageTextColor	string	No	
darkTheme.userMessageTextColor	string	No	
darkTheme.chatbotMessageBackgroundColor	string	No	
darkTheme.userMessageBackgroundColor	string	No	
darkTheme.chatbotMessageBackgroundShadowEnabled	boolean	No	
darkTheme.userMessageBackgroundShadowEnabled	boolean	No	
darkTheme.chatbotMessageGradientEnabled	boolean	No	
darkTheme.userMessageGradientEnabled	boolean	No	
enableFileUpload	boolean	No	
enableDisplayCitations	boolean	No	

Field	Type	Required	Description
toolDisplayMode	string (enum: full, compact, hidden)	No	`full` : Full ; `compact` : Compact ; `hidden` : Hidden;
enableAskOptionButtons	boolean	No	When enabled, ask_user_question options appear as a row of buttons above the input box, which remains usable. When disabled, the current overlay panel is retained. This gradual rollout toggle can be disabled at any time to revert to the previous behavior.
enableConversationHandoff	boolean	No	When enabled, this conversation platform's webchat displays the handoff UI (notification bar, summary card, and continue button) and registers handoff tools. It remains subject to the global handoff toggle in system settings: disabling the global toggle disables handoff everywhere. MaiGPT always displays the UI regardless of this toggle. The context usage percentage bar at the bottom is controlled separately by "Display context usage". Disabled by default, so customer-facing webchats display no handoff UI. This gradual rollout toggle can be disabled to revert immediately without rolling back the release.
enableDisplayContextUsage	boolean	No	When enabled, this conversation platform's webchat displays a context usage percentage bar below the input box. It is independent of conversation handoff: handoff toggles, including the global handoff toggle, do not affect it, and it does not affect the handoff notification bar. MaiGPT always displays the bar regardless of this toggle. Disabled by default; disabling it reverts immediately without rolling back the release.
enableDisplayThinking	boolean	No	
enableUserThinkingControl	boolean	No	
enableDisplayQueryMetadata	boolean	No	
enableDisplayHookMarkers	boolean	No	
hookMarkerTextInputModify	string	No	
hookMarkerTextOutputModify	string	No	
hookMarkerTextInputBlock	string	No	
hookMarkerTextOutputBlock	string	No	

Field	Type	Required	Description
enableShareConversation	boolean	No	
enableLocation	boolean	No	
enableShowPoweredBy	boolean	No	
poweredByLogo	string (uri)	No	
enableAnonymous	boolean	No	
enableDisplayPreviousConversation	boolean	No	
enableDisplayConversationHistory	boolean	No	
enableConversationTimer	boolean	No	
conversationTimerDuration	integer	No	Timer timeout duration, ranging from 3-60 minutes
enableAutoNewConversationOnTimeout	boolean	No	
enableSatisfactionSurvey	boolean	No	
satisfactionSurveyDelayMinutes	integer	No	Number of minutes after the last AI reply before the survey appears, ranging from 1-60 minutes
satisfactionSurveyPrompt	string	No	Custom survey title text; leave blank to use the frontend's default localized text
enableThemeModeToggle	boolean	No	
enableDisplayFontSizeSwitch	boolean	No	
defaultThemeMode	object	No	
enableDownloadCitations	boolean	No	
customDomain	object (contains 3 properties: id, domain, status)	No	
customDomain.domain	string	Yes	
enableDisplayChatbotAvatar	boolean	No	
enableDisplayChatbotName	boolean	No	
buttonIcon	string (uri)	No	
conversationStartersDisplayCount	integer	No	
preChatFormEnabled	boolean	No	
preChatFormFields	object	No	
preChatFormTitle	object	No	
preChatFormSubtitle	object	No	

Field	Type	Required	Description
loadingDisplayMode	object	No	Waiting-experience style. `narrative` shows per-stage copy; `brand_animation` plays the uploaded asset and hides every system narration line. Defaults to `narrative`, which with no copy configured beh...
loadingStageCopyByLocale	object	No	Locale-keyed per-stage waiting copy, shaped {locale: {stage: text}} where stage is one of LoadingStage. An absent locale or stage falls back to the built-in copy, so a partially filled dict is valid a...
loadingLongWaitCopyByLocale	object	No	Locale-keyed line shown once the wait exceeds `loading_long_wait_threshold_seconds`, shaped {locale: text}. Written in the brand character voice for the animation mode, but applies to both modes. Empt...
loadingLongWaitThresholdSeconds	integer	No	How long a single reply must be pending before the long-wait copy appears.
loadingAnimationUseSharedAsset	boolean	No	True (default) means every stage plays `loading_animation_shared_asset_url`, so the admin only uploads once. False expands per-stage assets, each falling back to the shared asset when its own slot is ...
loadingAnimationSharedAssetUrl	string (uri)	No	
loadingAnimationAssetUrlsByStage	object	No	Shaped {stage: url} keyed by LoadingStage. Only consulted when `loading_animation_use_shared_asset` is False; a missing stage falls back to the shared asset.
loadingTypingShowCopy	boolean	No	Only affects the first "typing" stage. True (default, the pre-existing behavior) shows the typing-stage copy next to the pre-first-char animation/dot; False plays only the animation with no text line....
toolCardRunningIconUrl	string (uri)	No	
toolCardCompletedIconUrl	string (uri)	No	

Example Request Structure

```
{
  "avatar"?: string (uri) // Optional
  "logo"?: string (uri) // Optional
  "description"?: string // Optional
  "cover"?: string (uri) // Optional
  "backUrl"?: string // Optional
  "isActive"?: boolean // Optional
  "theme": {
  {
```

```
    "primaryColor"?: string // Optional
    "navbarTextColor"?: string // Optional
    "conversationBackgroundColor"?: string // Optional
    "chatbotMessageTextColor"?: string // Optional
    "userMessageTextColor"?: string // Optional
    "chatbotMessageBackgroundColor"?: string // Optional
    "userMessageBackgroundColor"?: string // Optional
    "chatbotMessageBackgroundShadowEnabled"?: boolean // Optional
    "userMessageBackgroundShadowEnabled"?: boolean // Optional
    "chatbotMessageGradientEnabled"?: boolean // Optional
    "userMessageGradientEnabled"?: boolean // Optional
  }
  }
  "darkTheme": {
  {
    "primaryColor"?: string // Optional
    "navbarTextColor"?: string // Optional
    "conversationBackgroundColor"?: string // Optional
    "chatbotMessageTextColor"?: string // Optional
    "userMessageTextColor"?: string // Optional
    "chatbotMessageBackgroundColor"?: string // Optional
    "userMessageBackgroundColor"?: string // Optional
    "chatbotMessageBackgroundShadowEnabled"?: boolean // Optional
    "userMessageBackgroundShadowEnabled"?: boolean // Optional
    "chatbotMessageGradientEnabled"?: boolean // Optional
    "userMessageGradientEnabled"?: boolean // Optional
  }
  }
  "enableFileUpload"?: boolean // Optional
  "enableDisplayCitations"?: boolean // Optional
  "toolDisplayMode"?: string (enum: full, compact, hidden) // * `full` - Full
* `compact` - Compact
* `hidden` - Hidden (Optional)
  "enableAskOptionButtons"?: boolean // When enabled, ask_user_question options appear as a row of
buttons above the input box, which remains usable. When disabled, the current overlay panel is
retained. This gradual rollout toggle can be disabled at any time to revert to the previous behavior.
(Optional)
  "enableConversationHandoff"?: boolean // When enabled, this conversation platform's webchat
displays the handoff UI (notification bar, summary card, and continue button) and registers handoff
tools. It remains subject to the global handoff toggle in system settings: disabling the global
toggle disables handoff everywhere. MaiGPT always displays the UI regardless of this toggle. The
context usage percentage bar at the bottom is controlled separately by "Display context usage".
Disabled by default, so customer-facing webchats display no handoff UI. This gradual rollout toggle
can be disabled to revert immediately without rolling back the release. (Optional)
  "enableDisplayContextUsage"?: boolean // When enabled, this conversation platform's webchat
displays a context usage percentage bar below the input box. It is independent of conversation
handoff: handoff toggles, including the global handoff toggle, do not affect it, and it does not
affect the handoff notification bar. MaiGPT always displays the bar regardless of this toggle.
Disabled by default; disabling it reverts immediately without rolling back the release. (Optional)
  "enableDisplayThinking"?: boolean // Optional
  "enableUserThinkingControl"?: boolean // Optional
  "enableDisplayQueryMetadata"?: boolean // Optional
  "enableDisplayHookMarkers"?: boolean // Optional
  "hookMarkerTextInputModify"?: string // Optional
  "hookMarkerTextOutputModify"?: string // Optional
  "hookMarkerTextInputBlock"?: string // Optional
  "hookMarkerTextOutputBlock"?: string // Optional
  "enableShareConversation"?: boolean // Optional
  "enableLocation"?: boolean // Optional
  "enableShowPoweredBy"?: boolean // Optional
```

```
  "poweredByLogo"?: string (uri) // Optional
  "enableAnonymous"?: boolean // Optional
  "enableDisplayPreviousConversation"?: boolean // Optional
  "enableDisplayConversationHistory"?: boolean // Optional
  "enableConversationTimer"?: boolean // Optional
  "conversationTimerDuration"?: integer // Timer timeout duration, ranging from 3-60 minutes
(Optional)
  "enableAutoNewConversationOnTimeout"?: boolean // Optional
  "enableSatisfactionSurvey"?: boolean // Optional
  "satisfactionSurveyDelayMinutes"?: integer // Number of minutes after the last AI reply before the
survey appears, ranging from 1-60 minutes (Optional)
  "satisfactionSurveyPrompt"?: string // Custom survey title text; leave blank to use the frontend's
default localized text (Optional)
  "enableThemeModeToggle"?: boolean // Optional
  "enableDisplayFontSizeSwitch"?: boolean // Optional
  "defaultThemeMode"?:  // Optional
  {
  }
  "enableDownloadCitations"?: boolean // Optional
  "customDomain"?:  // Optional
  {
    "domain": string
  }
  "enableDisplayChatbotAvatar"?: boolean // Optional
  "enableDisplayChatbotName"?: boolean // Optional
  "buttonIcon"?: string (uri) // Optional
  "conversationStartersDisplayCount"?: integer // Optional
  "preChatFormEnabled"?: boolean // Optional
  "preChatFormFields"?: object // Optional
  "preChatFormTitle"?: object // Optional
  "preChatFormSubtitle"?: object // Optional
  "loadingDisplayMode"?:  // Waiting-experience style. `narrative` shows per-stage copy;
`brand_animation` plays the uploaded asset and hides every system narration line. Defaults to
`narrative`, which with no copy configured behaves exactly as before this field existed.

* `narrative` - Narrative copy
* `brand_animation` - Brand animation (Optional)
  {
  }
  "loadingStageCopyByLocale"?: object // Locale-keyed per-stage waiting copy, shaped {locale: {stage:
text}} where stage is one of LoadingStage. An absent locale or stage falls back to the built-in copy,
so a partially filled dict is valid and never blocks a reply. (Optional)
  "loadingLongWaitCopyByLocale"?: object // Locale-keyed line shown once the wait exceeds
`loading_long_wait_threshold_seconds`, shaped {locale: text}. Written in the brand character voice
for the animation mode, but applies to both modes. Empty means no long-wait line is shown. (Optional)
  "loadingLongWaitThresholdSeconds"?: integer // How long a single reply must be pending before the
long-wait copy appears. (Optional)
  "loadingAnimationUseSharedAsset"?: boolean // True (default) means every stage plays
`loading_animation_shared_asset_url`, so the admin only uploads once. False expands per-stage assets,
each falling back to the shared asset when its own slot is empty. (Optional)
  "loadingAnimationSharedAssetUrl"?: string (uri) // Optional
  "loadingAnimationAssetUrlsByStage"?: object // Shaped {stage: url} keyed by LoadingStage. Only
consulted when `loading_animation_use_shared_asset` is False; a missing stage falls back to the
shared asset. (Optional)
  "loadingTypingShowCopy"?: boolean // Only affects the first "typing" stage. True (default, the pre-
existing behavior) shows the typing-stage copy next to the pre-first-char animation/dot; False plays
only the animation with no text line. Thinking / analyzing / long-wait stages are unaffected.
(Optional)
  "toolCardRunningIconUrl"?: string (uri) // Optional
```

```
  "toolCardCompletedIconUrl"?: string (uri) // Optional
}
```

Example Request Values

```
{
  "avatar": "https://example.com/file.jpg",
  "logo": "https://example.com/file.jpg",
  "description": "Example string",
  "cover": "https://example.com/file.jpg",
  "backUrl": "Example string",
  "isActive": true,
  "theme": {
    "primaryColor": "Example string",
    "navbarTextColor": "Example string",
    "conversationBackgroundColor": "Example string",
    "chatbotMessageTextColor": "Example string",
    "userMessageTextColor": "Example string",
    "chatbotMessageBackgroundColor": "Example string",
    "userMessageBackgroundColor": "Example string",
    "chatbotMessageBackgroundShadowEnabled": true,
    "userMessageBackgroundShadowEnabled": true,
    "chatbotMessageGradientEnabled": true,
    "userMessageGradientEnabled": true
  },
  "darkTheme": {
    "primaryColor": "Example string",
    "navbarTextColor": "Example string",
    "conversationBackgroundColor": "Example string",
    "chatbotMessageTextColor": "Example string",
    "userMessageTextColor": "Example string",
    "chatbotMessageBackgroundColor": "Example string",
    "userMessageBackgroundColor": "Example string",
    "chatbotMessageBackgroundShadowEnabled": true,
    "userMessageBackgroundShadowEnabled": true,
    "chatbotMessageGradientEnabled": true,
    "userMessageGradientEnabled": true
  },
  "enableFileUpload": true,
  "enableDisplayCitations": true,
  "toolDisplayMode": "full",
  "enableAskOptionButtons": true,
  "enableConversationHandoff": true,
  "enableDisplayContextUsage": true,
  "enableDisplayThinking": true,
  "enableUserThinkingControl": true,
  "enableDisplayQueryMetadata": true,
  "enableDisplayHookMarkers": true,
  "hookMarkerTextInputModify": "Example string",
  "hookMarkerTextOutputModify": "Example string",
  "hookMarkerTextInputBlock": "Example string",
  "hookMarkerTextOutputBlock": "Example string",
  "enableShareConversation": true,
  "enableLocation": true,
  "enableShowPoweredBy": true,
  "poweredByLogo": "https://example.com/file.jpg",
  "enableAnonymous": true,
  "enableDisplayPreviousConversation": true,
```

```
  "enableDisplayConversationHistory": true,
  "enableConversationTimer": true,
  "conversationTimerDuration": 123,
  "enableAutoNewConversationOnTimeout": true,
  "enableSatisfactionSurvey": true,
  "satisfactionSurveyDelayMinutes": 123,
  "satisfactionSurveyPrompt": "Example string",
  "enableThemeModeToggle": true,
  "enableDisplayFontSizeSwitch": true,
  "defaultThemeMode": {},
  "enableDownloadCitations": true,
  "customDomain": {
    "domain": "Example string"
  },
  "enableDisplayChatbotAvatar": true,
  "enableDisplayChatbotName": true,
  "buttonIcon": "https://example.com/file.jpg",
  "conversationStartersDisplayCount": 123,
  "preChatFormEnabled": true,
  "preChatFormFields": null,
  "preChatFormTitle": null,
  "preChatFormSubtitle": null,
  "loadingDisplayMode": {},
  "loadingStageCopyByLocale": null,
  "loadingLongWaitCopyByLocale": null,
  "loadingLongWaitThresholdSeconds": 123,
  "loadingAnimationUseSharedAsset": true,
  "loadingAnimationSharedAssetUrl": "https://example.com/file.jpg",
  "loadingAnimationAssetUrlsByStage": null,
  "loadingTypingShowCopy": true,
  "toolCardRunningIconUrl": "https://example.com/file.jpg",
  "toolCardCompletedIconUrl": "https://example.com/file.jpg"
}
```


Code Examples

Shell/Bash

```
# API call example (Shell)
curl -X PUT "https://api.maiagent.ai/api/v1/web-chats/550e8400-e29b-41d4-a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "avatar": "https://example.com/file.jpg",
    "logo": "https://example.com/file.jpg",
    "description": "Example string",
    "cover": "https://example.com/file.jpg",
    "backUrl": "Example string",
    "isActive": true,
    "theme": {
      "primaryColor": "Example string",
      "navbarTextColor": "Example string",
      "conversationBackgroundColor": "Example string",
      "chatbotMessageTextColor": "Example string",
      "userMessageTextColor": "Example string",
      "chatbotMessageBackgroundColor": "Example string",
      "userMessageBackgroundColor": "Example string",
      "chatbotMessageBackgroundShadowEnabled": true,
      "userMessageBackgroundShadowEnabled": true,
      "chatbotMessageGradientEnabled": true,
      "userMessageGradientEnabled": true
    },
    "darkTheme": {
      "primaryColor": "Example string",
      "navbarTextColor": "Example string",
      "conversationBackgroundColor": "Example string",
      "chatbotMessageTextColor": "Example string",
      "userMessageTextColor": "Example string",
      "chatbotMessageBackgroundColor": "Example string",
      "userMessageBackgroundColor": "Example string",
      "chatbotMessageBackgroundShadowEnabled": true,
      "userMessageBackgroundShadowEnabled": true,
      "chatbotMessageGradientEnabled": true,
      "userMessageGradientEnabled": true
    },
    "enableFileUpload": true,
    "enableDisplayCitations": true,
    "toolDisplayMode": "full",
    "enableAskOptionButtons": true,
    "enableConversationHandoff": true,
    "enableDisplayContextUsage": true,
    "enableDisplayThinking": true,
    "enableUserThinkingControl": true,
    "enableDisplayQueryMetadata": true,
    "enableDisplayHookMarkers": true,
    "hookMarkerTextInputModify": "Example string",
    "hookMarkerTextOutputModify": "Example string",
    "hookMarkerTextInputBlock": "Example string",
    "hookMarkerTextOutputBlock": "Example string",
```

```
    "enableShareConversation": true,
    "enableLocation": true,
    "enableShowPoweredBy": true,
    "poweredByLogo": "https://example.com/file.jpg",
    "enableAnonymous": true,
    "enableDisplayPreviousConversation": true,
    "enableDisplayConversationHistory": true,
    "enableConversationTimer": true,
    "conversationTimerDuration": 123,
    "enableAutoNewConversationOnTimeout": true,
    "enableSatisfactionSurvey": true,
    "satisfactionSurveyDelayMinutes": 123,
    "satisfactionSurveyPrompt": "Example string",
    "enableThemeModeToggle": true,
    "enableDisplayFontSizeSwitch": true,
    "defaultThemeMode": {},
    "enableDownloadCitations": true,
    "customDomain": {
      "domain": "Example string"
    },
    "enableDisplayChatbotAvatar": true,
    "enableDisplayChatbotName": true,
    "buttonIcon": "https://example.com/file.jpg",
    "conversationStartersDisplayCount": 123,
    "preChatFormEnabled": true,
    "preChatFormFields": null,
    "preChatFormTitle": null,
    "preChatFormSubtitle": null,
    "loadingDisplayMode": {},
    "loadingStageCopyByLocale": null,
    "loadingLongWaitCopyByLocale": null,
    "loadingLongWaitThresholdSeconds": 123,
    "loadingAnimationUseSharedAsset": true,
    "loadingAnimationSharedAssetUrl": "https://example.com/file.jpg",
    "loadingAnimationAssetUrlsByStage": null,
    "loadingTypingShowCopy": true,
    "toolCardRunningIconUrl": "https://example.com/file.jpg",
    "toolCardCompletedIconUrl": "https://example.com/file.jpg"
  }'

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Configure request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// Request body (payload)
const data = {
    "avatar": "https://example.com/file.jpg",
    "logo": "https://example.com/file.jpg",
    "description": "Example string",
    "cover": "https://example.com/file.jpg",
    "backUrl": "Example string",
    "isActive": true,
    "theme": {
      "primaryColor": "Example string",
      "navbarTextColor": "Example string",
      "conversationBackgroundColor": "Example string",
      "chatbotMessageTextColor": "Example string",
      "userMessageTextColor": "Example string",
      "chatbotMessageBackgroundColor": "Example string",
      "userMessageBackgroundColor": "Example string",
      "chatbotMessageBackgroundShadowEnabled": true,
      "userMessageBackgroundShadowEnabled": true,
      "chatbotMessageGradientEnabled": true,
      "userMessageGradientEnabled": true
    },
    "darkTheme": {
      "primaryColor": "Example string",
      "navbarTextColor": "Example string",
      "conversationBackgroundColor": "Example string",
      "chatbotMessageTextColor": "Example string",
      "userMessageTextColor": "Example string",
      "chatbotMessageBackgroundColor": "Example string",
      "userMessageBackgroundColor": "Example string",
      "chatbotMessageBackgroundShadowEnabled": true,
      "userMessageBackgroundShadowEnabled": true,
      "chatbotMessageGradientEnabled": true,
      "userMessageGradientEnabled": true
    },
    "enableFileUpload": true,
    "enableDisplayCitations": true,
    "toolDisplayMode": "full",
    "enableAskOptionButtons": true,
    "enableConversationHandoff": true,
    "enableDisplayContextUsage": true,
    "enableDisplayThinking": true,
    "enableUserThinkingControl": true,
    "enableDisplayQueryMetadata": true,
    "enableDisplayHookMarkers": true,
```

```
    "hookMarkerTextInputModify": "Example string",
    "hookMarkerTextOutputModify": "Example string",
    "hookMarkerTextInputBlock": "Example string",
    "hookMarkerTextOutputBlock": "Example string",
    "enableShareConversation": true,
    "enableLocation": true,
    "enableShowPoweredBy": true,
    "poweredByLogo": "https://example.com/file.jpg",
    "enableAnonymous": true,
    "enableDisplayPreviousConversation": true,
    "enableDisplayConversationHistory": true,
    "enableConversationTimer": true,
    "conversationTimerDuration": 123,
    "enableAutoNewConversationOnTimeout": true,
    "enableSatisfactionSurvey": true,
    "satisfactionSurveyDelayMinutes": 123,
    "satisfactionSurveyPrompt": "Example string",
    "enableThemeModeToggle": true,
    "enableDisplayFontSizeSwitch": true,
    "defaultThemeMode": {},
    "enableDownloadCitations": true,
    "customDomain": {
      "domain": "Example string"
    },
    "enableDisplayChatbotAvatar": true,
    "enableDisplayChatbotName": true,
    "buttonIcon": "https://example.com/file.jpg",
    "conversationStartersDisplayCount": 123,
    "preChatFormEnabled": true,
    "preChatFormFields": null,
    "preChatFormTitle": null,
    "preChatFormSubtitle": null,
    "loadingDisplayMode": {},
    "loadingStageCopyByLocale": null,
    "loadingLongWaitCopyByLocale": null,
    "loadingLongWaitThresholdSeconds": 123,
    "loadingAnimationUseSharedAsset": true,
    "loadingAnimationSharedAssetUrl": "https://example.com/file.jpg",
    "loadingAnimationAssetUrlsByStage": null,
    "loadingTypingShowCopy": true,
    "toolCardRunningIconUrl": "https://example.com/file.jpg",
    "toolCardCompletedIconUrl": "https://example.com/file.jpg"
  };

axios.put("https://api.maiagent.ai/api/v1/web-chats/550e8400-e29b-41d4-a716-446655440000/",
data, config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request failed:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/web-chats/550e8400-e29b-41d4-a716-446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# Request body (payload)
data = {
    "avatar": "https://example.com/file.jpg",
    "logo": "https://example.com/file.jpg",
    "description": "Example string",
    "cover": "https://example.com/file.jpg",
    "backUrl": "Example string",
    "isActive": True,
    "theme": {
        "primaryColor": "Example string",
        "navbarTextColor": "Example string",
        "conversationBackgroundColor": "Example string",
        "chatbotMessageTextColor": "Example string",
        "userMessageTextColor": "Example string",
        "chatbotMessageBackgroundColor": "Example string",
        "userMessageBackgroundColor": "Example string",
        "chatbotMessageBackgroundShadowEnabled": True,
        "userMessageBackgroundShadowEnabled": True,
        "chatbotMessageGradientEnabled": True,
        "userMessageGradientEnabled": True
    },
    "darkTheme": {
        "primaryColor": "Example string",
        "navbarTextColor": "Example string",
        "conversationBackgroundColor": "Example string",
        "chatbotMessageTextColor": "Example string",
        "userMessageTextColor": "Example string",
        "chatbotMessageBackgroundColor": "Example string",
        "userMessageBackgroundColor": "Example string",
        "chatbotMessageBackgroundShadowEnabled": True,
        "userMessageBackgroundShadowEnabled": True,
        "chatbotMessageGradientEnabled": True,
        "userMessageGradientEnabled": True
    },
    "enableFileUpload": True,
    "enableDisplayCitations": True,
    "toolDisplayMode": "full",
    "enableAskOptionButtons": True,
    "enableConversationHandoff": True,
    "enableDisplayContextUsage": True,
    "enableDisplayThinking": True,
    "enableUserThinkingControl": True,
    "enableDisplayQueryMetadata": True,
    "enableDisplayHookMarkers": True,
    "hookMarkerTextInputModify": "Example string",
    "hookMarkerTextOutputModify": "Example string",
```

```
    "hookMarkerTextInputBlock": "Example string",
    "hookMarkerTextOutputBlock": "Example string",
    "enableShareConversation": True,
    "enableLocation": True,
    "enableShowPoweredBy": True,
    "poweredByLogo": "https://example.com/file.jpg",
    "enableAnonymous": True,
    "enableDisplayPreviousConversation": True,
    "enableDisplayConversationHistory": True,
    "enableConversationTimer": True,
    "conversationTimerDuration": 123,
    "enableAutoNewConversationOnTimeout": True,
    "enableSatisfactionSurvey": True,
    "satisfactionSurveyDelayMinutes": 123,
    "satisfactionSurveyPrompt": "Example string",
    "enableThemeModeToggle": True,
    "enableDisplayFontSizeSwitch": True,
    "defaultThemeMode": {},
    "enableDownloadCitations": True,
    "customDomain": {
        "domain": "Example string"
    },
    "enableDisplayChatbotAvatar": True,
    "enableDisplayChatbotName": True,
    "buttonIcon": "https://example.com/file.jpg",
    "conversationStartersDisplayCount": 123,
    "preChatFormEnabled": True,
    "preChatFormFields": None,
    "preChatFormTitle": None,
    "preChatFormSubtitle": None,
    "loadingDisplayMode": {},
    "loadingStageCopyByLocale": None,
    "loadingLongWaitCopyByLocale": None,
    "loadingLongWaitThresholdSeconds": 123,
    "loadingAnimationUseSharedAsset": True,
    "loadingAnimationSharedAssetUrl": "https://example.com/file.jpg",
    "loadingAnimationAssetUrlsByStage": None,
    "loadingTypingShowCopy": True,
    "toolCardRunningIconUrl": "https://example.com/file.jpg",
    "toolCardCompletedIconUrl": "https://example.com/file.jpg"
}

response = requests.put(url, json=data, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request failed:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->put("https://api.maiagent.ai/api/v1/web-chats/550e8400-e29b-41d4-a716-446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'avatar' => 'https://example.com/file.jpg',
            'logo' => 'https://example.com/file.jpg',
            'description' => 'Example string',
            'cover' => 'https://example.com/file.jpg',
            'backUrl' => 'Example string',
            'isActive' => true,
            'theme' => [
                'primaryColor' => 'Example string',
                'navbarTextColor' => 'Example string',
                'conversationBackgroundColor' => 'Example string',
                'chatbotMessageTextColor' => 'Example string',
                'userMessageTextColor' => 'Example string',
                'chatbotMessageBackgroundColor' => 'Example string',
                'userMessageBackgroundColor' => 'Example string',
                'chatbotMessageBackgroundShadowEnabled' => true,
                'userMessageBackgroundShadowEnabled' => true,
                'chatbotMessageGradientEnabled' => true,
                'userMessageGradientEnabled' => true
            ],
            'darkTheme' => [
                'primaryColor' => 'Example string',
                'navbarTextColor' => 'Example string',
                'conversationBackgroundColor' => 'Example string',
                'chatbotMessageTextColor' => 'Example string',
                'userMessageTextColor' => 'Example string',
                'chatbotMessageBackgroundColor' => 'Example string',
                'userMessageBackgroundColor' => 'Example string',
                'chatbotMessageBackgroundShadowEnabled' => true,
                'userMessageBackgroundShadowEnabled' => true,
                'chatbotMessageGradientEnabled' => true,
                'userMessageGradientEnabled' => true
            ],
            'enableFileUpload' => true,
            'enableDisplayCitations' => true,
            'toolDisplayMode' => 'full',
            'enableAskOptionButtons' => true,
            'enableConversationHandoff' => true,
            'enableDisplayContextUsage' => true,
            'enableDisplayThinking' => true,
            'enableUserThinkingControl' => true,
            'enableDisplayQueryMetadata' => true,
```

```
            'enableDisplayHookMarkers' => true,
            'hookMarkerTextInputModify' => 'Example string',
            'hookMarkerTextOutputModify' => 'Example string',
            'hookMarkerTextInputBlock' => 'Example string',
            'hookMarkerTextOutputBlock' => 'Example string',
            'enableShareConversation' => true,
            'enableLocation' => true,
            'enableShowPoweredBy' => true,
            'poweredByLogo' => 'https://example.com/file.jpg',
            'enableAnonymous' => true,
            'enableDisplayPreviousConversation' => true,
            'enableDisplayConversationHistory' => true,
            'enableConversationTimer' => true,
            'conversationTimerDuration' => 123,
            'enableAutoNewConversationOnTimeout' => true,
            'enableSatisfactionSurvey' => true,
            'satisfactionSurveyDelayMinutes' => 123,
            'satisfactionSurveyPrompt' => 'Example string',
            'enableThemeModeToggle' => true,
            'enableDisplayFontSizeSwitch' => true,
            'defaultThemeMode' => new \stdClass(),
            'enableDownloadCitations' => true,
            'customDomain' => [
                'domain' => 'Example string'
            ],
            'enableDisplayChatbotAvatar' => true,
            'enableDisplayChatbotName' => true,
            'buttonIcon' => 'https://example.com/file.jpg',
            'conversationStartersDisplayCount' => 123,
            'preChatFormEnabled' => true,
            'preChatFormFields' => null,
            'preChatFormTitle' => null,
            'preChatFormSubtitle' => null,
            'loadingDisplayMode' => new \stdClass(),
            'loadingStageCopyByLocale' => null,
            'loadingLongWaitCopyByLocale' => null,
            'loadingLongWaitThresholdSeconds' => 123,
            'loadingAnimationUseSharedAsset' => true,
            'loadingAnimationSharedAssetUrl' => 'https://example.com/file.jpg',
            'loadingAnimationAssetUrlsByStage' => null,
            'loadingTypingShowCopy' => true,
            'toolCardRunningIconUrl' => 'https://example.com/file.jpg',
            'toolCardCompletedIconUrl' => 'https://example.com/file.jpg'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request failed: ' . $e->getMessage();
}
?>
```

Response Body

Status code: `200`

Example Response Schema

```
{
  "id": string (uuid)
  "name": string
  "avatar"?: string (uri) // Optional
  "logo"?: string (uri) // Optional
  "description"?: string // Optional
  "cover"?: string (uri) // Optional
  "backUrl"?: string // Optional
  "isActive"?: boolean // Optional
  "enableSpeech": boolean
  "displayConversationStarters": [
    string
  ]
  "theme": {
  {
    "primaryColor"?: string // Optional
    "navbarTextColor"?: string // Optional
    "conversationBackgroundColor"?: string // Optional
    "chatbotMessageTextColor"?: string // Optional
    "userMessageTextColor"?: string // Optional
    "chatbotMessageBackgroundColor"?: string // Optional
    "userMessageBackgroundColor"?: string // Optional
    "chatbotMessageBackgroundShadowEnabled"?: boolean // Optional
    "userMessageBackgroundShadowEnabled"?: boolean // Optional
    "chatbotMessageGradientEnabled"?: boolean // Optional
    "userMessageGradientEnabled"?: boolean // Optional
  }
  }
  "darkTheme": {
  {
    "primaryColor"?: string // Optional
    "navbarTextColor"?: string // Optional
    "conversationBackgroundColor"?: string // Optional
    "chatbotMessageTextColor"?: string // Optional
    "userMessageTextColor"?: string // Optional
    "chatbotMessageBackgroundColor"?: string // Optional
    "userMessageBackgroundColor"?: string // Optional
    "chatbotMessageBackgroundShadowEnabled"?: boolean // Optional
    "userMessageBackgroundShadowEnabled"?: boolean // Optional
    "chatbotMessageGradientEnabled"?: boolean // Optional
    "userMessageGradientEnabled"?: boolean // Optional
  }
  }
  "enableFileUpload"?: boolean // Optional
  "enableDisplayCitations"?: boolean // Optional
  "toolDisplayMode"?: string (enum: full, compact, hidden) // * `full` - Full
* `compact` - Compact
* `hidden` - Hidden (Optional)
  "enableAskOptionButtons"?: boolean // When enabled, ask_user_question options appear as a row of
buttons above the input field, which remains usable. When disabled, the existing overlay panel is
retained. This gradual rollout switch can be disabled at any time to revert the behavior. (Optional)
```

```
  "enableConversationHandoff"?: boolean // When enabled, this conversation platform's webchat
displays the handoff UI (notification bar, summary card, and resume button) and registers handoff
tools. It remains subject to the global handoff switch in system settings (when the global switch is
off, handoff is disabled everywhere). MaiGPT always displays the UI regardless of this switch. The
context usage percentage bar at the bottom is controlled separately by “Display context usage”.
Disabled by default, so customer-facing webchat displays no handoff UI. This gradual rollout switch
reverts the behavior immediately when disabled, without a version rollback. (Optional)
  "enableDisplayContextUsage"?: boolean // When enabled, this conversation platform's webchat
displays a context usage percentage bar below the input field. It is independent of conversation
handoff: handoff switches (including the global handoff switch) do not affect it, and it does not
affect the handoff notification bar. MaiGPT always displays the bar regardless of this switch.
Disabled by default; disabling it immediately reverts the behavior without a version rollback.
(Optional)
  "enableDisplayThinking"?: boolean // Optional
  "enableUserThinkingControl"?: boolean // Optional
  "enableDisplayQueryMetadata"?: boolean // Optional
  "enableDisplayHookMarkers"?: boolean // Optional
  "hookMarkerTextInputModify"?: string // Optional
  "hookMarkerTextOutputModify"?: string // Optional
  "hookMarkerTextInputBlock"?: string // Optional
  "hookMarkerTextOutputBlock"?: string // Optional
  "enableShareConversation"?: boolean // Optional
  "enableLocation"?: boolean // Optional
  "enableShowPoweredBy"?: boolean // Optional
  "poweredByLogo"?: string (uri) // Optional
  "enableAnonymous"?: boolean // Optional
  "enableDisplayPreviousConversation"?: boolean // Optional
  "enableDisplayConversationHistory"?: boolean // Optional
  "enableConversationTimer"?: boolean // Optional
  "conversationTimerDuration"?: integer // Timer timeout duration, ranging from 3 to 60 minutes
(Optional)
  "enableAutoNewConversationOnTimeout"?: boolean // Optional
  "enableSatisfactionSurvey"?: boolean // Optional
  "satisfactionSurveyDelayMinutes"?: integer // Number of minutes after the last AI reply before the
survey appears, ranging from 1 to 60 minutes (Optional)
  "satisfactionSurveyPrompt"?: string // Custom survey title text; leave empty to use the frontend's
default localized text (Optional)
  "accessType":
  {
  }
  "enableThemeModeToggle"?: boolean // Optional
  "enableDisplayFontSizeSwitch"?: boolean // Optional
  "defaultThemeMode"?:  // Optional
  {
  }
  "enableDownloadCitations"?: boolean // Optional
  "customDomain"?:  // Optional
  {
    "id": string (uuid)
    "domain": string
    "status":
    {
    }
  }
  "enableDisplayChatbotAvatar"?: boolean // Optional
  "enableDisplayChatbotName"?: boolean // Optional
  "buttonIcon"?: string (uri) // Optional
  "enableCodeInterpreter": boolean // Read enable_code_interpreter from the inbox's chatbot.
  "voiceAgentEnabled": boolean // Whether the bound chatbot has the voice agent turned on (read-only)
  "conversationStartersDisplayCount"?: integer // Optional
```

```
  "includeGreetingInContext": boolean // When enabled, the conversation greeting and the numbered
conversation starters (in configured order, unshuffled and untruncated) are injected into the LLM
context so the agent can resolve short replies like "1" to the matching starter option.
  "tools": [ // Expose chatbot tools to SDK for the tool_mask selector.

Name resolution prefers ``display_name`` (set on MCP tools, where
``name`` is null) and falls back to ``name`` for API tools where
``display_name`` is null. Tools missing both are skipped — SDK
should never show an unnamed tool to a contact. Quick Menu tools are
static input-bar UI, never an LLM tool, so masking one is meaningless.
    object
  ]
  "preChatFormEnabled"?: boolean // Optional
  "preChatFormFields"?: object // Optional
  "preChatFormTitle"?: object // Optional
  "preChatFormSubtitle"?: object // Optional
  "loadingDisplayMode"?:  // Waiting-experience style. `narrative` shows per-stage copy;
`brand_animation` plays the uploaded asset and hides every system narration line. Defaults to
`narrative`, which with no copy configured behaves exactly as before this field existed.

* `narrative` - Narrative copy
* `brand_animation` - Brand animation (Optional)
  {
  }
  "loadingStageCopyByLocale"?: object // Locale-keyed per-stage waiting copy, shaped {locale: {stage:
text}} where stage is one of LoadingStage. An absent locale or stage falls back to the built-in copy,
so a partially filled dict is valid and never blocks a reply. (Optional)
  "loadingLongWaitCopyByLocale"?: object // Locale-keyed line shown once the wait exceeds
`loading_long_wait_threshold_seconds`, shaped {locale: text}. Written in the brand character voice
for the animation mode, but applies to both modes. Empty means no long-wait line is shown. (Optional)
  "loadingLongWaitThresholdSeconds"?: integer // How long a single reply must be pending before the
long-wait copy appears. (Optional)
  "loadingAnimationUseSharedAsset"?: boolean // True (default) means every stage plays
`loading_animation_shared_asset_url`, so the admin only uploads once. False expands per-stage assets,
each falling back to the shared asset when its own slot is empty. (Optional)
  "loadingAnimationSharedAssetUrl"?: string (uri) // Optional
  "loadingAnimationAssetUrlsByStage"?: object // Shaped {stage: url} keyed by LoadingStage. Only
consulted when `loading_animation_use_shared_asset` is False; a missing stage falls back to the
shared asset. (Optional)
  "loadingTypingShowCopy"?: boolean // Only affects the first "typing" stage. True (default, the pre-
existing behavior) shows the typing-stage copy next to the pre-first-char animation/dot; False plays
only the animation with no text line. Thinking / analyzing / long-wait stages are unaffected.
(Optional)
  "toolCardRunningIconUrl"?: string (uri) // Optional
  "toolCardCompletedIconUrl"?: string (uri) // Optional
  "inbox": object
  "quickMenu": object // Mounted Quick Menu Agent UI config for the web chat input bar; null when
absent (read-only)
}
```

Example Response Values

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "name": "Response string",
  "avatar": "https://example.com/file.jpg",
  "logo": "https://example.com/file.jpg",
  "description": "Response string",
```

```
  "cover": "https://example.com/file.jpg",
  "backUrl": "Response string",
  "isActive": false,
  "enableSpeech": false,
  "displayConversationStarters": [
    "Response string"
  ],
  "theme": {
    "primaryColor": "Response string",
    "navbarTextColor": "Response string",
    "conversationBackgroundColor": "Response string",
    "chatbotMessageTextColor": "Response string",
    "userMessageTextColor": "Response string",
    "chatbotMessageBackgroundColor": "Response string",
    "userMessageBackgroundColor": "Response string",
    "chatbotMessageBackgroundShadowEnabled": false,
    "userMessageBackgroundShadowEnabled": false,
    "chatbotMessageGradientEnabled": false,
    "userMessageGradientEnabled": false
  },
  "darkTheme": {
    "primaryColor": "Response string",
    "navbarTextColor": "Response string",
    "conversationBackgroundColor": "Response string",
    "chatbotMessageTextColor": "Response string",
    "userMessageTextColor": "Response string",
    "chatbotMessageBackgroundColor": "Response string",
    "userMessageBackgroundColor": "Response string",
    "chatbotMessageBackgroundShadowEnabled": false,
    "userMessageBackgroundShadowEnabled": false,
    "chatbotMessageGradientEnabled": false,
    "userMessageGradientEnabled": false
  },
  "enableFileUpload": false,
  "enableDisplayCitations": false,
  "toolDisplayMode": "full",
  "enableAskOptionButtons": false,
  "enableConversationHandoff": false,
  "enableDisplayContextUsage": false,
  "enableDisplayThinking": false,
  "enableUserThinkingControl": false,
  "enableDisplayQueryMetadata": false,
  "enableDisplayHookMarkers": false,
  "hookMarkerTextInputModify": "Response string",
  "hookMarkerTextOutputModify": "Response string",
  "hookMarkerTextInputBlock": "Response string",
  "hookMarkerTextOutputBlock": "Response string",
  "enableShareConversation": false,
  "enableLocation": false,
  "enableShowPoweredBy": false,
  "poweredByLogo": "https://example.com/file.jpg",
  "enableAnonymous": false,
  "enableDisplayPreviousConversation": false,
  "enableDisplayConversationHistory": false,
  "enableConversationTimer": false,
  "conversationTimerDuration": 456,
  "enableAutoNewConversationOnTimeout": false,
  "enableSatisfactionSurvey": false,
  "satisfactionSurveyDelayMinutes": 456,
  "satisfactionSurveyPrompt": "Response string",
```

```
  "accessType": {},
  "enableThemeModeToggle": false,
  "enableDisplayFontSizeSwitch": false,
  "defaultThemeMode": {},
  "enableDownloadCitations": false,
  "customDomain": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "domain": "Response string",
    "status": {}
  },
  "enableDisplayChatbotAvatar": false,
  "enableDisplayChatbotName": false,
  "buttonIcon": "https://example.com/file.jpg",
  "enableCodeInterpreter": false,
  "voiceAgentEnabled": false,
  "conversationStartersDisplayCount": 456,
  "includeGreetingInContext": false,
  "tools": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "Example Response Name",
      "description": "Example Response Description"
    }
  ],
  "preChatFormEnabled": false,
  "preChatFormFields": null,
  "preChatFormTitle": null,
  "preChatFormSubtitle": null,
  "loadingDisplayMode": {},
  "loadingStageCopyByLocale": null,
  "loadingLongWaitCopyByLocale": null,
  "loadingLongWaitThresholdSeconds": 456,
  "loadingAnimationUseSharedAsset": false,
  "loadingAnimationSharedAssetUrl": "https://example.com/file.jpg",
  "loadingAnimationAssetUrlsByStage": null,
  "loadingTypingShowCopy": false,
  "toolCardRunningIconUrl": "https://example.com/file.jpg",
  "toolCardCompletedIconUrl": "https://example.com/file.jpg",
  "inbox": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Example Response Name",
    "description": "Example Response Description"
  },
  "quickMenu": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Example Response Name",
    "description": "Example Response Description"
  }
}
```


Partially Update Web Chat

PATCH `/api/v1/web-chats/{id}`

Parameters

Parameter Name	Required	Type	Description
`id`	V	string	A UUID string identifying this web chat.

Request Body

Request Parameters

Field	Type	Required	Description
avatar	string (uri)	No	
logo	string (uri)	No	
description	string	No	
cover	string (uri)	No	
backUrl	string	No	
isActive	boolean	No	
theme	object	No	
theme.primaryColor	string	No	
theme.navbarTextColor	string	No	
theme.conversationBackgroundColor	string	No	
theme.chatbotMessageTextColor	string	No	
theme.userMessageTextColor	string	No	
theme.chatbotMessageBackgroundColor	string	No	
theme.userMessageBackgroundColor	string	No	
theme.chatbotMessageBackgroundShadowEnabled	boolean	No	
theme.userMessageBackgroundShadowEnabled	boolean	No	
theme.chatbotMessageGradientEnabled	boolean	No	
theme.userMessageGradientEnabled	boolean	No	
darkTheme	object	No	
darkTheme.primaryColor	string	No	
darkTheme.navbarTextColor	string	No	
darkTheme.conversationBackgroundColor	string	No	
darkTheme.chatbotMessageTextColor	string	No	
darkTheme.userMessageTextColor	string	No	

Field	Type	Required	Description
darkTheme.chatbotMessageBackgroundColor	string	No	
darkTheme.userMessageBackgroundColor	string	No	
darkTheme.chatbotMessageBackgroundShadowEnabled	boolean	No	
darkTheme.userMessageBackgroundShadowEnabled	boolean	No	
darkTheme.chatbotMessageGradientEnabled	boolean	No	
darkTheme.userMessageGradientEnabled	boolean	No	
enableFileUpload	boolean	No	
enableDisplayCitations	boolean	No	
toolDisplayMode	string (enum: full, compact, hidden)	No	`full` : Full ; `compact` : Compact ; `hidden` : Hidden;
enableAskOptionButtons	boolean	No	When enabled, ask_user_question options appear as a row of buttons above the input box, which remains usable. When disabled, the existing overlay panel is retained. This rollout toggle can be disabled at any time to revert the behavior.
enableConversationHandoff	boolean	No	When enabled, this conversation platform’ s webchat displays the handoff UI (notification bar, summary card, and continue button) and registers handoff tools. It remains subject to the global handoff toggle in system settings: disabling the global toggle disables handoff everywhere. MaiGPT always displays it regardless of this platform toggle. The context usage percentage bar at the bottom is controlled separately by “Display context usage”. Disabled by default, so customer-facing webchats show no handoff UI. This rollout toggle can be disabled to revert the behavior without rolling back the release.
enableDisplayContextUsage	boolean	No	When enabled, this conversation platform’ s webchat displays a context usage percentage bar below the input box. This is independent of conversation handoff: handoff toggles, including the global handoff toggle, do not affect it, and it does not affect the handoff notification bar. MaiGPT always displays it regardless of this toggle. Disabled by default; disable it to revert the behavior without rolling back the release.
enableDisplayThinking	boolean	No	

Field	Type	Required	Description
enableUserThinkingControl	boolean	No	
enableDisplayQueryMetadata	boolean	No	
enableDisplayHookMarkers	boolean	No	
hookMarkerTextInputModify	string	No	
hookMarkerTextOutputModify	string	No	
hookMarkerTextInputBlock	string	No	
hookMarkerTextOutputBlock	string	No	
enableShareConversation	boolean	No	
enableLocation	boolean	No	
enableShowPoweredBy	boolean	No	
poweredByLogo	string (uri)	No	
enableAnonymous	boolean	No	
enableDisplayPreviousConversation	boolean	No	
enableDisplayConversationHistory	boolean	No	
enableConversationTimer	boolean	No	
conversationTimerDuration	integer	No	Timer timeout duration, ranging from 3-60 minutes
enableAutoNewConversationOnTimeout	boolean	No	
enableSatisfactionSurvey	boolean	No	
satisfactionSurveyDelayMinutes	integer	No	Number of minutes after the last AI reply before the survey appears, ranging from 1-60 minutes
satisfactionSurveyPrompt	string	No	Custom survey title text; leave blank to use the frontend’ s default localized text
enableThemeModeToggle	boolean	No	
enableDisplayFontSizeSwitch	boolean	No	
defaultThemeMode	object	No	
enableDownloadCitations	boolean	No	
customDomain	object (contains 3 properties: id, domain, status)	No	
customDomain.domain	string	Yes	
enableDisplayChatbotAvatar	boolean	No	
enableDisplayChatbotName	boolean	No	

Field	Type	Required	Description
buttonIcon	string (uri)	No	
conversationStartersDisplayCount	integer	No	
preChatFormEnabled	boolean	No	
preChatFormFields	object	No	
preChatFormTitle	object	No	
preChatFormSubtitle	object	No	
loadingDisplayMode	object	No	Waiting-experience style. `narrative` shows per-stage copy; `brand_animation` plays the uploaded asset and hides every system narration line. Defaults to `narrative` , which with no copy configured beh...
loadingStageCopyByLocale	object	No	Locale-keyed per-stage waiting copy, shaped {locale: {stage: text}} where stage is one of LoadingStage. An absent locale or stage falls back to the built-in copy, so a partially filled dict is valid a...
loadingLongWaitCopyByLocale	object	No	Locale-keyed line shown once the wait exceeds `loading_long_wait_threshold_seconds` , shaped {locale: text}. Written in the brand character voice for the animation mode, but applies to both modes. Empt...
loadingLongWaitThresholdSeconds	integer	No	How long a single reply must be pending before the long-wait copy appears.
loadingAnimationUseSharedAsset	boolean	No	True (default) means every stage plays `loading_animation_shared_asset_url` , so the admin only uploads once. False expands per-stage assets, each falling back to the shared asset when its own slot is ...
loadingAnimationSharedAssetUrl	string (uri)	No	
loadingAnimationAssetUrlsByStage	object	No	Shaped {stage: url} keyed by LoadingStage. Only consulted when `loading_animation_use_shared_asset` is False; a missing stage falls back to the shared asset.
loadingTypingShowCopy	boolean	No	Only affects the first "typing" stage. True (default, the pre-existing behavior) shows the typing-stage copy next to the pre-first-char animation/dot; False plays only the animation with no text line....
toolCardRunningIconUrl	string (uri)	No	
toolCardCompletedIconUrl	string (uri)	No	

Request Schema Example

```
{
  "avatar"?: string (uri) // Optional
  "logo"?: string (uri) // Optional
  "description"?: string // Optional
  "cover"?: string (uri) // Optional
  "backUrl"?: string // Optional
  "isActive"?: boolean // Optional
  "theme"?: { // Optional
  {
    "primaryColor"?: string // Optional
    "navbarTextColor"?: string // Optional
    "conversationBackgroundColor"?: string // Optional
    "chatbotMessageTextColor"?: string // Optional
    "userMessageTextColor"?: string // Optional
    "chatbotMessageBackgroundColor"?: string // Optional
    "userMessageBackgroundColor"?: string // Optional
    "chatbotMessageBackgroundShadowEnabled"?: boolean // Optional
    "userMessageBackgroundShadowEnabled"?: boolean // Optional
    "chatbotMessageGradientEnabled"?: boolean // Optional
    "userMessageGradientEnabled"?: boolean // Optional
  }
  }
  "darkTheme"?: { // Optional
  {
    "primaryColor"?: string // Optional
    "navbarTextColor"?: string // Optional
    "conversationBackgroundColor"?: string // Optional
    "chatbotMessageTextColor"?: string // Optional
    "userMessageTextColor"?: string // Optional
    "chatbotMessageBackgroundColor"?: string // Optional
    "userMessageBackgroundColor"?: string // Optional
    "chatbotMessageBackgroundShadowEnabled"?: boolean // Optional
    "userMessageBackgroundShadowEnabled"?: boolean // Optional
    "chatbotMessageGradientEnabled"?: boolean // Optional
    "userMessageGradientEnabled"?: boolean // Optional
  }
  }
  "enableFileUpload"?: boolean // Optional
  "enableDisplayCitations"?: boolean // Optional
  "toolDisplayMode"?: string (enum: full, compact, hidden) // * `full` - Full
* `compact` - Compact
* `hidden` - Hidden (Optional)
  "enableAskOptionButtons"?: boolean // When enabled, ask_user_question options appear as a row of
buttons above the input box, which remains usable. When disabled, the existing overlay panel is
retained. This rollout toggle can be disabled at any time to revert the behavior. (Optional)
  "enableConversationHandoff"?: boolean // When enabled, this conversation platform’s webchat
displays the handoff UI (notification bar, summary card, and continue button) and registers handoff
tools. It remains subject to the global handoff toggle in system settings: disabling the global
toggle disables handoff everywhere. MaiGPT always displays it regardless of this platform toggle. The
context usage percentage bar at the bottom is controlled separately by “Display context usage”.
Disabled by default, so customer-facing webchats show no handoff UI. This rollout toggle can be
disabled to revert the behavior without rolling back the release. (Optional)
  "enableDisplayContextUsage"?: boolean // When enabled, this conversation platform’s webchat
displays a context usage percentage bar below the input box. This is independent of conversation
handoff: handoff toggles, including the global handoff toggle, do not affect it, and it does not
affect the handoff notification bar. MaiGPT always displays it regardless of this toggle. Disabled by
default; disable it to revert the behavior without rolling back the release. (Optional)
  "enableDisplayThinking"?: boolean // Optional
  "enableUserThinkingControl"?: boolean // Optional
```

```
  "enableDisplayQueryMetadata"?: boolean // Optional
  "enableDisplayHookMarkers"?: boolean // Optional
  "hookMarkerTextInputModify"?: string // Optional
  "hookMarkerTextOutputModify"?: string // Optional
  "hookMarkerTextInputBlock"?: string // Optional
  "hookMarkerTextOutputBlock"?: string // Optional
  "enableShareConversation"?: boolean // Optional
  "enableLocation"?: boolean // Optional
  "enableShowPoweredBy"?: boolean // Optional
  "poweredByLogo"?: string (uri) // Optional
  "enableAnonymous"?: boolean // Optional
  "enableDisplayPreviousConversation"?: boolean // Optional
  "enableDisplayConversationHistory"?: boolean // Optional
  "enableConversationTimer"?: boolean // Optional
  "conversationTimerDuration"?: integer // Timer timeout duration, ranging from 3-60 minutes
(Optional)
  "enableAutoNewConversationOnTimeout"?: boolean // Optional
  "enableSatisfactionSurvey"?: boolean // Optional
  "satisfactionSurveyDelayMinutes"?: integer // Number of minutes after the last AI reply before the
survey appears, ranging from 1-60 minutes (Optional)
  "satisfactionSurveyPrompt"?: string // Custom survey title text; leave blank to use the frontend's
default localized text (Optional)
  "enableThemeModeToggle"?: boolean // Optional
  "enableDisplayFontSizeSwitch"?: boolean // Optional
  "defaultThemeMode"?:  // Optional
  {
  }
  "enableDownloadCitations"?: boolean // Optional
  "customDomain"?:  // Optional
  {
    "domain": string
  }
  "enableDisplayChatbotAvatar"?: boolean // Optional
  "enableDisplayChatbotName"?: boolean // Optional
  "buttonIcon"?: string (uri) // Optional
  "conversationStartersDisplayCount"?: integer // Optional
  "preChatFormEnabled"?: boolean // Optional
  "preChatFormFields"?: object // Optional
  "preChatFormTitle"?: object // Optional
  "preChatFormSubtitle"?: object // Optional
  "loadingDisplayMode"?:  // Waiting-experience style. `narrative` shows per-stage copy;
`brand_animation` plays the uploaded asset and hides every system narration line. Defaults to
`narrative`, which with no copy configured behaves exactly as before this field existed.

* `narrative` - Narrative copy
* `brand_animation` - Brand animation (Optional)
  {
  }
  "loadingStageCopyByLocale"?: object // Locale-keyed per-stage waiting copy, shaped {locale: {stage:
text}} where stage is one of LoadingStage. An absent locale or stage falls back to the built-in copy,
so a partially filled dict is valid and never blocks a reply. (Optional)
  "loadingLongWaitCopyByLocale"?: object // Locale-keyed line shown once the wait exceeds
`loading_long_wait_threshold_seconds`, shaped {locale: text}. Written in the brand character voice
for the animation mode, but applies to both modes. Empty means no long-wait line is shown. (Optional)
  "loadingLongWaitThresholdSeconds"?: integer // How long a single reply must be pending before the
long-wait copy appears. (Optional)
  "loadingAnimationUseSharedAsset"?: boolean // True (default) means every stage plays
`loading_animation_shared_asset_url`, so the admin only uploads once. False expands per-stage assets,
each falling back to the shared asset when its own slot is empty. (Optional)
  "loadingAnimationSharedAssetUrl"?: string (uri) // Optional
```

```
  "loadingAnimationAssetUrlsByStage"?: object // Shaped {stage: url} keyed by LoadingStage. Only consulted when `loading_animation_use_shared_asset` is False; a missing stage falls back to the shared asset. (Optional)
  "loadingTypingShowCopy"?: boolean // Only affects the first "typing" stage. True (default, the pre-existing behavior) shows the typing-stage copy next to the pre-first-char animation/dot; False plays only the animation with no text line. Thinking / analyzing / long-wait stages are unaffected. (Optional)
  "toolCardRunningIconUrl"?: string (uri) // Optional
  "toolCardCompletedIconUrl"?: string (uri) // Optional
}
```

Example Request Values

```
{
  "avatar": "https://example.com/file.jpg",
  "logo": "https://example.com/file.jpg",
  "description": "Example string",
  "cover": "https://example.com/file.jpg",
  "backUrl": "Example string",
  "isActive": true,
  "theme": {
    "primaryColor": "Example string",
    "navbarTextColor": "Example string",
    "conversationBackgroundColor": "Example string",
    "chatbotMessageTextColor": "Example string",
    "userMessageTextColor": "Example string",
    "chatbotMessageBackgroundColor": "Example string",
    "userMessageBackgroundColor": "Example string",
    "chatbotMessageBackgroundShadowEnabled": true,
    "userMessageBackgroundShadowEnabled": true,
    "chatbotMessageGradientEnabled": true,
    "userMessageGradientEnabled": true
  },
  "darkTheme": {
    "primaryColor": "Example string",
    "navbarTextColor": "Example string",
    "conversationBackgroundColor": "Example string",
    "chatbotMessageTextColor": "Example string",
    "userMessageTextColor": "Example string",
    "chatbotMessageBackgroundColor": "Example string",
    "userMessageBackgroundColor": "Example string",
    "chatbotMessageBackgroundShadowEnabled": true,
    "userMessageBackgroundShadowEnabled": true,
    "chatbotMessageGradientEnabled": true,
    "userMessageGradientEnabled": true
  },
  "enableFileUpload": true,
  "enableDisplayCitations": true,
  "toolDisplayMode": "full",
  "enableAskOptionButtons": true,
  "enableConversationHandoff": true,
  "enableDisplayContextUsage": true,
  "enableDisplayThinking": true,
  "enableUserThinkingControl": true,
  "enableDisplayQueryMetadata": true,
  "enableDisplayHookMarkers": true,
  "hookMarkerTextInputModify": "Example string",
  "hookMarkerTextOutputModify": "Example string",
```

```
  "hookMarkerTextInputBlock": "Example string",
  "hookMarkerTextOutputBlock": "Example string",
  "enableShareConversation": true,
  "enableLocation": true,
  "enableShowPoweredBy": true,
  "poweredByLogo": "https://example.com/file.jpg",
  "enableAnonymous": true,
  "enableDisplayPreviousConversation": true,
  "enableDisplayConversationHistory": true,
  "enableConversationTimer": true,
  "conversationTimerDuration": 123,
  "enableAutoNewConversationOnTimeout": true,
  "enableSatisfactionSurvey": true,
  "satisfactionSurveyDelayMinutes": 123,
  "satisfactionSurveyPrompt": "Example string",
  "enableThemeModeToggle": true,
  "enableDisplayFontSizeSwitch": true,
  "defaultThemeMode": {},
  "enableDownloadCitations": true,
  "customDomain": {
    "domain": "Example string"
  },
  "enableDisplayChatbotAvatar": true,
  "enableDisplayChatbotName": true,
  "buttonIcon": "https://example.com/file.jpg",
  "conversationStartersDisplayCount": 123,
  "preChatFormEnabled": true,
  "preChatFormFields": null,
  "preChatFormTitle": null,
  "preChatFormSubtitle": null,
  "loadingDisplayMode": {},
  "loadingStageCopyByLocale": null,
  "loadingLongWaitCopyByLocale": null,
  "loadingLongWaitThresholdSeconds": 123,
  "loadingAnimationUseSharedAsset": true,
  "loadingAnimationSharedAssetUrl": "https://example.com/file.jpg",
  "loadingAnimationAssetUrlsByStage": null,
  "loadingTypingShowCopy": true,
  "toolCardRunningIconUrl": "https://example.com/file.jpg",
  "toolCardCompletedIconUrl": "https://example.com/file.jpg"
}
```


Code Examples

Shell/Bash

```
# API call example (Shell)
curl -X PATCH "https://api.maiagent.ai/api/v1/web-chats/550e8400-e29b-41d4-a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "avatar": "https://example.com/file.jpg",
    "logo": "https://example.com/file.jpg",
    "description": "Example string",
    "cover": "https://example.com/file.jpg",
    "backUrl": "Example string",
    "isActive": true,
    "theme": {
      "primaryColor": "Example string",
      "navbarTextColor": "Example string",
      "conversationBackgroundColor": "Example string",
      "chatbotMessageTextColor": "Example string",
      "userMessageTextColor": "Example string",
      "chatbotMessageBackgroundColor": "Example string",
      "userMessageBackgroundColor": "Example string",
      "chatbotMessageBackgroundShadowEnabled": true,
      "userMessageBackgroundShadowEnabled": true,
      "chatbotMessageGradientEnabled": true,
      "userMessageGradientEnabled": true
    },
    "darkTheme": {
      "primaryColor": "Example string",
      "navbarTextColor": "Example string",
      "conversationBackgroundColor": "Example string",
      "chatbotMessageTextColor": "Example string",
      "userMessageTextColor": "Example string",
      "chatbotMessageBackgroundColor": "Example string",
      "userMessageBackgroundColor": "Example string",
      "chatbotMessageBackgroundShadowEnabled": true,
      "userMessageBackgroundShadowEnabled": true,
      "chatbotMessageGradientEnabled": true,
      "userMessageGradientEnabled": true
    },
    "enableFileUpload": true,
    "enableDisplayCitations": true,
    "toolDisplayMode": "full",
    "enableAskOptionButtons": true,
    "enableConversationHandoff": true,
    "enableDisplayContextUsage": true,
    "enableDisplayThinking": true,
    "enableUserThinkingControl": true,
    "enableDisplayQueryMetadata": true,
    "enableDisplayHookMarkers": true,
    "hookMarkerTextInputModify": "Example string",
    "hookMarkerTextOutputModify": "Example string",
    "hookMarkerTextInputBlock": "Example string",
    "hookMarkerTextOutputBlock": "Example string",
```

```
    "enableShareConversation": true,
    "enableLocation": true,
    "enableShowPoweredBy": true,
    "poweredByLogo": "https://example.com/file.jpg",
    "enableAnonymous": true,
    "enableDisplayPreviousConversation": true,
    "enableDisplayConversationHistory": true,
    "enableConversationTimer": true,
    "conversationTimerDuration": 123,
    "enableAutoNewConversationOnTimeout": true,
    "enableSatisfactionSurvey": true,
    "satisfactionSurveyDelayMinutes": 123,
    "satisfactionSurveyPrompt": "Example string",
    "enableThemeModeToggle": true,
    "enableDisplayFontSizeSwitch": true,
    "defaultThemeMode": {},
    "enableDownloadCitations": true,
    "customDomain": {
      "domain": "Example string"
    },
    "enableDisplayChatbotAvatar": true,
    "enableDisplayChatbotName": true,
    "buttonIcon": "https://example.com/file.jpg",
    "conversationStartersDisplayCount": 123,
    "preChatFormEnabled": true,
    "preChatFormFields": null,
    "preChatFormTitle": null,
    "preChatFormSubtitle": null,
    "loadingDisplayMode": {},
    "loadingStageCopyByLocale": null,
    "loadingLongWaitCopyByLocale": null,
    "loadingLongWaitThresholdSeconds": 123,
    "loadingAnimationUseSharedAsset": true,
    "loadingAnimationSharedAssetUrl": "https://example.com/file.jpg",
    "loadingAnimationAssetUrlsByStage": null,
    "loadingTypingShowCopy": true,
    "toolCardRunningIconUrl": "https://example.com/file.jpg",
    "toolCardCompletedIconUrl": "https://example.com/file.jpg"
  }'

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// Request body (payload)
const data = {
    "avatar": "https://example.com/file.jpg",
    "logo": "https://example.com/file.jpg",
    "description": "Example string",
    "cover": "https://example.com/file.jpg",
    "backUrl": "Example string",
    "isActive": true,
    "theme": {
      "primaryColor": "Example string",
      "navbarTextColor": "Example string",
      "conversationBackgroundColor": "Example string",
      "chatbotMessageTextColor": "Example string",
      "userMessageTextColor": "Example string",
      "chatbotMessageBackgroundColor": "Example string",
      "userMessageBackgroundColor": "Example string",
      "chatbotMessageBackgroundShadowEnabled": true,
      "userMessageBackgroundShadowEnabled": true,
      "chatbotMessageGradientEnabled": true,
      "userMessageGradientEnabled": true
    },
    "darkTheme": {
      "primaryColor": "Example string",
      "navbarTextColor": "Example string",
      "conversationBackgroundColor": "Example string",
      "chatbotMessageTextColor": "Example string",
      "userMessageTextColor": "Example string",
      "chatbotMessageBackgroundColor": "Example string",
      "userMessageBackgroundColor": "Example string",
      "chatbotMessageBackgroundShadowEnabled": true,
      "userMessageBackgroundShadowEnabled": true,
      "chatbotMessageGradientEnabled": true,
      "userMessageGradientEnabled": true
    },
    "enableFileUpload": true,
    "enableDisplayCitations": true,
    "toolDisplayMode": "full",
    "enableAskOptionButtons": true,
    "enableConversationHandoff": true,
    "enableDisplayContextUsage": true,
    "enableDisplayThinking": true,
    "enableUserThinkingControl": true,
    "enableDisplayQueryMetadata": true,
    "enableDisplayHookMarkers": true,
```

```
    "hookMarkerTextInputModify": "Example string",
    "hookMarkerTextOutputModify": "Example string",
    "hookMarkerTextInputBlock": "Example string",
    "hookMarkerTextOutputBlock": "Example string",
    "enableShareConversation": true,
    "enableLocation": true,
    "enableShowPoweredBy": true,
    "poweredByLogo": "https://example.com/file.jpg",
    "enableAnonymous": true,
    "enableDisplayPreviousConversation": true,
    "enableDisplayConversationHistory": true,
    "enableConversationTimer": true,
    "conversationTimerDuration": 123,
    "enableAutoNewConversationOnTimeout": true,
    "enableSatisfactionSurvey": true,
    "satisfactionSurveyDelayMinutes": 123,
    "satisfactionSurveyPrompt": "Example string",
    "enableThemeModeToggle": true,
    "enableDisplayFontSizeSwitch": true,
    "defaultThemeMode": {},
    "enableDownloadCitations": true,
    "customDomain": {
      "domain": "Example string"
    },
    "enableDisplayChatbotAvatar": true,
    "enableDisplayChatbotName": true,
    "buttonIcon": "https://example.com/file.jpg",
    "conversationStartersDisplayCount": 123,
    "preChatFormEnabled": true,
    "preChatFormFields": null,
    "preChatFormTitle": null,
    "preChatFormSubtitle": null,
    "loadingDisplayMode": {},
    "loadingStageCopyByLocale": null,
    "loadingLongWaitCopyByLocale": null,
    "loadingLongWaitThresholdSeconds": 123,
    "loadingAnimationUseSharedAsset": true,
    "loadingAnimationSharedAssetUrl": "https://example.com/file.jpg",
    "loadingAnimationAssetUrlsByStage": null,
    "loadingTypingShowCopy": true,
    "toolCardRunningIconUrl": "https://example.com/file.jpg",
    "toolCardCompletedIconUrl": "https://example.com/file.jpg"
  };

axios.patch("https://api.maiagent.ai/api/v1/web-chats/550e8400-e29b-41d4-a716-446655440000/",
data, config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/web-chats/550e8400-e29b-41d4-a716-446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# Request body (payload)
data = {
    "avatar": "https://example.com/file.jpg",
    "logo": "https://example.com/file.jpg",
    "description": "Example string",
    "cover": "https://example.com/file.jpg",
    "backUrl": "Example string",
    "isActive": True,
    "theme": {
        "primaryColor": "Example string",
        "navbarTextColor": "Example string",
        "conversationBackgroundColor": "Example string",
        "chatbotMessageTextColor": "Example string",
        "userMessageTextColor": "Example string",
        "chatbotMessageBackgroundColor": "Example string",
        "userMessageBackgroundColor": "Example string",
        "chatbotMessageBackgroundShadowEnabled": True,
        "userMessageBackgroundShadowEnabled": True,
        "chatbotMessageGradientEnabled": True,
        "userMessageGradientEnabled": True
    },
    "darkTheme": {
        "primaryColor": "Example string",
        "navbarTextColor": "Example string",
        "conversationBackgroundColor": "Example string",
        "chatbotMessageTextColor": "Example string",
        "userMessageTextColor": "Example string",
        "chatbotMessageBackgroundColor": "Example string",
        "userMessageBackgroundColor": "Example string",
        "chatbotMessageBackgroundShadowEnabled": True,
        "userMessageBackgroundShadowEnabled": True,
        "chatbotMessageGradientEnabled": True,
        "userMessageGradientEnabled": True
    },
    "enableFileUpload": True,
    "enableDisplayCitations": True,
    "toolDisplayMode": "full",
    "enableAskOptionButtons": True,
    "enableConversationHandoff": True,
    "enableDisplayContextUsage": True,
    "enableDisplayThinking": True,
    "enableUserThinkingControl": True,
    "enableDisplayQueryMetadata": True,
    "enableDisplayHookMarkers": True,
    "hookMarkerTextInputModify": "Example string",
    "hookMarkerTextOutputModify": "Example string",
```

```
    "hookMarkerTextInputBlock": "Example string",
    "hookMarkerTextOutputBlock": "Example string",
    "enableShareConversation": True,
    "enableLocation": True,
    "enableShowPoweredBy": True,
    "poweredByLogo": "https://example.com/file.jpg",
    "enableAnonymous": True,
    "enableDisplayPreviousConversation": True,
    "enableDisplayConversationHistory": True,
    "enableConversationTimer": True,
    "conversationTimerDuration": 123,
    "enableAutoNewConversationOnTimeout": True,
    "enableSatisfactionSurvey": True,
    "satisfactionSurveyDelayMinutes": 123,
    "satisfactionSurveyPrompt": "Example string",
    "enableThemeModeToggle": True,
    "enableDisplayFontSizeSwitch": True,
    "defaultThemeMode": {},
    "enableDownloadCitations": True,
    "customDomain": {
        "domain": "Example string"
    },
    "enableDisplayChatbotAvatar": True,
    "enableDisplayChatbotName": True,
    "buttonIcon": "https://example.com/file.jpg",
    "conversationStartersDisplayCount": 123,
    "preChatFormEnabled": True,
    "preChatFormFields": None,
    "preChatFormTitle": None,
    "preChatFormSubtitle": None,
    "loadingDisplayMode": {},
    "loadingStageCopyByLocale": None,
    "loadingLongWaitCopyByLocale": None,
    "loadingLongWaitThresholdSeconds": 123,
    "loadingAnimationUseSharedAsset": True,
    "loadingAnimationSharedAssetUrl": "https://example.com/file.jpg",
    "loadingAnimationAssetUrlsByStage": None,
    "loadingTypingShowCopy": True,
    "toolCardRunningIconUrl": "https://example.com/file.jpg",
    "toolCardCompletedIconUrl": "https://example.com/file.jpg"
}

response = requests.patch(url, json=data, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->patch("https://api.maiagent.ai/api/v1/web-chats/550e8400-e29b-41d4-a716-446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'avatar' => 'https://example.com/file.jpg',
            'logo' => 'https://example.com/file.jpg',
            'description' => 'Example string',
            'cover' => 'https://example.com/file.jpg',
            'backUrl' => 'Example string',
            'isActive' => true,
            'theme' => [
                'primaryColor' => 'Example string',
                'navbarTextColor' => 'Example string',
                'conversationBackgroundColor' => 'Example string',
                'chatbotMessageTextColor' => 'Example string',
                'userMessageTextColor' => 'Example string',
                'chatbotMessageBackgroundColor' => 'Example string',
                'userMessageBackgroundColor' => 'Example string',
                'chatbotMessageBackgroundShadowEnabled' => true,
                'userMessageBackgroundShadowEnabled' => true,
                'chatbotMessageGradientEnabled' => true,
                'userMessageGradientEnabled' => true
            ],
            'darkTheme' => [
                'primaryColor' => 'Example string',
                'navbarTextColor' => 'Example string',
                'conversationBackgroundColor' => 'Example string',
                'chatbotMessageTextColor' => 'Example string',
                'userMessageTextColor' => 'Example string',
                'chatbotMessageBackgroundColor' => 'Example string',
                'userMessageBackgroundColor' => 'Example string',
                'chatbotMessageBackgroundShadowEnabled' => true,
                'userMessageBackgroundShadowEnabled' => true,
                'chatbotMessageGradientEnabled' => true,
                'userMessageGradientEnabled' => true
            ],
            'enableFileUpload' => true,
            'enableDisplayCitations' => true,
            'toolDisplayMode' => 'full',
            'enableAskOptionButtons' => true,
            'enableConversationHandoff' => true,
            'enableDisplayContextUsage' => true,
            'enableDisplayThinking' => true,
            'enableUserThinkingControl' => true,
            'enableDisplayQueryMetadata' => true,
```

```
            'enableDisplayHookMarkers' => true,
            'hookMarkerTextInputModify' => 'Example string',
            'hookMarkerTextOutputModify' => 'Example string',
            'hookMarkerTextInputBlock' => 'Example string',
            'hookMarkerTextOutputBlock' => 'Example string',
            'enableShareConversation' => true,
            'enableLocation' => true,
            'enableShowPoweredBy' => true,
            'poweredByLogo' => 'https://example.com/file.jpg',
            'enableAnonymous' => true,
            'enableDisplayPreviousConversation' => true,
            'enableDisplayConversationHistory' => true,
            'enableConversationTimer' => true,
            'conversationTimerDuration' => 123,
            'enableAutoNewConversationOnTimeout' => true,
            'enableSatisfactionSurvey' => true,
            'satisfactionSurveyDelayMinutes' => 123,
            'satisfactionSurveyPrompt' => 'Example string',
            'enableThemeModeToggle' => true,
            'enableDisplayFontSizeSwitch' => true,
            'defaultThemeMode' => new \stdClass(),
            'enableDownloadCitations' => true,
            'customDomain' => [
                'domain' => 'Example string'
            ],
            'enableDisplayChatbotAvatar' => true,
            'enableDisplayChatbotName' => true,
            'buttonIcon' => 'https://example.com/file.jpg',
            'conversationStartersDisplayCount' => 123,
            'preChatFormEnabled' => true,
            'preChatFormFields' => null,
            'preChatFormTitle' => null,
            'preChatFormSubtitle' => null,
            'loadingDisplayMode' => new \stdClass(),
            'loadingStageCopyByLocale' => null,
            'loadingLongWaitCopyByLocale' => null,
            'loadingLongWaitThresholdSeconds' => 123,
            'loadingAnimationUseSharedAsset' => true,
            'loadingAnimationSharedAssetUrl' => 'https://example.com/file.jpg',
            'loadingAnimationAssetUrlsByStage' => null,
            'loadingTypingShowCopy' => true,
            'toolCardRunningIconUrl' => 'https://example.com/file.jpg',
            'toolCardCompletedIconUrl' => 'https://example.com/file.jpg'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response Body

Status code: `200`

Example response schema

```
{
  "id": string (uuid)
  "name": string
  "avatar"?: string (uri) // Optional
  "logo"?: string (uri) // Optional
  "description"?: string // Optional
  "cover"?: string (uri) // Optional
  "backUrl"?: string // Optional
  "isActive"?: boolean // Optional
  "enableSpeech": boolean
  "displayConversationStarters": [
    string
  ]
  "theme": {
  {
    "primaryColor"?: string // Optional
    "navbarTextColor"?: string // Optional
    "conversationBackgroundColor"?: string // Optional
    "chatbotMessageTextColor"?: string // Optional
    "userMessageTextColor"?: string // Optional
    "chatbotMessageBackgroundColor"?: string // Optional
    "userMessageBackgroundColor"?: string // Optional
    "chatbotMessageBackgroundShadowEnabled"?: boolean // Optional
    "userMessageBackgroundShadowEnabled"?: boolean // Optional
    "chatbotMessageGradientEnabled"?: boolean // Optional
    "userMessageGradientEnabled"?: boolean // Optional
  }
  }
  "darkTheme": {
  {
    "primaryColor"?: string // Optional
    "navbarTextColor"?: string // Optional
    "conversationBackgroundColor"?: string // Optional
    "chatbotMessageTextColor"?: string // Optional
    "userMessageTextColor"?: string // Optional
    "chatbotMessageBackgroundColor"?: string // Optional
    "userMessageBackgroundColor"?: string // Optional
    "chatbotMessageBackgroundShadowEnabled"?: boolean // Optional
    "userMessageBackgroundShadowEnabled"?: boolean // Optional
    "chatbotMessageGradientEnabled"?: boolean // Optional
    "userMessageGradientEnabled"?: boolean // Optional
  }
  }
  "enableFileUpload"?: boolean // Optional
  "enableDisplayCitations"?: boolean // Optional
  "toolDisplayMode"?: string (enum: full, compact, hidden) // * `full` - Full
* `compact` - Compact
* `hidden` - Hidden (Optional)
  "enableAskOptionButtons"?: boolean // When enabled, ask_user_question options appear as a row of
buttons above the input field, which remains usable. When disabled, the existing overlay panel is
retained. This gradual rollout toggle can be disabled at any time to revert the behavior. (Optional)
```

```
  "enableConversationHandoff"?: boolean // When enabled, this conversation platform's webchat
displays the handoff UI (notification bar, summary card, and continuation button) and registers
handoff tools. The global handoff toggle in system settings still applies: disabling it disables
handoff everywhere. MaiGPT always displays the UI regardless of this toggle. The context usage
percentage bar at the bottom is controlled separately by "Display Context Usage". Disabled by
default, so customer-facing webchat displays no handoff UI. This gradual rollout toggle lets you
revert the behavior by disabling it without rolling back the release. (Optional)
  "enableDisplayContextUsage"?: boolean // When enabled, this conversation platform's webchat
displays a context usage percentage bar below the input field. This is independent of conversation
handoff: handoff toggles, including the global handoff toggle, do not affect it, and it does not
affect the handoff notification bar. MaiGPT always displays it regardless of this toggle. Disabled by
default; disabling it reverts the behavior without rolling back the release. (Optional)
  "enableDisplayThinking"?: boolean // Optional
  "enableUserThinkingControl"?: boolean // Optional
  "enableDisplayQueryMetadata"?: boolean // Optional
  "enableDisplayHookMarkers"?: boolean // Optional
  "hookMarkerTextInputModify"?: string // Optional
  "hookMarkerTextOutputModify"?: string // Optional
  "hookMarkerTextInputBlock"?: string // Optional
  "hookMarkerTextOutputBlock"?: string // Optional
  "enableShareConversation"?: boolean // Optional
  "enableLocation"?: boolean // Optional
  "enableShowPoweredBy"?: boolean // Optional
  "poweredByLogo"?: string (uri) // Optional
  "enableAnonymous"?: boolean // Optional
  "enableDisplayPreviousConversation"?: boolean // Optional
  "enableDisplayConversationHistory"?: boolean // Optional
  "enableConversationTimer"?: boolean // Optional
  "conversationTimerDuration"?: integer // Timer timeout duration, ranging from 3-60 minutes
(Optional)
  "enableAutoNewConversationOnTimeout"?: boolean // Optional
  "enableSatisfactionSurvey"?: boolean // Optional
  "satisfactionSurveyDelayMinutes"?: integer // Minutes after the last AI reply before the survey
appears, ranging from 1-60 minutes (Optional)
  "satisfactionSurveyPrompt"?: string // Custom survey title text; leave blank to use the frontend's
default localized text (Optional)
  "accessType":
  {
  }
  "enableThemeModeToggle"?: boolean // Optional
  "enableDisplayFontSizeSwitch"?: boolean // Optional
  "defaultThemeMode"?:  // Optional
  {
  }
  "enableDownloadCitations"?: boolean // Optional
  "customDomain"?:  // Optional
  {
    "id": string (uuid)
    "domain": string
    "status":
    {
    }
  }
  "enableDisplayChatbotAvatar"?: boolean // Optional
  "enableDisplayChatbotName"?: boolean // Optional
  "buttonIcon"?: string (uri) // Optional
  "enableCodeInterpreter": boolean // Read enable_code_interpreter from the inbox's chatbot.
  "voiceAgentEnabled": boolean // Whether the bound chatbot has the voice agent turned on (read-only)
  "conversationStartersDisplayCount"?: integer // Optional
  "includeGreetingInContext": boolean // When enabled, the conversation greeting and the numbered
```

```
conversation starters (in configured order, unshuffled and untruncated) are injected into the LLM
context so the agent can resolve short replies like "1" to the matching starter option.
  "tools": [ // Expose chatbot tools to SDK for the tool_mask selector.

Name resolution prefers ``display_name`` (set on MCP tools, where
``name`` is null) and falls back to ``name`` for API tools where
``display_name`` is null. Tools missing both are skipped — SDK
should never show an unnamed tool to a contact. Quick Menu tools are
static input-bar UI, never an LLM tool, so masking one is meaningless.
    object
  ]
  "preChatFormEnabled"?: boolean // Optional
  "preChatFormFields"?: object // Optional
  "preChatFormTitle"?: object // Optional
  "preChatFormSubtitle"?: object // Optional
  "loadingDisplayMode"?:  // Waiting-experience style. `narrative` shows per-stage copy;
`brand_animation` plays the uploaded asset and hides every system narration line. Defaults to
`narrative`, which with no copy configured behaves exactly as before this field existed.

* `narrative` - Narrative copy
* `brand_animation` - Brand animation (Optional)
  {
  }
  "loadingStageCopyByLocale"?: object // Locale-keyed per-stage waiting copy, shaped {locale: {stage:
text}} where stage is one of LoadingStage. An absent locale or stage falls back to the built-in copy,
so a partially filled dict is valid and never blocks a reply. (Optional)
  "loadingLongWaitCopyByLocale"?: object // Locale-keyed line shown once the wait exceeds
`loading_long_wait_threshold_seconds`, shaped {locale: text}. Written in the brand character voice
for the animation mode, but applies to both modes. Empty means no long-wait line is shown. (Optional)
  "loadingLongWaitThresholdSeconds"?: integer // How long a single reply must be pending before the
long-wait copy appears. (Optional)
  "loadingAnimationUseSharedAsset"?: boolean // True (default) means every stage plays
`loading_animation_shared_asset_url`, so the admin only uploads once. False expands per-stage assets,
each falling back to the shared asset when its own slot is empty. (Optional)
  "loadingAnimationSharedAssetUrl"?: string (uri) // Optional
  "loadingAnimationAssetUrlsByStage"?: object // Shaped {stage: url} keyed by LoadingStage. Only
consulted when `loading_animation_use_shared_asset` is False; a missing stage falls back to the
shared asset. (Optional)
  "loadingTypingShowCopy"?: boolean // Only affects the first "typing" stage. True (default, the pre-
existing behavior) shows the typing-stage copy next to the pre-first-char animation/dot; False plays
only the animation with no text line. Thinking / analyzing / long-wait stages are unaffected.
(Optional)
  "toolCardRunningIconUrl"?: string (uri) // Optional
  "toolCardCompletedIconUrl"?: string (uri) // Optional
  "inbox": object
  "quickMenu": object // Mounted Quick Menu Agent UI config for the web chat input bar; null when
absent (read-only)
}
```

Response Example Values

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "name": "Response string",
  "avatar": "https://example.com/file.jpg",
  "logo": "https://example.com/file.jpg",
  "description": "Response string",
  "cover": "https://example.com/file.jpg",
```

```
  "backUrl": "Response string",
  "isActive": false,
  "enableSpeech": false,
  "displayConversationStarters": [
    "Response string"
  ],
  "theme": {
    "primaryColor": "Response string",
    "navbarTextColor": "Response string",
    "conversationBackgroundColor": "Response string",
    "chatbotMessageTextColor": "Response string",
    "userMessageTextColor": "Response string",
    "chatbotMessageBackgroundColor": "Response string",
    "userMessageBackgroundColor": "Response string",
    "chatbotMessageBackgroundShadowEnabled": false,
    "userMessageBackgroundShadowEnabled": false,
    "chatbotMessageGradientEnabled": false,
    "userMessageGradientEnabled": false
  },
  "darkTheme": {
    "primaryColor": "Response string",
    "navbarTextColor": "Response string",
    "conversationBackgroundColor": "Response string",
    "chatbotMessageTextColor": "Response string",
    "userMessageTextColor": "Response string",
    "chatbotMessageBackgroundColor": "Response string",
    "userMessageBackgroundColor": "Response string",
    "chatbotMessageBackgroundShadowEnabled": false,
    "userMessageBackgroundShadowEnabled": false,
    "chatbotMessageGradientEnabled": false,
    "userMessageGradientEnabled": false
  },
  "enableFileUpload": false,
  "enableDisplayCitations": false,
  "toolDisplayMode": "full",
  "enableAskOptionButtons": false,
  "enableConversationHandoff": false,
  "enableDisplayContextUsage": false,
  "enableDisplayThinking": false,
  "enableUserThinkingControl": false,
  "enableDisplayQueryMetadata": false,
  "enableDisplayHookMarkers": false,
  "hookMarkerTextInputModify": "Response string",
  "hookMarkerTextOutputModify": "Response string",
  "hookMarkerTextInputBlock": "Response string",
  "hookMarkerTextOutputBlock": "Response string",
  "enableShareConversation": false,
  "enableLocation": false,
  "enableShowPoweredBy": false,
  "poweredByLogo": "https://example.com/file.jpg",
  "enableAnonymous": false,
  "enableDisplayPreviousConversation": false,
  "enableDisplayConversationHistory": false,
  "enableConversationTimer": false,
  "conversationTimerDuration": 456,
  "enableAutoNewConversationOnTimeout": false,
  "enableSatisfactionSurvey": false,
  "satisfactionSurveyDelayMinutes": 456,
  "satisfactionSurveyPrompt": "Response string",
  "accessType": {},
```

```
  "enableThemeModeToggle": false,
  "enableDisplayFontSizeSwitch": false,
  "defaultThemeMode": {},
  "enableDownloadCitations": false,
  "customDomain": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "domain": "Response string",
    "status": {}
  },
  "enableDisplayChatbotAvatar": false,
  "enableDisplayChatbotName": false,
  "buttonIcon": "https://example.com/file.jpg",
  "enableCodeInterpreter": false,
  "voiceAgentEnabled": false,
  "conversationStartersDisplayCount": 456,
  "includeGreetingInContext": false,
  "tools": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "Example response name",
      "description": "Example response description"
    }
  ],
  "preChatFormEnabled": false,
  "preChatFormFields": null,
  "preChatFormTitle": null,
  "preChatFormSubtitle": null,
  "loadingDisplayMode": {},
  "loadingStageCopyByLocale": null,
  "loadingLongWaitCopyByLocale": null,
  "loadingLongWaitThresholdSeconds": 456,
  "loadingAnimationUseSharedAsset": false,
  "loadingAnimationSharedAssetUrl": "https://example.com/file.jpg",
  "loadingAnimationAssetUrlsByStage": null,
  "loadingTypingShowCopy": false,
  "toolCardRunningIconUrl": "https://example.com/file.jpg",
  "toolCardCompletedIconUrl": "https://example.com/file.jpg",
  "inbox": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Example response name",
    "description": "Example response description"
  },
  "quickMenu": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Example response name",
    "description": "Example response description"
  }
}
```


Set Up Contact Credentials

POST `/api/v1/web-chats/{id}/setup-contact-credentials/`

Parameters

Parameter Name	Required	Type	Description
id	V	string	A UUID string identifying this web chat.

Request Body

Request Parameters

Field	Type	Required	Description
sourceId	string	Yes	Unique identifier for the contact
name	string	No	Contact display name
mcpCredentials	object (contains 2 properties: toolId, headers)	No	MCP credentials configuration
mcpCredentials.toolId	string (uuid)	Yes	MCP Tool ID
mcpCredentials.headers	object	No	Authentication headers
embedOrigin	string	No	Origin of the embedding page (forwarded by the web chat frontend) for allowlist validation
ts	integer	No	Unix timestamp (seconds, UTC) the signature was computed with. Required when the inbox login settings enable Source ID access with signature verification.
sig	string	No	Hex HMAC-SHA256 of "{webChatId}.{sourceId}.{ts}" computed by the embedding site backend

Request Schema Example

```
{
  "sourceId": string // Unique identifier for the contact
  "name"?: string // Contact display name (Optional)
  "mcpCredentials"?:  // MCP credentials configuration (Optional)
  {
    "toolId": string (uuid) // MCP Tool ID
    "headers"?: object // Authentication headers (Optional)
  }
  "embedOrigin"?: string // Origin of the embedding page (forwarded by the web chat frontend) for allowlist validation (Optional)
  "ts"?: integer // Unix timestamp (seconds, UTC) the signature was computed with. Required when the inbox login settings enable Source ID access with signature verification. (Optional)
  "sig"?: string // Hex HMAC-SHA256 of "{webChatId}.{sourceId}.{ts}" computed by the embedding site backend (Optional)
}
```

Request Example Values

```
{
  "sourceId": "Example string",
  "name": "Example name",
  "mcpCredentials": {
    "toolId": "550e8400-e29b-41d4-a716-446655440000",
    "headers": {}
  },
  "embedOrigin": "Example string",
  "ts": 123,
  "sig": "Example string"
}
```


Code Examples

Shell/Bash

```
# API call example (Shell)
curl -X POST "https://api.maiagent.ai/api/v1/web-chats/550e8400-e29b-41d4-a716-
446655440000/setup-contact-credentials/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "sourceId": "Example string",
    "name": "Example name",
    "mcpCredentials": {
      "toolId": "550e8400-e29b-41d4-a716-446655440000",
      "headers": {}
    },
    "embedOrigin": "Example string",
    "ts": 123,
    "sig": "Example string"
  }'

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// Request body (payload)
const data = {
    "sourceId": "Example string",
    "name": "Example name",
    "mcpCredentials": {
      "toolId": "550e8400-e29b-41d4-a716-446655440000",
      "headers": {}
    },
    "embedOrigin": "Example string",
    "ts": 123,
    "sig": "Example string"
  };

axios.post("https://api.maiagent.ai/api/v1/web-chats/550e8400-e29b-41d4-a716-446655440000/setup-contact-credentials/", data, config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/web-chats/550e8400-e29b-41d4-a716-446655440000/setup-contact-credentials/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# Request body (payload)
data = {
    "sourceId": "Example string",
    "name": "Example name",
    "mcpCredentials": {
        "toolId": "550e8400-e29b-41d4-a716-446655440000",
        "headers": {}
    },
    "embedOrigin": "Example string",
    "ts": 123,
    "sig": "Example string"
}

response = requests.post(url, json=data, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->post("https://api.maiagent.ai/api/v1/web-chats/550e8400-e29b-41d4-a716-446655440000/setup-contact-credentials/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'sourceId' => 'Example string',
            'name' => 'Example name',
            'mcpCredentials' => [
                'toolId' => '550e8400-e29b-41d4-a716-446655440000',
                'headers' => new \stdClass()
            ],
            'embedOrigin' => 'Example string',
            'ts' => 123,
            'sig' => 'Example string'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response Body

Status Code: 200

Response Schema Example

```
{
  "contactId": string (uuid) // The created or existing contact ID
  "created": boolean // Whether the contact was created by this call. False means an existing contact matched the source_id; in that case the request name is not applied (update names via PATCH /contacts/{id}/).
}
```

Response Example Values


```
{
  "contactId": "550e8400-e29b-41d4-a716-446655440000",
  "created": false
}
```


Status Code: 400 - No response body

Get Voice Agent Token

POST `/api/v1/web-chats/{id}/voice-agent/token/`

Parameters

Parameter Name	Required	Type	Description
id	V	string	A UUID string identifying this web chat.

Request Body

Request Parameters

Field	Type	Required	Description
avatar	string (uri)	No	
logo	string (uri)	No	
description	string	No	
cover	string (uri)	No	
backUrl	string	No	
isActive	boolean	No	
theme	object	Yes	
theme.primaryColor	string	No	
theme.navbarTextColor	string	No	
theme.conversationBackgroundColor	string	No	
theme.chatbotMessageTextColor	string	No	
theme.userMessageTextColor	string	No	

Field	Type	Required	Description
theme.chatbotMessageBackgroundColor	string	No	
theme.userMessageBackgroundColor	string	No	
theme.chatbotMessageBackgroundShadowEnabled	boolean	No	
theme.userMessageBackgroundShadowEnabled	boolean	No	
theme.chatbotMessageGradientEnabled	boolean	No	
theme.userMessageGradientEnabled	boolean	No	
darkTheme	object	Yes	
darkTheme.primaryColor	string	No	
darkTheme.navbarTextColor	string	No	
darkTheme.conversationBackgroundColor	string	No	
darkTheme.chatbotMessageTextColor	string	No	
darkTheme.userMessageTextColor	string	No	
darkTheme.chatbotMessageBackgroundColor	string	No	
darkTheme.userMessageBackgroundColor	string	No	
darkTheme.chatbotMessageBackgroundShadowEnabled	boolean	No	
darkTheme.userMessageBackgroundShadowEnabled	boolean	No	
darkTheme.chatbotMessageGradientEnabled	boolean	No	
darkTheme.userMessageGradientEnabled	boolean	No	
enableFileUpload	boolean	No	
enableDisplayCitations	boolean	No	
toolDisplayMode	string (enum: full, compact, hidden)	No	`full` : Full ; `compact` : Compact ; `hidden` : Hidden;
enableAskOptionButtons	boolean	No	When enabled, ask_user_question options appear as a row of buttons above the input field, which remains usable. When disabled, the existing overlay panel is retained. This gradual rollout switch can be turned off at any time to revert the behavior.
enableConversationHandoff	boolean	No	When enabled, this conversation platform's webchat displays the handoff UI (notification bar, summary card, and continuation button) and registers handoff tools. The global handoff switch in system settings still applies: when it is off, handoff is disabled everywhere. MaiGPT always displays the handoff UI regardless of this switch. The context

Field	Type	Required	Description
			usage percentage bar at the bottom is controlled separately by "Display context usage". Disabled by default, so customers' public webchats show no handoff UI. This gradual rollout switch can be turned off to revert the behavior without rolling back the release.
enableDisplayContextUsage	boolean	No	When enabled, this conversation platform's webchat displays a context usage percentage bar below the input field. It is independent of conversation handoff: handoff switches, including the global handoff switch, do not affect it, and it does not affect the handoff notification bar. MaiGPT always displays the bar regardless of this switch. Disabled by default; turn it off to revert the behavior without rolling back the release.
enableDisplayThinking	boolean	No	
enableUserThinkingControl	boolean	No	
enableDisplayQueryMetadata	boolean	No	
enableDisplayHookMarkers	boolean	No	
hookMarkerTextInputModify	string	No	
hookMarkerTextOutputModify	string	No	
hookMarkerTextInputBlock	string	No	
hookMarkerTextOutputBlock	string	No	
enableShareConversation	boolean	No	
enableLocation	boolean	No	
enableShowPoweredBy	boolean	No	
poweredByLogo	string (uri)	No	
enableAnonymous	boolean	No	
enableDisplayPreviousConversation	boolean	No	
enableDisplayConversationHistory	boolean	No	
enableConversationTimer	boolean	No	
conversationTimerDuration	integer	No	Timer timeout duration, from 3 to 60 minutes
enableAutoNewConversationOnTimeout	boolean	No	
enableSatisfactionSurvey	boolean	No	
satisfactionSurveyDelayMinutes	integer	No	Number of minutes after the last AI reply before the survey appears, from 1 to 60 minutes

Field	Type	Required	Description
satisfactionSurveyPrompt	string	No	Custom survey title text; leave blank to use the frontend's default localized text
enableThemeModeToggle	boolean	No	
enableDisplayFontSizeSwitch	boolean	No	
defaultThemeMode	object	No	
enableDownloadCitations	boolean	No	
customDomain	object (contains 3 properties: id, domain, status)	No	
customDomain.domain	string	Yes	
enableDisplayChatbotAvatar	boolean	No	
enableDisplayChatbotName	boolean	No	
buttonIcon	string (uri)	No	
conversationStartersDisplayCount	integer	No	
preChatFormEnabled	boolean	No	
preChatFormFields	object	No	
preChatFormTitle	object	No	
preChatFormSubtitle	object	No	
loadingDisplayMode	object	No	Waiting-experience style. `narrative` shows per-stage copy; `brand_animation` plays the uploaded asset and hides every system narration line. Defaults to `narrative` , which with no copy configured beh...
loadingStageCopyByLocale	object	No	Locale-keyed per-stage waiting copy, shaped {locale: {stage: text}} where stage is one of LoadingStage. An absent locale or stage falls back to the built-in copy, so a partially filled dict is valid a...
loadingLongWaitCopyByLocale	object	No	Locale-keyed line shown once the wait exceeds `loading_long_wait_threshold_seconds` , shaped {locale: text}. Written in the brand character voice for the animation mode, but applies to both modes. Empt...
loadingLongWaitThresholdSeconds	integer	No	How long a single reply must be pending before the long-wait copy appears.
loadingAnimationUseSharedAsset	boolean	No	True (default) means every stage plays `loading_animation_shared_asset_url` , so the admin only uploads once. False

Field	Type	Required	Description
			expands per-stage assets, each falling back to the shared asset when its own slot is ...
loadingAnimationSharedAssetUrl	string (uri)	No	
loadingAnimationAssetUrlsByStage	object	No	Shaped {stage: url} keyed by LoadingStage. Only consulted when `loading_animation_use_shared_asset` is False; a missing stage falls back to the shared asset.
loadingTypingShowCopy	boolean	No	Only affects the first "typing" stage. True (default, the pre-existing behavior) shows the typing-stage copy next to the pre-first-char animation/dot; False plays only the animation with no text line....
toolCardRunningIconUrl	string (uri)	No	
toolCardCompletedIconUrl	string (uri)	No	

Request Schema Example

```
{
  "avatar"?: string (uri) // Optional
  "logo"?: string (uri) // Optional
  "description"?: string // Optional
  "cover"?: string (uri) // Optional
  "backUrl"?: string // Optional
  "isActive"?: boolean // Optional
  "theme": {
  {
    "primaryColor"?: string // Optional
    "navbarTextColor"?: string // Optional
    "conversationBackgroundColor"?: string // Optional
    "chatbotMessageTextColor"?: string // Optional
    "userMessageTextColor"?: string // Optional
    "chatbotMessageBackgroundColor"?: string // Optional
    "userMessageBackgroundColor"?: string // Optional
    "chatbotMessageBackgroundShadowEnabled"?: boolean // Optional
    "userMessageBackgroundShadowEnabled"?: boolean // Optional
    "chatbotMessageGradientEnabled"?: boolean // Optional
    "userMessageGradientEnabled"?: boolean // Optional
  }
  }
  "darkTheme": {
  {
    "primaryColor"?: string // Optional
    "navbarTextColor"?: string // Optional
    "conversationBackgroundColor"?: string // Optional
    "chatbotMessageTextColor"?: string // Optional
    "userMessageTextColor"?: string // Optional
    "chatbotMessageBackgroundColor"?: string // Optional
    "userMessageBackgroundColor"?: string // Optional
    "chatbotMessageBackgroundShadowEnabled"?: boolean // Optional
    "userMessageBackgroundShadowEnabled"?: boolean // Optional
    "chatbotMessageGradientEnabled"?: boolean // Optional
```

```
    "userMessageGradientEnabled"?: boolean // Optional
  }
  }
  "enableFileUpload"?: boolean // Optional
  "enableDisplayCitations"?: boolean // Optional
  "toolDisplayMode"?: string (enum: full, compact, hidden) // * `full` - Full
* `compact` - Compact
* `hidden` - Hidden (Optional)
  "enableAskOptionButtons"?: boolean // When enabled, ask_user_question options appear as a row of
buttons above the input box, which remains usable. When disabled, the existing overlay panel is used.
This gradual rollout toggle can be disabled at any time to revert the behavior. (Optional)
  "enableConversationHandoff"?: boolean // When enabled, this conversation platform's webchat
displays the handoff UI (notification bar, summary card, and continuation button) and registers
handoff tools. The global handoff toggle in system settings still applies: disabling it disables
handoff everywhere. MaiGPT always displays the UI regardless of this toggle. The context usage
percentage bar at the bottom is controlled separately by "Display Context Usage". Disabled by
default, so customer-facing webchats display no handoff UI. This gradual rollout toggle reverts the
behavior when disabled, without rolling back the release. (Optional)
  "enableDisplayContextUsage"?: boolean // When enabled, this conversation platform's webchat
displays a context usage percentage bar below the input box. This is independent of conversation
handoff: handoff toggles, including the global toggle, do not affect it, and it does not affect the
handoff notification bar. MaiGPT always displays the bar regardless of this toggle. Disabled by
default; disabling it reverts the behavior without rolling back the release. (Optional)
  "enableDisplayThinking"?: boolean // Optional
  "enableUserThinkingControl"?: boolean // Optional
  "enableDisplayQueryMetadata"?: boolean // Optional
  "enableDisplayHookMarkers"?: boolean // Optional
  "hookMarkerTextInputModify"?: string // Optional
  "hookMarkerTextOutputModify"?: string // Optional
  "hookMarkerTextInputBlock"?: string // Optional
  "hookMarkerTextOutputBlock"?: string // Optional
  "enableShareConversation"?: boolean // Optional
  "enableLocation"?: boolean // Optional
  "enableShowPoweredBy"?: boolean // Optional
  "poweredByLogo"?: string (uri) // Optional
  "enableAnonymous"?: boolean // Optional
  "enableDisplayPreviousConversation"?: boolean // Optional
  "enableDisplayConversationHistory"?: boolean // Optional
  "enableConversationTimer"?: boolean // Optional
  "conversationTimerDuration"?: integer // Timer timeout duration, ranging from 3-60 minutes
(Optional)
  "enableAutoNewConversationOnTimeout"?: boolean // Optional
  "enableSatisfactionSurvey"?: boolean // Optional
  "satisfactionSurveyDelayMinutes"?: integer // Minutes after the last AI reply before the survey
appears, ranging from 1-60 minutes (Optional)
  "satisfactionSurveyPrompt"?: string // Custom survey title text; leave blank to use the frontend's
default localized text (Optional)
  "enableThemeModeToggle"?: boolean // Optional
  "enableDisplayFontSizeSwitch"?: boolean // Optional
  "defaultThemeMode"?:  // Optional
  {
  }
  "enableDownloadCitations"?: boolean // Optional
  "customDomain"?:  // Optional
  {
    "domain": string
  }
  "enableDisplayChatbotAvatar"?: boolean // Optional
  "enableDisplayChatbotName"?: boolean // Optional
  "buttonIcon"?: string (uri) // Optional
```

```
  "conversationStartersDisplayCount"?: integer // Optional
  "preChatFormEnabled"?: boolean // Optional
  "preChatFormFields"?: object // Optional
  "preChatFormTitle"?: object // Optional
  "preChatFormSubtitle"?: object // Optional
  "loadingDisplayMode"?:  // Waiting-experience style. `narrative` shows per-stage copy;
`brand_animation` plays the uploaded asset and hides every system narration line. Defaults to
`narrative`, which with no copy configured behaves exactly as before this field existed.

* `narrative` - Narrative copy
* `brand_animation` - Brand animation (Optional)
  {
  }
  "loadingStageCopyByLocale"?: object // Locale-keyed per-stage waiting copy, shaped {locale: {stage:
text}} where stage is one of LoadingStage. An absent locale or stage falls back to the built-in copy,
so a partially filled dict is valid and never blocks a reply. (Optional)
  "loadingLongWaitCopyByLocale"?: object // Locale-keyed line shown once the wait exceeds
`loading_long_wait_threshold_seconds`, shaped {locale: text}. Written in the brand character voice
for the animation mode, but applies to both modes. Empty means no long-wait line is shown. (Optional)
  "loadingLongWaitThresholdSeconds"?: integer // How long a single reply must be pending before the
long-wait copy appears. (Optional)
  "loadingAnimationUseSharedAsset"?: boolean // True (default) means every stage plays
`loading_animation_shared_asset_url`, so the admin only uploads once. False expands per-stage assets,
each falling back to the shared asset when its own slot is empty. (Optional)
  "loadingAnimationSharedAssetUrl"?: string (uri) // Optional
  "loadingAnimationAssetUrlsByStage"?: object // Shaped {stage: url} keyed by LoadingStage. Only
consulted when `loading_animation_use_shared_asset` is False; a missing stage falls back to the
shared asset. (Optional)
  "loadingTypingShowCopy"?: boolean // Only affects the first "typing" stage. True (default, the pre-
existing behavior) shows the typing-stage copy next to the pre-first-char animation/dot; False plays
only the animation with no text line. Thinking / analyzing / long-wait stages are unaffected.
(Optional)
  "toolCardRunningIconUrl"?: string (uri) // Optional
  "toolCardCompletedIconUrl"?: string (uri) // Optional
}
```

Example Request Values

```
{
  "avatar": "https://example.com/file.jpg",
  "logo": "https://example.com/file.jpg",
  "description": "Example string",
  "cover": "https://example.com/file.jpg",
  "backUrl": "Example string",
  "isActive": true,
  "theme": {
    "primaryColor": "Example string",
    "navbarTextColor": "Example string",
    "conversationBackgroundColor": "Example string",
    "chatbotMessageTextColor": "Example string",
    "userMessageTextColor": "Example string",
    "chatbotMessageBackgroundColor": "Example string",
    "userMessageBackgroundColor": "Example string",
    "chatbotMessageBackgroundShadowEnabled": true,
    "userMessageBackgroundShadowEnabled": true,
    "chatbotMessageGradientEnabled": true,
    "userMessageGradientEnabled": true
  },
```

```
  "darkTheme": {
    "primaryColor": "Example string",
    "navbarTextColor": "Example string",
    "conversationBackgroundColor": "Example string",
    "chatbotMessageTextColor": "Example string",
    "userMessageTextColor": "Example string",
    "chatbotMessageBackgroundColor": "Example string",
    "userMessageBackgroundColor": "Example string",
    "chatbotMessageBackgroundShadowEnabled": true,
    "userMessageBackgroundShadowEnabled": true,
    "chatbotMessageGradientEnabled": true,
    "userMessageGradientEnabled": true
  },
  "enableFileUpload": true,
  "enableDisplayCitations": true,
  "toolDisplayMode": "full",
  "enableAskOptionButtons": true,
  "enableConversationHandoff": true,
  "enableDisplayContextUsage": true,
  "enableDisplayThinking": true,
  "enableUserThinkingControl": true,
  "enableDisplayQueryMetadata": true,
  "enableDisplayHookMarkers": true,
  "hookMarkerTextInputModify": "Example string",
  "hookMarkerTextOutputModify": "Example string",
  "hookMarkerTextInputBlock": "Example string",
  "hookMarkerTextOutputBlock": "Example string",
  "enableShareConversation": true,
  "enableLocation": true,
  "enableShowPoweredBy": true,
  "poweredByLogo": "https://example.com/file.jpg",
  "enableAnonymous": true,
  "enableDisplayPreviousConversation": true,
  "enableDisplayConversationHistory": true,
  "enableConversationTimer": true,
  "conversationTimerDuration": 123,
  "enableAutoNewConversationOnTimeout": true,
  "enableSatisfactionSurvey": true,
  "satisfactionSurveyDelayMinutes": 123,
  "satisfactionSurveyPrompt": "Example string",
  "enableThemeModeToggle": true,
  "enableDisplayFontSizeSwitch": true,
  "defaultThemeMode": {},
  "enableDownloadCitations": true,
  "customDomain": {
    "domain": "Example string"
  },
  "enableDisplayChatbotAvatar": true,
  "enableDisplayChatbotName": true,
  "buttonIcon": "https://example.com/file.jpg",
  "conversationStartersDisplayCount": 123,
  "preChatFormEnabled": true,
  "preChatFormFields": null,
  "preChatFormTitle": null,
  "preChatFormSubtitle": null,
  "loadingDisplayMode": {},
  "loadingStageCopyByLocale": null,
  "loadingLongWaitCopyByLocale": null,
  "loadingLongWaitThresholdSeconds": 123,
  "loadingAnimationUseSharedAsset": true,
```

```
  "loadingAnimationSharedAssetUrl": "https://example.com/file.jpg",
  "loadingAnimationAssetUrlsByStage": null,
  "loadingTypingShowCopy": true,
  "toolCardRunningIconUrl": "https://example.com/file.jpg",
  "toolCardCompletedIconUrl": "https://example.com/file.jpg"
}
```


Code Examples

Shell/Bash

```
# API call example (Shell)
curl -X POST "https://api.maiagent.ai/api/v1/web-chats/550e8400-e29b-41d4-a716-
446655440000/voice-agent/token/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "avatar": "https://example.com/file.jpg",
    "logo": "https://example.com/file.jpg",
    "description": "Example string",
    "cover": "https://example.com/file.jpg",
    "backUrl": "Example string",
    "isActive": true,
    "theme": {
      "primaryColor": "Example string",
      "navbarTextColor": "Example string",
      "conversationBackgroundColor": "Example string",
      "chatbotMessageTextColor": "Example string",
      "userMessageTextColor": "Example string",
      "chatbotMessageBackgroundColor": "Example string",
      "userMessageBackgroundColor": "Example string",
      "chatbotMessageBackgroundShadowEnabled": true,
      "userMessageBackgroundShadowEnabled": true,
      "chatbotMessageGradientEnabled": true,
      "userMessageGradientEnabled": true
    },
    "darkTheme": {
      "primaryColor": "Example string",
      "navbarTextColor": "Example string",
      "conversationBackgroundColor": "Example string",
      "chatbotMessageTextColor": "Example string",
      "userMessageTextColor": "Example string",
      "chatbotMessageBackgroundColor": "Example string",
      "userMessageBackgroundColor": "Example string",
      "chatbotMessageBackgroundShadowEnabled": true,
      "userMessageBackgroundShadowEnabled": true,
      "chatbotMessageGradientEnabled": true,
      "userMessageGradientEnabled": true
    },
    "enableFileUpload": true,
    "enableDisplayCitations": true,
    "toolDisplayMode": "full",
    "enableAskOptionButtons": true,
    "enableConversationHandoff": true,
    "enableDisplayContextUsage": true,
    "enableDisplayThinking": true,
    "enableUserThinkingControl": true,
    "enableDisplayQueryMetadata": true,
    "enableDisplayHookMarkers": true,
    "hookMarkerTextInputModify": "Example string",
    "hookMarkerTextOutputModify": "Example string",
    "hookMarkerTextInputBlock": "Example string",
```

```
    "hookMarkerTextOutputBlock": "Example string",
    "enableShareConversation": true,
    "enableLocation": true,
    "enableShowPoweredBy": true,
    "poweredByLogo": "https://example.com/file.jpg",
    "enableAnonymous": true,
    "enableDisplayPreviousConversation": true,
    "enableDisplayConversationHistory": true,
    "enableConversationTimer": true,
    "conversationTimerDuration": 123,
    "enableAutoNewConversationOnTimeout": true,
    "enableSatisfactionSurvey": true,
    "satisfactionSurveyDelayMinutes": 123,
    "satisfactionSurveyPrompt": "Example string",
    "enableThemeModeToggle": true,
    "enableDisplayFontSizeSwitch": true,
    "defaultThemeMode": {},
    "enableDownloadCitations": true,
    "customDomain": {
      "domain": "Example string"
    },
    "enableDisplayChatbotAvatar": true,
    "enableDisplayChatbotName": true,
    "buttonIcon": "https://example.com/file.jpg",
    "conversationStartersDisplayCount": 123,
    "preChatFormEnabled": true,
    "preChatFormFields": null,
    "preChatFormTitle": null,
    "preChatFormSubtitle": null,
    "loadingDisplayMode": {},
    "loadingStageCopyByLocale": null,
    "loadingLongWaitCopyByLocale": null,
    "loadingLongWaitThresholdSeconds": 123,
    "loadingAnimationUseSharedAsset": true,
    "loadingAnimationSharedAssetUrl": "https://example.com/file.jpg",
    "loadingAnimationAssetUrlsByStage": null,
    "loadingTypingShowCopy": true,
    "toolCardRunningIconUrl": "https://example.com/file.jpg",
    "toolCardCompletedIconUrl": "https://example.com/file.jpg"
  }'

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// Request body (payload)
const data = {
    "avatar": "https://example.com/file.jpg",
    "logo": "https://example.com/file.jpg",
    "description": "Example string",
    "cover": "https://example.com/file.jpg",
    "backUrl": "Example string",
    "isActive": true,
    "theme": {
      "primaryColor": "Example string",
      "navbarTextColor": "Example string",
      "conversationBackgroundColor": "Example string",
      "chatbotMessageTextColor": "Example string",
      "userMessageTextColor": "Example string",
      "chatbotMessageBackgroundColor": "Example string",
      "userMessageBackgroundColor": "Example string",
      "chatbotMessageBackgroundShadowEnabled": true,
      "userMessageBackgroundShadowEnabled": true,
      "chatbotMessageGradientEnabled": true,
      "userMessageGradientEnabled": true
    },
    "darkTheme": {
      "primaryColor": "Example string",
      "navbarTextColor": "Example string",
      "conversationBackgroundColor": "Example string",
      "chatbotMessageTextColor": "Example string",
      "userMessageTextColor": "Example string",
      "chatbotMessageBackgroundColor": "Example string",
      "userMessageBackgroundColor": "Example string",
      "chatbotMessageBackgroundShadowEnabled": true,
      "userMessageBackgroundShadowEnabled": true,
      "chatbotMessageGradientEnabled": true,
      "userMessageGradientEnabled": true
    },
    "enableFileUpload": true,
    "enableDisplayCitations": true,
    "toolDisplayMode": "full",
    "enableAskOptionButtons": true,
    "enableConversationHandoff": true,
    "enableDisplayContextUsage": true,
    "enableDisplayThinking": true,
    "enableUserThinkingControl": true,
    "enableDisplayQueryMetadata": true,
    "enableDisplayHookMarkers": true,
```

```
    "hookMarkerTextInputModify": "Example string",
    "hookMarkerTextOutputModify": "Example string",
    "hookMarkerTextInputBlock": "Example string",
    "hookMarkerTextOutputBlock": "Example string",
    "enableShareConversation": true,
    "enableLocation": true,
    "enableShowPoweredBy": true,
    "poweredByLogo": "https://example.com/file.jpg",
    "enableAnonymous": true,
    "enableDisplayPreviousConversation": true,
    "enableDisplayConversationHistory": true,
    "enableConversationTimer": true,
    "conversationTimerDuration": 123,
    "enableAutoNewConversationOnTimeout": true,
    "enableSatisfactionSurvey": true,
    "satisfactionSurveyDelayMinutes": 123,
    "satisfactionSurveyPrompt": "Example string",
    "enableThemeModeToggle": true,
    "enableDisplayFontSizeSwitch": true,
    "defaultThemeMode": {},
    "enableDownloadCitations": true,
    "customDomain": {
      "domain": "Example string"
    },
    "enableDisplayChatbotAvatar": true,
    "enableDisplayChatbotName": true,
    "buttonIcon": "https://example.com/file.jpg",
    "conversationStartersDisplayCount": 123,
    "preChatFormEnabled": true,
    "preChatFormFields": null,
    "preChatFormTitle": null,
    "preChatFormSubtitle": null,
    "loadingDisplayMode": {},
    "loadingStageCopyByLocale": null,
    "loadingLongWaitCopyByLocale": null,
    "loadingLongWaitThresholdSeconds": 123,
    "loadingAnimationUseSharedAsset": true,
    "loadingAnimationSharedAssetUrl": "https://example.com/file.jpg",
    "loadingAnimationAssetUrlsByStage": null,
    "loadingTypingShowCopy": true,
    "toolCardRunningIconUrl": "https://example.com/file.jpg",
    "toolCardCompletedIconUrl": "https://example.com/file.jpg"
  };

axios.post("https://api.maiagent.ai/api/v1/web-chats/550e8400-e29b-41d4-a716-446655440000/voice-
agent/token/", data, config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/web-chats/550e8400-e29b-41d4-a716-446655440000/voice-agent/token/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# Request body (payload)
data = {
    "avatar": "https://example.com/file.jpg",
    "logo": "https://example.com/file.jpg",
    "description": "Example string",
    "cover": "https://example.com/file.jpg",
    "backUrl": "Example string",
    "isActive": True,
    "theme": {
        "primaryColor": "Example string",
        "navbarTextColor": "Example string",
        "conversationBackgroundColor": "Example string",
        "chatbotMessageTextColor": "Example string",
        "userMessageTextColor": "Example string",
        "chatbotMessageBackgroundColor": "Example string",
        "userMessageBackgroundColor": "Example string",
        "chatbotMessageBackgroundShadowEnabled": True,
        "userMessageBackgroundShadowEnabled": True,
        "chatbotMessageGradientEnabled": True,
        "userMessageGradientEnabled": True
    },
    "darkTheme": {
        "primaryColor": "Example string",
        "navbarTextColor": "Example string",
        "conversationBackgroundColor": "Example string",
        "chatbotMessageTextColor": "Example string",
        "userMessageTextColor": "Example string",
        "chatbotMessageBackgroundColor": "Example string",
        "userMessageBackgroundColor": "Example string",
        "chatbotMessageBackgroundShadowEnabled": True,
        "userMessageBackgroundShadowEnabled": True,
        "chatbotMessageGradientEnabled": True,
        "userMessageGradientEnabled": True
    },
    "enableFileUpload": True,
    "enableDisplayCitations": True,
    "toolDisplayMode": "full",
    "enableAskOptionButtons": True,
    "enableConversationHandoff": True,
    "enableDisplayContextUsage": True,
    "enableDisplayThinking": True,
    "enableUserThinkingControl": True,
    "enableDisplayQueryMetadata": True,
    "enableDisplayHookMarkers": True,
    "hookMarkerTextInputModify": "Example string",
```

```
    "hookMarkerTextOutputModify": "Example string",
    "hookMarkerTextInputBlock": "Example string",
    "hookMarkerTextOutputBlock": "Example string",
    "enableShareConversation": True,
    "enableLocation": True,
    "enableShowPoweredBy": True,
    "poweredByLogo": "https://example.com/file.jpg",
    "enableAnonymous": True,
    "enableDisplayPreviousConversation": True,
    "enableDisplayConversationHistory": True,
    "enableConversationTimer": True,
    "conversationTimerDuration": 123,
    "enableAutoNewConversationOnTimeout": True,
    "enableSatisfactionSurvey": True,
    "satisfactionSurveyDelayMinutes": 123,
    "satisfactionSurveyPrompt": "Example string",
    "enableThemeModeToggle": True,
    "enableDisplayFontSizeSwitch": True,
    "defaultThemeMode": {},
    "enableDownloadCitations": True,
    "customDomain": {
        "domain": "Example string"
    },
    "enableDisplayChatbotAvatar": True,
    "enableDisplayChatbotName": True,
    "buttonIcon": "https://example.com/file.jpg",
    "conversationStartersDisplayCount": 123,
    "preChatFormEnabled": True,
    "preChatFormFields": None,
    "preChatFormTitle": None,
    "preChatFormSubtitle": None,
    "loadingDisplayMode": {},
    "loadingStageCopyByLocale": None,
    "loadingLongWaitCopyByLocale": None,
    "loadingLongWaitThresholdSeconds": 123,
    "loadingAnimationUseSharedAsset": True,
    "loadingAnimationSharedAssetUrl": "https://example.com/file.jpg",
    "loadingAnimationAssetUrlsByStage": None,
    "loadingTypingShowCopy": True,
    "toolCardRunningIconUrl": "https://example.com/file.jpg",
    "toolCardCompletedIconUrl": "https://example.com/file.jpg"
}

response = requests.post(url, json=data, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->post("https://api.maiagent.ai/api/v1/web-chats/550e8400-e29b-41d4-a716-446655440000/voice-agent/token/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'avatar' => 'https://example.com/file.jpg',
            'logo' => 'https://example.com/file.jpg',
            'description' => 'Example string',
            'cover' => 'https://example.com/file.jpg',
            'backUrl' => 'Example string',
            'isActive' => true,
            'theme' => [
                'primaryColor' => 'Example string',
                'navbarTextColor' => 'Example string',
                'conversationBackgroundColor' => 'Example string',
                'chatbotMessageTextColor' => 'Example string',
                'userMessageTextColor' => 'Example string',
                'chatbotMessageBackgroundColor' => 'Example string',
                'userMessageBackgroundColor' => 'Example string',
                'chatbotMessageBackgroundShadowEnabled' => true,
                'userMessageBackgroundShadowEnabled' => true,
                'chatbotMessageGradientEnabled' => true,
                'userMessageGradientEnabled' => true
            ],
            'darkTheme' => [
                'primaryColor' => 'Example string',
                'navbarTextColor' => 'Example string',
                'conversationBackgroundColor' => 'Example string',
                'chatbotMessageTextColor' => 'Example string',
                'userMessageTextColor' => 'Example string',
                'chatbotMessageBackgroundColor' => 'Example string',
                'userMessageBackgroundColor' => 'Example string',
                'chatbotMessageBackgroundShadowEnabled' => true,
                'userMessageBackgroundShadowEnabled' => true,
                'chatbotMessageGradientEnabled' => true,
                'userMessageGradientEnabled' => true
            ],
            'enableFileUpload' => true,
            'enableDisplayCitations' => true,
            'toolDisplayMode' => 'full',
            'enableAskOptionButtons' => true,
            'enableConversationHandoff' => true,
            'enableDisplayContextUsage' => true,
            'enableDisplayThinking' => true,
            'enableUserThinkingControl' => true,
            'enableDisplayQueryMetadata' => true,
```

```
            'enableDisplayHookMarkers' => true,
            'hookMarkerTextInputModify' => 'Example string',
            'hookMarkerTextOutputModify' => 'Example string',
            'hookMarkerTextInputBlock' => 'Example string',
            'hookMarkerTextOutputBlock' => 'Example string',
            'enableShareConversation' => true,
            'enableLocation' => true,
            'enableShowPoweredBy' => true,
            'poweredByLogo' => 'https://example.com/file.jpg',
            'enableAnonymous' => true,
            'enableDisplayPreviousConversation' => true,
            'enableDisplayConversationHistory' => true,
            'enableConversationTimer' => true,
            'conversationTimerDuration' => 123,
            'enableAutoNewConversationOnTimeout' => true,
            'enableSatisfactionSurvey' => true,
            'satisfactionSurveyDelayMinutes' => 123,
            'satisfactionSurveyPrompt' => 'Example string',
            'enableThemeModeToggle' => true,
            'enableDisplayFontSizeSwitch' => true,
            'defaultThemeMode' => new \stdClass(),
            'enableDownloadCitations' => true,
            'customDomain' => [
                'domain' => 'Example string'
            ],
            'enableDisplayChatbotAvatar' => true,
            'enableDisplayChatbotName' => true,
            'buttonIcon' => 'https://example.com/file.jpg',
            'conversationStartersDisplayCount' => 123,
            'preChatFormEnabled' => true,
            'preChatFormFields' => null,
            'preChatFormTitle' => null,
            'preChatFormSubtitle' => null,
            'loadingDisplayMode' => new \stdClass(),
            'loadingStageCopyByLocale' => null,
            'loadingLongWaitCopyByLocale' => null,
            'loadingLongWaitThresholdSeconds' => 123,
            'loadingAnimationUseSharedAsset' => true,
            'loadingAnimationSharedAssetUrl' => 'https://example.com/file.jpg',
            'loadingAnimationAssetUrlsByStage' => null,
            'loadingTypingShowCopy' => true,
            'toolCardRunningIconUrl' => 'https://example.com/file.jpg',
            'toolCardCompletedIconUrl' => 'https://example.com/file.jpg'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response Body

Status Code: 200

Example Response Schema

```
{
  "id": string (uuid)
  "name": string
  "avatar"?: string (uri) // Optional
  "logo"?: string (uri) // Optional
  "description"?: string // Optional
  "cover"?: string (uri) // Optional
  "backUrl"?: string // Optional
  "isActive"?: boolean // Optional
  "enableSpeech": boolean
  "displayConversationStarters": [
    string
  ]
  "theme": {
  {
    "primaryColor"?: string // Optional
    "navbarTextColor"?: string // Optional
    "conversationBackgroundColor"?: string // Optional
    "chatbotMessageTextColor"?: string // Optional
    "userMessageTextColor"?: string // Optional
    "chatbotMessageBackgroundColor"?: string // Optional
    "userMessageBackgroundColor"?: string // Optional
    "chatbotMessageBackgroundShadowEnabled"?: boolean // Optional
    "userMessageBackgroundShadowEnabled"?: boolean // Optional
    "chatbotMessageGradientEnabled"?: boolean // Optional
    "userMessageGradientEnabled"?: boolean // Optional
  }
  }
  "darkTheme": {
  {
    "primaryColor"?: string // Optional
    "navbarTextColor"?: string // Optional
    "conversationBackgroundColor"?: string // Optional
    "chatbotMessageTextColor"?: string // Optional
    "userMessageTextColor"?: string // Optional
    "chatbotMessageBackgroundColor"?: string // Optional
    "userMessageBackgroundColor"?: string // Optional
    "chatbotMessageBackgroundShadowEnabled"?: boolean // Optional
    "userMessageBackgroundShadowEnabled"?: boolean // Optional
    "chatbotMessageGradientEnabled"?: boolean // Optional
    "userMessageGradientEnabled"?: boolean // Optional
  }
  }
  "enableFileUpload"?: boolean // Optional
  "enableDisplayCitations"?: boolean // Optional
  "toolDisplayMode"?: string (enum: full, compact, hidden) // * `full` - Full
* `compact` - Compact
* `hidden` - Hidden (Optional)
  "enableAskOptionButtons"?: boolean // When enabled, ask_user_question options appear as a row of
buttons above the input box, which remains usable. When disabled, the existing overlay panel is used.
This gradual rollout toggle can be disabled at any time to revert the behavior. (Optional)
```

```
  "enableConversationHandoff"?: boolean // When enabled, webchat on this conversation platform
displays the handoff UI (notification bar, summary card, and continue button) and registers handoff
tools. The global handoff toggle in system settings still applies: when it is off, handoff is
disabled everywhere. MaiGPT always displays the UI regardless of this toggle. The context usage
percentage bar at the bottom is controlled separately by "Display context usage". Disabled by
default, so customer-facing webchat shows no handoff UI. This gradual rollout toggle can be disabled
to revert the behavior without rolling back the release. (Optional)
  "enableDisplayContextUsage"?: boolean // When enabled, webchat on this conversation platform
displays a context usage percentage bar below the input box. This is independent of conversation
handoff: handoff toggles (including the global handoff toggle) do not affect it, and it does not
affect the handoff notification bar. MaiGPT always displays the bar regardless of this toggle.
Disabled by default; disabling it reverts the behavior without rolling back the release. (Optional)
  "enableDisplayThinking"?: boolean // Optional
  "enableUserThinkingControl"?: boolean // Optional
  "enableDisplayQueryMetadata"?: boolean // Optional
  "enableDisplayHookMarkers"?: boolean // Optional
  "hookMarkerTextInputModify"?: string // Optional
  "hookMarkerTextOutputModify"?: string // Optional
  "hookMarkerTextInputBlock"?: string // Optional
  "hookMarkerTextOutputBlock"?: string // Optional
  "enableShareConversation"?: boolean // Optional
  "enableLocation"?: boolean // Optional
  "enableShowPoweredBy"?: boolean // Optional
  "poweredByLogo"?: string (uri) // Optional
  "enableAnonymous"?: boolean // Optional
  "enableDisplayPreviousConversation"?: boolean // Optional
  "enableDisplayConversationHistory"?: boolean // Optional
  "enableConversationTimer"?: boolean // Optional
  "conversationTimerDuration"?: integer // Timer timeout duration, ranging from 3-60 minutes
(Optional)
  "enableAutoNewConversationOnTimeout"?: boolean // Optional
  "enableSatisfactionSurvey"?: boolean // Optional
  "satisfactionSurveyDelayMinutes"?: integer // Number of minutes after the last AI reply before the
survey appears, ranging from 1-60 minutes (Optional)
  "satisfactionSurveyPrompt"?: string // Custom survey title text; leave blank to use the default
localized text in the frontend (Optional)
  "accessType":
  {
  }
  "enableThemeModeToggle"?: boolean // Optional
  "enableDisplayFontSizeSwitch"?: boolean // Optional
  "defaultThemeMode"?:  // Optional
  {
  }
  "enableDownloadCitations"?: boolean // Optional
  "customDomain"?:  // Optional
  {
    "id": string (uuid)
    "domain": string
    "status":
    {
    }
  }
  "enableDisplayChatbotAvatar"?: boolean // Optional
  "enableDisplayChatbotName"?: boolean // Optional
  "buttonIcon"?: string (uri) // Optional
  "enableCodeInterpreter": boolean // Read enable_code_interpreter from the inbox's chatbot.
  "voiceAgentEnabled": boolean // Whether the bound chatbot has the voice agent turned on (read-only)
  "conversationStartersDisplayCount"?: integer // Optional
  "includeGreetingInContext": boolean // When enabled, the conversation greeting and the numbered
```

```
conversation starters (in configured order, unshuffled and untruncated) are injected into the LLM
context so the agent can resolve short replies like "1" to the matching starter option.
  "tools": [ // Expose chatbot tools to SDK for the tool_mask selector.

Name resolution prefers ``display_name`` (set on MCP tools, where
``name`` is null) and falls back to ``name`` for API tools where
``display_name`` is null. Tools missing both are skipped — SDK
should never show an unnamed tool to a contact. Quick Menu tools are
static input-bar UI, never an LLM tool, so masking one is meaningless.
    object
  ]
  "preChatFormEnabled"?: boolean // Optional
  "preChatFormFields"?: object // Optional
  "preChatFormTitle"?: object // Optional
  "preChatFormSubtitle"?: object // Optional
  "loadingDisplayMode"?:  // Waiting-experience style. `narrative` shows per-stage copy;
`brand_animation` plays the uploaded asset and hides every system narration line. Defaults to
`narrative`, which with no copy configured behaves exactly as before this field existed.

* `narrative` - Narrative copy
* `brand_animation` - Brand animation (Optional)
  {
  }
  "loadingStageCopyByLocale"?: object // Locale-keyed per-stage waiting copy, shaped {locale: {stage:
text}} where stage is one of LoadingStage. An absent locale or stage falls back to the built-in copy,
so a partially filled dict is valid and never blocks a reply. (Optional)
  "loadingLongWaitCopyByLocale"?: object // Locale-keyed line shown once the wait exceeds
`loading_long_wait_threshold_seconds`, shaped {locale: text}. Written in the brand character voice
for the animation mode, but applies to both modes. Empty means no long-wait line is shown. (Optional)
  "loadingLongWaitThresholdSeconds"?: integer // How long a single reply must be pending before the
long-wait copy appears. (Optional)
  "loadingAnimationUseSharedAsset"?: boolean // True (default) means every stage plays
`loading_animation_shared_asset_url`, so the admin only uploads once. False expands per-stage assets,
each falling back to the shared asset when its own slot is empty. (Optional)
  "loadingAnimationSharedAssetUrl"?: string (uri) // Optional
  "loadingAnimationAssetUrlsByStage"?: object // Shaped {stage: url} keyed by LoadingStage. Only
consulted when `loading_animation_use_shared_asset` is False; a missing stage falls back to the
shared asset. (Optional)
  "loadingTypingShowCopy"?: boolean // Only affects the first "typing" stage. True (default, the pre-
existing behavior) shows the typing-stage copy next to the pre-first-char animation/dot; False plays
only the animation with no text line. Thinking / analyzing / long-wait stages are unaffected.
(Optional)
  "toolCardRunningIconUrl"?: string (uri) // Optional
  "toolCardCompletedIconUrl"?: string (uri) // Optional
  "inbox": object
  "quickMenu": object // Mounted Quick Menu Agent UI config for the web chat input bar; null when
absent (read-only)
}
```

Example Response Values

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "name": "Response string",
  "avatar": "https://example.com/file.jpg",
  "logo": "https://example.com/file.jpg",
  "description": "Response string",
  "cover": "https://example.com/file.jpg",
```

```
  "backUrl": "Response string",
  "isActive": false,
  "enableSpeech": false,
  "displayConversationStarters": [
    "Response string"
  ],
  "theme": {
    "primaryColor": "Response string",
    "navbarTextColor": "Response string",
    "conversationBackgroundColor": "Response string",
    "chatbotMessageTextColor": "Response string",
    "userMessageTextColor": "Response string",
    "chatbotMessageBackgroundColor": "Response string",
    "userMessageBackgroundColor": "Response string",
    "chatbotMessageBackgroundShadowEnabled": false,
    "userMessageBackgroundShadowEnabled": false,
    "chatbotMessageGradientEnabled": false,
    "userMessageGradientEnabled": false
  },
  "darkTheme": {
    "primaryColor": "Response string",
    "navbarTextColor": "Response string",
    "conversationBackgroundColor": "Response string",
    "chatbotMessageTextColor": "Response string",
    "userMessageTextColor": "Response string",
    "chatbotMessageBackgroundColor": "Response string",
    "userMessageBackgroundColor": "Response string",
    "chatbotMessageBackgroundShadowEnabled": false,
    "userMessageBackgroundShadowEnabled": false,
    "chatbotMessageGradientEnabled": false,
    "userMessageGradientEnabled": false
  },
  "enableFileUpload": false,
  "enableDisplayCitations": false,
  "toolDisplayMode": "full",
  "enableAskOptionButtons": false,
  "enableConversationHandoff": false,
  "enableDisplayContextUsage": false,
  "enableDisplayThinking": false,
  "enableUserThinkingControl": false,
  "enableDisplayQueryMetadata": false,
  "enableDisplayHookMarkers": false,
  "hookMarkerTextInputModify": "Response string",
  "hookMarkerTextOutputModify": "Response string",
  "hookMarkerTextInputBlock": "Response string",
  "hookMarkerTextOutputBlock": "Response string",
  "enableShareConversation": false,
  "enableLocation": false,
  "enableShowPoweredBy": false,
  "poweredByLogo": "https://example.com/file.jpg",
  "enableAnonymous": false,
  "enableDisplayPreviousConversation": false,
  "enableDisplayConversationHistory": false,
  "enableConversationTimer": false,
  "conversationTimerDuration": 456,
  "enableAutoNewConversationOnTimeout": false,
  "enableSatisfactionSurvey": false,
  "satisfactionSurveyDelayMinutes": 456,
  "satisfactionSurveyPrompt": "Response string",
  "accessType": {},
```

```
  "enableThemeModeToggle": false,
  "enableDisplayFontSizeSwitch": false,
  "defaultThemeMode": {},
  "enableDownloadCitations": false,
  "customDomain": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "domain": "Response string",
    "status": {}
  },
  "enableDisplayChatbotAvatar": false,
  "enableDisplayChatbotName": false,
  "buttonIcon": "https://example.com/file.jpg",
  "enableCodeInterpreter": false,
  "voiceAgentEnabled": false,
  "conversationStartersDisplayCount": 456,
  "includeGreetingInContext": false,
  "tools": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "Example response name",
      "description": "Example response description"
    }
  ],
  "preChatFormEnabled": false,
  "preChatFormFields": null,
  "preChatFormTitle": null,
  "preChatFormSubtitle": null,
  "loadingDisplayMode": {},
  "loadingStageCopyByLocale": null,
  "loadingLongWaitCopyByLocale": null,
  "loadingLongWaitThresholdSeconds": 456,
  "loadingAnimationUseSharedAsset": false,
  "loadingAnimationSharedAssetUrl": "https://example.com/file.jpg",
  "loadingAnimationAssetUrlsByStage": null,
  "loadingTypingShowCopy": false,
  "toolCardRunningIconUrl": "https://example.com/file.jpg",
  "toolCardCompletedIconUrl": "https://example.com/file.jpg",
  "inbox": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Example response name",
    "description": "Example response description"
  },
  "quickMenu": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Example response name",
    "description": "Example response description"
  }
}
```


Upload a Batch QA File

POST `/api/v1/web-chats/{webchatPk}/batch-qas/`

Parameters

Parameter Name	Required	Type	Description
webchatPk	V	string	

Request Body

Request Parameters

Field	Type	Required	Description
file	string (uri)	Yes	

Example Request Schema

```
{
  "file": string (uri)
}
```

Example Request Values

```
{
  "file": "https://example.com/file.jpg"
}
```

Code Examples

Shell/Bash

```
# API call example (Shell)
curl -X POST "https://api.maiagent.ai/api/v1/web-chats/550e8400-e29b-41d4-a716-
446655440000/batch-qas/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "file": "https://example.com/file.jpg"
  }'

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// Request Body (payload)
const data = {
    "file": "https://example.com/file.jpg"
  };

axios.post("https://api.maiagent.ai/api/v1/web-chats/550e8400-e29b-41d4-a716-446655440000/batch-
qas/", data, config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/web-chats/550e8400-e29b-41d4-a716-446655440000/batch-qas/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# Request Body (payload)
data = {
    "file": "https://example.com/file.jpg"
}

response = requests.post(url, json=data, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->post("https://api.maiagent.ai/api/v1/web-chats/550e8400-e29b-41d4-a716-446655440000/batch-qas/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'file' => 'https://example.com/file.jpg'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response Body

Status Code: 201

Example Response Schema

```
{
  "id": string (uuid)
  "file": string (uri)
  "createdAt": string (timestamp)
}
```

Example Response Values

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "file": "https://example.com/file.jpg",
```

```
  "createdAt": "Response string"
}
```

Export Batch QA to Excel

GET `/api/v1/web-chats/{webchatPk}/batch-qas/{id}/export-excel/`

Parameters

Parameter Name	Required	Type	Description
`id`	V	string	A UUID string identifying this Chatbot Batch QA File.
`webchatPk`	V	string	

Code Examples

Shell/Bash

```
# API call example (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/web-chats/550e8400-e29b-41d4-a716-
446655440000/batch-qas/550e8400-e29b-41d4-a716-446655440000/export-excel/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/web-chats/550e8400-e29b-41d4-a716-446655440000/batch-qas/550e8400-e29b-41d4-a716-446655440000/export-excel/", config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/web-chats/550e8400-e29b-41d4-a716-446655440000/batch-qas/550e8400-e29b-41d4-a716-446655440000/export-excel/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->get("https://api.maiagent.ai/api/v1/web-chats/550e8400-e29b-41d4-a716-446655440000/batch-qas/550e8400-e29b-41d4-a716-446655440000/export-excel/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response Content

Status Code	Description
200	Excel File Download

Get LLM Usage Statistics

GET `/api/v1/chatbots/{chatbotPk}/llm-usage-statistics/`

Parameters

Parameter Name	Required	Type	Description
`chatbotPk`	V	string	A UUID string identifying this Chatbot ID
`endDate`	X	string	End date, format: YYYY-MM-DD

`startDate`	V	string	Start date, format: YYYY-MM-DD
`timeGranularity`	V	string	Time granularity (day/month)

Code Examples

Shell/Bash

```
# API call example (Shell)
curl -X GET "

  -H "Authorization: Api-Key YOUR_API_KEY"

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get(" config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->get(" [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response Content

Status Code: 200

Example Response Schema

```
[
  {
    "llmDetails": [
      {
        "chatbotId": string (uuid)
        "wordsCount": integer
        "inputTokenUsage": integer
        "outputTokenUsage": integer
        "cacheCreationInputTokens": integer
        "cacheReadInputTokens": integer
        "totalTokenUsage": integer
        "llmModelId": string (uuid)
        "llmModelName": string
        "llmModelProvider": string
      }
    ]
    "date"?: string (date) // Date when time_granularity=day (optional)
    "month"?: string (date) // Month when time_granularity=month (first day of the month) (optional)
    "totalWordsCount": integer
    "totalInputTokenUsage": integer
    "totalOutputTokenUsage": integer
    "totalCacheCreationInputTokens": integer
    "totalCacheReadInputTokens": integer
    "totalTokenUsage": integer
  }
]
```

Example Response Values


```
[
  [
    {
      "totalWordsCount": 511,
      "totalInputTokenUsage": 1200,
      "totalOutputTokenUsage": 300,
      "totalCacheCreationInputTokens": 0,
      "totalCacheReadInputTokens": 0,
      "totalTokenUsage": 1500,
      "month": "2025-03-01",
      "llmDetails": [
        {
          "chatbotId": "5b646600-f6e0-4f07-aec7-0207a26c0a9b",
          "wordsCount": 511,
          "inputTokenUsage": 1200,
          "outputTokenUsage": 300,
          "cacheCreationInputTokens": 0,
          "cacheReadInputTokens": 0,
          "totalTokenUsage": 1500,
          "llmModelId": "d4282719-f50e-4a82-88d0-953e202a3383",
          "llmModelName": "GPT-4o-2024-08-06",
          "llmModelProvider": "openai"
        }
      ]
```

```
    }
  ]
]
```


Status Code: 400

Example Response Schema


```
{
  "detail"?: string // Optional
  "valid_types"?: [ // Optional
    string
  ]
}
```


Example Response Values


```
[
  [
    {
      "totalWordsCount": 511,
      "totalInputTokenUsage": 1200,
      "totalOutputTokenUsage": 300,
      "totalCacheCreationInputTokens": 0,
      "totalCacheReadInputTokens": 0,
      "totalTokenUsage": 1500,
      "month": "2025-03-01",
      "llmDetails": [
        {
          "chatbotId": "5b646600-f6e0-4f07-aec7-0207a26c0a9b",
          "wordsCount": 511,
          "inputTokenUsage": 1200,
          "outputTokenUsage": 300,
          "cacheCreationInputTokens": 0,
          "cacheReadInputTokens": 0,
          "totalTokenUsage": 1500,
          "llmModelId": "d4282719-f50e-4a82-88d0-953e202a3383",
          "llmModelName": "GPT-4o-2024-08-06",
          "llmModelProvider": "openai"
        }
      ]
    }
  ]
]
```


Get AI Assistant Statistics

GET `/api/v1/chatbots/{chatbotPk}/statistics/`

Parameters

Parameter Name	Required	Type	Description
`chatbotPk`	V	string	A UUID string identifying this Chatbot ID
`endDate`	X	string	End date (YYYY-MM-DD), defaults to today
`startDate`	X	string	Start date (YYYY-MM-DD), defaults to today
`timeGranularity`	V	string	Time granularity (hour/day/month)

Code Examples

Shell/Bash

```
# API call example (Shell)
curl -X GET "

  -H "Authorization: Api-Key YOUR_API_KEY"

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get(" config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->get(" [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response Content

Status Code: 200

Example Response Schema

```
[
  {
    "datetime": string // Timestamp (milliseconds, string)
    "messagesCount": integer // Message count
    "conversationsCount": integer // Conversation count
    "avgMessagesPerConversation": number (double) // Average messages per conversation
    "avgLikesPerFeedback": number (double) // Satisfaction: likes / (likes + dislikes), 0 when there is no feedback
    "likesCount": integer // Like count (excluding feedback on opening messages; daily/monthly values are totals for the period)
    "dislikesCount": integer // Dislike count (excluding feedback on opening messages; daily/monthly values are totals for the period)
  }
]
```

Example Response Values

```
[
  {
    "datetime": "Response string",
    "messagesCount": 456,
    "conversationsCount": 456,
    "avgMessagesPerConversation": 456,
    "avgLikesPerFeedback": 456,
    "likesCount": 456,
    "dislikesCount": 456
  }
]
```

Example API Call (Shell)

目錄

1. Send Message (Streaming)
2. Send Message (Create)
3. Send an Outgoing Message
4. Create a New Conversation
5. List Messages
6. Retrieve a Specific Message
7. List Conversations
8. Retrieve a Specific Conversation
9. Rename Conversation
10. Delete Conversation
11. Stop AI Response
12. Submit Conversation Satisfaction
13. List Conversation Events
14. Assign Conversation to a Member
15. Claim Conversation
16. Transfer a conversation to another member
17. Return to AI Replies
18. List Conversation Output Files
19. Share a Conversation
20. Quick Share a Conversation
21. List Shared Conversations
22. Retrieve a Shared Conversation
23. Update a Shared Conversation
24. Delete a Shared Conversation
25. Fork a Shared Conversation
26. Retrieve My Shared Conversations
27. Create Message Feedback
28. Update Message Feedback
29. Delete Message Feedback
30. List conversation records
31. Retrieve a conversation record
32. Create a Conversation Record Export Request
33. Get Conversation Record Export Status

Example API Call (Shell)

Send Message (Streaming)

POST `/api/v1/chatbots/{chatbotId}/completions/`

Parameters

Parameter Name	Required	Type	Description
`chatbotId`	V	string	

Request Body

Request Parameters

Field	Type	Required	Description
conversation	string (uuid)	No	Unique conversation identifier; a new conversation is created if empty (optional)
message	object (with 9 properties: content, contentPayload, queryMetadata...)	Yes	Message to send
message.content	string	Yes	Message text; can be an empty string if attachments are provided
message.contentPayload	object	No	Additional message payload in JSON format (optional)
message.queryMetadata	object	No	Query metadata in JSON format (optional)
message.metadata	object	No	Message environment metadata, such as timezone information, in JSON format (optional)
message.attachments	array[AttachmentInput]	No	List of message attachments (optional)
message.toolIds	array[string]	No	List of tool IDs to enable for this message (optional)
message.clientTools	array[any]	No	List of tool definitions provided by the client (such as a Chrome extension) for this message (optional). Each entry must include name(str),

Field	Type	Required	Description
			description(str), and input_schema(dict). When the LLM calls a tool, the backend returns the clientToolCall content and ends the turn without executing the tool.
message.sender	string (uuid)	No	Sender's Contact ID (optional); mutually exclusive with externalUser
message.externalUser	object (with 4 properties: id, name, email...)	No	Ask a question as a user of the calling system (optional): MaiAgent finds or creates a contact by external user ID and associates the conversation with that contact. Mutually exclusive with sender; providing both returns 400
message.externalUser.id	string	Yes	User ID in the calling system (required; exact, case-sensitive string matching; empty or whitespace-only strings return 400). MaiAgent finds or creates a contact by (organization, external user ID). If an organization uses multiple external systems, a system prefix is recommended, such as projects:usr_123
message.externalUser.name	string	No	Contact name (optional); updated when provided, unchanged when omitted, null, or an empty string. For a new contact, defaults to the external user ID if omitted
message.externalUser.email	object	No	Contact email (optional); updated when provided, unchanged when omitted, null, or an empty string. A nonempty value with an invalid format returns 400
message.externalUser.metadata	object	No	Custom contact information (optional), using the same format as metadata in the Contact API; fully replaced

Field	Type	Required	Description
			when provided, unchanged when omitted or null
isStreaming	boolean	No	Whether to stream the response; defaults to false (optional)
waitForAttachments	boolean	No	Whether to wait for attachment processing to finish before entering the agent workflow; defaults to true (optional)

Request Schema Example

```
{
  "conversation"?: string (uuid) // Unique conversation identifier; a new conversation
is created if empty (optional) (Optional)
  "message":  // Message to send
  {
    "content": string // Message text; can be an empty string if attachments are
provided
    "contentPayload"?: object // Additional message payload in JSON format (optional)
(Optional)
    "queryMetadata"?: object // Query metadata in JSON format (optional) (Optional)
    "metadata"?: object // Message environment metadata, such as timezone information,
in JSON format (optional) (Optional)
    "attachments"?: [ // List of message attachments (optional) (Optional)
      {
        "id": string (uuid) // Unique attachment identifier
        "type":  // Attachment type; available values: image (image), video (video, in
development, not yet supported), audio (audio), sticker (sticker, in development, not
yet supported), other (other)

* `image` - Image
* `video` - Video
* `audio` - Audio
* `sticker` - Sticker
* `other` - Other
        {
        }
        "filename": string // Attachment filename
        "file": string (uri) // Attachment file URL
      }
    ]
    "toolIds"?: [ // List of tool IDs to enable for this message (optional) (Optional)
      string (uuid)
    ]
    "clientTools"?: [ // List of tool definitions provided by the client (such as a
Chrome extension) for this message (optional). Each entry must include name(str),
description(str), and input_schema(dict). When the LLM calls a tool, the backend returns
```

```
the clientToolCall content and ends the turn without executing the tool. (Optional)
      object
    ]
    "sender"?: string (uuid) // Sender's Contact ID (optional); mutually exclusive with
externalUser (Optional)
    "externalUser"?:  // Ask a question as a user of the calling system (optional):
MaiAgent finds or creates a contact by external user ID and associates the conversation
with that contact. Mutually exclusive with sender; providing both returns 400 (Optional)
    {
      "id": string // User ID in the calling system (required; exact, case-sensitive
string matching; empty or whitespace-only strings return 400). MaiAgent finds or creates
a contact by (organization, external user ID). If an organization uses multiple external
systems, a system prefix is recommended, such as projects:usr_123
      "name"?: string // Contact name (optional); updated when provided, unchanged when
omitted, null, or an empty string. For a new contact, defaults to the external user ID
if omitted (Optional)
      "email"?: // May have different types (Optional)
      string (email) // Contact email (optional); updated when provided, unchanged when
omitted, null, or an empty string. A nonempty value with an invalid format returns 400
(Optional)
      "metadata"?: object // Custom contact information (optional), using the same
format as metadata in the Contact API; fully replaced when provided, unchanged when
omitted or null (Optional)
    }
  }
  "isStreaming"?: boolean // Whether to stream the response; defaults to false
(optional) (Optional)
  "waitForAttachments"?: boolean // Whether to wait for attachment processing to finish
before entering the agent workflow; defaults to true (optional) (Optional)
}
```

Example Request Values

```
{
  "message": {
    "content": "Hello, please introduce yourself"
  },
  "is_streaming": true
}
```

Code Examples

Shell/Bash

```
# Example API Call (Shell)
curl -X POST "

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "message": {
      "content": "Hello, please introduce yourself"
    },
    "is_streaming": true
  }'

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// Request Body (payload)
const data = {
    "message": {
      "content": "Hello, please introduce yourself"
    },
    "is_streaming": true
  };

axios.post(" data, config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# Request Body (payload)
data = {
    "message": {
        "content": "Hello, please introduce yourself"
    },
    "is_streaming": True
}

response = requests.post(url, json=data, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->post(" [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'message' => [
                'content' => 'Hello, please introduce yourself'
            ],
            'is_streaming' => true
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response Body

Status Code	Description
200	Conversation response content; an event stream when streaming is enabled
202	Attachments are still being indexed: the body `status` is `pending_attachments`; retry later.
400	Invalid request parameters; possible causes include: the Contact ID does not belong to the organization Error codes (X-Error-Code): `contact_not_found`, `contact_organization_mismatch`, `contact_inbox_not_linked`, `contact_permission_denied`, `message_content_required`, `...

401	Error codes (X-Error-Code): `not_authenticated`, `authentication_failed`.
402	Error codes (X-Error-Code): `insufficient_credits`, `insufficient_quota`, `no_active_plan`.
403	Error codes (X-Error-Code): `permission_denied`.
404	Error codes (X-Error-Code): `conversation_not_found`, `not_found`.
429	Error codes (X-Error-Code): `throttled`.

Send Message (Create)

POST `/api/v1/messages/`

Request Body

Request Parameters

Field	Type	Required	Description
conversation	string (uuid)	Yes	
type	string	No	
content	string	No	
contentPayload	object	No	
attachments	array[MessageAttachmentInput]	No	
canvas	object	No	
canvas.name	string	Yes	
canvas.canvasType	object	Yes	
canvas.title	string	Yes	
canvas.content	string	Yes	
slideTemplate	object (with 3 properties: slug, displayName, thumbnailUrls)	No	
slideTemplate.slug	string	Yes	
slideTemplate.displayName	string	Yes	
slideTemplate.thumbnailUrls	array[string]	No	

Field	Type	Required	Description
queryMetadata	object	No	Query metadata controlling the scope of searchable knowledge; see each endpoint's documentation for details
queryMetadata.knowledgeBases	array[object]	No	List of searchable knowledge bases; an empty array or null means none are accessible (no permission); omitted means unrestricted
queryMetadata.labelRelations	object	No	Label filters; an empty conditions array means no label filtering (not a lack of permission). Must be provided together with knowledgeBases. If provided alone, label filtering is not applied to knowledge base retrieval (equivalent to no restrictions)
queryMetadata.labelRelations.operator	string (enum: AND, OR)	Yes	How to combine label conditions
queryMetadata.labelRelations.conditions	array[any]	No	List of label conditions; supports nested operator/conditions combinations
metadata	object	No	Message metadata, such as timezone and other environment information
broadcast	boolean	No	
skipCopilotTrigger	boolean	No	

Field	Type	Required	Description
suggestedForId	string (uuid)	No	
skillIds	array[string]	No	Per-message selected skill IDs from the WebChat client (camelCase: skillIds).
toolIds	array[string]	No	Per-message selected tool IDs from the WebChat client (camelCase: toolIds).
templateId	string (uuid)	No	Document/sheet template ID for file-level compilation (camelCase: templateId).

Request Schema Example

```
{
  "conversation": string (uuid)
  "type"?: string // Optional
  "content"?: string // Optional
  "contentPayload"?: object // Optional
  "attachments"?: [ // Optional
    {
      "id": string (uuid) // ID of an already-uploaded attachment, as returned by the
attachment upload endpoint. Required: a missing, null or non-UUID id is rejected with
HTTP 400 and the message is not created.
      "type"?:  // Optional
      {
      }
      "filename": string
      "file": string (uri)
      "conversation"?: string (uuid) // Optional
    }
  ]
  "canvas"?: { // Optional
  {
    "name": string
    "canvasType":
    {
    }
    "title": string
    "content": string
  }
  }
```

```
  "slideTemplate"?:  // Optional
  {
    "slug": string
    "displayName": string
    "thumbnailUrls"?: [ // Optional
      string
    ]
  }
  "queryMetadata"?: { // Query metadata controlling the scope of searchable knowledge;
see each endpoint's documentation for details (Optional)
  {
    "knowledgeBases"?: [ // List of searchable knowledge bases; an empty array or null
means none are accessible (no permission); omitted means unrestricted (Optional)
      {
        "knowledgeBaseId": string (uuid) // Knowledge base ID
        "chatbotFileIds"?: [ // List of file IDs (excluded or exclusively selected
depending on hasUserSelectedAll) (Optional)
          string (uuid)
        ]
        "knowledgeBaseFileIds"?: [ // List of file IDs (the new name for chatbotFileIds;
this field takes precedence when both are provided) (Optional)
          string (uuid)
        ]
        "faqIds"?: [ // List of FAQ IDs (excluded or exclusively selected depending on
hasUserSelectedAll) (Optional)
          string (uuid)
        ]
        "hasUserSelectedAll"?: boolean // true selects all knowledge base content except
the listed items; false selects only the listed items (Optional)
      }
    ]
    "labelRelations"?: { // Label filters; an empty conditions array means no label
filtering (not a lack of permission). Must be provided together with knowledgeBases. If
provided alone, label filtering is not applied to knowledge base retrieval (equivalent
to no restrictions) (Optional)
    {
      "operator": string (enum: AND, OR) // How to combine label conditions
      "conditions"?: [ // List of label conditions; supports nested operator/conditions
combinations (Optional)
        object
      ]
    }
    }
  }
  }
  "metadata"?: object // Message metadata, such as timezone and other environment
information (Optional)
  "broadcast"?: boolean // Optional
  "skipCopilotTrigger"?: boolean // Optional
  "suggestedForId"?: string (uuid) // Optional
  "skillIds"?: [ // Per-message selected skill IDs from the WebChat client (camelCase:
skillIds). (Optional)
    string (uuid)
```

```
  ]
  "toolIds"?: [ // Per-message selected tool IDs from the WebChat client (camelCase:
toolIds). (Optional)
    string (uuid)
  ]
  "templateId"?: string (uuid) // Document/sheet template ID for file-level compilation
(camelCase: templateId). (Optional)
}
```

Example Request Values


```
{
  "conversation": "c96a0fb9-d106-4b16-8706-3906533bafa2",
  "sender": {
    "id": 2.992461161002561e+38,
    "name": "jessiekuo",
    "avatar": "https://media-dev.maiagent.ai/static/images/default-user-avatar.png"
  },
  "type": "incoming",
  "content": "This is a test message",
  "contentPayload": {
    "content": "This is a test message",
    "items": [
      {
        "type": "text",
        "text": "This is a test message",
        "startTimestamp": null,
        "citations": []
      }
    ],
    "metadata": null
  },
  "feedback": null,
  "createdAt": "1748314926000",
  "attachments": [],
  "citations": [],
  "citationNodes": [],
  "canvas": {
    "id": "034eecd7-e0f4-46e9-88cb-4fefdb5b7ddd",
    "name": "system-architecture-diagram",
    "canvasType": "markdown",
    "title": "System Architecture Diagram",
    "content": "~<del>mermaid\ngraph TD\n    A[User] --> B[Frontend Interface]\n    B --
> C[API Layer]\n    C --> D[Database]\n</del>~",
    "createdAt": "1748314926000"
  }
}
```

Code Examples

Shell/Bash

```
# Example API Call (Shell)
curl -X POST "https://api.maiagent.ai/api/v1/messages/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "conversation": "c96a0fb9-d106-4b16-8706-3906533bafa2",
    "sender": {
      "id": 2.992461161002561e+38,
      "name": "jessiekuo",
      "avatar": "https://media-dev.maiagent.ai/static/images/default-user-
avatar.png"
    },
    "type": "incoming",
    "content": "This is a test message",
    "contentPayload": {
      "content": "This is a test message",
      "items": [
        {
          "type": "text",
          "text": "This is a test message",
          "startTimestamp": null,
          "citations": []
        }
      ],
      "metadata": null
    },
    "feedback": null,
    "createdAt": "1748314926000",
    "attachments": [],
    "citations": [],
    "citationNodes": [],
    "canvas": {
      "id": "034eecd7-e0f4-46e9-88cb-4fefdb5b7ddd",
      "name": "system-architecture-diagram",
      "canvasType": "markdown",
      "title": "System Architecture Diagram",
      "content": "~mermaid\ngraph TD\n    A[User] --> B[Frontend Interface]\n    B
--> C[API Layer]\n    C --> D[Database]\n~",
      "createdAt": "1748314926000"
    }
  }'

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// Request Body (payload)
const data = {
    "conversation": "c96a0fb9-d106-4b16-8706-3906533bafa2",
    "sender": {
      "id": 2.992461161002561e+38,
      "name": "jessiekuo",
      "avatar": "https://media-dev.maiagent.ai/static/images/default-user-
avatar.png"
    },
    "type": "incoming",
    "content": "This is a test message",
    "contentPayload": {
      "content": "This is a test message",
      "items": [
        {
          "type": "text",
          "text": "This is a test message",
          "startTimestamp": null,
          "citations": []
        }
      ],
      "metadata": null
    },
    "feedback": null,
    "createdAt": "1748314926000",
    "attachments": [],
    "citations": [],
    "citationNodes": [],
    "canvas": {
      "id": "034eecd7-e0f4-46e9-88cb-4fefdb5b7ddd",
      "name": "system-architecture-diagram",
      "canvasType": "markdown",
      "title": "System Architecture Diagram",
      "content": "~mermaid\ngraph TD\n    A[User] --> B[Frontend Interface]\n    B
--> C[API Layer]\n    C --> D[Database]\n~",
      "createdAt": "1748314926000"
    }
  };
```

```
axios.post("https://api.maiagent.ai/api/v1/messages/", data, config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/messages/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# Request Body (payload)
data = {
    "conversation": "c96a0fb9-d106-4b16-8706-3906533bafa2",
    "sender": {
        "id": 2.992461161002561e+38,
        "name": "jessiekuo",
        "avatar": "https://media-dev.maiagent.ai/static/images/default-user-
avatar.png"
    },
    "type": "incoming",
    "content": "This is a test message",
    "contentPayload": {
        "content": "This is a test message",
        "items": [
            {
                "type": "text",
                "text": "This is a test message",
                "startTimestamp": None,
                "citations": []
            }
        ],
        "metadata": None
    },
    "feedback": None,
    "createdAt": "1748314926000",
    "attachments": [],
    "citations": [],
    "citationNodes": [],
    "canvas": {
        "id": "034eecd7-e0f4-46e9-88cb-4fefdb5b7ddd",
        "name": "system-architecture-diagram",
        "canvasType": "markdown",
        "title": "System Architecture Diagram",
        "content": "~mermaid\ngraph TD\n    A[User] --> B[Frontend Interface]\n
B --> C[API Layer]\n    C --> D[Database]\n~",
        "createdAt": "1748314926000"
    }
}

response = requests.post(url, json=data, headers=headers)
```

```
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->post("https://api.maiagent.ai/api/v1/messages/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'conversation' => 'c96a0fb9-d106-4b16-8706-3906533bafa2',
            'sender' => [
                'id' => 2.992461161002561e+38,
                'name' => 'jessiekuo',
                'avatar' => 'https://media-dev.maiagent.ai/static/images/default-
user-avatar.png'
            ],
            'type' => 'incoming',
            'content' => 'This is a test message',
            'contentPayload' => [
                'content' => 'This is a test message',
                'items' => [
                    [
                        'type' => 'text',
                        'text' => 'This is a test message',
                        'startTimestamp' => null,
                        'citations' => []
                    ]
                ],
                'metadata' => null
            ],
            'feedback' => null,
            'createdAt' => '1748314926000',
            'attachments' => [],
            'citations' => [],
            'citationNodes' => [],
            'canvas' => [
                'id' => '034eecd7-e0f4-46e9-88cb-4fefdb5b7ddd',
                'name' => 'system-architecture-diagram',
                'canvasType' => 'markdown',
                'title' => 'System Architecture Diagram',
                'content' => '~~~mermaid
graph TD
    A[User] --> B[Frontend Interface]
    B --> C[API Layer]
    C --> D[Database]
```

```
    ~',
                    'createdAt' => '1748314926000'
                ]
            ]
        ]);

        $data = json_decode($response->getBody(), true);
        echo "Response received successfully:\n";
        print_r($data);
    } catch (Exception $e) {
        echo 'Request error: ' . $e->getMessage();
    }
    ?>
```

Response Body

Status Code: 201

Response Schema Example

```
{
  "id": string (uuid)
  "conversation": string (uuid)
  "sender":
  {
    "id": string (uuid)
    "name": string
    "avatar": string
    "email"?: string (email) // Optional
    "phoneNumber"?: string // Optional
  }
  "type"?: string // Optional
  "content"?: string // Optional
  "contentPayload"?: object // Optional
  "feedback":
  {
    "id": string (uuid)
    "type":
    {
    }
    "suggestion"?: string // Optional
    "updatedAt": string (timestamp)
  }
  "createdAt": string (timestamp)
```

```
  "attachments"?: [ // Optional
    {
      "id": string (uuid) // ID of an already-uploaded attachment, as returned by the
attachment upload endpoint. Required: a missing, null or non-UUID id is rejected with
HTTP 400 and the message is not created.
      "type"?:  // Optional
      {
      }
      "filename": string
      "file": string (uri)
      "expiresAt": string // ISO datetime when this attachment will be auto-deleted.

For conversation-bound attachments: conversation.last_message_created_at +
retention_days.
For attachments without a conversation: created_at + retention_days.
Returns None when cleanup is disabled (effective_from not set).
      "conversation"?: string (uuid) // Optional
    }
  ]
  "citations": [
    {
      "id": string (uuid)
      "filename": string // File name
      "file": string (uri) // File to upload
      "fileType": string
      "knowledgeBase"?:  // Optional
      {
        "id": string (uuid)
        "name": string
      }
      "size": integer // File size in bytes
      "status":
      {
      }
      "parser":
      {
        "id": string (uuid)
        "name": string
        "provider":
        {
        }
        "isTimestampSttProvider": boolean
      }
      "labels"?: [ // Optional
        {
          "id": string (uuid)
          "name": string
        }
      ]
      "rawUserDefineMetadata"?: object // Optional
      "speakerLabels": [
        {
          "id": string (uuid)
```

```
          "originalLabel": string // Original speaker label from diarization (e.g.,
SPEAKER_00)
          "customName"?: string // User-defined speaker name (e.g., John) (Optional)
          "displayName": string
        }
      ]
      "vectorStorageSize": integer // Size of vectors for this file in Elasticsearch
(bytes)
      "chunksCount": integer // Number of chunks/nodes generated from this file
      "waitingTime": number (double)
      "processingTime": number (double)
      "processingTimeDetails": object
      "ocrStatus": string // OCR result for scanned pages: done, skipped, partial, off;
null before parsing or for older files
      "ocrSkippedReason": string // Reason OCR was not performed on scanned pages:
no_azure_settings, azure_unavailable, insufficient_credits, transient_error,
time_budget, disabled; null when completed
      "previewUrl": string // For presentations (pptx/ppt), returns the URL of a
previewable PDF derivative (displayed with the frontend PDF viewer); None for other
files.

Generate URLs with the same CustomizedFileFieldSerializer as the `file` field to ensure
consistent formatting (including each
storage provider's presign/host rules). Do not use get_absolute_url(), which produces
incorrectly formatted URLs.
      "createdAt": string (timestamp)
    }
  ]
  "citationNodes": [
    {
      "chatbotTextNode": {
      {
        "id": string (uuid)
        "charactersCount": integer
        "hitsCount": integer
        "text": string
        "updatedAt": string (timestamp)
        "filename": string
        "chatbotFile": object // Return complete ChatbotFile information, including the
file URL and type, to support frontend image previews
        "knowledgeBaseFile": object // Same as get_chatbot_file, for backward
compatibility
        "pageNumber": integer // Backward-compatible alias of ``page_start``.
        "pageStart": integer
        "pageEnd": integer
        "citationTitle": string // Source title shown on the inline citation hover card.
        "citationDescription": string // Source description shown on the inline citation
hover card.
        "citationQuote": string // Quoted text snippet shown on the inline citation
hover card.
        "hasImage": boolean // Determine whether an image is present (check the file
type or Markdown images in text)
        "imageUrl": string // Extract the image URL (prefer the file URL; otherwise
```

```
extract it from Markdown)
        "displayText": string // Return the full text with Markdown image markup removed
        "displayTitle": string // Return the display title (fallback: citation_title ->
filename)
        "highlightedText": string // Return text with matched terms wrapped in
``<mark>`` tags.

Priority:
1. ES/OpenSearch native highlight (set by retrieve_api via ``_es_highlighted_text``)
2. Python regex fallback (keyword-based, works for all backends)
        "labels": [
          {
            "id": string (uuid)
            "name": string
          }
        ]
        "rawUserDefineMetadata"?: object // Metadata keys and values defined by the
user. (Optional)
        "metadataEnabledForSearch": object // Map each user-defined metadata key on this
node to whether it was sent into the LLM.

A key reaches the LLM only when its ``MetadataKey.enabled_for_search`` is True *and*
the node carries a value for it. Since this maps over ``raw_user_define_metadata``
(the keys the cited-documents block displays, all of which have a value),
``enabled_for_search`` alone decides the flag. The source of truth is the node's
knowledge base ``MetadataKey`` current setting, matching the AI Search indicator.
        "startCharIdx": integer
        "endCharIdx": integer
      }
      }
      "score"?: number (double) // Optional
      "displayScore": integer
      "citationNumber"?: integer // Citation number matching the [1], [2] markers in the
reply content (Optional)
      "highlightedText"?: string // ES/OpenSearch highlight result with <mark> tags
(Optional)
    }
  ]
  "canvas"?: { // Optional
  {
    "id": string (uuid)
    "name": string
    "canvasType":
    {
    }
    "title": string
    "content": string
    "createdAt": string (timestamp)
  }
  }
  "slideTemplate"?:  // Optional
  {
    "slug": string
```

```
    "displayName": string
    "thumbnailUrls"?: [ // Optional
      string
    ]
  }
  "queryMetadata"?: { // Query metadata that controls the scope of searchable knowledge;
see the description of each endpoint (Optional)
  {
    "knowledgeBases"?: [ // List of searchable knowledge bases; an empty array or null
means none can be searched (no permission); omitting it imposes no restriction
(Optional)
      {
        "knowledgeBaseId": string (uuid) // Knowledge base ID
        "chatbotFileIds"?: [ // List of file IDs (excluded or exclusively selected
depending on hasUserSelectedAll) (Optional)
          string (uuid)
        ]
        "knowledgeBaseFileIds"?: [ // List of file IDs (the new name for chatbotFileIds;
this field takes precedence when both are provided) (Optional)
          string (uuid)
        ]
        "faqIds"?: [ // List of FAQ IDs (excluded or exclusively selected depending on
hasUserSelectedAll) (Optional)
          string (uuid)
        ]
        "hasUserSelectedAll"?: boolean // true selects all knowledge base content except
the listed items; false selects only the listed items (Optional)
      }
    ]
    "labelRelations"?: { // Label filter criteria; an empty conditions array means no
label filtering (not a lack of permission). Must be provided together with
knowledgeBases; when provided alone, knowledge base retrieval does not apply label
filtering (equivalent to no restriction) (Optional)
    {
      "operator": string (enum: AND, OR) // How to combine label conditions
      "conditions"?: [ // List of label conditions; supports nested operator/conditions
combinations (Optional)
        object
      ]
    }
    }
  }
  }
  "metadata"?: object // Message metadata, such as timezone and other environment
information (Optional)
  "recordId": string // Return the ChatbotRecord ID corresponding to the Message

Note:
    For unsaved Messages (such as virtual Messages during streaming), return None
directly
    to avoid triggering a DB query on the OneToOneField reverse relation (the N+1
problem).
  "broadcast"?: boolean // Optional
```

```
  "skipCopilotTrigger"?: boolean // Optional
  "activeRevisionNumber": integer
  "revisions": [
    {
      "id": string (uuid)
      "revisionNumber": integer
      "content": string
      "contentPayload": object
      "isActive": boolean
      "createdAt": string (timestamp)
    }
  ]
  "suggestedForId"?: string (uuid) // Optional
  "suggestionStatus": string
  "suggestionTriggerSource": string
  "suggestionError": string
  "retryCount": integer // How many times the LLM call was auto-retried during this
message generation. Currently only Bedrock first-chunk stall triggers retry (max 1).
Detailed per-attempt records live in metadata["retry_attempts"].
  "skillIds"?: [ // Per-message selected skill IDs from the WebChat client (camelCase:
skillIds). (Optional)
    string (uuid)
  ]
  "toolIds"?: [ // Per-message selected tool IDs from the WebChat client (camelCase:
toolIds). (Optional)
    string (uuid)
  ]
  "templateId"?: string (uuid) // Document/sheet template ID for file-level compilation
(camelCase: templateId). (Optional)
  "videoGeneration": object // Return the latest GeneratedVideo state for FE reload
recovery;
``errorMessage`` is blank to match the socket emit (raw value stays on the DB row).
  "isGreeting": boolean // Whether this message is a greeting message.
}
```

Example Response Values

```
{
  "conversation": "c96a0fb9-d106-4b16-8706-3906533bafa2",
  "sender": {
    "id": 2.992461161002561e+38,
    "name": "jessiekuo",
    "avatar": "https://media-dev.maiagent.ai/static/images/default-user-avatar.png"
  },
  "type": "incoming",
  "content": "This is a test message",
  "contentPayload": {
    "content": "This is a test message",
    "items": [
      {
        "type": "text",
```

```
        "text": "This is a test message",
        "startTimestamp": null,
        "citations": []
      }
    ],
    "metadata": null
  },
  "feedback": null,
  "createdAt": "1748314926000",
  "attachments": [],
  "citations": [],
  "citationNodes": [],
  "canvas": {
    "id": "034eecd7-e0f4-46e9-88cb-4fefdb5b7ddd",
    "name": "system-architecture-diagram",
    "canvasType": "markdown",
    "title": "System Architecture Diagram",
    "content": "~<del>mermaid\ngraph TD\n    A[User] --> B[Frontend Interface]\n    B --
> C[API Layer]\n    C --> D[Database]\n</del>~",
    "createdAt": "1748314926000"
  }
}
```


Send an Outgoing Message

POST `/api/v1/messages/outgoing/`

Request Body

Request Parameters

Field	Type	Required	Description
conversation	string (uuid)	Yes	
type	string	No	
content	string	No	
contentPayload	object	No	
attachments	array[MessageAttachmentInput]	No	
canvas	object	No	

Field	Type	Required	Description
canvas.name	string	Yes	
canvas.canvasType	object	Yes	
canvas.title	string	Yes	
canvas.content	string	Yes	
slideTemplate	object (with 3 properties: slug, displayName, thumbnailUrls)	No	
slideTemplate.slug	string	Yes	
slideTemplate.displayName	string	Yes	
slideTemplate.thumbnailUrls	array[string]	No	
queryMetadata	object	No	Query metadata that controls the scope of searchable knowledge; see the description of each endpoint
queryMetadata.knowledgeBases	array[object]	No	List of searchable knowledge bases; an empty array or null means none can be searched (no permission); omitting it imposes no restriction
queryMetadata.labelRelations	object	No	Label filter criteria; an empty conditions array means no label filtering (not a lack of permission). Must be provided together with knowledgeBases; when provided alone, knowledge base retrieval does not apply label filtering (equivalent to no restriction)
queryMetadata.labelRelations.operator	string (enum: AND, OR)	Yes	How to combine label conditions
queryMetadata.labelRelations.conditions	array[any]	No	List of label conditions;

Field	Type	Required	Description
			supports nested operator/conditions combinations
metadata	object	No	Message metadata, such as timezone and other environment information
broadcast	boolean	No	
skipCopilotTrigger	boolean	No	
suggestedForId	string (uuid)	No	
skillIds	array[string]	No	Per-message selected skill IDs from the WebChat client (camelCase: skillIds).
toolIds	array[string]	No	Per-message selected tool IDs from the WebChat client (camelCase: toolIds).
templateId	string (uuid)	No	Document/sheet template ID for file-level compilation (camelCase: templateId).

Example Request Schema

```
{
  "conversation": string (uuid)
  "type"?: string // Optional
  "content"?: string // Optional
  "contentPayload"?: object // Optional
  "attachments"?: [ // Optional
    {
      "id": string (uuid) // ID of an already-uploaded attachment, as returned by the
attachment upload endpoint. Required: a missing, null or non-UUID id is rejected with
HTTP 400 and the message is not created.
      "type"?:  // Optional
      {
      }
      "filename": string
      "file": string (uri)
      "conversation"?: string (uuid) // Optional
```

```
    }
  ]
  "canvas"?: { // Optional
  {
    "name": string
    "canvasType":
    {
    }
    "title": string
    "content": string
  }
  }
  "slideTemplate"?:  // Optional
  {
    "slug": string
    "displayName": string
    "thumbnailUrls"?: [ // Optional
      string
    ]
  }
  "queryMetadata"?: { // Query metadata that controls the scope of searchable knowledge;
see the description of each endpoint (Optional)
  {
    "knowledgeBases"?: [ // List of searchable knowledge bases; an empty array or null
means none can be searched (no permission); omitting it imposes no restriction
(Optional)
      {
        "knowledgeBaseId": string (uuid) // Knowledge base ID
        "chatbotFileIds"?: [ // List of file IDs (excluded or exclusively selected
depending on hasUserSelectedAll) (Optional)
          string (uuid)
        ]
        "knowledgeBaseFileIds"?: [ // List of file IDs (the new name for chatbotFileIds;
this field takes precedence when both are provided) (Optional)
          string (uuid)
        ]
        "faqIds"?: [ // List of FAQ IDs (excluded or exclusively selected depending on
hasUserSelectedAll) (Optional)
          string (uuid)
        ]
        "hasUserSelectedAll"?: boolean // true selects all knowledge base content except
the listed items; false selects only the listed items (Optional)
      }
    ]
    "labelRelations"?: { // Label filter criteria; an empty conditions array means no
label filtering (not a lack of permission). Must be provided together with
knowledgeBases; when provided alone, knowledge base retrieval does not apply label
filtering (equivalent to no restriction) (Optional)
    {
      "operator": string (enum: AND, OR) // How to combine label conditions
      "conditions"?: [ // List of label conditions; supports nested operator/conditions
combinations (Optional)
        object
```

```
      ]
    }
    }
  }
  }
  "metadata"?: object // Message metadata, such as timezone and other environment
information (Optional)
  "broadcast"?: boolean // Optional
  "skipCopilotTrigger"?: boolean // Optional
  "suggestedForId"?: string (uuid) // Optional
  "skillIds"?: [ // Per-message selected skill IDs from the WebChat client (camelCase:
skillIds). (Optional)
    string (uuid)
  ]
  "toolIds"?: [ // Per-message selected tool IDs from the WebChat client (camelCase:
toolIds). (Optional)
    string (uuid)
  ]
  "templateId"?: string (uuid) // Document/sheet template ID for file-level compilation
(camelCase: templateId). (Optional)
}
```

Example Request Values

```
{
  "conversation": "550e8400-e29b-41d4-a716-446655440000",
  "type": "Example string",
  "content": "Hello! I would like to learn about your products.",
  "contentPayload": null,
  "attachments": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "type": {},
      "filename": "document.pdf",
      "file": "https://example.com/file.jpg",
      "conversation": "550e8400-e29b-41d4-a716-446655440000"
    }
  ],
  "canvas": {
    "name": "Example name",
    "canvasType": {},
    "title": "Example name",
    "content": "Hello! I would like to learn about your products."
  },
  "slideTemplate": {
    "slug": "Example string",
    "displayName": "Example string",
    "thumbnailUrls": [
      "Example string"
    ]
  },
```

```
  "queryMetadata": {
    "knowledgeBases": [
      {
        "knowledgeBaseId": "550e8400-e29b-41d4-a716-446655440000",
        "chatbotFileIds": [
          "550e8400-e29b-41d4-a716-446655440000"
        ],
        "knowledgeBaseFileIds": [
          "550e8400-e29b-41d4-a716-446655440000"
        ],
        "faqIds": [
          "550e8400-e29b-41d4-a716-446655440000"
        ],
        "hasUserSelectedAll": true
      }
    ],
    "labelRelations": {
      "operator": "AND",
      "conditions": [
        null
      ]
    }
  },
  "metadata": null,
  "broadcast": true,
  "skipCopilotTrigger": true,
  "suggestedForId": "550e8400-e29b-41d4-a716-446655440000",
  "skillIds": [
    "550e8400-e29b-41d4-a716-446655440000"
  ],
  "toolIds": [
    "550e8400-e29b-41d4-a716-446655440000"
  ],
  "templateId": "550e8400-e29b-41d4-a716-446655440000"
}
```


Code Examples

Shell/Bash

```
# API call example (Shell)
curl -X POST "https://api.maiagent.ai/api/v1/messages/outgoing/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "conversation": "550e8400-e29b-41d4-a716-446655440000",
    "type": "Example string",
    "content": "Hello! I would like to learn about your products.",
    "contentPayload": null,
    "attachments": [
      {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "type": {},
        "filename": "document.pdf",
        "file": "https://example.com/file.jpg",
        "conversation": "550e8400-e29b-41d4-a716-446655440000"
      }
    ],
    "canvas": {
      "name": "Example name",
      "canvasType": {},
      "title": "Example name",
      "content": "Hello! I would like to learn about your products."
    },
    "slideTemplate": {
      "slug": "Example string",
      "displayName": "Example string",
      "thumbnailUrls": [
        "Example string"
      ]
    },
    "queryMetadata": {
      "knowledgeBases": [
        {
          "knowledgeBaseId": "550e8400-e29b-41d4-a716-446655440000",
          "chatbotFileIds": [
            "550e8400-e29b-41d4-a716-446655440000"
          ],
          "knowledgeBaseFileIds": [
            "550e8400-e29b-41d4-a716-446655440000"
          ],
          "faqIds": [
            "550e8400-e29b-41d4-a716-446655440000"
          ],
          "hasUserSelectedAll": true
```

```
        }
      ],
      "labelRelations": {
        "operator": "AND",
        "conditions": [
          null
        ]
      }
    },
    "metadata": null,
    "broadcast": true,
    "skipCopilotTrigger": true,
    "suggestedForId": "550e8400-e29b-41d4-a716-446655440000",
    "skillIds": [
      "550e8400-e29b-41d4-a716-446655440000"
    ],
    "toolIds": [
      "550e8400-e29b-41d4-a716-446655440000"
    ],
    "templateId": "550e8400-e29b-41d4-a716-446655440000"
  }'

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// Request Body (payload)
const data = {
    "conversation": "550e8400-e29b-41d4-a716-446655440000",
    "type": "Example string",
    "content": "Hello! I would like to learn about your products.",
    "contentPayload": null,
    "attachments": [
      {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "type": {},
        "filename": "document.pdf",
        "file": "https://example.com/file.jpg",
        "conversation": "550e8400-e29b-41d4-a716-446655440000"
      }
    ],
    "canvas": {
      "name": "Example name",
      "canvasType": {},
      "title": "Example name",
      "content": "Hello! I would like to learn about your products."
    },
    "slideTemplate": {
      "slug": "Example string",
      "displayName": "Example string",
      "thumbnailUrls": [
        "Example string"
      ]
    },
    "queryMetadata": {
      "knowledgeBases": [
        {
          "knowledgeBaseId": "550e8400-e29b-41d4-a716-446655440000",
          "chatbotFileIds": [
            "550e8400-e29b-41d4-a716-446655440000"
          ],
          "knowledgeBaseFileIds": [
            "550e8400-e29b-41d4-a716-446655440000"
          ],
```

```
            "faqIds": [
              "550e8400-e29b-41d4-a716-446655440000"
            ],
            "hasUserSelectedAll": true
          }
        ],
        "labelRelations": {
          "operator": "AND",
          "conditions": [
            null
          ]
        }
      },
      "metadata": null,
      "broadcast": true,
      "skipCopilotTrigger": true,
      "suggestedForId": "550e8400-e29b-41d4-a716-446655440000",
      "skillIds": [
        "550e8400-e29b-41d4-a716-446655440000"
      ],
      "toolIds": [
        "550e8400-e29b-41d4-a716-446655440000"
      ],
      "templateId": "550e8400-e29b-41d4-a716-446655440000"
    };

  axios.post("https://api.maiagent.ai/api/v1/messages/outgoing/", data, config)
    .then(response => {
      console.log('Response received successfully:');
      console.log(response.data);
    })
    .catch(error => {
      console.error('Request error:');
      console.error(error.response?.data || error.message);
    });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/messages/outgoing/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# Request Body (payload)
data = {
    "conversation": "550e8400-e29b-41d4-a716-446655440000",
    "type": "Example string",
    "content": "Hello! I would like to learn about your products.",
    "contentPayload": None,
    "attachments": [
        {
            "id": "550e8400-e29b-41d4-a716-446655440000",
            "type": {},
            "filename": "document.pdf",
            "file": "https://example.com/file.jpg",
            "conversation": "550e8400-e29b-41d4-a716-446655440000"
        }
    ],
    "canvas": {
        "name": "Example name",
        "canvasType": {},
        "title": "Example name",
        "content": "Hello! I would like to learn about your products."
    },
    "slideTemplate": {
        "slug": "Example string",
        "displayName": "Example string",
        "thumbnailUrls": [
            "Example string"
        ]
    },
    "queryMetadata": {
        "knowledgeBases": [
            {
                "knowledgeBaseId": "550e8400-e29b-41d4-a716-446655440000",
                "chatbotFileIds": [
                    "550e8400-e29b-41d4-a716-446655440000"
                ],
                "knowledgeBaseFileIds": [
                    "550e8400-e29b-41d4-a716-446655440000"
                ],
                "faqIds": [
                    "550e8400-e29b-41d4-a716-446655440000"
```

```
                ],
                "hasUserSelectedAll": True
            }
        ],
        "labelRelations": {
            "operator": "AND",
            "conditions": [
                None
            ]
        }
    },
    "metadata": None,
    "broadcast": True,
    "skipCopilotTrigger": True,
    "suggestedForId": "550e8400-e29b-41d4-a716-446655440000",
    "skillIds": [
        "550e8400-e29b-41d4-a716-446655440000"
    ],
    "toolIds": [
        "550e8400-e29b-41d4-a716-446655440000"
    ],
    "templateId": "550e8400-e29b-41d4-a716-446655440000"
}

response = requests.post(url, json=data, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request failed:", e)
```

PHP

```
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->post("https://api.maiagent.ai/api/v1/messages/outgoing/",
[
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'conversation' => '550e8400-e29b-41d4-a716-446655440000',
            'type' => 'Example string',
            'content' => 'Hello! I would like to learn about the product.',
            'contentPayload' => null,
            'attachments' => [
                [
                    'id' => '550e8400-e29b-41d4-a716-446655440000',
                    'type' => new \stdClass(),
                    'filename' => 'document.pdf',
                    'file' => 'https://example.com/file.jpg',
                    'conversation' => '550e8400-e29b-41d4-a716-446655440000'
                ]
            ],
            'canvas' => [
                'name' => 'Example name',
                'canvasType' => new \stdClass(),
                'title' => 'Example name',
                'content' => 'Hello! I would like to learn about the product.'
            ],
            'slideTemplate' => [
                'slug' => 'Example string',
                'displayName' => 'Example string',
                'thumbnailUrls' => [
                    'Example string'
                ]
            ],
            'queryMetadata' => [
                'knowledgeBases' => [
                    [
                        'knowledgeBaseId' => '550e8400-e29b-41d4-a716-
446655440000',
                        'chatbotFileIds' => [
                            '550e8400-e29b-41d4-a716-446655440000'
                        ],
                        'knowledgeBaseFileIds' => [
```

```
                            '550e8400-e29b-41d4-a716-446655440000'
                        ],
                        'faqIds' => [
                            '550e8400-e29b-41d4-a716-446655440000'
                        ],
                        'hasUserSelectedAll' => true
                    ]
                ],
                'labelRelations' => [
                    'operator' => 'AND',
                    'conditions' => [
                        null
                    ]
                ]
            ],
            'metadata' => null,
            'broadcast' => true,
            'skipCopilotTrigger' => true,
            'suggestedForId' => '550e8400-e29b-41d4-a716-446655440000',
            'skillIds' => [
                '550e8400-e29b-41d4-a716-446655440000'
            ],
            'toolIds' => [
                '550e8400-e29b-41d4-a716-446655440000'
            ],
            'templateId' => '550e8400-e29b-41d4-a716-446655440000'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request failed: ' . $e->getMessage();
}
?>
```

Response Body

Status Code: 201

Example Response Schema

```
{
  "id": string (uuid)
  "conversation": string (uuid)
  "sender":
  {
    "id": string (uuid)
    "name": string
    "avatar": string
    "email"?: string (email) // Optional
    "phoneNumber"?: string // Optional
  }
  "type"?: string // Optional
  "content"?: string // Optional
  "contentPayload"?: object // Optional
  "feedback":
  {
    "id": string (uuid)
    "type":
    {
    }
    "suggestion"?: string // Optional
    "updatedAt": string (timestamp)
  }
  "createdAt": string (timestamp)
  "attachments"?: [ // Optional
    {
      "id": string (uuid) // ID of an already-uploaded attachment, as returned by the
attachment upload endpoint. Required: a missing, null or non-UUID id is rejected with
HTTP 400 and the message is not created.
      "type"?:  // Optional
      {
      }
      "filename": string
      "file": string (uri)
      "expiresAt": string // ISO datetime when this attachment will be auto-deleted.

For conversation-bound attachments: conversation.last_message_created_at +
retention_days.
For attachments without a conversation: created_at + retention_days.
Returns None when cleanup is disabled (effective_from not set).
      "conversation"?: string (uuid) // Optional
    }
  ]
  "citations": [
    {
      "id": string (uuid)
      "filename": string // File name
      "file": string (uri) // File to upload
      "fileType": string
      "knowledgeBase"?:  // Optional
      {
        "id": string (uuid)
```

```
        "name": string
      }
      "size": integer // File size in bytes
      "status":
      {
      }
      "parser":
      {
        "id": string (uuid)
        "name": string
        "provider":
        {
        }
        "isTimestampSttProvider": boolean
      }
      "labels"?: [ // Optional
        {
          "id": string (uuid)
          "name": string
        }
      ]
      "rawUserDefineMetadata"?: object // Optional
      "speakerLabels": [
        {
          "id": string (uuid)
          "originalLabel": string // Original speaker label from diarization (e.g.,
SPEAKER_00)
          "customName"?: string // User-defined speaker name (e.g., John) (Optional)
          "displayName": string
        }
      ]
      "vectorStorageSize": integer // Size of vectors for this file in Elasticsearch
(bytes)
      "chunksCount": integer // Number of chunks/nodes generated from this file
      "waitingTime": number (double)
      "processingTime": number (double)
      "processingTimeDetails": object
      "ocrStatus": string // OCR result for scanned pages: done, skipped, partial, off;
null before parsing or for legacy files
      "ocrSkippedReason": string // Reason OCR was not performed on scanned pages:
no_azure_settings, azure_unavailable, insufficient_credits, transient_error,
time_budget, disabled; null when OCR is completed
      "previewUrl": string // For presentations (pptx/ppt), returns the URL of a
previewable PDF derivative (displayed in the frontend PDF viewer); otherwise None.

Generate the URL with the same CustomizedFileFieldSerializer as the `file` field to
ensure a consistent format (including each
storage provider's presign/host rules). Do not use get_absolute_url(): it produces
incorrectly formatted URLs.
      "createdAt": string (timestamp)
    }
  ]
  "citationNodes": [
```

```
    {
      "chatbotTextNode": {
      {
        "id": string (uuid)
        "charactersCount": integer
        "hitsCount": integer
        "text": string
        "updatedAt": string (timestamp)
        "filename": string
        "chatbotFile": object // Return full ChatbotFile details, including the file URL
and type, to support image previews in the frontend
        "knowledgeBaseFile": object // Same as get_chatbot_file, provided for backward
compatibility
        "pageNumber": integer // Backward-compatible alias of ``page_start``.
        "pageStart": integer
        "pageEnd": integer
        "citationTitle": string // Source title shown on the inline citation hover card.
        "citationDescription": string // Source description shown on the inline citation
hover card.
        "citationQuote": string // Quoted text snippet shown on the inline citation
hover card.
        "hasImage": boolean // Check whether images are present (by checking the file
type or Markdown images in text)
        "imageUrl": string // Extract the image URL (prefer the file URL; otherwise
extract it from Markdown)
        "displayText": string // Return the full text with image Markdown markup removed
        "displayTitle": string // Return the display title (fallback: citation_title ->
filename)
        "highlightedText": string // Return text with matched terms wrapped in
``<mark>`` tags.

Priority:
1. ES/OpenSearch native highlight (set by retrieve_api via ``_es_highlighted_text``)
2. Python regex fallback (keyword-based, works for all backends)
        "labels": [
          {
            "id": string (uuid)
            "name": string
          }
        ]
        "rawUserDefineMetadata"?: object // Metadata keys and values defined by the
user. (Optional)
        "metadataEnabledForSearch": object // Map each user-defined metadata key on this
node to whether it was sent into the LLM.

A key reaches the LLM only when its ``MetadataKey.enabled_for_search`` is True *and*
the node carries a value for it. Since this maps over ``raw_user_define_metadata``
(the keys the cited-documents block displays, all of which have a value),
``enabled_for_search`` alone decides the flag. The source of truth is the node's
knowledge base ``MetadataKey`` current setting, matching the AI Search indicator.
        "startCharIdx": integer
        "endCharIdx": integer
      }
```

```
      }
      "score"?: number (double) // Optional
      "displayScore": integer
      "citationNumber"?: integer // Citation number matching the [1], [2] markers in the
reply content (Optional)
      "highlightedText"?: string // ES/OpenSearch highlight result with <mark> tags
(Optional)
    }
  ]
  "canvas"?: { // Optional
  {
    "id": string (uuid)
    "name": string
    "canvasType":
    {
    }
    "title": string
    "content": string
    "createdAt": string (timestamp)
  }
  }
  "slideTemplate"?:  // Optional
  {
    "slug": string
    "displayName": string
    "thumbnailUrls"?: [ // Optional
      string
    ]
  }
  "queryMetadata"?: { // Query metadata controlling the scope of searchable knowledge;
see each endpoint for details (Optional)
  {
    "knowledgeBases"?: [ // List of searchable knowledge bases; an empty array or null
means none are searchable (no permission); omission means no restriction (Optional)
      {
        "knowledgeBaseId": string (uuid) // Knowledge base ID
        "chatbotFileIds"?: [ // List of file IDs (excluded or exclusively selected
depending on hasUserSelectedAll) (Optional)
          string (uuid)
        ]
        "knowledgeBaseFileIds"?: [ // List of file IDs (the new name for chatbotFileIds;
this field takes precedence when both are provided) (Optional)
          string (uuid)
        ]
        "faqIds"?: [ // List of FAQ IDs (excluded or exclusively selected depending on
hasUserSelectedAll) (Optional)
          string (uuid)
        ]
        "hasUserSelectedAll"?: boolean // true selects all knowledge base content except
the listed items; false selects only the listed items (Optional)
      }
    ]
    "labelRelations"?: { // Label filter criteria; an empty conditions array means no
```

```
label filtering (not a lack of permission). Must be provided together with
knowledgeBases; when provided alone, label filtering is not applied to knowledge base
retrieval (equivalent to no restriction) (Optional)
    {
      "operator": string (enum: AND, OR) // How label conditions are combined
      "conditions"?: [ // List of label conditions; supports nested operator/conditions
combinations (Optional)
        object
      ]
    }
    }
  }
  }
  "metadata"?: object // Message metadata, such as timezone and other environment
information (Optional)
  "recordId": string // Return the ChatbotRecord ID associated with the Message

Note:
    For an unsaved Message (such as a virtual Message during streaming), return None
directly,
    avoiding a database query on the OneToOneField reverse relation (the N+1 problem).
  "broadcast"?: boolean // Optional
  "skipCopilotTrigger"?: boolean // Optional
  "activeRevisionNumber": integer
  "revisions": [
    {
      "id": string (uuid)
      "revisionNumber": integer
      "content": string
      "contentPayload": object
      "isActive": boolean
      "createdAt": string (timestamp)
    }
  ]
  "suggestedForId"?: string (uuid) // Optional
  "suggestionStatus": string
  "suggestionTriggerSource": string
  "suggestionError": string
  "retryCount": integer // How many times the LLM call was auto-retried during this
message generation. Currently only Bedrock first-chunk stall triggers retry (max 1).
Detailed per-attempt records live in metadata["retry_attempts"].
  "skillIds"?: [ // Per-message selected skill IDs from the WebChat client (camelCase:
skillIds). (Optional)
    string (uuid)
  ]
  "toolIds"?: [ // Per-message selected tool IDs from the WebChat client (camelCase:
toolIds). (Optional)
    string (uuid)
  ]
  "templateId"?: string (uuid) // Document/sheet template ID for file-level compilation
(camelCase: templateId). (Optional)
  "videoGeneration": object // Return the latest GeneratedVideo state for FE reload
recovery;
```

```
``errorMessage`` is blank to match the socket emit (raw value stays on the DB row).
  "isGreeting": boolean // Whether this message is a greeting message.
}
```

Example Response Value


```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "conversation": "550e8400-e29b-41d4-a716-446655440000",
  "sender": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Response string",
    "avatar": "Response string",
    "email": "response@example.com",
    "phoneNumber": "Response string"
  },
  "type": "Response string",
  "content": "Response string",
  "contentPayload": null,
  "feedback": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "type": {},
    "suggestion": "Response string",
    "updatedAt": "Response string"
  },
  "createdAt": "Response string",
  "attachments": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "type": {},
      "filename": "Response string",
      "file": "https://example.com/file.jpg",
      "expiresAt": "Response string",
      "conversation": "550e8400-e29b-41d4-a716-446655440000"
    }
  ],
  "citations": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "filename": "Response string",
      "file": "https://example.com/file.jpg",
      "fileType": "Response string",
      "knowledgeBase": {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "name": "Response string"
      },
      "size": 456,
      "status": {},
      "parser": {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "name": "Response string",
```

```
        "provider": {},
        "isTimestampSttProvider": false
      },
      "labels": [
        {
          "id": "550e8400-e29b-41d4-a716-446655440000",
          "name": "Response string"
        }
      ],
      "rawUserDefineMetadata": null,
      "speakerLabels": [
        {
          "id": "550e8400-e29b-41d4-a716-446655440000",
          "originalLabel": "Response string",
          "customName": "Response string",
          "displayName": "Response string"
        }
      ],
      "vectorStorageSize": 456,
      "chunksCount": 456,
      "waitingTime": 456,
      "processingTime": 456,
      "processingTimeDetails": null,
      "ocrStatus": "Response string",
      "ocrSkippedReason": "Response string",
      "previewUrl": "Response string",
      "createdAt": "Response string"
    }
  ],
  "citationNodes": [
    {
      "chatbotTextNode": {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "charactersCount": 456,
        "hitsCount": 456,
        "text": "Response string",
        "updatedAt": "Response string",
        "filename": "Response string",
        "chatbotFile": {
          "id": "550e8400-e29b-41d4-a716-446655440000",
          "name": "Example response name",
          "description": "Example response description"
        },
        "knowledgeBaseFile": {
          "id": "550e8400-e29b-41d4-a716-446655440000",
          "name": "Example response name",
          "description": "Example response description"
        },
        "pageNumber": 456,
        "pageStart": 456,
        "pageEnd": 456,
        "citationTitle": "Response string",
        "citationDescription": "Response string",
```

```
        "citationQuote": "Response string",
        "hasImage": false,
        "imageUrl": "Response string",
        "displayText": "Response string",
        "displayTitle": "Response string",
        "highlightedText": "Response string",
        "labels": [
          {
            "id": "550e8400-e29b-41d4-a716-446655440000",
            "name": "Response string"
          }
        ],
        "rawUserDefineMetadata": null,
        "metadataEnabledForSearch": {
          "key1": "value1",
          "key2": "value2",
          "createdAt": "2025-01-01T00:00:00.000Z"
        },
        "startCharIdx": 456,
        "endCharIdx": 456
      },
      "score": 456,
      "displayScore": 456,
      "citationNumber": 456,
      "highlightedText": "Response string"
    }
  ],
  "canvas": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Response string",
    "canvasType": {},
    "title": "Response string",
    "content": "Response string",
    "createdAt": "Response string"
  },
  "slideTemplate": {
    "slug": "Response string",
    "displayName": "Response string",
    "thumbnailUrls": [
      "Response string"
    ]
  },
  "queryMetadata": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Example response name",
    "description": "Example response description"
  },
  "metadata": null,
  "recordId": "Response string",
  "broadcast": false,
  "skipCopilotTrigger": false,
  "activeRevisionNumber": 456,
  "revisions": [
```

```
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "revisionNumber": 456,
      "content": "Response string",
      "contentPayload": null,
      "isActive": false,
      "createdAt": "Response string"
    }
  ],
  "suggestedForId": "550e8400-e29b-41d4-a716-446655440000",
  "suggestionStatus": "Response string",
  "suggestionTriggerSource": "Response string",
  "suggestionError": "Response string",
  "retryCount": 456,
  "skillIds": [
    "550e8400-e29b-41d4-a716-446655440000"
  ],
  "toolIds": [
    "550e8400-e29b-41d4-a716-446655440000"
  ],
  "templateId": "550e8400-e29b-41d4-a716-446655440000",
  "videoGeneration": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Example response name",
    "description": "Example response description"
  },
  "isGreeting": false
}
```


Create a New Conversation

POST `/api/v1/conversations/`

Request Body

Request Parameters

Field	Type	Required	Description
webChat	string (uuid)	Yes	
contact	string (uuid)	No	
clientPlatform	object	No	

Field	Type	Required	Description
workingDirectory	string	No	

Example Request Schema

```
{
  "webChat": string (uuid)
  "contact"?: string (uuid) // Optional
  "clientPlatform"?:  // Optional
  {
  }
  "workingDirectory"?: string // Optional
}
```

Example Request Value

```
{
  "webChat": "3fa85f64-5717-4562-b3fc-2c963f66afa6"
}
```

Code Examples

Shell/Bash

```
# API call example (Shell)
curl -X POST "https://api.maiagent.ai/api/v1/conversations/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "webChat": "3fa85f64-5717-4562-b3fc-2c963f66afa6"
  }'

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// Request Body (payload)
const data = {
    "webChat": "3fa85f64-5717-4562-b3fc-2c963f66afa6"
  };

axios.post("https://api.maiagent.ai/api/v1/conversations/", data, config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request failed:');
    console.error(error.response?.data || error.message);
  });
```

Python

```python
import requests

url = "https://api.maiagent.ai/api/v1/conversations/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# Request Body (payload)
data = {
    "webChat": "3fa85f64-5717-4562-b3fc-2c963f66afa6"
}

response = requests.post(url, json=data, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request failed:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->post("https://api.maiagent.ai/api/v1/conversations/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'webChat' => '3fa85f64-5717-4562-b3fc-2c963f66afa6'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request failed: ' . $e->getMessage();
}
?>
```

Response Body

Status Code: 201

Example Response Schema

```
{
  "id": string (uuid)
  "contact": { // Lightweight Contact Serializer for the Conversation List view

Includes only the fields required for the List view, omitting inboxes, mcp_credentials,
and api_credentials
to avoid N+1 queries. email / phone_number / metadata are scalar fields on Contact
itself,
needed for display in the frontend conversation sidebar, with no N+1 cost.
```

```
  {
    "id": string (uuid)
    "name": string
    "avatar"?: string // Stores our own media as a relative storage key, or an external
CDN URL as-is. (Optional)
    "email"?: // May have different types (Optional)
    string (email) // Optional
    "phoneNumber"?: string // Optional
    "metadata"?: object // Custom customer information shown in the customer panel of
the conversation page (Optional)
    "sourceId"?: string // Optional
    "tags": [
      {
        "id": string (uuid)
        "name": string
      }
    ]
  }
  }
  "inbox": { // Inbox summary embedded in a conversation payload.

``unread_conversations_count`` stays here because it is part of the
documented REST conversation API. It is an org-wide denormalized
counter, so WS emit paths must run the payload through
:func:`strip_org_wide_unread_count` before broadcasting it to rooms
that include members without ``GroupInbox.can_view_conversations``.
  {
    "id": string (uuid)
    "name": string
    "channelType": string (enum: line, telegram, teams, web, messenger, instagram,
email, whatsapp, slack, team_plus, line_works, viber) // * `line` - LINE
* `telegram` - Telegram
* `teams` - Teams
* `web` - Web
* `messenger` - Messenger
* `instagram` - Instagram
* `email` - Email
* `whatsapp` - WhatsApp
* `slack` - Slack
* `team_plus` - Team+
* `line_works` - LINE WORKS
* `viber` - Viber
    "unreadConversationsCount"?: integer // Optional
    "signAuth"?:  // Optional
    {
      "id": string (uuid)
      "signSource": string (uuid)
      "signParams": {
      {
        "keycloak":
        {
          "clientId": string
          "url": string
```

```
          "realm": string
        }
        "line":
        {
          "liffId": string
        }
        "ad":
        {
          "saml": string
        }
        "google"?:  // Optional
        {
          "enabled": boolean
        }
      }
      }
      "sourceIdAccessEnabled"?: boolean // When enabled, embedded visitors presenting a
Source ID (verified per the verify mode below) may chat without going through the login
flow. Disabled keeps every existing behavior unchanged. (Optional)
      "sourceIdVerifyMode"?:  // "Require signature verification": the embedding site
must send an HMAC signature computed on its backend. "Source ID only": anyone knowing a
Source ID can act as that contact; suitable only for testing or closed networks.

* `signature` - Require signature verification
* `raw` - Source ID only (Optional)
      {
      }
      "sourceIdSignatureTtlMinutes"?:  // How long a signature can be used to obtain the
contact identity. Not a session lifetime: once exchanged, the session follows the
existing WebChat mechanism.

* `1` - 1
* `5` - 5
* `15` - 15 (Optional)
      {
      }
      "keycloakTokenPassthrough"?: boolean // When enabled, the Keycloak access token a
visitor logged in with is forwarded as the Authorization header when the AI calls MCP
and API tools on their behalf, so tools do not require a separate per-tool login. Only
for the Keycloak sign source. Never overrides an Authorization header a tool already
resolves from its own credentials. The visitor identity is the organization member bound
to the conversation at login, never the contact Source ID. (Optional)
      "keycloakTokenPassthroughAllowedHosts"?: [ // Hostnames (or "*.example.com"
wildcards) of the tools the visitor Keycloak token may be sent to (Optional)
        string
      ]
      "organizationLogin": object // How visitors sign in when the sign source is
"organization" (mirrors the back-office login); null for other sign sources
    }
    "enableAnalysis"?: boolean // Optional
  }
  }
  "chatbot": object // Chatbot (Agent) summary from the conversation's inbox, already
```

```
eager-loaded.

``is_maigpt`` lets the client tell the default MaiGPT agent apart (icon, feature
gate) without comparing against the organization's ``maigpt_inbox`` id;
``file_workspace_mode`` is the effective P6 mode (MaiGPT, blueprint and the
organization's file-library switch already applied).
  "title": string
  "lastMessage"?: { // Optional
  {
    "id": string (uuid)
    "type"?: string // Optional
    "content"?: string // Optional
    "createdAt": string (timestamp)
  }
  }
  "callRecord":
  {
    "id": string (uuid)
    "status"?: string (enum: initiated, ringing, in-progress, completed, failed, busy,
no-answer, canceled) // * `initiated` - Initiated
* `ringing` - Ringing
* `in-progress` - In Progress
* `completed` - Completed
* `failed` - Failed
* `busy` - Busy
* `no-answer` - No Answer
* `canceled` - Canceled (Optional)
    "direction": string (enum: inbound, outbound) // * `inbound` - Inbound
* `outbound` - Outbound
    "isActive": boolean
    "canHangup": boolean
  }
  "lastMessageCreatedAt": string (timestamp)
  "unreadMessagesCount": integer
  "autoReplyEnabled": boolean
  "isAutoReplyNow": boolean
  "willAiReplyNow": boolean // Whether a text message arriving through the inbox gets an
AI reply right now.

The messaging channels are gated by ``is_auto_reply_now`` (auto reply on and inside the
inbox auto-reply schedule) and by the inbox having a chatbot. The chatbot's API web chat
is answered by the completions endpoint, which ignores the schedule, so there the
conversation switch alone decides. The channel is only looked up for a web inbox outside
its schedule.

Surfaces that ignore the schedule on any inbox answer from their own rule instead: the
completions endpoint continuing an existing conversation
(``completions_progress_status``)
and voice turns, which the voice agent answers.
  "lastReadAt": string (timestamp)
  "createdAt": string (timestamp)
  "isGroupChat": boolean
  "enableGroupMention"?: boolean // Optional
```

```
  "queryMetadata"?: { // Query metadata that controls the searchable knowledge scope;
see each endpoint for details (Optional)
  {
    "knowledgeBases"?: [ // List of searchable knowledge bases; an empty array or null
denies access to all knowledge bases (no permission); omission imposes no restriction
(Optional)
      {
        "knowledgeBaseId": string (uuid) // Knowledge base ID
        "chatbotFileIds"?: [ // List of file IDs (excluded or exclusively selected
depending on hasUserSelectedAll) (Optional)
          string (uuid)
        ]
        "knowledgeBaseFileIds"?: [ // List of file IDs (the new name for chatbotFileIds;
this field takes precedence when both are provided) (Optional)
          string (uuid)
        ]
        "faqIds"?: [ // List of FAQ IDs (excluded or exclusively selected depending on
hasUserSelectedAll) (Optional)
          string (uuid)
        ]
        "hasUserSelectedAll"?: boolean // true selects all knowledge base content except
the listed items; false selects only the listed items (Optional)
      }
    ]
    "labelRelations"?: { // Label filter criteria; an empty conditions array applies no
label filter (it does not deny access). Must be provided together with knowledgeBases;
when supplied alone, knowledge base retrieval does not apply label filtering (no
restriction) (Optional)
    {
      "operator": string (enum: AND, OR) // How label conditions are combined
      "conditions"?: [ // List of label conditions; supports nested operator/conditions
combinations (Optional)
        object
      ]
    }
    }
  }
  }
  "toolMask"?: object // Enabled/disabled state per tool: {tool_id: bool} (Optional)
  "connectorMask"?: object // Enabled/disabled state per connector: {connector_id: bool}
(Optional)
  "thinkingConfig"?: object // None = not set (inherit the chatbot setting); otherwise
{"reasoning_effort": <level>} (Optional)
  "thinkingConfigSchema": { // Thinking configuration form for this model; null means
the model has no thinking configuration
  {
    "type"?: string // Form type; always reasoning_effort (Optional)
    "fields"?: object // reasoning_effort field: options lists the thinking levels
accepted by this model (from lowest to highest); default is always null (Optional)
    "canDisable"?: boolean // Whether thinking can be disabled for this model; when
true, options includes off (Optional)
    "unsetBehavior"?: string (enum: off, model_default) // Actual behavior when neither
the conversation nor the assistant specifies a thinking level: off disables thinking
```

```
(fastest); model_default lets the model decide or enables thinking at the platform
default level (Optional)
    "unsetLevel"?: string // Level actually sent by the platform when no level is
configured; null omits the thinking parameter and uses the model default (Optional)
  }
  }
  "effectiveThinkingConfig": object // The level the next reply sends on this
conversation's model, after gating and clamping.

The stored choice resolves conversation > chatbot > the LLM row's default level; None
means
the model sends no thinking parameter, so the provider default applies.
  "llm": string (uuid) // The model the next reply runs on: the conversation's pin, else
its assistant's current model.

TC-0205: returning the stored ``conversation.llm`` would show a model an unpinned
conversation no
longer uses once its assistant switches model, while ``thinking_config_schema`` already
follows the
effective model. Read-only: displaying it never marks the conversation as explicitly
selected;
only the update-llm endpoint does.
  "deepResearchStatus":  // Status of deep research for this conversation

* `not_used` - Not Used
* `started` - Started
* `running` - Running
* `completed` - Completed
* `failed` - Failed
  {
  }
  "deepResearchOutputFormat": // May have different types
  string (enum: canvas, chat, file) // Chosen delivery form for the finished report. Set
only when the user clicks a format in the pre-research choice card; reset to NULL each
time Deep Research is (re-)armed. NULL means no explicit choice (or a plan-skipping
request) and falls back to Canvas at render time, but stays distinct from an explicit
canvas pick so the frontend can lock the card only after a real selection. To roll back
to fixed-Canvas behavior, force this to NULL/canvas — no redeploy needed.

* `canvas` - Canvas
* `chat` - Chat reply
* `file` - Downloadable file
  "ipAddress": string
  "ipCountryCode": string
  "ipRecordedAt": string (timestamp)
  "assignee":
  {
    "id": string (uuid)
    "name": string
    "userId": string (uuid)
  }
  "status"?: string (enum: open, resolved, queued) // * `open` - Open
* `resolved` - Resolved
```

```
* `queued` - Queued (Optional)
  "tags": [
    {
      "id": string (uuid)
      "name": string
      "memberIds"?: [ // Optional
        string (uuid)
      ]
    }
  ]
  "progressStatus": string
  "firstResponseAt"?: string (timestamp) // Optional
  "queuedAt"?: string (timestamp) // Optional
  "assignedAt"?: string (timestamp) // Optional
  "transferReason"?: string // Optional
  "satisfactionScore": integer // Conversation satisfaction rating on a 5-point scale
(1=very dissatisfied, 5=very satisfied)
  "satisfactionComment": string
  "satisfactionSubmittedAt": string (timestamp)
  "latestAnalysisSummary": string // The conversation's current analysis summary (its
active summary revision).

Reads the `latest_analysis_summary` annotation added by `setup_eager_loading`
to avoid an N+1 query. All read paths (list / retrieve / create) eager-load,
so the annotation is present; it falls back to '' only for instances built
outside `setup_eager_loading`.
  "clientPlatform":  // Client platform that created this conversation (web, desktop)

* `web` - Web
* `desktop` - Desktop
  {
  }
  "workingDirectory": string // Absolute path of the local folder bound to a desktop
conversation. Only set for desktop conversations; null for web conversations.
  "slideProjectId": string
  "matchedField": string // Cached per instance: ``get_matched_message_id`` /
``get_matched_snippet``
both read this, so resolving it once avoids recomputing the keyword and
title-match logic three times per serialized conversation.
  "matchedSnippet": string // Keyword-centred excerpt of the matched message, with
ellipses.

Reads the ``matched_message_content`` annotation added by
``ConversationViewSet._annotate_keyword_match``; no extra query.
  "matchedMessageId": string
  "pinnedAt": string (timestamp) // When the conversation was pinned. Null means
unpinned.
  "folder": string (uuid) // The user-defined sidebar folder this conversation is
grouped into. Null means unclassified (shown under the time groups). Deleting the folder
resets this to null without deleting the conversation.
  "hasActiveBrowserSession": boolean // Whether a browser_use session snapshot exists to
resume.
```

```
Lets the frontend know it should proactively re-request the browser
panel (emit ``browser:start``) after a page reload, instead of only
ever showing the panel when a live ``browser:frame`` push happens to
arrive first.
  "callerOrganizationId": string // Bound caller organization (stamped at conversation
start); null when unbound
  "handoff": object // Handoff information: enabled is the platform switch; the
continuation conversation includes source_conversation_id/source_title; the original
conversation being handed off includes continued_to_conversation_id/continued_to_title
and latest_summary_message_id
  "displayContextUsage": boolean // Whether to show the context usage percentage bar (a
conversation platform switch; always true for MaiGPT; independent of the handoff switch)
  "autoSplitReason": string // Reason this conversation was created by automatic
conversation splitting: resolved (after resolution) / idle (inactivity); null if not
created by splitting
  "continuedFrom": object // Conversation continued by this split conversation: {id,
last_message_at, deleted}; if the old conversation was deleted, id=null and deleted=true
  "continuedTo": object // Most recent conversation split from this conversation: {id,
created_at}; null if none
  "continuationSummary": object // Continuation summary: {state:
disabled|pending|ready|not_applied, items: [{conversation_id, content, generated_at,
last_message_at, old_status}]} (items ordered newest first); null if not created by
splitting
  "conversationKind": string // chat = a chat with an agent; secretary = the member's
personal secretary Work chat
}
```

Example response values


```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "contact": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "response string",
    "avatar": "response string",
    "email": "response@example.com",
    "phoneNumber": "response string",
    "metadata": null,
    "sourceId": "response string",
    "tags": [
      {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "name": "response string"
      }
    ]
  },
  "inbox": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "response string",
    "channelType": "line",
    "unreadConversationsCount": 456,
```

```
    "signAuth": {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "signSource": "550e8400-e29b-41d4-a716-446655440000",
      "signParams": {
        "keycloak": {
          "clientId": "response string",
          "url": "response string",
          "realm": "response string"
        },
        "line": {
          "liffId": "response string"
        },
        "ad": {
          "saml": "response string"
        },
        "google": {
          "enabled": false
        }
      },
      "sourceIdAccessEnabled": false,
      "sourceIdVerifyMode": {},
      "sourceIdSignatureTtlMinutes": {},
      "keycloakTokenPassthrough": false,
      "keycloakTokenPassthroughAllowedHosts": [
        "response string"
      ],
      "organizationLogin": {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "name": "Example response name",
        "description": "Example response description"
      }
    },
    "enableAnalysis": false
  },
  "chatbot": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Example response name",
    "description": "Example response description"
  },
  "title": "response string",
  "lastMessage": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "type": "response string",
    "content": "response string",
    "createdAt": "response string"
  },
  "callRecord": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "status": "initiated",
    "direction": "inbound",
    "isActive": false,
    "canHangup": false
  },
```

```
  "lastMessageCreatedAt": "response string",
  "unreadMessagesCount": 456,
  "autoReplyEnabled": false,
  "isAutoReplyNow": false,
  "willAiReplyNow": false,
  "lastReadAt": "response string",
  "createdAt": "response string",
  "isGroupChat": false,
  "enableGroupMention": false,
  "queryMetadata": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Example response name",
    "description": "Example response description"
  },
  "toolMask": null,
  "connectorMask": null,
  "thinkingConfig": null,
  "thinkingConfigSchema": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Example response name",
    "description": "Example response description"
  },
  "effectiveThinkingConfig": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Example response name",
    "description": "Example response description"
  },
  "llm": "550e8400-e29b-41d4-a716-446655440000",
  "deepResearchStatus": {},
  "deepResearchOutputFormat": "canvas",
  "ipAddress": "response string",
  "ipCountryCode": "response string",
  "ipRecordedAt": "response string",
  "assignee": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "response string",
    "userId": "550e8400-e29b-41d4-a716-446655440000"
  },
  "status": "open",
  "tags": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "response string",
      "memberIds": [
        "550e8400-e29b-41d4-a716-446655440000"
      ]
    }
  ],
  "progressStatus": "response string",
  "firstResponseAt": "response string",
  "queuedAt": "response string",
  "assignedAt": "response string",
  "transferReason": "response string",
```

```
  "satisfactionScore": 456,
  "satisfactionComment": "response string",
  "satisfactionSubmittedAt": "response string",
  "latestAnalysisSummary": "response string",
  "clientPlatform": {},
  "workingDirectory": "response string",
  "slideProjectId": "response string",
  "matchedField": "response string",
  "matchedSnippet": "response string",
  "matchedMessageId": "response string",
  "pinnedAt": "response string",
  "folder": "550e8400-e29b-41d4-a716-446655440000",
  "hasActiveBrowserSession": false,
  "callerOrganizationId": "response string",
  "handoff": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Example response name",
    "description": "Example response description"
  },
  "displayContextUsage": false,
  "autoSplitReason": "response string",
  "continuedFrom": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Example response name",
    "description": "Example response description"
  },
  "continuedTo": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Example response name",
    "description": "Example response description"
  },
  "continuationSummary": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Example response name",
    "description": "Example response description"
  },
  "conversationKind": "response string"
}
```


Status code: 4XX - Error response; X-Error-Code carries its code (see "Error codes").

List Messages

`GET` `/api/v1/messages/`

Parameters

Parameter name	Required	Type	Description
`conversation`	V	string	Conversation ID
`cursor`	X	string	The pagination cursor value.
`pageSize`	X	integer	Number of results to return per page.

Code examples

Shell/Bash

```
# API call example (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/messages/?
conversation=example&cursor=example&pageSize=1"

  -H "Authorization: Api-Key YOUR_API_KEY"

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/messages/?
conversation=example&cursor=example&pageSize=1", config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request failed:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/messages/?
conversation=example&cursor=example&pageSize=1"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request failed:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->get("https://api.maiagent.ai/api/v1/messages/?
conversation=example&cursor=example&pageSize=1", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request failed: ' . $e->getMessage();
}
?>
```

Response

Status code: 200

Example response schema

```
{
  "count": integer
  "next"?: string (uri) // Optional
  "previous"?: string (uri) // Optional
  "results": [
    {
      "id": string (uuid)
      "conversation": string (uuid)
      "sender":
      {
        "id": string (uuid)
        "name": string
```

```
        "avatar": string
        "email"?: string (email) // Optional
        "phoneNumber"?: string // Optional
      }
      "type"?: string // Optional
      "content"?: string // Optional
      "contentPayload"?: object // Optional
      "feedback":
      {
        "id": string (uuid)
        "type":
        {
        }
        "suggestion"?: string // Optional
        "updatedAt": string (timestamp)
      }
      "createdAt": string (timestamp)
      "attachments"?: [ // Optional
        {
          "id": string (uuid) // ID of an already-uploaded attachment, as returned by
the attachment upload endpoint. Required: a missing, null or non-UUID id is rejected
with HTTP 400 and the message is not created.
          "type"?:  // Optional
          {
          }
          "filename": string
          "file": string (uri)
          "expiresAt": string // ISO datetime when this attachment will be auto-deleted.

For conversation-bound attachments: conversation.last_message_created_at +
retention_days.
For attachments without a conversation: created_at + retention_days.
Returns None when cleanup is disabled (effective_from not set).
          "conversation"?: string (uuid) // Optional
        }
      ]
      "citations": [
        {
          "id": string (uuid)
          "filename": string // File name
          "file": string (uri) // File to upload
          "fileType": string
          "knowledgeBase"?:  // Optional
          {
            "id": string (uuid)
            "name": string
          }
          "size": integer // File size in bytes
          "status":
          {
          }
          "parser":
          {
```

```
            "id": string (uuid)
            "name": string
            "provider":
            {
            }
            "isTimestampSttProvider": boolean
          }
          "labels"?: [ // Optional
            {
              "id": string (uuid)
              "name": string
            }
          ]
          "rawUserDefineMetadata"?: object // Optional
          "speakerLabels": [
            {
              "id": string (uuid)
              "originalLabel": string // Original speaker label from diarization (e.g.,
SPEAKER_00)
              "customName"?: string // User-defined speaker name (e.g., John) (Optional)
              "displayName": string
            }
          ]
          "vectorStorageSize": integer // Size of vectors for this file in Elasticsearch
(bytes)
          "chunksCount": integer // Number of chunks/nodes generated from this file
          "waitingTime": number (double)
          "processingTime": number (double)
          "processingTimeDetails": object
          "ocrStatus": string // OCR result for scanned pages: done, skipped, partial,
off; null before parsing or for legacy files
          "ocrSkippedReason": string // Reason OCR was not performed on scanned pages:
no_azure_settings, azure_unavailable, insufficient_credits, transient_error,
time_budget, disabled; null when completed
          "previewUrl": string // For presentations (pptx/ppt), returns the URL of a
derived PDF for preview in the frontend PDF viewer; None for other file types.

Generate URLs using the same CustomizedFileFieldSerializer as the `file` field to ensure
a consistent format (including each
storage provider's presign/host rules). Do not use get_absolute_url(): it produces
incorrectly formatted URLs.
          "createdAt": string (timestamp)
        }
      ]
      "citationNodes": [
        {
          "chatbotTextNode": {
          {
            "id": string (uuid)
            "charactersCount": integer
            "hitsCount": integer
            "text": string
            "updatedAt": string (timestamp)
```

```
            "filename": string
            "chatbotFile": object // Return full ChatbotFile information, including the
file URL and type, to support frontend image previews
            "knowledgeBaseFile": object // Same as get_chatbot_file, for backward
compatibility
            "pageNumber": integer // Backward-compatible alias of ``page_start``.
            "pageStart": integer
            "pageEnd": integer
            "citationTitle": string // Source title shown on the inline citation hover
card.
            "citationDescription": string // Source description shown on the inline
citation hover card.
            "citationQuote": string // Quoted text snippet shown on the inline citation
hover card.
            "hasImage": boolean // Determine whether images are present (check the file
type or Markdown images in text)
            "imageUrl": string // Extract the image URL (prefer the file URL; otherwise
extract it from Markdown)
            "displayText": string // Return the full text with Markdown image markup
removed
            "displayTitle": string // Return the display title (fallback: citation_title
-> filename)
            "highlightedText": string // Return text with matched terms wrapped in
``<mark>`` tags.

Priority:
1. ES/OpenSearch native highlight (set by retrieve_api via ``_es_highlighted_text``)
2. Python regex fallback (keyword-based, works for all backends)
            "labels": [
              {
                "id": string (uuid)
                "name": string
              }
            ]
            "rawUserDefineMetadata"?: object // Metadata keys and values defined by the
user. (Optional)
            "metadataEnabledForSearch": object // Map each user-defined metadata key on
this node to whether it was sent into the LLM.

A key reaches the LLM only when its ``MetadataKey.enabled_for_search`` is True *and*
the node carries a value for it. Since this maps over ``raw_user_define_metadata``
(the keys the cited-documents block displays, all of which have a value),
``enabled_for_search`` alone decides the flag. The source of truth is the node's
knowledge base ``MetadataKey`` current setting, matching the AI Search indicator.
            "startCharIdx": integer
            "endCharIdx": integer
          }
          }
          "score"?: number (double) // Optional
          "displayScore": integer
          "citationNumber"?: integer // Citation number matching the [1], [2] markers in
the reply content (Optional)
          "highlightedText"?: string // ES/OpenSearch highlight result with <mark> tags
```

```
(Optional)
        }
      ]
      "canvas"?: { // Optional
      {
        "id": string (uuid)
        "name": string
        "canvasType":
        {
        }
        "title": string
        "content": string
        "createdAt": string (timestamp)
      }
      }
      "slideTemplate"?:  // Optional
      {
        "slug": string
        "displayName": string
        "thumbnailUrls"?: [ // Optional
          string
        ]
      }
      "queryMetadata"?: { // Query metadata controlling the scope of searchable
knowledge; see each endpoint description for details (Optional)
      {
        "knowledgeBases"?: [ // List of searchable knowledge bases; an empty array or
null denies access to all knowledge bases, while omission imposes no restriction
(Optional)
          {
            "knowledgeBaseId": string (uuid) // Knowledge base ID
            "chatbotFileIds"?: [ // List of file IDs (excluded or exclusively selected,
depending on hasUserSelectedAll) (Optional)
              string (uuid)
            ]
            "knowledgeBaseFileIds"?: [ // List of file IDs (the new name for
chatbotFileIds; this field takes precedence when both are provided) (Optional)
              string (uuid)
            ]
            "faqIds"?: [ // List of FAQ IDs (excluded or exclusively selected, depending
on hasUserSelectedAll) (Optional)
              string (uuid)
            ]
            "hasUserSelectedAll"?: boolean // true selects all knowledge base content
except the listed items; false selects only the listed items (Optional)
          }
        ]
        "labelRelations"?: { // Label filter criteria; an empty conditions array applies
no label filtering (it does not deny access). Must be provided together with
knowledgeBases; when provided alone, no label filtering is applied to knowledge base
retrieval (equivalent to no restriction) (Optional)
        {
          "operator": string (enum: AND, OR) // How label conditions are combined
```

```
          "conditions"?: [ // List of label conditions, supporting nested
operator/conditions combinations (Optional)
            object
          ]
        }
        }
      }
      }
      "metadata"?: object // Message metadata, such as timezone and other environment
information (Optional)
      "recordId": string // Return the ChatbotRecord ID associated with the Message

Note:
    For an unsaved Message (such as a virtual Message during streaming), return None
directly,
    avoiding a database query through the OneToOneField reverse relation (the N+1
problem).
      "broadcast"?: boolean // Optional
      "skipCopilotTrigger"?: boolean // Optional
      "activeRevisionNumber": integer
      "revisions": [
        {
          "id": string (uuid)
          "revisionNumber": integer
          "content": string
          "contentPayload": object
          "isActive": boolean
          "createdAt": string (timestamp)
        }
      ]
      "suggestedForId"?: string (uuid) // Optional
      "suggestionStatus": string
      "suggestionTriggerSource": string
      "suggestionError": string
      "retryCount": integer // How many times the LLM call was auto-retried during this
message generation. Currently only Bedrock first-chunk stall triggers retry (max 1).
Detailed per-attempt records live in metadata["retry_attempts"].
      "skillIds"?: [ // Per-message selected skill IDs from the WebChat client
(camelCase: skillIds). (Optional)
        string (uuid)
      ]
      "toolIds"?: [ // Per-message selected tool IDs from the WebChat client (camelCase:
toolIds). (Optional)
        string (uuid)
      ]
      "templateId"?: string (uuid) // Document/sheet template ID for file-level
compilation (camelCase: templateId). (Optional)
      "videoGeneration": object // Return the latest GeneratedVideo state for FE reload
recovery;
``errorMessage`` is blank to match the socket emit (raw value stays on the DB row).
      "isGreeting": boolean // Whether this message is a greeting message.
    }
```

```
  ]
}
```

Example Response Values


```
{
  "count": 123,
  "next": "http://api.example.org/accounts/?page=4",
  "previous": "http://api.example.org/accounts/?page=2",
  "results": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "conversation": "550e8400-e29b-41d4-a716-446655440000",
      "sender": {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "name": "Response string",
        "avatar": "Response string",
        "email": "response@example.com",
        "phoneNumber": "Response string"
      },
      "type": "Response string",
      "content": "Response string",
      "contentPayload": null,
      "feedback": {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "type": {},
        "suggestion": "Response string",
        "updatedAt": "Response string"
      },
      "createdAt": "Response string",
      "attachments": [
        {
          "id": "550e8400-e29b-41d4-a716-446655440000",
          "type": {},
          "filename": "Response string",
          "file": "https://example.com/file.jpg",
          "expiresAt": "Response string",
          "conversation": "550e8400-e29b-41d4-a716-446655440000"
        }
      ],
      "citations": [
        {
          "id": "550e8400-e29b-41d4-a716-446655440000",
          "filename": "Response string",
          "file": "https://example.com/file.jpg",
          "fileType": "Response string",
          "knowledgeBase": {
            "id": "550e8400-e29b-41d4-a716-446655440000",
            "name": "Response string"
          },
          "size": 456,
```

```
        "status": {},
        "parser": {
          "id": "550e8400-e29b-41d4-a716-446655440000",
          "name": "Response string",
          "provider": {},
          "isTimestampSttProvider": false
        },
        "labels": [
          {
            "id": "550e8400-e29b-41d4-a716-446655440000",
            "name": "Response string"
          }
        ],
        "rawUserDefineMetadata": null,
        "speakerLabels": [
          {
            "id": "550e8400-e29b-41d4-a716-446655440000",
            "originalLabel": "Response string",
            "customName": "Response string",
            "displayName": "Response string"
          }
        ],
        "vectorStorageSize": 456,
        "chunksCount": 456,
        "waitingTime": 456,
        "processingTime": 456,
        "processingTimeDetails": null,
        "ocrStatus": "Response string",
        "ocrSkippedReason": "Response string",
        "previewUrl": "Response string",
        "createdAt": "Response string"
      }
    ],
    "citationNodes": [
      {
        "chatbotTextNode": {
          "id": "550e8400-e29b-41d4-a716-446655440000",
          "charactersCount": 456,
          "hitsCount": 456,
          "text": "Response string",
          "updatedAt": "Response string",
          "filename": "Response string",
          "chatbotFile": {
            "id": "550e8400-e29b-41d4-a716-446655440000",
            "name": "Example response name",
            "description": "Example response description"
          },
          "knowledgeBaseFile": {
            "id": "550e8400-e29b-41d4-a716-446655440000",
            "name": "Example response name",
            "description": "Example response description"
          },
          "pageNumber": 456,
```

```
          "pageStart": 456,
          "pageEnd": 456,
          "citationTitle": "Response string",
          "citationDescription": "Response string",
          "citationQuote": "Response string",
          "hasImage": false,
          "imageUrl": "Response string",
          "displayText": "Response string",
          "displayTitle": "Response string",
          "highlightedText": "Response string",
          "labels": [
            {
              "id": "550e8400-e29b-41d4-a716-446655440000",
              "name": "Response string"
            }
          ],
          "rawUserDefineMetadata": null,
          "metadataEnabledForSearch": {
            "key1": "value1",
            "key2": "value2",
            "createdAt": "2025-01-01T00:00:00.000Z"
          },
          "startCharIdx": 456,
          "endCharIdx": 456
        },
        "score": 456,
        "displayScore": 456,
        "citationNumber": 456,
        "highlightedText": "Response string"
      }
    ],
    "canvas": {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "Response string",
      "canvasType": {},
      "title": "Response string",
      "content": "Response string",
      "createdAt": "Response string"
    },
    "slideTemplate": {
      "slug": "Response string",
      "displayName": "Response string",
      "thumbnailUrls": [
        "Response string"
      ]
    },
    "queryMetadata": {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "Example response name",
      "description": "Example response description"
    },
    "metadata": null,
    "recordId": "Response string",
```

```
      "broadcast": false,
      "skipCopilotTrigger": false,
      "activeRevisionNumber": 456,
      "revisions": [
        {
          "id": "550e8400-e29b-41d4-a716-446655440000",
          "revisionNumber": 456,
          "content": "Response string",
          "contentPayload": null,
          "isActive": false,
          "createdAt": "Response string"
        }
      ],
      "suggestedForId": "550e8400-e29b-41d4-a716-446655440000",
      "suggestionStatus": "Response string",
      "suggestionTriggerSource": "Response string",
      "suggestionError": "Response string",
      "retryCount": 456,
      "skillIds": [
        "550e8400-e29b-41d4-a716-446655440000"
      ],
      "toolIds": [
        "550e8400-e29b-41d4-a716-446655440000"
      ],
      "templateId": "550e8400-e29b-41d4-a716-446655440000",
      "videoGeneration": {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "name": "Example response name",
        "description": "Example response description"
      },
      "isGreeting": false
    }
  ]
}
```


Retrieve a Specific Message

`GET` `/api/v1/messages/{id}`

Parameters

Parameter Name	Required	Type	Description

`id`	V	string	A UUID string identifying this Message.
`conversation`	V	string	Conversation ID

Code Examples

Shell/Bash

```
# API call example (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/messages/550e8400-e29b-41d4-a716-
446655440000/?conversation=example"

  -H "Authorization: Api-Key YOUR_API_KEY"

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/messages/550e8400-e29b-41d4-a716-
446655440000/?conversation=example", config)
  .then(response => {
    console.log('Response retrieved successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/messages/550e8400-e29b-41d4-a716-
446655440000/?conversation=example"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("Response retrieved successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->get("https://api.maiagent.ai/api/v1/messages/550e8400-
e29b-41d4-a716-446655440000/?conversation=example", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response retrieved successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response Body

Status Code: 200

Example Response Schema

```
{
  "id": string (uuid)
  "conversation": string (uuid)
  "sender":
  {
    "id": string (uuid)
    "name": string
    "avatar": string
    "email"?: string (email) // Optional
    "phoneNumber"?: string // Optional
  }
  "type"?: string // Optional
```

```
  "content"?: string // Optional
  "contentPayload"?: object // Optional
  "feedback":
  {
    "id": string (uuid)
    "type":
    {
    }
    "suggestion"?: string // Optional
    "updatedAt": string (timestamp)
  }
  "createdAt": string (timestamp)
  "attachments"?: [ // Optional
    {
      "id": string (uuid) // ID of an already-uploaded attachment, as returned by the
attachment upload endpoint. Required: a missing, null or non-UUID id is rejected with
HTTP 400 and the message is not created.
      "type"?:  // Optional
      {
      }
      "filename": string
      "file": string (uri)
      "expiresAt": string // ISO datetime when this attachment will be auto-deleted.

For conversation-bound attachments: conversation.last_message_created_at +
retention_days.
For attachments without a conversation: created_at + retention_days.
Returns None when cleanup is disabled (effective_from not set).
      "conversation"?: string (uuid) // Optional
    }
  ]
  "citations": [
    {
      "id": string (uuid)
      "filename": string // File name
      "file": string (uri) // File to upload
      "fileType": string
      "knowledgeBase"?:  // Optional
      {
        "id": string (uuid)
        "name": string
      }
      "size": integer // File size in bytes
      "status":
      {
      }
      "parser":
      {
        "id": string (uuid)
        "name": string
        "provider":
        {
        }
```

```
        "isTimestampSttProvider": boolean
      }
      "labels"?: [ // Optional
        {
          "id": string (uuid)
          "name": string
        }
      ]
      "rawUserDefineMetadata"?: object // Optional
      "speakerLabels": [
        {
          "id": string (uuid)
          "originalLabel": string // Original speaker label from diarization (e.g.,
SPEAKER_00)
          "customName"?: string // User-defined speaker name (e.g., John) (Optional)
          "displayName": string
        }
      ]
      "vectorStorageSize": integer // Size of vectors for this file in Elasticsearch
(bytes)
      "chunksCount": integer // Number of chunks/nodes generated from this file
      "waitingTime": number (double)
      "processingTime": number (double)
      "processingTimeDetails": object
      "ocrStatus": string // OCR result for scanned pages: done, skipped, partial, off;
null before parsing or for legacy files
      "ocrSkippedReason": string // Reason OCR was not performed on scanned pages:
no_azure_settings, azure_unavailable, insufficient_credits, transient_error,
time_budget, disabled; null when completed
      "previewUrl": string // For presentations (pptx/ppt), returns the URL of a derived
PDF for preview in the frontend PDF viewer; None for other file types.

Generate URLs using the same CustomizedFileFieldSerializer as the `file` field to ensure
a consistent format (including each
storage provider's presign/host rules). Do not use get_absolute_url(): it produces
incorrectly formatted URLs.
      "createdAt": string (timestamp)
    }
  ]
  "citationNodes": [
    {
      "chatbotTextNode": {
      {
        "id": string (uuid)
        "charactersCount": integer
        "hitsCount": integer
        "text": string
        "updatedAt": string (timestamp)
        "filename": string
        "chatbotFile": object // Return full ChatbotFile information, including the file
URL and type, to support frontend image previews
        "knowledgeBaseFile": object // Same as get_chatbot_file, for backward
compatibility
```

```
        "pageNumber": integer // Backward-compatible alias of ``page_start``.
        "pageStart": integer
        "pageEnd": integer
        "citationTitle": string // Source title shown on the inline citation hover card.
        "citationDescription": string // Source description shown on the inline citation
hover card.
        "citationQuote": string // Quoted text snippet shown on the inline citation
hover card.
        "hasImage": boolean // Determine whether images are present (check the file type
or Markdown images in text)
        "imageUrl": string // Extract the image URL (prefer the file URL; otherwise
extract it from Markdown)
        "displayText": string // Return the full text with Markdown image markup removed
        "displayTitle": string // Return the display title (fallback: citation_title ->
filename)
        "highlightedText": string // Return text with matched terms wrapped in
``<mark>`` tags.

Priority:
1. ES/OpenSearch native highlight (set by retrieve_api via ``_es_highlighted_text``)
2. Python regex fallback (keyword-based, works for all backends)
        "labels": [
          {
            "id": string (uuid)
            "name": string
          }
        ]
        "rawUserDefineMetadata"?: object // Metadata keys and values defined by the
user. (Optional)
        "metadataEnabledForSearch": object // Map each user-defined metadata key on this
node to whether it was sent into the LLM.

A key reaches the LLM only when its ``MetadataKey.enabled_for_search`` is True *and*
the node carries a value for it. Since this maps over ``raw_user_define_metadata``
(the keys the cited-documents block displays, all of which have a value),
``enabled_for_search`` alone decides the flag. The source of truth is the node's
knowledge base ``MetadataKey`` current setting, matching the AI Search indicator.
        "startCharIdx": integer
        "endCharIdx": integer
      }
      }
      "score"?: number (double) // Optional
      "displayScore": integer
      "citationNumber"?: integer // Citation number matching the [1], [2] markers in the
reply content (Optional)
      "highlightedText"?: string // ES/OpenSearch highlight result with <mark> tags
(Optional)
    }
  ]
  "canvas"?: { // Optional
  {
    "id": string (uuid)
    "name": string
```

```
    "canvasType":
    {
    }
    "title": string
    "content": string
    "createdAt": string (timestamp)
  }
  }
  "slideTemplate"?:  // Optional
  {
    "slug": string
    "displayName": string
    "thumbnailUrls"?: [ // Optional
      string
    ]
  }
  "queryMetadata"?: { // Query metadata that controls which knowledge can be queried; see each endpoint for details (Optional)
  {
    "knowledgeBases"?: [ // List of queryable knowledge bases; an empty array or null means none can be queried (no permission); omitting it imposes no restriction (Optional)
      {
        "knowledgeBaseId": string (uuid) // Knowledge base ID
        "chatbotFileIds"?: [ // List of file IDs (excluded or exclusively selected, depending on hasUserSelectedAll) (Optional)
          string (uuid)
        ]
        "knowledgeBaseFileIds"?: [ // List of file IDs (the new name for chatbotFileIds; this field takes precedence when both are provided) (Optional)
          string (uuid)
        ]
        "faqIds"?: [ // List of FAQ IDs (excluded or exclusively selected, depending on hasUserSelectedAll) (Optional)
          string (uuid)
        ]
        "hasUserSelectedAll"?: boolean // true selects all knowledge base content except the listed items; false selects only the listed items (Optional)
      }
    ]
    "labelRelations"?: { // Label filter criteria; an empty conditions array means no label filtering (not a lack of permission). Must be provided together with knowledgeBases—if provided alone, knowledge base retrieval does not apply label filtering (equivalent to no restriction) (Optional)
    {
      "operator": string (enum: AND, OR) // How label conditions are combined
      "conditions"?: [ // List of label conditions; supports nested operator/conditions combinations (Optional)
        object
      ]
    }
    }
  }
  }
```

```
  "metadata"?: object // Message metadata, such as timezone and other environment
information (Optional)
  "recordId": string // Return the ChatbotRecord ID corresponding to the Message

Note:
    For unsaved Messages (such as virtual Messages during streaming), return None
directly,
    avoiding a DB query on the OneToOneField reverse relation (the N+1 problem).
  "broadcast"?: boolean // Optional
  "skipCopilotTrigger"?: boolean // Optional
  "activeRevisionNumber": integer
  "revisions": [
    {
      "id": string (uuid)
      "revisionNumber": integer
      "content": string
      "contentPayload": object
      "isActive": boolean
      "createdAt": string (timestamp)
    }
  ]
  "suggestedForId"?: string (uuid) // Optional
  "suggestionStatus": string
  "suggestionTriggerSource": string
  "suggestionError": string
  "retryCount": integer // How many times the LLM call was auto-retried during this
message generation. Currently only Bedrock first-chunk stall triggers retry (max 1).
Detailed per-attempt records live in metadata["retry_attempts"].
  "skillIds"?: [ // Per-message selected skill IDs from the WebChat client (camelCase:
skillIds). (Optional)
    string (uuid)
  ]
  "toolIds"?: [ // Per-message selected tool IDs from the WebChat client (camelCase:
toolIds). (Optional)
    string (uuid)
  ]
  "templateId"?: string (uuid) // Document/sheet template ID for file-level compilation
(camelCase: templateId). (Optional)
  "videoGeneration": object // Return the latest GeneratedVideo state for FE reload
recovery;
``errorMessage`` is blank to match the socket emit (raw value stays on the DB row).
  "isGreeting": boolean // Whether this message is a greeting message.
}
```

Example Response Values

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "conversation": "550e8400-e29b-41d4-a716-446655440000",
  "sender": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
```

```
    "name": "Response string",
    "avatar": "Response string",
    "email": "response@example.com",
    "phoneNumber": "Response string"
  },
  "type": "Response string",
  "content": "Response string",
  "contentPayload": null,
  "feedback": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "type": {},
    "suggestion": "Response string",
    "updatedAt": "Response string"
  },
  "createdAt": "Response string",
  "attachments": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "type": {},
      "filename": "Response string",
      "file": "https://example.com/file.jpg",
      "expiresAt": "Response string",
      "conversation": "550e8400-e29b-41d4-a716-446655440000"
    }
  ],
  "citations": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "filename": "Response string",
      "file": "https://example.com/file.jpg",
      "fileType": "Response string",
      "knowledgeBase": {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "name": "Response string"
      },
      "size": 456,
      "status": {},
      "parser": {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "name": "Response string",
        "provider": {},
        "isTimestampSttProvider": false
      },
      "labels": [
        {
          "id": "550e8400-e29b-41d4-a716-446655440000",
          "name": "Response string"
        }
      ],
      "rawUserDefineMetadata": null,
      "speakerLabels": [
        {
          "id": "550e8400-e29b-41d4-a716-446655440000",
```

```
          "originalLabel": "Response string",
          "customName": "Response string",
          "displayName": "Response string"
        }
      ],
      "vectorStorageSize": 456,
      "chunksCount": 456,
      "waitingTime": 456,
      "processingTime": 456,
      "processingTimeDetails": null,
      "ocrStatus": "Response string",
      "ocrSkippedReason": "Response string",
      "previewUrl": "Response string",
      "createdAt": "Response string"
    }
  ],
  "citationNodes": [
    {
      "chatbotTextNode": {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "charactersCount": 456,
        "hitsCount": 456,
        "text": "Response string",
        "updatedAt": "Response string",
        "filename": "Response string",
        "chatbotFile": {
          "id": "550e8400-e29b-41d4-a716-446655440000",
          "name": "Example response name",
          "description": "Example response description"
        },
        "knowledgeBaseFile": {
          "id": "550e8400-e29b-41d4-a716-446655440000",
          "name": "Example response name",
          "description": "Example response description"
        },
        "pageNumber": 456,
        "pageStart": 456,
        "pageEnd": 456,
        "citationTitle": "Response string",
        "citationDescription": "Response string",
        "citationQuote": "Response string",
        "hasImage": false,
        "imageUrl": "Response string",
        "displayText": "Response string",
        "displayTitle": "Response string",
        "highlightedText": "Response string",
        "labels": [
          {
            "id": "550e8400-e29b-41d4-a716-446655440000",
            "name": "Response string"
          }
        ],
        "rawUserDefineMetadata": null,
```

```
        "metadataEnabledForSearch": {
          "key1": "value1",
          "key2": "value2",
          "createdAt": "2025-01-01T00:00:00.000Z"
        },
        "startCharIdx": 456,
        "endCharIdx": 456
      },
      "score": 456,
      "displayScore": 456,
      "citationNumber": 456,
      "highlightedText": "Response string"
    }
  ],
  "canvas": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Response string",
    "canvasType": {},
    "title": "Response string",
    "content": "Response string",
    "createdAt": "Response string"
  },
  "slideTemplate": {
    "slug": "Response string",
    "displayName": "Response string",
    "thumbnailUrls": [
      "Response string"
    ]
  },
  "queryMetadata": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Example response name",
    "description": "Example response description"
  },
  "metadata": null,
  "recordId": "Response string",
  "broadcast": false,
  "skipCopilotTrigger": false,
  "activeRevisionNumber": 456,
  "revisions": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "revisionNumber": 456,
      "content": "Response string",
      "contentPayload": null,
      "isActive": false,
      "createdAt": "Response string"
    }
  ],
  "suggestedForId": "550e8400-e29b-41d4-a716-446655440000",
  "suggestionStatus": "Response string",
  "suggestionTriggerSource": "Response string",
  "suggestionError": "Response string",
```

```
  "retryCount": 456,
  "skillIds": [
    "550e8400-e29b-41d4-a716-446655440000"
  ],
  "toolIds": [
    "550e8400-e29b-41d4-a716-446655440000"
  ],
  "templateId": "550e8400-e29b-41d4-a716-446655440000",
  "videoGeneration": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Example response name",
    "description": "Example response description"
  },
  "isGreeting": false
}
```


List Conversations

`GET` `/api/v1/conversations/`

Parameters

Parameter Name	Required	Type	Description
`assignee`	X	string	
`chatbot`	X	string	
`contact`	X	string	Contact ID
`contactTags`	X	array	Multiple values may be separated by commas.
`cursor`	X	string	The pagination cursor value.
`endDate`	X	string	
`externalConversationId`	X	string	
`externalSource`	X	string	
`inbox`	X	string	Inbox ID
`isPinned`	X	string	

`keyword`	X	string	Keyword search
`kind`	X	string	`chat`: Chat ; `secretary`: Secretary;
`mine`	X	boolean	
`mode`	X	string	`chat`: Chat ; `cowork`: Cowork;
`pageSize`	X	integer	Number of results to return per page.
`startDate`	X	string	
`status`	X	array	`open`: Open ; `resolved`: Resolved ; `queued`: Queued;
`tags`	X	array	Multiple values may be separated by commas.
`unassigned`	X	boolean	
`updatedAfter`	X	string	

Code Examples

Shell/Bash

```
# API call example (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/conversations/?assignee=550e8400-e29b-
41d4-a716-446655440000&chatbot=550e8400-e29b-41d4-a716-
446655440000&contact=550e8400-e29b-41d4-a716-
446655440000&contactTags=example&cursor=example&endDate=example&externalConversatio
nId=example&externalSource=example&inbox=550e8400-e29b-41d4-a716-
446655440000&isPinned=example&keyword=example&kind=chat&mine=true&mode=chat&pageSiz
e=1&startDate=example&status=example&tags=example&unassigned=true&updatedAfter=2025
-01-01T00:00:00.000Z"

  -H "Authorization: Api-Key YOUR_API_KEY"

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/conversations/?assignee=550e8400-e29b-41d4-a716-446655440000&chatbot=550e8400-e29b-41d4-a716-446655440000&contact=550e8400-e29b-41d4-a716-446655440000&contactTags=example&cursor=example&endDate=example&externalConversationId=example&externalSource=example&inbox=550e8400-e29b-41d4-a716-446655440000&isPinned=example&keyword=example&kind=chat&mine=true&mode=chat&pageSize=1&startDate=example&status=example&tags=example&unassigned=true&updatedAfter=2025-01-01T00:00:00.000Z", config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/conversations/?assignee=550e8400-e29b-41d4-a716-446655440000&chatbot=550e8400-e29b-41d4-a716-446655440000&contact=550e8400-e29b-41d4-a716-446655440000&contactTags=example&cursor=example&endDate=example&externalConversationId=example&externalSource=example&inbox=550e8400-e29b-41d4-a716-446655440000&isPinned=example&keyword=example&kind=chat&mine=true&mode=chat&pageSize=1&startDate=example&status=example&tags=example&unassigned=true&updatedAfter=2025-01-01T00:00:00.000Z"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->get("https://api.maiagent.ai/api/v1/conversations/?
assignee=550e8400-e29b-41d4-a716-446655440000&chatbot=550e8400-e29b-41d4-a716-
446655440000&contact=550e8400-e29b-41d4-a716-
446655440000&contactTags=example&cursor=example&endDate=example&externalConversatio
nId=example&externalSource=example&inbox=550e8400-e29b-41d4-a716-
446655440000&isPinned=example&keyword=example&kind=chat&mine=true&mode=chat&pageSiz
e=1&startDate=example&status=example&tags=example&unassigned=true&updatedAfter=2025
-01-01T00:00:00.000Z", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response

Status Code: 200

Example Response Schema

```
{
  "count": integer
  "next"?: string (uri) // Optional
  "previous"?: string (uri) // Optional
  "results": [
    {
```

```
      "id": string (uuid)
      "contact": { // Lightweight Contact Serializer for the Conversation List view

Includes only the fields required by the List view, omitting inboxes, mcp_credentials,
and api_credentials
to avoid N+1 queries. email / phone_number / metadata are scalar fields on Contact
itself,
needed for display in the frontend conversation sidebar, with no N+1 cost.
      {
        "id": string (uuid)
        "name": string
        "avatar"?: string // Stores our own media as a relative storage key, or an
external CDN URL as-is. (Optional)
        "email"?: // May have different types (Optional)
        string (email) // Optional
        "phoneNumber"?: string // Optional
        "metadata"?: object // Custom customer information shown in the customer panel
of the conversation page (Optional)
        "sourceId"?: string // Optional
        "tags": [
          {
            "id": string (uuid)
            "name": string
          }
        ]
      }
      }
      "inbox": { // Inbox summary embedded in a conversation payload.

``unread_conversations_count`` stays here because it is part of the
documented REST conversation API. It is an org-wide denormalized
counter, so WS emit paths must run the payload through
:func:`strip_org_wide_unread_count` before broadcasting it to rooms
that include members without ``GroupInbox.can_view_conversations``.
      {
        "id": string (uuid)
        "name": string
        "channelType": string (enum: line, telegram, teams, web, messenger, instagram,
email, whatsapp, slack, team_plus, line_works, viber) // * `line` - LINE
* `telegram` - Telegram
* `teams` - Teams
* `web` - Web
* `messenger` - Messenger
* `instagram` - Instagram
* `email` - Email
* `whatsapp` - WhatsApp
* `slack` - Slack
* `team_plus` - Team+
* `line_works` - LINE WORKS
* `viber` - Viber
        "unreadConversationsCount"?: integer // Optional
        "signAuth"?:  // Optional
        {
```

```
          "id": string (uuid)
          "signSource": string (uuid)
          "signParams": {
          {
            "keycloak":
            {
              "clientId": string
              "url": string
              "realm": string
            }
            "line":
            {
              "liffId": string
            }
            "ad":
            {
              "saml": string
            }
            "google"?:  // Optional
            {
              "enabled": boolean
            }
          }
          }
          "sourceIdAccessEnabled"?: boolean // When enabled, embedded visitors
presenting a Source ID (verified per the verify mode below) may chat without going
through the login flow. Disabled keeps every existing behavior unchanged. (Optional)
          "sourceIdVerifyMode"?:  // "Require signature verification": the embedding
site must send an HMAC signature computed on its backend. "Source ID only": anyone
knowing a Source ID can act as that contact; suitable only for testing or closed
networks.

* `signature` - Require signature verification
* `raw` - Source ID only (Optional)
          {
          }
          "sourceIdSignatureTtlMinutes"?:  // How long a signature can be used to obtain
the contact identity. Not a session lifetime: once exchanged, the session follows the
existing WebChat mechanism.

* `1` - 1
* `5` - 5
* `15` - 15 (Optional)
          {
          }
          "keycloakTokenPassthrough"?: boolean // When enabled, the Keycloak access
token a visitor logged in with is forwarded as the Authorization header when the AI
calls MCP and API tools on their behalf, so tools do not require a separate per-tool
login. Only for the Keycloak sign source. Never overrides an Authorization header a tool
already resolves from its own credentials. The visitor identity is the organization
member bound to the conversation at login, never the contact Source ID. (Optional)
          "keycloakTokenPassthroughAllowedHosts"?: [ // Hostnames (or "*.example.com"
wildcards) of the tools the visitor Keycloak token may be sent to (Optional)
```

```
            string
          ]
          "organizationLogin": object // How visitors sign in when the sign source is
"organization" (mirrors the back-office login); null for other sign sources
        }
        "enableAnalysis"?: boolean // Optional
      }
      }
      "chatbot": object // Chatbot (Agent) summary from the conversation's inbox,
already eager-loaded.

``is_maigpt`` lets the client tell the default MaiGPT agent apart (icon, feature
gate) without comparing against the organization's ``maigpt_inbox`` id;
``file_workspace_mode`` is the effective P6 mode (MaiGPT, blueprint and the
organization's file-library switch already applied).
      "title": string
      "lastMessage"?: { // Optional
      {
        "id": string (uuid)
        "type"?: string // Optional
        "content"?: string // Optional
        "createdAt": string (timestamp)
      }
      }
      "callRecord":
      {
        "id": string (uuid)
        "status"?: string (enum: initiated, ringing, in-progress, completed, failed,
busy, no-answer, canceled) // * `initiated` - Initiated
* `ringing` - Ringing
* `in-progress` - In Progress
* `completed` - Completed
* `failed` - Failed
* `busy` - Busy
* `no-answer` - No Answer
* `canceled` - Canceled (Optional)
        "direction": string (enum: inbound, outbound) // * `inbound` - Inbound
* `outbound` - Outbound
        "isActive": boolean
        "canHangup": boolean
      }
      "lastMessageCreatedAt": string (timestamp)
      "unreadMessagesCount": integer
      "autoReplyEnabled": boolean
      "isAutoReplyNow": boolean
      "willAiReplyNow": boolean // Whether a text message arriving through the inbox
gets an AI reply right now.

The messaging channels are gated by ``is_auto_reply_now`` (auto reply on and inside the
inbox auto-reply schedule) and by the inbox having a chatbot. The chatbot's API web chat
is answered by the completions endpoint, which ignores the schedule, so there the
conversation switch alone decides. The channel is only looked up for a web inbox outside
its schedule.
```

```
Surfaces that ignore the schedule on any inbox answer from their own rule instead: the
completions endpoint continuing an existing conversation
(``completions_progress_status``)
and voice turns, which the voice agent answers.
      "lastReadAt": string (timestamp)
      "createdAt": string (timestamp)
      "isGroupChat": boolean
      "enableGroupMention"?: boolean // Optional
      "queryMetadata"?: { // Query metadata that controls the scope of searchable
knowledge; see each endpoint for details (Optional)
      {
        "knowledgeBases"?: [ // List of searchable knowledge bases; an empty array or
null denies all access (no permission); omitting it imposes no restriction (Optional)
          {
            "knowledgeBaseId": string (uuid) // Knowledge base ID
            "chatbotFileIds"?: [ // List of file IDs (excluded or exclusively selected
depending on hasUserSelectedAll) (Optional)
              string (uuid)
            ]
            "knowledgeBaseFileIds"?: [ // List of file IDs (the new name for
chatbotFileIds; this field takes precedence when both are provided) (Optional)
              string (uuid)
            ]
            "faqIds"?: [ // List of FAQ IDs (excluded or exclusively selected depending
on hasUserSelectedAll) (Optional)
              string (uuid)
            ]
            "hasUserSelectedAll"?: boolean // true selects all knowledge base content
except the listed items; false selects only the listed items (Optional)
          }
        ]
        "labelRelations"?: { // Label filter criteria; an empty conditions array means
no label filtering (not a lack of permission). Must be provided with knowledgeBases;
when provided alone, knowledge base retrieval does not apply label filtering (no
restriction) (Optional)
        {
          "operator": string (enum: AND, OR) // How label conditions are combined
          "conditions"?: [ // List of label conditions; supports nested
operator/conditions combinations (Optional)
            object
          ]
        }
        }
      }
      }
      "toolMask"?: object // Enabled/disabled state per tool: {tool_id: bool} (Optional)
      "connectorMask"?: object // Enabled/disabled state per connector: {connector_id:
bool} (Optional)
      "thinkingConfig"?: object // None = not set (inherit the chatbot setting);
otherwise {"reasoning_effort": <level>} (Optional)
      "thinkingConfigSchema": { // Thinking configuration form for this model; null
means the model has no thinking configuration
```

```
      {
        "type"?: string // Form type, always reasoning_effort (Optional)
        "fields"?: object // reasoning_effort field: options lists the thinking levels
this model accepts (from lowest to highest); default is always null (Optional)
        "canDisable"?: boolean // Whether thinking can be disabled for this model; when
true, options includes off (Optional)
        "unsetBehavior"?: string (enum: off, model_default) // Behavior when neither the
conversation nor the assistant sets a thinking level: off disables thinking (fastest);
model_default lets the model decide, or enables thinking through the platform default
level (Optional)
        "unsetLevel"?: string // Level the platform actually sends when no level is set;
null means no thinking parameter is sent, leaving the model to use its own default
(Optional)
      }
      }
      "effectiveThinkingConfig": object // The level the next reply sends on this
conversation's model, after gating and clamping.

The stored choice resolves conversation > chatbot > the LLM row's default level; None
means
the model sends no thinking parameter, so the provider default applies.
      "llm": string (uuid) // The model the next reply runs on: the conversation's pin,
else its assistant's current model.

TC-0205: returning the stored ``conversation.llm`` would show a model an unpinned
conversation no
longer uses once its assistant switches model, while ``thinking_config_schema`` already
follows the
effective model. Read-only: displaying it never marks the conversation as explicitly
selected;
only the update-llm endpoint does.
      "deepResearchStatus":  // Status of deep research for this conversation

* `not_used` - Not Used
* `started` - Started
* `running` - Running
* `completed` - Completed
* `failed` - Failed
      {
      }
      "deepResearchOutputFormat": // May have different types
      string (enum: canvas, chat, file) // Chosen delivery form for the finished report.
Set only when the user clicks a format in the pre-research choice card; reset to NULL
each time Deep Research is (re-)armed. NULL means no explicit choice (or a plan-skipping
request) and falls back to Canvas at render time, but stays distinct from an explicit
canvas pick so the frontend can lock the card only after a real selection. To roll back
to fixed-Canvas behavior, force this to NULL/canvas — no redeploy needed.

* `canvas` - Canvas
* `chat` - Chat reply
* `file` - Downloadable file
      "ipAddress": string
      "ipCountryCode": string
```

```
      "ipRecordedAt": string (timestamp)
      "assignee":
      {
        "id": string (uuid)
        "name": string
        "userId": string (uuid)
      }
      "status"?: string (enum: open, resolved, queued) // * `open` - Open
* `resolved` - Resolved
* `queued` - Queued (Optional)
      "tags": [
        {
          "id": string (uuid)
          "name": string
          "memberIds"?: [ // Optional
            string (uuid)
          ]
        }
      ]
      "progressStatus": string
      "firstResponseAt"?: string (timestamp) // Optional
      "queuedAt"?: string (timestamp) // Optional
      "assignedAt"?: string (timestamp) // Optional
      "transferReason"?: string // Optional
      "satisfactionScore": integer // Conversation satisfaction rating on a 5-point
scale (1=very dissatisfied, 5=very satisfied)
      "satisfactionComment": string
      "satisfactionSubmittedAt": string (timestamp)
      "latestAnalysisSummary": string // The conversation's current analysis summary
(its active summary revision).

Reads the `latest_analysis_summary` annotation added by `setup_eager_loading`
to avoid an N+1 query. All read paths (list / retrieve / create) eager-load,
so the annotation is present; it falls back to '' only for instances built
outside `setup_eager_loading`.
      "clientPlatform":  // Client platform that created this conversation (web,
desktop)

* `web` - Web
* `desktop` - Desktop
      {
      }
      "workingDirectory": string // Absolute path of the local folder bound to a desktop
conversation. Only set for desktop conversations; null for web conversations.
      "slideProjectId": string
      "matchedField": string // Cached per instance: ``get_matched_message_id`` /
``get_matched_snippet``
both read this, so resolving it once avoids recomputing the keyword and
title-match logic three times per serialized conversation.
      "matchedSnippet": string // Keyword-centred excerpt of the matched message, with
ellipses.

Reads the ``matched_message_content`` annotation added by
```

```
``ConversationViewSet._annotate_keyword_match``; no extra query.
      "matchedMessageId": string
      "pinnedAt": string (timestamp) // When the conversation was pinned. Null means
unpinned.
      "folder": string (uuid) // The user-defined sidebar folder this conversation is
grouped into. Null means unclassified (shown under the time groups). Deleting the folder
resets this to null without deleting the conversation.
      "hasActiveBrowserSession": boolean // Whether a browser_use session snapshot
exists to resume.

Lets the frontend know it should proactively re-request the browser
panel (emit ``browser:start``) after a page reload, instead of only
ever showing the panel when a live ``browser:frame`` push happens to
arrive first.
      "callerOrganizationId": string // Bound caller organization (stamped at
conversation start); null when unbound
      "handoff": object // Handoff information: enabled is the platform toggle; the
continuing conversation includes source_conversation_id/source_title; the original
conversation includes continued_to_conversation_id/continued_to_title and
latest_summary_message_id
      "displayContextUsage": boolean // Whether to display the context usage percentage
bar (a conversation platform toggle; always true for MaiGPT; independent of the handoff
toggle)
      "autoSplitReason": string // Reason automatic conversation splitting created this
conversation: resolved (after resolution) / idle (inactivity); null if not created by
splitting
      "continuedFrom": object // Conversation continued from when splitting: {id,
last_message_at, deleted}; if the old conversation was deleted, id=null and deleted=true
      "continuedTo": object // Most recent conversation split from this conversation:
{id, created_at}; null if none
      "continuationSummary": object // Continuation summary: {state:
disabled|pending|ready|not_applied, items: [{conversation_id, content, generated_at,
last_message_at, old_status}]} (items ordered newest to oldest); null if not created by
splitting
      "conversationKind": string // chat = a chat with an agent; secretary = the
member's personal secretary Work chat
    }
  ]
}
```

Example Response Values

```
{
  "count": 123,
  "next": "http://api.example.org/accounts/?page=4",
  "previous": "http://api.example.org/accounts/?page=2",
  "results": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "contact": {
        "id": "550e8400-e29b-41d4-a716-446655440000",
```

```
      "name": "Response string",
      "avatar": "Response string",
      "email": "response@example.com",
      "phoneNumber": "Response string",
      "metadata": null,
      "sourceId": "Response string",
      "tags": [
        {
          "id": "550e8400-e29b-41d4-a716-446655440000",
          "name": "Response string"
        }
      ]
    },
    "inbox": {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "Response string",
      "channelType": "line",
      "unreadConversationsCount": 456,
      "signAuth": {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "signSource": "550e8400-e29b-41d4-a716-446655440000",
        "signParams": {
          "keycloak": {
            "clientId": "Response string",
            "url": "Response string",
            "realm": "Response string"
          },
          "line": {
            "liffId": "Response string"
          },
          "ad": {
            "saml": "Response string"
          },
          "google": {
            "enabled": false
          }
        },
        "sourceIdAccessEnabled": false,
        "sourceIdVerifyMode": {},
        "sourceIdSignatureTtlMinutes": {},
        "keycloakTokenPassthrough": false,
        "keycloakTokenPassthroughAllowedHosts": [
          "Response string"
        ],
        "organizationLogin": {
          "id": "550e8400-e29b-41d4-a716-446655440000",
          "name": "Example response name",
          "description": "Example response description"
        }
      },
      "enableAnalysis": false
    },
    "chatbot": {
```

```
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Example response name",
    "description": "Example response description"
  },
  "title": "Response string",
  "lastMessage": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "type": "Response string",
    "content": "Response string",
    "createdAt": "Response string"
  },
  "callRecord": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "status": "initiated",
    "direction": "inbound",
    "isActive": false,
    "canHangup": false
  },
  "lastMessageCreatedAt": "Response string",
  "unreadMessagesCount": 456,
  "autoReplyEnabled": false,
  "isAutoReplyNow": false,
  "willAiReplyNow": false,
  "lastReadAt": "Response string",
  "createdAt": "Response string",
  "isGroupChat": false,
  "enableGroupMention": false,
  "queryMetadata": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Example response name",
    "description": "Example response description"
  },
  "toolMask": null,
  "connectorMask": null,
  "thinkingConfig": null,
  "thinkingConfigSchema": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Example response name",
    "description": "Example response description"
  },
  "effectiveThinkingConfig": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Example response name",
    "description": "Example response description"
  },
  "llm": "550e8400-e29b-41d4-a716-446655440000",
  "deepResearchStatus": {},
  "deepResearchOutputFormat": "canvas",
  "ipAddress": "Response string",
  "ipCountryCode": "Response string",
  "ipRecordedAt": "Response string",
  "assignee": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
```

```
    "name": "Response string",
    "userId": "550e8400-e29b-41d4-a716-446655440000"
  },
  "status": "open",
  "tags": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "Response string",
      "memberIds": [
        "550e8400-e29b-41d4-a716-446655440000"
      ]
    }
  ],
  "progressStatus": "Response string",
  "firstResponseAt": "Response string",
  "queuedAt": "Response string",
  "assignedAt": "Response string",
  "transferReason": "Response string",
  "satisfactionScore": 456,
  "satisfactionComment": "Response string",
  "satisfactionSubmittedAt": "Response string",
  "latestAnalysisSummary": "Response string",
  "clientPlatform": {},
  "workingDirectory": "Response string",
  "slideProjectId": "Response string",
  "matchedField": "Response string",
  "matchedSnippet": "Response string",
  "matchedMessageId": "Response string",
  "pinnedAt": "Response string",
  "folder": "550e8400-e29b-41d4-a716-446655440000",
  "hasActiveBrowserSession": false,
  "callerOrganizationId": "Response string",
  "handoff": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Example response name",
    "description": "Example response description"
  },
  "displayContextUsage": false,
  "autoSplitReason": "Response string",
  "continuedFrom": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Example response name",
    "description": "Example response description"
  },
  "continuedTo": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Example response name",
    "description": "Example response description"
  },
  "continuationSummary": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Example response name",
    "description": "Example response description"
```

```
      },
      "conversationKind": "Response string"
    }
  ]
}
```

Status code: 4XX - Error response; X-Error-Code carries its code (see "Error codes").

Retrieve a Specific Conversation

GET `/api/v1/conversations/{id}`

Parameters

Parameter Name	Required	Type	Description
`id`	V	string	A UUID string identifying this Conversation.

Code Examples

Shell/Bash

```
# API call example (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/conversations/550e8400-e29b-41d4-a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/conversations/550e8400-e29b-41d4-a716-446655440000/", config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/conversations/550e8400-e29b-41d4-a716-
446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/conversations/550e8400-e29b-41d4-a716-
446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response Content

Status code: 200

Example Response Schema

```
{
  "id": string (uuid)
  "contact": { // Lightweight Contact Serializer for the Conversation List view

Includes only fields required by the List view, excluding inboxes, mcp_credentials, and
api_credentials
to avoid N+1 queries. email / phone_number / metadata are scalar fields on Contact
itself,
needed for display in the frontend conversation sidebar, with no N+1 overhead.
  {
    "id": string (uuid)
```

```
    "name": string
    "avatar"?: string // Stores our own media as a relative storage key, or an external
CDN URL as-is. (Optional)
    "email"?: // May have different types (Optional)
    string (email) // Optional
    "phoneNumber"?: string // Optional
    "metadata"?: object // Custom customer information shown in the customer panel of
the conversation page (Optional)
    "sourceId"?: string // Optional
    "tags": [
      {
        "id": string (uuid)
        "name": string
      }
    ]
  }
  }
  "inbox": { // Inbox summary embedded in a conversation payload.

``unread_conversations_count`` stays here because it is part of the
documented REST conversation API. It is an org-wide denormalized
counter, so WS emit paths must run the payload through
:func:`strip_org_wide_unread_count` before broadcasting it to rooms
that include members without ``GroupInbox.can_view_conversations``.
  {
    "id": string (uuid)
    "name": string
    "channelType": string (enum: line, telegram, teams, web, messenger, instagram,
email, whatsapp, slack, team_plus, line_works, viber) // * `line` - LINE
* `telegram` - Telegram
* `teams` - Teams
* `web` - Web
* `messenger` - Messenger
* `instagram` - Instagram
* `email` - Email
* `whatsapp` - WhatsApp
* `slack` - Slack
* `team_plus` - Team+
* `line_works` - LINE WORKS
* `viber` - Viber
    "unreadConversationsCount"?: integer // Optional
    "signAuth"?:  // Optional
    {
      "id": string (uuid)
      "signSource": string (uuid)
      "signParams": {
      {
        "keycloak":
        {
          "clientId": string
          "url": string
          "realm": string
        }
```

```
        "line":
        {
          "liffId": string
        }
        "ad":
        {
          "saml": string
        }
        "google"?:  // Optional
        {
          "enabled": boolean
        }
      }
      }
      "sourceIdAccessEnabled"?: boolean // When enabled, embedded visitors presenting a
Source ID (verified per the verify mode below) may chat without going through the login
flow. Disabled keeps every existing behavior unchanged. (Optional)
      "sourceIdVerifyMode"?:  // "Require signature verification": the embedding site
must send an HMAC signature computed on its backend. "Source ID only": anyone knowing a
Source ID can act as that contact; suitable only for testing or closed networks.

* `signature` - Require signature verification
* `raw` - Source ID only (Optional)
      {
      }
      "sourceIdSignatureTtlMinutes"?:  // How long a signature can be used to obtain the
contact identity. Not a session lifetime: once exchanged, the session follows the
existing WebChat mechanism.

* `1` - 1
* `5` - 5
* `15` - 15 (Optional)
      {
      }
      "keycloakTokenPassthrough"?: boolean // When enabled, the Keycloak access token a
visitor logged in with is forwarded as the Authorization header when the AI calls MCP
and API tools on their behalf, so tools do not require a separate per-tool login. Only
for the Keycloak sign source. Never overrides an Authorization header a tool already
resolves from its own credentials. The visitor identity is the organization member bound
to the conversation at login, never the contact Source ID. (Optional)
      "keycloakTokenPassthroughAllowedHosts"?: [ // Hostnames (or "*.example.com"
wildcards) of the tools the visitor Keycloak token may be sent to (Optional)
        string
      ]
      "organizationLogin": object // How visitors sign in when the sign source is
"organization" (mirrors the back-office login); null for other sign sources
    }
    "enableAnalysis"?: boolean // Optional
  }
  }
  "chatbot": object // Chatbot (Agent) summary from the conversation's inbox, already
eager-loaded.
```

```
``is_maigpt`` lets the client tell the default MaiGPT agent apart (icon, feature
gate) without comparing against the organization's ``maigpt_inbox`` id;
``file_workspace_mode`` is the effective P6 mode (MaiGPT, blueprint and the
organization's file-library switch already applied).
  "title": string
  "lastMessage"?: { // Optional
  {
    "id": string (uuid)
    "type"?: string // Optional
    "content"?: string // Optional
    "createdAt": string (timestamp)
  }
  }
  "callRecord":
  {
    "id": string (uuid)
    "status"?: string (enum: initiated, ringing, in-progress, completed, failed, busy,
no-answer, canceled) // * `initiated` - Initiated
* `ringing` - Ringing
* `in-progress` - In Progress
* `completed` - Completed
* `failed` - Failed
* `busy` - Busy
* `no-answer` - No Answer
* `canceled` - Canceled (Optional)
    "direction": string (enum: inbound, outbound) // * `inbound` - Inbound
* `outbound` - Outbound
    "isActive": boolean
    "canHangup": boolean
  }
  "lastMessageCreatedAt": string (timestamp)
  "unreadMessagesCount": integer
  "autoReplyEnabled": boolean
  "isAutoReplyNow": boolean
  "willAiReplyNow": boolean // Whether a text message arriving through the inbox gets an
AI reply right now.

The messaging channels are gated by ``is_auto_reply_now`` (auto reply on and inside the
inbox auto-reply schedule) and by the inbox having a chatbot. The chatbot's API web chat
is answered by the completions endpoint, which ignores the schedule, so there the
conversation switch alone decides. The channel is only looked up for a web inbox outside
its schedule.

Surfaces that ignore the schedule on any inbox answer from their own rule instead: the
completions endpoint continuing an existing conversation
(``completions_progress_status``)
and voice turns, which the voice agent answers.
  "lastReadAt": string (timestamp)
  "createdAt": string (timestamp)
  "isGroupChat": boolean
  "enableGroupMention"?: boolean // Optional
  "queryMetadata"?: { // Query metadata controlling the scope of searchable knowledge;
see each endpoint for details (Optional)
```

```
  {
    "knowledgeBases"?: [ // List of searchable knowledge bases; an empty array or null
denies all access (no permission), while omission imposes no restriction (Optional)
      {
        "knowledgeBaseId": string (uuid) // Knowledge base ID
        "chatbotFileIds"?: [ // List of file IDs (excluded or exclusively selected
depending on hasUserSelectedAll) (Optional)
          string (uuid)
        ]
        "knowledgeBaseFileIds"?: [ // List of file IDs (the new name for chatbotFileIds;
this field takes precedence when both are provided) (Optional)
          string (uuid)
        ]
        "faqIds"?: [ // List of FAQ IDs (excluded or exclusively selected depending on
hasUserSelectedAll) (Optional)
          string (uuid)
        ]
        "hasUserSelectedAll"?: boolean // true selects all knowledge base content except
the listed items; false selects only the listed items (Optional)
      }
    ]
    "labelRelations"?: { // Label filter criteria; an empty conditions array means no
label filtering (not a denial of access). Must be provided together with knowledgeBases;
when provided alone, knowledge base retrieval does not apply label filtering (no
restriction) (Optional)
    {
      "operator": string (enum: AND, OR) // How label conditions are combined
      "conditions"?: [ // List of label conditions supporting nested operator/conditions
combinations (Optional)
        object
      ]
    }
    }
  }
  }
  "toolMask"?: object // Enabled/disabled state per tool: {tool_id: bool} (Optional)
  "connectorMask"?: object // Enabled/disabled state per connector: {connector_id: bool}
(Optional)
  "thinkingConfig"?: object // None = not set (inherit the chatbot setting); otherwise
{"reasoning_effort": <level>} (Optional)
  "thinkingConfigSchema": { // Thinking configuration form for this model; null means
the model has no thinking configuration
  {
    "type"?: string // Form type, always reasoning_effort (Optional)
    "fields"?: object // reasoning_effort field: options lists the thinking levels
accepted by this model (lowest to highest); default is always null (Optional)
    "canDisable"?: boolean // Whether thinking can be disabled for this model; when
true, options includes off (Optional)
    "unsetBehavior"?: string (enum: off, model_default) // Actual behavior when neither
the conversation nor the assistant sets a thinking level: off disables thinking
(fastest); model_default lets the model decide or enables thinking at the platform
default level (Optional)
    "unsetLevel"?: string // Level actually sent by the platform when no level is set;
```

```
null means no thinking parameter is sent, leaving the model default in effect (Optional)
  }
  }
  "effectiveThinkingConfig": object // The level the next reply sends on this
conversation's model, after gating and clamping.

The stored choice resolves conversation > chatbot > the LLM row's default level; None
means
the model sends no thinking parameter, so the provider default applies.
  "llm": string (uuid) // The model the next reply runs on: the conversation's pin, else
its assistant's current model.

TC-0205: returning the stored ``conversation.llm`` would show a model an unpinned
conversation no
longer uses once its assistant switches model, while ``thinking_config_schema`` already
follows the
effective model. Read-only: displaying it never marks the conversation as explicitly
selected;
only the update-llm endpoint does.
  "deepResearchStatus":  // Status of deep research for this conversation

* `not_used` - Not Used
* `started` - Started
* `running` - Running
* `completed` - Completed
* `failed` - Failed
  {
  }
  "deepResearchOutputFormat": // May have different types
  string (enum: canvas, chat, file) // Chosen delivery form for the finished report. Set
only when the user clicks a format in the pre-research choice card; reset to NULL each
time Deep Research is (re-)armed. NULL means no explicit choice (or a plan-skipping
request) and falls back to Canvas at render time, but stays distinct from an explicit
canvas pick so the frontend can lock the card only after a real selection. To roll back
to fixed-Canvas behavior, force this to NULL/canvas — no redeploy needed.

* `canvas` - Canvas
* `chat` - Chat reply
* `file` - Downloadable file
  "ipAddress": string
  "ipCountryCode": string
  "ipRecordedAt": string (timestamp)
  "assignee":
  {
    "id": string (uuid)
    "name": string
    "userId": string (uuid)
  }
  "status"?: string (enum: open, resolved, queued) // * `open` - Open
* `resolved` - Resolved
* `queued` - Queued (Optional)
  "tags": [
    {
```

```
      "id": string (uuid)
      "name": string
      "memberIds"?: [ // Optional
        string (uuid)
      ]
    }
  ]
  "progressStatus": string
  "firstResponseAt"?: string (timestamp) // Optional
  "queuedAt"?: string (timestamp) // Optional
  "assignedAt"?: string (timestamp) // Optional
  "transferReason"?: string // Optional
  "satisfactionScore": integer // Conversation satisfaction rating on a 5-point scale
(1=very dissatisfied, 5=very satisfied)
  "satisfactionComment": string
  "satisfactionSubmittedAt": string (timestamp)
  "latestAnalysisSummary": string // The conversation's current analysis summary (its
active summary revision).

Reads the `latest_analysis_summary` annotation added by `setup_eager_loading`
to avoid an N+1 query. All read paths (list / retrieve / create) eager-load,
so the annotation is present; it falls back to '' only for instances built
outside `setup_eager_loading`.
  "clientPlatform":  // Client platform that created this conversation (web, desktop)

* `web` - Web
* `desktop` - Desktop
  {
  }
  "workingDirectory": string // Absolute path of the local folder bound to a desktop
conversation. Only set for desktop conversations; null for web conversations.
  "slideProjectId": string
  "matchedField": string // Cached per instance: ``get_matched_message_id`` /
``get_matched_snippet``
both read this, so resolving it once avoids recomputing the keyword and
title-match logic three times per serialized conversation.
  "matchedSnippet": string // Keyword-centred excerpt of the matched message, with
ellipses.

Reads the ``matched_message_content`` annotation added by
``ConversationViewSet._annotate_keyword_match``; no extra query.
  "matchedMessageId": string
  "pinnedAt": string (timestamp) // When the conversation was pinned. Null means
unpinned.
  "folder": string (uuid) // The user-defined sidebar folder this conversation is
grouped into. Null means unclassified (shown under the time groups). Deleting the folder
resets this to null without deleting the conversation.
  "hasActiveBrowserSession": boolean // Whether a browser_use session snapshot exists to
resume.

Lets the frontend know it should proactively re-request the browser
panel (emit ``browser:start``) after a page reload, instead of only
ever showing the panel when a live ``browser:frame`` push happens to
```

```
arrive first.
  "callerOrganizationId": string // Bound caller organization (stamped at conversation
start); null when unbound
  "handoff": object // Handoff information: enabled is the platform switch; the
continuing conversation includes source_conversation_id/source_title; the original
conversation includes continued_to_conversation_id/continued_to_title and
latest_summary_message_id
  "displayContextUsage": boolean // Whether to display the context usage percentage bar
(a conversation platform switch, always true for MaiGPT; independent of the handoff
switch)
  "autoSplitReason": string // Reason this conversation was created by automatic
splitting: resolved (after resolution) or idle (inactivity); null if not created by
splitting
  "continuedFrom": object // Conversation this split conversation continues from: {id,
last_message_at, deleted}; if the previous conversation was deleted, id=null and
deleted=true
  "continuedTo": object // Most recent conversation split from this conversation: {id,
created_at}; null if none
  "continuationSummary": object // Continuation summary: {state:
disabled|pending|ready|not_applied, items: [{conversation_id, content, generated_at,
last_message_at, old_status}]} (items ordered newest to oldest); null if not created by
splitting
  "conversationKind": string // chat = a chat with an agent; secretary = the member's
personal secretary Work chat
}
```

Example Response Values

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "contact": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Response string",
    "avatar": "Response string",
    "email": "response@example.com",
    "phoneNumber": "Response string",
    "metadata": null,
    "sourceId": "Response string",
    "tags": [
      {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "name": "Response string"
      }
    ]
  },
  "inbox": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Response string",
    "channelType": "line",
    "unreadConversationsCount": 456,
    "signAuth": {
```

```
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "signSource": "550e8400-e29b-41d4-a716-446655440000",
      "signParams": {
        "keycloak": {
          "clientId": "Response string",
          "url": "Response string",
          "realm": "Response string"
        },
        "line": {
          "liffId": "Response string"
        },
        "ad": {
          "saml": "Response string"
        },
        "google": {
          "enabled": false
        }
      },
      "sourceIdAccessEnabled": false,
      "sourceIdVerifyMode": {},
      "sourceIdSignatureTtlMinutes": {},
      "keycloakTokenPassthrough": false,
      "keycloakTokenPassthroughAllowedHosts": [
        "Response string"
      ],
      "organizationLogin": {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "name": "Example response name",
        "description": "Example response description"
      }
    },
    "enableAnalysis": false
  },
  "chatbot": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Example response name",
    "description": "Example response description"
  },
  "title": "Response string",
  "lastMessage": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "type": "Response string",
    "content": "Response string",
    "createdAt": "Response string"
  },
  "callRecord": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "status": "initiated",
    "direction": "inbound",
    "isActive": false,
    "canHangup": false
  },
  "lastMessageCreatedAt": "Response string",
```

```
  "unreadMessagesCount": 456,
  "autoReplyEnabled": false,
  "isAutoReplyNow": false,
  "willAiReplyNow": false,
  "lastReadAt": "Response string",
  "createdAt": "Response string",
  "isGroupChat": false,
  "enableGroupMention": false,
  "queryMetadata": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Example response name",
    "description": "Example response description"
  },
  "toolMask": null,
  "connectorMask": null,
  "thinkingConfig": null,
  "thinkingConfigSchema": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Example response name",
    "description": "Example response description"
  },
  "effectiveThinkingConfig": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Example response name",
    "description": "Example response description"
  },
  "llm": "550e8400-e29b-41d4-a716-446655440000",
  "deepResearchStatus": {},
  "deepResearchOutputFormat": "canvas",
  "ipAddress": "Response string",
  "ipCountryCode": "Response string",
  "ipRecordedAt": "Response string",
  "assignee": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Response string",
    "userId": "550e8400-e29b-41d4-a716-446655440000"
  },
  "status": "open",
  "tags": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "Response string",
      "memberIds": [
        "550e8400-e29b-41d4-a716-446655440000"
      ]
    }
  ],
  "progressStatus": "Response string",
  "firstResponseAt": "Response string",
  "queuedAt": "Response string",
  "assignedAt": "Response string",
  "transferReason": "Response string",
  "satisfactionScore": 456,
```

```
  "satisfactionComment": "Response string",
  "satisfactionSubmittedAt": "Response string",
  "latestAnalysisSummary": "Response string",
  "clientPlatform": {},
  "workingDirectory": "Response string",
  "slideProjectId": "Response string",
  "matchedField": "Response string",
  "matchedSnippet": "Response string",
  "matchedMessageId": "Response string",
  "pinnedAt": "Response string",
  "folder": "550e8400-e29b-41d4-a716-446655440000",
  "hasActiveBrowserSession": false,
  "callerOrganizationId": "Response string",
  "handoff": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Example response name",
    "description": "Example response description"
  },
  "displayContextUsage": false,
  "autoSplitReason": "Response string",
  "continuedFrom": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Example response name",
    "description": "Example response description"
  },
  "continuedTo": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Example response name",
    "description": "Example response description"
  },
  "continuationSummary": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Example response name",
    "description": "Example response description"
  },
  "conversationKind": "Response string"
}
```


Status Code: 4XX - Error response; X-Error-Code carries its code (see "Error codes").

Rename Conversation

`PATCH` `/api/v1/conversations/{id}/rename/`

Parameters

Parameter Name	Required	Type	Description
id	V	string	A UUID string identifying this Conversation.

Request Body

Request Parameters

Field	Type	Required	Description
title	string	No	

Example Request Schema

```
{
  "title"?: string // Optional
}
```

Example Request Values

```
{
  "title": "Example name"
}
```

Code Examples

Shell/Bash

```
# API call example (Shell)
curl -X PATCH "https://api.maiagent.ai/api/v1/conversations/550e8400-e29b-41d4-
a716-446655440000/rename/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "title": "Example name"
  }'

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// Request Body (payload)
const data = {
    "title": "Example name"
  };

axios.patch("https://api.maiagent.ai/api/v1/conversations/550e8400-e29b-41d4-a716-446655440000/rename/", data, config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/conversations/550e8400-e29b-41d4-a716-
446655440000/rename/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# Request Body (payload)
data = {
    "title": "Example name"
}

response = requests.patch(url, json=data, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>patch("https://api.maiagent.ai/api/v1/conversations/550e8400-e29b-41d4-a716-
446655440000/rename/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'title' => 'Example name'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response Body

Status Code: 200

Example Response Schema

```
{
  "id": string (uuid)
  "contact": { // Lightweight Contact Serializer for the Conversation List view

Includes only the fields required by the List view, omitting inboxes, mcp_credentials
and api_credentials
to avoid N+1 queries. email / phone_number / metadata are scalar fields on Contact
```

```
itself,
needed for display in the frontend conversation sidebar, with no N+1 overhead.
  {
    "id": string (uuid)
    "name": string
    "avatar"?: string // Stores our own media as a relative storage key, or an external
CDN URL as-is. (Optional)
    "email"?: // May have different types (Optional)
    string (email) // Optional
    "phoneNumber"?: string // Optional
    "metadata"?: object // Custom customer information shown in the customer panel of
the conversation page (Optional)
    "sourceId"?: string // Optional
    "tags": [
      {
        "id": string (uuid)
        "name": string
      }
    ]
  }
  }
  "inbox": { // Inbox summary embedded in a conversation payload.

``unread_conversations_count`` stays here because it is part of the
documented REST conversation API. It is an org-wide denormalized
counter, so WS emit paths must run the payload through
:func:`strip_org_wide_unread_count` before broadcasting it to rooms
that include members without ``GroupInbox.can_view_conversations``.
  {
    "id": string (uuid)
    "name": string
    "channelType": string (enum: line, telegram, teams, web, messenger, instagram,
email, whatsapp, slack, team_plus, line_works, viber) // * `line` - LINE
* `telegram` - Telegram
* `teams` - Teams
* `web` - Web
* `messenger` - Messenger
* `instagram` - Instagram
* `email` - Email
* `whatsapp` - WhatsApp
* `slack` - Slack
* `team_plus` - Team+
* `line_works` - LINE WORKS
* `viber` - Viber
    "unreadConversationsCount"?: integer // Optional
    "signAuth"?:  // Optional
    {
      "id": string (uuid)
      "signSource": string (uuid)
      "signParams": {
      {
        "keycloak":
        {
```

```
          "clientId": string
          "url": string
          "realm": string
        }
        "line":
        {
          "liffId": string
        }
        "ad":
        {
          "saml": string
        }
        "google"?:  // Optional
        {
          "enabled": boolean
        }
      }
      }
      "sourceIdAccessEnabled"?: boolean // When enabled, embedded visitors presenting a
Source ID (verified per the verify mode below) may chat without going through the login
flow. Disabled keeps every existing behavior unchanged. (Optional)
      "sourceIdVerifyMode"?:  // "Require signature verification": the embedding site
must send an HMAC signature computed on its backend. "Source ID only": anyone knowing a
Source ID can act as that contact; suitable only for testing or closed networks.

* `signature` - Require signature verification
* `raw` - Source ID only (Optional)
      {
      }
      "sourceIdSignatureTtlMinutes"?:  // How long a signature can be used to obtain the
contact identity. Not a session lifetime: once exchanged, the session follows the
existing WebChat mechanism.

* `1` - 1
* `5` - 5
* `15` - 15 (Optional)
      {
      }
      "keycloakTokenPassthrough"?: boolean // When enabled, the Keycloak access token a
visitor logged in with is forwarded as the Authorization header when the AI calls MCP
and API tools on their behalf, so tools do not require a separate per-tool login. Only
for the Keycloak sign source. Never overrides an Authorization header a tool already
resolves from its own credentials. The visitor identity is the organization member bound
to the conversation at login, never the contact Source ID. (Optional)
      "keycloakTokenPassthroughAllowedHosts"?: [ // Hostnames (or "*.example.com"
wildcards) of the tools the visitor Keycloak token may be sent to (Optional)
        string
      ]
      "organizationLogin": object // How visitors sign in when the sign source is
"organization" (mirrors the back-office login); null for other sign sources
    }
    "enableAnalysis"?: boolean // Optional
  }
```

```
  }
  "chatbot": object // Chatbot (Agent) summary from the conversation's inbox, already
eager-loaded.

``is_maigpt`` lets the client tell the default MaiGPT agent apart (icon, feature
gate) without comparing against the organization's ``maigpt_inbox`` id;
``file_workspace_mode`` is the effective P6 mode (MaiGPT, blueprint and the
organization's file-library switch already applied).
  "title": string
  "lastMessage"?: { // Optional
  {
    "id": string (uuid)
    "type"?: string // Optional
    "content"?: string // Optional
    "createdAt": string (timestamp)
  }
  }
  "callRecord":
  {
    "id": string (uuid)
    "status"?: string (enum: initiated, ringing, in-progress, completed, failed, busy,
no-answer, canceled) // * `initiated` - Initiated
* `ringing` - Ringing
* `in-progress` - In Progress
* `completed` - Completed
* `failed` - Failed
* `busy` - Busy
* `no-answer` - No Answer
* `canceled` - Canceled (Optional)
    "direction": string (enum: inbound, outbound) // * `inbound` - Inbound
* `outbound` - Outbound
    "isActive": boolean
    "canHangup": boolean
  }
  "lastMessageCreatedAt": string (timestamp)
  "unreadMessagesCount": integer
  "autoReplyEnabled": boolean
  "isAutoReplyNow": boolean
  "willAiReplyNow": boolean // Whether a text message arriving through the inbox gets an
AI reply right now.

The messaging channels are gated by ``is_auto_reply_now`` (auto reply on and inside the
inbox auto-reply schedule) and by the inbox having a chatbot. The chatbot's API web chat
is answered by the completions endpoint, which ignores the schedule, so there the
conversation switch alone decides. The channel is only looked up for a web inbox outside
its schedule.

Surfaces that ignore the schedule on any inbox answer from their own rule instead: the
completions endpoint continuing an existing conversation
(``completions_progress_status``)
and voice turns, which the voice agent answers.
  "lastReadAt": string (timestamp)
  "createdAt": string (timestamp)
```

```
  "isGroupChat": boolean
  "enableGroupMention"?: boolean // Optional
  "queryMetadata"?: { // Query metadata controlling the scope of searchable knowledge;
see each endpoint for details (Optional)
  {
    "knowledgeBases"?: [ // List of searchable knowledge bases; an empty array or null
denies access to all knowledge bases (no permission), while omitting this field imposes
no restriction (Optional)
      {
        "knowledgeBaseId": string (uuid) // Knowledge base ID
        "chatbotFileIds"?: [ // List of file IDs (excluded or exclusively selected
depending on hasUserSelectedAll) (Optional)
          string (uuid)
        ]
        "knowledgeBaseFileIds"?: [ // List of file IDs (the new name for chatbotFileIds;
this field takes precedence when both are provided) (Optional)
          string (uuid)
        ]
        "faqIds"?: [ // List of FAQ IDs (excluded or exclusively selected depending on
hasUserSelectedAll) (Optional)
          string (uuid)
        ]
        "hasUserSelectedAll"?: boolean // true selects all knowledge base content except
the listed items; false selects only the listed items (Optional)
      }
    ]
    "labelRelations"?: { // Label filter criteria; an empty conditions array disables
label filtering (it does not deny access). Must be provided together with
knowledgeBases; when provided alone, label filtering is not applied to knowledge base
retrieval (no restriction) (Optional)
    {
      "operator": string (enum: AND, OR) // How label conditions are combined
      "conditions"?: [ // List of label conditions; supports nested operator/conditions
combinations (Optional)
        object
      ]
    }
    }
  }
  }
  "toolMask"?: object // Enabled/disabled state per tool: {tool_id: bool} (Optional)
  "connectorMask"?: object // Enabled/disabled state per connector: {connector_id: bool}
(Optional)
  "thinkingConfig"?: object // None = not set (inherit the chatbot setting); otherwise
{"reasoning_effort": <level>} (Optional)
  "thinkingConfigSchema": { // Thinking configuration form for this model; null means
the model has no thinking settings
  {
    "type"?: string // Form type, always reasoning_effort (Optional)
    "fields"?: object // reasoning_effort field: options lists the thinking levels
accepted by this model (from lowest to highest), and default is always null (Optional)
    "canDisable"?: boolean // Whether thinking can be disabled for this model; when
true, options includes off (Optional)
```

```
    "unsetBehavior"?: string (enum: off, model_default) // Actual behavior when neither
the conversation nor the assistant has a thinking level set: off disables thinking
(fastest); model_default lets the model decide or enables thinking through the platform
default level (Optional)
    "unsetLevel"?: string // Level the platform actually sends when no level is set;
null means no thinking parameter is sent, leaving the model default in effect (Optional)
  }
  }
  "effectiveThinkingConfig": object // The level the next reply sends on this
conversation's model, after gating and clamping.

The stored choice resolves conversation > chatbot > the LLM row's default level; None
means
the model sends no thinking parameter, so the provider default applies.
  "llm": string (uuid) // The model the next reply runs on: the conversation's pin, else
its assistant's current model.

TC-0205: returning the stored ``conversation.llm`` would show a model an unpinned
conversation no
longer uses once its assistant switches model, while ``thinking_config_schema`` already
follows the
effective model. Read-only: displaying it never marks the conversation as explicitly
selected;
only the update-llm endpoint does.
  "deepResearchStatus":  // Status of deep research for this conversation

* `not_used` - Not Used
* `started` - Started
* `running` - Running
* `completed` - Completed
* `failed` - Failed
  {
  }
  "deepResearchOutputFormat": // May have different types
  string (enum: canvas, chat, file) // Chosen delivery form for the finished report. Set
only when the user clicks a format in the pre-research choice card; reset to NULL each
time Deep Research is (re-)armed. NULL means no explicit choice (or a plan-skipping
request) and falls back to Canvas at render time, but stays distinct from an explicit
canvas pick so the frontend can lock the card only after a real selection. To roll back
to fixed-Canvas behavior, force this to NULL/canvas — no redeploy needed.

* `canvas` - Canvas
* `chat` - Chat reply
* `file` - Downloadable file
  "ipAddress": string
  "ipCountryCode": string
  "ipRecordedAt": string (timestamp)
  "assignee":
  {
    "id": string (uuid)
    "name": string
    "userId": string (uuid)
  }
```

```
  "status"?: string (enum: open, resolved, queued) // * `open` - Open
* `resolved` - Resolved
* `queued` - Queued (Optional)
  "tags": [
    {
      "id": string (uuid)
      "name": string
      "memberIds"?: [ // Optional
        string (uuid)
      ]
    }
  ]
  "progressStatus": string
  "firstResponseAt"?: string (timestamp) // Optional
  "queuedAt"?: string (timestamp) // Optional
  "assignedAt"?: string (timestamp) // Optional
  "transferReason"?: string // Optional
  "satisfactionScore": integer // Conversation satisfaction rating on a 5-point scale
(1=very dissatisfied, 5=very satisfied)
  "satisfactionComment": string
  "satisfactionSubmittedAt": string (timestamp)
  "latestAnalysisSummary": string // The conversation's current analysis summary (its
active summary revision).

Reads the `latest_analysis_summary` annotation added by `setup_eager_loading`
to avoid an N+1 query. All read paths (list / retrieve / create) eager-load,
so the annotation is present; it falls back to '' only for instances built
outside `setup_eager_loading`.
  "clientPlatform":  // Client platform that created this conversation (web, desktop)

* `web` - Web
* `desktop` - Desktop
  {
  }
  "workingDirectory": string // Absolute path of the local folder bound to a desktop
conversation. Only set for desktop conversations; null for web conversations.
  "slideProjectId": string
  "matchedField": string // Cached per instance: ``get_matched_message_id`` /
``get_matched_snippet``
both read this, so resolving it once avoids recomputing the keyword and
title-match logic three times per serialized conversation.
  "matchedSnippet": string // Keyword-centred excerpt of the matched message, with
ellipses.

Reads the ``matched_message_content`` annotation added by
``ConversationViewSet._annotate_keyword_match``; no extra query.
  "matchedMessageId": string
  "pinnedAt": string (timestamp) // When the conversation was pinned. Null means
unpinned.
  "folder": string (uuid) // The user-defined sidebar folder this conversation is
grouped into. Null means unclassified (shown under the time groups). Deleting the folder
resets this to null without deleting the conversation.
  "hasActiveBrowserSession": boolean // Whether a browser_use session snapshot exists to
```

```
resume.

Lets the frontend know it should proactively re-request the browser
panel (emit ``browser:start``) after a page reload, instead of only
ever showing the panel when a live ``browser:frame`` push happens to
arrive first.
  "callerOrganizationId": string // Bound caller organization (stamped at conversation
start); null when unbound
  "handoff": object // Handoff information: enabled is the platform toggle; the
continuing conversation includes source_conversation_id/source_title; the original
conversation being handed off includes continued_to_conversation_id/continued_to_title
and latest_summary_message_id
  "displayContextUsage": boolean // Whether to display the context usage percentage bar
(a conversation platform toggle, always true for MaiGPT; independent of the handoff
toggle)
  "autoSplitReason": string // Reason this conversation was created by automatic
conversation splitting: resolved (after resolution) or idle (inactivity); null if not
created by splitting
  "continuedFrom": object // Conversation from which this split conversation continues:
{id, last_message_at, deleted}; if the previous conversation was deleted, id=null and
deleted=true
  "continuedTo": object // Most recent conversation split from this conversation: {id,
created_at}; null if none
  "continuationSummary": object // Continuation summary: {state:
disabled|pending|ready|not_applied, items: [{conversation_id, content, generated_at,
last_message_at, old_status}]} (items ordered newest to oldest); null if not created by
splitting
  "conversationKind": string // chat = a chat with an agent; secretary = the member's
personal secretary Work chat
}
```

Example Response Values

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "contact": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Response string",
    "avatar": "Response string",
    "email": "response@example.com",
    "phoneNumber": "Response string",
    "metadata": null,
    "sourceId": "Response string",
    "tags": [
      {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "name": "Response string"
      }
    ]
  },
  "inbox": {
```

```
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Response string",
    "channelType": "line",
    "unreadConversationsCount": 456,
    "signAuth": {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "signSource": "550e8400-e29b-41d4-a716-446655440000",
      "signParams": {
        "keycloak": {
          "clientId": "Response string",
          "url": "Response string",
          "realm": "Response string"
        },
        "line": {
          "liffId": "Response string"
        },
        "ad": {
          "saml": "Response string"
        },
        "google": {
          "enabled": false
        }
      },
      "sourceIdAccessEnabled": false,
      "sourceIdVerifyMode": {},
      "sourceIdSignatureTtlMinutes": {},
      "keycloakTokenPassthrough": false,
      "keycloakTokenPassthroughAllowedHosts": [
        "Response string"
      ],
      "organizationLogin": {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "name": "Example response name",
        "description": "Example response description"
      }
    },
    "enableAnalysis": false
  },
  "chatbot": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Example response name",
    "description": "Example response description"
  },
  "title": "Response string",
  "lastMessage": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "type": "Response string",
    "content": "Response string",
    "createdAt": "Response string"
  },
  "callRecord": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "status": "initiated",
```

```
    "direction": "inbound",
    "isActive": false,
    "canHangup": false
  },
  "lastMessageCreatedAt": "Response string",
  "unreadMessagesCount": 456,
  "autoReplyEnabled": false,
  "isAutoReplyNow": false,
  "willAiReplyNow": false,
  "lastReadAt": "Response string",
  "createdAt": "Response string",
  "isGroupChat": false,
  "enableGroupMention": false,
  "queryMetadata": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Example response name",
    "description": "Example response description"
  },
  "toolMask": null,
  "connectorMask": null,
  "thinkingConfig": null,
  "thinkingConfigSchema": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Example response name",
    "description": "Example response description"
  },
  "effectiveThinkingConfig": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Example response name",
    "description": "Example response description"
  },
  "llm": "550e8400-e29b-41d4-a716-446655440000",
  "deepResearchStatus": {},
  "deepResearchOutputFormat": "canvas",
  "ipAddress": "Response string",
  "ipCountryCode": "Response string",
  "ipRecordedAt": "Response string",
  "assignee": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Response string",
    "userId": "550e8400-e29b-41d4-a716-446655440000"
  },
  "status": "open",
  "tags": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "Response string",
      "memberIds": [
        "550e8400-e29b-41d4-a716-446655440000"
      ]
    }
  ],
  "progressStatus": "Response string",
```

```
  "firstResponseAt": "Response string",
  "queuedAt": "Response string",
  "assignedAt": "Response string",
  "transferReason": "Response string",
  "satisfactionScore": 456,
  "satisfactionComment": "Response string",
  "satisfactionSubmittedAt": "Response string",
  "latestAnalysisSummary": "Response string",
  "clientPlatform": {},
  "workingDirectory": "Response string",
  "slideProjectId": "Response string",
  "matchedField": "Response string",
  "matchedSnippet": "Response string",
  "matchedMessageId": "Response string",
  "pinnedAt": "Response string",
  "folder": "550e8400-e29b-41d4-a716-446655440000",
  "hasActiveBrowserSession": false,
  "callerOrganizationId": "Response string",
  "handoff": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Example response name",
    "description": "Example response description"
  },
  "displayContextUsage": false,
  "autoSplitReason": "Response string",
  "continuedFrom": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Example response name",
    "description": "Example response description"
  },
  "continuedTo": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Example response name",
    "description": "Example response description"
  },
  "continuationSummary": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Example response name",
    "description": "Example response description"
  },
  "conversationKind": "Response string"
}
```


Status Code: 4XX - Error response; X-Error-Code carries its code (see "Error codes").

Delete Conversation

DELETE `/api/v1/conversations/{id}`

Parameters

Parameter Name	Required	Type	Description
`id`	V	string	A UUID string identifying this Conversation.

Code Examples

Shell/Bash

```
# API call example (Shell)
curl -X DELETE "https://api.maiagent.ai/api/v1/conversations/550e8400-e29b-41d4-
a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

// Request body (payload)
const data = null;

axios.delete("https://api.maiagent.ai/api/v1/conversations/550e8400-e29b-41d4-a716-446655440000/", data, config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request failed:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/conversations/550e8400-e29b-41d4-a716-
446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.delete(url, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request failed:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>delete("https://api.maiagent.ai/api/v1/conversations/550e8400-e29b-41d4-a716-
446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request failed: ' . $e->getMessage();
}
?>
```

Response Body

Status Code	Description
204	No response body
4XX	Error response; X-Error-Code carries its code (see "Error codes").

Stop AI Response

POST `/api/v1/conversations/{conversationId}/stop-response/`

Parameters

Parameter Name	Required	Type	Description
`conversationId`	V	string	

Code Examples

Shell/Bash

```
# API call example (Shell)
curl -X POST "https://api.maiagent.ai/api/v1/conversations/550e8400-e29b-41d4-a716-446655440000/stop-response/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

// Request body (payload)
const data = null;

axios.post("https://api.maiagent.ai/api/v1/conversations/550e8400-e29b-41d4-a716-446655440000/stop-response/", data, config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request failed:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/conversations/550e8400-e29b-41d4-a716-
446655440000/stop-response/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.post(url, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request failed:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>post("https://api.maiagent.ai/api/v1/conversations/550e8400-e29b-41d4-a716-
446655440000/stop-response/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request failed: ' . $e->getMessage();
}
?>
```

Response Body

Status Code	Description
200	No response body
4XX	Error response; X-Error-Code carries its code (see "Error codes").

Submit Conversation Satisfaction

POST `/api/v1/conversations/{id}/satisfaction/`

Satisfaction can only be submitted once per conversation.

Parameters

Parameter Name	Required	Type	Description
`id`	V	string	A UUID string identifying this Conversation.

Request Body

Request Parameters

Field	Type	Required	Description
satisfactionScore	integer	Yes	Conversation satisfaction rating on a 5-point scale (1=very dissatisfied, 5=very satisfied)
satisfactionComment	string	No	

Request Schema Example

```
{
  "satisfactionScore": integer // Conversation satisfaction rating on a 5-point scale
(1=very dissatisfied, 5=very satisfied)
  "satisfactionComment"?: string // Optional
}
```

Example Request Values

```
{
  "satisfactionScore": 5,
  "satisfactionComment": "The answer was clear and the issue has been resolved"
}
```

Code Examples

Shell/Bash

```
# API Call Example (Shell)
curl -X POST "https://api.maiagent.ai/api/v1/conversations/550e8400-e29b-41d4-a716-446655440000/satisfaction/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "satisfactionScore": 5,
    "satisfactionComment": "The answer was clear and the issue has been resolved"
  }'

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// Request Body (payload)
const data = {
    "satisfactionScore": 5,
    "satisfactionComment": "The answer was clear and the issue has been resolved"
  };

axios.post("https://api.maiagent.ai/api/v1/conversations/550e8400-e29b-41d4-a716-446655440000/satisfaction/", data, config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/conversations/550e8400-e29b-41d4-a716-
446655440000/satisfaction/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# Request Body (payload)
data = {
    "satisfactionScore": 5,
    "satisfactionComment": "The answer was clear and the issue has been resolved"
}

response = requests.post(url, json=data, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>post("https://api.maiagent.ai/api/v1/conversations/550e8400-e29b-41d4-a716-
446655440000/satisfaction/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'satisfactionScore' => 5,
            'satisfactionComment' => 'The answer was clear and the issue has been
resolved'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response Body

Status Code: 201

Response Schema Example

```
{
  "satisfactionScore": integer
  "satisfactionComment"?: string // Optional
  "satisfactionSubmittedAt": string // Submission time as an ISO 8601 UTC string, for
```

```
example 2026-10-09T15:10:48.717193Z
}
```

Example Response Values

```
{
  "satisfactionScore": 456,
  "satisfactionComment": "Response string",
  "satisfactionSubmittedAt": "Response string"
}
```

Status Code: 409 - Satisfaction has already been submitted for this conversation

List Conversation Events

GET `/api/v1/conversations/{id}/events/`

Event records for the human handoff workflow (event_type: transfer_triggered／human_assigned／returned_to_ai／queue_timeout), which can be reconciled with Webhooks. For the workflow, see Customer Service System Integration in the technical manual.

Parameters

Parameter Name	Required	Type	Description
`id`	V	string	A UUID string identifying this Conversation.

Code Examples

Shell/Bash

```
# API Call Example (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/conversations/550e8400-e29b-41d4-a716-446655440000/events/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/conversations/550e8400-e29b-41d4-a716-446655440000/events/", config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/conversations/550e8400-e29b-41d4-a716-
446655440000/events/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/conversations/550e8400-e29b-41d4-a716-
446655440000/events/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response Body

Status Code: 200

Response Schema Example

```
{
  "id": string (uuid)
  "contact": { // Lightweight Contact Serializer for the Conversation List view

Includes only the fields required by the List view, omitting inboxes, mcp_credentials,
and api_credentials
to avoid N+1 queries. email / phone_number / metadata are scalar fields on Contact
itself,
needed for display in the frontend conversation sidebar, with no N+1 overhead.
  {
    "id": string (uuid)
```

```
    "name": string
    "avatar"?: string // Stores our own media as a relative storage key, or an external
CDN URL as-is. (Optional)
    "email"?: // May have different types (Optional)
    string (email) // Optional
    "phoneNumber"?: string // Optional
    "metadata"?: object // Custom customer information shown in the customer panel of
the conversation page (Optional)
    "sourceId"?: string // Optional
    "tags": [
      {
        "id": string (uuid)
        "name": string
      }
    ]
  }
  }
  "inbox": { // Inbox summary embedded in a conversation payload.

``unread_conversations_count`` stays here because it is part of the
documented REST conversation API. It is an org-wide denormalized
counter, so WS emit paths must run the payload through
:func:`strip_org_wide_unread_count` before broadcasting it to rooms
that include members without ``GroupInbox.can_view_conversations``.
  {
    "id": string (uuid)
    "name": string
    "channelType": string (enum: line, telegram, teams, web, messenger, instagram,
email, whatsapp, slack, team_plus, line_works, viber) // * `line` - LINE
* `telegram` - Telegram
* `teams` - Teams
* `web` - Web
* `messenger` - Messenger
* `instagram` - Instagram
* `email` - Email
* `whatsapp` - WhatsApp
* `slack` - Slack
* `team_plus` - Team+
* `line_works` - LINE WORKS
* `viber` - Viber
    "unreadConversationsCount"?: integer // Optional
    "signAuth"?:  // Optional
    {
      "id": string (uuid)
      "signSource": string (uuid)
      "signParams": {
      {
        "keycloak":
        {
          "clientId": string
          "url": string
          "realm": string
        }
```

```
        "line":
        {
          "liffId": string
        }
        "ad":
        {
          "saml": string
        }
        "google"?:  // Optional
        {
          "enabled": boolean
        }
      }
      }
      "sourceIdAccessEnabled"?: boolean // When enabled, embedded visitors presenting a
Source ID (verified per the verify mode below) may chat without going through the login
flow. Disabled keeps every existing behavior unchanged. (Optional)
      "sourceIdVerifyMode"?:  // "Require signature verification": the embedding site
must send an HMAC signature computed on its backend. "Source ID only": anyone knowing a
Source ID can act as that contact; suitable only for testing or closed networks.

* `signature` - Require signature verification
* `raw` - Source ID only (Optional)
      {
      }
      "sourceIdSignatureTtlMinutes"?:  // How long a signature can be used to obtain the
contact identity. Not a session lifetime: once exchanged, the session follows the
existing WebChat mechanism.

* `1` - 1
* `5` - 5
* `15` - 15 (Optional)
      {
      }
      "keycloakTokenPassthrough"?: boolean // When enabled, the Keycloak access token a
visitor logged in with is forwarded as the Authorization header when the AI calls MCP
and API tools on their behalf, so tools do not require a separate per-tool login. Only
for the Keycloak sign source. Never overrides an Authorization header a tool already
resolves from its own credentials. The visitor identity is the organization member bound
to the conversation at login, never the contact Source ID. (Optional)
      "keycloakTokenPassthroughAllowedHosts"?: [ // Hostnames (or "*.example.com"
wildcards) of the tools the visitor Keycloak token may be sent to (Optional)
        string
      ]
      "organizationLogin": object // How visitors sign in when the sign source is
"organization" (mirrors the back-office login); null for other sign sources
    }
    "enableAnalysis"?: boolean // Optional
  }
  }
  "chatbot": object // Chatbot (Agent) summary from the conversation's inbox, already
eager-loaded.
```

```
``is_maigpt`` lets the client tell the default MaiGPT agent apart (icon, feature
gate) without comparing against the organization's ``maigpt_inbox`` id;
``file_workspace_mode`` is the effective P6 mode (MaiGPT, blueprint and the
organization's file-library switch already applied).
  "title": string
  "lastMessage"?: { // Optional
  {
    "id": string (uuid)
    "type"?: string // Optional
    "content"?: string // Optional
    "createdAt": string (timestamp)
  }
  }
  "callRecord":
  {
    "id": string (uuid)
    "status"?: string (enum: initiated, ringing, in-progress, completed, failed, busy,
no-answer, canceled) // * `initiated` - Initiated
* `ringing` - Ringing
* `in-progress` - In Progress
* `completed` - Completed
* `failed` - Failed
* `busy` - Busy
* `no-answer` - No Answer
* `canceled` - Canceled (Optional)
    "direction": string (enum: inbound, outbound) // * `inbound` - Inbound
* `outbound` - Outbound
    "isActive": boolean
    "canHangup": boolean
  }
  "lastMessageCreatedAt": string (timestamp)
  "unreadMessagesCount": integer
  "autoReplyEnabled": boolean
  "isAutoReplyNow": boolean
  "willAiReplyNow": boolean // Whether a text message arriving through the inbox gets an
AI reply right now.

The messaging channels are gated by ``is_auto_reply_now`` (auto reply on and inside the
inbox auto-reply schedule) and by the inbox having a chatbot. The chatbot's API web chat
is answered by the completions endpoint, which ignores the schedule, so there the
conversation switch alone decides. The channel is only looked up for a web inbox outside
its schedule.

Surfaces that ignore the schedule on any inbox answer from their own rule instead: the
completions endpoint continuing an existing conversation
(``completions_progress_status``)
and voice turns, which the voice agent answers.
  "lastReadAt": string (timestamp)
  "createdAt": string (timestamp)
  "isGroupChat": boolean
  "enableGroupMention"?: boolean // Optional
  "queryMetadata"?: { // Query metadata controlling the scope of accessible knowledge;
see each endpoint for details (Optional)
```

```
  {
    "knowledgeBases"?: [ // List of accessible knowledge bases; an empty array or null
means none are accessible (no permission); omitted means unrestricted (Optional)
      {
        "knowledgeBaseId": string (uuid) // Knowledge base ID
        "chatbotFileIds"?: [ // List of file IDs (excluded or exclusively selected
depending on hasUserSelectedAll) (Optional)
          string (uuid)
        ]
        "knowledgeBaseFileIds"?: [ // List of file IDs (the new name for chatbotFileIds;
this field takes precedence when both are provided) (Optional)
          string (uuid)
        ]
        "faqIds"?: [ // List of FAQ IDs (excluded or exclusively selected depending on
hasUserSelectedAll) (Optional)
          string (uuid)
        ]
        "hasUserSelectedAll"?: boolean // true = select all knowledge base content
except the listed items; false = select only the listed items (Optional)
      }
    ]
    "labelRelations"?: { // Tag filter criteria; an empty conditions array means no tag
filtering (not a lack of permission). Must be provided with knowledgeBases; when
supplied alone, tag filtering is not applied to knowledge base retrieval (equivalent to
unrestricted access) (Optional)
    {
      "operator": string (enum: AND, OR) // How tag conditions are combined
      "conditions"?: [ // List of tag conditions supporting nested operator/conditions
combinations (Optional)
        object
      ]
    }
    }
  }
  }
  "toolMask"?: object // Enabled/disabled state per tool: {tool_id: bool} (Optional)
  "connectorMask"?: object // Enabled/disabled state per connector: {connector_id: bool}
(Optional)
  "thinkingConfig"?: object // None = not set (inherit the chatbot setting); otherwise
{"reasoning_effort": <level>} (Optional)
  "thinkingConfigSchema": { // Thinking configuration form for this model; null means
the model has no thinking settings
  {
    "type"?: string // Form type, always reasoning_effort (Optional)
    "fields"?: object // reasoning_effort field: options lists the thinking levels
accepted by this model (from lowest to highest); default is always null (Optional)
    "canDisable"?: boolean // Whether thinking can be disabled for this model; when
true, options includes off (Optional)
    "unsetBehavior"?: string (enum: off, model_default) // Behavior when neither the
conversation nor the assistant specifies a thinking level: off = no thinking (fastest);
model_default = the model decides, or the platform default level enables thinking
(Optional)
    "unsetLevel"?: string // Level actually sent by the platform when no level is set;
```

```
null means no thinking parameter is sent, leaving the model default in effect (Optional)
  }
  }
  "effectiveThinkingConfig": object // The level the next reply sends on this
conversation's model, after gating and clamping.

The stored choice resolves conversation > chatbot > the LLM row's default level; None
means
the model sends no thinking parameter, so the provider default applies.
  "llm": string (uuid) // The model the next reply runs on: the conversation's pin, else
its assistant's current model.

TC-0205: returning the stored ``conversation.llm`` would show a model an unpinned
conversation no
longer uses once its assistant switches model, while ``thinking_config_schema`` already
follows the
effective model. Read-only: displaying it never marks the conversation as explicitly
selected;
only the update-llm endpoint does.
  "deepResearchStatus":  // Status of deep research for this conversation

* `not_used` - Not Used
* `started` - Started
* `running` - Running
* `completed` - Completed
* `failed` - Failed
  {
  }
  "deepResearchOutputFormat": // May have different types
  string (enum: canvas, chat, file) // Chosen delivery form for the finished report. Set
only when the user clicks a format in the pre-research choice card; reset to NULL each
time Deep Research is (re-)armed. NULL means no explicit choice (or a plan-skipping
request) and falls back to Canvas at render time, but stays distinct from an explicit
canvas pick so the frontend can lock the card only after a real selection. To roll back
to fixed-Canvas behavior, force this to NULL/canvas — no redeploy needed.

* `canvas` - Canvas
* `chat` - Chat reply
* `file` - Downloadable file
  "ipAddress": string
  "ipCountryCode": string
  "ipRecordedAt": string (timestamp)
  "assignee":
  {
    "id": string (uuid)
    "name": string
    "userId": string (uuid)
  }
  "status"?: string (enum: open, resolved, queued) // * `open` - Open
* `resolved` - Resolved
* `queued` - Queued (Optional)
  "tags": [
    {
```

```
      "id": string (uuid)
      "name": string
      "memberIds"?: [ // Optional
        string (uuid)
      ]
    }
  ]
  "progressStatus": string
  "firstResponseAt"?: string (timestamp) // Optional
  "queuedAt"?: string (timestamp) // Optional
  "assignedAt"?: string (timestamp) // Optional
  "transferReason"?: string // Optional
  "satisfactionScore": integer // Conversation satisfaction rating on a 5-point scale
(1=very dissatisfied, 5=very satisfied)
  "satisfactionComment": string
  "satisfactionSubmittedAt": string (timestamp)
  "latestAnalysisSummary": string // The conversation's current analysis summary (its
active summary revision).

Reads the `latest_analysis_summary` annotation added by `setup_eager_loading`
to avoid an N+1 query. All read paths (list / retrieve / create) eager-load,
so the annotation is present; it falls back to '' only for instances built
outside `setup_eager_loading`.
  "clientPlatform":  // Client platform that created this conversation (web, desktop)

* `web` - Web
* `desktop` - Desktop
  {
  }
  "workingDirectory": string // Absolute path of the local folder bound to a desktop
conversation. Only set for desktop conversations; null for web conversations.
  "slideProjectId": string
  "matchedField": string // Cached per instance: ``get_matched_message_id`` /
``get_matched_snippet``
both read this, so resolving it once avoids recomputing the keyword and
title-match logic three times per serialized conversation.
  "matchedSnippet": string // Keyword-centred excerpt of the matched message, with
ellipses.

Reads the ``matched_message_content`` annotation added by
``ConversationViewSet._annotate_keyword_match``; no extra query.
  "matchedMessageId": string
  "pinnedAt": string (timestamp) // When the conversation was pinned. Null means
unpinned.
  "folder": string (uuid) // The user-defined sidebar folder this conversation is
grouped into. Null means unclassified (shown under the time groups). Deleting the folder
resets this to null without deleting the conversation.
  "hasActiveBrowserSession": boolean // Whether a browser_use session snapshot exists to
resume.

Lets the frontend know it should proactively re-request the browser
panel (emit ``browser:start``) after a page reload, instead of only
ever showing the panel when a live ``browser:frame`` push happens to
```

```
arrive first.
  "callerOrganizationId": string // Bound caller organization (stamped at conversation
start); null when unbound
  "handoff": object // Handoff information: enabled = platform switch; the continuing
conversation includes source_conversation_id/source_title; the original conversation
being handed off includes continued_to_conversation_id/continued_to_title and
latest_summary_message_id
  "displayContextUsage": boolean // Whether to display the context usage percentage bar
(conversation platform switch, always true for MaiGPT; independent of the handoff
switch)
  "autoSplitReason": string // Reason this conversation was created by automatic
conversation splitting: resolved (after resolution)／idle (inactivity); null if not
created by splitting
  "continuedFrom": object // Conversation from which this split conversation continues:
{id, last_message_at, deleted}; if the previous conversation was deleted, id=null and
deleted=true
  "continuedTo": object // Most recent conversation split off from this conversation:
{id, created_at}; null if none
  "continuationSummary": object // Continuation summary: {state:
disabled|pending|ready|not_applied, items: [{conversation_id, content, generated_at,
last_message_at, old_status}]} (items ordered newest to oldest); null if not created by
splitting
  "conversationKind": string // chat = a chat with an agent; secretary = the member's
personal secretary Work chat
}
```

Example Response Values


```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "contact": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Response string",
    "avatar": "Response string",
    "email": "response@example.com",
    "phoneNumber": "Response string",
    "metadata": null,
    "sourceId": "Response string",
    "tags": [
      {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "name": "Response string"
      }
    ]
  },
  "inbox": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Response string",
    "channelType": "line",
    "unreadConversationsCount": 456,
    "signAuth": {
```

```
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "signSource": "550e8400-e29b-41d4-a716-446655440000",
      "signParams": {
        "keycloak": {
          "clientId": "Response string",
          "url": "Response string",
          "realm": "Response string"
        },
        "line": {
          "liffId": "Response string"
        },
        "ad": {
          "saml": "Response string"
        },
        "google": {
          "enabled": false
        }
      },
      "sourceIdAccessEnabled": false,
      "sourceIdVerifyMode": {},
      "sourceIdSignatureTtlMinutes": {},
      "keycloakTokenPassthrough": false,
      "keycloakTokenPassthroughAllowedHosts": [
        "Response string"
      ],
      "organizationLogin": {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "name": "Example Response Name",
        "description": "Example Response Description"
      }
    },
    "enableAnalysis": false
  },
  "chatbot": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Example Response Name",
    "description": "Example Response Description"
  },
  "title": "Response string",
  "lastMessage": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "type": "Response string",
    "content": "Response string",
    "createdAt": "Response string"
  },
  "callRecord": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "status": "initiated",
    "direction": "inbound",
    "isActive": false,
    "canHangup": false
  },
  "lastMessageCreatedAt": "Response string",
```

```
  "unreadMessagesCount": 456,
  "autoReplyEnabled": false,
  "isAutoReplyNow": false,
  "willAiReplyNow": false,
  "lastReadAt": "Response string",
  "createdAt": "Response string",
  "isGroupChat": false,
  "enableGroupMention": false,
  "queryMetadata": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Example Response Name",
    "description": "Example Response Description"
  },
  "toolMask": null,
  "connectorMask": null,
  "thinkingConfig": null,
  "thinkingConfigSchema": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Example Response Name",
    "description": "Example Response Description"
  },
  "effectiveThinkingConfig": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Example Response Name",
    "description": "Example Response Description"
  },
  "llm": "550e8400-e29b-41d4-a716-446655440000",
  "deepResearchStatus": {},
  "deepResearchOutputFormat": "canvas",
  "ipAddress": "Response string",
  "ipCountryCode": "Response string",
  "ipRecordedAt": "Response string",
  "assignee": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Response string",
    "userId": "550e8400-e29b-41d4-a716-446655440000"
  },
  "status": "open",
  "tags": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "Response string",
      "memberIds": [
        "550e8400-e29b-41d4-a716-446655440000"
      ]
    }
  ],
  "progressStatus": "Response string",
  "firstResponseAt": "Response string",
  "queuedAt": "Response string",
  "assignedAt": "Response string",
  "transferReason": "Response string",
  "satisfactionScore": 456,
```

```
  "satisfactionComment": "Response string",
  "satisfactionSubmittedAt": "Response string",
  "latestAnalysisSummary": "Response string",
  "clientPlatform": {},
  "workingDirectory": "Response string",
  "slideProjectId": "Response string",
  "matchedField": "Response string",
  "matchedSnippet": "Response string",
  "matchedMessageId": "Response string",
  "pinnedAt": "Response string",
  "folder": "550e8400-e29b-41d4-a716-446655440000",
  "hasActiveBrowserSession": false,
  "callerOrganizationId": "Response string",
  "handoff": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Example Response Name",
    "description": "Example Response Description"
  },
  "displayContextUsage": false,
  "autoSplitReason": "Response string",
  "continuedFrom": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Example Response Name",
    "description": "Example Response Description"
  },
  "continuedTo": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Example Response Name",
    "description": "Example Response Description"
  },
  "continuationSummary": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Example Response Name",
    "description": "Example Response Description"
  },
  "conversationKind": "Response string"
}
```


Status Code: 4XX - Error response; X-Error-Code carries its code (see "Error codes").

Assign Conversation to a Member

`PATCH` `/api/v1/conversations/{id}/assign/`

Set the member taking over and disable AI auto-reply; queued conversations move to in progress.

Parameters

Parameter Name	Required	Type	Description
id	V	string	A UUID string identifying this Conversation.

Request Body

Request Parameters

Field	Type	Required	Description
assignee	string (uuid)	No	
transferReason	string	No	
tagIds	array[string]	No	

Request Schema Example

```
{
  "assignee"?: string (uuid) // Optional
  "transferReason"?: string // Optional
  "tagIds"?: [ // Optional
    string (uuid)
  ]
}
```

Example Request Values

```
{
  "assignee": "550e8400-e29b-41d4-a716-446655440000",
  "transferReason": "Example string",
  "tagIds": [
    "550e8400-e29b-41d4-a716-446655440000"
  ]
}
```

Code Examples

Shell/Bash

```
# API call example (Shell)
curl -X PATCH "https://api.maiagent.ai/api/v1/conversations/550e8400-e29b-41d4-
a716-446655440000/assign/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "assignee": "550e8400-e29b-41d4-a716-446655440000",
    "transferReason": "Example string",
    "tagIds": [
      "550e8400-e29b-41d4-a716-446655440000"
    ]
  }'

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// Request body (payload)
const data = {
    "assignee": "550e8400-e29b-41d4-a716-446655440000",
    "transferReason": "Example string",
    "tagIds": [
      "550e8400-e29b-41d4-a716-446655440000"
    ]
  };

axios.patch("https://api.maiagent.ai/api/v1/conversations/550e8400-e29b-41d4-a716-
446655440000/assign/", data, config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request failed:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/conversations/550e8400-e29b-41d4-a716-
446655440000/assign/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# Request body (payload)
data = {
    "assignee": "550e8400-e29b-41d4-a716-446655440000",
    "transferReason": "Example string",
    "tagIds": [
        "550e8400-e29b-41d4-a716-446655440000"
    ]
}

response = requests.patch(url, json=data, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request failed:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>patch("https://api.maiagent.ai/api/v1/conversations/550e8400-e29b-41d4-a716-
446655440000/assign/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'assignee' => '550e8400-e29b-41d4-a716-446655440000',
            'transferReason' => 'Example string',
            'tagIds' => [
                '550e8400-e29b-41d4-a716-446655440000'
            ]
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request failed: ' . $e->getMessage();
}
?>
```

Response Body

Status code: 200

Example Response Schema

```
{
  "id": string (uuid)
  "contact": { // Lightweight Contact Serializer for the Conversation List view
```

```
Includes only the fields required for the List view; omits inboxes, mcp_credentials, and
api_credentials
to avoid N+1 queries. email / phone_number / metadata are scalar fields on Contact
itself,
needed for display in the frontend conversation sidebar, with no N+1 overhead.
  {
    "id": string (uuid)
    "name": string
    "avatar"?: string // Stores our own media as a relative storage key, or an external
CDN URL as-is. (Optional)
    "email"?: // May have different types (Optional)
    string (email) // Optional
    "phoneNumber"?: string // Optional
    "metadata"?: object // Custom customer information shown in the customer panel of
the conversation page (Optional)
    "sourceId"?: string // Optional
    "tags": [
      {
        "id": string (uuid)
        "name": string
      }
    ]
  }
  }
  "inbox": { // Inbox summary embedded in a conversation payload.

``unread_conversations_count`` stays here because it is part of the
documented REST conversation API. It is an org-wide denormalized
counter, so WS emit paths must run the payload through
:func:`strip_org_wide_unread_count` before broadcasting it to rooms
that include members without ``GroupInbox.can_view_conversations``.
  {
    "id": string (uuid)
    "name": string
    "channelType": string (enum: line, telegram, teams, web, messenger, instagram,
email, whatsapp, slack, team_plus, line_works, viber) // * `line` - LINE
* `telegram` - Telegram
* `teams` - Teams
* `web` - Web
* `messenger` - Messenger
* `instagram` - Instagram
* `email` - Email
* `whatsapp` - WhatsApp
* `slack` - Slack
* `team_plus` - Team+
* `line_works` - LINE WORKS
* `viber` - Viber
    "unreadConversationsCount"?: integer // Optional
    "signAuth"?:  // Optional
    {
      "id": string (uuid)
      "signSource": string (uuid)
```

```
      "signParams": {
      {
        "keycloak":
        {
          "clientId": string
          "url": string
          "realm": string
        }
        "line":
        {
          "liffId": string
        }
        "ad":
        {
          "saml": string
        }
        "google"?:  // Optional
        {
          "enabled": boolean
        }
      }
      }
      "sourceIdAccessEnabled"?: boolean // When enabled, embedded visitors presenting a Source ID (verified per the verify mode below) may chat without going through the login flow. Disabled keeps every existing behavior unchanged. (Optional)
      "sourceIdVerifyMode"?:  // "Require signature verification": the embedding site must send an HMAC signature computed on its backend. "Source ID only": anyone knowing a Source ID can act as that contact; suitable only for testing or closed networks.

* `signature` - Require signature verification
* `raw` - Source ID only (Optional)
      {
      }
      "sourceIdSignatureTtlMinutes"?:  // How long a signature can be used to obtain the contact identity. Not a session lifetime: once exchanged, the session follows the existing WebChat mechanism.

* `1` - 1
* `5` - 5
* `15` - 15 (Optional)
      {
      }
      "keycloakTokenPassthrough"?: boolean // When enabled, the Keycloak access token a visitor logged in with is forwarded as the Authorization header when the AI calls MCP and API tools on their behalf, so tools do not require a separate per-tool login. Only for the Keycloak sign source. Never overrides an Authorization header a tool already resolves from its own credentials. The visitor identity is the organization member bound to the conversation at login, never the contact Source ID. (Optional)
      "keycloakTokenPassthroughAllowedHosts"?: [ // Hostnames (or "*.example.com" wildcards) of the tools the visitor Keycloak token may be sent to (Optional)
        string
      ]
      "organizationLogin": object // How visitors sign in when the sign source is
```

```
"organization" (mirrors the back-office login); null for other sign sources
    }
    "enableAnalysis"?: boolean // Optional
  }
  }
  "chatbot": object // Chatbot (Agent) summary from the conversation's inbox, already
eager-loaded.

``is_maigpt`` lets the client tell the default MaiGPT agent apart (icon, feature
gate) without comparing against the organization's ``maigpt_inbox`` id;
``file_workspace_mode`` is the effective P6 mode (MaiGPT, blueprint and the
organization's file-library switch already applied).
  "title": string
  "lastMessage"?: { // Optional
  {
    "id": string (uuid)
    "type"?: string // Optional
    "content"?: string // Optional
    "createdAt": string (timestamp)
  }
  }
  "callRecord":
  {
    "id": string (uuid)
    "status"?: string (enum: initiated, ringing, in-progress, completed, failed, busy,
no-answer, canceled) // * `initiated` - Initiated
* `ringing` - Ringing
* `in-progress` - In Progress
* `completed` - Completed
* `failed` - Failed
* `busy` - Busy
* `no-answer` - No Answer
* `canceled` - Canceled (Optional)
    "direction": string (enum: inbound, outbound) // * `inbound` - Inbound
* `outbound` - Outbound
    "isActive": boolean
    "canHangup": boolean
  }
  "lastMessageCreatedAt": string (timestamp)
  "unreadMessagesCount": integer
  "autoReplyEnabled": boolean
  "isAutoReplyNow": boolean
  "willAiReplyNow": boolean // Whether a text message arriving through the inbox gets an
AI reply right now.

The messaging channels are gated by ``is_auto_reply_now`` (auto reply on and inside the
inbox auto-reply schedule) and by the inbox having a chatbot. The chatbot's API web chat
is answered by the completions endpoint, which ignores the schedule, so there the
conversation switch alone decides. The channel is only looked up for a web inbox outside
its schedule.

Surfaces that ignore the schedule on any inbox answer from their own rule instead: the
completions endpoint continuing an existing conversation
```

```
(``completions_progress_status``)
and voice turns, which the voice agent answers.
  "lastReadAt": string (timestamp)
  "createdAt": string (timestamp)
  "isGroupChat": boolean
  "enableGroupMention"?: boolean // Optional
  "queryMetadata"?: { // Query metadata controlling the scope of searchable knowledge;
see each endpoint for details (Optional)
  {
    "knowledgeBases"?: [ // List of searchable knowledge bases; an empty array or null
denies access to all knowledge bases (no permission); omission imposes no restriction
(Optional)
      {
        "knowledgeBaseId": string (uuid) // Knowledge base ID
        "chatbotFileIds"?: [ // List of file IDs (excluded or exclusively selected
according to hasUserSelectedAll) (Optional)
          string (uuid)
        ]
        "knowledgeBaseFileIds"?: [ // List of file IDs (the new name for chatbotFileIds;
this field takes precedence when both are provided) (Optional)
          string (uuid)
        ]
        "faqIds"?: [ // List of FAQ IDs (excluded or exclusively selected according to
hasUserSelectedAll) (Optional)
          string (uuid)
        ]
        "hasUserSelectedAll"?: boolean // true selects all knowledge base content except
the listed items; false selects only the listed items (Optional)
      }
    ]
    "labelRelations"?: { // Tag filter conditions; an empty conditions array applies no
tag filter (it does not deny access). Must be provided with knowledgeBases; when
provided alone, no tag filter is applied to knowledge base retrieval (no restriction)
(Optional)
    {
      "operator": string (enum: AND, OR) // How tag conditions are combined
      "conditions"?: [ // List of tag conditions; supports nested operator/conditions
combinations (Optional)
        object
      ]
    }
    }
  }
  }
  "toolMask"?: object // Enabled/disabled state per tool: {tool_id: bool} (Optional)
  "connectorMask"?: object // Enabled/disabled state per connector: {connector_id: bool}
(Optional)
  "thinkingConfig"?: object // None = not set (inherit the chatbot setting); otherwise
{"reasoning_effort": <level>} (Optional)
  "thinkingConfigSchema": { // Thinking configuration form for this model; null means
the model has no thinking settings
  {
    "type"?: string // Form type, always reasoning_effort (Optional)
```

```
    "fields"?: object // reasoning_effort field: options lists the thinking levels
accepted by this model (from lowest to highest); default is always null (Optional)
    "canDisable"?: boolean // Whether thinking can be disabled for this model; when
true, options includes off (Optional)
    "unsetBehavior"?: string (enum: off, model_default) // Actual behavior when neither
the conversation nor the assistant specifies a thinking level: off disables thinking
(fastest); model_default lets the model decide or enables thinking at the platform
default level (Optional)
    "unsetLevel"?: string // Level actually sent by the platform when none is set; null
means no thinking parameter is sent, leaving the model default in effect (Optional)
  }
  }
  "effectiveThinkingConfig": object // The level the next reply sends on this
conversation's model, after gating and clamping.

The stored choice resolves conversation > chatbot > the LLM row's default level; None
means
the model sends no thinking parameter, so the provider default applies.
  "llm": string (uuid) // The model the next reply runs on: the conversation's pin, else
its assistant's current model.

TC-0205: returning the stored ``conversation.llm`` would show a model an unpinned
conversation no
longer uses once its assistant switches model, while ``thinking_config_schema`` already
follows the
effective model. Read-only: displaying it never marks the conversation as explicitly
selected;
only the update-llm endpoint does.
  "deepResearchStatus":  // Status of deep research for this conversation

* `not_used` - Not Used
* `started` - Started
* `running` - Running
* `completed` - Completed
* `failed` - Failed
  {
  }
  "deepResearchOutputFormat": // May have different types
  string (enum: canvas, chat, file) // Chosen delivery form for the finished report. Set
only when the user clicks a format in the pre-research choice card; reset to NULL each
time Deep Research is (re-)armed. NULL means no explicit choice (or a plan-skipping
request) and falls back to Canvas at render time, but stays distinct from an explicit
canvas pick so the frontend can lock the card only after a real selection. To roll back
to fixed-Canvas behavior, force this to NULL/canvas — no redeploy needed.

* `canvas` - Canvas
* `chat` - Chat reply
* `file` - Downloadable file
  "ipAddress": string
  "ipCountryCode": string
  "ipRecordedAt": string (timestamp)
  "assignee":
  {
```

```
    "id": string (uuid)
    "name": string
    "userId": string (uuid)
  }
  "status"?: string (enum: open, resolved, queued) // * `open` - Open
* `resolved` - Resolved
* `queued` - Queued (Optional)
  "tags": [
    {
      "id": string (uuid)
      "name": string
      "memberIds"?: [ // Optional
        string (uuid)
      ]
    }
  ]
  "progressStatus": string
  "firstResponseAt"?: string (timestamp) // Optional
  "queuedAt"?: string (timestamp) // Optional
  "assignedAt"?: string (timestamp) // Optional
  "transferReason"?: string // Optional
  "satisfactionScore": integer // Conversation satisfaction rating on a 5-point scale
(1=very dissatisfied, 5=very satisfied)
  "satisfactionComment": string
  "satisfactionSubmittedAt": string (timestamp)
  "latestAnalysisSummary": string // The conversation's current analysis summary (its
active summary revision).

Reads the `latest_analysis_summary` annotation added by `setup_eager_loading`
to avoid an N+1 query. All read paths (list / retrieve / create) eager-load,
so the annotation is present; it falls back to '' only for instances built
outside `setup_eager_loading`.
  "clientPlatform":  // Client platform that created this conversation (web, desktop)

* `web` - Web
* `desktop` - Desktop
  {
  }
  "workingDirectory": string // Absolute path of the local folder bound to a desktop
conversation. Only set for desktop conversations; null for web conversations.
  "slideProjectId": string
  "matchedField": string // Cached per instance: ``get_matched_message_id`` /
``get_matched_snippet``
both read this, so resolving it once avoids recomputing the keyword and
title-match logic three times per serialized conversation.
  "matchedSnippet": string // Keyword-centred excerpt of the matched message, with
ellipses.

Reads the ``matched_message_content`` annotation added by
``ConversationViewSet._annotate_keyword_match``; no extra query.
  "matchedMessageId": string
  "pinnedAt": string (timestamp) // When the conversation was pinned. Null means
unpinned.
```

```
  "folder": string (uuid) // The user-defined sidebar folder this conversation is
grouped into. Null means unclassified (shown under the time groups). Deleting the folder
resets this to null without deleting the conversation.
  "hasActiveBrowserSession": boolean // Whether a browser_use session snapshot exists to
resume.

Lets the frontend know it should proactively re-request the browser
panel (emit ``browser:start``) after a page reload, instead of only
ever showing the panel when a live ``browser:frame`` push happens to
arrive first.
  "callerOrganizationId": string // Bound caller organization (stamped at conversation
start); null when unbound
  "handoff": object // Handoff information: enabled is the platform toggle; the
continuation conversation carries source_conversation_id/source_title; the original
conversation being handed off carries continued_to_conversation_id/continued_to_title
and latest_summary_message_id
  "displayContextUsage": boolean // Whether to show the context usage percentage bar
(conversation platform toggle; always true for MaiGPT; independent of the handoff
toggle)
  "autoSplitReason": string // Reason this conversation was created by automatic
splitting: resolved (after resolution) / idle (inactivity); null if not created by
splitting
  "continuedFrom": object // Conversation from which this split conversation continues:
{id, last_message_at, deleted}; if the previous conversation was deleted, id=null and
deleted=true
  "continuedTo": object // Most recent conversation split from this conversation: {id,
created_at}; null if none
  "continuationSummary": object // Continuation summary: {state:
disabled|pending|ready|not_applied, items: [{conversation_id, content, generated_at,
last_message_at, old_status}]} (items ordered newest to oldest); null if not created by
splitting
  "conversationKind": string // chat = a chat with an agent; secretary = the member's
personal secretary Work chat
}
```

Example Response Values


```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "contact": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Response string",
    "avatar": "Response string",
    "email": "response@example.com",
    "phoneNumber": "Response string",
    "metadata": null,
    "sourceId": "Response string",
    "tags": [
      {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "name": "Response string"
```

```
      }
    ]
  },
  "inbox": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Response string",
    "channelType": "line",
    "unreadConversationsCount": 456,
    "signAuth": {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "signSource": "550e8400-e29b-41d4-a716-446655440000",
      "signParams": {
        "keycloak": {
          "clientId": "Response string",
          "url": "Response string",
          "realm": "Response string"
        },
        "line": {
          "liffId": "Response string"
        },
        "ad": {
          "saml": "Response string"
        },
        "google": {
          "enabled": false
        }
      },
      "sourceIdAccessEnabled": false,
      "sourceIdVerifyMode": {},
      "sourceIdSignatureTtlMinutes": {},
      "keycloakTokenPassthrough": false,
      "keycloakTokenPassthroughAllowedHosts": [
        "Response string"
      ],
      "organizationLogin": {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "name": "Example response name",
        "description": "Example response description"
      }
    },
    "enableAnalysis": false
  },
  "chatbot": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Example response name",
    "description": "Example response description"
  },
  "title": "Response string",
  "lastMessage": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "type": "Response string",
    "content": "Response string",
    "createdAt": "Response string"
```

```
  },
  "callRecord": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "status": "initiated",
    "direction": "inbound",
    "isActive": false,
    "canHangup": false
  },
  "lastMessageCreatedAt": "Response string",
  "unreadMessagesCount": 456,
  "autoReplyEnabled": false,
  "isAutoReplyNow": false,
  "willAiReplyNow": false,
  "lastReadAt": "Response string",
  "createdAt": "Response string",
  "isGroupChat": false,
  "enableGroupMention": false,
  "queryMetadata": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Example response name",
    "description": "Example response description"
  },
  "toolMask": null,
  "connectorMask": null,
  "thinkingConfig": null,
  "thinkingConfigSchema": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Example response name",
    "description": "Example response description"
  },
  "effectiveThinkingConfig": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Example response name",
    "description": "Example response description"
  },
  "llm": "550e8400-e29b-41d4-a716-446655440000",
  "deepResearchStatus": {},
  "deepResearchOutputFormat": "canvas",
  "ipAddress": "Response string",
  "ipCountryCode": "Response string",
  "ipRecordedAt": "Response string",
  "assignee": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Response string",
    "userId": "550e8400-e29b-41d4-a716-446655440000"
  },
  "status": "open",
  "tags": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "Response string",
      "memberIds": [
        "550e8400-e29b-41d4-a716-446655440000"
```

```
      ]
    }
  ],
  "progressStatus": "Response string",
  "firstResponseAt": "Response string",
  "queuedAt": "Response string",
  "assignedAt": "Response string",
  "transferReason": "Response string",
  "satisfactionScore": 456,
  "satisfactionComment": "Response string",
  "satisfactionSubmittedAt": "Response string",
  "latestAnalysisSummary": "Response string",
  "clientPlatform": {},
  "workingDirectory": "Response string",
  "slideProjectId": "Response string",
  "matchedField": "Response string",
  "matchedSnippet": "Response string",
  "matchedMessageId": "Response string",
  "pinnedAt": "Response string",
  "folder": "550e8400-e29b-41d4-a716-446655440000",
  "hasActiveBrowserSession": false,
  "callerOrganizationId": "Response string",
  "handoff": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Example response name",
    "description": "Example response description"
  },
  "displayContextUsage": false,
  "autoSplitReason": "Response string",
  "continuedFrom": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Example response name",
    "description": "Example response description"
  },
  "continuedTo": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Example response name",
    "description": "Example response description"
  },
  "continuationSummary": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Example response name",
    "description": "Example response description"
  },
  "conversationKind": "Response string"
}
```


Status code: `4XX` - Error response; X-Error-Code carries its code (see "Error codes").

Claim Conversation

PATCH `/api/v1/conversations/{id}/claim/`

Assigns the conversation to the caller, with the same effect as "Assign Conversation".

Parameters

Parameter Name	Required	Type	Description
`id`	V	string	A UUID string identifying this Conversation.

Request Body

Request Parameters

Field	Type	Required	Description
transferReason	string	No	
tagIds	array[string]	No	

Example Request Schema

```
{
  "transferReason"?: string // Optional
  "tagIds"?: [ // Optional
    string (uuid)
  ]
}
```

Example Request Values

```
{
  "transferReason": "Example string",
  "tagIds": [
    "550e8400-e29b-41d4-a716-446655440000"
  ]
}
```

Code Examples

Shell/Bash

```
# API call example (Shell)
curl -X PATCH "https://api.maiagent.ai/api/v1/conversations/550e8400-e29b-41d4-
a716-446655440000/claim/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "transferReason": "Example string",
    "tagIds": [
      "550e8400-e29b-41d4-a716-446655440000"
    ]
  }'

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// Request body (payload)
const data = {
    "transferReason": "Example string",
    "tagIds": [
      "550e8400-e29b-41d4-a716-446655440000"
    ]
  };

axios.patch("https://api.maiagent.ai/api/v1/conversations/550e8400-e29b-41d4-a716-446655440000/claim/", data, config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request failed:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/conversations/550e8400-e29b-41d4-a716-
446655440000/claim/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# Request body (payload)
data = {
    "transferReason": "Example string",
    "tagIds": [
        "550e8400-e29b-41d4-a716-446655440000"
    ]
}

response = requests.patch(url, json=data, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request failed:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>patch("https://api.maiagent.ai/api/v1/conversations/550e8400-e29b-41d4-a716-
446655440000/claim/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'transferReason' => 'Example string',
            'tagIds' => [
                '550e8400-e29b-41d4-a716-446655440000'
            ]
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request failed: ' . $e->getMessage();
}
?>
```

Response body

Status code: 200

Response schema example

```
{
  "id": string (uuid)
  "contact": { // Lightweight Contact Serializer for the Conversation List view
```

```
Includes only the fields required by the List view, omitting inboxes, mcp_credentials,
and api_credentials
to avoid N+1 queries. email / phone_number / metadata are scalar fields on Contact
itself,
needed for display in the frontend conversation sidebar, with no N+1 overhead.
  {
    "id": string (uuid)
    "name": string
    "avatar"?: string // Stores our own media as a relative storage key, or an external
CDN URL as-is. (Optional)
    "email"?: // May have different types (Optional)
    string (email) // Optional
    "phoneNumber"?: string // Optional
    "metadata"?: object // Custom customer information shown in the customer panel of
the conversation page (Optional)
    "sourceId"?: string // Optional
    "tags": [
      {
        "id": string (uuid)
        "name": string
      }
    ]
  }
  }
  "inbox": { // Inbox summary embedded in a conversation payload.

``unread_conversations_count`` stays here because it is part of the
documented REST conversation API. It is an org-wide denormalized
counter, so WS emit paths must run the payload through
:func:`strip_org_wide_unread_count` before broadcasting it to rooms
that include members without ``GroupInbox.can_view_conversations``.
  {
    "id": string (uuid)
    "name": string
    "channelType": string (enum: line, telegram, teams, web, messenger, instagram,
email, whatsapp, slack, team_plus, line_works, viber) // * `line` - LINE
* `telegram` - Telegram
* `teams` - Teams
* `web` - Web
* `messenger` - Messenger
* `instagram` - Instagram
* `email` - Email
* `whatsapp` - WhatsApp
* `slack` - Slack
* `team_plus` - Team+
* `line_works` - LINE WORKS
* `viber` - Viber
    "unreadConversationsCount"?: integer // Optional
    "signAuth"?:  // Optional
    {
      "id": string (uuid)
      "signSource": string (uuid)
      "signParams": {
```

```
      {
        "keycloak":
        {
          "clientId": string
          "url": string
          "realm": string
        }
        "line":
        {
          "liffId": string
        }
        "ad":
        {
          "saml": string
        }
        "google"?:  // Optional
        {
          "enabled": boolean
        }
      }
      }
      "sourceIdAccessEnabled"?: boolean // When enabled, embedded visitors presenting a
Source ID (verified per the verify mode below) may chat without going through the login
flow. Disabled keeps every existing behavior unchanged. (Optional)
      "sourceIdVerifyMode"?:  // "Require signature verification": the embedding site
must send an HMAC signature computed on its backend. "Source ID only": anyone knowing a
Source ID can act as that contact; suitable only for testing or closed networks.

* `signature` - Require signature verification
* `raw` - Source ID only (Optional)
      {
      }
      "sourceIdSignatureTtlMinutes"?:  // How long a signature can be used to obtain the
contact identity. Not a session lifetime: once exchanged, the session follows the
existing WebChat mechanism.

* `1` - 1
* `5` - 5
* `15` - 15 (Optional)
      {
      }
      "keycloakTokenPassthrough"?: boolean // When enabled, the Keycloak access token a
visitor logged in with is forwarded as the Authorization header when the AI calls MCP
and API tools on their behalf, so tools do not require a separate per-tool login. Only
for the Keycloak sign source. Never overrides an Authorization header a tool already
resolves from its own credentials. The visitor identity is the organization member bound
to the conversation at login, never the contact Source ID. (Optional)
      "keycloakTokenPassthroughAllowedHosts"?: [ // Hostnames (or "*.example.com"
wildcards) of the tools the visitor Keycloak token may be sent to (Optional)
        string
      ]
      "organizationLogin": object // How visitors sign in when the sign source is
"organization" (mirrors the back-office login); null for other sign sources
```

```
    }
    "enableAnalysis"?: boolean // Optional
  }
  }
  "chatbot": object // Chatbot (Agent) summary from the conversation's inbox, already
eager-loaded.

``is_maigpt`` lets the client tell the default MaiGPT agent apart (icon, feature
gate) without comparing against the organization's ``maigpt_inbox`` id;
``file_workspace_mode`` is the effective P6 mode (MaiGPT, blueprint and the
organization's file-library switch already applied).
  "title": string
  "lastMessage"?: { // Optional
  {
    "id": string (uuid)
    "type"?: string // Optional
    "content"?: string // Optional
    "createdAt": string (timestamp)
  }
  }
  "callRecord":
  {
    "id": string (uuid)
    "status"?: string (enum: initiated, ringing, in-progress, completed, failed, busy,
no-answer, canceled) // * `initiated` - Initiated
* `ringing` - Ringing
* `in-progress` - In Progress
* `completed` - Completed
* `failed` - Failed
* `busy` - Busy
* `no-answer` - No Answer
* `canceled` - Canceled (Optional)
    "direction": string (enum: inbound, outbound) // * `inbound` - Inbound
* `outbound` - Outbound
    "isActive": boolean
    "canHangup": boolean
  }
  "lastMessageCreatedAt": string (timestamp)
  "unreadMessagesCount": integer
  "autoReplyEnabled": boolean
  "isAutoReplyNow": boolean
  "willAiReplyNow": boolean // Whether a text message arriving through the inbox gets an
AI reply right now.

The messaging channels are gated by ``is_auto_reply_now`` (auto reply on and inside the
inbox auto-reply schedule) and by the inbox having a chatbot. The chatbot's API web chat
is answered by the completions endpoint, which ignores the schedule, so there the
conversation switch alone decides. The channel is only looked up for a web inbox outside
its schedule.

Surfaces that ignore the schedule on any inbox answer from their own rule instead: the
completions endpoint continuing an existing conversation
(``completions_progress_status``)
```

```
and voice turns, which the voice agent answers.
  "lastReadAt": string (timestamp)
  "createdAt": string (timestamp)
  "isGroupChat": boolean
  "enableGroupMention"?: boolean // Optional
  "queryMetadata"?: { // Query metadata controlling the scope of searchable knowledge;
see the documentation for each endpoint (Optional)
  {
    "knowledgeBases"?: [ // List of searchable knowledge bases; an empty array or null
denies access to all knowledge bases, while omission imposes no restriction (Optional)
      {
        "knowledgeBaseId": string (uuid) // Knowledge base ID
        "chatbotFileIds"?: [ // List of file IDs (excluded or exclusively selected
depending on hasUserSelectedAll) (Optional)
          string (uuid)
        ]
        "knowledgeBaseFileIds"?: [ // List of file IDs (the new name for chatbotFileIds;
this field takes precedence when both are provided) (Optional)
          string (uuid)
        ]
        "faqIds"?: [ // List of FAQ IDs (excluded or exclusively selected depending on
hasUserSelectedAll) (Optional)
          string (uuid)
        ]
        "hasUserSelectedAll"?: boolean // true selects all knowledge base content except
the listed items; false selects only the listed items (Optional)
      }
    ]
    "labelRelations"?: { // Tag filter criteria; an empty conditions array disables tag
filtering (it does not deny access). Must be provided with knowledgeBases; when provided
alone, tag filtering is not applied to knowledge base retrieval (no restriction)
(Optional)
    {
      "operator": string (enum: AND, OR) // How tag conditions are combined
      "conditions"?: [ // List of tag conditions supporting nested operator/conditions
combinations (Optional)
        object
      ]
    }
    }
  }
  }
  "toolMask"?: object // Enabled/disabled state per tool: {tool_id: bool} (Optional)
  "connectorMask"?: object // Enabled/disabled state per connector: {connector_id: bool}
(Optional)
  "thinkingConfig"?: object // None = not set (inherit the chatbot setting); otherwise
{"reasoning_effort": <level>} (Optional)
  "thinkingConfigSchema": { // Thinking configuration form for this model; null means
the model has no thinking settings
  {
    "type"?: string // Form type, always reasoning_effort (Optional)
    "fields"?: object // reasoning_effort field: options lists the thinking levels
accepted by this model (from lowest to highest); default is always null (Optional)
```

```
    "canDisable"?: boolean // Whether thinking can be disabled for this model; if true,
options includes off (Optional)
    "unsetBehavior"?: string (enum: off, model_default) // Actual behavior when neither
the conversation nor the assistant has a thinking level set: off disables thinking
(fastest); model_default lets the model decide or enables thinking through the platform
default level (Optional)
    "unsetLevel"?: string // Level actually sent by the platform when no level is set;
null omits the thinking parameter and uses the model default (Optional)
  }
  }
  "effectiveThinkingConfig": object // The level the next reply sends on this
conversation's model, after gating and clamping.

The stored choice resolves conversation > chatbot > the LLM row's default level; None
means
the model sends no thinking parameter, so the provider default applies.
  "llm": string (uuid) // The model the next reply runs on: the conversation's pin, else
its assistant's current model.

TC-0205: returning the stored ``conversation.llm`` would show a model an unpinned
conversation no
longer uses once its assistant switches model, while ``thinking_config_schema`` already
follows the
effective model. Read-only: displaying it never marks the conversation as explicitly
selected;
only the update-llm endpoint does.
  "deepResearchStatus":  // Status of deep research for this conversation

* `not_used` - Not Used
* `started` - Started
* `running` - Running
* `completed` - Completed
* `failed` - Failed
  {
  }
  "deepResearchOutputFormat": // May have different types
  string (enum: canvas, chat, file) // Chosen delivery form for the finished report. Set
only when the user clicks a format in the pre-research choice card; reset to NULL each
time Deep Research is (re-)armed. NULL means no explicit choice (or a plan-skipping
request) and falls back to Canvas at render time, but stays distinct from an explicit
canvas pick so the frontend can lock the card only after a real selection. To roll back
to fixed-Canvas behavior, force this to NULL/canvas — no redeploy needed.

* `canvas` - Canvas
* `chat` - Chat reply
* `file` - Downloadable file
  "ipAddress": string
  "ipCountryCode": string
  "ipRecordedAt": string (timestamp)
  "assignee":
  {
    "id": string (uuid)
    "name": string
```

```
    "userId": string (uuid)
  }
  "status"?: string (enum: open, resolved, queued) // * `open` - Open
* `resolved` - Resolved
* `queued` - Queued (Optional)
  "tags": [
    {
      "id": string (uuid)
      "name": string
      "memberIds"?: [ // Optional
        string (uuid)
      ]
    }
  ]
  "progressStatus": string
  "firstResponseAt"?: string (timestamp) // Optional
  "queuedAt"?: string (timestamp) // Optional
  "assignedAt"?: string (timestamp) // Optional
  "transferReason"?: string // Optional
  "satisfactionScore": integer // Conversation satisfaction rating on a 5-point scale
(1=very dissatisfied, 5=very satisfied)
  "satisfactionComment": string
  "satisfactionSubmittedAt": string (timestamp)
  "latestAnalysisSummary": string // The conversation's current analysis summary (its
active summary revision).

Reads the `latest_analysis_summary` annotation added by `setup_eager_loading`
to avoid an N+1 query. All read paths (list / retrieve / create) eager-load,
so the annotation is present; it falls back to '' only for instances built
outside `setup_eager_loading`.
  "clientPlatform":  // Client platform that created this conversation (web, desktop)

* `web` - Web
* `desktop` - Desktop
  {
  }
  "workingDirectory": string // Absolute path of the local folder bound to a desktop
conversation. Only set for desktop conversations; null for web conversations.
  "slideProjectId": string
  "matchedField": string // Cached per instance: ``get_matched_message_id`` /
``get_matched_snippet``
both read this, so resolving it once avoids recomputing the keyword and
title-match logic three times per serialized conversation.
  "matchedSnippet": string // Keyword-centred excerpt of the matched message, with
ellipses.

Reads the ``matched_message_content`` annotation added by
``ConversationViewSet._annotate_keyword_match``; no extra query.
  "matchedMessageId": string
  "pinnedAt": string (timestamp) // When the conversation was pinned. Null means
unpinned.
  "folder": string (uuid) // The user-defined sidebar folder this conversation is
grouped into. Null means unclassified (shown under the time groups). Deleting the folder
```

```
resets this to null without deleting the conversation.
  "hasActiveBrowserSession": boolean // Whether a browser_use session snapshot exists to
resume.

Lets the frontend know it should proactively re-request the browser
panel (emit ``browser:start``) after a page reload, instead of only
ever showing the panel when a live ``browser:frame`` push happens to
arrive first.
  "callerOrganizationId": string // Bound caller organization (stamped at conversation
start); null when unbound
  "handoff": object // Handoff information: enabled is the platform toggle; the
continuing conversation includes source_conversation_id/source_title; the original
conversation being handed off includes continued_to_conversation_id/continued_to_title
and latest_summary_message_id
  "displayContextUsage": boolean // Whether to display the context usage percentage bar
(conversation platform toggle, always true for MaiGPT; independent of the handoff
toggle)
  "autoSplitReason": string // Reason this conversation was created by automatic
splitting: resolved (after resolution) / idle (inactivity); null if not created by
splitting
  "continuedFrom": object // Conversation from which this split conversation continues:
{id, last_message_at, deleted}; if the previous conversation was deleted, id=null and
deleted=true
  "continuedTo": object // Most recent conversation split from this conversation: {id,
created_at}; null if none
  "continuationSummary": object // Continuation summary: {state:
disabled|pending|ready|not_applied, items: [{conversation_id, content, generated_at,
last_message_at, old_status}]} (items ordered newest to oldest); null if not created by
splitting
  "conversationKind": string // chat = a chat with an agent; secretary = the member's
personal secretary Work chat
}
```

Example response values

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "contact": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Response string",
    "avatar": "Response string",
    "email": "response@example.com",
    "phoneNumber": "Response string",
    "metadata": null,
    "sourceId": "Response string",
    "tags": [
      {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "name": "Response string"
      }
    ]
```

```
  },
  "inbox": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Response string",
    "channelType": "line",
    "unreadConversationsCount": 456,
    "signAuth": {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "signSource": "550e8400-e29b-41d4-a716-446655440000",
      "signParams": {
        "keycloak": {
          "clientId": "Response string",
          "url": "Response string",
          "realm": "Response string"
        },
        "line": {
          "liffId": "Response string"
        },
        "ad": {
          "saml": "Response string"
        },
        "google": {
          "enabled": false
        }
      },
      "sourceIdAccessEnabled": false,
      "sourceIdVerifyMode": {},
      "sourceIdSignatureTtlMinutes": {},
      "keycloakTokenPassthrough": false,
      "keycloakTokenPassthroughAllowedHosts": [
        "Response string"
      ],
      "organizationLogin": {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "name": "Example response name",
        "description": "Example response description"
      }
    },
    "enableAnalysis": false
  },
  "chatbot": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Example response name",
    "description": "Example response description"
  },
  "title": "Response string",
  "lastMessage": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "type": "Response string",
    "content": "Response string",
    "createdAt": "Response string"
  },
  "callRecord": {
```

```
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "status": "initiated",
    "direction": "inbound",
    "isActive": false,
    "canHangup": false
  },
  "lastMessageCreatedAt": "Response string",
  "unreadMessagesCount": 456,
  "autoReplyEnabled": false,
  "isAutoReplyNow": false,
  "willAiReplyNow": false,
  "lastReadAt": "Response string",
  "createdAt": "Response string",
  "isGroupChat": false,
  "enableGroupMention": false,
  "queryMetadata": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Example response name",
    "description": "Example response description"
  },
  "toolMask": null,
  "connectorMask": null,
  "thinkingConfig": null,
  "thinkingConfigSchema": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Example response name",
    "description": "Example response description"
  },
  "effectiveThinkingConfig": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Example response name",
    "description": "Example response description"
  },
  "llm": "550e8400-e29b-41d4-a716-446655440000",
  "deepResearchStatus": {},
  "deepResearchOutputFormat": "canvas",
  "ipAddress": "Response string",
  "ipCountryCode": "Response string",
  "ipRecordedAt": "Response string",
  "assignee": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Response string",
    "userId": "550e8400-e29b-41d4-a716-446655440000"
  },
  "status": "open",
  "tags": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "Response string",
      "memberIds": [
        "550e8400-e29b-41d4-a716-446655440000"
      ]
    }
```

```
  ],
  "progressStatus": "Response string",
  "firstResponseAt": "Response string",
  "queuedAt": "Response string",
  "assignedAt": "Response string",
  "transferReason": "Response string",
  "satisfactionScore": 456,
  "satisfactionComment": "Response string",
  "satisfactionSubmittedAt": "Response string",
  "latestAnalysisSummary": "Response string",
  "clientPlatform": {},
  "workingDirectory": "Response string",
  "slideProjectId": "Response string",
  "matchedField": "Response string",
  "matchedSnippet": "Response string",
  "matchedMessageId": "Response string",
  "pinnedAt": "Response string",
  "folder": "550e8400-e29b-41d4-a716-446655440000",
  "hasActiveBrowserSession": false,
  "callerOrganizationId": "Response string",
  "handoff": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Example response name",
    "description": "Example response description"
  },
  "displayContextUsage": false,
  "autoSplitReason": "Response string",
  "continuedFrom": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Example response name",
    "description": "Example response description"
  },
  "continuedTo": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Example response name",
    "description": "Example response description"
  },
  "continuationSummary": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Example response name",
    "description": "Example response description"
  },
  "conversationKind": "Response string"
}
```


Status code: 4XX - Error response; X-Error-Code carries its code (see "Error codes").

Transfer a conversation to another member

`PATCH` `/api/v1/conversations/{id}/transfer/`

Parameters

Parameter name	Required	Type	Description
`id`	V	string	A UUID string identifying this Conversation.

Request body

Request parameters

Field	Type	Required	Description
assignee	string (uuid)	No	
transferReason	string	No	
tagIds	array[string]	No	

Request schema example

```
{
  "assignee"?: string (uuid) // Optional
  "transferReason"?: string // Optional
  "tagIds"?: [ // Optional
    string (uuid)
  ]
}
```

Example request values

```
{
  "assignee": "550e8400-e29b-41d4-a716-446655440000",
  "transferReason": "Example string",
  "tagIds": [
    "550e8400-e29b-41d4-a716-446655440000"
```

```
  ]
}
```

Code examples

Shell/Bash

```
# API call example (Shell)
curl -X PATCH "https://api.maiagent.ai/api/v1/conversations/550e8400-e29b-41d4-
a716-446655440000/transfer/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "assignee": "550e8400-e29b-41d4-a716-446655440000",
    "transferReason": "Example string",
    "tagIds": [
      "550e8400-e29b-41d4-a716-446655440000"
    ]
  }'

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Configure request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// Request body (payload)
const data = {
    "assignee": "550e8400-e29b-41d4-a716-446655440000",
    "transferReason": "Example string",
    "tagIds": [
      "550e8400-e29b-41d4-a716-446655440000"
    ]
  };

axios.patch("https://api.maiagent.ai/api/v1/conversations/550e8400-e29b-41d4-a716-
446655440000/transfer/", data, config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request failed:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/conversations/550e8400-e29b-41d4-a716-
446655440000/transfer/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# Request body (payload)
data = {
    "assignee": "550e8400-e29b-41d4-a716-446655440000",
    "transferReason": "Example string",
    "tagIds": [
        "550e8400-e29b-41d4-a716-446655440000"
    ]
}

response = requests.patch(url, json=data, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request failed:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>patch("https://api.maiagent.ai/api/v1/conversations/550e8400-e29b-41d4-a716-
446655440000/transfer/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'assignee' => '550e8400-e29b-41d4-a716-446655440000',
            'transferReason' => 'Example string',
            'tagIds' => [
                '550e8400-e29b-41d4-a716-446655440000'
            ]
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request failed: ' . $e->getMessage();
}
?>
```

Response Body

Status Code: 200

Response Schema Example

```
{
  "id": string (uuid)
  "contact": { // Lightweight Contact Serializer for the Conversation List view
```

```
Includes only the fields required for the List view, omitting inboxes, mcp_credentials,
and api_credentials
to avoid N+1 queries. email / phone_number / metadata are scalar fields on Contact
itself;
the frontend conversation sidebar needs to display them, with no N+1 cost.
  {
    "id": string (uuid)
    "name": string
    "avatar"?: string // Stores our own media as a relative storage key, or an external
CDN URL as-is. (Optional)
    "email"?: // May have different types (Optional)
    string (email) // Optional
    "phoneNumber"?: string // Optional
    "metadata"?: object // Custom customer information shown in the customer panel of
the conversation page (Optional)
    "sourceId"?: string // Optional
    "tags": [
      {
        "id": string (uuid)
        "name": string
      }
    ]
  }
  }
  "inbox": { // Inbox summary embedded in a conversation payload.

``unread_conversations_count`` stays here because it is part of the
documented REST conversation API. It is an org-wide denormalized
counter, so WS emit paths must run the payload through
:func:`strip_org_wide_unread_count` before broadcasting it to rooms
that include members without ``GroupInbox.can_view_conversations``.
  {
    "id": string (uuid)
    "name": string
    "channelType": string (enum: line, telegram, teams, web, messenger, instagram,
email, whatsapp, slack, team_plus, line_works, viber) // * `line` - LINE
* `telegram` - Telegram
* `teams` - Teams
* `web` - Web
* `messenger` - Messenger
* `instagram` - Instagram
* `email` - Email
* `whatsapp` - WhatsApp
* `slack` - Slack
* `team_plus` - Team+
* `line_works` - LINE WORKS
* `viber` - Viber
    "unreadConversationsCount"?: integer // Optional
    "signAuth"?:  // Optional
    {
      "id": string (uuid)
      "signSource": string (uuid)
```

```
      "signParams": {
      {
        "keycloak":
        {
          "clientId": string
          "url": string
          "realm": string
        }
        "line":
        {
          "liffId": string
        }
        "ad":
        {
          "saml": string
        }
        "google"?:  // Optional
        {
          "enabled": boolean
        }
      }
      }
      "sourceIdAccessEnabled"?: boolean // When enabled, embedded visitors presenting a Source ID (verified per the verify mode below) may chat without going through the login flow. Disabled keeps every existing behavior unchanged. (Optional)
      "sourceIdVerifyMode"?:  // "Require signature verification": the embedding site must send an HMAC signature computed on its backend. "Source ID only": anyone knowing a Source ID can act as that contact; suitable only for testing or closed networks.

* `signature` - Require signature verification
* `raw` - Source ID only (Optional)
      {
      }
      "sourceIdSignatureTtlMinutes"?:  // How long a signature can be used to obtain the contact identity. Not a session lifetime: once exchanged, the session follows the existing WebChat mechanism.

* `1` - 1
* `5` - 5
* `15` - 15 (Optional)
      {
      }
      "keycloakTokenPassthrough"?: boolean // When enabled, the Keycloak access token a visitor logged in with is forwarded as the Authorization header when the AI calls MCP and API tools on their behalf, so tools do not require a separate per-tool login. Only for the Keycloak sign source. Never overrides an Authorization header a tool already resolves from its own credentials. The visitor identity is the organization member bound to the conversation at login, never the contact Source ID. (Optional)
      "keycloakTokenPassthroughAllowedHosts"?: [ // Hostnames (or "*.example.com" wildcards) of the tools the visitor Keycloak token may be sent to (Optional)
        string
      ]
      "organizationLogin": object // How visitors sign in when the sign source is
```

```
"organization" (mirrors the back-office login); null for other sign sources
    }
    "enableAnalysis"?: boolean // Optional
  }
  }
  "chatbot": object // Chatbot (Agent) summary from the conversation's inbox, already
eager-loaded.

``is_maigpt`` lets the client tell the default MaiGPT agent apart (icon, feature
gate) without comparing against the organization's ``maigpt_inbox`` id;
``file_workspace_mode`` is the effective P6 mode (MaiGPT, blueprint and the
organization's file-library switch already applied).
  "title": string
  "lastMessage"?: { // Optional
  {
    "id": string (uuid)
    "type"?: string // Optional
    "content"?: string // Optional
    "createdAt": string (timestamp)
  }
  }
  "callRecord":
  {
    "id": string (uuid)
    "status"?: string (enum: initiated, ringing, in-progress, completed, failed, busy,
no-answer, canceled) // * `initiated` - Initiated
* `ringing` - Ringing
* `in-progress` - In Progress
* `completed` - Completed
* `failed` - Failed
* `busy` - Busy
* `no-answer` - No Answer
* `canceled` - Canceled (Optional)
    "direction": string (enum: inbound, outbound) // * `inbound` - Inbound
* `outbound` - Outbound
    "isActive": boolean
    "canHangup": boolean
  }
  "lastMessageCreatedAt": string (timestamp)
  "unreadMessagesCount": integer
  "autoReplyEnabled": boolean
  "isAutoReplyNow": boolean
  "willAiReplyNow": boolean // Whether a text message arriving through the inbox gets an
AI reply right now.

The messaging channels are gated by ``is_auto_reply_now`` (auto reply on and inside the
inbox auto-reply schedule) and by the inbox having a chatbot. The chatbot's API web chat
is answered by the completions endpoint, which ignores the schedule, so there the
conversation switch alone decides. The channel is only looked up for a web inbox outside
its schedule.

Surfaces that ignore the schedule on any inbox answer from their own rule instead: the
completions endpoint continuing an existing conversation
```

```
(``completions_progress_status``)
and voice turns, which the voice agent answers.
  "lastReadAt": string (timestamp)
  "createdAt": string (timestamp)
  "isGroupChat": boolean
  "enableGroupMention"?: boolean // Optional
  "queryMetadata"?: { // Query metadata controlling which knowledge can be queried; see
each endpoint for details (Optional)
  {
    "knowledgeBases"?: [ // List of queryable knowledge bases; an empty array or null
denies all access (no permission), while omitting this field imposes no restriction
(Optional)
      {
        "knowledgeBaseId": string (uuid) // Knowledge base ID
        "chatbotFileIds"?: [ // List of file IDs (excluded or exclusively selected
depending on hasUserSelectedAll) (Optional)
          string (uuid)
        ]
        "knowledgeBaseFileIds"?: [ // List of file IDs (the new name for chatbotFileIds;
this field takes precedence when both are provided) (Optional)
          string (uuid)
        ]
        "faqIds"?: [ // List of FAQ IDs (excluded or exclusively selected depending on
hasUserSelectedAll) (Optional)
          string (uuid)
        ]
        "hasUserSelectedAll"?: boolean // true selects all knowledge base content except
the listed items; false selects only the listed items (Optional)
      }
    ]
    "labelRelations"?: { // Label filter criteria; an empty conditions array disables
label filtering (it does not deny access). Must be provided with knowledgeBases; when
provided alone, knowledge base retrieval does not apply label filtering (no restriction)
(Optional)
    {
      "operator": string (enum: AND, OR) // How label conditions are combined
      "conditions"?: [ // List of label conditions, supporting nested
operator/conditions combinations (Optional)
        object
      ]
    }
    }
  }
  }
  "toolMask"?: object // Enabled/disabled state per tool: {tool_id: bool} (Optional)
  "connectorMask"?: object // Enabled/disabled state per connector: {connector_id: bool}
(Optional)
  "thinkingConfig"?: object // None = not set (inherit the chatbot setting); otherwise
{"reasoning_effort": <level>} (Optional)
  "thinkingConfigSchema": { // Thinking configuration form for this model; null means
the model has no thinking configuration
  {
    "type"?: string // Form type, always reasoning_effort (Optional)
```

```
    "fields"?: object // reasoning_effort field: options lists the thinking levels
accepted by this model (from lowest to highest); default is always null (Optional)
    "canDisable"?: boolean // Whether thinking can be disabled for this model; when
true, options includes off (Optional)
    "unsetBehavior"?: string (enum: off, model_default) // Actual behavior when neither
the conversation nor the assistant has a thinking level set: off disables thinking
(fastest); model_default lets the model decide or enables thinking through the platform
default level (Optional)
    "unsetLevel"?: string // Level actually sent by the platform when no level is set;
null omits the thinking parameter and uses the model default (Optional)
  }
  }
  "effectiveThinkingConfig": object // The level the next reply sends on this
conversation's model, after gating and clamping.

The stored choice resolves conversation > chatbot > the LLM row's default level; None
means
the model sends no thinking parameter, so the provider default applies.
  "llm": string (uuid) // The model the next reply runs on: the conversation's pin, else
its assistant's current model.

TC-0205: returning the stored ``conversation.llm`` would show a model an unpinned
conversation no
longer uses once its assistant switches model, while ``thinking_config_schema`` already
follows the
effective model. Read-only: displaying it never marks the conversation as explicitly
selected;
only the update-llm endpoint does.
  "deepResearchStatus":  // Status of deep research for this conversation

* `not_used` - Not Used
* `started` - Started
* `running` - Running
* `completed` - Completed
* `failed` - Failed
  {
  }
  "deepResearchOutputFormat": // May have different types
  string (enum: canvas, chat, file) // Chosen delivery form for the finished report. Set
only when the user clicks a format in the pre-research choice card; reset to NULL each
time Deep Research is (re-)armed. NULL means no explicit choice (or a plan-skipping
request) and falls back to Canvas at render time, but stays distinct from an explicit
canvas pick so the frontend can lock the card only after a real selection. To roll back
to fixed-Canvas behavior, force this to NULL/canvas — no redeploy needed.

* `canvas` - Canvas
* `chat` - Chat reply
* `file` - Downloadable file
  "ipAddress": string
  "ipCountryCode": string
  "ipRecordedAt": string (timestamp)
  "assignee":
  {
```

```
    "id": string (uuid)
    "name": string
    "userId": string (uuid)
  }
  "status"?: string (enum: open, resolved, queued) // * `open` - Open
* `resolved` - Resolved
* `queued` - Queued (Optional)
  "tags": [
    {
      "id": string (uuid)
      "name": string
      "memberIds"?: [ // Optional
        string (uuid)
      ]
    }
  ]
  "progressStatus": string
  "firstResponseAt"?: string (timestamp) // Optional
  "queuedAt"?: string (timestamp) // Optional
  "assignedAt"?: string (timestamp) // Optional
  "transferReason"?: string // Optional
  "satisfactionScore": integer // Conversation satisfaction rating on a 5-point scale
(1=very dissatisfied, 5=very satisfied)
  "satisfactionComment": string
  "satisfactionSubmittedAt": string (timestamp)
  "latestAnalysisSummary": string // The conversation's current analysis summary (its
active summary revision).

Reads the `latest_analysis_summary` annotation added by `setup_eager_loading`
to avoid an N+1 query. All read paths (list / retrieve / create) eager-load,
so the annotation is present; it falls back to '' only for instances built
outside `setup_eager_loading`.
  "clientPlatform":  // Client platform that created this conversation (web, desktop)

* `web` - Web
* `desktop` - Desktop
  {
  }
  "workingDirectory": string // Absolute path of the local folder bound to a desktop
conversation. Only set for desktop conversations; null for web conversations.
  "slideProjectId": string
  "matchedField": string // Cached per instance: ``get_matched_message_id`` /
``get_matched_snippet``
both read this, so resolving it once avoids recomputing the keyword and
title-match logic three times per serialized conversation.
  "matchedSnippet": string // Keyword-centred excerpt of the matched message, with
ellipses.

Reads the ``matched_message_content`` annotation added by
``ConversationViewSet._annotate_keyword_match``; no extra query.
  "matchedMessageId": string
  "pinnedAt": string (timestamp) // When the conversation was pinned. Null means
unpinned.
```

```
  "folder": string (uuid) // The user-defined sidebar folder this conversation is
grouped into. Null means unclassified (shown under the time groups). Deleting the folder
resets this to null without deleting the conversation.
  "hasActiveBrowserSession": boolean // Whether a browser_use session snapshot exists to
resume.

Lets the frontend know it should proactively re-request the browser
panel (emit ``browser:start``) after a page reload, instead of only
ever showing the panel when a live ``browser:frame`` push happens to
arrive first.
  "callerOrganizationId": string // Bound caller organization (stamped at conversation
start); null when unbound
  "handoff": object // Handoff information: enabled is the platform switch; the
continuing conversation includes source_conversation_id/source_title; the original
conversation being handed off includes continued_to_conversation_id/continued_to_title
and latest_summary_message_id
  "displayContextUsage": boolean // Whether to show the context usage percentage bar (a
conversation platform switch, always true for MaiGPT; independent of the handoff switch)
  "autoSplitReason": string // Reason this conversation was created by automatic
splitting: resolved (after resolution) or idle; null if not created by splitting
  "continuedFrom": object // Conversation from which this split conversation continues:
{id, last_message_at, deleted}; if the old conversation has been deleted, id=null and
deleted=true
  "continuedTo": object // Latest conversation split from this conversation: {id,
created_at}; null if none
  "continuationSummary": object // Continuation summary: {state:
disabled|pending|ready|not_applied, items: [{conversation_id, content, generated_at,
last_message_at, old_status}]} (items ordered newest to oldest); null if not created by
splitting
  "conversationKind": string // chat = a chat with an agent; secretary = the member's
personal secretary Work chat
}
```

Example Response Values

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "contact": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Response string",
    "avatar": "Response string",
    "email": "response@example.com",
    "phoneNumber": "Response string",
    "metadata": null,
    "sourceId": "Response string",
    "tags": [
      {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "name": "Response string"
      }
    ]
```

```
  },
  "inbox": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Response string",
    "channelType": "line",
    "unreadConversationsCount": 456,
    "signAuth": {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "signSource": "550e8400-e29b-41d4-a716-446655440000",
      "signParams": {
        "keycloak": {
          "clientId": "Response string",
          "url": "Response string",
          "realm": "Response string"
        },
        "line": {
          "liffId": "Response string"
        },
        "ad": {
          "saml": "Response string"
        },
        "google": {
          "enabled": false
        }
      },
      "sourceIdAccessEnabled": false,
      "sourceIdVerifyMode": {},
      "sourceIdSignatureTtlMinutes": {},
      "keycloakTokenPassthrough": false,
      "keycloakTokenPassthroughAllowedHosts": [
        "Response string"
      ],
      "organizationLogin": {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "name": "Example response name",
        "description": "Example response description"
      }
    },
    "enableAnalysis": false
  },
  "chatbot": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Example response name",
    "description": "Example response description"
  },
  "title": "Response string",
  "lastMessage": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "type": "Response string",
    "content": "Response string",
    "createdAt": "Response string"
  },
  "callRecord": {
```

```
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "status": "initiated",
    "direction": "inbound",
    "isActive": false,
    "canHangup": false
  },
  "lastMessageCreatedAt": "Response string",
  "unreadMessagesCount": 456,
  "autoReplyEnabled": false,
  "isAutoReplyNow": false,
  "willAiReplyNow": false,
  "lastReadAt": "Response string",
  "createdAt": "Response string",
  "isGroupChat": false,
  "enableGroupMention": false,
  "queryMetadata": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Example response name",
    "description": "Example response description"
  },
  "toolMask": null,
  "connectorMask": null,
  "thinkingConfig": null,
  "thinkingConfigSchema": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Example response name",
    "description": "Example response description"
  },
  "effectiveThinkingConfig": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Example response name",
    "description": "Example response description"
  },
  "llm": "550e8400-e29b-41d4-a716-446655440000",
  "deepResearchStatus": {},
  "deepResearchOutputFormat": "canvas",
  "ipAddress": "Response string",
  "ipCountryCode": "Response string",
  "ipRecordedAt": "Response string",
  "assignee": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Response string",
    "userId": "550e8400-e29b-41d4-a716-446655440000"
  },
  "status": "open",
  "tags": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "Response string",
      "memberIds": [
        "550e8400-e29b-41d4-a716-446655440000"
      ]
    }
```

```
  ],
  "progressStatus": "Response string",
  "firstResponseAt": "Response string",
  "queuedAt": "Response string",
  "assignedAt": "Response string",
  "transferReason": "Response string",
  "satisfactionScore": 456,
  "satisfactionComment": "Response string",
  "satisfactionSubmittedAt": "Response string",
  "latestAnalysisSummary": "Response string",
  "clientPlatform": {},
  "workingDirectory": "Response string",
  "slideProjectId": "Response string",
  "matchedField": "Response string",
  "matchedSnippet": "Response string",
  "matchedMessageId": "Response string",
  "pinnedAt": "Response string",
  "folder": "550e8400-e29b-41d4-a716-446655440000",
  "hasActiveBrowserSession": false,
  "callerOrganizationId": "Response string",
  "handoff": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Example response name",
    "description": "Example response description"
  },
  "displayContextUsage": false,
  "autoSplitReason": "Response string",
  "continuedFrom": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Example response name",
    "description": "Example response description"
  },
  "continuedTo": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Example response name",
    "description": "Example response description"
  },
  "continuationSummary": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Example response name",
    "description": "Example response description"
  },
  "conversationKind": "Response string"
}
```


Status Code: 4XX - Error response; X-Error-Code carries its code (see "Error codes").

Return to AI Replies

PATCH `/api/v1/conversations/{id}/return-to-ai/`

Clear the assigned member and resume automatic AI replies. Sends a handoff.returned_to_ai Webhook event on completion.

Parameters

Parameter Name	Required	Type	Description
`id`	V	string	A UUID string identifying this Conversation.

Request Body

Request Parameters

Field	Type	Required	Description
requireContextReady	boolean	No	

Request Schema Example

```
{
  "requireContextReady"?: boolean // Optional
}
```

Example Request Values

```
{
  "requireContextReady": true
}
```

Code Examples

Shell/Bash

```
# API call example (Shell)
curl -X PATCH "https://api.maiagent.ai/api/v1/conversations/550e8400-e29b-41d4-
a716-446655440000/return-to-ai/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "requireContextReady": true
  }'

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Configure request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// Request body (payload)
const data = {
    "requireContextReady": true
  };

axios.patch("https://api.maiagent.ai/api/v1/conversations/550e8400-e29b-41d4-a716-446655440000/return-to-ai/", data, config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request failed:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/conversations/550e8400-e29b-41d4-a716-
446655440000/return-to-ai/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# Request Body (payload)
data = {
    "requireContextReady": True
}

response = requests.patch(url, json=data, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request failed:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>patch("https://api.maiagent.ai/api/v1/conversations/550e8400-e29b-41d4-a716-
446655440000/return-to-ai/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'requireContextReady' => true
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request failed: ' . $e->getMessage();
}
?>
```

Response Body

Status Code: 200

Example Response Schema

```
{
  "id": string (uuid)
  "contact": { // Lightweight Contact Serializer for the Conversation List view

Includes only the fields required by the List view, omitting inboxes, mcp_credentials,
and api_credentials
to avoid N+1 queries. email / phone_number / metadata are scalar fields on Contact
```

```
itself,
displayed in the frontend conversation sidebar with no N+1 overhead.
  {
    "id": string (uuid)
    "name": string
    "avatar"?: string // Stores our own media as a relative storage key, or an external
CDN URL as-is. (Optional)
    "email"?: // May have different types (Optional)
    string (email) // Optional
    "phoneNumber"?: string // Optional
    "metadata"?: object // Custom customer information shown in the customer panel of
the conversation page (Optional)
    "sourceId"?: string // Optional
    "tags": [
      {
        "id": string (uuid)
        "name": string
      }
    ]
  }
  }
  "inbox": { // Inbox summary embedded in a conversation payload.

``unread_conversations_count`` stays here because it is part of the
documented REST conversation API. It is an org-wide denormalized
counter, so WS emit paths must run the payload through
:func:`strip_org_wide_unread_count` before broadcasting it to rooms
that include members without ``GroupInbox.can_view_conversations``.
  {
    "id": string (uuid)
    "name": string
    "channelType": string (enum: line, telegram, teams, web, messenger, instagram,
email, whatsapp, slack, team_plus, line_works, viber) // * `line` - LINE
* `telegram` - Telegram
* `teams` - Teams
* `web` - Web
* `messenger` - Messenger
* `instagram` - Instagram
* `email` - Email
* `whatsapp` - WhatsApp
* `slack` - Slack
* `team_plus` - Team+
* `line_works` - LINE WORKS
* `viber` - Viber
    "unreadConversationsCount"?: integer // Optional
    "signAuth"?:  // Optional
    {
      "id": string (uuid)
      "signSource": string (uuid)
      "signParams": {
      {
        "keycloak":
        {
```

```
          "clientId": string
          "url": string
          "realm": string
        }
        "line":
        {
          "liffId": string
        }
        "ad":
        {
          "saml": string
        }
        "google"?:  // Optional
        {
          "enabled": boolean
        }
      }
      }
      "sourceIdAccessEnabled"?: boolean // When enabled, embedded visitors presenting a
Source ID (verified per the verify mode below) may chat without going through the login
flow. Disabled keeps every existing behavior unchanged. (Optional)
      "sourceIdVerifyMode"?:  // "Require signature verification": the embedding site
must send an HMAC signature computed on its backend. "Source ID only": anyone knowing a
Source ID can act as that contact; suitable only for testing or closed networks.

* `signature` - Require signature verification
* `raw` - Source ID only (Optional)
      {
      }
      "sourceIdSignatureTtlMinutes"?:  // How long a signature can be used to obtain the
contact identity. Not a session lifetime: once exchanged, the session follows the
existing WebChat mechanism.

* `1` - 1
* `5` - 5
* `15` - 15 (Optional)
      {
      }
      "keycloakTokenPassthrough"?: boolean // When enabled, the Keycloak access token a
visitor logged in with is forwarded as the Authorization header when the AI calls MCP
and API tools on their behalf, so tools do not require a separate per-tool login. Only
for the Keycloak sign source. Never overrides an Authorization header a tool already
resolves from its own credentials. The visitor identity is the organization member bound
to the conversation at login, never the contact Source ID. (Optional)
      "keycloakTokenPassthroughAllowedHosts"?: [ // Hostnames (or "*.example.com"
wildcards) of the tools the visitor Keycloak token may be sent to (Optional)
        string
      ]
      "organizationLogin": object // How visitors sign in when the sign source is
"organization" (mirrors the back-office login); null for other sign sources
    }
    "enableAnalysis"?: boolean // Optional
  }
```

```
  }
  "chatbot": object // Chatbot (Agent) summary from the conversation's inbox, already
eager-loaded.

``is_maigpt`` lets the client tell the default MaiGPT agent apart (icon, feature
gate) without comparing against the organization's ``maigpt_inbox`` id;
``file_workspace_mode`` is the effective P6 mode (MaiGPT, blueprint and the
organization's file-library switch already applied).
  "title": string
  "lastMessage"?: { // Optional
  {
    "id": string (uuid)
    "type"?: string // Optional
    "content"?: string // Optional
    "createdAt": string (timestamp)
  }
  }
  "callRecord":
  {
    "id": string (uuid)
    "status"?: string (enum: initiated, ringing, in-progress, completed, failed, busy,
no-answer, canceled) // * `initiated` - Initiated
* `ringing` - Ringing
* `in-progress` - In Progress
* `completed` - Completed
* `failed` - Failed
* `busy` - Busy
* `no-answer` - No Answer
* `canceled` - Canceled (Optional)
    "direction": string (enum: inbound, outbound) // * `inbound` - Inbound
* `outbound` - Outbound
    "isActive": boolean
    "canHangup": boolean
  }
  "lastMessageCreatedAt": string (timestamp)
  "unreadMessagesCount": integer
  "autoReplyEnabled": boolean
  "isAutoReplyNow": boolean
  "willAiReplyNow": boolean // Whether a text message arriving through the inbox gets an
AI reply right now.

The messaging channels are gated by ``is_auto_reply_now`` (auto reply on and inside the
inbox auto-reply schedule) and by the inbox having a chatbot. The chatbot's API web chat
is answered by the completions endpoint, which ignores the schedule, so there the
conversation switch alone decides. The channel is only looked up for a web inbox outside
its schedule.

Surfaces that ignore the schedule on any inbox answer from their own rule instead: the
completions endpoint continuing an existing conversation
(``completions_progress_status``)
and voice turns, which the voice agent answers.
  "lastReadAt": string (timestamp)
  "createdAt": string (timestamp)
```

```
  "isGroupChat": boolean
  "enableGroupMention"?: boolean // Optional
  "queryMetadata"?: { // Query metadata that controls the scope of searchable knowledge; see each endpoint's documentation (Optional)
  {
    "knowledgeBases"?: [ // List of searchable knowledge bases; an empty array or null denies access to all, while omission imposes no restriction (Optional)
      {
        "knowledgeBaseId": string (uuid) // Knowledge base ID
        "chatbotFileIds"?: [ // List of file IDs (excluded or exclusively selected, depending on hasUserSelectedAll) (Optional)
          string (uuid)
        ]
        "knowledgeBaseFileIds"?: [ // List of file IDs (the new name for chatbotFileIds; this field takes precedence when both are provided) (Optional)
          string (uuid)
        ]
        "faqIds"?: [ // List of FAQ IDs (excluded or exclusively selected, depending on hasUserSelectedAll) (Optional)
          string (uuid)
        ]
        "hasUserSelectedAll"?: boolean // true selects all knowledge base content except the listed items; false selects only the listed items (Optional)
      }
    ]
    "labelRelations"?: { // Tag filters; an empty conditions array applies no tag filtering (it does not deny access). Must be provided together with knowledgeBases; when provided alone, knowledge base retrieval does not apply tag filtering (equivalent to no restriction) (Optional)
    {
      "operator": string (enum: AND, OR) // How tag conditions are combined
      "conditions"?: [ // List of tag conditions; supports nested operator/conditions combinations (Optional)
        object
      ]
    }
    }
  }
  }
  "toolMask"?: object // Enabled/disabled state per tool: {tool_id: bool} (Optional)
  "connectorMask"?: object // Enabled/disabled state per connector: {connector_id: bool} (Optional)
  "thinkingConfig"?: object // None = not set (inherit the chatbot setting); otherwise {"reasoning_effort": <level>} (Optional)
  "thinkingConfigSchema": { // Thinking configuration form for this model; null means the model has no thinking configuration
  {
    "type"?: string // Form type, always reasoning_effort (Optional)
    "fields"?: object // reasoning_effort field: options lists the thinking levels this model accepts (from lowest to highest); default is always null (Optional)
    "canDisable"?: boolean // Whether thinking can be disabled for this model; when true, options includes off (Optional)
    "unsetBehavior"?: string (enum: off, model_default) // Actual behavior when neither
```

```
the conversation nor the assistant has a thinking level set: off disables thinking
(fastest); model_default lets the model decide, or enables thinking at the platform's
default level (Optional)
    "unsetLevel"?: string // Level the platform actually sends when no level is set;
null omits the thinking parameter and uses the model's own default (Optional)
  }
  }
  "effectiveThinkingConfig": object // The level the next reply sends on this
conversation's model, after gating and clamping.

The stored choice resolves conversation > chatbot > the LLM row's default level; None
means
the model sends no thinking parameter, so the provider default applies.
  "llm": string (uuid) // The model the next reply runs on: the conversation's pin, else
its assistant's current model.

TC-0205: returning the stored ``conversation.llm`` would show a model an unpinned
conversation no
longer uses once its assistant switches model, while ``thinking_config_schema`` already
follows the
effective model. Read-only: displaying it never marks the conversation as explicitly
selected;
only the update-llm endpoint does.
  "deepResearchStatus":  // Status of deep research for this conversation

* `not_used` - Not Used
* `started` - Started
* `running` - Running
* `completed` - Completed
* `failed` - Failed
  {
  }
  "deepResearchOutputFormat": // May have different types
  string (enum: canvas, chat, file) // Chosen delivery form for the finished report. Set
only when the user clicks a format in the pre-research choice card; reset to NULL each
time Deep Research is (re-)armed. NULL means no explicit choice (or a plan-skipping
request) and falls back to Canvas at render time, but stays distinct from an explicit
canvas pick so the frontend can lock the card only after a real selection. To roll back
to fixed-Canvas behavior, force this to NULL/canvas — no redeploy needed.

* `canvas` - Canvas
* `chat` - Chat reply
* `file` - Downloadable file
  "ipAddress": string
  "ipCountryCode": string
  "ipRecordedAt": string (timestamp)
  "assignee":
  {
    "id": string (uuid)
    "name": string
    "userId": string (uuid)
  }
  "status"?: string (enum: open, resolved, queued) // * `open` - Open
```

```
* `resolved` - Resolved
* `queued` - Queued (Optional)
  "tags": [
    {
      "id": string (uuid)
      "name": string
      "memberIds"?: [ // Optional
        string (uuid)
      ]
    }
  ]
  "progressStatus": string
  "firstResponseAt"?: string (timestamp) // Optional
  "queuedAt"?: string (timestamp) // Optional
  "assignedAt"?: string (timestamp) // Optional
  "transferReason"?: string // Optional
  "satisfactionScore": integer // Conversation satisfaction rating on a 5-point scale
(1=very dissatisfied, 5=very satisfied)
  "satisfactionComment": string
  "satisfactionSubmittedAt": string (timestamp)
  "latestAnalysisSummary": string // The conversation's current analysis summary (its
active summary revision).

Reads the `latest_analysis_summary` annotation added by `setup_eager_loading`
to avoid an N+1 query. All read paths (list / retrieve / create) eager-load,
so the annotation is present; it falls back to '' only for instances built
outside `setup_eager_loading`.
  "clientPlatform":  // Client platform that created this conversation (web, desktop)

* `web` - Web
* `desktop` - Desktop
  {
  }
  "workingDirectory": string // Absolute path of the local folder bound to a desktop
conversation. Only set for desktop conversations; null for web conversations.
  "slideProjectId": string
  "matchedField": string // Cached per instance: ``get_matched_message_id`` /
``get_matched_snippet``
both read this, so resolving it once avoids recomputing the keyword and
title-match logic three times per serialized conversation.
  "matchedSnippet": string // Keyword-centred excerpt of the matched message, with
ellipses.

Reads the ``matched_message_content`` annotation added by
``ConversationViewSet._annotate_keyword_match``; no extra query.
  "matchedMessageId": string
  "pinnedAt": string (timestamp) // When the conversation was pinned. Null means
unpinned.
  "folder": string (uuid) // The user-defined sidebar folder this conversation is
grouped into. Null means unclassified (shown under the time groups). Deleting the folder
resets this to null without deleting the conversation.
  "hasActiveBrowserSession": boolean // Whether a browser_use session snapshot exists to
resume.
```

```
Lets the frontend know it should proactively re-request the browser
panel (emit ``browser:start``) after a page reload, instead of only
ever showing the panel when a live ``browser:frame`` push happens to
arrive first.
  "callerOrganizationId": string // Bound caller organization (stamped at conversation
start); null when unbound
  "handoff": object // Handoff information: enabled is the platform toggle; the
continuing conversation includes source_conversation_id/source_title; the original
conversation being handed off includes continued_to_conversation_id/continued_to_title
and latest_summary_message_id
  "displayContextUsage": boolean // Whether to show the context usage percentage bar
(conversation platform toggle; always true for MaiGPT; independent of the handoff
toggle)
  "autoSplitReason": string // Reason this conversation was created by automatic
splitting: resolved (after resolution) / idle (inactivity); null if not created by
splitting
  "continuedFrom": object // Conversation from which this split conversation continues:
{id, last_message_at, deleted}; if the old conversation was deleted, id=null and
deleted=true
  "continuedTo": object // Latest conversation split from this conversation: {id,
created_at}; null if none
  "continuationSummary": object // Continuation summary: {state:
disabled|pending|ready|not_applied, items: [{conversation_id, content, generated_at,
last_message_at, old_status}]} (items ordered newest to oldest); null if not created by
splitting
  "conversationKind": string // chat = a chat with an agent; secretary = the member's
personal secretary Work chat
}
```

Example Response Value


```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "contact": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Response string",
    "avatar": "Response string",
    "email": "response@example.com",
    "phoneNumber": "Response string",
    "metadata": null,
    "sourceId": "Response string",
    "tags": [
      {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "name": "Response string"
      }
    ]
  },
  "inbox": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
```

```
    "name": "Response string",
    "channelType": "line",
    "unreadConversationsCount": 456,
    "signAuth": {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "signSource": "550e8400-e29b-41d4-a716-446655440000",
      "signParams": {
        "keycloak": {
          "clientId": "Response string",
          "url": "Response string",
          "realm": "Response string"
        },
        "line": {
          "liffId": "Response string"
        },
        "ad": {
          "saml": "Response string"
        },
        "google": {
          "enabled": false
        }
      },
      "sourceIdAccessEnabled": false,
      "sourceIdVerifyMode": {},
      "sourceIdSignatureTtlMinutes": {},
      "keycloakTokenPassthrough": false,
      "keycloakTokenPassthroughAllowedHosts": [
        "Response string"
      ],
      "organizationLogin": {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "name": "Example response name",
        "description": "Example response description"
      }
    },
    "enableAnalysis": false
  },
  "chatbot": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Example response name",
    "description": "Example response description"
  },
  "title": "Response string",
  "lastMessage": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "type": "Response string",
    "content": "Response string",
    "createdAt": "Response string"
  },
  "callRecord": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "status": "initiated",
    "direction": "inbound",
```

```
    "isActive": false,
    "canHangup": false
  },
  "lastMessageCreatedAt": "Response string",
  "unreadMessagesCount": 456,
  "autoReplyEnabled": false,
  "isAutoReplyNow": false,
  "willAiReplyNow": false,
  "lastReadAt": "Response string",
  "createdAt": "Response string",
  "isGroupChat": false,
  "enableGroupMention": false,
  "queryMetadata": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Example response name",
    "description": "Example response description"
  },
  "toolMask": null,
  "connectorMask": null,
  "thinkingConfig": null,
  "thinkingConfigSchema": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Example response name",
    "description": "Example response description"
  },
  "effectiveThinkingConfig": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Example response name",
    "description": "Example response description"
  },
  "llm": "550e8400-e29b-41d4-a716-446655440000",
  "deepResearchStatus": {},
  "deepResearchOutputFormat": "canvas",
  "ipAddress": "Response string",
  "ipCountryCode": "Response string",
  "ipRecordedAt": "Response string",
  "assignee": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Response string",
    "userId": "550e8400-e29b-41d4-a716-446655440000"
  },
  "status": "open",
  "tags": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "Response string",
      "memberIds": [
        "550e8400-e29b-41d4-a716-446655440000"
      ]
    }
  ],
  "progressStatus": "Response string",
  "firstResponseAt": "Response string",
```

```
  "queuedAt": "Response string",
  "assignedAt": "Response string",
  "transferReason": "Response string",
  "satisfactionScore": 456,
  "satisfactionComment": "Response string",
  "satisfactionSubmittedAt": "Response string",
  "latestAnalysisSummary": "Response string",
  "clientPlatform": {},
  "workingDirectory": "Response string",
  "slideProjectId": "Response string",
  "matchedField": "Response string",
  "matchedSnippet": "Response string",
  "matchedMessageId": "Response string",
  "pinnedAt": "Response string",
  "folder": "550e8400-e29b-41d4-a716-446655440000",
  "hasActiveBrowserSession": false,
  "callerOrganizationId": "Response string",
  "handoff": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Example response name",
    "description": "Example response description"
  },
  "displayContextUsage": false,
  "autoSplitReason": "Response string",
  "continuedFrom": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Example response name",
    "description": "Example response description"
  },
  "continuedTo": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Example response name",
    "description": "Example response description"
  },
  "continuationSummary": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Example response name",
    "description": "Example response description"
  },
  "conversationKind": "Response string"
}
```


**Status Code: `409` - Agent context not ready: `detail` plus `agentContext` (pending
failed writes)**

List Conversation Output Files

GET `/api/v1/conversations/{conversationId}/outputs/`

For response fields (count, source, results[]), visibility, and sorting, see Conversation Outputs API in the technical manual.

Parameters

Parameter Name	Required	Type	Description
`conversationId`	V	string	

Code Examples

Shell/Bash

```
# API Call Example (Shell)
curl -X GET
"https://api.maiagent.ai/api/v1/conversations/{conversationId}/outputs/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/conversations/{conversationId}/outputs/",
config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request failed:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/conversations/{conversationId}/outputs/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request failed:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/conversations/{conversationId}/outputs/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request failed: ' . $e->getMessage();
}
?>
```

Response Body

Status Code	Description
200	No response body
4XX	Error response; X-Error-Code carries its code (see "Error codes").

Share a Conversation

POST `/api/v1/conversations/{conversationPk}/share/`

Parameters

Parameter Name	Required	Type	Description
`conversationPk`	V	string	

Request Body

Request Parameters

Field	Type	Required	Description
shareScope	string (enum: organization, group, member)	Yes	`organization` : Organization ; `group` : Group ; `member` : Member;
permission	object	No	
title	string	No	
description	string	No	
groupIds	array[string]	No	
memberIds	array[string]	No	

Example Request Schema

```
{
  "shareScope": string (enum: organization, group, member) // * `organization` -
Organization
* `group` - Group
* `member` - Member
  "permission"?:  // Optional
  {
  }
  "title"?: string // Optional
  "description"?: string // Optional
  "groupIds"?: [ // Optional
    string (uuid)
  ]
  "memberIds"?: [ // Optional
    string (uuid)
  ]
}
```

Example Request Values

```
{
  "shareScope": "organization",
  "permission": {},
  "title": "Example name",
  "description": "Example string",
  "groupIds": [
    "550e8400-e29b-41d4-a716-446655440000"
  ],
  "memberIds": [
    "550e8400-e29b-41d4-a716-446655440000"
  ]
}
```


Code Examples

Shell/Bash

```
# API call example (Shell)
curl -X POST "https://api.maiagent.ai/api/v1/conversations/{conversationPk}/share/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "shareScope": "organization",
    "permission": {},
    "title": "Example name",
    "description": "Example string",
    "groupIds": [
      "550e8400-e29b-41d4-a716-446655440000"
    ],
    "memberIds": [
      "550e8400-e29b-41d4-a716-446655440000"
    ]
  }'

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// Request Body (payload)
const data = {
    "shareScope": "organization",
    "permission": {},
    "title": "Example name",
    "description": "Example string",
    "groupIds": [
      "550e8400-e29b-41d4-a716-446655440000"
    ],
    "memberIds": [
      "550e8400-e29b-41d4-a716-446655440000"
    ]
  };

axios.post("https://api.maiagent.ai/api/v1/conversations/{conversationPk}/share/",
data, config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/conversations/{conversationPk}/share/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# Request Body (payload)
data = {
    "shareScope": "organization",
    "permission": {},
    "title": "Example name",
    "description": "Example string",
    "groupIds": [
        "550e8400-e29b-41d4-a716-446655440000"
    ],
    "memberIds": [
        "550e8400-e29b-41d4-a716-446655440000"
    ]
}

response = requests.post(url, json=data, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>post("https://api.maiagent.ai/api/v1/conversations/{conversationPk}/share/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'shareScope' => 'organization',
            'permission' => new \stdClass(),
            'title' => 'Example name',
            'description' => 'Example string',
            'groupIds' => [
                '550e8400-e29b-41d4-a716-446655440000'
            ],
            'memberIds' => [
                '550e8400-e29b-41d4-a716-446655440000'
            ]
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response Body

Status Code: 201

Example Response Schema

```
{
  "shareScope": string (enum: organization, group, member) // * `organization` -
Organization
* `group` - Group
* `member` - Member
  "permission"?:  // Optional
  {
  }
  "title"?: string // Optional
  "description"?: string // Optional
  "groupIds"?: [ // Optional
    string (uuid)
  ]
  "memberIds"?: [ // Optional
    string (uuid)
  ]
}
```

Example Response Values

```
{
  "shareScope": "organization",
  "permission": {},
  "title": "Response string",
  "description": "Response string",
  "groupIds": [
    "550e8400-e29b-41d4-a716-446655440000"
  ],
  "memberIds": [
    "550e8400-e29b-41d4-a716-446655440000"
  ]
}
```

Status Code: 4XX - Error response; X-Error-Code carries its code (see "Error codes").

Quick Share a Conversation

POST `/api/v1/conversations/{conversationPk}/share/quick/`

Parameters

Parameter Name	Required	Type	Description
`conversationPk`	V	string	

Request Body

Request Parameters

Field	Type	Required	Description
shareScope	string (enum: organization, group, member)	Yes	`organization` : Organization ; `group` : Group ; `member` : Member;
permission	object	No	
title	string	No	
description	string	No	
groupIds	array[string]	No	
memberIds	array[string]	No	

Example Request Schema

```
{
  "shareScope": string (enum: organization, group, member) // * `organization` -
Organization
* `group` - Group
* `member` - Member
  "permission"?:  // Optional
  {
  }
  "title"?: string // Optional
  "description"?: string // Optional
  "groupIds"?: [ // Optional
    string (uuid)
  ]
  "memberIds"?: [ // Optional
    string (uuid)
  ]
}
```

Example Request Values

```
{
  "shareScope": "organization",
  "permission": {},
```

```
  "title": "Example name",
  "description": "Example string",
  "groupIds": [
    "550e8400-e29b-41d4-a716-446655440000"
  ],
  "memberIds": [
    "550e8400-e29b-41d4-a716-446655440000"
  ]
}
```

Code Examples

Shell/Bash

```
# API call example (Shell)
curl -X POST
"https://api.maiagent.ai/api/v1/conversations/{conversationPk}/share/quick/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "shareScope": "organization",
    "permission": {},
    "title": "Example name",
    "description": "Example string",
    "groupIds": [
      "550e8400-e29b-41d4-a716-446655440000"
    ],
    "memberIds": [
      "550e8400-e29b-41d4-a716-446655440000"
    ]
  }'

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// Request Body (payload)
const data = {
    "shareScope": "organization",
    "permission": {},
    "title": "Example name",
    "description": "Example string",
    "groupIds": [
      "550e8400-e29b-41d4-a716-446655440000"
    ],
    "memberIds": [
      "550e8400-e29b-41d4-a716-446655440000"
    ]
  };

axios.post("https://api.maiagent.ai/api/v1/conversations/{conversationPk}/share/qui
ck/", data, config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/conversations/{conversationPk}/share/quick/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# Request Body (payload)
data = {
    "shareScope": "organization",
    "permission": {},
    "title": "Example name",
    "description": "Example string",
    "groupIds": [
        "550e8400-e29b-41d4-a716-446655440000"
    ],
    "memberIds": [
        "550e8400-e29b-41d4-a716-446655440000"
    ]
}

response = requests.post(url, json=data, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>post("https://api.maiagent.ai/api/v1/conversations/{conversationPk}/share/quick/",
[
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'shareScope' => 'organization',
            'permission' => new \stdClass(),
            'title' => 'Example name',
            'description' => 'Example string',
            'groupIds' => [
                '550e8400-e29b-41d4-a716-446655440000'
            ],
            'memberIds' => [
                '550e8400-e29b-41d4-a716-446655440000'
            ]
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response Body

Status Code: 200

Example Response Schema

```
{
  "shareScope": string (enum: organization, group, member) // * `organization` -
Organization
* `group` - Group
* `member` - Member
  "permission"?:  // Optional
  {
  }
  "title"?: string // Optional
  "description"?: string // Optional
  "groupIds"?: [ // Optional
    string (uuid)
  ]
  "memberIds"?: [ // Optional
    string (uuid)
  ]
}
```

Example Response Values

```
{
  "shareScope": "organization",
  "permission": {},
  "title": "Response string",
  "description": "Response string",
  "groupIds": [
    "550e8400-e29b-41d4-a716-446655440000"
  ],
  "memberIds": [
    "550e8400-e29b-41d4-a716-446655440000"
  ]
}
```

Status Code: 4XX - Error response; X-Error-Code carries its code (see "Error codes").

List Shared Conversations

GET `/api/v1/shared-conversations/`

Parameters

Parameter Name	Required	Type	Description
`page`	X	integer	A page number within the paginated result set.
`pageSize`	X	integer	Number of results to return per page.

Code Examples

Shell/Bash

```
# API call example (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/shared-conversations/?
page=1&pageSize=1"

  -H "Authorization: Api-Key YOUR_API_KEY"

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/shared-conversations/?page=1&pageSize=1",
config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/shared-conversations/?page=1&pageSize=1"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->get("https://api.maiagent.ai/api/v1/shared-conversations/?
page=1&pageSize=1", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response Body

Status Code: 200

Example Response Schema

```
{
  "count": integer
  "next"?: string (uri) // Optional
  "previous"?: string (uri) // Optional
  "results": [
    {
      "id": string (uuid)
      "title": string // Custom title for the shared conversation
      "description": string // Custom description for the shared conversation
      "shareScope":
      {
      }
```

```
      "permission":
      {
      }
      "sharedBy":
      {
        "id": string (uuid)
        "name": string
      }
      "isOwner": boolean
      "messageCount": integer // Messages the share shows; the view counts a whole page
at once (``context['message_counts']``).
      "createdAt": string (timestamp)
    }
  ]
}
```

Example Response Values

```
{
  "count": 123,
  "next": "http://api.example.org/accounts/?page=4",
  "previous": "http://api.example.org/accounts/?page=2",
  "results": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "title": "Response string",
      "description": "Response string",
      "shareScope": {},
      "permission": {},
      "sharedBy": {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "name": "Response string"
      },
      "isOwner": false,
      "messageCount": 456,
      "createdAt": "Response string"
    }
  ]
}
```

Retrieve a Shared Conversation

GET `/api/v1/shared-conversations/{id}`

Parameters

Parameter Name	Required	Type	Description
id	V	string	A UUID string identifying this Shared Conversation.

Code Examples

Shell/Bash

```
# API call example (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/shared-conversations/550e8400-e29b-
41d4-a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/shared-conversations/550e8400-e29b-41d4-a716-446655440000/", config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/shared-conversations/550e8400-e29b-41d4-a716-446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->get("https://api.maiagent.ai/api/v1/shared-
conversations/550e8400-e29b-41d4-a716-446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response Body

Status Code: 200

Example Response Schema

```
{
  "id": string (uuid)
  "title": string // Custom title for the shared conversation
  "description": string // Custom description for the shared conversation
  "shareScope":
  {
  }
  "permission":
  {
  }
  "sharedBy":
  {
```

```
    "id": string (uuid)
    "name": string
  }
  "isOwner": boolean
  "conversationId": string (uuid) // The original conversation, exposed only to the
sharer while the share still follows it ("continue").
  "groupIds": [ // Current recipients, for the sharer's settings dialog only.
    string (uuid)
  ]
  "memberIds": [ // Recipients that are still active members, so saving the dialog back
as-is stays valid.
    string (uuid)
  ]
  "needsContinueReminder": boolean // True when the sharer can continue the original
conversation and has not been warned yet.
  "createdAt": string (timestamp)
  "conversationSnapshot": object
}
```

Example Response Values

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "title": "Response string",
  "description": "Response string",
  "shareScope": {},
  "permission": {},
  "sharedBy": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Response string"
  },
  "isOwner": false,
  "conversationId": "550e8400-e29b-41d4-a716-446655440000",
  "groupIds": [
    "550e8400-e29b-41d4-a716-446655440000"
  ],
  "memberIds": [
    "550e8400-e29b-41d4-a716-446655440000"
  ],
  "needsContinueReminder": false,
  "createdAt": "Response string",
  "conversationSnapshot": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Example response name",
    "description": "Example response description"
  }
}
```

Update a Shared Conversation

PATCH `/api/v1/shared-conversations/{id}`

Parameters

Parameter Name	Required	Type	Description
`id`	V	string	A UUID string identifying this Shared Conversation.

Request Body

Request Parameters

Field	Type	Required	Description
title	string	No	
description	string	No	
permission	string (enum: readonly, copy)	No	`readonly` : Read Only ; `copy` : Copyable;
shareScope	string (enum: organization, group, member)	No	`organization` : Organization ; `group` : Group ; `member` : Member;
groupIds	array[string]	No	
memberIds	array[string]	No	

Example Request Schema

```
{
  "title"?: string // Optional
  "description"?: string // Optional
  "permission"?: string (enum: readonly, copy) // * `readonly` - Read Only
* `copy` - Copyable (Optional)
  "shareScope"?: string (enum: organization, group, member) // * `organization` -
Organization
* `group` - Group
* `member` - Member (Optional)
  "groupIds"?: [ // Optional
    string (uuid)
  ]
```

```
  "memberIds"?: [ // Optional
    string (uuid)
  ]
}
```

Example Request Values

```
{
  "title": "Example name",
  "description": "Example string",
  "permission": "readonly",
  "shareScope": "organization",
  "groupIds": [
    "550e8400-e29b-41d4-a716-446655440000"
  ],
  "memberIds": [
    "550e8400-e29b-41d4-a716-446655440000"
  ]
}
```

Code Examples

Shell/Bash

```
# API call example (Shell)
curl -X PATCH "https://api.maiagent.ai/api/v1/shared-conversations/550e8400-e29b-
41d4-a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "title": "Example name",
    "description": "Example string",
    "permission": "readonly",
    "shareScope": "organization",
    "groupIds": [
      "550e8400-e29b-41d4-a716-446655440000"
    ],
    "memberIds": [
      "550e8400-e29b-41d4-a716-446655440000"
    ]
  }'

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// Request body (payload)
const data = {
    "title": "Example name",
    "description": "Example string",
    "permission": "readonly",
    "shareScope": "organization",
    "groupIds": [
      "550e8400-e29b-41d4-a716-446655440000"
    ],
    "memberIds": [
      "550e8400-e29b-41d4-a716-446655440000"
    ]
  };

axios.patch("https://api.maiagent.ai/api/v1/shared-conversations/550e8400-e29b-
41d4-a716-446655440000/", data, config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request failed:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/shared-conversations/550e8400-e29b-41d4-a716-446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# Request body (payload)
data = {
    "title": "Example name",
    "description": "Example string",
    "permission": "readonly",
    "shareScope": "organization",
    "groupIds": [
        "550e8400-e29b-41d4-a716-446655440000"
    ],
    "memberIds": [
        "550e8400-e29b-41d4-a716-446655440000"
    ]
}

response = requests.patch(url, json=data, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request failed:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->patch("https://api.maiagent.ai/api/v1/shared-
conversations/550e8400-e29b-41d4-a716-446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'title' => 'Example name',
            'description' => 'Example string',
            'permission' => 'readonly',
            'shareScope' => 'organization',
            'groupIds' => [
                '550e8400-e29b-41d4-a716-446655440000'
            ],
            'memberIds' => [
                '550e8400-e29b-41d4-a716-446655440000'
            ]
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request failed: ' . $e->getMessage();
}
?>
```

Response Body

Status code: 200

Example Response Schema

```
{
  "title"?: string // Optional
  "description"?: string // Optional
  "permission"?: string (enum: readonly, copy) // * `readonly` - Read Only
* `copy` - Copyable (Optional)
  "shareScope"?: string (enum: organization, group, member) // * `organization` -
Organization
* `group` - Group
* `member` - Member (Optional)
  "groupIds"?: [ // Optional
    string (uuid)
  ]
  "memberIds"?: [ // Optional
    string (uuid)
  ]
}
```

Example Response Values

```
{
  "title": "Response string",
  "description": "Response string",
  "permission": "readonly",
  "shareScope": "organization",
  "groupIds": [
    "550e8400-e29b-41d4-a716-446655440000"
  ],
  "memberIds": [
    "550e8400-e29b-41d4-a716-446655440000"
  ]
}
```

Delete a Shared Conversation

DELETE `/api/v1/shared-conversations/{id}`

Parameters

Parameter Name	Required	Type	Description

id	V	string	A UUID string identifying this Shared Conversation.

Code Examples

Shell/Bash

```
# Example API Call (Shell)
curl -X DELETE "https://api.maiagent.ai/api/v1/shared-conversations/550e8400-e29b-
41d4-a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

// Request body (payload)
const data = null;

axios.delete("https://api.maiagent.ai/api/v1/shared-conversations/550e8400-e29b-41d4-a716-446655440000/", data, config)
  .then(response => {
    console.log('Response retrieved successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/shared-conversations/550e8400-e29b-41d4-a716-446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.delete(url, headers=headers)
try:
    print("Response retrieved successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->delete("https://api.maiagent.ai/api/v1/shared-
conversations/550e8400-e29b-41d4-a716-446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response retrieved successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response Body

Status Code	Description
204	No response body

Fork a Shared Conversation

POST `/api/v1/shared-conversations/{id}/fork/`

Parameters

Parameter Name	Required	Type	Description
id	V	string	A UUID string identifying this Shared Conversation.

Code Examples

Shell/Bash

```
# API Call Example (Shell)
curl -X POST "https://api.maiagent.ai/api/v1/shared-conversations/550e8400-e29b-
41d4-a716-446655440000/fork/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{}'

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// Request body (payload)
const data = {};

axios.post("https://api.maiagent.ai/api/v1/shared-conversations/550e8400-e29b-41d4-a716-446655440000/fork/", data, config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/shared-conversations/550e8400-e29b-41d4-a716-446655440000/fork/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# Request body (payload)
data = {}

response = requests.post(url, json=data, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->post("https://api.maiagent.ai/api/v1/shared-
conversations/550e8400-e29b-41d4-a716-446655440000/fork/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => new \stdClass()
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response Body

Status Code: 200

Example Response Schema

```
{
  "id": string (uuid)
  "title": string // Custom title for the shared conversation
  "description": string // Custom description for the shared conversation
  "shareScope":
  {
  }
  "permission":
  {
  }
```

```
  "sharedBy":
  {
    "id": string (uuid)
    "name": string
  }
  "isOwner": boolean
  "conversationId": string (uuid) // The original conversation, exposed only to the
sharer while the share still follows it ("continue").
  "groupIds": [ // Current recipients, for the sharer's settings dialog only.
    string (uuid)
  ]
  "memberIds": [ // Recipients that are still active members, so saving the dialog back
as-is stays valid.
    string (uuid)
  ]
  "needsContinueReminder": boolean // True when the sharer can continue the original
conversation and has not been warned yet.
  "createdAt": string (timestamp)
  "conversationSnapshot": object
}
```

Example Response Values

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "title": "Response string",
  "description": "Response string",
  "shareScope": {},
  "permission": {},
  "sharedBy": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Response string"
  },
  "isOwner": false,
  "conversationId": "550e8400-e29b-41d4-a716-446655440000",
  "groupIds": [
    "550e8400-e29b-41d4-a716-446655440000"
  ],
  "memberIds": [
    "550e8400-e29b-41d4-a716-446655440000"
  ],
  "needsContinueReminder": false,
  "createdAt": "Response string",
  "conversationSnapshot": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Example response name",
    "description": "Example response description"
  }
}
```

Retrieve My Shared Conversations

GET `/api/v1/shared-conversations/my-shares/`

Code Examples

Shell/Bash

```
# API Call Example (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/shared-conversations/my-shares/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/shared-conversations/my-shares/", config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/shared-conversations/my-shares/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->get("https://api.maiagent.ai/api/v1/shared-
conversations/my-shares/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response Body

Status Code: 200

Example Response Schema

```
{
  "id": string (uuid)
  "title": string // Custom title for the shared conversation
  "description": string // Custom description for the shared conversation
  "shareScope":
  {
  }
  "permission":
  {
  }
  "sharedBy":
  {
```

```
    "id": string (uuid)
    "name": string
  }
  "isOwner": boolean
  "messageCount": integer // Messages the share shows; the view counts a whole page at
once (``context['message_counts']``).
  "createdAt": string (timestamp)
}
```

Example Response Values

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "title": "Response string",
  "description": "Response string",
  "shareScope": {},
  "permission": {},
  "sharedBy": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Response string"
  },
  "isOwner": false,
  "messageCount": 456,
  "createdAt": "Response string"
}
```

Create Message Feedback

POST `/api/v1/messages/{messagePk}/feedback/`

Parameters

Parameter Name	Required	Type	Description
`messagePk`	V	string	

Request Body

Request Parameters

Field	Type	Required	Description
type	object	Yes	
suggestion	string	No	

Example Request Schema

```
{
  "type":
  {
  }
  "suggestion"?: string // Optional
}
```

Example Request Values

```
{
  "type": {},
  "suggestion": "example string"
}
```

Code Examples

Shell/Bash

```
# API call example (Shell)
curl -X POST "https://api.maiagent.ai/api/v1/messages/{messagePk}/feedback/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "type": {},
    "suggestion": "example string"
  }'

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// Request body (payload)
const data = {
    "type": {},
    "suggestion": "example string"
  };

axios.post("https://api.maiagent.ai/api/v1/messages/{messagePk}/feedback/", data,
config)
  .then(response => {
    console.log('Response retrieved successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/messages/{messagePk}/feedback/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# Request body (payload)
data = {
    "type": {},
    "suggestion": "example string"
}

response = requests.post(url, json=data, headers=headers)
try:
    print("Response retrieved successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>post("https://api.maiagent.ai/api/v1/messages/{messagePk}/feedback/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'type' => new \stdClass(),
            'suggestion' => 'example string'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response retrieved successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response Body

Status Code: 201

Example Response Schema

```
{
  "id": string (uuid)
  "type":
  {
  }
  "suggestion"?: string // Optional
```

```
  "updatedAt": string (timestamp)
}
```

Example Response Values

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "type": {},
  "suggestion": "response string",
  "updatedAt": "response string"
}
```

Status Code: 400 - This message already has feedback. Use PATCH to update it.

Update Message Feedback

PUT `/api/v1/messages/{messagePk}/feedback/{id}`

Parameters

Parameter Name	Required	Type	Description
`id`	V	string	A UUID string identifying this Message Feedback.
`messagePk`	V	string	

Request Body

Request Parameters

Field	Type	Required	Description
type	object	Yes	
suggestion	string	No	

Example Request Schema

```
{
  "type":
  {
  }
  "suggestion"?: string // Optional
}
```

Example Request Values

```
{
  "type": {},
  "suggestion": "example string"
}
```

Code Examples

Shell/Bash

```
# API call example (Shell)
curl -X PUT "https://api.maiagent.ai/api/v1/messages/{messagePk}/feedback/550e8400-
e29b-41d4-a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "type": {},
    "suggestion": "example string"
  }'

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// Request body (payload)
const data = {
    "type": {},
    "suggestion": "example string"
  };

axios.put("https://api.maiagent.ai/api/v1/messages/{messagePk}/feedback/550e8400-
e29b-41d4-a716-446655440000/", data, config)
  .then(response => {
    console.log('Response retrieved successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/messages/{messagePk}/feedback/550e8400-e29b-41d4-a716-446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# Request body (payload)
data = {
    "type": {},
    "suggestion": "example string"
}

response = requests.put(url, json=data, headers=headers)
try:
    print("Response retrieved successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>put("https://api.maiagent.ai/api/v1/messages/{messagePk}/feedback/550e8400-e29b-
41d4-a716-446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'type' => new \stdClass(),
            'suggestion' => 'example string'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response retrieved successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response Body

Status Code: 200

Example Response Schema

```
{
  "id": string (uuid)
  "type":
  {
  }
  "suggestion"?: string // Optional
```

```
  "updatedAt": string (timestamp)
}
```

Example Response Values

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "type": {},
  "suggestion": "response string",
  "updatedAt": "response string"
}
```

Delete Message Feedback

DELETE `/api/v1/messages/{messagePk}/feedback/{id}`

Parameters

Parameter Name	Required	Type	Description
`id`	V	string	A UUID string identifying this Message Feedback.
`messagePk`	V	string	

Code Examples

Shell/Bash

```shell
# API call example (Shell)
curl -X DELETE
"https://api.maiagent.ai/api/v1/messages/{messagePk}/feedback/550e8400-e29b-41d4-
a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```javascript
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

// Request body (payload)
const data = null;

axios.delete("https://api.maiagent.ai/api/v1/messages/{messagePk}/feedback/550e8400
-e29b-41d4-a716-446655440000/", data, config)
  .then(response => {
    console.log('Response retrieved successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/messages/{messagePk}/feedback/550e8400-e29b-41d4-a716-446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.delete(url, headers=headers)
try:
    print("Response retrieved successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>delete("https://api.maiagent.ai/api/v1/messages/{messagePk}/feedback/550e8400-
e29b-41d4-a716-446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response retrieved successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response Body

Status Code	Description
204	Feedback deleted successfully
400	This feedback does not belong to the specified message

List conversation records

GET `/api/v1/records/`

Parameters

Parameter name	Required	Type	Description
`callerMember`	X	array	Multiple values may be separated by commas.
`chatbot`	X	string	Filter by a specific AI assistant (UUID)
`endDate`	X	string	End date (format: YYYY-MM-DD, e.g., 2025-01-31)
`endDatetime`	X	string	
`errorType`	X	array	Multiple values may be separated by commas. `system`: System ; `llm`: LLM ; `embedding`: Embedding ; `reranker`: Reranker ; `vector_db`: Vector DB ; `workflow`: Workflow ; `tool`: Tool ; `timeout`: Ti...
`excludeBuiltIn`	X	boolean	When true, excludes data from official built-in Agents (locked instances created by renting from the Agent marketplace), retaining only assistants created by the organization. Copies created with "Copy as custom" count as custom assistants. Omitting this parameter or setting it to false leaves the results unfiltered by this condition.
`feedbackType`	X	array	Multiple values may be separated by commas. `like`: Like ; `dislike`: Dislike;
`hasError`	X	boolean	
`hasFeedback`	X	boolean	
`keyword`	X	string	Keyword search (searches both user messages and bot replies)
`largeLanguageModel`	X	string	Filter by a specific large language model (UUID)
`page`	X	integer	A page number within the paginated result set.
`pageSize`	X	integer	Number of results to return per page.
`source`	X	string	Filter by record source, separated by commas. Returns both sources when omitted. interactive = user conversations, scheduled = scheduled executions.
`startDate`	X	string	Start date (format: YYYY-MM-DD, e.g., 2025-01-01)
`startDatetime`	X	string	

`tool`	X	string	

Code examples

Shell/Bash

```
# API call example (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/records/?
callerMember=example&chatbot=example&endDate=example&endDatetime=2025-01-
01T00:00:00.000Z&errorType=example&excludeBuiltIn=true&feedbackType=example&hasErro
r=true&hasFeedback=true&keyword=example&largeLanguageModel=example&page=1&pageSize=
1&source=interactive&startDate=example&startDatetime=2025-01-
01T00:00:00.000Z&tool=example"

  -H "Authorization: Api-Key YOUR_API_KEY"

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/records/?
callerMember=example&chatbot=example&endDate=example&endDatetime=2025-01-
01T00:00:00.000Z&errorType=example&excludeBuiltIn=true&feedbackType=example&hasErro
r=true&hasFeedback=true&keyword=example&largeLanguageModel=example&page=1&pageSize=
1&source=interactive&startDate=example&startDatetime=2025-01-
01T00:00:00.000Z&tool=example", config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/records/?
callerMember=example&chatbot=example&endDate=example&endDatetime=2025-01-
01T00:00:00.000Z&errorType=example&excludeBuiltIn=true&feedbackType=example&hasErro
r=true&hasFeedback=true&keyword=example&largeLanguageModel=example&page=1&pageSize=
1&source=interactive&startDate=example&startDatetime=2025-01-
01T00:00:00.000Z&tool=example"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->get("https://api.maiagent.ai/api/v1/records/?
callerMember=example&chatbot=example&endDate=example&endDatetime=2025-01-
01T00:00:00.000Z&errorType=example&excludeBuiltIn=true&feedbackType=example&hasErro
r=true&hasFeedback=true&keyword=example&largeLanguageModel=example&page=1&pageSize=
1&source=interactive&startDate=example&startDatetime=2025-01-
01T00:00:00.000Z&tool=example", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response

Status code: 200

Example response schema

```
{
  "count": integer
  "next"?: string (uri) // Optional
  "previous"?: string (uri) // Optional
  "results": [
    {
      "id": string (uuid)
      "senderName": string // Returns the name of the user message sender
```

```
      "callerMemberId": string
      "callerMemberName": string
      "feedback":
      {
        "id": string (uuid)
        "type":
        {
        }
        "suggestion"?: string // Optional
        "updatedAt": string (timestamp)
      }
      "inputMessage": string
      "condenseMessage": string // User message rewritten from the chat history and
context.
      "outputMessage": string
      "faithfulnessScore": number (double) // Whether the chatbot reply is grounded in
the knowledge base rather than made up.
      "displayFaithfulnessScore": integer
      "answerRelevancyScore": number (double) // Whether the chatbot reply is relevant
to the user's question.
      "displayAnswerRelevancyScore": integer
      "contextPrecisionScore": number (double) // Whether the chatbot reply is relevant
to the reference context.
      "displayContextPrecisionScore": integer
      "answerCorrectnessScore": number (double) // Whether the chatbot reply is correct
(requires a ground-truth answer).
      "displayAnswerCorrectnessScore": integer
      "answerSimilarityScore": number (double) // Whether the chatbot reply is similar
to the ground-truth answer.
      "displayAnswerSimilarityScore": integer
      "contextRecallScore": number (double) // Whether the chatbot reply recalls the
relevant information from the reference context.
      "displayContextRecallScore": integer
      "replyTime": string
      "createdAt": string (timestamp)
      "error": string // Error message raised during execution.
      "errorType": // May have different types
      string (enum: system, llm, embedding, reranker, vector_db, workflow, tool,
timeout, client_interrupt, hook_blocked, evaluation, other) // Error source: system,
LLM, embedding, reranker, and so on.

* `system` - System
* `llm` - LLM
* `embedding` - Embedding
* `reranker` - Reranker
* `vector_db` - Vector DB
* `workflow` - Workflow
* `tool` - Tool
* `timeout` - Timeout
* `client_interrupt` - Client Interrupt
* `hook_blocked` - Hook Blocked
* `evaluation` - Evaluation
* `other` - Other
```

```
      "processingTime": object // Returns timing statistics for each processing stage,
including the streaming_metrics waterfall
      "usage":
      {
        "words":  // Word counts
        {
          "input": integer // User message word count (including the word equivalent
calculated from the number of images)
          "output": integer // AI assistant reply word count (including the word
equivalent calculated from the number of images)
          "total": integer // Sum of input and output
        }
        "tokens":  // token usage
        {
          "llm":  // LLM token usage
          {
            "input": integer // Number of LLM input tokens
            "output": integer // Number of LLM output tokens
            "cacheCreationInputTokens": integer // Number of input tokens written to the
prompt cache
            "cacheReadInputTokens": integer // Number of input tokens read from the
prompt cache
            "total": integer // Sum of input, output, and both cache token counts
          }
          "embedding": integer // Number of text embedding tokens
          "embeddingImage": integer // Number of image embedding tokens
          "reranker": integer // Number of chunks sent to the reranker
        }
        "llmCallBreakdown": [ // Token breakdown for each LLM call, ordered by call
time; always an empty array on list endpoints. Use the detail endpoint instead
          {
            "sequence": integer // Sequence number of the LLM call within this reply,
starting at 1
            "inputTokens": integer // Number of input tokens for this call
            "outputTokens": integer // Number of output tokens for this call
            "cacheCreationInputTokens": integer // Number of tokens written to the
prompt cache by this call
            "cacheReadInputTokens": integer // Number of tokens read from the prompt
cache by this call
            "processingTimeSecs": number (double) // Duration of this call in seconds;
null if not recorded
            "ttftSecs"?: number (double) // Time to first token for this call in
seconds; null if not recorded. Some older records omit this key (optional)
          }
        ]
      }
      "citationNodes": [
        {
          "id": string
          "text": string
          "chatbotFileId": string
          "fileName": string
          "url": string
```

```
        }
      ]
      "inputHookLogs": [
        {
          "id": string (uuid)
          "hook": string (uuid)
          "hookName": string
          "hookTypeLabel": string
          "hookAction": string
          "conversation": string (uuid)
          "message": string (uuid)
          "messageContent": string // Return the raw message text.
          "chatbotId": string
          "chatbotName": string
          "metadata": object
          "triggerPoint": string
          "createdAt": string (timestamp)
          "updatedAt": string (timestamp)
        }
      ]
      "outputHookLogs": [
        {
          "id": string (uuid)
          "hook": string (uuid)
          "hookName": string
          "hookTypeLabel": string
          "hookAction": string
          "conversation": string (uuid)
          "message": string (uuid)
          "messageContent": string // Return the raw message text.
          "chatbotId": string
          "chatbotName": string
          "metadata": object
          "triggerPoint": string
          "createdAt": string (timestamp)
          "updatedAt": string (timestamp)
        }
      ]
      "instructionId": string
      "llm":
      {
        "id": string (uuid)
        "name": string
      }
      "effectiveMaxLlmOutputTokens": integer // max_tokens actually used for this reply,
from Chatbot.custom_max_llm_output_tokens or LLM.max_tokens.
      "chatbot":
      {
        "id": string (uuid)
        "name": string
      }
      "context": string
      "conversationId": string (uuid)
```

```
      "inboxId": string (uuid)
      "botMessageId": string (uuid)
      "userMessageId": string (uuid)
      "creditCosts": [ // Credit deductions for this reply, grouped by billing item.
null if the organization does not use credit-based billing, or if it does but this reply
has no deduction transactions
        {
          "itemCode": string // Billing item code
          "itemName": string // Billing item name
          "category": string // Billing item category
          "credits": number (double) // Total credits deducted for this billing item in
this reply
          "quantity": number (double) // Total usage for this billing item (the unit
depends on the item, e.g., token count)
          "unitPrice": number (double) // Snapshot of the unit price at the time of
deduction; null if the unit price was not recorded
          "count": integer // Number of deduction transactions combined into this row
        }
      ]
      "cacheSavedCredits": number (double) // Net credits saved by prompt caching for
this reply; ``None`` outside credit mode.

Reuses the usage-statistics saving semantics (``compute_cache_saved_credits``)
on the reply's own billing batch, so the per-reply figure and the hourly
aggregate are defined by the same formula. The net value may be negative
(cache-creation premium exceeding read savings); the frontend hides
non-positive values by design.
      "trace": object // Return the round trace timeline for the detail view; ``None``
for legacy records.
      "llmRawRequest": object // Raw messages array sent to the LLM on the final round,
including system prompt and memory
      "source": string // Origin discriminator for the unified /records/ response.
      "schedule": object // Shape parity with scheduled rows, which link their owning
ChatbotSchedule here.
      "voiceOrigin": object // The voice session and turn that delegated this question
here, if it was a delegation.
    }
  ]
}
```

Example response values

```
{
  "count": 123,
  "next": "http://api.example.org/accounts/?page=4",
  "previous": "http://api.example.org/accounts/?page=2",
  "results": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "senderName": "Response string",
      "callerMemberId": "Response string",
```

```
  "callerMemberName": "Response string",
  "feedback": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "type": {},
    "suggestion": "Response string",
    "updatedAt": "Response string"
  },
  "inputMessage": "Response string",
  "condenseMessage": "Response string",
  "outputMessage": "Response string",
  "faithfulnessScore": 456,
  "displayFaithfulnessScore": 456,
  "answerRelevancyScore": 456,
  "displayAnswerRelevancyScore": 456,
  "contextPrecisionScore": 456,
  "displayContextPrecisionScore": 456,
  "answerCorrectnessScore": 456,
  "displayAnswerCorrectnessScore": 456,
  "answerSimilarityScore": 456,
  "displayAnswerSimilarityScore": 456,
  "contextRecallScore": 456,
  "displayContextRecallScore": 456,
  "replyTime": "Response string",
  "createdAt": "Response string",
  "error": "Response string",
  "errorType": "system",
  "processingTime": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Example response name",
    "description": "Example response description"
  },
  "usage": {
    "words": {
      "input": 456,
      "output": 456,
      "total": 456
    },
    "tokens": {
      "llm": {
        "input": 456,
        "output": 456,
        "cacheCreationInputTokens": 456,
        "cacheReadInputTokens": 456,
        "total": 456
      },
      "embedding": 456,
      "embeddingImage": 456,
      "reranker": 456
    },
    "llmCallBreakdown": [
      {
        "sequence": 456,
        "inputTokens": 456,
```

```
        "outputTokens": 456,
        "cacheCreationInputTokens": 456,
        "cacheReadInputTokens": 456,
        "processingTimeSecs": 456,
        "ttftSecs": 456
      }
    ]
  },
  "citationNodes": [
    {
      "id": "Response string",
      "text": "Response string",
      "chatbotFileId": "Response string",
      "fileName": "Response string",
      "url": "Response string"
    }
  ],
  "inputHookLogs": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "hook": "550e8400-e29b-41d4-a716-446655440000",
      "hookName": "Response string",
      "hookTypeLabel": "Response string",
      "hookAction": "Response string",
      "conversation": "550e8400-e29b-41d4-a716-446655440000",
      "message": "550e8400-e29b-41d4-a716-446655440000",
      "messageContent": "Response string",
      "chatbotId": "Response string",
      "chatbotName": "Response string",
      "metadata": null,
      "triggerPoint": "Response string",
      "createdAt": "Response string",
      "updatedAt": "Response string"
    }
  ],
  "outputHookLogs": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "hook": "550e8400-e29b-41d4-a716-446655440000",
      "hookName": "Response string",
      "hookTypeLabel": "Response string",
      "hookAction": "Response string",
      "conversation": "550e8400-e29b-41d4-a716-446655440000",
      "message": "550e8400-e29b-41d4-a716-446655440000",
      "messageContent": "Response string",
      "chatbotId": "Response string",
      "chatbotName": "Response string",
      "metadata": null,
      "triggerPoint": "Response string",
      "createdAt": "Response string",
      "updatedAt": "Response string"
    }
  ],
```

```
      "instructionId": "Response string",
      "llm": {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "name": "Response string"
      },
      "effectiveMaxLlmOutputTokens": 456,
      "chatbot": {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "name": "Response string"
      },
      "context": "Response string",
      "conversationId": "550e8400-e29b-41d4-a716-446655440000",
      "inboxId": "550e8400-e29b-41d4-a716-446655440000",
      "botMessageId": "550e8400-e29b-41d4-a716-446655440000",
      "userMessageId": "550e8400-e29b-41d4-a716-446655440000",
      "creditCosts": [
        {
          "itemCode": "Response string",
          "itemName": "Response string",
          "category": "Response string",
          "credits": 456,
          "quantity": 456,
          "unitPrice": 456,
          "count": 456
        }
      ],
      "cacheSavedCredits": 456,
      "trace": {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "name": "Example response name",
        "description": "Example response description"
      },
      "llmRawRequest": null,
      "source": "Response string",
      "schedule": {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "name": "Example response name",
        "description": "Example response description"
      },
      "voiceOrigin": {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "name": "Example response name",
        "description": "Example response description"
      }
    }
  ]
}
```

Retrieve a conversation record

`GET` `/api/v1/records/{id}`

Parameters

Parameter name	Required	Type	Description
`id`	V	string	A UUID string identifying this Chatbot Record.

Code examples

Shell/Bash

```
# API call example (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/records/550e8400-e29b-41d4-a716-
446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/records/550e8400-e29b-41d4-a716-
446655440000/", config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/records/550e8400-e29b-41d4-a716-
446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->get("https://api.maiagent.ai/api/v1/records/550e8400-e29b-
41d4-a716-446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response

Status code: 200

Example response schema

```
{
  "id": string (uuid)
  "senderName": string // Returns the name of the user message sender
  "callerMemberId": string
  "callerMemberName": string
  "feedback":
  {
    "id": string (uuid)
    "type":
    {
    }
    "suggestion"?: string // Optional
```

```
    "updatedAt": string (timestamp)
  }
  "inputMessage": string
  "condenseMessage": string // User message rewritten from the chat history and context.
  "outputMessage": string
  "faithfulnessScore": number (double) // Whether the chatbot reply is grounded in the
knowledge base rather than made up.
  "displayFaithfulnessScore": integer
  "answerRelevancyScore": number (double) // Whether the chatbot reply is relevant to
the user's question.
  "displayAnswerRelevancyScore": integer
  "contextPrecisionScore": number (double) // Whether the chatbot reply is relevant to
the reference context.
  "displayContextPrecisionScore": integer
  "answerCorrectnessScore": number (double) // Whether the chatbot reply is correct
(requires a ground-truth answer).
  "displayAnswerCorrectnessScore": integer
  "answerSimilarityScore": number (double) // Whether the chatbot reply is similar to
the ground-truth answer.
  "displayAnswerSimilarityScore": integer
  "contextRecallScore": number (double) // Whether the chatbot reply recalls the
relevant information from the reference context.
  "displayContextRecallScore": integer
  "replyTime": string
  "createdAt": string (timestamp)
  "error": string // Error message raised during execution.
  "errorType": // May have different types
  string (enum: system, llm, embedding, reranker, vector_db, workflow, tool, timeout,
client_interrupt, hook_blocked, evaluation, other) // Error source: system, LLM,
embedding, reranker, and so on.

* `system` - System
* `llm` - LLM
* `embedding` - Embedding
* `reranker` - Reranker
* `vector_db` - Vector DB
* `workflow` - Workflow
* `tool` - Tool
* `timeout` - Timeout
* `client_interrupt` - Client Interrupt
* `hook_blocked` - Hook Blocked
* `evaluation` - Evaluation
* `other` - Other
  "processingTime": object // Returns timing statistics for each processing stage,
including the streaming_metrics waterfall.
  "usage":
  {
    "words":  // Word counts
    {
      "input": integer // Word count of the user message (including image counts
converted to equivalent words)
      "output": integer // Word count of the AI assistant reply (including image counts
converted to equivalent words)
```

```
      "total": integer // Sum of input and output
    }
    "tokens":  // token usage
    {
      "llm":  // LLM token usage
      {
        "input": integer // Number of LLM input tokens
        "output": integer // Number of LLM output tokens
        "cacheCreationInputTokens": integer // Number of input tokens written to the
prompt cache
        "cacheReadInputTokens": integer // Number of input tokens read from the prompt
cache
        "total": integer // Sum of input, output, and both cache token counts
      }
      "embedding": integer // Number of text embedding tokens
      "embeddingImage": integer // Number of image embedding tokens
      "reranker": integer // Number of chunks sent to the reranker
    }
    "llmCallBreakdown": [ // Token breakdown for each LLM call, sorted by call time;
always an empty array on list endpoints. Use the detail endpoint instead.
      {
        "sequence": integer // LLM call sequence within this reply, starting at 1
        "inputTokens": integer // Number of input tokens for this call
        "outputTokens": integer // Number of output tokens for this call
        "cacheCreationInputTokens": integer // Number of tokens written to the prompt
cache for this call
        "cacheReadInputTokens": integer // Number of tokens read from the prompt cache
for this call
        "processingTimeSecs": number (double) // Duration of this call in seconds; null
if not recorded
        "ttftSecs"?: number (double) // Time to first token for this call in seconds;
null if not recorded. Some older records do not include this key. (Optional)
      }
    ]
  }
  "citationNodes": [
    {
      "id": string
      "text": string
      "chatbotFileId": string
      "fileName": string
      "url": string
    }
  ]
  "inputHookLogs": [
    {
      "id": string (uuid)
      "hook": string (uuid)
      "hookName": string
      "hookTypeLabel": string
      "hookAction": string
      "conversation": string (uuid)
      "message": string (uuid)
```

```
      "messageContent": string // Return the raw message text.
      "chatbotId": string
      "chatbotName": string
      "metadata": object
      "triggerPoint": string
      "createdAt": string (timestamp)
      "updatedAt": string (timestamp)
    }
  ]
  "outputHookLogs": [
    {
      "id": string (uuid)
      "hook": string (uuid)
      "hookName": string
      "hookTypeLabel": string
      "hookAction": string
      "conversation": string (uuid)
      "message": string (uuid)
      "messageContent": string // Return the raw message text.
      "chatbotId": string
      "chatbotName": string
      "metadata": object
      "triggerPoint": string
      "createdAt": string (timestamp)
      "updatedAt": string (timestamp)
    }
  ]
  "instructionId": string
  "llm":
  {
    "id": string (uuid)
    "name": string
  }
  "effectiveMaxLlmOutputTokens": integer // max_tokens actually used for this reply,
from Chatbot.custom_max_llm_output_tokens or LLM.max_tokens.
  "chatbot":
  {
    "id": string (uuid)
    "name": string
  }
  "context": string
  "conversationId": string (uuid)
  "inboxId": string (uuid)
  "botMessageId": string (uuid)
  "userMessageId": string (uuid)
  "creditCosts": [ // Credit deductions for this reply, grouped by billing item. Null if
the organization does not use credit-based billing, or if it does but this reply has no
deduction transactions.
    {
      "itemCode": string // Billing item code
      "itemName": string // Billing item name
      "category": string // Billing item category
      "credits": number (double) // Total credits deducted for this billing item in this
```

```
reply
      "quantity": number (double) // Total usage for this billing item (the unit depends
on the item, such as token count)
      "unitPrice": number (double) // Unit price snapshot at the time of deduction; null
if the unit price was not recorded
      "count": integer // Number of deduction transactions aggregated into this row
    }
  ]
  "cacheSavedCredits": number (double) // Net credits saved by prompt caching for this
reply; ``None`` outside credit mode.

Reuses the usage-statistics saving semantics (``compute_cache_saved_credits``)
on the reply's own billing batch, so the per-reply figure and the hourly
aggregate are defined by the same formula. The net value may be negative
(cache-creation premium exceeding read savings); the frontend hides
non-positive values by design.
  "trace": object // Return the round trace timeline for the detail view; ``None`` for
legacy records.
  "llmRawRequest": object // Raw messages array sent to the LLM on the final round,
including system prompt and memory
  "source": string // Origin discriminator for the unified /records/ response.
  "schedule": object // Shape parity with scheduled rows, which link their owning
ChatbotSchedule here.
  "voiceOrigin": object // The voice session and turn that delegated this question here,
if it was a delegation.
}
```

Example Response Values

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "senderName": "Response string",
  "callerMemberId": "Response string",
  "callerMemberName": "Response string",
  "feedback": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "type": {},
    "suggestion": "Response string",
    "updatedAt": "Response string"
  },
  "inputMessage": "Response string",
  "condenseMessage": "Response string",
  "outputMessage": "Response string",
  "faithfulnessScore": 456,
  "displayFaithfulnessScore": 456,
  "answerRelevancyScore": 456,
  "displayAnswerRelevancyScore": 456,
  "contextPrecisionScore": 456,
  "displayContextPrecisionScore": 456,
  "answerCorrectnessScore": 456,
  "displayAnswerCorrectnessScore": 456,
```

```
  "answerSimilarityScore": 456,
  "displayAnswerSimilarityScore": 456,
  "contextRecallScore": 456,
  "displayContextRecallScore": 456,
  "replyTime": "Response string",
  "createdAt": "Response string",
  "error": "Response string",
  "errorType": "system",
  "processingTime": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Example response name",
    "description": "Example response description"
  },
  "usage": {
    "words": {
      "input": 456,
      "output": 456,
      "total": 456
    },
    "tokens": {
      "llm": {
        "input": 456,
        "output": 456,
        "cacheCreationInputTokens": 456,
        "cacheReadInputTokens": 456,
        "total": 456
      },
      "embedding": 456,
      "embeddingImage": 456,
      "reranker": 456
    },
    "llmCallBreakdown": [
      {
        "sequence": 456,
        "inputTokens": 456,
        "outputTokens": 456,
        "cacheCreationInputTokens": 456,
        "cacheReadInputTokens": 456,
        "processingTimeSecs": 456,
        "ttftSecs": 456
      }
    ]
  },
  "citationNodes": [
    {
      "id": "Response string",
      "text": "Response string",
      "chatbotFileId": "Response string",
      "fileName": "Response string",
      "url": "Response string"
    }
  ],
  "inputHookLogs": [
```

```
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "hook": "550e8400-e29b-41d4-a716-446655440000",
      "hookName": "Response string",
      "hookTypeLabel": "Response string",
      "hookAction": "Response string",
      "conversation": "550e8400-e29b-41d4-a716-446655440000",
      "message": "550e8400-e29b-41d4-a716-446655440000",
      "messageContent": "Response string",
      "chatbotId": "Response string",
      "chatbotName": "Response string",
      "metadata": null,
      "triggerPoint": "Response string",
      "createdAt": "Response string",
      "updatedAt": "Response string"
    }
  ],
  "outputHookLogs": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "hook": "550e8400-e29b-41d4-a716-446655440000",
      "hookName": "Response string",
      "hookTypeLabel": "Response string",
      "hookAction": "Response string",
      "conversation": "550e8400-e29b-41d4-a716-446655440000",
      "message": "550e8400-e29b-41d4-a716-446655440000",
      "messageContent": "Response string",
      "chatbotId": "Response string",
      "chatbotName": "Response string",
      "metadata": null,
      "triggerPoint": "Response string",
      "createdAt": "Response string",
      "updatedAt": "Response string"
    }
  ],
  "instructionId": "Response string",
  "llm": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Response string"
  },
  "effectiveMaxLlmOutputTokens": 456,
  "chatbot": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Response string"
  },
  "context": "Response string",
  "conversationId": "550e8400-e29b-41d4-a716-446655440000",
  "inboxId": "550e8400-e29b-41d4-a716-446655440000",
  "botMessageId": "550e8400-e29b-41d4-a716-446655440000",
  "userMessageId": "550e8400-e29b-41d4-a716-446655440000",
  "creditCosts": [
    {
      "itemCode": "Response string",
```

```
      "itemName": "Response string",
      "category": "Response string",
      "credits": 456,
      "quantity": 456,
      "unitPrice": 456,
      "count": 456
    }
  ],
  "cacheSavedCredits": 456,
  "trace": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Example response name",
    "description": "Example response description"
  },
  "llmRawRequest": null,
  "source": "Response string",
  "schedule": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Example response name",
    "description": "Example response description"
  },
  "voiceOrigin": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Example response name",
    "description": "Example response description"
  }
}
```


Status Code: 404 - The specified conversation record was not found

Create a Conversation Record Export Request

`POST` `/api/v1/records/export-excel-requests/`

Request Body

Request Parameters

Field	Type	Required	Description
chatbot	string	No	Specify the Chatbot UUIDs to export. Multiple UUIDs can be separated by commas. Leave blank to export all Chatbots you have permission to access in the organization.

Field	Type	Required	Description
chatbotId	string (uuid)	No	Specify the Chatbot UUID to export (an alias for chatbot; supports a single UUID only).
keyword	string	No	Filter conversation records by keyword (searches user messages and bot replies).
largeLanguageModel	string	No	Specify the large language model UUIDs to export. Multiple UUIDs can be separated by commas.
startDate	string (date)	No	Start date (YYYY-MM-DD), inclusive.
endDate	string (date)	No	End date (YYYY-MM-DD), inclusive.
startDatetime	string (timestamp)	No	Exact start time (ISO 8601, inclusive), with the same semantics as the list drill-down filter.
endDatetime	string (timestamp)	No	Exact end time (ISO 8601, exclusive), with the same semantics as the list drill-down filter.
hasError	boolean	No	Filter records by whether they have errors (true includes only records with errors; false includes only records without errors).
errorType	string	No	Filter by error type. Supports multiple comma-separated values (OR logic), using the same allowed values as the conversation record list.
hasFeedback	boolean	No	Filter by whether user feedback exists (true includes only records with likes/dislikes; false includes only records without feedback).
feedbackType	string	No	Filter by user feedback type (like / dislike). Supports multiple comma-separated values (OR logic).
callerMember	string	No	Filter by the speaking member UUID. Supports multiple comma-separated values (OR logic).
tool	string (uuid)	No	Filter question-and-answer pairs that called this tool (tool UUID, including platform built-in tools; failed executions also count).
excludeBuiltIn	boolean	No	When true, excludes data from official built-in Agents (locked instances created by renting from the Agent Marketplace), keeping only assistants created by the organization. Copies made with “Copy as custom” count as organization-created assistants. Omitting this parameter or setting it to false applies no such filter.

Example Request Schema

```
{
  "chatbot"?: string // Specify the Chatbot UUIDs to export. Multiple UUIDs can be
```

```
separated by commas. Leave blank to export all Chatbots you have permission to access in
the organization. (Optional)
  "chatbotId"?: string (uuid) // Specify the Chatbot UUID to export (an alias for
chatbot; supports a single UUID only). (Optional)
  "keyword"?: string // Filter conversation records by keyword (searches user messages
and bot replies). (Optional)
  "largeLanguageModel"?: string // Specify the large language model UUIDs to export.
Multiple UUIDs can be separated by commas. (Optional)
  "startDate"?: string (date) // Start date (YYYY-MM-DD), inclusive. (Optional)
  "endDate"?: string (date) // End date (YYYY-MM-DD), inclusive. (Optional)
  "startDatetime"?: string (timestamp) // Exact start time (ISO 8601, inclusive), with
the same semantics as the list drill-down filter. (Optional)
  "endDatetime"?: string (timestamp) // Exact end time (ISO 8601, exclusive), with the
same semantics as the list drill-down filter. (Optional)
  "hasError"?: boolean // Filter records by whether they have errors (true includes only
records with errors; false includes only records without errors). (Optional)
  "errorType"?: string // Filter by error type. Supports multiple comma-separated values
(OR logic), using the same allowed values as the conversation record list. (Optional)
  "hasFeedback"?: boolean // Filter by whether user feedback exists (true includes only
records with likes/dislikes; false includes only records without feedback). (Optional)
  "feedbackType"?: string // Filter by user feedback type (like / dislike). Supports
multiple comma-separated values (OR logic). (Optional)
  "callerMember"?: string // Filter by the speaking member UUID. Supports multiple
comma-separated values (OR logic). (Optional)
  "tool"?: string (uuid) // Filter question-and-answer pairs that called this tool (tool
UUID, including platform built-in tools; failed executions also count). (Optional)
  "excludeBuiltIn"?: boolean // When true, excludes data from official built-in Agents
(locked instances created by renting from the Agent Marketplace), keeping only
assistants created by the organization. Copies made with “Copy as custom” count as
organization-created assistants. Omitting this parameter or setting it to false applies
no such filter. (Optional)
}
```

Example Request Values

```
{
  "chatbot": "Example string",
  "chatbotId": "550e8400-e29b-41d4-a716-446655440000",
  "keyword": "Example string",
  "largeLanguageModel": "Example string",
  "startDate": "Example string",
  "endDate": "Example string",
  "startDatetime": "Example string",
  "endDatetime": "Example string",
  "hasError": true,
  "errorType": "Example string",
  "hasFeedback": true,
  "feedbackType": "Example string",
  "callerMember": "Example string",
  "tool": "550e8400-e29b-41d4-a716-446655440000",
```

```
  "excludeBuiltIn": true
}
```

Code Examples

Shell/Bash

```
# API call example (Shell)
curl -X POST "https://api.maiagent.ai/api/v1/records/export-excel-requests/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "chatbot": "Example string",
    "chatbotId": "550e8400-e29b-41d4-a716-446655440000",
    "keyword": "Example string",
    "largeLanguageModel": "Example string",
    "startDate": "Example string",
    "endDate": "Example string",
    "startDatetime": "Example string",
    "endDatetime": "Example string",
    "hasError": true,
    "errorType": "Example string",
    "hasFeedback": true,
    "feedbackType": "Example string",
    "callerMember": "Example string",
    "tool": "550e8400-e29b-41d4-a716-446655440000",
    "excludeBuiltIn": true
  }'

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// Request Body (payload)
const data = {
    "chatbot": "Example string",
    "chatbotId": "550e8400-e29b-41d4-a716-446655440000",
    "keyword": "Example string",
    "largeLanguageModel": "Example string",
    "startDate": "Example string",
    "endDate": "Example string",
    "startDatetime": "Example string",
    "endDatetime": "Example string",
    "hasError": true,
    "errorType": "Example string",
    "hasFeedback": true,
    "feedbackType": "Example string",
    "callerMember": "Example string",
    "tool": "550e8400-e29b-41d4-a716-446655440000",
    "excludeBuiltIn": true
  };

axios.post("https://api.maiagent.ai/api/v1/records/export-excel-requests/", data,
config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request failed:');
    console.error(error.response?.data || error.message);
  });
```

Python

```python
import requests

url = "https://api.maiagent.ai/api/v1/records/export-excel-requests/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# Request Body (payload)
data = {
    "chatbot": "Example string",
    "chatbotId": "550e8400-e29b-41d4-a716-446655440000",
    "keyword": "Example string",
    "largeLanguageModel": "Example string",
    "startDate": "Example string",
    "endDate": "Example string",
    "startDatetime": "Example string",
    "endDatetime": "Example string",
    "hasError": True,
    "errorType": "Example string",
    "hasFeedback": True,
    "feedbackType": "Example string",
    "callerMember": "Example string",
    "tool": "550e8400-e29b-41d4-a716-446655440000",
    "excludeBuiltIn": True
}

response = requests.post(url, json=data, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request failed:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->post("https://api.maiagent.ai/api/v1/records/export-excel-requests/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'chatbot' => 'Example string',
            'chatbotId' => '550e8400-e29b-41d4-a716-446655440000',
            'keyword' => 'Example string',
            'largeLanguageModel' => 'Example string',
            'startDate' => 'Example string',
            'endDate' => 'Example string',
            'startDatetime' => 'Example string',
            'endDatetime' => 'Example string',
            'hasError' => true,
            'errorType' => 'Example string',
            'hasFeedback' => true,
            'feedbackType' => 'Example string',
            'callerMember' => 'Example string',
            'tool' => '550e8400-e29b-41d4-a716-446655440000',
            'excludeBuiltIn' => true
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request failed: ' . $e->getMessage();
}
?>
```

Response Body

Status Code: 201

Example Response Schema

```
{
  "id": string (uuid)
  "userEmail": string (email)
  "recordType":  // Which monitoring list this export was requested from. Text exports
read filter_params with the text record filters, voice exports with the voice session
filters.

* `text` - Text records
* `voice` - Voice sessions
  {
  }
  "chatbotId": string (uuid) // Specify the Chatbot to export (deprecated; use
chatbot_ids)
  "chatbotIds": object // List of Chatbot UUIDs to export; leave blank to export all
Chatbots you have permission to access in the organization
  "startDate": string (date) // Start date for exported records (inclusive)
  "endDate": string (date) // End date for exported records (inclusive)
  "status":
  {
  }
  "statusDisplay": string
  "fileUrl": string // Returns the file URL (valid permanently)
  "fileSize": integer // File size (bytes)
  "recordCount": integer // Total number of exported records
  "errorMessage": string
  "processingDurationSeconds": number (double) // Calculates the processing duration in
seconds
  "createdAt": string (timestamp)
  "startedAt": string (timestamp)
  "completedAt": string (timestamp)
}
```

Example Response Values

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "userEmail": "response@example.com",
  "recordType": {},
  "chatbotId": "550e8400-e29b-41d4-a716-446655440000",
  "chatbotIds": null,
  "startDate": "Response string",
  "endDate": "Response string",
```

```
  "status": {},
  "statusDisplay": "Response string",
  "fileUrl": "Response string",
  "fileSize": 456,
  "recordCount": 456,
  "errorMessage": "Response string",
  "processingDurationSeconds": 456,
  "createdAt": "Response string",
  "startedAt": "Response string",
  "completedAt": "Response string"
}
```


Get Conversation Record Export Status

GET `/api/v1/records/export-excel-requests/{exportId}`

Parameters

Parameter Name	Required	Type	Description
`exportId`	V	string	

Code Examples

Shell/Bash

```
# API call example (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/records/export-excel-
requests/{exportId}
"

  -H "Authorization: Api-Key YOUR_API_KEY"

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/records/export-excel-requests/{exportId}
", config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request failed:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/records/export-excel-requests/{exportId}
"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request failed:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->get("https://api.maiagent.ai/api/v1/records/export-excel-requests/{exportId}", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request failed: ' . $e->getMessage();
}
?>
```

Response Content

Status Code: 200

Example Response Structure

```
{
  "id": string (uuid)
  "senderName": string // Returns the name of the user who sent the message
  "callerMemberId": string
  "callerMemberName": string
  "inputMessage": string
  "outputMessage": string
  "chatbot":
  {
    "id": string (uuid)
    "name": string
```

```
  }
  "condenseMessage": string // User message rewritten from the chat history and context.
  "feedback":
  {
    "id": string (uuid)
    "type":
    {
    }
    "suggestion"?: string // Optional
    "updatedAt": string (timestamp)
  }
  "displayFaithfulnessScore": integer
  "displayAnswerRelevancyScore": integer
  "displayContextPrecisionScore": integer
  "displayAnswerCorrectnessScore": integer
  "displayAnswerSimilarityScore": integer
  "displayContextRecallScore": integer
  "replyTime": string
  "processingTime": object // Returns processing time statistics for the list view,
using the same calculation as the detail view but excluding the streaming_metrics
waterfall
  "usage":
  {
    "words":  // Word counts
    {
      "input": integer // User message word count (including the word equivalent
calculated from the number of images)
      "output": integer // AI assistant response word count (including the word
equivalent calculated from the number of images)
      "total": integer // Sum of input and output
    }
    "tokens":  // token usage
    {
      "llm":  // LLM token usage
      {
        "input": integer // LLM input token count
        "output": integer // LLM output token count
        "cacheCreationInputTokens": integer // Input token count for prompt cache writes
        "cacheReadInputTokens": integer // Input token count for prompt cache reads
        "total": integer // Sum of input, output, and both cache token counts
      }
      "embedding": integer // Text embedding token count
      "embeddingImage": integer // Image embedding token count
      "reranker": integer // Number of chunks sent to the reranker
    }
    "llmCallBreakdown": [ // Token breakdown for each LLM call, ordered by call time;
always an empty array on list endpoints. Use the detail endpoint instead
      {
        "sequence": integer // LLM call sequence number within this response, starting
at 1
        "inputTokens": integer // Input token count for this call
        "outputTokens": integer // Output token count for this call
        "cacheCreationInputTokens": integer // Token count written to the prompt cache
```

```
by this call
        "cacheReadInputTokens": integer // Token count read from the prompt cache by
this call
        "processingTimeSecs": number (double) // Call duration in seconds; null if not
recorded
        "ttftSecs"?: number (double) // Time to first token for this call in seconds;
null if not recorded. Some older records omit this key (Optional)
      }
    ]
  }
  "llm":
  {
    "id": string (uuid)
    "name": string
  }
  "createdAt": string (timestamp)
  "conversationId": string (uuid)
  "errorType": // May have different types
  string (enum: system, llm, embedding, reranker, vector_db, workflow, tool, timeout,
client_interrupt, hook_blocked, evaluation, other) // Error source: system, LLM,
embedding, reranker, and so on.

* `system` - System
* `llm` - LLM
* `embedding` - Embedding
* `reranker` - Reranker
* `vector_db` - Vector DB
* `workflow` - Workflow
* `tool` - Tool
* `timeout` - Timeout
* `client_interrupt` - Client Interrupt
* `hook_blocked` - Hook Blocked
* `evaluation` - Evaluation
* `other` - Other
  "creditCosts": [ // Credits deducted for this response, aggregated by billing item.
Null if the organization does not use credit-based billing, or if it does but this
response has no deduction transactions
    {
      "itemCode": string // Billing item code
      "itemName": string // Billing item name
      "category": string // Billing item category
      "credits": number (double) // Total credits deducted for this response under this
billing item
      "quantity": number (double) // Total usage for this billing item (the unit depends
on the item, such as token count)
      "unitPrice": number (double) // Unit price snapshot at the time of deduction; null
if no unit price was recorded
      "count": integer // Number of deduction transactions aggregated into this row
    }
  ]
  "source": string // Origin discriminator for the unified /records/ response.
  "schedule": object // Shape parity with scheduled rows, which link their owning
```

```
ChatbotSchedule here.
}
```

Example Response Values


```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "senderName": "Response string",
  "callerMemberId": "Response string",
  "callerMemberName": "Response string",
  "inputMessage": "Response string",
  "outputMessage": "Response string",
  "chatbot": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Response string"
  },
  "condenseMessage": "Response string",
  "feedback": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "type": {},
    "suggestion": "Response string",
    "updatedAt": "Response string"
  },
  "displayFaithfulnessScore": 456,
  "displayAnswerRelevancyScore": 456,
  "displayContextPrecisionScore": 456,
  "displayAnswerCorrectnessScore": 456,
  "displayAnswerSimilarityScore": 456,
  "displayContextRecallScore": 456,
  "replyTime": "Response string",
  "processingTime": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Example response name",
    "description": "Example response description"
  },
  "usage": {
    "words": {
      "input": 456,
      "output": 456,
      "total": 456
    },
    "tokens": {
      "llm": {
        "input": 456,
        "output": 456,
        "cacheCreationInputTokens": 456,
        "cacheReadInputTokens": 456,
        "total": 456
      },
      "embedding": 456,
      "embeddingImage": 456,
```

```
      "reranker": 456
    },
    "llmCallBreakdown": [
      {
        "sequence": 456,
        "inputTokens": 456,
        "outputTokens": 456,
        "cacheCreationInputTokens": 456,
        "cacheReadInputTokens": 456,
        "processingTimeSecs": 456,
        "ttftSecs": 456
      }
    ]
  },
  "llm": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Response string"
  },
  "createdAt": "Response string",
  "conversationId": "550e8400-e29b-41d4-a716-446655440000",
  "errorType": "system",
  "creditCosts": [
    {
      "itemCode": "Response string",
      "itemName": "Response string",
      "category": "Response string",
      "credits": 456,
      "quantity": 456,
      "unitPrice": 456,
      "count": 456
    }
  ],
  "source": "Response string",
  "schedule": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Example response name",
    "description": "Example response description"
  }
}
```

Example API call (Shell)

目錄

1. List Inboxes
2. Create an Inbox
3. Retrieve an Inbox
4. Update an Inbox
5. Partially Update Inbox
6. Delete a Conversation Platform
7. List Webhooks for an Inbox
8. Create a Webhook
9. Retrieve a Specific Webhook
10. Update a Webhook
11. Partially Update Webhook
12. Delete Webhook

Example API call (Shell)

An inbox is the unit to which conversations belong and where Webhooks are configured. Each inbox can have multiple Webhooks that send notifications to your system when a user message arrives (`incoming`) or an Agent replies (`outgoing`). Web Chat inboxes also have Web Chat endpoints. For configuration instructions and payload formats, see Webhook in the technical manual.

List Inboxes

`GET` `/api/v1/inboxes/`

Parameters

Parameter	Required	Type	Description
`accessType`	X	string	Filter by access type
`channelType`	X	string	Filter by channel type
`chatbot`	X	string	Filter by chatbot ID
`isActive`	X	boolean	Filter by active status
`ordering`	X	string	Which field to use when ordering the results.
`page`	X	integer	A page number within the paginated result set.
`pageSize`	X	integer	Number of results to return per page.
`pagination`	X	string	Whether to paginate (true/false). When set to false, returns a simplified data format
`query`	X	string	
`source`	X	string	`self_built`: self_built ; `built_in`: built_in ; `all`: all;

Code Examples

Shell/Bash

```
# Example API call (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/inboxes/?
accessType=example&channelType=example&chatbot=example&isActive=true&ordering=example&page=1&pageSize=
1&pagination=example&query=example&source=all"

  -H "Authorization: Api-Key YOUR_API_KEY"

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/inboxes/?
accessType=example&channelType=example&chatbot=example&isActive=true&ordering=example&page=1&pageSize=
1&pagination=example&query=example&source=all", config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/inboxes/?
accessType=example&channelType=example&chatbot=example&isActive=true&ordering=example&page=1&pageSize=
1&pagination=example&query=example&source=all"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->get("https://api.maiagent.ai/api/v1/inboxes/?
accessType=example&channelType=example&chatbot=example&isActive=true&ordering=example&page=1&pageSize=
1&pagination=example&query=example&source=all", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response Body

Status code: `200` - Inbox list

Example Response Schema

```
{
  "count": integer
  "next"?: string (uri) // Optional
  "previous"?: string (uri) // Optional
  "results": [
    {
      "id": string (uuid)
      "name": string
      "channelType": string (enum: line, telegram, teams, web, messenger, instagram, email, whatsapp, slack,
team_plus, line_works, viber) // * `line` - LINE
* `telegram` - Telegram
* `teams` - Teams
* `web` - Web
* `messenger` - Messenger
* `instagram` - Instagram
* `email` - Email
* `whatsapp` - WhatsApp
* `slack` - Slack
* `team_plus` - Team+
* `line_works` - LINE WORKS
* `viber` - Viber
      "unreadConversationsCount"?: integer // Optional
      "signAuth"?:  // Optional
      {
        "id": string (uuid)
        "signSource": string (uuid)
        "signParams": {
        {
          "keycloak":
          {
            "clientId": string
            "url": string
            "realm": string
          }
          "line":
          {
            "liffId": string
          }
          "ad":
          {
            "saml": string
          }
          "google"?:  // Optional
          {
            "enabled": boolean
          }
        }
        }
        "sourceIdAccessEnabled"?: boolean // When enabled, embedded visitors presenting a Source ID
(verified per the verify mode below) may chat without going through the login flow. Disabled keeps every
existing behavior unchanged. (Optional)
        "sourceIdVerifyMode"?:  // "Require signature verification": the embedding site must send an HMAC
signature computed on its backend. "Source ID only": anyone knowing a Source ID can act as that contact;
suitable only for testing or closed networks.

* `signature` - Require signature verification
* `raw` - Source ID only (Optional)
        {
```

```
        }
        "sourceIdSignatureTtlMinutes"?:  // How long a signature can be used to obtain the contact identity. Not a session lifetime: once exchanged, the session follows the existing WebChat mechanism.

* `1` - 1
* `5` - 5
* `15` - 15 (Optional)
        {
        }
        "keycloakTokenPassthrough"?: boolean // When enabled, the Keycloak access token a visitor logged in with is forwarded as the Authorization header when the AI calls MCP and API tools on their behalf, so tools do not require a separate per-tool login. Only for the Keycloak sign source. Never overrides an Authorization header a tool already resolves from its own credentials. The visitor identity is the organization member bound to the conversation at login, never the contact Source ID. (Optional)
        "keycloakTokenPassthroughAllowedHosts"?: [ // Hostnames (or "*.example.com" wildcards) of the tools the visitor Keycloak token may be sent to (Optional)
          string
        ]
        "organizationLogin": object // How visitors sign in when the sign source is "organization" (mirrors the back-office login); null for other sign sources
      }
      "enableAnalysis"?: boolean // Optional
    }
  ]
}
```

Example Response Values


```
{
  "count": 123,
  "next": "http://api.example.org/accounts/?page=4",
  "previous": "http://api.example.org/accounts/?page=2",
  "results": [
    {
      "id": "961dcaac-bd2e-44d3-9050-82596dbb3334",
      "chatbot": {
        "id": "80f3170d-eed7-4651-a8da-6b7e6bdbef8b",
        "name": "Customer Service Bot",
        "groups": [],
        "largeLanguageModel": {
          "id": "933aa8b3-cdf4-47a7-86d5-b5dc27fbb044",
          "name": "llm"
        },
        "embeddingModel": {
          "id": "aefcc4f9-917d-4a8a-bd36-d97e3b7cecfe",
          "name": "embedding",
          "icon": null,
          "isDefault": false
        },
        "rerankerModel": {
          "id": "86c2ddfd-0df9-47b9-8f3b-0c42e3347da3",
          "name": "rerank",
          "icon": null,
          "isDefault": true
        },
        "knowledgeBases": [],
        "tools": [],
        "agentMode": "normal",
        "replyMode": "normal",
        "updatedAt": "1739519493000",
        "enableEvaluation": false,
```

```
      "enableInlineCitations": false,
      "enableKnowledgeBaseRag": true,
      "enableAgenticTextToSql": true,
      "enableToolSearching": true,
      "numberOfRetrievedChunks": 12
    },
    "groups": [
      {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "name": "Administrators"
      }
    ],
    "channelType": "web",
    "channelTypeLabel": "Web",
    "name": "1345",
    "autoReplySchedules": [
      {
        "id": "2f4f6383-d8b5-4d88-b4a1-6d02d731f2a6",
        "weekday": 0,
        "isEnabled": true,
        "timeSlots": [
          [
            "00:00:00",
            "00:00:00"
          ]
        ],
        "weekdayName": "Monday"
      },
      {
        "id": "2866f624-a5c3-4ffb-b980-0f8d6a9f0c93",
        "weekday": 1,
        "isEnabled": true,
        "timeSlots": [
          [
            "00:00:00",
            "00:00:00"
          ]
        ],
        "weekdayName": "Tuesday"
      },
      {
        "id": "3cf1e488-fb13-426d-bd59-e62bd71aca85",
        "weekday": 2,
        "isEnabled": true,
        "timeSlots": [
          [
            "00:00:00",
            "00:00:00"
          ]
        ],
        "weekdayName": "Wednesday"
      },
      {
        "id": "491776a9-fcf1-4e2e-892f-6d9ad5aebea4",
        "weekday": 3,
        "isEnabled": true,
        "timeSlots": [
          [
            "00:00:00",
            "00:00:00"
          ]
        ],
        "weekdayName": "Thursday"
```

```
    },
    {
      "id": "dfecb0a9-5001-4aa0-b2cc-5459b6d64351",
      "weekday": 4,
      "isEnabled": true,
      "timeSlots": [
        [
          "00:00:00",
          "00:00:00"
        ]
      ],
      "weekdayName": "Friday"
    },
    {
      "id": "68b6b4d1-7ac8-450f-8877-41b72b499919",
      "weekday": 5,
      "isEnabled": true,
      "timeSlots": [
        [
          "00:00:00",
          "00:00:00"
        ]
      ],
      "weekdayName": "Saturday"
    },
    {
      "id": "15228ea1-4513-4504-81f4-4e486703d8b9",
      "weekday": 6,
      "isEnabled": true,
      "timeSlots": [
        [
          "00:00:00",
          "00:00:00"
        ]
      ],
      "weekdayName": "Sunday"
    }
  ],
  "unreadConversationsCount": 0,
  "totalConversationsCount": 42,
  "channel": {
    "id": "801a690a-1038-4fdd-8aba-bf003b12c3ef",
    "name": "1345",
    "avatar": "https://media-dev.maiagent.ai/static/images/default-chatbot-avatar.png",
    "logo": null,
    "description": "",
    "cover": null,
    "backUrl": "",
    "isActive": true,
    "enableSpeech": false,
    "displayGreeting": null,
    "displayConversationStarters": [],
    "theme": {
      "primaryColor": "#3854d8",
      "navbarTextColor": "#ffffff",
      "conversationBackgroundColor": "#ffffff",
      "chatbotMessageTextColor": "#374151",
      "userMessageTextColor": "#374151",
      "chatbotMessageBackgroundColor": "#DCE9F6",
      "userMessageBackgroundColor": "#DDEAF6",
      "chatbotMessageBackgroundShadowEnabled": true,
      "userMessageBackgroundShadowEnabled": true
    },
```

```
      "darkTheme": {
        "primaryColor": "#404040",
        "navbarTextColor": "#ffffff",
        "conversationBackgroundColor": "#18181B",
        "chatbotMessageTextColor": "#ffffff",
        "userMessageTextColor": "#ffffff",
        "chatbotMessageBackgroundColor": "#171717",
        "userMessageBackgroundColor": "#333842",
        "chatbotMessageBackgroundShadowEnabled": false,
        "userMessageBackgroundShadowEnabled": false
      },
      "enableFileUpload": true,
      "enableDisplayCitations": true,
      "enableShareConversation": false,
      "enableLocation": false,
      "enableShowPoweredBy": true,
      "enableDisplayChatbotAvatar": true,
      "enableDisplayChatbotName": true,
      "enableDisplayPreviousConversation": true,
      "enableDisplayConversationHistory": true,
      "enableConversationTimer": false,
      "conversationTimerDuration": null,
      "enableAutoNewConversationOnTimeout": false,
      "accessType": "api",
      "greetings": [],
      "greetingsByLocale": {
        "en": [
          "Hello, how can I help you?"
        ],
        "zh-hant": [
          "你好，我可以幫你什麼嗎？"
        ],
        "ja": [
          "こんにちは、何かお手伝いできますか？"
        ],
        "ko": [
          "안녕하세요, 무엇을 도와드릴까요?"
        ]
      },
      "conversationStarters": [],
      "conversationStartersByLocale": {
        "en": [
          "What can I help you with today?"
        ],
        "zh-hant": [
          "你今天需要什麼幫助？"
        ],
        "ja": [
          "今日は何かお手伝いできますか？"
        ],
        "ko": [
          "오늘 뭘 도와줄수있어？"
        ]
      }
    },
    "webhooks": [],
    "createdAt": "1739519493000",
    "updatedAt": "1739519493000",
    "organization": "24b619d9-e981-4a8b-96da-63dc4f96bda6",
    "signAuth": null
  }
```

```
  ]
}
```

Create an Inbox

`POST` `/api/v1/inboxes/`

Request Body

Request Parameters

Field	Type	Required	Description
name	string	Yes	
channelType	string (enum: line, telegram, teams, web, messenger, instagram, email, whatsapp, slack, team_plus, line_works, viber)	Yes	`line` : LINE ; `telegram` : Telegram ; `teams` : Teams ; `web` : Web ; `messenger` : Messenger ; `instagram` : Instagram ; `email` : Email ; `whatsapp` : WhatsApp ; `slack` : Slack ; `team_plus` : Team+ ; `lin...
unreadConversationsCount	integer	No	
signAuth	object (with 9 properties: id, signSource, signParams...)	No	
signAuth.signSource	string (uuid)	Yes	
signAuth.signParams	object	Yes	
signAuth.signParams.keycloak	object (with 3 properties: clientId, url, realm)	Yes	
signAuth.signParams.keycloak.clientId	string	Yes	
signAuth.signParams.keycloak.url	string	Yes	
signAuth.signParams.keycloak.realm	string	Yes	
signAuth.signParams.line	object (with 1 property: liffId)	Yes	
signAuth.signParams.line.liffId	string	Yes	
signAuth.signParams.ad	object (with 1 property: saml)	Yes	
signAuth.signParams.ad.saml	string	Yes	
signAuth.signParams.google	object (with 1 property: enabled)	No	

Field	Type	Required	Description
signAuth.signParams.google.enabled	boolean	Yes	
signAuth.sourceIdAccessEnabled	boolean	No	When enabled, embedded visitors presenting a Source ID (verified per the verify mode below) may chat without going through the login flow. Disabled keeps every existing behavior unchanged.
signAuth.sourceIdVerifyMode	object	No	"Require signature verification": the embedding site must send an HMAC signature computed on its backend. "Source ID only": anyone knowing a Source ID can act as that contact; suitable only for testin...
signAuth.sourceIdSignatureTtlMinutes	object	No	How long a signature can be used to obtain the contact identity. Not a session lifetime: once exchanged, the session follows the existing WebChat mechanism. `1` : 1 ; `5` : 5 ; `15` : 15;
signAuth.keycloakTokenPassthrough	boolean	No	When enabled, the Keycloak access token a visitor logged in with is forwarded as the Authorization header when the AI calls MCP and API tools on their behalf, so tools do not require a separate per-to...
signAuth.keycloakTokenPassthroughAllowedHosts	array[string]	No	Hostnames (or "*.example.com" wildcards) of the tools the visitor Keycloak token may be sent to
enableAnalysis	boolean	No	

Example Request Schema

```
{
  "name": string
  "channelType": string (enum: line, telegram, teams, web, messenger, instagram, email, whatsapp, slack,
team_plus, line_works, viber) // * `line` - LINE
* `telegram` - Telegram
* `teams` - Teams
* `web` - Web
* `messenger` - Messenger
* `instagram` - Instagram
* `email` - Email
* `whatsapp` - WhatsApp
* `slack` - Slack
* `team_plus` - Team+
* `line_works` - LINE WORKS
* `viber` - Viber
  "unreadConversationsCount"?: integer // Optional
  "signAuth"?:  // Optional
  {
    "signSource": string (uuid)
    "signParams": {
    {
      "keycloak":
      {
```

```
        "clientId": string
        "url": string
        "realm": string
      }
      "line":
      {
        "liffId": string
      }
      "ad":
      {
        "saml": string
      }
      "google"?:  // Optional
      {
        "enabled": boolean
      }
    }
    }
    "sourceIdAccessEnabled"?: boolean // When enabled, embedded visitors presenting a Source ID (verified per the verify mode below) may chat without going through the login flow. Disabled keeps every existing behavior unchanged. (Optional)
    "sourceIdVerifyMode"?:  // "Require signature verification": the embedding site must send an HMAC signature computed on its backend. "Source ID only": anyone knowing a Source ID can act as that contact; suitable only for testing or closed networks.

* `signature` - Require signature verification
* `raw` - Source ID only (Optional)
    {
    }
    "sourceIdSignatureTtlMinutes"?:  // How long a signature can be used to obtain the contact identity. Not a session lifetime: once exchanged, the session follows the existing WebChat mechanism.

* `1` - 1
* `5` - 5
* `15` - 15 (Optional)
    {
    }
    "keycloakTokenPassthrough"?: boolean // When enabled, the Keycloak access token a visitor logged in with is forwarded as the Authorization header when the AI calls MCP and API tools on their behalf, so tools do not require a separate per-tool login. Only for the Keycloak sign source. Never overrides an Authorization header a tool already resolves from its own credentials. The visitor identity is the organization member bound to the conversation at login, never the contact Source ID. (Optional)
    "keycloakTokenPassthroughAllowedHosts"?: [ // Hostnames (or "*.example.com" wildcards) of the tools the visitor Keycloak token may be sent to (Optional)
      string
    ]
  }
  "enableAnalysis"?: boolean // Optional
}
```

Example Request Values

```
{
  "chatbot": {
    "id": "80f3170d-eed7-4651-a8da-6b7e6bdbef8b"
  },
  "groups": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000"
    }
  ],
```

```
  "name": "Updated name"
}
```

Code Examples

Shell/Bash

```
# Example API call (Shell)
curl -X POST "https://api.maiagent.ai/api/v1/inboxes/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "chatbot": {
      "id": "80f3170d-eed7-4651-a8da-6b7e6bdbef8b"
    },
    "groups": [
      {
        "id": "550e8400-e29b-41d4-a716-446655440000"
      }
    ],
    "name": "Updated name"
  }'

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// Request Body (payload)
const data = {
    "chatbot": {
      "id": "80f3170d-eed7-4651-a8da-6b7e6bdbef8b"
    },
    "groups": [
      {
        "id": "550e8400-e29b-41d4-a716-446655440000"
      }
    ],
    "name": "Updated name"
  };

axios.post("https://api.maiagent.ai/api/v1/inboxes/", data, config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/inboxes/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# Request Body (payload)
data = {
    "chatbot": {
        "id": "80f3170d-eed7-4651-a8da-6b7e6bdbef8b"
    },
    "groups": [
        {
            "id": "550e8400-e29b-41d4-a716-446655440000"
        }
    ],
    "name": "Updated name"
}

response = requests.post(url, json=data, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->post("https://api.maiagent.ai/api/v1/inboxes/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'chatbot' => [
                'id' => '80f3170d-eed7-4651-a8da-6b7e6bdbef8b'
            ],
            'groups' => [
                [
                    'id' => '550e8400-e29b-41d4-a716-446655440000'
                ]
            ],
            'name' => 'Updated name'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response Body

Status code: 201

Example Response Schema

```
{
  "id": string (uuid)
  "name": string
  "channelType": string (enum: line, telegram, teams, web, messenger, instagram, email, whatsapp, slack,
team_plus, line_works, viber) // * `line` - LINE
* `telegram` - Telegram
* `teams` - Teams
* `web` - Web
* `messenger` - Messenger
* `instagram` - Instagram
* `email` - Email
```

```
* `whatsapp` - WhatsApp
* `slack` - Slack
* `team_plus` - Team+
* `line_works` - LINE WORKS
* `viber` - Viber
  "unreadConversationsCount"?: integer // Optional
  "signAuth"?:  // Optional
  {
    "id": string (uuid)
    "signSource": string (uuid)
    "signParams": {
    {
      "keycloak":
      {
        "clientId": string
        "url": string
        "realm": string
      }
      "line":
      {
        "liffId": string
      }
      "ad":
      {
        "saml": string
      }
      "google"?:  // Optional
      {
        "enabled": boolean
      }
    }
    }
    "sourceIdAccessEnabled"?: boolean // When enabled, embedded visitors presenting a Source ID (verified
per the verify mode below) may chat without going through the login flow. Disabled keeps every existing
behavior unchanged. (Optional)
    "sourceIdVerifyMode"?:  // "Require signature verification": the embedding site must send an HMAC
signature computed on its backend. "Source ID only": anyone knowing a Source ID can act as that contact;
suitable only for testing or closed networks.

* `signature` - Require signature verification
* `raw` - Source ID only (Optional)
    {
    }
    "sourceIdSignatureTtlMinutes"?:  // How long a signature can be used to obtain the contact identity. Not
a session lifetime: once exchanged, the session follows the existing WebChat mechanism.

* `1` - 1
* `5` - 5
* `15` - 15 (Optional)
    {
    }
    "keycloakTokenPassthrough"?: boolean // When enabled, the Keycloak access token a visitor logged in with
is forwarded as the Authorization header when the AI calls MCP and API tools on their behalf, so tools do
not require a separate per-tool login. Only for the Keycloak sign source. Never overrides an Authorization
header a tool already resolves from its own credentials. The visitor identity is the organization member
bound to the conversation at login, never the contact Source ID. (Optional)
    "keycloakTokenPassthroughAllowedHosts"?: [ // Hostnames (or "*.example.com" wildcards) of the tools the
visitor Keycloak token may be sent to (Optional)
      string
    ]
    "organizationLogin": object // How visitors sign in when the sign source is "organization" (mirrors the
back-office login); null for other sign sources
  }
```

```
  "enableAnalysis"?: boolean // Optional
}
```

Example Response Values


```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "name": "Response string",
  "channelType": "line",
  "unreadConversationsCount": 456,
  "signAuth": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "signSource": "550e8400-e29b-41d4-a716-446655440000",
    "signParams": {
      "keycloak": {
        "clientId": "Response string",
        "url": "Response string",
        "realm": "Response string"
      },
      "line": {
        "liffId": "Response string"
      },
      "ad": {
        "saml": "Response string"
      },
      "google": {
        "enabled": false
      }
    },
    "sourceIdAccessEnabled": false,
    "sourceIdVerifyMode": {},
    "sourceIdSignatureTtlMinutes": {},
    "keycloakTokenPassthrough": false,
    "keycloakTokenPassthroughAllowedHosts": [
      "Response string"
    ],
    "organizationLogin": {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "Example response name",
      "description": "Example response description"
    }
  },
  "enableAnalysis": false
}
```


Retrieve an Inbox

GET `/api/v1/inboxes/{id}`

Parameters

Parameter	Required	Type	Description

id	V	string	A UUID string identifying this Inbox.

Code Examples

Shell/Bash

```
# Example API call (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/inboxes/550e8400-e29b-41d4-a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/inboxes/550e8400-e29b-41d4-a716-446655440000/", config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```python
import requests

url = "https://api.maiagent.ai/api/v1/inboxes/550e8400-e29b-41d4-a716-446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->get("https://api.maiagent.ai/api/v1/inboxes/550e8400-e29b-41d4-a716-
446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response Body

Status Code: `200`

Example Response Schema

```
{
  "id": string (uuid)
  "name": string
  "channelType": string (enum: line, telegram, teams, web, messenger, instagram, email, whatsapp, slack,
team_plus, line_works, viber) // * `line` - LINE
* `telegram` - Telegram
* `teams` - Teams
* `web` - Web
* `messenger` - Messenger
* `instagram` - Instagram
* `email` - Email
* `whatsapp` - WhatsApp
* `slack` - Slack
* `team_plus` - Team+
* `line_works` - LINE WORKS
* `viber` - Viber
  "unreadConversationsCount"?: integer // Optional
  "signAuth"?:  // Optional
  {
    "id": string (uuid)
    "signSource": string (uuid)
    "signParams": {
    {
      "keycloak":
      {
        "clientId": string
        "url": string
        "realm": string
      }
      "line":
      {
        "liffId": string
      }
      "ad":
      {
        "saml": string
      }
      "google"?:  // Optional
      {
        "enabled": boolean
      }
    }
    }
    "sourceIdAccessEnabled"?: boolean // When enabled, embedded visitors presenting a Source ID (verified
per the verify mode below) may chat without going through the login flow. Disabled keeps every existing
behavior unchanged. (Optional)
    "sourceIdVerifyMode"?:  // "Require signature verification": the embedding site must send an HMAC
signature computed on its backend. "Source ID only": anyone knowing a Source ID can act as that contact;
suitable only for testing or closed networks.

* `signature` - Require signature verification
* `raw` - Source ID only (Optional)
    {
    }
    "sourceIdSignatureTtlMinutes"?:  // How long a signature can be used to obtain the contact identity. Not
a session lifetime: once exchanged, the session follows the existing WebChat mechanism.

* `1` - 1
* `5` - 5
* `15` - 15 (Optional)
```

```
    {
    }
    "keycloakTokenPassthrough"?: boolean // When enabled, the Keycloak access token a visitor logged in with is forwarded as the Authorization header when the AI calls MCP and API tools on their behalf, so tools do not require a separate per-tool login. Only for the Keycloak sign source. Never overrides an Authorization header a tool already resolves from its own credentials. The visitor identity is the organization member bound to the conversation at login, never the contact Source ID. (Optional)
    "keycloakTokenPassthroughAllowedHosts"?: [ // Hostnames (or "*.example.com" wildcards) of the tools the visitor Keycloak token may be sent to (Optional)
      string
    ]
    "organizationLogin": object // How visitors sign in when the sign source is "organization" (mirrors the back-office login); null for other sign sources
  }
  "enableAnalysis"?: boolean // Optional
}
```

Example Response Values


```
{
  "id": "961dcaac-bd2e-44d3-9050-82596dbb3334",
  "chatbot": {
    "id": "80f3170d-eed7-4651-a8da-6b7e6bdbef8b",
    "name": "Customer service chatbot",
    "groups": [],
    "largeLanguageModel": {
      "id": "933aa8b3-cdf4-47a7-86d5-b5dc27fbb044",
      "name": "llm"
    },
    "embeddingModel": {
      "id": "aefcc4f9-917d-4a8a-bd36-d97e3b7cecfe",
      "name": "embedding",
      "icon": null,
      "isDefault": false
    },
    "rerankerModel": {
      "id": "86c2ddfd-0df9-47b9-8f3b-0c42e3347da3",
      "name": "rerank",
      "icon": null,
      "isDefault": true
    },
    "knowledgeBases": [],
    "tools": [],
    "agentMode": "normal",
    "replyMode": "normal",
    "updatedAt": "1739519493000",
    "enableEvaluation": false,
    "enableInlineCitations": false,
    "enableKnowledgeBaseRag": true,
    "enableAgenticTextToSql": true,
    "enableToolSearching": true,
    "numberOfRetrievedChunks": 12
  },
  "groups": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "Administrator group"
    }
  ],
  "channelType": "web",
  "channelTypeLabel": "Web",
```

```
  "name": "1345",
  "autoReplySchedules": [
    {
      "id": "2f4f6383-d8b5-4d88-b4a1-6d02d731f2a6",
      "weekday": 0,
      "isEnabled": true,
      "timeSlots": [
        [
          "00:00:00",
          "00:00:00"
        ]
      ],
      "weekdayName": "Monday"
    },
    {
      "id": "2866f624-a5c3-4ffb-b980-0f8d6a9f0c93",
      "weekday": 1,
      "isEnabled": true,
      "timeSlots": [
        [
          "00:00:00",
          "00:00:00"
        ]
      ],
      "weekdayName": "Tuesday"
    },
    {
      "id": "3cf1e488-fb13-426d-bd59-e62bd71aca85",
      "weekday": 2,
      "isEnabled": true,
      "timeSlots": [
        [
          "00:00:00",
          "00:00:00"
        ]
      ],
      "weekdayName": "Wednesday"
    },
    {
      "id": "491776a9-fcf1-4e2e-892f-6d9ad5aebea4",
      "weekday": 3,
      "isEnabled": true,
      "timeSlots": [
        [
          "00:00:00",
          "00:00:00"
        ]
      ],
      "weekdayName": "Thursday"
    },
    {
      "id": "dfecb0a9-5001-4aa0-b2cc-5459b6d64351",
      "weekday": 4,
      "isEnabled": true,
      "timeSlots": [
        [
          "00:00:00",
          "00:00:00"
        ]
      ],
      "weekdayName": "Friday"
    },
    {
```

```
      "id": "68b6b4d1-7ac8-450f-8877-41b72b499919",
      "weekday": 5,
      "isEnabled": true,
      "timeSlots": [
        [
          "00:00:00",
          "00:00:00"
        ]
      ],
      "weekdayName": "Saturday"
    },
    {
      "id": "15228ea1-4513-4504-81f4-4e486703d8b9",
      "weekday": 6,
      "isEnabled": true,
      "timeSlots": [
        [
          "00:00:00",
          "00:00:00"
        ]
      ],
      "weekdayName": "Sunday"
    }
  ],
  "unreadConversationsCount": 0,
  "totalConversationsCount": 42,
  "channel": {
    "id": "801a690a-1038-4fdd-8aba-bf003b12c3ef",
    "name": "1345",
    "avatar": "https://media-dev.maiagent.ai/static/images/default-chatbot-avatar.png",
    "logo": null,
    "description": "",
    "cover": null,
    "backUrl": "",
    "isActive": true,
    "enableSpeech": false,
    "displayGreeting": null,
    "displayConversationStarters": [],
    "theme": {
      "primaryColor": "#3854d8",
      "navbarTextColor": "#ffffff",
      "conversationBackgroundColor": "#ffffff",
      "chatbotMessageTextColor": "#374151",
      "userMessageTextColor": "#374151",
      "chatbotMessageBackgroundColor": "#DCE9F6",
      "userMessageBackgroundColor": "#DDEAF6",
      "chatbotMessageBackgroundShadowEnabled": true,
      "userMessageBackgroundShadowEnabled": true
    },
    "darkTheme": {
      "primaryColor": "#404040",
      "navbarTextColor": "#ffffff",
      "conversationBackgroundColor": "#18181B",
      "chatbotMessageTextColor": "#ffffff",
      "userMessageTextColor": "#ffffff",
      "chatbotMessageBackgroundColor": "#171717",
      "userMessageBackgroundColor": "#333842",
      "chatbotMessageBackgroundShadowEnabled": false,
      "userMessageBackgroundShadowEnabled": false
    },
    "enableFileUpload": true,
    "enableDisplayCitations": true,
    "enableShareConversation": false,
```

```
    "enableLocation": false,
    "enableShowPoweredBy": true,
    "enableDisplayChatbotAvatar": true,
    "enableDisplayChatbotName": true,
    "enableDisplayPreviousConversation": true,
    "enableDisplayConversationHistory": true,
    "enableConversationTimer": false,
    "conversationTimerDuration": null,
    "enableAutoNewConversationOnTimeout": false,
    "accessType": "api",
    "greetings": [],
    "greetingsByLocale": {
      "en": [
        "Hello, how can I help you?"
      ],
      "zh-hant": [
        "你好，我可以幫你什麼嗎？"
      ],
      "ja": [
        "こんにちは、何かお手伝いできますか？"
      ],
      "ko": [
        "안녕하세요, 무엇을 도와드릴까요?"
      ]
    },
    "conversationStarters": [],
    "conversationStartersByLocale": {
      "en": [
        "What can I help you with today?"
      ],
      "zh-hant": [
        "你今天需要什麼幫助？"
      ],
      "ja": [
        "今日は何かお手伝いできますか？"
      ],
      "ko": [
        "오늘 뭘 도와줄수있어？"
      ]
    }
  },
  "webhooks": [],
  "createdAt": "1739519493000",
  "updatedAt": "1739519493000",
  "organization": "24b619d9-e981-4a8b-96da-63dc4f96bda6",
  "signAuth": null
}
```


Update an Inbox

PUT `/api/v1/inboxes/{id}`

Parameters

Parameter	Required	Type	Description
`id`	V	string	A UUID string identifying this Inbox.

Request Body

Request Parameters

Field	Type	Required	Description
name	string	Yes	
channelType	string (enum: line, telegram, teams, web, messenger, instagram, email, whatsapp, slack, team_plus, line_works, viber)	Yes	`line` : LINE ; `telegram` : Telegram ; `teams` : Teams ; `web` : Web ; `messenger` : Messenger ; `instagram` : Instagram ; `email` : Email ; `whatsapp` : WhatsApp ; `slack` : Slack ; `team_plus` : Team+ ; `lin...
unreadConversationsCount	integer	No	
signAuth	object (with 9 properties: id, signSource, signParams...)	No	
signAuth.signSource	string (uuid)	Yes	
signAuth.signParams	object	Yes	
signAuth.signParams.keycloak	object (with 3 properties: clientId, url, realm)	Yes	
signAuth.signParams.keycloak.clientId	string	Yes	
signAuth.signParams.keycloak.url	string	Yes	
signAuth.signParams.keycloak.realm	string	Yes	
signAuth.signParams.line	object (with 1 property: liffId)	Yes	
signAuth.signParams.line.liffId	string	Yes	
signAuth.signParams.ad	object (with 1 property: saml)	Yes	
signAuth.signParams.ad.saml	string	Yes	
signAuth.signParams.google	object (with 1 property: enabled)	No	
signAuth.signParams.google.enabled	boolean	Yes	
signAuth.sourceIdAccessEnabled	boolean	No	When enabled, embedded visitors presenting a Source ID (verified per the verify mode below) may chat without going through the login flow. Disabled keeps every existing behavior unchanged.

Field	Type	Required	Description
signAuth.sourceIdVerifyMode	object	No	"Require signature verification": the embedding site must send an HMAC signature computed on its backend. "Source ID only": anyone knowing a Source ID can act as that contact; suitable only for testin...
signAuth.sourceIdSignatureTtlMinutes	object	No	How long a signature can be used to obtain the contact identity. Not a session lifetime: once exchanged, the session follows the existing WebChat mechanism. `1` : 1 ; `5` : 5 ; `15` : 15;
signAuth.keycloakTokenPassthrough	boolean	No	When enabled, the Keycloak access token a visitor logged in with is forwarded as the Authorization header when the AI calls MCP and API tools on their behalf, so tools do not require a separate per-to...
signAuth.keycloakTokenPassthroughAllowedHosts	array[string]	No	Hostnames (or "*.example.com" wildcards) of the tools the visitor Keycloak token may be sent to
enableAnalysis	boolean	No	

Example Request Schema

```
{
  "name": string
  "channelType": string (enum: line, telegram, teams, web, messenger, instagram, email, whatsapp, slack,
team_plus, line_works, viber) // * `line` - LINE
* `telegram` - Telegram
* `teams` - Teams
* `web` - Web
* `messenger` - Messenger
* `instagram` - Instagram
* `email` - Email
* `whatsapp` - WhatsApp
* `slack` - Slack
* `team_plus` - Team+
* `line_works` - LINE WORKS
* `viber` - Viber
  "unreadConversationsCount"?: integer // Optional
  "signAuth"?:  // Optional
  {
    "signSource": string (uuid)
    "signParams": {
    {
      "keycloak":
      {
        "clientId": string
        "url": string
        "realm": string
      }
      "line":
      {
        "liffId": string
      }
      "ad":
```

```
      {
        "saml": string
      }
      "google"?:  // Optional
      {
        "enabled": boolean
      }
    }
    }
    "sourceIdAccessEnabled"?: boolean // When enabled, embedded visitors presenting a Source ID (verified per the verify mode below) may chat without going through the login flow. Disabled keeps every existing behavior unchanged. (Optional)
    "sourceIdVerifyMode"?:  // "Require signature verification": the embedding site must send an HMAC signature computed on its backend. "Source ID only": anyone knowing a Source ID can act as that contact; suitable only for testing or closed networks.

* `signature` - Require signature verification
* `raw` - Source ID only (Optional)
    {
    }
    "sourceIdSignatureTtlMinutes"?:  // How long a signature can be used to obtain the contact identity. Not a session lifetime: once exchanged, the session follows the existing WebChat mechanism.

* `1` - 1
* `5` - 5
* `15` - 15 (Optional)
    {
    }
    "keycloakTokenPassthrough"?: boolean // When enabled, the Keycloak access token a visitor logged in with is forwarded as the Authorization header when the AI calls MCP and API tools on their behalf, so tools do not require a separate per-tool login. Only for the Keycloak sign source. Never overrides an Authorization header a tool already resolves from its own credentials. The visitor identity is the organization member bound to the conversation at login, never the contact Source ID. (Optional)
    "keycloakTokenPassthroughAllowedHosts"?: [ // Hostnames (or "*.example.com" wildcards) of the tools the visitor Keycloak token may be sent to (Optional)
      string
    ]
  }
  "enableAnalysis"?: boolean // Optional
}
```

Example Request Values

```
{
  "chatbot": {
    "id": "80f3170d-eed7-4651-a8da-6b7e6bdbef8b"
  },
  "groups": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000"
    }
  ],
  "name": "Updated name"
}
```

Code Examples

Shell/Bash

```
# Example API call (Shell)
curl -X PUT "https://api.maiagent.ai/api/v1/inboxes/550e8400-e29b-41d4-a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "chatbot": {
      "id": "80f3170d-eed7-4651-a8da-6b7e6bdbef8b"
    },
    "groups": [
      {
        "id": "550e8400-e29b-41d4-a716-446655440000"
      }
    ],
    "name": "Updated name"
  }'

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// Request payload
const data = {
    "chatbot": {
      "id": "80f3170d-eed7-4651-a8da-6b7e6bdbef8b"
    },
    "groups": [
      {
        "id": "550e8400-e29b-41d4-a716-446655440000"
      }
    ],
    "name": "Updated name"
  };

axios.put("https://api.maiagent.ai/api/v1/inboxes/550e8400-e29b-41d4-a716-446655440000/", data,
config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/inboxes/550e8400-e29b-41d4-a716-446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# Request payload
data = {
    "chatbot": {
        "id": "80f3170d-eed7-4651-a8da-6b7e6bdbef8b"
    },
    "groups": [
        {
            "id": "550e8400-e29b-41d4-a716-446655440000"
        }
    ],
    "name": "Updated name"
}

response = requests.put(url, json=data, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->put("https://api.maiagent.ai/api/v1/inboxes/550e8400-e29b-41d4-a716-
446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'chatbot' => [
                'id' => '80f3170d-eed7-4651-a8da-6b7e6bdbef8b'
            ],
            'groups' => [
                [
                    'id' => '550e8400-e29b-41d4-a716-446655440000'
                ]
            ],
            'name' => 'Updated name'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response Body

Status Code: 200

Example Response Schema

```
{
  "id": string (uuid)
  "name": string
  "channelType": string (enum: line, telegram, teams, web, messenger, instagram, email, whatsapp, slack,
team_plus, line_works, viber) // * `line` - LINE
* `telegram` - Telegram
* `teams` - Teams
* `web` - Web
* `messenger` - Messenger
* `instagram` - Instagram
```

```
* `email` - Email
* `whatsapp` - WhatsApp
* `slack` - Slack
* `team_plus` - Team+
* `line_works` - LINE WORKS
* `viber` - Viber
  "unreadConversationsCount"?: integer // Optional
  "signAuth"?:  // Optional
  {
    "id": string (uuid)
    "signSource": string (uuid)
    "signParams": {
    {
      "keycloak":
      {
        "clientId": string
        "url": string
        "realm": string
      }
      "line":
      {
        "liffId": string
      }
      "ad":
      {
        "saml": string
      }
      "google"?:  // Optional
      {
        "enabled": boolean
      }
    }
    }
    "sourceIdAccessEnabled"?: boolean // When enabled, embedded visitors presenting a Source ID (verified per the verify mode below) may chat without going through the login flow. Disabled keeps every existing behavior unchanged. (Optional)
    "sourceIdVerifyMode"?:  // "Require signature verification": the embedding site must send an HMAC signature computed on its backend. "Source ID only": anyone knowing a Source ID can act as that contact; suitable only for testing or closed networks.

* `signature` - Require signature verification
* `raw` - Source ID only (Optional)
    {
    }
    "sourceIdSignatureTtlMinutes"?:  // How long a signature can be used to obtain the contact identity. Not a session lifetime: once exchanged, the session follows the existing WebChat mechanism.

* `1` - 1
* `5` - 5
* `15` - 15 (Optional)
    {
    }
    "keycloakTokenPassthrough"?: boolean // When enabled, the Keycloak access token a visitor logged in with is forwarded as the Authorization header when the AI calls MCP and API tools on their behalf, so tools do not require a separate per-tool login. Only for the Keycloak sign source. Never overrides an Authorization header a tool already resolves from its own credentials. The visitor identity is the organization member bound to the conversation at login, never the contact Source ID. (Optional)
    "keycloakTokenPassthroughAllowedHosts"?: [ // Hostnames (or "*.example.com" wildcards) of the tools the visitor Keycloak token may be sent to (Optional)
      string
    ]
    "organizationLogin": object // How visitors sign in when the sign source is "organization" (mirrors the back-office login); null for other sign sources
```

```
  }
  "enableAnalysis"?: boolean // Optional
}
```

Example Response Values


```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "name": "Response string",
  "channelType": "line",
  "unreadConversationsCount": 456,
  "signAuth": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "signSource": "550e8400-e29b-41d4-a716-446655440000",
    "signParams": {
      "keycloak": {
        "clientId": "Response string",
        "url": "Response string",
        "realm": "Response string"
      },
      "line": {
        "liffId": "Response string"
      },
      "ad": {
        "saml": "Response string"
      },
      "google": {
        "enabled": false
      }
    },
    "sourceIdAccessEnabled": false,
    "sourceIdVerifyMode": {},
    "sourceIdSignatureTtlMinutes": {},
    "keycloakTokenPassthrough": false,
    "keycloakTokenPassthroughAllowedHosts": [
      "Response string"
    ],
    "organizationLogin": {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "Example response name",
      "description": "Example response description"
    }
  },
  "enableAnalysis": false
}
```


Partially Update Inbox

PATCH `/api/v1/inboxes/{id}`

Parameters

Parameter Name	Required	Type	Description
`id`	V	string	A UUID string identifying this Inbox.

Request Body

Request Parameters

Field	Type	Required	Description
groups	array[IdName]	No	List of groups that can access this inbox
channelType	string (enum: line, telegram, teams, web, messenger, instagram, email, whatsapp, slack, team_plus, line_works, viber)	No	`line` : LINE ; `telegram` : Telegram ; `teams` : Teams ; `web` : Web ; `messenger` : Messenger ; `instagram` : Instagram ; `email` : Email ; `whatsapp` : WhatsApp ; `slack` : Slack ; `team_plus` : Team+ ; `lin...
name	string	No	
autoReplySchedules	array[AutoReplySchedule]	No	
channel	object	No	
organization	string (uuid)	No	
signAuth	object (with 10 properties: id, signSource, signParams...)	No	
signAuth.signSource	string (uuid)	Yes	
signAuth.signParams	object	Yes	
signAuth.signParams.keycloak	object (with 3 properties: clientId, url, realm)	Yes	
signAuth.signParams.keycloak.clientId	string	Yes	
signAuth.signParams.keycloak.url	string	Yes	
signAuth.signParams.keycloak.realm	string	Yes	
signAuth.signParams.line	object (with 1 property: liffId)	Yes	
signAuth.signParams.line.liffId	string	Yes	
signAuth.signParams.ad	object (with 1 property: saml)	Yes	
signAuth.signParams.ad.saml	string	Yes	
signAuth.signParams.google	object (with 1 property: enabled)	No	
signAuth.signParams.google.enabled	boolean	Yes	
signAuth.sourceIdAccessEnabled	boolean	No	When enabled, embedded visitors presenting a Source ID (verified per the verify mode below) may chat without going through the login flow.

Field	Type	Required	Description
			Disabled keeps every existing behavior unchanged.
signAuth.sourceIdVerifyMode	object	No	"Require signature verification": the embedding site must send an HMAC signature computed on its backend. "Source ID only": anyone knowing a Source ID can act as that contact; suitable only for testin...
signAuth.sourceIdSignatureTtlMinutes	object	No	How long a signature can be used to obtain the contact identity. Not a session lifetime: once exchanged, the session follows the existing WebChat mechanism. `1` : 1 ; `5` : 5 ; `15` : 15;
signAuth.keycloakTokenPassthrough	boolean	No	When enabled, the Keycloak access token a visitor logged in with is forwarded as the Authorization header when the AI calls MCP and API tools on their behalf, so tools do not require a separate per-to...
signAuth.keycloakTokenPassthroughAllowedHosts	array[string]	No	Hostnames (or "*.example.com" wildcards) of the tools the visitor Keycloak token may be sent to
enableTimeAwareResponse	boolean	No	Enable time aware responses for this inbox
defaultTimezone	string	No	Default timezone for this inbox (e.g., Asia/Taipei, America/New_York)
enableSenderNameAwareResponse	boolean	No	Enable sender name aware responses for this inbox
enableGpsAwareResponse	boolean	No	Enable GPS aware responses for this inbox
gpsRequestTiming	object	No	Web chat only. "on_open" asks the browser for the location as soon as the chat opens (current behavior); "on_demand" asks only when the AI requests it through an ask_user_question question carrying ex...
enableAiLineSticker	boolean	No	LINE inboxes only. When on, the AI may attach one LINE official sticker to a reply (from the global LINE AI sticker list).
enableOcr	boolean	No	Retired: attachments pick their parser by content detection (image-heavy files go to the Vision Parser, billed by token; scanned and text files to the MaiAgent Parser, scanned pages billed as OCR) and...
enableAgentAttachmentDecision	boolean	No	Kill switch for AGENT-mode attachment handling. When False (default), AGENT-mode chatbots skip auto-embedding on upload and let the agent handle attachments at

Field	Type	Required	Description
			runtime via ParseAttachmentContentTool /...
enableStreamMessage	boolean	No	
enableHumanHandoff	boolean	No	
handoffPrompt	string	No	
handoffLlm	string (uuid)	No	
handoffContextMessageLimit	integer	No	
handoffMessage	string	No	
queuingMessage	string	No	
assignedMessage	string	No	
enablePendingReplyMessage	boolean	No	Send a placeholder message to the user while the AI is processing.
pendingReplyMessage	string	No	
pendingReplyInitialDelaySeconds	integer	No	Delay before sending the first pending reply, so a fast AI response can pre-empt it.
pendingReplyIntervalSeconds	integer	No	Interval to repeat the pending reply while the AI is still processing.
enablePendingReplyCleanup	boolean	No	Delete pending reply messages after the AI reply is sent. Only effective on platforms that support message deletion (Teams, Telegram, Slack).
enableAnalysis	boolean	No	
analysisLlm	string (uuid)	No	
analysisPrompt	string	No	
analysisContextMessageLimit	integer	No	
analysisGenerateSummary	boolean	No	When on, conversation analysis writes the conversation summary (editable, with revisions); inbox auto split brings it to the next conversation
analysisApplyTags	boolean	No	When on, conversation analysis picks the conversation tags from the inbox tags
enableServiceHours	boolean	No	
serviceHoursTimezone	string	No	
offlineBehavior	string (enum: show_message, leave_message)	No	`show_message` : Show Message ; `leave_message` : Leave Message;
offlineMessage	string	No	
serviceHoursSchedules	array[ServiceHoursSchedule]	No	

Field	Type	Required	Description
dispatchMode	object	No	Auto dispatch assigns transferred conversations to an agent automatically. Claim (handover) leaves them unassigned for online agents to pick up themselves; timeout reassignment does not apply and the ...
assignmentRoutingModel	string (enum: round_robin, least_active)	No	`round_robin` : Round Robin ; `least_active` : Least Active;
assignmentMaxConcurrent	integer	No	
assignmentQueueTimeout	integer	No	Queue timeout in seconds
queueTimeoutMessage	string	No	
maxQueueSize	integer	No	
queueFullMessage	string	No	
assignmentTargetMembers	array[string]	No	
enableTagRouting	boolean	No	
enableReassignOnTimeout	boolean	No	When on, a queued or assigned-but-unanswered conversation that times out is reassigned to the next available agent (skipping already-tried agents) instead of returning straight to the AI; it only retu...
enableQueueReminder	boolean	No	Reply with a throttled waiting reminder when the contact sends messages while queued.
queueReminderMessage	string	No	
queueReminderCooldown	integer	No	Minimum seconds between queue reminders in one conversation
enableQueueCancel	boolean	No	Allow the contact to cancel a queued handoff and return to the AI by themselves.
queueCancelButtonText	string	No	Label of the cancel quick-reply button. Its text also counts as a cancel keyword, so tapping the button always cancels even when the keyword list changes.
queueCancelKeywords	object	No	Messages matching one of these exactly (after stripping surrounding whitespace) cancel the queued handoff. Empty means no keyword matching (the cancel button text still matches); the serializer requir...
queueCancelMessage	string	No	Sent to the contact right after they cancel the queued handoff.
enableIdleAutoResolve	boolean	No	Resolve a conversation served by a human agent once the agent replied last and the contact has not answered for the idle minutes. Frees

Field	Type	Required	Description
			the agent slot; queued conversations and ones where the contact ...
idleAutoResolveMinutes	integer	No	Minutes the contact may stay silent after the last agent reply before auto resolve
idleAutoResolveMessage	string	No	Sent to the contact when the conversation is auto resolved; blank sends nothing. LINE delivers it as a push message (counts toward the LINE message quota); Messenger / Instagram / WhatsApp skip it onc...
enableAgentReplyTimeout	boolean	No	When on, a conversation served by a human agent returns to the AI once a contact message has gone unanswered by any agent for the configured seconds; the AI then answers the last unanswered message. A...
agentReplyTimeout	integer	No	Seconds (60-86400) a contact message may go unanswered by a human agent before the AI takes over
agentReplyTimeoutMessage	string	No	Sent to the contact when the conversation returns to the AI; leave empty to send none.
enableReturnToPreviousAssignee	boolean	No	When on, a resolved conversation the contact writes to again within the configured hours reopens assigned to the agent who held it instead of to the AI. It still reopens to the AI when that agent is o...
returnToPreviousAssigneeHours	integer	No	Hours (1-720), counted from when the conversation was resolved, during which a returning contact goes back to the agent who held it
enableAutoSplit	boolean	No	When on, a one-to-one contact writing again after the conversation was resolved or went idle for the configured time starts a new conversation instead of continuing the old one. Web inboxes and group ...
autoSplitOnResolve	boolean	No	Split when the latest conversation was resolved more than the configured minutes ago
autoSplitResolveMinutes	integer	No	Minutes (0-10080) after the latest resolve; 0 splits on the next contact message
autoSplitOnIdle	boolean	No	Split when the last message of the latest conversation is older than the configured hours, unless a human agent is serving it or it is queued

Field	Type	Required	Description
autoSplitIdleHours	integer	No	Hours (1-720) since the last message of the latest conversation
enableContinuationSummary	boolean	No	When on, a conversation started by auto split gives its AI the previous conversations' analysis summaries; a previous conversation without a current summary gets one from conversation analysis (one bi...
continuationSummaryCount	integer	No	How many previous conversations (1-3) a new conversation looks back at for summaries
copilotEnabled	boolean	No	
copilotTriggerMode	string (enum: manual, every_incoming)	No	`manual` : Manual ; `every_incoming` : Every Incoming;
quotaExceededMessage	string	No	Custom message sent to the visitor when the inbox credit quota is exhausted. Used as the fallback when `quota_exceeded_message_by_locale` has no match for the conversation locale. Empty means the syst...
quotaExceededMessageByLocale	object	No	Locale-keyed quota-exceeded messages. A dict mapping normalized locale codes from CHAT_LANGUAGES (e.g. "en", "zh-hant", "ja") to a message string. Selected by the conversation locale; falls back to `q...

Example Request Schema

```
{
  "groups"?: [ // List of groups that can access this inbox (Optional)
    {
      "id": string (uuid)
    }
  ]
  "channelType"?: string (enum: line, telegram, teams, web, messenger, instagram, email, whatsapp, slack,
team_plus, line_works, viber) // * `line` - LINE
* `telegram` - Telegram
* `teams` - Teams
* `web` - Web
* `messenger` - Messenger
* `instagram` - Instagram
* `email` - Email
* `whatsapp` - WhatsApp
* `slack` - Slack
* `team_plus` - Team+
* `line_works` - LINE WORKS
* `viber` - Viber (Optional)
  "name"?: string // Optional
  "autoReplySchedules"?: [ // Optional
    {
      "isEnabled"?: boolean // Optional
      "timeSlots"?: [ // Optional
        array[string]
```

```
      ]
    }
  ]
  "channel"?: // May have different types (Optional)
  {
    "avatar"?: string (uri) // Optional
    "logo"?: string (uri) // Optional
    "description"?: string // Optional
    "cover"?: string (uri) // Optional
    "backUrl"?: string // Optional
    "isActive"?: boolean // Optional
    "theme": {
    {
      "primaryColor"?: string // Optional
      "navbarTextColor"?: string // Optional
      "conversationBackgroundColor"?: string // Optional
      "chatbotMessageTextColor"?: string // Optional
      "userMessageTextColor"?: string // Optional
      "chatbotMessageBackgroundColor"?: string // Optional
      "userMessageBackgroundColor"?: string // Optional
      "chatbotMessageBackgroundShadowEnabled"?: boolean // Optional
      "userMessageBackgroundShadowEnabled"?: boolean // Optional
      "chatbotMessageGradientEnabled"?: boolean // Optional
      "userMessageGradientEnabled"?: boolean // Optional
    }
    }
    "darkTheme": {
    {
      "primaryColor"?: string // Optional
      "navbarTextColor"?: string // Optional
      "conversationBackgroundColor"?: string // Optional
      "chatbotMessageTextColor"?: string // Optional
      "userMessageTextColor"?: string // Optional
      "chatbotMessageBackgroundColor"?: string // Optional
      "userMessageBackgroundColor"?: string // Optional
      "chatbotMessageBackgroundShadowEnabled"?: boolean // Optional
      "userMessageBackgroundShadowEnabled"?: boolean // Optional
      "chatbotMessageGradientEnabled"?: boolean // Optional
      "userMessageGradientEnabled"?: boolean // Optional
    }
    }
    "enableFileUpload"?: boolean // Optional
    "enableDisplayCitations"?: boolean // Optional
    "toolDisplayMode"?: string (enum: full, compact, hidden) // * `full` - Full
* `compact` - Compact
* `hidden` - Hidden (Optional)
    "enableAskOptionButtons"?: boolean // When enabled, ask_user_question options appear as a row of buttons above the input field, which remains usable. When disabled, the existing overlay panel is retained. This gradual rollout switch can be disabled at any time to revert the behavior. (Optional)
    "enableConversationHandoff"?: boolean // When enabled, this inbox's webchat displays the handoff UI (notification bar, summary card, and continuation button) and registers handoff tools. The global handoff switch in system settings still applies: disabling it disables handoff everywhere. MaiGPT always displays this UI regardless of this switch. The context usage percentage bar at the bottom is controlled separately by "Display Context Usage". Disabled by default, so customer-facing webchat shows no handoff UI. This gradual rollout switch can be disabled to revert the behavior without rolling back the release. (Optional)
    "enableDisplayContextUsage"?: boolean // When enabled, this inbox's webchat displays a context usage percentage bar below the input field. This is independent of conversation handoff: handoff switches, including the global handoff switch, do not affect it, and it does not affect the handoff notification bar. MaiGPT always displays the bar regardless of this switch. Disabled by default; disable it to revert the behavior without rolling back the release. (Optional)
    "enableDisplayThinking"?: boolean // Optional
    "enableUserThinkingControl"?: boolean // Optional
    "enableDisplayQueryMetadata"?: boolean // Optional
```

```
    "enableDisplayHookMarkers"?: boolean // Optional
    "hookMarkerTextInputModify"?: string // Optional
    "hookMarkerTextOutputModify"?: string // Optional
    "hookMarkerTextInputBlock"?: string // Optional
    "hookMarkerTextOutputBlock"?: string // Optional
    "enableShareConversation"?: boolean // Optional
    "enableLocation"?: boolean // Optional
    "enableShowPoweredBy"?: boolean // Optional
    "poweredByLogo"?: string (uri) // Optional
    "enableAnonymous"?: boolean // Optional
    "enableDisplayPreviousConversation"?: boolean // Optional
    "enableDisplayConversationHistory"?: boolean // Optional
    "enableConversationTimer"?: boolean // Optional
    "conversationTimerDuration"?: integer // Timer timeout duration, ranging from 3 to 60 minutes (Optional)
    "enableAutoNewConversationOnTimeout"?: boolean // Optional
    "enableSatisfactionSurvey"?: boolean // Optional
    "satisfactionSurveyDelayMinutes"?: integer // Minutes after the last AI reply before the survey appears,
ranging from 1 to 60 minutes (Optional)
    "satisfactionSurveyPrompt"?: string // Custom survey title; leave blank to use the frontend's default
localized text (Optional)
    "enableThemeModeToggle"?: boolean // Optional
    "enableDisplayFontSizeSwitch"?: boolean // Optional
    "defaultThemeMode"?:  // Optional
    {
    }
    "enableDownloadCitations"?: boolean // Optional
    "customDomain"?:  // Optional
    {
      "domain": string
    }
    "enableDisplayChatbotAvatar"?: boolean // Optional
    "enableDisplayChatbotName"?: boolean // Optional
    "buttonIcon"?: string (uri) // Optional
    "conversationStartersDisplayCount"?: integer // Optional
    "includeGreetingInContext"?: boolean // When enabled, the conversation greeting and the numbered
conversation starters (in configured order, unshuffled and untruncated) are injected into the LLM context so
the agent can resolve short replies like "1" to the matching starter option. (Optional)
    "preChatFormEnabled"?: boolean // Optional
    "preChatFormFields"?: object // Optional
    "preChatFormTitle"?: object // Optional
    "preChatFormSubtitle"?: object // Optional
    "loadingDisplayMode"?:  // Waiting-experience style. `narrative` shows per-stage copy; `brand_animation`
plays the uploaded asset and hides every system narration line. Defaults to `narrative`, which with no copy
configured behaves exactly as before this field existed.

* `narrative` - Narrative copy
* `brand_animation` - Brand animation (Optional)
    {
    }
    "loadingStageCopyByLocale"?: object // Locale-keyed per-stage waiting copy, shaped {locale: {stage:
text}} where stage is one of LoadingStage. An absent locale or stage falls back to the built-in copy, so a
partially filled dict is valid and never blocks a reply. (Optional)
    "loadingLongWaitCopyByLocale"?: object // Locale-keyed line shown once the wait exceeds
`loading_long_wait_threshold_seconds`, shaped {locale: text}. Written in the brand character voice for the
animation mode, but applies to both modes. Empty means no long-wait line is shown. (Optional)
    "loadingLongWaitThresholdSeconds"?: integer // How long a single reply must be pending before the long-
wait copy appears. (Optional)
    "loadingAnimationUseSharedAsset"?: boolean // True (default) means every stage plays
`loading_animation_shared_asset_url`, so the admin only uploads once. False expands per-stage assets, each
falling back to the shared asset when its own slot is empty. (Optional)
    "loadingAnimationSharedAssetUrl"?: string (uri) // Optional
    "loadingAnimationAssetUrlsByStage"?: object // Shaped {stage: url} keyed by LoadingStage. Only consulted
when `loading_animation_use_shared_asset` is False; a missing stage falls back to the shared asset.
```

```
(Optional)
    "loadingTypingShowCopy"?: boolean // Only affects the first "typing" stage. True (default, the pre-existing behavior) shows the typing-stage copy next to the pre-first-char animation/dot; False plays only the animation with no text line. Thinking / analyzing / long-wait stages are unaffected. (Optional)
    "toolCardRunningIconUrl"?: string (uri) // Optional
    "toolCardCompletedIconUrl"?: string (uri) // Optional
    "greetings"?: [ // Default greeting messages shown as the AI first message when a new conversation starts. One message is randomly selected per conversation. Used as the fallback when `greetings_by_locale` has no match for the request locale. (Optional)
      string
    ]
    "greetingsByLocale"?: object // Locale-keyed greetings. A dict mapping locale codes to a list of greeting strings (e.g. keys like "en", "zh-TW", "ja"). Selected by the conversation request Accept-Language header; falls back to `greetings` when no locale matches. (Optional)
    "voiceGreetings"?: [ // Greeting messages spoken aloud when a voice session starts. One message is randomly selected per session. The spoken greeting is ephemeral and NOT written back to conversation history. Used as the fallback when `voice_greetings_by_locale` has no match for the request locale. (Optional)
      string
    ]
    "voiceGreetingsByLocale"?: object // Locale-keyed voice greetings. A dict mapping locale codes to a list of greeting strings. Selected by the Accept-Language header; falls back to `voice_greetings` when no locale matches. (Optional)
    "conversationStarters"?: [ // Default suggested questions shown to the end-user as clickable prompts at the start of a conversation. Used as the fallback when `conversation_starters_by_locale` has no match for the request locale. (Optional)
      string
    ]
    "conversationStartersByLocale"?: object // Locale-keyed conversation starters. A dict mapping locale codes to a list of starter strings (e.g. keys like "en", "zh-TW", "ja"). Selected by the Accept-Language header; falls back to `conversation_starters` when no locale matches. (Optional)
    "allowedEmbedOrigins"?: [ // Origins allowed to embed this web chat and call the SDK contact-setup endpoint. Each entry is either an exact origin (scheme://host[:port], e.g. https://example.com) or a wildcard (*.example.com) that matches example.com and all of its subdomains on any scheme/port. An empty list means no restriction. Validated against the embedding page origin forwarded by the web chat frontend; bounds unauthorized-domain embedding. Browser-level enforcement (CSP frame-ancestors on the entry page) additionally requires an AWS/CloudFront deployment; on GCP storage the allowlist is enforced by the API alone. WARNING: leave empty until the web chat frontend forwards the embedding origin, otherwise setup calls fall back to the web chat host origin and every request is rejected. (Optional)
      string
    ]
  }
  "organization"?: string (uuid) // Optional
  "signAuth"?:  // Optional
  {
    "signSource": string (uuid)
    "signParams": {
    {
      "keycloak":
      {
        "clientId": string
        "url": string
        "realm": string
      }
      "line":
      {
        "liffId": string
      }
      "ad":
      {
        "saml": string
      }
      "google"?:  // Optional
```

```
      {
        "enabled": boolean
      }
    }
    }
    "sourceIdAccessEnabled"?: boolean // When enabled, embedded visitors presenting a Source ID (verified
per the verify mode below) may chat without going through the login flow. Disabled keeps every existing
behavior unchanged. (Optional)
    "sourceIdVerifyMode"?:  // "Require signature verification": the embedding site must send an HMAC
signature computed on its backend. "Source ID only": anyone knowing a Source ID can act as that contact;
suitable only for testing or closed networks.

* `signature` - Require signature verification
* `raw` - Source ID only (Optional)
    {
    }
    "sourceIdSignatureTtlMinutes"?:  // How long a signature can be used to obtain the contact identity. Not
a session lifetime: once exchanged, the session follows the existing WebChat mechanism.

* `1` - 1
* `5` - 5
* `15` - 15 (Optional)
    {
    }
    "keycloakTokenPassthrough"?: boolean // When enabled, the Keycloak access token a visitor logged in with
is forwarded as the Authorization header when the AI calls MCP and API tools on their behalf, so tools do
not require a separate per-tool login. Only for the Keycloak sign source. Never overrides an Authorization
header a tool already resolves from its own credentials. The visitor identity is the organization member
bound to the conversation at login, never the contact Source ID. (Optional)
    "keycloakTokenPassthroughAllowedHosts"?: [ // Hostnames (or "*.example.com" wildcards) of the tools the
visitor Keycloak token may be sent to (Optional)
      string
    ]
  }
  "enableTimeAwareResponse"?: boolean // Enable time aware responses for this inbox (Optional)
  "defaultTimezone"?: string // Default timezone for this inbox (e.g., Asia/Taipei, America/New_York)
(Optional)
  "enableSenderNameAwareResponse"?: boolean // Enable sender name aware responses for this inbox (Optional)
  "enableGpsAwareResponse"?: boolean // Enable GPS aware responses for this inbox (Optional)
  "gpsRequestTiming"?:  // Web chat only. "on_open" asks the browser for the location as soon as the chat
opens (current behavior); "on_demand" asks only when the AI requests it through an ask_user_question
question carrying extra_params.requestLocation. LINE always offers a share-location quick reply regardless
of this value.

* `on_open` - Ask when the chat opens
* `on_demand` - Ask only when the AI needs it (Optional)
  {
  }
  "enableAiLineSticker"?: boolean // LINE inboxes only. When on, the AI may attach one LINE official sticker
to a reply (from the global LINE AI sticker list). (Optional)
  "enableOcr"?: boolean // Retired: attachments pick their parser by content detection (image-heavy files go
to the Vision Parser, billed by token; scanned and text files to the MaiAgent Parser, scanned pages billed
as OCR) and this switch has no effect. (Optional)
  "enableAgentAttachmentDecision"?: boolean // Kill switch for AGENT-mode attachment handling. When False
(default), AGENT-mode chatbots skip auto-embedding on upload and let the agent handle attachments at runtime
via ParseAttachmentContentTool / IngestAttachmentTool. When True, AGENT-mode chatbots fall back to auto-
embedding chat attachments into the knowledge base on upload, same as non-AGENT modes. Has no effect on non-
AGENT chatbot modes (they always auto-embed). (Optional)
  "enableStreamMessage"?: boolean // Optional
  "enableHumanHandoff"?: boolean // Optional
  "handoffPrompt"?: string // Optional
  "handoffLlm"?: string (uuid) // Optional
  "handoffContextMessageLimit"?: integer // Optional
```

```
  "handoffMessage"?: string // Optional
  "queuingMessage"?: string // Optional
  "assignedMessage"?: string // Optional
  "enablePendingReplyMessage"?: boolean // Send a placeholder message to the user while the AI is
processing. (Optional)
  "pendingReplyMessage"?: string // Optional
  "pendingReplyInitialDelaySeconds"?: integer // Delay before sending the first pending reply, so a fast AI
response can pre-empt it. (Optional)
  "pendingReplyIntervalSeconds"?: integer // Interval to repeat the pending reply while the AI is still
processing. (Optional)
  "enablePendingReplyCleanup"?: boolean // Delete pending reply messages after the AI reply is sent. Only
effective on platforms that support message deletion (Teams, Telegram, Slack). (Optional)
  "enableAnalysis"?: boolean // Optional
  "analysisLlm"?: string (uuid) // Optional
  "analysisPrompt"?: string // Optional
  "analysisContextMessageLimit"?: integer // Optional
  "analysisGenerateSummary"?: boolean // When on, conversation analysis writes the conversation summary
(editable, with revisions); inbox auto split brings it to the next conversation (Optional)
  "analysisApplyTags"?: boolean // When on, conversation analysis picks the conversation tags from the inbox
tags (Optional)
  "enableServiceHours"?: boolean // Optional
  "serviceHoursTimezone"?: string // Optional
  "offlineBehavior"?: string (enum: show_message, leave_message) // * `show_message` - Show Message
* `leave_message` - Leave Message (Optional)
  "offlineMessage"?: string // Optional
  "serviceHoursSchedules"?: [ // Optional
    {
      "weekday": integer
      "startTime": string (time)
      "endTime": string (time)
      "isEnabled"?: boolean // Optional
    }
  ]
  "dispatchMode"?:  // Auto dispatch assigns transferred conversations to an agent automatically. Claim
(handover) leaves them unassigned for online agents to pick up themselves; timeout reassignment does not
apply and the queue timeout may be set to "no timeout".

* `auto` - Auto Dispatch
* `handover` - Claim (Handover) (Optional)
  {
  }
  "assignmentRoutingModel"?: string (enum: round_robin, least_active) // * `round_robin` - Round Robin
* `least_active` - Least Active (Optional)
  "assignmentMaxConcurrent"?: integer // Optional
  "assignmentQueueTimeout"?: integer // Queue timeout in seconds (Optional)
  "queueTimeoutMessage"?: string // Optional
  "maxQueueSize"?: integer // Optional
  "queueFullMessage"?: string // Optional
  "assignmentTargetMembers"?: [ // Optional
    string (uuid)
  ]
  "enableTagRouting"?: boolean // Optional
  "enableReassignOnTimeout"?: boolean // When on, a queued or assigned-but-unanswered conversation that
times out is reassigned to the next available agent (skipping already-tried agents) instead of returning
straight to the AI; it only returns to the AI once no agent is left to try. (Optional)
  "enableQueueReminder"?: boolean // Reply with a throttled waiting reminder when the contact sends messages
while queued. (Optional)
  "queueReminderMessage"?: string // Optional
  "queueReminderCooldown"?: integer // Minimum seconds between queue reminders in one conversation
(Optional)
  "enableQueueCancel"?: boolean // Allow the contact to cancel a queued handoff and return to the AI by
themselves. (Optional)
  "queueCancelButtonText"?: string // Label of the cancel quick-reply button. Its text also counts as a
```

```
cancel keyword, so tapping the button always cancels even when the keyword list changes. (Optional)
  "queueCancelKeywords"?: object // Messages matching one of these exactly (after stripping surrounding whitespace) cancel the queued handoff. Empty means no keyword matching (the cancel button text still matches); the serializer requires at least one keyword while queue cancel is enabled. (Optional)
  "queueCancelMessage"?: string // Sent to the contact right after they cancel the queued handoff. (Optional)
  "enableIdleAutoResolve"?: boolean // Resolve a conversation served by a human agent once the agent replied last and the contact has not answered for the idle minutes. Frees the agent slot; queued conversations and ones where the contact spoke last are never resolved. (Optional)
  "idleAutoResolveMinutes"?: integer // Minutes the contact may stay silent after the last agent reply before auto resolve (Optional)
  "idleAutoResolveMessage"?: string // Sent to the contact when the conversation is auto resolved; blank sends nothing. LINE delivers it as a push message (counts toward the LINE message quota); Messenger / Instagram / WhatsApp skip it once the contact last wrote more than 24 hours ago. (Optional)
  "enableAgentReplyTimeout"?: boolean // When on, a conversation served by a human agent returns to the AI once a contact message has gone unanswered by any agent for the configured seconds; the AI then answers the last unanswered message. Auto-dispatched conversations the agent has not answered yet are left to timeout reassignment while that is enabled. (Optional)
  "agentReplyTimeout"?: integer // Seconds (60-86400) a contact message may go unanswered by a human agent before the AI takes over (Optional)
  "agentReplyTimeoutMessage"?: string // Sent to the contact when the conversation returns to the AI; leave empty to send none. (Optional)
  "enableReturnToPreviousAssignee"?: boolean // When on, a resolved conversation the contact writes to again within the configured hours reopens assigned to the agent who held it instead of to the AI. It still reopens to the AI when that agent is offline, paused, off duty, no longer an active member with access to this inbox, or the inbox is outside its service hours. (Optional)
  "returnToPreviousAssigneeHours"?: integer // Hours (1-720), counted from when the conversation was resolved, during which a returning contact goes back to the agent who held it (Optional)
  "enableAutoSplit"?: boolean // When on, a one-to-one contact writing again after the conversation was resolved or went idle for the configured time starts a new conversation instead of continuing the old one. Web inboxes and group conversations are never split; a returning contact handed back to the previous assignee stays. (Optional)
  "autoSplitOnResolve"?: boolean // Split when the latest conversation was resolved more than the configured minutes ago (Optional)
  "autoSplitResolveMinutes"?: integer // Minutes (0-10080) after the latest resolve; 0 splits on the next contact message (Optional)
  "autoSplitOnIdle"?: boolean // Split when the last message of the latest conversation is older than the configured hours, unless a human agent is serving it or it is queued (Optional)
  "autoSplitIdleHours"?: integer // Hours (1-720) since the last message of the latest conversation (Optional)
  "enableContinuationSummary"?: boolean // When on, a conversation started by auto split gives its AI the previous conversations' analysis summaries; a previous conversation without a current summary gets one from conversation analysis (one billed model call on that conversation). Needs conversation analysis with its summary on. (Optional)
  "continuationSummaryCount"?: integer // How many previous conversations (1-3) a new conversation looks back at for summaries (Optional)
  "copilotEnabled"?: boolean // Optional
  "copilotTriggerMode"?: string (enum: manual, every_incoming) // * `manual` - Manual
* `every_incoming` - Every Incoming (Optional)
  "quotaExceededMessage"?: string // Custom message sent to the visitor when the inbox credit quota is exhausted. Used as the fallback when `quota_exceeded_message_by_locale` has no match for the conversation locale. Empty means the system default message is used. (Optional)
  "quotaExceededMessageByLocale"?: object // Locale-keyed quota-exceeded messages. A dict mapping normalized locale codes from CHAT_LANGUAGES (e.g. "en", "zh-hant", "ja") to a message string. Selected by the conversation locale; falls back to `quota_exceeded_message`. (Optional)
}
```

Example Request Values

```
{
  "chatbot": {
```

```
    "id": "80f3170d-eed7-4651-a8da-6b7e6bdbef8b"
  },
  "groups": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000"
    }
  ],
  "name": "Updated name"
}
```

Code Examples

Shell/Bash

```
# API call example (Shell)
curl -X PATCH "https://api.maiagent.ai/api/v1/inboxes/550e8400-e29b-41d4-a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "chatbot": {
      "id": "80f3170d-eed7-4651-a8da-6b7e6bdbef8b"
    },
    "groups": [
      {
        "id": "550e8400-e29b-41d4-a716-446655440000"
      }
    ],
    "name": "Updated name"
  }'

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// Request body (payload)
const data = {
    "chatbot": {
      "id": "80f3170d-eed7-4651-a8da-6b7e6bdbef8b"
    },
    "groups": [
      {
        "id": "550e8400-e29b-41d4-a716-446655440000"
      }
    ],
    "name": "Updated name"
  };

axios.patch("https://api.maiagent.ai/api/v1/inboxes/550e8400-e29b-41d4-a716-446655440000/", data,
config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/inboxes/550e8400-e29b-41d4-a716-446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# Request body (payload)
data = {
    "chatbot": {
        "id": "80f3170d-eed7-4651-a8da-6b7e6bdbef8b"
    },
    "groups": [
        {
            "id": "550e8400-e29b-41d4-a716-446655440000"
        }
    ],
    "name": "Updated name"
}

response = requests.patch(url, json=data, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->patch("https://api.maiagent.ai/api/v1/inboxes/550e8400-e29b-41d4-a716-
446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'chatbot' => [
                'id' => '80f3170d-eed7-4651-a8da-6b7e6bdbef8b'
            ],
            'groups' => [
                [
                    'id' => '550e8400-e29b-41d4-a716-446655440000'
                ]
            ],
            'name' => 'Updated name'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response

Status code: 200

Example Response Schema

```
{
  "id": string (uuid)
  "name": string
  "channelType": string (enum: line, telegram, teams, web, messenger, instagram, email, whatsapp, slack,
team_plus, line_works, viber) // * `line` - LINE
* `telegram` - Telegram
* `teams` - Teams
* `web` - Web
* `messenger` - Messenger
* `instagram` - Instagram
```

```
* `email` - Email
* `whatsapp` - WhatsApp
* `slack` - Slack
* `team_plus` - Team+
* `line_works` - LINE WORKS
* `viber` - Viber
  "unreadConversationsCount"?: integer // Optional
  "signAuth"?:  // Optional
  {
    "id": string (uuid)
    "signSource": string (uuid)
    "signParams": {
    {
      "keycloak":
      {
        "clientId": string
        "url": string
        "realm": string
      }
      "line":
      {
        "liffId": string
      }
      "ad":
      {
        "saml": string
      }
      "google"?:  // Optional
      {
        "enabled": boolean
      }
    }
    }
    "sourceIdAccessEnabled"?: boolean // When enabled, embedded visitors presenting a Source ID (verified per the verify mode below) may chat without going through the login flow. Disabled keeps every existing behavior unchanged. (Optional)
    "sourceIdVerifyMode"?:  // "Require signature verification": the embedding site must send an HMAC signature computed on its backend. "Source ID only": anyone knowing a Source ID can act as that contact; suitable only for testing or closed networks.

* `signature` - Require signature verification
* `raw` - Source ID only (Optional)
    {
    }
    "sourceIdSignatureTtlMinutes"?:  // How long a signature can be used to obtain the contact identity. Not a session lifetime: once exchanged, the session follows the existing WebChat mechanism.

* `1` - 1
* `5` - 5
* `15` - 15 (Optional)
    {
    }
    "keycloakTokenPassthrough"?: boolean // When enabled, the Keycloak access token a visitor logged in with is forwarded as the Authorization header when the AI calls MCP and API tools on their behalf, so tools do not require a separate per-tool login. Only for the Keycloak sign source. Never overrides an Authorization header a tool already resolves from its own credentials. The visitor identity is the organization member bound to the conversation at login, never the contact Source ID. (Optional)
    "keycloakTokenPassthroughAllowedHosts"?: [ // Hostnames (or "*.example.com" wildcards) of the tools the visitor Keycloak token may be sent to (Optional)
      string
    ]
    "organizationLogin": object // How visitors sign in when the sign source is "organization" (mirrors the back-office login); null for other sign sources
```

```
  }
  "enableAnalysis"?: boolean // Optional
}
```

Example Response Values


```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "name": "Response string",
  "channelType": "line",
  "unreadConversationsCount": 456,
  "signAuth": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "signSource": "550e8400-e29b-41d4-a716-446655440000",
    "signParams": {
      "keycloak": {
        "clientId": "Response string",
        "url": "Response string",
        "realm": "Response string"
      },
      "line": {
        "liffId": "Response string"
      },
      "ad": {
        "saml": "Response string"
      },
      "google": {
        "enabled": false
      }
    },
    "sourceIdAccessEnabled": false,
    "sourceIdVerifyMode": {},
    "sourceIdSignatureTtlMinutes": {},
    "keycloakTokenPassthrough": false,
    "keycloakTokenPassthroughAllowedHosts": [
      "Response string"
    ],
    "organizationLogin": {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "Example response name",
      "description": "Example response description"
    }
  },
  "enableAnalysis": false
}
```


Delete a Conversation Platform

DELETE `/api/v1/inboxes/{id}`

Parameters

Parameter name	Required	Type	Description
id	V	string	A UUID string identifying this Inbox.

Code examples

Shell/Bash

```
# Example API call (Shell)
curl -X DELETE "https://api.maiagent.ai/api/v1/inboxes/550e8400-e29b-41d4-a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

// Request body (payload)
const data = null;

axios.delete("https://api.maiagent.ai/api/v1/inboxes/550e8400-e29b-41d4-a716-446655440000/", data,
config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/inboxes/550e8400-e29b-41d4-a716-446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.delete(url, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->delete("https://api.maiagent.ai/api/v1/inboxes/550e8400-e29b-41d4-a716-
446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response body

Status Code	Description

204	No response body

List Webhooks for an Inbox

GET `/api/v1/inboxes/{inboxPk}/webhooks/`

Parameters

Parameter Name	Required	Type	Description
`inboxPk`	V	string	
`page`	X	integer	A page number within the paginated result set.
`pageSize`	X	integer	Number of results to return per page.

Code Examples

Shell/Bash

```
# Example API call (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/inboxes/550e8400-e29b-41d4-a716-446655440000/webhooks/?
page=1&pageSize=1"

  -H "Authorization: Api-Key YOUR_API_KEY"

# Before running, replace YOUR_API_KEY and verify the request data.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/inboxes/550e8400-e29b-41d4-a716-446655440000/webhooks/?
page=1&pageSize=1", config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/inboxes/550e8400-e29b-41d4-a716-446655440000/webhooks/?
page=1&pageSize=1"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->get("https://api.maiagent.ai/api/v1/inboxes/550e8400-e29b-41d4-a716-
446655440000/webhooks/?page=1&pageSize=1", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response Body

Status Code: 200

Example Response Schema

```
{
  "count": integer
  "next"?: string (uri) // Optional
  "previous"?: string (uri) // Optional
  "results": [
    {
      "id": string (uuid)
      "inbox": string (uuid)
      "name": string // Webhook configuration name for identification
      "direction":  // When to trigger: incoming (user messages) or outgoing (bot replies)

* `incoming` - Incoming
* `outgoing` - Outgoing
* `receive` - Receive
      {
      }
      "directionLabel": string
      "isEnabled"?: boolean // Optional
      "url": string (uri)
      "method"?:  // Optional
      {
      }
```

```
      "headersMasked": object
      "templatePreset"?: string (enum: maiagent_standard, genesys_cloud, custom) // * `maiagent_standard` -
MaiAgent Standard
* `genesys_cloud` - Genesys Cloud
* `custom` - Custom (Optional)
      "templatePresetLabel": string
      "customTemplate"?: string // Jinja2 template for custom payload format. Required when template_preset
is "custom". (Optional)
      "payloadPreset"?: // May have different types (Optional)
      string (enum: genesys_cloud) // Preset for parsing incoming webhook payloads (used with
direction=receive)

* `genesys_cloud` - Genesys Cloud (Optional)
      "payloadPresetLabel": string
      "receiveUrl": string
      "createdAt": string (timestamp)
      "updatedAt": string (timestamp)
    }
  ]
}
```

Example Response Values

```
{
  "count": 123,
  "next": "http://api.example.org/accounts/?page=4",
  "previous": "http://api.example.org/accounts/?page=2",
  "results": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "inbox": "550e8400-e29b-41d4-a716-446655440000",
      "name": "Response string",
      "direction": {},
      "directionLabel": "Response string",
      "isEnabled": false,
      "url": "https://example.com/file.jpg",
      "method": {},
      "headersMasked": {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "name": "Example response name",
        "description": "Example response description"
      },
      "templatePreset": "maiagent_standard",
      "templatePresetLabel": "Response string",
      "customTemplate": "Response string",
      "payloadPreset": "genesys_cloud",
      "payloadPresetLabel": "Response string",
      "receiveUrl": "Response string",
      "createdAt": "Response string",
      "updatedAt": "Response string"
    }
  ]
}
```

Create a Webhook

POST `/api/v1/inboxes/{inboxPk}/webhooks/`

Set direction to incoming (triggered when a user message arrives) or outgoing (triggered when the Agent replies); select maiagent_standard for template_preset to use the MaiAgent standard payload.

Parameters

Parameter Name	Required	Type	Description
`inboxPk`	V	string	

Request Body

Request Parameters

Field	Type	Required	Description
name	string	Yes	Webhook configuration name for identification
direction	object	Yes	When to trigger: incoming (user messages) or outgoing (bot replies) `incoming` : Incoming ; `outgoing` : Outgoing ; `receive` : Receive;
isEnabled	boolean	No	
url	string (uri)	No	
method	object	No	
headers	object	No	Custom HTTP headers as JSON object
templatePreset	string (enum: maiagent_standard, genesys_cloud, custom)	No	`maiagent_standard` : MaiAgent Standard ; `genesys_cloud` : Genesys Cloud ; `custom` : Custom;
customTemplate	string	No	Jinja2 template for custom payload format. Required when template_preset is "custom".
secretToken	string	No	Secret token for webhook signature verification
payloadPreset	object	No	Preset for parsing incoming webhook payloads (used with direction=receive) `genesys_cloud` : Genesys Cloud;

Example Request Schema

```
{
  "name": string // Webhook configuration name for identification
  "direction":  // When to trigger: incoming (user messages) or outgoing (bot replies)

* `incoming` - Incoming
* `outgoing` - Outgoing
* `receive` - Receive
  {
  }
  "isEnabled"?: boolean // Optional
  "url"?: string (uri) // Optional
  "method"?:  // Optional
```

```
  {
  }
  "headers"?: object // Custom HTTP headers as JSON object (Optional)
  "templatePreset"?: string (enum: maiagent_standard, genesys_cloud, custom) // * `maiagent_standard` -
MaiAgent Standard
* `genesys_cloud` - Genesys Cloud
* `custom` - Custom (Optional)
  "customTemplate"?: string // Jinja2 template for custom payload format. Required when template_preset is
"custom". (Optional)
  "secretToken"?: string // Secret token for webhook signature verification (Optional)
  "payloadPreset"?: // May have different types (Optional)
  string (enum: genesys_cloud) // Preset for parsing incoming webhook payloads (used with direction=receive)

* `genesys_cloud` - Genesys Cloud (Optional)
}
```

Example Request Values

```
{
  "name": "Example name",
  "direction": {},
  "isEnabled": true,
  "url": "https://example.com/file.jpg",
  "method": {},
  "headers": null,
  "templatePreset": "maiagent_standard",
  "customTemplate": "Example string",
  "secretToken": "Example string",
  "payloadPreset": null
}
```

Code Examples

Shell/Bash

```
# Example API call (Shell)
curl -X POST "https://api.maiagent.ai/api/v1/inboxes/550e8400-e29b-41d4-a716-446655440000/webhooks/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "name": "Example name",
    "direction": {},
    "isEnabled": true,
    "url": "https://example.com/file.jpg",
    "method": {},
    "headers": null,
    "templatePreset": "maiagent_standard",
    "customTemplate": "Example string",
    "secretToken": "Example string",
    "payloadPreset": null
  }'

# Before running, replace YOUR_API_KEY and verify the request data.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// Request Body (payload)
const data = {
    "name": "Example name",
    "direction": {},
    "isEnabled": true,
    "url": "https://example.com/file.jpg",
    "method": {},
    "headers": null,
    "templatePreset": "maiagent_standard",
    "customTemplate": "Example string",
    "secretToken": "Example string",
    "payloadPreset": null
  };

axios.post("https://api.maiagent.ai/api/v1/inboxes/550e8400-e29b-41d4-a716-446655440000/webhooks/",
data, config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/inboxes/550e8400-e29b-41d4-a716-446655440000/webhooks/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# Request Body (payload)
data = {
    "name": "Example name",
    "direction": {},
    "isEnabled": True,
    "url": "https://example.com/file.jpg",
    "method": {},
    "headers": None,
    "templatePreset": "maiagent_standard",
    "customTemplate": "Example string",
    "secretToken": "Example string",
    "payloadPreset": None
}

response = requests.post(url, json=data, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->post("https://api.maiagent.ai/api/v1/inboxes/550e8400-e29b-41d4-a716-
446655440000/webhooks/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'name' => 'Example name',
            'direction' => new \stdClass(),
            'isEnabled' => true,
            'url' => 'https://example.com/file.jpg',
            'method' => new \stdClass(),
            'headers' => null,
            'templatePreset' => 'maiagent_standard',
            'customTemplate' => 'Example string',
            'secretToken' => 'Example string',
            'payloadPreset' => null
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response Body

Status Code: 201

Example Response Schema

```
{
  "id": string (uuid)
  "inbox": string (uuid)
  "name": string // Webhook configuration name for identification
  "direction":  // When to trigger: incoming (user messages) or outgoing (bot replies)

* `incoming` - Incoming
* `outgoing` - Outgoing
* `receive` - Receive
```

```
  {
  }
  "directionLabel": string
  "isEnabled"?: boolean // Optional
  "url": string (uri)
  "method"?:  // Optional
  {
  }
  "headersMasked": object
  "templatePreset"?: string (enum: maiagent_standard, genesys_cloud, custom) // * `maiagent_standard` -
MaiAgent Standard
* `genesys_cloud` - Genesys Cloud
* `custom` - Custom (Optional)
  "templatePresetLabel": string
  "customTemplate"?: string // Jinja2 template for custom payload format. Required when template_preset is
"custom". (Optional)
  "payloadPreset"?: // May have different types (Optional)
  string (enum: genesys_cloud) // Preset for parsing incoming webhook payloads (used with direction=receive)

* `genesys_cloud` - Genesys Cloud (Optional)
  "payloadPresetLabel": string
  "receiveUrl": string
  "createdAt": string (timestamp)
  "updatedAt": string (timestamp)
}
```

Example Response Values

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "inbox": "550e8400-e29b-41d4-a716-446655440000",
  "name": "Response string",
  "direction": {},
  "directionLabel": "Response string",
  "isEnabled": false,
  "url": "https://example.com/file.jpg",
  "method": {},
  "headersMasked": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Example response name",
    "description": "Example response description"
  },
  "templatePreset": "maiagent_standard",
  "templatePresetLabel": "Response string",
  "customTemplate": "Response string",
  "payloadPreset": "genesys_cloud",
  "payloadPresetLabel": "Response string",
  "receiveUrl": "Response string",
  "createdAt": "Response string",
  "updatedAt": "Response string"
}
```

Retrieve a Specific Webhook

GET `/api/v1/inboxes/{inboxPk}/webhooks/{id}`

Parameters

Parameter Name	Required	Type	Description
`id`	V	string	A UUID string identifying this Inbox Webhook.
`inboxPk`	V	string	

Code Examples

Shell/Bash

```
# Example API call (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/inboxes/550e8400-e29b-41d4-a716-
446655440000/webhooks/550e8400-e29b-41d4-a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# Before running, replace YOUR_API_KEY and verify the request data.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/inboxes/550e8400-e29b-41d4-a716-
446655440000/webhooks/550e8400-e29b-41d4-a716-446655440000/", config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/inboxes/550e8400-e29b-41d4-a716-446655440000/webhooks/550e8400-
e29b-41d4-a716-446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->get("https://api.maiagent.ai/api/v1/inboxes/550e8400-e29b-41d4-a716-
446655440000/webhooks/550e8400-e29b-41d4-a716-446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response Body

Status Code: 200

Example Response Schema

```
{
  "id": string (uuid)
  "inbox": string (uuid)
  "name": string // Webhook configuration name for identification
  "direction":  // When to trigger: incoming (user messages) or outgoing (bot replies)

* `incoming` - Incoming
* `outgoing` - Outgoing
* `receive` - Receive
  {
  }
  "directionLabel": string
  "isEnabled"?: boolean // Optional
  "url": string (uri)
  "method"?:  // Optional
  {
  }
  "headersMasked": object
  "templatePreset"?: string (enum: maiagent_standard, genesys_cloud, custom) // * `maiagent_standard` -
MaiAgent Standard
* `genesys_cloud` - Genesys Cloud
* `custom` - Custom (Optional)
```

```
  "templatePresetLabel": string
  "customTemplate"?: string // Jinja2 template for custom payload format. Required when template_preset is
"custom". (Optional)
  "payloadPreset"?: // May have different types (Optional)
  string (enum: genesys_cloud) // Preset for parsing incoming webhook payloads (used with direction=receive)

* `genesys_cloud` - Genesys Cloud (Optional)
  "payloadPresetLabel": string
  "receiveUrl": string
  "createdAt": string (timestamp)
  "updatedAt": string (timestamp)
}
```

Example Response Values


```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "inbox": "550e8400-e29b-41d4-a716-446655440000",
  "name": "Response string",
  "direction": {},
  "directionLabel": "Response string",
  "isEnabled": false,
  "url": "https://example.com/file.jpg",
  "method": {},
  "headersMasked": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Example response name",
    "description": "Example response description"
  },
  "templatePreset": "maiagent_standard",
  "templatePresetLabel": "Response string",
  "customTemplate": "Response string",
  "payloadPreset": "genesys_cloud",
  "payloadPresetLabel": "Response string",
  "receiveUrl": "Response string",
  "createdAt": "Response string",
  "updatedAt": "Response string"
}
```


Update a Webhook

PUT `/api/v1/inboxes/{inboxPk}/webhooks/{id}`

Parameters

Parameter Name	Required	Type	Description
`id`	V	string	A UUID string identifying this Inbox Webhook.
`inboxPk`	V	string	

Request Body

Request Parameters

Field	Type	Required	Description
name	string	Yes	Webhook configuration name for identification
direction	object	Yes	When to trigger: incoming (user messages) or outgoing (bot replies) `incoming` : Incoming ; `outgoing` : Outgoing ; `receive` : Receive;
isEnabled	boolean	No	
url	string (uri)	No	
method	object	No	
headers	object	No	Custom HTTP headers as JSON object
templatePreset	string (enum: maiagent_standard, genesys_cloud, custom)	No	`maiagent_standard` : MaiAgent Standard ; `genesys_cloud` : Genesys Cloud ; `custom` : Custom;
customTemplate	string	No	Jinja2 template for custom payload format. Required when template_preset is "custom".
secretToken	string	No	Secret token for webhook signature verification
payloadPreset	object	No	Preset for parsing incoming webhook payloads (used with direction=receive) `genesys_cloud` : Genesys Cloud;

Example Request Schema

```
{
  "name": string // Webhook configuration name for identification
  "direction":  // When to trigger: incoming (user messages) or outgoing (bot replies)

* `incoming` - Incoming
* `outgoing` - Outgoing
* `receive` - Receive
  {
  }
  "isEnabled"?: boolean // Optional
  "url"?: string (uri) // Optional
  "method"?:  // Optional
  {
  }
  "headers"?: object // Custom HTTP headers as JSON object (Optional)
  "templatePreset"?: string (enum: maiagent_standard, genesys_cloud, custom) // * `maiagent_standard` -
MaiAgent Standard
* `genesys_cloud` - Genesys Cloud
* `custom` - Custom (Optional)
  "customTemplate"?: string // Jinja2 template for custom payload format. Required when template_preset is
"custom". (Optional)
  "secretToken"?: string // Secret token for webhook signature verification (Optional)
  "payloadPreset"?: // May have different types (Optional)
  string (enum: genesys_cloud) // Preset for parsing incoming webhook payloads (used with direction=receive)

* `genesys_cloud` - Genesys Cloud (Optional)
}
```

Example Request Values


```
{
  "name": "Example name",
  "direction": {},
  "isEnabled": true,
  "url": "https://example.com/file.jpg",
  "method": {},
  "headers": null,
  "templatePreset": "maiagent_standard",
  "customTemplate": "Example string",
  "secretToken": "Example string",
  "payloadPreset": null
}
```


Code Examples

Shell/Bash

```
# Example API call (Shell)
curl -X PUT "https://api.maiagent.ai/api/v1/inboxes/550e8400-e29b-41d4-a716-
446655440000/webhooks/550e8400-e29b-41d4-a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "name": "Example name",
    "direction": {},
    "isEnabled": true,
    "url": "https://example.com/file.jpg",
    "method": {},
    "headers": null,
    "templatePreset": "maiagent_standard",
    "customTemplate": "Example string",
    "secretToken": "Example string",
    "payloadPreset": null
  }'

# Before running, replace YOUR_API_KEY and verify the request data.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// Request Body (payload)
const data = {
    "name": "Example name",
    "direction": {},
    "isEnabled": true,
    "url": "https://example.com/file.jpg",
    "method": {},
    "headers": null,
    "templatePreset": "maiagent_standard",
    "customTemplate": "Example string",
    "secretToken": "Example string",
    "payloadPreset": null
  };

axios.put("https://api.maiagent.ai/api/v1/inboxes/550e8400-e29b-41d4-a716-
446655440000/webhooks/550e8400-e29b-41d4-a716-446655440000/", data, config)
  .then(response => {
    console.log('Successfully received response:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/inboxes/550e8400-e29b-41d4-a716-446655440000/webhooks/550e8400-e29b-41d4-a716-446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# Request Body (payload)
data = {
    "name": "Example name",
    "direction": {},
    "isEnabled": True,
    "url": "https://example.com/file.jpg",
    "method": {},
    "headers": None,
    "templatePreset": "maiagent_standard",
    "customTemplate": "Example string",
    "secretToken": "Example string",
    "payloadPreset": None
}

response = requests.put(url, json=data, headers=headers)
try:
    print("Successfully received response:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->put("https://api.maiagent.ai/api/v1/inboxes/550e8400-e29b-41d4-a716-
446655440000/webhooks/550e8400-e29b-41d4-a716-446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'name' => 'Example name',
            'direction' => new \stdClass(),
            'isEnabled' => true,
            'url' => 'https://example.com/file.jpg',
            'method' => new \stdClass(),
            'headers' => null,
            'templatePreset' => 'maiagent_standard',
            'customTemplate' => 'Example string',
            'secretToken' => 'Example string',
            'payloadPreset' => null
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Successfully received response:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response Body

Status Code: 200

Example Response Schema

```
{
  "id": string (uuid)
  "inbox": string (uuid)
  "name": string // Webhook configuration name for identification
  "direction":  // When to trigger: incoming (user messages) or outgoing (bot replies)

* `incoming` - Incoming
* `outgoing` - Outgoing
* `receive` - Receive
```

```
  {
  }
  "directionLabel": string
  "isEnabled"?: boolean // Optional
  "url": string (uri)
  "method"?:  // Optional
  {
  }
  "headersMasked": object
  "templatePreset"?: string (enum: maiagent_standard, genesys_cloud, custom) // * `maiagent_standard` -
MaiAgent Standard
* `genesys_cloud` - Genesys Cloud
* `custom` - Custom (Optional)
  "templatePresetLabel": string
  "customTemplate"?: string // Jinja2 template for custom payload format. Required when template_preset is
"custom". (Optional)
  "payloadPreset"?: // May have different types (Optional)
  string (enum: genesys_cloud) // Preset for parsing incoming webhook payloads (used with direction=receive)

* `genesys_cloud` - Genesys Cloud (Optional)
  "payloadPresetLabel": string
  "receiveUrl": string
  "createdAt": string (timestamp)
  "updatedAt": string (timestamp)
}
```

Example Response Values

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "inbox": "550e8400-e29b-41d4-a716-446655440000",
  "name": "Response string",
  "direction": {},
  "directionLabel": "Response string",
  "isEnabled": false,
  "url": "https://example.com/file.jpg",
  "method": {},
  "headersMasked": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Example response name",
    "description": "Example response description"
  },
  "templatePreset": "maiagent_standard",
  "templatePresetLabel": "Response string",
  "customTemplate": "Response string",
  "payloadPreset": "genesys_cloud",
  "payloadPresetLabel": "Response string",
  "receiveUrl": "Response string",
  "createdAt": "Response string",
  "updatedAt": "Response string"
}
```

Partially Update Webhook

PATCH `/api/v1/inboxes/{inboxPk}/webhooks/{id}`

Parameters

Parameter Name	Required	Type	Description
`id`	V	string	A UUID string identifying this Inbox Webhook.
`inboxPk`	V	string	

Request Body

Request Parameters

Field	Type	Required	Description
name	string	No	Webhook configuration name for identification
direction	object	No	When to trigger: incoming (user messages) or outgoing (bot replies) `incoming` : Incoming ; `outgoing` : Outgoing ; `receive` : Receive;
isEnabled	boolean	No	
url	string (uri)	No	
method	object	No	
headers	object	No	Custom HTTP headers as JSON object
templatePreset	string (enum: maiagent_standard, genesys_cloud, custom)	No	`maiagent_standard` : MaiAgent Standard ; `genesys_cloud` : Genesys Cloud ; `custom` : Custom;
customTemplate	string	No	Jinja2 template for custom payload format. Required when template_preset is "custom".
secretToken	string	No	Secret token for webhook signature verification
payloadPreset	object	No	Preset for parsing incoming webhook payloads (used with direction=receive) `genesys_cloud` : Genesys Cloud;

Example Request Schema

```
{
  "name"?: string // Webhook configuration name for identification (Optional)
  "direction"?:  // When to trigger: incoming (user messages) or outgoing (bot replies)

* `incoming` - Incoming
* `outgoing` - Outgoing
* `receive` - Receive (Optional)
  {
  }
  "isEnabled"?: boolean // Optional
  "url"?: string (uri) // Optional
  "method"?:  // Optional
  {
```

```
  }
  "headers"?: object // Custom HTTP headers as JSON object (Optional)
  "templatePreset"?: string (enum: maiagent_standard, genesys_cloud, custom) // * `maiagent_standard` -
MaiAgent Standard
* `genesys_cloud` - Genesys Cloud
* `custom` - Custom (Optional)
  "customTemplate"?: string // Jinja2 template for custom payload format. Required when template_preset is
"custom". (Optional)
  "secretToken"?: string // Secret token for webhook signature verification (Optional)
  "payloadPreset"?: // May have different types (Optional)
  string (enum: genesys_cloud) // Preset for parsing incoming webhook payloads (used with direction=receive)

* `genesys_cloud` - Genesys Cloud (Optional)
}
```

Example Request Values

```
{
  "name": "Example name",
  "direction": {},
  "isEnabled": true,
  "url": "https://example.com/file.jpg",
  "method": {},
  "headers": null,
  "templatePreset": "maiagent_standard",
  "customTemplate": "Example string",
  "secretToken": "Example string",
  "payloadPreset": null
}
```

Code Examples

Shell/Bash

```
# API call example (Shell)
curl -X PATCH "https://api.maiagent.ai/api/v1/inboxes/550e8400-e29b-41d4-a716-
446655440000/webhooks/550e8400-e29b-41d4-a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "name": "Example name",
    "direction": {},
    "isEnabled": true,
    "url": "https://example.com/file.jpg",
    "method": {},
    "headers": null,
    "templatePreset": "maiagent_standard",
    "customTemplate": "Example string",
    "secretToken": "Example string",
    "payloadPreset": null
  }'

# Before running, replace YOUR_API_KEY and verify the request data.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// Request Body (payload)
const data = {
    "name": "Example name",
    "direction": {},
    "isEnabled": true,
    "url": "https://example.com/file.jpg",
    "method": {},
    "headers": null,
    "templatePreset": "maiagent_standard",
    "customTemplate": "Example string",
    "secretToken": "Example string",
    "payloadPreset": null
  };

axios.patch("https://api.maiagent.ai/api/v1/inboxes/550e8400-e29b-41d4-a716-
446655440000/webhooks/550e8400-e29b-41d4-a716-446655440000/", data, config)
  .then(response => {
    console.log('Successfully received response:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/inboxes/550e8400-e29b-41d4-a716-446655440000/webhooks/550e8400-e29b-41d4-a716-446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# Request Body (payload)
data = {
    "name": "Example name",
    "direction": {},
    "isEnabled": True,
    "url": "https://example.com/file.jpg",
    "method": {},
    "headers": None,
    "templatePreset": "maiagent_standard",
    "customTemplate": "Example string",
    "secretToken": "Example string",
    "payloadPreset": None
}

response = requests.patch(url, json=data, headers=headers)
try:
    print("Successfully received response:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->patch("https://api.maiagent.ai/api/v1/inboxes/550e8400-e29b-41d4-a716-
446655440000/webhooks/550e8400-e29b-41d4-a716-446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'name' => 'Example name',
            'direction' => new \stdClass(),
            'isEnabled' => true,
            'url' => 'https://example.com/file.jpg',
            'method' => new \stdClass(),
            'headers' => null,
            'templatePreset' => 'maiagent_standard',
            'customTemplate' => 'Example string',
            'secretToken' => 'Example string',
            'payloadPreset' => null
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Successfully received response:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response Body

Status Code: 200

Example Response Schema

```
{
  "id": string (uuid)
  "inbox": string (uuid)
  "name": string // Webhook configuration name for identification
  "direction":  // When to trigger: incoming (user messages) or outgoing (bot replies)

* `incoming` - Incoming
* `outgoing` - Outgoing
* `receive` - Receive
```

```
  {
  }
  "directionLabel": string
  "isEnabled"?: boolean // Optional
  "url": string (uri)
  "method"?:  // Optional
  {
  }
  "headersMasked": object
  "templatePreset"?: string (enum: maiagent_standard, genesys_cloud, custom) // * `maiagent_standard` -
MaiAgent Standard
* `genesys_cloud` - Genesys Cloud
* `custom` - Custom (Optional)
  "templatePresetLabel": string
  "customTemplate"?: string // Jinja2 template for custom payload format. Required when template_preset is
"custom". (Optional)
  "payloadPreset"?: // May have different types (Optional)
  string (enum: genesys_cloud) // Preset for parsing incoming webhook payloads (used with direction=receive)

* `genesys_cloud` - Genesys Cloud (Optional)
  "payloadPresetLabel": string
  "receiveUrl": string
  "createdAt": string (timestamp)
  "updatedAt": string (timestamp)
}
```

Example Response Values

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "inbox": "550e8400-e29b-41d4-a716-446655440000",
  "name": "Response string",
  "direction": {},
  "directionLabel": "Response string",
  "isEnabled": false,
  "url": "https://example.com/file.jpg",
  "method": {},
  "headersMasked": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Example response name",
    "description": "Example response description"
  },
  "templatePreset": "maiagent_standard",
  "templatePresetLabel": "Response string",
  "customTemplate": "Response string",
  "payloadPreset": "genesys_cloud",
  "payloadPresetLabel": "Response string",
  "receiveUrl": "Response string",
  "createdAt": "Response string",
  "updatedAt": "Response string"
}
```

Delete Webhook

DELETE `/api/v1/inboxes/{inboxPk}/webhooks/{id}`

Parameters

Parameter Name	Required	Type	Description
`id`	V	string	A UUID string identifying this Inbox Webhook.
`inboxPk`	V	string	

Code Examples

Shell/Bash

```
# API Call Example (Shell)
curl -X DELETE "https://api.maiagent.ai/api/v1/inboxes/550e8400-e29b-41d4-a716-
446655440000/webhooks/550e8400-e29b-41d4-a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Configure request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

// Request body (payload)
const data = null;

axios.delete("https://api.maiagent.ai/api/v1/inboxes/550e8400-e29b-41d4-a716-
446655440000/webhooks/550e8400-e29b-41d4-a716-446655440000/", data, config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request failed:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/inboxes/550e8400-e29b-41d4-a716-446655440000/webhooks/550e8400-
e29b-41d4-a716-446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.delete(url, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request failed:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->delete("https://api.maiagent.ai/api/v1/inboxes/550e8400-e29b-41d4-a716-
446655440000/webhooks/550e8400-e29b-41d4-a716-446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request failed: ' . $e->getMessage();
}
?>
```

Response Body

Status Code	Description
204	No response body

API call example (Shell)

目錄

1. Create a tool
2. List tools
3. Retrieve a Specific Tool
4. Update a Tool
5. Partially update a tool
6. Delete a tool
7. List Available Tools
8. Create connector
9. List connectors
10. Retrieve a specific connector
11. Update Connector
12. Partially Update Connector
13. Delete Connector
14. List Authorized Connector Members
15. Remove Authorized Connector Member
16. List MCP Tool Registries
17. Retrieve a Specific MCP Tool Registry
18. List the Organization’ s Self-hosted MCP Servers
19. Add a Self-hosted MCP Server
20. Retrieve a Specific Self-hosted MCP Server
21. Partially Update a Self-hosted MCP Server
22. Delete a Self-hosted MCP Server
23. Test MCP Server Connection
24. List tool execution records
25. Retrieve a specific tool execution record
26. Get AI assistant filter options for execution records
27. Get tool filter options for execution records
28. List execution records for a specific tool
29. Get a specific execution record for a specific tool
30. Get AI Assistant Filter Options for a Specific Tool’ s Execution Records
31. Get Tool Filter Options for a Specific Tool's Execution Records

API call example (Shell)

Create a tool

POST `/api/v1/tools/`

Request body

Request parameters

Field	Type	Required	Description
name	object	No	Tool name may only contain letters, digits, underscores (_) and hyphens (-). Not required for MCP tools; for API tools it is the tool name given to the LLM.
displayName	string	Yes	A name with any characters, used by users for configuration and management.
description	string	No	Tool description shown to users. Not required for MCP tools.
prompt	string	No	Tool description/prompt given to the LLM. If empty, the description field is used. Not required for MCP tools.
toolType	string (enum: api, function, mcp, desktop, flex, quick_reply, quick_menu)	No	`api` : API ; `function` : Function ; `mcp` : MCP ; `desktop` : Desktop ; `flex` : Flex Message ; `quick_reply` : Quick Reply ; `quick_menu` : Quick Menu;
apiUrl	string	No	
httpMethod	object	No	
rawHeaders	object	No	
sensitiveHeaders	array[string]	No	

Field	Type	Required	Description
rawQueryParams	object	No	Query string parameters appended to every request of this API tool. Values support the same {{variable}} template rendering as raw_headers. On key collision with LLM-generated arguments, these values ...
rawParametersSchema	object	No	
functionCode	string	No	
mcpUrl	string	No	
mcpRegistry	string (uuid)	No	Registry backing this MCP tool. Null for manual-URL MCP tools.
mcpAllowedTools	object	No	
rawMcpHeader	object	No	Default headers used when the Contact has no matching MCP Credential.
authSubject	object	No	Shared uses the tool level token plus per contact credentials; contact requires per contact authentication only; caller mints a short-lived token for the conversation-bound member (falls back to per c...
flexTemplateJson	object	No	FlexMessage JSON template. Required for FLEX_MESSAGE tools. Stores the full LINE FlexMessage JSON structure (bubble / carousel / box / text / image / button etc.).
flexSchema	object	No	AI dynamic field schema for FlexMessage. JSON object whose keys are field paths parsed from

Field	Type	Required	Description
			flex_template_json (e.g. text / image url / button label / button uri / button message). Each value may be e...
quickReplyConfig	object	No	Authoring config for QUICK_REPLY tools. Structured JSON describing the chip buttons: static list or dynamic (LLM-generated) mode, each field either a fixed value or an LLM prompt.
quickMenuConfig	object	No	Authoring config for QUICK_MENU tools. Structured JSON describing the persistent input-bar menu rendered by the web chat only: layout (grid / list), default open state, and 2-6 items each carrying a d...
category	string (enum: knowledge_base, web_search, web_fetch, code_execution, file_processing, image_video_generation, database_query, third_party_integration, browser_operation, agent_collaboration, other)	No	`knowledge_base` : Knowledge base retrieval ; `web_search` : Web search ; `web_fetch` : Web page fetch ; `code_execution` : Code execution ; `file_processing` : File processing ; `image_video_generation` : ...
displayCopyByLocale	object	No	
outputRenderTemplateByLocale	object	No	
toolDisplayMode	object	No	
groups	array[IdName]	No	Groups this tool is assigned to. Non-owner members must pick at least one group they belong to.

Example request structure

```
{
  "name"?: // May have different types (optional)
  string // Tool name may only contain letters, digits, underscores (_) and
hyphens (-). Not required for MCP tools; for API tools it is the tool name given
to the LLM. (optional)
  "displayName": string // A name with any characters, used by users for
configuration and management.
  "description"?: string // Tool description shown to users. Not required for MCP
tools. (optional)
  "prompt"?: string // Tool description/prompt given to the LLM. If empty, the
description field is used. Not required for MCP tools. (optional)
  "toolType"?: string (enum: api, function, mcp, desktop, flex, quick_reply,
quick_menu) // * `api` - API
* `function` - Function
* `mcp` - MCP
* `desktop` - Desktop
* `flex` - Flex Message
* `quick_reply` - Quick Reply
* `quick_menu` - Quick Menu (optional)
  "apiUrl"?: string // optional
  "httpMethod"?: // May have different types (optional)
  string (enum: get, post, put, delete, patch) // optional
  "rawHeaders"?: object // optional
  "sensitiveHeaders"?: [ // optional
    string
  ]
  "rawQueryParams"?: object // Query string parameters appended to every request
of this API tool. Values support the same {{variable}} template rendering as
raw_headers. On key collision with LLM-generated arguments, these values win —
use this field for API keys that must travel in the query string. (optional)
  "rawParametersSchema"?: object // optional
  "functionCode"?: string // optional
  "mcpUrl"?: string // optional
  "mcpRegistry"?: string (uuid) // Registry backing this MCP tool. Null for
manual-URL MCP tools. (optional)
  "mcpAllowedTools"?: object // optional
  "rawMcpHeader"?: object // Default headers used when the Contact has no
matching MCP Credential. (optional)
  "authSubject"?:  // Shared uses the tool level token plus per contact
credentials; contact requires per contact authentication only; caller mints a
short-lived token for the conversation-bound member (falls back to per contact
credentials when the conversation has no bound member). MCP tools only.

* `shared` - Shared
* `contact` - Contact
* `caller` - Caller (optional)
```

```
  {
  }
  "flexTemplateJson"?: object // FlexMessage JSON template. Required for
FLEX_MESSAGE tools. Stores the full LINE FlexMessage JSON structure (bubble /
carousel / box / text / image / button etc.). (optional)
  "flexSchema"?: object // AI dynamic field schema for FlexMessage. JSON object
whose keys are field paths parsed from flex_template_json (e.g. text / image url
/ button label / button uri / button message). Each value may be either a plain
string (the AI prompt) or an object carrying additional metadata such as a field
tag, e.g. {"prompt": "...", "tag": "title"}. Empty values fall back to the
template default. (optional)
  "quickReplyConfig"?: object // Authoring config for QUICK_REPLY tools.
Structured JSON describing the chip buttons: static list or dynamic (LLM-
generated) mode, each field either a fixed value or an LLM prompt. (optional)
  "quickMenuConfig"?: object // Authoring config for QUICK_MENU tools. Structured
JSON describing the persistent input-bar menu rendered by the web chat only:
layout (grid / list), default open state, and 2-6 items each carrying a display
label plus an action payload (send prompt / prefill text / open http(s) link).
(optional)
  "category"?: string (enum: knowledge_base, web_search, web_fetch,
code_execution, file_processing, image_video_generation, database_query,
third_party_integration, browser_operation, agent_collaboration, other) // *
`knowledge_base` - Knowledge base retrieval
* `web_search` - Web search
* `web_fetch` - Web page fetch
* `code_execution` - Code execution
* `file_processing` - File processing
* `image_video_generation` - Image/video generation
* `database_query` - Database query
* `third_party_integration` - Third-party integration
* `browser_operation` - Browser operation
* `agent_collaboration` - Agent collaboration
* `other` - Other (catch-all) (optional)
  "displayCopyByLocale"?: object // optional
  "outputRenderTemplateByLocale"?: object // optional
  "toolDisplayMode"?: // May have different types (optional)
  string (enum: full, compact, hidden) // optional
  "groups"?: [ // Groups this tool is assigned to. Non-owner members must pick at
least one group they belong to. (optional)
    {
      "id": string (uuid)
    }
  ]
}
```

Example request values

```
{
  "name": null,
  "displayName": "Example string",
  "description": "Example string",
  "prompt": "Example string",
  "toolType": "api",
  "apiUrl": "Example string",
  "httpMethod": null,
  "rawHeaders": null,
  "sensitiveHeaders": [
    "Example string"
  ],
  "rawQueryParams": null,
  "rawParametersSchema": null,
  "functionCode": "Example string",
  "mcpUrl": "Example string",
  "mcpRegistry": "550e8400-e29b-41d4-a716-446655440000",
  "mcpAllowedTools": null,
  "rawMcpHeader": null,
  "authSubject": {},
  "flexTemplateJson": null,
  "flexSchema": null,
  "quickReplyConfig": null,
  "quickMenuConfig": null,
  "category": "knowledge_base",
  "displayCopyByLocale": null,
  "outputRenderTemplateByLocale": null,
  "toolDisplayMode": null,
  "groups": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000"
    }
  ]
}
```


Code examples

Shell/Bash

```
# API call example (Shell)
curl -X POST "https://api.maiagent.ai/api/v1/tools/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "name": null,
    "displayName": "Example string",
    "description": "Example string",
    "prompt": "Example string",
    "toolType": "api",
    "apiUrl": "Example string",
    "httpMethod": null,
    "rawHeaders": null,
    "sensitiveHeaders": [
      "Example string"
    ],
    "rawQueryParams": null,
    "rawParametersSchema": null,
    "functionCode": "Example string",
    "mcpUrl": "Example string",
    "mcpRegistry": "550e8400-e29b-41d4-a716-446655440000",
    "mcpAllowedTools": null,
    "rawMcpHeader": null,
    "authSubject": {},
    "flexTemplateJson": null,
    "flexSchema": null,
    "quickReplyConfig": null,
    "quickMenuConfig": null,
    "category": "knowledge_base",
    "displayCopyByLocale": null,
    "outputRenderTemplateByLocale": null,
    "toolDisplayMode": null,
    "groups": [
      {
        "id": "550e8400-e29b-41d4-a716-446655440000"
      }
    ]
  }'

# Before running, replace YOUR_API_KEY and verify the request data.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// Request payload
const data = {
    "name": null,
    "displayName": "Example string",
    "description": "Example string",
    "prompt": "Example string",
    "toolType": "api",
    "apiUrl": "Example string",
    "httpMethod": null,
    "rawHeaders": null,
    "sensitiveHeaders": [
      "Example string"
    ],
    "rawQueryParams": null,
    "rawParametersSchema": null,
    "functionCode": "Example string",
    "mcpUrl": "Example string",
    "mcpRegistry": "550e8400-e29b-41d4-a716-446655440000",
    "mcpAllowedTools": null,
    "rawMcpHeader": null,
    "authSubject": {},
    "flexTemplateJson": null,
    "flexSchema": null,
    "quickReplyConfig": null,
    "quickMenuConfig": null,
    "category": "knowledge_base",
    "displayCopyByLocale": null,
    "outputRenderTemplateByLocale": null,
    "toolDisplayMode": null,
    "groups": [
      {
        "id": "550e8400-e29b-41d4-a716-446655440000"
      }
    ]
```

```
  };

axios.post("https://api.maiagent.ai/api/v1/tools/", data, config)
  .then(response => {
    console.log('Response retrieved successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('An error occurred during the request:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/tools/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# Request payload
data = {
    "name": None,
    "displayName": "Example string",
    "description": "Example string",
    "prompt": "Example string",
    "toolType": "api",
    "apiUrl": "Example string",
    "httpMethod": None,
    "rawHeaders": None,
    "sensitiveHeaders": [
        "Example string"
    ],
    "rawQueryParams": None,
    "rawParametersSchema": None,
    "functionCode": "Example string",
    "mcpUrl": "Example string",
    "mcpRegistry": "550e8400-e29b-41d4-a716-446655440000",
    "mcpAllowedTools": None,
    "rawMcpHeader": None,
    "authSubject": {},
    "flexTemplateJson": None,
    "flexSchema": None,
    "quickReplyConfig": None,
    "quickMenuConfig": None,
    "category": "knowledge_base",
    "displayCopyByLocale": None,
    "outputRenderTemplateByLocale": None,
    "toolDisplayMode": None,
    "groups": [
        {
            "id": "550e8400-e29b-41d4-a716-446655440000"
        }
    ]
}
```

```
response = requests.post(url, json=data, headers=headers)
try:
    print("Response retrieved successfully:")
    print(response.json())
except Exception as e:
    print("An error occurred during the request:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->post("https://api.maiagent.ai/api/v1/tools/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'name' => null,
            'displayName' => 'Example string',
            'description' => 'Example string',
            'prompt' => 'Example string',
            'toolType' => 'api',
            'apiUrl' => 'Example string',
            'httpMethod' => null,
            'rawHeaders' => null,
            'sensitiveHeaders' => [
                'Example string'
            ],
            'rawQueryParams' => null,
            'rawParametersSchema' => null,
            'functionCode' => 'Example string',
            'mcpUrl' => 'Example string',
            'mcpRegistry' => '550e8400-e29b-41d4-a716-446655440000',
            'mcpAllowedTools' => null,
            'rawMcpHeader' => null,
            'authSubject' => new \stdClass(),
            'flexTemplateJson' => null,
            'flexSchema' => null,
            'quickReplyConfig' => null,
            'quickMenuConfig' => null,
            'category' => 'knowledge_base',
            'displayCopyByLocale' => null,
            'outputRenderTemplateByLocale' => null,
            'toolDisplayMode' => null,
            'groups' => [
                [
                    'id' => '550e8400-e29b-41d4-a716-446655440000'
                ]
            ]
```

```
            ]
        ]);

        $data = json_decode($response->getBody(), true);
        echo "Response retrieved successfully:\n";
        print_r($data);
    } catch (Exception $e) {
        echo 'An error occurred during the request: ' . $e->getMessage();
    }
    ?>
```

Response body

Status code: 201

Example response structure

```
{
  "id": string (uuid)
  "name"?: // May have different types (optional)
  string // Tool name may only contain letters, digits, underscores (_) and
hyphens (-). Not required for MCP tools; for API tools it is the tool name given
to the LLM. (optional)
  "displayName": string // A name with any characters, used by users for
configuration and management.
  "description"?: string // Tool description shown to users. Not required for MCP
tools. (optional)
  "prompt"?: string // Tool description/prompt given to the LLM. If empty, the
description field is used. Not required for MCP tools. (optional)
  "toolType"?: string (enum: api, function, mcp, desktop, flex, quick_reply,
quick_menu) // * `api` - API
* `function` - Function
* `mcp` - MCP
* `desktop` - Desktop
* `flex` - Flex Message
* `quick_reply` - Quick Reply
* `quick_menu` - Quick Menu (optional)
  "apiUrl"?: string // optional
  "httpMethod"?: // May have different types (optional)
  string (enum: get, post, put, delete, patch) // optional
  "rawHeaders"?: object // optional
```

```
  "rawHeadersMasked": object
  "sensitiveHeaders"?: [ // optional
    string
  ]
  "globalSensitiveHeaders": [ // Expose platform defaults as read-only authoring
guidance.
    string
  ]
  "rawQueryParams"?: object // Query string parameters appended to every request
of this API tool. Values support the same {{variable}} template rendering as
raw_headers. On key collision with LLM-generated arguments, these values win —
use this field for API keys that must travel in the query string. (optional)
  "rawQueryParamsMasked": object
  "rawParametersSchema"?: object // optional
  "functionCode"?: string // optional
  "organization": string (uuid)
  "createdBy": string (uuid)
  "isGlobal": boolean // If set as global tool, all organizations can use this
tool
  "mcpUrl"?: string // optional
  "mcpRegistry"?: string (uuid) // Registry backing this MCP tool. Null for
manual-URL MCP tools. (optional)
  "mcpAllowedTools"?: object // optional
  "rawMcpHeader"?: object // Default headers used when the Contact has no
matching MCP Credential. (optional)
  "rawMcpHeaderMasked": object
  "authSubject"?:  // Shared uses the tool level token plus per contact
credentials; contact requires per contact authentication only; caller mints a
short-lived token for the conversation-bound member (falls back to per contact
credentials when the conversation has no bound member). MCP tools only.

* `shared` - Shared
* `contact` - Contact
* `caller` - Caller (optional)
  {
  }
  "flexTemplateJson"?: object // FlexMessage JSON template. Required for
FLEX_MESSAGE tools. Stores the full LINE FlexMessage JSON structure (bubble /
carousel / box / text / image / button etc.). (optional)
  "flexSchema"?: object // AI dynamic field schema for FlexMessage. JSON object
whose keys are field paths parsed from flex_template_json (e.g. text / image url
/ button label / button uri / button message). Each value may be either a plain
string (the AI prompt) or an object carrying additional metadata such as a field
tag, e.g. {"prompt": "...", "tag": "title"}. Empty values fall back to the
template default. (optional)
  "quickReplyConfig"?: object // Authoring config for QUICK_REPLY tools.
Structured JSON describing the chip buttons: static list or dynamic (LLM-
generated) mode, each field either a fixed value or an LLM prompt. (optional)
  "quickMenuConfig"?: object // Authoring config for QUICK_MENU tools. Structured
```

```
JSON describing the persistent input-bar menu rendered by the web chat only:
layout (grid / list), default open state, and 2-6 items each carrying a display
label plus an action payload (send prompt / prefill text / open http(s) link).
(optional)
  "category"?: string (enum: knowledge_base, web_search, web_fetch,
code_execution, file_processing, image_video_generation, database_query,
third_party_integration, browser_operation, agent_collaboration, other) // *
`knowledge_base` - Knowledge base retrieval
* `web_search` - Web search
* `web_fetch` - Web page fetch
* `code_execution` - Code execution
* `file_processing` - File processing
* `image_video_generation` - Image/video generation
* `database_query` - Database query
* `third_party_integration` - Third-party integration
* `browser_operation` - Browser operation
* `agent_collaboration` - Agent collaboration
* `other` - Other (catch-all) (optional)
  "displayCopyByLocale"?: object // optional
  "outputRenderTemplateByLocale"?: object // optional
  "toolDisplayMode"?: // May have different types (optional)
  string (enum: full, compact, hidden) // optional
  "groups"?: [ // Groups this tool is assigned to. Non-owner members must pick at
least one group they belong to. (optional)
    {
      "id": string (uuid)
      "name": string
    }
  ]
  "createdAt": string (timestamp)
  "updatedAt": string (timestamp)
  "canUpdate": boolean // Return whether the current user can update this
resource.
  "canDelete": boolean // Return whether the current user can delete this
resource.
}
```

Example response values


```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "name": "Response string",
  "displayName": "Response string",
  "description": "Response string",
  "prompt": "Response string",
  "toolType": "api",
  "apiUrl": "Response string",
  "httpMethod": "get",
```

```
  "rawHeaders": null,
  "rawHeadersMasked": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Example response name",
    "description": "Example response description"
  },
  "sensitiveHeaders": [
    "Response string"
  ],
  "globalSensitiveHeaders": [
    "Response string"
  ],
  "rawQueryParams": null,
  "rawQueryParamsMasked": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Example response name",
    "description": "Example response description"
  },
  "rawParametersSchema": null,
  "functionCode": "Response string",
  "organization": "550e8400-e29b-41d4-a716-446655440000",
  "createdBy": "550e8400-e29b-41d4-a716-446655440000",
  "isGlobal": false,
  "mcpUrl": "Response string",
  "mcpRegistry": "550e8400-e29b-41d4-a716-446655440000",
  "mcpAllowedTools": null,
  "rawMcpHeader": null,
  "rawMcpHeaderMasked": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Example response name",
    "description": "Example response description"
  },
  "authSubject": {},
  "flexTemplateJson": null,
  "flexSchema": null,
  "quickReplyConfig": null,
  "quickMenuConfig": null,
  "category": "knowledge_base",
  "displayCopyByLocale": null,
  "outputRenderTemplateByLocale": null,
  "toolDisplayMode": "full",
  "groups": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "Response string"
    }
  ],
  "createdAt": "Response string",
  "updatedAt": "Response string",
```

```
  "canUpdate": false,
  "canDelete": false
}
```

List tools

`GET` `/api/v1/tools/`

Parameters

Parameter name	Required	Type	Description
`clientPlatform`	X	string	Calling client platform. Pass "desktop" to include desktop-type tools; any other value, or omitting it, excludes desktop tools by default
`isGlobal`	X	boolean	Set to "true" to retrieve global tools; otherwise organization tools are retrieved
`page`	X	integer	A page number within the paginated result set.
`pageSize`	X	integer	Number of results to return per page.
`toolType`	X	string	Filter by tool type: api, function, mcp, desktop

Code examples

Shell/Bash

```
# API call example (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/tools/?
clientPlatform=desktop&isGlobal=true&page=1&pageSize=1&toolType=api"

  -H "Authorization: Api-Key YOUR_API_KEY"

# Before running, replace YOUR_API_KEY and verify the request data.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/tools/?
clientPlatform=desktop&isGlobal=true&page=1&pageSize=1&toolType=api",
config)
  .then(response => {
    console.log('Successfully retrieved response:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('An error occurred during the request:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/tools/?
clientPlatform=desktop&isGlobal=true&page=1&pageSize=1&toolType=api"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("Successfully retrieved response:")
    print(response.json())
except Exception as e:
    print("An error occurred during the request:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->get("https://api.maiagent.ai/api/v1/tools/?
clientPlatform=desktop&isGlobal=true&page=1&pageSize=1&toolType=api", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Successfully retrieved response:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'An error occurred during the request: ' . $e->getMessage();
}
?>
```

Response Content

Status Code: 200

Example Response Schema

```
{
  "count": integer
  "next"?: string (uri) // Optional
  "previous"?: string (uri) // Optional
  "results": [
    {
      "id": string (uuid)
      "name"?: // May have different types (Optional)
```

```
      string // Tool name may only contain letters, digits, underscores (_) and
hyphens (-). Not required for MCP tools; for API tools it is the tool name given
to the LLM. (Optional)
      "displayName": string // A name with any characters, used by users for
configuration and management.
      "description"?: string // Tool description shown to users. Not required for
MCP tools. (Optional)
      "prompt"?: string // Tool description/prompt given to the LLM. If empty,
the description field is used. Not required for MCP tools. (Optional)
      "toolType"?: string (enum: api, function, mcp, desktop, flex, quick_reply,
quick_menu) // * `api` - API
* `function` - Function
* `mcp` - MCP
* `desktop` - Desktop
* `flex` - Flex Message
* `quick_reply` - Quick Reply
* `quick_menu` - Quick Menu (Optional)
      "apiUrl"?: string // Optional
      "httpMethod"?: // May have different types (Optional)
      string (enum: get, post, put, delete, patch) // Optional
      "rawHeaders"?: object // Optional
      "rawHeadersMasked": object
      "sensitiveHeaders"?: [ // Optional
        string
      ]
      "globalSensitiveHeaders": [ // Expose platform defaults as read-only
authoring guidance.
        string
      ]
      "rawQueryParams"?: object // Query string parameters appended to every
request of this API tool. Values support the same {{variable}} template rendering
as raw_headers. On key collision with LLM-generated arguments, these values win —
use this field for API keys that must travel in the query string. (Optional)
      "rawQueryParamsMasked": object
      "rawParametersSchema"?: object // Optional
      "functionCode"?: string // Optional
      "organization": string (uuid)
      "createdBy": string (uuid)
      "isGlobal": boolean // If set as global tool, all organizations can use
this tool
      "mcpUrl"?: string // Optional
      "mcpRegistry"?: string (uuid) // Registry backing this MCP tool. Null for
manual-URL MCP tools. (Optional)
      "mcpAllowedTools"?: object // Optional
      "rawMcpHeader"?: object // Default headers used when the Contact has no
matching MCP Credential. (Optional)
      "rawMcpHeaderMasked": object
      "authSubject"?:  // Shared uses the tool level token plus per contact
credentials; contact requires per contact authentication only; caller mints a
```

```
short-lived token for the conversation-bound member (falls back to per contact
credentials when the conversation has no bound member). MCP tools only.

* `shared` - Shared
* `contact` - Contact
* `caller` - Caller (Optional)
      {
      }
      "flexTemplateJson"?: object // FlexMessage JSON template. Required for
FLEX_MESSAGE tools. Stores the full LINE FlexMessage JSON structure (bubble /
carousel / box / text / image / button etc.). (Optional)
      "flexSchema"?: object // AI dynamic field schema for FlexMessage. JSON
object whose keys are field paths parsed from flex_template_json (e.g. text /
image url / button label / button uri / button message). Each value may be either
a plain string (the AI prompt) or an object carrying additional metadata such as
a field tag, e.g. {"prompt": "...", "tag": "title"}. Empty values fall back to
the template default. (Optional)
      "quickReplyConfig"?: object // Authoring config for QUICK_REPLY tools.
Structured JSON describing the chip buttons: static list or dynamic (LLM-
generated) mode, each field either a fixed value or an LLM prompt. (Optional)
      "quickMenuConfig"?: object // Authoring config for QUICK_MENU tools.
Structured JSON describing the persistent input-bar menu rendered by the web chat
only: layout (grid / list), default open state, and 2-6 items each carrying a
display label plus an action payload (send prompt / prefill text / open http(s)
link). (Optional)
      "category"?: string (enum: knowledge_base, web_search, web_fetch,
code_execution, file_processing, image_video_generation, database_query,
third_party_integration, browser_operation, agent_collaboration, other) // *
`knowledge_base` - Knowledge base retrieval
* `web_search` - Web search
* `web_fetch` - Web page fetch
* `code_execution` - Code execution
* `file_processing` - File processing
* `image_video_generation` - Image/video generation
* `database_query` - Database query
* `third_party_integration` - Third-party integration
* `browser_operation` - Browser operation
* `agent_collaboration` - Agent collaboration
* `other` - Other (catch-all) (Optional)
      "displayCopyByLocale"?: object // Optional
      "outputRenderTemplateByLocale"?: object // Optional
      "toolDisplayMode"?: // May have different types (Optional)
      string (enum: full, compact, hidden) // Optional
      "groups"?: [ // Groups this tool is assigned to. Non-owner members must
pick at least one group they belong to. (Optional)
        {
          "id": string (uuid)
          "name": string
        }
```

```
      ]
      "createdAt": string (timestamp)
      "updatedAt": string (timestamp)
      "canUpdate": boolean // Return whether the current user can update this
resource.
      "canDelete": boolean // Return whether the current user can delete this
resource.
    }
  ]
}
```

Example Response Values

```
{
  "count": 123,
  "next": "http://api.example.org/accounts/?page=4",
  "previous": "http://api.example.org/accounts/?page=2",
  "results": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "Response String",
      "displayName": "Response String",
      "description": "Response String",
      "prompt": "Response String",
      "toolType": "api",
      "apiUrl": "Response String",
      "httpMethod": "get",
      "rawHeaders": null,
      "rawHeadersMasked": {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "name": "Example response name",
        "description": "Example response description"
      },
      "sensitiveHeaders": [
        "Response String"
      ],
      "globalSensitiveHeaders": [
        "Response String"
      ],
      "rawQueryParams": null,
      "rawQueryParamsMasked": {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "name": "Example response name",
        "description": "Example response description"
      },
      "rawParametersSchema": null,
      "functionCode": "Response String",
      "organization": "550e8400-e29b-41d4-a716-446655440000",
```

```
      "createdBy": "550e8400-e29b-41d4-a716-446655440000",
      "isGlobal": false,
      "mcpUrl": "Response String",
      "mcpRegistry": "550e8400-e29b-41d4-a716-446655440000",
      "mcpAllowedTools": null,
      "rawMcpHeader": null,
      "rawMcpHeaderMasked": {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "name": "Example response name",
        "description": "Example response description"
      },
      "authSubject": {},
      "flexTemplateJson": null,
      "flexSchema": null,
      "quickReplyConfig": null,
      "quickMenuConfig": null,
      "category": "knowledge_base",
      "displayCopyByLocale": null,
      "outputRenderTemplateByLocale": null,
      "toolDisplayMode": "full",
      "groups": [
        {
          "id": "550e8400-e29b-41d4-a716-446655440000",
          "name": "Response String"
        }
      ],
      "createdAt": "Response String",
      "updatedAt": "Response String",
      "canUpdate": false,
      "canDelete": false
    }
  ]
}
```


Retrieve a Specific Tool

`GET` `/api/v1/tools/{id}`

Parameters

Parameter Name	Required	Type	Description
id	V	string	A UUID string identifying this Tool.

Code Examples

Shell/Bash

```
# API Call Example (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/tools/550e8400-e29b-41d4-a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/tools/550e8400-e29b-41d4-a716-
446655440000/", config)
  .then(response => {
    console.log('Successfully retrieved response:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('An error occurred during the request:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/tools/550e8400-e29b-41d4-a716-
446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("Successfully retrieved response:")
    print(response.json())
except Exception as e:
    print("An error occurred during the request:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->get("https://api.maiagent.ai/api/v1/tools/550e8400-e29b-41d4-a716-446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Successfully retrieved response:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'An error occurred during the request: ' . $e->getMessage();
}
?>
```

Response Content

Status Code: 200

Example Response Schema

```
{
  "id": string (uuid)
  "name"?: // May have different types (Optional)
  string // Tool name may only contain letters, digits, underscores (_) and hyphens (-). Not required for MCP tools; for API tools it is the tool name given to the LLM. (Optional)
  "displayName": string // A name with any characters, used by users for configuration and management.
```

```
  "description"?: string // Tool description shown to users. Not required for MCP
tools. (Optional)
  "prompt"?: string // Tool description/prompt given to the LLM. If empty, the
description field is used. Not required for MCP tools. (Optional)
  "toolType"?: string (enum: api, function, mcp, desktop, flex, quick_reply,
quick_menu) // * `api` - API
* `function` - Function
* `mcp` - MCP
* `desktop` - Desktop
* `flex` - Flex Message
* `quick_reply` - Quick Reply
* `quick_menu` - Quick Menu (Optional)
  "apiUrl"?: string // Optional
  "httpMethod"?: // May have different types (Optional)
  string (enum: get, post, put, delete, patch) // Optional
  "rawHeaders"?: object // Optional
  "rawHeadersMasked": object
  "sensitiveHeaders"?: [ // Optional
    string
  ]
  "globalSensitiveHeaders": [ // Expose platform defaults as read-only authoring
guidance.
    string
  ]
  "rawQueryParams"?: object // Query string parameters appended to every request
of this API tool. Values support the same {{variable}} template rendering as
raw_headers. On key collision with LLM-generated arguments, these values win —
use this field for API keys that must travel in the query string. (Optional)
  "rawQueryParamsMasked": object
  "rawParametersSchema"?: object // Optional
  "functionCode"?: string // Optional
  "organization": string (uuid)
  "createdBy": string (uuid)
  "isGlobal": boolean // If set as global tool, all organizations can use this
tool
  "mcpUrl"?: string // Optional
  "mcpRegistry"?: string (uuid) // Registry backing this MCP tool. Null for
manual-URL MCP tools. (Optional)
  "mcpAllowedTools"?: object // Optional
  "rawMcpHeader"?: object // Default headers used when the Contact has no
matching MCP Credential. (Optional)
  "rawMcpHeaderMasked": object
  "authSubject"?:  // Shared uses the tool level token plus per contact
credentials; contact requires per contact authentication only; caller mints a
short-lived token for the conversation-bound member (falls back to per contact
credentials when the conversation has no bound member). MCP tools only.

* `shared` - Shared
* `contact` - Contact
```

```
* `caller` - Caller (Optional)
  {
  }
  "flexTemplateJson"?: object // FlexMessage JSON template. Required for
FLEX_MESSAGE tools. Stores the full LINE FlexMessage JSON structure (bubble /
carousel / box / text / image / button etc.). (Optional)
  "flexSchema"?: object // AI dynamic field schema for FlexMessage. JSON object
whose keys are field paths parsed from flex_template_json (e.g. text / image url
/ button label / button uri / button message). Each value may be either a plain
string (the AI prompt) or an object carrying additional metadata such as a field
tag, e.g. {"prompt": "...", "tag": "title"}. Empty values fall back to the
template default. (Optional)
  "quickReplyConfig"?: object // Authoring config for QUICK_REPLY tools.
Structured JSON describing the chip buttons: static list or dynamic (LLM-
generated) mode, each field either a fixed value or an LLM prompt. (Optional)
  "quickMenuConfig"?: object // Authoring config for QUICK_MENU tools. Structured
JSON describing the persistent input-bar menu rendered by the web chat only:
layout (grid / list), default open state, and 2-6 items each carrying a display
label plus an action payload (send prompt / prefill text / open http(s) link).
(Optional)
  "category"?: string (enum: knowledge_base, web_search, web_fetch,
code_execution, file_processing, image_video_generation, database_query,
third_party_integration, browser_operation, agent_collaboration, other) // *
`knowledge_base` - Knowledge base retrieval
* `web_search` - Web search
* `web_fetch` - Web page fetch
* `code_execution` - Code execution
* `file_processing` - File processing
* `image_video_generation` - Image/video generation
* `database_query` - Database query
* `third_party_integration` - Third-party integration
* `browser_operation` - Browser operation
* `agent_collaboration` - Agent collaboration
* `other` - Other (catch-all) (Optional)
  "displayCopyByLocale"?: object // Optional
  "outputRenderTemplateByLocale"?: object // Optional
  "toolDisplayMode"?: // May have different types (Optional)
  string (enum: full, compact, hidden) // Optional
  "groups"?: [ // Groups this tool is assigned to. Non-owner members must pick at
least one group they belong to. (Optional)
    {
      "id": string (uuid)
      "name": string
    }
  ]
  "createdAt": string (timestamp)
  "updatedAt": string (timestamp)
  "canUpdate": boolean // Return whether the current user can update this
resource.
```

```
  "canDelete": boolean // Return whether the current user can delete this
resource.
}
```

Example Response Values

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "name": "Response String",
  "displayName": "Response String",
  "description": "Response String",
  "prompt": "Response String",
  "toolType": "api",
  "apiUrl": "Response String",
  "httpMethod": "get",
  "rawHeaders": null,
  "rawHeadersMasked": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Example response name",
    "description": "Example response description"
  },
  "sensitiveHeaders": [
    "Response String"
  ],
  "globalSensitiveHeaders": [
    "Response String"
  ],
  "rawQueryParams": null,
  "rawQueryParamsMasked": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Example response name",
    "description": "Example response description"
  },
  "rawParametersSchema": null,
  "functionCode": "Response String",
  "organization": "550e8400-e29b-41d4-a716-446655440000",
  "createdBy": "550e8400-e29b-41d4-a716-446655440000",
  "isGlobal": false,
  "mcpUrl": "Response String",
  "mcpRegistry": "550e8400-e29b-41d4-a716-446655440000",
  "mcpAllowedTools": null,
  "rawMcpHeader": null,
  "rawMcpHeaderMasked": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Example response name",
    "description": "Example response description"
  },
  "authSubject": {},
```

```
  "flexTemplateJson": null,
  "flexSchema": null,
  "quickReplyConfig": null,
  "quickMenuConfig": null,
  "category": "knowledge_base",
  "displayCopyByLocale": null,
  "outputRenderTemplateByLocale": null,
  "toolDisplayMode": "full",
  "groups": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "Response String"
    }
  ],
  "createdAt": "Response String",
  "updatedAt": "Response String",
  "canUpdate": false,
  "canDelete": false
}
```


Update a Tool

PUT `/api/v1/tools/{id}`

Parameters

Parameter Name	Required	Type	Description
`id`	V	string	A UUID string identifying this Tool.

Request Body

Request Parameters

Field	Type	Required	Description
name	object	No	Tool name may only contain letters, digits, underscores (_) and hyphens (-). Not required for MCP tools; for API tools it is the tool name given to the LLM.
displayName	string	Yes	A name with any characters, used by users for configuration and management.
description	string	No	Tool description shown to users. Not required for MCP tools.
prompt	string	No	Tool description/prompt given to the LLM. If empty, the description field is used. Not required for MCP tools.
toolType	string (enum: api, function, mcp, desktop, flex, quick_reply, quick_menu)	No	`api` : API ; `function` : Function ; `mcp` : MCP ; `desktop` : Desktop ; `flex` : Flex Message ; `quick_reply` : Quick Reply ; `quick_menu` : Quick Menu;
apiUrl	string	No	
httpMethod	object	No	
rawHeaders	object	No	
sensitiveHeaders	array[string]	No	
rawQueryParams	object	No	Query string parameters appended to every request of this API tool. Values support the same {{variable}} template rendering as raw_headers. On key collision with LLM-generated arguments, these values ...

Field	Type	Required	Description
rawParametersSchema	object	No	
functionCode	string	No	
mcpUrl	string	No	
mcpRegistry	string (uuid)	No	Registry backing this MCP tool. Null for manual-URL MCP tools.
mcpAllowedTools	object	No	
rawMcpHeader	object	No	Default headers used when the Contact has no matching MCP Credential.
authSubject	object	No	Shared uses the tool level token plus per contact credentials; contact requires per contact authentication only; caller mints a short-lived token for the conversation-bound member (falls back to per c...
flexTemplateJson	object	No	FlexMessage JSON template. Required for FLEX_MESSAGE tools. Stores the full LINE FlexMessage JSON structure (bubble / carousel / box / text / image / button etc.).
flexSchema	object	No	AI dynamic field schema for FlexMessage. JSON object whose keys are field paths parsed from flex_template_json (e.g. text / image url / button label / button uri / button message). Each value may be e...
quickReplyConfig	object	No	Authoring config for QUICK_REPLY tools. Structured JSON describing the chip

Field	Type	Required	Description
			buttons: static list or dynamic (LLM-generated) mode, each field either a fixed value or an LLM prompt.
quickMenuConfig	object	No	Authoring config for QUICK_MENU tools. Structured JSON describing the persistent input-bar menu rendered by the web chat only: layout (grid / list), default open state, and 2-6 items each carrying a d...
category	string (enum: knowledge_base, web_search, web_fetch, code_execution, file_processing, image_video_generation, database_query, third_party_integration, browser_operation, agent_collaboration, other)	No	`knowledge_base` : Knowledge base retrieval ; `web_search` : Web search ; `web_fetch` : Web page fetch ; `code_execution` : Code execution ; `file_processing` : File processing ; `image_video_generation` : ...
displayCopyByLocale	object	No	
outputRenderTemplateByLocale	object	No	
toolDisplayMode	object	No	
groups	array[IdName]	No	Groups this tool is assigned to. Non-owner members must pick at least one group they belong to.

Example Request Schema

```
{
  "name"?: // May have different types (Optional)
  string // Tool name may only contain letters, digits, underscores (_) and
hyphens (-). Not required for MCP tools; for API tools it is the tool name given
to the LLM. (Optional)
  "displayName": string // A name with any characters, used by users for
```

```
configuration and management.
  "description"?: string // Tool description shown to users. Not required for MCP tools. (Optional)
  "prompt"?: string // Tool description/prompt given to the LLM. If empty, the description field is used. Not required for MCP tools. (Optional)
  "toolType"?: string (enum: api, function, mcp, desktop, flex, quick_reply, quick_menu) // * `api` - API
* `function` - Function
* `mcp` - MCP
* `desktop` - Desktop
* `flex` - Flex Message
* `quick_reply` - Quick Reply
* `quick_menu` - Quick Menu (Optional)
  "apiUrl"?: string // Optional
  "httpMethod"?: // May have different types (Optional)
  string (enum: get, post, put, delete, patch) // Optional
  "rawHeaders"?: object // Optional
  "sensitiveHeaders"?: [ // Optional
    string
  ]
  "rawQueryParams"?: object // Query string parameters appended to every request of this API tool. Values support the same {{variable}} template rendering as raw_headers. On key collision with LLM-generated arguments, these values win — use this field for API keys that must travel in the query string. (Optional)
  "rawParametersSchema"?: object // Optional
  "functionCode"?: string // Optional
  "mcpUrl"?: string // Optional
  "mcpRegistry"?: string (uuid) // Registry backing this MCP tool. Null for manual-URL MCP tools. (Optional)
  "mcpAllowedTools"?: object // Optional
  "rawMcpHeader"?: object // Default headers used when the Contact has no matching MCP Credential. (Optional)
  "authSubject"?:  // Shared uses the tool level token plus per contact credentials; contact requires per contact authentication only; caller mints a short-lived token for the conversation-bound member (falls back to per contact credentials when the conversation has no bound member). MCP tools only.

* `shared` - Shared
* `contact` - Contact
* `caller` - Caller (Optional)
  {
  }
  "flexTemplateJson"?: object // FlexMessage JSON template. Required for FLEX_MESSAGE tools. Stores the full LINE FlexMessage JSON structure (bubble / carousel / box / text / image / button etc.). (Optional)
  "flexSchema"?: object // AI dynamic field schema for FlexMessage. JSON object whose keys are field paths parsed from flex_template_json (e.g. text / image url / button label / button uri / button message). Each value may be either a plain string (the AI prompt) or an object carrying additional metadata such as a field
```

```
tag, e.g. {"prompt": "...", "tag": "title"}. Empty values fall back to the
template default. (Optional)
  "quickReplyConfig"?: object // Authoring config for QUICK_REPLY tools.
Structured JSON describing the chip buttons: static list or dynamic (LLM-
generated) mode, each field either a fixed value or an LLM prompt. (Optional)
  "quickMenuConfig"?: object // Authoring config for QUICK_MENU tools. Structured
JSON describing the persistent input-bar menu rendered by the web chat only:
layout (grid / list), default open state, and 2-6 items each carrying a display
label plus an action payload (send prompt / prefill text / open http(s) link).
(Optional)
  "category"?: string (enum: knowledge_base, web_search, web_fetch,
code_execution, file_processing, image_video_generation, database_query,
third_party_integration, browser_operation, agent_collaboration, other) // *
`knowledge_base` - Knowledge base retrieval
* `web_search` - Web search
* `web_fetch` - Web page fetch
* `code_execution` - Code execution
* `file_processing` - File processing
* `image_video_generation` - Image/video generation
* `database_query` - Database query
* `third_party_integration` - Third-party integration
* `browser_operation` - Browser operation
* `agent_collaboration` - Agent collaboration
* `other` - Other (catch-all) (Optional)
  "displayCopyByLocale"?: object // Optional
  "outputRenderTemplateByLocale"?: object // Optional
  "toolDisplayMode"?: // May have different types (Optional)
  string (enum: full, compact, hidden) // Optional
  "groups"?: [ // Groups this tool is assigned to. Non-owner members must pick at
least one group they belong to. (Optional)
    {
      "id": string (uuid)
    }
  ]
}
```

Example request values

```
{
  "name": null,
  "displayName": "Example string",
  "description": "Example string",
  "prompt": "Example string",
  "toolType": "api",
  "apiUrl": "Example string",
  "httpMethod": null,
  "rawHeaders": null,
  "sensitiveHeaders": [
```

```
    "Example string"
  ],
  "rawQueryParams": null,
  "rawParametersSchema": null,
  "functionCode": "Example string",
  "mcpUrl": "Example string",
  "mcpRegistry": "550e8400-e29b-41d4-a716-446655440000",
  "mcpAllowedTools": null,
  "rawMcpHeader": null,
  "authSubject": {},
  "flexTemplateJson": null,
  "flexSchema": null,
  "quickReplyConfig": null,
  "quickMenuConfig": null,
  "category": "knowledge_base",
  "displayCopyByLocale": null,
  "outputRenderTemplateByLocale": null,
  "toolDisplayMode": null,
  "groups": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000"
    }
  ]
}
```


Code examples

Shell/Bash

```
# API call example (Shell)
curl -X PUT "https://api.maiagent.ai/api/v1/tools/550e8400-e29b-41d4-a716-
446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "name": null,
    "displayName": "Example string",
    "description": "Example string",
    "prompt": "Example string",
    "toolType": "api",
    "apiUrl": "Example string",
    "httpMethod": null,
    "rawHeaders": null,
    "sensitiveHeaders": [
      "Example string"
    ],
    "rawQueryParams": null,
    "rawParametersSchema": null,
    "functionCode": "Example string",
    "mcpUrl": "Example string",
    "mcpRegistry": "550e8400-e29b-41d4-a716-446655440000",
    "mcpAllowedTools": null,
    "rawMcpHeader": null,
    "authSubject": {},
    "flexTemplateJson": null,
    "flexSchema": null,
    "quickReplyConfig": null,
    "quickMenuConfig": null,
    "category": "knowledge_base",
    "displayCopyByLocale": null,
    "outputRenderTemplateByLocale": null,
    "toolDisplayMode": null,
    "groups": [
      {
        "id": "550e8400-e29b-41d4-a716-446655440000"
      }
    ]
  }'
```

```
# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// Request body (payload)
const data = {
    "name": null,
    "displayName": "Example string",
    "description": "Example string",
    "prompt": "Example string",
    "toolType": "api",
    "apiUrl": "Example string",
    "httpMethod": null,
    "rawHeaders": null,
    "sensitiveHeaders": [
      "Example string"
    ],
    "rawQueryParams": null,
    "rawParametersSchema": null,
    "functionCode": "Example string",
    "mcpUrl": "Example string",
    "mcpRegistry": "550e8400-e29b-41d4-a716-446655440000",
    "mcpAllowedTools": null,
    "rawMcpHeader": null,
    "authSubject": {},
    "flexTemplateJson": null,
    "flexSchema": null,
    "quickReplyConfig": null,
    "quickMenuConfig": null,
    "category": "knowledge_base",
    "displayCopyByLocale": null,
    "outputRenderTemplateByLocale": null,
    "toolDisplayMode": null,
    "groups": [
      {
        "id": "550e8400-e29b-41d4-a716-446655440000"
      }
    ]
```

```
  };

axios.put("https://api.maiagent.ai/api/v1/tools/550e8400-e29b-41d4-a716-
446655440000/", data, config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('An error occurred during the request:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/tools/550e8400-e29b-41d4-a716-
446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# Request body (payload)
data = {
    "name": None,
    "displayName": "Example string",
    "description": "Example string",
    "prompt": "Example string",
    "toolType": "api",
    "apiUrl": "Example string",
    "httpMethod": None,
    "rawHeaders": None,
    "sensitiveHeaders": [
        "Example string"
    ],
    "rawQueryParams": None,
    "rawParametersSchema": None,
    "functionCode": "Example string",
    "mcpUrl": "Example string",
    "mcpRegistry": "550e8400-e29b-41d4-a716-446655440000",
    "mcpAllowedTools": None,
    "rawMcpHeader": None,
    "authSubject": {},
    "flexTemplateJson": None,
    "flexSchema": None,
    "quickReplyConfig": None,
    "quickMenuConfig": None,
    "category": "knowledge_base",
    "displayCopyByLocale": None,
    "outputRenderTemplateByLocale": None,
    "toolDisplayMode": None,
    "groups": [
        {
            "id": "550e8400-e29b-41d4-a716-446655440000"
        }
    ]
}
```

```
response = requests.put(url, json=data, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("An error occurred during the request:", e)
```

PHP

```
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->put("https://api.maiagent.ai/api/v1/tools/550e8400-
e29b-41d4-a716-446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'name' => null,
            'displayName' => 'Example string',
            'description' => 'Example string',
            'prompt' => 'Example string',
            'toolType' => 'api',
            'apiUrl' => 'Example string',
            'httpMethod' => null,
            'rawHeaders' => null,
            'sensitiveHeaders' => [
                'Example string'
            ],
            'rawQueryParams' => null,
            'rawParametersSchema' => null,
            'functionCode' => 'Example string',
            'mcpUrl' => 'Example string',
            'mcpRegistry' => '550e8400-e29b-41d4-a716-446655440000',
            'mcpAllowedTools' => null,
            'rawMcpHeader' => null,
            'authSubject' => new \stdClass(),
            'flexTemplateJson' => null,
            'flexSchema' => null,
            'quickReplyConfig' => null,
            'quickMenuConfig' => null,
            'category' => 'knowledge_base',
            'displayCopyByLocale' => null,
            'outputRenderTemplateByLocale' => null,
            'toolDisplayMode' => null,
            'groups' => [
                [
                    'id' => '550e8400-e29b-41d4-a716-446655440000'
                ]
```

```
            ]
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'An error occurred during the request: ' . $e->getMessage();
}
?>
```

Response body

Status code: 200

Example response structure

```
{
  "id": string (uuid)
  "name"?: // May have different types (Optional)
  string // Tool name may only contain letters, digits, underscores (_) and
hyphens (-). Not required for MCP tools; for API tools it is the tool name given
to the LLM. (Optional)
  "displayName": string // A name with any characters, used by users for
configuration and management.
  "description"?: string // Tool description shown to users. Not required for MCP
tools. (Optional)
  "prompt"?: string // Tool description/prompt given to the LLM. If empty, the
description field is used. Not required for MCP tools. (Optional)
  "toolType"?: string (enum: api, function, mcp, desktop, flex, quick_reply,
quick_menu) // * `api` - API
* `function` - Function
* `mcp` - MCP
* `desktop` - Desktop
* `flex` - Flex Message
* `quick_reply` - Quick Reply
* `quick_menu` - Quick Menu (Optional)
  "apiUrl"?: string // Optional
  "httpMethod"?: // May have different types (Optional)
  string (enum: get, post, put, delete, patch) // Optional
```

```
  "rawHeaders"?: object // Optional
  "rawHeadersMasked": object
  "sensitiveHeaders"?: [ // Optional
    string
  ]
  "globalSensitiveHeaders": [ // Expose platform defaults as read-only authoring guidance.
    string
  ]
  "rawQueryParams"?: object // Query string parameters appended to every request of this API tool. Values support the same {{variable}} template rendering as raw_headers. On key collision with LLM-generated arguments, these values win — use this field for API keys that must travel in the query string. (Optional)
  "rawQueryParamsMasked": object
  "rawParametersSchema"?: object // Optional
  "functionCode"?: string // Optional
  "organization": string (uuid)
  "createdBy": string (uuid)
  "isGlobal": boolean // If set as global tool, all organizations can use this tool
  "mcpUrl"?: string // Optional
  "mcpRegistry"?: string (uuid) // Registry backing this MCP tool. Null for manual-URL MCP tools. (Optional)
  "mcpAllowedTools"?: object // Optional
  "rawMcpHeader"?: object // Default headers used when the Contact has no matching MCP Credential. (Optional)
  "rawMcpHeaderMasked": object
  "authSubject"?:  // Shared uses the tool level token plus per contact credentials; contact requires per contact authentication only; caller mints a short-lived token for the conversation-bound member (falls back to per contact credentials when the conversation has no bound member). MCP tools only.

* `shared` - Shared
* `contact` - Contact
* `caller` - Caller (Optional)
  {
  }
  "flexTemplateJson"?: object // FlexMessage JSON template. Required for FLEX_MESSAGE tools. Stores the full LINE FlexMessage JSON structure (bubble / carousel / box / text / image / button etc.). (Optional)
  "flexSchema"?: object // AI dynamic field schema for FlexMessage. JSON object whose keys are field paths parsed from flex_template_json (e.g. text / image url / button label / button uri / button message). Each value may be either a plain string (the AI prompt) or an object carrying additional metadata such as a field tag, e.g. {"prompt": "...", "tag": "title"}. Empty values fall back to the template default. (Optional)
  "quickReplyConfig"?: object // Authoring config for QUICK_REPLY tools. Structured JSON describing the chip buttons: static list or dynamic (LLM-generated) mode, each field either a fixed value or an LLM prompt. (Optional)
```

```
  "quickMenuConfig"?: object // Authoring config for QUICK_MENU tools. Structured
JSON describing the persistent input-bar menu rendered by the web chat only:
layout (grid / list), default open state, and 2-6 items each carrying a display
label plus an action payload (send prompt / prefill text / open http(s) link).
(Optional)
  "category"?: string (enum: knowledge_base, web_search, web_fetch,
code_execution, file_processing, image_video_generation, database_query,
third_party_integration, browser_operation, agent_collaboration, other) // *
`knowledge_base` - Knowledge base retrieval
* `web_search` - Web search
* `web_fetch` - Web page fetch
* `code_execution` - Code execution
* `file_processing` - File processing
* `image_video_generation` - Image/video generation
* `database_query` - Database query
* `third_party_integration` - Third-party integration
* `browser_operation` - Browser operation
* `agent_collaboration` - Agent collaboration
* `other` - Other (catch-all) (Optional)
  "displayCopyByLocale"?: object // Optional
  "outputRenderTemplateByLocale"?: object // Optional
  "toolDisplayMode"?: // May have different types (Optional)
  string (enum: full, compact, hidden) // Optional
  "groups"?: [ // Groups this tool is assigned to. Non-owner members must pick at
least one group they belong to. (Optional)
    {
      "id": string (uuid)
      "name": string
    }
  ]
  "createdAt": string (timestamp)
  "updatedAt": string (timestamp)
  "canUpdate": boolean // Return whether the current user can update this
resource.
  "canDelete": boolean // Return whether the current user can delete this
resource.
}
```

Example response values

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "name": "Response string",
  "displayName": "Response string",
  "description": "Response string",
  "prompt": "Response string",
  "toolType": "api",
  "apiUrl": "Response string",
```

```
  "httpMethod": "get",
  "rawHeaders": null,
  "rawHeadersMasked": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Example response name",
    "description": "Example response description"
  },
  "sensitiveHeaders": [
    "Response string"
  ],
  "globalSensitiveHeaders": [
    "Response string"
  ],
  "rawQueryParams": null,
  "rawQueryParamsMasked": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Example response name",
    "description": "Example response description"
  },
  "rawParametersSchema": null,
  "functionCode": "Response string",
  "organization": "550e8400-e29b-41d4-a716-446655440000",
  "createdBy": "550e8400-e29b-41d4-a716-446655440000",
  "isGlobal": false,
  "mcpUrl": "Response string",
  "mcpRegistry": "550e8400-e29b-41d4-a716-446655440000",
  "mcpAllowedTools": null,
  "rawMcpHeader": null,
  "rawMcpHeaderMasked": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Example response name",
    "description": "Example response description"
  },
  "authSubject": {},
  "flexTemplateJson": null,
  "flexSchema": null,
  "quickReplyConfig": null,
  "quickMenuConfig": null,
  "category": "knowledge_base",
  "displayCopyByLocale": null,
  "outputRenderTemplateByLocale": null,
  "toolDisplayMode": "full",
  "groups": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "Response string"
    }
  ],
  "createdAt": "Response string",
```

```
  "updatedAt": "Response string",
  "canUpdate": false,
  "canDelete": false
}
```


Partially update a tool

PATCH `/api/v1/tools/{id}`

Parameters

Parameter name	Required	Type	Description
`id`	V	string	A UUID string identifying this Tool.

Request body

Request parameters

Field	Type	Required	Description
name	object	No	Tool name may only contain letters, digits, underscores (_) and hyphens (-). Not required for MCP tools; for API tools it is the tool name given to the LLM.
displayName	string	No	A name with any characters, used by users for configuration and management.
description	string	No	Tool description shown to users. Not required for

Field	Type	Required	Description
			MCP tools.
prompt	string	No	Tool description/prompt given to the LLM. If empty, the description field is used. Not required for MCP tools.
toolType	string (enum: api, function, mcp, desktop, flex, quick_reply, quick_menu)	No	`api` : API ; `function` : Function ; `mcp` : MCP ; `desktop` : Desktop ; `flex` : Flex Message ; `quick_reply` : Quick Reply ; `quick_menu` : Quick Menu;
apiUrl	string	No	
httpMethod	object	No	
rawHeaders	object	No	
sensitiveHeaders	array[string]	No	
rawQueryParams	object	No	Query string parameters appended to every request of this API tool. Values support the same {{variable}} template rendering as raw_headers. On key collision with LLM-generated arguments, these values ...
rawParametersSchema	object	No	
functionCode	string	No	
mcpUrl	string	No	
mcpRegistry	string (uuid)	No	Registry backing this MCP tool. Null for manual-URL MCP tools.
mcpAllowedTools	object	No	
rawMcpHeader	object	No	Default headers used when the Contact has no matching MCP Credential.

Field	Type	Required	Description
authSubject	object	No	Shared uses the tool level token plus per contact credentials; contact requires per contact authentication only; caller mints a short-lived token for the conversation-bound member (falls back to per c...
flexTemplateJson	object	No	FlexMessage JSON template. Required for FLEX_MESSAGE tools. Stores the full LINE FlexMessage JSON structure (bubble / carousel / box / text / image / button etc.).
flexSchema	object	No	AI dynamic field schema for FlexMessage. JSON object whose keys are field paths parsed from flex_template_json (e.g. text / image url / button label / button uri / button message). Each value may be e...
quickReplyConfig	object	No	Authoring config for QUICK_REPLY tools. Structured JSON describing the chip buttons: static list or dynamic (LLM-generated) mode, each field either a fixed value or an LLM prompt.
quickMenuConfig	object	No	Authoring config for QUICK_MENU tools. Structured JSON describing the persistent input-bar menu rendered by the web chat only: layout (grid / list), default open state, and 2-6 items each carrying a d...

Field	Type	Required	Description
category	string (enum: knowledge_base, web_search, web_fetch, code_execution, file_processing, image_video_generation, database_query, third_party_integration, browser_operation, agent_collaboration, other)	No	`knowledge_base` : Knowledge base retrieval ; `web_search` : Web search ; `web_fetch` : Web page fetch ; `code_execution` : Code execution ; `file_processing` : File processing ; `image_video_generation` : ...
displayCopyByLocale	object	No	
outputRenderTemplateByLocale	object	No	
toolDisplayMode	object	No	
groups	array[IdName]	No	Groups this tool is assigned to. Non-owner members must pick at least one group they belong to.

Example request structure

```
{
  "name"?: // May have different types (optional)
  string // Tool name may only contain letters, digits, underscores (_) and
hyphens (-). Not required for MCP tools; for API tools it is the tool name given
to the LLM. (optional)
  "displayName"?: string // A name with any characters, used by users for
configuration and management. (optional)
  "description"?: string // Tool description shown to users. Not required for MCP
tools. (optional)
  "prompt"?: string // Tool description/prompt given to the LLM. If empty, the
description field is used. Not required for MCP tools. (optional)
  "toolType"?: string (enum: api, function, mcp, desktop, flex, quick_reply,
quick_menu) // * `api` - API
* `function` - Function
* `mcp` - MCP
* `desktop` - Desktop
* `flex` - Flex Message
* `quick_reply` - Quick Reply
* `quick_menu` - Quick Menu (optional)
  "apiUrl"?: string // optional
  "httpMethod"?: // May have different types (optional)
```

```
  string (enum: get, post, put, delete, patch) // optional
  "rawHeaders"?: object // optional
  "sensitiveHeaders"?: [ // optional
    string
  ]
  "rawQueryParams"?: object // Query string parameters appended to every request of this API tool. Values support the same {{variable}} template rendering as raw_headers. On key collision with LLM-generated arguments, these values win — use this field for API keys that must travel in the query string. (optional)
  "rawParametersSchema"?: object // optional
  "functionCode"?: string // optional
  "mcpUrl"?: string // optional
  "mcpRegistry"?: string (uuid) // Registry backing this MCP tool. Null for manual-URL MCP tools. (optional)
  "mcpAllowedTools"?: object // optional
  "rawMcpHeader"?: object // Default headers used when the Contact has no matching MCP Credential. (optional)
  "authSubject"?:  // Shared uses the tool level token plus per contact credentials; contact requires per contact authentication only; caller mints a short-lived token for the conversation-bound member (falls back to per contact credentials when the conversation has no bound member). MCP tools only.

* `shared` - Shared
* `contact` - Contact
* `caller` - Caller (optional)
  {
  }
  "flexTemplateJson"?: object // FlexMessage JSON template. Required for FLEX_MESSAGE tools. Stores the full LINE FlexMessage JSON structure (bubble / carousel / box / text / image / button etc.). (optional)
  "flexSchema"?: object // AI dynamic field schema for FlexMessage. JSON object whose keys are field paths parsed from flex_template_json (e.g. text / image url / button label / button uri / button message). Each value may be either a plain string (the AI prompt) or an object carrying additional metadata such as a field tag, e.g. {"prompt": "...", "tag": "title"}. Empty values fall back to the template default. (optional)
  "quickReplyConfig"?: object // Authoring config for QUICK_REPLY tools. Structured JSON describing the chip buttons: static list or dynamic (LLM-generated) mode, each field either a fixed value or an LLM prompt. (optional)
  "quickMenuConfig"?: object // Authoring config for QUICK_MENU tools. Structured JSON describing the persistent input-bar menu rendered by the web chat only: layout (grid / list), default open state, and 2-6 items each carrying a display label plus an action payload (send prompt / prefill text / open http(s) link). (optional)
  "category"?: string (enum: knowledge_base, web_search, web_fetch, code_execution, file_processing, image_video_generation, database_query, third_party_integration, browser_operation, agent_collaboration, other) // * `knowledge_base` - Knowledge base retrieval
* `web_search` - Web search
```

```
* `web_fetch` - Web page fetch
* `code_execution` - Code execution
* `file_processing` - File processing
* `image_video_generation` - Image/video generation
* `database_query` - Database query
* `third_party_integration` - Third-party integration
* `browser_operation` - Browser operation
* `agent_collaboration` - Agent collaboration
* `other` - Other (catch-all) (optional)
  "displayCopyByLocale"?: object // optional
  "outputRenderTemplateByLocale"?: object // optional
  "toolDisplayMode"?: // May have different types (optional)
  string (enum: full, compact, hidden) // optional
  "groups"?: [ // Groups this tool is assigned to. Non-owner members must pick at
least one group they belong to. (optional)
    {
      "id": string (uuid)
    }
  ]
}
```

Example request values

```
{
  "name": null,
  "displayName": "Example string",
  "description": "Example string",
  "prompt": "Example string",
  "toolType": "api",
  "apiUrl": "Example string",
  "httpMethod": null,
  "rawHeaders": null,
  "sensitiveHeaders": [
    "Example string"
  ],
  "rawQueryParams": null,
  "rawParametersSchema": null,
  "functionCode": "Example string",
  "mcpUrl": "Example string",
  "mcpRegistry": "550e8400-e29b-41d4-a716-446655440000",
  "mcpAllowedTools": null,
  "rawMcpHeader": null,
  "authSubject": {},
  "flexTemplateJson": null,
  "flexSchema": null,
  "quickReplyConfig": null,
  "quickMenuConfig": null,
  "category": "knowledge_base",
```

```
  "displayCopyByLocale": null,
  "outputRenderTemplateByLocale": null,
  "toolDisplayMode": null,
  "groups": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000"
    }
  ]
}
```


Code examples

Shell/Bash

```
# API call example (Shell)
curl -X PATCH "https://api.maiagent.ai/api/v1/tools/550e8400-e29b-41d4-a716-
446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "name": null,
    "displayName": "Example string",
    "description": "Example string",
    "prompt": "Example string",
    "toolType": "api",
    "apiUrl": "Example string",
    "httpMethod": null,
    "rawHeaders": null,
    "sensitiveHeaders": [
      "Example string"
    ],
    "rawQueryParams": null,
    "rawParametersSchema": null,
    "functionCode": "Example string",
    "mcpUrl": "Example string",
    "mcpRegistry": "550e8400-e29b-41d4-a716-446655440000",
    "mcpAllowedTools": null,
    "rawMcpHeader": null,
    "authSubject": {},
    "flexTemplateJson": null,
    "flexSchema": null,
    "quickReplyConfig": null,
    "quickMenuConfig": null,
    "category": "knowledge_base",
    "displayCopyByLocale": null,
    "outputRenderTemplateByLocale": null,
    "toolDisplayMode": null,
    "groups": [
      {
        "id": "550e8400-e29b-41d4-a716-446655440000"
      }
    ]
  }'
```

```
# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// Request payload
const data = {
    "name": null,
    "displayName": "Example string",
    "description": "Example string",
    "prompt": "Example string",
    "toolType": "api",
    "apiUrl": "Example string",
    "httpMethod": null,
    "rawHeaders": null,
    "sensitiveHeaders": [
      "Example string"
    ],
    "rawQueryParams": null,
    "rawParametersSchema": null,
    "functionCode": "Example string",
    "mcpUrl": "Example string",
    "mcpRegistry": "550e8400-e29b-41d4-a716-446655440000",
    "mcpAllowedTools": null,
    "rawMcpHeader": null,
    "authSubject": {},
    "flexTemplateJson": null,
    "flexSchema": null,
    "quickReplyConfig": null,
    "quickMenuConfig": null,
    "category": "knowledge_base",
    "displayCopyByLocale": null,
    "outputRenderTemplateByLocale": null,
    "toolDisplayMode": null,
    "groups": [
      {
        "id": "550e8400-e29b-41d4-a716-446655440000"
      }
    ]
```

```
  };

axios.patch("https://api.maiagent.ai/api/v1/tools/550e8400-e29b-41d4-a716-
446655440000/", data, config)
  .then(response => {
    console.log('Response retrieved successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('An error occurred during the request:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/tools/550e8400-e29b-41d4-a716-
446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# Request payload
data = {
    "name": None,
    "displayName": "Example string",
    "description": "Example string",
    "prompt": "Example string",
    "toolType": "api",
    "apiUrl": "Example string",
    "httpMethod": None,
    "rawHeaders": None,
    "sensitiveHeaders": [
        "Example string"
    ],
    "rawQueryParams": None,
    "rawParametersSchema": None,
    "functionCode": "Example string",
    "mcpUrl": "Example string",
    "mcpRegistry": "550e8400-e29b-41d4-a716-446655440000",
    "mcpAllowedTools": None,
    "rawMcpHeader": None,
    "authSubject": {},
    "flexTemplateJson": None,
    "flexSchema": None,
    "quickReplyConfig": None,
    "quickMenuConfig": None,
    "category": "knowledge_base",
    "displayCopyByLocale": None,
    "outputRenderTemplateByLocale": None,
    "toolDisplayMode": None,
    "groups": [
        {
            "id": "550e8400-e29b-41d4-a716-446655440000"
        }
    ]
}
```

```
response = requests.patch(url, json=data, headers=headers)
try:
    print("Response retrieved successfully:")
    print(response.json())
except Exception as e:
    print("An error occurred during the request:", e)
```

PHP

```
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>patch("https://api.maiagent.ai/api/v1/tools/550e8400-e29b-41d4-a716-
446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'name' => null,
            'displayName' => 'Example string',
            'description' => 'Example string',
            'prompt' => 'Example string',
            'toolType' => 'api',
            'apiUrl' => 'Example string',
            'httpMethod' => null,
            'rawHeaders' => null,
            'sensitiveHeaders' => [
                'Example string'
            ],
            'rawQueryParams' => null,
            'rawParametersSchema' => null,
            'functionCode' => 'Example string',
            'mcpUrl' => 'Example string',
            'mcpRegistry' => '550e8400-e29b-41d4-a716-446655440000',
            'mcpAllowedTools' => null,
            'rawMcpHeader' => null,
            'authSubject' => new \stdClass(),
            'flexTemplateJson' => null,
            'flexSchema' => null,
            'quickReplyConfig' => null,
            'quickMenuConfig' => null,
            'category' => 'knowledge_base',
            'displayCopyByLocale' => null,
            'outputRenderTemplateByLocale' => null,
            'toolDisplayMode' => null,
            'groups' => [
                [
                    'id' => '550e8400-e29b-41d4-a716-446655440000'
```

```
                ]
            ]
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response retrieved successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'An error occurred during the request: ' . $e->getMessage();
}
?>
```

Response body

Status code: 200

Example response structure

```
{
  "id": string (uuid)
  "name"?: // May have different types (optional)
  string // Tool name may only contain letters, digits, underscores (_) and
hyphens (-). Not required for MCP tools; for API tools it is the tool name given
to the LLM. (optional)
  "displayName": string // A name with any characters, used by users for
configuration and management.
  "description"?: string // Tool description shown to users. Not required for MCP
tools. (optional)
  "prompt"?: string // Tool description/prompt given to the LLM. If empty, the
description field is used. Not required for MCP tools. (optional)
  "toolType"?: string (enum: api, function, mcp, desktop, flex, quick_reply,
quick_menu) // * `api` - API
* `function` - Function
* `mcp` - MCP
* `desktop` - Desktop
* `flex` - Flex Message
* `quick_reply` - Quick Reply
* `quick_menu` - Quick Menu (optional)
  "apiUrl"?: string // optional
  "httpMethod"?: // May have different types (optional)
```

```
  string (enum: get, post, put, delete, patch) // optional
  "rawHeaders"?: object // optional
  "rawHeadersMasked": object
  "sensitiveHeaders"?: [ // optional
    string
  ]
  "globalSensitiveHeaders": [ // Expose platform defaults as read-only authoring
guidance.
    string
  ]
  "rawQueryParams"?: object // Query string parameters appended to every request
of this API tool. Values support the same {{variable}} template rendering as
raw_headers. On key collision with LLM-generated arguments, these values win —
use this field for API keys that must travel in the query string. (optional)
  "rawQueryParamsMasked": object
  "rawParametersSchema"?: object // optional
  "functionCode"?: string // optional
  "organization": string (uuid)
  "createdBy": string (uuid)
  "isGlobal": boolean // If set as global tool, all organizations can use this
tool
  "mcpUrl"?: string // optional
  "mcpRegistry"?: string (uuid) // Registry backing this MCP tool. Null for
manual-URL MCP tools. (optional)
  "mcpAllowedTools"?: object // optional
  "rawMcpHeader"?: object // Default headers used when the Contact has no
matching MCP Credential. (optional)
  "rawMcpHeaderMasked": object
  "authSubject"?:  // Shared uses the tool level token plus per contact
credentials; contact requires per contact authentication only; caller mints a
short-lived token for the conversation-bound member (falls back to per contact
credentials when the conversation has no bound member). MCP tools only.

* `shared` - Shared
* `contact` - Contact
* `caller` - Caller (optional)
  {
  }
  "flexTemplateJson"?: object // FlexMessage JSON template. Required for
FLEX_MESSAGE tools. Stores the full LINE FlexMessage JSON structure (bubble /
carousel / box / text / image / button etc.). (optional)
  "flexSchema"?: object // AI dynamic field schema for FlexMessage. JSON object
whose keys are field paths parsed from flex_template_json (e.g. text / image url
/ button label / button uri / button message). Each value may be either a plain
string (the AI prompt) or an object carrying additional metadata such as a field
tag, e.g. {"prompt": "...", "tag": "title"}. Empty values fall back to the
template default. (optional)
  "quickReplyConfig"?: object // Authoring config for QUICK_REPLY tools.
Structured JSON describing the chip buttons: static list or dynamic (LLM-
```

```
generated) mode, each field either a fixed value or an LLM prompt. (optional)
  "quickMenuConfig"?: object // Authoring config for QUICK_MENU tools. Structured
JSON describing the persistent input-bar menu rendered by the web chat only:
layout (grid / list), default open state, and 2-6 items each carrying a display
label plus an action payload (send prompt / prefill text / open http(s) link).
(optional)
  "category"?: string (enum: knowledge_base, web_search, web_fetch,
code_execution, file_processing, image_video_generation, database_query,
third_party_integration, browser_operation, agent_collaboration, other) // *
`knowledge_base` - Knowledge base retrieval
* `web_search` - Web search
* `web_fetch` - Web page fetch
* `code_execution` - Code execution
* `file_processing` - File processing
* `image_video_generation` - Image/video generation
* `database_query` - Database query
* `third_party_integration` - Third-party integration
* `browser_operation` - Browser operation
* `agent_collaboration` - Agent collaboration
* `other` - Other (catch-all) (optional)
  "displayCopyByLocale"?: object // optional
  "outputRenderTemplateByLocale"?: object // optional
  "toolDisplayMode"?: // May have different types (optional)
  string (enum: full, compact, hidden) // optional
  "groups"?: [ // Groups this tool is assigned to. Non-owner members must pick at
least one group they belong to. (optional)
    {
      "id": string (uuid)
      "name": string
    }
  ]
  "createdAt": string (timestamp)
  "updatedAt": string (timestamp)
  "canUpdate": boolean // Return whether the current user can update this
resource.
  "canDelete": boolean // Return whether the current user can delete this
resource.
}
```

Example response values

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "name": "Response string",
  "displayName": "Response string",
  "description": "Response string",
  "prompt": "Response string",
  "toolType": "api",
```

```
  "apiUrl": "Response string",
  "httpMethod": "get",
  "rawHeaders": null,
  "rawHeadersMasked": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Example response name",
    "description": "Example response description"
  },
  "sensitiveHeaders": [
    "Response string"
  ],
  "globalSensitiveHeaders": [
    "Response string"
  ],
  "rawQueryParams": null,
  "rawQueryParamsMasked": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Example response name",
    "description": "Example response description"
  },
  "rawParametersSchema": null,
  "functionCode": "Response string",
  "organization": "550e8400-e29b-41d4-a716-446655440000",
  "createdBy": "550e8400-e29b-41d4-a716-446655440000",
  "isGlobal": false,
  "mcpUrl": "Response string",
  "mcpRegistry": "550e8400-e29b-41d4-a716-446655440000",
  "mcpAllowedTools": null,
  "rawMcpHeader": null,
  "rawMcpHeaderMasked": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Example response name",
    "description": "Example response description"
  },
  "authSubject": {},
  "flexTemplateJson": null,
  "flexSchema": null,
  "quickReplyConfig": null,
  "quickMenuConfig": null,
  "category": "knowledge_base",
  "displayCopyByLocale": null,
  "outputRenderTemplateByLocale": null,
  "toolDisplayMode": "full",
  "groups": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "Response string"
    }
  ],
```

```
  "createdAt": "Response string",
  "updatedAt": "Response string",
  "canUpdate": false,
  "canDelete": false
}
```


Delete a tool

DELETE `/api/v1/tools/{id}`

Parameters

Parameter name	Required	Type	Description
`id`	V	string	A UUID string identifying this Tool.

Code examples

Shell/Bash

```
# API call example (Shell)
curl -X DELETE "https://api.maiagent.ai/api/v1/tools/550e8400-e29b-41d4-
a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

// Request payload
const data = null;

axios.delete("https://api.maiagent.ai/api/v1/tools/550e8400-e29b-41d4-a716-446655440000/", data, config)
  .then(response => {
    console.log('Response retrieved successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('An error occurred during the request:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/tools/550e8400-e29b-41d4-a716-
446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.delete(url, headers=headers)
try:
    print("Response retrieved successfully:")
    print(response.json())
except Exception as e:
    print("An error occurred during the request:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>delete("https://api.maiagent.ai/api/v1/tools/550e8400-e29b-41d4-a716-
446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response retrieved successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'An error occurred during the request: ' . $e->getMessage();
}
?>
```

Response body

Status code	Description
204	No response body

List Available Tools

POST `/api/v1/tools/available-tools/`

Request body

Request parameters

Field	Type	Required	Description
mcpUrl	string	Yes	MCP server URL (required)
rawMcpHeader	object	No	MCP Header (JSON format)
mcpAllowedTools	array[string]	No	List of allowed MCP tools
toolId	string (uuid)	No	Tool ID for per-member OAuth token lookup

Example request schema

```
{
  "mcpUrl": string // MCP server URL (required)
  "rawMcpHeader"?: object // MCP Header (JSON format) (Optional)
  "mcpAllowedTools"?: [ // List of allowed MCP tools (Optional)
    string
  ]
  "toolId"?: string (uuid) // Tool ID for per-member OAuth token lookup
(Optional)
}
```

Example request values

```
{
  "mcpUrl": "Example string",
  "rawMcpHeader": null,
  "mcpAllowedTools": [
    "Example string"
  ],
  "toolId": "550e8400-e29b-41d4-a716-446655440000"
}
```

Code Examples

Shell/Bash

```
# API call example (Shell)
curl -X POST "https://api.maiagent.ai/api/v1/tools/available-tools/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "mcpUrl": "Example string",
    "rawMcpHeader": null,
    "mcpAllowedTools": [
      "Example string"
    ],
    "toolId": "550e8400-e29b-41d4-a716-446655440000"
  }'

# Before running, replace YOUR_API_KEY and verify the request data.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// Request body (payload)
const data = {
    "mcpUrl": "Example string",
    "rawMcpHeader": null,
    "mcpAllowedTools": [
      "Example string"
    ],
    "toolId": "550e8400-e29b-41d4-a716-446655440000"
  };

axios.post("https://api.maiagent.ai/api/v1/tools/available-tools/", data,
config)
  .then(response => {
    console.log('Successfully received response:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/tools/available-tools/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# Request body (payload)
data = {
    "mcpUrl": "Example string",
    "rawMcpHeader": None,
    "mcpAllowedTools": [
        "Example string"
    ],
    "toolId": "550e8400-e29b-41d4-a716-446655440000"
}

response = requests.post(url, json=data, headers=headers)
try:
    print("Successfully received response:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>post("https://api.maiagent.ai/api/v1/tools/available-tools/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'mcpUrl' => 'Example string',
            'rawMcpHeader' => null,
            'mcpAllowedTools' => [
                'Example string'
            ],
            'toolId' => '550e8400-e29b-41d4-a716-446655440000'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Successfully received response:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response Body

Status Code: 200

Example Response Schema

```
{
  "mcpUrl": string // MCP server URL (required)
  "rawMcpHeader"?: object // MCP Header (JSON format) (Optional)
  "mcpAllowedTools"?: [ // List of allowed MCP tools (Optional)
    string
  ]
  "toolId"?: string (uuid) // Tool ID for per-member OAuth token lookup
(Optional)
  "availableTools": [ // List of all available MCP tools
    string
  ]
  "error":  // Reason for failure to retrieve tools: {code, message}; code is
url_rejected/invalid_header/dns_error/connect_error/tls_error/auth_error/
timeout_error/handshake_error/unknown_error. This is null when the connection
succeeds (including when the server has no tools); it is always null for the
deprecated GET endpoint
  {
    "code": string // url_rejected / invalid_header / dns_error / connect_error /
tls_error / auth_error / timeout_error / handshake_error / unknown_error
    "message": string // Reason translated into the user's language, ready to
display
  }
}
```

Example Response Values

```
{
  "mcpUrl": "Response string",
  "rawMcpHeader": null,
  "mcpAllowedTools": [
    "Response string"
  ],
  "toolId": "550e8400-e29b-41d4-a716-446655440000",
  "availableTools": [
    "Response string"
  ],
  "error": {
    "code": "Response string",
    "message": "Response string"
  }
}
```

Status Code: 400

Example Response Schema

```
{
  "detail"?: string // Optional
}
```

Example Response Values

```
{
  "detail": "Response string"
}
```

Create connector

POST `/api/v1/connectors/`

Request body

Request parameters

Field	Type	Required	Description
mcpRegistryId	string (uuid)	Yes	
displayName	string	No	Custom display name for this connector (defaults to MCP Registry name)
description	string	No	Custom description for this connector (defaults to MCP Registry description)
defaultCategory	object	No	Org-level override of the MCP Registry default category for this connector's dynamic tools. Empty = use the MCP Registry default_category. `knowledge_base` : Knowledge base retrieval ; `web_search` : We...

Field	Type	Required	Description
defaultDisplayGroupNameByLocale	object	No	Locale-keyed server-level default group headline shown in chat for this connector's dynamic MCP tools (those without an individual Tool row). Shape: {"": str}. The headline for the conversatio...
defaultToolIcon	string	No	Server-level default icon identifier (a frontend icon key, not an uploaded image) for this connector's dynamic MCP tools. Empty = frontend uses its default MCP icon. Streamed as toolIcon.
authHeaders	object	No	
allowedContextDataKeys	object	No	Allowlist of webchat contextData keys this connector may render into auth_headers through {{context_data.}}. An empty list disables the feature for this connector: the placeholder is left verbati...
exposedMcpTools	object	No	Allowlist of MCP tool names this connector exposes (to the agent and to SEP-1865 UI cards). Empty list = expose all of the server tools. Use this to limit a connector to a safe subset (e.g. read-only ...
isEnabled	boolean	No	Whether this connector is enabled for contacts in the organization

Example request schema

```
{
  "mcpRegistryId": string (uuid)
  "displayName"?: string // Custom display name for this connector (defaults to
MCP Registry name) (Optional)
  "description"?: string // Custom description for this connector (defaults to
MCP Registry description) (Optional)
  "defaultCategory"?: // May have different types (Optional)
  string (enum: knowledge_base, web_search, web_fetch, code_execution,
file_processing, image_video_generation, database_query, third_party_integration,
browser_operation, agent_collaboration, other) // Org-level override of the MCP
Registry default category for this connector's dynamic tools. Empty = use the MCP
```

```
Registry default_category.

* `knowledge_base` - Knowledge base retrieval
* `web_search` - Web search
* `web_fetch` - Web page fetch
* `code_execution` - Code execution
* `file_processing` - File processing
* `image_video_generation` - Image/video generation
* `database_query` - Database query
* `third_party_integration` - Third-party integration
* `browser_operation` - Browser operation
* `agent_collaboration` - Agent collaboration
* `other` - Other (catch-all) (Optional)
  "defaultDisplayGroupNameByLocale"?: object // Locale-keyed server-level default
group headline shown in chat for this connector's dynamic MCP tools (those
without an individual Tool row). Shape: {"<locale>": str}. The headline for the
conversation locale is resolved server-side (see
whizchat.tools.services.tool_category.resolve_localized_text): requested locale -
> settings.LANGUAGE_CODE locale -> empty, then streamed verbatim as
displayGroupName. Empty = frontend falls back to its name-based heuristic. An
individual Tool row overrides this. (Optional)
  "defaultToolIcon"?: string // Server-level default icon identifier (a frontend
icon key, not an uploaded image) for this connector's dynamic MCP tools. Empty =
frontend uses its default MCP icon. Streamed as toolIcon. (Optional)
  "authHeaders"?: object // Optional
  "allowedContextDataKeys"?: object // Allowlist of webchat contextData keys this
connector may render into auth_headers through {{context_data.<key>}}. An empty
list disables the feature for this connector: the placeholder is left verbatim,
exactly as before the feature existed. Keys are matched literally and are case-
sensitive; at most 20 keys of letters, digits and underscores. (Optional)
  "exposedMcpTools"?: object // Allowlist of MCP tool names this connector
exposes (to the agent and to SEP-1865 UI cards). Empty list = expose all of the
server tools. Use this to limit a connector to a safe subset (e.g. read-only
tools). (Optional)
  "isEnabled"?: boolean // Whether this connector is enabled for contacts in the
organization (Optional)
}
```

Example request values

```
{
  "mcpRegistryId": "550e8400-e29b-41d4-a716-446655440000",
  "displayName": "Example string",
  "description": "Example string",
  "defaultCategory": null,
  "defaultDisplayGroupNameByLocale": null,
  "defaultToolIcon": "Example string",
  "authHeaders": null,
```

```
  "allowedContextDataKeys": null,
  "exposedMcpTools": null,
  "isEnabled": true
}
```

Code examples

Shell/Bash

```
# API call example (Shell)
curl -X POST "https://api.maiagent.ai/api/v1/connectors/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "mcpRegistryId": "550e8400-e29b-41d4-a716-446655440000",
    "displayName": "Example string",
    "description": "Example string",
    "defaultCategory": null,
    "defaultDisplayGroupNameByLocale": null,
    "defaultToolIcon": "Example string",
    "authHeaders": null,
    "allowedContextDataKeys": null,
    "exposedMcpTools": null,
    "isEnabled": true
  }'

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// Request body (payload)
const data = {
    "mcpRegistryId": "550e8400-e29b-41d4-a716-446655440000",
    "displayName": "Example string",
    "description": "Example string",
    "defaultCategory": null,
    "defaultDisplayGroupNameByLocale": null,
    "defaultToolIcon": "Example string",
    "authHeaders": null,
    "allowedContextDataKeys": null,
    "exposedMcpTools": null,
    "isEnabled": true
  };

axios.post("https://api.maiagent.ai/api/v1/connectors/", data, config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/connectors/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# Request body (payload)
data = {
    "mcpRegistryId": "550e8400-e29b-41d4-a716-446655440000",
    "displayName": "Example string",
    "description": "Example string",
    "defaultCategory": None,
    "defaultDisplayGroupNameByLocale": None,
    "defaultToolIcon": "Example string",
    "authHeaders": None,
    "allowedContextDataKeys": None,
    "exposedMcpTools": None,
    "isEnabled": True
}

response = requests.post(url, json=data, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->post("https://api.maiagent.ai/api/v1/connectors/",
[
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'mcpRegistryId' => '550e8400-e29b-41d4-a716-446655440000',
            'displayName' => 'Example string',
            'description' => 'Example string',
            'defaultCategory' => null,
            'defaultDisplayGroupNameByLocale' => null,
            'defaultToolIcon' => 'Example string',
            'authHeaders' => null,
            'allowedContextDataKeys' => null,
            'exposedMcpTools' => null,
            'isEnabled' => true
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response body

Status code: 201

Example response schema

```
{
  "id": string (uuid)
  "mcpRegistry":
  {
    "id": string (uuid)
    "name": string // MCP service name (e.g., Supabase, Sentry). Only
alphanumeric, underscore and hyphen allowed.
    "displayName"?: string // Human-readable display name (defaults to name if
empty) (Optional)
    "description"?: string // Brief description of the MCP service (Optional)
    "remoteMcpUrl": string (uri) // The URL of the Remote MCP service
    "oauthServerUrl"?: // May have different types (Optional)
    string (uri) // Manual override for the OAuth authorization server URL. Leave
empty to auto-discover from the MCP server (RFC 9728 protected resource
metadata). Only fill in when auto-discovery fails or the server advertises
incorrect metadata. (e.g., Supabase MCP is at mcp.supabase.com but OAuth is at
api.supabase.com) (Optional)
    "logoUrl": string (uri)
    "isActive"?: boolean // Whether this MCP service is currently available for
use (Optional)
    "isGlobal"?: boolean // Global registries are maintained by the platform and
available to all organizations. (Optional)
    "authType"?:  // How to authenticate with this MCP server.

* `oauth` - OAuth 2.0
* `service_account` - Service Account
* `none` - No Authentication (Optional)
    {
    }
    "createdAt": string (timestamp)
    "updatedAt": string (timestamp)
  }
  "mcpRegistryId": string (uuid)
  "name": string
  "displayName"?: string // Custom display name for this connector (defaults to
MCP Registry name) (Optional)
  "description"?: string // Custom description for this connector (defaults to
MCP Registry description) (Optional)
  "defaultCategory"?: // May have different types (Optional)
  string (enum: knowledge_base, web_search, web_fetch, code_execution,
file_processing, image_video_generation, database_query, third_party_integration,
browser_operation, agent_collaboration, other) // Org-level override of the MCP
Registry default category for this connector's dynamic tools. Empty = use the MCP
Registry default_category.
```

```
* `knowledge_base` - Knowledge base retrieval
* `web_search` - Web search
* `web_fetch` - Web page fetch
* `code_execution` - Code execution
* `file_processing` - File processing
* `image_video_generation` - Image/video generation
* `database_query` - Database query
* `third_party_integration` - Third-party integration
* `browser_operation` - Browser operation
* `agent_collaboration` - Agent collaboration
* `other` - Other (catch-all) (Optional)
  "defaultDisplayGroupNameByLocale"?: object // Locale-keyed server-level default group headline shown in chat for this connector's dynamic MCP tools (those without an individual Tool row). Shape: {"<locale>": str}. The headline for the conversation locale is resolved server-side (see whizchat.tools.services.tool_category.resolve_localized_text): requested locale -> settings.LANGUAGE_CODE locale -> empty, then streamed verbatim as displayGroupName. Empty = frontend falls back to its name-based heuristic. An individual Tool row overrides this. (Optional)
  "defaultToolIcon"?: string // Server-level default icon identifier (a frontend icon key, not an uploaded image) for this connector's dynamic MCP tools. Empty = frontend uses its default MCP icon. Streamed as toolIcon. (Optional)
  "effectiveDescription": string
  "remoteMcpUrl": string
  "oauthServerUrl": string
  "logoUrl": string (uri)
  "authType": string
  "authHeaders"?: object // Optional
  "authHeadersMasked": object
  "allowedContextDataKeys"?: object // Allowlist of webchat contextData keys this connector may render into auth_headers through {{context_data.<key>}}. An empty list disables the feature for this connector: the placeholder is left verbatim, exactly as before the feature existed. Keys are matched literally and are case-sensitive; at most 20 keys of letters, digits and underscores. (Optional)
  "exposedMcpTools"?: object // Allowlist of MCP tool names this connector exposes (to the agent and to SEP-1865 UI cards). Empty list = expose all of the server tools. Use this to limit a connector to a safe subset (e.g. read-only tools). (Optional)
  "isEnabled"?: boolean // Whether this connector is enabled for contacts in the organization (Optional)
  "organization": string (uuid)
  "createdBy": string (uuid)
  "createdAt": string (timestamp)
  "updatedAt": string (timestamp)
}
```

Example response values

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "mcpRegistry": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Response string",
    "displayName": "Response string",
    "description": "Response string",
    "remoteMcpUrl": "https://example.com/file.jpg",
    "oauthServerUrl": "https://example.com/file.jpg",
    "logoUrl": "https://example.com/file.jpg",
    "isActive": false,
    "isGlobal": false,
    "authType": {},
    "createdAt": "Response string",
    "updatedAt": "Response string"
  },
  "mcpRegistryId": "550e8400-e29b-41d4-a716-446655440000",
  "name": "Response string",
  "displayName": "Response string",
  "description": "Response string",
  "defaultCategory": "knowledge_base",
  "defaultDisplayGroupNameByLocale": null,
  "defaultToolIcon": "Response string",
  "effectiveDescription": "Response string",
  "remoteMcpUrl": "Response string",
  "oauthServerUrl": "Response string",
  "logoUrl": "https://example.com/file.jpg",
  "authType": "Response string",
  "authHeaders": null,
  "authHeadersMasked": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Example response name",
    "description": "Example response description"
  },
  "allowedContextDataKeys": null,
  "exposedMcpTools": null,
  "isEnabled": false,
  "organization": "550e8400-e29b-41d4-a716-446655440000",
  "createdBy": "550e8400-e29b-41d4-a716-446655440000",
  "createdAt": "Response string",
  "updatedAt": "Response string"
}
```

List connectors

GET `/api/v1/connectors/`

Code examples

Shell/Bash

```
# API call example (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/connectors/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/connectors/", config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```python
import requests

url = "https://api.maiagent.ai/api/v1/connectors/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->get("https://api.maiagent.ai/api/v1/connectors/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response body

Status code: 200

Example response schema

```
[
  {
    "id": string (uuid)
    "displayName"?: string // Custom display name for this connector (defaults to
MCP Registry name) (Optional)
    "mcpRegistryName": string
    "mcpRegistryId": string
    "mcpRegistryIsGlobal": boolean
    "logoUrl": string (uri)
```

```
    "defaultCategory"?: // May have different types (Optional)
    string (enum: knowledge_base, web_search, web_fetch, code_execution,
file_processing, image_video_generation, database_query, third_party_integration,
browser_operation, agent_collaboration, other) // Org-level override of the MCP
Registry default category for this connector's dynamic tools. Empty = use the MCP
Registry default_category.

* `knowledge_base` - Knowledge base retrieval
* `web_search` - Web search
* `web_fetch` - Web page fetch
* `code_execution` - Code execution
* `file_processing` - File processing
* `image_video_generation` - Image/video generation
* `database_query` - Database query
* `third_party_integration` - Third-party integration
* `browser_operation` - Browser operation
* `agent_collaboration` - Agent collaboration
* `other` - Other (catch-all) (Optional)
    "isEnabled"?: boolean // Whether this connector is enabled for contacts in
the organization (Optional)
    "authHeadersMasked": object
    "allowedContextDataKeys": object // Allowlist of webchat contextData keys
this connector may render into auth_headers through {{context_data.<key>}}. An
empty list disables the feature for this connector: the placeholder is left
verbatim, exactly as before the feature existed. Keys are matched literally and
are case-sensitive; at most 20 keys of letters, digits and underscores.
    "authorizedMembersCount": integer
    "createdBy":
    {
      "id": string (uuid)
      "name": string
    }
    "createdAt": string (timestamp)
    "updatedAt": string (timestamp)
  }
]
```

Example response values

```
[
  {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "displayName": "Response string",
    "mcpRegistryName": "Response string",
    "mcpRegistryId": "Response string",
    "mcpRegistryIsGlobal": false,
    "logoUrl": "https://example.com/file.jpg",
    "defaultCategory": "knowledge_base",
```

```
    "isEnabled": false,
    "authHeadersMasked": {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "Example response name",
      "description": "Example response description"
    },
    "allowedContextDataKeys": null,
    "authorizedMembersCount": 456,
    "createdBy": {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "Response string"
    },
    "createdAt": "Response string",
    "updatedAt": "Response string"
  }
]
```


Retrieve a specific connector

`GET` `/api/v1/connectors/{id}`

Parameters

Parameter name	Required	Type	Description
`id`	V	string	

Code examples

Shell/Bash

```
# API call example (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/connectors/550e8400-e29b-41d4-
a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/connectors/550e8400-e29b-41d4-
a716-446655440000/", config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/connectors/550e8400-e29b-41d4-a716-
446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/connectors/550e8400-e29b-41d4-a716-
446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response body

Status code: 200

Example response schema

```
{
  "id": string (uuid)
  "mcpRegistry":
  {
    "id": string (uuid)
    "name": string // MCP service name (e.g., Supabase, Sentry). Only
alphanumeric, underscore and hyphen allowed.
```

```
    "displayName"?: string // Human-readable display name (defaults to name if
empty) (Optional)
    "description"?: string // Brief description of the MCP service (Optional)
    "remoteMcpUrl": string (uri) // The URL of the Remote MCP service
    "oauthServerUrl"?: // May have different types (Optional)
    string (uri) // Manual override for the OAuth authorization server URL. Leave
empty to auto-discover from the MCP server (RFC 9728 protected resource
metadata). Only fill in when auto-discovery fails or the server advertises
incorrect metadata. (e.g., Supabase MCP is at mcp.supabase.com but OAuth is at
api.supabase.com) (Optional)
    "logoUrl": string (uri)
    "isActive"?: boolean // Whether this MCP service is currently available for
use (Optional)
    "isGlobal"?: boolean // Global registries are maintained by the platform and
available to all organizations. (Optional)
    "authType"?:  // How to authenticate with this MCP server.

* `oauth` - OAuth 2.0
* `service_account` - Service Account
* `none` - No Authentication (Optional)
    {
    }
    "createdAt": string (timestamp)
    "updatedAt": string (timestamp)
  }
  "mcpRegistryId": string (uuid)
  "name": string
  "displayName"?: string // Custom display name for this connector (defaults to
MCP Registry name) (Optional)
  "description"?: string // Custom description for this connector (defaults to
MCP Registry description) (Optional)
  "defaultCategory"?: // May have different types (Optional)
  string (enum: knowledge_base, web_search, web_fetch, code_execution,
file_processing, image_video_generation, database_query, third_party_integration,
browser_operation, agent_collaboration, other) // Org-level override of the MCP
Registry default category for this connector's dynamic tools. Empty = use the MCP
Registry default_category.

* `knowledge_base` - Knowledge base retrieval
* `web_search` - Web search
* `web_fetch` - Web page fetch
* `code_execution` - Code execution
* `file_processing` - File processing
* `image_video_generation` - Image/video generation
* `database_query` - Database query
* `third_party_integration` - Third-party integration
* `browser_operation` - Browser operation
* `agent_collaboration` - Agent collaboration
* `other` - Other (catch-all) (Optional)
```

```
  "defaultDisplayGroupNameByLocale"?: object // Locale-keyed server-level default group headline shown in chat for this connector's dynamic MCP tools (those without an individual Tool row). Shape: {"<locale>": str}. The headline for the conversation locale is resolved server-side (see whizchat.tools.services.tool_category.resolve_localized_text): requested locale -> settings.LANGUAGE_CODE locale -> empty, then streamed verbatim as displayGroupName. Empty = frontend falls back to its name-based heuristic. An individual Tool row overrides this. (Optional)
  "defaultToolIcon"?: string // Server-level default icon identifier (a frontend icon key, not an uploaded image) for this connector's dynamic MCP tools. Empty = frontend uses its default MCP icon. Streamed as toolIcon. (Optional)
  "effectiveDescription": string
  "remoteMcpUrl": string
  "oauthServerUrl": string
  "logoUrl": string (uri)
  "authType": string
  "authHeaders"?: object // Optional
  "authHeadersMasked": object
  "allowedContextDataKeys"?: object // Allowlist of webchat contextData keys this connector may render into auth_headers through {{context_data.<key>}}. An empty list disables the feature for this connector: the placeholder is left verbatim, exactly as before the feature existed. Keys are matched literally and are case-sensitive; at most 20 keys of letters, digits and underscores. (Optional)
  "exposedMcpTools"?: object // Allowlist of MCP tool names this connector exposes (to the agent and to SEP-1865 UI cards). Empty list = expose all of the server tools. Use this to limit a connector to a safe subset (e.g. read-only tools). (Optional)
  "isEnabled"?: boolean // Whether this connector is enabled for contacts in the organization (Optional)
  "organization": string (uuid)
  "createdBy": string (uuid)
  "createdAt": string (timestamp)
  "updatedAt": string (timestamp)
}
```

Example Response Values


```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "mcpRegistry": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Response string",
    "displayName": "Response string",
    "description": "Response string",
    "remoteMcpUrl": "https://example.com/file.jpg",
    "oauthServerUrl": "https://example.com/file.jpg",
    "logoUrl": "https://example.com/file.jpg",
    "isActive": false,
```

```
    "isGlobal": false,
    "authType": {},
    "createdAt": "Response string",
    "updatedAt": "Response string"
  },
  "mcpRegistryId": "550e8400-e29b-41d4-a716-446655440000",
  "name": "Response string",
  "displayName": "Response string",
  "description": "Response string",
  "defaultCategory": "knowledge_base",
  "defaultDisplayGroupNameByLocale": null,
  "defaultToolIcon": "Response string",
  "effectiveDescription": "Response string",
  "remoteMcpUrl": "Response string",
  "oauthServerUrl": "Response string",
  "logoUrl": "https://example.com/file.jpg",
  "authType": "Response string",
  "authHeaders": null,
  "authHeadersMasked": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Example response name",
    "description": "Example response description"
  },
  "allowedContextDataKeys": null,
  "exposedMcpTools": null,
  "isEnabled": false,
  "organization": "550e8400-e29b-41d4-a716-446655440000",
  "createdBy": "550e8400-e29b-41d4-a716-446655440000",
  "createdAt": "Response string",
  "updatedAt": "Response string"
}
```


Update Connector

PUT `/api/v1/connectors/{id}`

Parameters

Parameter Name	Required	Type	Description
`id`	V	string	

Request Body

Request Parameters

Field	Type	Required	Description
mcpRegistryId	string (uuid)	Yes	
displayName	string	No	Custom display name for this connector (defaults to MCP Registry name)
description	string	No	Custom description for this connector (defaults to MCP Registry description)
defaultCategory	object	No	Org-level override of the MCP Registry default category for this connector's dynamic tools. Empty = use the MCP Registry default_category. `knowledge_base` : Knowledge base retrieval ; `web_search` : We...
defaultDisplayGroupNameByLocale	object	No	Locale-keyed server-level default group headline shown in chat for this connector's dynamic MCP tools (those without an individual Tool row). Shape: {"": str}. The headline for the conversatio...
defaultToolIcon	string	No	Server-level default icon identifier (a frontend icon key, not an uploaded image) for this connector's dynamic MCP tools. Empty = frontend uses its default MCP icon. Streamed as toolIcon.
authHeaders	object	No	

Field	Type	Required	Description
allowedContextDataKeys	object	No	Allowlist of webchat contextData keys this connector may render into auth_headers through {{context_data.}}. An empty list disables the feature for this connector: the placeholder is left verbati...
exposedMcpTools	object	No	Allowlist of MCP tool names this connector exposes (to the agent and to SEP-1865 UI cards). Empty list = expose all of the server tools. Use this to limit a connector to a safe subset (e.g. read-only ...
isEnabled	boolean	No	Whether this connector is enabled for contacts in the organization

Request Schema Example

```
{
  "mcpRegistryId": string (uuid)
  "displayName"?: string // Custom display name for this connector (defaults to
MCP Registry name) (Optional)
  "description"?: string // Custom description for this connector (defaults to
MCP Registry description) (Optional)
  "defaultCategory"?: // May have different types (Optional)
  string (enum: knowledge_base, web_search, web_fetch, code_execution,
file_processing, image_video_generation, database_query, third_party_integration,
browser_operation, agent_collaboration, other) // Org-level override of the MCP
Registry default category for this connector's dynamic tools. Empty = use the MCP
Registry default_category.

* `knowledge_base` - Knowledge base retrieval
* `web_search` - Web search
* `web_fetch` - Web page fetch
* `code_execution` - Code execution
* `file_processing` - File processing
* `image_video_generation` - Image/video generation
* `database_query` - Database query
* `third_party_integration` - Third-party integration
* `browser_operation` - Browser operation
* `agent_collaboration` - Agent collaboration
* `other` - Other (catch-all) (Optional)
  "defaultDisplayGroupNameByLocale"?: object // Locale-keyed server-level default
group headline shown in chat for this connector's dynamic MCP tools (those
```

```
without an individual Tool row). Shape: {"<locale>": str}. The headline for the
conversation locale is resolved server-side (see
whizchat.tools.services.tool_category.resolve_localized_text): requested locale -
> settings.LANGUAGE_CODE locale -> empty, then streamed verbatim as
displayGroupName. Empty = frontend falls back to its name-based heuristic. An
individual Tool row overrides this. (Optional)
  "defaultToolIcon"?: string // Server-level default icon identifier (a frontend
icon key, not an uploaded image) for this connector's dynamic MCP tools. Empty =
frontend uses its default MCP icon. Streamed as toolIcon. (Optional)
  "authHeaders"?: object // Optional
  "allowedContextDataKeys"?: object // Allowlist of webchat contextData keys this
connector may render into auth_headers through {{context_data.<key>}}. An empty
list disables the feature for this connector: the placeholder is left verbatim,
exactly as before the feature existed. Keys are matched literally and are case-
sensitive; at most 20 keys of letters, digits and underscores. (Optional)
  "exposedMcpTools"?: object // Allowlist of MCP tool names this connector
exposes (to the agent and to SEP-1865 UI cards). Empty list = expose all of the
server tools. Use this to limit a connector to a safe subset (e.g. read-only
tools). (Optional)
  "isEnabled"?: boolean // Whether this connector is enabled for contacts in the
organization (Optional)
}
```

Example Request Values

```
{
  "mcpRegistryId": "550e8400-e29b-41d4-a716-446655440000",
  "displayName": "Example string",
  "description": "Example string",
  "defaultCategory": null,
  "defaultDisplayGroupNameByLocale": null,
  "defaultToolIcon": "Example string",
  "authHeaders": null,
  "allowedContextDataKeys": null,
  "exposedMcpTools": null,
  "isEnabled": true
}
```

Code Examples

Shell/Bash

```
# API call example (Shell)
curl -X PUT "https://api.maiagent.ai/api/v1/connectors/550e8400-e29b-41d4-
a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "mcpRegistryId": "550e8400-e29b-41d4-a716-446655440000",
    "displayName": "Example string",
    "description": "Example string",
    "defaultCategory": null,
    "defaultDisplayGroupNameByLocale": null,
    "defaultToolIcon": "Example string",
    "authHeaders": null,
    "allowedContextDataKeys": null,
    "exposedMcpTools": null,
    "isEnabled": true
  }'

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// Request Body (payload)
const data = {
    "mcpRegistryId": "550e8400-e29b-41d4-a716-446655440000",
    "displayName": "Example string",
    "description": "Example string",
    "defaultCategory": null,
    "defaultDisplayGroupNameByLocale": null,
    "defaultToolIcon": "Example string",
    "authHeaders": null,
    "allowedContextDataKeys": null,
    "exposedMcpTools": null,
    "isEnabled": true
  };

axios.put("https://api.maiagent.ai/api/v1/connectors/550e8400-e29b-41d4-
a716-446655440000/", data, config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/connectors/550e8400-e29b-41d4-a716-
446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# Request Body (payload)
data = {
    "mcpRegistryId": "550e8400-e29b-41d4-a716-446655440000",
    "displayName": "Example string",
    "description": "Example string",
    "defaultCategory": None,
    "defaultDisplayGroupNameByLocale": None,
    "defaultToolIcon": "Example string",
    "authHeaders": None,
    "allowedContextDataKeys": None,
    "exposedMcpTools": None,
    "isEnabled": True
}

response = requests.put(url, json=data, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>put("https://api.maiagent.ai/api/v1/connectors/550e8400-e29b-41d4-a716-
446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'mcpRegistryId' => '550e8400-e29b-41d4-a716-446655440000',
            'displayName' => 'Example string',
            'description' => 'Example string',
            'defaultCategory' => null,
            'defaultDisplayGroupNameByLocale' => null,
            'defaultToolIcon' => 'Example string',
            'authHeaders' => null,
            'allowedContextDataKeys' => null,
            'exposedMcpTools' => null,
            'isEnabled' => true
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response Body

Status Code: 200

Response Schema Example

```
{
  "id": string (uuid)
  "mcpRegistry":
  {
    "id": string (uuid)
    "name": string // MCP service name (e.g., Supabase, Sentry). Only
alphanumeric, underscore and hyphen allowed.
    "displayName"?: string // Human-readable display name (defaults to name if
empty) (Optional)
    "description"?: string // Brief description of the MCP service (Optional)
    "remoteMcpUrl": string (uri) // The URL of the Remote MCP service
    "oauthServerUrl"?: // May have different types (Optional)
    string (uri) // Manual override for the OAuth authorization server URL. Leave
empty to auto-discover from the MCP server (RFC 9728 protected resource
metadata). Only fill in when auto-discovery fails or the server advertises
incorrect metadata. (e.g., Supabase MCP is at mcp.supabase.com but OAuth is at
api.supabase.com) (Optional)
    "logoUrl": string (uri)
    "isActive"?: boolean // Whether this MCP service is currently available for
use (Optional)
    "isGlobal"?: boolean // Global registries are maintained by the platform and
available to all organizations. (Optional)
    "authType"?:  // How to authenticate with this MCP server.

* `oauth` - OAuth 2.0
* `service_account` - Service Account
* `none` - No Authentication (Optional)
    {
    }
    "createdAt": string (timestamp)
    "updatedAt": string (timestamp)
  }
  "mcpRegistryId": string (uuid)
  "name": string
  "displayName"?: string // Custom display name for this connector (defaults to
MCP Registry name) (Optional)
  "description"?: string // Custom description for this connector (defaults to
MCP Registry description) (Optional)
  "defaultCategory"?: // May have different types (Optional)
  string (enum: knowledge_base, web_search, web_fetch, code_execution,
file_processing, image_video_generation, database_query, third_party_integration,
browser_operation, agent_collaboration, other) // Org-level override of the MCP
Registry default category for this connector's dynamic tools. Empty = use the MCP
Registry default_category.
```

```
* `knowledge_base` - Knowledge base retrieval
* `web_search` - Web search
* `web_fetch` - Web page fetch
* `code_execution` - Code execution
* `file_processing` - File processing
* `image_video_generation` - Image/video generation
* `database_query` - Database query
* `third_party_integration` - Third-party integration
* `browser_operation` - Browser operation
* `agent_collaboration` - Agent collaboration
* `other` - Other (catch-all) (Optional)
  "defaultDisplayGroupNameByLocale"?: object // Locale-keyed server-level default group headline shown in chat for this connector's dynamic MCP tools (those without an individual Tool row). Shape: {"<locale>": str}. The headline for the conversation locale is resolved server-side (see whizchat.tools.services.tool_category.resolve_localized_text): requested locale -> settings.LANGUAGE_CODE locale -> empty, then streamed verbatim as displayGroupName. Empty = frontend falls back to its name-based heuristic. An individual Tool row overrides this. (Optional)
  "defaultToolIcon"?: string // Server-level default icon identifier (a frontend icon key, not an uploaded image) for this connector's dynamic MCP tools. Empty = frontend uses its default MCP icon. Streamed as toolIcon. (Optional)
  "effectiveDescription": string
  "remoteMcpUrl": string
  "oauthServerUrl": string
  "logoUrl": string (uri)
  "authType": string
  "authHeaders"?: object // Optional
  "authHeadersMasked": object
  "allowedContextDataKeys"?: object // Allowlist of webchat contextData keys this connector may render into auth_headers through {{context_data.<key>}}. An empty list disables the feature for this connector: the placeholder is left verbatim, exactly as before the feature existed. Keys are matched literally and are case-sensitive; at most 20 keys of letters, digits and underscores. (Optional)
  "exposedMcpTools"?: object // Allowlist of MCP tool names this connector exposes (to the agent and to SEP-1865 UI cards). Empty list = expose all of the server tools. Use this to limit a connector to a safe subset (e.g. read-only tools). (Optional)
  "isEnabled"?: boolean // Whether this connector is enabled for contacts in the organization (Optional)
  "organization": string (uuid)
  "createdBy": string (uuid)
  "createdAt": string (timestamp)
  "updatedAt": string (timestamp)
}
```

Example Response Values

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "mcpRegistry": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Response string",
    "displayName": "Response string",
    "description": "Response string",
    "remoteMcpUrl": "https://example.com/file.jpg",
    "oauthServerUrl": "https://example.com/file.jpg",
    "logoUrl": "https://example.com/file.jpg",
    "isActive": false,
    "isGlobal": false,
    "authType": {},
    "createdAt": "Response string",
    "updatedAt": "Response string"
  },
  "mcpRegistryId": "550e8400-e29b-41d4-a716-446655440000",
  "name": "Response string",
  "displayName": "Response string",
  "description": "Response string",
  "defaultCategory": "knowledge_base",
  "defaultDisplayGroupNameByLocale": null,
  "defaultToolIcon": "Response string",
  "effectiveDescription": "Response string",
  "remoteMcpUrl": "Response string",
  "oauthServerUrl": "Response string",
  "logoUrl": "https://example.com/file.jpg",
  "authType": "Response string",
  "authHeaders": null,
  "authHeadersMasked": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Example response name",
    "description": "Example response description"
  },
  "allowedContextDataKeys": null,
  "exposedMcpTools": null,
  "isEnabled": false,
  "organization": "550e8400-e29b-41d4-a716-446655440000",
  "createdBy": "550e8400-e29b-41d4-a716-446655440000",
  "createdAt": "Response string",
  "updatedAt": "Response string"
}
```

Partially Update Connector

`PATCH` `/api/v1/connectors/{id}`

Parameters

Parameter Name	Required	Type	Description
`id`	V	string	

Request Body

Request Parameters

Field	Type	Required	Description
mcpRegistryId	string (uuid)	No	
displayName	string	No	Custom display name for this connector (defaults to MCP Registry name)
description	string	No	Custom description for this connector (defaults to MCP Registry description)
defaultCategory	object	No	Org-level override of the MCP Registry default category for this connector's dynamic tools. Empty = use the MCP Registry default_category. `knowledge_base` : Knowledge base retrieval ; `web_search` : We...
defaultDisplayGroupNameByLocale	object	No	Locale-keyed server-level default group headline shown in chat for this connector's dynamic MCP tools (those without an individual

Field	Type	Required	Description
			Tool row). Shape: {"": str}. The headline for the conversatio...
defaultToolIcon	string	No	Server-level default icon identifier (a frontend icon key, not an uploaded image) for this connector's dynamic MCP tools. Empty = frontend uses its default MCP icon. Streamed as toolIcon.
authHeaders	object	No	
allowedContextDataKeys	object	No	Allowlist of webchat contextData keys this connector may render into auth_headers through {{context_data.}}. An empty list disables the feature for this connector: the placeholder is left verbati...
exposedMcpTools	object	No	Allowlist of MCP tool names this connector exposes (to the agent and to SEP-1865 UI cards). Empty list = expose all of the server tools. Use this to limit a connector to a safe subset (e.g. read-only ...
isEnabled	boolean	No	Whether this connector is enabled for contacts in the organization

Request Schema Example

```
{
  "mcpRegistryId"?: string (uuid) // Optional
  "displayName"?: string // Custom display name for this connector (defaults to
MCP Registry name) (Optional)
  "description"?: string // Custom description for this connector (defaults to
MCP Registry description) (Optional)
  "defaultCategory"?: // May have different types (Optional)
  string (enum: knowledge_base, web_search, web_fetch, code_execution,
file_processing, image_video_generation, database_query, third_party_integration,
browser_operation, agent_collaboration, other) // Org-level override of the MCP
Registry default category for this connector's dynamic tools. Empty = use the MCP
Registry default_category.

* `knowledge_base` - Knowledge base retrieval
* `web_search` - Web search
* `web_fetch` - Web page fetch
```

```
* `code_execution` - Code execution
* `file_processing` - File processing
* `image_video_generation` - Image/video generation
* `database_query` - Database query
* `third_party_integration` - Third-party integration
* `browser_operation` - Browser operation
* `agent_collaboration` - Agent collaboration
* `other` - Other (catch-all) (Optional)
  "defaultDisplayGroupNameByLocale"?: object // Locale-keyed server-level default group headline shown in chat for this connector's dynamic MCP tools (those without an individual Tool row). Shape: {"<locale>": str}. The headline for the conversation locale is resolved server-side (see whizchat.tools.services.tool_category.resolve_localized_text): requested locale -> settings.LANGUAGE_CODE locale -> empty, then streamed verbatim as displayGroupName. Empty = frontend falls back to its name-based heuristic. An individual Tool row overrides this. (Optional)
  "defaultToolIcon"?: string // Server-level default icon identifier (a frontend icon key, not an uploaded image) for this connector's dynamic MCP tools. Empty = frontend uses its default MCP icon. Streamed as toolIcon. (Optional)
  "authHeaders"?: object // Optional
  "allowedContextDataKeys"?: object // Allowlist of webchat contextData keys this connector may render into auth_headers through {{context_data.<key>}}. An empty list disables the feature for this connector: the placeholder is left verbatim, exactly as before the feature existed. Keys are matched literally and are case-sensitive; at most 20 keys of letters, digits and underscores. (Optional)
  "exposedMcpTools"?: object // Allowlist of MCP tool names this connector exposes (to the agent and to SEP-1865 UI cards). Empty list = expose all of the server tools. Use this to limit a connector to a safe subset (e.g. read-only tools). (Optional)
  "isEnabled"?: boolean // Whether this connector is enabled for contacts in the organization (Optional)
}
```

Example Request Values

```
{
  "mcpRegistryId": "550e8400-e29b-41d4-a716-446655440000",
  "displayName": "Example string",
  "description": "Example string",
  "defaultCategory": null,
  "defaultDisplayGroupNameByLocale": null,
  "defaultToolIcon": "Example string",
  "authHeaders": null,
  "allowedContextDataKeys": null,
  "exposedMcpTools": null,
```

```
  "isEnabled": true
}
```

Code Examples

Shell/Bash

```
# API call example (Shell)
curl -X PATCH "https://api.maiagent.ai/api/v1/connectors/550e8400-e29b-41d4-
a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "mcpRegistryId": "550e8400-e29b-41d4-a716-446655440000",
    "displayName": "Example string",
    "description": "Example string",
    "defaultCategory": null,
    "defaultDisplayGroupNameByLocale": null,
    "defaultToolIcon": "Example string",
    "authHeaders": null,
    "allowedContextDataKeys": null,
    "exposedMcpTools": null,
    "isEnabled": true
  }'

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// Request body (payload)
const data = {
    "mcpRegistryId": "550e8400-e29b-41d4-a716-446655440000",
    "displayName": "Example string",
    "description": "Example string",
    "defaultCategory": null,
    "defaultDisplayGroupNameByLocale": null,
    "defaultToolIcon": "Example string",
    "authHeaders": null,
    "allowedContextDataKeys": null,
    "exposedMcpTools": null,
    "isEnabled": true
  };

axios.patch("https://api.maiagent.ai/api/v1/connectors/550e8400-e29b-41d4-
a716-446655440000/", data, config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/connectors/550e8400-e29b-41d4-a716-
446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# Request body (payload)
data = {
    "mcpRegistryId": "550e8400-e29b-41d4-a716-446655440000",
    "displayName": "Example string",
    "description": "Example string",
    "defaultCategory": None,
    "defaultDisplayGroupNameByLocale": None,
    "defaultToolIcon": "Example string",
    "authHeaders": None,
    "allowedContextDataKeys": None,
    "exposedMcpTools": None,
    "isEnabled": True
}

response = requests.patch(url, json=data, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>patch("https://api.maiagent.ai/api/v1/connectors/550e8400-e29b-41d4-a716-
446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'mcpRegistryId' => '550e8400-e29b-41d4-a716-446655440000',
            'displayName' => 'Example string',
            'description' => 'Example string',
            'defaultCategory' => null,
            'defaultDisplayGroupNameByLocale' => null,
            'defaultToolIcon' => 'Example string',
            'authHeaders' => null,
            'allowedContextDataKeys' => null,
            'exposedMcpTools' => null,
            'isEnabled' => true
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response Body

Status Code: 200

Example Response Schema

```
{
  "id": string (uuid)
  "mcpRegistry":
  {
    "id": string (uuid)
    "name": string // MCP service name (e.g., Supabase, Sentry). Only
alphanumeric, underscore and hyphen allowed.
    "displayName"?: string // Human-readable display name (defaults to name if
empty) (Optional)
    "description"?: string // Brief description of the MCP service (Optional)
    "remoteMcpUrl": string (uri) // The URL of the Remote MCP service
    "oauthServerUrl"?: // May have different types (Optional)
    string (uri) // Manual override for the OAuth authorization server URL. Leave
empty to auto-discover from the MCP server (RFC 9728 protected resource
metadata). Only fill in when auto-discovery fails or the server advertises
incorrect metadata. (e.g., Supabase MCP is at mcp.supabase.com but OAuth is at
api.supabase.com) (Optional)
    "logoUrl": string (uri)
    "isActive"?: boolean // Whether this MCP service is currently available for
use (Optional)
    "isGlobal"?: boolean // Global registries are maintained by the platform and
available to all organizations. (Optional)
    "authType"?:  // How to authenticate with this MCP server.

* `oauth` - OAuth 2.0
* `service_account` - Service Account
* `none` - No Authentication (Optional)
    {
    }
    "createdAt": string (timestamp)
    "updatedAt": string (timestamp)
  }
  "mcpRegistryId": string (uuid)
  "name": string
  "displayName"?: string // Custom display name for this connector (defaults to
MCP Registry name) (Optional)
  "description"?: string // Custom description for this connector (defaults to
MCP Registry description) (Optional)
  "defaultCategory"?: // May have different types (Optional)
  string (enum: knowledge_base, web_search, web_fetch, code_execution,
file_processing, image_video_generation, database_query, third_party_integration,
browser_operation, agent_collaboration, other) // Org-level override of the MCP
Registry default category for this connector's dynamic tools. Empty = use the MCP
Registry default_category.
```

```
* `knowledge_base` - Knowledge base retrieval
* `web_search` - Web search
* `web_fetch` - Web page fetch
* `code_execution` - Code execution
* `file_processing` - File processing
* `image_video_generation` - Image/video generation
* `database_query` - Database query
* `third_party_integration` - Third-party integration
* `browser_operation` - Browser operation
* `agent_collaboration` - Agent collaboration
* `other` - Other (catch-all) (Optional)
  "defaultDisplayGroupNameByLocale"?: object // Locale-keyed server-level default group headline shown in chat for this connector's dynamic MCP tools (those without an individual Tool row). Shape: {"<locale>": str}. The headline for the conversation locale is resolved server-side (see whizchat.tools.services.tool_category.resolve_localized_text): requested locale -> settings.LANGUAGE_CODE locale -> empty, then streamed verbatim as displayGroupName. Empty = frontend falls back to its name-based heuristic. An individual Tool row overrides this. (Optional)
  "defaultToolIcon"?: string // Server-level default icon identifier (a frontend icon key, not an uploaded image) for this connector's dynamic MCP tools. Empty = frontend uses its default MCP icon. Streamed as toolIcon. (Optional)
  "effectiveDescription": string
  "remoteMcpUrl": string
  "oauthServerUrl": string
  "logoUrl": string (uri)
  "authType": string
  "authHeaders"?: object // Optional
  "authHeadersMasked": object
  "allowedContextDataKeys"?: object // Allowlist of webchat contextData keys this connector may render into auth_headers through {{context_data.<key>}}. An empty list disables the feature for this connector: the placeholder is left verbatim, exactly as before the feature existed. Keys are matched literally and are case-sensitive; at most 20 keys of letters, digits and underscores. (Optional)
  "exposedMcpTools"?: object // Allowlist of MCP tool names this connector exposes (to the agent and to SEP-1865 UI cards). Empty list = expose all of the server tools. Use this to limit a connector to a safe subset (e.g. read-only tools). (Optional)
  "isEnabled"?: boolean // Whether this connector is enabled for contacts in the organization (Optional)
  "organization": string (uuid)
  "createdBy": string (uuid)
  "createdAt": string (timestamp)
  "updatedAt": string (timestamp)
}
```

Example Response Values

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "mcpRegistry": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Response string",
    "displayName": "Response string",
    "description": "Response string",
    "remoteMcpUrl": "https://example.com/file.jpg",
    "oauthServerUrl": "https://example.com/file.jpg",
    "logoUrl": "https://example.com/file.jpg",
    "isActive": false,
    "isGlobal": false,
    "authType": {},
    "createdAt": "Response string",
    "updatedAt": "Response string"
  },
  "mcpRegistryId": "550e8400-e29b-41d4-a716-446655440000",
  "name": "Response string",
  "displayName": "Response string",
  "description": "Response string",
  "defaultCategory": "knowledge_base",
  "defaultDisplayGroupNameByLocale": null,
  "defaultToolIcon": "Response string",
  "effectiveDescription": "Response string",
  "remoteMcpUrl": "Response string",
  "oauthServerUrl": "Response string",
  "logoUrl": "https://example.com/file.jpg",
  "authType": "Response string",
  "authHeaders": null,
  "authHeadersMasked": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Example response name",
    "description": "Example response description"
  },
  "allowedContextDataKeys": null,
  "exposedMcpTools": null,
  "isEnabled": false,
  "organization": "550e8400-e29b-41d4-a716-446655440000",
  "createdBy": "550e8400-e29b-41d4-a716-446655440000",
  "createdAt": "Response string",
  "updatedAt": "Response string"
}
```

Delete Connector

DELETE `/api/v1/connectors/{id}`

Parameters

Parameter Name	Required	Type	Description
`id`	V	string	

Code Examples

Shell/Bash

```
# API call example (Shell)
curl -X DELETE "https://api.maiagent.ai/api/v1/connectors/550e8400-e29b-
41d4-a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

// Request body (payload)
const data = null;

axios.delete("https://api.maiagent.ai/api/v1/connectors/550e8400-e29b-41d4-a716-446655440000/", data, config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/connectors/550e8400-e29b-41d4-a716-
446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.delete(url, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>delete("https://api.maiagent.ai/api/v1/connectors/550e8400-e29b-41d4-a716-
446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response Body

Status Code	Description
204	No response body

List Authorized Connector Members

GET `/api/v1/connectors/{id}/authorized-members/`

Parameters

Parameter Name	Required	Type	Description
`id`	V	string	

Code Examples

Shell/Bash

```
# API call example (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/connectors/550e8400-e29b-41d4-
a716-446655440000/authorized-members/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/connectors/550e8400-e29b-41d4-
a716-446655440000/authorized-members/", config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/connectors/550e8400-e29b-41d4-a716-446655440000/authorized-members/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/connectors/550e8400-e29b-41d4-a716-
446655440000/authorized-members/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response Body

Status Code: 200

Example Response Schema

```
{
  "id": string (uuid)
  "mcpRegistry":
  {
    "id": string (uuid)
    "name": string // MCP service name (e.g., Supabase, Sentry). Only
alphanumeric, underscore and hyphen allowed.
```

```
    "displayName"?: string // Human-readable display name (defaults to name if
empty) (Optional)
    "description"?: string // Brief description of the MCP service (Optional)
    "remoteMcpUrl": string (uri) // The URL of the Remote MCP service
    "oauthServerUrl"?: // May have different types (Optional)
    string (uri) // Manual override for the OAuth authorization server URL. Leave
empty to auto-discover from the MCP server (RFC 9728 protected resource
metadata). Only fill in when auto-discovery fails or the server advertises
incorrect metadata. (e.g., Supabase MCP is at mcp.supabase.com but OAuth is at
api.supabase.com) (Optional)
    "logoUrl": string (uri)
    "isActive"?: boolean // Whether this MCP service is currently available for
use (Optional)
    "isGlobal"?: boolean // Global registries are maintained by the platform and
available to all organizations. (Optional)
    "authType"?:  // How to authenticate with this MCP server.

* `oauth` - OAuth 2.0
* `service_account` - Service Account
* `none` - No Authentication (Optional)
    {
    }
    "createdAt": string (timestamp)
    "updatedAt": string (timestamp)
  }
  "mcpRegistryId": string (uuid)
  "name": string
  "displayName"?: string // Custom display name for this connector (defaults to
MCP Registry name) (Optional)
  "description"?: string // Custom description for this connector (defaults to
MCP Registry description) (Optional)
  "defaultCategory"?: // May have different types (Optional)
  string (enum: knowledge_base, web_search, web_fetch, code_execution,
file_processing, image_video_generation, database_query, third_party_integration,
browser_operation, agent_collaboration, other) // Org-level override of the MCP
Registry default category for this connector's dynamic tools. Empty = use the MCP
Registry default_category.

* `knowledge_base` - Knowledge base retrieval
* `web_search` - Web search
* `web_fetch` - Web page fetch
* `code_execution` - Code execution
* `file_processing` - File processing
* `image_video_generation` - Image/video generation
* `database_query` - Database query
* `third_party_integration` - Third-party integration
* `browser_operation` - Browser operation
* `agent_collaboration` - Agent collaboration
* `other` - Other (catch-all) (Optional)
```

```
  "defaultDisplayGroupNameByLocale"?: object // Locale-keyed server-level default group headline shown in chat for this connector's dynamic MCP tools (those without an individual Tool row). Shape: {"<locale>": str}. The headline for the conversation locale is resolved server-side (see whizchat.tools.services.tool_category.resolve_localized_text): requested locale -> settings.LANGUAGE_CODE locale -> empty, then streamed verbatim as displayGroupName. Empty = frontend falls back to its name-based heuristic. An individual Tool row overrides this. (Optional)
  "defaultToolIcon"?: string // Server-level default icon identifier (a frontend icon key, not an uploaded image) for this connector's dynamic MCP tools. Empty = frontend uses its default MCP icon. Streamed as toolIcon. (Optional)
  "effectiveDescription": string
  "remoteMcpUrl": string
  "oauthServerUrl": string
  "logoUrl": string (uri)
  "authType": string
  "authHeaders"?: object // Optional
  "authHeadersMasked": object
  "allowedContextDataKeys"?: object // Allowlist of webchat contextData keys this connector may render into auth_headers through {{context_data.<key>}}. An empty list disables the feature for this connector: the placeholder is left verbatim, exactly as before the feature existed. Keys are matched literally and are case-sensitive; at most 20 keys of letters, digits and underscores. (Optional)
  "exposedMcpTools"?: object // Allowlist of MCP tool names this connector exposes (to the agent and to SEP-1865 UI cards). Empty list = expose all of the server tools. Use this to limit a connector to a safe subset (e.g. read-only tools). (Optional)
  "isEnabled"?: boolean // Whether this connector is enabled for contacts in the organization (Optional)
  "organization": string (uuid)
  "createdBy": string (uuid)
  "createdAt": string (timestamp)
  "updatedAt": string (timestamp)
}
```

Example Response Values

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "mcpRegistry": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Response string",
    "displayName": "Response string",
    "description": "Response string",
    "remoteMcpUrl": "https://example.com/file.jpg",
    "oauthServerUrl": "https://example.com/file.jpg",
    "logoUrl": "https://example.com/file.jpg",
    "isActive": false,
```

```
    "isGlobal": false,
    "authType": {},
    "createdAt": "Response string",
    "updatedAt": "Response string"
  },
  "mcpRegistryId": "550e8400-e29b-41d4-a716-446655440000",
  "name": "Response string",
  "displayName": "Response string",
  "description": "Response string",
  "defaultCategory": "knowledge_base",
  "defaultDisplayGroupNameByLocale": null,
  "defaultToolIcon": "Response string",
  "effectiveDescription": "Response string",
  "remoteMcpUrl": "Response string",
  "oauthServerUrl": "Response string",
  "logoUrl": "https://example.com/file.jpg",
  "authType": "Response string",
  "authHeaders": null,
  "authHeadersMasked": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Example response name",
    "description": "Example response description"
  },
  "allowedContextDataKeys": null,
  "exposedMcpTools": null,
  "isEnabled": false,
  "organization": "550e8400-e29b-41d4-a716-446655440000",
  "createdBy": "550e8400-e29b-41d4-a716-446655440000",
  "createdAt": "Response string",
  "updatedAt": "Response string"
}
```


Remove Authorized Connector Member

`DELETE` `/api/v1/connectors/{id}/authorized-members/{memberId}`

Parameters

Parameter name	Required	Type	Description
`id`	V	string	
`memberId`	V	string	

Code Examples

Shell/Bash

```
# API call example (Shell)
curl -X DELETE "https://api.maiagent.ai/api/v1/connectors/550e8400-e29b-
41d4-a716-446655440000/authorized-members/{memberId}
"

  -H "Authorization: Api-Key YOUR_API_KEY"

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

// Request body (payload)
const data = null;

axios.delete("https://api.maiagent.ai/api/v1/connectors/550e8400-e29b-41d4-
a716-446655440000/authorized-members/{memberId}
", data, config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/connectors/550e8400-e29b-41d4-a716-
446655440000/authorized-members/{memberId}
"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.delete(url, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>delete("https://api.maiagent.ai/api/v1/connectors/550e8400-e29b-41d4-a716-
446655440000/authorized-members/{memberId}
", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response Body

Status code	Description
204	No response body

List MCP Tool Registries

GET `/api/v1/mcp/registry/`

Code Examples

Shell/Bash

```
# API call example (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/mcp/registry/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/mcp/registry/", config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/mcp/registry/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->get("https://api.maiagent.ai/api/v1/mcp/registry/",
[
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response Body

Status code: 200

Example Response Schema

```
[
  {
    "id": string (uuid)
    "name": string // MCP service name (e.g., Supabase, Sentry). Only
alphanumeric, underscore and hyphen allowed.
    "displayName"?: string // Human-readable display name (defaults to name if
empty) (Optional)
    "description"?: string // Brief description of the MCP service (Optional)
```

```
    "remoteMcpUrl": string (uri) // The URL of the Remote MCP service
    "oauthServerUrl"?: // May have different types (Optional)
    string (uri) // Manual override for the OAuth authorization server URL. Leave empty to auto-discover from the MCP server (RFC 9728 protected resource metadata). Only fill in when auto-discovery fails or the server advertises incorrect metadata. (e.g., Supabase MCP is at mcp.supabase.com but OAuth is at api.supabase.com) (Optional)
    "logoUrl": string (uri)
    "isActive"?: boolean // Whether this MCP service is currently available for use (Optional)
    "isGlobal"?: boolean // Global registries are maintained by the platform and available to all organizations. (Optional)
    "authType"?:  // How to authenticate with this MCP server.

* `oauth` - OAuth 2.0
* `service_account` - Service Account
* `none` - No Authentication (Optional)
    {
    }
    "createdAt": string (timestamp)
    "updatedAt": string (timestamp)
  }
]
```

Example Response Values

```
[
  {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Response string",
    "displayName": "Response string",
    "description": "Response string",
    "remoteMcpUrl": "https://example.com/file.jpg",
    "oauthServerUrl": "https://example.com/file.jpg",
    "logoUrl": "https://example.com/file.jpg",
    "isActive": false,
    "isGlobal": false,
    "authType": {},
    "createdAt": "Response string",
    "updatedAt": "Response string"
  }
]
```

Retrieve a Specific MCP Tool Registry

GET `/api/v1/mcp/registry/{id}`

Parameters

Parameter name	Required	Type	Description
`id`	V	string	

Code Examples

Shell/Bash

```
# API call example (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/mcp/registry/550e8400-e29b-41d4-
a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/mcp/registry/550e8400-e29b-41d4-
a716-446655440000/", config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/mcp/registry/550e8400-e29b-41d4-a716-446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->get("https://api.maiagent.ai/api/v1/mcp/registry/550e8400-e29b-41d4-a716-446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response Body

Status code: 200

Example Response Schema

```
{
  "id": string (uuid)
  "name": string // MCP service name (e.g., Supabase, Sentry). Only alphanumeric, underscore and hyphen allowed.
  "displayName"?: string // Human-readable display name (defaults to name if empty) (Optional)
  "description"?: string // Brief description of the MCP service (Optional)
```

```
  "remoteMcpUrl": string (uri) // The URL of the Remote MCP service
  "oauthServerUrl"?: // May have different types (Optional)
  string (uri) // Manual override for the OAuth authorization server URL. Leave empty to auto-discover from the MCP server (RFC 9728 protected resource metadata). Only fill in when auto-discovery fails or the server advertises incorrect metadata. (e.g., Supabase MCP is at mcp.supabase.com but OAuth is at api.supabase.com) (Optional)
  "logoUrl": string (uri)
  "isActive"?: boolean // Whether this MCP service is currently available for use (Optional)
  "isGlobal"?: boolean // Global registries are maintained by the platform and available to all organizations. (Optional)
  "authType"?:  // How to authenticate with this MCP server.

* `oauth` - OAuth 2.0
* `service_account` - Service Account
* `none` - No Authentication (Optional)
  {
  }
  "createdAt": string (timestamp)
  "updatedAt": string (timestamp)
}
```

Example Response Values

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "name": "Response string",
  "displayName": "Response string",
  "description": "Response string",
  "remoteMcpUrl": "https://example.com/file.jpg",
  "oauthServerUrl": "https://example.com/file.jpg",
  "logoUrl": "https://example.com/file.jpg",
  "isActive": false,
  "isGlobal": false,
  "authType": {},
  "createdAt": "Response string",
  "updatedAt": "Response string"
}
```

List the Organization’ s Self-hosted MCP Servers

GET `/api/v1/mcp/private-registry/`

Connector management permission is required. For connection instructions, see Self-hosted MCP Server in the technical manual.

Code Examples

Shell/Bash

```
# API call example (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/mcp/private-registry/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/mcp/private-registry/", config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/mcp/private-registry/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->get("https://api.maiagent.ai/api/v1/mcp/private-registry/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response Body

Status code: 200

Example Response Schema

```
[
  {
    "id": string (uuid)
    "name": string // MCP service name (e.g., Supabase, Sentry). Only alphanumeric, underscore and hyphen allowed.
    "displayName"?: string // Human-readable display name (defaults to name if empty) (Optional)
    "description"?: string // Brief description of the MCP service (Optional)
```

```
    "remoteMcpUrl": string (uri) // The URL of the Remote MCP service
    "oauthServerUrl"?: // May have different types (Optional)
    string (uri) // Manual override for the OAuth authorization server URL. Leave empty to auto-discover from the MCP server (RFC 9728 protected resource metadata). Only fill in when auto-discovery fails or the server advertises incorrect metadata. (e.g., Supabase MCP is at mcp.supabase.com but OAuth is at api.supabase.com) (Optional)
    "resourceIdentifier"?: // May have different types (Optional)
    string (uri) // Manual override for the OAuth resource identifier (RFC 9728 / RFC 8707). Leave empty to auto-discover from the MCP server's .well-known/oauth-protected-resource endpoint. Only fill in when auto-discovery fails or the metadata is incorrect. (e.g., Asana uses https://mcp.asana.com, Supabase uses https://mcp.supabase.com/mcp) (Optional)
    "oauthClientId"?: string // Pre-registered OAuth client ID for MCP servers that do not support dynamic client registration (RFC 7591). Leave empty if the server supports dynamic registration. (Optional)
    "oauthClientSecret"?: string // Pre-registered OAuth client secret. Required only if the MCP server requires a confidential client. Leave empty for public clients (token_endpoint_auth_method=none). (Optional)
    "logoUrl"?: // May have different types (Optional)
    string (uri) // Logo: the uploaded storage object key (media/...) or an external URL; read back as a signed URL. (Optional)
    "authType"?:  // How to authenticate with this MCP server.

* `oauth` - OAuth 2.0
* `service_account` - Service Account
* `none` - No Authentication (Optional)
    {
    }
    "cspAllowedOrigins"?: object // Extra origins a SEP-1865 MCP App card from this server may load from (script-src/img-src/connect-src etc.), e.g. ['https://viewer.diagrams.net']. The sandboxed iframe denies all external origins by default; list only what the app genuinely needs. Empty = the host's strict default (self only). (Optional)
    "isActive": boolean // Whether this MCP service is currently available for use
    "createdAt": string (timestamp)
    "updatedAt": string (timestamp)
  }
]
```

Example Response Values

```
[
  {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Response string",
    "displayName": "Response string",
```

```
    "description": "Response string",
    "remoteMcpUrl": "https://example.com/file.jpg",
    "oauthServerUrl": "https://example.com/file.jpg",
    "resourceIdentifier": "https://example.com/file.jpg",
    "oauthClientId": "Response string",
    "oauthClientSecret": "Response string",
    "logoUrl": "https://example.com/file.jpg",
    "authType": {},
    "cspAllowedOrigins": null,
    "isActive": false,
    "createdAt": "Response string",
    "updatedAt": "Response string"
  }
]
```


Add a Self-hosted MCP Server

POST `/api/v1/mcp/private-registry/`

Request Body

Request Parameters

Field	Type	Required	Description
name	string	Yes	MCP service name (e.g., Supabase, Sentry). Only alphanumeric, underscore and hyphen allowed.
displayName	string	No	Human-readable display name (defaults to name if empty)
description	string	No	Brief description of the MCP service
remoteMcpUrl	string (uri)	Yes	The URL of the Remote MCP service
oauthServerUrl	object	No	Manual override for the OAuth authorization server URL. Leave empty to auto-discover from the MCP server (RFC 9728 protected resource metadata). Only fill in when auto-discovery fails or the server ad...

Field	Type	Required	Description
resourceIdentifier	object	No	Manual override for the OAuth resource identifier (RFC 9728 / RFC 8707). Leave empty to auto-discover from the MCP server's .well-known/oauth-protected-resource endpoint. Only fill in when auto-discov...
oauthClientId	string	No	Pre-registered OAuth client ID for MCP servers that do not support dynamic client registration (RFC 7591). Leave empty if the server supports dynamic registration.
oauthClientSecret	string	No	Pre-registered OAuth client secret. Required only if the MCP server requires a confidential client. Leave empty for public clients (token_endpoint_auth_method=none).
logoUrl	object	No	Logo: the uploaded storage object key (media/...) or an external URL; read back as a signed URL.
authType	object	No	How to authenticate with this MCP server. `oauth` : OAuth 2.0 ; `service_account` : Service Account ; `none` : No Authentication;
cspAllowedOrigins	object	No	Extra origins a SEP-1865 MCP App card from this server may load from (script-src/img-src/connect-src etc.), e.g. ['https://viewer.diagrams.net']. The sandboxed iframe denies all external origins by de...

Example Request Schema

```
{
  "name": string // MCP service name (e.g., Supabase, Sentry). Only alphanumeric, underscore and hyphen allowed.
  "displayName"?: string // Human-readable display name (defaults to name if empty) (Optional)
  "description"?: string // Brief description of the MCP service (Optional)
  "remoteMcpUrl": string (uri) // The URL of the Remote MCP service
  "oauthServerUrl"?: // May have different types (Optional)
  string (uri) // Manual override for the OAuth authorization server URL. Leave empty to auto-discover from the MCP server (RFC 9728 protected resource metadata). Only fill in when auto-discovery fails or the server advertises incorrect metadata. (e.g., Supabase MCP is at mcp.supabase.com but OAuth is at api.supabase.com) (Optional)
  "resourceIdentifier"?: // May have different types (Optional)
  string (uri) // Manual override for the OAuth resource identifier (RFC 9728 / RFC 8707). Leave empty to auto-discover from the MCP server's .well-known/oauth-protected-resource endpoint. Only fill in when auto-discovery fails or the metadata is incorrect. (e.g., Asana uses https://mcp.asana.com, Supabase uses
```

```
https://mcp.supabase.com/mcp) (Optional)
  "oauthClientId"?: string // Pre-registered OAuth client ID for MCP servers that do not support dynamic client registration (RFC 7591). Leave empty if the server supports dynamic registration. (Optional)
  "oauthClientSecret"?: string // Pre-registered OAuth client secret. Required only if the MCP server requires a confidential client. Leave empty for public clients (token_endpoint_auth_method=none). (Optional)
  "logoUrl"?: // May have different types (Optional)
  string (uri) // Logo: the uploaded storage object key (media/...) or an external URL; read back as a signed URL. (Optional)
  "authType"?:  // How to authenticate with this MCP server.

* `oauth` - OAuth 2.0
* `service_account` - Service Account
* `none` - No Authentication (Optional)
  {
  }
  "cspAllowedOrigins"?: object // Extra origins a SEP-1865 MCP App card from this server may load from (script-src/img-src/connect-src etc.), e.g. ['https://viewer.diagrams.net']. The sandboxed iframe denies all external origins by default; list only what the app genuinely needs. Empty = the host's strict default (self only). (Optional)
}
```

Example Request Values

```
{
  "name": "Example name",
  "displayName": "Example string",
  "description": "Example string",
  "remoteMcpUrl": "https://example.com/file.jpg",
  "oauthServerUrl": null,
  "resourceIdentifier": null,
  "oauthClientId": "Example string",
  "oauthClientSecret": "Example string",
  "logoUrl": null,
  "authType": {},
  "cspAllowedOrigins": null
}
```

Code Examples

Shell/Bash

```
# API call example (Shell)
curl -X POST "https://api.maiagent.ai/api/v1/mcp/private-registry/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "name": "Example name",
    "displayName": "Example string",
    "description": "Example string",
    "remoteMcpUrl": "https://example.com/file.jpg",
    "oauthServerUrl": null,
    "resourceIdentifier": null,
    "oauthClientId": "Example string",
    "oauthClientSecret": "Example string",
    "logoUrl": null,
    "authType": {},
    "cspAllowedOrigins": null
  }'

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// Request body (payload)
const data = {
    "name": "Example name",
    "displayName": "Example string",
    "description": "Example string",
    "remoteMcpUrl": "https://example.com/file.jpg",
    "oauthServerUrl": null,
    "resourceIdentifier": null,
    "oauthClientId": "Example string",
    "oauthClientSecret": "Example string",
    "logoUrl": null,
    "authType": {},
    "cspAllowedOrigins": null
  };

axios.post("https://api.maiagent.ai/api/v1/mcp/private-registry/", data,
config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/mcp/private-registry/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# Request body (payload)
data = {
    "name": "Example name",
    "displayName": "Example string",
    "description": "Example string",
    "remoteMcpUrl": "https://example.com/file.jpg",
    "oauthServerUrl": None,
    "resourceIdentifier": None,
    "oauthClientId": "Example string",
    "oauthClientSecret": "Example string",
    "logoUrl": None,
    "authType": {},
    "cspAllowedOrigins": None
}

response = requests.post(url, json=data, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request failed:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->post("https://api.maiagent.ai/api/v1/mcp/private-registry/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'name' => 'Example name',
            'displayName' => 'Example string',
            'description' => 'Example string',
            'remoteMcpUrl' => 'https://example.com/file.jpg',
            'oauthServerUrl' => null,
            'resourceIdentifier' => null,
            'oauthClientId' => 'Example string',
            'oauthClientSecret' => 'Example string',
            'logoUrl' => null,
            'authType' => new \stdClass(),
            'cspAllowedOrigins' => null
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request failed: ' . $e->getMessage();
}
?>
```

Response Body

Status Code: 201

Example Response Schema

```
{
  "id": string (uuid)
  "name": string // MCP service name (e.g., Supabase, Sentry). Only alphanumeric, underscore and hyphen allowed.
  "displayName"?: string // Human-readable display name (defaults to name if empty) (Optional)
  "description"?: string // Brief description of the MCP service (Optional)
  "remoteMcpUrl": string (uri) // The URL of the Remote MCP service
  "oauthServerUrl"?: // May have different types (Optional)
  string (uri) // Manual override for the OAuth authorization server URL. Leave empty to auto-discover from the MCP server (RFC 9728 protected resource metadata). Only fill in when auto-discovery fails or the server advertises incorrect metadata. (e.g., Supabase MCP is at mcp.supabase.com but OAuth is at api.supabase.com) (Optional)
  "resourceIdentifier"?: // May have different types (Optional)
  string (uri) // Manual override for the OAuth resource identifier (RFC 9728 / RFC 8707). Leave empty to auto-discover from the MCP server's .well-known/oauth-protected-resource endpoint. Only fill in when auto-discovery fails or the metadata is incorrect. (e.g., Asana uses https://mcp.asana.com, Supabase uses https://mcp.supabase.com/mcp) (Optional)
  "oauthClientId"?: string // Pre-registered OAuth client ID for MCP servers that do not support dynamic client registration (RFC 7591). Leave empty if the server supports dynamic registration. (Optional)
  "oauthClientSecret"?: string // Pre-registered OAuth client secret. Required only if the MCP server requires a confidential client. Leave empty for public clients (token_endpoint_auth_method=none). (Optional)
  "logoUrl"?: // May have different types (Optional)
  string (uri) // Logo: the uploaded storage object key (media/...) or an external URL; read back as a signed URL. (Optional)
  "authType"?:  // How to authenticate with this MCP server.

* `oauth` - OAuth 2.0
* `service_account` - Service Account
* `none` - No Authentication (Optional)
  {
  }
  "cspAllowedOrigins"?: object // Extra origins a SEP-1865 MCP App card from this server may load from (script-src/img-src/connect-src etc.), e.g. ['https://viewer.diagrams.net']. The sandboxed iframe denies all external origins by default; list only what the app genuinely needs. Empty = the host's strict default (self only). (Optional)
  "isActive": boolean // Whether this MCP service is currently available for use
  "createdAt": string (timestamp)
```

```
  "updatedAt": string (timestamp)
}
```

Example Response Values

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "name": "Response string",
  "displayName": "Response string",
  "description": "Response string",
  "remoteMcpUrl": "https://example.com/file.jpg",
  "oauthServerUrl": "https://example.com/file.jpg",
  "resourceIdentifier": "https://example.com/file.jpg",
  "oauthClientId": "Response string",
  "oauthClientSecret": "Response string",
  "logoUrl": "https://example.com/file.jpg",
  "authType": {},
  "cspAllowedOrigins": null,
  "isActive": false,
  "createdAt": "Response string",
  "updatedAt": "Response string"
}
```

Retrieve a Specific Self-hosted MCP Server

GET `/api/v1/mcp/private-registry/{id}`

Parameters

Parameter Name	Required	Type	Description
`id`	V	string	A UUID string identifying this MCP Registry.

Code Examples

Shell/Bash

```
# API Call Example (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/mcp/private-registry/550e8400-
e29b-41d4-a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/mcp/private-registry/550e8400-
e29b-41d4-a716-446655440000/", config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request failed:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/mcp/private-registry/550e8400-e29b-
41d4-a716-446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request failed:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->get("https://api.maiagent.ai/api/v1/mcp/private-registry/550e8400-e29b-41d4-a716-446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request failed: ' . $e->getMessage();
}
?>
```

Response Body

Status Code: 200

Example Response Schema

```
{
  "id": string (uuid)
  "name": string // MCP service name (e.g., Supabase, Sentry). Only alphanumeric, underscore and hyphen allowed.
  "displayName"?: string // Human-readable display name (defaults to name if empty) (Optional)
  "description"?: string // Brief description of the MCP service (Optional)
  "remoteMcpUrl": string (uri) // The URL of the Remote MCP service
```

```
  "oauthServerUrl"?: // May have different types (Optional)
  string (uri) // Manual override for the OAuth authorization server URL. Leave
empty to auto-discover from the MCP server (RFC 9728 protected resource
metadata). Only fill in when auto-discovery fails or the server advertises
incorrect metadata. (e.g., Supabase MCP is at mcp.supabase.com but OAuth is at
api.supabase.com) (Optional)
  "resourceIdentifier"?: // May have different types (Optional)
  string (uri) // Manual override for the OAuth resource identifier (RFC 9728 /
RFC 8707). Leave empty to auto-discover from the MCP server's .well-known/oauth-
protected-resource endpoint. Only fill in when auto-discovery fails or the
metadata is incorrect. (e.g., Asana uses https://mcp.asana.com, Supabase uses
https://mcp.supabase.com/mcp) (Optional)
  "oauthClientId"?: string // Pre-registered OAuth client ID for MCP servers that
do not support dynamic client registration (RFC 7591). Leave empty if the server
supports dynamic registration. (Optional)
  "oauthClientSecret"?: string // Pre-registered OAuth client secret. Required
only if the MCP server requires a confidential client. Leave empty for public
clients (token_endpoint_auth_method=none). (Optional)
  "logoUrl"?: // May have different types (Optional)
  string (uri) // Logo: the uploaded storage object key (media/...) or an
external URL; read back as a signed URL. (Optional)
  "authType"?:  // How to authenticate with this MCP server.

* `oauth` - OAuth 2.0
* `service_account` - Service Account
* `none` - No Authentication (Optional)
  {
  }
  "cspAllowedOrigins"?: object // Extra origins a SEP-1865 MCP App card from this
server may load from (script-src/img-src/connect-src etc.), e.g.
['https://viewer.diagrams.net']. The sandboxed iframe denies all external origins
by default; list only what the app genuinely needs. Empty = the host's strict
default (self only). (Optional)
  "isActive": boolean // Whether this MCP service is currently available for use
  "createdAt": string (timestamp)
  "updatedAt": string (timestamp)
}
```

Example Response Values

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "name": "Response string",
  "displayName": "Response string",
  "description": "Response string",
  "remoteMcpUrl": "https://example.com/file.jpg",
  "oauthServerUrl": "https://example.com/file.jpg",
  "resourceIdentifier": "https://example.com/file.jpg",
```

```
  "oauthClientId": "Response string",
  "oauthClientSecret": "Response string",
  "logoUrl": "https://example.com/file.jpg",
  "authType": {},
  "cspAllowedOrigins": null,
  "isActive": false,
  "createdAt": "Response string",
  "updatedAt": "Response string"
}
```


Partially Update a Self-hosted MCP Server

PATCH `/api/v1/mcp/private-registry/{id}`

Parameters

Parameter Name	Required	Type	Description
`id`	V	string	A UUID string identifying this MCP Registry.

Request Body

Request Parameters

Field	Type	Required	Description
name	string	No	MCP service name (e.g., Supabase, Sentry). Only alphanumeric, underscore and hyphen allowed.
displayName	string	No	Human-readable display name (defaults to name if empty)
description	string	No	Brief description of the MCP service
remoteMcpUrl	string (uri)	No	The URL of the Remote MCP service

Field	Type	Required	Description
oauthServerUrl	object	No	Manual override for the OAuth authorization server URL. Leave empty to auto-discover from the MCP server (RFC 9728 protected resource metadata). Only fill in when auto-discovery fails or the server ad...
resourceIdentifier	object	No	Manual override for the OAuth resource identifier (RFC 9728 / RFC 8707). Leave empty to auto-discover from the MCP server's .well-known/oauth-protected-resource endpoint. Only fill in when auto-discov...
oauthClientId	string	No	Pre-registered OAuth client ID for MCP servers that do not support dynamic client registration (RFC 7591). Leave empty if the server supports dynamic registration.
oauthClientSecret	string	No	Pre-registered OAuth client secret. Required only if the MCP server requires a confidential client. Leave empty for public clients (token_endpoint_auth_method=none).
logoUrl	object	No	Logo: the uploaded storage object key (media/...) or an external URL; read back as a signed URL.
authType	object	No	How to authenticate with this MCP server. `oauth` : OAuth 2.0 ; `service_account` : Service Account ; `none` : No Authentication;
cspAllowedOrigins	object	No	Extra origins a SEP-1865 MCP App card from this server may load from (script-src/img-src/connect-src etc.), e.g. ['https://viewer.diagrams.net']. The sandboxed iframe denies all external origins by de...

Example Request Schema

```
{
  "name"?: string // MCP service name (e.g., Supabase, Sentry). Only
alphanumeric, underscore and hyphen allowed. (Optional)
  "displayName"?: string // Human-readable display name (defaults to name if
empty) (Optional)
  "description"?: string // Brief description of the MCP service (Optional)
  "remoteMcpUrl"?: string (uri) // The URL of the Remote MCP service (Optional)
  "oauthServerUrl"?: // May have different types (Optional)
  string (uri) // Manual override for the OAuth authorization server URL. Leave
empty to auto-discover from the MCP server (RFC 9728 protected resource
metadata). Only fill in when auto-discovery fails or the server advertises
incorrect metadata. (e.g., Supabase MCP is at mcp.supabase.com but OAuth is at
api.supabase.com) (Optional)
```

```
  "resourceIdentifier"?: // May have different types (Optional)
  string (uri) // Manual override for the OAuth resource identifier (RFC 9728 / RFC 8707). Leave empty to auto-discover from the MCP server's .well-known/oauth-protected-resource endpoint. Only fill in when auto-discovery fails or the metadata is incorrect. (e.g., Asana uses https://mcp.asana.com, Supabase uses https://mcp.supabase.com/mcp) (Optional)
  "oauthClientId"?: string // Pre-registered OAuth client ID for MCP servers that do not support dynamic client registration (RFC 7591). Leave empty if the server supports dynamic registration. (Optional)
  "oauthClientSecret"?: string // Pre-registered OAuth client secret. Required only if the MCP server requires a confidential client. Leave empty for public clients (token_endpoint_auth_method=none). (Optional)
  "logoUrl"?: // May have different types (Optional)
  string (uri) // Logo: the uploaded storage object key (media/...) or an external URL; read back as a signed URL. (Optional)
  "authType"?:  // How to authenticate with this MCP server.

* `oauth` - OAuth 2.0
* `service_account` - Service Account
* `none` - No Authentication (Optional)
  {
  }
  "cspAllowedOrigins"?: object // Extra origins a SEP-1865 MCP App card from this server may load from (script-src/img-src/connect-src etc.), e.g. ['https://viewer.diagrams.net']. The sandboxed iframe denies all external origins by default; list only what the app genuinely needs. Empty = the host's strict default (self only). (Optional)
}
```

Example Request Values

```
{
  "name": "Example name",
  "displayName": "Example string",
  "description": "Example string",
  "remoteMcpUrl": "https://example.com/file.jpg",
  "oauthServerUrl": null,
  "resourceIdentifier": null,
  "oauthClientId": "Example string",
  "oauthClientSecret": "Example string",
  "logoUrl": null,
  "authType": {},
  "cspAllowedOrigins": null
}
```

Code Examples

Shell/Bash

```
# API Call Example (Shell)
curl -X PATCH "https://api.maiagent.ai/api/v1/mcp/private-registry/550e8400-
e29b-41d4-a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "name": "Example name",
    "displayName": "Example string",
    "description": "Example string",
    "remoteMcpUrl": "https://example.com/file.jpg",
    "oauthServerUrl": null,
    "resourceIdentifier": null,
    "oauthClientId": "Example string",
    "oauthClientSecret": "Example string",
    "logoUrl": null,
    "authType": {},
    "cspAllowedOrigins": null
  }'

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// Request body (payload)
const data = {
    "name": "Example name",
    "displayName": "Example string",
    "description": "Example string",
    "remoteMcpUrl": "https://example.com/file.jpg",
    "oauthServerUrl": null,
    "resourceIdentifier": null,
    "oauthClientId": "Example string",
    "oauthClientSecret": "Example string",
    "logoUrl": null,
    "authType": {},
    "cspAllowedOrigins": null
  };

axios.patch("https://api.maiagent.ai/api/v1/mcp/private-registry/550e8400-
e29b-41d4-a716-446655440000/", data, config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request failed:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/mcp/private-registry/550e8400-e29b-
41d4-a716-446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# Request body (payload)
data = {
    "name": "Example name",
    "displayName": "Example string",
    "description": "Example string",
    "remoteMcpUrl": "https://example.com/file.jpg",
    "oauthServerUrl": None,
    "resourceIdentifier": None,
    "oauthClientId": "Example string",
    "oauthClientSecret": "Example string",
    "logoUrl": None,
    "authType": {},
    "cspAllowedOrigins": None
}

response = requests.patch(url, json=data, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request failed:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->patch("https://api.maiagent.ai/api/v1/mcp/private-registry/550e8400-e29b-41d4-a716-446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'name' => 'Example name',
            'displayName' => 'Example string',
            'description' => 'Example string',
            'remoteMcpUrl' => 'https://example.com/file.jpg',
            'oauthServerUrl' => null,
            'resourceIdentifier' => null,
            'oauthClientId' => 'Example string',
            'oauthClientSecret' => 'Example string',
            'logoUrl' => null,
            'authType' => new \stdClass(),
            'cspAllowedOrigins' => null
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request failed: ' . $e->getMessage();
}
?>
```

Response Body

Status Code: 200

Example Response Schema

```
{
  "id": string (uuid)
  "name": string // MCP service name (e.g., Supabase, Sentry). Only alphanumeric, underscore and hyphen allowed.
  "displayName"?: string // Human-readable display name (defaults to name if empty) (Optional)
  "description"?: string // Brief description of the MCP service (Optional)
  "remoteMcpUrl": string (uri) // The URL of the Remote MCP service
  "oauthServerUrl"?: // May have different types (Optional)
  string (uri) // Manual override for the OAuth authorization server URL. Leave empty to auto-discover from the MCP server (RFC 9728 protected resource metadata). Only fill in when auto-discovery fails or the server advertises incorrect metadata. (e.g., Supabase MCP is at mcp.supabase.com but OAuth is at api.supabase.com) (Optional)
  "resourceIdentifier"?: // May have different types (Optional)
  string (uri) // Manual override for the OAuth resource identifier (RFC 9728 / RFC 8707). Leave empty to auto-discover from the MCP server's .well-known/oauth-protected-resource endpoint. Only fill in when auto-discovery fails or the metadata is incorrect. (e.g., Asana uses https://mcp.asana.com, Supabase uses https://mcp.supabase.com/mcp) (Optional)
  "oauthClientId"?: string // Pre-registered OAuth client ID for MCP servers that do not support dynamic client registration (RFC 7591). Leave empty if the server supports dynamic registration. (Optional)
  "oauthClientSecret"?: string // Pre-registered OAuth client secret. Required only if the MCP server requires a confidential client. Leave empty for public clients (token_endpoint_auth_method=none). (Optional)
  "logoUrl"?: // May have different types (Optional)
  string (uri) // Logo: the uploaded storage object key (media/...) or an external URL; read back as a signed URL. (Optional)
  "authType"?:  // How to authenticate with this MCP server.

* `oauth` - OAuth 2.0
* `service_account` - Service Account
* `none` - No Authentication (Optional)
  {
  }
  "cspAllowedOrigins"?: object // Extra origins a SEP-1865 MCP App card from this server may load from (script-src/img-src/connect-src etc.), e.g. ['https://viewer.diagrams.net']. The sandboxed iframe denies all external origins by default; list only what the app genuinely needs. Empty = the host's strict default (self only). (Optional)
  "isActive": boolean // Whether this MCP service is currently available for use
  "createdAt": string (timestamp)
```

```
  "updatedAt": string (timestamp)
}
```

Example Response Values

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "name": "Response string",
  "displayName": "Response string",
  "description": "Response string",
  "remoteMcpUrl": "https://example.com/file.jpg",
  "oauthServerUrl": "https://example.com/file.jpg",
  "resourceIdentifier": "https://example.com/file.jpg",
  "oauthClientId": "Response string",
  "oauthClientSecret": "Response string",
  "logoUrl": "https://example.com/file.jpg",
  "authType": {},
  "cspAllowedOrigins": null,
  "isActive": false,
  "createdAt": "Response string",
  "updatedAt": "Response string"
}
```

Delete a Self-hosted MCP Server

DELETE `/api/v1/mcp/private-registry/{id}`

Parameters

Parameter Name	Required	Type	Description
`id`	V	string	A UUID string identifying this MCP Registry.

Code Examples

Shell/Bash

```
# API call example (Shell)
curl -X DELETE "https://api.maiagent.ai/api/v1/mcp/private-
registry/550e8400-e29b-41d4-a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

// Request body (payload)
const data = null;

axios.delete("https://api.maiagent.ai/api/v1/mcp/private-registry/550e8400-
e29b-41d4-a716-446655440000/", data, config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/mcp/private-registry/550e8400-e29b-
41d4-a716-446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.delete(url, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->delete("https://api.maiagent.ai/api/v1/mcp/private-registry/550e8400-e29b-41d4-a716-446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response Body

Status Code	Description
204	No response body

Test MCP Server Connection

POST `/api/v1/mcp/private-registry/test-connection/`

Request Body

Request Parameters

Field	Type	Required	Description
name	string	Yes	MCP service name (e.g., Supabase, Sentry). Only alphanumeric, underscore and hyphen allowed.
displayName	string	No	Human-readable display name (defaults to name if empty)
description	string	No	Brief description of the MCP service
remoteMcpUrl	string (uri)	Yes	The URL of the Remote MCP service
oauthServerUrl	object	No	Manual override for the OAuth authorization server URL. Leave empty to auto-discover from the MCP server (RFC 9728 protected resource metadata). Only fill in when auto-discovery fails or the server ad...
resourceIdentifier	object	No	Manual override for the OAuth resource identifier (RFC 9728 / RFC 8707). Leave empty to auto-discover from the MCP server's .well-known/oauth-protected-resource endpoint. Only fill in when auto-discov...
oauthClientId	string	No	Pre-registered OAuth client ID for MCP servers that do not support dynamic client registration (RFC 7591). Leave empty if the server supports dynamic registration.
oauthClientSecret	string	No	Pre-registered OAuth client secret. Required only if the MCP server requires a confidential client. Leave empty for public clients (token_endpoint_auth_method=none).
logoUrl	object	No	Logo: the uploaded storage object key (media/...) or an external URL; read back as a signed URL.
authType	object	No	How to authenticate with this MCP server. `oauth` : OAuth 2.0 ; `service_account` : Service Account ; `none` : No Authentication;
cspAllowedOrigins	object	No	Extra origins a SEP-1865 MCP App card from this server may load from (script-src/img-src/connect-src etc.), e.g. ['https://viewer.diagrams.net']. The sandboxed iframe denies all external origins by de...

Example Request Schema

```
{
  "name": string // MCP service name (e.g., Supabase, Sentry). Only alphanumeric, underscore and hyphen allowed.
  "displayName"?: string // Human-readable display name (defaults to name if empty) (Optional)
  "description"?: string // Brief description of the MCP service (Optional)
  "remoteMcpUrl": string (uri) // The URL of the Remote MCP service
  "oauthServerUrl"?: // May have different types (Optional)
  string (uri) // Manual override for the OAuth authorization server URL. Leave empty to auto-discover from the MCP server (RFC 9728 protected resource metadata). Only fill in when auto-discovery fails or the server advertises incorrect metadata. (e.g., Supabase MCP is at mcp.supabase.com but OAuth is at api.supabase.com) (Optional)
  "resourceIdentifier"?: // May have different types (Optional)
  string (uri) // Manual override for the OAuth resource identifier (RFC 9728 / RFC 8707). Leave empty to auto-discover from the MCP server's .well-known/oauth-protected-resource endpoint. Only fill in when auto-discovery fails or the metadata is incorrect. (e.g., Asana uses https://mcp.asana.com, Supabase uses https://mcp.supabase.com/mcp) (Optional)
  "oauthClientId"?: string // Pre-registered OAuth client ID for MCP servers that do not support dynamic client registration (RFC 7591). Leave empty if the server supports dynamic registration. (Optional)
  "oauthClientSecret"?: string // Pre-registered OAuth client secret. Required only if the MCP server requires a confidential client. Leave empty for public clients (token_endpoint_auth_method=none). (Optional)
  "logoUrl"?: // May have different types (Optional)
  string (uri) // Logo: the uploaded storage object key (media/...) or an external URL; read back as a signed URL. (Optional)
  "authType"?:  // How to authenticate with this MCP server.

* `oauth` - OAuth 2.0
* `service_account` - Service Account
* `none` - No Authentication (Optional)
  {
  }
  "cspAllowedOrigins"?: object // Extra origins a SEP-1865 MCP App card from this server may load from (script-src/img-src/connect-src etc.), e.g. ['https://viewer.diagrams.net']. The sandboxed iframe denies all external origins by default; list only what the app genuinely needs. Empty = the host's strict default (self only). (Optional)
}
```

Example Request Values

```
{
  "name": "Example name",
  "displayName": "Example string",
```

```
  "description": "Example string",
  "remoteMcpUrl": "https://example.com/file.jpg",
  "oauthServerUrl": null,
  "resourceIdentifier": null,
  "oauthClientId": "Example string",
  "oauthClientSecret": "Example string",
  "logoUrl": null,
  "authType": {},
  "cspAllowedOrigins": null
}
```


Code Examples

Shell/Bash

```
# API call example (Shell)
curl -X POST "https://api.maiagent.ai/api/v1/mcp/private-registry/test-
connection/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "name": "Example name",
    "displayName": "Example string",
    "description": "Example string",
    "remoteMcpUrl": "https://example.com/file.jpg",
    "oauthServerUrl": null,
    "resourceIdentifier": null,
    "oauthClientId": "Example string",
    "oauthClientSecret": "Example string",
    "logoUrl": null,
    "authType": {},
    "cspAllowedOrigins": null
  }'

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// Request body (payload)
const data = {
    "name": "Example name",
    "displayName": "Example string",
    "description": "Example string",
    "remoteMcpUrl": "https://example.com/file.jpg",
    "oauthServerUrl": null,
    "resourceIdentifier": null,
    "oauthClientId": "Example string",
    "oauthClientSecret": "Example string",
    "logoUrl": null,
    "authType": {},
    "cspAllowedOrigins": null
  };

axios.post("https://api.maiagent.ai/api/v1/mcp/private-registry/test-
connection/", data, config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/mcp/private-registry/test-connection/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# Request body (payload)
data = {
    "name": "Example name",
    "displayName": "Example string",
    "description": "Example string",
    "remoteMcpUrl": "https://example.com/file.jpg",
    "oauthServerUrl": None,
    "resourceIdentifier": None,
    "oauthClientId": "Example string",
    "oauthClientSecret": "Example string",
    "logoUrl": None,
    "authType": {},
    "cspAllowedOrigins": None
}

response = requests.post(url, json=data, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->post("https://api.maiagent.ai/api/v1/mcp/private-registry/test-connection/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'name' => 'Example name',
            'displayName' => 'Example string',
            'description' => 'Example string',
            'remoteMcpUrl' => 'https://example.com/file.jpg',
            'oauthServerUrl' => null,
            'resourceIdentifier' => null,
            'oauthClientId' => 'Example string',
            'oauthClientSecret' => 'Example string',
            'logoUrl' => null,
            'authType' => new \stdClass(),
            'cspAllowedOrigins' => null
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response Body

Status Code: 200

Example Response Schema

```
{
  "id": string (uuid)
  "name": string // MCP service name (e.g., Supabase, Sentry). Only alphanumeric, underscore and hyphen allowed.
  "displayName"?: string // Human-readable display name (defaults to name if empty) (Optional)
  "description"?: string // Brief description of the MCP service (Optional)
  "remoteMcpUrl": string (uri) // The URL of the Remote MCP service
  "oauthServerUrl"?: // May have different types (Optional)
  string (uri) // Manual override for the OAuth authorization server URL. Leave empty to auto-discover from the MCP server (RFC 9728 protected resource metadata). Only fill in when auto-discovery fails or the server advertises incorrect metadata. (e.g., Supabase MCP is at mcp.supabase.com but OAuth is at api.supabase.com) (Optional)
  "resourceIdentifier"?: // May have different types (Optional)
  string (uri) // Manual override for the OAuth resource identifier (RFC 9728 / RFC 8707). Leave empty to auto-discover from the MCP server's .well-known/oauth-protected-resource endpoint. Only fill in when auto-discovery fails or the metadata is incorrect. (e.g., Asana uses https://mcp.asana.com, Supabase uses https://mcp.supabase.com/mcp) (Optional)
  "oauthClientId"?: string // Pre-registered OAuth client ID for MCP servers that do not support dynamic client registration (RFC 7591). Leave empty if the server supports dynamic registration. (Optional)
  "oauthClientSecret"?: string // Pre-registered OAuth client secret. Required only if the MCP server requires a confidential client. Leave empty for public clients (token_endpoint_auth_method=none). (Optional)
  "logoUrl"?: // May have different types (Optional)
  string (uri) // Logo: the uploaded storage object key (media/...) or an external URL; read back as a signed URL. (Optional)
  "authType"?:  // How to authenticate with this MCP server.

* `oauth` - OAuth 2.0
* `service_account` - Service Account
* `none` - No Authentication (Optional)
  {
  }
  "cspAllowedOrigins"?: object // Extra origins a SEP-1865 MCP App card from this server may load from (script-src/img-src/connect-src etc.), e.g. ['https://viewer.diagrams.net']. The sandboxed iframe denies all external origins by default; list only what the app genuinely needs. Empty = the host's strict default (self only). (Optional)
  "isActive": boolean // Whether this MCP service is currently available for use
  "createdAt": string (timestamp)
```

```
  "updatedAt": string (timestamp)
}
```

Example Response Values

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "name": "Response string",
  "displayName": "Response string",
  "description": "Response string",
  "remoteMcpUrl": "https://example.com/file.jpg",
  "oauthServerUrl": "https://example.com/file.jpg",
  "resourceIdentifier": "https://example.com/file.jpg",
  "oauthClientId": "Response string",
  "oauthClientSecret": "Response string",
  "logoUrl": "https://example.com/file.jpg",
  "authType": {},
  "cspAllowedOrigins": null,
  "isActive": false,
  "createdAt": "Response string",
  "updatedAt": "Response string"
}
```

List tool execution records

`GET` `/api/v1/tool-execution-records/`

Parameters

Parameter name	Required	Type	Description
`chatbot`	X	string	Filter by AI assistant ID
`endDate`	X	string	End date (inclusive), format: YYYY-MM-DD
`page`	X	integer	A page number within the paginated result set.

`pageSize`	X	integer	Number of results to return per page.
`query`	X	string	Search by AI assistant name, tool name, or message content
`startDate`	X	string	Start date (inclusive), format: YYYY-MM-DD
`status`	X	string	Filter by execution status: success, failure, pending, timeout
`tool`	X	string	Filter by tool ID
`toolType`	X	string	Filter by tool type: api, function, mcp

Code examples

Shell/Bash

```
# API call example (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/tool-execution-records/?
chatbot=example&endDate=example&page=1&pageSize=1&query=example&startDate=ex
ample&status=failure&tool=example&toolType=api"

  -H "Authorization: Api-Key YOUR_API_KEY"

# Before running, replace YOUR_API_KEY and verify the request data.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/tool-execution-records/?
chatbot=example&endDate=example&page=1&pageSize=1&query=example&startDate=ex
ample&status=failure&tool=example&toolType=api", config)
  .then(response => {
    console.log('Successfully retrieved response:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('An error occurred during the request:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/tool-execution-records/?
chatbot=example&endDate=example&page=1&pageSize=1&query=example&startDate=ex
ample&status=failure&tool=example&toolType=api"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("Response retrieved successfully:")
    print(response.json())
except Exception as e:
    print("An error occurred during the request:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->get("https://api.maiagent.ai/api/v1/tool-execution-records/?chatbot=example&endDate=example&page=1&pageSize=1&query=example&startDate=example&status=failure&tool=example&toolType=api", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response retrieved successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'An error occurred during the request: ' . $e->getMessage();
}
?>
```

Response body

Status code: 200

Example response structure

```
{
  "count": integer
  "next"?: string (uri) // Optional
  "previous"?: string (uri) // Optional
  "results": [
    {
```

```
      "id": string (uuid)
      "tool": object // Tool information
      "chatbot": object // AI assistant information
      "messageContent": string // Message content
      "status"?: string (enum: success, failure, pending, timeout) // * `success`
- Success
* `failure` - Failed
* `pending` - Processing
* `timeout` - Timeout (Optional)
      "executionTime": integer // Execution time (milliseconds)
      "errorMessage"?: string // Optional
      "retryCount"?: integer // How many times the platform auto-retried this
tool call before the final outcome (0 = the first attempt was the final one). API
tools count tenacity retries inside APIRequestService; MCP tools count transient-
error retries (read-classified tools only). Function tools are never auto-
retried. (Optional)
      "createdAt": string (timestamp)
      "source": string // Scheduled runs' tool calls are attributed via
ChatbotScheduleExecution.user_message.
    }
  ]
}
```

Example response values

```
{
  "count": 123,
  "next": "http://api.example.org/accounts/?page=4",
  "previous": "http://api.example.org/accounts/?page=2",
  "results": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "tool": {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "name": "Example response name",
        "description": "Example response description"
      },
      "chatbot": {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "name": "Example response name",
        "description": "Example response description"
      },
      "messageContent": "Response string",
      "status": "success",
      "executionTime": 456,
      "errorMessage": "Response string",
      "retryCount": 456,
      "createdAt": "Response string",
```

```
      "source": "Response string"
    }
  ]
}
```

Retrieve a specific tool execution record

GET `/api/v1/tool-execution-records/{id}`

Parameters

Parameter name	Required	Type	Description
`id`	V	string	A UUID string identifying this Tool Execution Record.

Code examples

Shell/Bash

```
# API call example (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/tool-execution-records/550e8400-
e29b-41d4-a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# Before running, replace YOUR_API_KEY and verify the request data.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/tool-execution-records/550e8400-e29b-41d4-a716-446655440000/", config)
  .then(response => {
    console.log('Successfully retrieved response:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('An error occurred during the request:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/tool-execution-records/550e8400-e29b-41d4-a716-446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("Response retrieved successfully:")
    print(response.json())
except Exception as e:
    print("An error occurred during the request:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->get("https://api.maiagent.ai/api/v1/tool-execution-records/550e8400-e29b-41d4-a716-446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response retrieved successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'An error occurred during the request: ' . $e->getMessage();
}
?>
```

Response body

Status code: 200

Example response structure

```
{
  "id": string (uuid)
  "tool": object // Tool information, including operated_tool_name
  "chatbot": object // AI assistant information
  "message":
  {
    "id": string (uuid)
    "content": string
```

```
  }
  "inputParameters": object
  "outputResult"?: object // Optional
  "errorMessage"?: string // Optional
  "status"?: string (enum: success, failure, pending, timeout) // * `success` -
Success
* `failure` - Failed
* `pending` - Processing
* `timeout` - Timeout (Optional)
  "executionTime": integer // Execution time (milliseconds)
  "retryCount"?: integer // How many times the platform auto-retried this tool
call before the final outcome (0 = the first attempt was the final one). API
tools count tenacity retries inside APIRequestService; MCP tools count transient-
error retries (read-classified tools only). Function tools are never auto-
retried. (Optional)
  "requestUrl"?: // Can be of different types (Optional)
  string (uri) // Final rendered URL used when calling an API tool. Null for non-
API tools. (Optional)
  "requestMethod"?: string // HTTP method (GET/POST/...) used when calling an API
tool. Null for non-API tools. (Optional)
  "requestHeaders": object // Return rendered request headers with sensitive
values masked.

Three sources are unioned, any hit masks:
``settings.TOOL_API_SENSITIVE_HEADERS``,
APICredential keys for the (contact, tool) pair, and the tool's current
``sensitive_headers``. The tool list is applied at read time against the stored
value, so editing it changes how existing records render without rewriting them.
  "requestBody"?: object // Final rendered body sent to the external API. Null
for non-API tools or read-only methods. (Optional)
  "createdAt": string (timestamp)
  "updatedAt": string (timestamp)
  "source": string // Scheduled runs' tool calls are attributed via
ChatbotScheduleExecution.user_message.
}
```

Example response values

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "tool": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Example response name",
    "description": "Example response description"
  },
  "chatbot": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Example response name",
```

```
    "description": "Example response description"
  },
  "message": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "content": "Response string"
  },
  "inputParameters": null,
  "outputResult": null,
  "errorMessage": "Response string",
  "status": "success",
  "executionTime": 456,
  "retryCount": 456,
  "requestUrl": "https://example.com/file.jpg",
  "requestMethod": "Response string",
  "requestHeaders": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Example response name",
    "description": "Example response description"
  },
  "requestBody": null,
  "createdAt": "Response string",
  "updatedAt": "Response string",
  "source": "Response string"
}
```


Get AI assistant filter options for execution records

`GET` `/api/v1/tool-execution-records/chatbots/`

Parameters

Parameter Name	Required	Type	Description
`chatbot`	X	string	
`endDate`	X	string	
`query`	X	string	

`startDate`	X	string	
`status`	X	string	`success`: Success ; `failure`: Failed ; `pending`: Processing ; `timeout`: Timeout;
`tool`	X	string	
`toolType`	X	string	`api`: API ; `function`: Function ; `mcp`: MCP ; `desktop`: Desktop ; `flex`: Flex Message ; `quick_reply`: Quick Reply ; `quick_menu`: Quick Menu;

Code Examples

Shell/Bash

```
# API call example (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/tool-execution-
records/chatbots/?chatbot=550e8400-e29b-41d4-a716-
446655440000&endDate=example&query=example&startDate=example&status=failure&
tool=550e8400-e29b-41d4-a716-446655440000&toolType=api"

  -H "Authorization: Api-Key YOUR_API_KEY"

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/tool-execution-records/chatbots/?
chatbot=550e8400-e29b-41d4-a716-
446655440000&endDate=example&query=example&startDate=example&status=failure&
tool=550e8400-e29b-41d4-a716-446655440000&toolType=api", config)
  .then(response => {
    console.log('Response retrieved successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/tool-execution-records/chatbots/?
chatbot=550e8400-e29b-41d4-a716-
446655440000&endDate=example&query=example&startDate=example&status=failure&
tool=550e8400-e29b-41d4-a716-446655440000&toolType=api"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("Response retrieved successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->get("https://api.maiagent.ai/api/v1/tool-execution-records/chatbots/?chatbot=550e8400-e29b-41d4-a716-446655440000&endDate=example&query=example&startDate=example&status=failure&tool=550e8400-e29b-41d4-a716-446655440000&toolType=api", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response retrieved successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response Content

Status Code: 200

Response Schema Example

```
[
  {
    "id": string (uuid)
    "name": string // Chatbot name. In Agent mode it carries semantic meaning; in other modes it only distinguishes chatbots.
    "team":
```

```
    {
      "id": string (uuid)
      "name": string
    }
  }
]
```

Example Response Values

```
[
  {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Response string",
    "team": {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "Response string"
    }
  }
]
```

Get tool filter options for execution records

GET `/api/v1/tool-execution-records/tools/`

Parameters

Parameter name	Required	Type	Description
`chatbot`	X	string	
`endDate`	X	string	
`page`	X	integer	A page number within the paginated result set.
`pageSize`	X	integer	Number of results to return per page.
`query`	X	string	

`startDate`	X	string	
`status`	X	string	`success`: Success ; `failure`: Failed ; `pending`: Processing ; `timeout`: Timeout;
`tool`	X	string	
`toolType`	X	string	`api`: API ; `function`: Function ; `mcp`: MCP ; `desktop`: Desktop ; `flex`: Flex Message ; `quick_reply`: Quick Reply ; `quick_menu`: Quick Menu;

Code examples

Shell/Bash

```
# API call example (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/tool-execution-records/tools/?chatbot=550e8400-e29b-41d4-a716-446655440000&endDate=example&page=1&pageSize=1&query=example&startDate=example&status=failure&tool=550e8400-e29b-41d4-a716-446655440000&toolType=api"

  -H "Authorization: Api-Key YOUR_API_KEY"

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/tool-execution-records/tools/?
chatbot=550e8400-e29b-41d4-a716-
446655440000&endDate=example&page=1&pageSize=1&query=example&startDate=examp
le&status=failure&tool=550e8400-e29b-41d4-a716-446655440000&toolType=api",
config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request failed:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/tool-execution-records/tools/?
chatbot=550e8400-e29b-41d4-a716-
446655440000&endDate=example&page=1&pageSize=1&query=example&startDate=examp
le&status=failure&tool=550e8400-e29b-41d4-a716-446655440000&toolType=api"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request failed:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->get("https://api.maiagent.ai/api/v1/tool-execution-records/tools/?chatbot=550e8400-e29b-41d4-a716-446655440000&endDate=example&page=1&pageSize=1&query=example&startDate=example&status=failure&tool=550e8400-e29b-41d4-a716-446655440000&toolType=api", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request failed: ' . $e->getMessage();
}
?>
```

Response body

Status code: 200

Example Response Schema

```
{
  "count": integer
  "next"?: string (uri) // Optional
  "previous"?: string (uri) // Optional
  "results": [
    {
```

```
      "id": string (uuid)
      "displayName": string
    }
  ]
}
```

Example Response Values

```
{
  "count": 123,
  "next": "http://api.example.org/accounts/?page=4",
  "previous": "http://api.example.org/accounts/?page=2",
  "results": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "displayName": "Response string"
    }
  ]
}
```

List execution records for a specific tool

GET `/api/v1/tools/{toolPk}/tool-execution-records/`

Parameters

Parameter name	Required	Type	Description
`toolPk`	V	string	
`chatbot`	X	string	Filter by AI assistant ID
`endDate`	X	string	End date (inclusive), format: YYYY-MM-DD
`page`	X	integer	A page number within the paginated result set.
`pageSize`	X	integer	Number of results to return per page.

`query`	X	string	Search by AI assistant name, tool name, or message content
`startDate`	X	string	Start date (inclusive), format: YYYY-MM-DD
`status`	X	string	Filter by execution status: success, failure, pending, timeout
`tool`	X	string	Filter by tool ID
`toolType`	X	string	Filter by tool type: api, function, mcp

Code examples

Shell/Bash

```
# API call example (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/tools/550e8400-e29b-41d4-a716-446655440000/tool-execution-records/?chatbot=example&endDate=example&page=1&pageSize=1&query=example&startDate=example&status=failure&tool=example&toolType=api"

  -H "Authorization: Api-Key YOUR_API_KEY"

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/tools/550e8400-e29b-41d4-a716-446655440000/tool-execution-records/?chatbot=example&endDate=example&page=1&pageSize=1&query=example&startDate=example&status=failure&tool=example&toolType=api", config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request failed:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/tools/550e8400-e29b-41d4-a716-
446655440000/tool-execution-records/?
chatbot=example&endDate=example&page=1&pageSize=1&query=example&startDate=ex
ample&status=failure&tool=example&toolType=api"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request failed:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->get("https://api.maiagent.ai/api/v1/tools/550e8400-e29b-41d4-a716-446655440000/tool-execution-records/?chatbot=example&endDate=example&page=1&pageSize=1&query=example&startDate=example&status=failure&tool=example&toolType=api", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request failed: ' . $e->getMessage();
}
?>
```

Response body

Status code: 200

Example Response Schema

```
{
  "count": integer
  "next"?: string (uri) // Optional
  "previous"?: string (uri) // Optional
  "results": [
    {
```

```
      "id": string (uuid)
      "tool": object // Tool information
      "chatbot": object // AI assistant information
      "messageContent": string // Message content
      "status"?: string (enum: success, failure, pending, timeout) // * `success`
- Success
* `failure` - Failed
* `pending` - Processing
* `timeout` - Timeout (Optional)
      "executionTime": integer // Execution time (milliseconds)
      "errorMessage"?: string // Optional
      "retryCount"?: integer // How many times the platform auto-retried this
tool call before the final outcome (0 = the first attempt was the final one). API
tools count tenacity retries inside APIRequestService; MCP tools count transient-
error retries (read-classified tools only). Function tools are never auto-
retried. (Optional)
      "createdAt": string (timestamp)
      "source": string // Scheduled runs' tool calls are attributed via
ChatbotScheduleExecution.user_message.
    }
  ]
}
```

Example Response Values

```
{
  "count": 123,
  "next": "http://api.example.org/accounts/?page=4",
  "previous": "http://api.example.org/accounts/?page=2",
  "results": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "tool": {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "name": "Example response name",
        "description": "Example response description"
      },
      "chatbot": {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "name": "Example response name",
        "description": "Example response description"
      },
      "messageContent": "Response string",
      "status": "success",
      "executionTime": 456,
      "errorMessage": "Response string",
      "retryCount": 456,
      "createdAt": "Response string",
```

```
      "source": "Response string"
    }
  ]
}
```


Get a specific execution record for a specific tool

`GET` `/api/v1/tools/{toolPk}/tool-execution-records/{id}`

Parameters

Parameter name	Required	Type	Description
`id`	V	string	A UUID string identifying this Tool Execution Record.
`toolPk`	V	string	

Code examples

Shell/Bash

```
# API call example (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/tools/550e8400-e29b-41d4-a716-
446655440000/tool-execution-records/550e8400-e29b-41d4-a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/tools/550e8400-e29b-41d4-a716-
446655440000/tool-execution-records/550e8400-e29b-41d4-a716-446655440000/",
config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request failed:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/tools/550e8400-e29b-41d4-a716-
446655440000/tool-execution-records/550e8400-e29b-41d4-a716-446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request failed:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->get("https://api.maiagent.ai/api/v1/tools/550e8400-e29b-41d4-a716-446655440000/tool-execution-records/550e8400-e29b-41d4-a716-446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request failed: ' . $e->getMessage();
}
?>
```

Response body

Status code: 200

Example Response Schema

```
{
  "id": string (uuid)
  "tool": object // Tool information, including operated_tool_name
  "chatbot": object // AI assistant information
  "message":
  {
    "id": string (uuid)
```

```
    "content": string
  }
  "inputParameters": object
  "outputResult"?: object // Optional
  "errorMessage"?: string // Optional
  "status"?: string (enum: success, failure, pending, timeout) // * `success` -
Success
* `failure` - Failed
* `pending` - Processing
* `timeout` - Timeout (Optional)
  "executionTime": integer // Execution time (milliseconds)
  "retryCount"?: integer // How many times the platform auto-retried this tool
call before the final outcome (0 = the first attempt was the final one). API
tools count tenacity retries inside APIRequestService; MCP tools count transient-
error retries (read-classified tools only). Function tools are never auto-
retried. (Optional)
  "requestUrl"?: // May have different types (Optional)
  string (uri) // Final rendered URL used when calling an API tool. Null for non-
API tools. (Optional)
  "requestMethod"?: string // HTTP method (GET/POST/...) used when calling an API
tool. Null for non-API tools. (Optional)
  "requestHeaders": object // Return rendered request headers with sensitive
values masked.

Three sources are unioned, any hit masks:
``settings.TOOL_API_SENSITIVE_HEADERS``,
APICredential keys for the (contact, tool) pair, and the tool's current
``sensitive_headers``. The tool list is applied at read time against the stored
value, so editing it changes how existing records render without rewriting them.
  "requestBody"?: object // Final rendered body sent to the external API. Null
for non-API tools or read-only methods. (Optional)
  "createdAt": string (timestamp)
  "updatedAt": string (timestamp)
  "source": string // Scheduled runs' tool calls are attributed via
ChatbotScheduleExecution.user_message.
}
```

Example Response Values

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "tool": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Example response name",
    "description": "Example response description"
  },
  "chatbot": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
```

```
    "name": "Example response name",
    "description": "Example response description"
  },
  "message": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "content": "Response string"
  },
  "inputParameters": null,
  "outputResult": null,
  "errorMessage": "Response string",
  "status": "success",
  "executionTime": 456,
  "retryCount": 456,
  "requestUrl": "https://example.com/file.jpg",
  "requestMethod": "Response string",
  "requestHeaders": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Example response name",
    "description": "Example response description"
  },
  "requestBody": null,
  "createdAt": "Response string",
  "updatedAt": "Response string",
  "source": "Response string"
}
```


Get AI Assistant Filter Options for a Specific Tool’ s Execution Records

GET `/api/v1/tools/{toolPk}/tool-execution-records/chatbots/`

Parameters

Parameter Name	Required	Type	Description
`toolPk`	V	string	
`chatbot`	X	string	

`endDate`	X	string	
`query`	X	string	
`startDate`	X	string	
`status`	X	string	`success`: Success ; `failure`: Failed ; `pending`: Processing ; `timeout`: Timeout;
`tool`	X	string	
`toolType`	X	string	`api`: API ; `function`: Function ; `mcp`: MCP ; `desktop`: Desktop ; `flex`: Flex Message ; `quick_reply`: Quick Reply ; `quick_menu`: Quick Menu;

Code Examples

Shell/Bash

```
# API Call Example (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/tools/550e8400-e29b-41d4-a716-446655440000/tool-execution-records/chatbots/?chatbot=550e8400-e29b-41d4-a716-446655440000&endDate=example&query=example&startDate=example&status=failure&tool=550e8400-e29b-41d4-a716-446655440000&toolType=api"

  -H "Authorization: Api-Key YOUR_API_KEY"

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/tools/550e8400-e29b-41d4-a716-
446655440000/tool-execution-records/chatbots/?chatbot=550e8400-e29b-41d4-
a716-
446655440000&endDate=example&query=example&startDate=example&status=failure&
tool=550e8400-e29b-41d4-a716-446655440000&toolType=api", config)
  .then(response => {
    console.log('Response retrieved successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request failed:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/tools/550e8400-e29b-41d4-a716-
446655440000/tool-execution-records/chatbots/?chatbot=550e8400-e29b-41d4-
a716-
446655440000&endDate=example&query=example&startDate=example&status=failure&
tool=550e8400-e29b-41d4-a716-446655440000&toolType=api"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("Response retrieved successfully:")
    print(response.json())
except Exception as e:
    print("Request failed:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->get("https://api.maiagent.ai/api/v1/tools/550e8400-e29b-41d4-a716-446655440000/tool-execution-records/chatbots/?chatbot=550e8400-e29b-41d4-a716-446655440000&endDate=example&query=example&startDate=example&status=failure&tool=550e8400-e29b-41d4-a716-446655440000&toolType=api", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response retrieved successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request failed: ' . $e->getMessage();
}
?>
```

Response Body

Status Code: 200

Example Response Structure

```
[
  {
    "id": string (uuid)
    "name": string // Chatbot name. In Agent mode it carries semantic meaning; in other modes it only distinguishes chatbots.
```

```
    "team":
    {
      "id": string (uuid)
      "name": string
    }
  }
]
```

Example Response Values

```
[
  {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Response string",
    "team": {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "Response string"
    }
  }
]
```

Get Tool Filter Options for a Specific Tool's Execution Records

`GET` `/api/v1/tools/{toolPk}/tool-execution-records/tools/`

Parameters

Parameter Name	Required	Type	Description
`toolPk`	V	string	
`chatbot`	X	string	
`endDate`	X	string	
`page`	X	integer	A page number within the paginated result set.

`pageSize`	X	integer	Number of results to return per page.
`query`	X	string	
`startDate`	X	string	
`status`	X	string	`success`: Success ; `failure`: Failed ; `pending`: Processing ; `timeout`: Timeout;
`tool`	X	string	
`toolType`	X	string	`api`: API ; `function`: Function ; `mcp`: MCP ; `desktop`: Desktop ; `flex`: Flex Message ; `quick_reply`: Quick Reply ; `quick_menu`: Quick Menu;

Code Examples

Shell/Bash

```
# API Call Example (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/tools/550e8400-e29b-41d4-a716-446655440000/tool-execution-records/tools/?chatbot=550e8400-e29b-41d4-a716-446655440000&endDate=example&page=1&pageSize=1&query=example&startDate=example&status=failure&tool=550e8400-e29b-41d4-a716-446655440000&toolType=api"

  -H "Authorization: Api-Key YOUR_API_KEY"

# Make sure to replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/tools/550e8400-e29b-41d4-a716-
446655440000/tool-execution-records/tools/?chatbot=550e8400-e29b-41d4-a716-
446655440000&endDate=example&page=1&pageSize=1&query=example&startDate=examp
le&status=failure&tool=550e8400-e29b-41d4-a716-446655440000&toolType=api",
config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('An error occurred during the request:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/tools/550e8400-e29b-41d4-a716-446655440000/tool-execution-records/tools/?chatbot=550e8400-e29b-41d4-a716-446655440000&endDate=example&page=1&pageSize=1&query=example&startDate=example&status=failure&tool=550e8400-e29b-41d4-a716-446655440000&toolType=api"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("An error occurred during the request:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->get("https://api.maiagent.ai/api/v1/tools/550e8400-e29b-41d4-a716-446655440000/tool-execution-records/tools/?chatbot=550e8400-e29b-41d4-a716-446655440000&endDate=example&page=1&pageSize=1&query=example&startDate=example&status=failure&tool=550e8400-e29b-41d4-a716-446655440000&toolType=api", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'An error occurred during the request: ' . $e->getMessage();
}
?>
```

Response Body

Status Code: 200

Example Response Schema

```
{
  "count": integer
  "next"?: string (uri) // Optional
  "previous"?: string (uri) // Optional
  "results": [
```

```
    {
      "id": string (uuid)
      "displayName": string
    }
  ]
}
```

Example Response Values

```
{
  "count": 123,
  "next": "http://api.example.org/accounts/?page=4",
  "previous": "http://api.example.org/accounts/?page=2",
  "results": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "displayName": "Response string"
    }
  ]
}
```

API Call Example (Shell)

目錄

1. Upload a Skill
2. Create a Skill
3. List Skills
4. Retrieve a Specific Skill
5. Update Skill
6. Partially Update Skill
7. Delete Skill
8. Export Skill
9. Browse Skill Package Directory Structure
10. Reupload Skill
11. List Skill Resources
12. Upload Skill Resource
13. Delete Skill Resource
14. Download Skill Resource

API Call Example (Shell)

Upload a Skill

`POST` `/api/v1/skills/upload/`

Code Examples

Shell/Bash

```
# API Call Example (Shell)
curl -X POST "https://api.maiagent.ai/api/v1/skills/upload/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -F "file=@example_file.pdf"

  -F "attached_tool_ids=Example string"

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');
const FormData = require('form-data');

// Create a FormData object
const formData = new FormData();
// Replace with an actual file
formData.append('file',
* Actual file object *
, 'example_file.pdf');
formData.append('attached_tool_ids', 'Example string');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    ...formData.getHeaders()
  }
};

axios.post("https://api.maiagent.ai/api/v1/skills/upload/",
formData, config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request failed:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/skills/upload/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}

# Create file and form data
files = {
    'file': ('example_file.pdf', open('example_file.pdf', 'rb'),
'application/pdf'),
    'attached_tool_ids': (None, 'Example string')
}

response = requests.post(url, files=files, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request failed:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>post("https://api.maiagent.ai/api/v1/skills/upload/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ],
        'multipart' => [
            [
                'name' => 'file',
                'contents' => fopen('example_file.pdf', 'r'),
                'filename' => 'example_file.pdf'
            ],
            [
                'name' => 'attached_tool_ids',
                'contents' => 'Example string'
            ]
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request failed: ' . $e->getMessage();
}
?>
```

Response Body

Status Code: 201

Example Response Schema

```
{
  "id"?: string (uuid) // Optional
  "name"?: string // Optional
  "description"?: string // Optional
  "attached_tools"?: [ // Names of tools automatically attached based on
the skill package frontmatter (Optional)
    string
  ]
  "missing_tools"?: [ // Names of tools declared in the skill package
that are not found in this organization and must be attached manually
(Optional)
    string
  ]
  "message"?: string // Optional
}
```

Example Response Values

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "name": "Response string",
  "description": "Response string",
  "attached_tools": [
    "Response string"
  ],
  "missing_tools": [
    "Response string"
  ],
  "message": "Response string"
}
```

Status Code: 400

Example Response Schema

```
{
  "detail"?: string // Error message (Optional)
}
```

Example Response Values

```
{
  "detail": "Response string"
}
```

Create a Skill

POST `/api/v1/skills/`

Request Body

Request Parameters

Field	Type	Required	Description
name	string	Yes	
description	string	Yes	
whenToUse	string	No	Describe when the LLM should trigger this skill. Max 200 characters recommended.
instructions	string	No	Markdown text with instructions for the skill
attachedToolIds	array[string]	No	
groups	array[IdName]	No	Groups this skill is assigned to. Non-owner members must pick at least one

Field	Type	Required	Description
			group they belong to.
files	array[object]	No	Optional resource files to create with the skill. Each item must include path and content. content_encoding may be "text" or "base64".

Example Request Schema

```
{
  "name": string
  "description": string
  "whenToUse"?: string // Describe when the LLM should trigger this skill. Max 200 characters recommended. (Optional)
  "instructions"?: string // Markdown text with instructions for the skill (Optional)
  "attachedToolIds"?: [ // Optional
    string (uuid)
  ]
  "groups"?: [ // Groups this skill is assigned to. Non-owner members must pick at least one group they belong to. (Optional)
    {
      "id": string (uuid)
    }
  ]
  "files"?: [ // Optional resource files to create with the skill. Each item must include path and content. content_encoding may be "text" or "base64". (Optional)
    object
  ]
}
```

Example Request Values

```
{
  "name": "Example name",
  "description": "Example string",
  "whenToUse": "Example string",
  "instructions": "Example string",
  "attachedToolIds": [
    "550e8400-e29b-41d4-a716-446655440000"
```

```
  ],
  "groups": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000"
    }
  ],
  "files": [
    {}
  ]
}
```

Code Examples

Shell/Bash

```
# API Call Example (Shell)
curl -X POST "https://api.maiagent.ai/api/v1/skills/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "name": "Example name",
    "description": "Example string",
    "whenToUse": "Example string",
    "instructions": "Example string",
    "attachedToolIds": [
      "550e8400-e29b-41d4-a716-446655440000"
    ],
    "groups": [
      {
        "id": "550e8400-e29b-41d4-a716-446655440000"
      }
    ],
    "files": [
      {}
    ]
  }'

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// Request Body (payload)
const data = {
    "name": "Example name",
    "description": "Example string",
    "whenToUse": "Example string",
    "instructions": "Example string",
    "attachedToolIds": [
      "550e8400-e29b-41d4-a716-446655440000"
    ],
    "groups": [
      {
        "id": "550e8400-e29b-41d4-a716-446655440000"
      }
    ],
    "files": [
      {}
    ]
  };

axios.post("https://api.maiagent.ai/api/v1/skills/", data, config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request failed:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/skills/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# Request Body (payload)
data = {
    "name": "Example name",
    "description": "Example string",
    "whenToUse": "Example string",
    "instructions": "Example string",
    "attachedToolIds": [
        "550e8400-e29b-41d4-a716-446655440000"
    ],
    "groups": [
        {
            "id": "550e8400-e29b-41d4-a716-446655440000"
        }
    ],
    "files": [
        {}
    ]
}

response = requests.post(url, json=data, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request failed:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>post("https://api.maiagent.ai/api/v1/skills/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'name' => 'Example name',
            'description' => 'Example string',
            'whenToUse' => 'Example string',
            'instructions' => 'Example string',
            'attachedToolIds' => [
                '550e8400-e29b-41d4-a716-446655440000'
            ],
            'groups' => [
                [
                    'id' => '550e8400-e29b-41d4-a716-446655440000'
                ]
            ],
            'files' => [
                new \stdClass()
            ]
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request failed: ' . $e->getMessage();
}
?>
```

Response Body

Status Code: 201

Example Response Schema

```
{
  "id": string (uuid)
  "name": string
  "description": string
  "whenToUse": string // Describe when the LLM should trigger this skill.
Max 200 characters recommended.
  "instructions": string // Markdown text with instructions for the skill
  "compatibility": string // Optional environment requirements from the
Agent Skills Spec frontmatter (max 500 chars).
  "metadata": object // Optional arbitrary key-value mapping from the
Agent Skills Spec frontmatter.
  "allowedTools": object // Optional pre-approved tool list from the
Agent Skills Spec frontmatter (experimental).
  "source":  // How the skill was created: upload (.skill/.zip) or manual

* `upload` - Upload
* `manual` - Manual
  {
  }
  "skillPackagePath": string // S3 path for the uploaded .skill/.zip file
  "skillPackageName": string // Original filename of the uploaded skill
package
  "skillPackageSize": integer // Size of the uploaded skill package in
bytes
  "skillPackageUploadedAt": string (timestamp)
  "attachedTools": [
    {
      "id": string (uuid)
      "name": string
      "description": string
      "displayName": string
```

```
      "toolType": string
    }
  ]
  "resources": [
    {
      "id": string (uuid)
      "path": string // Relative path within the skill directory, e.g.
scripts/helper.py
      "filePath": string // S3 path:
skills/{organization_id}/{skill_id}/resources/
      "fileSize": integer // File size in bytes
      "mimeType": string
      "createdAt": string (timestamp)
    }
  ]
  "groups": [
    {
      "id": string (uuid)
      "name": string
    }
  ]
  "createdAt": string (timestamp)
  "updatedAt": string (timestamp)
  "lastUsedAt": string (timestamp)
  "canUpdate": boolean // Return whether the current user can update this
resource.
  "canDelete": boolean // Return whether the current user can delete this
resource.
}
```

Example Response Values

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "name": "Response string",
  "description": "Response string",
  "whenToUse": "Response string",
  "instructions": "Response string",
  "compatibility": "Response string",
  "metadata": null,
  "allowedTools": null,
  "source": {},
  "skillPackagePath": "Response string",
  "skillPackageName": "Response string",
```

```
  "skillPackageSize": 456,
  "skillPackageUploadedAt": "Response string",
  "attachedTools": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "Response string",
      "description": "Response string",
      "displayName": "Response string",
      "toolType": "Response string"
    }
  ],
  "resources": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "path": "Response string",
      "filePath": "Response string",
      "fileSize": 456,
      "mimeType": "Response string",
      "createdAt": "Response string"
    }
  ],
  "groups": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "Response string"
    }
  ],
  "createdAt": "Response string",
  "updatedAt": "Response string",
  "lastUsedAt": "Response string",
  "canUpdate": false,
  "canDelete": false
}
```


List Skills

GET `/api/v1/skills/`

Parameters

Parameter Name	Required	Type	Description
`isActive`	X	boolean	
`page`	X	integer	A page number within the paginated result set.
`pageSize`	X	integer	Number of results to return per page.
`search`	X	string	

Code Examples

Shell/Bash

```
# API Call Example (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/skills/?
isActive=true&page=1&pageSize=1&search=example"

  -H "Authorization: Api-Key YOUR_API_KEY"

# Make sure to replace YOUR_API_KEY and verify the request data
before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/skills/?
isActive=true&page=1&pageSize=1&search=example", config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('An error occurred during the request:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/skills/?
isActive=true&page=1&pageSize=1&search=example"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("An error occurred during the request:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/skills/?
isActive=true&page=1&pageSize=1&search=example", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'An error occurred during the request: ' . $e-
>getMessage();
}
?>
```

Response Body

Status Code: 200

Example Response Schema

```
{
  "count": integer
```

```
  "next"?: string (uri) // Optional
  "previous"?: string (uri) // Optional
  "results": [
    {
      "id": string (uuid)
      "name": string
      "description": string
      "whenToUse": string // Describe when the LLM should trigger this
skill. Max 200 characters recommended.
      "source":  // How the skill was created: upload (.skill/.zip) or
manual

* `upload` - Upload
* `manual` - Manual
      {
      }
      "attachedTools": [
        {
          "id": string (uuid)
          "name": string
          "description": string
          "displayName": string
          "toolType": string
        }
      ]
      "groups": [
        {
          "id": string (uuid)
          "name": string
        }
      ]
      "createdBy": object // Show 'System' as the creator for global
skills (uploaded by platform staff).
      "createdAt": string (timestamp)
      "updatedAt": string (timestamp)
      "lastUsedAt": string (timestamp)
      "canUpdate": boolean // Return whether the current user can update
this resource.
      "canDelete": boolean // Return whether the current user can delete
this resource.
    }
  ]
}
```

Example Response Values

```
{
  "count": 123,
  "next": "http://api.example.org/accounts/?page=4",
  "previous": "http://api.example.org/accounts/?page=2",
  "results": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "Response string",
      "description": "Response string",
      "whenToUse": "Response string",
      "source": {},
      "attachedTools": [
        {
          "id": "550e8400-e29b-41d4-a716-446655440000",
          "name": "Response string",
          "description": "Response string",
          "displayName": "Response string",
          "toolType": "Response string"
        }
      ],
      "groups": [
        {
          "id": "550e8400-e29b-41d4-a716-446655440000",
          "name": "Response string"
        }
      ],
      "createdBy": {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "name": "Example response name",
        "description": "Example response description"
      },
      "createdAt": "Response string",
      "updatedAt": "Response string",
      "lastUsedAt": "Response string",
      "canUpdate": false,
      "canDelete": false
    }
  ]
}
```

Retrieve a Specific Skill

GET `/api/v1/skills/{id}`

Parameters

Parameter Name	Required	Type	Description
`id`	V	string	A UUID string identifying this Skill.

Code Examples

Shell/Bash

```
# API Call Example (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/skills/550e8400-e29b-
41d4-a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/skills/550e8400-e29b-41d4-
a716-446655440000/", config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request failed:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/skills/550e8400-e29b-41d4-
a716-446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request failed:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/skills/550e8400-e29b-41d4-a716-
446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request failed: ' . $e->getMessage();
}
?>
```

Response Body

Status Code: 200

Example Response Schema

```
{
  "id": string (uuid)
  "name": string
```

```
  "description": string
  "whenToUse": string // Describe when the LLM should trigger this skill.
Max 200 characters recommended.
  "instructions": string // Markdown text with instructions for the skill
  "compatibility": string // Optional environment requirements from the
Agent Skills Spec frontmatter (max 500 chars).
  "metadata": object // Optional arbitrary key-value mapping from the
Agent Skills Spec frontmatter.
  "allowedTools": object // Optional pre-approved tool list from the
Agent Skills Spec frontmatter (experimental).
  "source":  // How the skill was created: upload (.skill/.zip) or manual

* `upload` - Upload
* `manual` - Manual
  {
  }
  "skillPackagePath": string // S3 path for the uploaded .skill/.zip file
  "skillPackageName": string // Original filename of the uploaded skill
package
  "skillPackageSize": integer // Size of the uploaded skill package in
bytes
  "skillPackageUploadedAt": string (timestamp)
  "attachedTools": [
    {
      "id": string (uuid)
      "name": string
      "description": string
      "displayName": string
      "toolType": string
    }
  ]
  "resources": [
    {
      "id": string (uuid)
      "path": string // Relative path within the skill directory, e.g.
scripts/helper.py
      "filePath": string // S3 path:
skills/{organization_id}/{skill_id}/resources/
      "fileSize": integer // File size in bytes
      "mimeType": string
      "createdAt": string (timestamp)
    }
  ]
  "groups": [
    {
```

```
      "id": string (uuid)
      "name": string
    }
  ]
  "createdAt": string (timestamp)
  "updatedAt": string (timestamp)
  "lastUsedAt": string (timestamp)
  "canUpdate": boolean // Return whether the current user can update this
resource.
  "canDelete": boolean // Return whether the current user can delete this
resource.
}
```

Example Response Values

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "name": "Response string",
  "description": "Response string",
  "whenToUse": "Response string",
  "instructions": "Response string",
  "compatibility": "Response string",
  "metadata": null,
  "allowedTools": null,
  "source": {},
  "skillPackagePath": "Response string",
  "skillPackageName": "Response string",
  "skillPackageSize": 456,
  "skillPackageUploadedAt": "Response string",
  "attachedTools": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "Response string",
      "description": "Response string",
      "displayName": "Response string",
      "toolType": "Response string"
    }
  ],
  "resources": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "path": "Response string",
      "filePath": "Response string",
      "fileSize": 456,
```

```
      "mimeType": "Response string",
      "createdAt": "Response string"
    }
  ],
  "groups": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "Response string"
    }
  ],
  "createdAt": "Response string",
  "updatedAt": "Response string",
  "lastUsedAt": "Response string",
  "canUpdate": false,
  "canDelete": false
}
```


Update Skill

PUT `/api/v1/skills/{id}`

Parameters

Parameter Name	Required	Type	Description
`id`	V	string	A UUID string identifying this Skill.

Request Body

Request Parameters

Field	Type	Required	Description
name	string	Yes	
description	string	Yes	
whenToUse	string	No	Describe when the LLM should trigger this skill. Max 200 characters recommended.
instructions	string	No	Markdown text with instructions for the skill
attachedToolIds	array[string]	No	
groups	array[IdName]	No	Groups this skill is assigned to. Non-owner members must pick at least one group they belong to.

Request Schema Example

```
{
  "name": string
  "description": string
  "whenToUse"?: string // Describe when the LLM should trigger this
skill. Max 200 characters recommended. (Optional)
  "instructions"?: string // Markdown text with instructions for the
skill (Optional)
  "attachedToolIds"?: [ // Optional
    string (uuid)
  ]
  "groups"?: [ // Groups this skill is assigned to. Non-owner members
must pick at least one group they belong to. (Optional)
    {
      "id": string (uuid)
    }
  ]
}
```

Example Request Values

```
{
  "name": "Example Name",
  "description": "Example string",
```

```
  "whenToUse": "Example string",
  "instructions": "Example string",
  "attachedToolIds": [
    "550e8400-e29b-41d4-a716-446655440000"
  ],
  "groups": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000"
    }
  ]
}
```


Code Examples

Shell/Bash

```
# API Call Example (Shell)
curl -X PUT "https://api.maiagent.ai/api/v1/skills/550e8400-e29b-
41d4-a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "name": "Example Name",
    "description": "Example string",
    "whenToUse": "Example string",
    "instructions": "Example string",
    "attachedToolIds": [
      "550e8400-e29b-41d4-a716-446655440000"
    ],
    "groups": [
      {
        "id": "550e8400-e29b-41d4-a716-446655440000"
      }
    ]
  }'

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Configure request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// Request Body (payload)
const data = {
    "name": "Example Name",
    "description": "Example string",
    "whenToUse": "Example string",
    "instructions": "Example string",
    "attachedToolIds": [
      "550e8400-e29b-41d4-a716-446655440000"
    ],
    "groups": [
      {
        "id": "550e8400-e29b-41d4-a716-446655440000"
      }
    ]
  };

axios.put("https://api.maiagent.ai/api/v1/skills/550e8400-e29b-41d4-
a716-446655440000/", data, config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/skills/550e8400-e29b-41d4-
a716-446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# Request Body (payload)
data = {
    "name": "Example Name",
    "description": "Example string",
    "whenToUse": "Example string",
    "instructions": "Example string",
    "attachedToolIds": [
        "550e8400-e29b-41d4-a716-446655440000"
    ],
    "groups": [
        {
            "id": "550e8400-e29b-41d4-a716-446655440000"
        }
    ]
}

response = requests.put(url, json=data, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>put("https://api.maiagent.ai/api/v1/skills/550e8400-e29b-41d4-a716-
446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'name' => 'Example Name',
            'description' => 'Example string',
            'whenToUse' => 'Example string',
            'instructions' => 'Example string',
            'attachedToolIds' => [
                '550e8400-e29b-41d4-a716-446655440000'
            ],
            'groups' => [
                [
                    'id' => '550e8400-e29b-41d4-a716-446655440000'
                ]
            ]
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response Body

Status Code: 200

Response Schema Example

```
{
  "id": string (uuid)
  "name": string
  "description": string
  "whenToUse": string // Describe when the LLM should trigger this skill.
Max 200 characters recommended.
  "instructions": string // Markdown text with instructions for the skill
  "compatibility": string // Optional environment requirements from the
Agent Skills Spec frontmatter (max 500 chars).
  "metadata": object // Optional arbitrary key-value mapping from the
Agent Skills Spec frontmatter.
  "allowedTools": object // Optional pre-approved tool list from the
Agent Skills Spec frontmatter (experimental).
  "source":  // How the skill was created: upload (.skill/.zip) or manual

* `upload` - Upload
* `manual` - Manual
  {
  }
  "skillPackagePath": string // S3 path for the uploaded .skill/.zip file
  "skillPackageName": string // Original filename of the uploaded skill
package
  "skillPackageSize": integer // Size of the uploaded skill package in
bytes
  "skillPackageUploadedAt": string (timestamp)
  "attachedTools": [
    {
      "id": string (uuid)
      "name": string
      "description": string
      "displayName": string
      "toolType": string
    }
  ]
  "resources": [
```

```
    {
      "id": string (uuid)
      "path": string // Relative path within the skill directory, e.g.
scripts/helper.py
      "filePath": string // S3 path:
skills/{organization_id}/{skill_id}/resources/
      "fileSize": integer // File size in bytes
      "mimeType": string
      "createdAt": string (timestamp)
    }
  ]
  "groups": [
    {
      "id": string (uuid)
      "name": string
    }
  ]
  "createdAt": string (timestamp)
  "updatedAt": string (timestamp)
  "lastUsedAt": string (timestamp)
  "canUpdate": boolean // Return whether the current user can update this
resource.
  "canDelete": boolean // Return whether the current user can delete this
resource.
}
```

Example Response Values

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "name": "Response string",
  "description": "Response string",
  "whenToUse": "Response string",
  "instructions": "Response string",
  "compatibility": "Response string",
  "metadata": null,
  "allowedTools": null,
  "source": {},
  "skillPackagePath": "Response string",
  "skillPackageName": "Response string",
  "skillPackageSize": 456,
  "skillPackageUploadedAt": "Response string",
  "attachedTools": [
    {
```

```
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "Response string",
      "description": "Response string",
      "displayName": "Response string",
      "toolType": "Response string"
    }
  ],
  "resources": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "path": "Response string",
      "filePath": "Response string",
      "fileSize": 456,
      "mimeType": "Response string",
      "createdAt": "Response string"
    }
  ],
  "groups": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "Response string"
    }
  ],
  "createdAt": "Response string",
  "updatedAt": "Response string",
  "lastUsedAt": "Response string",
  "canUpdate": false,
  "canDelete": false
}
```


Partially Update Skill

PATCH `/api/v1/skills/{id}`

Parameters

Parameter Name	Required	Type	Description
id	V	string	A UUID string identifying this Skill.

Request Body

Request Parameters

Field	Type	Required	Description
name	string	No	
description	string	No	
whenToUse	string	No	Describe when the LLM should trigger this skill. Max 200 characters recommended.
instructions	string	No	Markdown text with instructions for the skill
attachedToolIds	array[string]	No	
groups	array[IdName]	No	Groups this skill is assigned to. Non-owner members must pick at least one group they belong to.

Request Schema Example

```
{
  "name"?: string // Optional
  "description"?: string // Optional
  "whenToUse"?: string // Describe when the LLM should trigger this
skill. Max 200 characters recommended. (Optional)
  "instructions"?: string // Markdown text with instructions for the
skill (Optional)
  "attachedToolIds"?: [ // Optional
    string (uuid)
  ]
  "groups"?: [ // Groups this skill is assigned to. Non-owner members
must pick at least one group they belong to. (Optional)
```

```
    {
      "id": string (uuid)
    }
  ]
}
```

Example Request Values

```
{
  "name": "Example Name",
  "description": "Example string",
  "whenToUse": "Example string",
  "instructions": "Example string",
  "attachedToolIds": [
    "550e8400-e29b-41d4-a716-446655440000"
  ],
  "groups": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000"
    }
  ]
}
```

Code Examples

Shell/Bash

```
# API Call Example (Shell)
curl -X PATCH "https://api.maiagent.ai/api/v1/skills/550e8400-e29b-
41d4-a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "name": "Example Name",
    "description": "Example string",
    "whenToUse": "Example string",
    "instructions": "Example string",
    "attachedToolIds": [
      "550e8400-e29b-41d4-a716-446655440000"
    ],
    "groups": [
      {
        "id": "550e8400-e29b-41d4-a716-446655440000"
      }
    ]
  }'

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Configure request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// Request Body (payload)
const data = {
    "name": "Example Name",
    "description": "Example string",
    "whenToUse": "Example string",
    "instructions": "Example string",
    "attachedToolIds": [
      "550e8400-e29b-41d4-a716-446655440000"
    ],
    "groups": [
      {
        "id": "550e8400-e29b-41d4-a716-446655440000"
      }
    ]
  };

axios.patch("https://api.maiagent.ai/api/v1/skills/550e8400-e29b-
41d4-a716-446655440000/", data, config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/skills/550e8400-e29b-41d4-
a716-446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# Request Body (payload)
data = {
    "name": "Example Name",
    "description": "Example string",
    "whenToUse": "Example string",
    "instructions": "Example string",
    "attachedToolIds": [
        "550e8400-e29b-41d4-a716-446655440000"
    ],
    "groups": [
        {
            "id": "550e8400-e29b-41d4-a716-446655440000"
        }
    ]
}

response = requests.patch(url, json=data, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>patch("https://api.maiagent.ai/api/v1/skills/550e8400-e29b-41d4-
a716-446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'name' => 'Example Name',
            'description' => 'Example string',
            'whenToUse' => 'Example string',
            'instructions' => 'Example string',
            'attachedToolIds' => [
                '550e8400-e29b-41d4-a716-446655440000'
            ],
            'groups' => [
                [
                    'id' => '550e8400-e29b-41d4-a716-446655440000'
                ]
            ]
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response Body

Status Code: 200

Response Schema Example

```
{
  "id": string (uuid)
  "name": string
  "description": string
  "whenToUse": string // Describe when the LLM should trigger this skill.
Max 200 characters recommended.
  "instructions": string // Markdown text with instructions for the skill
  "compatibility": string // Optional environment requirements from the
Agent Skills Spec frontmatter (max 500 chars).
  "metadata": object // Optional arbitrary key-value mapping from the
Agent Skills Spec frontmatter.
  "allowedTools": object // Optional pre-approved tool list from the
Agent Skills Spec frontmatter (experimental).
  "source":  // How the skill was created: upload (.skill/.zip) or manual

* `upload` - Upload
* `manual` - Manual
  {
  }
  "skillPackagePath": string // S3 path for the uploaded .skill/.zip file
  "skillPackageName": string // Original filename of the uploaded skill
package
  "skillPackageSize": integer // Size of the uploaded skill package in
bytes
  "skillPackageUploadedAt": string (timestamp)
  "attachedTools": [
    {
      "id": string (uuid)
      "name": string
      "description": string
      "displayName": string
      "toolType": string
    }
  ]
  "resources": [
```

```
    {
      "id": string (uuid)
      "path": string // Relative path within the skill directory, e.g.
scripts/helper.py
      "filePath": string // S3 path:
skills/{organization_id}/{skill_id}/resources/
      "fileSize": integer // File size in bytes
      "mimeType": string
      "createdAt": string (timestamp)
    }
  ]
  "groups": [
    {
      "id": string (uuid)
      "name": string
    }
  ]
  "createdAt": string (timestamp)
  "updatedAt": string (timestamp)
  "lastUsedAt": string (timestamp)
  "canUpdate": boolean // Return whether the current user can update this
resource.
  "canDelete": boolean // Return whether the current user can delete this
resource.
}
```

Example Response Values

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "name": "Response string",
  "description": "Response string",
  "whenToUse": "Response string",
  "instructions": "Response string",
  "compatibility": "Response string",
  "metadata": null,
  "allowedTools": null,
  "source": {},
  "skillPackagePath": "Response string",
  "skillPackageName": "Response string",
  "skillPackageSize": 456,
  "skillPackageUploadedAt": "Response string",
  "attachedTools": [
    {
```

```
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "Response string",
      "description": "Response string",
      "displayName": "Response string",
      "toolType": "Response string"
    }
  ],
  "resources": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "path": "Response string",
      "filePath": "Response string",
      "fileSize": 456,
      "mimeType": "Response string",
      "createdAt": "Response string"
    }
  ],
  "groups": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "Response string"
    }
  ],
  "createdAt": "Response string",
  "updatedAt": "Response string",
  "lastUsedAt": "Response string",
  "canUpdate": false,
  "canDelete": false
}
```


Delete Skill

DELETE `/api/v1/skills/{id}`

Parameters

Parameter Name	Required	Type	Description
id	V	string	A UUID string identifying this Skill.

Code Examples

Shell/Bash

```
# API Call Example (Shell)
curl -X DELETE "https://api.maiagent.ai/api/v1/skills/550e8400-e29b-
41d4-a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Configure request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

// Request Body (payload)
const data = null;

axios.delete("https://api.maiagent.ai/api/v1/skills/550e8400-e29b-
41d4-a716-446655440000/", data, config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/skills/550e8400-e29b-41d4-
a716-446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.delete(url, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>delete("https://api.maiagent.ai/api/v1/skills/550e8400-e29b-41d4-
a716-446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response Body

Status Code	Description
204	No response body

Export Skill

GET `/api/v1/skills/{id}/export/`

Parameters

Parameter Name	Required	Type	Description
`id`	V	string	A UUID string identifying this Skill.

Code Examples

Shell/Bash

```
# API Call Example (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/skills/550e8400-e29b-
41d4-a716-446655440000/export/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Configure request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/skills/550e8400-e29b-41d4-a716-446655440000/export/", config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/skills/550e8400-e29b-41d4-
a716-446655440000/export/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/skills/550e8400-e29b-41d4-a716-
446655440000/export/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request failed: ' . $e->getMessage();
}
?>
```

Response Body

Status Code	Description
200	.skill file download

Browse Skill Package Directory Structure

GET `/api/v1/skills/{id}/package-structure/`

Parameters

Parameter Name	Required	Type	Description
`id`	V	string	A UUID string identifying this Skill.
`path`	X	string	Directory path to browse (defaults to the root directory)

Code Examples

Shell/Bash

```
# API call example (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/skills/550e8400-e29b-
41d4-a716-446655440000/package-structure/?path=example"

  -H "Authorization: Api-Key YOUR_API_KEY"

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/skills/550e8400-e29b-41d4-
a716-446655440000/package-structure/?path=example", config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request failed:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/skills/550e8400-e29b-41d4-
a716-446655440000/package-structure/?path=example"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request failed:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/skills/550e8400-e29b-41d4-a716-
446655440000/package-structure/?path=example", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request failed: ' . $e->getMessage();
}
?>
```

Response Body

Status Code: 200

Example Response Schema

```
{
  "package_name"?: string // Skill package file name (Optional)
  "package_size"?: integer // Skill package size (bytes) (Optional)
```

```
  "uploaded_at"?: string (date-time) // Upload time (Optional)
  "current_path"?: string // Current browsing path (Optional)
  "items"?: [ // Directory contents (directories first, sorted
alphabetically) (Optional)
    {
      "name"?: string // File or directory name (Optional)
      "type"?: string (enum: file, dir) // Item type (Optional)
      "size"?: integer // File size (bytes), returned only when type=file
(Optional)
      "item_count"?: integer // Number of immediate children in the
directory, returned only when type=dir (Optional)
    }
  ]
}
```

Example Response Values


```
{
  "package_name": "response string",
  "package_size": 456,
  "uploaded_at": "2025-01-01T00:00:00.000Z",
  "current_path": "response string",
  "items": [
    {
      "name": "response string",
      "type": "file",
      "size": 456,
      "item_count": 456
    }
  ]
}
```


Status Code: 400

Example Response Schema

```
{
  "detail"?: string // Error message (Optional)
}
```

Example Response Values

```
{
  "detail": "response string"
}
```


Reupload Skill

POST `/api/v1/skills/{id}/reupload/`

Parameters

Parameter Name	Required	Type	Description
`id`	V	string	A UUID string identifying this Skill.

Code Examples

Shell/Bash

```
# API call example (Shell)
curl -X POST "https://api.maiagent.ai/api/v1/skills/550e8400-e29b-
41d4-a716-446655440000/reupload/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -F "file=@example_file.pdf"

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');
const FormData = require('form-data');

// Create a FormData object
const formData = new FormData();
// Replace with the actual file
formData.append('file',
* Actual file object *
, 'example_file.pdf');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    ...formData.getHeaders()
  }
};

axios.post("https://api.maiagent.ai/api/v1/skills/550e8400-e29b-
41d4-a716-446655440000/reupload/", formData, config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request failed:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/skills/550e8400-e29b-41d4-
a716-446655440000/reupload/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}

# Prepare files and form data
files = {
    'file': ('example_file.pdf', open('example_file.pdf', 'rb'),
'application/pdf')
}

response = requests.post(url, files=files, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request failed:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>post("https://api.maiagent.ai/api/v1/skills/550e8400-e29b-41d4-
a716-446655440000/reupload/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ],
        'multipart' => [
            [
                'name' => 'file',
                'contents' => fopen('example_file.pdf', 'r'),
                'filename' => 'example_file.pdf'
            ]
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request failed: ' . $e->getMessage();
}
?>
```

Response Body

Status Code: 200

Example Response Schema

```
{
  "id"?: string (uuid) // Optional
  "name"?: string // Optional
  "description"?: string // Optional
  "message"?: string // Optional
}
```

Example Response Values

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "name": "response string",
  "description": "response string",
  "message": "response string"
}
```

Status Code: 400

Example Response Schema

```
{
  "detail"?: string // Error message (Optional)
}
```

Example Response Values

```
{
  "detail": "response string"
}
```

List Skill Resources

GET `/api/v1/skills/{skillPk}/resources/`

Parameters

Parameter Name	Required	Type	Description
`skillPk`	V	string	

Code Examples

Shell/Bash

```
# API call example (Shell)
curl -X GET
"https://api.maiagent.ai/api/v1/skills/{skillPk}/resources/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/skills/{skillPk}/resources
/", config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request failed:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/skills/{skillPk}/resources/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request failed:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/skills/{skillPk}/resources/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request failed: ' . $e->getMessage();
}
?>
```

Response Body

Status Code: 200

Example Response Schema

```
[
  {
    "id": string (uuid)
    "path": string // Relative path within the skill directory, e.g.
```

```
scripts/helper.py
    "filePath": string // S3 path:
skills/{organization_id}/{skill_id}/resources/
    "fileSize": integer // File size in bytes
    "mimeType": string
    "createdAt": string (timestamp)
  }
]
```

Example Response Values

```
[
  {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "path": "response string",
    "filePath": "response string",
    "fileSize": 456,
    "mimeType": "response string",
    "createdAt": "response string"
  }
]
```

Upload Skill Resource

POST `/api/v1/skills/{skillPk}/resources/`

Parameters

Parameter Name	Required	Type	Description
`skillPk`	V	string	

Code Examples

Shell/Bash

```
# API call example (Shell)
curl -X POST
"https://api.maiagent.ai/api/v1/skills/{skillPk}/resources/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -F "file=@example_file.pdf"

  -F "path=example string"

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');
const FormData = require('form-data');

// Create a FormData object
const formData = new FormData();
// Replace with the actual file
formData.append('file',
* Actual file object *
, 'example_file.pdf');
formData.append('path', 'example string');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    ...formData.getHeaders()
  }
};

axios.post("https://api.maiagent.ai/api/v1/skills/{skillPk}/resource
s/", formData, config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request failed:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/skills/{skillPk}/resources/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}

# Prepare files and form data
files = {
    'file': ('example_file.pdf', open('example_file.pdf', 'rb'),
'application/pdf'),
    'path': (None, 'example string')
}

response = requests.post(url, files=files, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request failed:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>post("https://api.maiagent.ai/api/v1/skills/{skillPk}/resources/",
[
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ],
        'multipart' => [
            [
                'name' => 'file',
                'contents' => fopen('example_file.pdf', 'r'),
                'filename' => 'example_file.pdf'
            ],
            [
                'name' => 'path',
                'contents' => 'example string'
            ]
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request failed: ' . $e->getMessage();
}
?>
```

Response Body

Status Code: 201

Example Response Schema

```
{
  "id": string (uuid)
  "path": string // Relative path within the skill directory, e.g.
scripts/helper.py
  "filePath": string // S3 path:
skills/{organization_id}/{skill_id}/resources/
  "fileSize": integer // File size in bytes
  "mimeType": string
  "createdAt": string (timestamp)
}
```

Example Response Values

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "path": "response string",
  "filePath": "response string",
  "fileSize": 456,
  "mimeType": "response string",
  "createdAt": "response string"
}
```

Status Code: 400

Example Response Schema

```
{
  "path"?: string // Path validation error (Optional)
  "file"?: string // File validation error (Optional)
}
```

Example Response Values

```
{
  "path": "response string",
  "file": "response string"
}
```


Delete Skill Resource

DELETE `/api/v1/skills/{skillPk}/resources/{id}`

Parameters

Parameter Name	Required	Type	Description
`id`	V	string	
`skillPk`	V	string	

Code Examples

Shell/Bash

```
# API call example (Shell)
curl -X DELETE
"https://api.maiagent.ai/api/v1/skills/{skillPk}/resources/550e8400-
e29b-41d4-a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

// Request body (payload)
const data = null;

axios.delete("https://api.maiagent.ai/api/v1/skills/{skillPk}/resour
ces/550e8400-e29b-41d4-a716-446655440000/", data, config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request failed:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url =
"https://api.maiagent.ai/api/v1/skills/{skillPk}/resources/550e8400-
e29b-41d4-a716-446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.delete(url, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request failed:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>delete("https://api.maiagent.ai/api/v1/skills/{skillPk}/resources/5
50e8400-e29b-41d4-a716-446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request failed: ' . $e->getMessage();
}
?>
```

Response Body

Status Code	Description
204	No response body

Download Skill Resource

GET `/api/v1/skills/{skillPk}/resources/{id}/download/`

Parameters

Parameter Name	Required	Type	Description
`id`	V	string	
`skillPk`	V	string	

Code Examples

Shell/Bash

```
# API call example (Shell)
curl -X GET
"https://api.maiagent.ai/api/v1/skills/{skillPk}/resources/550e8400-
e29b-41d4-a716-446655440000/download/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/skills/{skillPk}/resources
/550e8400-e29b-41d4-a716-446655440000/download/", config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request failed:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url =
"https://api.maiagent.ai/api/v1/skills/{skillPk}/resources/550e8400-
e29b-41d4-a716-446655440000/download/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request failed:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/skills/{skillPk}/resources/550e
8400-e29b-41d4-a716-446655440000/download/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request failed: ' . $e->getMessage();
}
?>
```

Response Body

Status Code	Description
200	File download

API call example (Shell)

目錄

1. List Meeting Records
2. Create a Meeting Record
3. Retrieve a Specific Meeting Record
4. Partially Update a Meeting Record
5. Delete Meeting Record
6. Import an Audio File and Start Transcription
7. Retrieve the Meeting Transcript (JSON)
8. List Meeting Summaries
9. Generate a Meeting Summary
10. Retrieve a Specific Meeting Summary
11. Upload Transcript to Knowledge Base
12. Download SRT Subtitle File
13. Download MP3 Audio File

API call example (Shell)

The meeting record endpoints let your system create meetings, import audio files for transcription, retrieve transcripts and summaries, and store transcripts in a knowledge base. Before importing an audio file, upload it using `POST /api/v1/upload-presigned-url/` (`modelName` is `meeting-record` and `fieldName` is `audio`), as described in Attachments and Files. For feature details, see Meeting Records in the user manual.

List Meeting Records

`GET` `/api/v1/meeting-records/`

Parameters

Parameter Name	Required	Type	Description

`endDate`	X		
`page`	X	integer	A page number within the paginated result set.
`pageSize`	X	integer	Number of results to return per page.
`query`	X		
`startDate`	X		
`status`	X	string	`pending`: Pending; `recording`: Recording; `processing`: Processing; `completed`: Completed; `failed`: Failed;

Code Examples

Shell/Bash

```
# API call example (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/meeting-records/?
endDate=example&page=1&pageSize=1&query=example&startDate=example&st
atus=completed"

  -H "Authorization: Api-Key YOUR_API_KEY"

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/meeting-records/?
endDate=example&page=1&pageSize=1&query=example&startDate=example&st
atus=completed", config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/meeting-records/?
endDate=example&page=1&pageSize=1&query=example&startDate=example&st
atus=completed"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/meeting-records/?
endDate=example&page=1&pageSize=1&query=example&startDate=example&st
atus=completed", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response Body

Status Code: 200

Example Response Structure

```
{
  "count": integer
```

```
  "next"?: string (uri) // Optional
  "previous"?: string (uri) // Optional
  "results": [
    {
      "id": string (uuid)
      "sttContext"?: string // Optional
      "sttContextLlmId"?: string (uuid) // Optional
      "liveTranscriptionResult": object
      "eventContext"?: object // Optional
      "meetingRecordSttProvider":
      {
        "id": string (uuid)
        "name": string // Display name for this STT provider
        "provider": string (enum: whisperlive, azure, deepgram,
assemblyai, bronci, alibaba, localai, openai, rap) // * `whisperlive` -
Whisperlive
* `azure` - Azure
* `deepgram` - Deepgram
* `assemblyai` - Assemblyai
* `bronci` - Bronci
* `alibaba` - Alibaba
* `localai` - Localai
* `openai` - Openai
* `rap` - Rap
        "modelName": string
      }
      "offlineTranscriptProviderDetail":
      {
        "id": string (uuid)
        "name": string // Display name for this provider
        "provider": string (enum: whisper_openai, whisper_groq,
whisper_offline, localai, azure, bronci, alibaba, rap, deepgram,
assemblyai) // * `whisper_openai` - whisper_openai
* `whisper_groq` - whisper_groq
* `whisper_offline` - whisper_offline
* `localai` - localai
* `azure` - azure
* `bronci` - bronci
* `alibaba` - alibaba
* `rap` - rap
* `deepgram` - deepgram
* `assemblyai` - assemblyai
        "modelName": string // Free-form vendor model identifier; any
string the vendor deployment accepts is valid.
      }
```

```
      "meetingRecordSttProviderId"?: string (uuid) // Optional
      "speakerDiarizationProvider":
      {
        "id": string (uuid)
        "name": string // Display name for this provider
        "provider": string (enum: pyannoteai) // * `pyannoteai` -
pyannoteai
        "modelName": string // Free-form vendor model identifier; any
string the vendor deployment accepts is valid.
      }
      "enableTranslation"?: boolean // Optional
      "targetLanguages"?: [ // Target language codes for live transcript
translation. (Optional)
        string
      ]
      "translationLlmId"?: string (uuid) // Optional
      "knowledgeBaseId"?: string (uuid) // Optional
      "audioUrl": string
      "transcriptUrl": string
      "mp3Url": string
      "backupAudioUrl": string
      "backupSyncStatus": string
      "backupUnavailableReason": string
      "backupError": object
      "backupDurationSeconds": number (double)
      "backupTotalParts": integer
      "backupTotalChunks": integer
      "backupRecordingStartedAt": string (timestamp)
      "backupLastActivityAt": string (timestamp)
      "backupFinalizedAt": string (timestamp)
      "knowledgeBase": object
      "transcriptFile": object
      "qaConfig": object // Generate qa_config for frontend to use with
chatbot completion API.
      "availableChatbots": [ // Get chatbots that have this meeting's
knowledge base (detail view only).
        object
      ]
      "createdBy":
      {
        "id": string (uuid)
        "name": string
      }
      "members": [ // The meeting's access roster, visible to anyone who
can see the meeting.
```

```
Editing (add/remove) is gated separately on the members endpoint; here
the
list is read-only context so members can see who participated and who
else
was granted view access.
        object
      ]
      "myRole": string // The requesting user's role on this meeting, or
None if not a member.
      "createdAt": string (timestamp)
      "updatedAt": string (timestamp)
      "meetingName": string
      "participants"?: object // List of meeting participants (Optional)
      "durationSeconds"?: number (double) // Optional
      "status"?: string (enum: pending, recording, processing, completed,
failed) // * `pending` - Pending
* `recording` - Recording
* `processing` - Processing
* `completed` - Completed
* `failed` - Failed (Optional)
      "stopRequestedAt": string (timestamp) // When a user explicitly
requested to stop the recording. A finished recording without this set
ended on the server side (e.g. the client connection was lost).
      "recordingLimitReachedAt": string (timestamp) // When LiveKit ended
the egress at its maximum recording duration. The main audio file ends
here; the STT agent and the browser backup keep going until the room
closes, and the meeting completes on room end.
      "failureReason": // May have different types
      string (enum: egress_not_started, egress_failed, finalize_timeout)
// Why the live recording ended as failed. Empty for meetings that did
not fail.

* `` - None
* `egress_not_started` - Recording did not start
* `egress_failed` - Recording failed
* `finalize_timeout` - Recording was never finalized
      "clientSurface":  // Durable client entry point captured when
recording starts. Legacy records remain unknown.

* `unknown` - Unknown
* `web` - Web
* `desktop` - Desktop
      {
      }
```

```
      "requestedSourceMode":  // Audio source mode requested by the
client when recording starts.

* `unknown` - Unknown
* `microphone` - Microphone
* `system_audio` - System Audio
* `both` - Microphone and System Audio
      {
      }
      "effectiveSourceMode":  // Server-resolved audio source mode used
for runtime and billing reconciliation.

* `unknown` - Unknown
* `microphone` - Microphone
* `system_audio` - System Audio
* `both` - Microphone and System Audio
      {
      }
      "sourceLanguages"?: object // Source languages for transcription
(Optional)
      "speakerDiarizationConfig": object // Per-meeting non-secret
speaker diarization hints, such as numSpeakers.
      "offlineAsrRequestOptions": object // Per-request ASR payload for
the offline audio import, keyed by the selected provider row
request_option_specs contract. EMPTY MEANS: no extra parameters.
      "audioProcessingSnapshot": object // Immutable audio processing
policy snapshot frozen from the platform active profile at meeting start
(via MeetingAudioProcessingProfile.to_snapshot). Downlinked to the
LiveKit Agent with this meeting client/source facts and used to correlate
per-track usage.
      "translationInputTokens"?: integer (int64) // Cumulative LLM input
tokens consumed by realtime translation. Atomically incremented per
translate() call; settled at egress completion. (Optional)
      "translationOutputTokens"?: integer (int64) // Cumulative LLM
output tokens consumed by realtime translation. (Optional)
      "deletedAt"?: string (timestamp) // Optional
      "translationLlm"?: string (uuid) // LLM model to use for
translation when enabled (Optional)
    }
  ]
}
```

Example Response Values

```
{
  "count": 123,
  "next": "http://api.example.org/accounts/?page=4",
  "previous": "http://api.example.org/accounts/?page=2",
  "results": [
    {
      "id": "a1b2c3d4-e5f6-7890-abcd-ef1234567890",
      "meeting_name": "Product Planning Meeting",
      "participants": [
        "Zhang San",
        "Li Si",
        "Wang Wu"
      ],
      "duration_seconds": 3600.5,
      "status": "completed",
      "audio_url": "https://cdn.example.com/media/meeting-
record/a1b2c3d4-e5f6-7890-abcd-ef1234567890.ogg",
      "transcript_url": "https://cdn.example.com/media/meeting-
record/a1b2c3d4_transcript.json",
      "mp3_url": "https://cdn.example.com/media/meeting-record/a1b2c3d4-
e5f6-7890-abcd-ef1234567890_mp3.mp3",
      "source_languages": [
        "zh-TW"
      ],
      "enable_translation": true,
      "target_languages": [
        "en-US",
        "ja-JP"
      ],
      "meeting_record_stt_provider": {
        "id": "c8dc9f8a-2b5e-4a2d-8f93-1a2b3c4d5e6f",
        "provider": "deepgram",
        "model_name": "nova-2",
        "supported_languages": [
          "zh-TW",
          "en-US",
          "ja-JP"
        ],
        "config": {
          "punctuate": true,
          "diarize": true
        },
        "created_at": "2025-01-15T10:00:00Z",
        "updated_at": "2025-01-15T10:00:00Z"
```

```
      },
      "created_at": "2025-01-15T14:00:00Z",
      "updated_at": "2025-01-15T15:00:00Z"
    }
  ]
}
```

Create a Meeting Record

`POST` `/api/v1/meeting-records/`

Request Body

Request Parameters

Field	Type	Required	Description
sttContext	string	No	
sttContextLlmId	string (uuid)	No	
eventContext	object	No	
meetingRecordSttProviderId	string (uuid)	No	
enableTranslation	boolean	No	
targetLanguages	array[string]	No	Target language codes for live transcript translation.
translationLlmId	string (uuid)	No	
knowledgeBaseId	string (uuid)	No	
meetingName	string	Yes	

Field	Type	Required	Description
participants	object	No	List of meeting participants
durationSeconds	number (double)	No	
status	string (enum: pending, recording, processing, completed, failed)	No	`pending` : Pending ; `recording` : Recording ; `processing` : Processing ; `completed` : Completed ; `failed` : Failed;
sourceLanguages	object	No	Source languages for transcription
translationInputTokens	integer (int64)	No	Cumulative LLM input tokens consumed by realtime translation. Atomically incremented per translate() call; settled at egress completion.
translationOutputTokens	integer (int64)	No	Cumulative LLM output tokens consumed by realtime translation.
deletedAt	string (timestamp)	No	
translationLlm	string (uuid)	No	LLM model to use for translation when enabled

Example Request Structure

```
{
  "sttContext"?: string // Optional
  "sttContextLlmId"?: string (uuid) // Optional
  "eventContext"?: object // Optional
  "meetingRecordSttProviderId"?: string (uuid) // Optional
  "enableTranslation"?: boolean // Optional
  "targetLanguages"?: [ // Target language codes for live transcript
```

```
translation. (Optional)
    string
  ]
  "translationLlmId"?: string (uuid) // Optional
  "knowledgeBaseId"?: string (uuid) // Optional
  "meetingName": string
  "participants"?: object // List of meeting participants (Optional)
  "durationSeconds"?: number (double) // Optional
  "status"?: string (enum: pending, recording, processing, completed,
failed) // * `pending` - Pending
* `recording` - Recording
* `processing` - Processing
* `completed` - Completed
* `failed` - Failed (Optional)
  "sourceLanguages"?: object // Source languages for transcription
(Optional)
  "translationInputTokens"?: integer (int64) // Cumulative LLM input
tokens consumed by realtime translation. Atomically incremented per
translate() call; settled at egress completion. (Optional)
  "translationOutputTokens"?: integer (int64) // Cumulative LLM output
tokens consumed by realtime translation. (Optional)
  "deletedAt"?: string (timestamp) // Optional
  "translationLlm"?: string (uuid) // LLM model to use for translation
when enabled (Optional)
}
```

Example Request Values

```
{
  "meeting_name": "Product Planning Meeting",
  "participants": [
    "Zhang San",
    "Li Si",
    "Wang Wu"
  ],
  "source_languages": [
    "zh-TW"
  ],
  "enable_translation": true,
  "target_languages": [
    "en-US",
    "ja-JP"
```

```
  ]
}
```

Code Examples

Shell/Bash

```
# API call example (Shell)
curl -X POST "https://api.maiagent.ai/api/v1/meeting-records/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "meeting_name": "Product Planning Meeting",
    "participants": [
      "Zhang San",
      "Li Si",
      "Wang Wu"
    ],
    "source_languages": [
      "zh-TW"
    ],
    "enable_translation": true,
    "target_languages": [
      "en-US",
      "ja-JP"
    ]
  }'

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// Request Body (payload)
const data = {
    "meeting_name": "Product Planning Meeting",
    "participants": [
      "Zhang San",
      "Li Si",
      "Wang Wu"
    ],
    "source_languages": [
      "zh-TW"
    ],
    "enable_translation": true,
    "target_languages": [
      "en-US",
      "ja-JP"
    ]
  };

axios.post("https://api.maiagent.ai/api/v1/meeting-records/", data,
config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/meeting-records/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# Request Body (payload)
data = {
    "meeting_name": "Product Planning Meeting",
    "participants": [
        "Zhang San",
        "Li Si",
        "Wang Wu"
    ],
    "source_languages": [
        "zh-TW"
    ],
    "enable_translation": True,
    "target_languages": [
        "en-US",
        "ja-JP"
    ]
}

response = requests.post(url, json=data, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>post("https://api.maiagent.ai/api/v1/meeting-records/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'meeting_name' => 'Product Planning Meeting',
            'participants' => [
                'Zhang San',
                'Li Si',
                'Wang Wu'
            ],
            'source_languages' => [
                'zh-TW'
            ],
            'enable_translation' => true,
            'target_languages' => [
                'en-US',
                'ja-JP'
            ]
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response Body

Status Code: 201

Example Response Structure

```
{
  "id": string (uuid)
  "sttContext"?: string // Optional
  "sttContextLlmId"?: string (uuid) // Optional
  "liveTranscriptionResult": object
  "eventContext"?: object // Optional
  "meetingRecordSttProvider":
  {
    "id": string (uuid)
    "name": string // Display name for this STT provider
    "provider": string (enum: whisperlive, azure, deepgram, assemblyai,
bronci, alibaba, localai, openai, rap) // * `whisperlive` - Whisperlive
* `azure` - Azure
* `deepgram` - Deepgram
* `assemblyai` - Assemblyai
* `bronci` - Bronci
* `alibaba` - Alibaba
* `localai` - Localai
* `openai` - Openai
* `rap` - Rap
    "modelName": string
  }
  "offlineTranscriptProviderDetail":
  {
    "id": string (uuid)
    "name": string // Display name for this provider
    "provider": string (enum: whisper_openai, whisper_groq,
whisper_offline, localai, azure, bronci, alibaba, rap, deepgram,
assemblyai) // * `whisper_openai` - whisper_openai
* `whisper_groq` - whisper_groq
* `whisper_offline` - whisper_offline
```

```
* `localai` - localai
* `azure` - azure
* `bronci` - bronci
* `alibaba` - alibaba
* `rap` - rap
* `deepgram` - deepgram
* `assemblyai` - assemblyai
    "modelName": string // Free-form vendor model identifier; any string
the vendor deployment accepts is valid.
  }
  "meetingRecordSttProviderId"?: string (uuid) // Optional
  "speakerDiarizationProvider":
  {
    "id": string (uuid)
    "name": string // Display name for this provider
    "provider": string (enum: pyannoteai) // * `pyannoteai` - pyannoteai
    "modelName": string // Free-form vendor model identifier; any string
the vendor deployment accepts is valid.
  }
  "enableTranslation"?: boolean // Optional
  "targetLanguages"?: [ // Target language codes for live transcript
translation. (Optional)
    string
  ]
  "translationLlmId"?: string (uuid) // Optional
  "knowledgeBaseId"?: string (uuid) // Optional
  "audioUrl": string
  "transcriptUrl": string
  "mp3Url": string
  "backupAudioUrl": string
  "backupSyncStatus": string
  "backupUnavailableReason": string
  "backupError": object
  "backupDurationSeconds": number (double)
  "backupTotalParts": integer
  "backupTotalChunks": integer
  "backupRecordingStartedAt": string (timestamp)
  "backupLastActivityAt": string (timestamp)
  "backupFinalizedAt": string (timestamp)
  "knowledgeBase": object
  "transcriptFile": object
  "qaConfig": object // Generate qa_config for frontend to use with
chatbot completion API.
  "availableChatbots": [ // Get chatbots that have this meeting's
knowledge base (detail view only).
```

```
    object
  ]
  "createdBy":
  {
    "id": string (uuid)
    "name": string
  }
  "members": [ // The meeting's access roster, visible to anyone who can
see the meeting.

Editing (add/remove) is gated separately on the members endpoint; here
the
list is read-only context so members can see who participated and who
else
was granted view access.
    object
  ]
  "myRole": string // The requesting user's role on this meeting, or None
if not a member.
  "createdAt": string (timestamp)
  "updatedAt": string (timestamp)
  "meetingName": string
  "participants"?: object // List of meeting participants (Optional)
  "durationSeconds"?: number (double) // Optional
  "status"?: string (enum: pending, recording, processing, completed,
failed) // * `pending` - Pending
* `recording` - Recording
* `processing` - Processing
* `completed` - Completed
* `failed` - Failed (Optional)
  "stopRequestedAt": string (timestamp) // When a user explicitly
requested to stop the recording. A finished recording without this set
ended on the server side (e.g. the client connection was lost).
  "recordingLimitReachedAt": string (timestamp) // When LiveKit ended the
egress at its maximum recording duration. The main audio file ends here;
the STT agent and the browser backup keep going until the room closes,
and the meeting completes on room end.
  "failureReason": // May have different types
  string (enum: egress_not_started, egress_failed, finalize_timeout) //
Why the live recording ended as failed. Empty for meetings that did not
fail.

* `` - None
* `egress_not_started` - Recording did not start
* `egress_failed` - Recording failed
```

```
* `finalize_timeout` - Recording was never finalized
  "clientSurface":  // Durable client entry point captured when recording
starts. Legacy records remain unknown.

* `unknown` - Unknown
* `web` - Web
* `desktop` - Desktop
  {
  }
  "requestedSourceMode":  // Audio source mode requested by the client
when recording starts.

* `unknown` - Unknown
* `microphone` - Microphone
* `system_audio` - System Audio
* `both` - Microphone and System Audio
  {
  }
  "effectiveSourceMode":  // Server-resolved audio source mode used for
runtime and billing reconciliation.

* `unknown` - Unknown
* `microphone` - Microphone
* `system_audio` - System Audio
* `both` - Microphone and System Audio
  {
  }
  "sourceLanguages"?: object // Source languages for transcription
(Optional)
  "speakerDiarizationConfig": object // Per-meeting non-secret speaker
diarization hints, such as numSpeakers.
  "offlineAsrRequestOptions": object // Per-request ASR payload for the
offline audio import, keyed by the selected provider row
request_option_specs contract. EMPTY MEANS: no extra parameters.
  "audioProcessingSnapshot": object // Immutable audio processing policy
snapshot frozen from the platform active profile at meeting start (via
MeetingAudioProcessingProfile.to_snapshot). Downlinked to the LiveKit
Agent with this meeting client/source facts and used to correlate per-
track usage.
  "translationInputTokens"?: integer (int64) // Cumulative LLM input
tokens consumed by realtime translation. Atomically incremented per
translate() call; settled at egress completion. (Optional)
  "translationOutputTokens"?: integer (int64) // Cumulative LLM output
tokens consumed by realtime translation. (Optional)
  "deletedAt"?: string (timestamp) // Optional
```

```
  "translationLlm"?: string (uuid) // LLM model to use for translation
when enabled (Optional)
}
```

Example Response Values


```
{
  "id": "a1b2c3d4-e5f6-7890-abcd-ef1234567890",
  "meeting_name": "Product Planning Meeting",
  "participants": [
    "Zhang San",
    "Li Si",
    "Wang Wu"
  ],
  "duration_seconds": 3600.5,
  "status": "completed",
  "audio_url": "https://cdn.example.com/media/meeting-record/a1b2c3d4-
e5f6-7890-abcd-ef1234567890.ogg",
  "transcript_url": "https://cdn.example.com/media/meeting-
record/a1b2c3d4_transcript.json",
  "mp3_url": "https://cdn.example.com/media/meeting-record/a1b2c3d4-e5f6-
7890-abcd-ef1234567890_mp3.mp3",
  "source_languages": [
    "zh-TW"
  ],
  "enable_translation": true,
  "target_languages": [
    "en-US",
    "ja-JP"
  ],
  "meeting_record_stt_provider": {
    "id": "c8dc9f8a-2b5e-4a2d-8f93-1a2b3c4d5e6f",
    "provider": "deepgram",
    "model_name": "nova-2",
    "supported_languages": [
      "zh-TW",
      "en-US",
      "ja-JP"
    ],
    "config": {
      "punctuate": true,
      "diarize": true
    },
    "created_at": "2025-01-15T10:00:00Z",
```

```
    "updated_at": "2025-01-15T10:00:00Z"
  },
  "created_at": "2025-01-15T14:00:00Z",
  "updated_at": "2025-01-15T15:00:00Z"
}
```


Retrieve a Specific Meeting Record

GET `/api/v1/meeting-records/{id}`

Parameters

Parameter Name	Required	Type	Description
`id`	V	string	A UUID string identifying this Meeting Record.

Code Examples

Shell/Bash

```
# API Call Example (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/meeting-
records/550e8400-e29b-41d4-a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/meeting-records/550e8400-
e29b-41d4-a716-446655440000/", config)
  .then(response => {
    console.log('Response retrieved successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/meeting-records/550e8400-e29b-41d4-a716-446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("Response retrieved successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/meeting-records/550e8400-e29b-
41d4-a716-446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response retrieved successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response Body

Status Code: 200

Example Response Schema

```
{
  "id": string (uuid)
  "sttContext"?: string // Optional
```

```
  "sttContextLlmId"?: string (uuid) // Optional
  "liveTranscriptionResult": object
  "eventContext"?: object // Optional
  "meetingRecordSttProvider":
  {
    "id": string (uuid)
    "name": string // Display name for this STT provider
    "provider": string (enum: whisperlive, azure, deepgram, assemblyai,
bronci, alibaba, localai, openai, rap) // * `whisperlive` - Whisperlive
* `azure` - Azure
* `deepgram` - Deepgram
* `assemblyai` - Assemblyai
* `bronci` - Bronci
* `alibaba` - Alibaba
* `localai` - Localai
* `openai` - Openai
* `rap` - Rap
    "modelName": string
  }
  "offlineTranscriptProviderDetail":
  {
    "id": string (uuid)
    "name": string // Display name for this provider
    "provider": string (enum: whisper_openai, whisper_groq,
whisper_offline, localai, azure, bronci, alibaba, rap, deepgram,
assemblyai) // * `whisper_openai` - whisper_openai
* `whisper_groq` - whisper_groq
* `whisper_offline` - whisper_offline
* `localai` - localai
* `azure` - azure
* `bronci` - bronci
* `alibaba` - alibaba
* `rap` - rap
* `deepgram` - deepgram
* `assemblyai` - assemblyai
    "modelName": string // Free-form vendor model identifier; any string
the vendor deployment accepts is valid.
  }
  "meetingRecordSttProviderId"?: string (uuid) // Optional
  "speakerDiarizationProvider":
  {
    "id": string (uuid)
    "name": string // Display name for this provider
    "provider": string (enum: pyannoteai) // * `pyannoteai` - pyannoteai
    "modelName": string // Free-form vendor model identifier; any string
```

```
the vendor deployment accepts is valid.
  }
  "enableTranslation"?: boolean // Optional
  "targetLanguages"?: [ // Target language codes for live transcript
translation. (Optional)
    string
  ]
  "translationLlmId"?: string (uuid) // Optional
  "knowledgeBaseId"?: string (uuid) // Optional
  "audioUrl": string
  "transcriptUrl": string
  "mp3Url": string
  "backupAudioUrl": string
  "backupSyncStatus": string
  "backupUnavailableReason": string
  "backupError": object
  "backupDurationSeconds": number (double)
  "backupTotalParts": integer
  "backupTotalChunks": integer
  "backupRecordingStartedAt": string (timestamp)
  "backupLastActivityAt": string (timestamp)
  "backupFinalizedAt": string (timestamp)
  "knowledgeBase": object
  "transcriptFile": object
  "qaConfig": object // Generate qa_config for frontend to use with
chatbot completion API.
  "availableChatbots": [ // Get chatbots that have this meeting's
knowledge base (detail view only).
    object
  ]
  "createdBy":
  {
    "id": string (uuid)
    "name": string
  }
  "members": [ // The meeting's access roster, visible to anyone who can
see the meeting.

Editing (add/remove) is gated separately on the members endpoint; here
the
list is read-only context so members can see who participated and who
else
was granted view access.
    object
  ]
```

```
  "myRole": string // The requesting user's role on this meeting, or None
if not a member.
  "createdAt": string (timestamp)
  "updatedAt": string (timestamp)
  "meetingName": string
  "participants"?: object // List of meeting participants (Optional)
  "durationSeconds"?: number (double) // Optional
  "status"?: string (enum: pending, recording, processing, completed,
failed) // * `pending` - Pending
* `recording` - Recording
* `processing` - Processing
* `completed` - Completed
* `failed` - Failed (Optional)
  "stopRequestedAt": string (timestamp) // When a user explicitly
requested to stop the recording. A finished recording without this set
ended on the server side (e.g. the client connection was lost).
  "recordingLimitReachedAt": string (timestamp) // When LiveKit ended the
egress at its maximum recording duration. The main audio file ends here;
the STT agent and the browser backup keep going until the room closes,
and the meeting completes on room end.
  "failureReason": // May have different types
  string (enum: egress_not_started, egress_failed, finalize_timeout) //
Why the live recording ended as failed. Empty for meetings that did not
fail.

* `` - None
* `egress_not_started` - Recording did not start
* `egress_failed` - Recording failed
* `finalize_timeout` - Recording was never finalized
  "clientSurface":  // Durable client entry point captured when recording
starts. Legacy records remain unknown.

* `unknown` - Unknown
* `web` - Web
* `desktop` - Desktop
  {
  }
  "requestedSourceMode":  // Audio source mode requested by the client
when recording starts.

* `unknown` - Unknown
* `microphone` - Microphone
* `system_audio` - System Audio
* `both` - Microphone and System Audio
  {
```

```
  }
  "effectiveSourceMode":  // Server-resolved audio source mode used for
runtime and billing reconciliation.

* `unknown` - Unknown
* `microphone` - Microphone
* `system_audio` - System Audio
* `both` - Microphone and System Audio
  {
  }
  "sourceLanguages"?: object // Source languages for transcription
(Optional)
  "speakerDiarizationConfig": object // Per-meeting non-secret speaker
diarization hints, such as numSpeakers.
  "offlineAsrRequestOptions": object // Per-request ASR payload for the
offline audio import, keyed by the selected provider row
request_option_specs contract. EMPTY MEANS: no extra parameters.
  "audioProcessingSnapshot": object // Immutable audio processing policy
snapshot frozen from the platform active profile at meeting start (via
MeetingAudioProcessingProfile.to_snapshot). Downlinked to the LiveKit
Agent with this meeting client/source facts and used to correlate per-
track usage.
  "translationInputTokens"?: integer (int64) // Cumulative LLM input
tokens consumed by realtime translation. Atomically incremented per
translate() call; settled at egress completion. (Optional)
  "translationOutputTokens"?: integer (int64) // Cumulative LLM output
tokens consumed by realtime translation. (Optional)
  "deletedAt"?: string (timestamp) // Optional
  "translationLlm"?: string (uuid) // LLM model to use for translation
when enabled (Optional)
}
```

Example Response Values

```
{
  "id": "a1b2c3d4-e5f6-7890-abcd-ef1234567890",
  "meeting_name": "Product Planning Meeting",
  "participants": [
    "Zhang San",
    "Li Si",
    "Wang Wu"
  ],
  "duration_seconds": 3600.5,
  "status": "completed",
```

```
  "audio_url": "https://cdn.example.com/media/meeting-record/a1b2c3d4-
e5f6-7890-abcd-ef1234567890.ogg",
  "transcript_url": "https://cdn.example.com/media/meeting-
record/a1b2c3d4_transcript.json",
  "mp3_url": "https://cdn.example.com/media/meeting-record/a1b2c3d4-e5f6-
7890-abcd-ef1234567890_mp3.mp3",
  "source_languages": [
    "zh-TW"
  ],
  "enable_translation": true,
  "target_languages": [
    "en-US",
    "ja-JP"
  ],
  "meeting_record_stt_provider": {
    "id": "c8dc9f8a-2b5e-4a2d-8f93-1a2b3c4d5e6f",
    "provider": "deepgram",
    "model_name": "nova-2",
    "supported_languages": [
      "zh-TW",
      "en-US",
      "ja-JP"
    ],
    "config": {
      "punctuate": true,
      "diarize": true
    },
    "created_at": "2025-01-15T10:00:00Z",
    "updated_at": "2025-01-15T10:00:00Z"
  },
  "created_at": "2025-01-15T14:00:00Z",
  "updated_at": "2025-01-15T15:00:00Z"
}
```


Partially Update a Meeting Record

PATCH `/api/v1/meeting-records/{id}`

Parameters

Parameter Name	Required	Type	Description
`id`	V	string	A UUID string identifying this Meeting Record.

Request Body

Request Parameters

Field	Type	Required	Description
sttContext	string	No	
sttContextLlmId	string (uuid)	No	
eventContext	object	No	
meetingRecordSttProviderId	string (uuid)	No	
enableTranslation	boolean	No	
targetLanguages	array[string]	No	Target language codes for live transcript translation.
translationLlmId	string (uuid)	No	
knowledgeBaseId	string (uuid)	No	
meetingName	string	No	
participants	object	No	List of meeting participants
durationSeconds	number (double)	No	
status	string (enum: pending, recording, processing,	No	`pending` : Pending ; `recording` : Recording ; `processing` : Processing ;

Field	Type	Required	Description
	completed, failed)		`completed` : Completed ; `failed` : Failed;
sourceLanguages	object	No	Source languages for transcription
translationInputTokens	integer (int64)	No	Cumulative LLM input tokens consumed by realtime translation. Atomically incremented per translate() call; settled at egress completion.
translationOutputTokens	integer (int64)	No	Cumulative LLM output tokens consumed by realtime translation.
deletedAt	string (timestamp)	No	
translationLlm	string (uuid)	No	LLM model to use for translation when enabled

Example Request Schema

```
{
  "sttContext"?: string // Optional
  "sttContextLlmId"?: string (uuid) // Optional
  "eventContext"?: object // Optional
  "meetingRecordSttProviderId"?: string (uuid) // Optional
  "enableTranslation"?: boolean // Optional
  "targetLanguages"?: [ // Target language codes for live transcript
translation. (Optional)
    string
  ]
  "translationLlmId"?: string (uuid) // Optional
  "knowledgeBaseId"?: string (uuid) // Optional
  "meetingName"?: string // Optional
  "participants"?: object // List of meeting participants (Optional)
  "durationSeconds"?: number (double) // Optional
  "status"?: string (enum: pending, recording, processing, completed,
failed) // * `pending` - Pending
```

```
* `recording` - Recording
* `processing` - Processing
* `completed` - Completed
* `failed` - Failed (Optional)
  "sourceLanguages"?: object // Source languages for transcription
(Optional)
  "translationInputTokens"?: integer (int64) // Cumulative LLM input
tokens consumed by realtime translation. Atomically incremented per
translate() call; settled at egress completion. (Optional)
  "translationOutputTokens"?: integer (int64) // Cumulative LLM output
tokens consumed by realtime translation. (Optional)
  "deletedAt"?: string (timestamp) // Optional
  "translationLlm"?: string (uuid) // LLM model to use for translation
when enabled (Optional)
}
```

Example Request Values

```
{
  "id": "a1b2c3d4-e5f6-7890-abcd-ef1234567890",
  "meeting_name": "Product Planning Meeting",
  "participants": [
    "Zhang San",
    "Li Si",
    "Wang Wu"
  ],
  "duration_seconds": 3600.5,
  "status": "completed",
  "audio_url": "https://cdn.example.com/media/meeting-record/a1b2c3d4-
e5f6-7890-abcd-ef1234567890.ogg",
  "transcript_url": "https://cdn.example.com/media/meeting-
record/a1b2c3d4_transcript.json",
  "mp3_url": "https://cdn.example.com/media/meeting-record/a1b2c3d4-e5f6-
7890-abcd-ef1234567890_mp3.mp3",
  "source_languages": [
    "zh-TW"
  ],
  "enable_translation": true,
  "target_languages": [
    "en-US",
    "ja-JP"
  ],
  "meeting_record_stt_provider": {
    "id": "c8dc9f8a-2b5e-4a2d-8f93-1a2b3c4d5e6f",
```

```
    "provider": "deepgram",
    "model_name": "nova-2",
    "supported_languages": [
      "zh-TW",
      "en-US",
      "ja-JP"
    ],
    "config": {
      "punctuate": true,
      "diarize": true
    },
    "created_at": "2025-01-15T10:00:00Z",
    "updated_at": "2025-01-15T10:00:00Z"
  },
  "created_at": "2025-01-15T14:00:00Z",
  "updated_at": "2025-01-15T15:00:00Z"
}
```


Code Examples

Shell/Bash

```
# API Call Example (Shell)
curl -X PATCH "https://api.maiagent.ai/api/v1/meeting-
records/550e8400-e29b-41d4-a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "id": "a1b2c3d4-e5f6-7890-abcd-ef1234567890",
    "meeting_name": "Product Planning Meeting",
    "participants": [
      "Zhang San",
      "Li Si",
      "Wang Wu"
    ],
    "duration_seconds": 3600.5,
    "status": "completed",
    "audio_url": "https://cdn.example.com/media/meeting-
record/a1b2c3d4-e5f6-7890-abcd-ef1234567890.ogg",
    "transcript_url": "https://cdn.example.com/media/meeting-
record/a1b2c3d4_transcript.json",
    "mp3_url": "https://cdn.example.com/media/meeting-
record/a1b2c3d4-e5f6-7890-abcd-ef1234567890_mp3.mp3",
    "source_languages": [
      "zh-TW"
    ],
    "enable_translation": true,
    "target_languages": [
      "en-US",
      "ja-JP"
    ],
    "meeting_record_stt_provider": {
      "id": "c8dc9f8a-2b5e-4a2d-8f93-1a2b3c4d5e6f",
      "provider": "deepgram",
      "model_name": "nova-2",
      "supported_languages": [
        "zh-TW",
        "en-US",
        "ja-JP"
```

```
      ],
      "config": {
        "punctuate": true,
        "diarize": true
      },
      "created_at": "2025-01-15T10:00:00Z",
      "updated_at": "2025-01-15T10:00:00Z"
    },
    "created_at": "2025-01-15T14:00:00Z",
    "updated_at": "2025-01-15T15:00:00Z"
  }'

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// Request body (payload)
const data = {
    "id": "a1b2c3d4-e5f6-7890-abcd-ef1234567890",
    "meeting_name": "Product Planning Meeting",
    "participants": [
      "Zhang San",
      "Li Si",
      "Wang Wu"
    ],
    "duration_seconds": 3600.5,
    "status": "completed",
    "audio_url": "https://cdn.example.com/media/meeting-
record/a1b2c3d4-e5f6-7890-abcd-ef1234567890.ogg",
    "transcript_url": "https://cdn.example.com/media/meeting-
record/a1b2c3d4_transcript.json",
    "mp3_url": "https://cdn.example.com/media/meeting-
record/a1b2c3d4-e5f6-7890-abcd-ef1234567890_mp3.mp3",
    "source_languages": [
      "zh-TW"
    ],
    "enable_translation": true,
    "target_languages": [
      "en-US",
      "ja-JP"
    ],
    "meeting_record_stt_provider": {
      "id": "c8dc9f8a-2b5e-4a2d-8f93-1a2b3c4d5e6f",
      "provider": "deepgram",
      "model_name": "nova-2",
      "supported_languages": [
```

```
        "zh-TW",
        "en-US",
        "ja-JP"
      ],
      "config": {
        "punctuate": true,
        "diarize": true
      },
      "created_at": "2025-01-15T10:00:00Z",
      "updated_at": "2025-01-15T10:00:00Z"
    },
    "created_at": "2025-01-15T14:00:00Z",
    "updated_at": "2025-01-15T15:00:00Z"
  };

axios.patch("https://api.maiagent.ai/api/v1/meeting-
records/550e8400-e29b-41d4-a716-446655440000/", data, config)
  .then(response => {
    console.log('Response retrieved successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/meeting-records/550e8400-e29b-
41d4-a716-446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# Request body (payload)
data = {
    "id": "a1b2c3d4-e5f6-7890-abcd-ef1234567890",
    "meeting_name": "Product Planning Meeting",
    "participants": [
        "Zhang San",
        "Li Si",
        "Wang Wu"
    ],
    "duration_seconds": 3600.5,
    "status": "completed",
    "audio_url": "https://cdn.example.com/media/meeting-
record/a1b2c3d4-e5f6-7890-abcd-ef1234567890.ogg",
    "transcript_url": "https://cdn.example.com/media/meeting-
record/a1b2c3d4_transcript.json",
    "mp3_url": "https://cdn.example.com/media/meeting-
record/a1b2c3d4-e5f6-7890-abcd-ef1234567890_mp3.mp3",
    "source_languages": [
        "zh-TW"
    ],
    "enable_translation": True,
    "target_languages": [
        "en-US",
        "ja-JP"
    ],
    "meeting_record_stt_provider": {
        "id": "c8dc9f8a-2b5e-4a2d-8f93-1a2b3c4d5e6f",
        "provider": "deepgram",
        "model_name": "nova-2",
        "supported_languages": [
            "zh-TW",
```

```
            "en-US",
            "ja-JP"
        ],
        "config": {
            "punctuate": True,
            "diarize": True
        },
        "created_at": "2025-01-15T10:00:00Z",
        "updated_at": "2025-01-15T10:00:00Z"
    },
    "created_at": "2025-01-15T14:00:00Z",
    "updated_at": "2025-01-15T15:00:00Z"
}

response = requests.patch(url, json=data, headers=headers)
try:
    print("Response retrieved successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>patch("https://api.maiagent.ai/api/v1/meeting-records/550e8400-
e29b-41d4-a716-446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'id' => 'a1b2c3d4-e5f6-7890-abcd-ef1234567890',
            'meeting_name' => 'Product Planning Meeting',
            'participants' => [
                'Zhang San',
                'Li Si',
                'Wang Wu'
            ],
            'duration_seconds' => 3600.5,
            'status' => 'completed',
            'audio_url' => 'https://cdn.example.com/media/meeting-
record/a1b2c3d4-e5f6-7890-abcd-ef1234567890.ogg',
            'transcript_url' =>
'https://cdn.example.com/media/meeting-
record/a1b2c3d4_transcript.json',
            'mp3_url' => 'https://cdn.example.com/media/meeting-
record/a1b2c3d4-e5f6-7890-abcd-ef1234567890_mp3.mp3',
            'source_languages' => [
                'zh-TW'
            ],
            'enable_translation' => true,
            'target_languages' => [
                'en-US',
                'ja-JP'
            ],
            'meeting_record_stt_provider' => [
                'id' => 'c8dc9f8a-2b5e-4a2d-8f93-1a2b3c4d5e6f',
```

```
                    'provider' => 'deepgram',
                    'model_name' => 'nova-2',
                    'supported_languages' => [
                        'zh-TW',
                        'en-US',
                        'ja-JP'
                    ],
                    'config' => [
                        'punctuate' => true,
                        'diarize' => true
                    ],
                    'created_at' => '2025-01-15T10:00:00Z',
                    'updated_at' => '2025-01-15T10:00:00Z'
                ],
                'created_at' => '2025-01-15T14:00:00Z',
                'updated_at' => '2025-01-15T15:00:00Z'
            ]
        ]);

        $data = json_decode($response->getBody(), true);
        echo "Response retrieved successfully:\n";
        print_r($data);
    } catch (Exception $e) {
        echo 'Request error: ' . $e->getMessage();
    }
    ?>
```

Response Body

Status Code: 200

Response Schema Example

```
{
  "id": string (uuid)
  "sttContext"?: string // Optional
  "sttContextLlmId"?: string (uuid) // Optional
```

```
  "liveTranscriptionResult": object
  "eventContext"?: object // Optional
  "meetingRecordSttProvider":
  {
    "id": string (uuid)
    "name": string // Display name for this STT provider
    "provider": string (enum: whisperlive, azure, deepgram, assemblyai,
bronci, alibaba, localai, openai, rap) // * `whisperlive` - Whisperlive
* `azure` - Azure
* `deepgram` - Deepgram
* `assemblyai` - Assemblyai
* `bronci` - Bronci
* `alibaba` - Alibaba
* `localai` - Localai
* `openai` - Openai
* `rap` - Rap
    "modelName": string
  }
  "offlineTranscriptProviderDetail":
  {
    "id": string (uuid)
    "name": string // Display name for this provider
    "provider": string (enum: whisper_openai, whisper_groq,
whisper_offline, localai, azure, bronci, alibaba, rap, deepgram,
assemblyai) // * `whisper_openai` - whisper_openai
* `whisper_groq` - whisper_groq
* `whisper_offline` - whisper_offline
* `localai` - localai
* `azure` - azure
* `bronci` - bronci
* `alibaba` - alibaba
* `rap` - rap
* `deepgram` - deepgram
* `assemblyai` - assemblyai
    "modelName": string // Free-form vendor model identifier; any string
the vendor deployment accepts is valid.
  }
  "meetingRecordSttProviderId"?: string (uuid) // Optional
  "speakerDiarizationProvider":
  {
    "id": string (uuid)
    "name": string // Display name for this provider
    "provider": string (enum: pyannoteai) // * `pyannoteai` - pyannoteai
    "modelName": string // Free-form vendor model identifier; any string
the vendor deployment accepts is valid.
```

```
  }
  "enableTranslation"?: boolean // Optional
  "targetLanguages"?: [ // Target language codes for live transcript
translation. (Optional)
    string
  ]
  "translationLlmId"?: string (uuid) // Optional
  "knowledgeBaseId"?: string (uuid) // Optional
  "audioUrl": string
  "transcriptUrl": string
  "mp3Url": string
  "backupAudioUrl": string
  "backupSyncStatus": string
  "backupUnavailableReason": string
  "backupError": object
  "backupDurationSeconds": number (double)
  "backupTotalParts": integer
  "backupTotalChunks": integer
  "backupRecordingStartedAt": string (timestamp)
  "backupLastActivityAt": string (timestamp)
  "backupFinalizedAt": string (timestamp)
  "knowledgeBase": object
  "transcriptFile": object
  "qaConfig": object // Generate qa_config for frontend to use with
chatbot completion API.
  "availableChatbots": [ // Get chatbots that have this meeting's
knowledge base (detail view only).
    object
  ]
  "createdBy":
  {
    "id": string (uuid)
    "name": string
  }
  "members": [ // The meeting's access roster, visible to anyone who can
see the meeting.

Editing (add/remove) is gated separately on the members endpoint; here
the
list is read-only context so members can see who participated and who
else
was granted view access.
    object
  ]
  "myRole": string // The requesting user's role on this meeting, or None
```

```
if not a member.
  "createdAt": string (timestamp)
  "updatedAt": string (timestamp)
  "meetingName": string
  "participants"?: object // List of meeting participants (Optional)
  "durationSeconds"?: number (double) // Optional
  "status"?: string (enum: pending, recording, processing, completed,
failed) // * `pending` - Pending
* `recording` - Recording
* `processing` - Processing
* `completed` - Completed
* `failed` - Failed (Optional)
  "stopRequestedAt": string (timestamp) // When a user explicitly
requested to stop the recording. A finished recording without this set
ended on the server side (e.g. the client connection was lost).
  "recordingLimitReachedAt": string (timestamp) // When LiveKit ended the
egress at its maximum recording duration. The main audio file ends here;
the STT agent and the browser backup keep going until the room closes,
and the meeting completes on room end.
  "failureReason": // May have different types
  string (enum: egress_not_started, egress_failed, finalize_timeout) //
Why the live recording ended as failed. Empty for meetings that did not
fail.

* `` - None
* `egress_not_started` - Recording did not start
* `egress_failed` - Recording failed
* `finalize_timeout` - Recording was never finalized
  "clientSurface":  // Durable client entry point captured when recording
starts. Legacy records remain unknown.

* `unknown` - Unknown
* `web` - Web
* `desktop` - Desktop
  {
  }
  "requestedSourceMode":  // Audio source mode requested by the client
when recording starts.

* `unknown` - Unknown
* `microphone` - Microphone
* `system_audio` - System Audio
* `both` - Microphone and System Audio
  {
  }
```

```
  "effectiveSourceMode":  // Server-resolved audio source mode used for
runtime and billing reconciliation.

* `unknown` - Unknown
* `microphone` - Microphone
* `system_audio` - System Audio
* `both` - Microphone and System Audio
  {
  }
  "sourceLanguages"?: object // Source languages for transcription
(Optional)
  "speakerDiarizationConfig": object // Per-meeting non-secret speaker
diarization hints, such as numSpeakers.
  "offlineAsrRequestOptions": object // Per-request ASR payload for the
offline audio import, keyed by the selected provider row
request_option_specs contract. EMPTY MEANS: no extra parameters.
  "audioProcessingSnapshot": object // Immutable audio processing policy
snapshot frozen from the platform active profile at meeting start (via
MeetingAudioProcessingProfile.to_snapshot). Downlinked to the LiveKit
Agent with this meeting client/source facts and used to correlate per-
track usage.
  "translationInputTokens"?: integer (int64) // Cumulative LLM input
tokens consumed by realtime translation. Atomically incremented per
translate() call; settled at egress completion. (Optional)
  "translationOutputTokens"?: integer (int64) // Cumulative LLM output
tokens consumed by realtime translation. (Optional)
  "deletedAt"?: string (timestamp) // Optional
  "translationLlm"?: string (uuid) // LLM model to use for translation
when enabled (Optional)
}
```

Example Response Values

```
{
  "id": "a1b2c3d4-e5f6-7890-abcd-ef1234567890",
  "meeting_name": "Product Planning Meeting",
  "participants": [
    "Zhang San",
    "Li Si",
    "Wang Wu"
  ],
  "duration_seconds": 3600.5,
  "status": "completed",
  "audio_url": "https://cdn.example.com/media/meeting-record/a1b2c3d4-
```

```
e5f6-7890-abcd-ef1234567890.ogg",
  "transcript_url": "https://cdn.example.com/media/meeting-
record/a1b2c3d4_transcript.json",
  "mp3_url": "https://cdn.example.com/media/meeting-record/a1b2c3d4-e5f6-
7890-abcd-ef1234567890_mp3.mp3",
  "source_languages": [
    "zh-TW"
  ],
  "enable_translation": true,
  "target_languages": [
    "en-US",
    "ja-JP"
  ],
  "meeting_record_stt_provider": {
    "id": "c8dc9f8a-2b5e-4a2d-8f93-1a2b3c4d5e6f",
    "provider": "deepgram",
    "model_name": "nova-2",
    "supported_languages": [
      "zh-TW",
      "en-US",
      "ja-JP"
    ],
    "config": {
      "punctuate": true,
      "diarize": true
    },
    "created_at": "2025-01-15T10:00:00Z",
    "updated_at": "2025-01-15T10:00:00Z"
  },
  "created_at": "2025-01-15T14:00:00Z",
  "updated_at": "2025-01-15T15:00:00Z"
}
```


Delete Meeting Record

DELETE `/api/v1/meeting-records/{id}`

Parameters

Parameter Name	Required	Type	Description
id	V	string	A UUID string identifying this Meeting Record.

Code Examples

Shell/Bash

```
# API call example (Shell)
curl -X DELETE "https://api.maiagent.ai/api/v1/meeting-
records/550e8400-e29b-41d4-a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

// Request Body (payload)
const data = null;

axios.delete("https://api.maiagent.ai/api/v1/meeting-
records/550e8400-e29b-41d4-a716-446655440000/", data, config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/meeting-records/550e8400-e29b-41d4-a716-446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.delete(url, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>delete("https://api.maiagent.ai/api/v1/meeting-records/550e8400-
e29b-41d4-a716-446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response Body

Status Code	Description
204	No response body

Import an Audio File and Start Transcription

`POST` `/api/v1/meeting-records/import-audio/`

Transcribe an uploaded audio file asynchronously; check transcription progress in the meeting record’ s status field.

Request Body

Request Parameters

Field	Type	Required	Description
sttContext	string	No	
sttContextLlmId	string (uuid)	No	
offlineTranscriptProviderId	string (uuid)	Yes	
asrOptions	object	No	Nested ASR selection shared by every ASR entry point: languages (at least one), provider payload keys governed by the provider row request_option_specs contract, and the diarization selection (source ...
meetingName	string	Yes	
audioFilePath	string	Yes	
clientSurface	object	No	Client uploading the audio. Omitting it stays unknown instead of claiming web. `unknown` : Unknown ; `web` : Web ; `desktop` : Desktop;

Example Request Schema

```
{
  "sttContext"?: string // Optional
  "sttContextLlmId"?: string (uuid) // Optional
  "offlineTranscriptProviderId": string (uuid)
  "asrOptions"?: object // Nested ASR selection shared by every ASR entry
point: languages (at least one), provider payload keys governed by the
provider row request_option_specs contract, and the diarization selection
(source / provider_id / options). (Optional)
  "meetingName": string
  "audioFilePath": string
  "clientSurface"?:  // Client uploading the audio. Omitting it stays
unknown instead of claiming web.

* `unknown` - Unknown
* `web` - Web
* `desktop` - Desktop (Optional)
  {
  }
}
```

Example Request Values

```
{
  "meeting_name": "Customer interview recording",
  "audio_file_path": "media/chatbot-file/2026/06/customer-interview.m4a",
  "offline_transcript_provider_id": "c8dc9f8a-2b5e-4a2d-8f93-
1a2b3c4d5e6f",
  "asr_options": {
    "languages": [
      "zh-TW"
    ],
    "diarization": {
      "source": "model",
      "provider_id": "a1b2c3d4-e5f6-7890-abcd-ef1234567890"
    }
  }
}
```

Code Examples

Shell/Bash

```
# API Call Example (Shell)
curl -X POST "https://api.maiagent.ai/api/v1/meeting-records/import-audio/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "meeting_name": "Customer interview recording",
    "audio_file_path": "media/chatbot-file/2026/06/customer-interview.m4a",
    "offline_transcript_provider_id": "c8dc9f8a-2b5e-4a2d-8f93-1a2b3c4d5e6f",
    "asr_options": {
      "languages": [
        "zh-TW"
      ],
      "diarization": {
        "source": "model",
        "provider_id": "a1b2c3d4-e5f6-7890-abcd-ef1234567890"
      }
    }
  }'

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set Request Headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// Request Body (payload)
const data = {
    "meeting_name": "Customer interview recording",
    "audio_file_path": "media/chatbot-file/2026/06/customer-
interview.m4a",
    "offline_transcript_provider_id": "c8dc9f8a-2b5e-4a2d-8f93-
1a2b3c4d5e6f",
    "asr_options": {
      "languages": [
        "zh-TW"
      ],
      "diarization": {
        "source": "model",
        "provider_id": "a1b2c3d4-e5f6-7890-abcd-ef1234567890"
      }
    }
  };

axios.post("https://api.maiagent.ai/api/v1/meeting-records/import-
audio/", data, config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request failed:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/meeting-records/import-audio/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# Request Body (payload)
data = {
    "meeting_name": "Customer interview recording",
    "audio_file_path": "media/chatbot-file/2026/06/customer-
interview.m4a",
    "offline_transcript_provider_id": "c8dc9f8a-2b5e-4a2d-8f93-
1a2b3c4d5e6f",
    "asr_options": {
        "languages": [
            "zh-TW"
        ],
        "diarization": {
            "source": "model",
            "provider_id": "a1b2c3d4-e5f6-7890-abcd-ef1234567890"
        }
    }
}

response = requests.post(url, json=data, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request failed:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>post("https://api.maiagent.ai/api/v1/meeting-records/import-
audio/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'meeting_name' => 'Customer interview recording',
            'audio_file_path' => 'media/chatbot-
file/2026/06/customer-interview.m4a',
            'offline_transcript_provider_id' => 'c8dc9f8a-2b5e-4a2d-
8f93-1a2b3c4d5e6f',
            'asr_options' => [
                'languages' => [
                    'zh-TW'
                ],
                'diarization' => [
                    'source' => 'model',
                    'provider_id' => 'a1b2c3d4-e5f6-7890-abcd-
ef1234567890'
                ]
            ]
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request failed: ' . $e->getMessage();
}
?>
```

Response Body

Status Code: 202

Example Response Schema

```
{
  "id": string (uuid)
  "sttContext"?: string // Optional
  "sttContextLlmId"?: string (uuid) // Optional
  "liveTranscriptionResult": object
  "eventContext"?: object // Optional
  "meetingRecordSttProvider":
  {
    "id": string (uuid)
    "name": string // Display name for this STT provider
    "provider": string (enum: whisperlive, azure, deepgram, assemblyai,
bronci, alibaba, localai, openai, rap) // * `whisperlive` - Whisperlive
* `azure` - Azure
* `deepgram` - Deepgram
* `assemblyai` - Assemblyai
* `bronci` - Bronci
* `alibaba` - Alibaba
* `localai` - Localai
* `openai` - Openai
* `rap` - Rap
    "modelName": string
  }
  "offlineTranscriptProviderDetail":
  {
    "id": string (uuid)
    "name": string // Display name for this provider
    "provider": string (enum: whisper_openai, whisper_groq,
whisper_offline, localai, azure, bronci, alibaba, rap, deepgram,
assemblyai) // * `whisper_openai` - whisper_openai
* `whisper_groq` - whisper_groq
* `whisper_offline` - whisper_offline
```

```
* `localai` - localai
* `azure` - azure
* `bronci` - bronci
* `alibaba` - alibaba
* `rap` - rap
* `deepgram` - deepgram
* `assemblyai` - assemblyai
    "modelName": string // Free-form vendor model identifier; any string
the vendor deployment accepts is valid.
  }
  "meetingRecordSttProviderId"?: string (uuid) // Optional
  "speakerDiarizationProvider":
  {
    "id": string (uuid)
    "name": string // Display name for this provider
    "provider": string (enum: pyannoteai) // * `pyannoteai` - pyannoteai
    "modelName": string // Free-form vendor model identifier; any string
the vendor deployment accepts is valid.
  }
  "enableTranslation"?: boolean // Optional
  "targetLanguages"?: [ // Target language codes for live transcript
translation. (Optional)
    string
  ]
  "translationLlmId"?: string (uuid) // Optional
  "knowledgeBaseId"?: string (uuid) // Optional
  "audioUrl": string
  "transcriptUrl": string
  "mp3Url": string
  "backupAudioUrl": string
  "backupSyncStatus": string
  "backupUnavailableReason": string
  "backupError": object
  "backupDurationSeconds": number (double)
  "backupTotalParts": integer
  "backupTotalChunks": integer
  "backupRecordingStartedAt": string (timestamp)
  "backupLastActivityAt": string (timestamp)
  "backupFinalizedAt": string (timestamp)
  "knowledgeBase": object
  "transcriptFile": object
  "qaConfig": object // Generate qa_config for frontend to use with
chatbot completion API.
  "availableChatbots": [ // Get chatbots that have this meeting's
knowledge base (detail view only).
```

```
    object
  ]
  "createdBy":
  {
    "id": string (uuid)
    "name": string
  }
  "members": [ // The meeting's access roster, visible to anyone who can
see the meeting.

Editing (add/remove) is gated separately on the members endpoint; here
the
list is read-only context so members can see who participated and who
else
was granted view access.
    object
  ]
  "myRole": string // The requesting user's role on this meeting, or None
if not a member.
  "createdAt": string (timestamp)
  "updatedAt": string (timestamp)
  "meetingName": string
  "participants"?: object // List of meeting participants (Optional)
  "durationSeconds"?: number (double) // Optional
  "status"?: string (enum: pending, recording, processing, completed,
failed) // * `pending` - Pending
* `recording` - Recording
* `processing` - Processing
* `completed` - Completed
* `failed` - Failed (Optional)
  "stopRequestedAt": string (timestamp) // When a user explicitly
requested to stop the recording. A finished recording without this set
ended on the server side (e.g. the client connection was lost).
  "recordingLimitReachedAt": string (timestamp) // When LiveKit ended the
egress at its maximum recording duration. The main audio file ends here;
the STT agent and the browser backup keep going until the room closes,
and the meeting completes on room end.
  "failureReason": // May have different types
  string (enum: egress_not_started, egress_failed, finalize_timeout) //
Why the live recording ended as failed. Empty for meetings that did not
fail.

* `` - None
* `egress_not_started` - Recording did not start
* `egress_failed` - Recording failed
```

```
* `finalize_timeout` - Recording was never finalized
  "clientSurface":  // Durable client entry point captured when recording
starts. Legacy records remain unknown.

* `unknown` - Unknown
* `web` - Web
* `desktop` - Desktop
  {
  }
  "requestedSourceMode":  // Audio source mode requested by the client
when recording starts.

* `unknown` - Unknown
* `microphone` - Microphone
* `system_audio` - System Audio
* `both` - Microphone and System Audio
  {
  }
  "effectiveSourceMode":  // Server-resolved audio source mode used for
runtime and billing reconciliation.

* `unknown` - Unknown
* `microphone` - Microphone
* `system_audio` - System Audio
* `both` - Microphone and System Audio
  {
  }
  "sourceLanguages"?: object // Source languages for transcription
(Optional)
  "speakerDiarizationConfig": object // Per-meeting non-secret speaker
diarization hints, such as numSpeakers.
  "offlineAsrRequestOptions": object // Per-request ASR payload for the
offline audio import, keyed by the selected provider row
request_option_specs contract. EMPTY MEANS: no extra parameters.
  "audioProcessingSnapshot": object // Immutable audio processing policy
snapshot frozen from the platform active profile at meeting start (via
MeetingAudioProcessingProfile.to_snapshot). Downlinked to the LiveKit
Agent with this meeting client/source facts and used to correlate per-
track usage.
  "translationInputTokens"?: integer (int64) // Cumulative LLM input
tokens consumed by realtime translation. Atomically incremented per
translate() call; settled at egress completion. (Optional)
  "translationOutputTokens"?: integer (int64) // Cumulative LLM output
tokens consumed by realtime translation. (Optional)
  "deletedAt"?: string (timestamp) // Optional
```

```
  "translationLlm"?: string (uuid) // LLM model to use for translation
when enabled (Optional)
}
```

Example Response Values


```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "sttContext": "Response string",
  "sttContextLlmId": "550e8400-e29b-41d4-a716-446655440000",
  "liveTranscriptionResult": null,
  "eventContext": null,
  "meetingRecordSttProvider": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Response string",
    "provider": "whisperlive",
    "modelName": "Response string"
  },
  "offlineTranscriptProviderDetail": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Response string",
    "provider": "whisper_openai",
    "modelName": "Response string"
  },
  "meetingRecordSttProviderId": "550e8400-e29b-41d4-a716-446655440000",
  "speakerDiarizationProvider": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Response string",
    "provider": "pyannoteai",
    "modelName": "Response string"
  },
  "enableTranslation": false,
  "targetLanguages": [
    "Response string"
  ],
  "translationLlmId": "550e8400-e29b-41d4-a716-446655440000",
  "knowledgeBaseId": "550e8400-e29b-41d4-a716-446655440000",
  "audioUrl": "Response string",
  "transcriptUrl": "Response string",
  "mp3Url": "Response string",
  "backupAudioUrl": "Response string",
  "backupSyncStatus": "Response string",
  "backupUnavailableReason": "Response string",
  "backupError": {
```

```
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Example Response Name",
    "description": "Example Response Description"
  },
  "backupDurationSeconds": 456,
  "backupTotalParts": 456,
  "backupTotalChunks": 456,
  "backupRecordingStartedAt": "Response string",
  "backupLastActivityAt": "Response string",
  "backupFinalizedAt": "Response string",
  "knowledgeBase": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Example Response Name",
    "description": "Example Response Description"
  },
  "transcriptFile": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Example Response Name",
    "description": "Example Response Description"
  },
  "qaConfig": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Example Response Name",
    "description": "Example Response Description"
  },
  "availableChatbots": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "Example Response Name",
      "description": "Example Response Description"
    }
  ],
  "createdBy": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Response string"
  },
  "members": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "Example Response Name",
      "description": "Example Response Description"
    }
  ],
  "myRole": "Response string",
  "createdAt": "Response string",
```

```
  "updatedAt": "Response string",
  "meetingName": "Response string",
  "participants": null,
  "durationSeconds": 456,
  "status": "pending",
  "stopRequestedAt": "Response string",
  "recordingLimitReachedAt": "Response string",
  "failureReason": "egress_not_started",
  "clientSurface": {},
  "requestedSourceMode": {},
  "effectiveSourceMode": {},
  "sourceLanguages": null,
  "speakerDiarizationConfig": null,
  "offlineAsrRequestOptions": null,
  "audioProcessingSnapshot": null,
  "translationInputTokens": 456,
  "translationOutputTokens": 456,
  "deletedAt": "Response string",
  "translationLlm": "550e8400-e29b-41d4-a716-446655440000"
}
```


Retrieve the Meeting Transcript (JSON)

GET `/api/v1/meeting-records/{id}/transcript/`

Parameters

Parameter Name	Required	Type	Description
`id`	V	string	A UUID string identifying this Meeting Record.

Code Examples

Shell/Bash

```
# Example API Call (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/meeting-
records/550e8400-e29b-41d4-a716-446655440000/transcript/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/meeting-records/550e8400-
e29b-41d4-a716-446655440000/transcript/", config)
  .then(response => {
    console.log('Response retrieved successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/meeting-records/550e8400-e29b-41d4-a716-446655440000/transcript/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("Response retrieved successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/meeting-records/550e8400-e29b-
41d4-a716-446655440000/transcript/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response retrieved successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response Body

Status Code: 200

Example Response Schema

```
object
```

Example Response Values


```
[
  {
    "id": "9f4a0a46-1c67-45fc-b2d0-35b0f2bb5a2e",
    "type": "final",
    "text": "Let’s first confirm the meeting summary workflow today.",
    "startTime": 0,
    "endTime": 2.5,
    "language": "zh-TW"
  }
]
```


Status Code: 400 - No response body

List Meeting Summaries

GET `/api/v1/meeting-records/{meetingRecordPk}/summaries/`

Parameters

Parameter Name	Required	Type	Description
`meetingRecordPk`	V	string	
`page`	X	integer	A page number within the paginated result set.
`pageSize`	X	integer	Number of results to return per page.

Code Examples

Shell/Bash

```
# Example API Call (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/meeting-
records/{meetingRecordPk}/summaries/?page=1&pageSize=1"

  -H "Authorization: Api-Key YOUR_API_KEY"

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/meeting-
records/{meetingRecordPk}/summaries/?page=1&pageSize=1", config)
  .then(response => {
    console.log('Response retrieved successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/meeting-
records/{meetingRecordPk}/summaries/?page=1&pageSize=1"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("Response retrieved successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/meeting-
records/{meetingRecordPk}/summaries/?page=1&pageSize=1", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response retrieved successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response Body

Status Code: 200

Example Response Schema

```
{
  "count": integer
  "next"?: string (uri) // Optional
```

```
  "previous"?: string (uri) // Optional
  "results": [
    {
      "id": string (uuid)
      "content"?: string // Summary content; empty while a background
generation is in progress. (Optional)
      "status":  // Manual create/edit rows stay completed; background
generations walk from pending to processing.

* `pending` - Pending
* `processing` - Processing
* `completed` - Completed
* `failed` - Failed
      {
      }
      "failureReason": string // Why the last save/generation failed, for
both AI-generated and manually-edited summaries.
      "completedSegments": integer
      "totalSegments": integer
      "transcriptOptimization": string (uuid) // Which re-transcribed
pass this summary was generated from. Null means the meeting's own
realtime transcript, which is the only other source a summary can have.
      "createdAt": string (timestamp)
      "updatedAt": string (timestamp)
    }
  ]
}
```

Example Response Values

```
{
  "count": 123,
  "next": "http://api.example.org/accounts/?page=4",
  "previous": "http://api.example.org/accounts/?page=2",
  "results": [
    {
      "id": "d1e2f3a4-b5c6-7890-abcd-ef1234567890",
      "content": "This meeting focused on product development progress,
and the team confirmed the milestone goals for next week...",
      "created_at": "2025-01-15T14:30:00Z",
      "updated_at": "2025-01-15T14:30:00Z"
    }
```

```
  ]
}
```

Generate a Meeting Summary

POST `/api/v1/meeting-records/{meetingRecordPk}/summaries/generate/`

Parameters

Parameter Name	Required	Type	Description
`meetingRecordPk`	V	string	

Request Body

Request Parameters

Field	Type	Required	Description
transcriptOptimizationId	string (uuid)	No	Optional re-transcribed pass to summarize, from GET /meeting-records/{id}/transcript-optimizations/; it must be completed and belong to this meeting. Omit it to summarize the meeting's own transcript.
chatbotId	string (uuid)	No	Optional summary agent; when set, the agent generates the summary itself, reading the transcript through the transcript-reading tool.

Field	Type	Required	Description
largeLanguageModelId	string (uuid)	No	Optional LLM override for the base (no-agent) mode; mutually exclusive with chatbot_id, whose agent always uses its own configured model.
knowledgeBaseIds	array[string]	No	Optional RBAC-filtered knowledge base ids for the base (no-agent) mode; mutually exclusive with chatbot_id, whose agent always uses its own configured knowledge bases.
customInstructions	string	No	Optional extra instructions appended to the built-in summary prompt.
clientPlatform	object	No	Client platform triggering this generation; stamped on the summary conversation. `web` : Web ; `desktop` : Desktop;

Example Request Schema

```
{
  "transcriptOptimizationId"?: string (uuid) // Optional re-transcribed pass to summarize, from GET /meeting-records/{id}/transcript-optimizations/; it must be completed and belong to this meeting. Omit it to summarize the meeting's own transcript. (Optional)
  "chatbotId"?: string (uuid) // Optional summary agent; when set, the agent generates the summary itself, reading the transcript through the transcript-reading tool. (Optional)
  "largeLanguageModelId"?: string (uuid) // Optional LLM override for the base (no-agent) mode; mutually exclusive with chatbot_id, whose agent always uses its own configured model. (Optional)
  "knowledgeBaseIds"?: [ // Optional RBAC-filtered knowledge base ids for the base (no-agent) mode; mutually exclusive with chatbot_id, whose agent always uses its own configured knowledge bases. (Optional)
    string (uuid)
  ]
  "customInstructions"?: string // Optional extra instructions appended to the built-in summary prompt. (Optional)
```

```
  "clientPlatform"?:  // Client platform triggering this generation;
stamped on the summary conversation.

* `web` - Web
* `desktop` - Desktop (Optional)
  {
  }
}
```

Example Request Values

```
{
  "transcriptOptimizationId": "550e8400-e29b-41d4-a716-446655440000",
  "chatbotId": "550e8400-e29b-41d4-a716-446655440000",
  "largeLanguageModelId": "550e8400-e29b-41d4-a716-446655440000",
  "knowledgeBaseIds": [
    "550e8400-e29b-41d4-a716-446655440000"
  ],
  "customInstructions": "Example string",
  "clientPlatform": {}
}
```

Code Examples

Shell/Bash

```
# Example API Call (Shell)
curl -X POST "https://api.maiagent.ai/api/v1/meeting-
records/{meetingRecordPk}/summaries/generate/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "transcriptOptimizationId": "550e8400-e29b-41d4-a716-
446655440000",
    "chatbotId": "550e8400-e29b-41d4-a716-446655440000",
    "largeLanguageModelId": "550e8400-e29b-41d4-a716-446655440000",
    "knowledgeBaseIds": [
      "550e8400-e29b-41d4-a716-446655440000"
    ],
    "customInstructions": "Example string",
    "clientPlatform": {}
  }'

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// Request body (payload)
const data = {
    "transcriptOptimizationId": "550e8400-e29b-41d4-a716-
446655440000",
    "chatbotId": "550e8400-e29b-41d4-a716-446655440000",
    "largeLanguageModelId": "550e8400-e29b-41d4-a716-446655440000",
    "knowledgeBaseIds": [
      "550e8400-e29b-41d4-a716-446655440000"
    ],
    "customInstructions": "Example string",
    "clientPlatform": {}
  };

axios.post("https://api.maiagent.ai/api/v1/meeting-
records/{meetingRecordPk}/summaries/generate/", data, config)
  .then(response => {
    console.log('Response retrieved successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/meeting-
records/{meetingRecordPk}/summaries/generate/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# Request body (payload)
data = {
    "transcriptOptimizationId": "550e8400-e29b-41d4-a716-
446655440000",
    "chatbotId": "550e8400-e29b-41d4-a716-446655440000",
    "largeLanguageModelId": "550e8400-e29b-41d4-a716-446655440000",
    "knowledgeBaseIds": [
        "550e8400-e29b-41d4-a716-446655440000"
    ],
    "customInstructions": "Example string",
    "clientPlatform": {}
}

response = requests.post(url, json=data, headers=headers)
try:
    print("Response retrieved successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>post("https://api.maiagent.ai/api/v1/meeting-
records/{meetingRecordPk}/summaries/generate/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'transcriptOptimizationId' => '550e8400-e29b-41d4-a716-
446655440000',
            'chatbotId' => '550e8400-e29b-41d4-a716-446655440000',
            'largeLanguageModelId' => '550e8400-e29b-41d4-a716-
446655440000',
            'knowledgeBaseIds' => [
                '550e8400-e29b-41d4-a716-446655440000'
            ],
            'customInstructions' => 'Example string',
            'clientPlatform' => new \stdClass()
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response retrieved successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response Body

Status Code: 200

Example Response Schema

```
{
  "id": string (uuid)
  "content"?: string // Summary content; empty while a background
generation is in progress. (Optional)
  "status":  // Manual create/edit rows stay completed; background
generations walk from pending to processing.

* `pending` - Pending
* `processing` - Processing
* `completed` - Completed
* `failed` - Failed
  {
  }
  "failureReason": string // Why the last save/generation failed, for
both AI-generated and manually-edited summaries.
  "completedSegments": integer
  "totalSegments": integer
  "transcriptOptimization": string (uuid) // Which re-transcribed pass
this summary was generated from. Null means the meeting's own realtime
transcript, which is the only other source a summary can have.
  "createdAt": string (timestamp)
  "updatedAt": string (timestamp)
}
```

Example Response Values

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "content": "Response string",
  "status": {},
  "failureReason": "Response string",
  "completedSegments": 456,
  "totalSegments": 456,
  "transcriptOptimization": "550e8400-e29b-41d4-a716-446655440000",
  "createdAt": "Response string",
```

```
  "updatedAt": "Response string"
}
```

Status Code: 202

Example Response Schema

```
{
  "id": string (uuid)
  "content"?: string // Summary content; empty while a background
generation is in progress. (Optional)
  "status":  // Manual create/edit rows stay completed; background
generations walk from pending to processing.

* `pending` - Pending
* `processing` - Processing
* `completed` - Completed
* `failed` - Failed
  {
  }
  "failureReason": string // Why the last save/generation failed, for
both AI-generated and manually-edited summaries.
  "completedSegments": integer
  "totalSegments": integer
  "transcriptOptimization": string (uuid) // Which re-transcribed pass
this summary was generated from. Null means the meeting's own realtime
transcript, which is the only other source a summary can have.
  "createdAt": string (timestamp)
  "updatedAt": string (timestamp)
}
```

Example Response Values

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "content": "Response string",
  "status": {},
  "failureReason": "Response string",
  "completedSegments": 456,
  "totalSegments": 456,
  "transcriptOptimization": "550e8400-e29b-41d4-a716-446655440000",
  "createdAt": "Response string",
```

```
  "updatedAt": "Response string"
}
```

Retrieve a Specific Meeting Summary

GET `/api/v1/meeting-records/{meetingRecordPk}/summaries/{id}`

Parameters

Parameter Name	Required	Type	Description
`id`	V	string	
`meetingRecordPk`	V	string	

Code Examples

Shell/Bash

```
# Example API Call (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/meeting-
records/{meetingRecordPk}/summaries/550e8400-e29b-41d4-a716-
446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/meeting-
records/{meetingRecordPk}/summaries/550e8400-e29b-41d4-a716-
446655440000/", config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request failed:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/meeting-
records/{meetingRecordPk}/summaries/550e8400-e29b-41d4-a716-
446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request failed:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/meeting-
records/{meetingRecordPk}/summaries/550e8400-e29b-41d4-a716-
446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request failed: ' . $e->getMessage();
}
?>
```

Response Body

Status Code: 200

Example Response Schema

```
{
  "id": string (uuid)
```

```
  "content"?: string // Summary content; empty while a background
generation is in progress. (optional)
  "status":  // Manual create/edit rows stay completed; background
generations walk from pending to processing.

* `pending` - Pending
* `processing` - Processing
* `completed` - Completed
* `failed` - Failed
  {
  }
  "failureReason": string // Why the last save/generation failed, for
both AI-generated and manually-edited summaries.
  "completedSegments": integer
  "totalSegments": integer
  "transcriptOptimization": string (uuid) // Which re-transcribed pass
this summary was generated from. Null means the meeting's own realtime
transcript, which is the only other source a summary can have.
  "createdAt": string (timestamp)
  "updatedAt": string (timestamp)
}
```

Example Response

```
{
  "id": "d1e2f3a4-b5c6-7890-abcd-ef1234567890",
  "content": "This meeting focused on product development progress, and
the team confirmed the milestone targets for next week...",
  "created_at": "2025-01-15T14:30:00Z",
  "updated_at": "2025-01-15T14:30:00Z"
}
```

Upload Transcript to Knowledge Base

POST `/api/v1/meeting-records/{id}/upload-transcript/`

Include knowledge_base_id for the first upload. If the transcript is deleted from the knowledge base, call this endpoint again to re-upload it.

Parameters

Parameter Name	Required	Type	Description
id	V	string	A UUID string identifying this Meeting Record.

Request Body

Request Parameters

Field	Type	Required	Description
knowledgeBaseId	string (uuid)	No	Knowledge base ID to upload transcript to. If not provided, uses existing knowledge base.

Example Request Schema

```
{
  "knowledgeBaseId"?: string (uuid) // Knowledge base ID to upload transcript to. If not provided, uses existing knowledge base. (optional)
}
```

Example Request

```
{
  "knowledge_base_id": "b1c2d3e4-f5a6-7890-abcd-ef1234567890"
}
```

Code Examples

Shell/Bash

```
# Example API call (Shell)
curl -X POST "https://api.maiagent.ai/api/v1/meeting-
records/550e8400-e29b-41d4-a716-446655440000/upload-transcript/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "knowledge_base_id": "b1c2d3e4-f5a6-7890-abcd-ef1234567890"
  }'

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// Request Body (payload)
const data = {
    "knowledge_base_id": "b1c2d3e4-f5a6-7890-abcd-ef1234567890"
  };

axios.post("https://api.maiagent.ai/api/v1/meeting-records/550e8400-
e29b-41d4-a716-446655440000/upload-transcript/", data, config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request failed:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/meeting-records/550e8400-e29b-
41d4-a716-446655440000/upload-transcript/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# Request Body (payload)
data = {
    "knowledge_base_id": "b1c2d3e4-f5a6-7890-abcd-ef1234567890"
}

response = requests.post(url, json=data, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request failed:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>post("https://api.maiagent.ai/api/v1/meeting-records/550e8400-e29b-
41d4-a716-446655440000/upload-transcript/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'knowledge_base_id' => 'b1c2d3e4-f5a6-7890-abcd-
ef1234567890'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request failed: ' . $e->getMessage();
}
?>
```

Response Body

Status Code	Description
202	No response body

400	No response body
404	No response body

Download SRT Subtitle File

GET `/api/v1/meeting-records/{id}/download-srt/`

Parameters

Parameter Name	Required	Type	Description
`id`	V	string	A UUID string identifying this Meeting Record.

Code Examples

Shell/Bash

```
# Example API call (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/meeting-
records/550e8400-e29b-41d4-a716-446655440000/download-srt/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/meeting-records/550e8400-
e29b-41d4-a716-446655440000/download-srt/", config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request failed:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/meeting-records/550e8400-e29b-41d4-a716-446655440000/download-srt/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request failed:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/meeting-records/550e8400-e29b-
41d4-a716-446655440000/download-srt/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request failed: ' . $e->getMessage();
}
?>
```

Response Body

Status Code: `200` - SRT subtitle file content

Example Response Schema

```
string (binary)
```

Example Response


```
"1\n00:00:00,000 --> 00:00:05,500\nWelcome to the
meeting\n\n2\n00:00:05,500 --> 00:00:10,200\nLet's begin the discussion"
```


Status Code: 400 - No response body

Download MP3 Audio File

GET `/api/v1/meeting-records/{id}/download-mp3/`

Parameters

Parameter Name	Required	Type	Description
id	V	string	A UUID string identifying this Meeting Record.

Code Examples

Shell/Bash

```
# Example API call (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/meeting-
records/550e8400-e29b-41d4-a716-446655440000/download-mp3/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/meeting-records/550e8400-
e29b-41d4-a716-446655440000/download-mp3/", config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request failed:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/meeting-records/550e8400-e29b-41d4-a716-446655440000/download-mp3/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request failed:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/meeting-records/550e8400-e29b-
41d4-a716-446655440000/download-mp3/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request failed: ' . $e->getMessage();
}
?>
```

Response Body

Status Code: 200

Example Response Schema

```
{
  "downloadUrl": string (uri) // Presigned download URL
  "filename": string // Suggested filename
```

```
  "expiresIn": integer // URL expiration time in seconds
}
```

Example Response

```
{
  "download_url": "https://s3.amazonaws.com/bucket/media/meeting-
record/xxx_mp3.mp3?X-Amz-...",
  "filename": "產品規劃會議_20250115.mp3",
  "expires_in": 3600
}
```

Status Code: `400` - No response body

Example API Call (Shell)

目錄

1. Create a Knowledge Base
2. List All Knowledge Bases
3. Retrieve Details of a Specific Knowledge Base
4. Search the Contents of a Specific Knowledge Base
5. Update a Knowledge Base
6. Partially Update a Knowledge Base
7. Delete a Knowledge Base
8. Check RRF Availability
9. Export Labels to Excel
10. Import Labels from Excel
11. Export Metadata to Excel
12. Import Metadata from Excel
13. Create a New Label
14. List labels in the knowledge base
15. Get details of a specific label
16. Update a label
17. Partially update a label
18. Delete a label
19. Create a metadata field
20. List Metadata Fields
21. Retrieve a Specific Metadata Field
22. Update a Metadata Field
23. Upload Files to a Knowledge Base
24. Update File Metadata
25. Batch Delete Files
26. Reparse Files in Bulk
27. List Files in a Knowledge Base
28. Get Details of a Specific File
29. Retrieve the Latest File Failure Reason
30. Retrieve File Transcription
31. Update File Information
32. Partially Update a File
33. Delete a File
34. Create a File Translation
35. List File Translations

36. Retrieve a Specific Translation
37. Delete a Translation
38. Download a Translated File
39. List Knowledge Base Documents
40. Update a Document
41. Partially Update a Document
42. Delete a Document
43. Create a new FAQ
44. Update FAQ metadata
45. Batch delete FAQs
46. List all FAQs in a specific knowledge base
47. Retrieve details of a specific FAQ
48. Update FAQ
49. Partially Update FAQ
50. Delete FAQ
51. Export FAQ Excel (or a Blank Template)
52. Import FAQ Excel (Asynchronous)
53. List FAQ Import Jobs
54. Retrieve a Specific FAQ Import Job
55. List Parsers
56. Retrieve a Specific Parser

Example API Call (Shell)

Create a Knowledge Base

`POST` `/api/v1/knowledge-bases/`

Request Body

Request Parameters

Field	Type	Required	Description
embeddingModel	string (uuid)	Yes	
rerankerModel	string (uuid)	Yes	
name	string	Yes	
description	string	No	
numberOfRetrievedChunks	integer	No	Number of reference chunks to retrieve; defaults to 12, with a minimum of 1
enableHyde	boolean	No	Enable HyDE; defaults to False
similarityCutoff	number (double)	No	Similarity threshold; defaults to 0.0, with a range of 0.0-1.0
enableRerank	boolean	No	Whether to enable reranking; defaults to True
enableRrf	boolean	No	Enable Reciprocal Rank Fusion for hybrid search. Disable this if using a custom Elasticsearch without enterprise license. If not provided, uses system default.
vectorDatabaseType	object	No	Type of vector database: elasticsearch, opensearch, oracle or synxdb. Defaults to the platform-managed engine. `elasticsearch` : Elasticsearch ; `opensearch` : OpenSearch ; `oracle` : Oracle AI Database ...
vectorDatabaseUrl	string	No	Custom vector database endpoint URL or Oracle DSN. For Elasticsearch/OpenSearch: URL format (e.g., "https://host:9200"). For

Field	Type	Required	Description
			Oracle: DSN format (e.g., "host:1521/service_name").
vectorDatabaseApiKey	string	No	API Key for Elasticsearch. Not used for OpenSearch.
opensearchUsername	string	No	Username for OpenSearch Basic Auth.
opensearchPassword	string	No	Password for OpenSearch Basic Auth.
oracleUser	string	No	Oracle database username.
oraclePassword	string	No	Oracle database password.
synxdbUser	string	No	SynxDB database username.
synxdbPassword	string	No	SynxDB database password.
chatbots	array[IdName]	No	
groups	array[IdName]	No	

Request Schema Example

```
{
  "embeddingModel": string (uuid)
  "rerankerModel": string (uuid)
  "name": string
  "description"?: string // Optional
  "numberOfRetrievedChunks"?: integer // Number of reference chunks to retrieve; defaults to 12, with a minimum of 1 (Optional)
  "enableHyde"?: boolean // Enable HyDE; defaults to False (Optional)
  "similarityCutoff"?: number (double) // Similarity threshold; defaults to 0.0, with a range of 0.0-1.0 (Optional)
  "enableRerank"?: boolean // Whether to enable reranking; defaults to True (Optional)
  "enableRrf"?: boolean // Enable Reciprocal Rank Fusion for hybrid search. Disable this if using a custom Elasticsearch without enterprise license. If not provided, uses system default. (Optional)
  "vectorDatabaseType"?:  // Type of vector database: elasticsearch, opensearch, oracle or synxdb. Defaults to the platform-managed engine.
```

```
* `elasticsearch` - Elasticsearch
* `opensearch` - OpenSearch
* `oracle` - Oracle AI Database 26ai
* `synxdb` - SynxDB (Optional)
  {
  }
  "vectorDatabaseUrl"?: string // Custom vector database endpoint URL or
Oracle DSN. For Elasticsearch/OpenSearch: URL format (e.g.,
"https://host:9200"). For Oracle: DSN format (e.g.,
"host:1521/service_name"). (Optional)
  "vectorDatabaseApiKey"?: string // API Key for Elasticsearch. Not used
for OpenSearch. (Optional)
  "opensearchUsername"?: string // Username for OpenSearch Basic Auth.
(Optional)
  "opensearchPassword"?: string // Password for OpenSearch Basic Auth.
(Optional)
  "oracleUser"?: string // Oracle database username. (Optional)
  "oraclePassword"?: string // Oracle database password. (Optional)
  "synxdbUser"?: string // SynxDB database username. (Optional)
  "synxdbPassword"?: string // SynxDB database password. (Optional)
  "chatbots"?: [ // Optional
    {
      "id": string (uuid)
    }
  ]
  "groups"?: [ // Optional
    {
      "id": string (uuid)
    }
  ]
}
```

Example Request Values

```
{
  "embeddingModel": "550e8400-e29b-41d4-a716-446655440000",
  "rerankerModel": "550e8400-e29b-41d4-a716-446655440000",
  "name": "Example Name",
  "description": "Example String",
  "numberOfRetrievedChunks": 123,
  "enableHyde": true,
  "similarityCutoff": 123,
  "enableRerank": true,
```

```
  "enableRrf": true,
  "vectorDatabaseType": {},
  "vectorDatabaseUrl": "Example String",
  "vectorDatabaseApiKey": "Example String",
  "opensearchUsername": "Example String",
  "opensearchPassword": "Example String",
  "oracleUser": "Example String",
  "oraclePassword": "Example String",
  "synxdbUser": "Example String",
  "synxdbPassword": "Example String",
  "chatbots": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000"
    }
  ],
  "groups": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000"
    }
  ]
}
```


Code Examples

Shell/Bash

```
# Example API Call (Shell)
curl -X POST "https://api.maiagent.ai/api/v1/knowledge-bases/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "embeddingModel": "550e8400-e29b-41d4-a716-446655440000",
    "rerankerModel": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Example Name",
    "description": "Example String",
    "numberOfRetrievedChunks": 123,
    "enableHyde": true,
    "similarityCutoff": 123,
    "enableRerank": true,
    "enableRrf": true,
    "vectorDatabaseType": {},
    "vectorDatabaseUrl": "Example String",
    "vectorDatabaseApiKey": "Example String",
    "opensearchUsername": "Example String",
    "opensearchPassword": "Example String",
    "oracleUser": "Example String",
    "oraclePassword": "Example String",
    "synxdbUser": "Example String",
    "synxdbPassword": "Example String",
    "chatbots": [
      {
        "id": "550e8400-e29b-41d4-a716-446655440000"
      }
    ],
    "groups": [
      {
        "id": "550e8400-e29b-41d4-a716-446655440000"
      }
    ]
  }'

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set Request Headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// Request Body (payload)
const data = {
    "embeddingModel": "550e8400-e29b-41d4-a716-446655440000",
    "rerankerModel": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Example Name",
    "description": "Example String",
    "numberOfRetrievedChunks": 123,
    "enableHyde": true,
    "similarityCutoff": 123,
    "enableRerank": true,
    "enableRrf": true,
    "vectorDatabaseType": {},
    "vectorDatabaseUrl": "Example String",
    "vectorDatabaseApiKey": "Example String",
    "opensearchUsername": "Example String",
    "opensearchPassword": "Example String",
    "oracleUser": "Example String",
    "oraclePassword": "Example String",
    "synxdbUser": "Example String",
    "synxdbPassword": "Example String",
    "chatbots": [
      {
        "id": "550e8400-e29b-41d4-a716-446655440000"
      }
    ],
    "groups": [
      {
        "id": "550e8400-e29b-41d4-a716-446655440000"
      }
    ]
```

```
  };

axios.post("https://api.maiagent.ai/api/v1/knowledge-bases/", data,
config)
  .then(response => {
    console.log('Response Received Successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request Error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/knowledge-bases/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# Request Body (payload)
data = {
    "embeddingModel": "550e8400-e29b-41d4-a716-446655440000",
    "rerankerModel": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Example Name",
    "description": "Example String",
    "numberOfRetrievedChunks": 123,
    "enableHyde": True,
    "similarityCutoff": 123,
    "enableRerank": True,
    "enableRrf": True,
    "vectorDatabaseType": {},
    "vectorDatabaseUrl": "Example String",
    "vectorDatabaseApiKey": "Example String",
    "opensearchUsername": "Example String",
    "opensearchPassword": "Example String",
    "oracleUser": "Example String",
    "oraclePassword": "Example String",
    "synxdbUser": "Example String",
    "synxdbPassword": "Example String",
    "chatbots": [
        {
            "id": "550e8400-e29b-41d4-a716-446655440000"
        }
    ],
    "groups": [
        {
            "id": "550e8400-e29b-41d4-a716-446655440000"
        }
    ]
}
```

```
response = requests.post(url, json=data, headers=headers)
try:
    print("Response Received Successfully:")
    print(response.json())
except Exception as e:
    print("Request Error:", e)
```

PHP

```
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>post("https://api.maiagent.ai/api/v1/knowledge-bases/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'embeddingModel' => '550e8400-e29b-41d4-a716-
446655440000',
            'rerankerModel' => '550e8400-e29b-41d4-a716-
446655440000',
            'name' => 'Example Name',
            'description' => 'Example String',
            'numberOfRetrievedChunks' => 123,
            'enableHyde' => true,
            'similarityCutoff' => 123,
            'enableRerank' => true,
            'enableRrf' => true,
            'vectorDatabaseType' => new \stdClass(),
            'vectorDatabaseUrl' => 'Example String',
            'vectorDatabaseApiKey' => 'Example String',
            'opensearchUsername' => 'Example String',
            'opensearchPassword' => 'Example String',
            'oracleUser' => 'Example String',
            'oraclePassword' => 'Example String',
            'synxdbUser' => 'Example String',
            'synxdbPassword' => 'Example String',
            'chatbots' => [
                [
                    'id' => '550e8400-e29b-41d4-a716-446655440000'
                ]
            ],
            'groups' => [
                [
```

```
                    'id' => '550e8400-e29b-41d4-a716-446655440000'
                ]
            ]
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response Received Successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request Error: ' . $e->getMessage();
}
?>
```

Response Body

Status Code: 201

Response Schema Example

```
{
  "id": string (uuid)
  "createdBy":
  {
    "id": string (uuid)
    "name": string
  }
  "organization"?: string (uuid) // Optional
  "embeddingModel": string (uuid)
  "rerankerModel": string (uuid)
  "name": string
  "description"?: string // Optional
  "numberOfRetrievedChunks"?: integer // Number of reference chunks to
retrieve; defaults to 12, with a minimum of 1 (Optional)
  "enableHyde"?: boolean // Enable HyDE; defaults to False (Optional)
  "similarityCutoff"?: number (double) // Similarity threshold; defaults
to 0.0, with a range of 0.0-1.0 (Optional)
```

```
  "enableRerank"?: boolean // Whether to enable reranking; defaults to
True (Optional)
  "enableRrf"?: boolean // Enable Reciprocal Rank Fusion for hybrid
search. Disable this if using a custom Elasticsearch without enterprise
license. (Optional)
  "vectorDatabaseType"?:  // Type of vector database: elasticsearch or
opensearch.

* `elasticsearch` - Elasticsearch
* `opensearch` - OpenSearch
* `oracle` - Oracle AI Database 26ai
* `synxdb` - SynxDB (Optional)
  {
  }
  "vectorDatabaseUrl"?: string // Custom vector database endpoint URL or
Oracle DSN. For Elasticsearch/OpenSearch: URL format (e.g.,
"https://host:9200"). For Oracle: DSN format (e.g.,
"host:1521/service_name"). (Optional)
  "vectorDatabaseApiKey"?: string // API Key for Elasticsearch. Not used
for OpenSearch. (Optional)
  "opensearchUsername"?: string // Username for OpenSearch Basic Auth.
(Optional)
  "opensearchPassword"?: string // Password for OpenSearch Basic Auth.
(Optional)
  "oracleUser"?: string // Oracle database username. (Optional)
  "oraclePassword"?: string // Oracle database password. (Optional)
  "synxdbUser"?: string // SynxDB database username. (Optional)
  "synxdbPassword"?: string // SynxDB database password. (Optional)
  "labels": [
    {
      "id": string (uuid)
      "name": string
    }
  ]
  "chatbots"?: [ // Optional
    {
      "id": string (uuid)
      "name": string
    }
  ]
  "groups"?: [ // List of groups that the knowledge base can access
(Optional)
    {
      "id": string (uuid)
      "name": string
```

```
    }
  ]
  "filesCount": integer // Return count of KnowledgeBaseFile excluding
processed files, conversation attachments, and soft-deleted.
  "vectorStorageSize": integer
  "chunksCount": integer
  "canUpdate": boolean // Return whether the current user can update this
resource.
  "canDelete": boolean // Return whether the current user can delete this
resource.
  "createdAt": string (timestamp)
  "updatedAt": string (timestamp)
}
```

Example Response Values


```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "createdBy": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Response String"
  },
  "organization": "550e8400-e29b-41d4-a716-446655440000",
  "embeddingModel": "550e8400-e29b-41d4-a716-446655440000",
  "rerankerModel": "550e8400-e29b-41d4-a716-446655440000",
  "name": "Response String",
  "description": "Response String",
  "numberOfRetrievedChunks": 456,
  "enableHyde": false,
  "similarityCutoff": 456,
  "enableRerank": false,
  "enableRrf": false,
  "vectorDatabaseType": {},
  "vectorDatabaseUrl": "Response String",
  "vectorDatabaseApiKey": "Response String",
  "opensearchUsername": "Response String",
  "opensearchPassword": "Response String",
  "oracleUser": "Response String",
  "oraclePassword": "Response String",
  "synxdbUser": "Response String",
  "synxdbPassword": "Response String",
  "labels": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
```

```
      "name": "Response String"
    }
  ],
  "chatbots": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "Response String"
    }
  ],
  "groups": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "Response String"
    }
  ],
  "filesCount": 456,
  "vectorStorageSize": 456,
  "chunksCount": 456,
  "canUpdate": false,
  "canDelete": false,
  "createdAt": "Response String",
  "updatedAt": "Response String"
}
```


List All Knowledge Bases

GET `/api/v1/knowledge-bases/`

Parameters

Parameter Name	Required	Type	Description
`embeddingModel`	X	string	

`page`	X	integer	A page number within the paginated result set.
`pageSize`	X	integer	Number of results to return per page.
`query`	X	string	
`rerankerModel`	X	string	

Code Examples

Shell/Bash

```
# Example API Call (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/knowledge-bases/?
embeddingModel=550e8400-e29b-41d4-a716-
446655440000&page=1&pageSize=1&query=example&rerankerModel=550e8400-
e29b-41d4-a716-446655440000"

  -H "Authorization: Api-Key YOUR_API_KEY"

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set Request Headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/knowledge-bases/?
embeddingModel=550e8400-e29b-41d4-a716-
446655440000&page=1&pageSize=1&query=example&rerankerModel=550e8400-
e29b-41d4-a716-446655440000", config)
  .then(response => {
    console.log('Response Received Successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request Error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/knowledge-bases/?
embeddingModel=550e8400-e29b-41d4-a716-
446655440000&page=1&pageSize=1&query=example&rerankerModel=550e8400-
e29b-41d4-a716-446655440000"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("Response Received Successfully:")
    print(response.json())
except Exception as e:
    print("Request Error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/knowledge-bases/?
embeddingModel=550e8400-e29b-41d4-a716-
446655440000&page=1&pageSize=1&query=example&rerankerModel=550e8400-
e29b-41d4-a716-446655440000", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response Received Successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request Error: ' . $e->getMessage();
}
?>
```

Response Body

Status Code: 200

Response Schema Example

```
{
  "count": integer
  "next"?: string (uri) // Optional
  "previous"?: string (uri) // Optional
  "results": [
    {
      "id": string (uuid)
      "createdBy":
      {
        "id": string (uuid)
        "name": string
      }
      "organization"?: string (uuid) // Optional
      "embeddingModel": string (uuid)
      "rerankerModel": string (uuid)
      "name": string
      "description"?: string // Optional
      "numberOfRetrievedChunks"?: integer // Number of reference chunks
to retrieve; defaults to 12, with a minimum of 1 (Optional)
      "enableHyde"?: boolean // Enable HyDE; defaults to False (Optional)
      "similarityCutoff"?: number (double) // Similarity threshold;
defaults to 0.0, with a range of 0.0-1.0 (Optional)
      "enableRerank"?: boolean // Whether to enable reranking; defaults
to True (Optional)
      "enableRrf"?: boolean // Enable Reciprocal Rank Fusion for hybrid
search. Disable this if using a custom Elasticsearch without enterprise
license. (Optional)
      "vectorDatabaseType"?:  // Type of vector database: elasticsearch
or opensearch.

* `elasticsearch` - Elasticsearch
* `opensearch` - OpenSearch
* `oracle` - Oracle AI Database 26ai
* `synxdb` - SynxDB (Optional)
      {
      }
      "vectorDatabaseUrl"?: string // Custom vector database endpoint URL
or Oracle DSN. For Elasticsearch/OpenSearch: URL format (e.g.,
"https://host:9200"). For Oracle: DSN format (e.g.,
"host:1521/service_name"). (Optional)
      "vectorDatabaseApiKey"?: string // API Key for Elasticsearch. Not
used for OpenSearch. (Optional)
      "opensearchUsername"?: string // Username for OpenSearch Basic
Auth. (Optional)
```

```
      "opensearchPassword"?: string // Password for OpenSearch Basic
Auth. (Optional)
      "oracleUser"?: string // Oracle database username. (Optional)
      "oraclePassword"?: string // Oracle database password. (Optional)
      "synxdbUser"?: string // SynxDB database username. (Optional)
      "synxdbPassword"?: string // SynxDB database password. (Optional)
      "labels": [
        {
          "id": string (uuid)
          "name": string
        }
      ]
      "chatbots"?: [ // Optional
        {
          "id": string (uuid)
          "name": string
        }
      ]
      "groups"?: [ // List of groups that the knowledge base can access
(Optional)
        {
          "id": string (uuid)
          "name": string
        }
      ]
      "filesCount": integer // Return count of KnowledgeBaseFile
excluding processed files, conversation attachments, and soft-deleted.
      "vectorStorageSize": integer
      "chunksCount": integer
      "canUpdate": boolean // Return whether the current user can update
this resource.
      "canDelete": boolean // Return whether the current user can delete
this resource.
      "createdAt": string (timestamp)
      "updatedAt": string (timestamp)
    }
  ]
}
```

Example Response Values

```
{
  "count": 123,
  "next": "http://api.example.org/accounts/?page=4",
```

```
  "previous": "http://api.example.org/accounts/?page=2",
  "results": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "createdBy": {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "name": "Response String"
      },
      "organization": "550e8400-e29b-41d4-a716-446655440000",
      "embeddingModel": "550e8400-e29b-41d4-a716-446655440000",
      "rerankerModel": "550e8400-e29b-41d4-a716-446655440000",
      "name": "Response String",
      "description": "Response String",
      "numberOfRetrievedChunks": 456,
      "enableHyde": false,
      "similarityCutoff": 456,
      "enableRerank": false,
      "enableRrf": false,
      "vectorDatabaseType": {},
      "vectorDatabaseUrl": "Response String",
      "vectorDatabaseApiKey": "Response String",
      "opensearchUsername": "Response String",
      "opensearchPassword": "Response String",
      "oracleUser": "Response String",
      "oraclePassword": "Response String",
      "synxdbUser": "Response String",
      "synxdbPassword": "Response String",
      "labels": [
        {
          "id": "550e8400-e29b-41d4-a716-446655440000",
          "name": "Response String"
        }
      ],
      "chatbots": [
        {
          "id": "550e8400-e29b-41d4-a716-446655440000",
          "name": "Response String"
        }
      ],
      "groups": [
        {
          "id": "550e8400-e29b-41d4-a716-446655440000",
          "name": "Response String"
        }
      ],
```

```
      "filesCount": 456,
      "vectorStorageSize": 456,
      "chunksCount": 456,
      "canUpdate": false,
      "canDelete": false,
      "createdAt": "Response String",
      "updatedAt": "Response String"
    }
  ]
}
```


Retrieve Details of a Specific Knowledge Base

GET `/api/v1/knowledge-bases/{id}`

Parameters

Parameter Name	Required	Type	Description
`id`	V	string	A UUID string identifying this Knowledge Base.

Code Examples

Shell/Bash

```shell
# Example API Call (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/knowledge-
bases/550e8400-e29b-41d4-a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```javascript
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-
e29b-41d4-a716-446655440000/", config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-e29b-41d4-a716-446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-e29b-
41d4-a716-446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response Body

Status Code: 200

Example Response Schema

```
{
  "id": string (uuid)
  "createdBy":
```

```
  {
    "id": string (uuid)
    "name": string
  }
  "organization"?: string (uuid) // Optional
  "embeddingModel": string (uuid)
  "rerankerModel": string (uuid)
  "name": string
  "description"?: string // Optional
  "numberOfRetrievedChunks"?: integer // Number of reference chunks to
retrieve; defaults to 12, minimum 1 (Optional)
  "enableHyde"?: boolean // Enable HyDE; defaults to False (Optional)
  "similarityCutoff"?: number (double) // Similarity threshold; defaults
to 0.0, range 0.0-1.0 (Optional)
  "enableRerank"?: boolean // Whether to enable reranking; defaults to
True (Optional)
  "enableRrf"?: boolean // Enable Reciprocal Rank Fusion for hybrid
search. Disable this if using a custom Elasticsearch without enterprise
license. (Optional)
  "vectorDatabaseType"?:  // Type of vector database: elasticsearch or
opensearch.

* `elasticsearch` - Elasticsearch
* `opensearch` - OpenSearch
* `oracle` - Oracle AI Database 26ai
* `synxdb` - SynxDB (Optional)
  {
  }
  "vectorDatabaseUrl"?: string // Custom vector database endpoint URL or
Oracle DSN. For Elasticsearch/OpenSearch: URL format (e.g.,
"https://host:9200"). For Oracle: DSN format (e.g.,
"host:1521/service_name"). (Optional)
  "vectorDatabaseApiKey"?: string // API Key for Elasticsearch. Not used
for OpenSearch. (Optional)
  "opensearchUsername"?: string // Username for OpenSearch Basic Auth.
(Optional)
  "opensearchPassword"?: string // Password for OpenSearch Basic Auth.
(Optional)
  "oracleUser"?: string // Oracle database username. (Optional)
  "oraclePassword"?: string // Oracle database password. (Optional)
  "synxdbUser"?: string // SynxDB database username. (Optional)
  "synxdbPassword"?: string // SynxDB database password. (Optional)
  "labels": [
    {
      "id": string (uuid)
```

```
      "name": string
    }
  ]
  "chatbots"?: [ // Optional
    {
      "id": string (uuid)
      "name": string
    }
  ]
  "groups"?: [ // List of groups that can access the knowledge base
(Optional)
    {
      "id": string (uuid)
      "name": string
    }
  ]
  "filesCount": integer // Return count of KnowledgeBaseFile excluding
processed files, conversation attachments, and soft-deleted.
  "vectorStorageSize": integer
  "chunksCount": integer
  "canUpdate": boolean // Return whether the current user can update this
resource.
  "canDelete": boolean // Return whether the current user can delete this
resource.
  "createdAt": string (timestamp)
  "updatedAt": string (timestamp)
}
```

Example Response Values

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "createdBy": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Response string"
  },
  "organization": "550e8400-e29b-41d4-a716-446655440000",
  "embeddingModel": "550e8400-e29b-41d4-a716-446655440000",
  "rerankerModel": "550e8400-e29b-41d4-a716-446655440000",
  "name": "Response string",
  "description": "Response string",
  "numberOfRetrievedChunks": 456,
  "enableHyde": false,
  "similarityCutoff": 456,
```

```
  "enableRerank": false,
  "enableRrf": false,
  "vectorDatabaseType": {},
  "vectorDatabaseUrl": "Response string",
  "vectorDatabaseApiKey": "Response string",
  "opensearchUsername": "Response string",
  "opensearchPassword": "Response string",
  "oracleUser": "Response string",
  "oraclePassword": "Response string",
  "synxdbUser": "Response string",
  "synxdbPassword": "Response string",
  "labels": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "Response string"
    }
  ],
  "chatbots": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "Response string"
    }
  ],
  "groups": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "Response string"
    }
  ],
  "filesCount": 456,
  "vectorStorageSize": 456,
  "chunksCount": 456,
  "canUpdate": false,
  "canDelete": false,
  "createdAt": "Response string",
  "updatedAt": "Response string"
}
```


Search the Contents of a Specific Knowledge Base

POST `/api/v1/knowledge-bases/{id}/search/`

Parameters

Parameter Name	Required	Type	Description
`id`	V	string	A UUID string identifying this Knowledge Base.
`embeddingModel`	X	string	
`page`	X	integer	A page number within the paginated result set.
`pageSize`	X	integer	Number of results to return per page.
`query`	X	string	
`rerankerModel`	X	string	

Request Body

Request Parameters

Field	Type	Required	Description
searchMode	object	No	Search mode: hybrid (default, vector + BM25), semantic (vector only), keyword (BM25 only) `hybrid` : Hybrid (vector + BM25) ; `semantic` : Semantic (vector only) ; `keyword` : Keyword (BM25 only);
queryMetadata	object	No	Query metadata used to control the search scope and method

Example Request Schema

```
{
  "searchMode"?:  // Search mode: hybrid (default, vector + BM25),
semantic (vector only), keyword (BM25 only)

* `hybrid` - Hybrid (vector + BM25)
* `semantic` - Semantic (vector only)
* `keyword` - Keyword (BM25 only) (Optional)
  {
  }
  "queryMetadata"?: object // Query metadata used to control the search
scope and method (Optional)
}
```

Example Request Values

```
{
  "query": "How to use the API"
}
```

Code Examples

Shell/Bash

```
# Example API call (Shell)
curl -X POST "https://api.maiagent.ai/api/v1/knowledge-
bases/550e8400-e29b-41d4-a716-446655440000/search/?
embeddingModel=550e8400-e29b-41d4-a716-
446655440000&page=1&pageSize=1&query=example&rerankerModel=550e8400-
e29b-41d4-a716-446655440000"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "query": "How to use the API"
  }'

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// Request Body (payload)
const data = {
    "query": "How to use the API"
  };

axios.post("https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-e29b-41d4-a716-446655440000/search/?embeddingModel=550e8400-e29b-41d4-a716-446655440000&page=1&pageSize=1&query=example&rerankerModel=550e8400-e29b-41d4-a716-446655440000", data, config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-e29b-41d4-a716-446655440000/search/?embeddingModel=550e8400-e29b-41d4-a716-446655440000&page=1&pageSize=1&query=example&rerankerModel=550e8400-e29b-41d4-a716-446655440000"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# Request Body (payload)
data = {
    "query": "How to use the API"
}

response = requests.post(url, json=data, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>post("https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-e29b-
41d4-a716-446655440000/search/?embeddingModel=550e8400-e29b-41d4-
a716-
446655440000&page=1&pageSize=1&query=example&rerankerModel=550e8400-
e29b-41d4-a716-446655440000", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'query' => 'How to use the API'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response Body

Status Code: 200

Example Response Schema

```
{
  "count": integer
  "next"?: string (uri) // Optional
  "previous"?: string (uri) // Optional
  "results": [
    {
      "id": string (uuid)
      "charactersCount": integer
      "hitsCount": integer
      "text": string
      "updatedAt": string (timestamp)
      "filename": string
      "chatbotFile": object // Return the complete ChatbotFile
information, including the file URL and type, to support frontend image
previews
      "knowledgeBaseFile": object // Same as get_chatbot_file, for
backward compatibility
      "pageNumber": integer // Backward-compatible alias of
``page_start``.
      "pageStart": integer
      "pageEnd": integer
      "citationTitle": string // Source title shown on the inline
citation hover card.
      "citationDescription": string // Source description shown on the
inline citation hover card.
      "citationQuote": string // Quoted text snippet shown on the inline
citation hover card.
      "hasImage": boolean // Determine whether an image is present (check
the file type or Markdown images in text)
      "imageUrl": string // Extract the image URL (prefer the file URL;
otherwise extract it from Markdown)
      "displayText": string // Return the full text with Markdown image
markup removed
      "displayTitle": string // Return the display title (fallback:
citation_title -> filename)
      "highlightedText": string // Return text with matched terms wrapped
in ``<mark>`` tags.

Priority:
1. ES/OpenSearch native highlight (set by retrieve_api via
``_es_highlighted_text``)
2. Python regex fallback (keyword-based, works for all backends)
      "labels": [
```

```
        {
          "id": string (uuid)
          "name": string
        }
      ]
      "rawUserDefineMetadata"?: object // Metadata keys and values
defined by the user. (Optional)
      "metadataEnabledForSearch": object // Map each user-defined
metadata key on this node to whether it was sent into the LLM.

A key reaches the LLM only when its ``MetadataKey.enabled_for_search`` is
True *and*
the node carries a value for it. Since this maps over
``raw_user_define_metadata``
(the keys the cited-documents block displays, all of which have a value),
``enabled_for_search`` alone decides the flag. The source of truth is the
node's
knowledge base ``MetadataKey`` current setting, matching the AI Search
indicator.
      "startCharIdx": integer
      "endCharIdx": integer
    }
  ]
}
```

Example Response Values

```
{
  "count": 123,
  "next": "http://api.example.org/accounts/?page=4",
  "previous": "http://api.example.org/accounts/?page=2",
  "results": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "charactersCount": 456,
      "hitsCount": 456,
      "text": "Response string",
      "updatedAt": "Response string",
      "filename": "Response string",
      "chatbotFile": {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "name": "Example response name",
        "description": "Example response description"
      },
```

```
      "knowledgeBaseFile": {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "name": "Example response name",
        "description": "Example response description"
      },
      "pageNumber": 456,
      "pageStart": 456,
      "pageEnd": 456,
      "citationTitle": "Response string",
      "citationDescription": "Response string",
      "citationQuote": "Response string",
      "hasImage": false,
      "imageUrl": "Response string",
      "displayText": "Response string",
      "displayTitle": "Response string",
      "highlightedText": "Response string",
      "labels": [
        {
          "id": "550e8400-e29b-41d4-a716-446655440000",
          "name": "Response string"
        }
      ],
      "rawUserDefineMetadata": null,
      "metadataEnabledForSearch": {
        "key1": "value1",
        "key2": "value2",
        "createdAt": "2025-01-01T00:00:00.000Z"
      },
      "startCharIdx": 456,
      "endCharIdx": 456
    }
  ]
}
```


Update a Knowledge Base

PUT `/api/v1/knowledge-bases/{id}`

Parameters

Parameter Name	Required	Type	Description
`id`	V	string	A UUID string identifying this Knowledge Base.

Request Body

Request Parameters

Field	Type	Required	Description
organization	string (uuid)	No	
embeddingModel	string (uuid)	Yes	
rerankerModel	string (uuid)	Yes	
name	string	Yes	
description	string	No	
numberOfRetrievedChunks	integer	No	Number of reference chunks to retrieve; defaults to 12, minimum 1
enableHyde	boolean	No	Enable HyDE; defaults to False
similarityCutoff	number (double)	No	Similarity threshold; defaults to 0.0, range 0.0-1.0
enableRerank	boolean	No	Whether to enable reranking; defaults to True
enableRrf	boolean	No	Enable Reciprocal Rank Fusion for hybrid search. Disable this if using a custom Elasticsearch without enterprise license.

Field	Type	Required	Description
vectorDatabaseType	object	No	Type of vector database: elasticsearch or opensearch. `elasticsearch` : Elasticsearch ; `opensearch` : OpenSearch ; `oracle` : Oracle AI Database 26ai ; `synxdb` : SynxDB;
vectorDatabaseUrl	string	No	Custom vector database endpoint URL or Oracle DSN. For Elasticsearch/OpenSearch: URL format (e.g., "https://host:9200"). For Oracle: DSN format (e.g., "host:1521/service_name").
vectorDatabaseApiKey	string	No	API Key for Elasticsearch. Not used for OpenSearch.
opensearchUsername	string	No	Username for OpenSearch Basic Auth.
opensearchPassword	string	No	Password for OpenSearch Basic Auth.
oracleUser	string	No	Oracle database username.
oraclePassword	string	No	Oracle database password.
synxdbUser	string	No	SynxDB database username.
synxdbPassword	string	No	SynxDB database password.
chatbots	array[IdName]	No	
groups	array[IdName]	No	List of groups that can access the knowledge base

Example Request Schema

```
{
  "organization"?: string (uuid) // Optional
  "embeddingModel": string (uuid)
  "rerankerModel": string (uuid)
  "name": string
  "description"?: string // Optional
  "numberOfRetrievedChunks"?: integer // Number of reference chunks to
retrieve; defaults to 12, minimum 1 (Optional)
  "enableHyde"?: boolean // Enable HyDE; defaults to False (Optional)
  "similarityCutoff"?: number (double) // Similarity threshold; defaults
to 0.0, range 0.0-1.0 (Optional)
  "enableRerank"?: boolean // Whether to enable reranking; defaults to
True (Optional)
  "enableRrf"?: boolean // Enable Reciprocal Rank Fusion for hybrid
search. Disable this if using a custom Elasticsearch without enterprise
license. (Optional)
  "vectorDatabaseType"?:  // Type of vector database: elasticsearch or
opensearch.

* `elasticsearch` - Elasticsearch
* `opensearch` - OpenSearch
* `oracle` - Oracle AI Database 26ai
* `synxdb` - SynxDB (Optional)
  {
  }
  "vectorDatabaseUrl"?: string // Custom vector database endpoint URL or
Oracle DSN. For Elasticsearch/OpenSearch: URL format (e.g.,
"https://host:9200"). For Oracle: DSN format (e.g.,
"host:1521/service_name"). (Optional)
  "vectorDatabaseApiKey"?: string // API Key for Elasticsearch. Not used
for OpenSearch. (Optional)
  "opensearchUsername"?: string // Username for OpenSearch Basic Auth.
(Optional)
  "opensearchPassword"?: string // Password for OpenSearch Basic Auth.
(Optional)
  "oracleUser"?: string // Oracle database username. (Optional)
  "oraclePassword"?: string // Oracle database password. (Optional)
  "synxdbUser"?: string // SynxDB database username. (Optional)
  "synxdbPassword"?: string // SynxDB database password. (Optional)
  "chatbots"?: [ // Optional
    {
      "id": string (uuid)
    }
  ]
```

```
  "groups"?: [ // List of groups that can access the knowledge base
(Optional)
    {
      "id": string (uuid)
    }
  ]
}
```

Example Request Values

```
{
  "organization": "550e8400-e29b-41d4-a716-446655440000",
  "embeddingModel": "550e8400-e29b-41d4-a716-446655440000",
  "rerankerModel": "550e8400-e29b-41d4-a716-446655440000",
  "name": "Example name",
  "description": "Example string",
  "numberOfRetrievedChunks": 123,
  "enableHyde": true,
  "similarityCutoff": 123,
  "enableRerank": true,
  "enableRrf": true,
  "vectorDatabaseType": {},
  "vectorDatabaseUrl": "Example string",
  "vectorDatabaseApiKey": "Example string",
  "opensearchUsername": "Example string",
  "opensearchPassword": "Example string",
  "oracleUser": "Example string",
  "oraclePassword": "Example string",
  "synxdbUser": "Example string",
  "synxdbPassword": "Example string",
  "chatbots": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000"
    }
  ],
  "groups": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000"
    }
  ]
}
```

Code Examples

Shell/Bash

```
# Example API call (Shell)
curl -X PUT "https://api.maiagent.ai/api/v1/knowledge-
bases/550e8400-e29b-41d4-a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "organization": "550e8400-e29b-41d4-a716-446655440000",
    "embeddingModel": "550e8400-e29b-41d4-a716-446655440000",
    "rerankerModel": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Example name",
    "description": "Example string",
    "numberOfRetrievedChunks": 123,
    "enableHyde": true,
    "similarityCutoff": 123,
    "enableRerank": true,
    "enableRrf": true,
    "vectorDatabaseType": {},
    "vectorDatabaseUrl": "Example string",
    "vectorDatabaseApiKey": "Example string",
    "opensearchUsername": "Example string",
    "opensearchPassword": "Example string",
    "oracleUser": "Example string",
    "oraclePassword": "Example string",
    "synxdbUser": "Example string",
    "synxdbPassword": "Example string",
    "chatbots": [
      {
        "id": "550e8400-e29b-41d4-a716-446655440000"
      }
    ],
    "groups": [
      {
        "id": "550e8400-e29b-41d4-a716-446655440000"
      }
    ]
  }'
```

```
# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// Request Body (payload)
const data = {
    "organization": "550e8400-e29b-41d4-a716-446655440000",
    "embeddingModel": "550e8400-e29b-41d4-a716-446655440000",
    "rerankerModel": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Example name",
    "description": "Example string",
    "numberOfRetrievedChunks": 123,
    "enableHyde": true,
    "similarityCutoff": 123,
    "enableRerank": true,
    "enableRrf": true,
    "vectorDatabaseType": {},
    "vectorDatabaseUrl": "Example string",
    "vectorDatabaseApiKey": "Example string",
    "opensearchUsername": "Example string",
    "opensearchPassword": "Example string",
    "oracleUser": "Example string",
    "oraclePassword": "Example string",
    "synxdbUser": "Example string",
    "synxdbPassword": "Example string",
    "chatbots": [
      {
        "id": "550e8400-e29b-41d4-a716-446655440000"
      }
    ],
    "groups": [
      {
        "id": "550e8400-e29b-41d4-a716-446655440000"
      }
```

```
    ]
  };

axios.put("https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-
e29b-41d4-a716-446655440000/", data, config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-e29b-
41d4-a716-446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# Request body (payload)
data = {
    "organization": "550e8400-e29b-41d4-a716-446655440000",
    "embeddingModel": "550e8400-e29b-41d4-a716-446655440000",
    "rerankerModel": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Example Name",
    "description": "Example String",
    "numberOfRetrievedChunks": 123,
    "enableHyde": True,
    "similarityCutoff": 123,
    "enableRerank": True,
    "enableRrf": True,
    "vectorDatabaseType": {},
    "vectorDatabaseUrl": "Example String",
    "vectorDatabaseApiKey": "Example String",
    "opensearchUsername": "Example String",
    "opensearchPassword": "Example String",
    "oracleUser": "Example String",
    "oraclePassword": "Example String",
    "synxdbUser": "Example String",
    "synxdbPassword": "Example String",
    "chatbots": [
        {
            "id": "550e8400-e29b-41d4-a716-446655440000"
        }
    ],
    "groups": [
        {
            "id": "550e8400-e29b-41d4-a716-446655440000"
        }
    ]
```

```
}

response = requests.put(url, json=data, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("An error occurred during the request:", e)
```

PHP

```
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>put("https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-e29b-
41d4-a716-446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'organization' => '550e8400-e29b-41d4-a716-
446655440000',
            'embeddingModel' => '550e8400-e29b-41d4-a716-
446655440000',
            'rerankerModel' => '550e8400-e29b-41d4-a716-
446655440000',
            'name' => 'Example Name',
            'description' => 'Example String',
            'numberOfRetrievedChunks' => 123,
            'enableHyde' => true,
            'similarityCutoff' => 123,
            'enableRerank' => true,
            'enableRrf' => true,
            'vectorDatabaseType' => new \stdClass(),
            'vectorDatabaseUrl' => 'Example String',
            'vectorDatabaseApiKey' => 'Example String',
            'opensearchUsername' => 'Example String',
            'opensearchPassword' => 'Example String',
            'oracleUser' => 'Example String',
            'oraclePassword' => 'Example String',
            'synxdbUser' => 'Example String',
            'synxdbPassword' => 'Example String',
            'chatbots' => [
                [
                    'id' => '550e8400-e29b-41d4-a716-446655440000'
                ]
```

```
            ],
            'groups' => [
                [
                    'id' => '550e8400-e29b-41d4-a716-446655440000'
                ]
            ]
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'An error occurred during the request: ' . $e-
>getMessage();
}
?>
```

Response Body

Status Code: 200

Example Response Schema

```
{
  "id": string (uuid)
  "createdBy":
  {
    "id": string (uuid)
    "name": string
  }
  "organization"?: string (uuid) // Optional
  "embeddingModel": string (uuid)
  "rerankerModel": string (uuid)
  "name": string
  "description"?: string // Optional
  "numberOfRetrievedChunks"?: integer // Number of reference chunks to
```

```
retrieve; defaults to 12, with a minimum of 1 (Optional)
  "enableHyde"?: boolean // Enable HyDE; defaults to False (Optional)
  "similarityCutoff"?: number (double) // Similarity threshold; defaults
to 0.0, with a range of 0.0-1.0 (Optional)
  "enableRerank"?: boolean // Whether to enable reranking; defaults to
True (Optional)
  "enableRrf"?: boolean // Enable Reciprocal Rank Fusion for hybrid
search. Disable this if using a custom Elasticsearch without enterprise
license. (Optional)
  "vectorDatabaseType"?:  // Type of vector database: elasticsearch or
opensearch.

* `elasticsearch` - Elasticsearch
* `opensearch` - OpenSearch
* `oracle` - Oracle AI Database 26ai
* `synxdb` - SynxDB (Optional)
  {
  }
  "vectorDatabaseUrl"?: string // Custom vector database endpoint URL or
Oracle DSN. For Elasticsearch/OpenSearch: URL format (e.g.,
"https://host:9200"). For Oracle: DSN format (e.g.,
"host:1521/service_name"). (Optional)
  "vectorDatabaseApiKey"?: string // API Key for Elasticsearch. Not used
for OpenSearch. (Optional)
  "opensearchUsername"?: string // Username for OpenSearch Basic Auth.
(Optional)
  "opensearchPassword"?: string // Password for OpenSearch Basic Auth.
(Optional)
  "oracleUser"?: string // Oracle database username. (Optional)
  "oraclePassword"?: string // Oracle database password. (Optional)
  "synxdbUser"?: string // SynxDB database username. (Optional)
  "synxdbPassword"?: string // SynxDB database password. (Optional)
  "labels": [
    {
      "id": string (uuid)
      "name": string
    }
  ]
  "chatbots"?: [ // Optional
    {
      "id": string (uuid)
      "name": string
    }
  ]
  "groups"?: [ // List of groups that can access the knowledge base
```

```
(Optional)
    {
      "id": string (uuid)
      "name": string
    }
  ]
  "filesCount": integer // Return count of KnowledgeBaseFile excluding
processed files, conversation attachments, and soft-deleted.
  "vectorStorageSize": integer
  "chunksCount": integer
  "canUpdate": boolean // Return whether the current user can update this
resource.
  "canDelete": boolean // Return whether the current user can delete this
resource.
  "createdAt": string (timestamp)
  "updatedAt": string (timestamp)
}
```

Example Response Values

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "createdBy": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Response String"
  },
  "organization": "550e8400-e29b-41d4-a716-446655440000",
  "embeddingModel": "550e8400-e29b-41d4-a716-446655440000",
  "rerankerModel": "550e8400-e29b-41d4-a716-446655440000",
  "name": "Response String",
  "description": "Response String",
  "numberOfRetrievedChunks": 456,
  "enableHyde": false,
  "similarityCutoff": 456,
  "enableRerank": false,
  "enableRrf": false,
  "vectorDatabaseType": {},
  "vectorDatabaseUrl": "Response String",
  "vectorDatabaseApiKey": "Response String",
  "opensearchUsername": "Response String",
  "opensearchPassword": "Response String",
  "oracleUser": "Response String",
  "oraclePassword": "Response String",
  "synxdbUser": "Response String",
```

```
  "synxdbPassword": "Response String",
  "labels": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "Response String"
    }
  ],
  "chatbots": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "Response String"
    }
  ],
  "groups": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "Response String"
    }
  ],
  "filesCount": 456,
  "vectorStorageSize": 456,
  "chunksCount": 456,
  "canUpdate": false,
  "canDelete": false,
  "createdAt": "Response String",
  "updatedAt": "Response String"
}
```


Partially Update a Knowledge Base

PATCH `/api/v1/knowledge-bases/{id}`

Parameters

Parameter Name	Required	Type	Description

`id`	V	string	A UUID string identifying this Knowledge Base.

Request Body

Request Parameters

Field	Type	Required	Description
organization	string (uuid)	No	
embeddingModel	string (uuid)	No	
rerankerModel	string (uuid)	No	
name	string	No	
description	string	No	
numberOfRetrievedChunks	integer	No	Number of reference chunks to retrieve; defaults to 12, with a minimum of 1
enableHyde	boolean	No	Enable HyDE; defaults to False
similarityCutoff	number (double)	No	Similarity threshold; defaults to 0.0, with a range of 0.0-1.0
enableRerank	boolean	No	Whether to enable reranking; defaults to True
enableRrf	boolean	No	Enable Reciprocal Rank Fusion for hybrid search. Disable this if using a custom Elasticsearch without enterprise license.
vectorDatabaseType	object	No	Type of vector database: elasticsearch or opensearch. `elasticsearch` : Elasticsearch ; `opensearch` : OpenSearch ;

Field	Type	Required	Description
			`oracle` : Oracle AI Database 26ai ; `synxdb` : SynxDB;
vectorDatabaseUrl	string	No	Custom vector database endpoint URL or Oracle DSN. For Elasticsearch/OpenSearch: URL format (e.g., "https://host:9200"). For Oracle: DSN format (e.g., "host:1521/service_name").
vectorDatabaseApiKey	string	No	API Key for Elasticsearch. Not used for OpenSearch.
opensearchUsername	string	No	Username for OpenSearch Basic Auth.
opensearchPassword	string	No	Password for OpenSearch Basic Auth.
oracleUser	string	No	Oracle database username.
oraclePassword	string	No	Oracle database password.
synxdbUser	string	No	SynxDB database username.
synxdbPassword	string	No	SynxDB database password.
chatbots	array[IdName]	No	
groups	array[IdName]	No	List of groups that can access the knowledge base

Example Request Schema

```
{
  "organization"?: string (uuid) // Optional
  "embeddingModel"?: string (uuid) // Optional
  "rerankerModel"?: string (uuid) // Optional
  "name"?: string // Optional
  "description"?: string // Optional
```

```
  "numberOfRetrievedChunks"?: integer // Number of reference chunks to
retrieve; defaults to 12, with a minimum of 1 (Optional)
  "enableHyde"?: boolean // Enable HyDE; defaults to False (Optional)
  "similarityCutoff"?: number (double) // Similarity threshold; defaults
to 0.0, with a range of 0.0-1.0 (Optional)
  "enableRerank"?: boolean // Whether to enable reranking; defaults to
True (Optional)
  "enableRrf"?: boolean // Enable Reciprocal Rank Fusion for hybrid
search. Disable this if using a custom Elasticsearch without enterprise
license. (Optional)
  "vectorDatabaseType"?:  // Type of vector database: elasticsearch or
opensearch.

* `elasticsearch` - Elasticsearch
* `opensearch` - OpenSearch
* `oracle` - Oracle AI Database 26ai
* `synxdb` - SynxDB (Optional)
  {
  }
  "vectorDatabaseUrl"?: string // Custom vector database endpoint URL or
Oracle DSN. For Elasticsearch/OpenSearch: URL format (e.g.,
"https://host:9200"). For Oracle: DSN format (e.g.,
"host:1521/service_name"). (Optional)
  "vectorDatabaseApiKey"?: string // API Key for Elasticsearch. Not used
for OpenSearch. (Optional)
  "opensearchUsername"?: string // Username for OpenSearch Basic Auth.
(Optional)
  "opensearchPassword"?: string // Password for OpenSearch Basic Auth.
(Optional)
  "oracleUser"?: string // Oracle database username. (Optional)
  "oraclePassword"?: string // Oracle database password. (Optional)
  "synxdbUser"?: string // SynxDB database username. (Optional)
  "synxdbPassword"?: string // SynxDB database password. (Optional)
  "chatbots"?: [ // Optional
    {
      "id": string (uuid)
    }
  ]
  "groups"?: [ // List of groups that can access the knowledge base
(Optional)
    {
      "id": string (uuid)
    }
```

```
  ]
}
```

Example Request Values

```
{
  "organization": "550e8400-e29b-41d4-a716-446655440000",
  "embeddingModel": "550e8400-e29b-41d4-a716-446655440000",
  "rerankerModel": "550e8400-e29b-41d4-a716-446655440000",
  "name": "Example Name",
  "description": "Example String",
  "numberOfRetrievedChunks": 123,
  "enableHyde": true,
  "similarityCutoff": 123,
  "enableRerank": true,
  "enableRrf": true,
  "vectorDatabaseType": {},
  "vectorDatabaseUrl": "Example String",
  "vectorDatabaseApiKey": "Example String",
  "opensearchUsername": "Example String",
  "opensearchPassword": "Example String",
  "oracleUser": "Example String",
  "oraclePassword": "Example String",
  "synxdbUser": "Example String",
  "synxdbPassword": "Example String",
  "chatbots": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000"
    }
  ],
  "groups": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000"
    }
  ]
}
```

Code Examples

Shell/Bash

```
# API call example (Shell)
curl -X PATCH "https://api.maiagent.ai/api/v1/knowledge-
bases/550e8400-e29b-41d4-a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "organization": "550e8400-e29b-41d4-a716-446655440000",
    "embeddingModel": "550e8400-e29b-41d4-a716-446655440000",
    "rerankerModel": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Example Name",
    "description": "Example String",
    "numberOfRetrievedChunks": 123,
    "enableHyde": true,
    "similarityCutoff": 123,
    "enableRerank": true,
    "enableRrf": true,
    "vectorDatabaseType": {},
    "vectorDatabaseUrl": "Example String",
    "vectorDatabaseApiKey": "Example String",
    "opensearchUsername": "Example String",
    "opensearchPassword": "Example String",
    "oracleUser": "Example String",
    "oraclePassword": "Example String",
    "synxdbUser": "Example String",
    "synxdbPassword": "Example String",
    "chatbots": [
      {
        "id": "550e8400-e29b-41d4-a716-446655440000"
      }
    ],
    "groups": [
      {
        "id": "550e8400-e29b-41d4-a716-446655440000"
      }
    ]
  }'
```

```
# Before running, replace YOUR_API_KEY and verify the request data.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// Request body (payload)
const data = {
    "organization": "550e8400-e29b-41d4-a716-446655440000",
    "embeddingModel": "550e8400-e29b-41d4-a716-446655440000",
    "rerankerModel": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Example Name",
    "description": "Example String",
    "numberOfRetrievedChunks": 123,
    "enableHyde": true,
    "similarityCutoff": 123,
    "enableRerank": true,
    "enableRrf": true,
    "vectorDatabaseType": {},
    "vectorDatabaseUrl": "Example String",
    "vectorDatabaseApiKey": "Example String",
    "opensearchUsername": "Example String",
    "opensearchPassword": "Example String",
    "oracleUser": "Example String",
    "oraclePassword": "Example String",
    "synxdbUser": "Example String",
    "synxdbPassword": "Example String",
    "chatbots": [
      {
        "id": "550e8400-e29b-41d4-a716-446655440000"
      }
    ],
    "groups": [
      {
        "id": "550e8400-e29b-41d4-a716-446655440000"
      }
```

```
    ]
  };

axios.patch("https://api.maiagent.ai/api/v1/knowledge-
bases/550e8400-e29b-41d4-a716-446655440000/", data, config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('An error occurred during the request:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-e29b-
41d4-a716-446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# Request body (payload)
data = {
    "organization": "550e8400-e29b-41d4-a716-446655440000",
    "embeddingModel": "550e8400-e29b-41d4-a716-446655440000",
    "rerankerModel": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Example Name",
    "description": "Example String",
    "numberOfRetrievedChunks": 123,
    "enableHyde": True,
    "similarityCutoff": 123,
    "enableRerank": True,
    "enableRrf": True,
    "vectorDatabaseType": {},
    "vectorDatabaseUrl": "Example String",
    "vectorDatabaseApiKey": "Example String",
    "opensearchUsername": "Example String",
    "opensearchPassword": "Example String",
    "oracleUser": "Example String",
    "oraclePassword": "Example String",
    "synxdbUser": "Example String",
    "synxdbPassword": "Example String",
    "chatbots": [
        {
            "id": "550e8400-e29b-41d4-a716-446655440000"
        }
    ],
    "groups": [
        {
            "id": "550e8400-e29b-41d4-a716-446655440000"
        }
    ]
```

```
}

response = requests.patch(url, json=data, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("An error occurred during the request:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>patch("https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-
e29b-41d4-a716-446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'organization' => '550e8400-e29b-41d4-a716-
446655440000',
            'embeddingModel' => '550e8400-e29b-41d4-a716-
446655440000',
            'rerankerModel' => '550e8400-e29b-41d4-a716-
446655440000',
            'name' => 'Example Name',
            'description' => 'Example String',
            'numberOfRetrievedChunks' => 123,
            'enableHyde' => true,
            'similarityCutoff' => 123,
            'enableRerank' => true,
            'enableRrf' => true,
            'vectorDatabaseType' => new \stdClass(),
            'vectorDatabaseUrl' => 'Example String',
            'vectorDatabaseApiKey' => 'Example String',
            'opensearchUsername' => 'Example String',
            'opensearchPassword' => 'Example String',
            'oracleUser' => 'Example String',
            'oraclePassword' => 'Example String',
            'synxdbUser' => 'Example String',
            'synxdbPassword' => 'Example String',
            'chatbots' => [
                [
                    'id' => '550e8400-e29b-41d4-a716-446655440000'
                ]
```

```
            ],
            'groups' => [
                [
                    'id' => '550e8400-e29b-41d4-a716-446655440000'
                ]
            ]
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'An error occurred during the request: ' . $e-
>getMessage();
}
?>
```

Response Body

Status Code: 200

Example Response Schema

```
{
  "id": string (uuid)
  "createdBy":
  {
    "id": string (uuid)
    "name": string
  }
  "organization"?: string (uuid) // Optional
  "embeddingModel": string (uuid)
  "rerankerModel": string (uuid)
  "name": string
  "description"?: string // Optional
  "numberOfRetrievedChunks"?: integer // Number of reference chunks to
```

```
retrieve; defaults to 12, with a minimum of 1 (Optional)
  "enableHyde"?: boolean // Enable HyDE; defaults to False (Optional)
  "similarityCutoff"?: number (double) // Similarity threshold; defaults
to 0.0, with a range of 0.0-1.0 (Optional)
  "enableRerank"?: boolean // Whether to enable reranking; defaults to
True (Optional)
  "enableRrf"?: boolean // Enable Reciprocal Rank Fusion for hybrid
search. Disable this if using a custom Elasticsearch without enterprise
license. (Optional)
  "vectorDatabaseType"?:  // Type of vector database: elasticsearch or
opensearch.

* `elasticsearch` - Elasticsearch
* `opensearch` - OpenSearch
* `oracle` - Oracle AI Database 26ai
* `synxdb` - SynxDB (Optional)
  {
  }
  "vectorDatabaseUrl"?: string // Custom vector database endpoint URL or
Oracle DSN. For Elasticsearch/OpenSearch: URL format (e.g.,
"https://host:9200"). For Oracle: DSN format (e.g.,
"host:1521/service_name"). (Optional)
  "vectorDatabaseApiKey"?: string // API Key for Elasticsearch. Not used
for OpenSearch. (Optional)
  "opensearchUsername"?: string // Username for OpenSearch Basic Auth.
(Optional)
  "opensearchPassword"?: string // Password for OpenSearch Basic Auth.
(Optional)
  "oracleUser"?: string // Oracle database username. (Optional)
  "oraclePassword"?: string // Oracle database password. (Optional)
  "synxdbUser"?: string // SynxDB database username. (Optional)
  "synxdbPassword"?: string // SynxDB database password. (Optional)
  "labels": [
    {
      "id": string (uuid)
      "name": string
    }
  ]
  "chatbots"?: [ // Optional
    {
      "id": string (uuid)
      "name": string
    }
  ]
  "groups"?: [ // List of groups that can access the knowledge base
```

```
(Optional)
    {
      "id": string (uuid)
      "name": string
    }
  ]
  "filesCount": integer // Return count of KnowledgeBaseFile excluding
processed files, conversation attachments, and soft-deleted.
  "vectorStorageSize": integer
  "chunksCount": integer
  "canUpdate": boolean // Return whether the current user can update this
resource.
  "canDelete": boolean // Return whether the current user can delete this
resource.
  "createdAt": string (timestamp)
  "updatedAt": string (timestamp)
}
```

Example Response Values

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "createdBy": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Response String"
  },
  "organization": "550e8400-e29b-41d4-a716-446655440000",
  "embeddingModel": "550e8400-e29b-41d4-a716-446655440000",
  "rerankerModel": "550e8400-e29b-41d4-a716-446655440000",
  "name": "Response String",
  "description": "Response String",
  "numberOfRetrievedChunks": 456,
  "enableHyde": false,
  "similarityCutoff": 456,
  "enableRerank": false,
  "enableRrf": false,
  "vectorDatabaseType": {},
  "vectorDatabaseUrl": "Response String",
  "vectorDatabaseApiKey": "Response String",
  "opensearchUsername": "Response String",
  "opensearchPassword": "Response String",
  "oracleUser": "Response String",
  "oraclePassword": "Response String",
  "synxdbUser": "Response String",
```

```
  "synxdbPassword": "Response String",
  "labels": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "Response String"
    }
  ],
  "chatbots": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "Response String"
    }
  ],
  "groups": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "Response String"
    }
  ],
  "filesCount": 456,
  "vectorStorageSize": 456,
  "chunksCount": 456,
  "canUpdate": false,
  "canDelete": false,
  "createdAt": "Response String",
  "updatedAt": "Response String"
}
```


Delete a Knowledge Base

DELETE `/api/v1/knowledge-bases/{id}`

Parameters

Parameter Name	Required	Type	Description

id	V	string	A UUID string identifying this Knowledge Base.

Code Examples

Shell/Bash

```
# API call example (Shell)
curl -X DELETE "https://api.maiagent.ai/api/v1/knowledge-
bases/550e8400-e29b-41d4-a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

// Request body (payload)
const data = null;

axios.delete("https://api.maiagent.ai/api/v1/knowledge-
bases/550e8400-e29b-41d4-a716-446655440000/", data, config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-e29b-41d4-a716-446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.delete(url, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>delete("https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-
e29b-41d4-a716-446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response Body

Status Code	Description
204	No response body

Check RRF Availability

GET `/api/v1/knowledge-bases/{id}/check-rrf-availability/`

Parameters

Parameter Name	Required	Type	Description
`id`	V	string	A UUID string identifying this Knowledge Base.

Code Examples

Shell/Bash

```
# API call example (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/knowledge-
bases/550e8400-e29b-41d4-a716-446655440000/check-rrf-availability/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-
e29b-41d4-a716-446655440000/check-rrf-availability/", config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-e29b-41d4-a716-446655440000/check-rrf-availability/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-e29b-
41d4-a716-446655440000/check-rrf-availability/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response Body

Status Code: 200

Response Schema Example

```
{
  "id": string (uuid)
  "createdBy":
```

```
  {
    "id": string (uuid)
    "name": string
  }
  "organization"?: string (uuid) // Optional
  "embeddingModel": string (uuid)
  "rerankerModel": string (uuid)
  "name": string
  "description"?: string // Optional
  "numberOfRetrievedChunks"?: integer // Number of reference chunks to
retrieve; default: 12, minimum: 1 (Optional)
  "enableHyde"?: boolean // Enable HyDE; default: False (Optional)
  "similarityCutoff"?: number (double) // Similarity threshold; default:
0.0, range: 0.0-1.0 (Optional)
  "enableRerank"?: boolean // Whether to enable reranking; default: True
(Optional)
  "enableRrf"?: boolean // Enable Reciprocal Rank Fusion for hybrid
search. Disable this if using a custom Elasticsearch without enterprise
license. (Optional)
  "vectorDatabaseType"?:  // Type of vector database: elasticsearch or
opensearch.

* `elasticsearch` - Elasticsearch
* `opensearch` - OpenSearch
* `oracle` - Oracle AI Database 26ai
* `synxdb` - SynxDB (Optional)
  {
  }
  "vectorDatabaseUrl"?: string // Custom vector database endpoint URL or
Oracle DSN. For Elasticsearch/OpenSearch: URL format (e.g.,
"https://host:9200"). For Oracle: DSN format (e.g.,
"host:1521/service_name"). (Optional)
  "vectorDatabaseApiKey"?: string // API Key for Elasticsearch. Not used
for OpenSearch. (Optional)
  "opensearchUsername"?: string // Username for OpenSearch Basic Auth.
(Optional)
  "opensearchPassword"?: string // Password for OpenSearch Basic Auth.
(Optional)
  "oracleUser"?: string // Oracle database username. (Optional)
  "oraclePassword"?: string // Oracle database password. (Optional)
  "synxdbUser"?: string // SynxDB database username. (Optional)
  "synxdbPassword"?: string // SynxDB database password. (Optional)
  "labels": [
    {
      "id": string (uuid)
```

```
      "name": string
    }
  ]
  "chatbots"?: [ // Optional
    {
      "id": string (uuid)
      "name": string
    }
  ]
  "groups"?: [ // List of groups that can access the knowledge base
(Optional)
    {
      "id": string (uuid)
      "name": string
    }
  ]
  "filesCount": integer // Return count of KnowledgeBaseFile excluding
processed files, conversation attachments, and soft-deleted.
  "vectorStorageSize": integer
  "chunksCount": integer
  "canUpdate": boolean // Return whether the current user can update this
resource.
  "canDelete": boolean // Return whether the current user can delete this
resource.
  "createdAt": string (timestamp)
  "updatedAt": string (timestamp)
}
```

Example Response Values

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "createdBy": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Response string"
  },
  "organization": "550e8400-e29b-41d4-a716-446655440000",
  "embeddingModel": "550e8400-e29b-41d4-a716-446655440000",
  "rerankerModel": "550e8400-e29b-41d4-a716-446655440000",
  "name": "Response string",
  "description": "Response string",
  "numberOfRetrievedChunks": 456,
  "enableHyde": false,
  "similarityCutoff": 456,
```

```
  "enableRerank": false,
  "enableRrf": false,
  "vectorDatabaseType": {},
  "vectorDatabaseUrl": "Response string",
  "vectorDatabaseApiKey": "Response string",
  "opensearchUsername": "Response string",
  "opensearchPassword": "Response string",
  "oracleUser": "Response string",
  "oraclePassword": "Response string",
  "synxdbUser": "Response string",
  "synxdbPassword": "Response string",
  "labels": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "Response string"
    }
  ],
  "chatbots": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "Response string"
    }
  ],
  "groups": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "Response string"
    }
  ],
  "filesCount": 456,
  "vectorStorageSize": 456,
  "chunksCount": 456,
  "canUpdate": false,
  "canDelete": false,
  "createdAt": "Response string",
  "updatedAt": "Response string"
}
```


Export Labels to Excel

GET `/api/v1/knowledge-bases/{id}/export-labels-excel/`

Parameters

Parameter Name	Required	Type	Description
`id`	V	string	A UUID string identifying this Knowledge Base.

Code Examples

Shell/Bash

```
# API call example (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/knowledge-
bases/550e8400-e29b-41d4-a716-446655440000/export-labels-excel/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-
e29b-41d4-a716-446655440000/export-labels-excel/", config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-e29b-41d4-a716-446655440000/export-labels-excel/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-e29b-
41d4-a716-446655440000/export-labels-excel/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response Body

Status Code	Description
200	Excel file download

Import Labels from Excel

POST `/api/v1/knowledge-bases/{id}/import-labels-excel/`

Parameters

Parameter Name	Required	Type	Description
`id`	V	string	A UUID string identifying this Knowledge Base.

Code Examples

Shell/Bash

```
# API call example (Shell)
curl -X POST "https://api.maiagent.ai/api/v1/knowledge-
bases/550e8400-e29b-41d4-a716-446655440000/import-labels-excel/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -F "excelFile=@example_file.txt"

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');
const FormData = require('form-data');

// Create a FormData object
const formData = new FormData();
// Replace with an actual file
formData.append('excelFile',
* Actual file object *
, 'example_file.txt');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    ...formData.getHeaders()
  }
};

axios.post("https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-
e29b-41d4-a716-446655440000/import-labels-excel/", formData, config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-e29b-
41d4-a716-446655440000/import-labels-excel/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}

# Prepare files and form data
files = {
    'excelFile': ('example_file.txt', open('example_file.txt',
'rb'), 'text/plain')
}

response = requests.post(url, files=files, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>post("https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-e29b-
41d4-a716-446655440000/import-labels-excel/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ],
        'multipart' => [
            [
                'name' => 'excelFile',
                'contents' => fopen('example_file.txt', 'r'),
                'filename' => 'example_file.txt'
            ]
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response Body

Status Code: 200

Response Schema Example

```
{
  "success"?: boolean // Optional
  "updated_count"?: integer // Optional
  "total_rows"?: integer // Optional
  "errors"?: [ // Optional
    {
      "row"?: integer // Optional
      "file_id"?: string // Optional
      "error"?: string // Optional
    }
  ]
}
```

Example Response Values

```
{
  "success": false,
  "updated_count": 456,
  "total_rows": 456,
  "errors": [
    {
      "row": 456,
      "file_id": "Response string",
      "error": "Response string"
    }
  ]
}
```

Export Metadata to Excel

GET `/api/v1/knowledge-bases/{id}/export-metadata-excel/`

Parameters

Parameter Name	Required	Type	Description
id	V	string	A UUID string identifying this Knowledge Base.

Code Examples

Shell/Bash

```
# API call example (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/knowledge-
bases/550e8400-e29b-41d4-a716-446655440000/export-metadata-excel/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-
e29b-41d4-a716-446655440000/export-metadata-excel/", config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-e29b-41d4-a716-446655440000/export-metadata-excel/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-e29b-
41d4-a716-446655440000/export-metadata-excel/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response Body

Status Code	Description
200	Excel file download

Import Metadata from Excel

POST `/api/v1/knowledge-bases/{id}/import-metadata-excel/`

Parameters

Parameter Name	Required	Type	Description
`id`	V	string	A UUID string identifying this Knowledge Base.

Code Examples

Shell/Bash

```
# API call example (Shell)
curl -X POST "https://api.maiagent.ai/api/v1/knowledge-
bases/550e8400-e29b-41d4-a716-446655440000/import-metadata-excel/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -F "excelFile=@example_file.txt"

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');
const FormData = require('form-data');

// Create a FormData object
const formData = new FormData();
// Replace with an actual file
formData.append('excelFile',
* Actual file object *
, 'example_file.txt');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    ...formData.getHeaders()
  }
};

axios.post("https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-
e29b-41d4-a716-446655440000/import-metadata-excel/", formData,
config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-e29b-
41d4-a716-446655440000/import-metadata-excel/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}

# Prepare files and form data
files = {
    'excelFile': ('example_file.txt', open('example_file.txt',
'rb'), 'text/plain')
}

response = requests.post(url, files=files, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>post("https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-e29b-
41d4-a716-446655440000/import-metadata-excel/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ],
        'multipart' => [
            [
                'name' => 'excelFile',
                'contents' => fopen('example_file.txt', 'r'),
                'filename' => 'example_file.txt'
            ]
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response Body

Status Code: 200

Response Schema Example

```
{
  "success"?: boolean // Optional
  "updated_count"?: integer // Optional
  "total_rows"?: integer // Optional
  "errors"?: [ // Optional
    {
      "row"?: integer // Optional
      "file_id"?: string // Optional
      "error"?: string // Optional
    }
  ]
}
```

Example Response Values


```
{
  "success": false,
  "updated_count": 456,
  "total_rows": 456,
  "errors": [
    {
      "row": 456,
      "file_id": "Response string",
      "error": "Response string"
    }
  ]
}
```


Create a New Label

POST `/api/v1/knowledge-bases/{knowledgeBasePk}/labels/`

Parameters

Parameter Name	Required	Type	Description
knowledgeBasePk	V	string	

Request Body

Request Parameters

Field	Type	Required	Description
name	string	Yes	

Request Schema Example

```
{
  "name": string
}
```

Example Request Values

```
{
  "name": "Example name"
}
```

Code Examples

Shell/Bash

```
# API call example (Shell)
curl -X POST "https://api.maiagent.ai/api/v1/knowledge-
bases/550e8400-e29b-41d4-a716-446655440000/labels/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "name": "Example name"
  }'

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// Request body (payload)
const data = {
    "name": "Example name"
  };

axios.post("https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-e29b-41d4-a716-446655440000/labels/", data, config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-e29b-
41d4-a716-446655440000/labels/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# Request body (payload)
data = {
    "name": "Example name"
}

response = requests.post(url, json=data, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>post("https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-e29b-
41d4-a716-446655440000/labels/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'name' => 'Example name'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response body

Status code: 201

Example response schema

```
{
  "id": string (uuid)
  "name"?: string // Optional
}
```

Example response values

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "name": "Response string"
}
```

List labels in the knowledge base

`GET` `/api/v1/knowledge-bases/{knowledgeBasePk}/labels/`

Parameters

Parameter name	Required	Type	Description
`knowledgeBasePk`	V	string	
`page`	X	integer	A page number within the paginated result set.
`pageSize`	X	integer	Number of results to return per page.

Code examples

Shell/Bash

```
# Example API call (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/knowledge-
bases/550e8400-e29b-41d4-a716-446655440000/labels/?
page=1&pageSize=1"

  -H "Authorization: Api-Key YOUR_API_KEY"

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-
e29b-41d4-a716-446655440000/labels/?page=1&pageSize=1", config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-e29b-41d4-a716-446655440000/labels/?page=1&pageSize=1"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-e29b-
41d4-a716-446655440000/labels/?page=1&pageSize=1", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response body

Status code: 200

Example response schema

```
{
  "count": integer
  "next"?: string (uri) // Optional
```

```
  "previous"?: string (uri) // Optional
  "results": [
    {
      "id": string (uuid)
      "name"?: string // Optional
    }
  ]
}
```

Example response values

```
{
  "count": 123,
  "next": "http://api.example.org/accounts/?page=4",
  "previous": "http://api.example.org/accounts/?page=2",
  "results": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "Response string"
    }
  ]
}
```

Get details of a specific label

GET `/api/v1/knowledge-bases/{knowledgeBasePk}/labels/{id}`

Parameters

Parameter name	Required	Type	Description
`id`	V	string	A UUID string identifying this knowledge base label.

`knowledgeBasePk`	V	string

Code examples

Shell/Bash

```
# Example API call (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/knowledge-
bases/550e8400-e29b-41d4-a716-446655440000/labels/550e8400-e29b-
41d4-a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-e29b-41d4-a716-446655440000/labels/550e8400-e29b-41d4-a716-446655440000/", config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-e29b-41d4-a716-446655440000/labels/550e8400-e29b-41d4-a716-446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-e29b-
41d4-a716-446655440000/labels/550e8400-e29b-41d4-a716-
446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response body

Status code: 200

Example response schema

```
{
  "id": string (uuid)
```

```
  "name"?: string // Optional
}
```

Example response values

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "name": "Response string"
}
```

Update a label

PUT `/api/v1/knowledge-bases/{knowledgeBasePk}/labels/{id}`

Parameters

Parameter name	Required	Type	Description
`id`	V	string	A UUID string identifying this knowledge base label.
`knowledgeBasePk`	V	string	

Request body

Request parameters

Field	Type	Required	Description
name	string	Yes	

Example request schema

```
{
  "name": string
}
```

Example request values

```
{
  "name": "Example name"
}
```

Code examples

Shell/Bash

```
# Example API call (Shell)
curl -X PUT "https://api.maiagent.ai/api/v1/knowledge-
bases/550e8400-e29b-41d4-a716-446655440000/labels/550e8400-e29b-
41d4-a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "name": "Example name"
  }'

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// Request body (payload)
const data = {
    "name": "Example name"
  };

axios.put("https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-
e29b-41d4-a716-446655440000/labels/550e8400-e29b-41d4-a716-
446655440000/", data, config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-e29b-
41d4-a716-446655440000/labels/550e8400-e29b-41d4-a716-446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# Request body (payload)
data = {
    "name": "Example name"
}

response = requests.put(url, json=data, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>put("https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-e29b-
41d4-a716-446655440000/labels/550e8400-e29b-41d4-a716-
446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'name' => 'Example name'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response body

Status code: 200

Example response schema

```
{
  "id": string (uuid)
  "name"?: string // Optional
}
```

Example response values

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "name": "Response string"
}
```

Partially update a label

`PATCH` `/api/v1/knowledge-bases/{knowledgeBasePk}/labels/{id}`

Parameters

Parameter name	Required	Type	Description
`id`	V	string	A UUID string identifying this knowledge base label.
`knowledgeBasePk`	V	string	

Request body

Request parameters

Field	Type	Required	Description
name	string	No	

Example request schema

```
{
  "name"?: string // Optional
}
```

Example request values

```
{
  "name": "Example name"
}
```

Code examples

Shell/Bash

```
# Example API call (Shell)
curl -X PATCH "https://api.maiagent.ai/api/v1/knowledge-
bases/550e8400-e29b-41d4-a716-446655440000/labels/550e8400-e29b-
41d4-a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "name": "Example name"
  }'

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// Request body (payload)
const data = {
    "name": "Example name"
  };

axios.patch("https://api.maiagent.ai/api/v1/knowledge-
bases/550e8400-e29b-41d4-a716-446655440000/labels/550e8400-e29b-
41d4-a716-446655440000/", data, config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-e29b-
41d4-a716-446655440000/labels/550e8400-e29b-41d4-a716-446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# Request body (payload)
data = {
    "name": "Example name"
}

response = requests.patch(url, json=data, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>patch("https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-
e29b-41d4-a716-446655440000/labels/550e8400-e29b-41d4-a716-
446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'name' => 'Example name'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response body

Status code: 200

Example response schema

```
{
  "id": string (uuid)
  "name"?: string // Optional
}
```

Example response values

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "name": "Response string"
}
```

Delete a label

DELETE `/api/v1/knowledge-bases/{knowledgeBasePk}/labels/{id}`

Parameters

Parameter name	Required	Type	Description
`id`	V	string	A UUID string identifying this knowledge base label.
`knowledgeBasePk`	V	string	

Code examples

Shell/Bash

```
# Example API call (Shell)
curl -X DELETE "https://api.maiagent.ai/api/v1/knowledge-
bases/550e8400-e29b-41d4-a716-446655440000/labels/550e8400-e29b-
41d4-a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

// Request body (payload)
const data = null;

axios.delete("https://api.maiagent.ai/api/v1/knowledge-
bases/550e8400-e29b-41d4-a716-446655440000/labels/550e8400-e29b-
41d4-a716-446655440000/", data, config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-e29b-41d4-a716-446655440000/labels/550e8400-e29b-41d4-a716-446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.delete(url, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>delete("https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-
e29b-41d4-a716-446655440000/labels/550e8400-e29b-41d4-a716-
446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response body

Status code	Description
204	No response body

Create a metadata field

POST `/api/v1/knowledge-bases/{knowledgeBasePk}/metadata-keys/`

Parameters

Parameter name	Required	Type	Description
knowledgeBasePk	V	string	

Request body

Request parameters

Field	Type	Required	Description
keyName	string	Yes	Metadata key name
description	string	No	Description of the purpose of this field
isRequired	boolean	No	Whether this field is required
defaultValue	string	No	Default value for new files
enabledForSearch	boolean	No	Whether to use this field during retrieval

Example request schema

```
{
  "keyName": string // Metadata key name
  "description"?: string // Description of the purpose of this field
(Optional)
  "isRequired"?: boolean // Whether this field is required (Optional)
  "defaultValue"?: string // Default value for new files (Optional)
  "enabledForSearch"?: boolean // Whether to use this field during
```

```
retrieval (Optional)
}
```

Example request values

```
{
  "keyName": "Example string",
  "description": "Example string",
  "isRequired": true,
  "defaultValue": "Example string",
  "enabledForSearch": true
}
```

Code examples

Shell/Bash

```
# Example API call (Shell)
curl -X POST "https://api.maiagent.ai/api/v1/knowledge-
bases/550e8400-e29b-41d4-a716-446655440000/metadata-keys/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "keyName": "Example string",
    "description": "Example string",
    "isRequired": true,
    "defaultValue": "Example string",
    "enabledForSearch": true
  }'

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// Request body (payload)
const data = {
    "keyName": "Example string",
    "description": "Example string",
    "isRequired": true,
    "defaultValue": "Example string",
    "enabledForSearch": true
  };

axios.post("https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-e29b-41d4-a716-446655440000/metadata-keys/", data, config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-e29b-
41d4-a716-446655440000/metadata-keys/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# Request Body (payload)
data = {
    "keyName": "Example string",
    "description": "Example string",
    "isRequired": True,
    "defaultValue": "Example string",
    "enabledForSearch": True
}

response = requests.post(url, json=data, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>post("https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-e29b-
41d4-a716-446655440000/metadata-keys/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'keyName' => 'Example string',
            'description' => 'Example string',
            'isRequired' => true,
            'defaultValue' => 'Example string',
            'enabledForSearch' => true
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response Body

Status Code: 201

Example Response Schema

```
{
  "id": string (uuid)
  "knowledgeBase":
  {
    "id": string (uuid)
    "name": string
  }
  "keyName": string // Metadata key name
  "keyType": string // Automatically determined from the field name
(default or custom field)
  "description"?: string // Describes the purpose of this field
(Optional)
  "isRequired"?: boolean // Whether this field is required (Optional)
  "defaultValue"?: string // Default value for new files (Optional)
  "enabledForSearch"?: boolean // Whether to use this field during
retrieval (Optional)
  "createdAt": string (timestamp)
  "updatedAt": string (timestamp)
}
```

Example Response Values

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "knowledgeBase": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Response string"
  },
  "keyName": "Response string",
  "keyType": "Response string",
  "description": "Response string",
  "isRequired": false,
  "defaultValue": "Response string",
  "enabledForSearch": false,
  "createdAt": "Response string",
  "updatedAt": "Response string"
}
```

List Metadata Fields

GET `/api/v1/knowledge-bases/{knowledgeBasePk}/metadata-keys/`

Parameters

Parameter Name	Required	Type	Description
`knowledgeBasePk`	V	string	
`page`	X	integer	A page number within the paginated result set.
`pageSize`	X	integer	Number of results to return per page.
`pagination`	X	boolean	Set to false to return all keys without pagination (defaults to true).

Code Examples

Shell/Bash

```
# API call example (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/knowledge-
bases/550e8400-e29b-41d4-a716-446655440000/metadata-keys/?
page=1&pageSize=1&pagination=true"

  -H "Authorization: Api-Key YOUR_API_KEY"

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-
e29b-41d4-a716-446655440000/metadata-keys/?
page=1&pageSize=1&pagination=true", config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-e29b-41d4-a716-446655440000/metadata-keys/?page=1&pageSize=1&pagination=true"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-e29b-
41d4-a716-446655440000/metadata-keys/?
page=1&pageSize=1&pagination=true", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response Body

Status Code: 200

Example Response Schema

```
{
  "count": integer
```

```
  "next"?: string (uri) // Optional
  "previous"?: string (uri) // Optional
  "results": [
    {
      "id": string (uuid)
      "knowledgeBase":
      {
        "id": string (uuid)
        "name": string
      }
      "keyName": string // Metadata key name
      "keyType": string // Automatically determined from the field name
(default or custom field)
      "description"?: string // Describes the purpose of this field
(Optional)
      "isRequired"?: boolean // Whether this field is required (Optional)
      "defaultValue"?: string // Default value for new files (Optional)
      "enabledForSearch"?: boolean // Whether to use this field during
retrieval (Optional)
      "createdAt": string (timestamp)
      "updatedAt": string (timestamp)
    }
  ]
}
```

Example Response Values

```
{
  "count": 123,
  "next": "http://api.example.org/accounts/?page=4",
  "previous": "http://api.example.org/accounts/?page=2",
  "results": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "knowledgeBase": {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "name": "Response string"
      },
      "keyName": "Response string",
      "keyType": "Response string",
      "description": "Response string",
      "isRequired": false,
      "defaultValue": "Response string",
      "enabledForSearch": false,
```

```
      "createdAt": "Response string",
      "updatedAt": "Response string"
    }
  ]
}
```

Retrieve a Specific Metadata Field

GET `/api/v1/knowledge-bases/{knowledgeBasePk}/metadata-keys/{id}`

Parameters

Parameter Name	Required	Type	Description
`id`	V	string	A UUID string identifying this Metadata Key.
`knowledgeBasePk`	V	string	

Code Examples

Shell/Bash

```
# API call example (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/knowledge-
bases/550e8400-e29b-41d4-a716-446655440000/metadata-keys/550e8400-
e29b-41d4-a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-e29b-41d4-a716-446655440000/metadata-keys/550e8400-e29b-41d4-a716-446655440000/", config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-e29b-41d4-a716-446655440000/metadata-keys/550e8400-e29b-41d4-a716-446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-e29b-
41d4-a716-446655440000/metadata-keys/550e8400-e29b-41d4-a716-
446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response Body

Status Code: 200

Example Response Schema

```
{
  "id": string (uuid)
```

```
  "knowledgeBase":
  {
    "id": string (uuid)
    "name": string
  }
  "keyName": string // Metadata key name
  "keyType": string // Automatically determined from the field name
(default or custom field)
  "description"?: string // Describes the purpose of this field
(Optional)
  "isRequired"?: boolean // Whether this field is required (Optional)
  "defaultValue"?: string // Default value for new files (Optional)
  "enabledForSearch"?: boolean // Whether to use this field during
retrieval (Optional)
  "createdAt": string (timestamp)
  "updatedAt": string (timestamp)
}
```

Example Response Values

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "knowledgeBase": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Response string"
  },
  "keyName": "Response string",
  "keyType": "Response string",
  "description": "Response string",
  "isRequired": false,
  "defaultValue": "Response string",
  "enabledForSearch": false,
  "createdAt": "Response string",
  "updatedAt": "Response string"
}
```

Update a Metadata Field

PUT `/api/v1/knowledge-bases/{knowledgeBasePk}/metadata-keys/{id}`

Parameters

Parameter Name	Required	Type	Description
`id`	V	string	A UUID string identifying this Metadata Key.
`knowledgeBasePk`	V	string	

Request Body

Request Parameters

Field	Type	Required	Description
keyName	string	Yes	Metadata key name
description	string	No	Describes the purpose of this field
isRequired	boolean	No	Whether this field is required
defaultValue	string	No	Default value for new files
enabledForSearch	boolean	No	Whether to use this field during retrieval

Example Request Schema

```
{
  "keyName": string // Metadata key name
  "description"?: string // Describes the purpose of this field
(Optional)
  "isRequired"?: boolean // Whether this field is required (Optional)
  "defaultValue"?: string // Default value for new files (Optional)
  "enabledForSearch"?: boolean // Whether to use this field during
```

```
retrieval (Optional)
}
```

Example Request Values

```
{
  "keyName": "Example string",
  "description": "Example string",
  "isRequired": true,
  "defaultValue": "Example string",
  "enabledForSearch": true
}
```

Code Examples

Shell/Bash

```
# API call example (Shell)
curl -X PUT "https://api.maiagent.ai/api/v1/knowledge-
bases/550e8400-e29b-41d4-a716-446655440000/metadata-keys/550e8400-
e29b-41d4-a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "keyName": "Example string",
    "description": "Example string",
    "isRequired": true,
    "defaultValue": "Example string",
    "enabledForSearch": true
  }'

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// Request Body (payload)
const data = {
    "keyName": "Example string",
    "description": "Example string",
    "isRequired": true,
    "defaultValue": "Example string",
    "enabledForSearch": true
  };

axios.put("https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-
e29b-41d4-a716-446655440000/metadata-keys/550e8400-e29b-41d4-a716-
446655440000/", data, config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-e29b-
41d4-a716-446655440000/metadata-keys/550e8400-e29b-41d4-a716-
446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# Request Body (payload)
data = {
    "keyName": "Example string",
    "description": "Example string",
    "isRequired": True,
    "defaultValue": "Example string",
    "enabledForSearch": True
}

response = requests.put(url, json=data, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>put("https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-e29b-
41d4-a716-446655440000/metadata-keys/550e8400-e29b-41d4-a716-
446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'keyName' => 'Example string',
            'description' => 'Example string',
            'isRequired' => true,
            'defaultValue' => 'Example string',
            'enabledForSearch' => true
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response Body

Status Code: 200

Example Response Schema

```
{
  "id": string (uuid)
  "knowledgeBase":
  {
    "id": string (uuid)
    "name": string
  }
  "keyName": string // Metadata key name
  "keyType": string // Automatically determined from the field name
(default or custom field)
  "description"?: string // Describes the purpose of this field
(Optional)
  "isRequired"?: boolean // Whether this field is required (Optional)
  "defaultValue"?: string // Default value for new files (Optional)
  "enabledForSearch"?: boolean // Whether to use this field during
retrieval (Optional)
  "createdAt": string (timestamp)
  "updatedAt": string (timestamp)
}
```

Example Response Values

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "knowledgeBase": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Response string"
  },
  "keyName": "Response string",
  "keyType": "Response string",
  "description": "Response string",
  "isRequired": false,
  "defaultValue": "Response string",
  "enabledForSearch": false,
  "createdAt": "Response string",
  "updatedAt": "Response string"
}
```

Upload Files to a Knowledge Base

POST `/api/v1/knowledge-bases/{knowledgeBasePk}/files/`

Parameters

Parameter Name	Required	Type	Description
`knowledgeBasePk`	V	string	
`fileType`	X	string	Filter by file type, such as pdf, docx, txt, xlsx, etc.
`knowledgeBase`	X	string	Knowledge base ID
`page`	X	integer	A page number within the paginated result set.
`pageSize`	X	integer	Number of results to return per page.
`query`	X	string	Search keywords; supports multiple space-separated criteria. Searchable fields: file ID, filename, label name, Metadata value
`status`	X	string	Filter by file status. Available values: initial (initial), processing (processing), done (done), deleting (deleting), deleted (deleted), failed (failed) `initial`: Initial ; `processing`: Processing ; `done`: Done ; `deleting`: Deleting ; `deleted`: Deleted ; `faile...

Request Body

Request Parameters

Field	Type	Required	Description
files	array[KnowledgeBaseFileCreate]	Yes	Supports uploading multiple files in one batch.

Example Request Schema

```
{
  "files": [ // Supports uploading multiple files in one batch.
    {
      "filename": string // Filename
      "file": string (uri) // File to upload
      "parser"?: string (uuid) // Optional
      "labels"?: [ // Optional
        {
          "id": string (uuid)
        }
      ]
      "rawUserDefineMetadata"?: object // Optional
      "asrOptions"?: object // Per-file canonical transcription options
(languages, prompt, diarization). Empty means no per-file options:
provider defaults apply. Completely decoupled from user-defined metadata;
never indexed for search. (Optional)
    }
  ]
}
```

Example Request Values

```
{
  "files": [
    {
      "filename": "my-file.pdf",
      "file": "string",
      "parser": "3fa85f64-5717-4562-b3fc-2c963f66afa6",
      "labels": [
        {
          "id": "3fa85f64-5717-4562-b3fc-2c963f66afa6",
          "name": "my-label"
        }
      ],
      "rawUserDefineMetadata": {
        "key1": "value1",
```

```
        "key2": "value2"
      }
    },
    {
      "filename": "you-can-upload-multiple-files.pdf",
      "file": "string",
      "parser": "3fa85f64-5717-4562-b3fc-2c963f66afa6"
    }
  ]
}
```

Code Examples

Shell/Bash

```
# API call example (Shell)
curl -X POST "https://api.maiagent.ai/api/v1/knowledge-
bases/550e8400-e29b-41d4-a716-446655440000/files/?
fileType=example&knowledgeBase=550e8400-e29b-41d4-a716-
446655440000&page=1&pageSize=1&query=example&status=delete_failed"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "files": [
      {
        "filename": "my-file.pdf",
        "file": "string",
        "parser": "3fa85f64-5717-4562-b3fc-2c963f66afa6",
        "labels": [
          {
            "id": "3fa85f64-5717-4562-b3fc-2c963f66afa6",
            "name": "my-label"
          }
        ],
        "rawUserDefineMetadata": {
          "key1": "value1",
          "key2": "value2"
        }
      },
      {
        "filename": "you-can-upload-multiple-files.pdf",
        "file": "string",
        "parser": "3fa85f64-5717-4562-b3fc-2c963f66afa6"
      }
    ]
  }'

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// Request Body (payload)
const data = {
    "files": [
      {
        "filename": "my-file.pdf",
        "file": "string",
        "parser": "3fa85f64-5717-4562-b3fc-2c963f66afa6",
        "labels": [
          {
            "id": "3fa85f64-5717-4562-b3fc-2c963f66afa6",
            "name": "my-label"
          }
        ],
        "rawUserDefineMetadata": {
          "key1": "value1",
          "key2": "value2"
        }
      },
      {
        "filename": "you-can-upload-multiple-files.pdf",
        "file": "string",
        "parser": "3fa85f64-5717-4562-b3fc-2c963f66afa6"
      }
    ]
  };

axios.post("https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-
e29b-41d4-a716-446655440000/files/?
fileType=example&knowledgeBase=550e8400-e29b-41d4-a716-
446655440000&page=1&pageSize=1&query=example&status=delete_failed",
```

```
  data, config)
    .then(response => {
      console.log('Response received successfully:');
      console.log(response.data);
    })
    .catch(error => {
      console.error('Request error:');
      console.error(error.response?.data || error.message);
    });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-e29b-
41d4-a716-446655440000/files/?
fileType=example&knowledgeBase=550e8400-e29b-41d4-a716-
446655440000&page=1&pageSize=1&query=example&status=delete_failed"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# Request Body (payload)
data = {
    "files": [
        {
            "filename": "my-file.pdf",
            "file": "string",
            "parser": "3fa85f64-5717-4562-b3fc-2c963f66afa6",
            "labels": [
                {
                    "id": "3fa85f64-5717-4562-b3fc-2c963f66afa6",
                    "name": "my-label"
                }
            ],
            "rawUserDefineMetadata": {
                "key1": "value1",
                "key2": "value2"
            }
        },
        {
            "filename": "you-can-upload-multiple-files.pdf",
            "file": "string",
            "parser": "3fa85f64-5717-4562-b3fc-2c963f66afa6"
        }
    ]
}

response = requests.post(url, json=data, headers=headers)
try:
    print("Response received successfully:")
```

```
        print(response.json())
    except Exception as e:
        print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>post("https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-e29b-
41d4-a716-446655440000/files/?
fileType=example&knowledgeBase=550e8400-e29b-41d4-a716-
446655440000&page=1&pageSize=1&query=example&status=delete_failed",
[
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'files' => [
                [
                    'filename' => 'my-file.pdf',
                    'file' => 'string',
                    'parser' => '3fa85f64-5717-4562-b3fc-
2c963f66afa6',
                    'labels' => [
                        [
                            'id' => '3fa85f64-5717-4562-b3fc-
2c963f66afa6',
                            'name' => 'my-label'
                        ]
                    ],
                    'rawUserDefineMetadata' => [
                        'key1' => 'value1',
                        'key2' => 'value2'
                    ]
                ],
                [
                    'filename' => 'you-can-upload-multiple-
files.pdf',
                    'file' => 'string',
                    'parser' => '3fa85f64-5717-4562-b3fc-
```

```
    2c963f66afa6'
                    ]
                ]
            ]
        ]);

        $data = json_decode($response->getBody(), true);
        echo "Response received successfully:\n";
        print_r($data);
    } catch (Exception $e) {
        echo 'Request error: ' . $e->getMessage();
    }
    ?>
```

Response Body

Status Code: 201

Example Response Schema

```
{
  "count": integer
  "next"?: string (uri) // Optional
  "previous"?: string (uri) // Optional
  "results": [
    {
      "id": string (uuid)
      "filename": string // Filename
      "file": string (uri) // File to upload
      "fileType": string
      "knowledgeBase"?:  // Optional
      {
        "id": string (uuid)
        "name": string
      }
      "size": integer // File size in bytes
      "status":
```

```
      {
      }
      "parser":
      {
        "id": string (uuid)
        "name": string
        "provider":
        {
        }
        "isTimestampSttProvider": boolean
      }
      "labels"?: [ // Optional
        {
          "id": string (uuid)
          "name": string
        }
      ]
      "rawUserDefineMetadata"?: object // Optional
      "speakerLabels": [
        {
          "id": string (uuid)
          "originalLabel": string // Original speaker label from
diarization (e.g., SPEAKER_00)
          "customName"?: string // User-defined speaker name (e.g., John)
(Optional)
          "displayName": string
        }
      ]
      "vectorStorageSize": integer // Size of vectors for this file in
Elasticsearch (bytes)
      "chunksCount": integer // Number of chunks/nodes generated from
this file
      "waitingTime": number (double)
      "processingTime": number (double)
      "processingTimeDetails": object
      "ocrStatus": string // OCR result for scanned pages: done, skipped,
partial, off; null before parsing or for older files
      "ocrSkippedReason": string // Reason OCR was not performed on
scanned pages: no_azure_settings, azure_unavailable,
insufficient_credits, transient_error, time_budget, disabled; null when
completed
      "parserAutoDetection":  // Result and reason for automatic parser
selection for this file; null for files with a user-selected parser,
files uploaded before launch, or files queued for reassessment
      {
```

```
        "parser":  // Parser selected by automatic detection
        {
          "id": string (uuid)
          "name": string
          "provider":
          {
          }
          "isTimestampSttProvider": boolean
        }
        "reason": string // Reason category: scanned, image_pages,
large_images, unmeasurable_images, presentation, no_image_content,
below_threshold, no_content, file_type_not_detected, detection_failed,
vision_unavailable; more categories may be added later. Display a generic
message when no matching text is available
        "facts": object // Numeric facts supporting the reason
(calculated at detection time and not recalculated later). PDF:
analyzed_pages (number of pages examined), partial (whether only the
first few pages were examined), non_blank_pages, scanned_pages,
image_pages (pages requiring image-based interpretation); Word: figures
(number of large images in the body), text_chars (number of characters in
the body); an empty object in other cases
        "detectedAt": string (timestamp) // Detection time
      }
      "previewUrl": string // For presentations (pptx/ppt), returns the
URL of a previewable derived pdf file (displayed using the PDF viewer in
the frontend); None for other files.

Generate URLs with the same CustomizedFileFieldSerializer as the `file`
field to ensure consistent formatting (including each
storage provider's presign/host rules). Do not use get_absolute_url()
because it produces incorrectly formatted URLs.
      "createdAt": string (timestamp)
    }
  ]
}
```

Example Response Values

```
{
  "count": 123,
  "next": "http://api.example.org/accounts/?page=4",
  "previous": "http://api.example.org/accounts/?page=2",
  "results": [
    {
```

```
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "filename": "Response string",
  "file": "https://example.com/file.jpg",
  "fileType": "Response string",
  "knowledgeBase": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Response string"
  },
  "size": 456,
  "status": {},
  "parser": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Response string",
    "provider": {},
    "isTimestampSttProvider": false
  },
  "labels": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "Response string"
    }
  ],
  "rawUserDefineMetadata": null,
  "speakerLabels": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "originalLabel": "Response string",
      "customName": "Response string",
      "displayName": "Response string"
    }
  ],
  "vectorStorageSize": 456,
  "chunksCount": 456,
  "waitingTime": 456,
  "processingTime": 456,
  "processingTimeDetails": null,
  "ocrStatus": "Response string",
  "ocrSkippedReason": "Response string",
  "parserAutoDetection": {
    "parser": {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "Response string",
      "provider": {},
      "isTimestampSttProvider": false
    },
```

```
        "reason": "Response string",
        "facts": {
          "id": "550e8400-e29b-41d4-a716-446655440000",
          "name": "Example response name",
          "description": "Example response description"
        },
        "detectedAt": "Response string"
      },
      "previewUrl": "Response string",
      "createdAt": "Response string"
    }
  ]
}
```


Update File Metadata

PATCH `/api/v1/knowledge-bases/{knowledgeBasePk}/files/{id}/update-metadata/`

Parameters

Parameter Name	Required	Type	Description
`id`	V	string	A UUID string identifying this Knowledge Base File.
`knowledgeBasePk`	V	string	

Request Body

Request Parameters

Field	Type	Required	Description
labels	array[IdName]	No	
rawUserDefineMetadata	object	No	

Example Request Schema

```
{
  "labels"?: [ // Optional
    {
      "id": string (uuid)
    }
  ]
  "rawUserDefineMetadata"?: object // Optional
}
```

Example Request Values

```
{
  "labels": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000"
    }
  ],
  "rawUserDefineMetadata": null
}
```

Code Examples

Shell/Bash

```
# API call example (Shell)
curl -X PATCH "https://api.maiagent.ai/api/v1/knowledge-
bases/550e8400-e29b-41d4-a716-446655440000/files/550e8400-e29b-41d4-
a716-446655440000/update-metadata/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "labels": [
      {
        "id": "550e8400-e29b-41d4-a716-446655440000"
      }
    ],
    "rawUserDefineMetadata": null
  }'

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// Request Body (payload)
const data = {
    "labels": [
      {
        "id": "550e8400-e29b-41d4-a716-446655440000"
      }
    ],
    "rawUserDefineMetadata": null
  };

axios.patch("https://api.maiagent.ai/api/v1/knowledge-
bases/550e8400-e29b-41d4-a716-446655440000/files/550e8400-e29b-41d4-
a716-446655440000/update-metadata/", data, config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-e29b-
41d4-a716-446655440000/files/550e8400-e29b-41d4-a716-
446655440000/update-metadata/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# Request Body (payload)
data = {
    "labels": [
        {
            "id": "550e8400-e29b-41d4-a716-446655440000"
        }
    ],
    "rawUserDefineMetadata": None
}

response = requests.patch(url, json=data, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>patch("https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-
e29b-41d4-a716-446655440000/files/550e8400-e29b-41d4-a716-
446655440000/update-metadata/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'labels' => [
                [
                    'id' => '550e8400-e29b-41d4-a716-446655440000'
                ]
            ],
            'rawUserDefineMetadata' => null
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response Body

Status Code: 200

Example Response Schema

```
{
  "id": string (uuid)
  "filename": string // Filename
  "file": string (uri) // File to upload
  "fileType": string
  "knowledgeBase"?:  // Optional
  {
    "id": string (uuid)
    "name": string
  }
  "size": integer // File size in bytes
  "status":
  {
  }
  "parser":
  {
    "id": string (uuid)
    "name": string
    "provider":
    {
    }
    "isTimestampSttProvider": boolean
  }
  "labels"?: [ // Optional
    {
      "id": string (uuid)
      "name": string
    }
  ]
  "rawUserDefineMetadata"?: object // Optional
  "speakerLabels": [
    {
      "id": string (uuid)
      "originalLabel": string // Original speaker label from diarization
(e.g., SPEAKER_00)
      "customName"?: string // User-defined speaker name (e.g., John)
```

```
(Optional)
      "displayName": string
    }
  ]
  "vectorStorageSize": integer // Size of vectors for this file in
Elasticsearch (bytes)
  "chunksCount": integer // Number of chunks/nodes generated from this
file
  "waitingTime": number (double)
  "processingTime": number (double)
  "processingTimeDetails": object
  "ocrStatus": string // OCR result for scanned pages: done, skipped,
partial, off; null before parsing or for older files
  "ocrSkippedReason": string // Reason OCR was not performed on scanned
pages: no_azure_settings, azure_unavailable, insufficient_credits,
transient_error, time_budget, disabled; null when completed
  "parserAutoDetection":  // Result and reason for automatic parser
selection for this file; null for files with a user-selected parser,
files uploaded before launch, or files queued for reassessment
  {
    "parser":  // Parser selected by automatic detection
    {
      "id": string (uuid)
      "name": string
      "provider":
      {
      }
      "isTimestampSttProvider": boolean
    }
    "reason": string // Reason category: scanned, image_pages,
large_images, unmeasurable_images, presentation, no_image_content,
below_threshold, no_content, file_type_not_detected, detection_failed,
vision_unavailable; more categories may be added later. Display a generic
message when no matching text is available
    "facts": object // Numeric facts supporting the reason (calculated at
detection time and not recalculated later). PDF: analyzed_pages (number
of pages examined), partial (whether only the first few pages were
examined), non_blank_pages, scanned_pages, image_pages (pages requiring
image-based interpretation); Word: figures (number of large images in the
body), text_chars (number of characters in the body); an empty object in
other cases
    "detectedAt": string (timestamp) // Detection time
  }
  "previewUrl": string // For presentations (pptx/ppt), returns the URL
of a previewable derived pdf file (displayed using the PDF viewer in the
```

```
frontend); None for other files.

Generate URLs with the same CustomizedFileFieldSerializer as the `file`
field to ensure consistent formatting (including each
storage provider's presign/host rules). Do not use get_absolute_url()
because it produces incorrectly formatted URLs.
  "createdAt": string (timestamp)
}
```

Example Response Values

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "filename": "Response string",
  "file": "https://example.com/file.jpg",
  "fileType": "Response string",
  "knowledgeBase": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Response string"
  },
  "size": 456,
  "status": {},
  "parser": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Response string",
    "provider": {},
    "isTimestampSttProvider": false
  },
  "labels": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "Response string"
    }
  ],
  "rawUserDefineMetadata": null,
  "speakerLabels": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "originalLabel": "Response string",
      "customName": "Response string",
      "displayName": "Response string"
    }
  ],
  "vectorStorageSize": 456,
```

```
  "chunksCount": 456,
  "waitingTime": 456,
  "processingTime": 456,
  "processingTimeDetails": null,
  "ocrStatus": "Response string",
  "ocrSkippedReason": "Response string",
  "parserAutoDetection": {
    "parser": {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "Response string",
      "provider": {},
      "isTimestampSttProvider": false
    },
    "reason": "Response string",
    "facts": {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "Example response name",
      "description": "Example response description"
    },
    "detectedAt": "Response string"
  },
  "previewUrl": "Response string",
  "createdAt": "Response string"
}
```


Batch Delete Files

POST `/api/v1/knowledge-bases/{knowledgeBasePk}/files/batch-delete/`

Parameters

Parameter Name	Required	Type	Description
knowledgeBasePk	V	string	

Request Body

Request Parameters

Field	Type	Required	Description
ids	array[string]	Yes	

Request Schema Example

```
{
  "ids": [
    string (uuid)
  ]
}
```

Example Request Values

```
{
  "ids": [
    "550e8400-e29b-41d4-a716-446655440000"
  ]
}
```

Code Examples

Shell/Bash

```
# API call example (Shell)
curl -X POST "https://api.maiagent.ai/api/v1/knowledge-
bases/550e8400-e29b-41d4-a716-446655440000/files/batch-delete/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "ids": [
      "550e8400-e29b-41d4-a716-446655440000"
    ]
  }'

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// Request Body (payload)
const data = {
    "ids": [
      "550e8400-e29b-41d4-a716-446655440000"
    ]
  };

axios.post("https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-
e29b-41d4-a716-446655440000/files/batch-delete/", data, config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-e29b-
41d4-a716-446655440000/files/batch-delete/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# Request Body (payload)
data = {
    "ids": [
        "550e8400-e29b-41d4-a716-446655440000"
    ]
}

response = requests.post(url, json=data, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>post("https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-e29b-
41d4-a716-446655440000/files/batch-delete/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'ids' => [
                '550e8400-e29b-41d4-a716-446655440000'
            ]
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response Body

Status Code: 200

Response Schema Example

```
{
  "queued": [
    string (uuid)
  ]
  "skipped": [
    {
      "id": string (uuid)
      "reason": string (enum: deleting) // * `deleting` - deleting
    }
  ]
}
```

Example Response Values

```
{
  "queued": [
    "550e8400-e29b-41d4-a716-446655440000"
  ],
  "skipped": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "reason": "deleting"
    }
  ]
}
```

Reparse Files in Bulk

PATCH `/api/v1/knowledge-bases/{knowledgeBasePk}/files/batch-reparse/`

Parameters

Parameter Name	Required	Type	Description
`knowledgeBasePk`	V	string	
`fileType`	X	string	Filter by file type, such as pdf, docx, txt, xlsx, etc.
`knowledgeBase`	X	string	Knowledge base ID
`query`	X	string	Search keywords. Supports multiple search terms separated by spaces. Searchable fields: file ID, filename, label name, and metadata value
`status`	X	string	Filter by file status. Available values: initial (initialized), processing (processing), done (completed), deleting (being deleted), deleted (deleted), failed (failed) `initial`: Initial ; `processing`: Processing ; `done`: Done ; `deleting`: Deleting ; `deleted`: Deleted ; `faile...

Code Examples

Shell/Bash

```
# API call example (Shell)
curl -X PATCH "https://api.maiagent.ai/api/v1/knowledge-
bases/550e8400-e29b-41d4-a716-446655440000/files/batch-reparse/?
fileType=example&knowledgeBase=550e8400-e29b-41d4-a716-
446655440000&query=example&status=delete_failed"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '[]'

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// Request body (payload)
const data = [];

axios.patch("https://api.maiagent.ai/api/v1/knowledge-
bases/550e8400-e29b-41d4-a716-446655440000/files/batch-reparse/?
fileType=example&knowledgeBase=550e8400-e29b-41d4-a716-
446655440000&query=example&status=delete_failed", data, config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request failed:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-e29b-
41d4-a716-446655440000/files/batch-reparse/?
fileType=example&knowledgeBase=550e8400-e29b-41d4-a716-
446655440000&query=example&status=delete_failed"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# Request body (payload)
data = []

response = requests.patch(url, json=data, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request failed:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>patch("https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-
e29b-41d4-a716-446655440000/files/batch-reparse/?
fileType=example&knowledgeBase=550e8400-e29b-41d4-a716-
446655440000&query=example&status=delete_failed", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => []
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request failed: ' . $e->getMessage();
}
?>
```

Response Body

Status Code: 200

Example Response Schema

```
[
  {
    "id": string (uuid)
    "filename": string // Filename
    "file": string (uri) // File to upload
    "fileType": string
    "knowledgeBase"?:  // Optional
    {
      "id": string (uuid)
      "name": string
    }
    "size": integer // File size in bytes
    "status":
    {
    }
    "parser":
    {
      "id": string (uuid)
      "name": string
      "provider":
      {
      }
      "isTimestampSttProvider": boolean
    }
    "labels"?: [ // Optional
      {
        "id": string (uuid)
        "name": string
      }
    ]
    "rawUserDefineMetadata"?: object // Optional
    "speakerLabels": [
      {
        "id": string (uuid)
        "originalLabel": string // Original speaker label from
diarization (e.g., SPEAKER_00)
        "customName"?: string // User-defined speaker name (e.g., John)
(Optional)
        "displayName": string
      }
    ]
    "vectorStorageSize": integer // Size of vectors for this file in
Elasticsearch (bytes)
    "chunksCount": integer // Number of chunks/nodes generated from this
```

```
file
    "waitingTime": number (double)
    "processingTime": number (double)
    "processingTimeDetails": object
    "ocrStatus": string // OCR result for scanned pages: done, skipped,
partial, or off; null before parsing or for older files
    "ocrSkippedReason": string // Reason OCR was not performed on scanned
pages: no_azure_settings, azure_unavailable, insufficient_credits,
transient_error, time_budget, or disabled; null when completed
    "parserAutoDetection":  // Result and reason for automatic parser
selection for this file; null for files with a manually selected parser,
files uploaded before this feature launched, or files queued for
reevaluation
    {
      "parser":  // Parser selected by automatic detection
      {
        "id": string (uuid)
        "name": string
        "provider":
        {
        }
        "isTimestampSttProvider": boolean
      }
      "reason": string // Reason category: scanned, image_pages,
large_images, unmeasurable_images, presentation, no_image_content,
below_threshold, no_content, file_type_not_detected, detection_failed, or
vision_unavailable; new categories may be added later. Display a generic
message if no matching text is available
      "facts": object // Numeric facts behind the reason (calculated at
detection time and not recalculated later). PDF: analyzed_pages (number
of pages examined), partial (whether only the first few pages were
examined), non_blank_pages, scanned_pages, image_pages (pages requiring
image-based interpretation); Word: figures (number of large images in the
body), text_chars (number of characters in the body); an empty object in
other cases
      "detectedAt": string (timestamp) // Detection time
    }
    "previewUrl": string // For presentations (pptx/ppt), returns the URL
of a derived PDF file for preview (displayed using the frontend PDF
viewer); None for other file types.

Generate the URL using the same CustomizedFileFieldSerializer as the
`file` field to ensure a consistent format (including each
storage provider's presign/host rules). Do not use get_absolute_url(); it
generates incorrectly formatted URLs.
```

```
    "createdAt": string (timestamp)
    "reparseSkippedReason": string
  }
]
```

Example Response Values

```
[
  {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "filename": "Response string",
    "file": "https://example.com/file.jpg",
    "fileType": "Response string",
    "knowledgeBase": {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "Response string"
    },
    "size": 456,
    "status": {},
    "parser": {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "Response string",
      "provider": {},
      "isTimestampSttProvider": false
    },
    "labels": [
      {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "name": "Response string"
      }
    ],
    "rawUserDefineMetadata": null,
    "speakerLabels": [
      {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "originalLabel": "Response string",
        "customName": "Response string",
        "displayName": "Response string"
      }
    ],
    "vectorStorageSize": 456,
    "chunksCount": 456,
    "waitingTime": 456,
    "processingTime": 456,
```

```
    "processingTimeDetails": null,
    "ocrStatus": "Response string",
    "ocrSkippedReason": "Response string",
    "parserAutoDetection": {
      "parser": {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "name": "Response string",
        "provider": {},
        "isTimestampSttProvider": false
      },
      "reason": "Response string",
      "facts": {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "name": "Example response name",
        "description": "Example response description"
      },
      "detectedAt": "Response string"
    },
    "previewUrl": "Response string",
    "createdAt": "Response string",
    "reparseSkippedReason": "Response string"
  }
]
```


List Files in a Knowledge Base

`GET` `/api/v1/knowledge-bases/{knowledgeBasePk}/files/`

For files whose parser is automatically detected by the system, parserAutoDetection in the response contains the selected parser, the reason category (reason), the numeric facts used for detection (facts), and the detection time. It is null for files whose parser was selected by the user. For field definitions, when the value is null, and how reason categories map to numeric facts, see Parser Auto-Detection Results.

Parameters

Parameter Name	Required	Type	Description
`knowledgeBasePk`	V	string	
`fileType`	X	string	Filter by file type, such as pdf, docx, txt, or xlsx
`knowledgeBase`	X	string	Knowledge Base ID
`page`	X	integer	A page number within the paginated result set.
`pageSize`	X	integer	Number of results to return per page.
`query`	X	string	Search keywords. Supports multiple conditions separated by spaces. Searchable fields: file ID, filename, label name, Metadata value
`status`	X	string	Filter by file status. Available values: initial (initializing), processing (processing), done (completed), deleting (deleting), deleted (deleted), failed (failed) `initial`: Initial ; `processing`: Processing ; `done`: Done ; `deleting`: Deleting ; `deleted`: Deleted ; `faile...

Code Examples

Shell/Bash

```
# API Call Example (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/knowledge-
bases/550e8400-e29b-41d4-a716-446655440000/files/?
fileType=example&knowledgeBase=550e8400-e29b-41d4-a716-
446655440000&page=1&pageSize=1&query=example&status=delete_failed"

  -H "Authorization: Api-Key YOUR_API_KEY"

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-e29b-41d4-a716-446655440000/files/?fileType=example&knowledgeBase=550e8400-e29b-41d4-a716-446655440000&page=1&pageSize=1&query=example&status=delete_failed", config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-e29b-41d4-a716-446655440000/files/?fileType=example&knowledgeBase=550e8400-e29b-41d4-a716-446655440000&page=1&pageSize=1&query=example&status=delete_failed"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-e29b-
41d4-a716-446655440000/files/?
fileType=example&knowledgeBase=550e8400-e29b-41d4-a716-
446655440000&page=1&pageSize=1&query=example&status=delete_failed",
[
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response

Status Code: 200

Example Response Schema

```
{
  "count": integer
  "next"?: string (uri) // Optional
  "previous"?: string (uri) // Optional
  "results": [
    {
      "id": string (uuid)
      "filename": string // Filename
      "file": string (uri) // File to upload
      "fileType": string
      "knowledgeBase"?:  // Optional
      {
        "id": string (uuid)
        "name": string
      }
      "size": integer // File size in bytes
      "status":
      {
      }
      "parser":
      {
        "id": string (uuid)
        "name": string
        "provider":
        {
        }
        "isTimestampSttProvider": boolean
      }
      "labels"?: [ // Optional
        {
          "id": string (uuid)
          "name": string
        }
      ]
      "rawUserDefineMetadata"?: object // Optional
      "speakerLabels": [
        {
          "id": string (uuid)
          "originalLabel": string // Original speaker label from
diarization (e.g., SPEAKER_00)
          "customName"?: string // User-defined speaker name (e.g., John)
(Optional)
          "displayName": string
        }
```

```
      ]
      "vectorStorageSize": integer // Size of vectors for this file in
Elasticsearch (bytes)
      "chunksCount": integer // Number of chunks/nodes generated from
this file
      "waitingTime": number (double)
      "processingTime": number (double)
      "processingTimeDetails": object
      "ocrStatus": string // OCR result for scanned pages: done, skipped,
partial, off; null before parsing or for older files
      "ocrSkippedReason": string // Reason OCR was not performed on
scanned pages: no_azure_settings, azure_unavailable,
insufficient_credits, transient_error, time_budget, disabled; null when
OCR completes
      "parserAutoDetection":  // Result and reason for automatic parser
selection for this file; null for files with a user-selected parser,
files uploaded before the feature launched, or files queued for re-
detection
      {
        "parser":  // Parser selected by auto-detection
        {
          "id": string (uuid)
          "name": string
          "provider":
          {
          }
          "isTimestampSttProvider": boolean
        }
        "reason": string // Reason category: scanned, image_pages,
large_images, unmeasurable_images, presentation, no_image_content,
below_threshold, no_content, file_type_not_detected, detection_failed,
vision_unavailable; more categories may be added later. Display a generic
message when no matching text is available
        "facts": object // Numeric facts for the reason (calculated at
detection time and not recalculated later). PDF: analyzed_pages (number
of pages examined), partial (whether only the first few pages were
examined), non_blank_pages, scanned_pages, image_pages (pages requiring
image-based interpretation); Word: figures (number of large images in the
body), text_chars (body text character count); an empty object in other
cases
        "detectedAt": string (timestamp) // Detection time
      }
      "previewUrl": string // For presentations (pptx/ppt), returns the
URL of a previewable PDF derivative (displayed in a PDF viewer on the
frontend); None for other files.
```

```
Generate the URL with the same CustomizedFileFieldSerializer used for the
`file` field to ensure a consistent format (including each
storage provider's presign/host rules). Do not use get_absolute_url(),
which produces incorrectly formatted URLs.
      "createdAt": string (timestamp)
    }
  ]
}
```

Example Response Values

```
{
  "count": 123,
  "next": "http://api.example.org/accounts/?page=4",
  "previous": "http://api.example.org/accounts/?page=2",
  "results": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "filename": "Response string",
      "file": "https://example.com/file.jpg",
      "fileType": "Response string",
      "knowledgeBase": {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "name": "Response string"
      },
      "size": 456,
      "status": {},
      "parser": {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "name": "Response string",
        "provider": {},
        "isTimestampSttProvider": false
      },
      "labels": [
        {
          "id": "550e8400-e29b-41d4-a716-446655440000",
          "name": "Response string"
        }
      ],
      "rawUserDefineMetadata": null,
      "speakerLabels": [
        {
          "id": "550e8400-e29b-41d4-a716-446655440000",
```

```
          "originalLabel": "Response string",
          "customName": "Response string",
          "displayName": "Response string"
        }
      ],
      "vectorStorageSize": 456,
      "chunksCount": 456,
      "waitingTime": 456,
      "processingTime": 456,
      "processingTimeDetails": null,
      "ocrStatus": "Response string",
      "ocrSkippedReason": "Response string",
      "parserAutoDetection": {
        "parser": {
          "id": "550e8400-e29b-41d4-a716-446655440000",
          "name": "Response string",
          "provider": {},
          "isTimestampSttProvider": false
        },
        "reason": "Response string",
        "facts": {
          "id": "550e8400-e29b-41d4-a716-446655440000",
          "name": "Example response name",
          "description": "Example response description"
        },
        "detectedAt": "Response string"
      },
      "previewUrl": "Response string",
      "createdAt": "Response string"
    }
  ]
}
```


Get Details of a Specific File

GET `/api/v1/knowledge-bases/{knowledgeBasePk}/files/{id}`

For files whose parser is automatically detected by the system, parserAutoDetection in the response contains the selected parser, the reason category (reason), the numeric facts used for detection

(facts), and the detection time. It is null for files whose parser was selected by the user. For field definitions, when the value is null, and how reason categories map to numeric facts, see Parser Auto-Detection Results.

Parameters

Parameter Name	Required	Type	Description
`id`	V	string	A UUID string identifying this Knowledge Base File.
`knowledgeBasePk`	V	string	

Code Examples

Shell/Bash

```
# API Call Example (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/knowledge-
bases/550e8400-e29b-41d4-a716-446655440000/files/550e8400-e29b-41d4-
a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-
e29b-41d4-a716-446655440000/files/550e8400-e29b-41d4-a716-
446655440000/", config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-e29b-41d4-a716-446655440000/files/550e8400-e29b-41d4-a716-446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-e29b-
41d4-a716-446655440000/files/550e8400-e29b-41d4-a716-446655440000/",
[
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response

Status Code: 200

Example Response Schema

```
{
  "id": string (uuid)
```

```
  "filename": string // Filename
  "file": string (uri) // File to upload
  "fileType": string
  "knowledgeBase"?:  // Optional
  {
    "id": string (uuid)
    "name": string
  }
  "size": integer // File size in bytes
  "status":
  {
  }
  "parser":
  {
    "id": string (uuid)
    "name": string
    "provider":
    {
    }
    "isTimestampSttProvider": boolean
  }
  "labels"?: [ // Optional
    {
      "id": string (uuid)
      "name": string
    }
  ]
  "rawUserDefineMetadata"?: object // Optional
  "speakerLabels": [
    {
      "id": string (uuid)
      "originalLabel": string // Original speaker label from diarization
(e.g., SPEAKER_00)
      "customName"?: string // User-defined speaker name (e.g., John)
(Optional)
      "displayName": string
    }
  ]
  "vectorStorageSize": integer // Size of vectors for this file in
Elasticsearch (bytes)
  "chunksCount": integer // Number of chunks/nodes generated from this
file
  "waitingTime": number (double)
  "processingTime": number (double)
  "processingTimeDetails": object
```

```
  "ocrStatus": string // OCR result for scanned pages: done, skipped,
partial, off; null before parsing or for older files
  "ocrSkippedReason": string // Reason OCR was not performed on scanned
pages: no_azure_settings, azure_unavailable, insufficient_credits,
transient_error, time_budget, disabled; null when OCR completes
  "parserAutoDetection":  // Result and reason for automatic parser
selection for this file; null for files with a user-selected parser,
files uploaded before the feature launched, or files queued for re-
detection
  {
    "parser":  // Parser selected by auto-detection
    {
      "id": string (uuid)
      "name": string
      "provider":
      {
      }
      "isTimestampSttProvider": boolean
    }
    "reason": string // Reason category: scanned, image_pages,
large_images, unmeasurable_images, presentation, no_image_content,
below_threshold, no_content, file_type_not_detected, detection_failed,
vision_unavailable; more categories may be added later. Display a generic
message when no matching text is available
    "facts": object // Numeric facts for the reason (calculated at
detection time and not recalculated later). PDF: analyzed_pages (number
of pages examined), partial (whether only the first few pages were
examined), non_blank_pages, scanned_pages, image_pages (pages requiring
image-based interpretation); Word: figures (number of large images in the
body), text_chars (body text character count); an empty object in other
cases
    "detectedAt": string (timestamp) // Detection time
  }
  "previewUrl": string // For presentations (pptx/ppt), returns the URL
of a previewable PDF derivative (displayed in a PDF viewer on the
frontend); None for other files.

Generate the URL with the same CustomizedFileFieldSerializer used for the
`file` field to ensure a consistent format (including each
storage provider's presign/host rules). Do not use get_absolute_url(),
which produces incorrectly formatted URLs.
  "createdAt": string (timestamp)
}
```

Example Response Values

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "filename": "Response string",
  "file": "https://example.com/file.jpg",
  "fileType": "Response string",
  "knowledgeBase": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Response string"
  },
  "size": 456,
  "status": {},
  "parser": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Response string",
    "provider": {},
    "isTimestampSttProvider": false
  },
  "labels": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "Response string"
    }
  ],
  "rawUserDefineMetadata": null,
  "speakerLabels": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "originalLabel": "Response string",
      "customName": "Response string",
      "displayName": "Response string"
    }
  ],
  "vectorStorageSize": 456,
  "chunksCount": 456,
  "waitingTime": 456,
  "processingTime": 456,
  "processingTimeDetails": null,
  "ocrStatus": "Response string",
  "ocrSkippedReason": "Response string",
  "parserAutoDetection": {
    "parser": {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "Response string",
      "provider": {},
```

```
      "isTimestampSttProvider": false
    },
    "reason": "Response string",
    "facts": {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "Example response name",
      "description": "Example response description"
    },
    "detectedAt": "Response string"
  },
  "previewUrl": "Response string",
  "createdAt": "Response string"
}
```


Retrieve the Latest File Failure Reason

GET `/api/v1/knowledge-bases/{knowledgeBasePk}/files/{id}/latest-failed-reason/`

Parameters

Parameter Name	Required	Type	Description
`id`	V	string	A UUID string identifying this Knowledge Base File.
`knowledgeBasePk`	V	string	

Code Examples

Shell/Bash

```
# Example API call (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/knowledge-
bases/550e8400-e29b-41d4-a716-446655440000/files/550e8400-e29b-41d4-
a716-446655440000/latest-failed-reason/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-
e29b-41d4-a716-446655440000/files/550e8400-e29b-41d4-a716-
446655440000/latest-failed-reason/", config)
  .then(response => {
    console.log('Response retrieved successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-e29b-41d4-a716-446655440000/files/550e8400-e29b-41d4-a716-446655440000/latest-failed-reason/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("Response retrieved successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-e29b-
41d4-a716-446655440000/files/550e8400-e29b-41d4-a716-
446655440000/latest-failed-reason/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response retrieved successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response Content

Status Code: 200

Example Response Schema

```
{
  "id": string (uuid)
```

```
  "errorMessage": string
  "errorCode"?: string // Machine-readable code of a known failure type
(see FAILED_REASON_LOCALIZED_MESSAGES in whizchat/parsers/exceptions.py);
the serializer translates it into the request language on read. An empty
string means no translation, and error_message is shown as is. (Optional)
  "createdAt": string (timestamp)
}
```

Example Response Values

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "errorMessage": "Response string",
  "errorCode": "Response string",
  "createdAt": "Response string"
}
```

Retrieve File Transcription

GET `/api/v1/knowledge-bases/{knowledgeBasePk}/files/{id}/transcription/`

Parameters

Parameter Name	Required	Type	Description
`id`	V	string	A UUID string identifying this Knowledge Base File.
`knowledgeBasePk`	V	string	

Code Examples

Shell/Bash

```
# API call example (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/knowledge-
bases/550e8400-e29b-41d4-a716-446655440000/files/550e8400-e29b-41d4-
a716-446655440000/transcription/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-
e29b-41d4-a716-446655440000/files/550e8400-e29b-41d4-a716-
446655440000/transcription/", config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-e29b-41d4-a716-446655440000/files/550e8400-e29b-41d4-a716-446655440000/transcription/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-e29b-
41d4-a716-446655440000/files/550e8400-e29b-41d4-a716-
446655440000/transcription/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response Body

Status Code: 200

Response Schema Example

```
{
  "id": string (uuid)
```

```
  "filename": string // File name
  "file": string (uri) // File to upload
  "fileType": string
  "knowledgeBase"?:  // Optional
  {
    "id": string (uuid)
    "name": string
  }
  "size": integer // File size in bytes
  "status":
  {
  }
  "parser":
  {
    "id": string (uuid)
    "name": string
    "provider":
    {
    }
    "isTimestampSttProvider": boolean
  }
  "labels"?: [ // Optional
    {
      "id": string (uuid)
      "name": string
    }
  ]
  "rawUserDefineMetadata"?: object // Optional
  "speakerLabels": [
    {
      "id": string (uuid)
      "originalLabel": string // Original speaker label from diarization
(e.g., SPEAKER_00)
      "customName"?: string // User-defined speaker name (e.g., John)
(Optional)
      "displayName": string
    }
  ]
  "vectorStorageSize": integer // Size of vectors for this file in
Elasticsearch (bytes)
  "chunksCount": integer // Number of chunks/nodes generated from this
file
  "waitingTime": number (double)
  "processingTime": number (double)
  "processingTimeDetails": object
```

```
  "ocrStatus": string // OCR result for scanned pages: done, skipped,
partial, or off; null before parsing or for older files
  "ocrSkippedReason": string // Reason OCR was not performed on scanned
pages: no_azure_settings, azure_unavailable, insufficient_credits,
transient_error, time_budget, or disabled; null when completed
  "parserAutoDetection":  // Result and reason for automatically
selecting a parser for this file; null for files with a user-selected
parser, files uploaded before launch, or files queued for re-detection
  {
    "parser":  // Parser selected by automatic detection
    {
      "id": string (uuid)
      "name": string
      "provider":
      {
      }
      "isTimestampSttProvider": boolean
    }
    "reason": string // Reason category: scanned, image_pages,
large_images, unmeasurable_images, presentation, no_image_content,
below_threshold, no_content, file_type_not_detected, detection_failed, or
vision_unavailable; more categories may be added later. Display a generic
message if no matching text is available
    "facts": object // Numeric facts for the reason (calculated at
detection time and not recalculated later). PDF: analyzed_pages (number
of pages examined), partial (whether only the first few pages were
examined), non_blank_pages, scanned_pages, image_pages (pages requiring
image-based interpretation); Word: figures (number of large images in the
body), text_chars (body text character count); an empty object in other
cases
    "detectedAt": string (timestamp) // Detection time
  }
  "previewUrl": string // For presentations (pptx/ppt), returns the URL
of a previewable PDF derivative (displayed with the PDF viewer on the
frontend); otherwise None.

Generate the URL using the same CustomizedFileFieldSerializer as the
`file` field to ensure a consistent format (including each
storage provider's presign/host rules). Do not use get_absolute_url(),
which produces an incorrectly formatted URL.
  "createdAt": string (timestamp)
}
```

Example Response Values

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "filename": "Response string",
  "file": "https://example.com/file.jpg",
  "fileType": "Response string",
  "knowledgeBase": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Response string"
  },
  "size": 456,
  "status": {},
  "parser": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Response string",
    "provider": {},
    "isTimestampSttProvider": false
  },
  "labels": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "Response string"
    }
  ],
  "rawUserDefineMetadata": null,
  "speakerLabels": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "originalLabel": "Response string",
      "customName": "Response string",
      "displayName": "Response string"
    }
  ],
  "vectorStorageSize": 456,
  "chunksCount": 456,
  "waitingTime": 456,
  "processingTime": 456,
  "processingTimeDetails": null,
  "ocrStatus": "Response string",
  "ocrSkippedReason": "Response string",
  "parserAutoDetection": {
    "parser": {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "Response string",
      "provider": {},
```

```
      "isTimestampSttProvider": false
    },
    "reason": "Response string",
    "facts": {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "Example response name",
      "description": "Example response description"
    },
    "detectedAt": "Response string"
  },
  "previewUrl": "Response string",
  "createdAt": "Response string"
}
```


Update File Information

PUT `/api/v1/knowledge-bases/{knowledgeBasePk}/files/{id}`

Parameters

Parameter Name	Required	Type	Description
`id`	V	string	A UUID string identifying this Knowledge Base File.
`knowledgeBasePk`	V	string	

Request Body

Request Parameters

Field	Type	Required	Description
filename	string	Yes	File name
file	string (uri)	Yes	File to upload
parser	string (uuid)	No	
labels	array[IdName]	No	
rawUserDefineMetadata	object	No	
asrOptions	object	No	Per-file canonical transcription options (languages, prompt, diarization). Empty means no per-file options: provider defaults apply. Completely decoupled from user-defined metadata; never indexed for ...

Request Schema Example

```
{
  "filename": string // File name
  "file": string (uri) // File to upload
  "parser"?: string (uuid) // Optional
  "labels"?: [ // Optional
    {
      "id": string (uuid)
    }
  ]
  "rawUserDefineMetadata"?: object // Optional
  "asrOptions"?: object // Per-file canonical transcription options
(languages, prompt, diarization). Empty means no per-file options:
provider defaults apply. Completely decoupled from user-defined metadata;
never indexed for search. (Optional)
}
```

Example Request Values

```
{
  "filename": "document.pdf",
  "file": "https://example.com/file.jpg",
  "parser": "550e8400-e29b-41d4-a716-446655440000",
```

```
  "labels": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000"
    }
  ],
  "rawUserDefineMetadata": null,
  "asrOptions": null
}
```

Code Examples

Shell/Bash

```
# API call example (Shell)
curl -X PUT "https://api.maiagent.ai/api/v1/knowledge-
bases/550e8400-e29b-41d4-a716-446655440000/files/550e8400-e29b-41d4-
a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "filename": "document.pdf",
    "file": "https://example.com/file.jpg",
    "parser": "550e8400-e29b-41d4-a716-446655440000",
    "labels": [
      {
        "id": "550e8400-e29b-41d4-a716-446655440000"
      }
    ],
    "rawUserDefineMetadata": null,
    "asrOptions": null
  }'

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// Request Body (payload)
const data = {
    "filename": "document.pdf",
    "file": "https://example.com/file.jpg",
    "parser": "550e8400-e29b-41d4-a716-446655440000",
    "labels": [
      {
        "id": "550e8400-e29b-41d4-a716-446655440000"
      }
    ],
    "rawUserDefineMetadata": null,
    "asrOptions": null
  };

axios.put("https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-
e29b-41d4-a716-446655440000/files/550e8400-e29b-41d4-a716-
446655440000/", data, config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-e29b-
41d4-a716-446655440000/files/550e8400-e29b-41d4-a716-446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# Request Body (payload)
data = {
    "filename": "document.pdf",
    "file": "https://example.com/file.jpg",
    "parser": "550e8400-e29b-41d4-a716-446655440000",
    "labels": [
        {
            "id": "550e8400-e29b-41d4-a716-446655440000"
        }
    ],
    "rawUserDefineMetadata": None,
    "asrOptions": None
}

response = requests.put(url, json=data, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>put("https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-e29b-
41d4-a716-446655440000/files/550e8400-e29b-41d4-a716-446655440000/",
[
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'filename' => 'document.pdf',
            'file' => 'https://example.com/file.jpg',
            'parser' => '550e8400-e29b-41d4-a716-446655440000',
            'labels' => [
                [
                    'id' => '550e8400-e29b-41d4-a716-446655440000'
                ]
            ],
            'rawUserDefineMetadata' => null,
            'asrOptions' => null
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response Body

Status Code: 200

Response Schema Example

```
{
  "id": string (uuid)
  "filename": string // File name
  "file": string (uri) // File to upload
  "fileType": string
  "knowledgeBase"?:  // Optional
  {
    "id": string (uuid)
    "name": string
  }
  "size": integer // File size in bytes
  "status":
  {
  }
  "parser":
  {
    "id": string (uuid)
    "name": string
    "provider":
    {
    }
    "isTimestampSttProvider": boolean
  }
  "labels"?: [ // Optional
    {
      "id": string (uuid)
      "name": string
    }
  ]
  "rawUserDefineMetadata"?: object // Optional
  "speakerLabels": [
    {
      "id": string (uuid)
      "originalLabel": string // Original speaker label from diarization
(e.g., SPEAKER_00)
```

```
      "customName"?: string // User-defined speaker name (e.g., John)
(Optional)
      "displayName": string
    }
  ]
  "vectorStorageSize": integer // Size of vectors for this file in
Elasticsearch (bytes)
  "chunksCount": integer // Number of chunks/nodes generated from this
file
  "waitingTime": number (double)
  "processingTime": number (double)
  "processingTimeDetails": object
  "ocrStatus": string // OCR result for scanned pages: done, skipped,
partial, or off; null before parsing or for older files
  "ocrSkippedReason": string // Reason OCR was not performed on scanned
pages: no_azure_settings, azure_unavailable, insufficient_credits,
transient_error, time_budget, or disabled; null when completed
  "parserAutoDetection":  // Result and reason for automatically
selecting a parser for this file; null for files with a user-selected
parser, files uploaded before launch, or files queued for re-detection
  {
    "parser":  // Parser selected by automatic detection
    {
      "id": string (uuid)
      "name": string
      "provider":
      {
      }
      "isTimestampSttProvider": boolean
    }
    "reason": string // Reason category: scanned, image_pages,
large_images, unmeasurable_images, presentation, no_image_content,
below_threshold, no_content, file_type_not_detected, detection_failed, or
vision_unavailable; more categories may be added later. Display a generic
message if no matching text is available
    "facts": object // Numeric facts for the reason (calculated at
detection time and not recalculated later). PDF: analyzed_pages (number
of pages examined), partial (whether only the first few pages were
examined), non_blank_pages, scanned_pages, image_pages (pages requiring
image-based interpretation); Word: figures (number of large images in the
body), text_chars (body text character count); an empty object in other
cases
    "detectedAt": string (timestamp) // Detection time
  }
  "previewUrl": string // For presentations (pptx/ppt), returns the URL
```

```
of a previewable PDF derivative (displayed with the PDF viewer on the
frontend); otherwise None.

Generate the URL using the same CustomizedFileFieldSerializer as the
`file` field to ensure a consistent format (including each
storage provider's presign/host rules). Do not use get_absolute_url(),
which produces an incorrectly formatted URL.
  "createdAt": string (timestamp)
}
```

Example Response Values

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "filename": "Response string",
  "file": "https://example.com/file.jpg",
  "fileType": "Response string",
  "knowledgeBase": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Response string"
  },
  "size": 456,
  "status": {},
  "parser": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Response string",
    "provider": {},
    "isTimestampSttProvider": false
  },
  "labels": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "Response string"
    }
  ],
  "rawUserDefineMetadata": null,
  "speakerLabels": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "originalLabel": "Response string",
      "customName": "Response string",
      "displayName": "Response string"
    }
  ],
```

```
  "vectorStorageSize": 456,
  "chunksCount": 456,
  "waitingTime": 456,
  "processingTime": 456,
  "processingTimeDetails": null,
  "ocrStatus": "Response string",
  "ocrSkippedReason": "Response string",
  "parserAutoDetection": {
    "parser": {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "Response string",
      "provider": {},
      "isTimestampSttProvider": false
    },
    "reason": "Response string",
    "facts": {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "Example response name",
      "description": "Example response description"
    },
    "detectedAt": "Response string"
  },
  "previewUrl": "Response string",
  "createdAt": "Response string"
}
```


Partially Update a File

PATCH `/api/v1/knowledge-bases/{knowledgeBasePk}/files/{id}`

Parameters

Parameter Name	Required	Type	Description
`id`	V	string	A UUID string identifying this Knowledge Base File.

`knowledgeBasePk`	V	string

Request Body

Request Parameters

Field	Type	Required	Description
filename	string	No	File name
file	string (uri)	No	File to upload
parser	string (uuid)	No	
labels	array[IdName]	No	
rawUserDefineMetadata	object	No	
asrOptions	object	No	Per-file canonical transcription options (languages, prompt, diarization). Empty means no per-file options: provider defaults apply. Completely decoupled from user-defined metadata; never indexed for ...

Request Schema Example

```
{
  "filename"?: string // File name (Optional)
  "file"?: string (uri) // File to upload (Optional)
  "parser"?: string (uuid) // Optional
  "labels"?: [ // Optional
    {
      "id": string (uuid)
    }
  ]
  "rawUserDefineMetadata"?: object // Optional
  "asrOptions"?: object // Per-file canonical transcription options
(languages, prompt, diarization). Empty means no per-file options:
provider defaults apply. Completely decoupled from user-defined metadata;
```

```
never indexed for search. (Optional)
}
```

Example Request Values

```
{
  "filename": "document.pdf",
  "file": "https://example.com/file.jpg",
  "parser": "550e8400-e29b-41d4-a716-446655440000",
  "labels": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000"
    }
  ],
  "rawUserDefineMetadata": null,
  "asrOptions": null
}
```

Code Examples

Shell/Bash

```
# API call example (Shell)
curl -X PATCH "https://api.maiagent.ai/api/v1/knowledge-
bases/550e8400-e29b-41d4-a716-446655440000/files/550e8400-e29b-41d4-
a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "filename": "document.pdf",
    "file": "https://example.com/file.jpg",
    "parser": "550e8400-e29b-41d4-a716-446655440000",
    "labels": [
      {
        "id": "550e8400-e29b-41d4-a716-446655440000"
      }
    ],
    "rawUserDefineMetadata": null,
    "asrOptions": null
  }'

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// Request Body (payload)
const data = {
    "filename": "document.pdf",
    "file": "https://example.com/file.jpg",
    "parser": "550e8400-e29b-41d4-a716-446655440000",
    "labels": [
      {
        "id": "550e8400-e29b-41d4-a716-446655440000"
      }
    ],
    "rawUserDefineMetadata": null,
    "asrOptions": null
  };

axios.patch("https://api.maiagent.ai/api/v1/knowledge-
bases/550e8400-e29b-41d4-a716-446655440000/files/550e8400-e29b-41d4-
a716-446655440000/", data, config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-e29b-
41d4-a716-446655440000/files/550e8400-e29b-41d4-a716-446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# Request Body (payload)
data = {
    "filename": "document.pdf",
    "file": "https://example.com/file.jpg",
    "parser": "550e8400-e29b-41d4-a716-446655440000",
    "labels": [
        {
            "id": "550e8400-e29b-41d4-a716-446655440000"
        }
    ],
    "rawUserDefineMetadata": None,
    "asrOptions": None
}

response = requests.patch(url, json=data, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>patch("https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-
e29b-41d4-a716-446655440000/files/550e8400-e29b-41d4-a716-
446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'filename' => 'document.pdf',
            'file' => 'https://example.com/file.jpg',
            'parser' => '550e8400-e29b-41d4-a716-446655440000',
            'labels' => [
                [
                    'id' => '550e8400-e29b-41d4-a716-446655440000'
                ]
            ],
            'rawUserDefineMetadata' => null,
            'asrOptions' => null
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response Body

Status code: 200

Example Response Schema

```
{
  "id": string (uuid)
  "filename": string // File name
  "file": string (uri) // File to upload
  "fileType": string
  "knowledgeBase"?:  // Optional
  {
    "id": string (uuid)
    "name": string
  }
  "size": integer // File size in bytes
  "status":
  {
  }
  "parser":
  {
    "id": string (uuid)
    "name": string
    "provider":
    {
    }
    "isTimestampSttProvider": boolean
  }
  "labels"?: [ // Optional
    {
      "id": string (uuid)
      "name": string
    }
  ]
  "rawUserDefineMetadata"?: object // Optional
  "speakerLabels": [
    {
      "id": string (uuid)
      "originalLabel": string // Original speaker label from diarization
(e.g., SPEAKER_00)
```

```
      "customName"?: string // User-defined speaker name (e.g., John)
(Optional)
      "displayName": string
    }
  ]
  "vectorStorageSize": integer // Size of vectors for this file in
Elasticsearch (bytes)
  "chunksCount": integer // Number of chunks/nodes generated from this
file
  "waitingTime": number (double)
  "processingTime": number (double)
  "processingTimeDetails": object
  "ocrStatus": string // OCR result for scanned pages: done, skipped,
partial, or off; null before parsing or for older files
  "ocrSkippedReason": string // Reason OCR was not performed on scanned
pages: no_azure_settings, azure_unavailable, insufficient_credits,
transient_error, time_budget, or disabled; null when OCR is completed
  "parserAutoDetection":  // Result and reason for automatic parser
selection for this file; null for files with a user-selected parser,
files uploaded before this feature launched, or files queued for
reassessment
  {
    "parser":  // Parser selected by automatic detection
    {
      "id": string (uuid)
      "name": string
      "provider":
      {
      }
      "isTimestampSttProvider": boolean
    }
    "reason": string // Reason category: scanned, image_pages,
large_images, unmeasurable_images, presentation, no_image_content,
below_threshold, no_content, file_type_not_detected, detection_failed, or
vision_unavailable; more categories may be added, so display a generic
message when no matching text is available
    "facts": object // Numeric values supporting the reason (calculated
at detection time and not recalculated later). PDF: analyzed_pages
(number of pages examined), partial (whether only the first few pages
were examined), non_blank_pages, scanned_pages, image_pages (pages
requiring image-based interpretation); Word: figures (number of large
images in the body), text_chars (number of characters in the body); an
empty object in other cases
    "detectedAt": string (timestamp) // Detection time
  }
```

```
  "previewUrl": string // For presentations (pptx/ppt), returns the URL
of a derived PDF for preview (displayed with a PDF viewer on the
frontend); None for other file types.

Generate the URL with the same CustomizedFileFieldSerializer used for the
`file` field to ensure consistent formatting (including each
storage provider's presign/host rules). Do not use get_absolute_url(),
which produces an incorrectly formatted URL.
  "createdAt": string (timestamp)
}
```

Example Response Values


```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "filename": "Response string",
  "file": "https://example.com/file.jpg",
  "fileType": "Response string",
  "knowledgeBase": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Response string"
  },
  "size": 456,
  "status": {},
  "parser": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Response string",
    "provider": {},
    "isTimestampSttProvider": false
  },
  "labels": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "Response string"
    }
  ],
  "rawUserDefineMetadata": null,
  "speakerLabels": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "originalLabel": "Response string",
      "customName": "Response string",
      "displayName": "Response string"
    }
```

```
  ],
  "vectorStorageSize": 456,
  "chunksCount": 456,
  "waitingTime": 456,
  "processingTime": 456,
  "processingTimeDetails": null,
  "ocrStatus": "Response string",
  "ocrSkippedReason": "Response string",
  "parserAutoDetection": {
    "parser": {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "Response string",
      "provider": {},
      "isTimestampSttProvider": false
    },
    "reason": "Response string",
    "facts": {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "Example response name",
      "description": "Example response description"
    },
    "detectedAt": "Response string"
  },
  "previewUrl": "Response string",
  "createdAt": "Response string"
}
```


Delete a File

DELETE `/api/v1/knowledge-bases/{knowledgeBasePk}/files/{id}`

Parameters

Parameter Name	Required	Type	Description

`id`	V	string	A UUID string identifying this Knowledge Base File.
`knowledgeBasePk`	V	string	

Code Examples

Shell/Bash

```
# Example API call (Shell)
curl -X DELETE "https://api.maiagent.ai/api/v1/knowledge-
bases/550e8400-e29b-41d4-a716-446655440000/files/550e8400-e29b-41d4-
a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

// Request body (payload)
const data = null;

axios.delete("https://api.maiagent.ai/api/v1/knowledge-
bases/550e8400-e29b-41d4-a716-446655440000/files/550e8400-e29b-41d4-
a716-446655440000/", data, config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request failed:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-e29b-41d4-a716-446655440000/files/550e8400-e29b-41d4-a716-446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.delete(url, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request failed:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>delete("https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-
e29b-41d4-a716-446655440000/files/550e8400-e29b-41d4-a716-
446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request failed: ' . $e->getMessage();
}
?>
```

Response Body

Status Code: 202

Example Response Schema

```
{
  "detail": string
```

```
}
```

Example Response Values

```
{
  "detail": "response string"
}
```

Status Code: 204 - No response body

Create a File Translation

POST `/api/v1/knowledge-bases/{knowledgeBasePk}/files/{knowledgeBaseFilePk}/translations/`

Parameters

Parameter name	Required	Type	Description
`knowledgeBaseFilePk`	V	string	
`knowledgeBasePk`	V	string	

Request body

Request parameters

Field	Type	Required	Description
sourceLanguage	string	No	
targetLanguage	string	Yes	

Field	Type	Required	Description
customPrompt	string	No	
largeLanguageModelId	string (uuid)	Yes	

Example request schema

```
{
  "sourceLanguage"?: string // Optional
  "targetLanguage": string
  "customPrompt"?: string // Optional
  "largeLanguageModelId": string (uuid)
}
```

Example request values

```
{
  "sourceLanguage": "Example string",
  "targetLanguage": "Example string",
  "customPrompt": "Example string",
  "largeLanguageModelId": "550e8400-e29b-41d4-a716-446655440000"
}
```

Code examples

Shell/Bash

```
# API call example (Shell)
curl -X POST "https://api.maiagent.ai/api/v1/knowledge-
bases/{knowledgeBasePk}/files/{knowledgeBaseFilePk}/translations/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "sourceLanguage": "Example string",
    "targetLanguage": "Example string",
    "customPrompt": "Example string",
    "largeLanguageModelId": "550e8400-e29b-41d4-a716-446655440000"
  }'

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// Request body (payload)
const data = {
    "sourceLanguage": "Example string",
    "targetLanguage": "Example string",
    "customPrompt": "Example string",
    "largeLanguageModelId": "550e8400-e29b-41d4-a716-446655440000"
  };

axios.post("https://api.maiagent.ai/api/v1/knowledge-
bases/{knowledgeBasePk}/files/{knowledgeBaseFilePk}/translations/",
data, config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/knowledge-
bases/{knowledgeBasePk}/files/{knowledgeBaseFilePk}/translations/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# Request body (payload)
data = {
    "sourceLanguage": "Example string",
    "targetLanguage": "Example string",
    "customPrompt": "Example string",
    "largeLanguageModelId": "550e8400-e29b-41d4-a716-446655440000"
}

response = requests.post(url, json=data, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>post("https://api.maiagent.ai/api/v1/knowledge-
bases/{knowledgeBasePk}/files/{knowledgeBaseFilePk}/translations/",
[
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'sourceLanguage' => 'Example string',
            'targetLanguage' => 'Example string',
            'customPrompt' => 'Example string',
            'largeLanguageModelId' => '550e8400-e29b-41d4-a716-
446655440000'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response body

Status code: 201

Example response schema

```
{
  "sourceLanguage"?: string // Optional
  "targetLanguage": string
  "customPrompt"?: string // Optional
  "largeLanguageModelId": string (uuid)
}
```

Example response values

```
{
  "sourceLanguage": "Response string",
  "targetLanguage": "Response string",
  "customPrompt": "Response string",
  "largeLanguageModelId": "550e8400-e29b-41d4-a716-446655440000"
}
```

List File Translations

GET `/api/v1/knowledge-bases/{knowledgeBasePk}/files/{knowledgeBaseFilePk}/translations/`

Parameters

Parameter name	Required	Type	Description
`knowledgeBaseFilePk`	V	string	
`knowledgeBasePk`	V	string	

`page`	X	integer	A page number within the paginated result set.
`pageSize`	X	integer	Number of results to return per page.

Code examples

Shell/Bash

```
# API call example (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/knowledge-
bases/{knowledgeBasePk}/files/{knowledgeBaseFilePk}/translations/?
page=1&pageSize=1"

  -H "Authorization: Api-Key YOUR_API_KEY"

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/knowledge-
bases/{knowledgeBasePk}/files/{knowledgeBaseFilePk}/translations/?
page=1&pageSize=1", config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/knowledge-
bases/{knowledgeBasePk}/files/{knowledgeBaseFilePk}/translations/?
page=1&pageSize=1"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/knowledge-
bases/{knowledgeBasePk}/files/{knowledgeBaseFilePk}/translations/?
page=1&pageSize=1", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response body

Status code: 200

Example response schema

```
{
  "count": integer
```

```
  "next"?: string (uri) // Optional
  "previous"?: string (uri) // Optional
  "results": [
    {
      "id": string (uuid)
      "chatbotFileId": string (uuid)
      "chatbotFileFilename": string
      "organization": string (uuid)
      "largeLanguageModel":
      {
        "id": string (uuid)
        "name": string
      }
      "sourceLanguage": string
      "targetLanguage": string
      "customPrompt": string // User-provided terminology/glossary rules
      "status":
      {
      }
      "errorMessage": string
      "translatedFileUrl": string
      "bilingualFileUrl": string
      "processDuration": string
      "processingDurationSeconds": number (double)
      "pageCount": integer
      "originalWordCount": integer
      "translatedWordCount": integer
      "inputTokensUsed": integer
      "outputTokensUsed": integer
      "totalTokensUsed": integer
      "originalFileSize": integer
      "translatedFileSize": integer
      "bilingualFileSize": integer
      "llmTranslationDuration": string // Total time spent on LLM API
calls
      "llmTranslationDurationSeconds": number (double)
      "llmCallCount": integer // Number of LLM API calls made
      "avgLlmCallDuration": number (double) // Average time per LLM call
in seconds
      "pdfParsingDuration": string // Time spent on PDF parsing and
processing
      "pdfParsingDurationSeconds": number (double)
      "fileSavingDuration": string // Time spent on saving output files
      "fileSavingDurationSeconds": number (double)
      "startedAt": string (timestamp)
```

```
      "completedAt": string (timestamp)
      "createdAt": string (timestamp)
      "updatedAt": string (timestamp)
    }
  ]
}
```

Example response values

```
{
  "count": 123,
  "next": "http://api.example.org/accounts/?page=4",
  "previous": "http://api.example.org/accounts/?page=2",
  "results": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "chatbotFileId": "550e8400-e29b-41d4-a716-446655440000",
      "chatbotFileFilename": "Response string",
      "organization": "550e8400-e29b-41d4-a716-446655440000",
      "largeLanguageModel": {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "name": "Response string"
      },
      "sourceLanguage": "Response string",
      "targetLanguage": "Response string",
      "customPrompt": "Response string",
      "status": {},
      "errorMessage": "Response string",
      "translatedFileUrl": "Response string",
      "bilingualFileUrl": "Response string",
      "processDuration": "Response string",
      "processingDurationSeconds": 456,
      "pageCount": 456,
      "originalWordCount": 456,
      "translatedWordCount": 456,
      "inputTokensUsed": 456,
      "outputTokensUsed": 456,
      "totalTokensUsed": 456,
      "originalFileSize": 456,
      "translatedFileSize": 456,
      "bilingualFileSize": 456,
      "llmTranslationDuration": "Response string",
      "llmTranslationDurationSeconds": 456,
      "llmCallCount": 456,
```

```
      "avgLlmCallDuration": 456,
      "pdfParsingDuration": "Response string",
      "pdfParsingDurationSeconds": 456,
      "fileSavingDuration": "Response string",
      "fileSavingDurationSeconds": 456,
      "startedAt": "Response string",
      "completedAt": "Response string",
      "createdAt": "Response string",
      "updatedAt": "Response string"
    }
  ]
}
```


Retrieve a Specific Translation

`GET` `/api/v1/knowledge-bases/{knowledgeBasePk}/files/{knowledgeBaseFilePk}/translations/{id}`

Parameters

Parameter name	Required	Type	Description
`id`	V	string	A UUID string identifying this File Translation.
`knowledgeBaseFilePk`	V	string	
`knowledgeBasePk`	V	string	

Code examples

Shell/Bash

```
# API call example (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/knowledge-
bases/{knowledgeBasePk}/files/{knowledgeBaseFilePk}/translations/550
e8400-e29b-41d4-a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/knowledge-
bases/{knowledgeBasePk}/files/{knowledgeBaseFilePk}/translations/550
e8400-e29b-41d4-a716-446655440000/", config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/knowledge-
bases/{knowledgeBasePk}/files/{knowledgeBaseFilePk}/translations/550
e8400-e29b-41d4-a716-446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/knowledge-
bases/{knowledgeBasePk}/files/{knowledgeBaseFilePk}/translations/550
e8400-e29b-41d4-a716-446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response body

Status code: 200

Example response schema

```
{
  "id": string (uuid)
```

```
  "chatbotFileId": string (uuid)
  "chatbotFileFilename": string
  "organization": string (uuid)
  "largeLanguageModel":
  {
    "id": string (uuid)
    "name": string
  }
  "sourceLanguage": string
  "targetLanguage": string
  "customPrompt": string // User-provided terminology/glossary rules
  "status":
  {
  }
  "errorMessage": string
  "translatedFileUrl": string
  "bilingualFileUrl": string
  "processDuration": string
  "processingDurationSeconds": number (double)
  "pageCount": integer
  "originalWordCount": integer
  "translatedWordCount": integer
  "inputTokensUsed": integer
  "outputTokensUsed": integer
  "totalTokensUsed": integer
  "originalFileSize": integer
  "translatedFileSize": integer
  "bilingualFileSize": integer
  "llmTranslationDuration": string // Total time spent on LLM API calls
  "llmTranslationDurationSeconds": number (double)
  "llmCallCount": integer // Number of LLM API calls made
  "avgLlmCallDuration": number (double) // Average time per LLM call in
seconds
  "pdfParsingDuration": string // Time spent on PDF parsing and
processing
  "pdfParsingDurationSeconds": number (double)
  "fileSavingDuration": string // Time spent on saving output files
  "fileSavingDurationSeconds": number (double)
  "startedAt": string (timestamp)
  "completedAt": string (timestamp)
  "createdAt": string (timestamp)
  "updatedAt": string (timestamp)
}
```

Example response values

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "chatbotFileId": "550e8400-e29b-41d4-a716-446655440000",
  "chatbotFileFilename": "Response string",
  "organization": "550e8400-e29b-41d4-a716-446655440000",
  "largeLanguageModel": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Response string"
  },
  "sourceLanguage": "Response string",
  "targetLanguage": "Response string",
  "customPrompt": "Response string",
  "status": {},
  "errorMessage": "Response string",
  "translatedFileUrl": "Response string",
  "bilingualFileUrl": "Response string",
  "processDuration": "Response string",
  "processingDurationSeconds": 456,
  "pageCount": 456,
  "originalWordCount": 456,
  "translatedWordCount": 456,
  "inputTokensUsed": 456,
  "outputTokensUsed": 456,
  "totalTokensUsed": 456,
  "originalFileSize": 456,
  "translatedFileSize": 456,
  "bilingualFileSize": 456,
  "llmTranslationDuration": "Response string",
  "llmTranslationDurationSeconds": 456,
  "llmCallCount": 456,
  "avgLlmCallDuration": 456,
  "pdfParsingDuration": "Response string",
  "pdfParsingDurationSeconds": 456,
  "fileSavingDuration": "Response string",
  "fileSavingDurationSeconds": 456,
  "startedAt": "Response string",
  "completedAt": "Response string",
  "createdAt": "Response string",
  "updatedAt": "Response string"
}
```

Delete a Translation

`DELETE` `/api/v1/knowledge-bases/{knowledgeBasePk}/files/{knowledgeBaseFilePk}/translations/{id}`

Parameters

Parameter name	Required	Type	Description
`id`	V	string	A UUID string identifying this File Translation.
`knowledgeBaseFilePk`	V	string	
`knowledgeBasePk`	V	string	

Code examples

Shell/Bash

```
# API call example (Shell)
curl -X DELETE "https://api.maiagent.ai/api/v1/knowledge-
bases/{knowledgeBasePk}/files/{knowledgeBaseFilePk}/translations/550
e8400-e29b-41d4-a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

// Request body (payload)
const data = null;

axios.delete("https://api.maiagent.ai/api/v1/knowledge-
bases/{knowledgeBasePk}/files/{knowledgeBaseFilePk}/translations/550
e8400-e29b-41d4-a716-446655440000/", data, config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/knowledge-
bases/{knowledgeBasePk}/files/{knowledgeBaseFilePk}/translations/550
e8400-e29b-41d4-a716-446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.delete(url, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>delete("https://api.maiagent.ai/api/v1/knowledge-
bases/{knowledgeBasePk}/files/{knowledgeBaseFilePk}/translations/550
e8400-e29b-41d4-a716-446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response body

Status code	Description
204	No response body

Download a Translated File

GET `/api/v1/knowledge-bases/{knowledgeBasePk}/files/{knowledgeBaseFilePk}/translations/{id}/download/`

Parameters

Parameter name	Required	Type	Description
`id`	V	string	A UUID string identifying this File Translation.
`knowledgeBaseFilePk`	V	string	
`knowledgeBasePk`	V	string	

Code examples

Shell/Bash

```
# API call example (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/knowledge-
bases/{knowledgeBasePk}/files/{knowledgeBaseFilePk}/translations/550
e8400-e29b-41d4-a716-446655440000/download/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/knowledge-
bases/{knowledgeBasePk}/files/{knowledgeBaseFilePk}/translations/550
e8400-e29b-41d4-a716-446655440000/download/", config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/knowledge-
bases/{knowledgeBasePk}/files/{knowledgeBaseFilePk}/translations/550
e8400-e29b-41d4-a716-446655440000/download/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/knowledge-
bases/{knowledgeBasePk}/files/{knowledgeBaseFilePk}/translations/550
e8400-e29b-41d4-a716-446655440000/download/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response body

Status code: 200

Example response schema

```
{
  "id": string (uuid)
```

```
  "chatbotFileId": string (uuid)
  "chatbotFileFilename": string
  "organization": string (uuid)
  "largeLanguageModel":
  {
    "id": string (uuid)
    "name": string
  }
  "sourceLanguage": string
  "targetLanguage": string
  "customPrompt": string // User-provided terminology/glossary rules
  "status":
  {
  }
  "errorMessage": string
  "translatedFileUrl": string
  "bilingualFileUrl": string
  "processDuration": string
  "processingDurationSeconds": number (double)
  "pageCount": integer
  "originalWordCount": integer
  "translatedWordCount": integer
  "inputTokensUsed": integer
  "outputTokensUsed": integer
  "totalTokensUsed": integer
  "originalFileSize": integer
  "translatedFileSize": integer
  "bilingualFileSize": integer
  "llmTranslationDuration": string // Total time spent on LLM API calls
  "llmTranslationDurationSeconds": number (double)
  "llmCallCount": integer // Number of LLM API calls made
  "avgLlmCallDuration": number (double) // Average time per LLM call in
seconds
  "pdfParsingDuration": string // Time spent on PDF parsing and
processing
  "pdfParsingDurationSeconds": number (double)
  "fileSavingDuration": string // Time spent on saving output files
  "fileSavingDurationSeconds": number (double)
  "startedAt": string (timestamp)
  "completedAt": string (timestamp)
  "createdAt": string (timestamp)
  "updatedAt": string (timestamp)
}
```

Example Response Values

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "chatbotFileId": "550e8400-e29b-41d4-a716-446655440000",
  "chatbotFileFilename": "Response string",
  "organization": "550e8400-e29b-41d4-a716-446655440000",
  "largeLanguageModel": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Response string"
  },
  "sourceLanguage": "Response string",
  "targetLanguage": "Response string",
  "customPrompt": "Response string",
  "status": {},
  "errorMessage": "Response string",
  "translatedFileUrl": "Response string",
  "bilingualFileUrl": "Response string",
  "processDuration": "Response string",
  "processingDurationSeconds": 456,
  "pageCount": 456,
  "originalWordCount": 456,
  "translatedWordCount": 456,
  "inputTokensUsed": 456,
  "outputTokensUsed": 456,
  "totalTokensUsed": 456,
  "originalFileSize": 456,
  "translatedFileSize": 456,
  "bilingualFileSize": 456,
  "llmTranslationDuration": "Response string",
  "llmTranslationDurationSeconds": 456,
  "llmCallCount": 456,
  "avgLlmCallDuration": 456,
  "pdfParsingDuration": "Response string",
  "pdfParsingDurationSeconds": 456,
  "fileSavingDuration": "Response string",
  "fileSavingDurationSeconds": 456,
  "startedAt": "Response string",
  "completedAt": "Response string",
  "createdAt": "Response string",
  "updatedAt": "Response string"
}
```

List Knowledge Base Documents

GET `/api/v1/knowledge-bases/{knowledgeBasePk}/documents/`

Parameters

Parameter Name	Required	Type	Description
`knowledgeBasePk`	V	string	
`chatbotFileId`	X	string	[To be deprecated] File ID (use knowledge_base_file_id)
`knowledgeBaseFileId`	X	string	Knowledge Base File ID

Code Examples

Shell/Bash

```
# API call example (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/knowledge-
bases/550e8400-e29b-41d4-a716-446655440000/documents/?
chatbotFileId=example&knowledgeBaseFileId=example"

  -H "Authorization: Api-Key YOUR_API_KEY"

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Configure request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-
e29b-41d4-a716-446655440000/documents/?
chatbotFileId=example&knowledgeBaseFileId=example", config)
  .then(response => {
    console.log('Response retrieved successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request failed:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-e29b-
41d4-a716-446655440000/documents/?
chatbotFileId=example&knowledgeBaseFileId=example"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("Response retrieved successfully:")
    print(response.json())
except Exception as e:
    print("Request failed:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-e29b-
41d4-a716-446655440000/documents/?
chatbotFileId=example&knowledgeBaseFileId=example", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response retrieved successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request failed: ' . $e->getMessage();
}
?>
```

Response Body

Status Code: 200

Example Response Schema

```
[
  {
```

```
    "id": string (uuid)
    "fileName": string
    "pageNumber"?: integer // Optional
    "chatbotFile": string (uuid)
    "excludedEmbedMetadataKeys"?: object // List[str]: metadata keys to
exclude from the embedding. (Optional)
    "excludedLlmMetadataKeys"?: object // List[str]: metadata keys to
exclude from the LLM context. (Optional)
    "llamaIndexObjectJson"?: object // Optional
    "metadata"?: object // Optional
    "text": string
    "updatedAt": string (timestamp)
  }
]
```

Example Response Values

```
[
  {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "fileName": "Response string",
    "pageNumber": 456,
    "chatbotFile": "550e8400-e29b-41d4-a716-446655440000",
    "excludedEmbedMetadataKeys": null,
    "excludedLlmMetadataKeys": null,
    "llamaIndexObjectJson": null,
    "metadata": null,
    "text": "Response string",
    "updatedAt": "Response string"
  }
]
```

Status Code: `404` - The knowledge base file does not exist or does not belong to the current organization

Update a Document

PUT `/api/v1/knowledge-bases/{knowledgeBasePk}/documents/{id}`

Parameters

Parameter Name	Required	Type	Description
`id`	V	string	A UUID string identifying this Chatbot Document.
`knowledgeBasePk`	V	string	

Request Body

Request Parameters

Field	Type	Required	Description
fileName	string	Yes	
pageNumber	integer	No	
chatbotFile	string (uuid)	Yes	
excludedEmbedMetadataKeys	object	No	List[str]: metadata keys to exclude from the embedding.
excludedLlmMetadataKeys	object	No	List[str]: metadata keys to exclude from the LLM context.
llamaIndexObjectJson	object	No	
metadata	object	No	
text	string	Yes	

Example Request Schema

```
{
  "fileName": string
  "pageNumber"?: integer // Optional
  "chatbotFile": string (uuid)
  "excludedEmbedMetadataKeys"?: object // List[str]: metadata keys to
exclude from the embedding. (Optional)
  "excludedLlmMetadataKeys"?: object // List[str]: metadata keys to
exclude from the LLM context. (Optional)
  "llamaIndexObjectJson"?: object // Optional
  "metadata"?: object // Optional
  "text": string
}
```

Example Request Values

```
{
  "fileName": "Example string",
  "pageNumber": 123,
  "chatbotFile": "550e8400-e29b-41d4-a716-446655440000",
  "excludedEmbedMetadataKeys": null,
  "excludedLlmMetadataKeys": null,
  "llamaIndexObjectJson": null,
  "metadata": null,
  "text": "This is an example message"
}
```

Code Examples

Shell/Bash

```
# API call example (Shell)
curl -X PUT "https://api.maiagent.ai/api/v1/knowledge-
bases/550e8400-e29b-41d4-a716-446655440000/documents/550e8400-e29b-
41d4-a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "fileName": "Example string",
    "pageNumber": 123,
    "chatbotFile": "550e8400-e29b-41d4-a716-446655440000",
    "excludedEmbedMetadataKeys": null,
    "excludedLlmMetadataKeys": null,
    "llamaIndexObjectJson": null,
    "metadata": null,
    "text": "This is an example message"
  }'

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Configure request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// Request Body (payload)
const data = {
    "fileName": "Example string",
    "pageNumber": 123,
    "chatbotFile": "550e8400-e29b-41d4-a716-446655440000",
    "excludedEmbedMetadataKeys": null,
    "excludedLlmMetadataKeys": null,
    "llamaIndexObjectJson": null,
    "metadata": null,
    "text": "This is an example message"
  };

axios.put("https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-
e29b-41d4-a716-446655440000/documents/550e8400-e29b-41d4-a716-
446655440000/", data, config)
  .then(response => {
    console.log('Response retrieved successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request failed:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-e29b-41d4-a716-446655440000/documents/550e8400-e29b-41d4-a716-446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# Request Body (payload)
data = {
    "fileName": "Example string",
    "pageNumber": 123,
    "chatbotFile": "550e8400-e29b-41d4-a716-446655440000",
    "excludedEmbedMetadataKeys": None,
    "excludedLlmMetadataKeys": None,
    "llamaIndexObjectJson": None,
    "metadata": None,
    "text": "This is an example message"
}

response = requests.put(url, json=data, headers=headers)
try:
    print("Response retrieved successfully:")
    print(response.json())
except Exception as e:
    print("Request failed:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>put("https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-e29b-
41d4-a716-446655440000/documents/550e8400-e29b-41d4-a716-
446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'fileName' => 'Example string',
            'pageNumber' => 123,
            'chatbotFile' => '550e8400-e29b-41d4-a716-446655440000',
            'excludedEmbedMetadataKeys' => null,
            'excludedLlmMetadataKeys' => null,
            'llamaIndexObjectJson' => null,
            'metadata' => null,
            'text' => 'This is an example message'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response retrieved successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request failed: ' . $e->getMessage();
}
?>
```

Response Body

Status Code: 200

Example Response Schema

```
{
  "id": string (uuid)
  "fileName": string
  "pageNumber"?: integer // Optional
  "chatbotFile": string (uuid)
  "excludedEmbedMetadataKeys"?: object // List[str]: metadata keys to
exclude from the embedding. (Optional)
  "excludedLlmMetadataKeys"?: object // List[str]: metadata keys to
exclude from the LLM context. (Optional)
  "llamaIndexObjectJson"?: object // Optional
  "metadata"?: object // Optional
  "text": string
  "updatedAt": string (timestamp)
}
```

Example Response Values

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "fileName": "Response string",
  "pageNumber": 456,
  "chatbotFile": "550e8400-e29b-41d4-a716-446655440000",
  "excludedEmbedMetadataKeys": null,
  "excludedLlmMetadataKeys": null,
  "llamaIndexObjectJson": null,
  "metadata": null,
  "text": "Response string",
  "updatedAt": "Response string"
}
```

Partially Update a Document

PATCH `/api/v1/knowledge-bases/{knowledgeBasePk}/documents/{id}`

Parameters

Parameter Name	Required	Type	Description
`id`	V	string	A UUID string identifying this Chatbot Document.
`knowledgeBasePk`	V	string	

Request Body

Request Parameters

Field	Type	Required	Description
fileName	string	No	
pageNumber	integer	No	
chatbotFile	string (uuid)	No	
excludedEmbedMetadataKeys	object	No	List[str]: metadata keys to exclude from the embedding.
excludedLlmMetadataKeys	object	No	List[str]: metadata keys to exclude from the LLM context.
llamaIndexObjectJson	object	No	
metadata	object	No	
text	string	No	

Example Request Schema

```
{
  "fileName"?: string // Optional
  "pageNumber"?: integer // Optional
  "chatbotFile"?: string (uuid) // Optional
  "excludedEmbedMetadataKeys"?: object // List[str]: metadata keys to
exclude from the embedding. (Optional)
  "excludedLlmMetadataKeys"?: object // List[str]: metadata keys to
exclude from the LLM context. (Optional)
  "llamaIndexObjectJson"?: object // Optional
  "metadata"?: object // Optional
  "text"?: string // Optional
}
```

Example Request Values

```
{
  "fileName": "Example string",
  "pageNumber": 123,
  "chatbotFile": "550e8400-e29b-41d4-a716-446655440000",
  "excludedEmbedMetadataKeys": null,
  "excludedLlmMetadataKeys": null,
  "llamaIndexObjectJson": null,
  "metadata": null,
  "text": "This is an example message"
}
```

Code Examples

Shell/Bash

```
# API call example (Shell)
curl -X PATCH "https://api.maiagent.ai/api/v1/knowledge-
bases/550e8400-e29b-41d4-a716-446655440000/documents/550e8400-e29b-
41d4-a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "fileName": "Example string",
    "pageNumber": 123,
    "chatbotFile": "550e8400-e29b-41d4-a716-446655440000",
    "excludedEmbedMetadataKeys": null,
    "excludedLlmMetadataKeys": null,
    "llamaIndexObjectJson": null,
    "metadata": null,
    "text": "This is an example message"
  }'

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Configure request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// Request Body (payload)
const data = {
    "fileName": "Example string",
    "pageNumber": 123,
    "chatbotFile": "550e8400-e29b-41d4-a716-446655440000",
    "excludedEmbedMetadataKeys": null,
    "excludedLlmMetadataKeys": null,
    "llamaIndexObjectJson": null,
    "metadata": null,
    "text": "This is an example message"
  };

axios.patch("https://api.maiagent.ai/api/v1/knowledge-
bases/550e8400-e29b-41d4-a716-446655440000/documents/550e8400-e29b-
41d4-a716-446655440000/", data, config)
  .then(response => {
    console.log('Response retrieved successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request failed:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-e29b-41d4-a716-446655440000/documents/550e8400-e29b-41d4-a716-446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# Request Body (payload)
data = {
    "fileName": "Example string",
    "pageNumber": 123,
    "chatbotFile": "550e8400-e29b-41d4-a716-446655440000",
    "excludedEmbedMetadataKeys": None,
    "excludedLlmMetadataKeys": None,
    "llamaIndexObjectJson": None,
    "metadata": None,
    "text": "This is an example message"
}

response = requests.patch(url, json=data, headers=headers)
try:
    print("Response retrieved successfully:")
    print(response.json())
except Exception as e:
    print("Request failed:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>patch("https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-
e29b-41d4-a716-446655440000/documents/550e8400-e29b-41d4-a716-
446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'fileName' => 'Example string',
            'pageNumber' => 123,
            'chatbotFile' => '550e8400-e29b-41d4-a716-446655440000',
            'excludedEmbedMetadataKeys' => null,
            'excludedLlmMetadataKeys' => null,
            'llamaIndexObjectJson' => null,
            'metadata' => null,
            'text' => 'This is an example message'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response retrieved successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request failed: ' . $e->getMessage();
}
?>
```

Response Body

Status Code: 200

Example Response Schema

```
{
  "id": string (uuid)
  "fileName": string
  "pageNumber"?: integer // Optional
  "chatbotFile": string (uuid)
  "excludedEmbedMetadataKeys"?: object // List[str]: metadata keys to
exclude from the embedding. (Optional)
  "excludedLlmMetadataKeys"?: object // List[str]: metadata keys to
exclude from the LLM context. (Optional)
  "llamaIndexObjectJson"?: object // Optional
  "metadata"?: object // Optional
  "text": string
  "updatedAt": string (timestamp)
}
```

Example Response Values

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "fileName": "Response string",
  "pageNumber": 456,
  "chatbotFile": "550e8400-e29b-41d4-a716-446655440000",
  "excludedEmbedMetadataKeys": null,
  "excludedLlmMetadataKeys": null,
  "llamaIndexObjectJson": null,
  "metadata": null,
  "text": "Response string",
  "updatedAt": "Response string"
}
```

Delete a Document

DELETE `/api/v1/knowledge-bases/{knowledgeBasePk}/documents/{id}`

Parameters

Parameter Name	Required	Type	Description
`id`	V	string	A UUID string identifying this Chatbot Document.
`knowledgeBasePk`	V	string	

Code Examples

Shell/Bash

```
# API call example (Shell)
curl -X DELETE "https://api.maiagent.ai/api/v1/knowledge-
bases/550e8400-e29b-41d4-a716-446655440000/documents/550e8400-e29b-
41d4-a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Configure request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

// Request Body (payload)
const data = null;

axios.delete("https://api.maiagent.ai/api/v1/knowledge-
bases/550e8400-e29b-41d4-a716-446655440000/documents/550e8400-e29b-
41d4-a716-446655440000/", data, config)
  .then(response => {
    console.log('Response retrieved successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request failed:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-e29b-41d4-a716-446655440000/documents/550e8400-e29b-41d4-a716-446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.delete(url, headers=headers)
try:
    print("Response retrieved successfully:")
    print(response.json())
except Exception as e:
    print("Request failed:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>delete("https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-
e29b-41d4-a716-446655440000/documents/550e8400-e29b-41d4-a716-
446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response body

Status code	Description
204	No response body

Create a new FAQ

POST `/api/v1/knowledge-bases/{knowledgeBasePk}/faqs/`

Parameters

Parameter name	Required	Type	Description
knowledgeBasePk	V	string	

Request body

Request parameters

Field	Type	Required	Description
question	string	Yes	
answer	string	Yes	
answerMediaUrls	object	No	URLs of media files, such as images and videos, in the answer.
labels	array[IdName]	No	
rawUserDefineMetadata	object	No	

Example request schema

```
{
  "question": string
  "answer": string
  "answerMediaUrls"?: object // URLs of media files, such as images and
videos, in the answer. (Optional)
```

```
  "labels"?: [ // Optional
    {
      "id": string (uuid)
    }
  ]
  "rawUserDefineMetadata"?: object // Optional
}
```

Example request values

```
{
  "question": "Example string",
  "answer": "Example string",
  "answerMediaUrls": null,
  "labels": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000"
    }
  ],
  "rawUserDefineMetadata": null
}
```

Code examples

Shell/Bash

```
# API call example (Shell)
curl -X POST "https://api.maiagent.ai/api/v1/knowledge-
bases/550e8400-e29b-41d4-a716-446655440000/faqs/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "question": "Example string",
    "answer": "Example string",
    "answerMediaUrls": null,
    "labels": [
      {
        "id": "550e8400-e29b-41d4-a716-446655440000"
      }
    ],
    "rawUserDefineMetadata": null
  }'

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// Request body (payload)
const data = {
    "question": "Example string",
    "answer": "Example string",
    "answerMediaUrls": null,
    "labels": [
      {
        "id": "550e8400-e29b-41d4-a716-446655440000"
      }
    ],
    "rawUserDefineMetadata": null
  };

axios.post("https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-
e29b-41d4-a716-446655440000/faqs/", data, config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-e29b-
41d4-a716-446655440000/faqs/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# Request body (payload)
data = {
    "question": "Example string",
    "answer": "Example string",
    "answerMediaUrls": None,
    "labels": [
        {
            "id": "550e8400-e29b-41d4-a716-446655440000"
        }
    ],
    "rawUserDefineMetadata": None
}

response = requests.post(url, json=data, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>post("https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-e29b-
41d4-a716-446655440000/faqs/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'question' => 'Example string',
            'answer' => 'Example string',
            'answerMediaUrls' => null,
            'labels' => [
                [
                    'id' => '550e8400-e29b-41d4-a716-446655440000'
                ]
            ],
            'rawUserDefineMetadata' => null
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response body

Status code: 201

Example response schema

```
{
  "id": string (uuid)
  "question": string
  "answer": string
  "answerMediaUrls"?: object // URLs of media files, such as images and
videos, in the answer. (Optional)
  "hitsCount": integer
  "embeddingTokensCount": integer // Number of embedding tokens used to
create this FAQ.
  "labels"?: [ // Optional
    {
      "id": string (uuid)
      "name": string
    }
  ]
  "rawUserDefineMetadata"?: object // Optional
  "knowledgeBase":  // Always taken from the knowledge base in the URL; a
value in the request body is ignored.
  {
    "id": string (uuid)
    "name": string
  }
}
```

Example response values

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "question": "Response string",
  "answer": "Response string",
  "answerMediaUrls": null,
  "hitsCount": 456,
  "embeddingTokensCount": 456,
  "labels": [
    {
```

```
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "Response string"
    }
  ],
  "rawUserDefineMetadata": null,
  "knowledgeBase": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Response string"
  }
}
```


Update FAQ metadata

PATCH `/api/v1/knowledge-bases/{knowledgeBasePk}/faqs/{id}/update-metadata/`

Parameters

Parameter name	Required	Type	Description
`id`	V	string	A UUID string identifying this FAQ.
`knowledgeBasePk`	V	string	

Request body

Request parameters

Field	Type	Required	Description
labels	array[IdName]	No	
rawUserDefineMetadata	object	No	

Example request schema

```
{
  "labels"?: [ // Optional
    {
      "id": string (uuid)
    }
  ]
  "rawUserDefineMetadata"?: object // Optional
}
```

Example request values

```
{
  "labels": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000"
    }
  ],
  "rawUserDefineMetadata": null
}
```

Code examples

Shell/Bash

```
# API call example (Shell)
curl -X PATCH "https://api.maiagent.ai/api/v1/knowledge-
bases/550e8400-e29b-41d4-a716-446655440000/faqs/550e8400-e29b-41d4-
a716-446655440000/update-metadata/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "labels": [
      {
        "id": "550e8400-e29b-41d4-a716-446655440000"
      }
    ],
    "rawUserDefineMetadata": null
  }'

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// Request body (payload)
const data = {
    "labels": [
      {
        "id": "550e8400-e29b-41d4-a716-446655440000"
      }
    ],
    "rawUserDefineMetadata": null
  };

axios.patch("https://api.maiagent.ai/api/v1/knowledge-
bases/550e8400-e29b-41d4-a716-446655440000/faqs/550e8400-e29b-41d4-
a716-446655440000/update-metadata/", data, config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-e29b-
41d4-a716-446655440000/faqs/550e8400-e29b-41d4-a716-
446655440000/update-metadata/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# Request body (payload)
data = {
    "labels": [
        {
            "id": "550e8400-e29b-41d4-a716-446655440000"
        }
    ],
    "rawUserDefineMetadata": None
}

response = requests.patch(url, json=data, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>patch("https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-
e29b-41d4-a716-446655440000/faqs/550e8400-e29b-41d4-a716-
446655440000/update-metadata/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'labels' => [
                [
                    'id' => '550e8400-e29b-41d4-a716-446655440000'
                ]
            ],
            'rawUserDefineMetadata' => null
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response body

Status code: `200`

Example response schema

```
{
  "id": string (uuid)
  "question": string
  "answer": string
  "answerMediaUrls"?: object // URLs of media files, such as images and
videos, in the answer. (Optional)
  "hitsCount": integer
  "embeddingTokensCount": integer // Number of embedding tokens used to
create this FAQ.
  "labels"?: [ // Optional
    {
      "id": string (uuid)
      "name": string
    }
  ]
  "rawUserDefineMetadata"?: object // Optional
  "knowledgeBase":  // Always taken from the knowledge base in the URL; a
value in the request body is ignored.
  {
    "id": string (uuid)
    "name": string
  }
}
```

Example response values

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "question": "Response string",
  "answer": "Response string",
  "answerMediaUrls": null,
  "hitsCount": 456,
  "embeddingTokensCount": 456,
  "labels": [
    {
```

```
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "Response string"
    }
  ],
  "rawUserDefineMetadata": null,
  "knowledgeBase": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Response string"
  }
}
```


Batch delete FAQs

POST `/api/v1/knowledge-bases/{knowledgeBasePk}/faqs/batch-delete/`

Parameters

Parameter name	Required	Type	Description
knowledgeBasePk	V	string	

Request body

Request parameters

Field	Type	Required	Description
ids	array[string]	No	

Example request schema

```
{
  "ids"?: [ // Optional
    string (uuid)
  ]
}
```

Example request values

```
{
  "ids": [
    "550e8400-e29b-41d4-a716-446655440000"
  ]
}
```

Code examples

Shell/Bash

```
# API call example (Shell)
curl -X POST "https://api.maiagent.ai/api/v1/knowledge-
bases/550e8400-e29b-41d4-a716-446655440000/faqs/batch-delete/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "ids": [
      "550e8400-e29b-41d4-a716-446655440000"
    ]
  }'

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// Request body (payload)
const data = {
    "ids": [
      "550e8400-e29b-41d4-a716-446655440000"
    ]
  };

axios.post("https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-
e29b-41d4-a716-446655440000/faqs/batch-delete/", data, config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-e29b-
41d4-a716-446655440000/faqs/batch-delete/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# Request body (payload)
data = {
    "ids": [
        "550e8400-e29b-41d4-a716-446655440000"
    ]
}

response = requests.post(url, json=data, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>post("https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-e29b-
41d4-a716-446655440000/faqs/batch-delete/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'ids' => [
                '550e8400-e29b-41d4-a716-446655440000'
            ]
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response body

Status code	Description

204	No response body

List all FAQs in a specific knowledge base

GET `/api/v1/knowledge-bases/{knowledgeBasePk}/faqs/`

Parameters

Parameter name	Required	Type	Description
`knowledgeBasePk`	V	string	
`page`	X	integer	A page number within the paginated result set.
`pageSize`	X	integer	Number of results to return per page.
`query`	X	string	Search keywords. Supports multiple search criteria separated by spaces. Searchable fields: FAQ ID, question, answer, label name, and Metadata value

Code examples

Shell/Bash

```
# API call example (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/knowledge-
bases/550e8400-e29b-41d4-a716-446655440000/faqs/?
page=1&pageSize=1&query=example"

  -H "Authorization: Api-Key YOUR_API_KEY"

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-
e29b-41d4-a716-446655440000/faqs/?page=1&pageSize=1&query=example",
config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-e29b-41d4-a716-446655440000/faqs/?page=1&pageSize=1&query=example"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-e29b-
41d4-a716-446655440000/faqs/?page=1&pageSize=1&query=example", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response body

Status code: 200

Example response schema

```
{
  "count": integer
  "next"?: string (uri) // Optional
```

```
  "previous"?: string (uri) // Optional
  "results": [
    {
      "id": string (uuid)
      "question": string
      "answer": string
      "answerMediaUrls"?: object // URLs of media files, such as images
and videos, in the answer. (Optional)
      "hitsCount": integer
      "embeddingTokensCount": integer // Number of embedding tokens used
to create this FAQ.
      "labels"?: [ // Optional
        {
          "id": string (uuid)
          "name": string
        }
      ]
      "rawUserDefineMetadata"?: object // Optional
      "knowledgeBase":  // Always taken from the knowledge base in the
URL; a value in the request body is ignored.
      {
        "id": string (uuid)
        "name": string
      }
    }
  ]
}
```

Example response values

```
{
  "count": 123,
  "next": "http://api.example.org/accounts/?page=4",
  "previous": "http://api.example.org/accounts/?page=2",
  "results": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "question": "Response string",
      "answer": "Response string",
      "answerMediaUrls": null,
      "hitsCount": 456,
      "embeddingTokensCount": 456,
      "labels": [
        {
```

```
          "id": "550e8400-e29b-41d4-a716-446655440000",
          "name": "Response string"
        }
      ],
      "rawUserDefineMetadata": null,
      "knowledgeBase": {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "name": "Response string"
      }
    }
  ]
}
```


Retrieve details of a specific FAQ

GET `/api/v1/knowledge-bases/{knowledgeBasePk}/faqs/{id}`

Parameters

Parameter name	Required	Type	Description
`id`	V	string	A UUID string identifying this FAQ.
`knowledgeBasePk`	V	string	

Code examples

Shell/Bash

```
# API call example (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/knowledge-
bases/550e8400-e29b-41d4-a716-446655440000/faqs/550e8400-e29b-41d4-
a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-e29b-41d4-a716-446655440000/faqs/550e8400-e29b-41d4-a716-446655440000/", config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-e29b-41d4-a716-446655440000/faqs/550e8400-e29b-41d4-a716-446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-e29b-
41d4-a716-446655440000/faqs/550e8400-e29b-41d4-a716-446655440000/",
[
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response Body

Status Code: 200

Example Response Schema

```
{
  "id": string (uuid)
```

```
  "question": string
  "answer": string
  "answerMediaUrls"?: object // URLs of media files, such as images and
videos, in the answer. (Optional)
  "hitsCount": integer
  "embeddingTokensCount": integer // Number of embedding tokens used to
create this FAQ.
  "labels"?: [ // Optional
    {
      "id": string (uuid)
      "name": string
    }
  ]
  "rawUserDefineMetadata"?: object // Optional
  "knowledgeBase":  // Always taken from the knowledge base in the URL; a
value in the request body is ignored.
  {
    "id": string (uuid)
    "name": string
  }
}
```

Example Response Values

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "question": "Response string",
  "answer": "Response string",
  "answerMediaUrls": null,
  "hitsCount": 456,
  "embeddingTokensCount": 456,
  "labels": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "Response string"
    }
  ],
  "rawUserDefineMetadata": null,
  "knowledgeBase": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Response string"
```

```
    }
}
```

Update FAQ

PUT `/api/v1/knowledge-bases/{knowledgeBasePk}/faqs/{id}`

Parameters

Parameter Name	Required	Type	Description
`id`	V	string	A UUID string identifying this FAQ.
`knowledgeBasePk`	V	string	

Request Body

Request Parameters

Field	Type	Required	Description
question	string	Yes	
answer	string	Yes	
answerMediaUrls	object	No	URLs of media files, such as images and videos, in the answer.
labels	array[IdName]	No	
rawUserDefineMetadata	object	No	

Example Request Schema

```
{
  "question": string
  "answer": string
  "answerMediaUrls"?: object // URLs of media files, such as images and
videos, in the answer. (Optional)
  "labels"?: [ // Optional
    {
      "id": string (uuid)
    }
  ]
  "rawUserDefineMetadata"?: object // Optional
}
```

Example Request Values

```
{
  "question": "Example string",
  "answer": "Example string",
  "answerMediaUrls": null,
  "labels": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000"
    }
  ],
  "rawUserDefineMetadata": null
}
```

Code Examples

Shell/Bash

```
# API call example (Shell)
curl -X PUT "https://api.maiagent.ai/api/v1/knowledge-
bases/550e8400-e29b-41d4-a716-446655440000/faqs/550e8400-e29b-41d4-
a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "question": "Example string",
    "answer": "Example string",
    "answerMediaUrls": null,
    "labels": [
      {
        "id": "550e8400-e29b-41d4-a716-446655440000"
      }
    ],
    "rawUserDefineMetadata": null
  }'

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// Request Body (payload)
const data = {
    "question": "Example string",
    "answer": "Example string",
    "answerMediaUrls": null,
    "labels": [
      {
        "id": "550e8400-e29b-41d4-a716-446655440000"
      }
    ],
    "rawUserDefineMetadata": null
  };

axios.put("https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-
e29b-41d4-a716-446655440000/faqs/550e8400-e29b-41d4-a716-
446655440000/", data, config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-e29b-
41d4-a716-446655440000/faqs/550e8400-e29b-41d4-a716-446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# Request Body (payload)
data = {
    "question": "Example string",
    "answer": "Example string",
    "answerMediaUrls": None,
    "labels": [
        {
            "id": "550e8400-e29b-41d4-a716-446655440000"
        }
    ],
    "rawUserDefineMetadata": None
}

response = requests.put(url, json=data, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>put("https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-e29b-
41d4-a716-446655440000/faqs/550e8400-e29b-41d4-a716-446655440000/",
[
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'question' => 'Example string',
            'answer' => 'Example string',
            'answerMediaUrls' => null,
            'labels' => [
                [
                    'id' => '550e8400-e29b-41d4-a716-446655440000'
                ]
            ],
            'rawUserDefineMetadata' => null
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response Body

Status Code: 200

Example Response Schema

```
{
  "id": string (uuid)
  "question": string
  "answer": string
  "answerMediaUrls"?: object // URLs of media files, such as images and
videos, in the answer. (Optional)
  "hitsCount": integer
  "embeddingTokensCount": integer // Number of embedding tokens used to
create this FAQ.
  "labels"?: [ // Optional
    {
      "id": string (uuid)
      "name": string
    }
  ]
  "rawUserDefineMetadata"?: object // Optional
  "knowledgeBase":  // Always taken from the knowledge base in the URL; a
value in the request body is ignored.
  {
    "id": string (uuid)
    "name": string
  }
}
```

Example Response Values

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "question": "Response string",
  "answer": "Response string",
  "answerMediaUrls": null,
  "hitsCount": 456,
  "embeddingTokensCount": 456,
  "labels": [
    {
```

```
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "Response string"
    }
  ],
  "rawUserDefineMetadata": null,
  "knowledgeBase": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Response string"
  }
}
```


Partially Update FAQ

PATCH `/api/v1/knowledge-bases/{knowledgeBasePk}/faqs/{id}`

Parameters

Parameter Name	Required	Type	Description
`id`	V	string	A UUID string identifying this FAQ.
`knowledgeBasePk`	V	string	

Request Body

Request Parameters

Field	Type	Required	Description
question	string	No	
answer	string	No	

Field	Type	Required	Description
answerMediaUrls	object	No	URLs of media files, such as images and videos, in the answer.
labels	array[IdName]	No	
rawUserDefineMetadata	object	No	

Example Request Schema

```
{
  "question"?: string // Optional
  "answer"?: string // Optional
  "answerMediaUrls"?: object // URLs of media files, such as images and
videos, in the answer. (Optional)
  "labels"?: [ // Optional
    {
      "id": string (uuid)
    }
  ]
  "rawUserDefineMetadata"?: object // Optional
}
```

Example Request Values

```
{
  "question": "Example string",
  "answer": "Example string",
  "answerMediaUrls": null,
  "labels": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000"
    }
  ],
  "rawUserDefineMetadata": null
}
```

Code Examples

Shell/Bash

```
# API call example (Shell)
curl -X PATCH "https://api.maiagent.ai/api/v1/knowledge-
bases/550e8400-e29b-41d4-a716-446655440000/faqs/550e8400-e29b-41d4-
a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "question": "Example string",
    "answer": "Example string",
    "answerMediaUrls": null,
    "labels": [
      {
        "id": "550e8400-e29b-41d4-a716-446655440000"
      }
    ],
    "rawUserDefineMetadata": null
  }'

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// Request Body (payload)
const data = {
    "question": "Example string",
    "answer": "Example string",
    "answerMediaUrls": null,
    "labels": [
      {
        "id": "550e8400-e29b-41d4-a716-446655440000"
      }
    ],
    "rawUserDefineMetadata": null
  };

axios.patch("https://api.maiagent.ai/api/v1/knowledge-
bases/550e8400-e29b-41d4-a716-446655440000/faqs/550e8400-e29b-41d4-
a716-446655440000/", data, config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-e29b-41d4-a716-446655440000/faqs/550e8400-e29b-41d4-a716-446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# Request Body (payload)
data = {
    "question": "Example string",
    "answer": "Example string",
    "answerMediaUrls": None,
    "labels": [
        {
            "id": "550e8400-e29b-41d4-a716-446655440000"
        }
    ],
    "rawUserDefineMetadata": None
}

response = requests.patch(url, json=data, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>patch("https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-
e29b-41d4-a716-446655440000/faqs/550e8400-e29b-41d4-a716-
446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'question' => 'Example string',
            'answer' => 'Example string',
            'answerMediaUrls' => null,
            'labels' => [
                [
                    'id' => '550e8400-e29b-41d4-a716-446655440000'
                ]
            ],
            'rawUserDefineMetadata' => null
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response Body

Status Code: 200

Example Response Schema

```
{
  "id": string (uuid)
  "question": string
  "answer": string
  "answerMediaUrls"?: object // URLs of media files, such as images and
videos, in the answer. (Optional)
  "hitsCount": integer
  "embeddingTokensCount": integer // Number of embedding tokens used to
create this FAQ.
  "labels"?: [ // Optional
    {
      "id": string (uuid)
      "name": string
    }
  ]
  "rawUserDefineMetadata"?: object // Optional
  "knowledgeBase":  // Always taken from the knowledge base in the URL; a
value in the request body is ignored.
  {
    "id": string (uuid)
    "name": string
  }
}
```

Example Response Values

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "question": "Response string",
  "answer": "Response string",
  "answerMediaUrls": null,
  "hitsCount": 456,
  "embeddingTokensCount": 456,
  "labels": [
    {
```

```
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "Response string"
    }
  ],
  "rawUserDefineMetadata": null,
  "knowledgeBase": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Response string"
  }
}
```


Delete FAQ

DELETE `/api/v1/knowledge-bases/{knowledgeBasePk}/faqs/{id}`

Parameters

Parameter Name	Required	Type	Description
`id`	V	string	A UUID string identifying this FAQ.
`knowledgeBasePk`	V	string	

Code Examples

Shell/Bash

```
# API call example (Shell)
curl -X DELETE "https://api.maiagent.ai/api/v1/knowledge-
bases/550e8400-e29b-41d4-a716-446655440000/faqs/550e8400-e29b-41d4-
a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

// Request Body (payload)
const data = null;

axios.delete("https://api.maiagent.ai/api/v1/knowledge-
bases/550e8400-e29b-41d4-a716-446655440000/faqs/550e8400-e29b-41d4-
a716-446655440000/", data, config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-e29b-41d4-a716-446655440000/faqs/550e8400-e29b-41d4-a716-446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.delete(url, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>delete("https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-
e29b-41d4-a716-446655440000/faqs/550e8400-e29b-41d4-a716-
446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response Body

Status Code	Description
204	No response body

Export FAQ Excel (or a Blank Template)

GET `/api/v1/knowledge-bases/{id}/export-faq-excel/`

Parameters

Parameter Name	Required	Type	Description
`id`	V	string	A UUID string identifying this Knowledge Base.

Code Examples

Shell/Bash

```
# API call example (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/knowledge-
bases/550e8400-e29b-41d4-a716-446655440000/export-faq-excel/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-
e29b-41d4-a716-446655440000/export-faq-excel/", config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-e29b-41d4-a716-446655440000/export-faq-excel/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-e29b-
41d4-a716-446655440000/export-faq-excel/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response Body

Status Code: 200

Example Response Schema

```
{
  "id": string (uuid)
  "createdBy":
```

```
  {
    "id": string (uuid)
    "name": string
  }
  "organization"?: string (uuid) // Optional
  "embeddingModel": string (uuid)
  "rerankerModel": string (uuid)
  "name": string
  "description"?: string // Optional
  "numberOfRetrievedChunks"?: integer // Number of reference chunks to
retrieve; defaults to 12, with a minimum of 1 (Optional)
  "enableHyde"?: boolean // Enable HyDE; defaults to False (Optional)
  "similarityCutoff"?: number (double) // Similarity threshold; defaults
to 0.0, with a range of 0.0-1.0 (Optional)
  "enableRerank"?: boolean // Whether to enable reranking; defaults to
True (Optional)
  "enableRrf"?: boolean // Enable Reciprocal Rank Fusion for hybrid
search. Disable this if using a custom Elasticsearch without enterprise
license. (Optional)
  "vectorDatabaseType"?:  // Type of vector database: elasticsearch or
opensearch.

* `elasticsearch` - Elasticsearch
* `opensearch` - OpenSearch
* `oracle` - Oracle AI Database 26ai
* `synxdb` - SynxDB (Optional)
  {
  }
  "vectorDatabaseUrl"?: string // Custom vector database endpoint URL or
Oracle DSN. For Elasticsearch/OpenSearch: URL format (e.g.,
"https://host:9200"). For Oracle: DSN format (e.g.,
"host:1521/service_name"). (Optional)
  "vectorDatabaseApiKey"?: string // API Key for Elasticsearch. Not used
for OpenSearch. (Optional)
  "opensearchUsername"?: string // Username for OpenSearch Basic Auth.
(Optional)
  "opensearchPassword"?: string // Password for OpenSearch Basic Auth.
(Optional)
  "oracleUser"?: string // Oracle database username. (Optional)
  "oraclePassword"?: string // Oracle database password. (Optional)
  "synxdbUser"?: string // SynxDB database username. (Optional)
  "synxdbPassword"?: string // SynxDB database password. (Optional)
  "labels": [
    {
      "id": string (uuid)
```

```
      "name": string
    }
  ]
  "chatbots"?: [ // Optional
    {
      "id": string (uuid)
      "name": string
    }
  ]
  "groups"?: [ // List of groups that can access the knowledge base
(Optional)
    {
      "id": string (uuid)
      "name": string
    }
  ]
  "filesCount": integer // Return count of KnowledgeBaseFile excluding
processed files, conversation attachments, and soft-deleted.
  "vectorStorageSize": integer
  "chunksCount": integer
  "canUpdate": boolean // Return whether the current user can update this
resource.
  "canDelete": boolean // Return whether the current user can delete this
resource.
  "createdAt": string (timestamp)
  "updatedAt": string (timestamp)
}
```

Example Response Values

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "createdBy": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "response string"
  },
  "organization": "550e8400-e29b-41d4-a716-446655440000",
  "embeddingModel": "550e8400-e29b-41d4-a716-446655440000",
  "rerankerModel": "550e8400-e29b-41d4-a716-446655440000",
  "name": "response string",
  "description": "response string",
  "numberOfRetrievedChunks": 456,
  "enableHyde": false,
  "similarityCutoff": 456,
```

```
  "enableRerank": false,
  "enableRrf": false,
  "vectorDatabaseType": {},
  "vectorDatabaseUrl": "response string",
  "vectorDatabaseApiKey": "response string",
  "opensearchUsername": "response string",
  "opensearchPassword": "response string",
  "oracleUser": "response string",
  "oraclePassword": "response string",
  "synxdbUser": "response string",
  "synxdbPassword": "response string",
  "labels": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "response string"
    }
  ],
  "chatbots": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "response string"
    }
  ],
  "groups": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "response string"
    }
  ],
  "filesCount": 456,
  "vectorStorageSize": 456,
  "chunksCount": 456,
  "canUpdate": false,
  "canDelete": false,
  "createdAt": "response string",
  "updatedAt": "response string"
}
```


Import FAQ Excel (Asynchronous)

POST `/api/v1/knowledge-bases/{id}/import-faq-excel/`

Only one import job can run at a time for a knowledge base. Calling this endpoint while a job is running returns 409; use the FAQ import job endpoints below to check progress.

Parameters

Parameter Name	Required	Type	Description
`id`	V	string	A UUID string identifying this Knowledge Base.

Code Examples

Shell/Bash

```
# Example API call (Shell)
curl -X POST "https://api.maiagent.ai/api/v1/knowledge-
bases/550e8400-e29b-41d4-a716-446655440000/import-faq-excel/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -F "excelFile=@example_file.txt"

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');
const FormData = require('form-data');

// Create a FormData object
const formData = new FormData();
// Replace with the actual file
formData.append('excelFile',
* Actual file object *
, 'example_file.txt');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    ...formData.getHeaders()
  }
};

axios.post("https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-
e29b-41d4-a716-446655440000/import-faq-excel/", formData, config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-e29b-
41d4-a716-446655440000/import-faq-excel/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}

# Create file and form data
files = {
    'excelFile': ('example_file.txt', open('example_file.txt',
'rb'), 'text/plain')
}

response = requests.post(url, files=files, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>post("https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-e29b-
41d4-a716-446655440000/import-faq-excel/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ],
        'multipart' => [
            [
                'name' => 'excelFile',
                'contents' => fopen('example_file.txt', 'r'),
                'filename' => 'example_file.txt'
            ]
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response Body

Status Code: 202

Example Response Schema

```
{
  "jobId": string (uuid)
  "status": string (enum: pending, processing, done, failed) // *
`pending` - Pending
* `processing` - Processing
* `done` - Done
* `failed` - Failed
}
```

Example Response Values

```
{
  "jobId": "550e8400-e29b-41d4-a716-446655440000",
  "status": "pending"
}
```

Status Code: 409

Example Response Schema

```
{
  "detail": string
  "jobId": string (uuid)
}
```

Example Response Values

```
{
  "detail": "response string",
  "jobId": "550e8400-e29b-41d4-a716-446655440000"
}
```

List FAQ Import Jobs

`GET` `/api/v1/knowledge-bases/{id}/faq-import-jobs/`

Parameters

Parameter Name	Required	Type	Description
`id`	V	string	A UUID string identifying this Knowledge Base.
`embeddingModel`	X	string	
`page`	X	integer	A page number within the paginated result set.
`pageSize`	X	integer	Number of results to return per page.
`pagination`	X	boolean	Set to false to return all jobs without pagination (defaults to true).
`query`	X	string	
`rerankerModel`	X	string	

Code Examples

Shell/Bash

```
# Example API call (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/knowledge-
bases/550e8400-e29b-41d4-a716-446655440000/faq-import-jobs/?
embeddingModel=550e8400-e29b-41d4-a716-
446655440000&page=1&pageSize=1&pagination=true&query=example&reranke
rModel=550e8400-e29b-41d4-a716-446655440000"

  -H "Authorization: Api-Key YOUR_API_KEY"

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-e29b-41d4-a716-446655440000/faq-import-jobs/?embeddingModel=550e8400-e29b-41d4-a716-446655440000&page=1&pageSize=1&pagination=true&query=example&rerankerModel=550e8400-e29b-41d4-a716-446655440000", config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-e29b-41d4-a716-446655440000/faq-import-jobs/?embeddingModel=550e8400-e29b-41d4-a716-446655440000&page=1&pageSize=1&pagination=true&query=example&rerankerModel=550e8400-e29b-41d4-a716-446655440000"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-e29b-
41d4-a716-446655440000/faq-import-jobs/?embeddingModel=550e8400-
e29b-41d4-a716-
446655440000&page=1&pageSize=1&pagination=true&query=example&reranke
rModel=550e8400-e29b-41d4-a716-446655440000", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response

Status Code: 200

Example Response Schema

```
{
  "count": integer
  "next"?: string (uri) // Optional
  "previous"?: string (uri) // Optional
  "results": [
    {
      "id": string (uuid)
      "status":
      {
      }
      "totalRows": integer
      "processedRows": integer
      "createdCount": integer
      "skippedDuplicateCount": integer // Rows skipped because their
whitespace-normalized question already exists in the knowledge base or
appears earlier in the same file.
      "errors": object // Row-level parse errors and chunk-level import
errors.
      "createdAt": string (timestamp)
      "updatedAt": string (timestamp)
    }
  ]
}
```

Example Response Values

```
{
  "count": 123,
  "next": "http://api.example.org/accounts/?page=4",
  "previous": "http://api.example.org/accounts/?page=2",
  "results": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "status": {},
      "totalRows": 456,
      "processedRows": 456,
      "createdCount": 456,
      "skippedDuplicateCount": 456,
      "errors": null,
      "createdAt": "response string",
      "updatedAt": "response string"
    }
```

```
  ]
}
```

Retrieve a Specific FAQ Import Job

GET `/api/v1/knowledge-bases/{id}/faq-import-jobs/{jobId}`

Parameters

Parameter Name	Required	Type	Description
`id`	V	string	A UUID string identifying this Knowledge Base.
`jobId`	V	string	

Code Examples

Shell/Bash

```
# Example API call (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/knowledge-
bases/550e8400-e29b-41d4-a716-446655440000/faq-import-jobs/{jobId}
"

  -H "Authorization: Api-Key YOUR_API_KEY"

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-
e29b-41d4-a716-446655440000/faq-import-jobs/{jobId}
", config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-e29b-
41d4-a716-446655440000/faq-import-jobs/{jobId}
"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/knowledge-bases/550e8400-e29b-
41d4-a716-446655440000/faq-import-jobs/{jobId}
", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response

Status Code: 200

Example Response Schema

```
{
  "id": string (uuid)
```

```
  "status":
  {
  }
  "totalRows": integer
  "processedRows": integer
  "createdCount": integer
  "skippedDuplicateCount": integer // Rows skipped because their
whitespace-normalized question already exists in the knowledge base or
appears earlier in the same file.
  "errors": object // Row-level parse errors and chunk-level import
errors.
  "createdAt": string (timestamp)
  "updatedAt": string (timestamp)
}
```

Example Response Values

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "status": {},
  "totalRows": 456,
  "processedRows": 456,
  "createdCount": 456,
  "skippedDuplicateCount": 456,
  "errors": null,
  "createdAt": "response string",
  "updatedAt": "response string"
}
```

List Parsers

GET `/api/v1/parsers/`

When uploading a file to a knowledge base, set the parser field to the parser id returned by this endpoint.

Code Examples

Shell/Bash

```
# API call example (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/parsers/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/parsers/", config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/parsers/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/parsers/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response

Status Code: 200

Example Response Schema

```
[
  {
    "id": string (uuid)
    "name": string
```

```
    "description": string
    "provider":
    {
    }
    "order"?: integer // Optional
    "isTimestampSttProvider": boolean
    "asrProvider": object // The provider spec, built once per provider
row per response.

The spec is platform-level, not per parser, and it is large — a
whisper-family row carries a 100-entry language catalog in its
``languages`` spec, as codes plus display names. This serializer is
nested per row in the knowledge-base file listing and in message
citations, so without memoizing, one response rebuilds the same
catalog for every row. ``self.context`` is the root serializer's shared
dict, which is also what keeps ``get_active_diarization_rows`` at one
query per response.
  }
]
```

Example Response Values

```
[
  {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Response string",
    "description": "Response string",
    "provider": {},
    "order": 456,
    "isTimestampSttProvider": false,
    "asrProvider": {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "Example response name",
      "description": "Example response description"
    }
  }
]
```

Retrieve a Specific Parser

GET `/api/v1/parsers/{id}`

Parameters

Parameter Name	Required	Type	Description
`id`	V	string	A UUID string identifying this parser.

Code Examples

Shell/Bash

```
# API call example (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/parsers/550e8400-e29b-
41d4-a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/parsers/550e8400-e29b-
41d4-a716-446655440000/", config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/parsers/550e8400-e29b-41d4-
a716-446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/parsers/550e8400-e29b-41d4-
a716-446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response

Status Code: 200

Example Response Schema

```
{
  "id": string (uuid)
  "name": string
```

```
  "description": string
  "provider":
  {
  }
  "order"?: integer // Optional
  "isTimestampSttProvider": boolean
  "asrProvider": object // The provider spec, built once per provider row
per response.

The spec is platform-level, not per parser, and it is large — a
whisper-family row carries a 100-entry language catalog in its
``languages`` spec, as codes plus display names. This serializer is
nested per row in the knowledge-base file listing and in message
citations, so without memoizing, one response rebuilds the same
catalog for every row. ``self.context`` is the root serializer's shared
dict, which is also what keeps ``get_active_diarization_rows`` at one
query per response.
}
```

Example Response Values

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "name": "Response string",
  "description": "Response string",
  "provider": {},
  "order": 456,
  "isTimestampSttProvider": false,
  "asrProvider": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Example response name",
    "description": "Example response description"
  }
}
```

API call example (Shell)

目錄

1. List Knowledge Base Files for an AI Assistant
2. List Knowledge Base FAQs for an AI Assistant
3. Retrieve text nodes from all files for an AI assistant
4. Retrieve a text node from a specific file for an AI assistant
5. Search Test
6. List parsers supported by file type

API call example (Shell)

List Knowledge Base Files for an AI Assistant

`GET` `/api/v1/chatbots/{id}/knowledge-bases-files/`

Parameters

Parameter Name	Required	Type	Description
`id`	V	string	
`createdByMember`	X	string	Creator filter: the id of a member in this organization (the id returned by the member directory, including deactivated members). Returns only AI assistants created by that member.
`largeLanguageModel`	X	string	
`page`	X	integer	A page number within the paginated result set.
`pageSize`	X	integer	Number of results to return per page.
`query`	X	string	

`replyMode`	X	string	
`source`	X	string	`self_built`: self_built ; `built_in`: built_in ; `all`: all;

Code Examples

Shell/Bash

```
# API call example (Shell)
curl -X GET "

  -H "Authorization: Api-Key YOUR_API_KEY"

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get(" config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->get(" [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response

Status Code: 200

Example Response Schema

```
{
  "count": integer
  "next"?: string (uri) // Optional
  "previous"?: string (uri) // Optional
  "results": [
```

```
    {
      "id": string (uuid)
      "filename": string // File name
      "file": string (uri) // File to upload
      "fileType": string
      "knowledgeBase"?:  // Optional
      {
        "id": string (uuid)
        "name": string
      }
      "size": integer // File size in bytes
      "status":
      {
      }
      "parser":
      {
        "id": string (uuid)
        "name": string
        "provider":
        {
        }
        "isTimestampSttProvider": boolean
      }
      "labels"?: [ // Optional
        {
          "id": string (uuid)
          "name": string
        }
      ]
      "rawUserDefineMetadata"?: object // Optional
      "speakerLabels": [
        {
          "id": string (uuid)
          "originalLabel": string // Original speaker label from
diarization (e.g., SPEAKER_00)
          "customName"?: string // User-defined speaker name (e.g., John)
(Optional)
          "displayName": string
        }
      ]
      "vectorStorageSize": integer // Size of vectors for this file in
Elasticsearch (bytes)
      "chunksCount": integer // Number of chunks/nodes generated from
this file
      "waitingTime": number (double)
```

```
      "processingTime": number (double)
      "processingTimeDetails": object
      "ocrStatus": string // OCR result for scanned pages: done, skipped,
partial, or off; null before parsing or for older files
      "ocrSkippedReason": string // Reason OCR was not performed on
scanned pages: no_azure_settings, azure_unavailable,
insufficient_credits, transient_error, time_budget, or disabled; null
when OCR completed
      "parserAutoDetection":  // Result and reason for automatic parser
selection for this file; null for files with a manually selected parser,
files uploaded before this feature launched, or files queued for
reassessment
      {
        "parser":  // Parser selected by automatic detection
        {
          "id": string (uuid)
          "name": string
          "provider":
          {
          }
          "isTimestampSttProvider": boolean
        }
        "reason": string // Reason category: scanned, image_pages,
large_images, unmeasurable_images, presentation, no_image_content,
below_threshold, no_content, file_type_not_detected, detection_failed, or
vision_unavailable; more categories may be added later, so display a
generic message when no matching text is available
        "facts": object // Numeric facts supporting the reason
(calculated at assessment time and not recalculated later). PDF:
analyzed_pages (number of pages examined), partial (whether only the
first few pages were examined), non_blank_pages, scanned_pages,
image_pages (pages requiring visual interpretation); Word: figures
(number of large images in the body), text_chars (number of characters in
the body); an empty object in other cases
        "detectedAt": string (timestamp) // Assessment time
      }
      "previewUrl": string // For presentations (pptx/ppt), returns the
URL of a derived pdf file for preview (displayed using the PDF viewer on
the frontend); None for other files.

Generate the URL with the same CustomizedFileFieldSerializer used for the
`file` field to ensure a consistent format (including each
storage provider's presign/host rules). Do not use get_absolute_url(),
which produces an incorrectly formatted URL.
      "createdAt": string (timestamp)
```

```
    }
  ]
}
```

Example Response Values

```
{
  "count": 123,
  "next": "http://api.example.org/accounts/?page=4",
  "previous": "http://api.example.org/accounts/?page=2",
  "results": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "filename": "Response string",
      "file": "https://example.com/file.jpg",
      "fileType": "Response string",
      "knowledgeBase": {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "name": "Response string"
      },
      "size": 456,
      "status": {},
      "parser": {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "name": "Response string",
        "provider": {},
        "isTimestampSttProvider": false
      },
      "labels": [
        {
          "id": "550e8400-e29b-41d4-a716-446655440000",
          "name": "Response string"
        }
      ],
      "rawUserDefineMetadata": null,
      "speakerLabels": [
        {
          "id": "550e8400-e29b-41d4-a716-446655440000",
          "originalLabel": "Response string",
          "customName": "Response string",
          "displayName": "Response string"
        }
      ],
      "vectorStorageSize": 456,
```

```
      "chunksCount": 456,
      "waitingTime": 456,
      "processingTime": 456,
      "processingTimeDetails": null,
      "ocrStatus": "Response string",
      "ocrSkippedReason": "Response string",
      "parserAutoDetection": {
        "parser": {
          "id": "550e8400-e29b-41d4-a716-446655440000",
          "name": "Response string",
          "provider": {},
          "isTimestampSttProvider": false
        },
        "reason": "Response string",
        "facts": {
          "id": "550e8400-e29b-41d4-a716-446655440000",
          "name": "Example response name",
          "description": "Example response description"
        },
        "detectedAt": "Response string"
      },
      "previewUrl": "Response string",
      "createdAt": "Response string"
    }
  ]
}
```


List Knowledge Base FAQs for an AI Assistant

`GET` `/api/v1/chatbots/{id}/knowledge-bases-faqs/`

Parameters

Parameter Name	Required	Type	Description
`id`	V	string	

`createdByMember`	X	string	Creator filter: the ID of a member in this organization (the ID returned by the member roster, including deactivated members). Returns only AI assistants created by that member.
`largeLanguageModel`	X	string	
`page`	X	integer	A page number within the paginated result set.
`pageSize`	X	integer	Number of results to return per page.
`query`	X	string	
`replyMode`	X	string	
`source`	X	string	`self_built`: self_built ; `built_in`: built_in ; `all`: all;

Code Examples

Shell/Bash

```
# Example API call (Shell)
curl -X GET "

  -H "Authorization: Api-Key YOUR_API_KEY"

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get(" config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->get(" [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response

Status Code: 200

Example Response Schema

```
{
  "count": integer
  "next"?: string (uri) // Optional
  "previous"?: string (uri) // Optional
  "results": [
```

```
    {
      "id": string (uuid)
      "question": string
      "answer": string
      "answerMediaUrls"?: object // URLs of media files, such as images
and videos, in the answer. (Optional)
      "hitsCount": integer
      "embeddingTokensCount": integer // Number of embedding tokens used
to create this FAQ.
      "labels"?: [ // Optional
        {
          "id": string (uuid)
          "name": string
        }
      ]
      "rawUserDefineMetadata"?: object // Optional
      "knowledgeBase":  // Always taken from the knowledge base in the
URL; a value in the request body is ignored.
      {
        "id": string (uuid)
        "name": string
      }
    }
  ]
}
```

Example Response Values

```
{
  "count": 123,
  "next": "http://api.example.org/accounts/?page=4",
  "previous": "http://api.example.org/accounts/?page=2",
  "results": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "question": "response string",
      "answer": "response string",
      "answerMediaUrls": null,
      "hitsCount": 456,
      "embeddingTokensCount": 456,
      "labels": [
        {
          "id": "550e8400-e29b-41d4-a716-446655440000",
          "name": "response string"
```

```
        }
      ],
      "rawUserDefineMetadata": null,
      "knowledgeBase": {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "name": "response string"
      }
    }
  ]
}
```


Retrieve text nodes from all files for an AI assistant

GET `/api/v1/chatbot-text-nodes/`

Parameters

Parameter name	Required	Type	Description
`chatbotFile`	X	string	[To be deprecated] Chatbot file ID (use knowledge_base_file)
`knowledgeBaseFile`	X	string	Knowledge base file ID (recommended)
`page`	X	integer	A page number within the paginated result set.
`pageSize`	X	integer	Number of results to return per page.

Code examples

Shell/Bash

```
# Example API call (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/chatbot-text-nodes/?
chatbotFile=example&knowledgeBaseFile=example&page=1&pageSize=1"

  -H "Authorization: Api-Key YOUR_API_KEY"

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/chatbot-text-nodes/?
chatbotFile=example&knowledgeBaseFile=example&page=1&pageSize=1",
config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request failed:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/chatbot-text-nodes/?
chatbotFile=example&knowledgeBaseFile=example&page=1&pageSize=1"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request failed:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/chatbot-text-nodes/?
chatbotFile=example&knowledgeBaseFile=example&page=1&pageSize=1", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request failed: ' . $e->getMessage();
}
?>
```

Response content

Status code: 200

Example response schema

```
{
  "count": integer
  "next"?: string (uri) // Optional
```

```
  "previous"?: string (uri) // Optional
  "results": [
    {
      "id": string (uuid)
      "charactersCount": integer
      "hitsCount": integer
      "text": string
      "updatedAt": string (timestamp)
      "filename": string
      "chatbotFile": object // Return complete ChatbotFile information,
including the file URL and type, to support image previews in the
frontend
      "knowledgeBaseFile": object // Same as get_chatbot_file, for
backward compatibility
      "pageNumber": integer // Backward-compatible alias of
``page_start``.
      "pageStart": integer
      "pageEnd": integer
      "citationTitle": string // Source title shown on the inline
citation hover card.
      "citationDescription": string // Source description shown on the
inline citation hover card.
      "citationQuote": string // Quoted text snippet shown on the inline
citation hover card.
      "hasImage": boolean // Determine whether images are present (check
the file type or Markdown images in text)
      "imageUrl": string // Extract the image URL (use the file URL if
available; otherwise, extract it from Markdown)
      "displayText": string // Return the full text with Markdown image
markup removed
      "displayTitle": string // Return the display title (fallback:
citation_title -> filename)
      "highlightedText": string // Return text with matched terms wrapped
in ``<mark>`` tags.

Priority:
1. ES/OpenSearch native highlight (set by retrieve_api via
``_es_highlighted_text``)
2. Python regex fallback (keyword-based, works for all backends)
      "labels": [
        {
          "id": string (uuid)
          "name": string
        }
      ]
```

```
      "rawUserDefineMetadata"?: object // Metadata keys and values
defined by the user. (Optional)
      "metadataEnabledForSearch": object // Map each user-defined
metadata key on this node to whether it was sent into the LLM.

A key reaches the LLM only when its ``MetadataKey.enabled_for_search`` is
True *and*
the node carries a value for it. Since this maps over
``raw_user_define_metadata``
(the keys the cited-documents block displays, all of which have a value),
``enabled_for_search`` alone decides the flag. The source of truth is the
node's
knowledge base ``MetadataKey`` current setting, matching the AI Search
indicator.
      "startCharIdx": integer
      "endCharIdx": integer
    }
  ]
}
```

Example response values

```
{
  "count": 123,
  "next": "http://api.example.org/accounts/?page=4",
  "previous": "http://api.example.org/accounts/?page=2",
  "results": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "charactersCount": 456,
      "hitsCount": 456,
      "text": "Response string",
      "updatedAt": "Response string",
      "filename": "Response string",
      "chatbotFile": {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "name": "Example response name",
        "description": "Example response description"
      },
      "knowledgeBaseFile": {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "name": "Example response name",
        "description": "Example response description"
      },
```

```
      "pageNumber": 456,
      "pageStart": 456,
      "pageEnd": 456,
      "citationTitle": "Response string",
      "citationDescription": "Response string",
      "citationQuote": "Response string",
      "hasImage": false,
      "imageUrl": "Response string",
      "displayText": "Response string",
      "displayTitle": "Response string",
      "highlightedText": "Response string",
      "labels": [
        {
          "id": "550e8400-e29b-41d4-a716-446655440000",
          "name": "Response string"
        }
      ],
      "rawUserDefineMetadata": null,
      "metadataEnabledForSearch": {
        "key1": "value1",
        "key2": "value2",
        "createdAt": "2025-01-01T00:00:00.000Z"
      },
      "startCharIdx": 456,
      "endCharIdx": 456
    }
  ]
}
```


Status code: 403 - You do not have permission to read text nodes from this file: knowledge base files require chatbot_knowledge_base_access and group access to the knowledge base; conversation attachments require chatbot_chatbot_access for the assistant; inbox files require group access to the inbox

Status code: 404 - The knowledge base file does not exist or does not belong to the current organization

Retrieve a text node from a specific file for an AI assistant

GET `/api/v1/chatbot-text-nodes/{id}`

Parameters

Parameter name	Required	Type	Description
`id`	V	string	A UUID string identifying this ChatbotTextNode.

Code examples

Shell/Bash

```
# Example API call (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/chatbot-text-
nodes/550e8400-e29b-41d4-a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/chatbot-text-
nodes/550e8400-e29b-41d4-a716-446655440000/", config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request failed:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/chatbot-text-nodes/550e8400-
e29b-41d4-a716-446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request failed:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/chatbot-text-nodes/550e8400-
e29b-41d4-a716-446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request failed: ' . $e->getMessage();
}
?>
```

Response content

Status code: 200

Example response schema

```
{
  "id": string (uuid)
  "charactersCount": integer
```

```
  "hitsCount": integer
  "text": string
  "updatedAt": string (timestamp)
  "filename": string
  "chatbotFile": object // Return complete ChatbotFile information,
including the file URL and type, to support image previews in the
frontend
  "knowledgeBaseFile": object // Same as get_chatbot_file, for backward
compatibility
  "pageNumber": integer // Backward-compatible alias of ``page_start``.
  "pageStart": integer
  "pageEnd": integer
  "citationTitle": string // Source title shown on the inline citation
hover card.
  "citationDescription": string // Source description shown on the inline
citation hover card.
  "citationQuote": string // Quoted text snippet shown on the inline
citation hover card.
  "hasImage": boolean // Determine whether images are present (check the
file type or Markdown images in text)
  "imageUrl": string // Extract the image URL (use the file URL if
available; otherwise, extract it from Markdown)
  "displayText": string // Return the full text with Markdown image
markup removed
  "displayTitle": string // Return the display title (fallback:
citation_title -> filename)
  "highlightedText": string // Return text with matched terms wrapped in
``<mark>`` tags.

Priority:
1. ES/OpenSearch native highlight (set by retrieve_api via
``_es_highlighted_text``)
2. Python regex fallback (keyword-based, works for all backends)
  "labels": [
    {
      "id": string (uuid)
      "name": string
    }
  ]
  "rawUserDefineMetadata"?: object // Metadata keys and values defined by
the user. (Optional)
  "metadataEnabledForSearch": object // Map each user-defined metadata
key on this node to whether it was sent into the LLM.

A key reaches the LLM only when its ``MetadataKey.enabled_for_search`` is
```

```
True *and*
the node carries a value for it. Since this maps over
``raw_user_define_metadata``
(the keys the cited-documents block displays, all of which have a value),
``enabled_for_search`` alone decides the flag. The source of truth is the
node's
knowledge base ``MetadataKey`` current setting, matching the AI Search
indicator.
  "startCharIdx": integer
  "endCharIdx": integer
}
```

Example Response Values


```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "charactersCount": 456,
  "hitsCount": 456,
  "text": "Response string",
  "updatedAt": "Response string",
  "filename": "Response string",
  "chatbotFile": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Example response name",
    "description": "Example response description"
  },
  "knowledgeBaseFile": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Example response name",
    "description": "Example response description"
  },
  "pageNumber": 456,
  "pageStart": 456,
  "pageEnd": 456,
  "citationTitle": "Response string",
  "citationDescription": "Response string",
  "citationQuote": "Response string",
  "hasImage": false,
  "imageUrl": "Response string",
  "displayText": "Response string",
  "displayTitle": "Response string",
  "highlightedText": "Response string",
  "labels": [
    {
```

```
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "Response string"
    }
  ],
  "rawUserDefineMetadata": null,
  "metadataEnabledForSearch": {
    "key1": "value1",
    "key2": "value2",
    "createdAt": "2025-01-01T00:00:00.000Z"
  },
  "startCharIdx": 456,
  "endCharIdx": 456
}
```


Search Test

POST `/api/v1/chatbots/{id}/search/`

Parameters

Parameter Name	Required	Type	Description
`id`	V	string	
`createdByMember`	X	string	Creator filter: the ID of a member of this organization (the ID returned by the member roster, including deactivated members). Returns only AI assistants created by that member.
`largeLanguageModel`	X	string	
`page`	X	integer	A page number within the paginated result set.
`pageSize`	X	integer	Number of results to return per page.

`query`	X	string	
`replyMode`	X	string	
`source`	X	string	`self_built`: self_built ; `built_in`: built_in ; `all`: all;

Request Body

Request Parameters

Field	Type	Required	Description
queryMetadata	object	No	Not supported for chatbot-wide search; providing a value returns 400.

Example Request Schema

```
{
  "queryMetadata"?: object // Not supported for chatbot-wide search;
providing a value returns 400. (Optional)
}
```

Example Request Values

```
{
  "queryMetadata": null
}
```

Code Examples

Shell/Bash

```
# API call example (Shell)
curl -X POST "

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "query": "Example string",
    "queryMetadata": null
  }'

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// Request Body (payload)
const data = {
    "query": "Example string",
    "queryMetadata": null
  };

axios.post(" data, config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# Request Body (payload)
data = {
    "query": "Example string",
    "queryMetadata": None
}

response = requests.post(url, json=data, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->post(" [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'query' => 'Example string',
            'queryMetadata' => null
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response Body

Status Code: 200

Example Response Schema

```
{
  "count": integer
  "next"?: string (uri) // Optional
  "previous"?: string (uri) // Optional
  "results": [
    {
      "id": string (uuid)
      "charactersCount": integer
      "hitsCount": integer
      "text": string
      "updatedAt": string (timestamp)
      "filename": string
      "chatbotFile": object // Returns complete ChatbotFile information,
including the file URL and type, to support image previews in the
frontend.
      "knowledgeBaseFile": object // Same as get_chatbot_file, for
backward compatibility.
      "pageNumber": integer // Backward-compatible alias of
``page_start``.
      "pageStart": integer
      "pageEnd": integer
      "citationTitle": string // Source title shown on the inline
citation hover card.
      "citationDescription": string // Source description shown on the
inline citation hover card.
      "citationQuote": string // Quoted text snippet shown on the inline
citation hover card.
      "hasImage": boolean // Checks whether images are present (by
checking the file type or Markdown images in text).
      "imageUrl": string // Extracts the image URL (uses the file URL
first; otherwise extracts it from Markdown).
      "displayText": string // Returns the full text with Markdown image
markup removed.
      "displayTitle": string // Returns the display title (fallback:
citation_title -> filename).
      "highlightedText": string // Return text with matched terms wrapped
in ``<mark>`` tags.

Priority:
1. ES/OpenSearch native highlight (set by retrieve_api via
``_es_highlighted_text``)
2. Python regex fallback (keyword-based, works for all backends)
      "labels": [
        {
```

```
          "id": string (uuid)
          "name": string
        }
      ]
      "rawUserDefineMetadata"?: object // Metadata keys and values
defined by the user. (Optional)
      "metadataEnabledForSearch": object // Map each user-defined
metadata key on this node to whether it was sent into the LLM.

A key reaches the LLM only when its ``MetadataKey.enabled_for_search`` is
True *and*
the node carries a value for it. Since this maps over
``raw_user_define_metadata``
(the keys the cited-documents block displays, all of which have a value),
``enabled_for_search`` alone decides the flag. The source of truth is the
node's
knowledge base ``MetadataKey`` current setting, matching the AI Search
indicator.
      "startCharIdx": integer
      "endCharIdx": integer
    }
  ]
}
```

Example Response Values

```
{
  "count": 123,
  "next": "http://api.example.org/accounts/?page=4",
  "previous": "http://api.example.org/accounts/?page=2",
  "results": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "charactersCount": 456,
      "hitsCount": 456,
      "text": "Response string",
      "updatedAt": "Response string",
      "filename": "Response string",
      "chatbotFile": {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "name": "Example response name",
        "description": "Example response description"
      },
      "knowledgeBaseFile": {
```

```
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "name": "Example response name",
        "description": "Example response description"
      },
      "pageNumber": 456,
      "pageStart": 456,
      "pageEnd": 456,
      "citationTitle": "Response string",
      "citationDescription": "Response string",
      "citationQuote": "Response string",
      "hasImage": false,
      "imageUrl": "Response string",
      "displayText": "Response string",
      "displayTitle": "Response string",
      "highlightedText": "Response string",
      "labels": [
        {
          "id": "550e8400-e29b-41d4-a716-446655440000",
          "name": "Response string"
        }
      ],
      "rawUserDefineMetadata": null,
      "metadataEnabledForSearch": {
        "key1": "value1",
        "key2": "value2",
        "createdAt": "2025-01-01T00:00:00.000Z"
      },
      "startCharIdx": 456,
      "endCharIdx": 456
    }
  ]
}
```


List parsers supported by file type

GET `/api/v1/parsers/supported-file-types/`

Parameters

Parameter name	Required	Type	Description
`knowledgeBaseId`	X	string	Knowledge base ID. When provided and the knowledge base does not support multimodal embeddings, image file types will be filtered out.

Code examples

Shell/Bash

```
# API call example (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/parsers/supported-file-types/?knowledgeBaseId=example"

  -H "Authorization: Api-Key YOUR_API_KEY"

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/parsers/supported-file-types/?knowledgeBaseId=example", config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/parsers/supported-file-types/?
knowledgeBaseId=example"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/parsers/supported-file-types/?
knowledgeBaseId=example", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response body

Status code: 200

Example response schema

```
[
  {
    "fileType": string
```

```
    "parsers": [
      {
        "id": string (uuid)
        "name": string
        "description": string
        "provider":
        {
        }
        "order"?: integer // Optional
        "isTimestampSttProvider": boolean
        "asrProvider": object // The provider spec, built once per
provider row per response.

The spec is platform-level, not per parser, and it is large — a
whisper-family row carries a 100-entry language catalog in its
``languages`` spec, as codes plus display names. This serializer is
nested per row in the knowledge-base file listing and in message
citations, so without memoizing, one response rebuilds the same
catalog for every row. ``self.context`` is the root serializer's shared
dict, which is also what keeps ``get_active_diarization_rows`` at one
query per response.
      }
    ]
    "autoDetect": boolean // Whether files of this type get parser auto-
detection after upload
(the system auto-detects a parser when the user did not choose one).
  }
]
```

Example response values

```
[
  [
    {
      "fileType": ".pdf",
      "parsers": [
        {
          "id": "ab83f144-5026-4bce-993f-5c982cc19318",
          "name": "MaiAgent Parser",
          "provider": "maiagent",
          "order": 0,
          "isDefault": true,
          "visionTier": null,
          "pricingBasis": "page",
```

```
          "creditsPerPage": "13.3",
          "pricingSource": "measured",
          "pricingNote": "Scanned pages incur an additional OCR charge of
19.8 credits/page"
        },
        {
          "id": "6d0f4c5e-2f1a-4c47-9a7e-7f4b8f0c2a11",
          "name": "MaiAgent Vision Parser",
          "provider": "anthropic",
          "order": 1,
          "isDefault": false,
          "visionTier": "high_quality",
          "pricingBasis": "page",
          "creditsPerPage": null,
          "pricingSource": null,
          "pricingNote": "Billed by the amount of page content; the
displayed value is the average over the past 30 days"
        },
        {
          "id": "9b1c7d2e-4f3a-4e8b-a6d5-0c2f8e9a7b14",
          "name": "MaiAgent OCR Parser (CPU)",
          "provider": "docling",
          "order": 5,
          "isDefault": false,
          "visionTier": null,
          "pricingBasis": null,
          "creditsPerPage": null,
          "pricingSource": null,
          "pricingNote": null
        },
        {
          "id": "8b2f6d14-0c3e-4a7b-9e51-2d6f8a0c4e97",
          "name": "MaiAgent Vision Parser (Gemma 4 31B)",
          "provider": "anthropic",
          "order": 3,
          "isDefault": false,
          "visionTier": "high_quality",
          "pricingBasis": "page",
          "creditsPerPage": "22.275",
          "pricingSource": "reference",
          "pricingNote": "Reference price; actual charges depend on
tokens and the number of OCR pages"
        }
      ]
    },
```

```
    {
      "fileType": ".doc",
      "parsers": [
        {
          "id": "ab83f144-5026-4bce-993f-5c982cc19318",
          "name": "MaiAgent Parser",
          "provider": "maiagent",
          "order": 0,
          "isDefault": true
        },
        {
          "id": "6d0f4c5e-2f1a-4c47-9a7e-7f4b8f0c2a11",
          "name": "MaiAgent Vision Parser",
          "provider": "anthropic",
          "order": 1,
          "isDefault": false
        }
      ]
    },
    {
      "fileType": ".docx",
      "parsers": [
        {
          "id": "ab83f144-5026-4bce-993f-5c982cc19318",
          "name": "MaiAgent Parser",
          "provider": "maiagent",
          "order": 0,
          "isDefault": true
        },
        {
          "id": "22fdcbb5-f075-4aad-bb81-048289ca4b25",
          "name": "MaiAgent Parser (Online)",
          "provider": "llama",
          "order": 2,
          "isDefault": false
        }
      ]
    },
    {
      "fileType": ".ppt",
      "parsers": [
        {
          "id": "ab83f144-5026-4bce-993f-5c982cc19318",
          "name": "MaiAgent Parser",
          "provider": "maiagent",
```

```
          "order": 0,
          "isDefault": true
        },
        {
          "id": "6d0f4c5e-2f1a-4c47-9a7e-7f4b8f0c2a11",
          "name": "MaiAgent Vision Parser",
          "provider": "anthropic",
          "order": 1,
          "isDefault": false
        }
      ]
    },
    {
      "fileType": ".pptx",
      "parsers": [
        {
          "id": "ab83f144-5026-4bce-993f-5c982cc19318",
          "name": "MaiAgent Parser",
          "provider": "maiagent",
          "order": 0,
          "isDefault": true
        },
        {
          "id": "6d0f4c5e-2f1a-4c47-9a7e-7f4b8f0c2a11",
          "name": "MaiAgent Vision Parser",
          "provider": "anthropic",
          "order": 1,
          "isDefault": false
        }
      ]
    },
    {
      "fileType": ".xls",
      "parsers": [
        {
          "id": "ab83f144-5026-4bce-993f-5c982cc19318",
          "name": "MaiAgent Parser",
          "provider": "maiagent",
          "order": 0,
          "isDefault": true
        }
      ]
    },
    {
      "fileType": ".xlsx",
```

```
      "parsers": [
        {
          "id": "ab83f144-5026-4bce-993f-5c982cc19318",
          "name": "MaiAgent Parser",
          "provider": "maiagent",
          "order": 0,
          "isDefault": true
        }
      ]
    },
    {
      "fileType": ".csv",
      "parsers": [
        {
          "id": "ab83f144-5026-4bce-993f-5c982cc19318",
          "name": "MaiAgent Parser",
          "provider": "maiagent",
          "order": 0,
          "isDefault": true
        }
      ]
    },
    {
      "fileType": ".txt",
      "parsers": [
        {
          "id": "ab83f144-5026-4bce-993f-5c982cc19318",
          "name": "MaiAgent Parser",
          "provider": "maiagent",
          "order": 0,
          "isDefault": true
        }
      ]
    },
    {
      "fileType": ".md",
      "parsers": [
        {
          "id": "ab83f144-5026-4bce-993f-5c982cc19318",
          "name": "MaiAgent Parser",
          "provider": "maiagent",
          "order": 0,
          "isDefault": true
        }
      ]
```

```
    },
    {
      "fileType": ".json",
      "parsers": [
        {
          "id": "ab83f144-5026-4bce-993f-5c982cc19318",
          "name": "MaiAgent Parser",
          "provider": "maiagent",
          "order": 0,
          "isDefault": true
        }
      ]
    },
    {
      "fileType": ".jsonl",
      "parsers": [
        {
          "id": "ab83f144-5026-4bce-993f-5c982cc19318",
          "name": "MaiAgent Parser",
          "provider": "maiagent",
          "order": 0,
          "isDefault": true
        }
      ]
    },
    {
      "fileType": ".html",
      "parsers": [
        {
          "id": "ab83f144-5026-4bce-993f-5c982cc19318",
          "name": "MaiAgent Parser",
          "provider": "maiagent",
          "order": 0,
          "isDefault": true
        }
      ]
    },
    {
      "fileType": ".mp3",
      "parsers": [
        {
          "id": "4c47e305-2eb7-4438-8d3c-d91eb0b06cc0",
          "name": "Azure Speech",
          "provider": "azure",
          "order": 1,
```

```
          "isDefault": true
        }
      ]
    },
    {
      "fileType": ".wav",
      "parsers": [
        {
          "id": "4c47e305-2eb7-4438-8d3c-d91eb0b06cc0",
          "name": "Azure Speech",
          "provider": "azure",
          "order": 1,
          "isDefault": true
        }
      ]
    }
  ]
]
```

Example API call (Shell)

目錄

1. Register an Account
2. Change Password
3. Create an organization
4. Add a Member to the Specified Organization
5. Bulk Import Members
6. List Organizations
7. Retrieve Organization Details
8. Get Current User Details
9. Get Current User Permissions
10. List Members of a Specified Organization
11. Get Member Details
12. Update Organization
13. Update Current User Details
14. Update Member Roles
15. Update member name
16. Invite members to the organization
17. List organization email invitation records
18. Resend organization invitation email
19. List Organization API Keys
20. Issue an API Key for a Member
21. Retrieve a Specific API Key
22. Update API Key Settings
23. Revoke API Key
24. Get the Organization an API Key Belongs To
25. Issue a Member Embed Token
26. List OAuth Applications
27. Register OAuth Application
28. Retrieve OAuth Application
29. Update OAuth Application
30. Delete OAuth Application and Revoke Its Tokens
31. Regenerate Client Secret
32. List OAuth applications I have authorized
33. Revoke my authorization for an application
34. Delete organization
35. Delete a specified member

36. Get member usage statistics
37. Retrieve Member Usage Statistics Summary
38. Get AI Assistant Usage Statistics
39. Retrieve AI Assistant Usage Statistics Summary
40. List Your Memories
41. Create or Update Your Memories
42. Modify or Reactivate Your Memories
43. Delete Your Own Memory

Example API call (Shell)

Register an Account

`POST` `/api/v1/auth/registration/`

Request Body

Request Parameters

Field	Type	Required	Description
email	string (email)	Yes	
password1	string	Yes	
password2	string	Yes	
name	string	Yes	
company	string	Yes	
referralCode	string	No	
authSource	object (contains 2 properties: id, name)	No	
authSource.id	string (uuid)	Yes	

Request Schema Example

```
{
  "email": string (email)
  "password1": string
  "password2": string
  "name": string
  "company": string
  "referralCode"?: string // Optional
  "authSource"?:  // Optional
  {
    "id": string (uuid)
  }
}
```

Example Request Values

```
{
  "email": "user@example.com",
  "password1": "Example string",
  "password2": "Example string",
  "name": "Example name",
  "company": "Example string",
  "referralCode": "Example string",
  "authSource": {
    "id": "550e8400-e29b-41d4-a716-446655440000"
  }
}
```

Code Examples

Shell/Bash

```
# Example API call (Shell)
curl -X POST "https://api.maiagent.ai/api/v1/auth/registration/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "email": "user@example.com",
    "password1": "Example string",
    "password2": "Example string",
    "name": "Example name",
    "company": "Example string",
    "referralCode": "Example string",
    "authSource": {
      "id": "550e8400-e29b-41d4-a716-446655440000"
    }
  }'

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// Request Body (payload)
const data = {
    "email": "user@example.com",
    "password1": "Example string",
    "password2": "Example string",
    "name": "Example name",
    "company": "Example string",
    "referralCode": "Example string",
    "authSource": {
      "id": "550e8400-e29b-41d4-a716-446655440000"
    }
  };

axios.post("https://api.maiagent.ai/api/v1/auth/registration/",
data, config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request failed:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/auth/registration/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# Request Body (payload)
data = {
    "email": "user@example.com",
    "password1": "Example string",
    "password2": "Example string",
    "name": "Example name",
    "company": "Example string",
    "referralCode": "Example string",
    "authSource": {
        "id": "550e8400-e29b-41d4-a716-446655440000"
    }
}

response = requests.post(url, json=data, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request failed:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>post("https://api.maiagent.ai/api/v1/auth/registration/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'email' => 'user@example.com',
            'password1' => 'Example string',
            'password2' => 'Example string',
            'name' => 'Example name',
            'company' => 'Example string',
            'referralCode' => 'Example string',
            'authSource' => [
                'id' => '550e8400-e29b-41d4-a716-446655440000'
            ]
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request failed: ' . $e->getMessage();
}
?>
```

Response Body

Status Code: 201

Response Schema Example

```
{
  "email": string (email)
  "password1": string
  "password2": string
  "name": string
  "company": string
  "referralCode"?: string // Optional
  "authSource"?:  // Optional
  {
    "id": string (uuid)
    "name": string
  }
}
```

Example Response Values

```
{
  "email": "response@example.com",
  "password1": "Response string",
  "password2": "Response string",
  "name": "Response string",
  "company": "Response string",
  "referralCode": "Response string",
  "authSource": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Response string"
  }
}
```

Change Password

POST `/api/v1/auth/password/change/`

Request Body

Request Parameters

Field	Type	Required	Description
oldPassword	string	Yes	
newPassword1	string	Yes	
newPassword2	string	Yes	

Request Schema Example

```
{
  "oldPassword": string
  "newPassword1": string
  "newPassword2": string
}
```

Example Request Values

```
{
  "oldPassword": "Example string",
  "newPassword1": "Example string",
  "newPassword2": "Example string"
}
```

Code Examples

Shell/Bash

```
# Example API call (Shell)
curl -X POST "https://api.maiagent.ai/api/v1/auth/password/change/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "oldPassword": "Example string",
    "newPassword1": "Example string",
    "newPassword2": "Example string"
  }'

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// Request Body (payload)
const data = {
    "oldPassword": "Example string",
    "newPassword1": "Example string",
    "newPassword2": "Example string"
  };

axios.post("https://api.maiagent.ai/api/v1/auth/password/change/",
data, config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request failed:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/auth/password/change/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# Request Body (payload)
data = {
    "oldPassword": "Example string",
    "newPassword1": "Example string",
    "newPassword2": "Example string"
}

response = requests.post(url, json=data, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request failed:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>post("https://api.maiagent.ai/api/v1/auth/password/change/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'oldPassword' => 'Example string',
            'newPassword1' => 'Example string',
            'newPassword2' => 'Example string'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request failed: ' . $e->getMessage();
}
?>
```

Response Body

Status Code: 200

Response Schema Example

```
{
  "detail": string
}
```

Example Response Values

```
{
  "detail": "Response string"
}
```

Create an organization

POST `/api/v1/organizations/`

Request body

Request parameters

Field	Type	Required	Description
name	string	Yes	Organization name
compact_logo	string (binary)	No	Compact logo (optional, available only on the Enterprise plan)
full_logo	string (binary)	No	Full logo (optional, available only on the Enterprise plan)

Example request schema

```
{
  "name": string // Organization name
  "compact_logo"?: string (binary) // Compact logo (optional, available
```

```
only on the Enterprise plan) (Optional)
  "full_logo"?: string (binary) // Full logo (optional, available only on
the Enterprise plan) (Optional)
}
```

Example request values

```
{
  "name": "My Organization"
}
```

Code examples

Shell/Bash

```
# API call example (Shell)
curl -X POST "https://api.maiagent.ai/api/v1/organizations/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "name": "My Organization"
  }'

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// Request body (payload)
const data = {
    "name": "My Organization"
  };

axios.post("https://api.maiagent.ai/api/v1/organizations/", data,
config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/organizations/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# Request body (payload)
data = {
    "name": "My Organization"
}

response = requests.post(url, json=data, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>post("https://api.maiagent.ai/api/v1/organizations/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'name' => 'My Organization'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response body

Status code: 201

Example response schema

```
{
  "id": string (uuid)
  "name": string
  "createdAt": string (timestamp)
  "compactLogo"?: string (uri) // Optional
  "fullLogo"?: string (uri) // Optional
  "themePrimaryColor"?: // May have different types (Optional)
  string // UI theme color for buttons, links, and other elements (HEX
format, e.g. #0960bd); leave blank if unset to fall back to the system
brand primary color (Optional)
  "usageStatistics": object
  "organizationPlan": object
  "creditWallet": object // Return credit wallet with ID only.
  "maigptInboxId": string (uuid)
  "canUseCustomElasticsearch": boolean // Allow this organization to
configure custom Elasticsearch endpoints for knowledge bases.
  "canUseVoiceAgent": boolean // Allow this organization to use voice
agent features.
  "canUseMeetingRecords": boolean // Allow this organization to use
meeting records features.
  "canUseCallCenter": boolean // Allow this organization to use call
center features.
  "canUseHookSystem": boolean // Manual override to grant this
organization the hook system regardless of plan. Enterprise-plan
organizations get access automatically without this flag. Layered under
the global Config.hook_system_enabled switch: it must also be enabled.
  "canUseAiGateway": boolean // Allow this organization to call the
OpenAI-compatible `/api/v1/chat/completions` Gateway. On by default for
license installs, otherwise off until a platform admin enables it.
  "canUseGroupAssistant": boolean // Allow this organization to use the
personal secretary (its LINE group features). Off by default; the
organization admin still switches the assistant on in Admin.
  "canUseAgentTeams": boolean // Read-only projection of the platform-
wide Agent Teams switch (Config.enable_agent_teams). Not a per-
organization flag; member-level access is still governed by RBAC.
  "canUseFileLibrary": boolean // Allow this organization to use the file
library.
  "canUseFileOnlineEditing": boolean // Enable online editing in the file
library (P7): the text editor and upload-new-version entries. Requires
can_use_file_library to also be on.
  "canUseOfficeOnlineEditing": boolean // Enable Office (xlsx/docx/pptx)
online editing in the file library (P7 S9). Requires
can_use_file_online_editing to also be on.
  "canUseRolePermissionGovernance": boolean // Always true: batch role
```

```
permission settings and the effective permissions view are available to every organization. Kept for clients that still read it; access is governed by organization_overview_access.
  "enableAgentMemory": boolean // Enable persistent cross-conversation memory for agents in this organization. When off, agents use only in-session memory. On by default on SaaS; license installs remain opt-in. Members can still turn it off for themselves in Profile > AI Memory.
  "hideChinaModels"?: boolean // When on, platform models whose developer is based in China (including ones added later) cannot be used in this organization: model menus, assistants, the API and AI Gateway exclude them, and live transcription lists China-developed speech engines as unavailable. Off by default; turn it on for public-sector or other organizations that must not use them. (Optional)
  "autoActivateNewChatbotChannels"?: boolean // Initial state of the web chat and API channels of a new chatbot whose creator did not set them (duplicates, templates and API calls without the values included). When on, they start active; when off (the platform default), they start inactive until a member turns them on. The creator can still override both channels in the New Chatbot dialog or the create API. The backstage (admin) channel is always active. Changing this does not affect existing chatbots. (Optional)
  "gatewayServiceFeePercent": string (decimal) // Markup applied on top of the token price when billing MaiAgent-managed models called through the AI Gateway (/v1/chat/completions and /v1/embeddings). Managed gateway markup only; the organization's own models (BYOK / self-hosted) are billed via the AI Gateway traffic fee percent instead.
  "gatewayTrafficFeePercent": string (decimal) // Pass-through fee for calls that run on this organization's own AI Gateway models (BYOK / self-hosted): charged as the call's total tokens (input, output, and prompt-cache) x this percent in credits, with no LLM token pricing. Adjustable per organization; changes apply to new calls only.
  "platformProcessingFeePercent": string (decimal) // Surcharge on every credit consumption of this organization, billed as a separate "Platform Processing Fee" line equal to the consumed credits x this percent. 0 disables the fee. Applies to new consumption only; the percent is shown read-only on the customer pricing page.
  "platformProcessingFeeEnabled": boolean // Whether new consumption of this organization accrues the platform processing fee. The percent is exposed read-only as platform_processing_fee_percent.
  "isTrial": boolean // Whether the organization is in a trial period. True when the organization has exactly one trial plan and it is currently active
  "expirationDays": integer // Days since expiration. A positive number indicates days expired; null indicates a plan that has not expired or a permanent plan
```

```
  "showTrialBanner": boolean // Controls whether the frontend displays
the trial/free plan banner
  "agentScheduleMinIntervalSeconds": integer // Minimum schedule
execution interval in seconds, configured by the platform; the frontend
displays this minimum when creating or editing schedules, while the
schedule API enforces it
  "noActivePlanDays": integer // Consecutive days without an active paid
plan. null when cleanup is disabled.
  "cleanupRemainingDays": integer // Days remaining before organization
data is permanently deleted. null when cleanup is disabled, org has an
active paid plan, or no_active_plan_days is 0.
  "estimatedCleanupDate": string // ISO date when organization data will
be permanently deleted. null when cleanup_remaining_days is null.
  "approvalStatus":  // Trial-eligibility review status. Only approved
organizations can receive a trial plan when organization approval is
enabled. Paid plan activation auto-approves the organization.

* `pending` - Pending Review
* `approved` - Approved
* `rejected` - Rejected
  {
  }
  "companyName"?: string // Applicant-reported company name collected at
organization creation for approval review. (Optional)
  "taxId"?: // May have different types (Optional)
  string // Applicant-reported business tax ID (8 digits, optional).
Stored as-is; not verified. (Optional)
  "contactPhone"?: string // Applicant-reported contact phone collected
at organization creation for approval review. (Optional)
  "applicationMetadata"?: object // Extra applicant-reported key-value
fields collected at organization creation. Lets the frontend collect
additional review fields without a schema migration; the core review
fields (company name, tax ID, contact phone) stay as named columns.
(Optional)
  "invitationCode"?: string // Optional
  "ipAllowlistEnabled": boolean // Restrict this organization to the
source IPs listed in allowed_ip_cidrs. Layered under the global
Config.ip_allowlist_enforcement_enabled switch: both must be enabled.
Disabled by default so existing organizations keep unrestricted access.
  "allowedIpCidrs": string // Source IPs or CIDRs allowed to reach this
organization, one per line (e.g. 203.0.113.0/24); commas also work. While
the IP allowlist is enabled, an empty list rejects everything. A non-
empty list whose entries are all invalid rejects everything rather than
silently reverting to unrestricted, so a typo cannot quietly disable the
protection. Matching uses the load-balancer-appended client IP.
```

```
  "enforceIpAllowlistOnAdminUi": boolean // Apply the allowlist to
browser sessions: the admin console and its WebSocket connections. Only
takes effect while ip_allowlist_enabled is on.
  "enforceIpAllowlistOnApiKey": boolean // Apply the allowlist to Open
API (Api-Key) and AI Gateway (Bearer) requests. Only takes effect while
ip_allowlist_enabled is on.
}
```

Example response values


```
{
  "id": "5b01e0b9-0b0e-4079-8150-d12015576d2c",
  "name": "My Organization",
  "createdAt": "1748336288000",
  "compactLogo": null,
  "fullLogo": null,
  "usageStatistics": {
    "chatbotsCount": 0,
    "countableChatbotsCount": 0,
    "exemptChatbotsByMode": {},
    "canCreateChatbot": true,
    "createChatbotLimit": 1,
    "currentMonthWordsCountTotal": 1000000,
    "currentMonthUsedWordsCountTotal": 0,
    "currentMonthUsedConversationsCountTotal": 0,
    "availableUploadFilesSizeTotal": 104857600,
    "usedUploadFileSizeTotal": 0
  },
  "organizationPlan": {
    "id": "cac825e8-cb9b-4a16-b440-4ff6b2e73911",
    "planName": "Free plan",
    "planType": "free",
    "expiredAt": null
  },
  "maigptInboxId": null,
  "canUseCustomElasticsearch": false,
  "isTrial": true,
  "expirationDays": null
}
```

Add a Member to the Specified Organization

POST `/api/v1/organizations/{organizationPk}/members/`

Parameters

Parameter Name	Required	Type	Description
`organizationPk`	V	string	A UUID string identifying this Organization ID

Request Body

Request Parameters

Field	Type	Required	Description
email	string (email)	Yes	
organization	string (uuid)	No	

Request Schema Example

```
{
  "email": string (email)
  "organization"?: string (uuid) // Optional
}
```

Example Request Values

```
{
  "organization": "613c86f7-a45f-4e29-b255-29caff89de32",
```

```
  "is_owner": false
}
```

Code Examples

Shell/Bash

```
# Example API call (Shell)
curl -X POST "https://api.maiagent.ai/api/v1/organizations/550e8400-
e29b-41d4-a716-446655440000/members/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "organization": "613c86f7-a45f-4e29-b255-29caff89de32",
    "is_owner": false
  }'

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// Request Body (payload)
const data = {
    "organization": "613c86f7-a45f-4e29-b255-29caff89de32",
    "is_owner": false
  };

axios.post("https://api.maiagent.ai/api/v1/organizations/550e8400-
e29b-41d4-a716-446655440000/members/", data, config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request failed:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-
41d4-a716-446655440000/members/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# Request Body (payload)
data = {
    "organization": "613c86f7-a45f-4e29-b255-29caff89de32",
    "is_owner": False
}

response = requests.post(url, json=data, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request failed:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>post("https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-
41d4-a716-446655440000/members/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'organization' => '613c86f7-a45f-4e29-b255-
29caff89de32',
            'is_owner' => false
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request failed: ' . $e->getMessage();
}
?>
```

Response Body

Status Code: 201

Response Schema Example

```
{
  "organization": string (uuid) // Organization ID
  "is_owner": boolean // Whether the member is the organization owner
}
```

Example Response Values

```
{
  "organization": "613c86f7-a45f-4e29-b255-29caff89de32",
  "is_owner": false
}
```

Bulk Import Members

POST `/api/v1/organizations/{organizationPk}/members/bulk-import/`

Upload file (.xlsx) using multipart/form-data. The Email(required) column is required, and the Name column is optional. Each upload supports up to 25,000 rows (excluding the header). If this limit is exceeded, the entire file is rejected with 400; split the file into smaller files for import. If any row has a blank or invalid Email, or a Name longer than 255 characters, the entire file is also rejected, and the 400 response's detail is an array of strings listing errors by row. If the Email(required) column is missing or the file has no data rows, detail is a single string. If the file is not .xlsx, the error is returned in the file field. When an Email appears more than once, only the first occurrence is processed. People whose Email is not yet in the organization are added and counted in added. Name becomes their name within the organization (if the account is also created during this import, Name is also used as the account name; if omitted, the Email prefix is used). For existing members, behavior depends on the importer's role: when the organization owner imports, a Name that differs from the current display name updates the member's name within the organization (updated); a blank or identical Name leaves it unchanged (unchanged); if Name differs but the member is managed through SCIM synchronization, the name is not updated (scimSkipped). For imports by non-owners, the existing behavior is preserved: existing members are skipped and their names are not updated (skippedExisting). importerIsOwner indicates whether the importer is the owner. Only names within the organization are updated; existing members' account names are not changed. created retains its original meaning: the total of newly added and existing members, equal to the sum of added,

updated, unchanged, scimSkipped, and skippedExisting. Integrations that read only created require no changes. message contains messages for individual rows. For imports by the owner, “Already in the organization” is replaced with “Row N: Name updated”, “Row N: Unchanged”, or “Row N: Managed through SCIM synchronization; not updated”. For imports by non-owners, the original messages are preserved.

Parameters

Parameter Name	Required	Type	Description
`organizationPk`	V	string	A UUID string identifying this organization ID

Code Examples

Shell/Bash

```
# API call example (Shell)
curl -X POST "https://api.maiagent.ai/api/v1/organizations/550e8400-
e29b-41d4-a716-446655440000/members/bulk-import/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -F "file=@example_file.xlsx"

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');
const FormData = require('form-data');

// Create a FormData object
const formData = new FormData();
// Replace with an actual file
formData.append('file',
* actual file object *
, 'example_file.xlsx');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    ...formData.getHeaders()
  }
};

axios.post("https://api.maiagent.ai/api/v1/organizations/550e8400-
e29b-41d4-a716-446655440000/members/bulk-import/", formData, config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request failed:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-
41d4-a716-446655440000/members/bulk-import/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}

# Prepare the file and form data
files = {
    'file': ('example_file.xlsx', open('example_file.xlsx', 'rb'),
'application/vnd.openxmlformats-officedocument.spreadsheetml.sheet')
}

response = requests.post(url, files=files, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request failed:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>post("https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-
41d4-a716-446655440000/members/bulk-import/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ],
        'multipart' => [
            [
                'name' => 'file',
                'contents' => fopen('example_file.xlsx', 'r'),
                'filename' => 'example_file.xlsx'
            ]
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request failed: ' . $e->getMessage();
}
?>
```

Response

Status Code: 201

Example Response Schema

```
{
  "created": integer // Total number of members processed (including
newly created and existing members)
  "added": integer // Number of members newly added to the organization
  "updated": integer // Number of existing members whose names within the
organization were updated during an import by the owner
  "unchanged": integer // Number of existing members left unchanged
during an import by the owner because Name was blank or matched the
current display name
  "scimSkipped": integer // Number of existing members whose names were
not updated during an import by the owner because they are managed
through SCIM synchronization
  "skippedExisting": integer // Number of members skipped during an
import by a non-owner because they are already in the organization; 0 for
imports by the owner
  "importerIsOwner": boolean // Whether the importer is the organization
owner
  "message"?: [ // Per-row messages (omitted when there are none).
Imports by the owner: “Row N: Name updated / Unchanged / Managed through
SCIM synchronization; not updated”. Imports by non-owners: row numbers
and email addresses skipped because they are already in the organization
(optional)
    string
  ]
}
```

Example Response Values

```
{
  "created": 5,
  "added": 2,
  "updated": 1,
  "unchanged": 1,
  "scimSkipped": 1,
  "skippedExisting": 0,
  "importerIsOwner": true,
  "message": [
    "Row 2: Name updated",
    "Row 3: Unchanged",
    "Row 5: Managed through SCIM synchronization; not updated"
```

```
  ]
}
```

Status Code: 400 - Validation error; the entire file is rejected

Example Response Schema

```
{
  "detail"?: // May have different types (optional)
  array[string] // Reason the entire file is rejected. Array of strings:
errors listed by row (such as a blank Email or a Name longer than 255
characters), or exceeding the 25,000-row limit per upload; string: a
missing required column or a file with no data rows (optional)
  "file"?: [ // The file is not in .xlsx format (optional)
    string
  ]
}
```

Example Response Values

```
{
  "detail": [
    "Row 3: Email cannot be blank",
    "Row 5: Email cannot be blank"
  ]
}
```

List Organizations

GET `/api/v1/organizations/`

Parameters

Parameter	Required	Type	Description
`page`	X	integer	A page number within the paginated result set.
`pageSize`	X	integer	Number of results to return per page.
`pagination`	X	string	Whether to paginate (true/false)

Code Examples

Shell/Bash

```
# Example API call (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/organizations/?
page=1&pageSize=1&pagination=example"

  -H "Authorization: Api-Key YOUR_API_KEY"

# Make sure to replace YOUR_API_KEY and verify the request data
before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/organizations/?
page=1&pageSize=1&pagination=example", config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request failed:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/organizations/?
page=1&pageSize=1&pagination=example"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request failed:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/organizations/?
page=1&pageSize=1&pagination=example", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request failed: ' . $e->getMessage();
}
?>
```

Response Body

Status Code: 200

Example Response Schema

```
{
  "count": integer
  "next"?: string (uri) // Optional
```

```
  "previous"?: string (uri) // Optional
  "results": [
    {
      "id": string (uuid)
      "name": string
      "createdAt": string (timestamp)
      "memberCreatedAt": string (timestamp)
      "approvalStatus": string
    }
  ]
}
```

Example Response Values

```
{
  "count": 123,
  "next": "http://api.example.org/accounts/?page=4",
  "previous": "http://api.example.org/accounts/?page=2",
  "results": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "Response string",
      "createdAt": "Response string",
      "memberCreatedAt": "Response string",
      "approvalStatus": "Response string"
    }
  ]
}
```

Retrieve Organization Details

GET `/api/v1/organizations/{id}`

Parameters

Parameter Name	Required	Type	Description
id	V	string	A UUID string identifying this organization.

Code Examples

Shell/Bash

```
# API Call Example (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/organizations/550e8400-
e29b-41d4-a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/organizations/550e8400-
e29b-41d4-a716-446655440000/", config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request failed:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-
41d4-a716-446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request failed:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-
41d4-a716-446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request failed: ' . $e->getMessage();
}
?>
```

Response

Status Code: 200

Example Response Schema

```
{
  "id": string (uuid)
  "name": string
```

```
  "createdAt": string (timestamp)
  "compactLogo"?: string (uri) // Optional
  "fullLogo"?: string (uri) // Optional
  "themePrimaryColor"?: // May have different types (Optional)
  string // UI theme color for buttons, links, and other elements (HEX format, e.g. #0960bd); leave blank to use the system brand primary color as the frontend fallback (Optional)
  "usageStatistics": object
  "organizationPlan": object
  "creditWallet": object // Return credit wallet with ID only.
  "maigptInboxId": string (uuid)
  "canUseCustomElasticsearch": boolean // Allow this organization to configure custom Elasticsearch endpoints for knowledge bases.
  "canUseVoiceAgent": boolean // Allow this organization to use voice agent features.
  "canUseMeetingRecords": boolean // Allow this organization to use meeting records features.
  "canUseCallCenter": boolean // Allow this organization to use call center features.
  "canUseHookSystem": boolean // Manual override to grant this organization the hook system regardless of plan. Enterprise-plan organizations get access automatically without this flag. Layered under the global Config.hook_system_enabled switch: it must also be enabled.
  "canUseAiGateway": boolean // Allow this organization to call the OpenAI-compatible `/api/v1/chat/completions` Gateway. On by default for license installs, otherwise off until a platform admin enables it.
  "canUseGroupAssistant": boolean // Allow this organization to use the personal secretary (its LINE group features). Off by default; the organization admin still switches the assistant on in Admin.
  "canUseAgentTeams": boolean // Read-only projection of the platform-wide Agent Teams switch (Config.enable_agent_teams). Not a per-organization flag; member-level access is still governed by RBAC.
  "canUseFileLibrary": boolean // Allow this organization to use the file library.
  "canUseFileOnlineEditing": boolean // Enable online editing in the file library (P7): the text editor and upload-new-version entries. Requires can_use_file_library to also be on.
  "canUseOfficeOnlineEditing": boolean // Enable Office (xlsx/docx/pptx) online editing in the file library (P7 S9). Requires can_use_file_online_editing to also be on.
  "canUseRolePermissionGovernance": boolean // Always true: batch role permission settings and the effective permissions view are available to every organization. Kept for clients that still read it; access is governed by organization_overview_access.
  "enableAgentMemory": boolean // Enable persistent cross-conversation
```

```
memory for agents in this organization. When off, agents use only in-session memory. On by default on SaaS; license installs remain opt-in. Members can still turn it off for themselves in Profile > AI Memory.
  "hideChinaModels"?: boolean // When on, platform models whose developer is based in China (including ones added later) cannot be used in this organization: model menus, assistants, the API and AI Gateway exclude them, and live transcription lists China-developed speech engines as unavailable. Off by default; turn it on for public-sector or other organizations that must not use them. (Optional)
  "autoActivateNewChatbotChannels"?: boolean // Initial state of the web chat and API channels of a new chatbot whose creator did not set them (duplicates, templates and API calls without the values included). When on, they start active; when off (the platform default), they start inactive until a member turns them on. The creator can still override both channels in the New Chatbot dialog or the create API. The backstage (admin) channel is always active. Changing this does not affect existing chatbots. (Optional)
  "gatewayServiceFeePercent": string (decimal) // Markup applied on top of the token price when billing MaiAgent-managed models called through the AI Gateway (/v1/chat/completions and /v1/embeddings). Managed gateway markup only; the organization's own models (BYOK / self-hosted) are billed via the AI Gateway traffic fee percent instead.
  "gatewayTrafficFeePercent": string (decimal) // Pass-through fee for calls that run on this organization's own AI Gateway models (BYOK / self-hosted): charged as the call's total tokens (input, output, and prompt-cache) x this percent in credits, with no LLM token pricing. Adjustable per organization; changes apply to new calls only.
  "platformProcessingFeePercent": string (decimal) // Surcharge on every credit consumption of this organization, billed as a separate "Platform Processing Fee" line equal to the consumed credits x this percent. 0 disables the fee. Applies to new consumption only; the percent is shown read-only on the customer pricing page.
  "platformProcessingFeeEnabled": boolean // Whether new consumption of this organization accrues the platform processing fee. The percent is exposed read-only as platform_processing_fee_percent.
  "isTrial": boolean // Whether the organization is in a trial period. True when the organization has exactly one trial plan and it is currently active
  "expirationDays": integer // Days since expiration. A positive number indicates days since expiration; null means the plan has not expired or is permanent
  "showTrialBanner": boolean // Controls whether the frontend displays the trial/free plan banner
  "agentScheduleMinIntervalSeconds": integer // Minimum schedule execution interval in seconds, configured by the platform; the frontend
```

```
displays this minimum when creating or editing a schedule, while the
schedule API enforces it
  "noActivePlanDays": integer // Consecutive days without an active paid
plan. null when cleanup is disabled.
  "cleanupRemainingDays": integer // Days remaining before organization
data is permanently deleted. null when cleanup is disabled, org has an
active paid plan, or no_active_plan_days is 0.
  "estimatedCleanupDate": string // ISO date when organization data will
be permanently deleted. null when cleanup_remaining_days is null.
  "approvalStatus":  // Trial-eligibility review status. Only approved
organizations can receive a trial plan when organization approval is
enabled. Paid plan activation auto-approves the organization.

* `pending` - Pending Review
* `approved` - Approved
* `rejected` - Rejected
  {
  }
  "companyName"?: string // Applicant-reported company name collected at
organization creation for approval review. (Optional)
  "taxId"?: // May have different types (Optional)
  string // Applicant-reported business tax ID (8 digits, optional).
Stored as-is; not verified. (Optional)
  "contactPhone"?: string // Applicant-reported contact phone collected
at organization creation for approval review. (Optional)
  "applicationMetadata"?: object // Extra applicant-reported key-value
fields collected at organization creation. Lets the frontend collect
additional review fields without a schema migration; the core review
fields (company name, tax ID, contact phone) stay as named columns.
(Optional)
  "invitationCode"?: string // Optional
  "ipAllowlistEnabled": boolean // Restrict this organization to the
source IPs listed in allowed_ip_cidrs. Layered under the global
Config.ip_allowlist_enforcement_enabled switch: both must be enabled.
Disabled by default so existing organizations keep unrestricted access.
  "allowedIpCidrs": string // Source IPs or CIDRs allowed to reach this
organization, one per line (e.g. 203.0.113.0/24); commas also work. While
the IP allowlist is enabled, an empty list rejects everything. A non-
empty list whose entries are all invalid rejects everything rather than
silently reverting to unrestricted, so a typo cannot quietly disable the
protection. Matching uses the load-balancer-appended client IP.
  "enforceIpAllowlistOnAdminUi": boolean // Apply the allowlist to
browser sessions: the admin console and its WebSocket connections. Only
takes effect while ip_allowlist_enabled is on.
  "enforceIpAllowlistOnApiKey": boolean // Apply the allowlist to Open
```

```
API (Api-Key) and AI Gateway (Bearer) requests. Only takes effect while
ip_allowlist_enabled is on.
}
```

Example Response Values


```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "name": "Response string",
  "createdAt": "Response string",
  "compactLogo": "https://example.com/file.jpg",
  "fullLogo": "https://example.com/file.jpg",
  "themePrimaryColor": "Response string",
  "usageStatistics": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Example response name",
    "description": "Example response description"
  },
  "organizationPlan": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Example response name",
    "description": "Example response description"
  },
  "creditWallet": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Example response name",
    "description": "Example response description"
  },
  "maigptInboxId": "550e8400-e29b-41d4-a716-446655440000",
  "canUseCustomElasticsearch": false,
  "canUseVoiceAgent": false,
  "canUseMeetingRecords": false,
  "canUseCallCenter": false,
  "canUseHookSystem": false,
  "canUseAiGateway": false,
  "canUseGroupAssistant": false,
  "canUseAgentTeams": false,
  "canUseFileLibrary": false,
  "canUseFileOnlineEditing": false,
  "canUseOfficeOnlineEditing": false,
  "canUseRolePermissionGovernance": false,
  "enableAgentMemory": false,
  "hideChinaModels": false,
  "autoActivateNewChatbotChannels": false,
```

```
  "gatewayServiceFeePercent": "Response string",
  "gatewayTrafficFeePercent": "Response string",
  "platformProcessingFeePercent": "Response string",
  "platformProcessingFeeEnabled": false,
  "isTrial": false,
  "expirationDays": 456,
  "showTrialBanner": false,
  "agentScheduleMinIntervalSeconds": 456,
  "noActivePlanDays": 456,
  "cleanupRemainingDays": 456,
  "estimatedCleanupDate": "Response string",
  "approvalStatus": {},
  "companyName": "Response string",
  "taxId": "Response string",
  "contactPhone": "Response string",
  "applicationMetadata": null,
  "invitationCode": "Response string",
  "ipAllowlistEnabled": false,
  "allowedIpCidrs": "Response string",
  "enforceIpAllowlistOnAdminUi": false,
  "enforceIpAllowlistOnApiKey": false
}
```


Get Current User Details

`GET` `/api/v1/users/current/`

Code Examples

Shell/Bash

```
# Example API call (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/users/current/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# Make sure to replace YOUR_API_KEY and verify the request data
before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/users/current/", config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request failed:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/users/current/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request failed:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/users/current/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request failed: ' . $e->getMessage();
}
?>
```

Response Body

Status Code: 200

Example Response Schema

```
{
  "id": string (uuid)
  "avatar"?: string (uri) // Optional
  "originalAvatar"?: string (uri) // The original avatar image uploaded
```

```
by the user (long edge capped at 2048px). Every edit re-crops from this
image to avoid cumulative distortion from cropping an already-cropped
result. Legacy data from before this feature launched is empty and is not
backfilled (Optional)
  "avatarCropBox"?: object // Position and size of the last crop box on
the original image (x/y/width/height, with optional
rotate/scale_x/scale_y); coordinates are relative to the stored original
image (Optional)
  "name": string
  "email": string (email)
  "authSource":
  {
    "id": string (uuid)
    "name": string
  }
  "company"?: string // Optional
  "invitationCode"?: // Multiple types possible (Optional)
  string // Optional
  "apiKeys": [ // Get the list of the user's API keys in the specified
organization.

Flow:
1. Get the current organization instance from the request
2. If there is no organization instance (usually during third-party SSO
login), use the user's auth source
   to look up that auth source's default organization
(is_auth_source_default_organization=True)

Note:
<ul>
  <li>During third-party SSO login, the request does not contain
organization_instance</li>
  <li>The organization must be located via the auth_source and
is_auth_source_default_organization flags</li>
</ul>
    object
  ]
  "permissions": object // Get the user's permissions in the current
organization (nested parent-child structure).
  "resourcePermissions": object // Get the user's resource creation
permissions in the current organization.
  "isOwner": boolean // Determine whether the user is an Owner in the
current organization.
  "maigptCapabilities": object // The member's effective built-in feature
capabilities in MaiGPT (resolved from role permissions), used by the
```

```
frontend to show/hide features.

When there is no member context (not bound to an organization), the
resolved result is fully open, consistent with the resolver's "missing
data does not lock out" principle;
hiding in the frontend is only a UX layer, and the authoritative check is
the gate in the reply path.
}
```

Example Response Values


```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "avatar": "https://example.com/file.jpg",
  "originalAvatar": "https://example.com/file.jpg",
  "avatarCropBox": null,
  "name": "Response string",
  "email": "response@example.com",
  "authSource": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Response string"
  },
  "company": "Response string",
  "invitationCode": "Response string",
  "apiKeys": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "Example response name",
      "description": "Example response description"
    }
  ],
  "permissions": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Example response name",
    "description": "Example response description"
  },
  "resourcePermissions": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Example response name",
    "description": "Example response description"
  },
  "isOwner": false,
  "maigptCapabilities": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
```

```
    "name": "Example response name",
    "description": "Example response description"
  }
}
```


Get Current User Permissions

GET `/api/v1/permissions/`

Code Examples

Shell/Bash


```
# Example API call (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/permissions/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# Make sure to replace YOUR_API_KEY and verify the request data
before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/permissions/", config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request failed:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/permissions/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request failed:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/permissions/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request failed: ' . $e->getMessage();
}
?>
```

Response Body

Status Code: 200

Example Response Schema

```
[
  {
    "id": string (uuid)
    "name": string
```

```
    "value": string
    "description": string
    "children": [
      object
    ]
  }
]
```

Example Response Values

```
[
  {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Response string",
    "value": "Response string",
    "description": "Response string",
    "children": [
      {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "name": "Example response name",
        "description": "Example response description"
      }
    ]
  }
]
```

List Members of a Specified Organization

GET `/api/v1/organizations/{organizationPk}/members/`

Parameters

Parameter	Required	Type	Description

`organizationPk`	V	string	A UUID string identifying this organization ID
`group`	X	string	
`ids`	X	string	
`inbox`	X	string	
`isActive`	X	boolean	
`page`	X	integer	A page number within the paginated result set.
`pageSize`	X	integer	Number of results to return per page.
`pagination`	X	string	Whether to paginate (true/false)
`query`	X	string	
`search`	X	string	
`withGroupSources`	X	boolean	When true, `groups` lists each role only once and additionally returns `sources` (how the role was assigned: manual／ldap／scim／eip／cloudflare_access, deduplicated and sorted; default roles have an empty array). Only supported for paginated lists.

Code Examples

Shell/Bash

```
# Example API call (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/organizations/550e8400-
e29b-41d4-a716-446655440000/members/?group=550e8400-e29b-41d4-a716-
446655440000&ids=example&inbox=550e8400-e29b-41d4-a716-
446655440000&isActive=true&page=1&pageSize=1&pagination=example&quer
y=example&search=example&withGroupSources=true"

  -H "Authorization: Api-Key YOUR_API_KEY"

# Before running, replace YOUR_API_KEY and verify the request data.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/organizations/550e8400-
e29b-41d4-a716-446655440000/members/?group=550e8400-e29b-41d4-a716-
446655440000&ids=example&inbox=550e8400-e29b-41d4-a716-
446655440000&isActive=true&page=1&pageSize=1&pagination=example&quer
y=example&search=example&withGroupSources=true", config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('An error occurred during the request:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-
41d4-a716-446655440000/members/?group=550e8400-e29b-41d4-a716-
446655440000&ids=example&inbox=550e8400-e29b-41d4-a716-
446655440000&isActive=true&page=1&pageSize=1&pagination=example&quer
y=example&search=example&withGroupSources=true"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("An error occurred during the request:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-
41d4-a716-446655440000/members/?group=550e8400-e29b-41d4-a716-
446655440000&ids=example&inbox=550e8400-e29b-41d4-a716-
446655440000&isActive=true&page=1&pageSize=1&pagination=example&quer
y=example&search=example&withGroupSources=true", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'An error occurred during the request: ' . $e-
>getMessage();
}
?>
```

Response

Status code: 200

Response Schema Example

```
{
  "count": integer
  "next"?: string (uri) // Optional
  "previous"?: string (uri) // Optional
  "results": [
    {
      "id": string (uuid)
      "name": string
      "displayName": string // Name set by the organization owner for
this organization only; empty string when not set (``name`` then falls
back to the account name).
      "accountName": string // Account name of the member (shared across
organizations); shown when display name is cleared.
      "isScimManaged": boolean // True when the member is provisioned by
SCIM; the identity provider manages the member and the organization name
cannot be changed manually.
      "email": string
      "isActive": boolean
      "isOwner": boolean // Checks whether the member is an organization
owner (via the OWNER Group)

Uses a cache to avoid duplicate queries within the same request
Cache lifetime: valid for as long as the member instance exists

Prefers the annotated result (if available) to avoid duplicate queries
      "permissions": [ // Compute the permission tree once per
(organization, custom-group set) per request.

The tree depends only on the member's organization (default groups,
feature
flags, plan whitelist), the member's custom groups, and the global
``Config``,
so members sharing a group set get the same result. A large role's
``pagination=false`` listing otherwise recomputes it per row — one Redis
``Config`` fetch plus the permission walk each time (issue #8436; the
largest
prod role has 3,837 members and a single group set). The memo lives in
the
serializer context, so it never outlives the request. Rows without the
eager
loaded ``_custom_groups_cache`` (single-object paths) keep computing
directly.
        object
      ]
```

```
      "groups": [
        object
      ]
      "creditQuotaRequired"?: boolean // When True, member must have an
active quota to consume credits (optional)
      "activeQuota": object // Return the most recent quota summary
(active first), via prefetch to avoid N+1.
      "metadata": object // Organization-scoped member attributes,
injected into LLM system prompt
      "availabilityStatus":  // Self-declared availability for auto-
assignment. Paused members are skipped by the dispatch engine but can
still be manually assigned or claim conversations. Not touched by SCIM
provisioning.

* `available` - Available
* `paused` - Paused
      {
      }
      "createdAt": string (timestamp)
    }
  ]
}
```

Response Example Value

```
{
  "count": 123,
  "next": "http://api.example.org/accounts/?page=4",
  "previous": "http://api.example.org/accounts/?page=2",
  "results": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "Response string",
      "displayName": "Response string",
      "accountName": "Response string",
      "isScimManaged": false,
      "email": "Response string",
      "isActive": false,
      "isOwner": false,
      "permissions": [
        {
          "id": "550e8400-e29b-41d4-a716-446655440000",
          "name": "Response example name",
          "description": "Response example description"
```

```
        }
      ],
      "groups": [
        {
          "id": "550e8400-e29b-41d4-a716-446655440000",
          "name": "Response example name",
          "description": "Response example description"
        }
      ],
      "creditQuotaRequired": false,
      "activeQuota": {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "name": "Response example name",
        "description": "Response example description"
      },
      "metadata": null,
      "availabilityStatus": {},
      "createdAt": "Response string"
    }
  ]
}
```


Get Member Details

`GET` `/api/v1/organizations/{organizationPk}/members/{id}`

Parameters

Parameter	Required	Type	Description
`id`	V	string	A UUID string identifying this member.
`organizationPk`	V	string	A UUID string identifying this organization ID

Code Examples

Shell/Bash

```
# Example API call (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/organizations/550e8400-
e29b-41d4-a716-446655440000/members/550e8400-e29b-41d4-a716-
446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# Before running, replace YOUR_API_KEY and verify the request data.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/organizations/550e8400-
e29b-41d4-a716-446655440000/members/550e8400-e29b-41d4-a716-
446655440000/", config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('An error occurred during the request:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-
41d4-a716-446655440000/members/550e8400-e29b-41d4-a716-
446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("An error occurred during the request:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-
41d4-a716-446655440000/members/550e8400-e29b-41d4-a716-
446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'An error occurred during the request: ' . $e-
>getMessage();
}
?>
```

Response

Status code: 200

Response Schema Example

```
{
  "id": string (uuid)
  "name": string
  "displayName": string // Name set by the organization owner for this
organization only; empty string when not set (``name`` then falls back to
the account name).
  "accountName": string // Account name of the member (shared across
organizations); shown when display name is cleared.
  "isScimManaged": boolean // True when the member is provisioned by
SCIM; the identity provider manages the member and the organization name
cannot be changed manually.
  "email": string
  "isActive": boolean
  "isOwner": boolean // Checks whether the member is an organization
owner (via the OWNER Group)

Uses a cache to avoid duplicate queries within the same request
Cache lifetime: valid for as long as the member instance exists

Prefers the annotated result (if available) to avoid duplicate queries
  "permissions": [ // Compute the permission tree once per (organization,
custom-group set) per request.

The tree depends only on the member's organization (default groups,
feature
flags, plan whitelist), the member's custom groups, and the global
``Config``,
so members sharing a group set get the same result. A large role's
``pagination=false`` listing otherwise recomputes it per row — one Redis
``Config`` fetch plus the permission walk each time (issue #8436; the
largest
prod role has 3,837 members and a single group set). The memo lives in
the
serializer context, so it never outlives the request. Rows without the
eager
loaded ``_custom_groups_cache`` (single-object paths) keep computing
directly.
    object
  ]
  "groups": [
    object
  ]
  "creditQuotaRequired"?: boolean // When True, member must have an
active quota to consume credits (optional)
```

```
  "activeQuota": object // Return the most recent quota summary (active
first), via prefetch to avoid N+1.
  "metadata": object // Organization-scoped member attributes, injected
into LLM system prompt
  "availabilityStatus":  // Self-declared availability for auto-
assignment. Paused members are skipped by the dispatch engine but can
still be manually assigned or claim conversations. Not touched by SCIM
provisioning.

* `available` - Available
* `paused` - Paused
  {
  }
  "createdAt": string (timestamp)
}
```

Response Example Value


```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "name": "Response string",
  "displayName": "Response string",
  "accountName": "Response string",
  "isScimManaged": false,
  "email": "Response string",
  "isActive": false,
  "isOwner": false,
  "permissions": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "Response example name",
      "description": "Response example description"
    }
  ],
  "groups": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "Response example name",
      "description": "Response example description"
    }
  ],
  "creditQuotaRequired": false,
  "activeQuota": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
```

```
    "name": "Response example name",
    "description": "Response example description"
  },
  "metadata": null,
  "availabilityStatus": {},
  "createdAt": "Response string"
}
```


Update Organization

PUT `/api/v1/organizations/{id}`

Parameters

Parameter	Required	Type	Description
`id`	V	string	A UUID string identifying this organization.

Request Body

Request Parameters

Field	Type	Required	Description
name	string	Yes	
compactLogo	string (uri)	No	
fullLogo	string (uri)	No	
themePrimaryColor	object	No	UI theme color used for buttons, links, and other

Field	Type	Required	Description
			elements (HEX format, e.g. #0960bd); leave empty for unset, in which case the frontend falls back to the system brand color
hideChinaModels	boolean	No	When on, platform models whose developer is based in China (including ones added later) cannot be used in this organization: model menus, assistants, the API and AI Gateway exclude them, and live tran...
autoActivateNewChatbotChannels	boolean	No	Initial state of the web chat and API channels of a new chatbot whose creator did not set them (duplicates, templates and API calls without the values included). When on, they start active; when off (...
companyName	string	No	Applicant-reported company name collected at organization creation for approval review.
taxId	object	No	Applicant-reported business tax ID (8 digits, optional). Stored as-is; not verified.
contactPhone	string	No	Applicant-reported contact phone collected at organization creation for approval review.
applicationMetadata	object	No	Extra applicant-reported key-value fields collected at organization creation. Lets the frontend collect

Field	Type	Required	Description
			additional review fields without a schema migration; the core review fields (company name, tax I...
invitationCode	string	No	

Request Schema Example

```
{
  "name": string
  "compactLogo"?: string (uri) // Optional
  "fullLogo"?: string (uri) // Optional
  "themePrimaryColor"?: // May be of different types (optional)
  string // UI theme color used for buttons, links, and other elements
(HEX format, e.g. #0960bd); leave empty for unset, in which case the
frontend falls back to the system brand color (optional)
  "hideChinaModels"?: boolean // When on, platform models whose developer
is based in China (including ones added later) cannot be used in this
organization: model menus, assistants, the API and AI Gateway exclude
them, and live transcription lists China-developed speech engines as
unavailable. Off by default; turn it on for public-sector or other
organizations that must not use them. (optional)
  "autoActivateNewChatbotChannels"?: boolean // Initial state of the web
chat and API channels of a new chatbot whose creator did not set them
(duplicates, templates and API calls without the values included). When
on, they start active; when off (the platform default), they start
inactive until a member turns them on. The creator can still override
both channels in the New Chatbot dialog or the create API. The backstage
(admin) channel is always active. Changing this does not affect existing
chatbots. (optional)
  "companyName"?: string // Applicant-reported company name collected at
organization creation for approval review. (optional)
  "taxId"?: // May be of different types (optional)
  string // Applicant-reported business tax ID (8 digits, optional).
Stored as-is; not verified. (optional)
  "contactPhone"?: string // Applicant-reported contact phone collected
at organization creation for approval review. (optional)
  "applicationMetadata"?: object // Extra applicant-reported key-value
fields collected at organization creation. Lets the frontend collect
additional review fields without a schema migration; the core review
fields (company name, tax ID, contact phone) stay as named columns.
```

```
(optional)
  "invitationCode"?: string // Optional
}
```

Request Example Value


```
{
  "id": "5b01e0b9-0b0e-4079-8150-d12015576d2c",
  "name": "Updated Org Name",
  "created_at": "1748336288000",
  "usage_statistics": {
    "chatbots_count": 0,
    "countable_chatbots_count": 0,
    "exempt_chatbots_by_mode": {},
    "allowed_chatbot_reply_modes": [],
    "can_create_chatbot": true,
    "create_chatbot_limit": 1,
    "current_month_words_count_total": 1000000,
    "current_month_used_words_count_total": 0,
    "current_month_used_conversations_count_total": 0,
    "available_upload_files_size_total": 104857600,
    "used_upload_file_size_total": 0
  },
  "organization_plan": {
    "id": "cac825e8-cb9b-4a16-b440-4ff6b2e73911",
    "plan_name": "Free Plan",
    "expired_at": null
  },
  "is_trial": false,
  "expiration_days": null
}
```


Code Examples

Shell/Bash

```
# Example API call (Shell)
curl -X PUT "https://api.maiagent.ai/api/v1/organizations/550e8400-
e29b-41d4-a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "id": "5b01e0b9-0b0e-4079-8150-d12015576d2c",
    "name": "Updated Org Name",
    "created_at": "1748336288000",
    "usage_statistics": {
      "chatbots_count": 0,
      "countable_chatbots_count": 0,
      "exempt_chatbots_by_mode": {},
      "allowed_chatbot_reply_modes": [],
      "can_create_chatbot": true,
      "create_chatbot_limit": 1,
      "current_month_words_count_total": 1000000,
      "current_month_used_words_count_total": 0,
      "current_month_used_conversations_count_total": 0,
      "available_upload_files_size_total": 104857600,
      "used_upload_file_size_total": 0
    },
    "organization_plan": {
      "id": "cac825e8-cb9b-4a16-b440-4ff6b2e73911",
      "plan_name": "Free Plan",
      "expired_at": null
    },
    "is_trial": false,
    "expiration_days": null
  }'

# Before running, replace YOUR_API_KEY and verify the request data.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// Request body (payload)
const data = {
    "id": "5b01e0b9-0b0e-4079-8150-d12015576d2c",
    "name": "Updated Org Name",
    "created_at": "1748336288000",
    "usage_statistics": {
      "chatbots_count": 0,
      "countable_chatbots_count": 0,
      "exempt_chatbots_by_mode": {},
      "allowed_chatbot_reply_modes": [],
      "can_create_chatbot": true,
      "create_chatbot_limit": 1,
      "current_month_words_count_total": 1000000,
      "current_month_used_words_count_total": 0,
      "current_month_used_conversations_count_total": 0,
      "available_upload_files_size_total": 104857600,
      "used_upload_file_size_total": 0
    },
    "organization_plan": {
      "id": "cac825e8-cb9b-4a16-b440-4ff6b2e73911",
      "plan_name": "Free Plan",
      "expired_at": null
    },
    "is_trial": false,
    "expiration_days": null
  };

axios.put("https://api.maiagent.ai/api/v1/organizations/550e8400-
e29b-41d4-a716-446655440000/", data, config)
  .then(response => {
```

```
  console.log('Response received successfully:');
  console.log(response.data);
})
.catch(error => {
  console.error('An error occurred during the request:');
  console.error(error.response?.data || error.message);
});
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-
41d4-a716-446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# Request body (payload)
data = {
    "id": "5b01e0b9-0b0e-4079-8150-d12015576d2c",
    "name": "Updated Org Name",
    "created_at": "1748336288000",
    "usage_statistics": {
        "chatbots_count": 0,
        "countable_chatbots_count": 0,
        "exempt_chatbots_by_mode": {},
        "allowed_chatbot_reply_modes": [],
        "can_create_chatbot": True,
        "create_chatbot_limit": 1,
        "current_month_words_count_total": 1000000,
        "current_month_used_words_count_total": 0,
        "current_month_used_conversations_count_total": 0,
        "available_upload_files_size_total": 104857600,
        "used_upload_file_size_total": 0
    },
    "organization_plan": {
        "id": "cac825e8-cb9b-4a16-b440-4ff6b2e73911",
        "plan_name": "Free Plan",
        "expired_at": None
    },
    "is_trial": False,
    "expiration_days": None
}

response = requests.put(url, json=data, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
```

```
except Exception as e:
    print("An error occurred during the request:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>put("https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-
41d4-a716-446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'id' => '5b01e0b9-0b0e-4079-8150-d12015576d2c',
            'name' => 'Updated Org Name',
            'created_at' => '1748336288000',
            'usage_statistics' => [
                'chatbots_count' => 0,
                'countable_chatbots_count' => 0,
                'exempt_chatbots_by_mode' => new \stdClass(),
                'allowed_chatbot_reply_modes' => [],
                'can_create_chatbot' => true,
                'create_chatbot_limit' => 1,
                'current_month_words_count_total' => 1000000,
                'current_month_used_words_count_total' => 0,
                'current_month_used_conversations_count_total' => 0,
                'available_upload_files_size_total' => 104857600,
                'used_upload_file_size_total' => 0
            ],
            'organization_plan' => [
                'id' => 'cac825e8-cb9b-4a16-b440-4ff6b2e73911',
                'plan_name' => 'Free Plan',
                'expired_at' => null
            ],
            'is_trial' => false,
            'expiration_days' => null
        ]
    ]);
```

```
    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request failed: ' . $e->getMessage();
}
?>
```

Response

Status code: 200

Example Response Schema

```
{
  "id": string (uuid) // Organization ID
  "name": string // Organization name
  "created_at": string (timestamp) // Creation timestamp
  "usage_statistics": { // Usage statistics
  {
    "chatbots_count"?: integer // Number of chatbots (optional)
    "countable_chatbots_count"?: integer // Number of chatbots that count
toward the creation quota (chatbots with modes outside the plan allowlist
are excluded) (optional)
    "exempt_chatbots_by_mode"?: object // Number of chatbots excluded
from the quota, grouped by the mode that exempts them (optional)
    "allowed_chatbot_reply_modes"?: [ // Allowlist of reply modes
permitted for chatbot creation under the plan (an empty array means no
restrictions) (optional)
      string
    ]
    "can_create_chatbot"?: boolean // Whether a chatbot can be created
(optional)
    "create_chatbot_limit"?: integer // Maximum number of chatbots that
can be created (-1 means unlimited; 0 means creation is prohibited)
(optional)
    "current_month_words_count_total"?: integer // Total word limit for
```

```
the current month (optional)
    "current_month_used_words_count_total"?: integer // Words used this
month (optional)
    "current_month_used_conversations_count_total"?: integer //
Conversations used this month (optional)
    "available_upload_files_size_total"?: integer // Total size available
for file uploads (bytes) (optional)
    "used_upload_file_size_total"?: integer // Size used by uploaded
files (bytes) (optional)
  }
  }
  "organization_plan": { // Organization plan information
  {
    "id"?: string (uuid) // Plan ID (optional)
    "plan_name"?: string // Plan name (optional)
    "expired_at"?: string (date-time) // Expiration time (optional)
  }
  }
  "is_trial"?: boolean // Whether the organization is in a trial period.
True when the organization has exactly one trial plan and it is currently
active (optional)
  "expiration_days"?: integer // Days since expiration. A positive number
indicates days since expiration; null indicates a plan that has not
expired or a permanent plan (optional)
}
```

Example Response Values


```
{
  "id": "5b01e0b9-0b0e-4079-8150-d12015576d2c",
  "name": "Updated Org Name",
  "created_at": "1748336288000",
  "usage_statistics": {
    "chatbots_count": 0,
    "countable_chatbots_count": 0,
    "exempt_chatbots_by_mode": {},
    "allowed_chatbot_reply_modes": [],
    "can_create_chatbot": true,
    "create_chatbot_limit": 1,
    "current_month_words_count_total": 1000000,
    "current_month_used_words_count_total": 0,
    "current_month_used_conversations_count_total": 0,
    "available_upload_files_size_total": 104857600,
    "used_upload_file_size_total": 0
```

```
  },
  "organization_plan": {
    "id": "cac825e8-cb9b-4a16-b440-4ff6b2e73911",
    "plan_name": "Free Plan",
    "expired_at": null
  },
  "is_trial": false,
  "expiration_days": null
}
```


Update Current User Details

PUT `/api/v1/users/current/`

Request Body

Request Parameters

Field	Type	Required	Description
avatar	string (uri)	No	
originalAvatar	string (uri)	No	Original avatar image uploaded by the user (long edge capped at 2048px). Each edit re-crops from this image to avoid cumulative distortion from cropping an already-cropped result. Legacy data from before this feature launched is empty and is not backfilled
avatarCropBox	object	No	Position and size of the last crop box on the original image (x/y/width/height, with optional rotate/scale_x/scale_y); coordinates are relative to the stored original image
name	string	Yes	

Field	Type	Required	Description
email	string (email)	Yes	
company	string	No	
invitationCode	object	No	

Request Schema Example

```
{
  "avatar"?: string (uri) // Optional
  "originalAvatar"?: string (uri) // Original avatar uploaded by the user (long edge limited to 2048px). Every edit re-crops from this image to avoid cumulative distortion from cropping an already-cropped result. Legacy data created before this feature launched is empty and is not backfilled (Optional)
  "avatarCropBox"?: object // Position and size of the last crop box on the original image (x/y/width/height, with optional rotate/scale_x/scale_y); coordinates are relative to the stored original image (Optional)
  "name": string
  "email": string (email)
  "company"?: string // Optional
  "invitationCode"?: // Can be of different types (Optional)
  string // Optional
}
```

Example Request Values

```
{
  "avatar": "https://example.com/file.jpg",
  "originalAvatar": "https://example.com/file.jpg",
  "avatarCropBox": null,
  "name": "Example name",
  "email": "user@example.com",
  "company": "Example string",
  "invitationCode": null
}
```

Code Examples

Shell/Bash

```
# Example API call (Shell)
curl -X PUT "https://api.maiagent.ai/api/v1/users/current/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# Make sure to replace YOUR_API_KEY and verify the request data
before running.
```

JavaScript

```
const axios = require('axios');
const FormData = require('form-data');

// Create FormData object
const formData = new FormData();
// Add form fields

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    ...formData.getHeaders()
  }
};

axios.put("https://api.maiagent.ai/api/v1/users/current/", formData,
config)
  .then(response => {
    console.log('Successfully retrieved response:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/users/current/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}

# Create file and form data
files = {
    'file': ('example.pdf', open('example.pdf', 'rb'),
'application/pdf')
}

response = requests.put(url, files=files, headers=headers)
try:
    print("Successfully retrieved response:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>put("https://api.maiagent.ai/api/v1/users/current/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ],
        'multipart' => [
            [
                'name' => 'file',
                'contents' => fopen('example.pdf', 'r'),
                'filename' => 'example.pdf'
            ]
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Successfully retrieved response:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response Body

Status Code: 200

Response Schema Example

```
{
  "id": string (uuid)
  "avatar"?: string (uri) // Optional
  "originalAvatar"?: string (uri) // Original avatar uploaded by the user
(long edge limited to 2048px). Every edit re-crops from this image to
avoid cumulative distortion from cropping an already-cropped result.
Legacy data created before this feature launched is empty and is not
backfilled (Optional)
  "avatarCropBox"?: object // Position and size of the last crop box on
the original image (x/y/width/height, with optional
rotate/scale_x/scale_y); coordinates are relative to the stored original
image (Optional)
  "name": string
  "email": string (email)
  "authSource":
  {
    "id": string (uuid)
    "name": string
  }
  "company"?: string // Optional
  "invitationCode"?: // Can be of different types (Optional)
  string // Optional
  "apiKeys": [ // Get the list of the user's API keys in the specified
organization.

Flow:
1. Get the current organization instance from the request
2. If there is no organization instance (usually during third-party SSO
login), use the user's authentication source
   to look up that authentication source's default organization
(is_auth_source_default_organization=True)

Note:
<ul>
  <li>The request does not contain organization_instance during third-
party SSO login</li>
  <li>The organization must be located via the auth_source and
is_auth_source_default_organization flags</li>
</ul>
    object
  ]
  "permissions": object // Get the user's permissions in the current
organization (nested parent-child structure).
```

```
  "resourcePermissions": object // Get the user's resource creation
permissions in the current organization.
  "isOwner": boolean // Determine whether the user is an Owner in the
current organization.
  "maigptCapabilities": object // Effective built-in feature capabilities
of the member in MaiGPT (role permission resolution result), used by the
frontend to show/hide features.

When there is no member context (not bound to an organization), the
resolved result is all enabled, consistent with the resolver's "do not
lock out on missing data"
behavior; hiding in the frontend is only a UX layer, and the
authoritative check is the gate on the reply path.
}
```

Example Response Values

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "avatar": "https://example.com/file.jpg",
  "originalAvatar": "https://example.com/file.jpg",
  "avatarCropBox": null,
  "name": "Response string",
  "email": "response@example.com",
  "authSource": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Response string"
  },
  "company": "Response string",
  "invitationCode": "Response string",
  "apiKeys": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "Example response name",
      "description": "Example response description"
    }
  ],
  "permissions": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Example response name",
    "description": "Example response description"
  },
  "resourcePermissions": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
```

```
    "name": "Example response name",
    "description": "Example response description"
  },
  "isOwner": false,
  "maigptCapabilities": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Example response name",
    "description": "Example response description"
  }
}
```


Update Member Roles

POST `/api/v1/organizations/{organizationPk}/members/{id}/update-groups/`

Parameters

Parameter Name	Required	Type	Description
`id`	V	string	A UUID string identifying this member.
`organizationPk`	V	string	A UUID string identifying this organization ID

Request Body

Request Parameters

Field	Type	Required	Description
groups	array[string]	Yes	

Request Schema Example

```
{
  "groups": [
    string (uuid)
  ]
}
```

Request Example Values

```
{
  "groups": [
    "4e368ab4-c543-48a2-bbb8-f6f5a0bf6c61",
    "5f479bc5-d654-59b3-ccc9-g7g6b1cg7d72"
  ]
}
```

Code Examples

Shell/Bash

```
# API call example (Shell)
curl -X POST "https://api.maiagent.ai/api/v1/organizations/550e8400-
e29b-41d4-a716-446655440000/members/550e8400-e29b-41d4-a716-
446655440000/update-groups/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "groups": [
      "4e368ab4-c543-48a2-bbb8-f6f5a0bf6c61",
      "5f479bc5-d654-59b3-ccc9-g7g6b1cg7d72"
    ]
  }'

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// Request body (payload)
const data = {
    "groups": [
      "4e368ab4-c543-48a2-bbb8-f6f5a0bf6c61",
      "5f479bc5-d654-59b3-ccc9-g7g6b1cg7d72"
    ]
  };

axios.post("https://api.maiagent.ai/api/v1/organizations/550e8400-
e29b-41d4-a716-446655440000/members/550e8400-e29b-41d4-a716-
446655440000/update-groups/", data, config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request failed:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-
41d4-a716-446655440000/members/550e8400-e29b-41d4-a716-
446655440000/update-groups/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# Request body (payload)
data = {
    "groups": [
        "4e368ab4-c543-48a2-bbb8-f6f5a0bf6c61",
        "5f479bc5-d654-59b3-ccc9-g7g6b1cg7d72"
    ]
}

response = requests.post(url, json=data, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request failed:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>post("https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-
41d4-a716-446655440000/members/550e8400-e29b-41d4-a716-
446655440000/update-groups/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'groups' => [
                '4e368ab4-c543-48a2-bbb8-f6f5a0bf6c61',
                '5f479bc5-d654-59b3-ccc9-g7g6b1cg7d72'
            ]
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request failed: ' . $e->getMessage();
}
?>
```

Response Body

Status Code: 200

Response Schema Example

```
{
  "id": string (uuid)
  "name": string
  "displayName": string // Name set by the organization owner for this
organization only; empty string when not set (``name`` then falls back to
the account name).
  "accountName": string // Account name of the member (shared across
organizations); shown when display name is cleared.
  "isScimManaged": boolean // True when the member is provisioned by
SCIM; the identity provider manages the member and the organization name
cannot be changed manually.
  "email": string
  "isActive": boolean
  "isOwner": boolean // Check whether the member is the organization
owner (via the OWNER Group)

Use caching to avoid duplicate queries within the same request
Cache lifetime: valid for the lifetime of the member instance

Prefer annotation results (when available) to avoid duplicate queries
  "permissions": [ // Compute the permission tree once per (organization,
custom-group set) per request.

The tree depends only on the member's organization (default groups,
feature
flags, plan whitelist), the member's custom groups, and the global
``Config``,
so members sharing a group set get the same result. A large role's
``pagination=false`` listing otherwise recomputes it per row — one Redis
``Config`` fetch plus the permission walk each time (issue #8436; the
largest
prod role has 3,837 members and a single group set). The memo lives in
the
serializer context, so it never outlives the request. Rows without the
eager
loaded ``_custom_groups_cache`` (single-object paths) keep computing
directly.
    object
  ]
  "groups": [
    object
```

```
  ]
  "creditQuotaRequired"?: boolean // When True, member must have an
active quota to consume credits (Optional)
  "activeQuota": object // Return the most recent quota summary (active
first), via prefetch to avoid N+1.
  "metadata": object // Organization-scoped member attributes, injected
into LLM system prompt
  "availabilityStatus":  // Self-declared availability for auto-
assignment. Paused members are skipped by the dispatch engine but can
still be manually assigned or claim conversations. Not touched by SCIM
provisioning.

* `available` - Available
* `paused` - Paused
  {
  }
  "createdAt": string (timestamp)
}
```

Response Example Values

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "name": "Response string",
  "displayName": "Response string",
  "accountName": "Response string",
  "isScimManaged": false,
  "email": "Response string",
  "isActive": false,
  "isOwner": false,
  "permissions": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "Example response name",
      "description": "Example response description"
    }
  ],
  "groups": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "Example response name",
      "description": "Example response description"
    }
  ],
```

```
  "creditQuotaRequired": false,
  "activeQuota": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Example response name",
    "description": "Example response description"
  },
  "metadata": null,
  "availabilityStatus": {},
  "createdAt": "Response string"
}
```


Status Code: 400

Response Schema Example


```
object
```


Update member name

PATCH `/api/v1/organizations/{organizationPk}/members/{id}/display-name/`

Required permissions: Only the organization owner can call this endpoint; non-owners receive 403 even if they have member management permissions. This changes only the member’ s display name in this organization (organization-specific name), without changing their account name or affecting other organizations they belong to. Other member data, including roles, quotas, and custom attributes, is unaffected. Leading and trailing whitespace in displayName is trimmed. The name can contain up to 255 characters and does not need to be unique. An empty or whitespace-only string clears the name, so the account name (accountName) is displayed instead. If the value matches the current display name (name, which falls back to the account name when no organization-specific name is set), it is treated as unchanged: nothing is written, no activity is logged, and 200 is still returned. If the member is managed by SCIM (isScimManaged is true), the endpoint returns 400; change the name in the identity provider instead. It returns 404 if the member does not belong to this organization. On success, it returns the same member object as “Get specific member details”, with name containing the new display name. Actual changes are recorded in the organization’ s activity log.

Parameters

Parameter name	Required	Type	Description
`id`	V	string	A UUID string identifying this member.
`organizationPk`	V	string	A UUID string identifying this organization ID

Request body

Request parameters

Field	Type	Required	Description
displayName	string	Yes	New name of the member in this organization. Leading/trailing whitespace is trimmed; an empty or whitespace-only value clears it so the account name is shown again.

Request schema example

```
{
  "displayName": string // New name of the member in this organization.
Leading/trailing whitespace is trimmed; an empty or whitespace-only value
clears it so the account name is shown again.
}
```

Example request values

```
{
  "displayName": "Example string"
}
```

Code examples

Shell/Bash

```
# API call example (Shell)
curl -X PATCH
"https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-41d4-
a716-446655440000/members/550e8400-e29b-41d4-a716-
446655440000/display-name/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "displayName": "Example string"
  }'

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// Request body (payload)
const data = {
    "displayName": "Example string"
  };

axios.patch("https://api.maiagent.ai/api/v1/organizations/550e8400-
e29b-41d4-a716-446655440000/members/550e8400-e29b-41d4-a716-
446655440000/display-name/", data, config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request failed:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-
41d4-a716-446655440000/members/550e8400-e29b-41d4-a716-
446655440000/display-name/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# Request body (payload)
data = {
    "displayName": "Example string"
}

response = requests.patch(url, json=data, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request failed:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>patch("https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-
41d4-a716-446655440000/members/550e8400-e29b-41d4-a716-
446655440000/display-name/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'displayName' => 'Example string'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request failed: ' . $e->getMessage();
}
?>
```

Response body

Status code: 200

Response schema example

```
{
  "id": string (uuid)
  "name": string
  "displayName": string // Name set by the organization owner for this
organization only; empty string when not set (``name`` then falls back to
the account name).
  "accountName": string // Account name of the member (shared across
organizations); shown when display name is cleared.
  "isScimManaged": boolean // True when the member is provisioned by
SCIM; the identity provider manages the member and the organization name
cannot be changed manually.
  "email": string
  "isActive": boolean
  "isOwner": boolean // Check whether the member is the organization
owner (via the OWNER Group)

Use caching to avoid duplicate queries within the same request
Cache lifetime: valid for the lifetime of the member instance

Prefer annotation results, if available, to avoid duplicate queries
  "permissions": [ // Compute the permission tree once per (organization,
custom-group set) per request.

The tree depends only on the member's organization (default groups,
feature
flags, plan whitelist), the member's custom groups, and the global
``Config``,
so members sharing a group set get the same result. A large role's
``pagination=false`` listing otherwise recomputes it per row — one Redis
``Config`` fetch plus the permission walk each time (issue #8436; the
largest
prod role has 3,837 members and a single group set). The memo lives in
the
serializer context, so it never outlives the request. Rows without the
eager
loaded ``_custom_groups_cache`` (single-object paths) keep computing
directly.
    object
  ]
  "groups": [
    object
  ]
  "creditQuotaRequired"?: boolean // When True, member must have an
active quota to consume credits (Optional)
```

```
  "activeQuota": object // Return the most recent quota summary (active
first), via prefetch to avoid N+1.
  "metadata": object // Organization-scoped member attributes, injected
into LLM system prompt
  "availabilityStatus":  // Self-declared availability for auto-
assignment. Paused members are skipped by the dispatch engine but can
still be manually assigned or claim conversations. Not touched by SCIM
provisioning.

* `available` - Available
* `paused` - Paused
  {
  }
  "createdAt": string (timestamp)
}
```

Example response values


```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "name": "Response string",
  "displayName": "Response string",
  "accountName": "Response string",
  "isScimManaged": false,
  "email": "Response string",
  "isActive": false,
  "isOwner": false,
  "permissions": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "Example response name",
      "description": "Example response description"
    }
  ],
  "groups": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "Example response name",
      "description": "Example response description"
    }
  ],
  "creditQuotaRequired": false,
  "activeQuota": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
```

```
    "name": "Example response name",
    "description": "Example response description"
  },
  "metadata": null,
  "availabilityStatus": {},
  "createdAt": "Response string"
}
```

Status code: 400 - The member is managed by SCIM, the name exceeds 255 characters, or displayName is missing

Response schema example

```
{
  "displayName"?: [ // Error reason: The member is managed by SCIM, the name exceeds 255 characters, or displayName is missing (Optional)
    string
  ]
}
```

Example response values

```
{
  "displayName": [
    "This member’s name is managed by the identity provider (SCIM) and cannot be changed manually"
  ]
}
```

Status code: 403 - The caller is not the organization owner

Response schema example

```
{
  "detail"?: string // Optional
}
```

Example response values

```
{
  "detail": "Only the organization owner can change the name"
}
```


Status code: 404 - The member does not exist or does not belong to this organization

Invite members to the organization

POST `/api/v1/auth/unified-invitations/`

The organization associated with the API Key is used. Organization overview permission is required (organization owners are exempt). emails accepts up to 100 addresses per request. Registered users become members immediately (returned in members); unregistered email addresses receive invitations and join after registration (returned in mailInvitations). Existing members are listed in skippedEmails. groups specifies the roles assigned on joining, in the format [{"id": "Role ID"}]. Include creditQuota to preset individual quotas for this batch of invitees, allocated only when they join: quotaLimit (required), validUntil (optional; an ISO 8601 string such as 2026-12-31T23:59:59+08:00, or a 13-digit millisecond timestamp as a string or number; Taiwan time is used if no time zone is specified; must be in the future; omitting it means no expiration), resetPeriod (none
daily
weekly
monthly, default none), and note (optional). Including creditQuota also requires Credit management permission, and the organization must use Credit billing. If omitted, the default quota for new members applies if enabled.

Request body

Request parameters

Field	Type	Required	Description
creditQuota	object (with 4 properties: quotaLimit, validUntil, resetPeriod...)	No	Optional credit quota allocated to the invitee when they join.
creditQuota.quotaLimit	string (decimal)	Yes	
creditQuota.validUntil	object	No	ISO 8601 date-time or 13-digit epoch milliseconds (string or number).
creditQuota.resetPeriod	object	No	
creditQuota.note	string	No	
groups	array[IdName]	No	
emails	array[string]	Yes	Email address list to invite. Up to 100 emails.

Request schema example

```
{
  "creditQuota"?:  // Optional credit quota allocated to the invitee when
they join. (Optional)
  {
    "quotaLimit": string (decimal)
    "validUntil"?: // May have different types (Optional)
    string (date-time) // ISO 8601 date-time or 13-digit epoch
milliseconds (string or number). (Optional)
    "resetPeriod"?:  // Optional
    {
    }
    "note"?: string // Optional
  }
  "groups"?: [ // Optional
    {
      "id": string (uuid)
    }
  ]
  "emails": [ // Email address list to invite. Up to 100 emails.
    string (email)
```

```
  ]
}
```

Example request values

```
{
  "emails": [
    "user@example.com",
    "user2@example.com"
  ],
  "groups": [
    {
      "id": "12345678-1234-5678-1234-567812345678"
    }
  ]
}
```

Code examples

Shell/Bash

```
# API call example (Shell)
curl -X POST "https://api.maiagent.ai/api/v1/auth/unified-
invitations/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "emails": [
      "user@example.com",
      "user2@example.com"
    ],
    "groups": [
      {
        "id": "12345678-1234-5678-1234-567812345678"
      }
    ]
  }'

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// Request body (payload)
const data = {
    "emails": [
      "user@example.com",
      "user2@example.com"
    ],
    "groups": [
      {
        "id": "12345678-1234-5678-1234-567812345678"
      }
    ]
  };

axios.post("https://api.maiagent.ai/api/v1/auth/unified-
invitations/", data, config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request failed:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/auth/unified-invitations/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# Request body (payload)
data = {
    "emails": [
        "user@example.com",
        "user2@example.com"
    ],
    "groups": [
        {
            "id": "12345678-1234-5678-1234-567812345678"
        }
    ]
}

response = requests.post(url, json=data, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request failed:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>post("https://api.maiagent.ai/api/v1/auth/unified-invitations/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'emails' => [
                'user@example.com',
                'user2@example.com'
            ],
            'groups' => [
                [
                    'id' => '12345678-1234-5678-1234-567812345678'
                ]
            ]
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request failed: ' . $e->getMessage();
}
?>
```

Response body

Status code: 200

Response schema example

```
{
  "members": [
    {
      "id": string (uuid)
      "email": string (email)
      "name": string
    }
  ]
  "mailInvitations": [
    {
      "creditQuota":
      {
        "quotaLimit": string (decimal)
        "validUntil": string (date-time)
        "resetPeriod":
        {
        }
        "note": string
      }
      "creditQuotaSource": string
      "id": string (uuid)
      "email": string (email)
      "displayStatus": string
      "code": string
      "inviter": string (uuid)
      "organization"?: string (uuid) // Optional
      "groups"?: [ // Optional
        {
          "id": string (uuid)
          "name": string
        }
      ]
      "createdAt"?: string (timestamp) // Optional
      "acceptedAt"?: string (timestamp) // Optional
      "lastSentAt": string (timestamp)
      "failureReason": string
```

```
      "retryCount": integer
      "canResend": boolean
    }
  ]
  "skippedEmails": [
    string (email)
  ]
}
```

Example response values

```
{
  "members": [
    {
      "id": "33333333-3333-3333-3333-333333333333",
      "email": "user2@example.com",
      "name": "User Two"
    }
  ],
  "mailInvitations": [
    {
      "id": "87654321-4321-8765-4321-876543210000",
      "email": "user@example.com",
      "displayStatus": "pending",
      "creditQuota": {
        "quotaLimit": "500.000000",
        "validUntil": "2026-12-31T15:59:59+00:00",
        "resetPeriod": "monthly",
        "note": "New employee quota"
      },
      "creditQuotaSource": "invitation_override"
    }
  ],
  "skippedEmails": []
}
```

Status code: `400` - Invalid request body, such as an invalid email format, a nonexistent role, an invalid or expired `creditQuota.validUntil`, or `creditQuota` provided for an organization that does not use Credit billing

Status code: `403` - Missing organization overview permission, `creditQuota` provided without Credit management permission, or a non-owner assigning the owner role or reinviting a pending invitation with the owner role

List organization email invitation records

`GET` `/api/v1/auth/organization-mail-invitations/`

Query invitation delivery and acceptance status. Filter with status, which accepts multiple values (for example, status=pending&status=mail_failed); omit it to return all statuses. Set pagination=false to disable pagination. Users with organization overview permission can see invitations across the organization (only organization owners can see invitations assigning the owner role). Other users can see only invitations they sent.

Parameters

Parameter name	Required	Type	Description
`pagination`	X	boolean	Whether to paginate
`status`	X	string	Invitation status; multiple values are supported (for example, status=pending&status=mail_failed). Omit to return all statuses

Code examples

Shell/Bash

```
# API call example (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/auth/organization-mail-
invitations/?pagination=true&status=accepted"

  -H "Authorization: Api-Key YOUR_API_KEY"

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/auth/organization-mail-
invitations/?pagination=true&status=accepted", config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request failed:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/auth/organization-mail-
invitations/?pagination=true&status=accepted"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request failed:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/auth/organization-mail-
invitations/?pagination=true&status=accepted", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request failed: ' . $e->getMessage();
}
?>
```

Response body

Status code: 200

Response schema example

```
[
  {
    "creditQuota":
```

```
    {
      "quotaLimit": string (decimal)
      "validUntil": string (date-time)
      "resetPeriod":
      {
      }
      "note": string
    }
    "creditQuotaSource": string
    "id": string (uuid)
    "email": string (email)
    "displayStatus": string
    "code": string
    "inviter": string (uuid)
    "organization"?: string (uuid) // Optional
    "groups"?: [ // Optional
      {
        "id": string (uuid)
        "name": string
      }
    ]
    "createdAt"?: string (timestamp) // Optional
    "acceptedAt"?: string (timestamp) // Optional
    "lastSentAt": string (timestamp)
    "failureReason": string
    "retryCount": integer
    "canResend": boolean
  }
]
```

Example response values

```
[
  {
    "creditQuota": {
      "quotaLimit": "Response string",
      "validUntil": "2026-12-31T23:59:59+08:00",
      "resetPeriod": {},
      "note": "Response string"
    },
    "creditQuotaSource": "Response string",
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "email": "response@example.com",
    "displayStatus": "Response string",
```

```
    "code": "Response string",
    "inviter": "550e8400-e29b-41d4-a716-446655440000",
    "organization": "550e8400-e29b-41d4-a716-446655440000",
    "groups": [
      {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "name": "Response string"
      }
    ],
    "createdAt": "Response string",
    "acceptedAt": "Response string",
    "lastSentAt": "Response string",
    "failureReason": "Response string",
    "retryCount": 456,
    "canResend": false
  }
]
```


Resend organization invitation email

POST `/api/v1/auth/organization-mail-invitations/{id}/resend/`

Requires organization overview permission. No request body is needed. Only pending invitations or invitations with failed delivery can be resent (accepted or revoked invitations return 400). An invitation can be resent up to 3 times, at intervals of at least 5 minutes.

Parameters

Parameter name	Required	Type	Description
`id`	V	string	

Code examples

Shell/Bash

```
# Example API call (Shell)
curl -X POST "https://api.maiagent.ai/api/v1/auth/organization-mail-invitations/550e8400-e29b-41d4-a716-446655440000/resend/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

// Request body (payload)
const data = null;

axios.post("https://api.maiagent.ai/api/v1/auth/organization-mail-
invitations/550e8400-e29b-41d4-a716-446655440000/resend/", data,
config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/auth/organization-mail-
invitations/550e8400-e29b-41d4-a716-446655440000/resend/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.post(url, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>post("https://api.maiagent.ai/api/v1/auth/organization-mail-
invitations/550e8400-e29b-41d4-a716-446655440000/resend/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response

Status code: 200

Example response schema

```
{
  "creditQuota":
  {
```

```
    "quotaLimit": string (decimal)
    "validUntil": string (date-time)
    "resetPeriod":
    {
    }
    "note": string
  }
  "creditQuotaSource": string
  "id": string (uuid)
  "email": string (email)
  "displayStatus": string
  "code": string
  "inviter": string (uuid)
  "organization"?: string (uuid) // Optional
  "groups"?: [ // Optional
    {
      "id": string (uuid)
      "name": string
    }
  ]
  "createdAt"?: string (timestamp) // Optional
  "acceptedAt"?: string (timestamp) // Optional
  "lastSentAt": string (timestamp)
  "failureReason": string
  "retryCount": integer
  "canResend": boolean
}
```

Example response values

```
{
  "creditQuota": {
    "quotaLimit": "Response string",
    "validUntil": "2026-12-31T23:59:59+08:00",
    "resetPeriod": {},
    "note": "Response string"
  },
  "creditQuotaSource": "Response string",
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "email": "response@example.com",
  "displayStatus": "Response string",
  "code": "Response string",
  "inviter": "550e8400-e29b-41d4-a716-446655440000",
  "organization": "550e8400-e29b-41d4-a716-446655440000",
```

```
  "groups": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "Response string"
    }
  ],
  "createdAt": "Response string",
  "acceptedAt": "Response string",
  "lastSentAt": "Response string",
  "failureReason": "Response string",
  "retryCount": 456,
  "canResend": false
}
```


List Organization API Keys

`GET` `/api/v1/organizations/{organizationPk}/api-keys/`

API key management for administrators requires the API Key Management permission. Members can hold multiple active keys at the same time, allowing you to issue a new key, deploy it, and then revoke the old one. See API Authentication for how to obtain a key.

Parameters

Parameter Name	Required	Type	Description
`organizationPk`	V	string	A UUID string identifying this organization ID
`page`	X	integer	A page number within the paginated result set.
`pageSize`	X	integer	Number of results to return per page.
`query`	X	string	

`source`	X	string	
`status`	X	string	

Code Examples

Shell/Bash

```
# API call example (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/organizations/550e8400-
e29b-41d4-a716-446655440000/api-keys/?
page=1&pageSize=1&query=example&source=example&status=example"

  -H "Authorization: Api-Key YOUR_API_KEY"

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/organizations/550e8400-
e29b-41d4-a716-446655440000/api-keys/?
page=1&pageSize=1&query=example&source=example&status=example",
config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request failed:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-
41d4-a716-446655440000/api-keys/?
page=1&pageSize=1&query=example&source=example&status=example"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request failed:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-
41d4-a716-446655440000/api-keys/?
page=1&pageSize=1&query=example&source=example&status=example", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request failed: ' . $e->getMessage();
}
?>
```

Response Body

Status Code: 200

Response Schema Example

```
{
  "count": integer
```

```
  "next"?: string (uri) // Optional
  "previous"?: string (uri) // Optional
  "results": [
    {
      "id": string
      "name"?: string // A free-form name for the API key. Need not be
unique. 50 characters max. (Optional)
      "prefix": string
      "status": string
      "source": string
      "isActive"?: boolean // Reversible enable switch. A disabled key is
rejected exactly like an unknown key (generic 401, no information leak),
but keeps its secret and usage history and can be re-enabled at any time
— unlike the irreversible revoked flag. (Optional)
      "rateLimitRpm"?: integer // Max requests per minute across every
platform API this key can call. Null = unlimited. (Optional)
      "rateLimitTpm"?: integer // Max LLM tokens per minute through the
AI Gateway inference endpoints. Null = unlimited. (Optional)
      "creditBudgetDaily"?: string (decimal) // Max credits this key may
spend through the AI Gateway per natural day (Asia/Taipei). Once reached,
further inference calls are refused with 402 key_budget_exceeded until
the next day. Null = unlimited. (Optional)
      "creditBudgetMonthly"?: string (decimal) // Max credits this key
may spend through the AI Gateway per calendar month (Asia/Taipei). Once
reached, further inference calls are refused with 402 key_budget_exceeded
until the next month. Null = unlimited. (Optional)
      "creditUsedToday": string (decimal)
      "creditUsedThisMonth": string (decimal)
      "gatewayAllowedLlmCount": integer // Size of the gateway allow-
list, when the queryset annotated it.

0 means "no restriction" (see ``api_key_allowed_llm_ids``). ``None``
on surfaces that did not annotate (login payload, PAT list) so a
missing count is never mistaken for "unrestricted".
      "expiryDate"?: string (timestamp) // Once API key expires, clients
cannot use it anymore. (Optional)
      "createdAt": string (timestamp)
      "lastUsedAt"?: string (timestamp) // Optional
      "member": object
      "createdByName": string
      "revokedAt"?: string (timestamp) // Optional
      "revokedByName": string
    }
```

```
  ]
}
```

Response Example Values


```
{
  "count": 123,
  "next": "http://api.example.org/accounts/?page=4",
  "previous": "http://api.example.org/accounts/?page=2",
  "results": [
    {
      "id": "Response string",
      "name": "Response string",
      "prefix": "Response string",
      "status": "Response string",
      "source": "Response string",
      "isActive": false,
      "rateLimitRpm": 456,
      "rateLimitTpm": 456,
      "creditBudgetDaily": "Response string",
      "creditBudgetMonthly": "Response string",
      "creditUsedToday": "Response string",
      "creditUsedThisMonth": "Response string",
      "gatewayAllowedLlmCount": 456,
      "expiryDate": "Response string",
      "createdAt": "Response string",
      "lastUsedAt": "Response string",
      "member": {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "name": "Example response name",
        "description": "Example response description"
      },
      "createdByName": "Response string",
      "revokedAt": "Response string",
      "revokedByName": "Response string"
    }
  ]
}
```


Status Code: 403 - Insufficient permissions

Issue an API Key for a Member

POST `/api/v1/organizations/{organizationPk}/api-keys/`

Parameters

Parameter Name	Required	Type	Description
`organizationPk`	V	string	A UUID string identifying this organization ID

Request Body

Request Parameters

Field	Type	Required	Description
name	string	Yes	
expiryDate	string (timestamp)	No	
memberId	string (uuid)	Yes	
isActive	boolean	No	
creditBudgetDaily	string (decimal)	No	
creditBudgetMonthly	string (decimal)	No	

Request Schema Example

```
{
  "name": string
  "expiryDate"?: string (timestamp) // Optional
  "memberId": string (uuid)
```

```
  "isActive"?: boolean // Optional
  "creditBudgetDaily"?: string (decimal) // Optional
  "creditBudgetMonthly"?: string (decimal) // Optional
}
```

Request Example Values

```
{
  "name": "My API Key",
  "member_id": "00000000-0000-0000-0000-000000000000",
  "expiry_date": "2027-12-31T23:59:59Z"
}
```

Code Examples

Shell/Bash

```
# API call example (Shell)
curl -X POST "https://api.maiagent.ai/api/v1/organizations/550e8400-
e29b-41d4-a716-446655440000/api-keys/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "name": "My API Key",
    "member_id": "00000000-0000-0000-0000-000000000000",
    "expiry_date": "2027-12-31T23:59:59Z"
  }'

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// Request body (payload)
const data = {
    "name": "My API Key",
    "member_id": "00000000-0000-0000-0000-000000000000",
    "expiry_date": "2027-12-31T23:59:59Z"
  };

axios.post("https://api.maiagent.ai/api/v1/organizations/550e8400-
e29b-41d4-a716-446655440000/api-keys/", data, config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request failed:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-
41d4-a716-446655440000/api-keys/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# Request body (payload)
data = {
    "name": "My API Key",
    "member_id": "00000000-0000-0000-0000-000000000000",
    "expiry_date": "2027-12-31T23:59:59Z"
}

response = requests.post(url, json=data, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request failed:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>post("https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-
41d4-a716-446655440000/api-keys/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'name' => 'My API Key',
            'member_id' => '00000000-0000-0000-0000-000000000000',
            'expiry_date' => '2027-12-31T23:59:59Z'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request failed: ' . $e->getMessage();
}
?>
```

Response Body

Status Code: 201

Response Schema Example

```
{
  "id": string
  "name"?: string // A free-form name for the API key. Need not be
unique. 50 characters max. (Optional)
  "prefix": string
  "key": string // The full API key. Shown only in this response and
never stored, so it
cannot be retrieved again.
  "status": string
  "source": string
  "isActive"?: boolean // Reversible enable switch. A disabled key is
rejected exactly like an unknown key (generic 401, no information leak),
but keeps its secret and usage history and can be re-enabled at any time
— unlike the irreversible revoked flag. (Optional)
  "expiryDate"?: string (timestamp) // Once API key expires, clients
cannot use it anymore. (Optional)
  "createdAt": string (timestamp)
}
```

Response Example Values

```
{
  "id": "Response string",
  "name": "Response string",
  "prefix": "Response string",
  "key": "Response string",
  "status": "Response string",
  "source": "Response string",
  "isActive": false,
  "expiryDate": "Response string",
  "createdAt": "Response string"
}
```

Status Code: `400` - Validation error (e.g., an empty name or an expiry date in the past)

Status Code: `403` - Insufficient permissions

Retrieve a Specific API Key

GET `/api/v1/organizations/{organizationPk}/api-keys/{id}`

Parameters

Parameter Name	Required	Type	Description
`id`	V	string	
`organizationPk`	V	string	A UUID string identifying this organization ID

Code Examples

Shell/Bash

```
# API call example (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/organizations/550e8400-
e29b-41d4-a716-446655440000/api-keys/550e8400-e29b-41d4-a716-
446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/organizations/550e8400-
e29b-41d4-a716-446655440000/api-keys/550e8400-e29b-41d4-a716-
446655440000/", config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request failed:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-
41d4-a716-446655440000/api-keys/550e8400-e29b-41d4-a716-
446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request failed:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-
41d4-a716-446655440000/api-keys/550e8400-e29b-41d4-a716-
446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request failed: ' . $e->getMessage();
}
?>
```

Response Body

Status Code: 200

Response Schema Example

```
{
  "id": string
```

```
  "name"?: string // A free-form name for the API key. Need not be
unique. 50 characters max. (Optional)
  "prefix": string
  "status": string
  "source": string
  "isActive"?: boolean // Reversible enable switch. A disabled key is
rejected exactly like an unknown key (generic 401, no information leak),
but keeps its secret and usage history and can be re-enabled at any time
— unlike the irreversible revoked flag. (Optional)
  "rateLimitRpm"?: integer // Max requests per minute across every
platform API this key can call. Null = unlimited. (Optional)
  "rateLimitTpm"?: integer // Max LLM tokens per minute through the AI
Gateway inference endpoints. Null = unlimited. (Optional)
  "creditBudgetDaily"?: string (decimal) // Max credits this key may
spend through the AI Gateway per natural day (Asia/Taipei). Once reached,
further inference calls are refused with 402 key_budget_exceeded until
the next day. Null = unlimited. (Optional)
  "creditBudgetMonthly"?: string (decimal) // Max credits this key may
spend through the AI Gateway per calendar month (Asia/Taipei). Once
reached, further inference calls are refused with 402 key_budget_exceeded
until the next month. Null = unlimited. (Optional)
  "creditUsedToday": string (decimal)
  "creditUsedThisMonth": string (decimal)
  "gatewayAllowedLlmCount": integer // Size of the gateway allow-list,
when the queryset annotated it.

0 means "no restriction" (see ``api_key_allowed_llm_ids``). ``None``
on surfaces that did not annotate (login payload, PAT list) so a
missing count is never mistaken for "unrestricted".
  "expiryDate"?: string (timestamp) // Once API key expires, clients
cannot use it anymore. (Optional)
  "createdAt": string (timestamp)
  "lastUsedAt"?: string (timestamp) // Optional
  "member": object
  "createdByName": string
  "revokedAt"?: string (timestamp) // Optional
  "revokedByName": string
  "gatewayAllowedLlmIds": [
    string (uuid)
  ]
}
```

Example Response Values

```
{
  "id": "response string",
  "name": "response string",
  "prefix": "response string",
  "status": "response string",
  "source": "response string",
  "isActive": false,
  "rateLimitRpm": 456,
  "rateLimitTpm": 456,
  "creditBudgetDaily": "response string",
  "creditBudgetMonthly": "response string",
  "creditUsedToday": "response string",
  "creditUsedThisMonth": "response string",
  "gatewayAllowedLlmCount": 456,
  "expiryDate": "response string",
  "createdAt": "response string",
  "lastUsedAt": "response string",
  "member": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Example response name",
    "description": "Example response description"
  },
  "createdByName": "response string",
  "revokedAt": "response string",
  "revokedByName": "response string",
  "gatewayAllowedLlmIds": [
    "550e8400-e29b-41d4-a716-446655440000"
  ]
}
```


Update API Key Settings

`PATCH` `/api/v1/organizations/{organizationPk}/api-keys/{id}`

Adjust the enabled status, requests per minute (RPM), and expiration time. Disabling is reversible; use DELETE to revoke the key.

Parameters

Parameter Name	Required	Type	Description
`id`	V	string	
`organizationPk`	V	string	A UUID string identifying this organization ID

Request Body

Request Parameters

Field	Type	Required	Description
name	string	No	A free-form name for the API key. Need not be unique. 50 characters max.
isActive	boolean	No	Reversible enable switch. A disabled key is rejected exactly like an unknown key (generic 401, no information leak), but keeps its secret and usage history and can be re-enabled at any time — unlike t...
rateLimitRpm	integer	No	Max requests per minute across every platform API this key can call. Null = unlimited.
rateLimitTpm	integer	No	Max LLM tokens per minute through the AI Gateway inference endpoints. Null = unlimited.
creditBudgetDaily	string (decimal)	No	Max credits this key may spend through the AI Gateway per natural day (Asia/Taipei). Once reached, further inference calls are refused with 402 key_budget_exceeded

Field	Type	Required	Description
			until the next day. Null = unlimited...
creditBudgetMonthly	string (decimal)	No	Max credits this key may spend through the AI Gateway per calendar month (Asia/Taipei). Once reached, further inference calls are refused with 402 key_budget_exceeded until the next month. Null = unli...
expiryDate	string (timestamp)	No	Once API key expires, clients cannot use it anymore.
lastUsedAt	string (timestamp)	No	
revokedAt	string (timestamp)	No	

Example Request Schema

```
{
  "name"?: string // A free-form name for the API key. Need not be
unique. 50 characters max. (Optional)
  "isActive"?: boolean // Reversible enable switch. A disabled key is
rejected exactly like an unknown key (generic 401, no information leak),
but keeps its secret and usage history and can be re-enabled at any time
— unlike the irreversible revoked flag. (Optional)
  "rateLimitRpm"?: integer // Max requests per minute across every
platform API this key can call. Null = unlimited. (Optional)
  "rateLimitTpm"?: integer // Max LLM tokens per minute through the AI
Gateway inference endpoints. Null = unlimited. (Optional)
  "creditBudgetDaily"?: string (decimal) // Max credits this key may
spend through the AI Gateway per natural day (Asia/Taipei). Once reached,
further inference calls are refused with 402 key_budget_exceeded until
the next day. Null = unlimited. (Optional)
  "creditBudgetMonthly"?: string (decimal) // Max credits this key may
spend through the AI Gateway per calendar month (Asia/Taipei). Once
reached, further inference calls are refused with 402 key_budget_exceeded
until the next month. Null = unlimited. (Optional)
  "expiryDate"?: string (timestamp) // Once API key expires, clients
cannot use it anymore. (Optional)
```

```
  "lastUsedAt"?: string (timestamp) // Optional
  "revokedAt"?: string (timestamp) // Optional
}
```

Example Request Values

```
{
  "name": "Example name",
  "isActive": true,
  "rateLimitRpm": 123,
  "rateLimitTpm": 123,
  "creditBudgetDaily": "example string",
  "creditBudgetMonthly": "example string",
  "expiryDate": "example string",
  "lastUsedAt": "example string",
  "revokedAt": "example string"
}
```

Code Examples

Shell/Bash

```
# API call example (Shell)
curl -X PATCH
"https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-41d4-
a716-446655440000/api-keys/550e8400-e29b-41d4-a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "name": "Example name",
    "isActive": true,
    "rateLimitRpm": 123,
    "rateLimitTpm": 123,
    "creditBudgetDaily": "example string",
    "creditBudgetMonthly": "example string",
    "expiryDate": "example string",
    "lastUsedAt": "example string",
    "revokedAt": "example string"
  }'

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// Request Body (payload)
const data = {
    "name": "Example name",
    "isActive": true,
    "rateLimitRpm": 123,
    "rateLimitTpm": 123,
    "creditBudgetDaily": "example string",
    "creditBudgetMonthly": "example string",
    "expiryDate": "example string",
    "lastUsedAt": "example string",
    "revokedAt": "example string"
  };

axios.patch("https://api.maiagent.ai/api/v1/organizations/550e8400-
e29b-41d4-a716-446655440000/api-keys/550e8400-e29b-41d4-a716-
446655440000/", data, config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-
41d4-a716-446655440000/api-keys/550e8400-e29b-41d4-a716-
446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# Request Body (payload)
data = {
    "name": "Example name",
    "isActive": True,
    "rateLimitRpm": 123,
    "rateLimitTpm": 123,
    "creditBudgetDaily": "example string",
    "creditBudgetMonthly": "example string",
    "expiryDate": "example string",
    "lastUsedAt": "example string",
    "revokedAt": "example string"
}

response = requests.patch(url, json=data, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>patch("https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-
41d4-a716-446655440000/api-keys/550e8400-e29b-41d4-a716-
446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'name' => 'Example name',
            'isActive' => true,
            'rateLimitRpm' => 123,
            'rateLimitTpm' => 123,
            'creditBudgetDaily' => 'example string',
            'creditBudgetMonthly' => 'example string',
            'expiryDate' => 'example string',
            'lastUsedAt' => 'example string',
            'revokedAt' => 'example string'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response Body

Status Code: 200

Example Response Schema

```
{
  "id": string
  "name"?: string // A free-form name for the API key. Need not be
unique. 50 characters max. (Optional)
  "prefix": string
  "status": string
  "source": string
  "isActive"?: boolean // Reversible enable switch. A disabled key is
rejected exactly like an unknown key (generic 401, no information leak),
but keeps its secret and usage history and can be re-enabled at any time
— unlike the irreversible revoked flag. (Optional)
  "rateLimitRpm"?: integer // Max requests per minute across every
platform API this key can call. Null = unlimited. (Optional)
  "rateLimitTpm"?: integer // Max LLM tokens per minute through the AI
Gateway inference endpoints. Null = unlimited. (Optional)
  "creditBudgetDaily"?: string (decimal) // Max credits this key may
spend through the AI Gateway per natural day (Asia/Taipei). Once reached,
further inference calls are refused with 402 key_budget_exceeded until
the next day. Null = unlimited. (Optional)
  "creditBudgetMonthly"?: string (decimal) // Max credits this key may
spend through the AI Gateway per calendar month (Asia/Taipei). Once
reached, further inference calls are refused with 402 key_budget_exceeded
until the next month. Null = unlimited. (Optional)
  "creditUsedToday": string (decimal)
  "creditUsedThisMonth": string (decimal)
  "gatewayAllowedLlmCount": integer // Size of the gateway allow-list,
when the queryset annotated it.

0 means "no restriction" (see ``api_key_allowed_llm_ids``). ``None``
on surfaces that did not annotate (login payload, PAT list) so a
missing count is never mistaken for "unrestricted".
  "expiryDate"?: string (timestamp) // Once API key expires, clients
cannot use it anymore. (Optional)
  "createdAt": string (timestamp)
  "lastUsedAt"?: string (timestamp) // Optional
  "member": object
```

```
  "createdByName": string
  "revokedAt"?: string (timestamp) // Optional
  "revokedByName": string
  "gatewayAllowedLlmIds": [
    string (uuid)
  ]
}
```

Example Response Values

```
{
  "id": "response string",
  "name": "response string",
  "prefix": "response string",
  "status": "response string",
  "source": "response string",
  "isActive": false,
  "rateLimitRpm": 456,
  "rateLimitTpm": 456,
  "creditBudgetDaily": "response string",
  "creditBudgetMonthly": "response string",
  "creditUsedToday": "response string",
  "creditUsedThisMonth": "response string",
  "gatewayAllowedLlmCount": 456,
  "expiryDate": "response string",
  "createdAt": "response string",
  "lastUsedAt": "response string",
  "member": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Example response name",
    "description": "Example response description"
  },
  "createdByName": "response string",
  "revokedAt": "response string",
  "revokedByName": "response string",
  "gatewayAllowedLlmIds": [
    "550e8400-e29b-41d4-a716-446655440000"
  ]
}
```

Revoke API Key

DELETE `/api/v1/organizations/{organizationPk}/api-keys/{id}`

Parameters

Parameter Name	Required	Type	Description
`id`	V	string	
`organizationPk`	V	string	A UUID string identifying this Organization ID

Code Examples

Shell/Bash

```
# Example API Call (Shell)
curl -X DELETE
"https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-41d4-
a716-446655440000/api-keys/550e8400-e29b-41d4-a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

// Request Body (payload)
const data = null;

axios.delete("https://api.maiagent.ai/api/v1/organizations/550e8400-
e29b-41d4-a716-446655440000/api-keys/550e8400-e29b-41d4-a716-
446655440000/", data, config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-
41d4-a716-446655440000/api-keys/550e8400-e29b-41d4-a716-
446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.delete(url, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>delete("https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-
41d4-a716-446655440000/api-keys/550e8400-e29b-41d4-a716-
446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response Content

Status Code	Description
204	API Key revoked successfully
400	API Key has already been revoked
403	Insufficient permissions

404	API Key not found

Get the Organization an API Key Belongs To

GET `/api/v1/users/api-key-context/`

Accepts only Authorization: Api-Key and returns the organization the key is bound to; it does not count toward the key's RPM quota. For usage, see Common Conventions: Confirm the Organization a Key Belongs To。

Code Examples

Shell/Bash

```
# Example API Call (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/users/api-key-context/"
  -H "Authorization: Api-Key YOUR_API_KEY"
# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/users/api-key-context/",
config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/users/api-key-context/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/users/api-key-context/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response Content

Status Code: 200

Example Response Structure

```
{
  "organizationId": string (uuid)
}
```

Example Response Values

```
{
  "organizationId": "550e8400-e29b-41d4-a716-446655440000"
}
```

Status Code: 401 - Missing or invalid API Key, or a non-API-Key credential was used

Issue a Member Embed Token

POST `/api/v1/members/embed-tokens/`

Uses an organization API Key to issue a token valid for 15 minutes for a specified member, so your system can embed MaiGPT as that member. Only keys held by the organization owner or by members with the "Organization Overview" management permission can call this endpoint. For the flow, see the technical manual MaiGPT Member Identity Embedding。

Request Body

Request Parameters

Field	Type	Required	Description
email	string (email)	No	
memberId	string (uuid)	No	

Request Schema Example

```
{
  "email"?: string (email) // Optional
  "memberId"?: string (uuid) // Optional
}
```

Example Request Values

```
{
  "email": "user@example.com",
  "memberId": "550e8400-e29b-41d4-a716-446655440000"
}
```

Code Examples

Shell/Bash

```
# Example API Call (Shell)
curl -X POST "https://api.maiagent.ai/api/v1/members/embed-tokens/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "email": "user@example.com",
    "memberId": "550e8400-e29b-41d4-a716-446655440000"
  }'

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// Request Body (payload)
const data = {
    "email": "user@example.com",
    "memberId": "550e8400-e29b-41d4-a716-446655440000"
  };

axios.post("https://api.maiagent.ai/api/v1/members/embed-tokens/",
data, config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```python
import requests

url = "https://api.maiagent.ai/api/v1/members/embed-tokens/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# Request Body (payload)
data = {
    "email": "user@example.com",
    "memberId": "550e8400-e29b-41d4-a716-446655440000"
}

response = requests.post(url, json=data, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>post("https://api.maiagent.ai/api/v1/members/embed-tokens/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'email' => 'user@example.com',
            'memberId' => '550e8400-e29b-41d4-a716-446655440000'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response Body

Status Code: 201

Response Schema Example

```
{
  "accessToken": string
  "organizationId": string (uuid)
  "expiresAt": string (timestamp)
  "member": {
  {
    "id": string (uuid)
    "userId": string (uuid)
    "email": string (email)
    "name": string
  }
  }
}
```

Example Response Values

```
{
  "accessToken": "Response string",
  "organizationId": "550e8400-e29b-41d4-a716-446655440000",
  "expiresAt": "Response string",
  "member": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "userId": "550e8400-e29b-41d4-a716-446655440000",
    "email": "response@example.com",
    "name": "Response string"
  }
}
```

Status Code: `400` - Provide exactly one of email and memberId

Status Code: `401` - Not authenticated with an Api-Key

Status Code: `403` - The API Key holder is neither an organization owner nor has organization management permission

Status Code: `404` - The specified member does not exist, is disabled, or does not belong to this organization

List OAuth Applications

`GET` `/api/v1/oauth/applications/`

When MaiAgent acts as an OAuth 2.1 authorization server, your application registers here first. For the flow, see the technical manual MaiAgent as an OAuth Authorization Server.

Parameters

Parameter Name	Required	Type	Description
`page`	X	integer	A page number within the paginated result set.
`pageSize`	X	integer	Number of results to return per page.

Code Examples

Shell/Bash

```
# Example API Call (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/oauth/applications/?
page=1&pageSize=1"

  -H "Authorization: Api-Key YOUR_API_KEY"

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/oauth/applications/?
page=1&pageSize=1", config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/oauth/applications/?
page=1&pageSize=1"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/oauth/applications/?
page=1&pageSize=1", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response Body

Status Code: 200

Response Schema Example

```
{
  "count": integer
  "next"?: string (uri) // Optional
```

```
  "previous"?: string (uri) // Optional
  "results": [
    {
      "id": string (uuid)
      "name": string
      "clientId": string
      "clientType":
      {
      }
      "redirectUris": [
        string
      ]
      "authorizedUserCount": integer
      "createdByName": string
      "created": string (timestamp)
      "updated": string (timestamp)
    }
  ]
}
```

Example Response Values

```
{
  "count": 123,
  "next": "http://api.example.org/accounts/?page=4",
  "previous": "http://api.example.org/accounts/?page=2",
  "results": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "Response string",
      "clientId": "Response string",
      "clientType": {},
      "redirectUris": [
        "Response string"
      ],
      "authorizedUserCount": 456,
      "createdByName": "Response string",
      "created": "Response string",
      "updated": "Response string"
    }
```

```
  ]
}
```

Register OAuth Application

POST `/api/v1/oauth/applications/`

Request Body

Request Parameters

Field	Type	Required	Description
name	string	Yes	
clientType	object	No	
redirectUris	array[string]	Yes	

Request Schema Example

```
{
  "name": string
  "clientType"?:  // Optional
  {
  }
  "redirectUris": [
    string
  ]
}
```

Example Request Values

```
{
  "name": "Example name",
  "clientType": {},
  "redirectUris": [
    "Example string"
  ]
}
```

Code Examples

Shell/Bash

```
# Example API Call (Shell)
curl -X POST "https://api.maiagent.ai/api/v1/oauth/applications/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "name": "Example name",
    "clientType": {},
    "redirectUris": [
      "Example string"
    ]
  }'

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// Request Body (payload)
const data = {
    "name": "Example name",
    "clientType": {},
    "redirectUris": [
      "Example string"
    ]
  };

axios.post("https://api.maiagent.ai/api/v1/oauth/applications/",
data, config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/oauth/applications/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# Request Body (payload)
data = {
    "name": "Example name",
    "clientType": {},
    "redirectUris": [
        "Example string"
    ]
}

response = requests.post(url, json=data, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>post("https://api.maiagent.ai/api/v1/oauth/applications/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'name' => 'Example name',
            'clientType' => new \stdClass(),
            'redirectUris' => [
                'Example string'
            ]
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response Body

Status Code: 201

Response Schema Example

```
{
  "id": string (uuid)
  "name": string
  "clientId": string
  "clientType":
  {
  }
  "redirectUris": [
    string
  ]
  "authorizedUserCount": integer
  "createdByName": string
  "created": string (timestamp)
  "updated": string (timestamp)
  "clientSecret": string
}
```

Example Response Values

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "name": "Response string",
  "clientId": "Response string",
  "clientType": {},
  "redirectUris": [
    "Response string"
  ],
  "authorizedUserCount": 456,
  "createdByName": "Response string",
  "created": "Response string",
  "updated": "Response string",
  "clientSecret": "Response string"
}
```

Retrieve OAuth Application

GET `/api/v1/oauth/applications/{id}`

Parameters

Parameter Name	Required	Type	Description
`id`	V	string	A UUID string identifying this MaiAgent OAuth application.

Code Examples

Shell/Bash

```
# Example API Call (Shell)
curl -X GET
"https://api.maiagent.ai/api/v1/oauth/applications/550e8400-e29b-
41d4-a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/oauth/applications/550e8400-e29b-41d4-a716-446655440000/", config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/oauth/applications/550e8400-
e29b-41d4-a716-446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/oauth/applications/550e8400-
e29b-41d4-a716-446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response Body

Status Code: 200

Response Schema Example

```
{
  "id": string (uuid)
  "name": string
```

```
  "clientId": string
  "clientType":
  {
  }
  "redirectUris": [
    string
  ]
  "authorizedUserCount": integer
  "createdByName": string
  "created": string (timestamp)
  "updated": string (timestamp)
}
```

Example Response Values

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "name": "Response string",
  "clientId": "Response string",
  "clientType": {},
  "redirectUris": [
    "Response string"
  ],
  "authorizedUserCount": 456,
  "createdByName": "Response string",
  "created": "Response string",
  "updated": "Response string"
}
```

Update OAuth Application

PATCH `/api/v1/oauth/applications/{id}`

Parameters

Parameter Name	Required	Type	Description
`id`	V	string	A UUID string identifying this MaiAgent OAuth application.

Request Body

Request Parameters

Field	Type	Required	Description
name	string	No	
redirectUris	array[string]	No	

Request Schema Example

```
{
  "name"?: string // Optional
  "redirectUris"?: [ // Optional
    string
  ]
}
```

Example Request Values

```
{
  "name": "Example name",
  "redirectUris": [
    "Example string"
  ]
}
```

Code Examples

Shell/Bash

```
# Example API Call (Shell)
curl -X PATCH
"https://api.maiagent.ai/api/v1/oauth/applications/550e8400-e29b-
41d4-a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "name": "Example name",
    "redirectUris": [
      "Example string"
    ]
  }'

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// Request Body (payload)
const data = {
    "name": "Example name",
    "redirectUris": [
      "Example string"
    ]
  };

axios.patch("https://api.maiagent.ai/api/v1/oauth/applications/550e8
400-e29b-41d4-a716-446655440000/", data, config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/oauth/applications/550e8400-
e29b-41d4-a716-446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# Request Body (payload)
data = {
    "name": "Example name",
    "redirectUris": [
        "Example string"
    ]
}

response = requests.patch(url, json=data, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>patch("https://api.maiagent.ai/api/v1/oauth/applications/550e8400-
e29b-41d4-a716-446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'name' => 'Example name',
            'redirectUris' => [
                'Example string'
            ]
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response Body

Status Code: 200

Response Schema Example

```
{
  "id": string (uuid)
  "name": string
  "clientId": string
  "clientType":
  {
  }
  "redirectUris": [
    string
  ]
  "authorizedUserCount": integer
  "createdByName": string
  "created": string (timestamp)
  "updated": string (timestamp)
}
```

Example Response Values

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "name": "Response string",
  "clientId": "Response string",
  "clientType": {},
  "redirectUris": [
    "Response string"
  ],
  "authorizedUserCount": 456,
  "createdByName": "Response string",
  "created": "Response string",
  "updated": "Response string"
}
```

Delete OAuth Application and Revoke Its Tokens

DELETE `/api/v1/oauth/applications/{id}`

Parameters

Parameter Name	Required	Type	Description
`id`	V	string	A UUID string identifying this MaiAgent OAuth application.

Code Examples

Shell/Bash

```
# Example API Call (Shell)
curl -X DELETE
"https://api.maiagent.ai/api/v1/oauth/applications/550e8400-e29b-
41d4-a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

// Request Body (payload)
const data = null;

axios.delete("https://api.maiagent.ai/api/v1/oauth/applications/550e
8400-e29b-41d4-a716-446655440000/", data, config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/oauth/applications/550e8400-
e29b-41d4-a716-446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.delete(url, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>delete("https://api.maiagent.ai/api/v1/oauth/applications/550e8400-
e29b-41d4-a716-446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response Body

Status Code	Description
204	No response body

Regenerate Client Secret

POST `/api/v1/oauth/applications/{id}/regenerate-secret/`

Parameters

Parameter Name	Required	Type	Description
`id`	V	string	A UUID string identifying this MaiAgent OAuth application.

Code Examples

Shell/Bash

```
# Example API Call (Shell)
curl -X POST
"https://api.maiagent.ai/api/v1/oauth/applications/550e8400-e29b-
41d4-a716-446655440000/regenerate-secret/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# Please make sure to replace YOUR_API_KEY and verify the request
data before executing.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

// Request Body (payload)
const data = null;

axios.post("https://api.maiagent.ai/api/v1/oauth/applications/550e84
00-e29b-41d4-a716-446655440000/regenerate-secret/", data, config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/oauth/applications/550e8400-
e29b-41d4-a716-446655440000/regenerate-secret/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.post(url, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>post("https://api.maiagent.ai/api/v1/oauth/applications/550e8400-
e29b-41d4-a716-446655440000/regenerate-secret/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response Body

Status Code: 200

Response Schema Example

```
{
  "id": string (uuid)
  "name": string
```

```
  "clientId": string
  "clientType":
  {
  }
  "redirectUris": [
    string
  ]
  "authorizedUserCount": integer
  "createdByName": string
  "created": string (timestamp)
  "updated": string (timestamp)
  "clientSecret": string
}
```

Response Example

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "name": "Response string",
  "clientId": "Response string",
  "clientType": {},
  "redirectUris": [
    "Response string"
  ],
  "authorizedUserCount": 456,
  "createdByName": "Response string",
  "created": "Response string",
  "updated": "Response string",
  "clientSecret": "Response string"
}
```

List OAuth applications I have authorized

GET `/api/v1/oauth/authorized-applications/`

Parameters

Parameter Name	Required	Type	Description
`page`	X	integer	A page number within the paginated result set.
`pageSize`	X	integer	Number of results to return per page.

Code Examples

Shell/Bash

```
# Example API Call (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/oauth/authorized-
applications/?page=1&pageSize=1"

  -H "Authorization: Api-Key YOUR_API_KEY"

# Please make sure to replace YOUR_API_KEY and verify the request
data before executing.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/oauth/authorized-
applications/?page=1&pageSize=1", config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/oauth/authorized-
applications/?page=1&pageSize=1"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/oauth/authorized-applications/?
page=1&pageSize=1", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response Body

Status Code: 200

Response Schema Example

```
{
  "count": integer
  "next"?: string (uri) // optional
```

```
  "previous"?: string (uri) // optional
  "results": [
    {
      "id": string (uuid)
      "name": string
      "organization": string (uuid)
      "organizationName": string
      "tokenCount": integer
      "lastAuthorizedAt": string (timestamp)
      "latestExpiresAt": string (timestamp)
    }
  ]
}
```

Response Example

```
{
  "count": 123,
  "next": "http://api.example.org/accounts/?page=4",
  "previous": "http://api.example.org/accounts/?page=2",
  "results": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "Response string",
      "organization": "550e8400-e29b-41d4-a716-446655440000",
      "organizationName": "Response string",
      "tokenCount": 456,
      "lastAuthorizedAt": "Response string",
      "latestExpiresAt": "Response string"
    }
  ]
}
```

Revoke my authorization for an application

DELETE `/api/v1/oauth/authorized-applications/{id}`

Parameters

Parameter Name	Required	Type	Description
id	V	string	

Code Examples

Shell/Bash

```
# Example API Call (Shell)
curl -X DELETE "https://api.maiagent.ai/api/v1/oauth/authorized-
applications/550e8400-e29b-41d4-a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# Please make sure to replace YOUR_API_KEY and verify the request
data before executing.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

// Request Body (payload)
const data = null;

axios.delete("https://api.maiagent.ai/api/v1/oauth/authorized-
applications/550e8400-e29b-41d4-a716-446655440000/", data, config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/oauth/authorized-
applications/550e8400-e29b-41d4-a716-446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.delete(url, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>delete("https://api.maiagent.ai/api/v1/oauth/authorized-
applications/550e8400-e29b-41d4-a716-446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response Body

Status Code	Description
204	No response body

Delete organization

DELETE `/api/v1/organizations/{id}`

Parameters

Parameter Name	Required	Type	Description
`id`	V	string	A UUID string identifying this Organization.

Code Examples

Shell/Bash

```
# Example API Call (Shell)
curl -X DELETE
"https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-41d4-
a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# Please make sure to replace YOUR_API_KEY and verify the request
data before executing.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

// Request Body (payload)
const data = null;

axios.delete("https://api.maiagent.ai/api/v1/organizations/550e8400-
e29b-41d4-a716-446655440000/", data, config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-
41d4-a716-446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.delete(url, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>delete("https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-
41d4-a716-446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response Body

Status Code	Description
204	No response body

Delete a specified member

DELETE `/api/v1/organizations/{organizationPk}/members/{id}`

Parameters

Parameter Name	Required	Type	Description
`id`	V	string	A UUID string identifying this Member.
`organizationPk`	V	string	A UUID string identifying this Organization ID

Code Examples

Shell/Bash

```
# Example API Call (Shell)
curl -X DELETE
"https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-41d4-
a716-446655440000/members/550e8400-e29b-41d4-a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# Please make sure to replace YOUR_API_KEY and verify the request
data before executing.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

// Request Body (payload)
const data = null;

axios.delete("https://api.maiagent.ai/api/v1/organizations/550e8400-
e29b-41d4-a716-446655440000/members/550e8400-e29b-41d4-a716-
446655440000/", data, config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-
41d4-a716-446655440000/members/550e8400-e29b-41d4-a716-
446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.delete(url, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>delete("https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-
41d4-a716-446655440000/members/550e8400-e29b-41d4-a716-
446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response Body

Status Code	Description
204	No response body

Get member usage statistics

GET `/api/v1/organizations/{organizationPk}/usage-statistics/members/`

Parameters

Parameter Name	Required	Type	Description
`organizationPk`	V	string	A UUID string identifying this Organization ID
`chatbot`	X	string	Filter by a specific AI assistant ID
`chatbotId`	X	string	
`endDate`	X	string	End date, format: YYYY-MM-DD
`includeTime`	X	boolean	Whether to return time-series data aggregated by time only, for trend charts (true/false). When set to true, the response contains no entity information, only time fields and statistical values, and is not paginated.
`memberId`	X	string	
`page`	X	integer	Page number
`pageSize`	X	integer	Number of items per page
`search`	X	string	Search by member ID, name, or Email
`sortBy`	X	string	Sort field
`sortOrder`	X	string	Sort order (asc/desc)
`startDate`	V	string	Start date, format: YYYY-MM-DD

timeGranularity	X	string	Time granularity (hour/day/month)

Code Examples

Shell/Bash

```
# Example API Call (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/organizations/550e8400-
e29b-41d4-a716-446655440000/usage-statistics/members/?
chatbot=example&chatbotId=550e8400-e29b-41d4-a716-
446655440000&endDate=example&includeTime=true&memberId=550e8400-
e29b-41d4-a716-
446655440000&page=1&pageSize=1&search=example&sortBy=conversations_c
ount&sortOrder=asc&startDate=example&timeGranularity=day"

  -H "Authorization: Api-Key YOUR_API_KEY"

# Please make sure to replace YOUR_API_KEY and verify the request
data before executing.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/organizations/550e8400-
e29b-41d4-a716-446655440000/usage-statistics/members/?
chatbot=example&chatbotId=550e8400-e29b-41d4-a716-
446655440000&endDate=example&includeTime=true&memberId=550e8400-
e29b-41d4-a716-
446655440000&page=1&pageSize=1&search=example&sortBy=conversations_c
ount&sortOrder=asc&startDate=example&timeGranularity=day", config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-
41d4-a716-446655440000/usage-statistics/members/?
chatbot=example&chatbotId=550e8400-e29b-41d4-a716-
446655440000&endDate=example&includeTime=true&memberId=550e8400-
e29b-41d4-a716-
446655440000&page=1&pageSize=1&search=example&sortBy=conversations_c
ount&sortOrder=asc&startDate=example&timeGranularity=day"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-
41d4-a716-446655440000/usage-statistics/members/?
chatbot=example&chatbotId=550e8400-e29b-41d4-a716-
446655440000&endDate=example&includeTime=true&memberId=550e8400-
e29b-41d4-a716-
446655440000&page=1&pageSize=1&search=example&sortBy=conversations_c
ount&sortOrder=asc&startDate=example&timeGranularity=day", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response Body

Status Code: 200

Response Schema Example

```
{
  "count": integer
  "next"?: string (uri) // optional
  "previous"?: string (uri) // optional
  "results": [
    {
      "count"?: integer // Result count (optional)
      "results"?: [ // optional
        {
          "member"?: { // optional
          {
            "id"?: string (uuid) // Member ID (optional)
            "name"?: string // Member name (optional)
            "email"?: string // Member email (optional)
          }
          }
          "datetime"?: string (date-time) // Timestamp (only appears when
include_time=true and time_granularity=hour) (optional)
          "period"?: string (date) // Date (only appears when
include_time=true and time_granularity=day/month) (optional)
          "input_characters_count"?: integer // Input character count
(optional)
          "output_characters_count"?: integer // Output character count
(optional)
          "input_token_usage"?: integer // Input token count (optional)
          "output_token_usage"?: integer // Output token count (optional)
          "messages_count"?: integer // Message count (optional)
          "conversations_count"?: integer // Conversation count
(optional)
          "total_characters_count"?: integer // Total character count
(optional)
          "total_token_usage"?: integer // Total token count (optional)
        }
      ]
    }
  ]
}
```

Response Example

```
{
  "count": 123,
  "next": "http://api.example.org/accounts/?page=4",
```

```
  "previous": "http://api.example.org/accounts/?page=2",
  "results": [
    {
      "count": 2,
      "results": [
        {
          "member": {
            "id": "3a245511-d5e0-4e06-9dc6-1106915b9a8a",
            "name": "Wang Xiaoming",
            "email": "wang@example.com"
          },
          "input_characters_count": 10000,
          "output_characters_count": 15000,
          "input_token_usage": 2500,
          "output_token_usage": 3750,
          "messages_count": 100,
          "conversations_count": 50,
          "total_characters_count": 25000,
          "total_token_usage": 6250
        }
      ]
    }
  ]
}
```


Retrieve Member Usage Statistics Summary

`GET` `/api/v1/organizations/{organizationPk}/usage-statistics/members/summary/`

Parameters

Parameter Name	Required	Type	Description
`organizationPk`	V	string	A UUID string identifying this organization ID

`endDate`	X	string	End date, format: YYYY-MM-DD
`startDate`	V	string	Start date, format: YYYY-MM-DD
`timeGranularity`	X	string	Time granularity (hour/day/month)

Code Examples

Shell/Bash

```
# API call example (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/organizations/550e8400-
e29b-41d4-a716-446655440000/usage-statistics/members/summary/?
endDate=example&startDate=example&timeGranularity=day"

  -H "Authorization: Api-Key YOUR_API_KEY"

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/organizations/550e8400-
e29b-41d4-a716-446655440000/usage-statistics/members/summary/?
endDate=example&startDate=example&timeGranularity=day", config)
  .then(response => {
    console.log('Response retrieved successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-
41d4-a716-446655440000/usage-statistics/members/summary/?
endDate=example&startDate=example&timeGranularity=day"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("Response retrieved successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-
41d4-a716-446655440000/usage-statistics/members/summary/?
endDate=example&startDate=example&timeGranularity=day", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response retrieved successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response Content

Status Code: 200

Example Response Schema

```
{
  "totalInputCharacters"?: integer // Total input characters (Optional)
```

```
  "totalOutputCharacters"?: integer // Total output characters (Optional)
  "totalCharacters"?: integer // Total characters (Optional)
  "totalInputTokens"?: integer // Total input tokens (Optional)
  "totalOutputTokens"?: integer // Total output tokens (Optional)
  "totalTokens"?: integer // Total tokens (Optional)
  "totalMessages"?: integer // Total messages (Optional)
  "totalConversations"?: integer // Total conversations (Optional)
  "chatbotScope"?: string (enum: organization, accessible_chatbots) //
Usage statistics scope for the caller: organization = the entire
organization; accessible_chatbots = only AI assistants authorized for the
caller's roles (Optional)
  "totalCount"?: integer // Number of hourly member statistics records
matching the query: each combination of member, hour, and AI assistant
counts as a separate record; this is not the number of members (Optional)
}
```

Example Response Values


```
{
  "totalInputCharacters": 456,
  "totalOutputCharacters": 456,
  "totalCharacters": 456,
  "totalInputTokens": 456,
  "totalOutputTokens": 456,
  "totalTokens": 456,
  "totalMessages": 456,
  "totalConversations": 456,
  "chatbotScope": "organization",
  "totalCount": 456
}
```


Get AI Assistant Usage Statistics

`GET` `/api/v1/organizations/{organizationPk}/usage-statistics/chatbots/`

Parameters

Parameter Name	Required	Type	Description
`organizationPk`	V	string	A UUID string identifying this Organization ID
`chatbotId`	X	string	
`endDate`	X	string	End date, format: YYYY-MM-DD
`includeTime`	X	boolean	Whether to return time-series data aggregated by time only, for trend charts (true/false). When set to true, the response contains no entity information, only time fields and statistics, and is not paginated.
`page`	X	integer	Page number
`pageSize`	X	integer	Number of results per page
`search`	X	string	Search by AI assistant ID or name
`sortBy`	X	string	Sort field
`sortOrder`	X	string	Sort order (asc/desc)
`startDate`	V	string	Start date, format: YYYY-MM-DD
`timeGranularity`	X	string	Time granularity (hour/day/month)

Code Examples

Shell/Bash

```
# Example API call (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/organizations/550e8400-
e29b-41d4-a716-446655440000/usage-statistics/chatbots/?
chatbotId=550e8400-e29b-41d4-a716-
446655440000&endDate=example&includeTime=true&page=1&pageSize=1&sear
ch=example&sortBy=conversations_count&sortOrder=asc&startDate=exampl
e&timeGranularity=day"

  -H "Authorization: Api-Key YOUR_API_KEY"

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/organizations/550e8400-
e29b-41d4-a716-446655440000/usage-statistics/chatbots/?
chatbotId=550e8400-e29b-41d4-a716-
446655440000&endDate=example&includeTime=true&page=1&pageSize=1&sear
ch=example&sortBy=conversations_count&sortOrder=asc&startDate=exampl
e&timeGranularity=day", config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('An error occurred during the request:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-
41d4-a716-446655440000/usage-statistics/chatbots/?
chatbotId=550e8400-e29b-41d4-a716-
446655440000&endDate=example&includeTime=true&page=1&pageSize=1&sear
ch=example&sortBy=conversations_count&sortOrder=asc&startDate=exampl
e&timeGranularity=day"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("An error occurred during the request:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-
41d4-a716-446655440000/usage-statistics/chatbots/?
chatbotId=550e8400-e29b-41d4-a716-
446655440000&endDate=example&includeTime=true&page=1&pageSize=1&sear
ch=example&sortBy=conversations_count&sortOrder=asc&startDate=exampl
e&timeGranularity=day", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'An error occurred during the request: ' . $e-
>getMessage();
}
?>
```

Response Body

Status Code: 200

Response Schema Example

```
{
  "count": integer
  "next"?: string (uri) // Optional
  "previous"?: string (uri) // Optional
  "results": [
    {
      "count"?: integer // Number of results (Optional)
      "results"?: [ // Optional
        {
          "chatbot"?: { // Optional
          {
            "id"?: string (uuid) // AI assistant ID (Optional)
            "name"?: string // AI assistant name (Optional)
          }
          }
          "datetime"?: string (date-time) // Timestamp (appears only when
include_time=true and time_granularity=hour) (Optional)
          "period"?: string (date) // Date (appears only when
include_time=true and time_granularity=day/month) (Optional)
          "input_characters_count"?: integer // Input characters
(Optional)
          "output_characters_count"?: integer // Output characters
(Optional)
          "input_token_usage"?: integer // Input tokens (Optional)
          "output_token_usage"?: integer // Output tokens (Optional)
          "messages_count"?: integer // Messages (Optional)
          "conversations_count"?: integer // Conversations (Optional)
          "total_characters_count"?: integer // Total characters
(Optional)
          "total_token_usage"?: integer // Total tokens (Optional)
        }
      ]
    }
  ]
}
```

Example Response Values

```
{
  "count": 123,
  "next": "http://api.example.org/accounts/?page=4",
  "previous": "http://api.example.org/accounts/?page=2",
  "results": [
```

```
    {
      "count": 2,
      "results": [
        {
          "chatbot": {
            "id": "5b646600-f6e0-4f07-aec7-0207a26c0a9b",
            "name": "Customer Service Assistant"
          },
          "input_characters_count": 10000,
          "output_characters_count": 15000,
          "input_token_usage": 2500,
          "output_token_usage": 3750,
          "messages_count": 100,
          "conversations_count": 50,
          "total_characters_count": 25000,
          "total_token_usage": 6250
        }
      ]
    }
  ]
}
```


Retrieve AI Assistant Usage Statistics Summary

`GET` `/api/v1/organizations/{organizationPk}/usage-statistics/chatbots/summary/`

Parameters

Parameter Name	Required	Type	Description
`organizationPk`	V	string	A UUID string identifying this organization ID
`endDate`	X	string	End date, format: YYYY-MM-DD
`startDate`	V	string	Start date, format: YYYY-MM-DD

`timeGranularity`	X	string	Time granularity (hour/day/month)

Code Examples

Shell/Bash

```
# API call example (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/organizations/550e8400-
e29b-41d4-a716-446655440000/usage-statistics/chatbots/summary/?
endDate=example&startDate=example&timeGranularity=day"

  -H "Authorization: Api-Key YOUR_API_KEY"

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/organizations/550e8400-
e29b-41d4-a716-446655440000/usage-statistics/chatbots/summary/?
endDate=example&startDate=example&timeGranularity=day", config)
  .then(response => {
    console.log('Response retrieved successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request failed:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-
41d4-a716-446655440000/usage-statistics/chatbots/summary/?
endDate=example&startDate=example&timeGranularity=day"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("Response retrieved successfully:")
    print(response.json())
except Exception as e:
    print("Request failed:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-
41d4-a716-446655440000/usage-statistics/chatbots/summary/?
endDate=example&startDate=example&timeGranularity=day", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response retrieved successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request failed: ' . $e->getMessage();
}
?>
```

Response

Status code: 200

Example Response Schema

```
{
  "totalInputCharacters"?: integer // Total input characters (Optional)
```

```
  "totalOutputCharacters"?: integer // Total output characters (Optional)
  "totalCharacters"?: integer // Total characters (Optional)
  "totalInputTokens"?: integer // Total input tokens (Optional)
  "totalOutputTokens"?: integer // Total output tokens (Optional)
  "totalTokens"?: integer // Total tokens (Optional)
  "totalMessages"?: integer // Total messages (Optional)
  "totalConversations"?: integer // Total conversations (Optional)
  "chatbotScope"?: string (enum: organization, accessible_chatbots) //
Usage statistics scope for the caller: organization = the entire
organization; accessible_chatbots = only AI assistants authorized for the
caller's roles (Optional)
  "totalChatbots"?: integer // Number of unique AI assistants with usage
records during the query period; excludes assistants with no usage during
that period and is not the total number of AI assistants in the
organization (Optional)
}
```

Example Response Values

```
{
  "totalInputCharacters": 456,
  "totalOutputCharacters": 456,
  "totalCharacters": 456,
  "totalInputTokens": 456,
  "totalOutputTokens": 456,
  "totalTokens": 456,
  "totalMessages": 456,
  "totalConversations": 456,
  "chatbotScope": "organization",
  "totalChatbots": 456
}
```

List Your Memories

GET `/api/v1/me/memories/`

Include the X-Organization-Id header to specify the organization to operate on, including when calling with an API key. Use the status (active
expired) and kind (fact
preference
instruction) query parameters to filter results; pending and rejected memories are excluded. For behavior details, see Member Memory Management API in the technical manual.

Parameters

Parameter Name	Required	Type	Description
`kind`	X	string	`fact`: Fact ; `preference`: Preference ; `instruction`: Instruction ; `summary`: Summary ; `profile`: Profile;
`page`	X	integer	A page number within the paginated result set.
`pageSize`	X	integer	Number of results to return per page.
`status`	X	string	`pending`: Pending ; `active`: Active ; `rejected`: Rejected ; `expired`: Expired;

Code Examples

Shell/Bash

```
# API call example (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/me/memories/?
kind=fact&page=1&pageSize=1&status=active"

  -H "Authorization: Api-Key YOUR_API_KEY"

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/me/memories/?
kind=fact&page=1&pageSize=1&status=active", config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/me/memories/?
kind=fact&page=1&pageSize=1&status=active"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/me/memories/?
kind=fact&page=1&pageSize=1&status=active", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response Body

Status Code: 200

Example Response Schema

```
{
  "count": integer
  "next"?: string (uri) // Optional
```

```
  "previous"?: string (uri) // Optional
  "results": [
    {
      "id": string (uuid)
      "topic": string // LLM-assigned topic slug for grouping related
memories (e.g. "language_preferences", "role", "communication_style").
Null means legacy memory without topic grouping.
      "category": // May have different types
      string (enum: personal_info, work_role, projects, communication,
response_format, tools_tech, interests, health_lifestyle, schedule_plans,
other) // Fixed category shown to users. Null means legacy memory without
a category.

* `personal_info` - Personal Info
* `work_role` - Work and Role
* `projects` - Projects and Work
* `communication` - Communication Preferences
* `response_format` - Response Format Preferences
* `tools_tech` - Tools and Technology
* `interests` - Interests and Hobbies
* `health_lifestyle` - Health and Lifestyle
* `schedule_plans` - Schedule and Plans
* `other` - Other
      "categoryDisplay": string // Translated category name.
      "summary": string // One-line summary of the memory topic.
      "details": object // Concrete facts for this topic, stored as a
list of strings.
      "kind":
      {
      }
      "source":  // How this memory was created: user explicitly stated,
agent extracted, or manually added.

* `user_stated` - User Stated
* `agent_extracted` - Agent Extracted
* `agent_stated` - Agent Stated
* `user_manual` - User Manual
      {
      }
      "requestedByUser": boolean // True when the user explicitly asked
the agent to remember this. Only affects the UI label (S12), not LRU
eviction priority (S6).
      "status":
      {
      }
```

```
      "createdAt": string (timestamp)
      "updatedAt": string (timestamp)
    }
  ]
}
```

Example Response Values

```
{
  "count": 123,
  "next": "http://api.example.org/accounts/?page=4",
  "previous": "http://api.example.org/accounts/?page=2",
  "results": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "topic": "Response string",
      "category": "personal_info",
      "categoryDisplay": "Response string",
      "summary": "Response string",
      "details": null,
      "kind": {},
      "source": {},
      "requestedByUser": false,
      "status": {},
      "createdAt": "Response string",
      "updatedAt": "Response string"
    }
  ]
}
```

Create or Update Your Memories

POST `/api/v1/me/memories/`

Include the X-Organization-Id header to specify the organization to operate on, including when calling with an API key. Request fields: topic (required, up to 100 characters; only lowercase English letters, digits, and underscores between them), summary (required, up to 500 characters), details

(required, an array of strings with up to 20 items, each up to 500 characters), and kind (fact preference
instruction, default: fact). If the same member already has an active memory with the same topic, update it and return 200; return 201 when creating a new memory.

Request Body

Request Parameters

Field	Type	Required	Description
topic	string	Yes	
category	string (enum: personal_info, work_role, projects, communication, response_format, tools_tech, interests, health_lifestyle, schedule_plans, other)	No	`personal_info` : Personal Info ; `work_role` : Work and Role ; `projects` : Projects and Work ; `communication` : Communication Preferences ; `response_format` : Response Format Preferences ; `tools_tech` ...
summary	string	Yes	
details	array[string]	Yes	
kind	object	No	

Example Request Schema

```
{
  "topic": string
  "category"?: string (enum: personal_info, work_role, projects,
communication, response_format, tools_tech, interests, health_lifestyle,
schedule_plans, other) // * `personal_info` - Personal Info
* `work_role` - Work and Role
* `projects` - Projects and Work
* `communication` - Communication Preferences
* `response_format` - Response Format Preferences
* `tools_tech` - Tools and Technology
* `interests` - Interests and Hobbies
* `health_lifestyle` - Health and Lifestyle
* `schedule_plans` - Schedule and Plans
```

```
* `other` - Other (Optional)
  "summary": string
  "details": [
    string
  ]
  "kind"?:  // Optional
  {
  }
}
```

Example Request Values

```
{
  "topic": "Example string",
  "category": "personal_info",
  "summary": "Example string",
  "details": [
    "Example string"
  ],
  "kind": {}
}
```

Code Examples

Shell/Bash

```
# API call example (Shell)
curl -X POST "https://api.maiagent.ai/api/v1/me/memories/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "topic": "Example string",
    "category": "personal_info",
    "summary": "Example string",
    "details": [
      "Example string"
    ],
    "kind": {}
  }'

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// Request Body (payload)
const data = {
    "topic": "Example string",
    "category": "personal_info",
    "summary": "Example string",
    "details": [
      "Example string"
    ],
    "kind": {}
  };

axios.post("https://api.maiagent.ai/api/v1/me/memories/", data,
config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/me/memories/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# Request Body (payload)
data = {
    "topic": "Example string",
    "category": "personal_info",
    "summary": "Example string",
    "details": [
        "Example string"
    ],
    "kind": {}
}

response = requests.post(url, json=data, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>post("https://api.maiagent.ai/api/v1/me/memories/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'topic' => 'Example string',
            'category' => 'personal_info',
            'summary' => 'Example string',
            'details' => [
                'Example string'
            ],
            'kind' => new \stdClass()
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response Body

Status Code: 200

Example Response Schema

```
{
  "id": string (uuid)
  "topic": string // LLM-assigned topic slug for grouping related
memories (e.g. "language_preferences", "role", "communication_style").
Null means legacy memory without topic grouping.
  "category": // May have different types
  string (enum: personal_info, work_role, projects, communication,
response_format, tools_tech, interests, health_lifestyle, schedule_plans,
other) // Fixed category shown to users. Null means legacy memory without
a category.

* `personal_info` - Personal Info
* `work_role` - Work and Role
* `projects` - Projects and Work
* `communication` - Communication Preferences
* `response_format` - Response Format Preferences
* `tools_tech` - Tools and Technology
* `interests` - Interests and Hobbies
* `health_lifestyle` - Health and Lifestyle
* `schedule_plans` - Schedule and Plans
* `other` - Other
  "categoryDisplay": string // Translated category name.
  "summary": string // One-line summary of the memory topic.
  "details": object // Concrete facts for this topic, stored as a list of
strings.
  "kind":
  {
  }
  "source":  // How this memory was created: user explicitly stated,
agent extracted, or manually added.

* `user_stated` - User Stated
* `agent_extracted` - Agent Extracted
* `agent_stated` - Agent Stated
* `user_manual` - User Manual
  {
  }
  "requestedByUser": boolean // True when the user explicitly asked the
agent to remember this. Only affects the UI label (S12), not LRU eviction
priority (S6).
  "status":
```

```
  {
  }
  "createdAt": string (timestamp)
  "updatedAt": string (timestamp)
}
```

Example Response Values

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "topic": "Response string",
  "category": "personal_info",
  "categoryDisplay": "Response string",
  "summary": "Response string",
  "details": null,
  "kind": {},
  "source": {},
  "requestedByUser": false,
  "status": {},
  "createdAt": "Response string",
  "updatedAt": "Response string"
}
```

Status Code: 201

Example Response Schema

```
{
  "id": string (uuid)
  "topic": string // LLM-assigned topic slug for grouping related
memories (e.g. "language_preferences", "role", "communication_style").
Null means legacy memory without topic grouping.
  "category": // May have different types
  string (enum: personal_info, work_role, projects, communication,
response_format, tools_tech, interests, health_lifestyle, schedule_plans,
other) // Fixed category shown to users. Null means legacy memory without
a category.

* `personal_info` - Personal Info
* `work_role` - Work and Role
* `projects` - Projects and Work
* `communication` - Communication Preferences
```

```
* `response_format` - Response Format Preferences
* `tools_tech` - Tools and Technology
* `interests` - Interests and Hobbies
* `health_lifestyle` - Health and Lifestyle
* `schedule_plans` - Schedule and Plans
* `other` - Other
  "categoryDisplay": string // Translated category name.
  "summary": string // One-line summary of the memory topic.
  "details": object // Concrete facts for this topic, stored as a list of
strings.
  "kind":
  {
  }
  "source":  // How this memory was created: user explicitly stated,
agent extracted, or manually added.

* `user_stated` - User Stated
* `agent_extracted` - Agent Extracted
* `agent_stated` - Agent Stated
* `user_manual` - User Manual
  {
  }
  "requestedByUser": boolean // True when the user explicitly asked the
agent to remember this. Only affects the UI label (S12), not LRU eviction
priority (S6).
  "status":
  {
  }
  "createdAt": string (timestamp)
  "updatedAt": string (timestamp)
}
```

Example Response Values

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "topic": "Response string",
  "category": "personal_info",
  "categoryDisplay": "Response string",
  "summary": "Response string",
  "details": null,
  "kind": {},
  "source": {},
  "requestedByUser": false,
```

```
  "status": {},
  "createdAt": "Response string",
  "updatedAt": "Response string"
}
```


Modify or Reactivate Your Memories

PATCH `/api/v1/me/memories/{id}`

Include the X-Organization-Id header to specify the organization to operate on, including when calling with an API key. Provide topic, summary, or details (with the same limits as for creation) to modify the content, or status (active
expired) to deactivate or reactivate the memory; provide at least one of these fields.

Parameters

Parameter Name	Required	Type	Description
`id`	V	string	A UUID string identifying this Memory Entry.

Request Body

Request Parameters

Field	Type	Required	Description
topic	string	No	
category	string (enum: personal_info, work_role, projects, communication, response_format, tools_tech, interests,	No	`personal_info` : Personal Info ; `work_role` : Work and Role ; `projects` : Projects and Work ; `communication` : Communication Preferences ;

Field	Type	Required	Description
	health_lifestyle, schedule_plans, other)		`response_format` : Response Format Preferences ; `tools_tech` ...
summary	string	No	
details	array[string]	No	
status	string (enum: active, expired)	No	`active` : active ; `expired` : expired;

Example Request Schema

```
{
  "topic"?: string // Optional
  "category"?: string (enum: personal_info, work_role, projects,
communication, response_format, tools_tech, interests, health_lifestyle,
schedule_plans, other) // * `personal_info` - Personal Info
* `work_role` - Work and Role
* `projects` - Projects and Work
* `communication` - Communication Preferences
* `response_format` - Response Format Preferences
* `tools_tech` - Tools and Technology
* `interests` - Interests and Hobbies
* `health_lifestyle` - Health and Lifestyle
* `schedule_plans` - Schedule and Plans
* `other` - Other (Optional)
  "summary"?: string // Optional
  "details"?: [ // Optional
    string
  ]
  "status"?: string (enum: active, expired) // * `active` - active
* `expired` - expired (Optional)
}
```

Example Request Values

```
{
  "topic": "Example string",
  "category": "personal_info",
  "summary": "Example string",
  "details": [
```

```
    "Example string"
  ],
  "status": "active"
}
```

Code Examples

Shell/Bash

```
# API call example (Shell)
curl -X PATCH "https://api.maiagent.ai/api/v1/me/memories/550e8400-
e29b-41d4-a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "topic": "Example string",
    "category": "personal_info",
    "summary": "Example string",
    "details": [
      "Example string"
    ],
    "status": "active"
  }'

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Configure request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// Request body (payload)
const data = {
    "topic": "Example string",
    "category": "personal_info",
    "summary": "Example string",
    "details": [
      "Example string"
    ],
    "status": "active"
  };

axios.patch("https://api.maiagent.ai/api/v1/me/memories/550e8400-
e29b-41d4-a716-446655440000/", data, config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request failed:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/me/memories/550e8400-e29b-
41d4-a716-446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# Request body (payload)
data = {
    "topic": "Example string",
    "category": "personal_info",
    "summary": "Example string",
    "details": [
        "Example string"
    ],
    "status": "active"
}

response = requests.patch(url, json=data, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request failed:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>patch("https://api.maiagent.ai/api/v1/me/memories/550e8400-e29b-
41d4-a716-446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'topic' => 'Example string',
            'category' => 'personal_info',
            'summary' => 'Example string',
            'details' => [
                'Example string'
            ],
            'status' => 'active'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request failed: ' . $e->getMessage();
}
?>
```

Response Body

Status Code: 200

Example Response Schema

```
{
  "id": string (uuid)
  "topic": string // LLM-assigned topic slug for grouping related
memories (e.g. "language_preferences", "role", "communication_style").
Null means legacy memory without topic grouping.
  "category": // May have different types
  string (enum: personal_info, work_role, projects, communication,
response_format, tools_tech, interests, health_lifestyle, schedule_plans,
other) // Fixed category shown to users. Null means legacy memory without
a category.

* `personal_info` - Personal Info
* `work_role` - Work and Role
* `projects` - Projects and Work
* `communication` - Communication Preferences
* `response_format` - Response Format Preferences
* `tools_tech` - Tools and Technology
* `interests` - Interests and Hobbies
* `health_lifestyle` - Health and Lifestyle
* `schedule_plans` - Schedule and Plans
* `other` - Other
  "categoryDisplay": string // Translated category name.
  "summary": string // One-line summary of the memory topic.
  "details": object // Concrete facts for this topic, stored as a list of
strings.
  "kind":
  {
  }
  "source":  // How this memory was created: user explicitly stated,
agent extracted, or manually added.

* `user_stated` - User Stated
* `agent_extracted` - Agent Extracted
* `agent_stated` - Agent Stated
* `user_manual` - User Manual
  {
```

```
  }
  "requestedByUser": boolean // True when the user explicitly asked the
agent to remember this. Only affects the UI label (S12), not LRU eviction
priority (S6).
  "status":
  {
  }
  "createdAt": string (timestamp)
  "updatedAt": string (timestamp)
}
```

Example Response Values

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "topic": "Response string",
  "category": "personal_info",
  "categoryDisplay": "Response string",
  "summary": "Response string",
  "details": null,
  "kind": {},
  "source": {},
  "requestedByUser": false,
  "status": {},
  "createdAt": "Response string",
  "updatedAt": "Response string"
}
```

Delete Your Own Memory

DELETE `/api/v1/me/memories/{id}`

Include the X-Organization-Id header to specify the organization to operate on, including when calling with an API key.

Parameters

Parameter Name	Required	Type	Description
`id`	V	string	A UUID string identifying this Memory Entry.

Code Examples

Shell/Bash

```
# API Call Example (Shell)
curl -X DELETE "https://api.maiagent.ai/api/v1/me/memories/550e8400-
e29b-41d4-a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Configure request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

// Request body (payload)
const data = null;

axios.delete("https://api.maiagent.ai/api/v1/me/memories/550e8400-
e29b-41d4-a716-446655440000/", data, config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request failed:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/me/memories/550e8400-e29b-
41d4-a716-446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.delete(url, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request failed:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>delete("https://api.maiagent.ai/api/v1/me/memories/550e8400-e29b-
41d4-a716-446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request failed: ' . $e->getMessage();
}
?>
```

Response Body

Status Code	Description
204	No response body

API call example (Shell)

目錄

1. List contacts
2. Create a contact
3. Get contact details
4. Update Contact
5. Partially Update Contact
6. Delete Contact
7. List a Contact’ s Conversations
8. Get the Contact’ s Latest Conversation
9. Broadcast Messages
10. Create API Credentials for a Contact
11. Update API Credentials for a Contact
12. Delete Contact's API Credentials
13. Create MCP credentials for a contact
14. Update MCP credentials for a contact
15. Delete Contact's MCP Credentials
16. Download the Contact Bulk Import Template
17. Bulk Import Contacts

API call example (Shell)

List contacts

`GET` `/api/v1/contacts/`

Parameters

Parameter name	Required	Type	Description
`channels`	X	array	Multiple values may be separated by commas.
`externalId`	X	string	External user ID (exact match)

`inbox`	X	string	Deprecated: Use inboxes instead
`inboxes`	X	string	Conversation platform ID (filters contacts for a specific inbox)
`page`	X	integer	A page number within the paginated result set.
`pageSize`	X	integer	Number of results to return per page.
`query`	X	string	Search by name or source ID
`search`	X	string	Full-text search
`tags`	X	array	Multiple values may be separated by commas.

Code examples

Shell/Bash

```
# API call example (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/contacts/?
channels=example&externalId=example&inbox=550e8400-e29b-41d4-a716-
446655440000&inboxes=example&page=1&pageSize=1&query=example&search=exa
mple&tags=example"

  -H "Authorization: Api-Key YOUR_API_KEY"

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/contacts/?
channels=example&externalId=example&inbox=550e8400-e29b-41d4-a716-
446655440000&inboxes=example&page=1&pageSize=1&query=example&search=exa
mple&tags=example", config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/contacts/?
channels=example&externalId=example&inbox=550e8400-e29b-41d4-a716-
446655440000&inboxes=example&page=1&pageSize=1&query=example&search=exa
mple&tags=example"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->get("https://api.maiagent.ai/api/v1/contacts/?channels=example&externalId=example&inbox=550e8400-e29b-41d4-a716-446655440000&inboxes=example&page=1&pageSize=1&query=example&search=example&tags=example", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response

Status code: 200

Example response schema

```
{
  "count": integer
  "next"?: string (uri) // Optional
  "previous"?: string (uri) // Optional
```

```
  "results": [
    {
      "id": string (uuid)
      "inboxes"?: [ // Optional
        {
          "id": string (uuid)
          "name": string
        }
      ]
      "inbox"?:  // Backward-compatible field: a single inbox; ignored if
inboxes is also provided (Optional)
      {
        "id": string (uuid)
        "name": string
      }
      "name": string
      "avatar"?: // May have different types (Optional)
      string (uri) // Contact avatar URL; supports an absolute URL or a
relative path (Optional)
      "phoneNumber"?: string // Optional
      "email"?: // May have different types (Optional)
      string (email) // Optional
      "sourceId"?: string // Optional
      "externalId"?: string // External user ID: the user ID in the calling
system, unique within the organization (excluding deleted contacts). Matching
uses the exact original string and is case-sensitive; the conversation API
uses message.externalUser.id to find the contact by this ID. Empty or
whitespace-only strings return 400; pass null to clear the value. For
multiple external systems, use a system prefix, such as projects:usr_123
(Optional)
      "queryMetadata"?: { // Query metadata that controls the scope of
searchable knowledge; see each endpoint for details (Optional)
      {
        "knowledgeBases"?: [ // List of searchable knowledge bases; an empty
array or null denies access to all knowledge bases, while omission imposes no
restrictions (Optional)
          {
            "knowledgeBaseId": string (uuid) // Knowledge base ID
            "chatbotFileIds"?: [ // List of file IDs to exclude or select
exclusively, depending on hasUserSelectedAll (Optional)
              string (uuid)
            ]
            "knowledgeBaseFileIds"?: [ // List of file IDs (the new name for
chatbotFileIds; this field takes precedence if both are provided) (Optional)
              string (uuid)
            ]
            "faqIds"?: [ // List of FAQ IDs to exclude or select exclusively,
```

```
depending on hasUserSelectedAll (Optional)
              string (uuid)
            ]
            "hasUserSelectedAll"?: boolean // true selects all knowledge base
content except the listed items; false selects only the listed items
(Optional)
          }
        ]
        "labelRelations"?: { // Label filters; an empty conditions array
means no label filtering (it does not mean access is denied). Must be
provided together with knowledgeBases; when provided alone, label filtering
is not applied to knowledge base retrieval (equivalent to no restrictions)
(Optional)
        {
          "operator": string (enum: AND, OR) // How label conditions are
combined
          "conditions"?: [ // List of label conditions; supports nested
operator/conditions combinations (Optional)
            object
          ]
        }
        }
      }
      }
      "metadata"?: object // Custom customer information shown in the
customer panel of the conversation page (Optional)
      "mcpCredentials": [ // List of MCP authentication credentials for the
contact
        object
      ]
      "apiCredentials": [ // List of API authentication credentials for the
contact
        object
      ]
      "contactConnectors": [ // List of Connector OAuth authorizations for
the contact (excluding token values)
        object
      ]
      "tags": [
        {
          "id": string (uuid)
          "name": string
          "createdAt": string (timestamp)
          "updatedAt": string (timestamp)
        }
      ]
      "preChatFieldIndex": object // Pre-chat form field configuration from
```

```
the inboxes this Contact belongs to, mapped as {field_id: {label: {locale:
text}}}; the frontend uses it to resolve UUID keys in metadata to display
names
      "createdAt": string (timestamp)
      "updatedAt": string (timestamp)
    }
  ]
}
```

Example response value

```
{
  "count": 123,
  "next": "http://api.example.org/accounts/?page=4",
  "previous": "http://api.example.org/accounts/?page=2",
  "results": [
    [
      {
        "id": "user1_uuid",
        "inboxes": [
          {
            "id": "inbox_uuid",
            "name": "inbox_name"
          }
        ],
        "name": "user1",
        "avatar": "",
        "sourceId": null,
        "queryMetadata": null,
        "createdAt": "1751875361000",
        "updatedAt": "1751875361000"
      },
      {
        "id": "user2_uuid",
        "inboxes": [
          {
            "id": "inbox_uuid",
            "name": "inbox_name"
          }
        ],
        "name": "user2",
        "avatar": "avatar_url",
        "sourceId": "self defined source id",
        "queryMetadata": {
          "knowledgeBases": [
```

```
            {
              "knowledgeBaseId": "5f8c6a99-5515-43aa-8e83-fdeea327a3a2",
              "hasUserSelectedAll": true
            }
          ],
          "labelRelations": {
            "operator": "OR",
            "conditions": [
              {
                "labelId": "957998f9-1824-4872-becd-b7f8a7962896"
              }
            ]
          }
        },
        "createdAt": "1751875400000",
        "updatedAt": "1751875400000"
      }
    ]
  ]
}
```


Status code: 4XX - Error response; X-Error-Code carries its code (see "Error codes").

Create a contact

POST `/api/v1/contacts/`

Code examples

Shell/Bash

```
# API call example (Shell)
curl -X POST "https://api.maiagent.ai/api/v1/contacts/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "inboxes": [
      {
        "id": "inbox_uuid"
      }
    ],
    "name": "user1",
    "avatar": "",
    "phoneNumber": 912345678,
    "email": "user1@example.com",
    "sourceId": "self defined source id",
    "queryMetadata": {
      "knowledgeBases": [
        {
          "knowledgeBaseId": "5f8c6a99-5515-43aa-8e83-fdeea327a3a2",
          "hasUserSelectedAll": true
        }
      ],
      "labelRelations": {
        "operator": "OR",
        "conditions": [
          {
            "labelId": "957998f9-1824-4872-becd-b7f8a7962896"
          }
        ]
      }
    },
    "metadata": [
      {
        "key": "Customer tier",
        "value": "VIP"
      },
      {
        "key": "Preferred language",
        "value": "Traditional Chinese"
```

```
      }
    ]
  }'

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// Request body (payload)
const data = {
    "inboxes": [
      {
        "id": "inbox_uuid"
      }
    ],
    "name": "user1",
    "avatar": "",
    "phoneNumber": 912345678,
    "email": "user1@example.com",
    "sourceId": "self defined source id",
    "queryMetadata": {
      "knowledgeBases": [
        {
          "knowledgeBaseId": "5f8c6a99-5515-43aa-8e83-fdeea327a3a2",
          "hasUserSelectedAll": true
        }
      ],
      "labelRelations": {
        "operator": "OR",
        "conditions": [
          {
            "labelId": "957998f9-1824-4872-becd-b7f8a7962896"
          }
        ]
      }
    },
    "metadata": [
      {
        "key": "Customer tier",
        "value": "VIP"
```

```
      },
      {
        "key": "Preferred language",
        "value": "Traditional Chinese"
      }
    ]
  };

axios.post("https://api.maiagent.ai/api/v1/contacts/", data, config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/contacts/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# Request body (payload)
data = {
    "inboxes": [
        {
            "id": "inbox_uuid"
        }
    ],
    "name": "user1",
    "avatar": "",
    "phoneNumber": 912345678,
    "email": "user1@example.com",
    "sourceId": "self defined source id",
    "queryMetadata": {
        "knowledgeBases": [
            {
                "knowledgeBaseId": "5f8c6a99-5515-43aa-8e83-
fdeea327a3a2",
                "hasUserSelectedAll": True
            }
        ],
        "labelRelations": {
            "operator": "OR",
            "conditions": [
                {
                    "labelId": "957998f9-1824-4872-becd-b7f8a7962896"
                }
            ]
        }
    },
    "metadata": [
        {
            "key": "Customer tier",
            "value": "VIP"
        },
```

```
        {
            "key": "Preferred language",
            "value": "Traditional Chinese"
        }
    ]
}

response = requests.post(url, json=data, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>post("https://api.maiagent.ai/api/v1/contacts/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'inboxes' => [
                [
                    'id' => 'inbox_uuid'
                ]
            ],
            'name' => 'user1',
            'avatar' => '',
            'phoneNumber' => 912345678,
            'email' => 'user1@example.com',
            'sourceId' => 'self defined source id',
            'queryMetadata' => [
                'knowledgeBases' => [
                    [
                        'knowledgeBaseId' => '5f8c6a99-5515-43aa-8e83-
fdeea327a3a2',
                        'hasUserSelectedAll' => true
                    ]
                ],
                'labelRelations' => [
                    'operator' => 'OR',
                    'conditions' => [
                        [
                            'labelId' => '957998f9-1824-4872-becd-
b7f8a7962896'
                        ]
                    ]
                ]
            ],
            'metadata' => [
```

```
                [
                    'key' => 'Customer tier',
                    'value' => 'VIP'
                ],
                [
                    'key' => 'Preferred language',
                    'value' => 'Traditional Chinese'
                ]
            ]
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response

Status code: 201

Example response schema

```
{
  "id": string (uuid)
  "inboxes"?: [ // Optional
    {
      "id": string (uuid)
      "name": string
    }
  ]
  "inbox"?:  // Backward-compatible field: a single inbox; ignored if inboxes
is also provided (Optional)
  {
    "id": string (uuid)
```

```
    "name": string
  }
  "name": string
  "avatar"?: // May have different types (Optional)
  string (uri) // Contact avatar URL; supports an absolute URL or a relative
path (Optional)
  "phoneNumber"?: string // Optional
  "email"?: // May have different types (Optional)
  string (email) // Optional
  "sourceId"?: string // Optional
  "externalId"?: string // External user ID: the user ID in the calling
system, unique within the organization (excluding deleted contacts). Matching
uses the exact original string and is case-sensitive; the conversation API
uses message.externalUser.id to find the contact by this ID. Empty or
whitespace-only strings return 400; pass null to clear the value. For
multiple external systems, use a system prefix, such as projects:usr_123
(Optional)
  "queryMetadata"?: { // Query metadata that controls the scope of searchable
knowledge; see each endpoint for details (Optional)
  {
    "knowledgeBases"?: [ // List of searchable knowledge bases; an empty
array or null denies access to all knowledge bases, while omission imposes no
restrictions (Optional)
      {
        "knowledgeBaseId": string (uuid) // Knowledge base ID
        "chatbotFileIds"?: [ // List of file IDs to exclude or select
exclusively, depending on hasUserSelectedAll (Optional)
          string (uuid)
        ]
        "knowledgeBaseFileIds"?: [ // List of file IDs (the new name for
chatbotFileIds; this field takes precedence if both are provided) (Optional)
          string (uuid)
        ]
        "faqIds"?: [ // List of FAQ IDs to exclude or select exclusively,
depending on hasUserSelectedAll (Optional)
          string (uuid)
        ]
        "hasUserSelectedAll"?: boolean // true selects all knowledge base
content except the listed items; false selects only the listed items
(Optional)
      }
    ]
    "labelRelations"?: { // Label filters; an empty conditions array means no
label filtering (it does not mean access is denied). Must be provided
together with knowledgeBases; when provided alone, label filtering is not
applied to knowledge base retrieval (equivalent to no restrictions)
(Optional)
```

```
    {
      "operator": string (enum: AND, OR) // How label conditions are combined
      "conditions"?: [ // List of label conditions; supports nested
operator/conditions combinations (Optional)
        object
      ]
    }
    }
  }
  }
  "metadata"?: object // Custom customer information shown in the customer
panel of the conversation page (Optional)
  "mcpCredentials": [ // List of MCP authentication credentials for the
contact
    object
  ]
  "apiCredentials": [ // List of API authentication credentials for the
contact
    object
  ]
  "contactConnectors": [ // List of Connector OAuth authorizations for the
contact (excluding token values)
    object
  ]
  "tags": [
    {
      "id": string (uuid)
      "name": string
      "createdAt": string (timestamp)
      "updatedAt": string (timestamp)
    }
  ]
  "preChatFieldIndex": object // Pre-chat form field configuration from the
inboxes this Contact belongs to, mapped as {field_id: {label: {locale:
text}}}; the frontend uses it to resolve UUID keys in metadata to display
names
  "createdAt": string (timestamp)
  "updatedAt": string (timestamp)
}
```

Example response value

```
{
  "id": "user1_uuid",
  "inboxes": [
```

```
    {
      "id": "inbox_uuid",
      "name": "inbox_name"
    }
  ],
  "name": "user1",
  "avatar": "",
  "phoneNumber": 912345678,
  "email": "user1@example.com",
  "sourceId": null,
  "queryMetadata": null,
  "createdAt": "1751875361000",
  "updatedAt": "1751875361000"
}
```


Status code: 4XX - Error response; X-Error-Code carries its code (see "Error codes").

Get contact details

`GET` `/api/v1/contacts/{id}`

Parameters

Parameter name	Required	Type	Description
`id`	V	string	A UUID string identifying this Contact.

Code examples

Shell/Bash

```
# API call example (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/contacts/550e8400-e29b-
41d4-a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/contacts/550e8400-e29b-41d4-
a716-446655440000/", config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/contacts/550e8400-e29b-41d4-a716-446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/contacts/550e8400-e29b-41d4-a716-
446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response

Status code: 200

Example response schema

```
{
  "id": string (uuid)
  "inboxes"?: [ // Optional
    {
      "id": string (uuid)
```

```
      "name": string
    }
  ]
  "inbox"?:  // Backward-compatible field: a single inbox; ignored when
inboxes is also provided (Optional)
  {
    "id": string (uuid)
    "name": string
  }
  "name": string
  "avatar"?: // May have different types (Optional)
  string (uri) // Contact avatar URL; supports absolute URLs or relative
paths (Optional)
  "phoneNumber"?: string // Optional
  "email"?: // May have different types (Optional)
  string (email) // Optional
  "sourceId"?: string // Optional
  "externalId"?: string // External user ID: the user ID in the calling
system, unique within the organization (excluding deleted contacts). Matching
is exact and case-sensitive; the conversation API uses
message.externalUser.id to find the contact by this ID. An empty or
whitespace-only string returns 400; pass null to clear it. For multiple
external systems, use a system prefix, such as projects:usr_123 (Optional)
  "queryMetadata"?: { // Query metadata controlling the scope of searchable
knowledge; see each endpoint’s description (Optional)
  {
    "knowledgeBases"?: [ // List of queryable knowledge bases; an empty array
or null denies all access, while omission leaves access unrestricted
(Optional)
      {
        "knowledgeBaseId": string (uuid) // Knowledge base ID
        "chatbotFileIds"?: [ // List of file IDs (excluded or exclusively
selected, depending on hasUserSelectedAll) (Optional)
          string (uuid)
        ]
        "knowledgeBaseFileIds"?: [ // List of file IDs (the new name for
chatbotFileIds; this field takes precedence when both are provided)
(Optional)
          string (uuid)
        ]
        "faqIds"?: [ // List of FAQ IDs (excluded or exclusively selected,
depending on hasUserSelectedAll) (Optional)
          string (uuid)
        ]
        "hasUserSelectedAll"?: boolean // true selects all knowledge base
content except the listed items; false selects only the listed items
(Optional)
```

```
      }
    ]
    "labelRelations"?: { // Tag filter criteria; an empty conditions array
disables tag filtering (it does not deny access). Must be provided together
with knowledgeBases. When provided alone, tag filtering is not applied to
knowledge base retrieval (equivalent to unrestricted access) (Optional)
    {
      "operator": string (enum: AND, OR) // How tag conditions are combined
      "conditions"?: [ // List of tag conditions; supports nested
operator/conditions combinations (Optional)
        object
      ]
    }
    }
  }
  }
  "metadata"?: object // Custom customer information shown in the customer
panel of the conversation page (Optional)
  "mcpCredentials": [ // List of the contact’s MCP authentication credentials
    object
  ]
  "apiCredentials": [ // List of the contact’s API authentication credentials
    object
  ]
  "contactConnectors": [ // List of the contact’s Connector OAuth
authorizations (excluding the tokens themselves)
    object
  ]
  "tags": [
    {
      "id": string (uuid)
      "name": string
      "createdAt": string (timestamp)
      "updatedAt": string (timestamp)
    }
  ]
  "preChatFieldIndex": object // Pre-chat form field settings from the
inboxes this Contact belongs to, mapped as {field_id: {label: {locale:
text}}}. The frontend uses this mapping to resolve UUID keys in metadata to
display names
  "createdAt": string (timestamp)
  "updatedAt": string (timestamp)
}
```

Example Response Values

```
{
  "id": "user1_uuid",
  "inboxes": [
    {
      "id": "inbox_uuid",
      "name": "inbox_name"
    }
  ],
  "name": "user1",
  "avatar": "",
  "phoneNumber": 912345678,
  "email": "user1@example.com",
  "sourceId": null,
  "queryMetadata": null,
  "createdAt": "1751875361000",
  "updatedAt": "1751875361000"
}
```


Status Code: 4XX - Error response; X-Error-Code carries its code (see "Error codes").

Update Contact

PUT `/api/v1/contacts/{id}`

Parameters

Parameter Name	Required	Type	Description
`id`	V	string	A UUID string identifying this Contact.

Request Body

Request Parameters

Field	Type	Required	Description
name	string	No	Contact name
inboxes	array[object]	No	List of conversation platforms (new format)
inbox	object	No	Single conversation platform (legacy format, backward compatible)
inbox.id	string (uuid)	Yes	Conversation platform ID
avatar	string	No	Avatar URL
phoneNumber	string	No	Contact phone number
email	string (email)	No	Contact email address
sourceId	string	No	Source ID
queryMetadata	object	No	Query Metadata controls the scope of searchable knowledge. Omitted or null means unset (unrestricted); an empty object {} also means unrestricted (all selected), rather than no access. If knowledgeBases is an empty array or null, no knowledge can be queried (no access). An empty labelRelations.conditions array disables tag filtering (it does not deny access). See this endpoint’ s description for details.
queryMetadata.knowledgeBases	array[object]	No	List of queryable knowledge bases; an empty array or null denies all access, while

Field	Type	Required	Description
			omission leaves access unrestricted
queryMetadata.labelRelations	object	No	Tag filter criteria; an empty conditions array disables tag filtering (it does not deny access). Must be provided together with knowledgeBases. When provided alone, tag filtering is not applied to knowledge base retrieval (equivalent to unrestricted access)
queryMetadata.labelRelations.operator	string (enum: AND, OR)	Yes	How tag conditions are combined
queryMetadata.labelRelations.conditions	array[any]	No	List of tag conditions; supports nested operator/conditions combinations
metadata	array[object]	No	List of custom contact attributes

Request Schema Example

```
{
  "name"?: string // Contact name (Optional)
  "inboxes"?: [ // List of conversation platforms (new format) (Optional)
    {
      "id": string (uuid) // Conversation platform ID
    }
  ]
  "inbox"?: { // Single conversation platform (legacy format, backward
compatible) (Optional)
  {
    "id": string (uuid) // Conversation platform ID
  }
  }
  "avatar"?: string // Avatar URL (Optional)
  "phoneNumber"?: string // Contact phone number (Optional)
```

```
  "email"?: string (email) // Contact email address (Optional)
  "sourceId"?: string // Source ID (Optional)
  "queryMetadata"?: { // Query Metadata controls the scope of searchable
knowledge. Omitted or null means unset (unrestricted); an empty object {}
also means unrestricted (all selected), rather than no access. If
knowledgeBases is an empty array or null, no knowledge can be queried (no
access). An empty labelRelations.conditions array disables tag filtering (it
does not deny access). See this endpoint’s description for details.
(Optional)
  {
    "knowledgeBases"?: [ // List of queryable knowledge bases; an empty array
or null denies all access, while omission leaves access unrestricted
(Optional)
      {
        "knowledgeBaseId": string (uuid) // Knowledge base ID
        "chatbotFileIds"?: [ // List of file IDs (excluded or exclusively
selected, depending on hasUserSelectedAll) (Optional)
          string (uuid)
        ]
        "knowledgeBaseFileIds"?: [ // List of file IDs (the new name for
chatbotFileIds; this field takes precedence when both are provided)
(Optional)
          string (uuid)
        ]
        "faqIds"?: [ // List of FAQ IDs (excluded or exclusively selected,
depending on hasUserSelectedAll) (Optional)
          string (uuid)
        ]
        "hasUserSelectedAll"?: boolean // true selects all knowledge base
content except the listed items; false selects only the listed items
(Optional)
      }
    ]
    "labelRelations"?: { // Tag filter criteria; an empty conditions array
disables tag filtering (it does not deny access). Must be provided together
with knowledgeBases. When provided alone, tag filtering is not applied to
knowledge base retrieval (equivalent to unrestricted access) (Optional)
    {
      "operator": string (enum: AND, OR) // How tag conditions are combined
      "conditions"?: [ // List of tag conditions; supports nested
operator/conditions combinations (Optional)
        object
      ]
    }
    }
  }
  }
```

```
  "metadata"?: [ // List of custom contact attributes (Optional)
    {
      "key": string // Attribute name
      "value": string // Attribute value
      "updatedAt"?: string // Update time (ISO format; optional, populated
automatically if omitted) (Optional)
    }
  ]
}
```

Example Request Values

```
{
  "inboxes": [
    {
      "id": "new_inbox_uuid"
    }
  ],
  "name": "updated_user_name",
  "avatar": "updated_avatar_url",
  "phoneNumber": 987654321,
  "email": "updated@example.com",
  "sourceId": "updated_source_id",
  "queryMetadata": {
    "knowledgeBases": []
  },
  "metadata": [
    {
      "key": "Customer tier",
      "value": "VVIP"
    },
    {
      "key": "Preferred language",
      "value": "日本語"
    }
  ]
}
```

Code Examples

Shell/Bash

```
# API call example (Shell)
curl -X PUT "https://api.maiagent.ai/api/v1/contacts/550e8400-e29b-
41d4-a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "inboxes": [
      {
        "id": "new_inbox_uuid"
      }
    ],
    "name": "updated_user_name",
    "avatar": "updated_avatar_url",
    "phoneNumber": 987654321,
    "email": "updated@example.com",
    "sourceId": "updated_source_id",
    "queryMetadata": {
      "knowledgeBases": []
    },
    "metadata": [
      {
        "key": "Customer tier",
        "value": "VVIP"
      },
      {
        "key": "Preferred language",
        "value": "日本語"
      }
    ]
  }'

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// Request body (payload)
const data = {
    "inboxes": [
      {
        "id": "new_inbox_uuid"
      }
    ],
    "name": "updated_user_name",
    "avatar": "updated_avatar_url",
    "phoneNumber": 987654321,
    "email": "updated@example.com",
    "sourceId": "updated_source_id",
    "queryMetadata": {
      "knowledgeBases": []
    },
    "metadata": [
      {
        "key": "Customer tier",
        "value": "VVIP"
      },
      {
        "key": "Preferred language",
        "value": "日本語"
      }
    ]
  };

axios.put("https://api.maiagent.ai/api/v1/contacts/550e8400-e29b-41d4-
a716-446655440000/", data, config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
```

```
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/contacts/550e8400-e29b-41d4-a716-
446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# Request body (payload)
data = {
    "inboxes": [
        {
            "id": "new_inbox_uuid"
        }
    ],
    "name": "updated_user_name",
    "avatar": "updated_avatar_url",
    "phoneNumber": 987654321,
    "email": "updated@example.com",
    "sourceId": "updated_source_id",
    "queryMetadata": {
        "knowledgeBases": []
    },
    "metadata": [
        {
            "key": "Customer tier",
            "value": "VVIP"
        },
        {
            "key": "Preferred language",
            "value": "日本語"
        }
    ]
}

response = requests.put(url, json=data, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
```

```
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>put("https://api.maiagent.ai/api/v1/contacts/550e8400-e29b-41d4-a716-
446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'inboxes' => [
                [
                    'id' => 'new_inbox_uuid'
                ]
            ],
            'name' => 'updated_user_name',
            'avatar' => 'updated_avatar_url',
            'phoneNumber' => 987654321,
            'email' => 'updated@example.com',
            'sourceId' => 'updated_source_id',
            'queryMetadata' => [
                'knowledgeBases' => []
            ],
            'metadata' => [
                [
                    'key' => 'Customer tier',
                    'value' => 'VVIP'
                ],
                [
                    'key' => 'Preferred language',
                    'value' => '日本語'
                ]
            ]
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
```

```
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response Body

Status Code: 200

Response Schema Example

```
{
  "id": string (uuid)
  "inboxes"?: [ // Optional
    {
      "id": string (uuid)
      "name": string
    }
  ]
  "inbox"?:  // Backward-compatible field: a single inbox; ignored when
inboxes is also provided (Optional)
  {
    "id": string (uuid)
    "name": string
  }
  "name": string
  "avatar"?: // May have different types (Optional)
  string (uri) // Contact avatar URL; supports absolute URLs or relative
paths (Optional)
  "phoneNumber"?: string // Optional
  "email"?: // May have different types (Optional)
  string (email) // Optional
  "sourceId"?: string // Optional
  "externalId"?: string // External user ID: the user ID in the calling
system, unique within the organization (excluding deleted contacts). Matching
is exact and case-sensitive; the conversation API uses
message.externalUser.id to find the contact by this ID. An empty or
```

```
whitespace-only string returns 400; pass null to clear it. For multiple
external systems, use a system prefix, such as projects:usr_123 (Optional)
  "queryMetadata"?: { // Query metadata controlling the scope of searchable
knowledge; see each endpoint’s description (Optional)
  {
    "knowledgeBases"?: [ // List of queryable knowledge bases; an empty array
or null denies all access, while omission leaves access unrestricted
(Optional)
      {
        "knowledgeBaseId": string (uuid) // Knowledge base ID
        "chatbotFileIds"?: [ // List of file IDs (excluded or exclusively
selected, depending on hasUserSelectedAll) (Optional)
          string (uuid)
        ]
        "knowledgeBaseFileIds"?: [ // List of file IDs (the new name for
chatbotFileIds; this field takes precedence when both are provided)
(Optional)
          string (uuid)
        ]
        "faqIds"?: [ // List of FAQ IDs (excluded or exclusively selected,
depending on hasUserSelectedAll) (Optional)
          string (uuid)
        ]
        "hasUserSelectedAll"?: boolean // true selects all knowledge base
content except the listed items; false selects only the listed items
(Optional)
      }
    ]
    "labelRelations"?: { // Tag filter criteria; an empty conditions array
disables tag filtering (it does not deny access). Must be provided together
with knowledgeBases. When provided alone, tag filtering is not applied to
knowledge base retrieval (equivalent to unrestricted access) (Optional)
    {
      "operator": string (enum: AND, OR) // How tag conditions are combined
      "conditions"?: [ // List of tag conditions; supports nested
operator/conditions combinations (Optional)
        object
      ]
    }
    }
  }
  }
  "metadata"?: object // Custom customer information shown in the customer
panel of the conversation page (Optional)
  "mcpCredentials": [ // List of the contact’s MCP authentication credentials
    object
  ]
```

```
  "apiCredentials": [ // List of the contact’s API authentication credentials
    object
  ]
  "contactConnectors": [ // List of the contact’s Connector OAuth
authorizations (excluding the tokens themselves)
    object
  ]
  "tags": [
    {
      "id": string (uuid)
      "name": string
      "createdAt": string (timestamp)
      "updatedAt": string (timestamp)
    }
  ]
  "preChatFieldIndex": object // Pre-chat form field settings from the
inboxes this Contact belongs to, mapped as {field_id: {label: {locale:
text}}}. The frontend uses this mapping to resolve UUID keys in metadata to
display names
  "createdAt": string (timestamp)
  "updatedAt": string (timestamp)
}
```

Example Response Values

```
{
  "id": "user1_uuid",
  "inboxes": [
    {
      "id": "inbox_uuid",
      "name": "inbox_name"
    }
  ],
  "name": "user1",
  "avatar": "",
  "phoneNumber": 912345678,
  "email": "user1@example.com",
  "sourceId": null,
  "queryMetadata": null,
  "createdAt": "1751875361000",
  "updatedAt": "1751875361000"
}
```

Status Code: 4XX - Error response; X-Error-Code carries its code (see "Error codes").

Partially Update Contact

`PATCH` `/api/v1/contacts/{id}`

Parameters

Parameter Name	Required	Type	Description
`id`	V	string	A UUID string identifying this Contact.

Request Body

Request Parameters

Field	Type	Required	Description
name	string	No	Contact name
inboxes	array[object]	No	List of conversation platforms (new format)
inbox	object	No	Single conversation platform (legacy format, backward compatible)
inbox.id	string (uuid)	Yes	Conversation platform ID
avatar	string	No	Avatar URL
phoneNumber	string	No	Contact phone number

Field	Type	Required	Description
email	string (email)	No	Contact email address
sourceId	string	No	Source ID
queryMetadata	object	No	Query Metadata controls the scope of searchable knowledge. Omitted or null means unset (unrestricted); an empty object {} also means unrestricted (all selected), rather than no access. If knowledgeBases is an empty array or null, no knowledge can be queried (no access). An empty labelRelations.conditions array disables tag filtering (it does not deny access). See this endpoint’ s description for details.
queryMetadata.knowledgeBases	array[object]	No	List of queryable knowledge bases; an empty array or null denies all access, while omission leaves access unrestricted
queryMetadata.labelRelations	object	No	Tag filter criteria; an empty conditions array disables tag filtering (it does not deny access). Must be provided together with knowledgeBases. When provided alone, tag filtering is not applied to knowledge base retrieval (equivalent to unrestricted access)

Field	Type	Required	Description
queryMetadata.labelRelations.operator	string (enum: AND, OR)	Yes	How tag conditions are combined
queryMetadata.labelRelations.conditions	array[any]	No	List of tag conditions; supports nested operator/conditions combinations
metadata	array[object]	No	List of custom contact attributes

Request Schema Example

```
{
  "name"?: string // Contact name (Optional)
  "inboxes"?: [ // List of conversation platforms (new format) (Optional)
    {
      "id": string (uuid) // Conversation platform ID
    }
  ]
  "inbox"?: { // Single conversation platform (legacy format, backward
compatible) (Optional)
  {
    "id": string (uuid) // Conversation platform ID
  }
  }
  "avatar"?: string // Avatar URL (Optional)
  "phoneNumber"?: string // Contact phone number (Optional)
  "email"?: string (email) // Contact email address (Optional)
  "sourceId"?: string // Source ID (Optional)
  "queryMetadata"?: { // Query Metadata controls the scope of searchable
knowledge. Omitted or null means unset (unrestricted); an empty object {}
also means unrestricted (all selected), rather than no access. If
knowledgeBases is an empty array or null, no knowledge can be queried (no
access). An empty labelRelations.conditions array disables tag filtering (it
does not deny access). See this endpoint’s description for details.
(Optional)
  {
    "knowledgeBases"?: [ // List of queryable knowledge bases; an empty array
or null denies all access, while omission leaves access unrestricted
(Optional)
      {
        "knowledgeBaseId": string (uuid) // Knowledge base ID
```

```
        "chatbotFileIds"?: [ // List of file IDs (excluded or exclusively
selected, depending on hasUserSelectedAll) (Optional)
          string (uuid)
        ]
        "knowledgeBaseFileIds"?: [ // List of file IDs (the new name for
chatbotFileIds; this field takes precedence when both are provided)
(Optional)
          string (uuid)
        ]
        "faqIds"?: [ // List of FAQ IDs (excluded or exclusively selected,
depending on hasUserSelectedAll) (Optional)
          string (uuid)
        ]
        "hasUserSelectedAll"?: boolean // true selects all knowledge base
content except the listed items; false selects only the listed items
(Optional)
      }
    ]
    "labelRelations"?: { // Tag filter criteria; an empty conditions array
disables tag filtering (it does not deny access). Must be provided together
with knowledgeBases. When provided alone, tag filtering is not applied to
knowledge base retrieval (equivalent to unrestricted access) (Optional)
    {
      "operator": string (enum: AND, OR) // How tag conditions are combined
      "conditions"?: [ // List of tag conditions; supports nested
operator/conditions combinations (Optional)
        object
      ]
    }
    }
  }
  }
  "metadata"?: [ // List of custom contact attributes (Optional)
    {
      "key": string // Attribute name
      "value": string // Attribute value
      "updatedAt"?: string // Update time (ISO format; optional, populated
automatically if omitted) (Optional)
    }
  ]
}
```

Example Request Values

```
{
  "inboxes": [
    {
      "id": "new_inbox_uuid"
    }
  ],
  "name": "updated_user_name",
  "avatar": "updated_avatar_url",
  "phoneNumber": 987654321,
  "email": "updated@example.com",
  "sourceId": "updated_source_id",
  "queryMetadata": {
    "knowledgeBases": []
  },
  "metadata": [
    {
      "key": "Customer tier",
      "value": "VVIP"
    },
    {
      "key": "Preferred language",
      "value": "日本語"
    }
  ]
}
```


Code Examples

Shell/Bash

```
# API call example (Shell)
curl -X PATCH "https://api.maiagent.ai/api/v1/contacts/550e8400-e29b-
41d4-a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "inboxes": [
      {
        "id": "new_inbox_uuid"
      }
    ],
    "name": "updated_user_name",
    "avatar": "updated_avatar_url",
    "phoneNumber": 987654321,
    "email": "updated@example.com",
    "sourceId": "updated_source_id",
    "queryMetadata": {
      "knowledgeBases": []
    },
    "metadata": [
      {
        "key": "Customer tier",
        "value": "VVIP"
      },
      {
        "key": "Preferred language",
        "value": "日本語"
      }
    ]
  }'

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// Request body (payload)
const data = {
    "inboxes": [
      {
        "id": "new_inbox_uuid"
      }
    ],
    "name": "updated_user_name",
    "avatar": "updated_avatar_url",
    "phoneNumber": 987654321,
    "email": "updated@example.com",
    "sourceId": "updated_source_id",
    "queryMetadata": {
      "knowledgeBases": []
    },
    "metadata": [
      {
        "key": "Customer tier",
        "value": "VVIP"
      },
      {
        "key": "Preferred language",
        "value": "Japanese"
      }
    ]
  };

axios.patch("https://api.maiagent.ai/api/v1/contacts/550e8400-e29b-
41d4-a716-446655440000/", data, config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
```

```
  })
  .catch(error => {
    console.error('Request failed:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/contacts/550e8400-e29b-41d4-a716-
446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# Request body (payload)
data = {
    "inboxes": [
        {
            "id": "new_inbox_uuid"
        }
    ],
    "name": "updated_user_name",
    "avatar": "updated_avatar_url",
    "phoneNumber": 987654321,
    "email": "updated@example.com",
    "sourceId": "updated_source_id",
    "queryMetadata": {
        "knowledgeBases": []
    },
    "metadata": [
        {
            "key": "Customer tier",
            "value": "VVIP"
        },
        {
            "key": "Preferred language",
            "value": "Japanese"
        }
    ]
}

response = requests.patch(url, json=data, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
```

```
except Exception as e:
    print("Request failed:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->patch("https://api.maiagent.ai/api/v1/contacts/550e8400-e29b-41d4-a716-446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'inboxes' => [
                [
                    'id' => 'new_inbox_uuid'
                ]
            ],
            'name' => 'updated_user_name',
            'avatar' => 'updated_avatar_url',
            'phoneNumber' => 987654321,
            'email' => 'updated@example.com',
            'sourceId' => 'updated_source_id',
            'queryMetadata' => [
                'knowledgeBases' => []
            ],
            'metadata' => [
                [
                    'key' => 'Customer tier',
                    'value' => 'VVIP'
                ],
                [
                    'key' => 'Preferred language',
                    'value' => 'Japanese'
                ]
            ]
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
```

```
    print_r($data);
} catch (Exception $e) {
    echo 'Request failed: ' . $e->getMessage();
}
?>
```

Response body

Status code: `200`

Example response structure

```
{
  "id": string (uuid)
  "inboxes"?: [ // Optional
    {
      "id": string (uuid)
      "name": string
    }
  ]
  "inbox"?:  // Backward compatibility field: a single inbox; ignored if
inboxes is also provided (Optional)
  {
    "id": string (uuid)
    "name": string
  }
  "name": string
  "avatar"?: // May have different types (Optional)
  string (uri) // Contact avatar URL; supports absolute URLs or relative
paths (Optional)
  "phoneNumber"?: string // Optional
  "email"?: // May have different types (Optional)
  string (email) // Optional
  "sourceId"?: string // Optional
  "externalId"?: string // External user ID: the user ID in the calling
system, unique within the organization (excluding deleted contacts). Matching
uses the exact, case-sensitive string; the conversation API uses
message.externalUser.id to find the contact by this ID. Empty or whitespace-
```

```
only strings return 400; pass null to clear it. For multiple external
systems, use a system prefix, such as projects:usr_123 (Optional)
  "queryMetadata"?: { // Query metadata that controls the scope of accessible
knowledge; see each endpoint for details (Optional)
  {
    "knowledgeBases"?: [ // List of accessible knowledge bases; an empty
array or null denies access to all knowledge bases (no permission); omitting
this field imposes no restriction (Optional)
      {
        "knowledgeBaseId": string (uuid) // Knowledge base ID
        "chatbotFileIds"?: [ // List of file IDs (excluded or exclusively
selected depending on hasUserSelectedAll) (Optional)
          string (uuid)
        ]
        "knowledgeBaseFileIds"?: [ // List of file IDs (the new name for
chatbotFileIds; this field takes precedence if both are provided) (Optional)
          string (uuid)
        ]
        "faqIds"?: [ // List of FAQ IDs (excluded or exclusively selected
depending on hasUserSelectedAll) (Optional)
          string (uuid)
        ]
        "hasUserSelectedAll"?: boolean // true selects all knowledge base
content except the listed items; false selects only the listed items
(Optional)
      }
    ]
    "labelRelations"?: { // Label filter criteria; an empty conditions array
disables label filtering (it does not deny access). Must be provided together
with knowledgeBases; when provided alone, label filtering is not applied to
knowledge base retrieval (equivalent to no restriction) (Optional)
    {
      "operator": string (enum: AND, OR) // How label conditions are combined
      "conditions"?: [ // List of label conditions; supports nested
operator/conditions combinations (Optional)
        object
      ]
    }
    }
  }
  }
  "metadata"?: object // Custom customer information shown in the customer
panel of the conversation page (Optional)
  "mcpCredentials": [ // List of MCP authentication credentials for the
contact
    object
  ]
```

```
  "apiCredentials": [ // List of API authentication credentials for the
contact
    object
  ]
  "contactConnectors": [ // List of Connector OAuth authorizations for the
contact (excluding token contents)
    object
  ]
  "tags": [
    {
      "id": string (uuid)
      "name": string
      "createdAt": string (timestamp)
      "updatedAt": string (timestamp)
    }
  ]
  "preChatFieldIndex": object // Pre-chat form field settings from the
inboxes this Contact belongs to, mapped as {field_id: {label: {locale:
text}}}; the frontend uses these settings to resolve UUID keys in metadata to
display names
  "createdAt": string (timestamp)
  "updatedAt": string (timestamp)
}
```

Example response values

```
{
  "id": "user1_uuid",
  "inboxes": [
    {
      "id": "inbox_uuid",
      "name": "inbox_name"
    }
  ],
  "name": "user1",
  "avatar": "",
  "phoneNumber": 912345678,
  "email": "user1@example.com",
  "sourceId": null,
  "queryMetadata": null,
  "createdAt": "1751875361000",
  "updatedAt": "1751875361000"
}
```

Status code: 4XX - Error response; X-Error-Code carries its code (see "Error codes").

Delete Contact

`DELETE` `/api/v1/contacts/{id}`

Parameters

Parameter	Required	Type	Description
`id`	V	string	A UUID string identifying this Contact.

Code Examples

Shell/Bash

```
# API call example (Shell)
curl -X DELETE "https://api.maiagent.ai/api/v1/contacts/550e8400-e29b-41d4-a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

// Request payload
const data = null;

axios.delete("https://api.maiagent.ai/api/v1/contacts/550e8400-e29b-
41d4-a716-446655440000/", data, config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/contacts/550e8400-e29b-41d4-a716-446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.delete(url, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>delete("https://api.maiagent.ai/api/v1/contacts/550e8400-e29b-41d4-
a716-446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response

Status Code	Description
204	No response body
400	The contact still has associated conversations and cannot be deleted

List a Contact’ s Conversations

`GET` `/api/v1/contacts/{id}/conversations/`

Parameters

Parameter Name	Required	Type	Description
`id`	V	string	A UUID string identifying this Contact.
`channels`	X	array	Multiple values may be separated by commas.
`externalId`	X	string	External user ID (exact match)
`inbox`	X	string	Filter by a single inbox ID (UUID format)
`inboxes`	X	string	Filter by multiple inbox IDs (comma-separated, for example: uuid1,uuid2, or use multiple inboxes parameters)
`keyword`	X	string	Search message content in conversations (case-insensitive)
`page`	X	integer	A page number within the paginated result set.
`pageSize`	X	integer	Number of results to return per page.
`query`	X	string	
`tags`	X	array	Multiple values may be separated by commas.

Code Examples

Shell/Bash

```
# API request example (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/contacts/550e8400-e29b-
41d4-a716-446655440000/conversations/?
channels=example&externalId=example&inbox=example&inboxes=example&keywo
rd=example&page=1&pageSize=1&query=example&tags=example"

  -H "Authorization: Api-Key YOUR_API_KEY"

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/contacts/550e8400-e29b-41d4-
a716-446655440000/conversations/?
channels=example&externalId=example&inbox=example&inboxes=example&keywo
rd=example&page=1&pageSize=1&query=example&tags=example", config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/contacts/550e8400-e29b-41d4-a716-
446655440000/conversations/?
channels=example&externalId=example&inbox=example&inboxes=example&keywo
rd=example&page=1&pageSize=1&query=example&tags=example"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/contacts/550e8400-e29b-41d4-a716-
446655440000/conversations/?
channels=example&externalId=example&inbox=example&inboxes=example&keywo
rd=example&page=1&pageSize=1&query=example&tags=example", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response Body

Status Code: 200

Example Response Schema

```
{
  "count": integer
  "next"?: string (uri) // Optional
```

```
  "previous"?: string (uri) // Optional
  "results": [
    {
      "id": string (uuid)
      "contact": { // Lightweight Contact Serializer for the Conversation
List view

Includes only fields required by the List view, omitting inboxes,
mcp_credentials, and api_credentials
to avoid N+1 queries. email / phone_number / metadata are scalar fields on
Contact itself,
needed for display in the frontend conversation sidebar, with no N+1
overhead.
      {
        "id": string (uuid)
        "name": string
        "avatar"?: string // Stores our own media as a relative storage key,
or an external CDN URL as-is. (Optional)
        "email"?: // May have different types (Optional)
        string (email) // Optional
        "phoneNumber"?: string // Optional
        "metadata"?: object // Custom customer information shown in the
customer panel of the conversation page (Optional)
        "sourceId"?: string // Optional
        "tags": [
          {
            "id": string (uuid)
            "name": string
          }
        ]
      }
      }
      "inbox": { // Inbox summary embedded in a conversation payload.

``unread_conversations_count`` stays here because it is part of the
documented REST conversation API. It is an org-wide denormalized
counter, so WS emit paths must run the payload through
:func:`strip_org_wide_unread_count` before broadcasting it to rooms
that include members without ``GroupInbox.can_view_conversations``.
      {
        "id": string (uuid)
        "name": string
        "channelType": string (enum: line, telegram, teams, web, messenger,
instagram, email, whatsapp, slack, team_plus, line_works, viber) // * `line`
- LINE
* `telegram` - Telegram
* `teams` - Teams
```

```
* `web` - Web
* `messenger` - Messenger
* `instagram` - Instagram
* `email` - Email
* `whatsapp` - WhatsApp
* `slack` - Slack
* `team_plus` - Team+
* `line_works` - LINE WORKS
* `viber` - Viber
        "unreadConversationsCount"?: integer // Optional
        "signAuth"?:  // Optional
        {
          "id": string (uuid)
          "signSource": string (uuid)
          "signParams": {
          {
            "keycloak":
            {
              "clientId": string
              "url": string
              "realm": string
            }
            "line":
            {
              "liffId": string
            }
            "ad":
            {
              "saml": string
            }
            "google"?:  // Optional
            {
              "enabled": boolean
            }
          }
          }
          "sourceIdAccessEnabled"?: boolean // When enabled, embedded
visitors presenting a Source ID (verified per the verify mode below) may chat
without going through the login flow. Disabled keeps every existing behavior
unchanged. (Optional)
          "sourceIdVerifyMode"?:  // "Require signature verification": the
embedding site must send an HMAC signature computed on its backend. "Source
ID only": anyone knowing a Source ID can act as that contact; suitable only
for testing or closed networks.

* `signature` - Require signature verification
* `raw` - Source ID only (Optional)
```

```
          {
          }
          "sourceIdSignatureTtlMinutes"?:  // How long a signature can be
used to obtain the contact identity. Not a session lifetime: once exchanged,
the session follows the existing WebChat mechanism.

* `1` - 1
* `5` - 5
* `15` - 15 (Optional)
          {
          }
          "keycloakTokenPassthrough"?: boolean // When enabled, the Keycloak
access token a visitor logged in with is forwarded as the Authorization
header when the AI calls MCP and API tools on their behalf, so tools do not
require a separate per-tool login. Only for the Keycloak sign source. Never
overrides an Authorization header a tool already resolves from its own
credentials. The visitor identity is the organization member bound to the
conversation at login, never the contact Source ID. (Optional)
          "keycloakTokenPassthroughAllowedHosts"?: [ // Hostnames (or
"*.example.com" wildcards) of the tools the visitor Keycloak token may be
sent to (Optional)
            string
          ]
          "organizationLogin": object // How visitors sign in when the sign
source is "organization" (mirrors the back-office login); null for other sign
sources
        }
        "enableAnalysis"?: boolean // Optional
      }
      }
      "chatbot": object // Chatbot (Agent) summary from the conversation's
inbox, already eager-loaded.

``is_maigpt`` lets the client tell the default MaiGPT agent apart (icon,
feature
gate) without comparing against the organization's ``maigpt_inbox`` id;
``file_workspace_mode`` is the effective P6 mode (MaiGPT, blueprint and the
organization's file-library switch already applied).
      "title": string
      "lastMessage"?: { // Optional
      {
        "id": string (uuid)
        "type"?: string // Optional
        "content"?: string // Optional
        "createdAt": string (timestamp)
      }
      }
```

```
      "callRecord":
      {
        "id": string (uuid)
        "status"?: string (enum: initiated, ringing, in-progress, completed,
failed, busy, no-answer, canceled) // * `initiated` - Initiated
* `ringing` - Ringing
* `in-progress` - In Progress
* `completed` - Completed
* `failed` - Failed
* `busy` - Busy
* `no-answer` - No Answer
* `canceled` - Canceled (Optional)
        "direction": string (enum: inbound, outbound) // * `inbound` -
Inbound
* `outbound` - Outbound
        "isActive": boolean
        "canHangup": boolean
      }
      "lastMessageCreatedAt": string (timestamp)
      "unreadMessagesCount": integer
      "autoReplyEnabled": boolean
      "isAutoReplyNow": boolean
      "willAiReplyNow": boolean // Whether a text message arriving through
the inbox gets an AI reply right now.

The messaging channels are gated by ``is_auto_reply_now`` (auto reply on and
inside the
inbox auto-reply schedule) and by the inbox having a chatbot. The chatbot's
API web chat
is answered by the completions endpoint, which ignores the schedule, so there
the
conversation switch alone decides. The channel is only looked up for a web
inbox outside
its schedule.

Surfaces that ignore the schedule on any inbox answer from their own rule
instead: the
completions endpoint continuing an existing conversation
(``completions_progress_status``)
and voice turns, which the voice agent answers.
      "lastReadAt": string (timestamp)
      "createdAt": string (timestamp)
      "isGroupChat": boolean
      "enableGroupMention"?: boolean // Optional
      "queryMetadata"?: { // Query metadata that controls the scope of
searchable knowledge; see each endpoint’s description for details (Optional)
      {
```

```
        "knowledgeBases"?: [ // List of searchable knowledge bases; an empty
array or null means none are searchable (no permission); omitting it imposes
no restriction (Optional)
          {
            "knowledgeBaseId": string (uuid) // Knowledge base ID
            "chatbotFileIds"?: [ // List of file IDs (excluded or exclusively
selected depending on hasUserSelectedAll) (Optional)
              string (uuid)
            ]
            "knowledgeBaseFileIds"?: [ // List of file IDs (the new name for
chatbotFileIds; this field takes precedence when both are provided)
(Optional)
              string (uuid)
            ]
            "faqIds"?: [ // List of FAQ IDs (excluded or exclusively selected
depending on hasUserSelectedAll) (Optional)
              string (uuid)
            ]
            "hasUserSelectedAll"?: boolean // true selects all knowledge base
content except the listed items; false selects only the listed items
(Optional)
          }
        ]
        "labelRelations"?: { // Tag filter criteria; an empty conditions
array means no tag filtering (not a lack of permission). Must be provided
together with knowledgeBases; when provided alone, tag filtering is not
applied to knowledge base retrieval (equivalent to no restriction) (Optional)
        {
          "operator": string (enum: AND, OR) // How tag conditions are
combined
          "conditions"?: [ // List of tag conditions; supports nested
operator/conditions combinations (Optional)
            object
          ]
        }
        }
      }
      }
      "toolMask"?: object // Enabled/disabled state per tool: {tool_id: bool}
(Optional)
      "connectorMask"?: object // Enabled/disabled state per connector:
{connector_id: bool} (Optional)
      "thinkingConfig"?: object // None = not set (inherit the chatbot
setting); otherwise {"reasoning_effort": <level>} (Optional)
      "thinkingConfigSchema": { // Thinking configuration form for this
model; null means this model has no thinking configuration
      {
```

```
        "type"?: string // Form type, always reasoning_effort (Optional)
        "fields"?: object // reasoning_effort field: options lists the
thinking levels accepted by this model (from lowest to highest); default is
always null (Optional)
        "canDisable"?: boolean // Whether thinking can be disabled for this
model; when true, options includes off (Optional)
        "unsetBehavior"?: string (enum: off, model_default) // Actual
behavior when neither the conversation nor the assistant has a thinking level
set: off means no thinking (fastest); model_default means the model thinks on
its own or the platform’s default level enables thinking (Optional)
        "unsetLevel"?: string // Level actually sent by the platform when
none is set; null means no thinking parameter is sent and the model’s own
default applies (Optional)
      }
      }
      "effectiveThinkingConfig": object // The level the next reply sends on
this conversation's model, after gating and clamping.

The stored choice resolves conversation > chatbot > the LLM row's default
level; None means
the model sends no thinking parameter, so the provider default applies.
      "llm": string (uuid) // The model the next reply runs on: the
conversation's pin, else its assistant's current model.

TC-0205: returning the stored ``conversation.llm`` would show a model an
unpinned conversation no
longer uses once its assistant switches model, while
``thinking_config_schema`` already follows the
effective model. Read-only: displaying it never marks the conversation as
explicitly selected;
only the update-llm endpoint does.
      "deepResearchStatus":  // Status of deep research for this conversation

* `not_used` - Not Used
* `started` - Started
* `running` - Running
* `completed` - Completed
* `failed` - Failed
      {
      }
      "deepResearchOutputFormat": // May have different types
      string (enum: canvas, chat, file) // Chosen delivery form for the
finished report. Set only when the user clicks a format in the pre-research
choice card; reset to NULL each time Deep Research is (re-)armed. NULL means
no explicit choice (or a plan-skipping request) and falls back to Canvas at
render time, but stays distinct from an explicit canvas pick so the frontend
can lock the card only after a real selection. To roll back to fixed-Canvas
```

```
behavior, force this to NULL/canvas — no redeploy needed.

* `canvas` - Canvas
* `chat` - Chat reply
* `file` - Downloadable file
      "ipAddress": string
      "ipCountryCode": string
      "ipRecordedAt": string (timestamp)
      "assignee":
      {
        "id": string (uuid)
        "name": string
        "userId": string (uuid)
      }
      "status"?: string (enum: open, resolved, queued) // * `open` - Open
* `resolved` - Resolved
* `queued` - Queued (Optional)
      "tags": [
        {
          "id": string (uuid)
          "name": string
          "memberIds"?: [ // Optional
            string (uuid)
          ]
        }
      ]
      "progressStatus": string
      "firstResponseAt"?: string (timestamp) // Optional
      "queuedAt"?: string (timestamp) // Optional
      "assignedAt"?: string (timestamp) // Optional
      "transferReason"?: string // Optional
      "satisfactionScore": integer // Conversation satisfaction rating on a
5-point scale (1=very dissatisfied, 5=very satisfied)
      "satisfactionComment": string
      "satisfactionSubmittedAt": string (timestamp)
      "latestAnalysisSummary": string // The conversation's current analysis
summary (its active summary revision).

Reads the `latest_analysis_summary` annotation added by `setup_eager_loading`
to avoid an N+1 query. All read paths (list / retrieve / create) eager-load,
so the annotation is present; it falls back to '' only for instances built
outside `setup_eager_loading`.
      "clientPlatform":  // Client platform that created this conversation
(web, desktop)

* `web` - Web
* `desktop` - Desktop
```

```
      {
      }
      "workingDirectory": string // Absolute path of the local folder bound
to a desktop conversation. Only set for desktop conversations; null for web
conversations.
      "slideProjectId": string
      "matchedField": string // Cached per instance:
``get_matched_message_id`` / ``get_matched_snippet``
both read this, so resolving it once avoids recomputing the keyword and
title-match logic three times per serialized conversation.
      "matchedSnippet": string // Keyword-centred excerpt of the matched
message, with ellipses.

Reads the ``matched_message_content`` annotation added by
``ConversationViewSet._annotate_keyword_match``; no extra query.
      "matchedMessageId": string
      "pinnedAt": string (timestamp) // When the conversation was pinned.
Null means unpinned.
      "folder": string (uuid) // The user-defined sidebar folder this
conversation is grouped into. Null means unclassified (shown under the time
groups). Deleting the folder resets this to null without deleting the
conversation.
      "hasActiveBrowserSession": boolean // Whether a browser_use session
snapshot exists to resume.

Lets the frontend know it should proactively re-request the browser
panel (emit ``browser:start``) after a page reload, instead of only
ever showing the panel when a live ``browser:frame`` push happens to
arrive first.
      "callerOrganizationId": string // Bound caller organization (stamped at
conversation start); null when unbound
      "handoff": object // Handoff information: enabled is the platform
toggle; the continuing conversation includes
source_conversation_id/source_title; the original conversation being handed
off includes continued_to_conversation_id/continued_to_title and
latest_summary_message_id
      "displayContextUsage": boolean // Whether to display the context usage
percentage bar (a conversation platform toggle, always true for MaiGPT;
independent of the handoff toggle)
      "autoSplitReason": string // Reason this conversation was created by
automatic conversation splitting: resolved (after resolution) / idle
(inactivity); null if not created by splitting
      "continuedFrom": object // Conversation continued by this split-created
conversation: {id, last_message_at, deleted}; if the previous conversation
has been deleted, id=null and deleted=true
      "continuedTo": object // Latest conversation split off from this
conversation: {id, created_at}; null if none
```

```
      "continuationSummary": object // Continuation summary: {state:
disabled|pending|ready|not_applied, items: [{conversation_id, content,
generated_at, last_message_at, old_status}]} (items ordered newest to
oldest); null if not created by splitting
      "conversationKind": string // chat = a chat with an agent; secretary =
the member's personal secretary Work chat
    }
  ]
}
```

Example Response Values

```
{
  "count": 123,
  "next": "http://api.example.org/accounts/?page=4",
  "previous": "http://api.example.org/accounts/?page=2",
  "results": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "contact": {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "name": "Response string",
        "avatar": "Response string",
        "email": "response@example.com",
        "phoneNumber": "Response string",
        "metadata": null,
        "sourceId": "Response string",
        "tags": [
          {
            "id": "550e8400-e29b-41d4-a716-446655440000",
            "name": "Response string"
          }
        ]
      },
      "inbox": {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "name": "Response string",
        "channelType": "line",
        "unreadConversationsCount": 456,
        "signAuth": {
          "id": "550e8400-e29b-41d4-a716-446655440000",
          "signSource": "550e8400-e29b-41d4-a716-446655440000",
          "signParams": {
            "keycloak": {
              "clientId": "Response string",
```

```
            "url": "Response string",
            "realm": "Response string"
          },
          "line": {
            "liffId": "Response string"
          },
          "ad": {
            "saml": "Response string"
          },
          "google": {
            "enabled": false
          }
        },
        "sourceIdAccessEnabled": false,
        "sourceIdVerifyMode": {},
        "sourceIdSignatureTtlMinutes": {},
        "keycloakTokenPassthrough": false,
        "keycloakTokenPassthroughAllowedHosts": [
          "Response string"
        ],
        "organizationLogin": {
          "id": "550e8400-e29b-41d4-a716-446655440000",
          "name": "Example response name",
          "description": "Example response description"
        }
      },
      "enableAnalysis": false
    },
    "chatbot": {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "Example response name",
      "description": "Example response description"
    },
    "title": "Response string",
    "lastMessage": {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "type": "Response string",
      "content": "Response string",
      "createdAt": "Response string"
    },
    "callRecord": {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "status": "initiated",
      "direction": "inbound",
      "isActive": false,
      "canHangup": false
    },
```

```
      "lastMessageCreatedAt": "Response string",
      "unreadMessagesCount": 456,
      "autoReplyEnabled": false,
      "isAutoReplyNow": false,
      "willAiReplyNow": false,
      "lastReadAt": "Response string",
      "createdAt": "Response string",
      "isGroupChat": false,
      "enableGroupMention": false,
      "queryMetadata": {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "name": "Example response name",
        "description": "Example response description"
      },
      "toolMask": null,
      "connectorMask": null,
      "thinkingConfig": null,
      "thinkingConfigSchema": {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "name": "Example response name",
        "description": "Example response description"
      },
      "effectiveThinkingConfig": {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "name": "Example response name",
        "description": "Example response description"
      },
      "llm": "550e8400-e29b-41d4-a716-446655440000",
      "deepResearchStatus": {},
      "deepResearchOutputFormat": "canvas",
      "ipAddress": "Response string",
      "ipCountryCode": "Response string",
      "ipRecordedAt": "Response string",
      "assignee": {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "name": "Response string",
        "userId": "550e8400-e29b-41d4-a716-446655440000"
      },
      "status": "open",
      "tags": [
        {
          "id": "550e8400-e29b-41d4-a716-446655440000",
          "name": "Response string",
          "memberIds": [
            "550e8400-e29b-41d4-a716-446655440000"
          ]
        }
```

```
      ],
      "progressStatus": "Response string",
      "firstResponseAt": "Response string",
      "queuedAt": "Response string",
      "assignedAt": "Response string",
      "transferReason": "Response string",
      "satisfactionScore": 456,
      "satisfactionComment": "Response string",
      "satisfactionSubmittedAt": "Response string",
      "latestAnalysisSummary": "Response string",
      "clientPlatform": {},
      "workingDirectory": "Response string",
      "slideProjectId": "Response string",
      "matchedField": "Response string",
      "matchedSnippet": "Response string",
      "matchedMessageId": "Response string",
      "pinnedAt": "Response string",
      "folder": "550e8400-e29b-41d4-a716-446655440000",
      "hasActiveBrowserSession": false,
      "callerOrganizationId": "Response string",
      "handoff": {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "name": "Example response name",
        "description": "Example response description"
      },
      "displayContextUsage": false,
      "autoSplitReason": "Response string",
      "continuedFrom": {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "name": "Example response name",
        "description": "Example response description"
      },
      "continuedTo": {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "name": "Example response name",
        "description": "Example response description"
      },
      "continuationSummary": {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "name": "Example response name",
        "description": "Example response description"
      },
      "conversationKind": "Response string"
    }
  ]
}
```

Status code: 4XX - Error response; X-Error-Code carries its code (see "Error codes").

Get the Contact’ s Latest Conversation

`GET` `/api/v1/contacts/{id}/conversations/latest/`

Parameters

Parameter name	Required	Type	Description
`id`	V	string	A UUID string identifying this Contact.
`inbox`	X	string	Filter by a single inbox ID (UUID format)
`inboxes`	X	string	Filter by multiple inbox IDs (comma-separated, e.g., uuid1,uuid2, or use multiple inboxes parameters)
`keyword`	X	string	Search message content in conversations (case-insensitive)

Code Examples

Shell/Bash

```
# API call example (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/contacts/550e8400-e29b-
41d4-a716-446655440000/conversations/latest/?
inbox=example&inboxes=example&keyword=example"

  -H "Authorization: Api-Key YOUR_API_KEY"

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/contacts/550e8400-e29b-41d4-
a716-446655440000/conversations/latest/?
inbox=example&inboxes=example&keyword=example", config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/contacts/550e8400-e29b-41d4-a716-
446655440000/conversations/latest/?
inbox=example&inboxes=example&keyword=example"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/contacts/550e8400-e29b-41d4-a716-
446655440000/conversations/latest/?
inbox=example&inboxes=example&keyword=example", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response

Status code: 200

Example Response Schema

```
{
  "id": string (uuid)
  "contact": { // Lightweight Contact Serializer for the Conversation List
view
```

```
Includes only the fields required by the List view, omitting inboxes,
mcp_credentials, and api_credentials
to avoid N+1 queries. email / phone_number / metadata are scalar fields on
Contact itself;
the frontend conversation sidebar needs to display them, with no N+1
overhead.
  {
    "id": string (uuid)
    "name": string
    "avatar"?: string // Stores our own media as a relative storage key, or
an external CDN URL as-is. (Optional)
    "email"?: // May have different types (Optional)
    string (email) // Optional
    "phoneNumber"?: string // Optional
    "metadata"?: object // Custom customer information shown in the customer
panel of the conversation page (Optional)
    "sourceId"?: string // Optional
    "tags": [
      {
        "id": string (uuid)
        "name": string
      }
    ]
  }
  }
  "inbox": { // Inbox summary embedded in a conversation payload.

``unread_conversations_count`` stays here because it is part of the
documented REST conversation API. It is an org-wide denormalized
counter, so WS emit paths must run the payload through
:func:`strip_org_wide_unread_count` before broadcasting it to rooms
that include members without ``GroupInbox.can_view_conversations``.
  {
    "id": string (uuid)
    "name": string
    "channelType": string (enum: line, telegram, teams, web, messenger,
instagram, email, whatsapp, slack, team_plus, line_works, viber) // * `line`
- LINE
* `telegram` - Telegram
* `teams` - Teams
* `web` - Web
* `messenger` - Messenger
* `instagram` - Instagram
* `email` - Email
* `whatsapp` - WhatsApp
* `slack` - Slack
```

```
* `team_plus` - Team+
* `line_works` - LINE WORKS
* `viber` - Viber
    "unreadConversationsCount"?: integer // Optional
    "signAuth"?:  // Optional
    {
      "id": string (uuid)
      "signSource": string (uuid)
      "signParams": {
      {
        "keycloak":
        {
          "clientId": string
          "url": string
          "realm": string
        }
        "line":
        {
          "liffId": string
        }
        "ad":
        {
          "saml": string
        }
        "google"?:  // Optional
        {
          "enabled": boolean
        }
      }
      }
      "sourceIdAccessEnabled"?: boolean // When enabled, embedded visitors presenting a Source ID (verified per the verify mode below) may chat without going through the login flow. Disabled keeps every existing behavior unchanged. (Optional)
      "sourceIdVerifyMode"?:  // "Require signature verification": the embedding site must send an HMAC signature computed on its backend. "Source ID only": anyone knowing a Source ID can act as that contact; suitable only for testing or closed networks.

* `signature` - Require signature verification
* `raw` - Source ID only (Optional)
      {
      }
      "sourceIdSignatureTtlMinutes"?:  // How long a signature can be used to obtain the contact identity. Not a session lifetime: once exchanged, the session follows the existing WebChat mechanism.
```

```
* `1` - 1
* `5` - 5
* `15` - 15 (Optional)
      {
      }
      "keycloakTokenPassthrough"?: boolean // When enabled, the Keycloak
access token a visitor logged in with is forwarded as the Authorization
header when the AI calls MCP and API tools on their behalf, so tools do not
require a separate per-tool login. Only for the Keycloak sign source. Never
overrides an Authorization header a tool already resolves from its own
credentials. The visitor identity is the organization member bound to the
conversation at login, never the contact Source ID. (Optional)
      "keycloakTokenPassthroughAllowedHosts"?: [ // Hostnames (or
"*.example.com" wildcards) of the tools the visitor Keycloak token may be
sent to (Optional)
        string
      ]
      "organizationLogin": object // How visitors sign in when the sign
source is "organization" (mirrors the back-office login); null for other sign
sources
    }
    "enableAnalysis"?: boolean // Optional
  }
  }
  "chatbot": object // Chatbot (Agent) summary from the conversation's inbox,
already eager-loaded.

``is_maigpt`` lets the client tell the default MaiGPT agent apart (icon,
feature
gate) without comparing against the organization's ``maigpt_inbox`` id;
``file_workspace_mode`` is the effective P6 mode (MaiGPT, blueprint and the
organization's file-library switch already applied).
  "title": string
  "lastMessage"?: { // Optional
  {
    "id": string (uuid)
    "type"?: string // Optional
    "content"?: string // Optional
    "createdAt": string (timestamp)
  }
  }
  "callRecord":
  {
    "id": string (uuid)
    "status"?: string (enum: initiated, ringing, in-progress, completed,
failed, busy, no-answer, canceled) // * `initiated` - Initiated
* `ringing` - Ringing
```

```
* `in-progress` - In Progress
* `completed` - Completed
* `failed` - Failed
* `busy` - Busy
* `no-answer` - No Answer
* `canceled` - Canceled (Optional)
    "direction": string (enum: inbound, outbound) // * `inbound` - Inbound
* `outbound` - Outbound
    "isActive": boolean
    "canHangup": boolean
  }
  "lastMessageCreatedAt": string (timestamp)
  "unreadMessagesCount": integer
  "autoReplyEnabled": boolean
  "isAutoReplyNow": boolean
  "willAiReplyNow": boolean // Whether a text message arriving through the
inbox gets an AI reply right now.

The messaging channels are gated by ``is_auto_reply_now`` (auto reply on and
inside the
inbox auto-reply schedule) and by the inbox having a chatbot. The chatbot's
API web chat
is answered by the completions endpoint, which ignores the schedule, so there
the
conversation switch alone decides. The channel is only looked up for a web
inbox outside
its schedule.

Surfaces that ignore the schedule on any inbox answer from their own rule
instead: the
completions endpoint continuing an existing conversation
(``completions_progress_status``)
and voice turns, which the voice agent answers.
  "lastReadAt": string (timestamp)
  "createdAt": string (timestamp)
  "isGroupChat": boolean
  "enableGroupMention"?: boolean // Optional
  "queryMetadata"?: { // Query metadata controlling the scope of searchable
knowledge; see each endpoint’s description (Optional)
  {
    "knowledgeBases"?: [ // List of searchable knowledge bases; an empty
array or null means none are searchable (no permission); omitted means
unrestricted (Optional)
      {
        "knowledgeBaseId": string (uuid) // Knowledge base ID
        "chatbotFileIds"?: [ // List of file IDs (excluded or exclusively
selected depending on hasUserSelectedAll) (Optional)
```

```
          string (uuid)
        ]
        "knowledgeBaseFileIds"?: [ // List of file IDs (the new name for
chatbotFileIds; this field takes precedence if both are provided) (Optional)
          string (uuid)
        ]
        "faqIds"?: [ // List of FAQ IDs (excluded or exclusively selected
depending on hasUserSelectedAll) (Optional)
          string (uuid)
        ]
        "hasUserSelectedAll"?: boolean // true = select all knowledge base
content except the listed items; false = select only the listed items
(Optional)
      }
    ]
    "labelRelations"?: { // Tag filter conditions; an empty conditions array
means no tag filtering (not a lack of permission). Must be provided together
with knowledgeBases; when provided alone, tag filtering is not applied to
knowledge base retrieval (equivalent to unrestricted access) (Optional)
    {
      "operator": string (enum: AND, OR) // How tag conditions are combined
      "conditions"?: [ // List of tag conditions supporting nested
operator/conditions combinations (Optional)
        object
      ]
    }
    }
  }
  }
  "toolMask"?: object // Enabled/disabled state per tool: {tool_id: bool}
(Optional)
  "connectorMask"?: object // Enabled/disabled state per connector:
{connector_id: bool} (Optional)
  "thinkingConfig"?: object // None = not set (inherit the chatbot setting);
otherwise {"reasoning_effort": <level>} (Optional)
  "thinkingConfigSchema": { // Thinking configuration form for this model;
null means the model has no thinking settings
  {
    "type"?: string // Form type, always reasoning_effort (Optional)
    "fields"?: object // reasoning_effort field: options lists the thinking
levels accepted by this model (from lowest to highest); default is always
null (Optional)
    "canDisable"?: boolean // Whether thinking can be disabled for this
model; when true, options includes off (Optional)
    "unsetBehavior"?: string (enum: off, model_default) // Effective behavior
when neither the conversation nor the assistant specifies a thinking level:
off = no thinking (fastest); model_default = the model decides, or the
```

```
platform’s default level enables thinking (Optional)
    "unsetLevel"?: string // Level actually sent by the platform when none is set; null means no thinking parameter is sent, leaving the model’s own default in effect (Optional)
  }
  }
  "effectiveThinkingConfig": object // The level the next reply sends on this conversation's model, after gating and clamping.

The stored choice resolves conversation > chatbot > the LLM row's default level; None means
the model sends no thinking parameter, so the provider default applies.
  "llm": string (uuid) // The model the next reply runs on: the conversation's pin, else its assistant's current model.

TC-0205: returning the stored ``conversation.llm`` would show a model an unpinned conversation no
longer uses once its assistant switches model, while
``thinking_config_schema`` already follows the
effective model. Read-only: displaying it never marks the conversation as explicitly selected;
only the update-llm endpoint does.
  "deepResearchStatus":  // Status of deep research for this conversation

* `not_used` - Not Used
* `started` - Started
* `running` - Running
* `completed` - Completed
* `failed` - Failed
  {
  }
  "deepResearchOutputFormat": // May have different types
  string (enum: canvas, chat, file) // Chosen delivery form for the finished report. Set only when the user clicks a format in the pre-research choice card; reset to NULL each time Deep Research is (re-)armed. NULL means no explicit choice (or a plan-skipping request) and falls back to Canvas at render time, but stays distinct from an explicit canvas pick so the frontend can lock the card only after a real selection. To roll back to fixed-Canvas behavior, force this to NULL/canvas — no redeploy needed.

* `canvas` - Canvas
* `chat` - Chat reply
* `file` - Downloadable file
  "ipAddress": string
  "ipCountryCode": string
  "ipRecordedAt": string (timestamp)
  "assignee":
```

```
  {
    "id": string (uuid)
    "name": string
    "userId": string (uuid)
  }
  "status"?: string (enum: open, resolved, queued) // * `open` - Open
* `resolved` - Resolved
* `queued` - Queued (Optional)
  "tags": [
    {
      "id": string (uuid)
      "name": string
      "memberIds"?: [ // Optional
        string (uuid)
      ]
    }
  ]
  "progressStatus": string
  "firstResponseAt"?: string (timestamp) // Optional
  "queuedAt"?: string (timestamp) // Optional
  "assignedAt"?: string (timestamp) // Optional
  "transferReason"?: string // Optional
  "satisfactionScore": integer // Conversation satisfaction rating on a 5-
point scale (1=very dissatisfied, 5=very satisfied)
  "satisfactionComment": string
  "satisfactionSubmittedAt": string (timestamp)
  "latestAnalysisSummary": string // The conversation's current analysis
summary (its active summary revision).

Reads the `latest_analysis_summary` annotation added by `setup_eager_loading`
to avoid an N+1 query. All read paths (list / retrieve / create) eager-load,
so the annotation is present; it falls back to '' only for instances built
outside `setup_eager_loading`.
  "clientPlatform":  // Client platform that created this conversation (web,
desktop)

* `web` - Web
* `desktop` - Desktop
  {
  }
  "workingDirectory": string // Absolute path of the local folder bound to a
desktop conversation. Only set for desktop conversations; null for web
conversations.
  "slideProjectId": string
  "matchedField": string // Cached per instance: ``get_matched_message_id`` /
``get_matched_snippet``
both read this, so resolving it once avoids recomputing the keyword and
```

```
title-match logic three times per serialized conversation.
  "matchedSnippet": string // Keyword-centred excerpt of the matched message,
with ellipses.

Reads the ``matched_message_content`` annotation added by
``ConversationViewSet._annotate_keyword_match``; no extra query.
  "matchedMessageId": string
  "pinnedAt": string (timestamp) // When the conversation was pinned. Null
means unpinned.
  "folder": string (uuid) // The user-defined sidebar folder this
conversation is grouped into. Null means unclassified (shown under the time
groups). Deleting the folder resets this to null without deleting the
conversation.
  "hasActiveBrowserSession": boolean // Whether a browser_use session
snapshot exists to resume.

Lets the frontend know it should proactively re-request the browser
panel (emit ``browser:start``) after a page reload, instead of only
ever showing the panel when a live ``browser:frame`` push happens to
arrive first.
  "callerOrganizationId": string // Bound caller organization (stamped at
conversation start); null when unbound
  "handoff": object // Handoff information: enabled = platform toggle; the
continuation conversation includes source_conversation_id/source_title; the
original handed-off conversation includes
continued_to_conversation_id/continued_to_title and latest_summary_message_id
  "displayContextUsage": boolean // Whether to display the context usage
percentage bar (conversation platform toggle; always true for MaiGPT;
independent of the handoff toggle)
  "autoSplitReason": string // Reason this conversation was created by
automatic splitting: resolved (after resolution) / idle (inactivity); null if
not created by splitting
  "continuedFrom": object // Conversation from which this split conversation
continues: {id, last_message_at, deleted}; if the old conversation was
deleted, id=null and deleted=true
  "continuedTo": object // Latest conversation split from this conversation:
{id, created_at}; null if none
  "continuationSummary": object // Continuation summary: {state:
disabled|pending|ready|not_applied, items: [{conversation_id, content,
generated_at, last_message_at, old_status}]} (items ordered newest to
oldest); null if not created by splitting
  "conversationKind": string // chat = a chat with an agent; secretary = the
member's personal secretary Work chat
}
```

Example Response Value

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "contact": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Response string",
    "avatar": "Response string",
    "email": "response@example.com",
    "phoneNumber": "Response string",
    "metadata": null,
    "sourceId": "Response string",
    "tags": [
      {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "name": "Response string"
      }
    ]
  },
  "inbox": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Response string",
    "channelType": "line",
    "unreadConversationsCount": 456,
    "signAuth": {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "signSource": "550e8400-e29b-41d4-a716-446655440000",
      "signParams": {
        "keycloak": {
          "clientId": "Response string",
          "url": "Response string",
          "realm": "Response string"
        },
        "line": {
          "liffId": "Response string"
        },
        "ad": {
          "saml": "Response string"
        },
        "google": {
          "enabled": false
        }
      },
      "sourceIdAccessEnabled": false,
      "sourceIdVerifyMode": {},
      "sourceIdSignatureTtlMinutes": {},
      "keycloakTokenPassthrough": false,
      "keycloakTokenPassthroughAllowedHosts": [
```

```
        "Response string"
      ],
      "organizationLogin": {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "name": "Example response name",
        "description": "Example response description"
      }
    },
    "enableAnalysis": false
  },
  "chatbot": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Example response name",
    "description": "Example response description"
  },
  "title": "Response string",
  "lastMessage": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "type": "Response string",
    "content": "Response string",
    "createdAt": "Response string"
  },
  "callRecord": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "status": "initiated",
    "direction": "inbound",
    "isActive": false,
    "canHangup": false
  },
  "lastMessageCreatedAt": "Response string",
  "unreadMessagesCount": 456,
  "autoReplyEnabled": false,
  "isAutoReplyNow": false,
  "willAiReplyNow": false,
  "lastReadAt": "Response string",
  "createdAt": "Response string",
  "isGroupChat": false,
  "enableGroupMention": false,
  "queryMetadata": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Example response name",
    "description": "Example response description"
  },
  "toolMask": null,
  "connectorMask": null,
  "thinkingConfig": null,
  "thinkingConfigSchema": {
```

```
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Example response name",
    "description": "Example response description"
  },
  "effectiveThinkingConfig": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Example response name",
    "description": "Example response description"
  },
  "llm": "550e8400-e29b-41d4-a716-446655440000",
  "deepResearchStatus": {},
  "deepResearchOutputFormat": "canvas",
  "ipAddress": "Response string",
  "ipCountryCode": "Response string",
  "ipRecordedAt": "Response string",
  "assignee": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Response string",
    "userId": "550e8400-e29b-41d4-a716-446655440000"
  },
  "status": "open",
  "tags": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "Response string",
      "memberIds": [
        "550e8400-e29b-41d4-a716-446655440000"
      ]
    }
  ],
  "progressStatus": "Response string",
  "firstResponseAt": "Response string",
  "queuedAt": "Response string",
  "assignedAt": "Response string",
  "transferReason": "Response string",
  "satisfactionScore": 456,
  "satisfactionComment": "Response string",
  "satisfactionSubmittedAt": "Response string",
  "latestAnalysisSummary": "Response string",
  "clientPlatform": {},
  "workingDirectory": "Response string",
  "slideProjectId": "Response string",
  "matchedField": "Response string",
  "matchedSnippet": "Response string",
  "matchedMessageId": "Response string",
  "pinnedAt": "Response string",
  "folder": "550e8400-e29b-41d4-a716-446655440000",
```

```
  "hasActiveBrowserSession": false,
  "callerOrganizationId": "Response string",
  "handoff": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Example response name",
    "description": "Example response description"
  },
  "displayContextUsage": false,
  "autoSplitReason": "Response string",
  "continuedFrom": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Example response name",
    "description": "Example response description"
  },
  "continuedTo": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Example response name",
    "description": "Example response description"
  },
  "continuationSummary": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Example response name",
    "description": "Example response description"
  },
  "conversationKind": "Response string"
}
```


Status Code: 404 - No response body

Broadcast Messages

POST `/api/v1/contacts/broadcast-message/`

Request Body

Request Parameters

Field	Type	Required	Description
contactIds	array[string]	No	[Explicit selection mode] List of contact IDs to send messages to
inboxId	string (uuid)	No	[Exclusion/send-to-all mode] Inbox ID; sends to all contacts in this inbox
excludeContactIds	array[string]	No	[Exclusion mode] List of contact IDs to exclude; must be used with inbox_id
message	string	Yes	Message content to send

Example Request Schema

```
{
  "contactIds"?: [ // [Explicit selection mode] List of contact IDs to send
messages to (Optional)
    string (uuid)
  ]
  "inboxId"?: string (uuid) // [Exclusion/send-to-all mode] Inbox ID; sends
to all contacts in this inbox (Optional)
  "excludeContactIds"?: [ // [Exclusion mode] List of contact IDs to exclude;
must be used with inbox_id (Optional)
    string (uuid)
  ]
  "message": string // Message content to send
}
```

Example Request Values

```
{
  "contactIds": [
    "550e8400-e29b-41d4-a716-446655440000"
  ],
  "inboxId": "550e8400-e29b-41d4-a716-446655440000",
  "excludeContactIds": [
    "550e8400-e29b-41d4-a716-446655440000"
  ],
  "message": "This is a sample message"
}
```

Code Examples

Shell/Bash

```
# API call example (Shell)
curl -X POST "https://api.maiagent.ai/api/v1/contacts/broadcast-
message/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "contactIds": [
      "550e8400-e29b-41d4-a716-446655440000"
    ],
    "inboxId": "550e8400-e29b-41d4-a716-446655440000",
    "excludeContactIds": [
      "550e8400-e29b-41d4-a716-446655440000"
    ],
    "message": "This is a sample message"
  }'

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// Request Body (payload)
const data = {
    "contactIds": [
      "550e8400-e29b-41d4-a716-446655440000"
    ],
    "inboxId": "550e8400-e29b-41d4-a716-446655440000",
    "excludeContactIds": [
      "550e8400-e29b-41d4-a716-446655440000"
    ],
    "message": "This is a sample message"
  };

axios.post("https://api.maiagent.ai/api/v1/contacts/broadcast-
message/", data, config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```python
import requests

url = "https://api.maiagent.ai/api/v1/contacts/broadcast-message/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# Request Body (payload)
data = {
    "contactIds": [
        "550e8400-e29b-41d4-a716-446655440000"
    ],
    "inboxId": "550e8400-e29b-41d4-a716-446655440000",
    "excludeContactIds": [
        "550e8400-e29b-41d4-a716-446655440000"
    ],
    "message": "This is a sample message"
}

response = requests.post(url, json=data, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>post("https://api.maiagent.ai/api/v1/contacts/broadcast-message/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'contactIds' => [
                '550e8400-e29b-41d4-a716-446655440000'
            ],
            'inboxId' => '550e8400-e29b-41d4-a716-446655440000',
            'excludeContactIds' => [
                '550e8400-e29b-41d4-a716-446655440000'
            ],
            'message' => 'This is a sample message'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response Body

Status Code: 200

Example Response Schema

```
{
  "results"?: [ // Optional
    {
      "contactId"?: string (uuid) // Optional
      "conversationId"?: string (uuid) // Optional
      "messageId"?: string (uuid) // Optional
      "status"?: string // Optional
    }
  ]
  "errors"?: [ // Optional
    {
      "contactId"?: string (uuid) // Optional
      "error"?: string // Optional
    }
  ]
  "totalContacts"?: integer // Optional
  "successCount"?: integer // Optional
  "errorCount"?: integer // Optional
}
```

Example Response Values


```
{
  "results": [
    {
      "contactId": "550e8400-e29b-41d4-a716-446655440000",
      "conversationId": "550e8400-e29b-41d4-a716-446655440000",
      "messageId": "550e8400-e29b-41d4-a716-446655440000",
      "status": "success"
    }
  ],
  "errors": [
    {
      "contactId": "550e8400-e29b-41d4-a716-446655440000",
      "error": "Response string"
    }
  ],
  "totalContacts": 456,
  "successCount": 456,
```

```
  "errorCount": 456
}
```

Status Code: 4XX - Error response; X-Error-Code carries its code (see "Error codes").

Create API Credentials for a Contact

POST `/api/v1/contacts/{id}/api-credentials/`

Allow the Agent to call your API tools on behalf of this contact. For the workflow, see the technical manual: Contact Credential Synchronization ◦

Parameters

Parameter Name	Required	Type	Description
`id`	V	string	A UUID string identifying this Contact.

Request Body

Request Parameters

Field	Type	Required	Description
tool	string (uuid)	Yes	API tool ID
headers	object	No	Dictionary of authentication headers

Example Request Schema

```
{
  "tool": string (uuid) // API tool ID
```

```
  "headers"?: object // Dictionary of authentication headers (Optional)
}
```

Example Request Values

```
{
  "tool": "550e8400-e29b-41d4-a716-446655440000",
  "headers": {}
}
```

Code Examples

Shell/Bash

```
# API call example (Shell)
curl -X POST "https://api.maiagent.ai/api/v1/contacts/550e8400-e29b-
41d4-a716-446655440000/api-credentials/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "tool": "550e8400-e29b-41d4-a716-446655440000",
    "headers": {}
  }'

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// Request Body (payload)
const data = {
    "tool": "550e8400-e29b-41d4-a716-446655440000",
    "headers": {}
  };

axios.post("https://api.maiagent.ai/api/v1/contacts/550e8400-e29b-41d4-
a716-446655440000/api-credentials/", data, config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/contacts/550e8400-e29b-41d4-a716-446655440000/api-credentials/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# Request Body (payload)
data = {
    "tool": "550e8400-e29b-41d4-a716-446655440000",
    "headers": {}
}

response = requests.post(url, json=data, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>post("https://api.maiagent.ai/api/v1/contacts/550e8400-e29b-41d4-a716-
446655440000/api-credentials/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'tool' => '550e8400-e29b-41d4-a716-446655440000',
            'headers' => new \stdClass()
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response Body

Status Code: 201

Example Response Schema

```
{
  "id": string (uuid)
  "inboxes"?: [ // Optional
    {
      "id": string (uuid)
      "name": string
    }
  ]
  "inbox"?:  // Backward-compatible field: a single inbox; ignored when
inboxes is also provided (Optional)
  {
    "id": string (uuid)
    "name": string
  }
  "name": string
  "avatar"?: // May have different types (Optional)
  string (uri) // Contact avatar URL; supports absolute URLs or relative
paths (Optional)
  "phoneNumber"?: string // Optional
  "email"?: // May have different types (Optional)
  string (email) // Optional
  "sourceId"?: string // Optional
  "externalId"?: string // External user ID: the user ID in the calling
system, unique within the organization (excluding deleted contacts). Matching
uses the exact original string and is case-sensitive; the conversation API
uses message.externalUser.id to find the contact by this value. Empty or
whitespace-only strings return 400; pass null to clear it. For multiple
external systems, use a system prefix, such as projects:usr_123 (Optional)
  "queryMetadata"?: { // Query metadata that controls the scope of queryable
knowledge; see each endpoint description for details (Optional)
  {
    "knowledgeBases"?: [ // List of queryable knowledge bases; an empty array
or null denies all access (no permission); omitting this field imposes no
restriction (Optional)
      {
        "knowledgeBaseId": string (uuid) // Knowledge base ID
        "chatbotFileIds"?: [ // List of file IDs (excluded or exclusively
selected depending on hasUserSelectedAll) (Optional)
          string (uuid)
        ]
        "knowledgeBaseFileIds"?: [ // List of file IDs (the new name for
chatbotFileIds; this field takes precedence if both are provided) (Optional)
          string (uuid)
        ]
        "faqIds"?: [ // List of FAQ IDs (excluded or exclusively selected
depending on hasUserSelectedAll) (Optional)
```

```
          string (uuid)
        ]
        "hasUserSelectedAll"?: boolean // true selects all knowledge base
content except the listed items; false selects only the listed items
(Optional)
      }
    ]
    "labelRelations"?: { // Label filter criteria; an empty conditions array
means no label filtering (not a lack of access). Must be provided together
with knowledgeBases; when provided alone, label filtering is not applied to
knowledge base retrieval (equivalent to no restriction) (Optional)
    {
      "operator": string (enum: AND, OR) // How label conditions are combined
      "conditions"?: [ // List of label conditions; supports nested
operator/conditions combinations (Optional)
        object
      ]
    }
    }
  }
  }
  "metadata"?: object // Custom customer information shown in the customer
panel of the conversation page (Optional)
  "mcpCredentials": [ // List of MCP authentication credentials for the
contact
    object
  ]
  "apiCredentials": [ // List of API authentication credentials for the
contact
    object
  ]
  "contactConnectors": [ // List of Connector OAuth authorizations for the
contact (excluding the tokens themselves)
    object
  ]
  "tags": [
    {
      "id": string (uuid)
      "name": string
      "createdAt": string (timestamp)
      "updatedAt": string (timestamp)
    }
  ]
  "preChatFieldIndex": object // Pre-chat form field settings from the
inboxes this Contact belongs to, mapped as {field_id: {label: {locale:
text}}}; the frontend uses this to resolve UUID keys in metadata to display
names
```

```
  "createdAt": string (timestamp)
  "updatedAt": string (timestamp)
}
```

Example Response Values

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "inboxes": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "Response string"
    }
  ],
  "inbox": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Response string"
  },
  "name": "Response string",
  "avatar": "https://example.com/file.jpg",
  "phoneNumber": "Response string",
  "email": "response@example.com",
  "sourceId": "Response string",
  "externalId": "Response string",
  "queryMetadata": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Example response name",
    "description": "Example response description"
  },
  "metadata": null,
  "mcpCredentials": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "Example response name",
      "description": "Example response description"
    }
  ],
  "apiCredentials": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "Example response name",
      "description": "Example response description"
    }
  ],
  "contactConnectors": [
```

```
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "Example response name",
      "description": "Example response description"
    }
  ],
  "tags": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "Response string",
      "createdAt": "Response string",
      "updatedAt": "Response string"
    }
  ],
  "preChatFieldIndex": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Example response name",
    "description": "Example response description"
  },
  "createdAt": "Response string",
  "updatedAt": "Response string"
}
```


Status Code: 400 - No response body

Update API Credentials for a Contact

PATCH `/api/v1/contacts/{id}/api-credentials/{credentialId}`

Parameters

Parameter Name	Required	Type	Description
`credentialId`	V	string	
`id`	V	string	A UUID string identifying this Contact.

Request Body

Request Parameters

Field	Type	Required	Description
headers	object	No	Dictionary of authentication headers

Example Request Schema

```
{
  "headers"?: object // Dictionary of authentication headers (Optional)
}
```

Example Request Values

```
{
  "headers": {}
}
```

Code Examples

Shell/Bash

```
# API call example (Shell)
curl -X PATCH "https://api.maiagent.ai/api/v1/contacts/550e8400-e29b-
41d4-a716-446655440000/api-credentials/{credentialId}
"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "headers": {}
  }'

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// Request Body (payload)
const data = {
    "headers": {}
  };

axios.patch("https://api.maiagent.ai/api/v1/contacts/550e8400-e29b-
41d4-a716-446655440000/api-credentials/{credentialId}
", data, config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/contacts/550e8400-e29b-41d4-a716-
446655440000/api-credentials/{credentialId}
"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# Request Body (payload)
data = {
    "headers": {}
}

response = requests.patch(url, json=data, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>patch("https://api.maiagent.ai/api/v1/contacts/550e8400-e29b-41d4-
a716-446655440000/api-credentials/{credentialId}
", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'headers' => new \stdClass()
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response

Status code: 200

Example response schema

```
{
  "id": string (uuid)
  "inboxes"?: [ // Optional
    {
      "id": string (uuid)
      "name": string
    }
  ]
  "inbox"?:  // Backward-compatible field: a single inbox; ignored if inboxes
is also provided (Optional)
  {
    "id": string (uuid)
    "name": string
  }
  "name": string
  "avatar"?: // May have different types (Optional)
  string (uri) // Contact avatar URL; supports absolute URLs or relative
paths (Optional)
  "phoneNumber"?: string // Optional
  "email"?: // May have different types (Optional)
  string (email) // Optional
  "sourceId"?: string // Optional
  "externalId"?: string // External user ID: the user ID in the calling
system, unique within the organization (excluding deleted contacts). Matching
uses the exact string and is case-sensitive; the conversation API uses
message.externalUser.id to find the contact by this ID. Empty or whitespace-
only strings return 400; pass null to clear it. When using multiple external
systems, a system prefix is recommended, such as projects:usr_123 (Optional)
  "queryMetadata"?: { // Query metadata that controls the scope of accessible
knowledge; see each endpoint for details (Optional)
  {
    "knowledgeBases"?: [ // List of accessible knowledge bases; an empty
array or null means none are accessible (no permission); omission means no
restriction (Optional)
      {
        "knowledgeBaseId": string (uuid) // Knowledge base ID
        "chatbotFileIds"?: [ // List of file IDs (excluded or exclusively
selected depending on hasUserSelectedAll) (Optional)
          string (uuid)
        ]
        "knowledgeBaseFileIds"?: [ // List of file IDs (the new name for
chatbotFileIds; this field takes precedence when both are provided)
(Optional)
          string (uuid)
        ]
        "faqIds"?: [ // List of FAQ IDs (excluded or exclusively selected
```

```
depending on hasUserSelectedAll) (Optional)
          string (uuid)
        ]
        "hasUserSelectedAll"?: boolean // true = select all knowledge base
content except the listed items; false = select only the listed items
(Optional)
      }
    ]
    "labelRelations"?: { // Tag filter criteria; an empty conditions array
means no tag filtering (not a lack of permission). Must be provided together
with knowledgeBases; when provided alone, tag filtering is not applied to
knowledge base retrieval (equivalent to no restriction) (Optional)
    {
      "operator": string (enum: AND, OR) // How tag conditions are combined
      "conditions"?: [ // List of tag conditions; supports nested
operator/conditions combinations (Optional)
        object
      ]
    }
    }
  }
  }
  "metadata"?: object // Custom customer information shown in the customer
panel of the conversation page (Optional)
  "mcpCredentials": [ // List of MCP credentials for the contact
    object
  ]
  "apiCredentials": [ // List of API credentials for the contact
    object
  ]
  "contactConnectors": [ // List of Connector OAuth authorizations for the
contact (excluding the tokens themselves)
    object
  ]
  "tags": [
    {
      "id": string (uuid)
      "name": string
      "createdAt": string (timestamp)
      "updatedAt": string (timestamp)
    }
  ]
  "preChatFieldIndex": object // Pre-chat form field configuration from the
inboxes this Contact belongs to, with mapping {field_id: {label: {locale:
text}}}; the frontend uses it to resolve UUID keys in metadata to display
names
  "createdAt": string (timestamp)
```

```
  "updatedAt": string (timestamp)
}
```

Example response values

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "inboxes": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "Response string"
    }
  ],
  "inbox": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Response string"
  },
  "name": "Response string",
  "avatar": "https://example.com/file.jpg",
  "phoneNumber": "Response string",
  "email": "response@example.com",
  "sourceId": "Response string",
  "externalId": "Response string",
  "queryMetadata": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Example response name",
    "description": "Example response description"
  },
  "metadata": null,
  "mcpCredentials": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "Example response name",
      "description": "Example response description"
    }
  ],
  "apiCredentials": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "Example response name",
      "description": "Example response description"
    }
  ],
  "contactConnectors": [
    {
```

```
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "Example response name",
      "description": "Example response description"
    }
  ],
  "tags": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "Response string",
      "createdAt": "Response string",
      "updatedAt": "Response string"
    }
  ],
  "preChatFieldIndex": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Example response name",
    "description": "Example response description"
  },
  "createdAt": "Response string",
  "updatedAt": "Response string"
}
```


Status code: 404 - No response body

Delete Contact's API Credentials

`DELETE` `/api/v1/contacts/{id}/api-credentials/{credentialId}`

Parameters

Parameter Name	Required	Type	Description
`credentialId`	V	string	
`id`	V	string	A UUID string identifying this Contact.

Code Examples

Shell/Bash

```
# API call example (Shell)
curl -X DELETE "https://api.maiagent.ai/api/v1/contacts/550e8400-e29b-
41d4-a716-446655440000/api-credentials/{credentialId}
"

  -H "Authorization: Api-Key YOUR_API_KEY"

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

// Request body (payload)
const data = null;

axios.delete("https://api.maiagent.ai/api/v1/contacts/550e8400-e29b-
41d4-a716-446655440000/api-credentials/{credentialId}
", data, config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/contacts/550e8400-e29b-41d4-a716-
446655440000/api-credentials/{credentialId}
"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.delete(url, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>delete("https://api.maiagent.ai/api/v1/contacts/550e8400-e29b-41d4-
a716-446655440000/api-credentials/{credentialId}
", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response

Status Code	Description
204	No response body
404	No response body

Create MCP credentials for a contact

`POST` `/api/v1/contacts/{id}/mcp-credentials/`

Parameters

Parameter name	Required	Type	Description
`id`	V	string	A UUID string identifying this Contact.

Request body

Request parameters

Field	Type	Required	Description
tool	string (uuid)	Yes	MCP tool ID
headers	object	No	Dictionary of authentication headers

Example request schema

```
{
  "tool": string (uuid) // MCP tool ID
  "headers"?: object // Dictionary of authentication headers (Optional)
}
```

Example request values

```
{
  "tool": "550e8400-e29b-41d4-a716-446655440000",
```

```
  "headers": {}
}
```

Code examples

Shell/Bash

```
# API call example (Shell)
curl -X POST "https://api.maiagent.ai/api/v1/contacts/550e8400-e29b-
41d4-a716-446655440000/mcp-credentials/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "tool": "550e8400-e29b-41d4-a716-446655440000",
    "headers": {}
  }'

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// Request body (payload)
const data = {
    "tool": "550e8400-e29b-41d4-a716-446655440000",
    "headers": {}
  };

axios.post("https://api.maiagent.ai/api/v1/contacts/550e8400-e29b-41d4-
a716-446655440000/mcp-credentials/", data, config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/contacts/550e8400-e29b-41d4-a716-446655440000/mcp-credentials/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# Request body (payload)
data = {
    "tool": "550e8400-e29b-41d4-a716-446655440000",
    "headers": {}
}

response = requests.post(url, json=data, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>post("https://api.maiagent.ai/api/v1/contacts/550e8400-e29b-41d4-a716-
446655440000/mcp-credentials/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'tool' => '550e8400-e29b-41d4-a716-446655440000',
            'headers' => new \stdClass()
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response body

Status code: 201

Example response schema

```
{
  "id": string (uuid)
  "inboxes"?: [ // Optional
    {
      "id": string (uuid)
      "name": string
    }
  ]
  "inbox"?:  // Backward-compatible field: a single inbox; ignored if inboxes
is also provided (Optional)
  {
    "id": string (uuid)
    "name": string
  }
  "name": string
  "avatar"?: // May have different types (Optional)
  string (uri) // Contact avatar URL; supports absolute URLs or relative
paths (Optional)
  "phoneNumber"?: string // Optional
  "email"?: // May have different types (Optional)
  string (email) // Optional
  "sourceId"?: string // Optional
  "externalId"?: string // External user ID: the user ID in the calling
system, unique within the organization (excluding deleted contacts). Matched
exactly and case-sensitively against the original string; the conversation
API uses message.externalUser.id to find the contact by this ID. Empty or
whitespace-only strings return 400; pass null to clear it. When using
multiple external systems, a system prefix is recommended, such as
projects:usr_123 (Optional)
  "queryMetadata"?: { // Query metadata that controls the scope of searchable
knowledge; see each endpoint for details (Optional)
  {
    "knowledgeBases"?: [ // List of searchable knowledge bases; an empty
array or null means none can be searched (no permission); omitting this field
imposes no restriction (Optional)
      {
        "knowledgeBaseId": string (uuid) // Knowledge base ID
        "chatbotFileIds"?: [ // List of file IDs (excluded or exclusively
selected depending on hasUserSelectedAll) (Optional)
          string (uuid)
        ]
        "knowledgeBaseFileIds"?: [ // List of file IDs (the new name for
chatbotFileIds; this field takes precedence if both are provided) (Optional)
          string (uuid)
        ]
        "faqIds"?: [ // List of FAQ IDs (excluded or exclusively selected
```

```
depending on hasUserSelectedAll) (Optional)
          string (uuid)
        ]
        "hasUserSelectedAll"?: boolean // true selects all content in the
knowledge base except the listed items; false selects only the listed items
(Optional)
      }
    ]
    "labelRelations"?: { // Tag filter criteria; an empty conditions array
means no tag filtering (it does not mean no permission). Must be provided
together with knowledgeBases; when provided alone, tag filtering is not
applied to knowledge base retrieval (equivalent to no restriction) (Optional)
    {
      "operator": string (enum: AND, OR) // How tag conditions are combined
      "conditions"?: [ // List of tag conditions; supports nested
operator/conditions combinations (Optional)
        object
      ]
    }
    }
  }
  }
  "metadata"?: object // Custom customer information shown in the customer
panel of the conversation page (Optional)
  "mcpCredentials": [ // List of MCP authentication credentials for the
contact
    object
  ]
  "apiCredentials": [ // List of API authentication credentials for the
contact
    object
  ]
  "contactConnectors": [ // List of Connector OAuth authorizations for the
contact (excluding token values)
    object
  ]
  "tags": [
    {
      "id": string (uuid)
      "name": string
      "createdAt": string (timestamp)
      "updatedAt": string (timestamp)
    }
  ]
  "preChatFieldIndex": object // Pre-chat form field settings from the
inboxes this Contact belongs to, mapped as {field_id: {label: {locale:
text}}}; the frontend uses these settings to resolve UUID keys in metadata to
```

```
display names
  "createdAt": string (timestamp)
  "updatedAt": string (timestamp)
}
```

Example response values


```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "inboxes": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "Response string"
    }
  ],
  "inbox": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Response string"
  },
  "name": "Response string",
  "avatar": "https://example.com/file.jpg",
  "phoneNumber": "Response string",
  "email": "response@example.com",
  "sourceId": "Response string",
  "externalId": "Response string",
  "queryMetadata": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Example response name",
    "description": "Example response description"
  },
  "metadata": null,
  "mcpCredentials": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "Example response name",
      "description": "Example response description"
    }
  ],
  "apiCredentials": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "Example response name",
      "description": "Example response description"
    }
  ],
```

```
  "contactConnectors": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "Example response name",
      "description": "Example response description"
    }
  ],
  "tags": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "Response string",
      "createdAt": "Response string",
      "updatedAt": "Response string"
    }
  ],
  "preChatFieldIndex": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Example response name",
    "description": "Example response description"
  },
  "createdAt": "Response string",
  "updatedAt": "Response string"
}
```


Status code: 400 - No response body

Update MCP credentials for a contact

PATCH `/api/v1/contacts/{id}/mcp-credentials/{credentialId}`

Parameters

Parameter name	Required	Type	Description
credentialId	V	string	

`id`	V	string	A UUID string identifying this Contact.

Request body

Request parameters

Field	Type	Required	Description
headers	object	No	Dictionary of authentication headers

Example request schema

```
{
  "headers"?: object // Dictionary of authentication headers (Optional)
}
```

Example request values

```
{
  "headers": {}
}
```

Code examples

Shell/Bash

```
# API call example (Shell)
curl -X PATCH "https://api.maiagent.ai/api/v1/contacts/550e8400-e29b-
41d4-a716-446655440000/mcp-credentials/{credentialId}
"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "headers": {}
  }'

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// Request body (payload)
const data = {
    "headers": {}
  };

axios.patch("https://api.maiagent.ai/api/v1/contacts/550e8400-e29b-
41d4-a716-446655440000/mcp-credentials/{credentialId}
", data, config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/contacts/550e8400-e29b-41d4-a716-
446655440000/mcp-credentials/{credentialId}
"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# Request body (payload)
data = {
    "headers": {}
}

response = requests.patch(url, json=data, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>patch("https://api.maiagent.ai/api/v1/contacts/550e8400-e29b-41d4-
a716-446655440000/mcp-credentials/{credentialId}
", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'headers' => new \stdClass()
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response body

Status code: 200

Example response schema

```
{
  "id": string (uuid)
  "inboxes"?: [ // Optional
    {
      "id": string (uuid)
      "name": string
    }
  ]
  "inbox"?:  // Backward-compatible field: a single inbox; ignored if inboxes
is also provided (Optional)
  {
    "id": string (uuid)
    "name": string
  }
  "name": string
  "avatar"?: // May have different types (Optional)
  string (uri) // Contact avatar URL; supports absolute URLs or relative
paths (Optional)
  "phoneNumber"?: string // Optional
  "email"?: // May have different types (Optional)
  string (email) // Optional
  "sourceId"?: string // Optional
  "externalId"?: string // External user ID: the user ID in the calling
system, unique within the organization (excluding deleted contacts). Matched
exactly and case-sensitively against the original string; the conversation
API uses message.externalUser.id to find the contact by this ID. Empty or
whitespace-only strings return 400; pass null to clear it. When using
multiple external systems, a system prefix is recommended, such as
projects:usr_123 (Optional)
  "queryMetadata"?: { // Query metadata that controls the scope of searchable
knowledge; see each endpoint for details (Optional)
  {
    "knowledgeBases"?: [ // List of searchable knowledge bases; an empty
array or null means none can be searched (no permission); omitting this field
imposes no restriction (Optional)
      {
        "knowledgeBaseId": string (uuid) // Knowledge base ID
        "chatbotFileIds"?: [ // List of file IDs (excluded or exclusively
selected depending on hasUserSelectedAll) (Optional)
          string (uuid)
        ]
        "knowledgeBaseFileIds"?: [ // List of file IDs (the new name for
chatbotFileIds; this field takes precedence if both are provided) (Optional)
          string (uuid)
        ]
        "faqIds"?: [ // List of FAQ IDs (excluded or exclusively selected
```

```
depending on hasUserSelectedAll) (Optional)
          string (uuid)
        ]
        "hasUserSelectedAll"?: boolean // true selects all content in the
knowledge base except the listed items; false selects only the listed items
(Optional)
      }
    ]
    "labelRelations"?: { // Tag filter criteria; an empty conditions array
means no tag filtering (it does not mean no permission). Must be provided
together with knowledgeBases; when provided alone, tag filtering is not
applied to knowledge base retrieval (equivalent to no restriction) (Optional)
    {
      "operator": string (enum: AND, OR) // How tag conditions are combined
      "conditions"?: [ // List of tag conditions; supports nested
operator/conditions combinations (Optional)
        object
      ]
    }
    }
  }
  }
  "metadata"?: object // Custom customer information shown in the customer
panel of the conversation page (Optional)
  "mcpCredentials": [ // List of MCP authentication credentials for the
contact
    object
  ]
  "apiCredentials": [ // List of API authentication credentials for the
contact
    object
  ]
  "contactConnectors": [ // List of Connector OAuth authorizations for the
contact (excluding token values)
    object
  ]
  "tags": [
    {
      "id": string (uuid)
      "name": string
      "createdAt": string (timestamp)
      "updatedAt": string (timestamp)
    }
  ]
  "preChatFieldIndex": object // Pre-chat form field settings from the
inboxes this Contact belongs to, mapped as {field_id: {label: {locale:
text}}}; the frontend uses these settings to resolve UUID keys in metadata to
```

```
display names
  "createdAt": string (timestamp)
  "updatedAt": string (timestamp)
}
```

Example response values


```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "inboxes": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "Response string"
    }
  ],
  "inbox": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Response string"
  },
  "name": "Response string",
  "avatar": "https://example.com/file.jpg",
  "phoneNumber": "Response string",
  "email": "response@example.com",
  "sourceId": "Response string",
  "externalId": "Response string",
  "queryMetadata": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Example response name",
    "description": "Example response description"
  },
  "metadata": null,
  "mcpCredentials": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "Example response name",
      "description": "Example response description"
    }
  ],
  "apiCredentials": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "Example response name",
      "description": "Example response description"
    }
  ],
```

```
  "contactConnectors": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "Example response name",
      "description": "Example response description"
    }
  ],
  "tags": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "Response string",
      "createdAt": "Response string",
      "updatedAt": "Response string"
    }
  ],
  "preChatFieldIndex": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Example response name",
    "description": "Example response description"
  },
  "createdAt": "Response string",
  "updatedAt": "Response string"
}
```


Status code: 404 - No response body

Delete Contact's MCP Credentials

`DELETE` `/api/v1/contacts/{id}/mcp-credentials/{credentialId}`

Parameters

Parameter Name	Required	Type	Description
credentialId	V	string	

`id`	V	string	A UUID string identifying this Contact.

Code Examples

Shell/Bash

```
# API call example (Shell)
curl -X DELETE "https://api.maiagent.ai/api/v1/contacts/550e8400-e29b-
41d4-a716-446655440000/mcp-credentials/{credentialId}
"

  -H "Authorization: Api-Key YOUR_API_KEY"

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

// Request body (payload)
const data = null;

axios.delete("https://api.maiagent.ai/api/v1/contacts/550e8400-e29b-
41d4-a716-446655440000/mcp-credentials/{credentialId}
", data, config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/contacts/550e8400-e29b-41d4-a716-
446655440000/mcp-credentials/{credentialId}
"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.delete(url, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>delete("https://api.maiagent.ai/api/v1/contacts/550e8400-e29b-41d4-
a716-446655440000/mcp-credentials/{credentialId}
", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response

Status Code	Description
204	No response body
404	No response body

Download the Contact Bulk Import Template

GET `/api/v1/contacts/bulk-import-template/`

Code Examples

Shell/Bash

```
# API Call Example (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/contacts/bulk-import-
template/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/contacts/bulk-import-
template/", config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/contacts/bulk-import-template/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/contacts/bulk-import-template/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response Body

Status Code: 200

Example Response Schema

```
{
  "id": string (uuid)
  "inboxes"?: [ // Optional
    {
      "id": string (uuid)
      "name": string
```

```
    }
  ]
  "inbox"?:  // Backward-compatible field: a single inbox; ignored if inboxes
is also provided (Optional)
  {
    "id": string (uuid)
    "name": string
  }
  "name": string
  "avatar"?: // May have different types (Optional)
  string (uri) // Contact avatar URL; supports an absolute URL or a relative
path (Optional)
  "phoneNumber"?: string // Optional
  "email"?: // May have different types (Optional)
  string (email) // Optional
  "sourceId"?: string // Optional
  "externalId"?: string // External user ID: the user ID in the calling
system, unique within the organization (excluding deleted contacts). Matching
uses the exact, case-sensitive string; the conversation API uses
message.externalUser.id to find the contact by this ID. An empty or
whitespace-only string returns 400; pass null to clear the value. For
multiple external systems, use a system prefix, such as projects:usr_123
(Optional)
  "queryMetadata"?: { // Query metadata that controls which knowledge can be
queried; see each endpoint description (Optional)
  {
    "knowledgeBases"?: [ // List of queryable knowledge bases; an empty array
or null means none can be queried (no access), while omitting the field
imposes no restriction (Optional)
      {
        "knowledgeBaseId": string (uuid) // Knowledge base ID
        "chatbotFileIds"?: [ // List of file IDs (excluded or exclusively
selected depending on hasUserSelectedAll) (Optional)
          string (uuid)
        ]
        "knowledgeBaseFileIds"?: [ // List of file IDs (the new name for
chatbotFileIds; this field takes precedence if both are provided) (Optional)
          string (uuid)
        ]
        "faqIds"?: [ // List of FAQ IDs (excluded or exclusively selected
depending on hasUserSelectedAll) (Optional)
          string (uuid)
        ]
        "hasUserSelectedAll"?: boolean // true selects all knowledge base
content except the listed items; false selects only the listed items
(Optional)
      }
```

```
    ]
    "labelRelations"?: { // Tag filter criteria; an empty conditions array
means no tag filtering (not no access). Must be provided together with
knowledgeBases; when provided alone, tag filtering is not applied to
knowledge base retrieval (no restriction) (Optional)
    {
      "operator": string (enum: AND, OR) // How tag conditions are combined
      "conditions"?: [ // List of tag conditions; supports nested
operator/conditions combinations (Optional)
        object
      ]
    }
    }
  }
  }
  "metadata"?: object // Custom customer information shown in the customer
panel of the conversation page (Optional)
  "mcpCredentials": [ // List of MCP authentication credentials for the
contact
    object
  ]
  "apiCredentials": [ // List of API authentication credentials for the
contact
    object
  ]
  "contactConnectors": [ // List of Connector OAuth authorizations for the
contact (excluding the tokens themselves)
    object
  ]
  "tags": [
    {
      "id": string (uuid)
      "name": string
      "createdAt": string (timestamp)
      "updatedAt": string (timestamp)
    }
  ]
  "preChatFieldIndex": object // Pre-chat form field settings from the
inboxes this Contact belongs to, mapped as {field_id: {label: {locale:
text}}}; the frontend uses these settings to resolve UUID keys in metadata to
display names
  "createdAt": string (timestamp)
  "updatedAt": string (timestamp)
}
```

Example Response Values

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "inboxes": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "Response string"
    }
  ],
  "inbox": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Response string"
  },
  "name": "Response string",
  "avatar": "https://example.com/file.jpg",
  "phoneNumber": "Response string",
  "email": "response@example.com",
  "sourceId": "Response string",
  "externalId": "Response string",
  "queryMetadata": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Example response name",
    "description": "Example response description"
  },
  "metadata": null,
  "mcpCredentials": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "Example response name",
      "description": "Example response description"
    }
  ],
  "apiCredentials": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "Example response name",
      "description": "Example response description"
    }
  ],
  "contactConnectors": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "Example response name",
      "description": "Example response description"
    }
  ],
  "tags": [
```

```
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "Response string",
      "createdAt": "Response string",
      "updatedAt": "Response string"
    }
  ],
  "preChatFieldIndex": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Example response name",
    "description": "Example response description"
  },
  "createdAt": "Response string",
  "updatedAt": "Response string"
}
```


Status Code: 4XX - Error response; X-Error-Code carries its code (see "Error codes").

Bulk Import Contacts

POST `/api/v1/contacts/bulk-import/`

Upload an Excel file filled out using the template; pass dry_run=true to report only the number of records that would be created or updated without writing any data (returns 200 rather than 201).

Code Examples

Shell/Bash

```
# API Call Example (Shell)
curl -X POST "https://api.maiagent.ai/api/v1/contacts/bulk-import/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');
const FormData = require('form-data');

// Create a FormData object
const formData = new FormData();
// Add form fields

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    ...formData.getHeaders()
  }
};

axios.post("https://api.maiagent.ai/api/v1/contacts/bulk-import/",
formData, config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/contacts/bulk-import/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}

# Create file and form data
files = {
    'file': ('example.pdf', open('example.pdf', 'rb'),
'application/pdf')
}

response = requests.post(url, files=files, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>post("https://api.maiagent.ai/api/v1/contacts/bulk-import/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ],
        'multipart' => [
            [
                'name' => 'file',
                'contents' => fopen('example.pdf', 'r'),
                'filename' => 'example.pdf'
            ]
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response Body

Status Code: 200

Example Response Schema

```
{
  "id": string (uuid)
  "inboxes"?: [ // Optional
    {
      "id": string (uuid)
      "name": string
    }
  ]
  "inbox"?:  // Backward-compatible field: a single inbox; ignored if inboxes
is also provided (Optional)
  {
    "id": string (uuid)
    "name": string
  }
  "name": string
  "avatar"?: // May have different types (Optional)
  string (uri) // Contact avatar URL; supports an absolute URL or a relative
path (Optional)
  "phoneNumber"?: string // Optional
  "email"?: // May have different types (Optional)
  string (email) // Optional
  "sourceId"?: string // Optional
  "externalId"?: string // External user ID: the user ID in the calling
system, unique within the organization (excluding deleted contacts). Matching
uses the exact, case-sensitive string; the conversation API uses
message.externalUser.id to find the contact by this ID. An empty or
whitespace-only string returns 400; pass null to clear the value. For
multiple external systems, use a system prefix, such as projects:usr_123
(Optional)
  "queryMetadata"?: { // Query metadata that controls which knowledge can be
queried; see each endpoint description (Optional)
  {
    "knowledgeBases"?: [ // List of queryable knowledge bases; an empty array
or null means none can be queried (no access), while omitting the field
imposes no restriction (Optional)
      {
        "knowledgeBaseId": string (uuid) // Knowledge base ID
        "chatbotFileIds"?: [ // List of file IDs (excluded or exclusively
selected depending on hasUserSelectedAll) (Optional)
          string (uuid)
        ]
        "knowledgeBaseFileIds"?: [ // List of file IDs (the new name for
chatbotFileIds; this field takes precedence if both are provided) (Optional)
          string (uuid)
        ]
        "faqIds"?: [ // List of FAQ IDs (excluded or exclusively selected
```

```
depending on hasUserSelectedAll) (Optional)
          string (uuid)
        ]
        "hasUserSelectedAll"?: boolean // true selects all knowledge base
content except the listed items; false selects only the listed items
(Optional)
      }
    ]
    "labelRelations"?: { // Tag filter criteria; an empty conditions array
means no tag filtering (not no access). Must be provided together with
knowledgeBases; when provided alone, tag filtering is not applied to
knowledge base retrieval (no restriction) (Optional)
    {
      "operator": string (enum: AND, OR) // How tag conditions are combined
      "conditions"?: [ // List of tag conditions; supports nested
operator/conditions combinations (Optional)
        object
      ]
    }
    }
  }
  }
  "metadata"?: object // Custom customer information shown in the customer
panel of the conversation page (Optional)
  "mcpCredentials": [ // List of MCP authentication credentials for the
contact
    object
  ]
  "apiCredentials": [ // List of API authentication credentials for the
contact
    object
  ]
  "contactConnectors": [ // List of Connector OAuth authorizations for the
contact (excluding the tokens themselves)
    object
  ]
  "tags": [
    {
      "id": string (uuid)
      "name": string
      "createdAt": string (timestamp)
      "updatedAt": string (timestamp)
    }
  ]
  "preChatFieldIndex": object // Pre-chat form field settings from the
inboxes this Contact belongs to, mapped as {field_id: {label: {locale:
text}}}; the frontend uses these settings to resolve UUID keys in metadata to
```

```
display names
  "createdAt": string (timestamp)
  "updatedAt": string (timestamp)
}
```

Example Response Values

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "inboxes": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "Response string"
    }
  ],
  "inbox": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Response string"
  },
  "name": "Response string",
  "avatar": "https://example.com/file.jpg",
  "phoneNumber": "Response string",
  "email": "response@example.com",
  "sourceId": "Response string",
  "externalId": "Response string",
  "queryMetadata": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Example response name",
    "description": "Example response description"
  },
  "metadata": null,
  "mcpCredentials": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "Example response name",
      "description": "Example response description"
    }
  ],
  "apiCredentials": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "Example response name",
      "description": "Example response description"
    }
  ],
```

```
  "contactConnectors": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "Example response name",
      "description": "Example response description"
    }
  ],
  "tags": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "Response string",
      "createdAt": "Response string",
      "updatedAt": "Response string"
    }
  ],
  "preChatFieldIndex": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Example response name",
    "description": "Example response description"
  },
  "createdAt": "Response string",
  "updatedAt": "Response string"
}
```


Status Code: 4XX - Error response; X-Error-Code carries its code (see "Error codes").

API call example (Shell)

目錄

1. Create a Role
2. Bulk Add Role Members
3. Bulk assign AI assistants to a role
4. Bulk Assign Inboxes to Role
5. Bulk Assign Knowledge Bases to a Role
6. Bulk Assign Databases to a Role
7. List Permissions
8. List Roles
9. Get Role Details
10. List Role Members
11. Retrieve a Role Member
12. List AI Assistants for a Role
13. List Role Inboxes
14. List Role Knowledge Bases
15. List Role Databases
16. Update a Role
17. Partially Update a Role
18. Delete Role
19. Remove Role Member
20. Remove AI Assistant from Role
21. Remove Inbox from Role
22. Remove Knowledge Base from Role
23. Remove Database from Role

API call example (Shell)

Create a Role

`POST` `/api/v1/organizations/{organizationPk}/groups/`

Parameters

Parameter Name	Required	Type	Description
`organizationPk`	V	string	A UUID string identifying this Organization ID

Request Body

Request Parameters

Field	Type	Required	Description
name	string	Yes	
organization	string (uuid)	No	
permissions	array[string]	Yes	
canCreateChatbot	boolean	No	
canCreateKnowledgeBase	boolean	No	
canCreateInbox	boolean	No	
canCreateDatabase	boolean	No	
canCreateTool	boolean	No	
canCreateAgentUiTool	boolean	No	
canCreateSkill	boolean	No	
maigptCanCodeInterpreter	boolean	No	Whether members of this role may use the code interpreter built-in tool in MaiGPT.
maigptCanRag	boolean	No	Whether members of this role may use the knowledge base RAG built-in tool in MaiGPT.

Field	Type	Required	Description
maigptCanDeepResearch	boolean	No	Whether members of this role may use Deep Research in MaiGPT. Deep Research reaches the public internet through its own built-in search, so a role that revokes the official web-search tools needs this...
maigptCanBrowserTool	boolean	No	Whether members of this role may use the browser built-in tool in MaiGPT.
maigptAllLlms	boolean	No	Whether members of this role may use every organization-available LLM in MaiGPT. Off = only the bound LLMs; an empty binding then means none.
maigptAllTools	boolean	No	Whether members of this role may call every official (global) tool in MaiGPT. Off = only the bound tools; an empty binding then means none.
maigptAllConnectors	boolean	No	Whether members of this role may call every official (global) MCP connector in MaiGPT. Off = only the bound connectors; an empty binding then means none.
maigptAllSkills	boolean	No	Whether members of this role may use every official (global) skill in MaiGPT. Off = only the bound skills; an empty binding then means none.
usageStatisticsScope	object	No	What this role's usage statistics permission shows: the whole organization, or only the AI assistants granted to the member's roles. A member with any

Field	Type	Required	Description
			organization-wide granting role sees the whole or...
allowedLlms	array[string]	No	
allowedTools	array[string]	No	
allowedConnectors	array[string]	No	
allowedSkills	array[string]	No	

Request Schema Example

```
{
  "name": string
  "organization"?: string (uuid) // Optional
  "permissions": [
    string (uuid)
  ]
  "canCreateChatbot"?: boolean // Optional
  "canCreateKnowledgeBase"?: boolean // Optional
  "canCreateInbox"?: boolean // Optional
  "canCreateDatabase"?: boolean // Optional
  "canCreateTool"?: boolean // Optional
  "canCreateAgentUiTool"?: boolean // Optional
  "canCreateSkill"?: boolean // Optional
  "maigptCanCodeInterpreter"?: boolean // Whether members of this role
may use the code interpreter built-in tool in MaiGPT. (Optional)
  "maigptCanRag"?: boolean // Whether members of this role may use the
knowledge base RAG built-in tool in MaiGPT. (Optional)
  "maigptCanDeepResearch"?: boolean // Whether members of this role may
use Deep Research in MaiGPT. Deep Research reaches the public internet
through its own built-in search, so a role that revokes the official web-
search tools needs this switch too. (Optional)
  "maigptCanBrowserTool"?: boolean // Whether members of this role may
use the browser built-in tool in MaiGPT. (Optional)
  "maigptAllLlms"?: boolean // Whether members of this role may use every
organization-available LLM in MaiGPT. Off = only the bound LLMs; an empty
binding then means none. (Optional)
  "maigptAllTools"?: boolean // Whether members of this role may call
every official (global) tool in MaiGPT. Off = only the bound tools; an
empty binding then means none. (Optional)
  "maigptAllConnectors"?: boolean // Whether members of this role may
```

```
call every official (global) MCP connector in MaiGPT. Off = only the
bound connectors; an empty binding then means none. (Optional)
  "maigptAllSkills"?: boolean // Whether members of this role may use
every official (global) skill in MaiGPT. Off = only the bound skills; an
empty binding then means none. (Optional)
  "usageStatisticsScope"?:  // What this role's usage statistics
permission shows: the whole organization, or only the AI assistants
granted to the member's roles. A member with any organization-wide
granting role sees the whole organization.

* `organization` - Organization-wide
* `accessible_chatbots` - Authorized AI assistants only (Optional)
  {
  }
  "allowedLlms"?: [ // Optional
    string (uuid)
  ]
  "allowedTools"?: [ // Optional
    string (uuid)
  ]
  "allowedConnectors"?: [ // Optional
    string (uuid)
  ]
  "allowedSkills"?: [ // Optional
    string (uuid)
  ]
}
```

Example Request Values

```
{
  "name": "Example name",
  "organization": "550e8400-e29b-41d4-a716-446655440000",
  "permissions": [
    "550e8400-e29b-41d4-a716-446655440000"
  ],
  "canCreateChatbot": true,
  "canCreateKnowledgeBase": true,
  "canCreateInbox": true,
  "canCreateDatabase": true,
  "canCreateTool": true,
  "canCreateAgentUiTool": true,
  "canCreateSkill": true,
  "maigptCanCodeInterpreter": true,
```

```
  "maigptCanRag": true,
  "maigptCanDeepResearch": true,
  "maigptCanBrowserTool": true,
  "maigptAllLlms": true,
  "maigptAllTools": true,
  "maigptAllConnectors": true,
  "maigptAllSkills": true,
  "usageStatisticsScope": {},
  "allowedLlms": [
    "550e8400-e29b-41d4-a716-446655440000"
  ],
  "allowedTools": [
    "550e8400-e29b-41d4-a716-446655440000"
  ],
  "allowedConnectors": [
    "550e8400-e29b-41d4-a716-446655440000"
  ],
  "allowedSkills": [
    "550e8400-e29b-41d4-a716-446655440000"
  ]
}
```


Code Examples

Shell/Bash

```
# API call example (Shell)
curl -X POST "https://api.maiagent.ai/api/v1/organizations/550e8400-
e29b-41d4-a716-446655440000/groups/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "name": "Example name",
    "organization": "550e8400-e29b-41d4-a716-446655440000",
    "permissions": [
      "550e8400-e29b-41d4-a716-446655440000"
    ],
    "canCreateChatbot": true,
    "canCreateKnowledgeBase": true,
    "canCreateInbox": true,
    "canCreateDatabase": true,
    "canCreateTool": true,
    "canCreateAgentUiTool": true,
    "canCreateSkill": true,
    "maigptCanCodeInterpreter": true,
    "maigptCanRag": true,
    "maigptCanDeepResearch": true,
    "maigptCanBrowserTool": true,
    "maigptAllLlms": true,
    "maigptAllTools": true,
    "maigptAllConnectors": true,
    "maigptAllSkills": true,
    "usageStatisticsScope": {},
    "allowedLlms": [
      "550e8400-e29b-41d4-a716-446655440000"
    ],
    "allowedTools": [
      "550e8400-e29b-41d4-a716-446655440000"
    ],
    "allowedConnectors": [
      "550e8400-e29b-41d4-a716-446655440000"
    ],
    "allowedSkills": [
```

```
      "550e8400-e29b-41d4-a716-446655440000"
    ]
  }'

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// Request Body (payload)
const data = {
    "name": "Example name",
    "organization": "550e8400-e29b-41d4-a716-446655440000",
    "permissions": [
      "550e8400-e29b-41d4-a716-446655440000"
    ],
    "canCreateChatbot": true,
    "canCreateKnowledgeBase": true,
    "canCreateInbox": true,
    "canCreateDatabase": true,
    "canCreateTool": true,
    "canCreateAgentUiTool": true,
    "canCreateSkill": true,
    "maigptCanCodeInterpreter": true,
    "maigptCanRag": true,
    "maigptCanDeepResearch": true,
    "maigptCanBrowserTool": true,
    "maigptAllLlms": true,
    "maigptAllTools": true,
    "maigptAllConnectors": true,
    "maigptAllSkills": true,
    "usageStatisticsScope": {},
    "allowedLlms": [
      "550e8400-e29b-41d4-a716-446655440000"
    ],
    "allowedTools": [
      "550e8400-e29b-41d4-a716-446655440000"
    ],
    "allowedConnectors": [
```

```
      "550e8400-e29b-41d4-a716-446655440000"
    ],
    "allowedSkills": [
      "550e8400-e29b-41d4-a716-446655440000"
    ]
  };

axios.post("https://api.maiagent.ai/api/v1/organizations/550e8400-
e29b-41d4-a716-446655440000/groups/", data, config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-
41d4-a716-446655440000/groups/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# Request Body (payload)
data = {
    "name": "Example name",
    "organization": "550e8400-e29b-41d4-a716-446655440000",
    "permissions": [
        "550e8400-e29b-41d4-a716-446655440000"
    ],
    "canCreateChatbot": True,
    "canCreateKnowledgeBase": True,
    "canCreateInbox": True,
    "canCreateDatabase": True,
    "canCreateTool": True,
    "canCreateAgentUiTool": True,
    "canCreateSkill": True,
    "maigptCanCodeInterpreter": True,
    "maigptCanRag": True,
    "maigptCanDeepResearch": True,
    "maigptCanBrowserTool": True,
    "maigptAllLlms": True,
    "maigptAllTools": True,
    "maigptAllConnectors": True,
    "maigptAllSkills": True,
    "usageStatisticsScope": {},
    "allowedLlms": [
        "550e8400-e29b-41d4-a716-446655440000"
    ],
    "allowedTools": [
        "550e8400-e29b-41d4-a716-446655440000"
    ],
    "allowedConnectors": [
        "550e8400-e29b-41d4-a716-446655440000"
```

```
    ],
    "allowedSkills": [
        "550e8400-e29b-41d4-a716-446655440000"
    ]
}

response = requests.post(url, json=data, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>post("https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-
41d4-a716-446655440000/groups/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'name' => 'Example name',
            'organization' => '550e8400-e29b-41d4-a716-
446655440000',
            'permissions' => [
                '550e8400-e29b-41d4-a716-446655440000'
            ],
            'canCreateChatbot' => true,
            'canCreateKnowledgeBase' => true,
            'canCreateInbox' => true,
            'canCreateDatabase' => true,
            'canCreateTool' => true,
            'canCreateAgentUiTool' => true,
            'canCreateSkill' => true,
            'maigptCanCodeInterpreter' => true,
            'maigptCanRag' => true,
            'maigptCanDeepResearch' => true,
            'maigptCanBrowserTool' => true,
            'maigptAllLlms' => true,
            'maigptAllTools' => true,
            'maigptAllConnectors' => true,
            'maigptAllSkills' => true,
            'usageStatisticsScope' => new \stdClass(),
            'allowedLlms' => [
                '550e8400-e29b-41d4-a716-446655440000'
            ],
            'allowedTools' => [
```

```
                '550e8400-e29b-41d4-a716-446655440000'
            ],
            'allowedConnectors' => [
                '550e8400-e29b-41d4-a716-446655440000'
            ],
            'allowedSkills' => [
                '550e8400-e29b-41d4-a716-446655440000'
            ]
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response Body

Status Code: 201

Response Schema Example

```
{
  "id": string (uuid)
  "name": string
  "type":
  {
  }
  "permissions": [
    object
  ]
  "membersPreview": [
    string
  ]
```

```
  "membersCount": integer // Returns the number of remaining members
(after subtracting the 3 shown in the list), for the frontend +N badge

Unlike resource counts:
<ul>
  <li>members_count: Returns total - 3 (for the +N badge); None indicates
a total <= 3</li>
  <li>chatbots_count/knowledge_bases_count/inboxes_count: Returns the
total count</li>
</ul>
  "chatbotsCount": integer
  "chatbotsPreview": [
    string
  ]
  "knowledgeBasesCount": integer
  "knowledgeBasesPreview": [
    string
  ]
  "inboxesCount": integer
  "inboxesPreview": [
    string
  ]
  "databasesCount": integer
  "databasesPreview": [
    string
  ]
  "canCreateChatbot"?: boolean // Optional
  "canCreateKnowledgeBase"?: boolean // Optional
  "canCreateInbox"?: boolean // Optional
  "canCreateDatabase"?: boolean // Optional
  "canCreateTool"?: boolean // Optional
  "canCreateAgentUiTool"?: boolean // Optional
  "canCreateSkill"?: boolean // Optional
  "maigptCanCodeInterpreter"?: boolean // Whether members of this role
may use the code interpreter built-in tool in MaiGPT. (Optional)
  "maigptCanRag"?: boolean // Whether members of this role may use the
knowledge base RAG built-in tool in MaiGPT. (Optional)
  "maigptCanDeepResearch"?: boolean // Whether members of this role may
use Deep Research in MaiGPT. Deep Research reaches the public internet
through its own built-in search, so a role that revokes the official web-
search tools needs this switch too. (Optional)
  "maigptCanBrowserTool"?: boolean // Whether members of this role may
use the browser built-in tool in MaiGPT. (Optional)
  "maigptAllLlms"?: boolean // Whether members of this role may use every
organization-available LLM in MaiGPT. Off = only the bound LLMs; an empty
```

```
binding then means none. (Optional)
  "maigptAllTools"?: boolean // Whether members of this role may call
every official (global) tool in MaiGPT. Off = only the bound tools; an
empty binding then means none. (Optional)
  "maigptAllConnectors"?: boolean // Whether members of this role may
call every official (global) MCP connector in MaiGPT. Off = only the
bound connectors; an empty binding then means none. (Optional)
  "maigptAllSkills"?: boolean // Whether members of this role may use
every official (global) skill in MaiGPT. Off = only the bound skills; an
empty binding then means none. (Optional)
  "usageStatisticsScope"?:  // What this role's usage statistics
permission shows: the whole organization, or only the AI assistants
granted to the member's roles. A member with any organization-wide
granting role sees the whole organization.

* `organization` - Organization-wide
* `accessible_chatbots` - Authorized AI assistants only (Optional)
  {
  }
  "createdAt": string (timestamp)
}
```

Example Response Values

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "name": "Response string",
  "type": {},
  "permissions": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "Example response name",
      "description": "Example response description"
    }
  ],
  "membersPreview": [
    "Response string"
  ],
  "membersCount": 456,
  "chatbotsCount": 456,
  "chatbotsPreview": [
    "Response string"
  ],
  "knowledgeBasesCount": 456,
```

```
  "knowledgeBasesPreview": [
    "Response string"
  ],
  "inboxesCount": 456,
  "inboxesPreview": [
    "Response string"
  ],
  "databasesCount": 456,
  "databasesPreview": [
    "Response string"
  ],
  "canCreateChatbot": false,
  "canCreateKnowledgeBase": false,
  "canCreateInbox": false,
  "canCreateDatabase": false,
  "canCreateTool": false,
  "canCreateAgentUiTool": false,
  "canCreateSkill": false,
  "maigptCanCodeInterpreter": false,
  "maigptCanRag": false,
  "maigptCanDeepResearch": false,
  "maigptCanBrowserTool": false,
  "maigptAllLlms": false,
  "maigptAllTools": false,
  "maigptAllConnectors": false,
  "maigptAllSkills": false,
  "usageStatisticsScope": {},
  "createdAt": "Response string"
}
```


Bulk Add Role Members

POST `/api/v1/organizations/{organizationPk}/groups/{groupPk}/group-members/bulk-create/`

Parameters

Parameter Name	Required	Type	Description
`groupPk`	V	string	
`organizationPk`	V	string	A UUID string identifying this organization ID

Request Body

Request Parameters

Field	Type	Required	Description
members	array[string]	Yes	

Example Request Structure

```
{
  "members": [
    string (uuid)
  ]
}
```

Example Request Values

```
{
  "members": [
    "550e8400-e29b-41d4-a716-446655440000"
  ]
}
```

Code Examples

Shell/Bash

```
# Example API call (Shell)
curl -X POST "https://api.maiagent.ai/api/v1/organizations/550e8400-
e29b-41d4-a716-446655440000/groups/550e8400-e29b-41d4-a716-
446655440000/group-members/bulk-create/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "members": [
      "550e8400-e29b-41d4-a716-446655440000"
    ]
  }'

# Make sure to replace YOUR_API_KEY and verify the request data
before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// Request body (payload)
const data = {
    "members": [
      "550e8400-e29b-41d4-a716-446655440000"
    ]
  };

axios.post("https://api.maiagent.ai/api/v1/organizations/550e8400-
e29b-41d4-a716-446655440000/groups/550e8400-e29b-41d4-a716-
446655440000/group-members/bulk-create/", data, config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-
41d4-a716-446655440000/groups/550e8400-e29b-41d4-a716-
446655440000/group-members/bulk-create/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# Request body (payload)
data = {
    "members": [
        "550e8400-e29b-41d4-a716-446655440000"
    ]
}

response = requests.post(url, json=data, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>post("https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-
41d4-a716-446655440000/groups/550e8400-e29b-41d4-a716-
446655440000/group-members/bulk-create/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'members' => [
                '550e8400-e29b-41d4-a716-446655440000'
            ]
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response Content

Status code: 201

Example Response Structure

```
[
  {
    "id"?: string (uuid) // Role member ID (optional)
    "member"?: { // optional
    {
      "id"?: string (uuid) // Member ID (optional)
      "name"?: string // Member name (optional)
      "email"?: string (email) // Member email (optional)
      "organization"?: { // optional
      {
        "id"?: string (uuid) // Organization ID (optional)
        "name"?: string // Organization name (optional)
        "createdAt"?: string // Organization creation timestamp
(optional)
        "usageStatistics"?: { // optional
        {
          "chatbotsCount"?: integer // Number of chatbots (optional)
          "countableChatbotsCount"?: integer // Number of chatbots that
count toward the creation quota (chatbots whose mode is not in the plan
allowlist are excluded) (optional)
          "exemptChatbotsByMode"?: object // Number of chatbots exempt
from the quota, grouped by the mode that exempts them (optional)
          "canCreateChatbot"?: boolean // Whether chatbots can be created
(optional)
          "createChatbotLimit"?: integer // Maximum number of chatbots
that can be created (-1 means unlimited, 0 means creation is disabled)
(optional)
          "currentMonthWordsCountTotal"?: integer // Total word limit for
the current month (optional)
          "currentMonthUsedWordsCountTotal"?: integer // Words used in
the current month (optional)
          "currentMonthUsedConversationsCountTotal"?: integer //
Conversations used in the current month (optional)
          "availableUploadFilesSizeTotal"?: integer // Total size of
files that can be uploaded (optional)
          "usedUploadFileSizeTotal"?: integer // Size of uploaded files
used (optional)
        }
        }
        "organizationPlan"?: { // optional
        {
          "id"?: string (uuid) // Plan ID (optional)
          "planName"?: string // Plan name (optional)
```

```
          "expiredAt"?: string // Plan expiration time (optional)
        }
        }
      }
      }
      "isOwner"?: boolean // Whether the member is the organization owner
(optional)
      "permissions"?: { // optional
      {
        "hasOrganizationAccessPermission"?: boolean // Whether the member
has organization access permission (optional)
        "hasChatAccessPermission"?: boolean // Whether the member has
chat access permission (optional)
        "hasConversationAccessPermission"?: boolean // Whether the member
has conversation access permission (optional)
        "hasChatbotAccessPermission"?: boolean // Whether the member has
chatbot access permission (optional)
      }
      }
      "createdAt"?: string // Member creation timestamp (optional)
    }
    }
    "createdAt"?: string // Role member creation timestamp (optional)
  }
]
```

Example Response Values


```
[
  {
    "id": "c1e54f04-01fc-45e9-b40c-9d8b37bd0ac0",
    "member": {
      "id": "af4e472d-3f9b-446b-bab8-05de4112d086",
      "name": "h",
      "email": "h@gmail.com",
      "organization": {
        "id": "670e3d30-9d24-47b4-b2cc-6bf224b2f3bb",
        "name": "Updated Org Name",
        "createdAt": "1745288290000",
        "usageStatistics": {
          "chatbotsCount": 1,
          "countableChatbotsCount": 1,
          "exemptChatbotsByMode": {},
          "canCreateChatbot": false,
```

```
          "createChatbotLimit": 1,
          "currentMonthWordsCountTotal": 1000000,
          "currentMonthUsedWordsCountTotal": 0,
          "currentMonthUsedConversationsCountTotal": 0,
          "availableUploadFilesSizeTotal": 104857600,
          "usedUploadFileSizeTotal": 0
        },
        "organizationPlan": {
          "id": "16136181-ae0d-4b3f-aaeb-9a6ed251459f",
          "planName": "Free Plan",
          "expiredAt": null
        }
      },
      "isOwner": false,
      "permissions": {
        "hasMaigptAccessPermission": false,
        "hasChatbotAccessPermission": false,
        "hasAgentopsAccessPermission": false,
        "hasConversationAccessPermission": false,
        "hasChatAccessPermission": false,
        "hasDeveloperAccessPermission": false,
        "hasOrganizationAccessPermission": true
      },
      "createdAt": "1748335331000"
    },
    "createdAt": "1748341252000"
  }
]
```


Bulk assign AI assistants to a role

POST `/api/v1/organizations/{organizationPk}/groups/{groupPk}/group-chatbots/bulk-create/`

Parameters

Parameter name	Required	Type	Description
`groupPk`	V	string	
`organizationPk`	V	string	A UUID string identifying this organization ID
`page`	X	integer	A page number within the paginated result set.
`pageSize`	X	integer	Number of results to return per page.
`query`	X	string	
`search`	X	string	

Request body

Request parameters

Field	Type	Required	Description
chatbots	array[string]	Yes	

Example request schema

```
{
  "chatbots": [
    string (uuid)
  ]
}
```

Example request values

```
{
  "chatbots": [
    "550e8400-e29b-41d4-a716-446655440000"
```

```
  ]
}
```

Code examples

Shell/Bash

```
# Example API call (Shell)
curl -X POST "https://api.maiagent.ai/api/v1/organizations/550e8400-
e29b-41d4-a716-446655440000/groups/550e8400-e29b-41d4-a716-
446655440000/group-chatbots/bulk-create/?
page=1&pageSize=1&query=example&search=example"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "chatbots": [
      "550e8400-e29b-41d4-a716-446655440000"
    ]
  }'

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// Request body (payload)
const data = {
    "chatbots": [
      "550e8400-e29b-41d4-a716-446655440000"
    ]
  };

axios.post("https://api.maiagent.ai/api/v1/organizations/550e8400-
e29b-41d4-a716-446655440000/groups/550e8400-e29b-41d4-a716-
446655440000/group-chatbots/bulk-create/?
page=1&pageSize=1&query=example&search=example", data, config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-
41d4-a716-446655440000/groups/550e8400-e29b-41d4-a716-
446655440000/group-chatbots/bulk-create/?
page=1&pageSize=1&query=example&search=example"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# Request body (payload)
data = {
    "chatbots": [
        "550e8400-e29b-41d4-a716-446655440000"
    ]
}

response = requests.post(url, json=data, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>post("https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-
41d4-a716-446655440000/groups/550e8400-e29b-41d4-a716-
446655440000/group-chatbots/bulk-create/?
page=1&pageSize=1&query=example&search=example", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'chatbots' => [
                '550e8400-e29b-41d4-a716-446655440000'
            ]
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response body

Status code: 201

Example response schema

```
{
  "count": integer
  "next"?: string (uri) // Optional
  "previous"?: string (uri) // Optional
  "results": [
    {
      "id": string (uuid)
      "group": string (uuid)
      "chatbot":
      {
        "id": string (uuid)
        "name": string // Chatbot name. In Agent mode it carries semantic
meaning; in other modes it only distinguishes chatbots.
        "largeLanguageModel": string (uuid) // The large language model
used by the chatbot to generate responses (including the organization's
custom AI Gateway models). On creation, this can only be omitted if the
organization has configured a default model in its AI assistant defaults.
        "llm":  // The bound model's id, name, and retirement
information, read directly from the foreign key. Returned even if the
organization has disabled the model.
        {
          "id": string (uuid)
          "name": string
          "retiresAt": string (date) // The provider's retirement date.
Once reached, the daily scheduled job switches assistants to the
replacement and disables this model. null means no retirement is
scheduled.
          "replacement":  // The replacement model after retirement (id
and name). null means no replacement is specified and no automatic
migration occurs on retirement.
          {
            "id": string (uuid)
            "name": string
          }
        }
        "organizationEnforcedSettings": [ // Setting codes enforced on
this assistant by the organization's AI assistant defaults (matching the
keys in the AI assistant defaults API). These fields return the enforced
values; updates with different values are rejected (read-only; empty for
official built-in Agents and MaiGPT).
          string
```

```
        ]
        "embeddingModel"?: string (uuid) // The embedding model used to
vectorize text; optional (Optional)
        "rerankerModel"?: string (uuid) // The model used for reranking;
optional (Optional)
        "instructions"?: string // Role instructions describing the
chatbot's role and behavior. (Optional)
        "knowledgeBases"?: [ // Knowledge bases accessible to the chatbot
(Optional)
          {
            "id": string (uuid)
            "name": string
          }
        ]
        "databases"?: [ // SQL databases accessible to the chatbot (for
Text-to-SQL) (Optional)
          {
            "id": string (uuid)
            "name": string
          }
        ]
        "updatedAt": string (timestamp)
        "organization"?: string (uuid) // The organization the chatbot
belongs to. If empty, this is a personal chatbot. (Optional)
        "replyMode"?:  // Reply mode: normal or streaming replies

* `normal` - Normal
* `template` - Template
* `hybrid` - Hybrid
* `agent` - Agent (Optional)
        {
        }
        "template"?: string // Template used by Template and Hybrid
modes. (Optional)
        "unanswerableTemplate"?: string // Template used by Template and
Hybrid modes when the question cannot be answered. (Optional)
        "totalWordsCount"?: integer (int64) // Accumulated total word
count used. (Optional)
        "outputMode"?:  // Output mode: text, table, or custom format

* `text` - Text
* `json_schema` - JSON Schema (Optional)
        {
        }
        "rawOutputFormat"?: object // JSON schema definition for the
```

```
custom output format (Optional)
        "groups"?: [ // Groups accessible to the chatbot (Optional)
          {
            "id": string (uuid)
            "name": string
          }
        ]
        "tools"?: [ // Tools available to the chatbot (Optional)
          {
            "id": string (uuid)
            "name": string
            "description": string
            "displayName": string
            "toolType": string
          }
        ]
        "skills"?: [ // Skills associated with the chatbot (Optional)
          {
            "id": string (uuid)
            "name": string
            "description": string
          }
        ]
        "connectors"?: [ // Connectors associated with this chatbot,
gating per-contact OAuth authorization (Optional)
          {
            "id": string (uuid)
            "name": string
          }
        ]
        "agentMode"?:  // Agent mode: normal, SQL, or workflow mode

* `normal` - Normal
* `canvas` - Canvas
* `team` - Team (Optional)
        {
        }
        "numberOfRetrievedChunks"?: integer // Number of reference chunks
to retrieve. Defaults to 12; minimum: 1. (Optional)
        "defaultLabelRelations"?: object // Assistant-level default
knowledge base label filter, using the same format as
query_metadata.label_relations. null means no filtering. Applied as the
lowest-priority fallback only when the caller omits query_metadata.
(Optional)
        "useFullRetrievalRange"?: boolean // When enabled, ignores the
```

```
LLM's top_k truncation and returns the full reranker results. (Optional)
        "enableEvaluation"?: boolean // Optional
        "enableInlineCitations"?: boolean // Enables inline citations,
inserting citation markers such as [1][2] into responses. (Optional)
        "enableCodeInterpreter"?: boolean // When enabled, provides the
Code Interpreter tool to run code in an isolated container. (Optional)
        "enableBrowserTool"?: boolean // Enable browser automation tool
for web tasks (Optional)
        "enableImageSearch"?: boolean // Provide the image_search tool
when any attached knowledge base uses a multimodal embedding model.
Disable to remove the tool entirely. (Optional)
        "enableClaudeStreamRetry"?: boolean // When a Claude streaming
call stalls (first-chunk or mid-stream), abort and re-issue the call once
in non-streaming mode. Mid-stream retries send a reset signal so the
client discards any partial output already rendered. Each retry incurs a
second billing for the same prompt. (Optional)
        "customMaxLlmOutputTokens"?: integer // Custom maximum number of
LLM output tokens; minimum: 512. (Optional)
        "voiceConfig"?: { // Optional
        {
          "enabled"?: boolean // Whether this chatbot can be used as a
voice agent. Checked by every conversation platform (WebChat, SIP phone,
admin/marketplace voice test) instead of a per-platform toggle.
(Optional)
          "voiceAgentType"?: string (uuid) // Voice agent mode type.
(Optional)
          "sttProvider"?: string (uuid) // Speech-to-Text service
provider. (Optional)
          "sttConfig"?: object // STT configuration parameters (JSON).
(Optional)
          "ttsProvider"?: string (uuid) // Text-to-Speech service
provider. (Optional)
          "ttsConfig"?: object // TTS configuration parameters (JSON).
(Optional)
          "realtimeProvider"?: string (uuid) // Realtime end-to-end voice
model provider. (Optional)
          "realtimeConfig"?: object // Realtime configuration parameters
(JSON). (Optional)
          "realtimeInstructions"?: string // Prompt dedicated to the
realtime voice session; falls back to chatbot instructions when empty
(Optional)
          "turnHandling"?: object // Turn-taking and interruption
settings for the voice agent. (Optional)
          "enableVoiceReply"?: boolean // When disabled, the voice agent
replies in text only and does not speak (Optional)
```

```
        }
        }
        "thinkingConfig"?: object // Thinking level: null (model default)
or {"reasoning_effort": "off|minimal|low|medium|high|xhigh|max"}
(Optional)
        "enableToolSearching"?: boolean // Legacy field; use
tool_loading_mode instead. Writing true is equivalent to
tool_loading_mode=search, and false to all. If both are provided,
tool_loading_mode takes precedence. Reading returns whether the tool
loading mode is anything other than load all. (Optional)
        "toolLoadingMode"?:  // Tool loading mode: auto (selected
automatically based on the tools available for the turn and the model),
all (load all), or search (dynamic search). New assistants default to
auto. Existing assistants without this setting return a value derived
from the legacy toggle (on → search, off → all).

* `auto` - Auto
* `all` - Load all
* `search` - Dynamic search (Optional)
        {
        }
        "maxAgentIterations"?: integer // Maximum number of iterations
for AgentWorkflow (1-100, default: 20) (Optional)
        "agentTimeoutSeconds"?: integer // Timeout in seconds for
AgentWorkflow execution (30-1200, default: 600) (Optional)
        "agentTimeoutMessage"?: string // Custom user-facing message
shown when AgentWorkflow times out (max 500 chars). Leave empty to use
the system default. (Optional)
        "requireTextWithFlexCards"?: boolean // When enabled, a turn that
would end with only Flex Message cards and no text for the user is re-
issued to the LLM once, asking it to write the text first and then send
the card. Each retry incurs a second billing for the same prompt.
(Optional)
        "isMultimodalLlm": boolean // Whether the chatbot LLM supports
multimodal (read-only)
        "enableSizeBasedToolResultTruncation"?: boolean // When enabled,
tool results exceeding the character threshold are kept as head+tail
(with the identifiers found in the cut part) when written to conversation
history; knowledge base, SQL and conversation search results keep their
100-character cut either way. Reduces memory bloat from large tool
outputs (code interpreter bash stdout, web search results, etc.).
(Optional)
        "toolResultMaxChars"?: integer // Character threshold for size-
based tool result truncation (500-50000). Only effective when
enable_size_based_tool_result_truncation is True. (Optional)
```

```
        "enableVectorMemory"?: boolean // When enabled, archived messages are vectorized and processed by fact extraction for semantic retrieval (existing behavior). When disabled, archived messages are discarded and only the active chat history window is used for multi-turn context. (Optional)
        "longTermMemoryTopK"?: integer // Number of memory nodes returned per long-term memory retrieval (similarity_top_k for vector retrieval). Defaults to 10; range: 1–50. (Optional)
        "enableCrossConversationSearch"?: boolean // When enabled, the conversation history tools also reach this contact's other conversations in the same inbox, within the lookback window. When disabled, they only reach the current conversation. (Optional)
        "crossConversationLookbackDays"?: integer // How far back cross-conversation search may reach, measured from each conversation's last message (1-365 days). Leave empty to fall back to 90 days. Only effective when enable_cross_conversation_search is True. (Optional)
        "useGatewayFallback"?: boolean // When enabled, use the fallback group instead of the single LLM (Optional)
        "gatewayFallbackGroup"?: string (uuid) // Optional
        "enableSearchMessagesTool"?: boolean // Allow the AI to search past messages in the current conversation. (Optional)
        "enableGetMessageContextTool"?: boolean // Allow the AI to retrieve messages surrounding a specific message for context. (Optional)
        "enableReadAttachmentFullTextTool"?: boolean // Allow the AI to read the full text of plain-text attachments. AGENT mode only. (Optional)
        "enableParseAttachmentContentTool"?: boolean // Allow the AI to parse PDF, Office, audio, and other attachments. AGENT mode only. (Optional)
        "enableListAvailableParsersTool"?: boolean // Allow the AI to list available parsers and their capabilities. AGENT mode only. (Optional)
        "enableGetDownloadLinkTool"?: boolean // Allow the AI to generate shareable download links for produced content. AGENT mode only. (Optional)
        "isLocked": boolean // Locked instance: config follows the official version; only the dedicated KB can be modified
        "sourceBuildInAgent": string (uuid) // Points to the official Build-in Agent blueprint when instantiated by a rental
        "canUpdate": boolean // Return whether the current user can update this resource.
        "canDelete": boolean // Return whether the current user can delete this resource.
        "team":
        {
          "id": string (uuid)
```

```
          "name": string
        }
        "webChatIsActive"?: boolean // Optional, create only. Whether the
web widget channel starts active. Omitted or null: follows the
organization's default for new chatbot channels (inactive unless a
platform admin turned it on). Ignored on update; change an existing
channel from its channel settings instead. (Optional)
        "apiIsActive"?: boolean // Optional, create only. Whether the API
channel starts active. Omitted or null: follows the organization's
default for new chatbot channels (inactive unless a platform admin turned
it on). Ignored on update; change an existing channel from its channel
settings instead. The backstage (admin) channel always starts active and
cannot be set here. (Optional)
        "fileWorkspaceMode"?:  // File workspace mode in Work internal
conversations: none, bound or user_mount.

* `none` - None
* `bound` - Bound workspace
* `user_mount` - User mount (Optional)
        {
        }
        "fileWorkspaceFolder"?: string (uuid) // The bound workspace
(folder id); required when the mode is bound, cleared otherwise.
(Optional)
        "fileWorkspaceStatus": object // Read-only. {"folder": {"id",
"name"} | null, "state": "ok" | "missing" | "builder_lost_edit" | null}
        "fileWorkspaceAvailable": boolean // Read-only. Whether the
organization has the file library and this agent can configure a file
workspace.
      }
      "canRead"?: boolean // Optional
      "canUpdate"?: boolean // Optional
      "canDelete"?: boolean // Optional
      "createdAt": string (timestamp)
    }
  ]
}
```

Example response values

```
{
  "count": 123,
  "next": "http://api.example.org/accounts/?page=4",
  "previous": "http://api.example.org/accounts/?page=2",
```

```
  "results": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "group": "550e8400-e29b-41d4-a716-446655440000",
      "chatbot": {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "name": "Response string",
        "largeLanguageModel": "550e8400-e29b-41d4-a716-446655440000",
        "llm": {
          "id": "550e8400-e29b-41d4-a716-446655440000",
          "name": "Response string",
          "retiresAt": "Response string",
          "replacement": {
            "id": "550e8400-e29b-41d4-a716-446655440000",
            "name": "Response string"
          }
        },
        "organizationEnforcedSettings": [
          "Response string"
        ],
        "embeddingModel": "550e8400-e29b-41d4-a716-446655440000",
        "rerankerModel": "550e8400-e29b-41d4-a716-446655440000",
        "instructions": "Response string",
        "knowledgeBases": [
          {
            "id": "550e8400-e29b-41d4-a716-446655440000",
            "name": "Response string"
          }
        ],
        "databases": [
          {
            "id": "550e8400-e29b-41d4-a716-446655440000",
            "name": "Response string"
          }
        ],
        "updatedAt": "Response string",
        "organization": "550e8400-e29b-41d4-a716-446655440000",
        "replyMode": {},
        "template": "Response string",
        "unanswerableTemplate": "Response string",
        "totalWordsCount": 456,
        "outputMode": {},
        "rawOutputFormat": null,
        "groups": [
          {
```

```
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "Response string"
    }
  ],
  "tools": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "Response string",
      "description": "Response string",
      "displayName": "Response string",
      "toolType": "Response string"
    }
  ],
  "skills": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "Response string",
      "description": "Response string"
    }
  ],
  "connectors": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "Response string"
    }
  ],
  "agentMode": {},
  "numberOfRetrievedChunks": 456,
  "defaultLabelRelations": null,
  "useFullRetrievalRange": false,
  "enableEvaluation": false,
  "enableInlineCitations": false,
  "enableCodeInterpreter": false,
  "enableBrowserTool": false,
  "enableImageSearch": false,
  "enableClaudeStreamRetry": false,
  "customMaxLlmOutputTokens": 456,
  "voiceConfig": {
    "enabled": false,
    "voiceAgentType": "550e8400-e29b-41d4-a716-446655440000",
    "sttProvider": "550e8400-e29b-41d4-a716-446655440000",
    "sttConfig": null,
    "ttsProvider": "550e8400-e29b-41d4-a716-446655440000",
    "ttsConfig": null,
    "realtimeProvider": "550e8400-e29b-41d4-a716-446655440000",
```

```
      "realtimeConfig": null,
      "realtimeInstructions": "Response string",
      "turnHandling": null,
      "enableVoiceReply": false
    },
    "thinkingConfig": null,
    "enableToolSearching": false,
    "toolLoadingMode": {},
    "maxAgentIterations": 456,
    "agentTimeoutSeconds": 456,
    "agentTimeoutMessage": "Response string",
    "requireTextWithFlexCards": false,
    "isMultimodalLlm": false,
    "enableSizeBasedToolResultTruncation": false,
    "toolResultMaxChars": 456,
    "enableVectorMemory": false,
    "longTermMemoryTopK": 456,
    "enableCrossConversationSearch": false,
    "crossConversationLookbackDays": 456,
    "useGatewayFallback": false,
    "gatewayFallbackGroup": "550e8400-e29b-41d4-a716-446655440000",
    "enableSearchMessagesTool": false,
    "enableGetMessageContextTool": false,
    "enableReadAttachmentFullTextTool": false,
    "enableParseAttachmentContentTool": false,
    "enableListAvailableParsersTool": false,
    "enableGetDownloadLinkTool": false,
    "isLocked": false,
    "sourceBuildInAgent": "550e8400-e29b-41d4-a716-446655440000",
    "canUpdate": false,
    "canDelete": false,
    "team": {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "Response string"
    },
    "webChatIsActive": false,
    "apiIsActive": false,
    "fileWorkspaceMode": {},
    "fileWorkspaceFolder": "550e8400-e29b-41d4-a716-446655440000",
    "fileWorkspaceStatus": {
      "name": "example.pdf",
      "content": "base64encoded_content",
      "contentType": "application/pdf"
    },
    "fileWorkspaceAvailable": false
```

```
      },
      "canRead": false,
      "canUpdate": false,
      "canDelete": false,
      "createdAt": "Response string"
    }
  ]
}
```


Bulk Assign Inboxes to Role

POST `/api/v1/organizations/{organizationPk}/groups/{groupPk}/group-inboxes/bulk-create/`

Parameters

Parameter	Required	Type	Description
`groupPk`	V	string	
`organizationPk`	V	string	A UUID string identifying this organization ID

Code Examples

Shell/Bash

```
# Example API call (Shell)
curl -X POST "https://api.maiagent.ai/api/v1/organizations/550e8400-
e29b-41d4-a716-446655440000/groups/550e8400-e29b-41d4-a716-
446655440000/group-inboxes/bulk-create/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# Make sure to replace YOUR_API_KEY and verify the request data
before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

// Request body (payload)
const data = null;

axios.post("https://api.maiagent.ai/api/v1/organizations/550e8400-
e29b-41d4-a716-446655440000/groups/550e8400-e29b-41d4-a716-
446655440000/group-inboxes/bulk-create/", data, config)
  .then(response => {
    console.log('Successfully retrieved response:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-41d4-a716-446655440000/groups/550e8400-e29b-41d4-a716-446655440000/group-inboxes/bulk-create/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.post(url, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>post("https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-
41d4-a716-446655440000/groups/550e8400-e29b-41d4-a716-
446655440000/group-inboxes/bulk-create/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response

Status Code	Description
200	No response body

Bulk Assign Knowledge Bases to a Role

POST `/api/v1/organizations/{organizationPk}/groups/{groupPk}/group-knowledge-bases/bulk-create/`

Parameters

Parameter	Required	Type	Description
`groupPk`	V	string	
`organizationPk`	V	string	A UUID string identifying this Organization ID
`page`	X	integer	A page number within the paginated result set.
`pageSize`	X	integer	Number of results to return per page.
`query`	X	string	
`search`	X	string	

Request

Request Parameters

Field	Type	Required	Description
knowledgeBases	array[string]	Yes	

Request Schema

```
{
  "knowledgeBases": [
```

```
    string (uuid)
  ]
}
```

Request Example

```
{
  "knowledgeBases": [
    "550e8400-e29b-41d4-a716-446655440000"
  ]
}
```

Code Examples

Shell/Bash

```
# API call example (Shell)
curl -X POST "https://api.maiagent.ai/api/v1/organizations/550e8400-
e29b-41d4-a716-446655440000/groups/550e8400-e29b-41d4-a716-
446655440000/group-knowledge-bases/bulk-create/?
page=1&pageSize=1&query=example&search=example"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "knowledgeBases": [
      "550e8400-e29b-41d4-a716-446655440000"
    ]
  }'

# Make sure to replace YOUR_API_KEY and verify the request data
before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// Request payload
const data = {
    "knowledgeBases": [
      "550e8400-e29b-41d4-a716-446655440000"
    ]
  };

axios.post("https://api.maiagent.ai/api/v1/organizations/550e8400-
e29b-41d4-a716-446655440000/groups/550e8400-e29b-41d4-a716-
446655440000/group-knowledge-bases/bulk-create/?
page=1&pageSize=1&query=example&search=example", data, config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-
41d4-a716-446655440000/groups/550e8400-e29b-41d4-a716-
446655440000/group-knowledge-bases/bulk-create/?
page=1&pageSize=1&query=example&search=example"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# Request payload
data = {
    "knowledgeBases": [
        "550e8400-e29b-41d4-a716-446655440000"
    ]
}

response = requests.post(url, json=data, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>post("https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-
41d4-a716-446655440000/groups/550e8400-e29b-41d4-a716-
446655440000/group-knowledge-bases/bulk-create/?
page=1&pageSize=1&query=example&search=example", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'knowledgeBases' => [
                '550e8400-e29b-41d4-a716-446655440000'
            ]
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response

Status Code: 201

Response Schema

```
{
  "count": integer
  "next"?: string (uri) // optional
  "previous"?: string (uri) // optional
  "results": [
    {
      "id": string (uuid)
      "group": string (uuid)
      "knowledgeBase":
      {
        "id": string (uuid)
        "createdBy":
        {
          "id": string (uuid)
          "name": string
        }
        "organization"?: string (uuid) // optional
        "embeddingModel": string (uuid)
        "rerankerModel": string (uuid)
        "name": string
        "description"?: string // optional
        "numberOfRetrievedChunks"?: integer // Number of retrieved
reference chunks. Default is 12, minimum is 1 (optional)
        "enableHyde"?: boolean // Enable HyDE. Default is False
(optional)
        "similarityCutoff"?: number (double) // Similarity threshold.
Default is 0.0, range 0.0-1.0 (optional)
        "enableRerank"?: boolean // Whether to enable reranking. Default
is True (optional)
        "enableRrf"?: boolean // Enable Reciprocal Rank Fusion for hybrid
search. Disable this if using a custom Elasticsearch without enterprise
license. (optional)
        "vectorDatabaseType"?:  // Type of vector database: elasticsearch
or opensearch.

* `elasticsearch` - Elasticsearch
* `opensearch` - OpenSearch
* `oracle` - Oracle AI Database 26ai
* `synxdb` - SynxDB (optional)
        {
        }
```

```
        "vectorDatabaseUrl"?: string // Custom vector database endpoint
URL or Oracle DSN. For Elasticsearch/OpenSearch: URL format (e.g.,
"https://host:9200"). For Oracle: DSN format (e.g.,
"host:1521/service_name"). (optional)
        "vectorDatabaseApiKey"?: string // API Key for Elasticsearch. Not
used for OpenSearch. (optional)
        "opensearchUsername"?: string // Username for OpenSearch Basic
Auth. (optional)
        "opensearchPassword"?: string // Password for OpenSearch Basic
Auth. (optional)
        "oracleUser"?: string // Oracle database username. (optional)
        "oraclePassword"?: string // Oracle database password. (optional)
        "synxdbUser"?: string // SynxDB database username. (optional)
        "synxdbPassword"?: string // SynxDB database password. (optional)
        "labels": [
          {
            "id": string (uuid)
            "name": string
          }
        ]
        "chatbots"?: [ // optional
          {
            "id": string (uuid)
            "name": string
          }
        ]
        "groups"?: [ // List of groups that can access the knowledge base
(optional)
          {
            "id": string (uuid)
            "name": string
          }
        ]
        "filesCount": integer // Return count of KnowledgeBaseFile
excluding processed files, conversation attachments, and soft-deleted.
        "vectorStorageSize": integer
        "chunksCount": integer
        "canUpdate": boolean // Return whether the current user can
update this resource.
        "canDelete": boolean // Return whether the current user can
delete this resource.
        "createdAt": string (timestamp)
        "updatedAt": string (timestamp)
      }
      "canRead"?: boolean // optional
```

```
      "canUpdate"?: boolean // optional
      "canDelete"?: boolean // optional
      "createdAt": string (timestamp)
    }
  ]
}
```

Response Example


```
{
  "count": 123,
  "next": "http://api.example.org/accounts/?page=4",
  "previous": "http://api.example.org/accounts/?page=2",
  "results": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "group": "550e8400-e29b-41d4-a716-446655440000",
      "knowledgeBase": {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "createdBy": {
          "id": "550e8400-e29b-41d4-a716-446655440000",
          "name": "response string"
        },
        "organization": "550e8400-e29b-41d4-a716-446655440000",
        "embeddingModel": "550e8400-e29b-41d4-a716-446655440000",
        "rerankerModel": "550e8400-e29b-41d4-a716-446655440000",
        "name": "response string",
        "description": "response string",
        "numberOfRetrievedChunks": 456,
        "enableHyde": false,
        "similarityCutoff": 456,
        "enableRerank": false,
        "enableRrf": false,
        "vectorDatabaseType": {},
        "vectorDatabaseUrl": "response string",
        "vectorDatabaseApiKey": "response string",
        "opensearchUsername": "response string",
        "opensearchPassword": "response string",
        "oracleUser": "response string",
        "oraclePassword": "response string",
        "synxdbUser": "response string",
        "synxdbPassword": "response string",
        "labels": [
          {
```

```
            "id": "550e8400-e29b-41d4-a716-446655440000",
            "name": "response string"
          }
        ],
        "chatbots": [
          {
            "id": "550e8400-e29b-41d4-a716-446655440000",
            "name": "response string"
          }
        ],
        "groups": [
          {
            "id": "550e8400-e29b-41d4-a716-446655440000",
            "name": "response string"
          }
        ],
        "filesCount": 456,
        "vectorStorageSize": 456,
        "chunksCount": 456,
        "canUpdate": false,
        "canDelete": false,
        "createdAt": "response string",
        "updatedAt": "response string"
      },
      "canRead": false,
      "canUpdate": false,
      "canDelete": false,
      "createdAt": "response string"
    }
  ]
}
```


Bulk Assign Databases to a Role

POST `/api/v1/organizations/{organizationPk}/groups/{groupPk}/group-databases/bulk-create/`

Parameters

Parameter	Required	Type	Description
`groupPk`	V	string	
`organizationPk`	V	string	A UUID string identifying this Organization ID
`page`	X	integer	A page number within the paginated result set.
`pageSize`	X	integer	Number of results to return per page.
`query`	X	string	
`search`	X	string	

Request

Request Parameters

Field	Type	Required	Description
databases	array[string]	Yes	

Request Schema

```
{
  "databases": [
    string (uuid)
  ]
}
```

Request Example

```
{
  "databases": [
```

```
    "550e8400-e29b-41d4-a716-446655440000"
  ]
}
```

Code Examples

Shell/Bash

```
# API call example (Shell)
curl -X POST "https://api.maiagent.ai/api/v1/organizations/550e8400-
e29b-41d4-a716-446655440000/groups/550e8400-e29b-41d4-a716-
446655440000/group-databases/bulk-create/?
page=1&pageSize=1&query=example&search=example"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "databases": [
      "550e8400-e29b-41d4-a716-446655440000"
    ]
  }'

# Make sure to replace YOUR_API_KEY and verify the request data
before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// Request payload
const data = {
    "databases": [
      "550e8400-e29b-41d4-a716-446655440000"
    ]
  };

axios.post("https://api.maiagent.ai/api/v1/organizations/550e8400-
e29b-41d4-a716-446655440000/groups/550e8400-e29b-41d4-a716-
446655440000/group-databases/bulk-create/?
page=1&pageSize=1&query=example&search=example", data, config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-
41d4-a716-446655440000/groups/550e8400-e29b-41d4-a716-
446655440000/group-databases/bulk-create/?
page=1&pageSize=1&query=example&search=example"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# Request payload
data = {
    "databases": [
        "550e8400-e29b-41d4-a716-446655440000"
    ]
}

response = requests.post(url, json=data, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>post("https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-
41d4-a716-446655440000/groups/550e8400-e29b-41d4-a716-
446655440000/group-databases/bulk-create/?
page=1&pageSize=1&query=example&search=example", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'databases' => [
                '550e8400-e29b-41d4-a716-446655440000'
            ]
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response

Status Code: 201

Response Schema

```
{
  "count": integer
  "next"?: string (uri) // optional
  "previous"?: string (uri) // optional
  "results": [
    {
      "id": string (uuid)
      "group": string (uuid)
      "database":
      {
        "id": string (uuid)
        "name": string // Display name for this database connection
        "description": string // Description of the database and its
purpose
        "databaseType":  // Type of database: PostgreSQL, MySQL, MSSQL,
Oracle, SynxDB, or MaiAgent

* `postgresql` - PostgreSQL
* `mysql` - MySQL
* `maiagent` - MaiAgent
* `oracle` - Oracle
* `mssql` - MSSQL
* `synxdb` - SynxDB
        {
        }
        "includeTables": object // Optional list of tables to include.
Format: {"tables": ["table1", "table2"]}. For MaiAgent type, this is
auto-populated from uploaded files.
        "isActive": boolean // When disabled, this database will not be
used in Text-to-SQL queries
        "status":
        {
        }
        "deletedAt": string (timestamp)
        "tables": [
          {
            "id": string (uuid)
            "tableName": string // Name of the table in the database
            "sheetName": string // Name of the source worksheet/sheet
this table was created from. Empty for tables created before this field
was added.
```

```
            "description"?: string // Description of the table and its
data for better Text-to-SQL understanding (optional)
            "status":
            {
            }
            "errorMessage": string // Error details if table creation or
deletion failed
            "sourceFile":
            {
              "id": string (uuid)
              "name": string
              "isFromKnowledgeBase": boolean // Determine if the source
file originated from a knowledge base upload.

Returns True if the file was uploaded via knowledge base,
False if uploaded directly to the database.
            }
            "columns": [
              {
                "id": string (uuid)
                "columnName": string
                "columnType"?: string // Data type of the column (e.g.,
VARCHAR, INTEGER, TIMESTAMP) (optional)
                "description"?: string // Description of the column for
better Text-to-SQL understanding (optional)
                "isPrimaryKey"?: boolean // optional
                "isNullable"?: boolean // optional
                "createdAt": string (timestamp)
                "updatedAt": string (timestamp)
              }
            ]
            "createdAt": string (timestamp)
            "updatedAt": string (timestamp)
          }
        ]
        "chatbots": [
          {
            "id": string (uuid)
            "name": string
          }
        ]
        "groups": [
          {
            "id": string (uuid)
            "name": string
```

```
          }
        ]
        "createdAt": string (timestamp)
        "updatedAt": string (timestamp)
      }
      "canRead"?: boolean // optional
      "canUpdate"?: boolean // optional
      "canDelete"?: boolean // optional
      "createdAt": string (timestamp)
    }
  ]
}
```

Response Example

```
{
  "count": 123,
  "next": "http://api.example.org/accounts/?page=4",
  "previous": "http://api.example.org/accounts/?page=2",
  "results": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "group": "550e8400-e29b-41d4-a716-446655440000",
      "database": {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "name": "response string",
        "description": "response string",
        "databaseType": {},
        "includeTables": null,
        "isActive": false,
        "status": {},
        "deletedAt": "response string",
        "tables": [
          {
            "id": "550e8400-e29b-41d4-a716-446655440000",
            "tableName": "response string",
            "sheetName": "response string",
            "description": "response string",
            "status": {},
            "errorMessage": "response string",
            "sourceFile": {
              "id": "550e8400-e29b-41d4-a716-446655440000",
              "name": "response string",
              "isFromKnowledgeBase": false
```

```
            },
            "columns": [
              {
                "id": "550e8400-e29b-41d4-a716-446655440000",
                "columnName": "response string",
                "columnType": "response string",
                "description": "response string",
                "isPrimaryKey": false,
                "isNullable": false,
                "createdAt": "response string",
                "updatedAt": "response string"
              }
            ],
            "createdAt": "response string",
            "updatedAt": "response string"
          }
        ],
        "chatbots": [
          {
            "id": "550e8400-e29b-41d4-a716-446655440000",
            "name": "response string"
          }
        ],
        "groups": [
          {
            "id": "550e8400-e29b-41d4-a716-446655440000",
            "name": "response string"
          }
        ],
        "createdAt": "response string",
        "updatedAt": "response string"
      },
      "canRead": false,
      "canUpdate": false,
      "canDelete": false,
      "createdAt": "response string"
    }
  ]
}
```

List Permissions

GET `/api/v1/permissions/`

Code Examples

Shell/Bash

```
# API call example (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/permissions/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# Make sure to replace YOUR_API_KEY and verify the request data
before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/permissions/", config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/permissions/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/permissions/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response

Status Code: 200

Response Schema

```
[
  {
    "id": string (uuid)
    "name": string
```

```
    "value": string
    "description": string
    "children": [
      object
    ]
  }
]
```

Example Response Values

```
[
  {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Response string",
    "value": "Response string",
    "description": "Response string",
    "children": [
      {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "name": "Response example name",
        "description": "Response example description"
      }
    ]
  }
]
```

List Roles

GET `/api/v1/organizations/{organizationPk}/groups/`

Parameters

Parameter Name	Required	Type	Description

`organizationPk`	V	string	A UUID string identifying this organization ID
`page`	X	integer	A page number within the paginated result set.
`pageSize`	X	integer	Number of results to return per page.
`query`	X	string	
`search`	X	string	
`type`	X	string	`owner`: Owner ; `default`: Default role ; `custom`: Custom role;

Code Examples

Shell/Bash

```
# API call example (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/organizations/550e8400-
e29b-41d4-a716-446655440000/groups/?
page=1&pageSize=1&query=example&search=example&type=custom"

  -H "Authorization: Api-Key YOUR_API_KEY"

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/organizations/550e8400-
e29b-41d4-a716-446655440000/groups/?
page=1&pageSize=1&query=example&search=example&type=custom", config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('An error occurred during the request:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-
41d4-a716-446655440000/groups/?
page=1&pageSize=1&query=example&search=example&type=custom"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("An error occurred during the request:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-
41d4-a716-446655440000/groups/?
page=1&pageSize=1&query=example&search=example&type=custom", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'An error occurred during the request: ' . $e-
>getMessage();
}
?>
```

Response

Status Code: 200

Response Schema Example

```
{
  "count": integer
  "next"?: string (uri) // Optional
  "previous"?: string (uri) // Optional
  "results": [
    {
      "id": string (uuid)
      "name": string
      "type":
      {
      }
      "permissions": [
        object
      ]
      "membersPreview": [
        string
      ]
      "membersCount": integer // Returns the remaining number of members
(after deducting the 3 shown in the list), used for the frontend +N badge
display

Unlike resource counts:
<ul>
  <li>members_count: returns total - 3 (used for the +N badge); None
means the total is <= 3</li>
  <li>chatbots_count/knowledge_bases_count/inboxes_count: return the
total count</li>
</ul>
      "chatbotsCount": integer
      "chatbotsPreview": [
        string
      ]
      "knowledgeBasesCount": integer
      "knowledgeBasesPreview": [
        string
      ]
      "inboxesCount": integer
      "inboxesPreview": [
        string
      ]
      "databasesCount": integer
      "databasesPreview": [
        string
      ]
```

```
      "canCreateChatbot"?: boolean // Optional
      "canCreateKnowledgeBase"?: boolean // Optional
      "canCreateInbox"?: boolean // Optional
      "canCreateDatabase"?: boolean // Optional
      "canCreateTool"?: boolean // Optional
      "canCreateAgentUiTool"?: boolean // Optional
      "canCreateSkill"?: boolean // Optional
      "maigptCanCodeInterpreter"?: boolean // Whether members of this
role may use the code interpreter built-in tool in MaiGPT. (Optional)
      "maigptCanRag"?: boolean // Whether members of this role may use
the knowledge base RAG built-in tool in MaiGPT. (Optional)
      "maigptCanDeepResearch"?: boolean // Whether members of this role
may use Deep Research in MaiGPT. Deep Research reaches the public
internet through its own built-in search, so a role that revokes the
official web-search tools needs this switch too. (Optional)
      "maigptCanBrowserTool"?: boolean // Whether members of this role
may use the browser built-in tool in MaiGPT. (Optional)
      "maigptAllLlms"?: boolean // Whether members of this role may use
every organization-available LLM in MaiGPT. Off = only the bound LLMs; an
empty binding then means none. (Optional)
      "maigptAllTools"?: boolean // Whether members of this role may call
every official (global) tool in MaiGPT. Off = only the bound tools; an
empty binding then means none. (Optional)
      "maigptAllConnectors"?: boolean // Whether members of this role may
call every official (global) MCP connector in MaiGPT. Off = only the
bound connectors; an empty binding then means none. (Optional)
      "maigptAllSkills"?: boolean // Whether members of this role may use
every official (global) skill in MaiGPT. Off = only the bound skills; an
empty binding then means none. (Optional)
      "usageStatisticsScope"?:  // What this role's usage statistics
permission shows: the whole organization, or only the AI assistants
granted to the member's roles. A member with any organization-wide
granting role sees the whole organization.

* `organization` - Organization-wide
* `accessible_chatbots` - Authorized AI assistants only (Optional)
      {
      }
      "createdAt": string (timestamp)
    }
  ]
}
```

Response Example Value

```
{
  "count": 123,
  "next": "http://api.example.org/accounts/?page=4",
  "previous": "http://api.example.org/accounts/?page=2",
  "results": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "response string",
      "type": {},
      "permissions": [
        {
          "id": "550e8400-e29b-41d4-a716-446655440000",
          "name": "response example name",
          "description": "response example description"
        }
      ],
      "membersPreview": [
        "response string"
      ],
      "membersCount": 456,
      "chatbotsCount": 456,
      "chatbotsPreview": [
        "response string"
      ],
      "knowledgeBasesCount": 456,
      "knowledgeBasesPreview": [
        "response string"
      ],
      "inboxesCount": 456,
      "inboxesPreview": [
        "response string"
      ],
      "databasesCount": 456,
      "databasesPreview": [
        "response string"
      ],
      "canCreateChatbot": false,
      "canCreateKnowledgeBase": false,
      "canCreateInbox": false,
      "canCreateDatabase": false,
      "canCreateTool": false,
      "canCreateAgentUiTool": false,
      "canCreateSkill": false,
      "maigptCanCodeInterpreter": false,
```

```
      "maigptCanRag": false,
      "maigptCanDeepResearch": false,
      "maigptCanBrowserTool": false,
      "maigptAllLlms": false,
      "maigptAllTools": false,
      "maigptAllConnectors": false,
      "maigptAllSkills": false,
      "usageStatisticsScope": {},
      "createdAt": "response string"
    }
  ]
}
```


Get Role Details

GET `/api/v1/organizations/{organizationPk}/groups/{id}`

Parameters

Parameter Name	Required	Type	Description
`id`	V	string	A UUID string identifying this Group.
`organizationPk`	V	string	A UUID string identifying this organization ID

Code Examples

Shell/Bash

```
# API call example (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/organizations/550e8400-
e29b-41d4-a716-446655440000/groups/550e8400-e29b-41d4-a716-
446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/organizations/550e8400-
e29b-41d4-a716-446655440000/groups/550e8400-e29b-41d4-a716-
446655440000/", config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('An error occurred during the request:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-
41d4-a716-446655440000/groups/550e8400-e29b-41d4-a716-446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("An error occurred during the request:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-
41d4-a716-446655440000/groups/550e8400-e29b-41d4-a716-
446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'An error occurred during the request: ' . $e-
>getMessage();
}
?>
```

Response

Status Code: 200

Response Schema Example

```
{
  "id": string (uuid)
  "name": string
  "type":
  {
  }
  "permissions": [
    object
  ]
  "membersPreview": [
    string
  ]
  "membersCount": integer // Returns the remaining number of members
(after deducting the 3 shown in the list), used for the frontend +N badge
display

Unlike resource counts:
<ul>
  <li>members_count: returns total - 3 (used for the +N badge); None
means the total is <= 3</li>
  <li>chatbots_count/knowledge_bases_count/inboxes_count: return the
total count</li>
</ul>
  "chatbotsCount": integer
  "chatbotsPreview": [
    string
  ]
  "knowledgeBasesCount": integer
  "knowledgeBasesPreview": [
    string
  ]
  "inboxesCount": integer
  "inboxesPreview": [
    string
  ]
  "databasesCount": integer
  "databasesPreview": [
    string
  ]
  "canCreateChatbot"?: boolean // Optional
  "canCreateKnowledgeBase"?: boolean // Optional
  "canCreateInbox"?: boolean // Optional
  "canCreateDatabase"?: boolean // Optional
  "canCreateTool"?: boolean // Optional
```

```
  "canCreateAgentUiTool"?: boolean // Optional
  "canCreateSkill"?: boolean // Optional
  "maigptCanCodeInterpreter"?: boolean // Whether members of this role
may use the code interpreter built-in tool in MaiGPT. (Optional)
  "maigptCanRag"?: boolean // Whether members of this role may use the
knowledge base RAG built-in tool in MaiGPT. (Optional)
  "maigptCanDeepResearch"?: boolean // Whether members of this role may
use Deep Research in MaiGPT. Deep Research reaches the public internet
through its own built-in search, so a role that revokes the official web-
search tools needs this switch too. (Optional)
  "maigptCanBrowserTool"?: boolean // Whether members of this role may
use the browser built-in tool in MaiGPT. (Optional)
  "maigptAllLlms"?: boolean // Whether members of this role may use every
organization-available LLM in MaiGPT. Off = only the bound LLMs; an empty
binding then means none. (Optional)
  "maigptAllTools"?: boolean // Whether members of this role may call
every official (global) tool in MaiGPT. Off = only the bound tools; an
empty binding then means none. (Optional)
  "maigptAllConnectors"?: boolean // Whether members of this role may
call every official (global) MCP connector in MaiGPT. Off = only the
bound connectors; an empty binding then means none. (Optional)
  "maigptAllSkills"?: boolean // Whether members of this role may use
every official (global) skill in MaiGPT. Off = only the bound skills; an
empty binding then means none. (Optional)
  "usageStatisticsScope"?:  // What this role's usage statistics
permission shows: the whole organization, or only the AI assistants
granted to the member's roles. A member with any organization-wide
granting role sees the whole organization.

* `organization` - Organization-wide
* `accessible_chatbots` - Authorized AI assistants only (Optional)
  {
  }
  "createdAt": string (timestamp)
}
```

Response Example Value

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "name": "response string",
  "type": {},
  "permissions": [
    {
```

```
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "response example name",
      "description": "response example description"
    }
  ],
  "membersPreview": [
    "response string"
  ],
  "membersCount": 456,
  "chatbotsCount": 456,
  "chatbotsPreview": [
    "response string"
  ],
  "knowledgeBasesCount": 456,
  "knowledgeBasesPreview": [
    "response string"
  ],
  "inboxesCount": 456,
  "inboxesPreview": [
    "response string"
  ],
  "databasesCount": 456,
  "databasesPreview": [
    "response string"
  ],
  "canCreateChatbot": false,
  "canCreateKnowledgeBase": false,
  "canCreateInbox": false,
  "canCreateDatabase": false,
  "canCreateTool": false,
  "canCreateAgentUiTool": false,
  "canCreateSkill": false,
  "maigptCanCodeInterpreter": false,
  "maigptCanRag": false,
  "maigptCanDeepResearch": false,
  "maigptCanBrowserTool": false,
  "maigptAllLlms": false,
  "maigptAllTools": false,
  "maigptAllConnectors": false,
  "maigptAllSkills": false,
  "usageStatisticsScope": {},
  "createdAt": "response string"
}
```

List Role Members

`GET` `/api/v1/organizations/{organizationPk}/groups/{groupPk}/group-members/`

Parameters

Parameter Name	Required	Type	Description
`groupPk`	V	string	
`organizationPk`	V	string	A UUID string identifying this organization ID
`page`	X	integer	A page number within the paginated result set.
`pageSize`	X	integer	Number of results to return per page.
`query`	X	string	
`search`	X	string	

Code Examples

Shell/Bash

```
# API call example (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/organizations/550e8400-
e29b-41d4-a716-446655440000/groups/550e8400-e29b-41d4-a716-
446655440000/group-members/?
page=1&pageSize=1&query=example&search=example"

  -H "Authorization: Api-Key YOUR_API_KEY"

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/organizations/550e8400-
e29b-41d4-a716-446655440000/groups/550e8400-e29b-41d4-a716-
446655440000/group-members/?
page=1&pageSize=1&query=example&search=example", config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-
41d4-a716-446655440000/groups/550e8400-e29b-41d4-a716-
446655440000/group-members/?
page=1&pageSize=1&query=example&search=example"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-
41d4-a716-446655440000/groups/550e8400-e29b-41d4-a716-
446655440000/group-members/?
page=1&pageSize=1&query=example&search=example", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response

Status Code: 200

Response Schema Example

```
{
  "count": integer
  "next"?: string (uri) // Optional
  "previous"?: string (uri) // Optional
  "results": [
    {
      "id": string (uuid)
      "member": {
      {
        "id": string (uuid)
        "name": string
        "displayName": string // Name set by the organization owner for
this organization only; empty string when not set (``name`` then falls
back to the account name).
        "accountName": string // Account name of the member (shared
across organizations); shown when display name is cleared.
        "isScimManaged": boolean // True when the member is provisioned
by SCIM; the identity provider manages the member and the organization
name cannot be changed manually.
        "email": string
        "isActive": boolean
        "isOwner": boolean // Check whether the member is an organization
owner (via the OWNER Group)

Use caching to avoid repeated queries within the same request
Cache lifetime: valid for the lifetime of the member instance

Prefer annotation results, if available, to avoid repeated queries
        "permissions": [ // Compute the permission tree once per
(organization, custom-group set) per request.

The tree depends only on the member's organization (default groups,
feature
flags, plan whitelist), the member's custom groups, and the global
``Config``,
so members sharing a group set get the same result. A large role's
``pagination=false`` listing otherwise recomputes it per row — one Redis
``Config`` fetch plus the permission walk each time (issue #8436; the
largest
prod role has 3,837 members and a single group set). The memo lives in
the
serializer context, so it never outlives the request. Rows without the
eager
loaded ``_custom_groups_cache`` (single-object paths) keep computing
```

```
directly.
          object
        ]
        "groups": [
          object
        ]
        "creditQuotaRequired"?: boolean // When True, member must have an
active quota to consume credits (Optional)
        "activeQuota": object // Return the most recent quota summary
(active first), via prefetch to avoid N+1.
        "metadata": object // Organization-scoped member attributes,
injected into LLM system prompt
        "availabilityStatus":  // Self-declared availability for auto-
assignment. Paused members are skipped by the dispatch engine but can
still be manually assigned or claim conversations. Not touched by SCIM
provisioning.

* `available` - Available
* `paused` - Paused
        {
        }
        "createdAt": string (timestamp)
      }
      }
      "createdAt": string (timestamp)
    }
  ]
}
```

Example Response Values

```
{
  "count": 123,
  "next": "http://api.example.org/accounts/?page=4",
  "previous": "http://api.example.org/accounts/?page=2",
  "results": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "member": {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "name": "response string",
        "displayName": "response string",
        "accountName": "response string",
        "isScimManaged": false,
```

```
        "email": "response string",
        "isActive": false,
        "isOwner": false,
        "permissions": [
          {
            "id": "550e8400-e29b-41d4-a716-446655440000",
            "name": "Example response name",
            "description": "Example response description"
          }
        ],
        "groups": [
          {
            "id": "550e8400-e29b-41d4-a716-446655440000",
            "name": "Example response name",
            "description": "Example response description"
          }
        ],
        "creditQuotaRequired": false,
        "activeQuota": {
          "id": "550e8400-e29b-41d4-a716-446655440000",
          "name": "Example response name",
          "description": "Example response description"
        },
        "metadata": null,
        "availabilityStatus": {},
        "createdAt": "response string"
      },
      "createdAt": "response string"
    }
  ]
}
```


Retrieve a Role Member

`GET` `/api/v1/organizations/{organizationPk}/groups/{groupPk}/group-members/{id}`

Parameters

Parameter Name	Required	Type	Description
`groupPk`	V	string	
`id`	V	string	A UUID string identifying this Group Member.
`organizationPk`	V	string	A UUID string identifying this organization ID

Code Examples

Shell/Bash

```
# API call example (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/organizations/550e8400-
e29b-41d4-a716-446655440000/groups/550e8400-e29b-41d4-a716-
446655440000/group-members/550e8400-e29b-41d4-a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/organizations/550e8400-
e29b-41d4-a716-446655440000/groups/550e8400-e29b-41d4-a716-
446655440000/group-members/550e8400-e29b-41d4-a716-446655440000/",
config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-
41d4-a716-446655440000/groups/550e8400-e29b-41d4-a716-
446655440000/group-members/550e8400-e29b-41d4-a716-446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-
41d4-a716-446655440000/groups/550e8400-e29b-41d4-a716-
446655440000/group-members/550e8400-e29b-41d4-a716-446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response

Status Code: 200

Response Schema Example

```
{
  "id": string (uuid)
```

```
  "member": {
  {
    "id": string (uuid)
    "name": string
    "displayName": string // Name set by the organization owner for this
organization only; empty string when not set (``name`` then falls back to
the account name).
    "accountName": string // Account name of the member (shared across
organizations); shown when display name is cleared.
    "isScimManaged": boolean // True when the member is provisioned by
SCIM; the identity provider manages the member and the organization name
cannot be changed manually.
    "email": string
    "isActive": boolean
    "isOwner": boolean // Check whether the member is an organization
owner (via the OWNER Group)

Use caching to avoid repeated queries within the same request
Cache lifetime: valid for the lifetime of the member instance

Prefer annotation results, if available, to avoid repeated queries
    "permissions": [ // Compute the permission tree once per
(organization, custom-group set) per request.

The tree depends only on the member's organization (default groups,
feature
flags, plan whitelist), the member's custom groups, and the global
``Config``,
so members sharing a group set get the same result. A large role's
``pagination=false`` listing otherwise recomputes it per row — one Redis
``Config`` fetch plus the permission walk each time (issue #8436; the
largest
prod role has 3,837 members and a single group set). The memo lives in
the
serializer context, so it never outlives the request. Rows without the
eager
loaded ``_custom_groups_cache`` (single-object paths) keep computing
directly.
      object
    ]
    "groups": [
      object
    ]
    "creditQuotaRequired"?: boolean // When True, member must have an
active quota to consume credits (Optional)
```

```
    "activeQuota": object // Return the most recent quota summary (active
first), via prefetch to avoid N+1.
    "metadata": object // Organization-scoped member attributes, injected
into LLM system prompt
    "availabilityStatus":  // Self-declared availability for auto-
assignment. Paused members are skipped by the dispatch engine but can
still be manually assigned or claim conversations. Not touched by SCIM
provisioning.

* `available` - Available
* `paused` - Paused
    {
    }
    "createdAt": string (timestamp)
  }
  }
  "createdAt": string (timestamp)
}
```

Example Response Values

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "member": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "response string",
    "displayName": "response string",
    "accountName": "response string",
    "isScimManaged": false,
    "email": "response string",
    "isActive": false,
    "isOwner": false,
    "permissions": [
      {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "name": "Example response name",
        "description": "Example response description"
      }
    ],
    "groups": [
      {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "name": "Example response name",
        "description": "Example response description"
```

```
      }
    ],
    "creditQuotaRequired": false,
    "activeQuota": {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "Example response name",
      "description": "Example response description"
    },
    "metadata": null,
    "availabilityStatus": {},
    "createdAt": "response string"
  },
  "createdAt": "response string"
}
```


List AI Assistants for a Role

GET `/api/v1/organizations/{organizationPk}/groups/{groupPk}/group-chatbots/`

Parameters

Parameter Name	Required	Type	Description
`groupPk`	V	string	
`organizationPk`	V	string	A UUID string identifying this organization ID
`page`	X	integer	A page number within the paginated result set.
`pageSize`	X	integer	Number of results to return per page.
`query`	X	string	

`search`	X	string

Code Examples

Shell/Bash

```
# API call example (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/organizations/550e8400-
e29b-41d4-a716-446655440000/groups/550e8400-e29b-41d4-a716-
446655440000/group-chatbots/?
page=1&pageSize=1&query=example&search=example"

  -H "Authorization: Api-Key YOUR_API_KEY"

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/organizations/550e8400-
e29b-41d4-a716-446655440000/groups/550e8400-e29b-41d4-a716-
446655440000/group-chatbots/?
page=1&pageSize=1&query=example&search=example", config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-
41d4-a716-446655440000/groups/550e8400-e29b-41d4-a716-
446655440000/group-chatbots/?
page=1&pageSize=1&query=example&search=example"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-
41d4-a716-446655440000/groups/550e8400-e29b-41d4-a716-
446655440000/group-chatbots/?
page=1&pageSize=1&query=example&search=example", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response

Status Code: 200

Response Schema Example

```
{
  "count": integer
  "next"?: string (uri) // Optional
  "previous"?: string (uri) // Optional
  "results": [
    {
      "id": string (uuid)
      "group": string (uuid)
      "chatbot":
      {
        "id": string (uuid)
        "name": string // Chatbot name. In Agent mode it carries semantic meaning; in other modes it only distinguishes chatbots.
        "largeLanguageModel": string (uuid) // The large language model the chatbot uses to generate responses (including custom AI Gateway models configured by the organization); it can be omitted during creation only if the organization has set a default model in its AI assistant defaults
        "llm":  // The linked model's id, name, and retirement information, read directly from the FK; returned even if the organization has disabled the model
        {
          "id": string (uuid)
          "name": string
          "retiresAt": string (date) // The provider's retirement date; once reached, the daily scheduled task switches the assistant to the replacement and disables this model. null means no retirement is scheduled
          "replacement":  // The replacement model after retirement (id and name); null means none is specified and no automatic migration occurs on the retirement date
          {
            "id": string (uuid)
            "name": string
          }
        }
        "organizationEnforcedSettings": [ // Setting codes enforced for this assistant by the organization's AI assistant defaults (matching the keys in the AI assistant defaults API); these fields return the enforced values, and updates with different values are rejected (read-only; empty for official built-in Agents and MaiGPT)
          string
        ]
        "embeddingModel"?: string (uuid) // Embedding model used to
```

```
vectorize text; optional (Optional)
        "rerankerModel"?: string (uuid) // Model used for reranking;
optional (Optional)
        "instructions"?: string // Role instructions describing the
chatbot's role and behavior. (Optional)
        "knowledgeBases"?: [ // Knowledge bases the chatbot can access
(Optional)
          {
            "id": string (uuid)
            "name": string
          }
        ]
        "databases"?: [ // SQL databases the chatbot can access (for
Text-to-SQL) (Optional)
          {
            "id": string (uuid)
            "name": string
          }
        ]
        "updatedAt": string (timestamp)
        "organization"?: string (uuid) // The organization the chatbot
belongs to; if empty, this is a personal chatbot (Optional)
        "replyMode"?:  // Reply mode: standard or streaming responses

* `normal` - Normal
* `template` - Template
* `hybrid` - Hybrid
* `agent` - Agent (Optional)
        {
        }
        "template"?: string // Template used by Template and Hybrid
modes. (Optional)
        "unanswerableTemplate"?: string // Template used by Template and
Hybrid modes when the question cannot be answered. (Optional)
        "totalWordsCount"?: integer (int64) // Accumulated total word
count used. (Optional)
        "outputMode"?:  // Output mode: text, table, or custom format

* `text` - Text
* `json_schema` - JSON Schema (Optional)
        {
        }
        "rawOutputFormat"?: object // JSON schema definition for the
custom output format (Optional)
        "groups"?: [ // Groups the chatbot can access (Optional)
```

```
          {
            "id": string (uuid)
            "name": string
          }
        ]
        "tools"?: [ // Tools available to the chatbot (Optional)
          {
            "id": string (uuid)
            "name": string
            "description": string
            "displayName": string
            "toolType": string
          }
        ]
        "skills"?: [ // Skills associated with the chatbot (Optional)
          {
            "id": string (uuid)
            "name": string
            "description": string
          }
        ]
        "connectors"?: [ // Connectors associated with this chatbot,
gating per-contact OAuth authorization (Optional)
          {
            "id": string (uuid)
            "name": string
          }
        ]
        "agentMode"?:  // Agent mode: normal, SQL, or workflow mode

* `normal` - Normal
* `canvas` - Canvas
* `team` - Team (Optional)
        {
        }
        "numberOfRetrievedChunks"?: integer // Number of reference chunks
to retrieve; defaults to 12, minimum 1 (Optional)
        "defaultLabelRelations"?: object // Default assistant-level
knowledge base label filters, using the same format as
query_metadata.label_relations; null means no filtering. Applied as the
lowest-priority fallback only when the caller omits query_metadata.
(Optional)
        "useFullRetrievalRange"?: boolean // When enabled, ignores LLM
top_k truncation and returns the full reranker results (Optional)
        "enableEvaluation"?: boolean // Optional
```

```
        "enableInlineCitations"?: boolean // Enables inline citations,
inserting citation markers such as [1][2] into responses. (Optional)
        "enableCodeInterpreter"?: boolean // When enabled, provides the
Code Interpreter tool to run code in an isolated container. (Optional)
        "enableBrowserTool"?: boolean // Enable browser automation tool
for web tasks (Optional)
        "enableImageSearch"?: boolean // Provide the image_search tool
when any attached knowledge base uses a multimodal embedding model.
Disable to remove the tool entirely. (Optional)
        "enableClaudeStreamRetry"?: boolean // When a Claude streaming
call stalls (first-chunk or mid-stream), abort and re-issue the call once
in non-streaming mode. Mid-stream retries send a reset signal so the
client discards any partial output already rendered. Each retry incurs a
second billing for the same prompt. (Optional)
        "customMaxLlmOutputTokens"?: integer // Custom maximum number of
LLM output tokens, minimum 512 (Optional)
        "voiceConfig"?: { // Optional
        {
          "enabled"?: boolean // Whether this chatbot can be used as a
voice agent. Checked by every conversation platform (WebChat, SIP phone,
admin/marketplace voice test) instead of a per-platform toggle.
(Optional)
          "voiceAgentType"?: string (uuid) // Voice agent mode type.
(Optional)
          "sttProvider"?: string (uuid) // Speech-to-Text service
provider. (Optional)
          "sttConfig"?: object // STT configuration parameters (JSON).
(Optional)
          "ttsProvider"?: string (uuid) // Text-to-Speech service
provider. (Optional)
          "ttsConfig"?: object // TTS configuration parameters (JSON).
(Optional)
          "realtimeProvider"?: string (uuid) // Realtime end-to-end voice
model provider. (Optional)
          "realtimeConfig"?: object // Realtime configuration parameters
(JSON). (Optional)
          "realtimeInstructions"?: string // Prompt dedicated to the
realtime voice session; falls back to chatbot instructions when empty
(Optional)
          "turnHandling"?: object // Turn-taking and interruption
settings for the voice agent. (Optional)
          "enableVoiceReply"?: boolean // When disabled, the voice agent
replies in text only and does not speak (Optional)
        }
        }
```

```
        "thinkingConfig"?: object // Reasoning level: null (model
default) or {"reasoning_effort": "off|minimal|low|medium|high|xhigh|max"}
(Optional)
        "enableToolSearching"?: boolean // Legacy field; use
tool_loading_mode instead. Writing true is equivalent to
tool_loading_mode=search, and false to all; tool_loading_mode takes
precedence when both are provided. On read, returns whether the tool
loading mode is other than all. (Optional)
        "toolLoadingMode"?:  // Tool loading mode: auto (selected
automatically based on the number of available tools and the model for
the current turn), all (load all), or search (dynamic search). New
assistants default to auto; existing assistants without an explicit
setting return a value derived from the previous toggle (on → search, off
→ all).

* `auto` - Auto
* `all` - Load all
* `search` - Dynamic search (Optional)
        {
        }
        "maxAgentIterations"?: integer // Maximum number of iterations
for AgentWorkflow (1-100, default: 20) (Optional)
        "agentTimeoutSeconds"?: integer // Timeout in seconds for
AgentWorkflow execution (30-1200, default: 600) (Optional)
        "agentTimeoutMessage"?: string // Custom user-facing message
shown when AgentWorkflow times out (max 500 chars). Leave empty to use
the system default. (Optional)
        "requireTextWithFlexCards"?: boolean // When enabled, a turn that
would end with only Flex Message cards and no text for the user is re-
issued to the LLM once, asking it to write the text first and then send
the card. Each retry incurs a second billing for the same prompt.
(Optional)
        "isMultimodalLlm": boolean // Whether the chatbot LLM supports
multimodal (read-only)
        "enableSizeBasedToolResultTruncation"?: boolean // When enabled,
tool results exceeding the character threshold are kept as head+tail
(with the identifiers found in the cut part) when written to conversation
history; knowledge base, SQL and conversation search results keep their
100-character cut either way. Reduces memory bloat from large tool
outputs (code interpreter bash stdout, web search results, etc.).
(Optional)
        "toolResultMaxChars"?: integer // Character threshold for size-
based tool result truncation (500-50000). Only effective when
enable_size_based_tool_result_truncation is True. (Optional)
        "enableVectorMemory"?: boolean // When enabled, archived messages
```

```
are vectorized and processed by fact extraction for semantic retrieval
(existing behavior). When disabled, archived messages are discarded and
only the active chat history window is used for multi-turn context.
(Optional)
        "longTermMemoryTopK"?: integer // Number of long-term memory
nodes retrieved per search (similarity_top_k for vector retrieval);
defaults to 10, range 1–50 (Optional)
        "enableCrossConversationSearch"?: boolean // When enabled, the
conversation history tools also reach this contact's other conversations
in the same inbox, within the lookback window. When disabled, they only
reach the current conversation. (Optional)
        "crossConversationLookbackDays"?: integer // How far back cross-
conversation search may reach, measured from each conversation's last
message (1-365 days). Leave empty to fall back to 90 days. Only effective
when enable_cross_conversation_search is True. (Optional)
        "useGatewayFallback"?: boolean // When enabled, use the fallback
group instead of the single LLM (Optional)
        "gatewayFallbackGroup"?: string (uuid) // Optional
        "enableSearchMessagesTool"?: boolean // Allow the AI to search
past messages in the current conversation. (Optional)
        "enableGetMessageContextTool"?: boolean // Allow the AI to
retrieve messages surrounding a specific message for context. (Optional)
        "enableReadAttachmentFullTextTool"?: boolean // Allow the AI to
read the full text of plain-text attachments. AGENT mode only. (Optional)
        "enableParseAttachmentContentTool"?: boolean // Allow the AI to
parse PDF, Office, audio, and other attachments. AGENT mode only.
(Optional)
        "enableListAvailableParsersTool"?: boolean // Allow the AI to
list available parsers and their capabilities. AGENT mode only.
(Optional)
        "enableGetDownloadLinkTool"?: boolean // Allow the AI to generate
shareable download links for produced content. AGENT mode only.
(Optional)
        "isLocked": boolean // Locked instance: config follows the
official version; only the dedicated KB can be modified
        "sourceBuildInAgent": string (uuid) // Points to the official
Build-in Agent blueprint when instantiated by a rental
        "canUpdate": boolean // Return whether the current user can
update this resource.
        "canDelete": boolean // Return whether the current user can
delete this resource.
        "team":
        {
          "id": string (uuid)
          "name": string
```

```
        }
        "webChatIsActive"?: boolean // Optional, create only. Whether the
web widget channel starts active. Omitted or null: follows the
organization's default for new chatbot channels (inactive unless a
platform admin turned it on). Ignored on update; change an existing
channel from its channel settings instead. (Optional)
        "apiIsActive"?: boolean // Optional, create only. Whether the API
channel starts active. Omitted or null: follows the organization's
default for new chatbot channels (inactive unless a platform admin turned
it on). Ignored on update; change an existing channel from its channel
settings instead. The backstage (admin) channel always starts active and
cannot be set here. (Optional)
        "fileWorkspaceMode"?:  // File workspace mode in Work internal
conversations: none, bound or user_mount.

* `none` - None
* `bound` - Bound workspace
* `user_mount` - User mount (Optional)
        {
        }
        "fileWorkspaceFolder"?: string (uuid) // The bound workspace
(folder id); required when the mode is bound, cleared otherwise.
(Optional)
        "fileWorkspaceStatus": object // Read-only. {"folder": {"id",
"name"} | null, "state": "ok" | "missing" | "builder_lost_edit" | null}
        "fileWorkspaceAvailable": boolean // Read-only. Whether the
organization has the file library and this agent can configure a file
workspace.
      }
      "canRead"?: boolean // Optional
      "canUpdate"?: boolean // Optional
      "canDelete"?: boolean // Optional
      "createdAt": string (timestamp)
    }
  ]
}
```

Example response values

```
{
  "count": 123,
  "next": "http://api.example.org/accounts/?page=4",
  "previous": "http://api.example.org/accounts/?page=2",
  "results": [
```

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "group": "550e8400-e29b-41d4-a716-446655440000",
  "chatbot": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Response string",
    "largeLanguageModel": "550e8400-e29b-41d4-a716-446655440000",
    "llm": {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "Response string",
      "retiresAt": "Response string",
      "replacement": {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "name": "Response string"
      }
    },
    "organizationEnforcedSettings": [
      "Response string"
    ],
    "embeddingModel": "550e8400-e29b-41d4-a716-446655440000",
    "rerankerModel": "550e8400-e29b-41d4-a716-446655440000",
    "instructions": "Response string",
    "knowledgeBases": [
      {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "name": "Response string"
      }
    ],
    "databases": [
      {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "name": "Response string"
      }
    ],
    "updatedAt": "Response string",
    "organization": "550e8400-e29b-41d4-a716-446655440000",
    "replyMode": {},
    "template": "Response string",
    "unanswerableTemplate": "Response string",
    "totalWordsCount": 456,
    "outputMode": {},
    "rawOutputFormat": null,
    "groups": [
      {
        "id": "550e8400-e29b-41d4-a716-446655440000",
```

```
      "name": "Response string"
    }
  ],
  "tools": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "Response string",
      "description": "Response string",
      "displayName": "Response string",
      "toolType": "Response string"
    }
  ],
  "skills": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "Response string",
      "description": "Response string"
    }
  ],
  "connectors": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "Response string"
    }
  ],
  "agentMode": {},
  "numberOfRetrievedChunks": 456,
  "defaultLabelRelations": null,
  "useFullRetrievalRange": false,
  "enableEvaluation": false,
  "enableInlineCitations": false,
  "enableCodeInterpreter": false,
  "enableBrowserTool": false,
  "enableImageSearch": false,
  "enableClaudeStreamRetry": false,
  "customMaxLlmOutputTokens": 456,
  "voiceConfig": {
    "enabled": false,
    "voiceAgentType": "550e8400-e29b-41d4-a716-446655440000",
    "sttProvider": "550e8400-e29b-41d4-a716-446655440000",
    "sttConfig": null,
    "ttsProvider": "550e8400-e29b-41d4-a716-446655440000",
    "ttsConfig": null,
    "realtimeProvider": "550e8400-e29b-41d4-a716-446655440000",
    "realtimeConfig": null,
```

```
        "realtimeInstructions": "Response string",
        "turnHandling": null,
        "enableVoiceReply": false
      },
      "thinkingConfig": null,
      "enableToolSearching": false,
      "toolLoadingMode": {},
      "maxAgentIterations": 456,
      "agentTimeoutSeconds": 456,
      "agentTimeoutMessage": "Response string",
      "requireTextWithFlexCards": false,
      "isMultimodalLlm": false,
      "enableSizeBasedToolResultTruncation": false,
      "toolResultMaxChars": 456,
      "enableVectorMemory": false,
      "longTermMemoryTopK": 456,
      "enableCrossConversationSearch": false,
      "crossConversationLookbackDays": 456,
      "useGatewayFallback": false,
      "gatewayFallbackGroup": "550e8400-e29b-41d4-a716-446655440000",
      "enableSearchMessagesTool": false,
      "enableGetMessageContextTool": false,
      "enableReadAttachmentFullTextTool": false,
      "enableParseAttachmentContentTool": false,
      "enableListAvailableParsersTool": false,
      "enableGetDownloadLinkTool": false,
      "isLocked": false,
      "sourceBuildInAgent": "550e8400-e29b-41d4-a716-446655440000",
      "canUpdate": false,
      "canDelete": false,
      "team": {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "name": "Response string"
      },
      "webChatIsActive": false,
      "apiIsActive": false,
      "fileWorkspaceMode": {},
      "fileWorkspaceFolder": "550e8400-e29b-41d4-a716-446655440000",
      "fileWorkspaceStatus": {
        "name": "example.pdf",
        "content": "base64encoded_content",
        "contentType": "application/pdf"
      },
      "fileWorkspaceAvailable": false
    },
```

```
        "canRead": false,
        "canUpdate": false,
        "canDelete": false,
        "createdAt": "Response string"
      }
    ]
}
```


List Role Inboxes

GET `/api/v1/organizations/{organizationPk}/groups/{groupPk}/group-inboxes/`

Parameters

Parameter Name	Required	Type	Description
`groupPk`	V	string	
`organizationPk`	V	string	A UUID string identifying this organization ID
`channelType`	X	string	`line`: LINE ; `telegram`: Telegram ; `teams`: Teams ; `web`: Web ; `messenger`: Messenger ; `instagram`: Instagram ; `email`: Email ; `whatsapp`: WhatsApp ; `slack`: Slack ; `team_plus`: Team+ ; `lin...
`chatbot`	X	string	
`isActive`	X	boolean	
`page`	X	integer	A page number within the paginated result set.

`pageSize`	X	integer	Number of results to return per page.
`query`	X	string	
`search`	X	string	

Code Examples

Shell/Bash

```
# Example API call (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-41d4-a716-446655440000/groups/550e8400-e29b-41d4-a716-446655440000/group-inboxes/?channelType=email&chatbot=550e8400-e29b-41d4-a716-446655440000&isActive=true&page=1&pageSize=1&query=example&search=example"

  -H "Authorization: Api-Key YOUR_API_KEY"

# Make sure to replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/organizations/550e8400-
e29b-41d4-a716-446655440000/groups/550e8400-e29b-41d4-a716-
446655440000/group-inboxes/?channelType=email&chatbot=550e8400-e29b-
41d4-a716-
446655440000&isActive=true&page=1&pageSize=1&query=example&search=ex
ample", config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-41d4-a716-446655440000/groups/550e8400-e29b-41d4-a716-446655440000/group-inboxes/?channelType=email&chatbot=550e8400-e29b-41d4-a716-446655440000&isActive=true&page=1&pageSize=1&query=example&search=example"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-
41d4-a716-446655440000/groups/550e8400-e29b-41d4-a716-
446655440000/group-inboxes/?channelType=email&chatbot=550e8400-e29b-
41d4-a716-
446655440000&isActive=true&page=1&pageSize=1&query=example&search=ex
ample", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response Content

Status code: 200

Example Response Structure

```
{
  "count": integer
  "next"?: string (uri) // optional
  "previous"?: string (uri) // optional
  "results": [
    {
      "id": string (uuid)
      "group": string (uuid)
      "inbox":
      {
        "id": string (uuid)
        "channelType": string (enum: line, telegram, teams, web,
messenger, instagram, email, whatsapp, slack, team_plus, line_works,
viber) // * `line` - LINE
* `telegram` - Telegram
* `teams` - Teams
* `web` - Web
* `messenger` - Messenger
* `instagram` - Instagram
* `email` - Email
* `whatsapp` - WhatsApp
* `slack` - Slack
* `team_plus` - Team+
* `line_works` - LINE WORKS
* `viber` - Viber
        "name": string
        "unreadConversationsCount": integer
        "accessType": string
      }
      "canRead"?: boolean // optional
      "canUpdate"?: boolean // optional
      "canDelete"?: boolean // optional
      "canViewConversations"?: boolean // Whether group members can
browse all conversations of this inbox in the conversations page.
Independent from can_read, which controls using the inbox for chatting.
(optional)
      "createdAt": string (timestamp)
    }
  ]
}
```

Example Response Values

```
{
  "count": 123,
  "next": "http://api.example.org/accounts/?page=4",
  "previous": "http://api.example.org/accounts/?page=2",
  "results": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "group": "550e8400-e29b-41d4-a716-446655440000",
      "inbox": {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "channelType": "line",
        "name": "Example response string",
        "unreadConversationsCount": 456,
        "accessType": "Example response string"
      },
      "canRead": false,
      "canUpdate": false,
      "canDelete": false,
      "canViewConversations": false,
      "createdAt": "Example response string"
    }
  ]
}
```


List Role Knowledge Bases

`GET` `/api/v1/organizations/{organizationPk}/groups/{groupPk}/group-knowledge-bases/`

Parameters

Parameter Name	Required	Type	Description
`groupPk`	V	string	

`organizationPk`	V	string	A UUID string identifying this organization ID
`page`	X	integer	A page number within the paginated result set.
`pageSize`	X	integer	Number of results to return per page.
`query`	X	string	
`search`	X	string	

Code Examples

Shell/Bash

```
# Example API call (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/organizations/550e8400-
e29b-41d4-a716-446655440000/groups/550e8400-e29b-41d4-a716-
446655440000/group-knowledge-bases/?
page=1&pageSize=1&query=example&search=example"

  -H "Authorization: Api-Key YOUR_API_KEY"

# Make sure to replace YOUR_API_KEY and verify the request data
before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/organizations/550e8400-
e29b-41d4-a716-446655440000/groups/550e8400-e29b-41d4-a716-
446655440000/group-knowledge-bases/?
page=1&pageSize=1&query=example&search=example", config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-
41d4-a716-446655440000/groups/550e8400-e29b-41d4-a716-
446655440000/group-knowledge-bases/?
page=1&pageSize=1&query=example&search=example"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-
41d4-a716-446655440000/groups/550e8400-e29b-41d4-a716-
446655440000/group-knowledge-bases/?
page=1&pageSize=1&query=example&search=example", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response Content

Status code: 200

Example Response Structure

```
{
  "count": integer
  "next"?: string (uri) // optional
  "previous"?: string (uri) // optional
  "results": [
    {
      "id": string (uuid)
      "group": string (uuid)
      "knowledgeBase":
      {
        "id": string (uuid)
        "createdBy":
        {
          "id": string (uuid)
          "name": string
        }
        "organization"?: string (uuid) // optional
        "embeddingModel": string (uuid)
        "rerankerModel": string (uuid)
        "name": string
        "description"?: string // optional
        "numberOfRetrievedChunks"?: integer // Number of retrieved
reference chunks. Default is 12, minimum is 1 (optional)
        "enableHyde"?: boolean // Enable HyDE. Default is False
(optional)
        "similarityCutoff"?: number (double) // Similarity threshold.
Default is 0.0, range 0.0-1.0 (optional)
        "enableRerank"?: boolean // Whether to enable reranking. Default
is True (optional)
        "enableRrf"?: boolean // Enable Reciprocal Rank Fusion for hybrid
search. Disable this if using a custom Elasticsearch without enterprise
license. (optional)
        "vectorDatabaseType"?:  // Type of vector database: elasticsearch
or opensearch.

* `elasticsearch` - Elasticsearch
* `opensearch` - OpenSearch
* `oracle` - Oracle AI Database 26ai
* `synxdb` - SynxDB (optional)
        {
        }
        "vectorDatabaseUrl"?: string // Custom vector database endpoint
URL or Oracle DSN. For Elasticsearch/OpenSearch: URL format (e.g.,
"https://host:9200"). For Oracle: DSN format (e.g.,
```

```
"host:1521/service_name"). (optional)
        "vectorDatabaseApiKey"?: string // API Key for Elasticsearch. Not
used for OpenSearch. (optional)
        "opensearchUsername"?: string // Username for OpenSearch Basic
Auth. (optional)
        "opensearchPassword"?: string // Password for OpenSearch Basic
Auth. (optional)
        "oracleUser"?: string // Oracle database username. (optional)
        "oraclePassword"?: string // Oracle database password. (optional)
        "synxdbUser"?: string // SynxDB database username. (optional)
        "synxdbPassword"?: string // SynxDB database password. (optional)
        "labels": [
          {
            "id": string (uuid)
            "name": string
          }
        ]
        "chatbots"?: [ // optional
          {
            "id": string (uuid)
            "name": string
          }
        ]
        "groups"?: [ // List of groups that can access the knowledge base
(optional)
          {
            "id": string (uuid)
            "name": string
          }
        ]
        "filesCount": integer // Return count of KnowledgeBaseFile
excluding processed files, conversation attachments, and soft-deleted.
        "vectorStorageSize": integer
        "chunksCount": integer
        "canUpdate": boolean // Return whether the current user can
update this resource.
        "canDelete": boolean // Return whether the current user can
delete this resource.
        "createdAt": string (timestamp)
        "updatedAt": string (timestamp)
      }
      "canRead"?: boolean // optional
      "canUpdate"?: boolean // optional
      "canDelete"?: boolean // optional
      "createdAt": string (timestamp)
```

```
    }
  ]
}
```

Example Response Values

```
{
  "count": 123,
  "next": "http://api.example.org/accounts/?page=4",
  "previous": "http://api.example.org/accounts/?page=2",
  "results": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "group": "550e8400-e29b-41d4-a716-446655440000",
      "knowledgeBase": {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "createdBy": {
          "id": "550e8400-e29b-41d4-a716-446655440000",
          "name": "Example response string"
        },
        "organization": "550e8400-e29b-41d4-a716-446655440000",
        "embeddingModel": "550e8400-e29b-41d4-a716-446655440000",
        "rerankerModel": "550e8400-e29b-41d4-a716-446655440000",
        "name": "Example response string",
        "description": "Example response string",
        "numberOfRetrievedChunks": 456,
        "enableHyde": false,
        "similarityCutoff": 456,
        "enableRerank": false,
        "enableRrf": false,
        "vectorDatabaseType": {},
        "vectorDatabaseUrl": "Example response string",
        "vectorDatabaseApiKey": "Example response string",
        "opensearchUsername": "Example response string",
        "opensearchPassword": "Example response string",
        "oracleUser": "Example response string",
        "oraclePassword": "Example response string",
        "synxdbUser": "Example response string",
        "synxdbPassword": "Example response string",
        "labels": [
          {
            "id": "550e8400-e29b-41d4-a716-446655440000",
            "name": "Example response string"
          }
```

```
        ],
        "chatbots": [
          {
            "id": "550e8400-e29b-41d4-a716-446655440000",
            "name": "Example response string"
          }
        ],
        "groups": [
          {
            "id": "550e8400-e29b-41d4-a716-446655440000",
            "name": "Example response string"
          }
        ],
        "filesCount": 456,
        "vectorStorageSize": 456,
        "chunksCount": 456,
        "canUpdate": false,
        "canDelete": false,
        "createdAt": "Example response string",
        "updatedAt": "Example response string"
      },
      "canRead": false,
      "canUpdate": false,
      "canDelete": false,
      "createdAt": "Example response string"
    }
  ]
}
```


List Role Databases

`GET` `/api/v1/organizations/{organizationPk}/groups/{groupPk}/group-databases/`

Parameters

Parameter Name	Required	Type	Description
`groupPk`	V	string	
`organizationPk`	V	string	A UUID string identifying this organization ID
`page`	X	integer	A page number within the paginated result set.
`pageSize`	X	integer	Number of results to return per page.
`query`	X	string	
`search`	X	string	

Code Examples

Shell/Bash

```
# Example API call (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/organizations/550e8400-
e29b-41d4-a716-446655440000/groups/550e8400-e29b-41d4-a716-
446655440000/group-databases/?
page=1&pageSize=1&query=example&search=example"

  -H "Authorization: Api-Key YOUR_API_KEY"

# Make sure to replace YOUR_API_KEY and verify the request data
before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/organizations/550e8400-
e29b-41d4-a716-446655440000/groups/550e8400-e29b-41d4-a716-
446655440000/group-databases/?
page=1&pageSize=1&query=example&search=example", config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-
41d4-a716-446655440000/groups/550e8400-e29b-41d4-a716-
446655440000/group-databases/?
page=1&pageSize=1&query=example&search=example"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-
41d4-a716-446655440000/groups/550e8400-e29b-41d4-a716-
446655440000/group-databases/?
page=1&pageSize=1&query=example&search=example", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response Content

Status code: 200

Example Response Structure

```
{
  "count": integer
  "next"?: string (uri) // optional
  "previous"?: string (uri) // optional
  "results": [
    {
      "id": string (uuid)
      "group": string (uuid)
      "database":
      {
        "id": string (uuid)
        "name": string // Display name for this database connection
        "description": string // Description of the database and its
purpose
        "databaseType":  // Type of database: PostgreSQL, MySQL, MSSQL,
Oracle, SynxDB, or MaiAgent

* `postgresql` - PostgreSQL
* `mysql` - MySQL
* `maiagent` - MaiAgent
* `oracle` - Oracle
* `mssql` - MSSQL
* `synxdb` - SynxDB
        {
        }
        "includeTables": object // Optional list of tables to include.
Format: {"tables": ["table1", "table2"]}. For MaiAgent type, this is
auto-populated from uploaded files.
        "isActive": boolean // When disabled, this database will not be
used in Text-to-SQL queries
        "status":
        {
        }
        "deletedAt": string (timestamp)
        "tables": [
          {
            "id": string (uuid)
            "tableName": string // Name of the table in the database
            "sheetName": string // Name of the source worksheet/sheet
this table was created from. Empty for tables created before this field
was added.
            "description"?: string // Description of the table and its
data for better Text-to-SQL understanding (optional)
            "status":
```

```
            {
            }
            "errorMessage": string // Error details if table creation or
deletion failed
            "sourceFile":
            {
              "id": string (uuid)
              "name": string
              "isFromKnowledgeBase": boolean // Determine if the source
file originated from a knowledge base upload.

Returns True if the file was uploaded via knowledge base,
False if uploaded directly to the database.
            }
            "columns": [
              {
                "id": string (uuid)
                "columnName": string
                "columnType"?: string // Data type of the column (e.g.,
VARCHAR, INTEGER, TIMESTAMP) (optional)
                "description"?: string // Description of the column for
better Text-to-SQL understanding (optional)
                "isPrimaryKey"?: boolean // optional
                "isNullable"?: boolean // optional
                "createdAt": string (timestamp)
                "updatedAt": string (timestamp)
              }
            ]
            "createdAt": string (timestamp)
            "updatedAt": string (timestamp)
          }
        ]
        "chatbots": [
          {
            "id": string (uuid)
            "name": string
          }
        ]
        "groups": [
          {
            "id": string (uuid)
            "name": string
          }
        ]
        "createdAt": string (timestamp)
```

```
        "updatedAt": string (timestamp)
      }
      "canRead"?: boolean // optional
      "canUpdate"?: boolean // optional
      "canDelete"?: boolean // optional
      "createdAt": string (timestamp)
    }
  ]
}
```

Example Response Values

```
{
  "count": 123,
  "next": "http://api.example.org/accounts/?page=4",
  "previous": "http://api.example.org/accounts/?page=2",
  "results": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "group": "550e8400-e29b-41d4-a716-446655440000",
      "database": {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "name": "Example response string",
        "description": "Example response string",
        "databaseType": {},
        "includeTables": null,
        "isActive": false,
        "status": {},
        "deletedAt": "Example response string",
        "tables": [
          {
            "id": "550e8400-e29b-41d4-a716-446655440000",
            "tableName": "Example response string",
            "sheetName": "Example response string",
            "description": "Example response string",
            "status": {},
            "errorMessage": "Example response string",
            "sourceFile": {
              "id": "550e8400-e29b-41d4-a716-446655440000",
              "name": "Example response string",
              "isFromKnowledgeBase": false
            },
            "columns": [
              {
```

```
                "id": "550e8400-e29b-41d4-a716-446655440000",
                "columnName": "Example response string",
                "columnType": "Example response string",
                "description": "Example response string",
                "isPrimaryKey": false,
                "isNullable": false,
                "createdAt": "Example response string",
                "updatedAt": "Example response string"
              }
            ],
            "createdAt": "Example response string",
            "updatedAt": "Example response string"
          }
        ],
        "chatbots": [
          {
            "id": "550e8400-e29b-41d4-a716-446655440000",
            "name": "Example response string"
          }
        ],
        "groups": [
          {
            "id": "550e8400-e29b-41d4-a716-446655440000",
            "name": "Example response string"
          }
        ],
        "createdAt": "Example response string",
        "updatedAt": "Example response string"
      },
      "canRead": false,
      "canUpdate": false,
      "canDelete": false,
      "createdAt": "Example response string"
    }
  ]
}
```


Update a Role

PUT `/api/v1/organizations/{organizationPk}/groups/{id}`

Parameters

Parameter Name	Required	Type	Description
`id`	V	string	A UUID string identifying this Group.
`organizationPk`	V	string	A UUID string identifying this Organization ID

Request Body

Request Parameters

Field	Type	Required	Description
name	string	Yes	
organization	string (uuid)	No	
permissions	array[string]	Yes	
canCreateChatbot	boolean	No	
canCreateKnowledgeBase	boolean	No	
canCreateInbox	boolean	No	
canCreateDatabase	boolean	No	
canCreateTool	boolean	No	
canCreateAgentUiTool	boolean	No	
canCreateSkill	boolean	No	

Field	Type	Required	Description
maigptCanCodeInterpreter	boolean	No	Whether members of this role may use the code interpreter built-in tool in MaiGPT.
maigptCanRag	boolean	No	Whether members of this role may use the knowledge base RAG built-in tool in MaiGPT.
maigptCanDeepResearch	boolean	No	Whether members of this role may use Deep Research in MaiGPT. Deep Research reaches the public internet through its own built-in search, so a role that revokes the official web-search tools needs this...
maigptCanBrowserTool	boolean	No	Whether members of this role may use the browser built-in tool in MaiGPT.
maigptAllLlms	boolean	No	Whether members of this role may use every organization-available LLM in MaiGPT. Off = only the bound LLMs; an empty binding then means none.
maigptAllTools	boolean	No	Whether members of this role may call every official (global) tool in MaiGPT. Off = only the bound tools; an empty binding then means none.
maigptAllConnectors	boolean	No	Whether members of this role may call every official (global) MCP connector in MaiGPT. Off = only the bound connectors; an empty binding then means none.
maigptAllSkills	boolean	No	Whether members of this role may use every official (global) skill in MaiGPT. Off = only the

Field	Type	Required	Description
			bound skills; an empty binding then means none.
usageStatisticsScope	object	No	What this role's usage statistics permission shows: the whole organization, or only the AI assistants granted to the member's roles. A member with any organization-wide granting role sees the whole or...
allowedLlms	array[string]	No	
allowedTools	array[string]	No	
allowedConnectors	array[string]	No	
allowedSkills	array[string]	No	

Request Schema Example

```
{
  "name": string
  "organization"?: string (uuid) // Optional
  "permissions": [
    string (uuid)
  ]
  "canCreateChatbot"?: boolean // Optional
  "canCreateKnowledgeBase"?: boolean // Optional
  "canCreateInbox"?: boolean // Optional
  "canCreateDatabase"?: boolean // Optional
  "canCreateTool"?: boolean // Optional
  "canCreateAgentUiTool"?: boolean // Optional
  "canCreateSkill"?: boolean // Optional
  "maigptCanCodeInterpreter"?: boolean // Whether members of this role
may use the code interpreter built-in tool in MaiGPT. (Optional)
  "maigptCanRag"?: boolean // Whether members of this role may use the
knowledge base RAG built-in tool in MaiGPT. (Optional)
  "maigptCanDeepResearch"?: boolean // Whether members of this role may
use Deep Research in MaiGPT. Deep Research reaches the public internet
through its own built-in search, so a role that revokes the official web-
search tools needs this switch too. (Optional)
  "maigptCanBrowserTool"?: boolean // Whether members of this role may
```

```
use the browser built-in tool in MaiGPT. (Optional)
  "maigptAllLlms"?: boolean // Whether members of this role may use every
organization-available LLM in MaiGPT. Off = only the bound LLMs; an empty
binding then means none. (Optional)
  "maigptAllTools"?: boolean // Whether members of this role may call
every official (global) tool in MaiGPT. Off = only the bound tools; an
empty binding then means none. (Optional)
  "maigptAllConnectors"?: boolean // Whether members of this role may
call every official (global) MCP connector in MaiGPT. Off = only the
bound connectors; an empty binding then means none. (Optional)
  "maigptAllSkills"?: boolean // Whether members of this role may use
every official (global) skill in MaiGPT. Off = only the bound skills; an
empty binding then means none. (Optional)
  "usageStatisticsScope"?:  // What this role's usage statistics
permission shows: the whole organization, or only the AI assistants
granted to the member's roles. A member with any organization-wide
granting role sees the whole organization.

* `organization` - Organization-wide
* `accessible_chatbots` - Authorized AI assistants only (Optional)
  {
  }
  "allowedLlms"?: [ // Optional
    string (uuid)
  ]
  "allowedTools"?: [ // Optional
    string (uuid)
  ]
  "allowedConnectors"?: [ // Optional
    string (uuid)
  ]
  "allowedSkills"?: [ // Optional
    string (uuid)
  ]
}
```

Example Request Values

```
{
  "name": "Example name",
  "organization": "550e8400-e29b-41d4-a716-446655440000",
  "permissions": [
    "550e8400-e29b-41d4-a716-446655440000"
  ],
```

```
  "canCreateChatbot": true,
  "canCreateKnowledgeBase": true,
  "canCreateInbox": true,
  "canCreateDatabase": true,
  "canCreateTool": true,
  "canCreateAgentUiTool": true,
  "canCreateSkill": true,
  "maigptCanCodeInterpreter": true,
  "maigptCanRag": true,
  "maigptCanDeepResearch": true,
  "maigptCanBrowserTool": true,
  "maigptAllLlms": true,
  "maigptAllTools": true,
  "maigptAllConnectors": true,
  "maigptAllSkills": true,
  "usageStatisticsScope": {},
  "allowedLlms": [
    "550e8400-e29b-41d4-a716-446655440000"
  ],
  "allowedTools": [
    "550e8400-e29b-41d4-a716-446655440000"
  ],
  "allowedConnectors": [
    "550e8400-e29b-41d4-a716-446655440000"
  ],
  "allowedSkills": [
    "550e8400-e29b-41d4-a716-446655440000"
  ]
}
```


Code Examples

Shell/Bash

```
# Example API call (Shell)
curl -X PUT "https://api.maiagent.ai/api/v1/organizations/550e8400-
e29b-41d4-a716-446655440000/groups/550e8400-e29b-41d4-a716-
446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "name": "Example name",
    "organization": "550e8400-e29b-41d4-a716-446655440000",
    "permissions": [
      "550e8400-e29b-41d4-a716-446655440000"
    ],
    "canCreateChatbot": true,
    "canCreateKnowledgeBase": true,
    "canCreateInbox": true,
    "canCreateDatabase": true,
    "canCreateTool": true,
    "canCreateAgentUiTool": true,
    "canCreateSkill": true,
    "maigptCanCodeInterpreter": true,
    "maigptCanRag": true,
    "maigptCanDeepResearch": true,
    "maigptCanBrowserTool": true,
    "maigptAllLlms": true,
    "maigptAllTools": true,
    "maigptAllConnectors": true,
    "maigptAllSkills": true,
    "usageStatisticsScope": {},
    "allowedLlms": [
      "550e8400-e29b-41d4-a716-446655440000"
    ],
    "allowedTools": [
      "550e8400-e29b-41d4-a716-446655440000"
    ],
    "allowedConnectors": [
      "550e8400-e29b-41d4-a716-446655440000"
    ],
```

```
    "allowedSkills": [
      "550e8400-e29b-41d4-a716-446655440000"
    ]
  }'

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// Request Body (payload)
const data = {
    "name": "Example name",
    "organization": "550e8400-e29b-41d4-a716-446655440000",
    "permissions": [
      "550e8400-e29b-41d4-a716-446655440000"
    ],
    "canCreateChatbot": true,
    "canCreateKnowledgeBase": true,
    "canCreateInbox": true,
    "canCreateDatabase": true,
    "canCreateTool": true,
    "canCreateAgentUiTool": true,
    "canCreateSkill": true,
    "maigptCanCodeInterpreter": true,
    "maigptCanRag": true,
    "maigptCanDeepResearch": true,
    "maigptCanBrowserTool": true,
    "maigptAllLlms": true,
    "maigptAllTools": true,
    "maigptAllConnectors": true,
    "maigptAllSkills": true,
    "usageStatisticsScope": {},
    "allowedLlms": [
      "550e8400-e29b-41d4-a716-446655440000"
    ],
    "allowedTools": [
      "550e8400-e29b-41d4-a716-446655440000"
    ],
    "allowedConnectors": [
```

```
      "550e8400-e29b-41d4-a716-446655440000"
    ],
    "allowedSkills": [
      "550e8400-e29b-41d4-a716-446655440000"
    ]
  };

axios.put("https://api.maiagent.ai/api/v1/organizations/550e8400-
e29b-41d4-a716-446655440000/groups/550e8400-e29b-41d4-a716-
446655440000/", data, config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-
41d4-a716-446655440000/groups/550e8400-e29b-41d4-a716-446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# Request Body (payload)
data = {
    "name": "Example name",
    "organization": "550e8400-e29b-41d4-a716-446655440000",
    "permissions": [
        "550e8400-e29b-41d4-a716-446655440000"
    ],
    "canCreateChatbot": True,
    "canCreateKnowledgeBase": True,
    "canCreateInbox": True,
    "canCreateDatabase": True,
    "canCreateTool": True,
    "canCreateAgentUiTool": True,
    "canCreateSkill": True,
    "maigptCanCodeInterpreter": True,
    "maigptCanRag": True,
    "maigptCanDeepResearch": True,
    "maigptCanBrowserTool": True,
    "maigptAllLlms": True,
    "maigptAllTools": True,
    "maigptAllConnectors": True,
    "maigptAllSkills": True,
    "usageStatisticsScope": {},
    "allowedLlms": [
        "550e8400-e29b-41d4-a716-446655440000"
    ],
    "allowedTools": [
        "550e8400-e29b-41d4-a716-446655440000"
    ],
    "allowedConnectors": [
        "550e8400-e29b-41d4-a716-446655440000"
```

```
    ],
    "allowedSkills": [
        "550e8400-e29b-41d4-a716-446655440000"
    ]
}

response = requests.put(url, json=data, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>put("https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-
41d4-a716-446655440000/groups/550e8400-e29b-41d4-a716-
446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'name' => 'Example name',
            'organization' => '550e8400-e29b-41d4-a716-
446655440000',
            'permissions' => [
                '550e8400-e29b-41d4-a716-446655440000'
            ],
            'canCreateChatbot' => true,
            'canCreateKnowledgeBase' => true,
            'canCreateInbox' => true,
            'canCreateDatabase' => true,
            'canCreateTool' => true,
            'canCreateAgentUiTool' => true,
            'canCreateSkill' => true,
            'maigptCanCodeInterpreter' => true,
            'maigptCanRag' => true,
            'maigptCanDeepResearch' => true,
            'maigptCanBrowserTool' => true,
            'maigptAllLlms' => true,
            'maigptAllTools' => true,
            'maigptAllConnectors' => true,
            'maigptAllSkills' => true,
            'usageStatisticsScope' => new \stdClass(),
            'allowedLlms' => [
                '550e8400-e29b-41d4-a716-446655440000'
            ],
```

```
                'allowedTools' => [
                    '550e8400-e29b-41d4-a716-446655440000'
                ],
                'allowedConnectors' => [
                    '550e8400-e29b-41d4-a716-446655440000'
                ],
                'allowedSkills' => [
                    '550e8400-e29b-41d4-a716-446655440000'
                ]
            ]
        ]);

        $data = json_decode($response->getBody(), true);
        echo "Response received successfully:\n";
        print_r($data);
    } catch (Exception $e) {
        echo 'Request error: ' . $e->getMessage();
    }
    ?>
```

Response Body

Status Code: 200

Response Schema Example

```
{
  "id": string (uuid)
  "name": string
  "type":
  {
  }
  "permissions": [
    object
  ]
  "membersPreview": [
    string
```

```
  ]
  "membersCount": integer // Returns the number of remaining members
(after subtracting the 3 shown in the list), for the frontend +N badge

Unlike resource counts:
<ul>
  <li>members_count: Returns total - 3 (for the +N badge); None indicates
a total <= 3</li>
  <li>chatbots_count/knowledge_bases_count/inboxes_count: Returns the
total count</li>
</ul>
  "chatbotsCount": integer
  "chatbotsPreview": [
    string
  ]
  "knowledgeBasesCount": integer
  "knowledgeBasesPreview": [
    string
  ]
  "inboxesCount": integer
  "inboxesPreview": [
    string
  ]
  "databasesCount": integer
  "databasesPreview": [
    string
  ]
  "canCreateChatbot"?: boolean // Optional
  "canCreateKnowledgeBase"?: boolean // Optional
  "canCreateInbox"?: boolean // Optional
  "canCreateDatabase"?: boolean // Optional
  "canCreateTool"?: boolean // Optional
  "canCreateAgentUiTool"?: boolean // Optional
  "canCreateSkill"?: boolean // Optional
  "maigptCanCodeInterpreter"?: boolean // Whether members of this role
may use the code interpreter built-in tool in MaiGPT. (Optional)
  "maigptCanRag"?: boolean // Whether members of this role may use the
knowledge base RAG built-in tool in MaiGPT. (Optional)
  "maigptCanDeepResearch"?: boolean // Whether members of this role may
use Deep Research in MaiGPT. Deep Research reaches the public internet
through its own built-in search, so a role that revokes the official web-
search tools needs this switch too. (Optional)
  "maigptCanBrowserTool"?: boolean // Whether members of this role may
use the browser built-in tool in MaiGPT. (Optional)
  "maigptAllLlms"?: boolean // Whether members of this role may use every
```

```
organization-available LLM in MaiGPT. Off = only the bound LLMs; an empty
binding then means none. (Optional)
  "maigptAllTools"?: boolean // Whether members of this role may call
every official (global) tool in MaiGPT. Off = only the bound tools; an
empty binding then means none. (Optional)
  "maigptAllConnectors"?: boolean // Whether members of this role may
call every official (global) MCP connector in MaiGPT. Off = only the
bound connectors; an empty binding then means none. (Optional)
  "maigptAllSkills"?: boolean // Whether members of this role may use
every official (global) skill in MaiGPT. Off = only the bound skills; an
empty binding then means none. (Optional)
  "usageStatisticsScope"?:  // What this role's usage statistics
permission shows: the whole organization, or only the AI assistants
granted to the member's roles. A member with any organization-wide
granting role sees the whole organization.

* `organization` - Organization-wide
* `accessible_chatbots` - Authorized AI assistants only (Optional)
  {
  }
  "createdAt": string (timestamp)
}
```

Example Response Values

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "name": "Response string",
  "type": {},
  "permissions": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "Example response name",
      "description": "Example response description"
    }
  ],
  "membersPreview": [
    "Response string"
  ],
  "membersCount": 456,
  "chatbotsCount": 456,
  "chatbotsPreview": [
    "Response string"
  ],
```

```
  "knowledgeBasesCount": 456,
  "knowledgeBasesPreview": [
    "Response string"
  ],
  "inboxesCount": 456,
  "inboxesPreview": [
    "Response string"
  ],
  "databasesCount": 456,
  "databasesPreview": [
    "Response string"
  ],
  "canCreateChatbot": false,
  "canCreateKnowledgeBase": false,
  "canCreateInbox": false,
  "canCreateDatabase": false,
  "canCreateTool": false,
  "canCreateAgentUiTool": false,
  "canCreateSkill": false,
  "maigptCanCodeInterpreter": false,
  "maigptCanRag": false,
  "maigptCanDeepResearch": false,
  "maigptCanBrowserTool": false,
  "maigptAllLlms": false,
  "maigptAllTools": false,
  "maigptAllConnectors": false,
  "maigptAllSkills": false,
  "usageStatisticsScope": {},
  "createdAt": "Response string"
}
```


Partially Update a Role

PATCH `/api/v1/organizations/{organizationPk}/groups/{id}`

Parameters

Parameter Name	Required	Type	Description
`id`	V	string	A UUID string identifying this Group.
`organizationPk`	V	string	A UUID string identifying this Organization ID

Request Body

Request Parameters

Field	Type	Required	Description
name	string	No	
organization	string (uuid)	No	
permissions	array[string]	No	
canCreateChatbot	boolean	No	
canCreateKnowledgeBase	boolean	No	
canCreateInbox	boolean	No	
canCreateDatabase	boolean	No	
canCreateTool	boolean	No	
canCreateAgentUiTool	boolean	No	
canCreateSkill	boolean	No	
maigptCanCodeInterpreter	boolean	No	Whether members of this role may use the code interpreter built-in tool in MaiGPT.
maigptCanRag	boolean	No	Whether members of this role may use the knowledge base RAG built-in tool in MaiGPT.
maigptCanDeepResearch	boolean	No	Whether members of this role may use Deep Research in MaiGPT. Deep Research

Field	Type	Required	Description
			reaches the public internet through its own built-in search, so a role that revokes the official web-search tools needs this...
maigptCanBrowserTool	boolean	No	Whether members of this role may use the browser built-in tool in MaiGPT.
maigptAllLlms	boolean	No	Whether members of this role may use every organization-available LLM in MaiGPT. Off = only the bound LLMs; an empty binding then means none.
maigptAllTools	boolean	No	Whether members of this role may call every official (global) tool in MaiGPT. Off = only the bound tools; an empty binding then means none.
maigptAllConnectors	boolean	No	Whether members of this role may call every official (global) MCP connector in MaiGPT. Off = only the bound connectors; an empty binding then means none.
maigptAllSkills	boolean	No	Whether members of this role may use every official (global) skill in MaiGPT. Off = only the bound skills; an empty binding then means none.
usageStatisticsScope	object	No	What this role's usage statistics permission shows: the whole organization, or only the AI assistants granted to the member's roles. A member with any organization-wide granting role sees the whole or...

Field	Type	Required	Description
allowedLlms	array[string]	No	
allowedTools	array[string]	No	
allowedConnectors	array[string]	No	
allowedSkills	array[string]	No	

Request Schema Example

```
{
  "name"?: string // Optional
  "organization"?: string (uuid) // Optional
  "permissions"?: [ // Optional
    string (uuid)
  ]
  "canCreateChatbot"?: boolean // Optional
  "canCreateKnowledgeBase"?: boolean // Optional
  "canCreateInbox"?: boolean // Optional
  "canCreateDatabase"?: boolean // Optional
  "canCreateTool"?: boolean // Optional
  "canCreateAgentUiTool"?: boolean // Optional
  "canCreateSkill"?: boolean // Optional
  "maigptCanCodeInterpreter"?: boolean // Whether members of this role
may use the code interpreter built-in tool in MaiGPT. (Optional)
  "maigptCanRag"?: boolean // Whether members of this role may use the
knowledge base RAG built-in tool in MaiGPT. (Optional)
  "maigptCanDeepResearch"?: boolean // Whether members of this role may
use Deep Research in MaiGPT. Deep Research reaches the public internet
through its own built-in search, so a role that revokes the official web-
search tools needs this switch too. (Optional)
  "maigptCanBrowserTool"?: boolean // Whether members of this role may
use the browser built-in tool in MaiGPT. (Optional)
  "maigptAllLlms"?: boolean // Whether members of this role may use every
organization-available LLM in MaiGPT. Off = only the bound LLMs; an empty
binding then means none. (Optional)
  "maigptAllTools"?: boolean // Whether members of this role may call
every official (global) tool in MaiGPT. Off = only the bound tools; an
empty binding then means none. (Optional)
  "maigptAllConnectors"?: boolean // Whether members of this role may
call every official (global) MCP connector in MaiGPT. Off = only the
bound connectors; an empty binding then means none. (Optional)
  "maigptAllSkills"?: boolean // Whether members of this role may use
```

```
every official (global) skill in MaiGPT. Off = only the bound skills; an
empty binding then means none. (Optional)
  "usageStatisticsScope"?:  // What this role's usage statistics
permission shows: the whole organization, or only the AI assistants
granted to the member's roles. A member with any organization-wide
granting role sees the whole organization.

* `organization` - Organization-wide
* `accessible_chatbots` - Authorized AI assistants only (Optional)
  {
  }
  "allowedLlms"?: [ // Optional
    string (uuid)
  ]
  "allowedTools"?: [ // Optional
    string (uuid)
  ]
  "allowedConnectors"?: [ // Optional
    string (uuid)
  ]
  "allowedSkills"?: [ // Optional
    string (uuid)
  ]
}
```

Example Request Values

```
{
  "name": "Example name",
  "organization": "550e8400-e29b-41d4-a716-446655440000",
  "permissions": [
    "550e8400-e29b-41d4-a716-446655440000"
  ],
  "canCreateChatbot": true,
  "canCreateKnowledgeBase": true,
  "canCreateInbox": true,
  "canCreateDatabase": true,
  "canCreateTool": true,
  "canCreateAgentUiTool": true,
  "canCreateSkill": true,
  "maigptCanCodeInterpreter": true,
  "maigptCanRag": true,
  "maigptCanDeepResearch": true,
  "maigptCanBrowserTool": true,
```

```
  "maigptAllLlms": true,
  "maigptAllTools": true,
  "maigptAllConnectors": true,
  "maigptAllSkills": true,
  "usageStatisticsScope": {},
  "allowedLlms": [
    "550e8400-e29b-41d4-a716-446655440000"
  ],
  "allowedTools": [
    "550e8400-e29b-41d4-a716-446655440000"
  ],
  "allowedConnectors": [
    "550e8400-e29b-41d4-a716-446655440000"
  ],
  "allowedSkills": [
    "550e8400-e29b-41d4-a716-446655440000"
  ]
}
```


Code Examples

Shell/Bash

```
# API call example (Shell)
curl -X PATCH
"https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-41d4-
a716-446655440000/groups/550e8400-e29b-41d4-a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "name": "Example name",
    "organization": "550e8400-e29b-41d4-a716-446655440000",
    "permissions": [
      "550e8400-e29b-41d4-a716-446655440000"
    ],
    "canCreateChatbot": true,
    "canCreateKnowledgeBase": true,
    "canCreateInbox": true,
    "canCreateDatabase": true,
    "canCreateTool": true,
    "canCreateAgentUiTool": true,
    "canCreateSkill": true,
    "maigptCanCodeInterpreter": true,
    "maigptCanRag": true,
    "maigptCanDeepResearch": true,
    "maigptCanBrowserTool": true,
    "maigptAllLlms": true,
    "maigptAllTools": true,
    "maigptAllConnectors": true,
    "maigptAllSkills": true,
    "usageStatisticsScope": {},
    "allowedLlms": [
      "550e8400-e29b-41d4-a716-446655440000"
    ],
    "allowedTools": [
      "550e8400-e29b-41d4-a716-446655440000"
    ],
    "allowedConnectors": [
      "550e8400-e29b-41d4-a716-446655440000"
    ],
```

```
    "allowedSkills": [
      "550e8400-e29b-41d4-a716-446655440000"
    ]
  }'

# Make sure to replace YOUR_API_KEY and verify the request data
before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// Request Body (payload)
const data = {
    "name": "Example name",
    "organization": "550e8400-e29b-41d4-a716-446655440000",
    "permissions": [
      "550e8400-e29b-41d4-a716-446655440000"
    ],
    "canCreateChatbot": true,
    "canCreateKnowledgeBase": true,
    "canCreateInbox": true,
    "canCreateDatabase": true,
    "canCreateTool": true,
    "canCreateAgentUiTool": true,
    "canCreateSkill": true,
    "maigptCanCodeInterpreter": true,
    "maigptCanRag": true,
    "maigptCanDeepResearch": true,
    "maigptCanBrowserTool": true,
    "maigptAllLlms": true,
    "maigptAllTools": true,
    "maigptAllConnectors": true,
    "maigptAllSkills": true,
    "usageStatisticsScope": {},
    "allowedLlms": [
      "550e8400-e29b-41d4-a716-446655440000"
    ],
    "allowedTools": [
      "550e8400-e29b-41d4-a716-446655440000"
    ],
    "allowedConnectors": [
```

```
      "550e8400-e29b-41d4-a716-446655440000"
    ],
    "allowedSkills": [
      "550e8400-e29b-41d4-a716-446655440000"
    ]
  };

axios.patch("https://api.maiagent.ai/api/v1/organizations/550e8400-
e29b-41d4-a716-446655440000/groups/550e8400-e29b-41d4-a716-
446655440000/", data, config)
  .then(response => {
    console.log('Successfully retrieved the response:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-
41d4-a716-446655440000/groups/550e8400-e29b-41d4-a716-446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# Request Body (payload)
data = {
    "name": "Example name",
    "organization": "550e8400-e29b-41d4-a716-446655440000",
    "permissions": [
        "550e8400-e29b-41d4-a716-446655440000"
    ],
    "canCreateChatbot": True,
    "canCreateKnowledgeBase": True,
    "canCreateInbox": True,
    "canCreateDatabase": True,
    "canCreateTool": True,
    "canCreateAgentUiTool": True,
    "canCreateSkill": True,
    "maigptCanCodeInterpreter": True,
    "maigptCanRag": True,
    "maigptCanDeepResearch": True,
    "maigptCanBrowserTool": True,
    "maigptAllLlms": True,
    "maigptAllTools": True,
    "maigptAllConnectors": True,
    "maigptAllSkills": True,
    "usageStatisticsScope": {},
    "allowedLlms": [
        "550e8400-e29b-41d4-a716-446655440000"
    ],
    "allowedTools": [
        "550e8400-e29b-41d4-a716-446655440000"
    ],
    "allowedConnectors": [
        "550e8400-e29b-41d4-a716-446655440000"
```

```
    ],
    "allowedSkills": [
        "550e8400-e29b-41d4-a716-446655440000"
    ]
}

response = requests.patch(url, json=data, headers=headers)
try:
    print("Successfully retrieved the response:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>patch("https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-
41d4-a716-446655440000/groups/550e8400-e29b-41d4-a716-
446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'name' => 'Example name',
            'organization' => '550e8400-e29b-41d4-a716-
446655440000',
            'permissions' => [
                '550e8400-e29b-41d4-a716-446655440000'
            ],
            'canCreateChatbot' => true,
            'canCreateKnowledgeBase' => true,
            'canCreateInbox' => true,
            'canCreateDatabase' => true,
            'canCreateTool' => true,
            'canCreateAgentUiTool' => true,
            'canCreateSkill' => true,
            'maigptCanCodeInterpreter' => true,
            'maigptCanRag' => true,
            'maigptCanDeepResearch' => true,
            'maigptCanBrowserTool' => true,
            'maigptAllLlms' => true,
            'maigptAllTools' => true,
            'maigptAllConnectors' => true,
            'maigptAllSkills' => true,
            'usageStatisticsScope' => new \stdClass(),
            'allowedLlms' => [
                '550e8400-e29b-41d4-a716-446655440000'
            ],
```

```
                'allowedTools' => [
                    '550e8400-e29b-41d4-a716-446655440000'
                ],
                'allowedConnectors' => [
                    '550e8400-e29b-41d4-a716-446655440000'
                ],
                'allowedSkills' => [
                    '550e8400-e29b-41d4-a716-446655440000'
                ]
            ]
        ]);

        $data = json_decode($response->getBody(), true);
        echo "Successfully retrieved the response:\n";
        print_r($data);
    } catch (Exception $e) {
        echo 'Request error: ' . $e->getMessage();
    }
    ?>
```

Response Body

Status Code: 200

Response Schema Example

```
{
  "id": string (uuid)
  "name": string
  "type":
  {
  }
  "permissions": [
    object
  ]
  "membersPreview": [
    string
```

```
  ]
  "membersCount": integer // Returns the remaining member count (after
deducting the 3 shown in the list), used for the frontend +N badge
display

Unlike the resource counts:
<ul>
  <li>members_count: returns total - 3 (used for the +N badge); None
means the total is <= 3</li>
  <li>chatbots_count/knowledge_bases_count/inboxes_count: returns the
total count</li>
</ul>
  "chatbotsCount": integer
  "chatbotsPreview": [
    string
  ]
  "knowledgeBasesCount": integer
  "knowledgeBasesPreview": [
    string
  ]
  "inboxesCount": integer
  "inboxesPreview": [
    string
  ]
  "databasesCount": integer
  "databasesPreview": [
    string
  ]
  "canCreateChatbot"?: boolean // Optional
  "canCreateKnowledgeBase"?: boolean // Optional
  "canCreateInbox"?: boolean // Optional
  "canCreateDatabase"?: boolean // Optional
  "canCreateTool"?: boolean // Optional
  "canCreateAgentUiTool"?: boolean // Optional
  "canCreateSkill"?: boolean // Optional
  "maigptCanCodeInterpreter"?: boolean // Whether members of this role
may use the code interpreter built-in tool in MaiGPT. (Optional)
  "maigptCanRag"?: boolean // Whether members of this role may use the
knowledge base RAG built-in tool in MaiGPT. (Optional)
  "maigptCanDeepResearch"?: boolean // Whether members of this role may
use Deep Research in MaiGPT. Deep Research reaches the public internet
through its own built-in search, so a role that revokes the official web-
search tools needs this switch too. (Optional)
  "maigptCanBrowserTool"?: boolean // Whether members of this role may
use the browser built-in tool in MaiGPT. (Optional)
```

```
  "maigptAllLlms"?: boolean // Whether members of this role may use every organization-available LLM in MaiGPT. Off = only the bound LLMs; an empty binding then means none. (Optional)
  "maigptAllTools"?: boolean // Whether members of this role may call every official (global) tool in MaiGPT. Off = only the bound tools; an empty binding then means none. (Optional)
  "maigptAllConnectors"?: boolean // Whether members of this role may call every official (global) MCP connector in MaiGPT. Off = only the bound connectors; an empty binding then means none. (Optional)
  "maigptAllSkills"?: boolean // Whether members of this role may use every official (global) skill in MaiGPT. Off = only the bound skills; an empty binding then means none. (Optional)
  "usageStatisticsScope"?:  // What this role's usage statistics permission shows: the whole organization, or only the AI assistants granted to the member's roles. A member with any organization-wide granting role sees the whole organization.

* `organization` - Organization-wide
* `accessible_chatbots` - Authorized AI assistants only (Optional)
  {
  }
  "createdAt": string (timestamp)
}
```

Example Response Values

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "name": "Response string",
  "type": {},
  "permissions": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "Response example name",
      "description": "Response example description"
    }
  ],
  "membersPreview": [
    "Response string"
  ],
  "membersCount": 456,
  "chatbotsCount": 456,
  "chatbotsPreview": [
    "Response string"
```

```
  ],
  "knowledgeBasesCount": 456,
  "knowledgeBasesPreview": [
    "Response string"
  ],
  "inboxesCount": 456,
  "inboxesPreview": [
    "Response string"
  ],
  "databasesCount": 456,
  "databasesPreview": [
    "Response string"
  ],
  "canCreateChatbot": false,
  "canCreateKnowledgeBase": false,
  "canCreateInbox": false,
  "canCreateDatabase": false,
  "canCreateTool": false,
  "canCreateAgentUiTool": false,
  "canCreateSkill": false,
  "maigptCanCodeInterpreter": false,
  "maigptCanRag": false,
  "maigptCanDeepResearch": false,
  "maigptCanBrowserTool": false,
  "maigptAllLlms": false,
  "maigptAllTools": false,
  "maigptAllConnectors": false,
  "maigptAllSkills": false,
  "usageStatisticsScope": {},
  "createdAt": "Response string"
}
```


Delete Role

DELETE `/api/v1/organizations/{organizationPk}/groups/{id}`

Parameters

Parameter	Required	Type	Description
`id`	V	string	A UUID string identifying this Group.
`organizationPk`	V	string	A UUID string identifying this Organization ID

Code Examples

Shell/Bash

```
# Example API call (Shell)
curl -X DELETE
"https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-41d4-
a716-446655440000/groups/550e8400-e29b-41d4-a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# Make sure to replace YOUR_API_KEY and verify the request data
before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

// Request payload
const data = null;

axios.delete("https://api.maiagent.ai/api/v1/organizations/550e8400-
e29b-41d4-a716-446655440000/groups/550e8400-e29b-41d4-a716-
446655440000/", data, config)
  .then(response => {
    console.log('Successfully received response:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-
41d4-a716-446655440000/groups/550e8400-e29b-41d4-a716-446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.delete(url, headers=headers)
try:
    print("Successfully received response:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>delete("https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-
41d4-a716-446655440000/groups/550e8400-e29b-41d4-a716-
446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Successfully received response:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response

Status Code	Description
204	No response body

Remove Role Member

DELETE `/api/v1/organizations/{organizationPk}/groups/{groupPk}/group-members/{id}`

Parameters

Parameter	Required	Type	Description
`groupPk`	V	string	
`id`	V	string	A UUID string identifying this Group Member.
`organizationPk`	V	string	A UUID string identifying this Organization ID

Code Examples

Shell/Bash

```
# Example API call (Shell)
curl -X DELETE
"https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-41d4-
a716-446655440000/groups/550e8400-e29b-41d4-a716-446655440000/group-
members/550e8400-e29b-41d4-a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# Make sure to replace YOUR_API_KEY and verify the request data
before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

// Request payload
const data = null;

axios.delete("https://api.maiagent.ai/api/v1/organizations/550e8400-
e29b-41d4-a716-446655440000/groups/550e8400-e29b-41d4-a716-
446655440000/group-members/550e8400-e29b-41d4-a716-446655440000/",
data, config)
  .then(response => {
    console.log('Successfully received response:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-
41d4-a716-446655440000/groups/550e8400-e29b-41d4-a716-
446655440000/group-members/550e8400-e29b-41d4-a716-446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.delete(url, headers=headers)
try:
    print("Successfully received response:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>delete("https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-
41d4-a716-446655440000/groups/550e8400-e29b-41d4-a716-
446655440000/group-members/550e8400-e29b-41d4-a716-446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Successfully received response:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response

Status Code	Description
204	No response body

Remove AI Assistant from Role

`DELETE` `/api/v1/organizations/{organizationPk}/groups/{groupPk}/group-chatbots/{id}`

Parameters

Parameter	Required	Type	Description
`groupPk`	V	string	
`id`	V	string	A UUID string identifying this Group Chatbot.
`organizationPk`	V	string	A UUID string identifying this Organization ID

Code Examples

Shell/Bash

```
# Example API call (Shell)
curl -X DELETE
"https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-41d4-
a716-446655440000/groups/550e8400-e29b-41d4-a716-446655440000/group-
chatbots/550e8400-e29b-41d4-a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# Make sure to replace YOUR_API_KEY and verify the request data
before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

// Request payload
const data = null;

axios.delete("https://api.maiagent.ai/api/v1/organizations/550e8400-
e29b-41d4-a716-446655440000/groups/550e8400-e29b-41d4-a716-
446655440000/group-chatbots/550e8400-e29b-41d4-a716-446655440000/",
data, config)
  .then(response => {
    console.log('Successfully received response:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-
41d4-a716-446655440000/groups/550e8400-e29b-41d4-a716-
446655440000/group-chatbots/550e8400-e29b-41d4-a716-446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.delete(url, headers=headers)
try:
    print("Successfully received response:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>delete("https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-
41d4-a716-446655440000/groups/550e8400-e29b-41d4-a716-
446655440000/group-chatbots/550e8400-e29b-41d4-a716-446655440000/",
[
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Successfully received response:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response

Status Code	Description
204	No response body

Remove Inbox from Role

DELETE `/api/v1/organizations/{organizationPk}/groups/{groupPk}/group-inboxes/{id}`

Parameters

Parameter	Required	Type	Description
`groupPk`	V	string	
`id`	V	string	A UUID string identifying this Group Inbox.
`organizationPk`	V	string	A UUID string identifying this Organization ID

Code Examples

Shell/Bash

```
# Example API call (Shell)
curl -X DELETE
"https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-41d4-
a716-446655440000/groups/550e8400-e29b-41d4-a716-446655440000/group-
inboxes/550e8400-e29b-41d4-a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# Make sure to replace YOUR_API_KEY and verify the request data
before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

// Request payload
const data = null;

axios.delete("https://api.maiagent.ai/api/v1/organizations/550e8400-
e29b-41d4-a716-446655440000/groups/550e8400-e29b-41d4-a716-
446655440000/group-inboxes/550e8400-e29b-41d4-a716-446655440000/",
data, config)
  .then(response => {
    console.log('Successfully received response:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-
41d4-a716-446655440000/groups/550e8400-e29b-41d4-a716-
446655440000/group-inboxes/550e8400-e29b-41d4-a716-446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.delete(url, headers=headers)
try:
    print("Successfully received response:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>delete("https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-
41d4-a716-446655440000/groups/550e8400-e29b-41d4-a716-
446655440000/group-inboxes/550e8400-e29b-41d4-a716-446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'An error occurred during the request: ' . $e-
>getMessage();
}
?>
```

Response

Status Code	Description
204	No response body

Remove Knowledge Base from Role

DELETE `/api/v1/organizations/{organizationPk}/groups/{groupPk}/group-knowledge-bases/{id}`

Parameters

Parameter Name	Required	Type	Description
`groupPk`	V	string	
`id`	V	string	A UUID string identifying this Group KnowledgeBase.
`organizationPk`	V	string	A UUID string identifying this Organization ID

Code Examples

Shell/Bash

```
# API call example (Shell)
curl -X DELETE
"https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-41d4-
a716-446655440000/groups/550e8400-e29b-41d4-a716-446655440000/group-
knowledge-bases/550e8400-e29b-41d4-a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

// Request Body (payload)
const data = null;

axios.delete("https://api.maiagent.ai/api/v1/organizations/550e8400-
e29b-41d4-a716-446655440000/groups/550e8400-e29b-41d4-a716-
446655440000/group-knowledge-bases/550e8400-e29b-41d4-a716-
446655440000/", data, config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('An error occurred during the request:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-
41d4-a716-446655440000/groups/550e8400-e29b-41d4-a716-
446655440000/group-knowledge-bases/550e8400-e29b-41d4-a716-
446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.delete(url, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("An error occurred during the request:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>delete("https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-
41d4-a716-446655440000/groups/550e8400-e29b-41d4-a716-
446655440000/group-knowledge-bases/550e8400-e29b-41d4-a716-
446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'An error occurred during the request: ' . $e-
>getMessage();
}
?>
```

Response

Status Code	Description
204	No response body

Remove Database from Role

DELETE `/api/v1/organizations/{organizationPk}/groups/{groupPk}/group-databases/{id}`

Parameters

Parameter Name	Required	Type	Description
`groupPk`	V	string	
`id`	V	string	A UUID string identifying this Group Database.
`organizationPk`	V	string	A UUID string identifying this Organization ID

Code Examples

Shell/Bash

```
# API call example (Shell)
curl -X DELETE
"https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-41d4-
a716-446655440000/groups/550e8400-e29b-41d4-a716-446655440000/group-
databases/550e8400-e29b-41d4-a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

// Request Body (payload)
const data = null;

axios.delete("https://api.maiagent.ai/api/v1/organizations/550e8400-
e29b-41d4-a716-446655440000/groups/550e8400-e29b-41d4-a716-
446655440000/group-databases/550e8400-e29b-41d4-a716-446655440000/",
data, config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('An error occurred during the request:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-
41d4-a716-446655440000/groups/550e8400-e29b-41d4-a716-
446655440000/group-databases/550e8400-e29b-41d4-a716-446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.delete(url, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("An error occurred during the request:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>delete("https://api.maiagent.ai/api/v1/organizations/550e8400-e29b-
41d4-a716-446655440000/groups/550e8400-e29b-41d4-a716-
446655440000/group-databases/550e8400-e29b-41d4-a716-446655440000/",
[
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'An error occurred during the request: ' . $e-
>getMessage();
}
?>
```

Response

Status Code	Description
204	No response body

API call example (Shell)

目錄

1. List Test Sets
2. Create an empty test set
3. Upload CSV or Excel to create a test set
4. Generate a test set from a knowledge base file
5. List knowledge base files available for test case generation
6. Retrieve a specific test set
7. Retrieve a test set with its single-turn test cases
8. Update a test set
9. Partially update a test set
10. Delete a test set
11. List single-turn test cases
12. Create a Single-Turn Test Case
13. Upload a CSV or Excel File to Add Test Cases
14. Generate Single-Turn Test Cases from Knowledge Base Files
15. List Test Case Generation Jobs
16. Get Test Case Generation Job Progress
17. Update a Single-Turn Test Case
18. Partially Update Single-Turn Test Case
19. Delete Single-Turn Test Case
20. Bulk delete single-turn test cases
21. List Multi-Turn Test Cases
22. Create a multi-turn test case
23. Generate Multi-Turn Test Cases from Knowledge Base Files
24. Retrieve a Specific Multi-Turn Test Case
25. Update a Multi-Turn Test Case
26. Partially Update a Multi-Turn Test Case
27. Delete a Multi-Turn Test Case
28. List Available Evaluation Models
29. Run Single-Turn Evaluation
30. Run Multi-Turn Evaluation
31. List Evaluations
32. Get Evaluation Result
33. List Per-Question Results of a Single-Turn Evaluation
34. List Per-Conversation Results of a Multi-Turn Evaluation
35. Cancel a Running Evaluation

36. Resume Incomplete Evaluation
37. Export Evaluation Report
38. Get Latest Export Status
39. List Export Records
40. Edit Evaluation Name and Description
41. Delete Evaluation

API call example (Shell)

The evaluation and test set endpoints correspond to "Test Sets" and "Automated Testing" in the AgentOps back office, letting you batch-test Agents from your own systems. The full flow is:

1. **Create a test set**: Use `POST /api/v1/dataset/` to create an empty test set, or use `POST /api/v1/dataset/upload/` to upload a CSV/Excel file and create one in a single step.
2. **Add test cases**: For single-turn Q&A, use `/api/v1/test-case/` (create one by one, upload a file, or generate from a knowledge base file); for multi-turn conversation scenarios, use `/api/v1/multi-turn-test-case/`. Generating from a knowledge base file runs in the background and returns `202` with a `jobId`; track it with Retrieve test case generation job progress.
3. **Run an evaluation**: Use `POST /api/v1/evaluations/evaluate/` (single-turn) or `POST /api/v1/evaluations/multi-turn-evaluate/` (multi-turn) to specify the test set and Agent. The response is `202` with an `evaluationId`.
4. **Read results and export**: Poll `GET /api/v1/evaluations/{id}/` until `status` becomes `completed`, `partial_completed`, or `failed`. Per-question results for single-turn evaluations are in `details`, and per-conversation results for multi-turn evaluations are in `multi-turn-results`. A completed single-turn evaluation can be exported as an Excel report with `export`, and the download URL is available from `export-status`.

Required permissions: The API Key calls the API as the member who created it. Listing and all write operations on `/dataset/`, `/test-case/`, and `/multi-turn-test-case/` require a role with the "Test Set permission"; listing and all write operations on `/evaluations/` require the "Automated Testing permission" (the AgentOps permissions in Role Permissions; owners always have them). Insufficient permissions return `403`. Members other than the owner can only see and evaluate Agents that their role is allowed to use.

Credit: Generating test cases from knowledge base files deducts the pricing item `agentops_test_gen` based on the number of questions actually generated. Running an evaluation deducts `agentops_test_run` and `agentops_deepeval` when it finishes, based on the number of completed test cases, and the evaluation model calls used for scoring are billed separately according to that model's usage. Before a generation or evaluation request is submitted, the system checks the organization's Credit and quota, and returns `402` if they are insufficient. Manual creation, file upload, and reading results do not deduct Credit; for unit prices, see List pricing items.

For features and back-office operations, see the user manual pages Test Set Management and Automated Evaluation and Agent Monitoring.

List Test Sets

`GET` `/api/v1/dataset/`

Parameters

Parameter	Required	Type	Description
`isActive`	X	boolean	List only active (true) or inactive (false) datasets
`ordering`	X	string	Sort field: created_at or updated_at. Prefix with - for newest first (e.g. -updated_at). If not specified, sorted by creation time, newest first
`page`	X	integer	Page number, starting from 1. Returns 404 if beyond the last page
`pageSize`	X	integer	Number of items per page. Default 20, maximum 100 (values above 100 are treated as 100)
`query`	X	string	Keyword; matches the dataset name, description, or ID (partial match)
`search`	X	string	Keyword; matches the dataset name or description (partial, case-insensitive match; when multiple keywords are separated by spaces, all must match)

Code Examples

Shell/Bash

```
# API call example (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/dataset/?
isActive=true&ordering=example&page=1&pageSize=1&query=example&searc
h=example"

  -H "Authorization: Api-Key YOUR_API_KEY"

# Make sure to replace YOUR_API_KEY and verify the request data
before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/dataset/?
isActive=true&ordering=example&page=1&pageSize=1&query=example&searc
h=example", config)
  .then(response => {
    console.log('Successfully retrieved the response:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/dataset/?
isActive=true&ordering=example&page=1&pageSize=1&query=example&searc
h=example"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("Successfully retrieved the response:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/dataset/?
isActive=true&ordering=example&page=1&pageSize=1&query=example&searc
h=example", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Successfully retrieved the response:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response Body

Status Code: 200

Response Schema Example

```
{
  "count": integer
```

```
  "next"?: string (uri) // Optional
  "previous"?: string (uri) // Optional
  "results": [
    {
      "id": string (uuid)
      "name": string
      "description"?: string // Optional
      "organization":
      {
        "id": string (uuid)
        "name": string
      }
      "createdBy":
      {
        "id": string (uuid)
        "name": string
      }
      "isActive"?: boolean // Optional
      "singleTurnTestCaseCount": integer
      "multiTurnTestCaseCount": integer
      "createdAt": string (timestamp)
      "updatedAt": string (timestamp)
    }
  ]
}
```

Example Response Values

```
{
  "count": 123,
  "next": "http://api.example.org/accounts/?page=4",
  "previous": "http://api.example.org/accounts/?page=2",
  "results": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "Response string",
      "description": "Response string",
      "organization": {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "name": "Response string"
      },
      "createdBy": {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "name": "Response string"
```

```
      },
      "isActive": false,
      "singleTurnTestCaseCount": 456,
      "multiTurnTestCaseCount": 456,
      "createdAt": "Response string",
      "updatedAt": "Response string"
    }
  ]
}
```


Create an empty test set

POST `/api/v1/dataset/`

Test set names must be unique within an organization; a duplicate name returns 400.

Request Content

Request Parameters

Field	Type	Required	Description
name	string	Yes	
description	string	No	

Example Request Structure


```
{
  "name": string
  "description"?: string // Optional
}
```


Example Request Values

```
{
  "name": "Example name",
  "description": "Example string"
}
```

Code Examples

Shell/Bash

```
# API call example (Shell)
curl -X POST "https://api.maiagent.ai/api/v1/dataset/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "name": "Example name",
    "description": "Example string"
  }'

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// Request body (payload)
const data = {
    "name": "Example name",
    "description": "Example string"
  };

axios.post("https://api.maiagent.ai/api/v1/dataset/", data, config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/dataset/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# Request body (payload)
data = {
    "name": "Example name",
    "description": "Example string"
}

response = requests.post(url, json=data, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>post("https://api.maiagent.ai/api/v1/dataset/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'name' => 'Example name',
            'description' => 'Example string'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response Content

Status code: 201

Example Response Structure

```
{
  "id": string (uuid)
  "name": string
  "description"?: string // Optional
  "organization":
  {
    "id": string (uuid)
    "name": string
  }
  "createdBy":
  {
    "id": string (uuid)
    "name": string
  }
  "isActive"?: boolean // Optional
  "singleTurnTestCaseCount": integer
  "multiTurnTestCaseCount": integer
  "createdAt": string (timestamp)
  "updatedAt": string (timestamp)
}
```

Example Response Values

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "name": "Response string",
  "description": "Response string",
  "organization": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Response string"
  },
  "createdBy": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Response string"
  },
  "isActive": false,
  "singleTurnTestCaseCount": 456,
  "multiTurnTestCaseCount": 456,
  "createdAt": "Response string",
```

```
  "updatedAt": "Response string"
}
```

Upload CSV or Excel to create a test set

POST `/api/v1/dataset/upload/`

Upload as multipart/form-data: file and name are required, and description is optional. The file format is the same as Upload CSV or Excel to add test cases; test set names must be unique within an organization.

Code Examples

Shell/Bash

```
# API call example (Shell)
curl -X POST "https://api.maiagent.ai/api/v1/dataset/upload/"
  -H "Authorization: Api-Key YOUR_API_KEY"
  -F "file=@example_file.csv"
  -F "name=Example string"
  -F "description=Example string"
# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');
const FormData = require('form-data');

// Create a FormData object
const formData = new FormData();
// Replace with the actual file
formData.append('file',
* actual file object *
, 'example_file.csv');
formData.append('name', 'Example string');
formData.append('description', 'Example string');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    ...formData.getHeaders()
  }
};

axios.post("https://api.maiagent.ai/api/v1/dataset/upload/",
formData, config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/dataset/upload/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}

# Create the file and form data
files = {
    'file': ('example_file.csv', open('example_file.csv', 'rb'),
'text/csv'),
    'name': (None, 'Example string'),
    'description': (None, 'Example string')
}

response = requests.post(url, files=files, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>post("https://api.maiagent.ai/api/v1/dataset/upload/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ],
        'multipart' => [
            [
                'name' => 'file',
                'contents' => fopen('example_file.csv', 'r'),
                'filename' => 'example_file.csv'
            ],
            [
                'name' => 'name',
                'contents' => 'Example string'
            ],
            [
                'name' => 'description',
                'contents' => 'Example string'
            ]
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response Content

Status code: 201

Example Response Structure

```
{
  "id": string (uuid)
  "name": string
  "description"?: string // Optional
  "organization":
  {
    "id": string (uuid)
    "name": string
  }
  "createdBy":
  {
    "id": string (uuid)
    "name": string
  }
  "isActive"?: boolean // Optional
  "singleTurnTestCaseCount": integer
  "multiTurnTestCaseCount": integer
  "createdAt": string (timestamp)
  "updatedAt": string (timestamp)
}
```

Example Response Values

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "name": "Response string",
  "description": "Response string",
  "organization": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Response string"
  },
  "createdBy": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
```

```
    "name": "Response string"
  },
  "isActive": false,
  "singleTurnTestCaseCount": 456,
  "multiTurnTestCaseCount": 456,
  "createdAt": "Response string",
  "updatedAt": "Response string"
}
```


Generate a test set from a knowledge base file

POST `/api/v1/dataset/generate-from-file/`

Creates a new test set from a single knowledge base file (knowledgeBaseFileId) and generates single-turn test cases; numTestCases ranges from 1 to 50 (default 10). Generation runs in the background, and the actual response is 202 with a taskId; it does not include the test set ID, and there is no progress to query. Once generation finishes, the new test set appears in the list. If you need to track progress, first create an empty test set and then use Generate single-turn test cases from a knowledge base file. Credit: The organization's Credit is checked before submission, and 402 is returned if it is insufficient; agentops_test_gen is deducted based on the number of questions actually generated.

Request Content

Request Parameters

Field	Type	Required	Description
name	string	Yes	
description	string	No	
chatbotFileId	string (uuid)	No	
knowledgeBaseFileId	string (uuid)	No	
numTestCases	integer	No	

Example Request Structure

```
{
  "name": string
  "description"?: string // Optional
  "chatbotFileId"?: string (uuid) // Optional
  "knowledgeBaseFileId"?: string (uuid) // Optional
  "numTestCases"?: integer // Optional
}
```

Example Request Values

```
{
  "name": "Example name",
  "description": "Example string",
  "chatbotFileId": "550e8400-e29b-41d4-a716-446655440000",
  "knowledgeBaseFileId": "550e8400-e29b-41d4-a716-446655440000",
  "numTestCases": 123
}
```

Code Examples

Shell/Bash

```
# API call example (Shell)
curl -X POST "https://api.maiagent.ai/api/v1/dataset/generate-from-
file/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "name": "Example name",
    "description": "Example string",
    "chatbotFileId": "550e8400-e29b-41d4-a716-446655440000",
    "knowledgeBaseFileId": "550e8400-e29b-41d4-a716-446655440000",
    "numTestCases": 123
  }'

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// Request payload
const data = {
    "name": "Example name",
    "description": "Example string",
    "chatbotFileId": "550e8400-e29b-41d4-a716-446655440000",
    "knowledgeBaseFileId": "550e8400-e29b-41d4-a716-446655440000",
    "numTestCases": 123
  };

axios.post("https://api.maiagent.ai/api/v1/dataset/generate-from-
file/", data, config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```python
import requests

url = "https://api.maiagent.ai/api/v1/dataset/generate-from-file/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# Request payload
data = {
    "name": "Example name",
    "description": "Example string",
    "chatbotFileId": "550e8400-e29b-41d4-a716-446655440000",
    "knowledgeBaseFileId": "550e8400-e29b-41d4-a716-446655440000",
    "numTestCases": 123
}

response = requests.post(url, json=data, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>post("https://api.maiagent.ai/api/v1/dataset/generate-from-file/",
[
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'name' => 'Example name',
            'description' => 'Example string',
            'chatbotFileId' => '550e8400-e29b-41d4-a716-
446655440000',
            'knowledgeBaseFileId' => '550e8400-e29b-41d4-a716-
446655440000',
            'numTestCases' => 123
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response Content

Status code: 202

Example Response Structure

```
{
  "status": string (enum: accepted) // * `accepted` - Always accepted,
indicating the request has been accepted and queued for background
execution
  "message": string // Acceptance message
  "taskId": string // Background task ID
}
```

Example Response Values

```
{
  "status": "accepted",
  "message": "Response string",
  "taskId": "Response string"
}
```

List knowledge base files available for test case generation

`GET` `/api/v1/dataset/knowledge-base-files/`

Grouped by knowledge base, lists only fully processed files of type txt, docx, pdf, md, markdown, or mdx. pageSize is the maximum number of files returned per knowledge base (default 5, maximum 100); search filters by filename.

Parameters

Parameter name	Required	Type	Description
`pageSize`	X	integer	Maximum number of files returned per knowledge base (default 5, maximum 100)
`search`	X	string	Filter by filename (case-insensitive partial match)

Code examples

Shell/Bash

```
# Example API call (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/dataset/knowledge-base-files/?pageSize=1&search=example"

  -H "Authorization: Api-Key YOUR_API_KEY"

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/dataset/knowledge-base-files/?pageSize=1&search=example", config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/dataset/knowledge-base-files/?
pageSize=1&search=example"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/dataset/knowledge-base-files/?
pageSize=1&search=example", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response body

Status code: 200

Example response schema

```
{
  "knowledgeBases": [ // Knowledge bases with available files, sorted by
name; knowledge bases without available files are excluded
```

```
    {
      "id": string (uuid)
      "name": string
      "files":
      {
        "count": integer // Total number of matching files in this
knowledge base
        "results": [ // The latest page_size files
          {
            "id": string (uuid)
            "filename": string
            "fileType": string
            "size": integer // File size in bytes
            "knowledgeBase":
            {
              "id": string (uuid)
              "name": string
            }
          }
        ]
      }
    }
  ]
}
```

Example response values

```
{
  "knowledgeBases": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "Response string",
      "files": {
        "count": 456,
        "results": [
          {
            "id": "550e8400-e29b-41d4-a716-446655440000",
            "filename": "Response string",
            "fileType": "Response string",
            "size": 456,
            "knowledgeBase": {
              "id": "550e8400-e29b-41d4-a716-446655440000",
              "name": "Response string"
            }
```

```
            }
          ]
        }
      }
    ]
  }
```

Retrieve a specific test set

`GET` `/api/v1/dataset/{id}`

Parameters

Parameter Name	Required	Type	Description
`id`	V	string	Dataset ID

Code Examples

Shell/Bash

```
# API call example (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/dataset/550e8400-e29b-
41d4-a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/dataset/550e8400-e29b-
41d4-a716-446655440000/", config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/dataset/550e8400-e29b-41d4-
a716-446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/dataset/550e8400-e29b-41d4-
a716-446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response Content

Status code: 200

Example Response Structure

```
{
  "id": string (uuid)
  "name": string
```

```
  "description"?: string // Optional
  "organization":
  {
    "id": string (uuid)
    "name": string
  }
  "createdBy":
  {
    "id": string (uuid)
    "name": string
  }
  "isActive"?: boolean // Optional
  "singleTurnTestCaseCount": integer
  "multiTurnTestCaseCount": integer
  "createdAt": string (timestamp)
  "updatedAt": string (timestamp)
}
```

Example Response Values

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "name": "Response string",
  "description": "Response string",
  "organization": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Response string"
  },
  "createdBy": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Response string"
  },
  "isActive": false,
  "singleTurnTestCaseCount": 456,
  "multiTurnTestCaseCount": 456,
  "createdAt": "Response string",
  "updatedAt": "Response string"
}
```

Retrieve a test set with its single-turn test cases

`GET` `/api/v1/dataset/{id}/details/`

In addition to the test set fields, the response includes a testCases array that contains only single-turn test cases; for multi-turn test cases, use GET /api/v1/multi-turn-test-case/?datasetId={id}.

Parameters

Parameter Name	Required	Type	Description
`id`	V	string	Dataset ID

Code Examples

Shell/Bash

```
# API call example (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/dataset/550e8400-e29b-
41d4-a716-446655440000/details/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/dataset/550e8400-e29b-
41d4-a716-446655440000/details/", config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/dataset/550e8400-e29b-41d4-
a716-446655440000/details/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/dataset/550e8400-e29b-41d4-
a716-446655440000/details/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response Content

Status code: 200

Example Response Structure

```
{
  "id": string (uuid)
  "name": string
```

```
  "description"?: string // Optional
  "organization":
  {
    "id": string (uuid)
    "name": string
  }
  "createdBy":
  {
    "id": string (uuid)
    "name": string
  }
  "isActive"?: boolean // Optional
  "singleTurnTestCaseCount": integer
  "multiTurnTestCaseCount": integer
  "createdAt": string (timestamp)
  "updatedAt": string (timestamp)
  "testCases": [ // All single-turn test cases in this test set, ordered from oldest to newest by creation time; an empty array when there are no test cases
    {
      "id": string (uuid)
      "dataset":
      {
        "id": string (uuid)
        "name": string
      }
      "question": string
      "groundTruth"?: string // Optional
      "status"?: string (enum: active, inactive, pending) // * `active` - Active
* `inactive` - Inactive
* `pending` - Pending Review (Optional)
      "creationMethod"?: string (enum: manual, file, generate) // * `manual` - Manual
* `file` - File import
* `generate` - Generated (Optional)
      "sourceFile"?: string // Name of the CSV, Excel or knowledge base file this test case came from (Optional)
      "flaky"?: boolean // Flaky test cases still run and keep their results, but are excluded from the pass rate. (Optional)
      "createdAt": string (timestamp)
      "updatedAt": string (timestamp)
    }
```

```
  ]
}
```

Example Response Values

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "name": "Response string",
  "description": "Response string",
  "organization": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Response string"
  },
  "createdBy": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Response string"
  },
  "isActive": false,
  "singleTurnTestCaseCount": 456,
  "multiTurnTestCaseCount": 456,
  "createdAt": "Response string",
  "updatedAt": "Response string",
  "testCases": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "dataset": {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "name": "Response string"
      },
      "question": "Response string",
      "groundTruth": "Response string",
      "status": "active",
      "creationMethod": "manual",
      "sourceFile": "Response string",
      "flaky": false,
      "createdAt": "Response string",
      "updatedAt": "Response string"
    }
  ]
}
```

Update a test set

PUT `/api/v1/dataset/{id}`

Parameters

Parameter Name	Required	Type	Description
id	V	string	Dataset ID

Request Content

Request Parameters

Field	Type	Required	Description
name	string	Yes	
description	string	No	
isActive	boolean	No	

Example Request Structure

```
{
  "name": string
  "description"?: string // Optional
  "isActive"?: boolean // Optional
}
```

Example Request Values

```
{
  "name": "Example name",
  "description": "Example string",
  "isActive": true
}
```

Code Examples

Shell/Bash

```
# API call example (Shell)
curl -X PUT "https://api.maiagent.ai/api/v1/dataset/550e8400-e29b-
41d4-a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "name": "Example name",
    "description": "Example string",
    "isActive": true
  }'

# Make sure to replace YOUR_API_KEY and verify the request data
before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// Request payload
const data = {
    "name": "Example name",
    "description": "Example string",
    "isActive": true
  };

axios.put("https://api.maiagent.ai/api/v1/dataset/550e8400-e29b-
41d4-a716-446655440000/", data, config)
  .then(response => {
    console.log('Successfully retrieved the response:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/dataset/550e8400-e29b-41d4-
a716-446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# Request payload
data = {
    "name": "Example name",
    "description": "Example string",
    "isActive": True
}

response = requests.put(url, json=data, headers=headers)
try:
    print("Successfully retrieved the response:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>put("https://api.maiagent.ai/api/v1/dataset/550e8400-e29b-41d4-
a716-446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'name' => 'Example name',
            'description' => 'Example string',
            'isActive' => true
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Successfully retrieved the response:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response Content

Status Code: 200

Example Response Structure

```
{
  "id": string (uuid)
  "name": string
  "description"?: string // Optional
  "organization":
  {
    "id": string (uuid)
    "name": string
  }
  "createdBy":
  {
    "id": string (uuid)
    "name": string
  }
  "isActive"?: boolean // Optional
  "singleTurnTestCaseCount": integer
  "multiTurnTestCaseCount": integer
  "createdAt": string (timestamp)
  "updatedAt": string (timestamp)
}
```

Example Response Values

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "name": "Response string",
  "description": "Response string",
  "organization": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Response string"
  },
  "createdBy": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Response string"
  },
  "isActive": false,
  "singleTurnTestCaseCount": 456,
  "multiTurnTestCaseCount": 456,
  "createdAt": "Response string",
```

```
  "updatedAt": "Response string"
}
```

Partially update a test set

PATCH `/api/v1/dataset/{id}`

Parameters

Parameter Name	Required	Type	Description
id	V	string	Dataset ID

Request Content

Request Parameters

Field	Type	Required	Description
name	string	No	
description	string	No	
isActive	boolean	No	

Example Request Structure

```
{
  "name"?: string // Optional
  "description"?: string // Optional
```

```
  "isActive"?: boolean // Optional
}
```

Example Request Values

```
{
  "name": "Example name",
  "description": "Example string",
  "isActive": true
}
```

Code Examples

Shell/Bash

```
# API call example (Shell)
curl -X PATCH "https://api.maiagent.ai/api/v1/dataset/550e8400-e29b-
41d4-a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "name": "Example name",
    "description": "Example string",
    "isActive": true
  }'

# Make sure to replace YOUR_API_KEY and verify the request data
before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// Request payload
const data = {
    "name": "Example name",
    "description": "Example string",
    "isActive": true
  };

axios.patch("https://api.maiagent.ai/api/v1/dataset/550e8400-e29b-
41d4-a716-446655440000/", data, config)
  .then(response => {
    console.log('Successfully retrieved the response:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/dataset/550e8400-e29b-41d4-
a716-446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# Request payload
data = {
    "name": "Example name",
    "description": "Example string",
    "isActive": True
}

response = requests.patch(url, json=data, headers=headers)
try:
    print("Successfully retrieved the response:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>patch("https://api.maiagent.ai/api/v1/dataset/550e8400-e29b-41d4-
a716-446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'name' => 'Example name',
            'description' => 'Example string',
            'isActive' => true
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Successfully retrieved the response:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response Content

Status Code: 200

Example Response Structure

```
{
  "id": string (uuid)
  "name": string
  "description"?: string // Optional
  "organization":
  {
    "id": string (uuid)
    "name": string
  }
  "createdBy":
  {
    "id": string (uuid)
    "name": string
  }
  "isActive"?: boolean // Optional
  "singleTurnTestCaseCount": integer
  "multiTurnTestCaseCount": integer
  "createdAt": string (timestamp)
  "updatedAt": string (timestamp)
}
```

Example Response Values

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "name": "Response string",
  "description": "Response string",
  "organization": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Response string"
  },
  "createdBy": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Response string"
  },
  "isActive": false,
  "singleTurnTestCaseCount": 456,
  "multiTurnTestCaseCount": 456,
  "createdAt": "Response string",
```

```
  "updatedAt": "Response string"
}
```

Delete a test set

DELETE `/api/v1/dataset/{id}`

This cannot be undone. Deleting a test set also deletes all test cases in it, as well as the evaluations and results that were run with this test set.

Parameters

Parameter Name	Required	Type	Description
`id`	V	string	Dataset ID

Code Examples

Shell/Bash

```
# API call example (Shell)
curl -X DELETE "https://api.maiagent.ai/api/v1/dataset/550e8400-
e29b-41d4-a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# Make sure to replace YOUR_API_KEY and verify the request data
before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

// Request payload
const data = null;

axios.delete("https://api.maiagent.ai/api/v1/dataset/550e8400-e29b-
41d4-a716-446655440000/", data, config)
  .then(response => {
    console.log('Successfully retrieved the response:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/dataset/550e8400-e29b-41d4-
a716-446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.delete(url, headers=headers)
try:
    print("Successfully retrieved the response:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>delete("https://api.maiagent.ai/api/v1/dataset/550e8400-e29b-41d4-
a716-446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Successfully retrieved the response:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response Content

Status code	Description
204	No response body

List single-turn test cases

`GET` `/api/v1/test-case/`

Use datasetId to filter by a single test set. You can also filter by status and creationMethod (manual, file, generate).

Parameters

Parameter Name	Required	Type	Description
`creationMethod`	X	string	List only test cases created with this method. Allowed values: `manual`: Manual ; `file`: File import ; `generate`: Generated;
`datasetId`	X	string	List only test cases from this dataset
`ordering`	X	string	Sort field: created_at or updated_at. Prefix with - for newest first (e.g. -updated_at). If not specified, sorted by creation time, newest first
`page`	X	integer	Page number, starting from 1. Returns 404 if beyond the last page
`pageSize`	X	integer	Number of items per page. Default 20, maximum 100 (values above 100 are treated as 100)
`query`	X	string	Keyword matched against the question, ground truth, or ID (partial match)
`search`	X	string	Keyword matched against the question or ground truth (partial match, case-insensitive; when multiple keywords are separated by spaces, all must match)

`status`	X	string	List only test cases with this status. Allowed values: `active`: Active ; `inactive`: Inactive ; `pending`: Pending Review;

Code Examples

Shell/Bash

```
# API call example (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/test-case/?
creationMethod=file&datasetId=550e8400-e29b-41d4-a716-
446655440000&ordering=example&page=1&pageSize=1&query=example&search
=example&status=active"

  -H "Authorization: Api-Key YOUR_API_KEY"

# Make sure to replace YOUR_API_KEY and verify the request data
before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/test-case/?
creationMethod=file&datasetId=550e8400-e29b-41d4-a716-
446655440000&ordering=example&page=1&pageSize=1&query=example&search
=example&status=active", config)
  .then(response => {
    console.log('Successfully retrieved the response:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/test-case/?
creationMethod=file&datasetId=550e8400-e29b-41d4-a716-
446655440000&ordering=example&page=1&pageSize=1&query=example&search
=example&status=active"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("Successfully retrieved the response:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->get("https://api.maiagent.ai/api/v1/test-case/?creationMethod=file&datasetId=550e8400-e29b-41d4-a716-446655440000&ordering=example&page=1&pageSize=1&query=example&search=example&status=active", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Successfully retrieved the response:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response Content

Status Code: 200

Example Response Structure

```
{
  "count": integer
```

```
  "next"?: string (uri) // Optional
  "previous"?: string (uri) // Optional
  "results": [
    {
      "id": string (uuid)
      "dataset":
      {
        "id": string (uuid)
        "name": string
      }
      "question": string
      "groundTruth"?: string // Optional
      "status"?: string (enum: active, inactive, pending) // * `active` -
Active
* `inactive` - Inactive
* `pending` - Pending Review (Optional)
      "creationMethod"?: string (enum: manual, file, generate) // *
`manual` - Manual
* `file` - File import
* `generate` - Generated (Optional)
      "sourceFile"?: string // Name of the CSV, Excel or knowledge base
file this test case came from (Optional)
      "flaky"?: boolean // Flaky test cases still run and keep their
results, but are excluded from the pass rate. (Optional)
      "createdAt": string (timestamp)
      "updatedAt": string (timestamp)
    }
  ]
}
```

Example Response Values

```
{
  "count": 123,
  "next": "http://api.example.org/accounts/?page=4",
  "previous": "http://api.example.org/accounts/?page=2",
  "results": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "dataset": {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "name": "Response string"
      },
      "question": "Response string",
```

```
        "groundTruth": "Response string",
        "status": "active",
        "creationMethod": "manual",
        "sourceFile": "Response string",
        "flaky": false,
        "createdAt": "Response string",
        "updatedAt": "Response string"
      }
    ]
}
```


Create a Single-Turn Test Case

POST `/api/v1/test-case/`

datasetId, question, and groundTruth are required. status defaults to active; evaluations only run test cases that are active.

Request Content

Request Parameters

Field	Type	Required	Description
datasetId	string (uuid)	Yes	
question	string	Yes	
groundTruth	string	Yes	
status	string	No	
flaky	boolean	No	

Example Request Structure

```
{
  "datasetId": string (uuid)
  "question": string
  "groundTruth": string
  "status"?: string // Optional
  "flaky"?: boolean // Optional
}
```

Example Request Values

```
{
  "datasetId": "550e8400-e29b-41d4-a716-446655440000",
  "question": "Example string",
  "groundTruth": "Example string",
  "status": "Example string",
  "flaky": true
}
```

Code Examples

Shell/Bash

```
# API call example (Shell)
curl -X POST "https://api.maiagent.ai/api/v1/test-case/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "datasetId": "550e8400-e29b-41d4-a716-446655440000",
    "question": "Example string",
    "groundTruth": "Example string",
    "status": "Example string",
    "flaky": true
  }'

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// Request payload
const data = {
    "datasetId": "550e8400-e29b-41d4-a716-446655440000",
    "question": "Example string",
    "groundTruth": "Example string",
    "status": "Example string",
    "flaky": true
  };

axios.post("https://api.maiagent.ai/api/v1/test-case/", data,
config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```python
import requests

url = "https://api.maiagent.ai/api/v1/test-case/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# Request payload
data = {
    "datasetId": "550e8400-e29b-41d4-a716-446655440000",
    "question": "Example string",
    "groundTruth": "Example string",
    "status": "Example string",
    "flaky": True
}

response = requests.post(url, json=data, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->post("https://api.maiagent.ai/api/v1/test-case/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'datasetId' => '550e8400-e29b-41d4-a716-446655440000',
            'question' => 'Example string',
            'groundTruth' => 'Example string',
            'status' => 'Example string',
            'flaky' => true
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response Content

Status code: 201

Example Response Structure

```
{
  "id": string (uuid)
  "dataset":
  {
    "id": string (uuid)
    "name": string
  }
  "question": string
  "groundTruth"?: string // Optional
  "status"?: string (enum: active, inactive, pending) // * `active` -
Active
* `inactive` - Inactive
* `pending` - Pending Review (Optional)
  "creationMethod"?: string (enum: manual, file, generate) // * `manual`
- Manual
* `file` - File import
* `generate` - Generated (Optional)
  "sourceFile"?: string // Name of the CSV, Excel or knowledge base file
this test case came from (Optional)
  "flaky"?: boolean // Flaky test cases still run and keep their results,
but are excluded from the pass rate. (Optional)
  "createdAt": string (timestamp)
  "updatedAt": string (timestamp)
}
```

Example Response Values

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "dataset": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Response string"
  },
  "question": "Response string",
  "groundTruth": "Response string",
  "status": "active",
  "creationMethod": "manual",
  "sourceFile": "Response string",
  "flaky": false,
  "createdAt": "Response string",
```

```
  "updatedAt": "Response string"
}
```

Upload a CSV or Excel File to Add Test Cases

POST `/api/v1/test-case/upload/`

Upload with multipart/form-data; both file and dataset_id are required. The file must be .csv, .xlsx, or .xls, and the header row must include the question and ground_truth columns. Each row adds one single-turn test case. Use UTF-8 encoding for CSV files. The response is an array of the newly created test cases.

Code Examples

Shell/Bash

```
# Example API call (Shell)
curl -X POST "https://api.maiagent.ai/api/v1/test-case/upload/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -F "file=@example_file.csv"

  -F "dataset_id=550e8400-e29b-41d4-a716-446655440000"

# Make sure to replace YOUR_API_KEY and verify the request data
before running.
```

JavaScript

```
const axios = require('axios');
const FormData = require('form-data');

// Create a FormData object
const formData = new FormData();
// Replace with the actual file
formData.append('file',
* actual file object *
, 'example_file.csv');
formData.append('dataset_id', '550e8400-e29b-41d4-a716-
446655440000');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    ...formData.getHeaders()
  }
};

axios.post("https://api.maiagent.ai/api/v1/test-case/upload/",
formData, config)
  .then(response => {
    console.log('Successfully retrieved the response:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('An error occurred with the request:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/test-case/upload/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}

# Create the file and form data
files = {
    'file': ('example_file.csv', open('example_file.csv', 'rb'),
'text/csv'),
    'dataset_id': (None, '550e8400-e29b-41d4-a716-446655440000')
}

response = requests.post(url, files=files, headers=headers)
try:
    print("Successfully retrieved the response:")
    print(response.json())
except Exception as e:
    print("An error occurred with the request:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->post("https://api.maiagent.ai/api/v1/test-case/upload/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ],
        'multipart' => [
            [
                'name' => 'file',
                'contents' => fopen('example_file.csv', 'r'),
                'filename' => 'example_file.csv'
            ],
            [
                'name' => 'dataset_id',
                'contents' => '550e8400-e29b-41d4-a716-446655440000'
            ]
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Successfully retrieved the response:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'An error occurred with the request: ' . $e->getMessage();
}
?>
```

Response Body

Status code: 201

Example Response Structure

```
[
  {
    "id": string (uuid)
    "dataset":
    {
      "id": string (uuid)
      "name": string
    }
    "question": string
    "groundTruth"?: string // Optional
    "status"?: string (enum: active, inactive, pending) // * `active` -
Active
* `inactive` - Inactive
* `pending` - Pending Review (Optional)
    "creationMethod"?: string (enum: manual, file, generate) // *
`manual` - Manual
* `file` - File import
* `generate` - Generated (Optional)
    "sourceFile"?: string // Name of the CSV, Excel or knowledge base
file this test case came from (Optional)
    "flaky"?: boolean // Flaky test cases still run and keep their
results, but are excluded from the pass rate. (Optional)
    "createdAt": string (timestamp)
    "updatedAt": string (timestamp)
  }
]
```

Example Response Values

```
[
  {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "dataset": {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "Response string"
```

```
    },
    "question": "Response string",
    "groundTruth": "Response string",
    "status": "active",
    "creationMethod": "manual",
    "sourceFile": "Response string",
    "flaky": false,
    "createdAt": "Response string",
    "updatedAt": "Response string"
  }
]
```


Generate Single-Turn Test Cases from Knowledge Base Files

POST `/api/v1/test-case/generate-from-file/`

Specify the source with knowledgeBaseIds (expanded to all processed files of a supported type in the knowledge base) or knowledgeBaseFileIds; the two can be used together. Supported formats are txt, docx, pdf, md, markdown, and mdx. numTestCases is the total number of test cases to generate in this run (default 10). If the number of files or test cases exceeds the platform limit, the API returns 400 and the message states the limit. Generation runs in the background, and the response is 202 with a jobId. If the same dataset already has a generation job in progress, that job's jobId is returned and no duplicate job is created. Credit: The organization's Credit is checked before submission, and 402 is returned if it is insufficient; agentops_test_gen is deducted based on the number of test cases actually generated.

Request Content

Request Parameters

Field	Type	Required	Description
chatbotFileIds	array[string]	No	List of KnowledgeBaseFile IDs to generate test cases from (deprecated)

Field	Type	Required	Description
knowledgeBaseFileIds	array[string]	No	List of KnowledgeBaseFile IDs to generate test cases from
knowledgeBaseIds	array[string]	No	List of KnowledgeBase IDs to generate test cases from all their files
datasetId	string (uuid)	Yes	
numTestCases	integer	No	

Example Request Structure

```
{
  "chatbotFileIds"?: [ // List of KnowledgeBaseFile IDs to generate test cases from (deprecated) (Optional)
    string (uuid)
  ]
  "knowledgeBaseFileIds"?: [ // List of KnowledgeBaseFile IDs to generate test cases from (Optional)
    string (uuid)
  ]
  "knowledgeBaseIds"?: [ // List of KnowledgeBase IDs to generate test cases from all their files (Optional)
    string (uuid)
  ]
  "datasetId": string (uuid)
  "numTestCases"?: integer // Optional
}
```

Example Request Values

```
{
  "chatbotFileIds": [
    "550e8400-e29b-41d4-a716-446655440000"
  ],
  "knowledgeBaseFileIds": [
    "550e8400-e29b-41d4-a716-446655440000"
  ],
  "knowledgeBaseIds": [
    "550e8400-e29b-41d4-a716-446655440000"
```

```
  ],
  "datasetId": "550e8400-e29b-41d4-a716-446655440000",
  "numTestCases": 123
}
```

Code Examples

Shell/Bash

```
# Example API call (Shell)
curl -X POST "https://api.maiagent.ai/api/v1/test-case/generate-
from-file/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "chatbotFileIds": [
      "550e8400-e29b-41d4-a716-446655440000"
    ],
    "knowledgeBaseFileIds": [
      "550e8400-e29b-41d4-a716-446655440000"
    ],
    "knowledgeBaseIds": [
      "550e8400-e29b-41d4-a716-446655440000"
    ],
    "datasetId": "550e8400-e29b-41d4-a716-446655440000",
    "numTestCases": 123
  }'

# Make sure to replace YOUR_API_KEY and verify the request data
before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// Request payload
const data = {
    "chatbotFileIds": [
      "550e8400-e29b-41d4-a716-446655440000"
    ],
    "knowledgeBaseFileIds": [
      "550e8400-e29b-41d4-a716-446655440000"
    ],
    "knowledgeBaseIds": [
      "550e8400-e29b-41d4-a716-446655440000"
    ],
    "datasetId": "550e8400-e29b-41d4-a716-446655440000",
    "numTestCases": 123
  };

axios.post("https://api.maiagent.ai/api/v1/test-case/generate-from-
file/", data, config)
  .then(response => {
    console.log('Successfully retrieved the response:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('An error occurred with the request:');
    console.error(error.response?.data || error.message);
  });
```

Python

```python
import requests

url = "https://api.maiagent.ai/api/v1/test-case/generate-from-file/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# Request payload
data = {
    "chatbotFileIds": [
        "550e8400-e29b-41d4-a716-446655440000"
    ],
    "knowledgeBaseFileIds": [
        "550e8400-e29b-41d4-a716-446655440000"
    ],
    "knowledgeBaseIds": [
        "550e8400-e29b-41d4-a716-446655440000"
    ],
    "datasetId": "550e8400-e29b-41d4-a716-446655440000",
    "numTestCases": 123
}

response = requests.post(url, json=data, headers=headers)
try:
    print("Successfully retrieved the response:")
    print(response.json())
except Exception as e:
    print("An error occurred with the request:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->post("https://api.maiagent.ai/api/v1/test-case/generate-from-file/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'chatbotFileIds' => [
                '550e8400-e29b-41d4-a716-446655440000'
            ],
            'knowledgeBaseFileIds' => [
                '550e8400-e29b-41d4-a716-446655440000'
            ],
            'knowledgeBaseIds' => [
                '550e8400-e29b-41d4-a716-446655440000'
            ],
            'datasetId' => '550e8400-e29b-41d4-a716-446655440000',
            'numTestCases' => 123
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Successfully retrieved the response:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'An error occurred with the request: ' . $e->getMessage();
}
?>
```

Response Body

Status code: 202

Example Response Structure

```
{
  "status": string (enum: accepted) // * `accepted` - Always accepted,
indicating the request was accepted and queued for background execution
  "message": string // Acceptance message
  "jobId": string (uuid) // Generation job ID. Use GET /api/v1/test-
case/generation-jobs/{jobId}/ to check progress. If the same dataset
already has a generation job in progress, the ID of that job is returned
  "taskId": string // Background task ID
}
```

Example Response Values

```
{
  "status": "accepted",
  "message": "Response string",
  "jobId": "550e8400-e29b-41d4-a716-446655440000",
  "taskId": "Response string"
}
```

List Test Case Generation Jobs

GET `/api/v1/test-case/generation-jobs/`

Lists the organization's single-turn and multi-turn generation jobs, sorted from newest to oldest. Filter by datasetId and status.

Parameters

Parameter Name	Required	Type	Description
`datasetId`	X	string	List only generation jobs for this dataset
`page`	X	integer	Page number, starting from 1. Returns 404 if beyond the last page
`pageSize`	X	integer	Number of items per page. Default 20, maximum 100 (values above 100 are treated as 100)
`status`	X	string	Filter by status: pending running completed partial_completed failed

Code Examples

Shell/Bash

```
# Example API call (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/test-case/generation-
jobs/?datasetId=example&page=1&pageSize=1&status=example"

  -H "Authorization: Api-Key YOUR_API_KEY"

# Make sure to replace YOUR_API_KEY and verify the request data
before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/test-case/generation-
jobs/?datasetId=example&page=1&pageSize=1&status=example", config)
  .then(response => {
    console.log('Successfully retrieved the response:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('An error occurred with the request:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/test-case/generation-jobs/?
datasetId=example&page=1&pageSize=1&status=example"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("Successfully retrieved the response:")
    print(response.json())
except Exception as e:
    print("An error occurred with the request:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->get("https://api.maiagent.ai/api/v1/test-case/generation-jobs/?datasetId=example&page=1&pageSize=1&status=example", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Successfully retrieved the response:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'An error occurred with the request: ' . $e->getMessage();
}
?>
```

Response Body

Status code: 200

Example Response Structure

```
{
  "count": integer
  "next"?: string (uri) // Optional
```

```
  "previous"?: string (uri) // Optional
  "results": [
    {
      "id": string (uuid)
      "dataset":
      {
        "id": string (uuid)
        "name": string
      }
      "status"?: string (enum: pending, running, completed,
partial_completed, failed) // * `pending` - Pending
* `running` - Generating
* `completed` - Completed
* `partial_completed` - Partially completed
* `failed` - Generation failed (Optional)
      "jobType"?:  // Single-turn Q&A test data or multi-turn
conversation test data

* `single_turn` - Single turn
* `multi_turn` - Multi turn (Optional)
      {
      }
      "requestedNumTestCases"?: integer // Optional
      "totalFiles"?: integer // Optional
      "processedFiles"?: integer // Optional
      "generatedCount"?: integer // Optional
      "progressPercentage": number (double)
      "errorMessage"?: string // Error message recorded when the whole
batch fails (Optional)
      "fileResults"?: object // Result for each file, such as
[{'file_id', 'filename', 'status', 'generated', 'error'}] (Optional)
      "startedAt"?: string (timestamp) // Optional
      "completedAt"?: string (timestamp) // Optional
      "createdAt": string (timestamp)
      "updatedAt": string (timestamp)
    }
  ]
}
```

Example Response Values

```
{
  "count": 123,
  "next": "http://api.example.org/accounts/?page=4",
```

```
  "previous": "http://api.example.org/accounts/?page=2",
  "results": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "dataset": {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "name": "Response string"
      },
      "status": "pending",
      "jobType": {},
      "requestedNumTestCases": 456,
      "totalFiles": 456,
      "processedFiles": 456,
      "generatedCount": 456,
      "progressPercentage": 456,
      "errorMessage": "Response string",
      "fileResults": null,
      "startedAt": "Response string",
      "completedAt": "Response string",
      "createdAt": "Response string",
      "updatedAt": "Response string"
    }
  ]
}
```


Get Test Case Generation Job Progress

`GET` `/api/v1/test-case/generation-jobs/{jobId}`

status is pending, running, completed, partial_completed, or failed. generatedCount is the number of test cases generated so far, and fileResults lists the result and failure reason for each file. Both single-turn and multi-turn generation jobs are queried through this endpoint and are distinguished by jobType.

Parameters

Parameter Name	Required	Type	Description
`jobId`	V	string	Generation job ID, i.e. the jobId returned by "Generate Test Cases from Knowledge Base Files"

Code Examples

Shell/Bash

```
# Example API call (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/test-case/generation-jobs/550e8400-e29b-41d4-a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# Make sure to replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/test-case/generation-
jobs/550e8400-e29b-41d4-a716-446655440000/", config)
  .then(response => {
    console.log('Successfully retrieved the response:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('An error occurred with the request:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/test-case/generation-
jobs/550e8400-e29b-41d4-a716-446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("Successfully retrieved the response:")
    print(response.json())
except Exception as e:
    print("An error occurred with the request:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->get("https://api.maiagent.ai/api/v1/test-
case/generation-jobs/550e8400-e29b-41d4-a716-446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Successfully retrieved the response:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'An error occurred with the request: ' . $e->getMessage();
}
?>
```

Response Body

Status code: 200

Example Response Structure

```
{
  "id": string (uuid)
  "dataset":
  {
```

```
    "id": string (uuid)
    "name": string
  }
  "status"?: string (enum: pending, running, completed,
partial_completed, failed) // * `pending` - Pending
* `running` - Generating
* `completed` - Completed
* `partial_completed` - Partially completed
* `failed` - Generation failed (Optional)
  "jobType"?:  // Single-turn Q&A test data or multi-turn conversation
test data

* `single_turn` - Single turn
* `multi_turn` - Multi turn (Optional)
  {
  }
  "requestedNumTestCases"?: integer // Optional
  "totalFiles"?: integer // Optional
  "processedFiles"?: integer // Optional
  "generatedCount"?: integer // Optional
  "progressPercentage": number (double)
  "errorMessage"?: string // Error message recorded when the whole batch
fails (Optional)
  "fileResults"?: object // Result for each file, such as [{'file_id',
'filename', 'status', 'generated', 'error'}] (Optional)
  "startedAt"?: string (timestamp) // Optional
  "completedAt"?: string (timestamp) // Optional
  "createdAt": string (timestamp)
  "updatedAt": string (timestamp)
}
```

Example Response Values

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "dataset": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Response string"
  },
  "status": "pending",
  "jobType": {},
  "requestedNumTestCases": 456,
  "totalFiles": 456,
  "processedFiles": 456,
```

```
  "generatedCount": 456,
  "progressPercentage": 456,
  "errorMessage": "Response string",
  "fileResults": null,
  "startedAt": "Response string",
  "completedAt": "Response string",
  "createdAt": "Response string",
  "updatedAt": "Response string"
}
```


Update a Single-Turn Test Case

PUT `/api/v1/test-case/{id}`

Parameters

Parameter Name	Required	Type	Description
`id`	V	string	Test case ID

Request Content

Request Parameters

Field	Type	Required	Description
question	string	Yes	
groundTruth	string	No	
status	string (enum: active, inactive,	No	`active` : Active ; `inactive` : Inactive ; `pending` : Pending Review;

Field	Type	Required	Description
	pending)		
flaky	boolean	No	Flaky test cases still run and keep their results, but are excluded from the pass rate.

Example Request Structure

```
{
  "question": string
  "groundTruth"?: string // Optional
  "status"?: string (enum: active, inactive, pending) // * `active` -
Active
* `inactive` - Inactive
* `pending` - Pending Review (Optional)
  "flaky"?: boolean // Flaky test cases still run and keep their results,
but are excluded from the pass rate. (Optional)
}
```

Example Request Values

```
{
  "question": "Example string",
  "groundTruth": "Example string",
  "status": "active",
  "flaky": true
}
```

Code Examples

Shell/Bash

```
# API call example (Shell)
curl -X PUT "https://api.maiagent.ai/api/v1/test-case/550e8400-e29b-
41d4-a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "question": "Example string",
    "groundTruth": "Example string",
    "status": "active",
    "flaky": true
  }'

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// Request body (payload)
const data = {
    "question": "Example string",
    "groundTruth": "Example string",
    "status": "active",
    "flaky": true
  };

axios.put("https://api.maiagent.ai/api/v1/test-case/550e8400-e29b-
41d4-a716-446655440000/", data, config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/test-case/550e8400-e29b-41d4-
a716-446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# Request body (payload)
data = {
    "question": "Example string",
    "groundTruth": "Example string",
    "status": "active",
    "flaky": True
}

response = requests.put(url, json=data, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->put("https://api.maiagent.ai/api/v1/test-case/550e8400-e29b-41d4-a716-446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'question' => 'Example string',
            'groundTruth' => 'Example string',
            'status' => 'active',
            'flaky' => true
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response Content

Status code: 200

Example Response Structure

```
{
  "id": string (uuid)
  "dataset":
  {
    "id": string (uuid)
    "name": string
  }
  "question": string
  "groundTruth"?: string // Optional
  "status"?: string (enum: active, inactive, pending) // * `active` -
Active
* `inactive` - Inactive
* `pending` - Pending Review (Optional)
  "creationMethod"?: string (enum: manual, file, generate) // * `manual`
- Manual
* `file` - File import
* `generate` - Generated (Optional)
  "sourceFile"?: string // Name of the CSV, Excel or knowledge base file
this test case came from (Optional)
  "flaky"?: boolean // Flaky test cases still run and keep their results,
but are excluded from the pass rate. (Optional)
  "createdAt": string (timestamp)
  "updatedAt": string (timestamp)
}
```

Example Response Values

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "dataset": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Response string"
  },
  "question": "Response string",
  "groundTruth": "Response string",
  "status": "active",
  "creationMethod": "manual",
  "sourceFile": "Response string",
  "flaky": false,
  "createdAt": "Response string",
```

```
  "updatedAt": "Response string"
}
```

Partially Update Single-Turn Test Case

PATCH `/api/v1/test-case/{id}`

To temporarily skip a question, set status to inactive. Evaluations will skip it, and past evaluation results are kept.

Parameters

Parameter Name	Required	Type	Description
`id`	V	string	Test case ID

Request Content

Request Parameters

Field	Type	Required	Description
question	string	No	
groundTruth	string	No	
status	string (enum: active, inactive, pending)	No	`active` : Active ; `inactive` : Inactive ; `pending` : Pending Review;
flaky	boolean	No	Flaky test cases still run and keep their results, but are excluded from the pass rate.

Example Request Structure

```
{
  "question"?: string // Optional
  "groundTruth"?: string // Optional
  "status"?: string (enum: active, inactive, pending) // * `active` -
Active
* `inactive` - Inactive
* `pending` - Pending Review (Optional)
  "flaky"?: boolean // Flaky test cases still run and keep their results,
but are excluded from the pass rate. (Optional)
}
```

Example Request Values

```
{
  "question": "Example string",
  "groundTruth": "Example string",
  "status": "active",
  "flaky": true
}
```

Code Examples

Shell/Bash

```
# API call example (Shell)
curl -X PATCH "https://api.maiagent.ai/api/v1/test-case/550e8400-
e29b-41d4-a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "question": "Example string",
    "groundTruth": "Example string",
    "status": "active",
    "flaky": true
  }'

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// Request body (payload)
const data = {
    "question": "Example string",
    "groundTruth": "Example string",
    "status": "active",
    "flaky": true
  };

axios.patch("https://api.maiagent.ai/api/v1/test-case/550e8400-e29b-
41d4-a716-446655440000/", data, config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/test-case/550e8400-e29b-41d4-
a716-446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# Request body (payload)
data = {
    "question": "Example string",
    "groundTruth": "Example string",
    "status": "active",
    "flaky": True
}

response = requests.patch(url, json=data, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->patch("https://api.maiagent.ai/api/v1/test-case/550e8400-e29b-41d4-a716-446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'question' => 'Example string',
            'groundTruth' => 'Example string',
            'status' => 'active',
            'flaky' => true
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response Content

Status code: 200

Example Response Structure

```
{
  "id": string (uuid)
  "dataset":
  {
    "id": string (uuid)
    "name": string
  }
  "question": string
  "groundTruth"?: string // Optional
  "status"?: string (enum: active, inactive, pending) // * `active` -
Active
* `inactive` - Inactive
* `pending` - Pending Review (Optional)
  "creationMethod"?: string (enum: manual, file, generate) // * `manual`
- Manual
* `file` - File import
* `generate` - Generated (Optional)
  "sourceFile"?: string // Name of the CSV, Excel or knowledge base file
this test case came from (Optional)
  "flaky"?: boolean // Flaky test cases still run and keep their results,
but are excluded from the pass rate. (Optional)
  "createdAt": string (timestamp)
  "updatedAt": string (timestamp)
}
```

Example Response Values

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "dataset": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Response string"
  },
  "question": "Response string",
  "groundTruth": "Response string",
  "status": "active",
  "creationMethod": "manual",
  "sourceFile": "Response string",
  "flaky": false,
  "createdAt": "Response string",
```

```
  "updatedAt": "Response string"
}
```

Delete Single-Turn Test Case

DELETE `/api/v1/test-case/{id}`

This also deletes this test case's per-question results from past evaluations. To only pause testing, use status instead.

Parameters

Parameter Name	Required	Type	Description
`id`	V	string	Test case ID

Code Examples

Shell/Bash

```
# API call example (Shell)
curl -X DELETE "https://api.maiagent.ai/api/v1/test-case/550e8400-
e29b-41d4-a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

// Request body (payload)
const data = null;

axios.delete("https://api.maiagent.ai/api/v1/test-case/550e8400-
e29b-41d4-a716-446655440000/", data, config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/test-case/550e8400-e29b-41d4-
a716-446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.delete(url, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>delete("https://api.maiagent.ai/api/v1/test-case/550e8400-e29b-
41d4-a716-446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response

Status code	Description
204	No response body

Bulk delete single-turn test cases

`POST` `/api/v1/test-case/bulk-delete/`

Pass an array of test case IDs to delete as testCaseIds; success returns 204. The impact of deletion is the same as Delete a single-turn test case.

Request

Request Parameters

Field	Type	Required	Description
test_case_ids	array[string]	Yes	List of test case IDs to delete

Request Schema Example

```
{
  "test_case_ids": [ // List of test case IDs to delete
    string (uuid)
  ]
}
```

Request Example Values

```
{
  "test_case_ids": [
    "550e8400-e29b-41d4-a716-446655440000"
  ]
}
```

Code Examples

Shell/Bash

```
# API call example (Shell)
curl -X POST "https://api.maiagent.ai/api/v1/test-case/bulk-delete/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "test_case_ids": [
      "550e8400-e29b-41d4-a716-446655440000"
    ]
  }'

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// Request body (payload)
const data = {
    "test_case_ids": [
      "550e8400-e29b-41d4-a716-446655440000"
    ]
  };

axios.post("https://api.maiagent.ai/api/v1/test-case/bulk-delete/",
data, config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/test-case/bulk-delete/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# Request body (payload)
data = {
    "test_case_ids": [
        "550e8400-e29b-41d4-a716-446655440000"
    ]
}

response = requests.post(url, json=data, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->post("https://api.maiagent.ai/api/v1/test-case/bulk-delete/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'test_case_ids' => [
                '550e8400-e29b-41d4-a716-446655440000'
            ]
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response

Status code	Description

204	No response body

List Multi-Turn Test Cases

`GET` `/api/v1/multi-turn-test-case/`

Use datasetId to filter by a single test set.

Parameters

Parameter	Required	Type	Description
`dataset`	X	string	Same as datasetId. Lists only the multi-turn conversation test cases of this dataset
`datasetId`	X	string	Lists only the multi-turn conversation test cases of this dataset
`ordering`	X	string	Sort field: created_at or updated_at. Prefix with - for newest first (e.g. -updated_at). If not specified, results are sorted by creation time, newest first
`page`	X	integer	Page number, starting from 1. Returns 404 if beyond the last page
`pageSize`	X	integer	Number of items per page. Default 20, maximum 100 (values above 100 are treated as 100)
`search`	X	string	Keyword. Matches the scenario or the expected outcome (expected_outcome) (partial match, case-insensitive; when multiple keywords are separated by spaces, all of them must match)

status	X	string	Lists only multi-turn conversation test cases with this status. Allowed values: `active`: Active ; `inactive`: Inactive;

Code Examples

Shell/Bash

```
# API call example (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/multi-turn-test-case/?
dataset=550e8400-e29b-41d4-a716-446655440000&datasetId=550e8400-
e29b-41d4-a716-
446655440000&ordering=example&page=1&pageSize=1&search=example&statu
s=active"

  -H "Authorization: Api-Key YOUR_API_KEY"

# Make sure to replace YOUR_API_KEY and verify the request data
before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/multi-turn-test-case/?
dataset=550e8400-e29b-41d4-a716-446655440000&datasetId=550e8400-
e29b-41d4-a716-
446655440000&ordering=example&page=1&pageSize=1&search=example&statu
s=active", config)
  .then(response => {
    console.log('Successfully retrieved the response:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('An error occurred during the request:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/multi-turn-test-case/?
dataset=550e8400-e29b-41d4-a716-446655440000&datasetId=550e8400-
e29b-41d4-a716-
446655440000&ordering=example&page=1&pageSize=1&search=example&statu
s=active"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("Successfully retrieved the response:")
    print(response.json())
except Exception as e:
    print("An error occurred during the request:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->get("https://api.maiagent.ai/api/v1/multi-turn-test-case/?dataset=550e8400-e29b-41d4-a716-446655440000&datasetId=550e8400-e29b-41d4-a716-446655440000&ordering=example&page=1&pageSize=1&search=example&status=active", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Successfully retrieved the response:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'An error occurred during the request: ' . $e->getMessage();
}
?>
```

Response Body

Status Code: 200

Response Schema Example

```
{
  "count": integer
  "next"?: string (uri) // Optional
  "previous"?: string (uri) // Optional
  "results": [
    {
      "id": string (uuid)
      "dataset":
      {
        "id": string (uuid)
        "name": string
      }
      "scenario": string // Task scenario the simulated user should
accomplish
      "expectedOutcome": string // Outcome a successful conversation
should reach, also used as the simulation stop condition
      "userDescription"?: string // Persona of the simulated user, such
as tone, background and level of expertise (Optional)
      "status"?: string (enum: active, inactive) // * `active` - Active
* `inactive` - Inactive (Optional)
      "creationMethod":
      {
      }
      "sourceFile": string // Name of the knowledge base file this multi-
turn test case was generated from
      "flaky"?: boolean // Flaky test cases still run and keep their
results, but are excluded from the pass rate. (Optional)
      "createdAt": string (timestamp)
      "updatedAt": string (timestamp)
    }
  ]
}
```

Example Response Values

```
{
  "count": 123,
  "next": "http://api.example.org/accounts/?page=4",
  "previous": "http://api.example.org/accounts/?page=2",
  "results": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "dataset": {
```

```
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "name": "Response string"
      },
      "scenario": "Response string",
      "expectedOutcome": "Response string",
      "userDescription": "Response string",
      "status": "active",
      "creationMethod": {},
      "sourceFile": "Response string",
      "flaky": false,
      "createdAt": "Response string",
      "updatedAt": "Response string"
    }
  ]
}
```


Create a multi-turn test case

POST `/api/v1/multi-turn-test-case/`

datasetId, scenario (the task scenario the simulated user should accomplish), and expectedOutcome (the outcome a successful conversation should reach, which is also the stop condition for the simulated conversation) are required; userDescription is optional and describes the simulated user's tone, background, and level of expertise.

Request

Request Parameters

Field	Type	Required	Description
datasetId	string (uuid)	Yes	
scenario	string	Yes	
expectedOutcome	string	Yes	

Field	Type	Required	Description
userDescription	string	No	
status	object	No	
flaky	boolean	No	

Request Schema Example

```
{
  "datasetId": string (uuid)
  "scenario": string
  "expectedOutcome": string
  "userDescription"?: string // Optional
  "status"?:  // Optional
  {
  }
  "flaky"?: boolean // Optional
}
```

Request Example Values

```
{
  "datasetId": "550e8400-e29b-41d4-a716-446655440000",
  "scenario": "Example string",
  "expectedOutcome": "Example string",
  "userDescription": "Example string",
  "status": {},
  "flaky": true
}
```

Code Examples

Shell/Bash

```
# API call example (Shell)
curl -X POST "https://api.maiagent.ai/api/v1/multi-turn-test-case/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "datasetId": "550e8400-e29b-41d4-a716-446655440000",
    "scenario": "Example string",
    "expectedOutcome": "Example string",
    "userDescription": "Example string",
    "status": {},
    "flaky": true
  }'

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// Request body (payload)
const data = {
    "datasetId": "550e8400-e29b-41d4-a716-446655440000",
    "scenario": "Example string",
    "expectedOutcome": "Example string",
    "userDescription": "Example string",
    "status": {},
    "flaky": true
  };

axios.post("https://api.maiagent.ai/api/v1/multi-turn-test-case/",
data, config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/multi-turn-test-case/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# Request body (payload)
data = {
    "datasetId": "550e8400-e29b-41d4-a716-446655440000",
    "scenario": "Example string",
    "expectedOutcome": "Example string",
    "userDescription": "Example string",
    "status": {},
    "flaky": True
}

response = requests.post(url, json=data, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->post("https://api.maiagent.ai/api/v1/multi-turn-test-case/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'datasetId' => '550e8400-e29b-41d4-a716-446655440000',
            'scenario' => 'Example string',
            'expectedOutcome' => 'Example string',
            'userDescription' => 'Example string',
            'status' => new \stdClass(),
            'flaky' => true
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response

Status code: 201

Response Schema Example

```
{
  "id": string (uuid)
  "dataset":
  {
    "id": string (uuid)
    "name": string
  }
  "scenario": string // Task scenario the simulated user should
accomplish
  "expectedOutcome": string // Outcome a successful conversation should
reach, also used as the simulation stop condition
  "userDescription"?: string // Persona of the simulated user, such as
tone, background and level of expertise (Optional)
  "status"?: string (enum: active, inactive) // * `active` - Active
* `inactive` - Inactive (Optional)
  "creationMethod":
  {
  }
  "sourceFile": string // Name of the knowledge base file this multi-turn
test case was generated from
  "flaky"?: boolean // Flaky test cases still run and keep their results,
but are excluded from the pass rate. (Optional)
  "createdAt": string (timestamp)
  "updatedAt": string (timestamp)
}
```

Response Example Values

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "dataset": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Response string"
  },
  "scenario": "Response string",
  "expectedOutcome": "Response string",
  "userDescription": "Response string",
  "status": "active",
  "creationMethod": {},
```

```
  "sourceFile": "Response string",
  "flaky": false,
  "createdAt": "Response string",
  "updatedAt": "Response string"
}
```

Generate Multi-Turn Test Cases from Knowledge Base Files

POST `/api/v1/multi-turn-test-case/generate-from-file/`

Specify the source files with knowledgeBaseFileIds; numTestCases defaults to 5 and allows at most 20. Generation runs in the background and returns 202 with a jobId; track it with Retrieve test case generation job progress. Credit: Same as single-turn generation; agentops_test_gen is deducted based on the number of questions actually generated.

Request Content

Request Parameters

Field	Type	Required	Description
datasetId	string (uuid)	Yes	
knowledgeBaseFileIds	array[string]	Yes	List of KnowledgeBaseFile IDs to generate multi-turn test cases from
numTestCases	integer	No	

Example Request Structure

```
{
  "datasetId": string (uuid)
  "knowledgeBaseFileIds": [ // List of KnowledgeBaseFile IDs to generate
multi-turn test cases from
    string (uuid)
```

```
  ]
  "numTestCases"?: integer // Optional
}
```

Example Request Values

```
{
  "datasetId": "550e8400-e29b-41d4-a716-446655440000",
  "knowledgeBaseFileIds": [
    "550e8400-e29b-41d4-a716-446655440000"
  ],
  "numTestCases": 123
}
```

Code Examples

Shell/Bash

```
# API call example (Shell)
curl -X POST "https://api.maiagent.ai/api/v1/multi-turn-test-
case/generate-from-file/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "datasetId": "550e8400-e29b-41d4-a716-446655440000",
    "knowledgeBaseFileIds": [
      "550e8400-e29b-41d4-a716-446655440000"
    ],
    "numTestCases": 123
  }'

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// Request payload
const data = {
    "datasetId": "550e8400-e29b-41d4-a716-446655440000",
    "knowledgeBaseFileIds": [
      "550e8400-e29b-41d4-a716-446655440000"
    ],
    "numTestCases": 123
  };

axios.post("https://api.maiagent.ai/api/v1/multi-turn-test-
case/generate-from-file/", data, config)
  .then(response => {
    console.log('Successfully retrieved the response:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('An error occurred during the request:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/multi-turn-test-case/generate-
from-file/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# Request payload
data = {
    "datasetId": "550e8400-e29b-41d4-a716-446655440000",
    "knowledgeBaseFileIds": [
        "550e8400-e29b-41d4-a716-446655440000"
    ],
    "numTestCases": 123
}

response = requests.post(url, json=data, headers=headers)
try:
    print("Successfully retrieved the response:")
    print(response.json())
except Exception as e:
    print("An error occurred during the request:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->post("https://api.maiagent.ai/api/v1/multi-turn-test-case/generate-from-file/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'datasetId' => '550e8400-e29b-41d4-a716-446655440000',
            'knowledgeBaseFileIds' => [
                '550e8400-e29b-41d4-a716-446655440000'
            ],
            'numTestCases' => 123
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Successfully retrieved the response:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'An error occurred during the request: ' . $e->getMessage();
}
?>
```

Response Content

Status Code: 202

Example Response Structure

```
{
  "status": string (enum: accepted) // * `accepted` - Always accepted,
indicating the request has been accepted and queued for background
execution
  "message": string // Acceptance message
  "jobId": string (uuid) // Generation job ID; use GET /api/v1/test-
case/generation-jobs/{jobId}/ to check progress. If the same test set
already has a generation job in progress, that job is returned
  "taskId": string // Background task ID
}
```

Example Response Values

```
{
  "status": "accepted",
  "message": "Response string",
  "jobId": "550e8400-e29b-41d4-a716-446655440000",
  "taskId": "Response string"
}
```

Retrieve a Specific Multi-Turn Test Case

GET `/api/v1/multi-turn-test-case/{id}`

Parameters

Parameter	Required	Type	Description

id	V	string	Multi-turn test case ID

Code Examples

Shell/Bash

```
# API call example (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/multi-turn-test-
case/550e8400-e29b-41d4-a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/multi-turn-test-
case/550e8400-e29b-41d4-a716-446655440000/", config)
  .then(response => {
    console.log('Successfully retrieved the response:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('An error occurred during the request:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/multi-turn-test-case/550e8400-
e29b-41d4-a716-446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("Successfully retrieved the response:")
    print(response.json())
except Exception as e:
    print("An error occurred during the request:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->get("https://api.maiagent.ai/api/v1/multi-turn-test-case/550e8400-e29b-41d4-a716-446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Successfully retrieved the response:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'An error occurred during the request: ' . $e->getMessage();
}
?>
```

Response Content

Status Code: 200

Example Response Structure

```
{
  "id": string (uuid)
  "dataset":
```

```
  {
    "id": string (uuid)
    "name": string
  }
  "scenario": string // Task scenario the simulated user should
accomplish
  "expectedOutcome": string // Outcome a successful conversation should
reach, also used as the simulation stop condition
  "userDescription"?: string // Persona of the simulated user, such as
tone, background and level of expertise (Optional)
  "status"?: string (enum: active, inactive) // * `active` - Active
* `inactive` - Inactive (Optional)
  "creationMethod":
  {
  }
  "sourceFile": string // Name of the knowledge base file this multi-turn
test case was generated from
  "flaky"?: boolean // Flaky test cases still run and keep their results,
but are excluded from the pass rate. (Optional)
  "createdAt": string (timestamp)
  "updatedAt": string (timestamp)
}
```

Example Response Values

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "dataset": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Response string"
  },
  "scenario": "Response string",
  "expectedOutcome": "Response string",
  "userDescription": "Response string",
  "status": "active",
  "creationMethod": {},
  "sourceFile": "Response string",
  "flaky": false,
  "createdAt": "Response string",
  "updatedAt": "Response string"
}
```

Update a Multi-Turn Test Case

PUT `/api/v1/multi-turn-test-case/{id}`

Parameters

Parameter	Required	Type	Description
`id`	V	string	Multi-turn test case ID

Request Content

Request Parameters

Field	Type	Required	Description
scenario	string	Yes	Task scenario the simulated user should accomplish
expectedOutcome	string	Yes	Outcome a successful conversation should reach, also used as the simulation stop condition
userDescription	string	No	Persona of the simulated user, such as tone, background and level of expertise
status	string (enum: active, inactive)	No	`active` : Active ; `inactive` : Inactive;
flaky	boolean	No	Flaky test cases still run and keep their results, but are excluded from the pass rate.

Example Request Structure

```
{
  "scenario": string // Task scenario the simulated user should
accomplish
  "expectedOutcome": string // Outcome a successful conversation should
reach, also used as the simulation stop condition
  "userDescription"?: string // Persona of the simulated user, such as
tone, background and level of expertise (Optional)
  "status"?: string (enum: active, inactive) // * `active` - Active
* `inactive` - Inactive (Optional)
  "flaky"?: boolean // Flaky test cases still run and keep their results,
but are excluded from the pass rate. (Optional)
}
```

Example Request Values

```
{
  "scenario": "Example string",
  "expectedOutcome": "Example string",
  "userDescription": "Example string",
  "status": "active",
  "flaky": true
}
```

Code Examples

Shell/Bash

```
# API call example (Shell)
curl -X PUT "https://api.maiagent.ai/api/v1/multi-turn-test-
case/550e8400-e29b-41d4-a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "scenario": "Example string",
    "expectedOutcome": "Example string",
    "userDescription": "Example string",
    "status": "active",
    "flaky": true
  }'

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// Request payload
const data = {
    "scenario": "Example string",
    "expectedOutcome": "Example string",
    "userDescription": "Example string",
    "status": "active",
    "flaky": true
  };

axios.put("https://api.maiagent.ai/api/v1/multi-turn-test-
case/550e8400-e29b-41d4-a716-446655440000/", data, config)
  .then(response => {
    console.log('Successfully retrieved the response:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('An error occurred during the request:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/multi-turn-test-case/550e8400-
e29b-41d4-a716-446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# Request payload
data = {
    "scenario": "Example string",
    "expectedOutcome": "Example string",
    "userDescription": "Example string",
    "status": "active",
    "flaky": True
}

response = requests.put(url, json=data, headers=headers)
try:
    print("Successfully retrieved the response:")
    print(response.json())
except Exception as e:
    print("An error occurred during the request:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->put("https://api.maiagent.ai/api/v1/multi-turn-test-case/550e8400-e29b-41d4-a716-446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'scenario' => 'Example string',
            'expectedOutcome' => 'Example string',
            'userDescription' => 'Example string',
            'status' => 'active',
            'flaky' => true
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Successfully retrieved the response:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'An error occurred during the request: ' . $e->getMessage();
}
?>
```

Response Content

Status Code: 200

Example Response Structure

```
{
  "id": string (uuid)
  "dataset":
  {
    "id": string (uuid)
    "name": string
  }
  "scenario": string // Task scenario the simulated user should
accomplish
  "expectedOutcome": string // Outcome a successful conversation should
reach, also used as the simulation stop condition
  "userDescription"?: string // Persona of the simulated user, such as
tone, background and level of expertise (Optional)
  "status"?: string (enum: active, inactive) // * `active` - Active
* `inactive` - Inactive (Optional)
  "creationMethod":
  {
  }
  "sourceFile": string // Name of the knowledge base file this multi-turn
test case was generated from
  "flaky"?: boolean // Flaky test cases still run and keep their results,
but are excluded from the pass rate. (Optional)
  "createdAt": string (timestamp)
  "updatedAt": string (timestamp)
}
```

Example Response Values

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "dataset": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Response string"
  },
  "scenario": "Response string",
  "expectedOutcome": "Response string",
  "userDescription": "Response string",
  "status": "active",
  "creationMethod": {},
```

```
  "sourceFile": "Response string",
  "flaky": false,
  "createdAt": "Response string",
  "updatedAt": "Response string"
}
```


Partially Update a Multi-Turn Test Case

PATCH `/api/v1/multi-turn-test-case/{id}`

Parameters

Parameter	Required	Type	Description
`id`	V	string	Multi-turn test case ID

Request Content

Request Parameters

Field	Type	Required	Description
scenario	string	No	Task scenario the simulated user should accomplish
expectedOutcome	string	No	Outcome a successful conversation should reach, also used as the simulation stop condition
userDescription	string	No	Persona of the simulated user, such as tone, background and level of expertise

Field	Type	Required	Description
status	string (enum: active, inactive)	No	`active` : Active ; `inactive` : Inactive;
flaky	boolean	No	Flaky test cases still run and keep their results, but are excluded from the pass rate.

Example Request Structure

```
{
  "scenario"?: string // Task scenario the simulated user should accomplish (Optional)
  "expectedOutcome"?: string // Outcome a successful conversation should reach, also used as the simulation stop condition (Optional)
  "userDescription"?: string // Persona of the simulated user, such as tone, background and level of expertise (Optional)
  "status"?: string (enum: active, inactive) // * `active` - Active * `inactive` - Inactive (Optional)
  "flaky"?: boolean // Flaky test cases still run and keep their results, but are excluded from the pass rate. (Optional)
}
```

Example Request Values

```
{
  "scenario": "Example string",
  "expectedOutcome": "Example string",
  "userDescription": "Example string",
  "status": "active",
  "flaky": true
}
```

Code Examples

Shell/Bash

```
# API call example (Shell)
curl -X PATCH "https://api.maiagent.ai/api/v1/multi-turn-test-
case/550e8400-e29b-41d4-a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "scenario": "Example string",
    "expectedOutcome": "Example string",
    "userDescription": "Example string",
    "status": "active",
    "flaky": true
  }'

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// Request payload
const data = {
    "scenario": "Example string",
    "expectedOutcome": "Example string",
    "userDescription": "Example string",
    "status": "active",
    "flaky": true
  };

axios.patch("https://api.maiagent.ai/api/v1/multi-turn-test-
case/550e8400-e29b-41d4-a716-446655440000/", data, config)
  .then(response => {
    console.log('Successfully retrieved the response:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('An error occurred during the request:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/multi-turn-test-case/550e8400-
e29b-41d4-a716-446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# Request payload
data = {
    "scenario": "Example string",
    "expectedOutcome": "Example string",
    "userDescription": "Example string",
    "status": "active",
    "flaky": True
}

response = requests.patch(url, json=data, headers=headers)
try:
    print("Successfully retrieved the response:")
    print(response.json())
except Exception as e:
    print("An error occurred during the request:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->patch("https://api.maiagent.ai/api/v1/multi-turn-test-case/550e8400-e29b-41d4-a716-446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'scenario' => 'Example string',
            'expectedOutcome' => 'Example string',
            'userDescription' => 'Example string',
            'status' => 'active',
            'flaky' => true
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Successfully retrieved the response:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'An error occurred during the request: ' . $e->getMessage();
}
?>
```

Response Content

Status Code: 200

Example Response Structure

```
{
  "id": string (uuid)
  "dataset":
  {
    "id": string (uuid)
    "name": string
  }
  "scenario": string // Task scenario the simulated user should
accomplish
  "expectedOutcome": string // Outcome a successful conversation should
reach, also used as the simulation stop condition
  "userDescription"?: string // Persona of the simulated user, such as
tone, background and level of expertise (Optional)
  "status"?: string (enum: active, inactive) // * `active` - Active
* `inactive` - Inactive (Optional)
  "creationMethod":
  {
  }
  "sourceFile": string // Name of the knowledge base file this multi-turn
test case was generated from
  "flaky"?: boolean // Flaky test cases still run and keep their results,
but are excluded from the pass rate. (Optional)
  "createdAt": string (timestamp)
  "updatedAt": string (timestamp)
}
```

Example Response Values

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "dataset": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Response string"
  },
  "scenario": "Response string",
  "expectedOutcome": "Response string",
  "userDescription": "Response string",
  "status": "active",
  "creationMethod": {},
```

```
  "sourceFile": "Response string",
  "flaky": false,
  "createdAt": "Response string",
  "updatedAt": "Response string"
}
```


Delete a Multi-Turn Test Case

DELETE `/api/v1/multi-turn-test-case/{id}`

Parameters

Parameter	Required	Type	Description
`id`	V	string	Multi-turn test case ID

Code Examples

Shell/Bash

```
# API call example (Shell)
curl -X DELETE "https://api.maiagent.ai/api/v1/multi-turn-test-
case/550e8400-e29b-41d4-a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

// Request body (payload)
const data = null;

axios.delete("https://api.maiagent.ai/api/v1/multi-turn-test-
case/550e8400-e29b-41d4-a716-446655440000/", data, config)
  .then(response => {
    console.log('Successfully retrieved the response:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/multi-turn-test-case/550e8400-e29b-41d4-a716-446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.delete(url, headers=headers)
try:
    print("Successfully retrieved the response:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>delete("https://api.maiagent.ai/api/v1/multi-turn-test-
case/550e8400-e29b-41d4-a716-446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Successfully retrieved the response:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response Body

Status Code	Description
204	No response body

List Available Evaluation Models

`GET` `/api/v1/evaluations/evaluation-llms/`

The model whose isDefault is true is the default evaluation model used when evaluationLlmId is not specified for an evaluation run.

Code Examples

Shell/Bash

```
# API call example (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/evaluations/evaluation-
llms/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# Make sure to replace YOUR_API_KEY and verify the request data
before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/evaluations/evaluation-
llms/", config)
  .then(response => {
    console.log('Successfully retrieved the response:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/evaluations/evaluation-llms/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("Successfully retrieved the response:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/evaluations/evaluation-llms/",
[
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Successfully retrieved the response:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response Body

Status Code: 200

Response Schema Example

```
[
  {
    "id": string (uuid)
```

```
    "name": string
    "value": string
    "provider": string
    "isDefault": boolean
  }
]
```

Example Response Values

```
[
  {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Response string",
    "value": "Response string",
    "provider": "Response string",
    "isDefault": false
  }
]
```

Run Single-Turn Evaluation

POST `/api/v1/evaluations/evaluate/`

datasetId and chatbotId are required; if evaluationLlmId is omitted, the default evaluation model is used. metricConfig turns built-in metrics on or off with boolean values, and customMetrics accepts up to 10 custom metrics. Only test cases with the active status are evaluated. The evaluation runs in the background and the response is 202 with an evaluationId. Credit: The organization's Credit is checked before submission, and 402 is returned if it is insufficient; when the evaluation finishes, agentops_test_run and agentops_deepeval are deducted based on the number of completed test cases, and calls to the evaluation model are charged separately.

Request Content

Request Parameters

Field	Type	Required	Description
datasetId	string (uuid)	Yes	
chatbotId	string (uuid)	Yes	
evaluationLlmId	string (uuid)	No	
name	string	No	
description	string	No	
metricConfig	object	No	
customMetrics	array[DatasetEvaluationCustomMetric]	No	

Example Request Structure

```
{
  "datasetId": string (uuid)
  "chatbotId": string (uuid)
  "evaluationLlmId"?: string (uuid) // Optional
  "name"?: string // Optional
  "description"?: string // Optional
  "metricConfig"?: object // Optional
  "customMetrics"?: [ // Optional
    {
      "name": string
      "criteria"?: string // Optional
      "evaluationSteps"?: [ // Optional
        string
      ]
      "threshold"?: number (double) // Optional
    }
  ]
}
```

Example Request Values

```
{
  "dataset_id": "3fa85f64-5717-4562-b3fc-2c963f66afa6",
  "chatbot_id": "3fa85f64-5717-4562-b3fc-2c963f66afa6",
  "evaluation_llm_id": "3fa85f64-5717-4562-b3fc-2c963f66afa6",
  "name": "Evaluation Name",
```

```
  "description": "Evaluation Description",
  "metric_config": {
    "ground_truth": true,
    "task_completion": false,
    "tool_correctness": false,
    "guardrail": true,
    "summarize": false,
    "hallucination": true
  },
  "custom_metrics": [
    {
      "name": "Support Tone",
      "criteria": "The answer should be polite, empathetic, and
professional in tone.",
      "threshold": 0.6
    }
  ]
}
```

Code Examples

Shell/Bash

```
# API call example (Shell)
curl -X POST "https://api.maiagent.ai/api/v1/evaluations/evaluate/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "dataset_id": "3fa85f64-5717-4562-b3fc-2c963f66afa6",
    "chatbot_id": "3fa85f64-5717-4562-b3fc-2c963f66afa6",
    "evaluation_llm_id": "3fa85f64-5717-4562-b3fc-2c963f66afa6",
    "name": "Evaluation Name",
    "description": "Evaluation Description",
    "metric_config": {
      "ground_truth": true,
      "task_completion": false,
      "tool_correctness": false,
      "guardrail": true,
      "summarize": false,
      "hallucination": true
    },
    "custom_metrics": [
      {
        "name": "Support Tone",
        "criteria": "The answer should be polite, empathetic, and
professional in tone.",
        "threshold": 0.6
      }
    ]
  }'

# Make sure to replace YOUR_API_KEY and verify the request data
before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// Request body (payload)
const data = {
    "dataset_id": "3fa85f64-5717-4562-b3fc-2c963f66afa6",
    "chatbot_id": "3fa85f64-5717-4562-b3fc-2c963f66afa6",
    "evaluation_llm_id": "3fa85f64-5717-4562-b3fc-2c963f66afa6",
    "name": "Evaluation Name",
    "description": "Evaluation Description",
    "metric_config": {
      "ground_truth": true,
      "task_completion": false,
      "tool_correctness": false,
      "guardrail": true,
      "summarize": false,
      "hallucination": true
    },
    "custom_metrics": [
      {
        "name": "Support Tone",
        "criteria": "The answer should be polite, empathetic, and
professional in tone.",
        "threshold": 0.6
      }
    ]
  };

axios.post("https://api.maiagent.ai/api/v1/evaluations/evaluate/",
data, config)
  .then(response => {
    console.log('Successfully retrieved the response:');
    console.log(response.data);
```

```
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/evaluations/evaluate/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# Request body (payload)
data = {
    "dataset_id": "3fa85f64-5717-4562-b3fc-2c963f66afa6",
    "chatbot_id": "3fa85f64-5717-4562-b3fc-2c963f66afa6",
    "evaluation_llm_id": "3fa85f64-5717-4562-b3fc-2c963f66afa6",
    "name": "Evaluation Name",
    "description": "Evaluation Description",
    "metric_config": {
        "ground_truth": True,
        "task_completion": False,
        "tool_correctness": False,
        "guardrail": True,
        "summarize": False,
        "hallucination": True
    },
    "custom_metrics": [
        {
            "name": "Support Tone",
            "criteria": "The answer should be polite, empathetic,
and professional in tone.",
            "threshold": 0.6
        }
    ]
}

response = requests.post(url, json=data, headers=headers)
try:
    print("Successfully retrieved the response:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>post("https://api.maiagent.ai/api/v1/evaluations/evaluate/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'dataset_id' => '3fa85f64-5717-4562-b3fc-2c963f66afa6',
            'chatbot_id' => '3fa85f64-5717-4562-b3fc-2c963f66afa6',
            'evaluation_llm_id' => '3fa85f64-5717-4562-b3fc-
2c963f66afa6',
            'name' => 'Evaluation Name',
            'description' => 'Evaluation Description',
            'metric_config' => [
                'ground_truth' => true,
                'task_completion' => false,
                'tool_correctness' => false,
                'guardrail' => true,
                'summarize' => false,
                'hallucination' => true
            ],
            'custom_metrics' => [
                [
                    'name' => 'Support Tone',
                    'criteria' => 'The answer should be polite,
empathetic, and professional in tone.',
                    'threshold' => 0.6
                ]
            ]
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Successfully retrieved the response:\n";
```

```
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response Body

Status Code: 202

Response Schema Example

```
{
  "status": string (enum: accepted) // * `accepted` - Always accepted,
indicating the request has been accepted and queued for background
execution
  "message": string // Acceptance message
  "evaluationId": string (uuid) // Evaluation ID; poll status with GET
/api/v1/evaluations/{id}/ until it finishes
}
```

Example Response Values

```
{
  "status": "accepted",
  "message": "Response string",
  "evaluationId": "550e8400-e29b-41d4-a716-446655440000"
}
```

Run Multi-Turn Evaluation

POST `/api/v1/evaluations/multi-turn-evaluate/`

Simulates a conversation between a user and the Agent using the multi-turn test cases in the test set, then scores it. maxTurns is the maximum number of turns the simulated user speaks (2–10, default 6), and language is the language of the simulated user (Traditional Chinese, Simplified Chinese, English, Japanese, Korean; default Traditional Chinese). Returns 400 if the test set has no active multi-turn test cases. The response and Credit handling are the same as Run a single-turn evaluation.

Request Content

Request Parameters

Field	Type	Required	Description
datasetId	string (uuid)	Yes	
chatbotId	string (uuid)	Yes	
evaluationLlmId	string (uuid)	No	
name	string	No	
description	string	No	
maxTurns	integer	No	
minTurns	integer	No	
turnFaithfulness	boolean	No	
turnRelevancy	boolean	No	
conversationCompleteness	boolean	No	
language	object	No	
customMetrics	array[MultiTurnCustomMetric]	No	

Example Request Structure

```
{
  "datasetId": string (uuid)
  "chatbotId": string (uuid)
  "evaluationLlmId"?: string (uuid) // Optional
```

```
  "name"?: string // Optional
  "description"?: string // Optional
  "maxTurns"?: integer // Optional
  "minTurns"?: integer // Optional
  "turnFaithfulness"?: boolean // Optional
  "turnRelevancy"?: boolean // Optional
  "conversationCompleteness"?: boolean // Optional
  "language"?:  // Optional
  {
  }
  "customMetrics"?: [ // Optional
    {
      "name": string
      "criteria"?: string // Optional
      "evaluationSteps"?: [ // Optional
        string
      ]
      "threshold"?: number (double) // Optional
    }
  ]
}
```

Example Request Values

```
{
  "dataset_id": "3fa85f64-5717-4562-b3fc-2c963f66afa6",
  "chatbot_id": "3fa85f64-5717-4562-b3fc-2c963f66afa6",
  "max_turns": 6,
  "min_turns": 2,
  "custom_metrics": [
    {
      "name": "Identity Check",
      "criteria": "The assistant confirms the user identity before
sharing account details.",
      "threshold": 0.6
    }
  ]
}
```

Code Examples

Shell/Bash

```
# API call example (Shell)
curl -X POST "https://api.maiagent.ai/api/v1/evaluations/multi-turn-evaluate/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "dataset_id": "3fa85f64-5717-4562-b3fc-2c963f66afa6",
    "chatbot_id": "3fa85f64-5717-4562-b3fc-2c963f66afa6",
    "max_turns": 6,
    "min_turns": 2,
    "custom_metrics": [
      {
        "name": "Identity Check",
        "criteria": "The assistant confirms the user identity before sharing account details.",
        "threshold": 0.6
      }
    ]
  }'

# Make sure to replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// Request body (payload)
const data = {
    "dataset_id": "3fa85f64-5717-4562-b3fc-2c963f66afa6",
    "chatbot_id": "3fa85f64-5717-4562-b3fc-2c963f66afa6",
    "max_turns": 6,
    "min_turns": 2,
    "custom_metrics": [
      {
        "name": "Identity Check",
        "criteria": "The assistant confirms the user identity before
sharing account details.",
        "threshold": 0.6
      }
    ]
  };

axios.post("https://api.maiagent.ai/api/v1/evaluations/multi-turn-
evaluate/", data, config)
  .then(response => {
    console.log('Successfully retrieved the response:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/evaluations/multi-turn-
evaluate/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# Request body (payload)
data = {
    "dataset_id": "3fa85f64-5717-4562-b3fc-2c963f66afa6",
    "chatbot_id": "3fa85f64-5717-4562-b3fc-2c963f66afa6",
    "max_turns": 6,
    "min_turns": 2,
    "custom_metrics": [
        {
            "name": "Identity Check",
            "criteria": "The assistant confirms the user identity
before sharing account details.",
            "threshold": 0.6
        }
    ]
}

response = requests.post(url, json=data, headers=headers)
try:
    print("Successfully retrieved the response:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>post("https://api.maiagent.ai/api/v1/evaluations/multi-turn-
evaluate/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'dataset_id' => '3fa85f64-5717-4562-b3fc-2c963f66afa6',
            'chatbot_id' => '3fa85f64-5717-4562-b3fc-2c963f66afa6',
            'max_turns' => 6,
            'min_turns' => 2,
            'custom_metrics' => [
                [
                    'name' => 'Identity Check',
                    'criteria' => 'The assistant confirms the user
identity before sharing account details.',
                    'threshold' => 0.6
                ]
            ]
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Successfully retrieved the response:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response Body

Status Code: 202

Response Schema Example

```
{
  "status": string (enum: accepted) // * `accepted` - Always accepted,
indicating the request has been accepted and queued for background
execution
  "message": string // Acceptance message
  "evaluationId": string (uuid) // Evaluation ID; poll status with GET
/api/v1/evaluations/{id}/ until it finishes
}
```

Example Response Values

```
{
  "status": "accepted",
  "message": "Response string",
  "evaluationId": "550e8400-e29b-41d4-a716-446655440000"
}
```

List Evaluations

GET `/api/v1/evaluations/`

Filter by datasetId, chatbotId, and status.

Parameters

Parameter	Required	Type	Description
`chatbotId`	X	string	List only evaluations of this AI assistant
`datasetId`	X	string	List only evaluations that use this dataset
`excludeBuiltIn`	X	string	When true, exclude data from official built-in Agents (locked instances created by renting from the Agent Marketplace), leaving only assistants created by the organization. Copies made with “Copy as Custom” count as custom assistants. Omitting this parameter or setting it to false applies no such filter.
`ordering`	X	string	Sort by created_at or updated_at. Prefix with - for newest first (e.g., -updated_at). Defaults to creation time, newest first
`page`	X	integer	Page number, starting at 1; returns 404 if the number exceeds the last page
`pageSize`	X	integer	Results per page; defaults to 20, with a maximum of 100 (values above 100 are capped at 100)
`query`	X	string	Keyword matched against the evaluation name, description, or ID (partial match)
`search`	X	string	Keyword matched against the evaluation name, dataset name, or AI assistant name (case-insensitive partial match; all space-separated keywords must match)
`status`	X	string	List only evaluations with this status. Allowed values: `pending`: Pending evaluation ; `running`: Evaluating ; `stopping`: Stopping ; `completed`: Completed ; `partial_completed`: Partially completed ; `failed`: Evaluation failed;

Code Examples

Shell/Bash

```
# Example API call (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/evaluations/?
chatbotId=550e8400-e29b-41d4-a716-446655440000&datasetId=550e8400-
e29b-41d4-a716-
446655440000&excludeBuiltIn=example&ordering=example&page=1&pageSize
=1&query=example&search=example&status=completed"

  -H "Authorization: Api-Key YOUR_API_KEY"

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/evaluations/?
chatbotId=550e8400-e29b-41d4-a716-446655440000&datasetId=550e8400-
e29b-41d4-a716-
446655440000&excludeBuiltIn=example&ordering=example&page=1&pageSize
=1&query=example&search=example&status=completed", config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/evaluations/?
chatbotId=550e8400-e29b-41d4-a716-446655440000&datasetId=550e8400-
e29b-41d4-a716-
446655440000&excludeBuiltIn=example&ordering=example&page=1&pageSize
=1&query=example&search=example&status=completed"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/evaluations/?
chatbotId=550e8400-e29b-41d4-a716-446655440000&datasetId=550e8400-
e29b-41d4-a716-
446655440000&excludeBuiltIn=example&ordering=example&page=1&pageSize
=1&query=example&search=example&status=completed", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response Body

Status code: 200

Example Response Schema

```
{
  "count": integer
  "next"?: string (uri) // Optional
  "previous"?: string (uri) // Optional
  "results": [
    {
      "id": string (uuid)
      "name": string
      "description": string
      "chatbot":
      {
        "id": string (uuid)
        "name": string
      }
      "dataset":
      {
        "id": string (uuid)
        "name": string
      }
      "organization":
      {
        "id": string (uuid)
        "name": string
      }
      "evaluationLlm":
      {
        "id": string (uuid)
        "name": string
      }
      "status":
      {
      }
      "startedAt": string (timestamp)
      "completedAt": string (timestamp)
      "totalTestCases": integer
      "completedTestCases": integer
      "passedTestCases": integer // Number of test cases that passed
      "metricScores": object // Detailed score per evaluation metric,
such as ground_truth, task_completion and tool_correctness
      "evaluationConfig": object
      "progressPercentage": number (double)
      "overallScore": number (double)
      "passRate": number (double)
      "averageExecutionTimeMs": integer
```

```
      "totalExecutionTimeMs": integer
      "chatbotConfig": string
      "createdAt": string (timestamp)
      "updatedAt": string (timestamp)
      "insights":
      {
        "summary": string
        "metricStats"?: object // Optional
        "recommendations"?: object // Optional
      }
    }
  ]
}
```

Example Response Values


```
{
  "count": 123,
  "next": "http://api.example.org/accounts/?page=4",
  "previous": "http://api.example.org/accounts/?page=2",
  "results": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "Response string",
      "description": "Response string",
      "chatbot": {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "name": "Response string"
      },
      "dataset": {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "name": "Response string"
      },
      "organization": {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "name": "Response string"
      },
      "evaluationLlm": {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "name": "Response string"
      },
      "status": {},
      "startedAt": "Response string",
      "completedAt": "Response string",
```

```
      "totalTestCases": 456,
      "completedTestCases": 456,
      "passedTestCases": 456,
      "metricScores": null,
      "evaluationConfig": null,
      "progressPercentage": 456,
      "overallScore": 456,
      "passRate": 456,
      "averageExecutionTimeMs": 456,
      "totalExecutionTimeMs": 456,
      "chatbotConfig": "Response string",
      "createdAt": "Response string",
      "updatedAt": "Response string",
      "insights": {
        "summary": "Response string",
        "metricStats": null,
        "recommendations": null
      }
    }
  ]
}
```


Get Evaluation Result

`GET` `/api/v1/evaluations/{id}`

status is one of pending, running, stopping, completed, partial_completed, or failed. While running, check progressPercentage; once finished, check passRate, overallScore, and the per-metric metricScores. If no test case completes, the evaluation ends as failed.

Parameters

Parameter Name	Required	Type	Description

id	V	string	Evaluation ID

Code Examples

Shell/Bash

```
# API call example (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/evaluations/550e8400-
e29b-41d4-a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# Make sure to replace YOUR_API_KEY and verify the request data
before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/evaluations/550e8400-e29b-41d4-a716-446655440000/", config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/evaluations/550e8400-e29b-
41d4-a716-446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/evaluations/550e8400-e29b-41d4-
a716-446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response Content

Status code: 200

Example Response Structure

```
{
  "id": string (uuid)
  "name": string
```

```
  "description": string
  "chatbot":
  {
    "id": string (uuid)
    "name": string
  }
  "dataset":
  {
    "id": string (uuid)
    "name": string
  }
  "organization":
  {
    "id": string (uuid)
    "name": string
  }
  "evaluationLlm":
  {
    "id": string (uuid)
    "name": string
  }
  "status":
  {
  }
  "startedAt": string (timestamp)
  "completedAt": string (timestamp)
  "totalTestCases": integer
  "completedTestCases": integer
  "passedTestCases": integer // Number of test cases that passed
  "metricScores": object // Detailed score per evaluation metric, such as
ground_truth, task_completion and tool_correctness
  "evaluationConfig": object
  "progressPercentage": number (double)
  "overallScore": number (double)
  "passRate": number (double)
  "averageExecutionTimeMs": integer
  "totalExecutionTimeMs": integer
  "chatbotConfig": string
  "createdAt": string (timestamp)
  "updatedAt": string (timestamp)
  "insights":
  {
    "summary": string
    "metricStats"?: object // Optional
    "recommendations"?: object // Optional
```

```
  }
}
```

Example Response Values

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "name": "Response string",
  "description": "Response string",
  "chatbot": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Response string"
  },
  "dataset": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Response string"
  },
  "organization": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Response string"
  },
  "evaluationLlm": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Response string"
  },
  "status": {},
  "startedAt": "Response string",
  "completedAt": "Response string",
  "totalTestCases": 456,
  "completedTestCases": 456,
  "passedTestCases": 456,
  "metricScores": null,
  "evaluationConfig": null,
  "progressPercentage": 456,
  "overallScore": 456,
  "passRate": 456,
  "averageExecutionTimeMs": 456,
  "totalExecutionTimeMs": 456,
  "chatbotConfig": "Response string",
  "createdAt": "Response string",
  "updatedAt": "Response string",
  "insights": {
    "summary": "Response string",
    "metricStats": null,
```

```
    "recommendations": null
  }
}
```


List Per-Question Results of a Single-Turn Evaluation

GET `/api/v1/evaluations/{id}/details/`

Single-turn evaluations only; multi-turn evaluations return 400. The response is an array of all test case results and is not paginated.

Parameters

Parameter Name	Required	Type	Description
`id`	V	string	Evaluation ID

Code Examples

Shell/Bash

```
# API call example (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/evaluations/550e8400-
e29b-41d4-a716-446655440000/details/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# Make sure to replace YOUR_API_KEY and verify the request data
before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/evaluations/550e8400-e29b-
41d4-a716-446655440000/details/", config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/evaluations/550e8400-e29b-
41d4-a716-446655440000/details/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/evaluations/550e8400-e29b-41d4-
a716-446655440000/details/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response Content

Status code: 200

Example Response Structure

```
[
  {
    "id": string (uuid)
```

```
    "datasetEvaluation":
    {
      "id": string (uuid)
      "name": string
    }
    "testCase":
    {
      "id": string (uuid)
      "dataset":
      {
        "id": string (uuid)
        "name": string
      }
      "question": string
      "groundTruth"?: string // Optional
      "status"?: string (enum: active, inactive, pending) // * `active` -
Active
* `inactive` - Inactive
* `pending` - Pending Review (Optional)
      "creationMethod"?: string (enum: manual, file, generate) // *
`manual` - Manual
* `file` - File import
* `generate` - Generated (Optional)
      "sourceFile"?: string // Name of the CSV, Excel or knowledge base
file this test case came from (Optional)
      "flaky"?: boolean // Flaky test cases still run and keep their
results, but are excluded from the pass rate. (Optional)
      "createdAt": string (timestamp)
      "updatedAt": string (timestamp)
    }
    "status":
    {
    }
    "chatbotResponse": string
    "context": [ // Enrich each context item with is_deleted status for
referenced knowledge base files.
      object
    ]
    "metricScores": object
    "executionTimeMs": integer
    "executionTimeSeconds": number (double)
    "passed": boolean
    "errorMessage": string // Error message recorded when the evaluation
fails
    "startedAt": string (timestamp)
```

```
    "completedAt": string (timestamp)
    "retryCount": integer // Number of times this test case has been
retried
    "lastAttemptAt": string (timestamp) // Time of the last evaluation
attempt
    "createdAt": string (timestamp)
    "updatedAt": string (timestamp)
  }
]
```

Example Response Values

```
[
  {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "datasetEvaluation": {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "Response string"
    },
    "testCase": {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "dataset": {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "name": "Response string"
      },
      "question": "Response string",
      "groundTruth": "Response string",
      "status": "active",
      "creationMethod": "manual",
      "sourceFile": "Response string",
      "flaky": false,
      "createdAt": "Response string",
      "updatedAt": "Response string"
    },
    "status": {},
    "chatbotResponse": "Response string",
    "context": [
      {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "name": "Example name",
        "description": "Example description"
      }
    ],
    "metricScores": null,
```

```
    "executionTimeMs": 456,
    "executionTimeSeconds": 456,
    "passed": false,
    "errorMessage": "Response string",
    "startedAt": "Response string",
    "completedAt": "Response string",
    "retryCount": 456,
    "lastAttemptAt": "Response string",
    "createdAt": "Response string",
    "updatedAt": "Response string"
  }
]
```


List Per-Conversation Results of a Multi-Turn Evaluation

`GET` `/api/v1/evaluations/{id}/multi-turn-results/`

Multi-turn evaluations only; single-turn evaluations return 400. The response is paginated.

Parameters

Parameter Name	Required	Type	Description
`id`	V	string	Evaluation ID
`page`	X	integer	Page number, starting from 1; a page beyond the last page returns 404
`pageSize`	X	integer	Items per page. Default 20, maximum 100 (values above 100 are treated as 100)

Code Examples

Shell/Bash

```
# API call example (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/evaluations/550e8400-
e29b-41d4-a716-446655440000/multi-turn-results/?page=1&pageSize=1"

  -H "Authorization: Api-Key YOUR_API_KEY"

# Make sure to replace YOUR_API_KEY and verify the request data
before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/evaluations/550e8400-e29b-
41d4-a716-446655440000/multi-turn-results/?page=1&pageSize=1",
config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/evaluations/550e8400-e29b-
41d4-a716-446655440000/multi-turn-results/?page=1&pageSize=1"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/evaluations/550e8400-e29b-41d4-
a716-446655440000/multi-turn-results/?page=1&pageSize=1", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response Content

Status code: 200

Example Response Structure

```
{
  "count": integer
  "next"?: string (uri) // Optional
```

```
  "previous"?: string (uri) // Optional
  "results": [
    {
      "id": string (uuid)
      "multiTurnTestCase": string (uuid)
      "scenario": string
      "expectedOutcome": string
      "flaky": boolean
      "status":
      {
      }
      "turns": object // The whole simulated conversation; each turn is
{role, content, retrieval_context}
      "metricScores": object
      "passed": boolean
      "errorMessage": string
      "startedAt": string (timestamp)
      "completedAt": string (timestamp)
      "createdAt": string (timestamp)
    }
  ]
}
```

Example Response Values

```
{
  "count": 123,
  "next": "http://api.example.org/accounts/?page=4",
  "previous": "http://api.example.org/accounts/?page=2",
  "results": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "multiTurnTestCase": "550e8400-e29b-41d4-a716-446655440000",
      "scenario": "Response string",
      "expectedOutcome": "Response string",
      "flaky": false,
      "status": {},
      "turns": null,
      "metricScores": null,
      "passed": false,
      "errorMessage": "Response string",
      "startedAt": "Response string",
      "completedAt": "Response string",
      "createdAt": "Response string"
```

```
    }
  ]
}
```

Cancel a Running Evaluation

POST `/api/v1/evaluations/{id}/cancel/`

Only evaluations whose status is running can be canceled; otherwise 400 is returned. After cancellation, status first becomes stopping and ends as partial_completed once stopped. Scores already calculated are kept, and completed test cases still consume Credit as usual. You can later run the remaining test cases with Resume an incomplete evaluation.

Parameters

Parameter Name	Required	Type	Description
`id`	V	string	Evaluation ID

Code Examples

Shell/Bash

```
# API call example (Shell)
curl -X POST "https://api.maiagent.ai/api/v1/evaluations/550e8400-
e29b-41d4-a716-446655440000/cancel/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# Make sure to replace YOUR_API_KEY and verify the request data
before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

// Request body (payload)
const data = null;

axios.post("https://api.maiagent.ai/api/v1/evaluations/550e8400-
e29b-41d4-a716-446655440000/cancel/", data, config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/evaluations/550e8400-e29b-
41d4-a716-446655440000/cancel/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.post(url, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>post("https://api.maiagent.ai/api/v1/evaluations/550e8400-e29b-
41d4-a716-446655440000/cancel/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response Content

Status code: 200

Example Response Structure

```
{
  "id": string (uuid)
  "name": string
```

```
  "description": string
  "chatbot":
  {
    "id": string (uuid)
    "name": string
  }
  "dataset":
  {
    "id": string (uuid)
    "name": string
  }
  "organization":
  {
    "id": string (uuid)
    "name": string
  }
  "evaluationLlm":
  {
    "id": string (uuid)
    "name": string
  }
  "status":
  {
  }
  "startedAt": string (timestamp)
  "completedAt": string (timestamp)
  "totalTestCases": integer
  "completedTestCases": integer
  "passedTestCases": integer // Number of test cases that passed
  "metricScores": object // Detailed score per evaluation metric, such as
ground_truth, task_completion and tool_correctness
  "evaluationConfig": object
  "progressPercentage": number (double)
  "overallScore": number (double)
  "passRate": number (double)
  "averageExecutionTimeMs": integer
  "totalExecutionTimeMs": integer
  "chatbotConfig": string
  "createdAt": string (timestamp)
  "updatedAt": string (timestamp)
  "insights":
  {
    "summary": string
    "metricStats"?: object // Optional
    "recommendations"?: object // Optional
```

```
  }
}
```

Example Response Values

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "name": "Response string",
  "description": "Response string",
  "chatbot": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Response string"
  },
  "dataset": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Response string"
  },
  "organization": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Response string"
  },
  "evaluationLlm": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Response string"
  },
  "status": {},
  "startedAt": "Response string",
  "completedAt": "Response string",
  "totalTestCases": 456,
  "completedTestCases": 456,
  "passedTestCases": 456,
  "metricScores": null,
  "evaluationConfig": null,
  "progressPercentage": 456,
  "overallScore": 456,
  "passRate": 456,
  "averageExecutionTimeMs": 456,
  "totalExecutionTimeMs": 456,
  "chatbotConfig": "Response string",
  "createdAt": "Response string",
  "updatedAt": "Response string",
  "insights": {
    "summary": "Response string",
    "metricStats": null,
```

```
    "recommendations": null
  }
}
```

Resume Incomplete Evaluation

POST `/api/v1/evaluations/{id}/resume/`

Only evaluations whose status is partial_completed can be resumed; otherwise 400 is returned. Failed and not-yet-run test cases are re-run while completed results are kept, and 202 is returned; Credits are deducted only for completed cases that were not previously billed.

Parameters

Parameter Name	Required	Type	Description
`id`	V	string	Evaluation ID

Code Examples

Shell/Bash

```
# API call example (Shell)
curl -X POST "https://api.maiagent.ai/api/v1/evaluations/550e8400-
e29b-41d4-a716-446655440000/resume/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

// Request body (payload)
const data = null;

axios.post("https://api.maiagent.ai/api/v1/evaluations/550e8400-
e29b-41d4-a716-446655440000/resume/", data, config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/evaluations/550e8400-e29b-
41d4-a716-446655440000/resume/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.post(url, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>post("https://api.maiagent.ai/api/v1/evaluations/550e8400-e29b-
41d4-a716-446655440000/resume/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response Content

Status code: 202

Example Response Structure

```
{
  "status": string (enum: accepted) // * `accepted` - Always accepted,
indicating the request has been accepted and queued for background
```

```
execution
  "message": string // Acceptance description
  "taskId": string // Background task ID
}
```

Example Response Values

```
{
  "status": "accepted",
  "message": "Response string",
  "taskId": "Response string"
}
```

Export Evaluation Report

POST `/api/v1/evaluations/{id}/export/`

Only single-turn evaluations whose status is completed can be exported; multi-turn evaluations are not currently supported and return 400. The report is generated as an Excel file in the background, and 201 is returned with the export record. Then use Get Latest Export Status to get the download URL.

Parameters

Parameter Name	Required	Type	Description
`id`	V	string	Evaluation ID

Code Examples

Shell/Bash

```
# API call example (Shell)
curl -X POST "https://api.maiagent.ai/api/v1/evaluations/550e8400-
e29b-41d4-a716-446655440000/export/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

// Request body (payload)
const data = null;

axios.post("https://api.maiagent.ai/api/v1/evaluations/550e8400-
e29b-41d4-a716-446655440000/export/", data, config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/evaluations/550e8400-e29b-
41d4-a716-446655440000/export/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.post(url, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>post("https://api.maiagent.ai/api/v1/evaluations/550e8400-e29b-
41d4-a716-446655440000/export/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response Content

Status code: 201

Example Response Structure

```
{
  "id": string (uuid)
  "userEmail": string (email)
```

```
  "datasetEvaluationId": string (uuid)
  "datasetEvaluationName": string
  "status":
  {
  }
  "statusDisplay": string
  "fileUrl": string // Returns the file URL
  "fileSize": integer // File size in bytes
  "errorMessage": string
  "processingDurationSeconds": number (double) // Calculated processing
duration (seconds)
  "createdAt": string (timestamp)
  "startedAt": string (timestamp)
  "completedAt": string (timestamp)
}
```

Example Response Values

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "userEmail": "response@example.com",
  "datasetEvaluationId": "550e8400-e29b-41d4-a716-446655440000",
  "datasetEvaluationName": "Response string",
  "status": {},
  "statusDisplay": "Response string",
  "fileUrl": "Response string",
  "fileSize": 456,
  "errorMessage": "Response string",
  "processingDurationSeconds": 456,
  "createdAt": "Response string",
  "startedAt": "Response string",
  "completedAt": "Response string"
}
```

Get Latest Export Status

GET `/api/v1/evaluations/{id}/export-status/`

Returns the most recent export record for this evaluation: status is pending, processing, completed, or failed; when completed, download from fileUrl. If this evaluation has no export record, 404 is returned.

Parameters

Parameter Name	Required	Type	Description
`id`	V	string	Evaluation ID

Code Examples

Shell/Bash

```
# API call example (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/evaluations/550e8400-
e29b-41d4-a716-446655440000/export-status/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/evaluations/550e8400-e29b-
41d4-a716-446655440000/export-status/", config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/evaluations/550e8400-e29b-
41d4-a716-446655440000/export-status/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/evaluations/550e8400-e29b-41d4-
a716-446655440000/export-status/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response Content

Status code: 200

Example Response Structure

```
{
  "id": string (uuid)
  "userEmail": string (email)
```

```
  "datasetEvaluationId": string (uuid)
  "datasetEvaluationName": string
  "status":
  {
  }
  "statusDisplay": string
  "fileUrl": string // Returns the file URL
  "fileSize": integer // File size in bytes
  "errorMessage": string
  "processingDurationSeconds": number (double) // Calculated processing
duration (seconds)
  "createdAt": string (timestamp)
  "startedAt": string (timestamp)
  "completedAt": string (timestamp)
}
```

Example Response Values

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "userEmail": "response@example.com",
  "datasetEvaluationId": "550e8400-e29b-41d4-a716-446655440000",
  "datasetEvaluationName": "Response string",
  "status": {},
  "statusDisplay": "Response string",
  "fileUrl": "Response string",
  "fileSize": 456,
  "errorMessage": "Response string",
  "processingDurationSeconds": 456,
  "createdAt": "Response string",
  "startedAt": "Response string",
  "completedAt": "Response string"
}
```

List Export Records

GET `/api/v1/evaluations/{id}/exports/`

The response is an array of all export records for this evaluation, sorted from newest to oldest, without pagination.

Parameters

Parameter Name	Required	Type	Description
`id`	V	string	Evaluation ID

Code Examples

Shell/Bash

```
# API call example (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/evaluations/550e8400-
e29b-41d4-a716-446655440000/exports/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/evaluations/550e8400-e29b-
41d4-a716-446655440000/exports/", config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/evaluations/550e8400-e29b-
41d4-a716-446655440000/exports/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/evaluations/550e8400-e29b-41d4-
a716-446655440000/exports/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response Content

Status code: 200

Example Response Structure

```
[
  {
    "id": string (uuid)
```

```
    "userEmail": string (email)
    "datasetEvaluationId": string (uuid)
    "datasetEvaluationName": string
    "status":
    {
    }
    "statusDisplay": string
    "fileUrl": string // Returns the file URL
    "fileSize": integer // File size in bytes
    "processingDurationSeconds": number (double) // Calculated processing
duration (seconds)
    "createdAt": string (timestamp)
    "startedAt": string (timestamp)
    "completedAt": string (timestamp)
  }
]
```

Example Response Values

```
[
  {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "userEmail": "response@example.com",
    "datasetEvaluationId": "550e8400-e29b-41d4-a716-446655440000",
    "datasetEvaluationName": "Response string",
    "status": {},
    "statusDisplay": "Response string",
    "fileUrl": "Response string",
    "fileSize": 456,
    "processingDurationSeconds": 456,
    "createdAt": "Response string",
    "startedAt": "Response string",
    "completedAt": "Response string"
  }
]
```

Edit Evaluation Name and Description

PATCH `/api/v1/evaluations/{id}`

Only name and description are accepted; other fields are ignored. Evaluations can be edited in any status.

Parameters

Parameter Name	Required	Type	Description
`id`	V	string	Evaluation ID

Request Content

Request Parameters

Field	Type	Required	Description
name	string	No	
description	string	No	

Example Request Structure

```
{
  "name"?: string // Optional
  "description"?: string // Optional
}
```

Example Request Values

```
{
  "name": "Example name",
```

```
  "description": "Example string"
}
```

Code Examples

Shell/Bash

```
# API call example (Shell)
curl -X PATCH "https://api.maiagent.ai/api/v1/evaluations/550e8400-
e29b-41d4-a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "name": "Example name",
    "description": "Example string"
  }'

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// Request body (payload)
const data = {
    "name": "Example name",
    "description": "Example string"
  };

axios.patch("https://api.maiagent.ai/api/v1/evaluations/550e8400-
e29b-41d4-a716-446655440000/", data, config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/evaluations/550e8400-e29b-
41d4-a716-446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# Request body (payload)
data = {
    "name": "Example name",
    "description": "Example string"
}

response = requests.patch(url, json=data, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>patch("https://api.maiagent.ai/api/v1/evaluations/550e8400-e29b-
41d4-a716-446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'name' => 'Example name',
            'description' => 'Example string'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response Content

Status code: 200

Example Response Structure

```
{
  "id": string (uuid)
  "name": string
  "description": string
  "chatbot":
  {
    "id": string (uuid)
    "name": string
  }
  "dataset":
  {
    "id": string (uuid)
    "name": string
  }
  "organization":
  {
    "id": string (uuid)
    "name": string
  }
  "evaluationLlm":
  {
    "id": string (uuid)
    "name": string
  }
  "status":
  {
  }
  "startedAt": string (timestamp)
  "completedAt": string (timestamp)
  "totalTestCases": integer
  "completedTestCases": integer
  "passedTestCases": integer // Number of test cases that passed
  "metricScores": object // Detailed score per evaluation metric, such as
ground_truth, task_completion and tool_correctness
  "evaluationConfig": object
  "progressPercentage": number (double)
  "overallScore": number (double)
  "passRate": number (double)
  "averageExecutionTimeMs": integer
  "totalExecutionTimeMs": integer
  "chatbotConfig": string
  "createdAt": string (timestamp)
  "updatedAt": string (timestamp)
  "insights":
```

```
  {
    "summary": string
    "metricStats"?: object // Optional
    "recommendations"?: object // Optional
  }
}
```

Example Response Values

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "name": "Response string",
  "description": "Response string",
  "chatbot": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Response string"
  },
  "dataset": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Response string"
  },
  "organization": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Response string"
  },
  "evaluationLlm": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Response string"
  },
  "status": {},
  "startedAt": "Response string",
  "completedAt": "Response string",
  "totalTestCases": 456,
  "completedTestCases": 456,
  "passedTestCases": 456,
  "metricScores": null,
  "evaluationConfig": null,
  "progressPercentage": 456,
  "overallScore": 456,
  "passRate": 456,
  "averageExecutionTimeMs": 456,
  "totalExecutionTimeMs": 456,
  "chatbotConfig": "Response string",
  "createdAt": "Response string",
```

```
  "updatedAt": "Response string",
  "insights": {
    "summary": "Response string",
    "metricStats": null,
    "recommendations": null
  }
}
```


Delete Evaluation

DELETE `/api/v1/evaluations/{id}`

Parameters

Parameter Name	Required	Type	Description
`id`	V	string	Evaluation ID

Code Examples

Shell/Bash

```
# API call example (Shell)
curl -X DELETE "https://api.maiagent.ai/api/v1/evaluations/550e8400-
e29b-41d4-a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

// Request body (payload)
const data = null;

axios.delete("https://api.maiagent.ai/api/v1/evaluations/550e8400-
e29b-41d4-a716-446655440000/", data, config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/evaluations/550e8400-e29b-
41d4-a716-446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.delete(url, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>delete("https://api.maiagent.ai/api/v1/evaluations/550e8400-e29b-
41d4-a716-446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response Content

Status Code	Description
204	No response body

API Call Example (Shell)

目錄

1. Create SQL Database Connection
2. List SQL Databases
3. Get Specific SQL Database
4. Update SQL Database
5. Partially Update SQL Database
6. Delete SQL Database
7. Test database connection
8. Upload files to a database
9. Batch delete SQL databases
10. List database tables
11. Create a database table
12. Get Specific Table
13. Update Table
14. Partially Update Table
15. Delete Table
16. Batch delete tables
17. List table columns
18. Get a specific table column
19. Update a table column
20. Partially update a table column
21. Test Database Connection (General)
22. List Database Connection String Examples
23. Retrieve a Specific Connection String Example
24. List Database Configurations of an AI Assistant
25. Add Database Configuration to an AI Assistant
26. Get Specific Database Configuration
27. Update Database Configuration
28. Partially Update Database Configuration
29. Delete Database Configuration

API Call Example (Shell)

Create SQL Database Connection

`POST` `/api/v1/sql-databases/`

Request Body

Request Parameters

Field	Type	Required	Description
name	string	Yes	Display name for this database connection
description	string	No	Description of the database and its purpose
databaseType	object	Yes	Type of database: PostgreSQL, MySQL, MSSQL, Oracle, SynxDB, or MaiAgent `postgresql` : PostgreSQL ; `mysql` : MySQL ; `maiagent` : MaiAgent ; `oracle` : Oracle ; `mssql` : MSSQL ; `synxdb` : SynxDB;
databaseUrl	string	No	Connection string for external databases. Not required for MaiAgent type as it uses the system default.
includeTables	object	No	Optional list of tables to include. Format: {"tables": ["table1", "table2"]}. For MaiAgent type, this is auto-populated from uploaded files.
isActive	boolean	No	When disabled, this database will not be used in Text-to-SQL queries
chatbots	array[IdName]	No	
groups	array[IdName]	No	

Example Request Schema

```
{
  "name": string // Display name for this database connection
  "description"?: string // Description of the database and its purpose
(Optional)
  "databaseType":  // Type of database: PostgreSQL, MySQL, MSSQL, Oracle,
SynxDB, or MaiAgent

* `postgresql` - PostgreSQL
* `mysql` - MySQL
* `maiagent` - MaiAgent
* `oracle` - Oracle
* `mssql` - MSSQL
* `synxdb` - SynxDB
  {
  }
  "databaseUrl"?: string // Connection string for external databases. Not
required for MaiAgent type as it uses the system default. (Optional)
  "includeTables"?: object // Optional list of tables to include. Format:
{"tables": ["table1", "table2"]}. For MaiAgent type, this is auto-
populated from uploaded files. (Optional)
  "isActive"?: boolean // When disabled, this database will not be used
in Text-to-SQL queries (Optional)
  "chatbots"?: [ // Optional
    {
      "id": string (uuid)
    }
  ]
  "groups"?: [ // Optional
    {
      "id": string (uuid)
    }
  ]
}
```

Example Request Values

```
{
  "name": "Example name",
  "description": "Example string",
  "databaseType": {},
  "databaseUrl": "Example string",
  "includeTables": null,
  "isActive": true,
```

```
  "chatbots": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000"
    }
  ],
  "groups": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000"
    }
  ]
}
```


Code Examples

Shell/Bash

```
# API Call Example (Shell)
curl -X POST "https://api.maiagent.ai/api/v1/sql-databases/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "name": "Example name",
    "description": "Example string",
    "databaseType": {},
    "databaseUrl": "Example string",
    "includeTables": null,
    "isActive": true,
    "chatbots": [
      {
        "id": "550e8400-e29b-41d4-a716-446655440000"
      }
    ],
    "groups": [
      {
        "id": "550e8400-e29b-41d4-a716-446655440000"
      }
    ]
  }'

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// Request body (payload)
const data = {
    "name": "Example name",
    "description": "Example string",
    "databaseType": {},
    "databaseUrl": "Example string",
    "includeTables": null,
    "isActive": true,
    "chatbots": [
      {
        "id": "550e8400-e29b-41d4-a716-446655440000"
      }
    ],
    "groups": [
      {
        "id": "550e8400-e29b-41d4-a716-446655440000"
      }
    ]
  };

axios.post("https://api.maiagent.ai/api/v1/sql-databases/", data,
config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request failed:');
```

```
  console.error(error.response?.data || error.message);
});
```

Python

```python
import requests

url = "https://api.maiagent.ai/api/v1/sql-databases/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# Request body (payload)
data = {
    "name": "Example name",
    "description": "Example string",
    "databaseType": {},
    "databaseUrl": "Example string",
    "includeTables": None,
    "isActive": True,
    "chatbots": [
        {
            "id": "550e8400-e29b-41d4-a716-446655440000"
        }
    ],
    "groups": [
        {
            "id": "550e8400-e29b-41d4-a716-446655440000"
        }
    ]
}

response = requests.post(url, json=data, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request failed:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->post("https://api.maiagent.ai/api/v1/sql-databases/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'name' => 'Example name',
            'description' => 'Example string',
            'databaseType' => new \stdClass(),
            'databaseUrl' => 'Example string',
            'includeTables' => null,
            'isActive' => true,
            'chatbots' => [
                [
                    'id' => '550e8400-e29b-41d4-a716-446655440000'
                ]
            ],
            'groups' => [
                [
                    'id' => '550e8400-e29b-41d4-a716-446655440000'
                ]
            ]
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request failed: ' . $e->getMessage();
}
?>
```

Response Body

Status Code: 201

Example Response Schema

```
{
  "id": string (uuid)
  "name": string // Display name for this database connection
  "description"?: string // Description of the database and its purpose
(Optional)
  "databaseType":  // Type of database: PostgreSQL, MySQL, MSSQL, Oracle,
SynxDB, or MaiAgent

* `postgresql` - PostgreSQL
* `mysql` - MySQL
* `maiagent` - MaiAgent
* `oracle` - Oracle
* `mssql` - MSSQL
* `synxdb` - SynxDB
  {
  }
  "databaseUrlMasked": string
  "includeTables"?: object // Optional list of tables to include. Format:
{"tables": ["table1", "table2"]}. For MaiAgent type, this is auto-
populated from uploaded files. (Optional)
  "isActive"?: boolean // When disabled, this database will not be used
in Text-to-SQL queries (Optional)
  "status":
  {
  }
  "deletedAt": string (timestamp)
  "tables": [
    {
      "id": string (uuid)
      "tableName": string // Name of the table in the database
      "sheetName": string // Name of the source worksheet/sheet this
```

```
table was created from. Empty for tables created before this field was
added.
      "description"?: string // Description of the table and its data for
better Text-to-SQL understanding (Optional)
      "status":
      {
      }
      "errorMessage": string // Error details if table creation or
deletion failed
      "sourceFile":
      {
        "id": string (uuid)
        "name": string
        "isFromKnowledgeBase": boolean // Determine if the source file
originated from a knowledge base upload.

Returns True if the file was uploaded via knowledge base,
False if uploaded directly to the database.
      }
      "columns": [
        {
          "id": string (uuid)
          "columnName": string
          "columnType"?: string // Data type of the column (e.g.,
VARCHAR, INTEGER, TIMESTAMP) (Optional)
          "description"?: string // Description of the column for better
Text-to-SQL understanding (Optional)
          "isPrimaryKey"?: boolean // Optional
          "isNullable"?: boolean // Optional
          "createdAt": string (timestamp)
          "updatedAt": string (timestamp)
        }
      ]
      "createdAt": string (timestamp)
      "updatedAt": string (timestamp)
    }
  ]
  "chatbots": [
    {
      "id": string (uuid)
      "name": string
    }
  ]
  "groups": [
    {
```

```
      "id": string (uuid)
      "name": string
    }
  ]
  "createdBy":
  {
    "id": string (uuid)
    "name": string
  }
  "canUpdate": boolean // Return whether the current user can update this
resource.
  "canDelete": boolean // Return whether the current user can delete this
resource.
  "createdAt": string (timestamp)
  "updatedAt": string (timestamp)
}
```

Example Response Values

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "name": "Response string",
  "description": "Response string",
  "databaseType": {},
  "databaseUrlMasked": "Response string",
  "includeTables": null,
  "isActive": false,
  "status": {},
  "deletedAt": "Response string",
  "tables": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "tableName": "Response string",
      "sheetName": "Response string",
      "description": "Response string",
      "status": {},
      "errorMessage": "Response string",
      "sourceFile": {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "name": "Response string",
        "isFromKnowledgeBase": false
      },
      "columns": [
        {
```

```
          "id": "550e8400-e29b-41d4-a716-446655440000",
          "columnName": "Response string",
          "columnType": "Response string",
          "description": "Response string",
          "isPrimaryKey": false,
          "isNullable": false,
          "createdAt": "Response string",
          "updatedAt": "Response string"
        }
      ],
      "createdAt": "Response string",
      "updatedAt": "Response string"
    }
  ],
  "chatbots": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "Response string"
    }
  ],
  "groups": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "Response string"
    }
  ],
  "createdBy": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Response string"
  },
  "canUpdate": false,
  "canDelete": false,
  "createdAt": "Response string",
  "updatedAt": "Response string"
}
```


List SQL Databases

GET `/api/v1/sql-databases/`

Parameters

Parameter Name	Required	Type	Description
`databaseType`	X	string	Type of database: PostgreSQL, MySQL, MSSQL, Oracle, SynxDB, or MaiAgent `postgresql`: PostgreSQL ; `mysql`: MySQL ; `maiagent`: MaiAgent ; `oracle`: Oracle ; `mssql`: MSSQL ; `synxdb`: SynxDB;
`isActive`	X	boolean	
`isExternal`	X	boolean	
`page`	X	integer	A page number within the paginated result set.
`pageSize`	X	integer	Number of results to return per page.
`pagination`	X	boolean	Set to false to return all databases without pagination (defaults to true).
`query`	X	string	

Code Examples

Shell/Bash

```
# API call example (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/sql-databases/?
databaseType=maiagent&isActive=true&isExternal=true&page=1&pageSize=
1&pagination=true&query=example"

  -H "Authorization: Api-Key YOUR_API_KEY"

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/sql-databases/?
databaseType=maiagent&isActive=true&isExternal=true&page=1&pageSize=
1&pagination=true&query=example", config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/sql-databases/?
databaseType=maiagent&isActive=true&isExternal=true&page=1&pageSize=
1&pagination=true&query=example"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->get("https://api.maiagent.ai/api/v1/sql-databases/?databaseType=maiagent&isActive=true&isExternal=true&page=1&pageSize=1&pagination=true&query=example", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response Content

Status code: 200

Response Schema Example

```
{
  "count": integer
```

```
  "next"?: string (uri) // Optional
  "previous"?: string (uri) // Optional
  "results": [
    {
      "id": string (uuid)
      "name": string // Display name for this database connection
      "description"?: string // Description of the database and its
purpose (Optional)
      "databaseType":  // Type of database: PostgreSQL, MySQL, MSSQL,
Oracle, SynxDB, or MaiAgent

* `postgresql` - PostgreSQL
* `mysql` - MySQL
* `maiagent` - MaiAgent
* `oracle` - Oracle
* `mssql` - MSSQL
* `synxdb` - SynxDB
      {
      }
      "databaseUrlMasked": string
      "includeTables"?: object // Optional list of tables to include.
Format: {"tables": ["table1", "table2"]}. For MaiAgent type, this is
auto-populated from uploaded files. (Optional)
      "isActive"?: boolean // When disabled, this database will not be
used in Text-to-SQL queries (Optional)
      "status":
      {
      }
      "deletedAt": string (timestamp)
      "tables": [
        {
          "id": string (uuid)
          "tableName": string // Name of the table in the database
        }
      ]
      "tablesCount": integer
      "chatbots": [
        {
          "id": string (uuid)
          "name": string
        }
      ]
      "groups": [
        {
          "id": string (uuid)
```

```
          "name": string
        }
      ]
      "createdBy":
      {
        "id": string (uuid)
        "name": string
      }
      "canUpdate": boolean // Return whether the current user can update
this resource.
      "canDelete": boolean // Return whether the current user can delete
this resource.
      "createdAt": string (timestamp)
      "updatedAt": string (timestamp)
    }
  ]
}
```

Response Example Values

```
{
  "count": 123,
  "next": "http://api.example.org/accounts/?page=4",
  "previous": "http://api.example.org/accounts/?page=2",
  "results": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "response string",
      "description": "response string",
      "databaseType": {},
      "databaseUrlMasked": "response string",
      "includeTables": null,
      "isActive": false,
      "status": {},
      "deletedAt": "response string",
      "tables": [
        {
          "id": "550e8400-e29b-41d4-a716-446655440000",
          "tableName": "response string"
        }
      ],
      "tablesCount": 456,
      "chatbots": [
        {
```

```
            "id": "550e8400-e29b-41d4-a716-446655440000",
            "name": "response string"
          }
        ],
        "groups": [
          {
            "id": "550e8400-e29b-41d4-a716-446655440000",
            "name": "response string"
          }
        ],
        "createdBy": {
          "id": "550e8400-e29b-41d4-a716-446655440000",
          "name": "response string"
        },
        "canUpdate": false,
        "canDelete": false,
        "createdAt": "response string",
        "updatedAt": "response string"
      }
    ]
}
```


Get Specific SQL Database

`GET` `/api/v1/sql-databases/{id}`

Parameters

Parameter Name	Required	Type	Description
`id`	V	string	A UUID string identifying this SQL Database.

Code Examples

Shell/Bash

```
# API Call Example (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/sql-databases/550e8400-
e29b-41d4-a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/sql-databases/550e8400-
e29b-41d4-a716-446655440000/", config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request failed:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/sql-databases/550e8400-e29b-
41d4-a716-446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request failed:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->get("https://api.maiagent.ai/api/v1/sql-databases/550e8400-e29b-41d4-a716-446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request failed: ' . $e->getMessage();
}
?>
```

Response Body

Status Code: 200

Example Response Schema

```
{
  "id": string (uuid)
  "name": string // Display name for this database connection
  "description"?: string // Description of the database and its purpose
```

```
(Optional)
  "databaseType":  // Type of database: PostgreSQL, MySQL, MSSQL, Oracle,
SynxDB, or MaiAgent

* `postgresql` - PostgreSQL
* `mysql` - MySQL
* `maiagent` - MaiAgent
* `oracle` - Oracle
* `mssql` - MSSQL
* `synxdb` - SynxDB
  {
  }
  "databaseUrlMasked": string
  "includeTables"?: object // Optional list of tables to include. Format:
{"tables": ["table1", "table2"]}. For MaiAgent type, this is auto-
populated from uploaded files. (Optional)
  "isActive"?: boolean // When disabled, this database will not be used
in Text-to-SQL queries (Optional)
  "status":
  {
  }
  "deletedAt": string (timestamp)
  "tables": [
    {
      "id": string (uuid)
      "tableName": string // Name of the table in the database
      "sheetName": string // Name of the source worksheet/sheet this
table was created from. Empty for tables created before this field was
added.
      "description"?: string // Description of the table and its data for
better Text-to-SQL understanding (Optional)
      "status":
      {
      }
      "errorMessage": string // Error details if table creation or
deletion failed
      "sourceFile":
      {
        "id": string (uuid)
        "name": string
        "isFromKnowledgeBase": boolean // Determine if the source file
originated from a knowledge base upload.

Returns True if the file was uploaded via knowledge base,
False if uploaded directly to the database.
```

```
      }
      "columns": [
        {
          "id": string (uuid)
          "columnName": string
          "columnType"?: string // Data type of the column (e.g.,
VARCHAR, INTEGER, TIMESTAMP) (Optional)
          "description"?: string // Description of the column for better
Text-to-SQL understanding (Optional)
          "isPrimaryKey"?: boolean // Optional
          "isNullable"?: boolean // Optional
          "createdAt": string (timestamp)
          "updatedAt": string (timestamp)
        }
      ]
      "createdAt": string (timestamp)
      "updatedAt": string (timestamp)
    }
  ]
  "chatbots": [
    {
      "id": string (uuid)
      "name": string
    }
  ]
  "groups": [
    {
      "id": string (uuid)
      "name": string
    }
  ]
  "createdBy":
  {
    "id": string (uuid)
    "name": string
  }
  "canUpdate": boolean // Return whether the current user can update this
resource.
  "canDelete": boolean // Return whether the current user can delete this
resource.
  "createdAt": string (timestamp)
  "updatedAt": string (timestamp)
}
```

Example Response Values

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "name": "Response string",
  "description": "Response string",
  "databaseType": {},
  "databaseUrlMasked": "Response string",
  "includeTables": null,
  "isActive": false,
  "status": {},
  "deletedAt": "Response string",
  "tables": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "tableName": "Response string",
      "sheetName": "Response string",
      "description": "Response string",
      "status": {},
      "errorMessage": "Response string",
      "sourceFile": {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "name": "Response string",
        "isFromKnowledgeBase": false
      },
      "columns": [
        {
          "id": "550e8400-e29b-41d4-a716-446655440000",
          "columnName": "Response string",
          "columnType": "Response string",
          "description": "Response string",
          "isPrimaryKey": false,
          "isNullable": false,
          "createdAt": "Response string",
          "updatedAt": "Response string"
        }
      ],
      "createdAt": "Response string",
      "updatedAt": "Response string"
    }
  ],
  "chatbots": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "Response string"
    }
```

```
  ],
  "groups": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "Response string"
    }
  ],
  "createdBy": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Response string"
  },
  "canUpdate": false,
  "canDelete": false,
  "createdAt": "Response string",
  "updatedAt": "Response string"
}
```


Update SQL Database

PUT `/api/v1/sql-databases/{id}`

Parameters

Parameter Name	Required	Type	Description
`id`	V	string	A UUID string identifying this SQL Database.

Request Body

Request Parameters

Field	Type	Required	Description
name	string	Yes	Display name for this database connection
description	string	No	Description of the database and its purpose
databaseUrl	string	No	Connection string for external databases. Not required for MaiAgent type as it uses the system default.
includeTables	object	No	Optional list of tables to include. Format: {"tables": ["table1", "table2"]}. For MaiAgent type, this is auto-populated from uploaded files.
isActive	boolean	No	When disabled, this database will not be used in Text-to-SQL queries
chatbots	array[IdName]	No	
groups	array[IdName]	No	

Example Request Schema

```
{
  "name": string // Display name for this database connection
  "description"?: string // Description of the database and its purpose
(Optional)
  "databaseUrl"?: string // Connection string for external databases. Not
required for MaiAgent type as it uses the system default. (Optional)
  "includeTables"?: object // Optional list of tables to include. Format:
{"tables": ["table1", "table2"]}. For MaiAgent type, this is auto-
populated from uploaded files. (Optional)
  "isActive"?: boolean // When disabled, this database will not be used
in Text-to-SQL queries (Optional)
  "chatbots"?: [ // Optional
    {
      "id": string (uuid)
    }
  ]
  "groups"?: [ // Optional
    {
      "id": string (uuid)
    }
```

```
  ]
}
```

Example Request Values

```
{
  "name": "Example name",
  "description": "Example string",
  "databaseUrl": "Example string",
  "includeTables": null,
  "isActive": true,
  "chatbots": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000"
    }
  ],
  "groups": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000"
    }
  ]
}
```

Code Examples

Shell/Bash

```
# API Call Example (Shell)
curl -X PUT "https://api.maiagent.ai/api/v1/sql-databases/550e8400-
e29b-41d4-a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "name": "Example name",
    "description": "Example string",
    "databaseUrl": "Example string",
    "includeTables": null,
    "isActive": true,
    "chatbots": [
      {
        "id": "550e8400-e29b-41d4-a716-446655440000"
      }
    ],
    "groups": [
      {
        "id": "550e8400-e29b-41d4-a716-446655440000"
      }
    ]
  }'

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// Request body (payload)
const data = {
    "name": "Example name",
    "description": "Example string",
    "databaseUrl": "Example string",
    "includeTables": null,
    "isActive": true,
    "chatbots": [
      {
        "id": "550e8400-e29b-41d4-a716-446655440000"
      }
    ],
    "groups": [
      {
        "id": "550e8400-e29b-41d4-a716-446655440000"
      }
    ]
  };

axios.put("https://api.maiagent.ai/api/v1/sql-databases/550e8400-
e29b-41d4-a716-446655440000/", data, config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request failed:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/sql-databases/550e8400-e29b-
41d4-a716-446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# Request body (payload)
data = {
    "name": "Example name",
    "description": "Example string",
    "databaseUrl": "Example string",
    "includeTables": None,
    "isActive": True,
    "chatbots": [
        {
            "id": "550e8400-e29b-41d4-a716-446655440000"
        }
    ],
    "groups": [
        {
            "id": "550e8400-e29b-41d4-a716-446655440000"
        }
    ]
}

response = requests.put(url, json=data, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request failed:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->put("https://api.maiagent.ai/api/v1/sql-databases/550e8400-e29b-41d4-a716-446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'name' => 'Example name',
            'description' => 'Example string',
            'databaseUrl' => 'Example string',
            'includeTables' => null,
            'isActive' => true,
            'chatbots' => [
                [
                    'id' => '550e8400-e29b-41d4-a716-446655440000'
                ]
            ],
            'groups' => [
                [
                    'id' => '550e8400-e29b-41d4-a716-446655440000'
                ]
            ]
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request failed: ' . $e->getMessage();
}
?>
```

Response Body

Status Code: 200

Example Response Schema

```
{
  "id": string (uuid)
  "name": string // Display name for this database connection
  "description"?: string // Description of the database and its purpose
(Optional)
  "databaseType":  // Type of database: PostgreSQL, MySQL, MSSQL, Oracle,
SynxDB, or MaiAgent

* `postgresql` - PostgreSQL
* `mysql` - MySQL
* `maiagent` - MaiAgent
* `oracle` - Oracle
* `mssql` - MSSQL
* `synxdb` - SynxDB
  {
  }
  "databaseUrlMasked": string
  "includeTables"?: object // Optional list of tables to include. Format:
{"tables": ["table1", "table2"]}. For MaiAgent type, this is auto-
populated from uploaded files. (Optional)
  "isActive"?: boolean // When disabled, this database will not be used
in Text-to-SQL queries (Optional)
  "status":
  {
  }
  "deletedAt": string (timestamp)
  "tables": [
    {
      "id": string (uuid)
      "tableName": string // Name of the table in the database
      "sheetName": string // Name of the source worksheet/sheet this
```

```
table was created from. Empty for tables created before this field was
added.
      "description"?: string // Description of the table and its data for
better Text-to-SQL understanding (Optional)
      "status":
      {
      }
      "errorMessage": string // Error details if table creation or
deletion failed
      "sourceFile":
      {
        "id": string (uuid)
        "name": string
        "isFromKnowledgeBase": boolean // Determine if the source file
originated from a knowledge base upload.

Returns True if the file was uploaded via knowledge base,
False if uploaded directly to the database.
      }
      "columns": [
        {
          "id": string (uuid)
          "columnName": string
          "columnType"?: string // Data type of the column (e.g.,
VARCHAR, INTEGER, TIMESTAMP) (Optional)
          "description"?: string // Description of the column for better
Text-to-SQL understanding (Optional)
          "isPrimaryKey"?: boolean // Optional
          "isNullable"?: boolean // Optional
          "createdAt": string (timestamp)
          "updatedAt": string (timestamp)
        }
      ]
      "createdAt": string (timestamp)
      "updatedAt": string (timestamp)
    }
  ]
  "chatbots": [
    {
      "id": string (uuid)
      "name": string
    }
  ]
  "groups": [
    {
```

```
      "id": string (uuid)
      "name": string
    }
  ]
  "createdBy":
  {
    "id": string (uuid)
    "name": string
  }
  "canUpdate": boolean // Return whether the current user can update this
resource.
  "canDelete": boolean // Return whether the current user can delete this
resource.
  "createdAt": string (timestamp)
  "updatedAt": string (timestamp)
}
```

Example Response Values

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "name": "Response string",
  "description": "Response string",
  "databaseType": {},
  "databaseUrlMasked": "Response string",
  "includeTables": null,
  "isActive": false,
  "status": {},
  "deletedAt": "Response string",
  "tables": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "tableName": "Response string",
      "sheetName": "Response string",
      "description": "Response string",
      "status": {},
      "errorMessage": "Response string",
      "sourceFile": {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "name": "Response string",
        "isFromKnowledgeBase": false
      },
      "columns": [
        {
```

```
          "id": "550e8400-e29b-41d4-a716-446655440000",
          "columnName": "Response string",
          "columnType": "Response string",
          "description": "Response string",
          "isPrimaryKey": false,
          "isNullable": false,
          "createdAt": "Response string",
          "updatedAt": "Response string"
        }
      ],
      "createdAt": "Response string",
      "updatedAt": "Response string"
    }
  ],
  "chatbots": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "Response string"
    }
  ],
  "groups": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "Response string"
    }
  ],
  "createdBy": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Response string"
  },
  "canUpdate": false,
  "canDelete": false,
  "createdAt": "Response string",
  "updatedAt": "Response string"
}
```


Partially Update SQL Database

PATCH `/api/v1/sql-databases/{id}`

Parameters

Parameter Name	Required	Type	Description
`id`	V	string	A UUID string identifying this SQL Database.

Request Body

Request Parameters

Field	Type	Required	Description
name	string	No	Display name for this database connection
description	string	No	Description of the database and its purpose
databaseUrl	string	No	Connection string for external databases. Not required for MaiAgent type as it uses the system default.
includeTables	object	No	Optional list of tables to include. Format: {"tables": ["table1", "table2"]}. For MaiAgent type, this is auto-populated from uploaded files.
isActive	boolean	No	When disabled, this database will not be used in Text-to-SQL queries
chatbots	array[IdName]	No	
groups	array[IdName]	No	

Example Request Schema

```
{
  "name"?: string // Display name for this database connection (Optional)
  "description"?: string // Description of the database and its purpose
(Optional)
  "databaseUrl"?: string // Connection string for external databases. Not
required for MaiAgent type as it uses the system default. (Optional)
  "includeTables"?: object // Optional list of tables to include. Format:
{"tables": ["table1", "table2"]}. For MaiAgent type, this is auto-
populated from uploaded files. (Optional)
  "isActive"?: boolean // When disabled, this database will not be used
in Text-to-SQL queries (Optional)
  "chatbots"?: [ // Optional
    {
      "id": string (uuid)
    }
  ]
  "groups"?: [ // Optional
    {
      "id": string (uuid)
    }
  ]
}
```

Example Request Values

```
{
  "name": "Example name",
  "description": "Example string",
  "databaseUrl": "Example string",
  "includeTables": null,
  "isActive": true,
  "chatbots": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000"
    }
  ],
  "groups": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000"
    }
```

```
  ]
}
```

Code Examples

Shell/Bash

```
# API Call Example (Shell)
curl -X PATCH "https://api.maiagent.ai/api/v1/sql-
databases/550e8400-e29b-41d4-a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "name": "Example name",
    "description": "Example string",
    "databaseUrl": "Example string",
    "includeTables": null,
    "isActive": true,
    "chatbots": [
      {
        "id": "550e8400-e29b-41d4-a716-446655440000"
      }
    ],
    "groups": [
      {
        "id": "550e8400-e29b-41d4-a716-446655440000"
      }
    ]
  }'

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// Request body (payload)
const data = {
    "name": "Example name",
    "description": "Example string",
    "databaseUrl": "Example string",
    "includeTables": null,
    "isActive": true,
    "chatbots": [
      {
        "id": "550e8400-e29b-41d4-a716-446655440000"
      }
    ],
    "groups": [
      {
        "id": "550e8400-e29b-41d4-a716-446655440000"
      }
    ]
  };

axios.patch("https://api.maiagent.ai/api/v1/sql-databases/550e8400-
e29b-41d4-a716-446655440000/", data, config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request failed:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/sql-databases/550e8400-e29b-
41d4-a716-446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# Request body (payload)
data = {
    "name": "Example name",
    "description": "Example string",
    "databaseUrl": "Example string",
    "includeTables": None,
    "isActive": True,
    "chatbots": [
        {
            "id": "550e8400-e29b-41d4-a716-446655440000"
        }
    ],
    "groups": [
        {
            "id": "550e8400-e29b-41d4-a716-446655440000"
        }
    ]
}

response = requests.patch(url, json=data, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request failed:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->patch("https://api.maiagent.ai/api/v1/sql-databases/550e8400-e29b-41d4-a716-446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'name' => 'Example name',
            'description' => 'Example string',
            'databaseUrl' => 'Example string',
            'includeTables' => null,
            'isActive' => true,
            'chatbots' => [
                [
                    'id' => '550e8400-e29b-41d4-a716-446655440000'
                ]
            ],
            'groups' => [
                [
                    'id' => '550e8400-e29b-41d4-a716-446655440000'
                ]
            ]
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request failed: ' . $e->getMessage();
}
?>
```

Response Body

Status Code: 200

Example Response Schema

```
{
  "id": string (uuid)
  "name": string // Display name for this database connection
  "description"?: string // Description of the database and its purpose
(Optional)
  "databaseType":  // Type of database: PostgreSQL, MySQL, MSSQL, Oracle,
SynxDB, or MaiAgent

* `postgresql` - PostgreSQL
* `mysql` - MySQL
* `maiagent` - MaiAgent
* `oracle` - Oracle
* `mssql` - MSSQL
* `synxdb` - SynxDB
  {
  }
  "databaseUrlMasked": string
  "includeTables"?: object // Optional list of tables to include. Format:
{"tables": ["table1", "table2"]}. For MaiAgent type, this is auto-
populated from uploaded files. (Optional)
  "isActive"?: boolean // When disabled, this database will not be used
in Text-to-SQL queries (Optional)
  "status":
  {
  }
  "deletedAt": string (timestamp)
  "tables": [
    {
      "id": string (uuid)
      "tableName": string // Name of the table in the database
      "sheetName": string // Name of the source worksheet/sheet this
```

```
table was created from. Empty for tables created before this field was
added.
      "description"?: string // Description of the table and its data for
better Text-to-SQL understanding (Optional)
      "status":
      {
      }
      "errorMessage": string // Error details if table creation or
deletion failed
      "sourceFile":
      {
        "id": string (uuid)
        "name": string
        "isFromKnowledgeBase": boolean // Determine if the source file
originated from a knowledge base upload.

Returns True if the file was uploaded via knowledge base,
False if uploaded directly to the database.
      }
      "columns": [
        {
          "id": string (uuid)
          "columnName": string
          "columnType"?: string // Data type of the column (e.g.,
VARCHAR, INTEGER, TIMESTAMP) (Optional)
          "description"?: string // Description of the column for better
Text-to-SQL understanding (Optional)
          "isPrimaryKey"?: boolean // Optional
          "isNullable"?: boolean // Optional
          "createdAt": string (timestamp)
          "updatedAt": string (timestamp)
        }
      ]
      "createdAt": string (timestamp)
      "updatedAt": string (timestamp)
    }
  ]
  "chatbots": [
    {
      "id": string (uuid)
      "name": string
    }
  ]
  "groups": [
    {
```

```
      "id": string (uuid)
      "name": string
    }
  ]
  "createdBy":
  {
    "id": string (uuid)
    "name": string
  }
  "canUpdate": boolean // Return whether the current user can update this
resource.
  "canDelete": boolean // Return whether the current user can delete this
resource.
  "createdAt": string (timestamp)
  "updatedAt": string (timestamp)
}
```

Example Response Values


```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "name": "Response string",
  "description": "Response string",
  "databaseType": {},
  "databaseUrlMasked": "Response string",
  "includeTables": null,
  "isActive": false,
  "status": {},
  "deletedAt": "Response string",
  "tables": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "tableName": "Response string",
      "sheetName": "Response string",
      "description": "Response string",
      "status": {},
      "errorMessage": "Response string",
      "sourceFile": {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "name": "Response string",
        "isFromKnowledgeBase": false
      },
      "columns": [
        {
```

```
          "id": "550e8400-e29b-41d4-a716-446655440000",
          "columnName": "Response string",
          "columnType": "Response string",
          "description": "Response string",
          "isPrimaryKey": false,
          "isNullable": false,
          "createdAt": "Response string",
          "updatedAt": "Response string"
        }
      ],
      "createdAt": "Response string",
      "updatedAt": "Response string"
    }
  ],
  "chatbots": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "Response string"
    }
  ],
  "groups": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "Response string"
    }
  ],
  "createdBy": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Response string"
  },
  "canUpdate": false,
  "canDelete": false,
  "createdAt": "Response string",
  "updatedAt": "Response string"
}
```


Delete SQL Database

DELETE `/api/v1/sql-databases/{id}`

Parameters

Parameter Name	Required	Type	Description
`id`	V	string	A UUID string identifying this SQL Database.

Code Examples

Shell/Bash

```
# Example API call (Shell)
curl -X DELETE "https://api.maiagent.ai/api/v1/sql-
databases/550e8400-e29b-41d4-a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# Replace YOUR_API_KEY and check the request data before running
this example.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

// Request body (payload)
const data = null;

axios.delete("https://api.maiagent.ai/api/v1/sql-databases/550e8400-
e29b-41d4-a716-446655440000/", data, config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request failed:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/sql-databases/550e8400-e29b-
41d4-a716-446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.delete(url, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request failed:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->delete("https://api.maiagent.ai/api/v1/sql-databases/550e8400-e29b-41d4-a716-446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request failed: ' . $e->getMessage();
}
?>
```

Response body

Status code	Description
204	No response body

Test database connection

POST `/api/v1/sql-databases/{id}/test-connection/`

Parameters

Parameter name	Required	Type	Description
`id`	V	string	A UUID string identifying this SQL Database.

Request body

Request parameters

Field	Type	Required	Description
databaseType	string (enum: postgresql, mysql, maiagent, oracle, mssql, synxdb)	Yes	`postgresql` : PostgreSQL ; `mysql` : MySQL ; `maiagent` : MaiAgent ; `oracle` : Oracle ; `mssql` : MSSQL ; `synxdb` : SynxDB;
databaseUrl	string	Yes	

Request schema example

```
{
  "databaseType": string (enum: postgresql, mysql, maiagent, oracle,
mssql, synxdb) // * `postgresql` - PostgreSQL
* `mysql` - MySQL
* `maiagent` - MaiAgent
* `oracle` - Oracle
* `mssql` - MSSQL
* `synxdb` - SynxDB
  "databaseUrl": string
}
```

Request example value

```
{
  "databaseType": "postgresql",
  "databaseUrl": "Example string"
}
```

Code examples

Shell/Bash

```
# Example API call (Shell)
curl -X POST "https://api.maiagent.ai/api/v1/sql-databases/550e8400-
e29b-41d4-a716-446655440000/test-connection/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "databaseType": "postgresql",
    "databaseUrl": "Example string"
  }'

# Replace YOUR_API_KEY and check the request data before running
this example.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// Request body (payload)
const data = {
    "databaseType": "postgresql",
    "databaseUrl": "Example string"
  };

axios.post("https://api.maiagent.ai/api/v1/sql-databases/550e8400-
e29b-41d4-a716-446655440000/test-connection/", data, config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request failed:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/sql-databases/550e8400-e29b-
41d4-a716-446655440000/test-connection/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# Request body (payload)
data = {
    "databaseType": "postgresql",
    "databaseUrl": "Example string"
}

response = requests.post(url, json=data, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request failed:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->post("https://api.maiagent.ai/api/v1/sql-databases/550e8400-e29b-41d4-a716-446655440000/test-connection/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'databaseType' => 'postgresql',
            'databaseUrl' => 'Example string'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request failed: ' . $e->getMessage();
}
?>
```

Response body

Status code: 200

Response schema example

```
{
  "success"?: boolean // optional
  "message"?: string // optional
}
```

Response example value

```
{
  "success": false,
  "message": "Response string"
}
```

Upload files to a database

POST `/api/v1/sql-databases/{id}/upload-files/`

Parameters

Parameter name	Required	Type	Description
`id`	V	string	A UUID string identifying this SQL Database.

Request body

Request parameters

Field	Type	Required	Description
files	array[object]	Yes	

Request schema example

```
{
  "files": [
    {
      "file": string // File path from presigned URL upload (e.g.,
media/chatbotfiles/xxx/file.csv)
      "filename": string // Original filename
      "size": integer // File size in bytes
    }
  ]
}
```

Request example value

```
{
  "files": [
    {
      "file": "media/chatbotfiles/xxx/data.csv",
      "filename": "data.csv",
      "size": 1024
    },
    {
      "file": "media/chatbotfiles/xxx/report.xlsx",
      "filename": "report.xlsx",
      "size": 2048
    }
  ]
}
```

Code examples

Shell/Bash

```
# Example API call (Shell)
curl -X POST "https://api.maiagent.ai/api/v1/sql-databases/550e8400-
e29b-41d4-a716-446655440000/upload-files/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "files": [
      {
        "file": "media/chatbotfiles/xxx/data.csv",
        "filename": "data.csv",
        "size": 1024
      },
      {
        "file": "media/chatbotfiles/xxx/report.xlsx",
        "filename": "report.xlsx",
        "size": 2048
      }
    ]
  }'

# Replace YOUR_API_KEY and check the request data before running
this example.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// Request body (payload)
const data = {
    "files": [
      {
        "file": "media/chatbotfiles/xxx/data.csv",
        "filename": "data.csv",
        "size": 1024
      },
      {
        "file": "media/chatbotfiles/xxx/report.xlsx",
        "filename": "report.xlsx",
        "size": 2048
      }
    ]
  };

axios.post("https://api.maiagent.ai/api/v1/sql-databases/550e8400-
e29b-41d4-a716-446655440000/upload-files/", data, config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request failed:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/sql-databases/550e8400-e29b-
41d4-a716-446655440000/upload-files/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# Request body (payload)
data = {
    "files": [
        {
            "file": "media/chatbotfiles/xxx/data.csv",
            "filename": "data.csv",
            "size": 1024
        },
        {
            "file": "media/chatbotfiles/xxx/report.xlsx",
            "filename": "report.xlsx",
            "size": 2048
        }
    ]
}

response = requests.post(url, json=data, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request failed:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->post("https://api.maiagent.ai/api/v1/sql-databases/550e8400-e29b-41d4-a716-446655440000/upload-files/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'files' => [
                [
                    'file' => 'media/chatbotfiles/xxx/data.csv',
                    'filename' => 'data.csv',
                    'size' => 1024
                ],
                [
                    'file' => 'media/chatbotfiles/xxx/report.xlsx',
                    'filename' => 'report.xlsx',
                    'size' => 2048
                ]
            ]
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request failed: ' . $e->getMessage();
}
?>
```

Response body

Status code: 201

Response schema example

```
{
  "message"?: string // optional
  "filesCount"?: integer // optional
  "fileIds"?: [ // optional
    string (uuid)
  ]
}
```

Response example value

```
{
  "message": "Response string",
  "filesCount": 456,
  "fileIds": [
    "550e8400-e29b-41d4-a716-446655440000"
  ]
}
```

Batch delete SQL databases

POST `/api/v1/sql-databases/batch-delete/`

Request body

Request parameters

Field	Type	Required	Description
ids	array[string]	Yes	

Request schema example

```
{
  "ids": [
    string (uuid)
  ]
}
```

Request example value

```
{
  "ids": [
    "550e8400-e29b-41d4-a716-446655440000"
  ]
}
```

Code examples

Shell/Bash

```
# Example API call (Shell)
curl -X POST "https://api.maiagent.ai/api/v1/sql-databases/batch-
delete/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "ids": [
      "550e8400-e29b-41d4-a716-446655440000"
    ]
  }'

# Replace YOUR_API_KEY and check the request data before running
this example.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// Request body (payload)
const data = {
    "ids": [
      "550e8400-e29b-41d4-a716-446655440000"
    ]
  };

axios.post("https://api.maiagent.ai/api/v1/sql-databases/batch-
delete/", data, config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request failed:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/sql-databases/batch-delete/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# Request body (payload)
data = {
    "ids": [
        "550e8400-e29b-41d4-a716-446655440000"
    ]
}

response = requests.post(url, json=data, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request failed:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->post("https://api.maiagent.ai/api/v1/sql-
databases/batch-delete/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'ids' => [
                '550e8400-e29b-41d4-a716-446655440000'
            ]
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request failed: ' . $e->getMessage();
}
?>
```

Response body

Status code	Description

204	No response body

List database tables

GET `/api/v1/sql-databases/{sqlDatabasePk}/tables/`

Parameters

Parameter name	Required	Type	Description
`sqlDatabasePk`	V	string	
`page`	X	integer	A page number within the paginated result set.
`pageSize`	X	integer	Number of results to return per page.
`query`	X	string	
`status`	X	string	`pending`: Pending ; `processing`: Processing ; `success`: Success ; `failed`: Failed ; `dropping`: Dropping ; `drop_failed`: Drop Failed;

Code examples

Shell/Bash

```
# Example API call (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/sql-
databases/{sqlDatabasePk}/tables/?
page=1&pageSize=1&query=example&status=drop_failed"

  -H "Authorization: Api-Key YOUR_API_KEY"

# Replace YOUR_API_KEY and check the request data before running
this example.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/sql-
databases/{sqlDatabasePk}/tables/?
page=1&pageSize=1&query=example&status=drop_failed", config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request failed:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/sql-
databases/{sqlDatabasePk}/tables/?
page=1&pageSize=1&query=example&status=drop_failed"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request failed:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->get("https://api.maiagent.ai/api/v1/sql-databases/{sqlDatabasePk}/tables/?page=1&pageSize=1&query=example&status=drop_failed", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request failed: ' . $e->getMessage();
}
?>
```

Response body

Status code: 200

Response schema example

```
{
  "count": integer
  "next"?: string (uri) // optional
```

```
  "previous"?: string (uri) // optional
  "results": [
    {
      "id": string (uuid)
      "tableName": string // Name of the table in the database
      "sheetName": string // Name of the source worksheet/sheet this
table was created from. Empty for tables created before this field was
added.
      "description"?: string // Description of the table and its data for
better Text-to-SQL understanding (optional)
      "status":
      {
      }
      "errorMessage": string // Error details if table creation or
deletion failed
      "sourceFile":
      {
        "id": string (uuid)
        "name": string
        "isFromKnowledgeBase": boolean // Determine if the source file
originated from a knowledge base upload.

Returns True if the file was uploaded via knowledge base,
False if uploaded directly to the database.
      }
      "columns": [
        {
          "id": string (uuid)
          "columnName": string
          "columnType"?: string // Data type of the column (e.g.,
VARCHAR, INTEGER, TIMESTAMP) (optional)
          "description"?: string // Description of the column for better
Text-to-SQL understanding (optional)
          "isPrimaryKey"?: boolean // optional
          "isNullable"?: boolean // optional
          "createdAt": string (timestamp)
          "updatedAt": string (timestamp)
        }
      ]
      "createdAt": string (timestamp)
      "updatedAt": string (timestamp)
    }
  ]
}
```

Response example value


```
{
  "count": 123,
  "next": "http://api.example.org/accounts/?page=4",
  "previous": "http://api.example.org/accounts/?page=2",
  "results": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "tableName": "Response string",
      "sheetName": "Response string",
      "description": "Response string",
      "status": {},
      "errorMessage": "Response string",
      "sourceFile": {
        "id": "550e8400-e29b-41d4-a716-446655440000",
        "name": "Response string",
        "isFromKnowledgeBase": false
      },
      "columns": [
        {
          "id": "550e8400-e29b-41d4-a716-446655440000",
          "columnName": "Response string",
          "columnType": "Response string",
          "description": "Response string",
          "isPrimaryKey": false,
          "isNullable": false,
          "createdAt": "Response string",
          "updatedAt": "Response string"
        }
      ],
      "createdAt": "Response string",
      "updatedAt": "Response string"
    }
  ]
}
```


Create a database table

POST `/api/v1/sql-databases/{sqlDatabasePk}/tables/`

Parameters

Parameter name	Required	Type	Description
sqlDatabasePk	V	string	

Request body

Request parameters

Field	Type	Required	Description
tableName	string	Yes	Name of the table in the database
description	string	No	Description of the table and its data for better Text-to-SQL understanding

Request schema example

```
{
  "tableName": string // Name of the table in the database
  "description"?: string // Description of the table and its data for
better Text-to-SQL understanding (optional)
}
```

Request example value

```
{
  "tableName": "Example string",
```

```
  "description": "Example string"
}
```

Code examples

Shell/Bash

```
# Example API call (Shell)
curl -X POST "https://api.maiagent.ai/api/v1/sql-
databases/{sqlDatabasePk}/tables/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "tableName": "Example string",
    "description": "Example string"
  }'

# Replace YOUR_API_KEY and check the request data before running
this example.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// Request body (payload)
const data = {
    "tableName": "Example string",
    "description": "Example string"
  };

axios.post("https://api.maiagent.ai/api/v1/sql-
databases/{sqlDatabasePk}/tables/", data, config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request failed:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/sql-
databases/{sqlDatabasePk}/tables/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# Request body (payload)
data = {
    "tableName": "Example string",
    "description": "Example string"
}

response = requests.post(url, json=data, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request failed:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->post("https://api.maiagent.ai/api/v1/sql-databases/{sqlDatabasePk}/tables/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'tableName' => 'Example string',
            'description' => 'Example string'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request failed: ' . $e->getMessage();
}
?>
```

Response Body

Status Code: 201

Example Response Schema

```
{
  "id": string (uuid)
  "tableName": string // Name of the table in the database
  "sheetName": string // Name of the source worksheet/sheet this table
was created from. Empty for tables created before this field was added.
  "description"?: string // Description of the table and its data for
better Text-to-SQL understanding (Optional)
  "status":
  {
  }
  "errorMessage": string // Error details if table creation or deletion
failed
  "sourceFile":
  {
    "id": string (uuid)
    "name": string
    "isFromKnowledgeBase": boolean // Determine if the source file
originated from a knowledge base upload.

Returns True if the file was uploaded via knowledge base,
False if uploaded directly to the database.
  }
  "columns": [
    {
      "id": string (uuid)
      "columnName": string
      "columnType"?: string // Data type of the column (e.g., VARCHAR,
INTEGER, TIMESTAMP) (Optional)
      "description"?: string // Description of the column for better
Text-to-SQL understanding (Optional)
      "isPrimaryKey"?: boolean // Optional
      "isNullable"?: boolean // Optional
      "createdAt": string (timestamp)
      "updatedAt": string (timestamp)
    }
  ]
  "createdAt": string (timestamp)
  "updatedAt": string (timestamp)
}
```

Example Response Values

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "tableName": "Response string",
  "sheetName": "Response string",
  "description": "Response string",
  "status": {},
  "errorMessage": "Response string",
  "sourceFile": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Response string",
    "isFromKnowledgeBase": false
  },
  "columns": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "columnName": "Response string",
      "columnType": "Response string",
      "description": "Response string",
      "isPrimaryKey": false,
      "isNullable": false,
      "createdAt": "Response string",
      "updatedAt": "Response string"
    }
  ],
  "createdAt": "Response string",
  "updatedAt": "Response string"
}
```


Get Specific Table

`GET` `/api/v1/sql-databases/{sqlDatabasePk}/tables/{id}`

Parameters

Parameter Name	Required	Type	Description
`id`	V	string	A UUID string identifying this Database Table.
`sqlDatabasePk`	V	string	

Code Examples

Shell/Bash

```
# API Call Example (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/sql-
databases/{sqlDatabasePk}/tables/550e8400-e29b-41d4-a716-
446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/sql-
databases/{sqlDatabasePk}/tables/550e8400-e29b-41d4-a716-
446655440000/", config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request failed:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/sql-
databases/{sqlDatabasePk}/tables/550e8400-e29b-41d4-a716-
446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request failed:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->get("https://api.maiagent.ai/api/v1/sql-databases/{sqlDatabasePk}/tables/550e8400-e29b-41d4-a716-446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request failed: ' . $e->getMessage();
}
?>
```

Response Body

Status Code: 200

Example Response Schema

```
{
  "id": string (uuid)
  "tableName": string // Name of the table in the database
```

```
  "sheetName": string // Name of the source worksheet/sheet this table
was created from. Empty for tables created before this field was added.
  "description"?: string // Description of the table and its data for
better Text-to-SQL understanding (Optional)
  "status":
  {
  }
  "errorMessage": string // Error details if table creation or deletion
failed
  "sourceFile":
  {
    "id": string (uuid)
    "name": string
    "isFromKnowledgeBase": boolean // Determine if the source file
originated from a knowledge base upload.

Returns True if the file was uploaded via knowledge base,
False if uploaded directly to the database.
  }
  "columns": [
    {
      "id": string (uuid)
      "columnName": string
      "columnType"?: string // Data type of the column (e.g., VARCHAR,
INTEGER, TIMESTAMP) (Optional)
      "description"?: string // Description of the column for better
Text-to-SQL understanding (Optional)
      "isPrimaryKey"?: boolean // Optional
      "isNullable"?: boolean // Optional
      "createdAt": string (timestamp)
      "updatedAt": string (timestamp)
    }
  ]
  "createdAt": string (timestamp)
  "updatedAt": string (timestamp)
}
```

Example Response Values

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "tableName": "Response string",
  "sheetName": "Response string",
  "description": "Response string",
```

```
  "status": {},
  "errorMessage": "Response string",
  "sourceFile": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Response string",
    "isFromKnowledgeBase": false
  },
  "columns": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "columnName": "Response string",
      "columnType": "Response string",
      "description": "Response string",
      "isPrimaryKey": false,
      "isNullable": false,
      "createdAt": "Response string",
      "updatedAt": "Response string"
    }
  ],
  "createdAt": "Response string",
  "updatedAt": "Response string"
}
```


Update Table

PUT `/api/v1/sql-databases/{sqlDatabasePk}/tables/{id}`

Parameters

Parameter Name	Required	Type	Description
`id`	V	string	A UUID string identifying this Database Table.
`sqlDatabasePk`	V	string	

Request Body

Request Parameters

Field	Type	Required	Description
tableName	string	Yes	Name of the table in the database
description	string	No	Description of the table and its data for better Text-to-SQL understanding

Example Request Schema

```
{
  "tableName": string // Name of the table in the database
  "description"?: string // Description of the table and its data for
better Text-to-SQL understanding (Optional)
}
```

Example Request Values

```
{
  "tableName": "Example string",
  "description": "Example string"
}
```

Code Examples

Shell/Bash

```
# API Call Example (Shell)
curl -X PUT "https://api.maiagent.ai/api/v1/sql-
databases/{sqlDatabasePk}/tables/550e8400-e29b-41d4-a716-
446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "tableName": "Example string",
    "description": "Example string"
  }'

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// Request body (payload)
const data = {
    "tableName": "Example string",
    "description": "Example string"
  };

axios.put("https://api.maiagent.ai/api/v1/sql-
databases/{sqlDatabasePk}/tables/550e8400-e29b-41d4-a716-
446655440000/", data, config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request failed:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/sql-
databases/{sqlDatabasePk}/tables/550e8400-e29b-41d4-a716-
446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# Request body (payload)
data = {
    "tableName": "Example string",
    "description": "Example string"
}

response = requests.put(url, json=data, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request failed:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->put("https://api.maiagent.ai/api/v1/sql-databases/{sqlDatabasePk}/tables/550e8400-e29b-41d4-a716-446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'tableName' => 'Example string',
            'description' => 'Example string'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request failed: ' . $e->getMessage();
}
?>
```

Response Body

Status Code: 200

Example Response Schema

```
{
  "id": string (uuid)
  "tableName": string // Name of the table in the database
  "sheetName": string // Name of the source worksheet/sheet this table
was created from. Empty for tables created before this field was added.
  "description"?: string // Description of the table and its data for
better Text-to-SQL understanding (Optional)
  "status":
  {
  }
  "errorMessage": string // Error details if table creation or deletion
failed
  "sourceFile":
  {
    "id": string (uuid)
    "name": string
    "isFromKnowledgeBase": boolean // Determine if the source file
originated from a knowledge base upload.

Returns True if the file was uploaded via knowledge base,
False if uploaded directly to the database.
  }
  "columns": [
    {
      "id": string (uuid)
      "columnName": string
      "columnType"?: string // Data type of the column (e.g., VARCHAR,
INTEGER, TIMESTAMP) (Optional)
      "description"?: string // Description of the column for better
Text-to-SQL understanding (Optional)
      "isPrimaryKey"?: boolean // Optional
      "isNullable"?: boolean // Optional
      "createdAt": string (timestamp)
      "updatedAt": string (timestamp)
    }
  ]
  "createdAt": string (timestamp)
  "updatedAt": string (timestamp)
}
```

Example Response Values

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "tableName": "Response string",
  "sheetName": "Response string",
  "description": "Response string",
  "status": {},
  "errorMessage": "Response string",
  "sourceFile": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Response string",
    "isFromKnowledgeBase": false
  },
  "columns": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "columnName": "Response string",
      "columnType": "Response string",
      "description": "Response string",
      "isPrimaryKey": false,
      "isNullable": false,
      "createdAt": "Response string",
      "updatedAt": "Response string"
    }
  ],
  "createdAt": "Response string",
  "updatedAt": "Response string"
}
```


Partially Update Table

PATCH `/api/v1/sql-databases/{sqlDatabasePk}/tables/{id}`

Parameters

Parameter Name	Required	Type	Description
`id`	V	string	A UUID string identifying this Database Table.
`sqlDatabasePk`	V	string	

Request Body

Request Parameters

Field	Type	Required	Description
tableName	string	No	Name of the table in the database
description	string	No	Description of the table and its data for better Text-to-SQL understanding

Example Request Schema

```
{
  "tableName"?: string // Name of the table in the database (Optional)
  "description"?: string // Description of the table and its data for
better Text-to-SQL understanding (Optional)
}
```

Example Request Values

```
{
  "tableName": "Example string",
  "description": "Example string"
}
```

Code Examples

Shell/Bash

```
# API Call Example (Shell)
curl -X PATCH "https://api.maiagent.ai/api/v1/sql-
databases/{sqlDatabasePk}/tables/550e8400-e29b-41d4-a716-
446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "tableName": "Example string",
    "description": "Example string"
  }'

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// Request body (payload)
const data = {
    "tableName": "Example string",
    "description": "Example string"
  };

axios.patch("https://api.maiagent.ai/api/v1/sql-
databases/{sqlDatabasePk}/tables/550e8400-e29b-41d4-a716-
446655440000/", data, config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request failed:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/sql-
databases/{sqlDatabasePk}/tables/550e8400-e29b-41d4-a716-
446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# Request body (payload)
data = {
    "tableName": "Example string",
    "description": "Example string"
}

response = requests.patch(url, json=data, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request failed:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->patch("https://api.maiagent.ai/api/v1/sql-databases/{sqlDatabasePk}/tables/550e8400-e29b-41d4-a716-446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'tableName' => 'Example string',
            'description' => 'Example string'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request failed: ' . $e->getMessage();
}
?>
```

Response Body

Status Code: 200

Example Response Schema

```
{
  "id": string (uuid)
  "tableName": string // Name of the table in the database
  "sheetName": string // Name of the source worksheet/sheet this table
was created from. Empty for tables created before this field was added.
  "description"?: string // Description of the table and its data for
better Text-to-SQL understanding (Optional)
  "status":
  {
  }
  "errorMessage": string // Error details if table creation or deletion
failed
  "sourceFile":
  {
    "id": string (uuid)
    "name": string
    "isFromKnowledgeBase": boolean // Determine if the source file
originated from a knowledge base upload.

Returns True if the file was uploaded via knowledge base,
False if uploaded directly to the database.
  }
  "columns": [
    {
      "id": string (uuid)
      "columnName": string
      "columnType"?: string // Data type of the column (e.g., VARCHAR,
INTEGER, TIMESTAMP) (Optional)
      "description"?: string // Description of the column for better
Text-to-SQL understanding (Optional)
      "isPrimaryKey"?: boolean // Optional
      "isNullable"?: boolean // Optional
      "createdAt": string (timestamp)
      "updatedAt": string (timestamp)
    }
  ]
  "createdAt": string (timestamp)
  "updatedAt": string (timestamp)
}
```

Example Response Values

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "tableName": "Response string",
  "sheetName": "Response string",
  "description": "Response string",
  "status": {},
  "errorMessage": "Response string",
  "sourceFile": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Response string",
    "isFromKnowledgeBase": false
  },
  "columns": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "columnName": "Response string",
      "columnType": "Response string",
      "description": "Response string",
      "isPrimaryKey": false,
      "isNullable": false,
      "createdAt": "Response string",
      "updatedAt": "Response string"
    }
  ],
  "createdAt": "Response string",
  "updatedAt": "Response string"
}
```


Delete Table

DELETE `/api/v1/sql-databases/{sqlDatabasePk}/tables/{id}`

Parameters

Parameter Name	Required	Type	Description
`id`	V	string	A UUID string identifying this Database Table.
`sqlDatabasePk`	V	string	

Code Examples

Shell/Bash

```
# API Call Example (Shell)
curl -X DELETE "https://api.maiagent.ai/api/v1/sql-
databases/{sqlDatabasePk}/tables/550e8400-e29b-41d4-a716-
446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

// Request body (payload)
const data = null;

axios.delete("https://api.maiagent.ai/api/v1/sql-
databases/{sqlDatabasePk}/tables/550e8400-e29b-41d4-a716-
446655440000/", data, config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request failed:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/sql-
databases/{sqlDatabasePk}/tables/550e8400-e29b-41d4-a716-
446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.delete(url, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request failed:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->delete("https://api.maiagent.ai/api/v1/sql-databases/{sqlDatabasePk}/tables/550e8400-e29b-41d4-a716-446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request failed: ' . $e->getMessage();
}
?>
```

Response Body

Status code	Description
204	No response body

Batch delete tables

POST `/api/v1/sql-databases/{sqlDatabasePk}/tables/batch-delete/`

Parameters

Parameter Name	Required	Type	Description
sqlDatabasePk	V	string	

Request Body

Request Parameters

Field	Type	Required	Description
ids	array[string]	Yes	

Example Request Schema

```
{
  "ids": [
    string (uuid)
  ]
}
```

Example Request Values

```
{
  "ids": [
    "550e8400-e29b-41d4-a716-446655440000"
```

```
  ]
}
```

Code Examples

Shell/Bash

```
# API Call Example (Shell)
curl -X POST "https://api.maiagent.ai/api/v1/sql-
databases/{sqlDatabasePk}/tables/batch-delete/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "ids": [
      "550e8400-e29b-41d4-a716-446655440000"
    ]
  }'

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// Request body (payload)
const data = {
    "ids": [
      "550e8400-e29b-41d4-a716-446655440000"
    ]
  };

axios.post("https://api.maiagent.ai/api/v1/sql-
databases/{sqlDatabasePk}/tables/batch-delete/", data, config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request failed:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/sql-
databases/{sqlDatabasePk}/tables/batch-delete/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# Request body (payload)
data = {
    "ids": [
        "550e8400-e29b-41d4-a716-446655440000"
    ]
}

response = requests.post(url, json=data, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request failed:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->post("https://api.maiagent.ai/api/v1/sql-databases/{sqlDatabasePk}/tables/batch-delete/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'ids' => [
                '550e8400-e29b-41d4-a716-446655440000'
            ]
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request failed: ' . $e->getMessage();
}
?>
```

Response Body

Status code	Description

204	No response body

List table columns

GET `/api/v1/sql-databases/{sqlDatabasePk}/tables/{tablePk}/columns/`

Parameters

Parameter Name	Required	Type	Description
`sqlDatabasePk`	V	string	
`tablePk`	V	string	

Code Examples

Shell/Bash

```
# API Call Example (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/sql-
databases/{sqlDatabasePk}/tables/{tablePk}/columns/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/sql-
databases/{sqlDatabasePk}/tables/{tablePk}/columns/", config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request failed:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/sql-
databases/{sqlDatabasePk}/tables/{tablePk}/columns/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request failed:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->get("https://api.maiagent.ai/api/v1/sql-databases/{sqlDatabasePk}/tables/{tablePk}/columns/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request failed: ' . $e->getMessage();
}
?>
```

Response Body

Status Code: 200

Example Response Schema

```
[
  {
    "id": string (uuid)
    "columnName": string
```

```
    "columnType"?: string // Data type of the column (e.g., VARCHAR,
INTEGER, TIMESTAMP) (Optional)
    "description"?: string // Description of the column for better Text-
to-SQL understanding (Optional)
    "isPrimaryKey"?: boolean // Optional
    "isNullable"?: boolean // Optional
    "createdAt": string (timestamp)
    "updatedAt": string (timestamp)
  }
]
```

Example Response Values

```
[
  {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "columnName": "Response string",
    "columnType": "Response string",
    "description": "Response string",
    "isPrimaryKey": false,
    "isNullable": false,
    "createdAt": "Response string",
    "updatedAt": "Response string"
  }
]
```

Get a specific table column

GET `/api/v1/sql-databases/{sqlDatabasePk}/tables/{tablePk}/columns/{id}`

Parameters

Parameter Name	Required	Type	Description

`id`	V	string	A UUID string identifying this Database Table Column.
`sqlDatabasePk`	V	string	
`tablePk`	V	string	

Code Examples

Shell/Bash

```
# API Call Example (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/sql-
databases/{sqlDatabasePk}/tables/{tablePk}/columns/550e8400-e29b-
41d4-a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/sql-
databases/{sqlDatabasePk}/tables/{tablePk}/columns/550e8400-e29b-
41d4-a716-446655440000/", config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request failed:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/sql-databases/{sqlDatabasePk}/tables/{tablePk}/columns/550e8400-e29b-41d4-a716-446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request failed:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->get("https://api.maiagent.ai/api/v1/sql-databases/{sqlDatabasePk}/tables/{tablePk}/columns/550e8400-e29b-41d4-a716-446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request failed: ' . $e->getMessage();
}
?>
```

Response Body

Status Code: 200

Example Response Schema

```
{
  "id": string (uuid)
  "columnName": string
```

```
  "columnType"?: string // Data type of the column (e.g., VARCHAR,
INTEGER, TIMESTAMP) (Optional)
  "description"?: string // Description of the column for better Text-to-
SQL understanding (Optional)
  "isPrimaryKey"?: boolean // Optional
  "isNullable"?: boolean // Optional
  "createdAt": string (timestamp)
  "updatedAt": string (timestamp)
}
```

Example Response Values

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "columnName": "Response string",
  "columnType": "Response string",
  "description": "Response string",
  "isPrimaryKey": false,
  "isNullable": false,
  "createdAt": "Response string",
  "updatedAt": "Response string"
}
```

Update a table column

PUT `/api/v1/sql-databases/{sqlDatabasePk}/tables/{tablePk}/columns/{id}`

Parameters

Parameter Name	Required	Type	Description
`id`	V	string	A UUID string identifying this Database Table Column.

`sqlDatabasePk`	V	string	
`tablePk`	V	string	

Request Body

Request Parameters

Field	Type	Required	Description
columnName	string	Yes	
columnType	string	No	Data type of the column (e.g., VARCHAR, INTEGER, TIMESTAMP)
description	string	No	Description of the column for better Text-to-SQL understanding
isPrimaryKey	boolean	No	
isNullable	boolean	No	

Example Request Schema

```
{
  "columnName": string
  "columnType"?: string // Data type of the column (e.g., VARCHAR,
INTEGER, TIMESTAMP) (Optional)
  "description"?: string // Description of the column for better Text-to-
SQL understanding (Optional)
  "isPrimaryKey"?: boolean // Optional
  "isNullable"?: boolean // Optional
}
```

Example Request Values

```
{
  "columnName": "Example string",
  "columnType": "Example string",
  "description": "Example string",
```

```
  "isPrimaryKey": true,
  "isNullable": true
}
```

Code Examples

Shell/Bash

```
# API Call Example (Shell)
curl -X PUT "https://api.maiagent.ai/api/v1/sql-
databases/{sqlDatabasePk}/tables/{tablePk}/columns/550e8400-e29b-
41d4-a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "columnName": "Example string",
    "columnType": "Example string",
    "description": "Example string",
    "isPrimaryKey": true,
    "isNullable": true
  }'

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// Request body (payload)
const data = {
    "columnName": "Example string",
    "columnType": "Example string",
    "description": "Example string",
    "isPrimaryKey": true,
    "isNullable": true
  };

axios.put("https://api.maiagent.ai/api/v1/sql-
databases/{sqlDatabasePk}/tables/{tablePk}/columns/550e8400-e29b-
41d4-a716-446655440000/", data, config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request failed:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/sql-
databases/{sqlDatabasePk}/tables/{tablePk}/columns/550e8400-e29b-
41d4-a716-446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# Request body (payload)
data = {
    "columnName": "Example string",
    "columnType": "Example string",
    "description": "Example string",
    "isPrimaryKey": True,
    "isNullable": True
}

response = requests.put(url, json=data, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request failed:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->put("https://api.maiagent.ai/api/v1/sql-databases/{sqlDatabasePk}/tables/{tablePk}/columns/550e8400-e29b-41d4-a716-446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'columnName' => 'Example string',
            'columnType' => 'Example string',
            'description' => 'Example string',
            'isPrimaryKey' => true,
            'isNullable' => true
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request failed: ' . $e->getMessage();
}
?>
```

Response Body

Status Code: 200

Example Response Schema

```
{
  "id": string (uuid)
  "columnName": string
  "columnType"?: string // Data type of the column (e.g., VARCHAR,
INTEGER, TIMESTAMP) (Optional)
  "description"?: string // Description of the column for better Text-to-
SQL understanding (Optional)
  "isPrimaryKey"?: boolean // Optional
  "isNullable"?: boolean // Optional
  "createdAt": string (timestamp)
  "updatedAt": string (timestamp)
}
```

Example Response Values

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "columnName": "Response string",
  "columnType": "Response string",
  "description": "Response string",
  "isPrimaryKey": false,
  "isNullable": false,
  "createdAt": "Response string",
  "updatedAt": "Response string"
}
```

Partially update a table column

PATCH `/api/v1/sql-databases/{sqlDatabasePk}/tables/{tablePk}/columns/{id}`

Parameters

Parameter Name	Required	Type	Description
`id`	V	string	A UUID string identifying this Database Table Column.
`sqlDatabasePk`	V	string	
`tablePk`	V	string	

Request Body

Request Parameters

Field	Type	Required	Description
columnName	string	No	
columnType	string	No	Data type of the column (e.g., VARCHAR, INTEGER, TIMESTAMP)
description	string	No	Description of the column for better Text-to-SQL understanding
isPrimaryKey	boolean	No	
isNullable	boolean	No	

Example Request Schema

```
{
  "columnName"?: string // Optional
  "columnType"?: string // Data type of the column (e.g., VARCHAR,
INTEGER, TIMESTAMP) (Optional)
  "description"?: string // Description of the column for better Text-to-
SQL understanding (Optional)
  "isPrimaryKey"?: boolean // Optional
```

```
  "isNullable"?: boolean // Optional
}
```

Example Request Values

```
{
  "columnName": "Example string",
  "columnType": "Example string",
  "description": "Example string",
  "isPrimaryKey": true,
  "isNullable": true
}
```

Code Examples

Shell/Bash

```
# API Call Example (Shell)
curl -X PATCH "https://api.maiagent.ai/api/v1/sql-
databases/{sqlDatabasePk}/tables/{tablePk}/columns/550e8400-e29b-
41d4-a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "columnName": "Example string",
    "columnType": "Example string",
    "description": "Example string",
    "isPrimaryKey": true,
    "isNullable": true
  }'

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// Request body (payload)
const data = {
    "columnName": "Example string",
    "columnType": "Example string",
    "description": "Example string",
    "isPrimaryKey": true,
    "isNullable": true
  };

axios.patch("https://api.maiagent.ai/api/v1/sql-
databases/{sqlDatabasePk}/tables/{tablePk}/columns/550e8400-e29b-
41d4-a716-446655440000/", data, config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request failed:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/sql-
databases/{sqlDatabasePk}/tables/{tablePk}/columns/550e8400-e29b-
41d4-a716-446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# Request body (payload)
data = {
    "columnName": "Example string",
    "columnType": "Example string",
    "description": "Example string",
    "isPrimaryKey": True,
    "isNullable": True
}

response = requests.patch(url, json=data, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request failed:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->patch("https://api.maiagent.ai/api/v1/sql-databases/{sqlDatabasePk}/tables/{tablePk}/columns/550e8400-e29b-41d4-a716-446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'columnName' => 'Example string',
            'columnType' => 'Example string',
            'description' => 'Example string',
            'isPrimaryKey' => true,
            'isNullable' => true
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request failed: ' . $e->getMessage();
}
?>
```

Response Body

Status Code: 200

Example Response Schema

```
{
  "id": string (uuid)
  "columnName": string
  "columnType"?: string // Data type of the column (e.g., VARCHAR,
INTEGER, TIMESTAMP) (Optional)
  "description"?: string // Description of the column for better Text-to-
SQL understanding (Optional)
  "isPrimaryKey"?: boolean // Optional
  "isNullable"?: boolean // Optional
  "createdAt": string (timestamp)
  "updatedAt": string (timestamp)
}
```

Example Response Values

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "columnName": "Response string",
  "columnType": "Response string",
  "description": "Response string",
  "isPrimaryKey": false,
  "isNullable": false,
  "createdAt": "Response string",
  "updatedAt": "Response string"
}
```

Test Database Connection (General)

POST `/api/v1/database-connection/test/`

Request Body

Request Parameters

Field	Type	Required	Description
databaseType	object	Yes	Database type (excluding the type used internally by MaiAgent) `postgresql` : PostgreSQL ; `mysql` : MySQL ; `oracle` : Oracle ; `mssql` : MSSQL ; `synxdb` : SynxDB;
databaseUrl	string	Yes	Database connection string

Example Request Schema

```
{
  "databaseType":  // Database type (excluding the type used internally
by MaiAgent)

* `postgresql` - PostgreSQL
* `mysql` - MySQL
* `oracle` - Oracle
* `mssql` - MSSQL
* `synxdb` - SynxDB
  {
  }
  "databaseUrl": string // Database connection string
}
```

Example Request Values

```
{
  "database_type": "postgresql",
  "database_url": "postgresql://user:password@localhost:5432/dbname"
}
```

Code Examples

Shell/Bash

```
# API Call Example (Shell)
curl -X POST "https://api.maiagent.ai/api/v1/database-
connection/test/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "database_type": "postgresql",
    "database_url":
"postgresql://user:password@localhost:5432/dbname"
  }'

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// Request body (payload)
const data = {
    "database_type": "postgresql",
    "database_url":
"postgresql://user:password@localhost:5432/dbname"
  };

axios.post("https://api.maiagent.ai/api/v1/database-
connection/test/", data, config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request failed:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/database-connection/test/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# Request body (payload)
data = {
    "database_type": "postgresql",
    "database_url":
"postgresql://user:password@localhost:5432/dbname"
}

response = requests.post(url, json=data, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request failed:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>post("https://api.maiagent.ai/api/v1/database-connection/test/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'database_type' => 'postgresql',
            'database_url' =>
'postgresql://user:password@localhost:5432/dbname'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request failed: ' . $e->getMessage();
}
?>
```

Response Body

Status Code: 200

Example Response Schema

```
{
  "status":  // Connection status

* `success` - success
* `failed` - failed
  {
  }
  "responseTime"?: number (double) // Response time (seconds) (Optional)
  "message"?: string // Success message (Optional)
  "errorMessage"?: string // Error message (Optional)
}
```

Example Response Values

```
{
  "status": "success",
  "response_time": 0.123,
  "message": "Successfully connected to PostgreSQL database"
}
```

Status Code: 400

Example Response Schema

```
{
  "detail"?: string // Optional
}
```

Example Response Values

```
{
  "status": "success",
  "response_time": 0.123,
  "message": "Successfully connected to PostgreSQL database"
}
```

List Database Connection String Examples

GET `/api/v1/database-examples/`

Code Examples

Shell/Bash

```
# Example API call (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/database-examples/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/database-examples/",
config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request failed:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/database-examples/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request failed:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/database-examples/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request failed: ' . $e->getMessage();
}
?>
```

Response Body

Status Code: 200

Example Response Schema

```
[
  {
    "databaseType"?:  // Database type option
```

```
* `postgresql` - PostgreSQL
* `mysql` - MySQL
* `maiagent` - MaiAgent
* `oracle` - Oracle
* `mssql` - MSSQL
* `synxdb` - SynxDB (Optional)
    {
    }
    "databaseTypeExample": string // For example:
postgresql://db_user:db_password@db_ip:db_port/db_name
  }
]
```

Example Response Values

```
[
  {
    "databaseType": {},
    "databaseTypeExample": "Response string"
  }
]
```

Status Code: 401

Example Response Schema

```
{
  "detail"?: string // Optional
}
```

Example Response Values

```
{
  "detail": "Response string"
}
```

Retrieve a Specific Connection String Example

GET `/api/v1/database-examples/{id}`

Parameters

Parameter	Required	Type	Description
`id`	V	string	A UUID string identifying this Database Connection Example.

Code Examples

Shell/Bash

```
# Example API call (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/database-
examples/550e8400-e29b-41d4-a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/database-
examples/550e8400-e29b-41d4-a716-446655440000/", config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request failed:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/database-examples/550e8400-
e29b-41d4-a716-446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request failed:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/database-examples/550e8400-
e29b-41d4-a716-446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request failed: ' . $e->getMessage();
}
?>
```

Response Body

Status Code: 200

Example Response Schema

```
{
  "databaseType"?:  // Database type option
```

```
* `postgresql` - PostgreSQL
* `mysql` - MySQL
* `maiagent` - MaiAgent
* `oracle` - Oracle
* `mssql` - MSSQL
* `synxdb` - SynxDB (Optional)
  {
  }
  "databaseTypeExample": string // For example:
postgresql://db_user:db_password@db_ip:db_port/db_name
}
```

Example Response Values

```
{
  "databaseType": {},
  "databaseTypeExample": "Response string"
}
```

List Database Configurations of an AI Assistant

GET `/api/v1/chatbots/{chatbotPk}/databases/`

Parameters

Parameter Name	Required	Type	Description
`chatbotPk`	V	string	A UUID string identifying this Chatbot ID
`page`	X	integer	A page number within the paginated result set.

`pageSize`	X	integer	Number of results to return per page.

Code Examples

Shell/Bash

```
# API Call Example (Shell)
curl -X GET "

  -H "Authorization: Api-Key YOUR_API_KEY"

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get(" config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request failed:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request failed:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->get(" [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request failed: ' . $e->getMessage();
}
?>
```

Response Body

Status Code: 200

Example Response Schema

```
{
  "count": integer
  "next"?: string (uri) // Optional
  "previous"?: string (uri) // Optional
  "results": [
```

```
    {
      "id": string (uuid)
      "name": string // Display name, for example: Main Business DB,
Analytics DB.
      "databaseType":  // Database type: MySQL, PostgreSQL, MSSQL,
Oracle, SynxDB, or MaiAgent.

* `postgresql` - PostgreSQL
* `mysql` - MySQL
* `maiagent` - MaiAgent
* `oracle` - Oracle
* `mssql` - MSSQL
* `synxdb` - SynxDB
      {
      }
      "databaseUrl": string // Database connection string.
      "databaseUrlMasked": string
      "includeTables"?: object // Tables to query, formatted as
{"tables": ["table1", "table2"]}. The MaiAgent type reads them from
uploaded files automatically, so no manual setup is needed. (Optional)
      "isActive"?: boolean // When inactive, this database is not used
for Text-to-SQL queries. (Optional)
      "createdAt": string (timestamp)
      "updatedAt": string (timestamp)
    }
  ]
}
```

Example Response Values

```
{
  "count": 123,
  "next": "http://api.example.org/accounts/?page=4",
  "previous": "http://api.example.org/accounts/?page=2",
  "results": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "name": "Response string",
      "databaseType": {},
      "databaseUrl": "Response string",
      "databaseUrlMasked": "Response string",
      "includeTables": null,
      "isActive": false,
      "createdAt": "Response string",
```

```
        "updatedAt": "Response string"
      }
    ]
  }
```


Add Database Configuration to an AI Assistant

POST `/api/v1/chatbots/{chatbotPk}/databases/`

Parameters

Parameter Name	Required	Type	Description
`chatbotPk`	V	string	A UUID string identifying this Chatbot ID

Request Body

Request Parameters

Field	Type	Required	Description
name	string	Yes	Display name, for example: Main Business DB, Analytics DB.
databaseType	object	Yes	Database type: MySQL, PostgreSQL, MSSQL, Oracle, SynxDB, or MaiAgent. `postgresql` : PostgreSQL ; `mysql` : MySQL ; `maiagent` : MaiAgent ; `oracle` : Oracle ; `mssql` : MSSQL ; `synxdb` : SynxDB;
databaseUrl	string	Yes	Database connection string.

Field	Type	Required	Description
includeTables	object	No	Tables to query, formatted as {"tables": ["table1", "table2"]}. The MaiAgent type reads them from uploaded files automatically, so no manual setup is needed.
isActive	boolean	No	When inactive, this database is not used for Text-to-SQL queries.

Example Request Schema

```
{
  "name": string // Display name, for example: Main Business DB,
Analytics DB.
  "databaseType":  // Database type: MySQL, PostgreSQL, MSSQL, Oracle,
SynxDB, or MaiAgent.

* `postgresql` - PostgreSQL
* `mysql` - MySQL
* `maiagent` - MaiAgent
* `oracle` - Oracle
* `mssql` - MSSQL
* `synxdb` - SynxDB
  {
  }
  "databaseUrl": string // Database connection string.
  "includeTables"?: object // Tables to query, formatted as {"tables":
["table1", "table2"]}. The MaiAgent type reads them from uploaded files
automatically, so no manual setup is needed. (Optional)
  "isActive"?: boolean // When inactive, this database is not used for
Text-to-SQL queries. (Optional)
}
```

Example Request Values

```
{
  "name": "Example name",
  "databaseType": {},
  "databaseUrl": "Example string",
  "includeTables": null,
```

```
  "isActive": true
}
```

Code Examples

Shell/Bash

```
# API Call Example (Shell)
curl -X POST "

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "name": "Example name",
    "databaseType": {},
    "databaseUrl": "Example string",
    "includeTables": null,
    "isActive": true
  }'

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// Request body (payload)
const data = {
    "name": "Example name",
    "databaseType": {},
    "databaseUrl": "Example string",
    "includeTables": null,
    "isActive": true
  };

axios.post(" data, config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request failed:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# Request body (payload)
data = {
    "name": "Example name",
    "databaseType": {},
    "databaseUrl": "Example string",
    "includeTables": None,
    "isActive": True
}

response = requests.post(url, json=data, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request failed:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->post(" [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'name' => 'Example name',
            'databaseType' => new \stdClass(),
            'databaseUrl' => 'Example string',
            'includeTables' => null,
            'isActive' => true
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request failed: ' . $e->getMessage();
}
?>
```

Response Body

Status Code: 201

Example Response Schema

```
{
  "id": string (uuid)
  "name": string // Display name, for example: Main Business DB,
Analytics DB.
  "databaseType":  // Database type: MySQL, PostgreSQL, MSSQL, Oracle,
SynxDB, or MaiAgent.

* `postgresql` - PostgreSQL
* `mysql` - MySQL
* `maiagent` - MaiAgent
* `oracle` - Oracle
* `mssql` - MSSQL
* `synxdb` - SynxDB
  {
  }
  "databaseUrl": string // Database connection string.
  "databaseUrlMasked": string
  "includeTables"?: object // Tables to query, formatted as {"tables":
["table1", "table2"]}. The MaiAgent type reads them from uploaded files
automatically, so no manual setup is needed. (Optional)
  "isActive"?: boolean // When inactive, this database is not used for
Text-to-SQL queries. (Optional)
  "createdAt": string (timestamp)
  "updatedAt": string (timestamp)
}
```

Example Response Values

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "name": "Response string",
  "databaseType": {},
  "databaseUrl": "Response string",
  "databaseUrlMasked": "Response string",
  "includeTables": null,
  "isActive": false,
  "createdAt": "Response string",
  "updatedAt": "Response string"
}
```

Get Specific Database Configuration

GET `/api/v1/chatbots/{chatbotPk}/databases/{id}`

Parameters

Parameter Name	Required	Type	Description
`chatbotPk`	V	string	A UUID string identifying this Chatbot ID
`id`	V	string	A UUID string identifying this Chatbot Database Configuration.

Code Examples

Shell/Bash

```
# API Call Example (Shell)
curl -X GET "

  -H "Authorization: Api-Key YOUR_API_KEY"

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get(" config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request failed:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request failed:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->get(" [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request failed: ' . $e->getMessage();
}
?>
```

Response Body

Status Code: 200

Example Response Schema

```
{
  "id": string (uuid)
  "name": string // Display name, for example: Main Business DB,
Analytics DB.
  "databaseType":  // Database type: MySQL, PostgreSQL, MSSQL, Oracle,
```

```
SynxDB, or MaiAgent.

* `postgresql` - PostgreSQL
* `mysql` - MySQL
* `maiagent` - MaiAgent
* `oracle` - Oracle
* `mssql` - MSSQL
* `synxdb` - SynxDB
  {
  }
  "databaseUrl": string // Database connection string.
  "databaseUrlMasked": string
  "includeTables"?: object // Tables to query, formatted as {"tables":
["table1", "table2"]}. The MaiAgent type reads them from uploaded files
automatically, so no manual setup is needed. (Optional)
  "isActive"?: boolean // When inactive, this database is not used for
Text-to-SQL queries. (Optional)
  "createdAt": string (timestamp)
  "updatedAt": string (timestamp)
}
```

Example Response Values

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "name": "Response string",
  "databaseType": {},
  "databaseUrl": "Response string",
  "databaseUrlMasked": "Response string",
  "includeTables": null,
  "isActive": false,
  "createdAt": "Response string",
  "updatedAt": "Response string"
}
```

Update Database Configuration

PUT `/api/v1/chatbots/{chatbotPk}/databases/{id}`

Parameters

Parameter Name	Required	Type	Description
`chatbotPk`	V	string	A UUID string identifying this Chatbot ID
`id`	V	string	A UUID string identifying this Chatbot Database Configuration.

Request Body

Request Parameters

Field	Type	Required	Description
name	string	Yes	Display name, for example: Main Business DB, Analytics DB.
databaseType	object	Yes	Database type: MySQL, PostgreSQL, MSSQL, Oracle, SynxDB, or MaiAgent. `postgresql` : PostgreSQL ; `mysql` : MySQL ; `maiagent` : MaiAgent ; `oracle` : Oracle ; `mssql` : MSSQL ; `synxdb` : SynxDB;
databaseUrl	string	Yes	Database connection string.
includeTables	object	No	Tables to query, formatted as {"tables": ["table1", "table2"]}. The MaiAgent type reads them from uploaded files automatically, so no manual setup is needed.
isActive	boolean	No	When inactive, this database is not used for Text-to-SQL queries.

Example Request Schema

```
{
  "name": string // Display name, for example: Main Business DB,
Analytics DB.
  "databaseType":  // Database type: MySQL, PostgreSQL, MSSQL, Oracle,
SynxDB, or MaiAgent.

* `postgresql` - PostgreSQL
* `mysql` - MySQL
* `maiagent` - MaiAgent
* `oracle` - Oracle
* `mssql` - MSSQL
* `synxdb` - SynxDB
  {
  }
  "databaseUrl": string // Database connection string.
  "includeTables"?: object // Tables to query, formatted as {"tables":
["table1", "table2"]}. The MaiAgent type reads them from uploaded files
automatically, so no manual setup is needed. (Optional)
  "isActive"?: boolean // When inactive, this database is not used for
Text-to-SQL queries. (Optional)
}
```

Example Request Values

```
{
  "name": "Example name",
  "databaseType": {},
  "databaseUrl": "Example string",
  "includeTables": null,
  "isActive": true
}
```

Code Examples

Shell/Bash

```
# API Call Example (Shell)
curl -X PUT "

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "name": "Example name",
    "databaseType": {},
    "databaseUrl": "Example string",
    "includeTables": null,
    "isActive": true
  }'

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// Request body (payload)
const data = {
    "name": "Example name",
    "databaseType": {},
    "databaseUrl": "Example string",
    "includeTables": null,
    "isActive": true
  };

axios.put(" data, config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request failed:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# Request body (payload)
data = {
    "name": "Example name",
    "databaseType": {},
    "databaseUrl": "Example string",
    "includeTables": None,
    "isActive": True
}

response = requests.put(url, json=data, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request failed:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->put(" [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'name' => 'Example name',
            'databaseType' => new \stdClass(),
            'databaseUrl' => 'Example string',
            'includeTables' => null,
            'isActive' => true
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request failed: ' . $e->getMessage();
}
?>
```

Response Body

Status Code: 200

Example Response Schema

```
{
  "id": string (uuid)
  "name": string // Display name, for example: Main Business DB,
Analytics DB.
  "databaseType":  // Database type: MySQL, PostgreSQL, MSSQL, Oracle,
SynxDB, or MaiAgent.

* `postgresql` - PostgreSQL
* `mysql` - MySQL
* `maiagent` - MaiAgent
* `oracle` - Oracle
* `mssql` - MSSQL
* `synxdb` - SynxDB
  {
  }
  "databaseUrl": string // Database connection string.
  "databaseUrlMasked": string
  "includeTables"?: object // Tables to query, formatted as {"tables":
["table1", "table2"]}. The MaiAgent type reads them from uploaded files
automatically, so no manual setup is needed. (Optional)
  "isActive"?: boolean // When inactive, this database is not used for
Text-to-SQL queries. (Optional)
  "createdAt": string (timestamp)
  "updatedAt": string (timestamp)
}
```

Example Response Values

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "name": "Response string",
  "databaseType": {},
  "databaseUrl": "Response string",
  "databaseUrlMasked": "Response string",
  "includeTables": null,
  "isActive": false,
  "createdAt": "Response string",
  "updatedAt": "Response string"
}
```

Partially Update Database Configuration

`PATCH` `/api/v1/chatbots/{chatbotPk}/databases/{id}`

Parameters

Parameter Name	Required	Type	Description
`chatbotPk`	V	string	A UUID string identifying this Chatbot ID
`id`	V	string	A UUID string identifying this Chatbot Database Configuration.

Request Body

Request Parameters

Field	Type	Required	Description
name	string	No	Display name, for example: Main Business DB, Analytics DB.
databaseType	object	No	Database type: MySQL, PostgreSQL, MSSQL, Oracle, SynxDB, or MaiAgent. `postgresql` : PostgreSQL ; `mysql` : MySQL ; `maiagent` : MaiAgent ; `oracle` : Oracle ; `mssql` : MSSQL ; `synxdb` : SynxDB;
databaseUrl	string	No	Database connection string.
includeTables	object	No	Tables to query, formatted as {"tables": ["table1", "table2"]}. The MaiAgent type reads them from uploaded files automatically, so no manual setup is needed.

Field	Type	Required	Description
isActive	boolean	No	When inactive, this database is not used for Text-to-SQL queries.

Example Request Schema

```
{
  "name"?: string // Display name, for example: Main Business DB, Analytics DB. (Optional)
  "databaseType"?:  // Database type: MySQL, PostgreSQL, MSSQL, Oracle, SynxDB, or MaiAgent.

* `postgresql` - PostgreSQL
* `mysql` - MySQL
* `maiagent` - MaiAgent
* `oracle` - Oracle
* `mssql` - MSSQL
* `synxdb` - SynxDB (Optional)
  {
  }
  "databaseUrl"?: string // Database connection string. (Optional)
  "includeTables"?: object // Tables to query, formatted as {"tables": ["table1", "table2"]}. The MaiAgent type reads them from uploaded files automatically, so no manual setup is needed. (Optional)
  "isActive"?: boolean // When inactive, this database is not used for Text-to-SQL queries. (Optional)
}
```

Example Request Values

```
{
  "name": "Example name",
  "databaseType": {},
  "databaseUrl": "Example string",
  "includeTables": null,
  "isActive": true
}
```

Code Examples

Shell/Bash

```
# API Call Example (Shell)
curl -X PATCH "

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "name": "Example name",
    "databaseType": {},
    "databaseUrl": "Example string",
    "includeTables": null,
    "isActive": true
  }'

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// Request body (payload)
const data = {
    "name": "Example name",
    "databaseType": {},
    "databaseUrl": "Example string",
    "includeTables": null,
    "isActive": true
  };

axios.patch(" data, config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request failed:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# Request body (payload)
data = {
    "name": "Example name",
    "databaseType": {},
    "databaseUrl": "Example string",
    "includeTables": None,
    "isActive": True
}

response = requests.patch(url, json=data, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request failed:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->patch(" [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'name' => 'Example name',
            'databaseType' => new \stdClass(),
            'databaseUrl' => 'Example string',
            'includeTables' => null,
            'isActive' => true
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request failed: ' . $e->getMessage();
}
?>
```

Response Body

Status Code: 200

Example Response Schema

```
{
  "id": string (uuid)
  "name": string // Display name, for example: Main Business DB,
Analytics DB.
  "databaseType":  // Database type: MySQL, PostgreSQL, MSSQL, Oracle,
SynxDB, or MaiAgent.

* `postgresql` - PostgreSQL
* `mysql` - MySQL
* `maiagent` - MaiAgent
* `oracle` - Oracle
* `mssql` - MSSQL
* `synxdb` - SynxDB
  {
  }
  "databaseUrl": string // Database connection string.
  "databaseUrlMasked": string
  "includeTables"?: object // Tables to query, formatted as {"tables":
["table1", "table2"]}. The MaiAgent type reads them from uploaded files
automatically, so no manual setup is needed. (Optional)
  "isActive"?: boolean // When inactive, this database is not used for
Text-to-SQL queries. (Optional)
  "createdAt": string (timestamp)
  "updatedAt": string (timestamp)
}
```

Example Response Values

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "name": "Response string",
  "databaseType": {},
  "databaseUrl": "Response string",
  "databaseUrlMasked": "Response string",
  "includeTables": null,
  "isActive": false,
  "createdAt": "Response string",
  "updatedAt": "Response string"
}
```

Delete Database Configuration

DELETE `/api/v1/chatbots/{chatbotPk}/databases/{id}`

Parameters

Parameter Name	Required	Type	Description
`chatbotPk`	V	string	A UUID string identifying this Chatbot ID
`id`	V	string	A UUID string identifying this Chatbot Database Configuration.

Code Examples

Shell/Bash

```
# API Call Example (Shell)
curl -X DELETE "

  -H "Authorization: Api-Key YOUR_API_KEY"

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

// Request body (payload)
const data = null;

axios.delete(" data, config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request failed:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.delete(url, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request failed:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->delete(" [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request failed: ' . $e->getMessage();
}
?>
```

Response Body

Status Code	Description
204	No response body

API call example (Shell)

目錄

1. Create New Attachment (Integrated)
2. Get Presigned URL for File Upload
3. Upload Attachment via Presigned URL
4. Get Specific Attachment
5. Create Conversation Attachment
6. Retrieve Allowed File Specifications
7. List Conversation Attachments
8. Delete Conversation Attachment

API call example (Shell)

Create New Attachment (Integrated)

`POST` `/api/v1/attachments-upload/`

Code Examples

Shell/Bash

```
# API call example (Shell)
curl -X POST "https://api.maiagent.ai/api/v1/attachments-upload/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -F "file=@example_file.pdf"

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');
const FormData = require('form-data');

// Create a FormData object
const formData = new FormData();
// Replace with the actual file
formData.append('file',
* actual file object *
, 'example_file.pdf');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    ...formData.getHeaders()
  }
};

axios.post("https://api.maiagent.ai/api/v1/attachments-upload/",
formData, config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/attachments-upload/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}

# Create file and form data
files = {
    'file': ('example_file.pdf', open('example_file.pdf', 'rb'),
'application/pdf')
}

response = requests.post(url, files=files, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>post("https://api.maiagent.ai/api/v1/attachments-upload/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ],
        'multipart' => [
            [
                'name' => 'file',
                'contents' => fopen('example_file.pdf', 'r'),
                'filename' => 'example_file.pdf'
            ]
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response

Status Code: 201

Response Schema Example

```
{
  "id": string (uuid)
  "type"?:  // optional
  {
  }
  "filename": string
  "file": string (uri)
  "expiresAt": string // ISO datetime when this attachment will be auto-deleted.

For conversation-bound attachments: conversation.last_message_created_at + retention_days.
For attachments without a conversation: created_at + retention_days.
Returns None when cleanup is disabled (effective_from not set).
}
```

Example Response Values

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "type": {},
  "filename": "response string",
  "file": "https://example.com/file.jpg",
  "expiresAt": "response string"
}
```

Get Presigned URL for File Upload

POST `/api/v1/upload-presigned-url/`

Request Body

Request Parameters

Field	Type	Required	Description
modelName	string	Yes	Model name, such as attachment、web-chat、faq、organization、chatbot-file、contact、meeting-record
fieldName	string	Yes	Field name, such as file、logo、avatar、powered-by-logo、answer、compact_logo、audio
filename	string	Yes	File name, such as example.pdf
fileSize	integer	Yes	File size (bytes)

Request Schema Example

```
{
  "modelName": string // Model name, such as attachment、web-chat、faq、organization、chatbot-file、contact、meeting-record
  "fieldName": string // Field name, such as file、logo、avatar、powered-by-logo、answer、compact_logo、audio
  "filename": string // File name, such as example.pdf
  "fileSize": integer // File size (bytes)
}
```

Example Request Values

```
{
  "modelName": "attachment",
  "fieldName": "file",
  "filename": "example.pdf",
  "fileSize": 102400
}
```

Code Examples

Shell/Bash

```
# API call example (Shell)
curl -X POST "https://api.maiagent.ai/api/v1/upload-presigned-url/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "modelName": "attachment",
    "fieldName": "file",
    "filename": "example.pdf",
    "fileSize": 102400
  }'

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// Request body (payload)
const data = {
    "modelName": "attachment",
    "fieldName": "file",
    "filename": "example.pdf",
    "fileSize": 102400
  };

axios.post("https://api.maiagent.ai/api/v1/upload-presigned-url/",
data, config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/upload-presigned-url/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# Request body (payload)
data = {
    "modelName": "attachment",
    "fieldName": "file",
    "filename": "example.pdf",
    "fileSize": 102400
}

response = requests.post(url, json=data, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>post("https://api.maiagent.ai/api/v1/upload-presigned-url/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'modelName' => 'attachment',
            'fieldName' => 'file',
            'filename' => 'example.pdf',
            'fileSize' => 102400
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response

Status Code: 200

Response Schema Example

```
{
  "url": string (uri) // Upload target URL (bucket URL for S3/GCS; blob
URL with SAS for Azure)
  "fields": object // POST form fields; Azure includes only key
  "method"?:  // POST if absent; Azure Blob returns PUT

* `POST` - POST
* `PUT` - PUT (optional)
  {
  }
  "headers"?: object // Request headers required for PUT (optional)
}
```

Example Response Values

```
{
  "url": "https://s3.example.com/bucket-name",
  "fields": {
    "key": "media/chat/attachment/filename.pdf",
    "x-amz-algorithm": "AWS4-HMAC-SHA256",
    "x-amz-credential":
"AKIAXXXXXXXXXXXXXXX/YYYYMMDD/region/s3/aws4_request",
    "x-amz-date": "YYYYMMDDTHHMMSSZ",
    "policy": "base64-encoded-policy-document",
    "x-amz-signature": "generated-signature-hash"
  }
}
```

Upload Attachment via Presigned URL

POST `/api/v1/attachments/`

Request Body

Request Parameters

Field	Type	Required	Description
type	object	No	
filename	string	Yes	
file	string (uri)	Yes	

Request Schema Example

```
{
  "type"?:  // Optional
  {
  }
  "filename": string
  "file": string (uri)
}
```

Request Example

```
{
  "type": {},
  "filename": "document.pdf",
  "file": "https://example.com/file.jpg"
}
```

Code Examples

Shell/Bash

```
# Example API call (Shell)
curl -X POST "https://api.maiagent.ai/api/v1/attachments/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "type": {},
    "filename": "document.pdf",
    "file": "https://example.com/file.jpg"
  }'

# Make sure to replace YOUR_API_KEY and verify the request data
before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// Request payload
const data = {
    "type": {},
    "filename": "document.pdf",
    "file": "https://example.com/file.jpg"
  };

axios.post("https://api.maiagent.ai/api/v1/attachments/", data,
config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('An error occurred during the request:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/attachments/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# Request payload
data = {
    "type": {},
    "filename": "document.pdf",
    "file": "https://example.com/file.jpg"
}

response = requests.post(url, json=data, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("An error occurred during the request:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>post("https://api.maiagent.ai/api/v1/attachments/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'type' => new \stdClass(),
            'filename' => 'document.pdf',
            'file' => 'https://example.com/file.jpg'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'An error occurred during the request: ' . $e-
>getMessage();
}
?>
```

Response

Status Code: 201

Response Schema Example

```
{
  "id": string (uuid)
  "type"?:  // Optional
  {
  }
  "filename": string
  "file": string (uri)
  "expiresAt": string // ISO datetime when this attachment will be auto-deleted.

For conversation-bound attachments: conversation.last_message_created_at + retention_days.
For attachments without a conversation: created_at + retention_days.
Returns None when cleanup is disabled (effective_from not set).
  "downloadStatus": string
}
```

Response Example

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "type": {},
  "filename": "response string",
  "file": "https://example.com/file.jpg",
  "expiresAt": "response string",
  "downloadStatus": "response string"
}
```

Get Specific Attachment

GET `/api/v1/attachments/{id}`

Parameters

Parameter	Required	Type	Description
`id`	V	string	A UUID string identifying this attachment.

Code Examples

Shell/Bash

```
# Example API call (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/attachments/550e8400-
e29b-41d4-a716-446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# Make sure to replace YOUR_API_KEY and verify the request data
before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/attachments/550e8400-e29b-
41d4-a716-446655440000/", config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('An error occurred during the request:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/attachments/550e8400-e29b-
41d4-a716-446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("An error occurred during the request:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->get("https://api.maiagent.ai/api/v1/attachments/550e8400-e29b-41d4-a716-446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'An error occurred during the request: ' . $e->getMessage();
}
?>
```

Response

Status Code: 200

Response Schema Example

```
{
  "id": string (uuid)
```

```
  "type"?:  // Optional
  {
  }
  "filename": string
  "file": string (uri)
  "expiresAt": string // ISO datetime when this attachment will be auto-
deleted.

For conversation-bound attachments: conversation.last_message_created_at
+ retention_days.
For attachments without a conversation: created_at + retention_days.
Returns None when cleanup is disabled (effective_from not set).
  "downloadStatus": string
}
```

Response Example


```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "type": {},
  "filename": "response string",
  "file": "https://example.com/file.jpg",
  "expiresAt": "response string",
  "downloadStatus": "response string"
}
```


Create Conversation Attachment

POST `/api/v1/conversations/{conversationPk}/attachments/`

Parameters

Parameter	Required	Type	Description

conversationPk	V	string	

Request Body

Request Parameters

Field	Type	Required	Description
type	object	No	
filename	string	Yes	
file	string (uri)	Yes	
conversation	string (uuid)	No	

Example Request Schema

```
{
  "type"?:  // Optional
  {
  }
  "filename": string
  "file": string (uri)
  "conversation"?: string (uuid) // Optional
}
```

Example Request Values

```
{
  "type": {},
  "filename": "document.pdf",
  "file": "https://example.com/file.jpg",
  "conversation": "550e8400-e29b-41d4-a716-446655440000"
}
```

Code Examples

Shell/Bash

```
# Example API call (Shell)
curl -X POST "https://api.maiagent.ai/api/v1/conversations/550e8400-
e29b-41d4-a716-446655440000/attachments/"

  -H "Authorization: Api-Key YOUR_API_KEY"

  -H "Content-Type: application/json"

  -d '{
    "type": {},
    "filename": "document.pdf",
    "file": "https://example.com/file.jpg",
    "conversation": "550e8400-e29b-41d4-a716-446655440000"
  }'

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY',
    'Content-Type': 'application/json'
  }
};

// Request Body (payload)
const data = {
    "type": {},
    "filename": "document.pdf",
    "file": "https://example.com/file.jpg",
    "conversation": "550e8400-e29b-41d4-a716-446655440000"
  };

axios.post("https://api.maiagent.ai/api/v1/conversations/550e8400-
e29b-41d4-a716-446655440000/attachments/", data, config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/conversations/550e8400-e29b-
41d4-a716-446655440000/attachments/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY",
    "Content-Type": "application/json"
}

# Request Body (payload)
data = {
    "type": {},
    "filename": "document.pdf",
    "file": "https://example.com/file.jpg",
    "conversation": "550e8400-e29b-41d4-a716-446655440000"
}

response = requests.post(url, json=data, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>post("https://api.maiagent.ai/api/v1/conversations/550e8400-e29b-
41d4-a716-446655440000/attachments/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY',
            'Content-Type' => 'application/json'
        ],
        'json' => [
            'type' => new \stdClass(),
            'filename' => 'document.pdf',
            'file' => 'https://example.com/file.jpg',
            'conversation' => '550e8400-e29b-41d4-a716-446655440000'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response Body

Status code: 201

Example Response Schema

```
{
  "id": string (uuid)
  "type"?:  // Optional
  {
  }
  "filename": string
  "file": string (uri)
  "expiresAt": string // ISO datetime when this attachment will be auto-
deleted.

For conversation-bound attachments: conversation.last_message_created_at
+ retention_days.
For attachments without a conversation: created_at + retention_days.
Returns None when cleanup is disabled (effective_from not set).
  "conversation"?: string (uuid) // Optional
  "parser": object
  "parserAutoDetected": boolean
}
```

Example Response Values

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "type": {},
  "filename": "Response string",
  "file": "https://example.com/file.jpg",
  "expiresAt": "Response string",
  "conversation": "550e8400-e29b-41d4-a716-446655440000",
  "parser": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "name": "Example response name",
    "description": "Example response description"
  },
  "parserAutoDetected": false
}
```

Status code: `400` - Error codes (X-Error-Code): `conversation_attachment_limit_reached`, `conversation_attachment_storage_limit_reached`, `invalid`.

Status code: `404` - Error codes (X-Error-Code): `not_found`.

Status code: `429` - Error codes (X-Error-Code): `throttled`.

Retrieve Allowed File Specifications

`GET` `/api/v1/allowed-file-specs/`

Code Examples

Shell/Bash

```
# Example API call (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/allowed-file-specs/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# Replace YOUR_API_KEY and verify the request data before running.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/allowed-file-specs/",
config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/allowed-file-specs/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request error:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>get("https://api.maiagent.ai/api/v1/allowed-file-specs/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error: ' . $e->getMessage();
}
?>
```

Response Body

Status code: 200

Example Response Schema

```
{
  "webChat": object
  "organization": object
  "attachment": object
```

```
  "chatbotFile": object
  "knowledgeBaseFile": object
  "batchQa": object
  "meetingRecord": object
  "documentTranslation": object
}
```

Example Response Values

```
{
  "web_chat": {
    "logo": [
      {
        "content_type": {
          ".jpg": "image/jpeg",
          ".jpeg": "image/jpeg",
          ".png": "image/png",
          ".gif": "image/gif"
        },
        "max_size": 5242880
      }
    ],
    "avatar": [
      {
        "content_type": {
          ".jpg": "image/jpeg",
          ".jpeg": "image/jpeg",
          ".png": "image/png",
          ".gif": "image/gif"
        },
        "max_size": 2097152
      }
    ],
    "cover": [
      {
        "content_type": {
          ".jpg": "image/jpeg",
          ".jpeg": "image/jpeg",
          ".png": "image/png",
          ".gif": "image/gif"
        },
        "max_size": 10485760
      }
    ],
```

```
    "powered-by-logo": [
      {
        "content_type": {
          ".jpg": "image/jpeg",
          ".jpeg": "image/jpeg",
          ".png": "image/png",
          ".gif": "image/gif"
        },
        "max_size": 5242880
      }
    ]
  },
  "organization": {
    "compact_logo": [
      {
        "content_type": {
          ".jpg": "image/jpeg",
          ".jpeg": "image/jpeg",
          ".png": "image/png",
          ".gif": "image/gif"
        },
        "max_size": 2097152
      }
    ],
    "full_logo": [
      {
        "content_type": {
          ".jpg": "image/jpeg",
          ".jpeg": "image/jpeg",
          ".png": "image/png",
          ".gif": "image/gif"
        },
        "max_size": 2097152
      }
    ]
  },
  "attachment": {
    "file": [
      {
        "content_type": {
          ".pdf": "application/pdf",
          ".doc": "application/msword",
          ".docx": "application/vnd.openxmlformats-
officedocument.wordprocessingml.document",
          ".txt": "text/plain"
```

```
        },
        "max_size": 20971520
      },
      {
        "content_type": {
          ".jpg": "image/jpeg",
          ".jpeg": "image/jpeg",
          ".png": "image/png",
          ".gif": "image/gif"
        },
        "max_size": 5242880
      }
    ]
  },
  "chatbot_file": {
    "file": [
      {
        "content_type": {
          ".pdf": "application/pdf",
          ".doc": "application/msword",
          ".docx": "application/vnd.openxmlformats-
officedocument.wordprocessingml.document",
          ".xlsx": "application/vnd.openxmlformats-
officedocument.spreadsheetml.sheet",
          ".ppt": "application/vnd.ms-powerpoint",
          ".pptx": "application/vnd.openxmlformats-
officedocument.presentationml.presentation",
          ".txt": "text/plain"
        },
        "max_size": 104857600
      }
    ]
  },
  "batch_qa": {
    "file": [
      {
        "content_type": null,
        "max_size": 104857600
      }
    ]
  },
  "faq": {
    "answer": [
      {
        "content_type": {
```

```
            ".jpg": "image/jpeg",
            ".jpeg": "image/jpeg",
            ".png": "image/png",
            ".gif": "image/gif",
            ".webp": "image/webp",
            ".tiff": "image/tiff",
            ".mp4": "video/mp4"
          },
          "max_size": 104857600
        }
      ]
    }
}
```


List Conversation Attachments

`GET` `/api/v1/file-library/conversation-attachments/`

Required permissions: The organization has the file library enabled, and the caller's role has any file library permission. For the visible scope and how expiresAt is calculated, see the technical manual Conversation Attachment Management API。

Parameters

Parameter Name	Required	Type	Description
`page`	X	integer	A page number within the paginated result set.
`pageSize`	X	integer	Number of results to return per page.

Code Examples

Shell/Bash

```
# API call example (Shell)
curl -X GET "https://api.maiagent.ai/api/v1/file-
library/conversation-attachments/?page=1&pageSize=1"

  -H "Authorization: Api-Key YOUR_API_KEY"

# Please make sure to replace YOUR_API_KEY and verify the request
data before executing.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

axios.get("https://api.maiagent.ai/api/v1/file-library/conversation-attachments/?page=1&pageSize=1", config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error occurred:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/file-library/conversation-
attachments/?page=1&pageSize=1"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.get(url, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request error occurred:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client->get("https://api.maiagent.ai/api/v1/file-
library/conversation-attachments/?page=1&pageSize=1", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error occurred: ' . $e->getMessage();
}
?>
```

Response

Status Code: 200

Response Schema Example

```
{
  "count": integer
  "next"?: string (uri) // Optional
  "previous"?: string (uri) // Optional
```

```
  "results": [
    {
      "id": string (uuid)
      "filename": string
      "fileSize": integer
      "type":
      {
      }
      "conversationId": string (uuid)
      "expiresAt": string
      "createdAt": string (timestamp)
    }
  ]
}
```

Response Example Values


```
{
  "count": 123,
  "next": "http://api.example.org/accounts/?page=4",
  "previous": "http://api.example.org/accounts/?page=2",
  "results": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "filename": "Response string",
      "fileSize": 456,
      "type": {},
      "conversationId": "550e8400-e29b-41d4-a716-446655440000",
      "expiresAt": "Response string",
      "createdAt": "Response string"
    }
  ]
}
```


Delete Conversation Attachment

DELETE `/api/v1/file-library/conversation-attachments/{id}`

Required permissions: Same as "List Conversation Attachments". You can only delete attachments visible to the caller; other attachments return 404. Deleting also removes the stored file if no other attachment or file shares it.

Parameters

Parameter Name	Required	Type	Description
id	V	string	

Code Examples

Shell/Bash

```
# API call example (Shell)
curl -X DELETE "https://api.maiagent.ai/api/v1/file-
library/conversation-attachments/550e8400-e29b-41d4-a716-
446655440000/"

  -H "Authorization: Api-Key YOUR_API_KEY"

# Please make sure to replace YOUR_API_KEY and verify the request
data before executing.
```

JavaScript

```
const axios = require('axios');

// Set request headers
const config = {
  headers: {
    'Authorization': 'Api-Key YOUR_API_KEY'
  }
};

// Request body (payload)
const data = null;

axios.delete("https://api.maiagent.ai/api/v1/file-
library/conversation-attachments/550e8400-e29b-41d4-a716-
446655440000/", data, config)
  .then(response => {
    console.log('Response received successfully:');
    console.log(response.data);
  })
  .catch(error => {
    console.error('Request error occurred:');
    console.error(error.response?.data || error.message);
  });
```

Python

```
import requests

url = "https://api.maiagent.ai/api/v1/file-library/conversation-
attachments/550e8400-e29b-41d4-a716-446655440000/"
headers = {
    "Authorization": "Api-Key YOUR_API_KEY"
}


response = requests.delete(url, headers=headers)
try:
    print("Response received successfully:")
    print(response.json())
except Exception as e:
    print("Request error occurred:", e)
```

PHP

```php
<?php
require 'vendor/autoload.php';

$client = new GuzzleHttp\Client();

try {
    $response = $client-
>delete("https://api.maiagent.ai/api/v1/file-library/conversation-
attachments/550e8400-e29b-41d4-a716-446655440000/", [
        'headers' => [
            'Authorization' => 'Api-Key YOUR_API_KEY'
        ]
    ]);

    $data = json_decode($response->getBody(), true);
    echo "Response received successfully:\n";
    print_r($data);
} catch (Exception $e) {
    echo 'Request error occurred: ' . $e->getMessage();
}
?>
```

Response

Status Code	Description
204	No response body