2016.0 RANGE ROVER (LG), 100-00

GENERAL INFORMATION

DESCRIPTION AND OPERATION

TERRAIN RESPONSE SWITCHPACK (TR)

CAUTION:

Diagnosis by substitution from a donor vehicle is **NOT** acceptable. Substitution of control modules does not guarantee confirmation of a fault, and may also cause additional faults in the vehicle being tested and/or the donor vehicle.

NOTES:

- If a control module or a component is suspect and the vehicle remains under manufacturer warranty, refer to the Warranty Policy and Procedures manual, or determine if any prior approval programme is in operation, prior to the installation of a new module/component.
- Generic scan tools may not read the codes listed, or may read only 5-digit codes. Match the 5 digits from the scan tool to the first 5 digits of the 7-digit code listed to identify the fault (the last 2 digits give extra information read by the manufacturer-approved diagnostic system).
- When performing voltage or resistance tests, always use a digital multimeter accurate to three decimal places, and with an up-to-date calibration certificate. When testing resistance always take the resistance of the digital multimeter leads into account.
- Check and rectify basic faults before beginning diagnostic routines involving pinpoint tests.
- Inspect connectors for signs of water ingress, and pins for damage and/or corrosion.
- If DTCs are recorded and, after performing the pinpoint tests, a fault is not present, an intermittent concern may be the cause. Always check for loose connections and corroded terminals.
- Check DDW for open campaigns. Refer to the corresponding bulletins and SSMs which may be valid for the specific customer complaint and carry out the recommendations as required.

The table below lists all Diagnostic Trouble Codes (DTCs) that could be logged in the Terrain Response Switchpack (TR). For additional diagnosis and testing information, refer to the relevant Diagnosis and Testing section in the workshop manual.

For additional information, refer to: Ride and Handling Optimization (204-06

Ride and Handling Optimization, Diagnosis and Testing).

DTC	DESCRIPTION	POSSIBLE CAUSES	ACTION
C1A01-96	LED Circuit - Component internal failure	▪ Terrain response switchpack LED internal circuit failure	**NOTE:** This DTC is set 1000ms after ignition on/power up, after 1000ms of low voltage measured, after 1000ms of engine cranking, or after 1000ms of CAN bus restart. ▪ Using the manufacturer approved diagnostic system, clear the DTCs and retest. If the fault persists, install a new terrain response switchpack
U0001-82	High Speed CAN Communication Bus - Alive/sequence counter incorrect / not updated	▪ Invalid data received from another control module via the high speed CAN bus (chassis)	▪ Using the manufacturer approved diagnostic system, check the snapshot data to determine the invalid data source control module. Check the relevant control module for related DTCs and refer to the relevant DTC index
U0001-87	High Speed CAN Communication Bus - Missing message	▪ Missing message from another control module via the high speed CAN bus (chassis)	▪ Using the manufacturer approved diagnostic system, check the snapshot data to determine the missing message source control module. Check the relevant control module for related DTCs and refer to the relevant DTC index
U0001-88	High Speed CAN Communication Bus - Bus off	▪ High speed CAN bus (chassis) circuit short circuit to ground, short circuit to power, open circuit, high	**NOTE:** This DTC is set 1000ms after ignition on/power up, after 1000ms of low voltage measured, after 1000ms of engine cranking, or after 1000ms of CAN bus restart.

		resistance	▪ Using the manufacturer approved diagnostic system, perform a CAN network integrity test. Refer to the electrical circuit diagrams and check the high speed CAN bus (chassis) circuit for short circuit to ground, short circuit to power, open circuit, high resistance. Clear DTCs and retest

U0300-00	Internal Control Module Software Incompatibility - No sub type information	▪ Mismatch between the configuration of the central junction box and the terrain response switchpack	**NOTE:**
			This DTC is set 1000ms after ignition on/power up, after 1000ms of low voltage measured, after 1000ms of engine cranking, or after 1000ms of CAN bus restart.
			▪ Using the manufacturer approved diagnostic system, check for related DTCs in other control modules
			  ▪ Related DTCs in other control modules: Using the manufacturer approved diagnostic system, re-configure the central junction box with the latest level software, clear DTCs and retest
			  ▪ No related DTCs in other control modules: Using the manufacturer approved diagnostic system, re-configure the terrain response switchpack with the latest level software, clear the DTCs and retest. If the fault persists, install a new terrain response switchpack as necessary

U2014-56	Control Module Hardware - Invalid/incomplete configuration	▪ Car configuration file mismatch with vehicle specification ▪ Incorrect terrain response switchpack installed	**NOTE:** This DTC is set 1000ms after ignition on/power up, after 1000ms of low voltage measured, after 1000ms of engine cranking, or after 1000ms of CAN bus restart.

			▪ Using the manufacturer approved diagnostic system, check and up-date the car configuration file as necessary ▪ Install the correct terrain response switchpack as necessary