

2016.0 RANGE ROVER (LG), 502-00

UNI-BODY, SUBFRAME AND MOUNTING SYSTEM

SPECIFICATIONS

DESCRIPTION	NM	LB-FT
Front subframe to body bolts		
Front bolts *		
Stage 1	100	74
Stage 2	Then a further 300 degrees	Then a further 300 degrees
Centre bolts *		
Stage 1	100	74
Stage 2	Then a further 240 degrees	Then a further 240 degrees
Rear bolts *		
Stage 1	70	52
Stage 2	Then a further 120 degrees	Then a further 120 degrees
Front dynamic stabilizer bar support bracket to subframe bolts *		
M12 bolts		
Stage 1	90	66
Stage 2	Then a further 180 degrees	Then a further 180 degrees
M14 bolts		

Stage 1	140	96
stage 2	Then a further 120 degrees	Then a further 120 degrees
Rear subframe to body bolts		
Front bolts		
	170	125
Rear bolts *		
Stage 1	100	74
Stage 2	Then a further 300 degrees	Then a further 300 degrees
Rear subframe support bracket to body bolts		
	60	44

*** New nuts/bolts must be installed**

RECOMMENDED LUBRICANT FOR SUBFRAME BUSHES

CIRCO Light rubber process oil
