

2016.0 RANGE ROVER (LG), 206-00

BRAKE SYSTEM – GENERAL INFORMATION

SPECIFICATIONS

Brake Hydraulic Fluid - All vehicles except 5.0L AJ133 550PS

Item	Specification
* Recommended hydraulic fluid	Land Rover approved fluid
Fluid quantity	890 cm ³

CAUTION:

* If the above fluid is not available, use a low viscosity DOT 4 brake fluid meeting ISO 4925 Class 6 and Land Rover LRES22BF03 requirements.

Brake Hydraulic Fluid - Vehicles with 5.0L AJ133 550PS

Item	Specification
* Recommended hydraulic fluid	Land Rover approved fluid
Fluid quantity	890 cm ³

CAUTION:

If the above fluid is not available, use an equivalent high performance ISO 4925 DOT 4, class 4 brake fluid with a ERBP (dry boiling point) of at least 300 deg C and a WERBP (wet boiling point) of 250 deg C.

General Specification: Vehicles with High Performance Brakes

Item	Specification
Footbrake type:	Hydraulic, servo assisted, self-adjusting with front/rear split hydraulic system, opposed six piston calipers to the front and single piston sliding calipers to the rear
Disc type and diameter	
Front - ventilated	380 mm (14.9 in)
Rear - ventilated	365 mm (14.4 in)
Front disc thickness:	
New	34.0 mm (1.33 in)
Service limit	marked on the disc
Rear disc thickness:	
New	25.0 mm (0.98 in)
Service limit	marked on the disc
Maximum disc run out:	
Front	0.050 mm with wheel fitted
Rear	0.070 mm with wheel fitted
Minimum pad material thickness - Front and rear:	3 mm (0.11 in)
Pad material	Asbestos free
Front Caliper	

Type	Six piston
Piston diameter - 1 and 2	36 mm (1.41 in)
Piston diameter - 3 and 4	38 mm (1.49 in)
Piston diameter - 5 and 6	40 mm (1.57 in)
Rear caliper	
Piston diameter	43 mm (1.69 in)

General Specification: Vehicles with Standard Brakes

Item	Specification
Footbrake type:	Hydraulic, servo assisted, self-adjusting with front/rear split hydraulic system, twin piston sliding calipers to the front and single piston sliding calipers to the rear
Disc type and diameter	
Front - ventilated	360 mm (14.2 in)
Rear - ventilated	350 mm (13.8 in)
Front disc thickness:	
New	30.0 mm (1.18 in)
Service limit	marked on the disc
Rear disc thickness:	
New	25 mm (0.98 in)
Service limit	marked on the disc
Maximum disc run out:	
Front	0.050 mm (0.002 in) with wheel fitted
Rear	0.070 mm (0.003 in) with wheel fitted
Minimum pad material thickness - Front and rear:	3 mm (0.11 in)

Pad material	Asbestos free
Front Caliper	
Type	Twin piston
Piston diameter - 1 and 2	48 mm (1.90 in)
Rear caliper	
Piston diameter	43 mm (1.69 in)

Torque Specifications

ITEM	NM	LB-FT	LB-IN
Primary circuit brake pipe bleed screw	18	13	-
Secondary circuit brake pipe bleed screw	18	13	-
Rear brake caliper bleed screw	11	8	-
Front brake caliper bleed screw	8	-	71