

2016.0 RANGE ROVER (LG), 206-03

FRONT DISC BRAKE

SPECIFICATIONS

Item	Specification
Disc type	Ventilated
Disc diameter:	
Vehicles with Standard brakes	360 mm (14.2 in)
Vehicles with High performance brakes	380 mm (14.9 in)
Disc thickness:	
Vehicles with Standard brakes:	
New	30.0 mm (1.18 in)
Service limit	marked on the disc
Maximum disc run out	0.050 mm (0.002 in) with wheel fitted
Vehicles with High performance brakes:	
New	34.0 mm (1.33 in)
Service limit	marked on the disc
Maximum disc run out	0.050 mm (0.002 in) with wheel fitted
Vehicles with Standard brakes:	
Caliper type	Twin piston
Piston diameter	48 mm (1.90 in)
Pad minimum thickness	3.0 mm (1.12 in)
Vehicles with High performance brakes:	
Caliper type	Six piston

Piston diameter - 1 and 2	36 mm (1.41 in)
Piston diameter - 3 and 4	38 mm (1.49 in)
Piston diameter - 5 and 6	40 mm (1.57 in)
Pad minimum thickness	3.0 mm (0.12 in)
Brake pad wear sensor lead:	
Location	Front left hand brake pad
Activates at	75% of pad life utilised

Torque Specifications Vehicles with Standard brakes

DESCRIPTION	NM	LB-FT
Brake caliper bleed screw	8	6
Brake disc retaining bolt	16	12
Brake caliper anchor plate to hub bolts	133 + 60°	98 + 60°
Brake caliper housing to anchor plate bolts	35	26
Brake hose union	32	24

Torque Specifications Vehicles with High performance brakes

DESCRIPTION	NM	LB-FT
Brake caliper bleed screw	8	6
Brake disc retaining bolt	35	26
Brake caliper retaining bolts:	133 + 60°	98 + 60°
Brake hose union	32	24
Brake pad centre bolt	30	22