

2016.0 RANGE ROVER (LG), 205-01

# DRIVESHAFT

## SPECIFICATIONS

---

### Front Drive (Propeller) Shaft

| Item                     | Specification                                                                                                                                                                                                                                  |
|--------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Type                     | The front driveshaft is a one piece unit, connected to the transfer box and front differential unit via Constant velocity (CV) joints.                                                                                                         |
| Constant velocity joints | The front shaft assembly comprises of a DTF CV joint that is pushed into place on the front differential pinion shaft and secured by a retaining lock nut. The front shaft is attached to the transfer box by a CV joint with a 6 bolt fixing. |

### Rear Drive (Propeller) Shaft Except GTDi and Hybrid Electric Vehicles (HEV)

| Item                     | Specification                                                                                                                                                                                                                                                                     |
|--------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Type                     | The rear driveshaft comprises of front and rear shaft assemblies and a centrally mounted shaft bearing.                                                                                                                                                                           |
| Constant velocity joints | The rear shaft comprises of an internal spline bore, which is attached to the input shaft of the front driveshaft assembly via the shaft bearing assembly and a DTF CV joint that is pushed into place on the rear differential pinion shaft and secured by a retaining lock nut. |

### Rear Drive (Propeller) Shaft GTDi and Hybrid Electric Vehicles (HEV)

| Item     | Specification                                                                                           |
|----------|---------------------------------------------------------------------------------------------------------|
| Type     | The rear driveshaft comprises of front and rear shaft assemblies and a centrally mounted shaft bearing. |
| Constant | The rear shaft comprises of an internal spline bore, which is attached to the                           |

|                 |                                                                                                                                                                 |
|-----------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------|
| velocity joints | input shaft of the front driveshaft assembly via the shaft bearing assembly and a CV joint that is fixed to the rear differential pinion using a 6 bolt fixing. |
|-----------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------|

## Torque Specifications

| DESCRIPTION                                                                                                    | NM          | LB-FT       |
|----------------------------------------------------------------------------------------------------------------|-------------|-------------|
| <b>* Front driveshaft to front axle drive flange Torx bolts:</b>                                               |             |             |
| Stage 1                                                                                                        | 45          | 33          |
| Stage 2                                                                                                        | Further 90° | Further 90° |
| * Rear driveshaft to rear axle drive flange Torx bolts - GTDi and Hybrid Electric Vehicles (HEV) only          | 73          | 54          |
| * Rear driveshaft to transfer case drive flange Torx bolts                                                     | 150         | 111         |
| Rear driveshaft center bearing bolts                                                                           | 48          | 35          |
| Fuel tank heat shield bolts                                                                                    | 5           | 4           |
| + Front driveshaft to front differential DTF CV joint lock nut                                                 | 150         | 111         |
| ++ Rear driveshaft to rear differential DTF CV joint lock nut - except GTDi and Hybrid Electric Vehicles (HEV) | 150         | 111         |

**\* New 'Patched' Torx bolts must be installed**

**+ Refer to the front driveshaft tightening procedure in the workshop manual**

**++ Refer to the rear driveshaft tightening procedure in the workshop manual**