

2016.0 RANGE ROVER (LG), 205-05

REAR DRIVE HALFSHAFTS

SPECIFICATIONS

Recommended Lubricant

Item	Specification
Outboard joint	Use grease supplied with replacement boot kit
Inboard joint	Use grease supplied with replacement boot kit

General Specification

Item	Specification
Type	Fixed outer CV, plunging inboard joint, solid interconnecting shafts, with inner and outer constant velocity joints

Torque Specifications

ITEM	NM	LB-FT	LB-IN
* Lower arm to wheel knuckle bolt	70 + 240°	52 + 240°	-
Upper arm to wheel knuckle nut and bolt	50 + 60°	37 + 60°	-
** Toe link to lower arm nut and bolt	50 + 180°	37 + 180°	-
** Toe link to wheel knuckle nut and bolt	70 + 240°	52 + 240°	-
** Shock absorber to wheel knuckle nut and bolt	100 + 240°	74 + 240°	-
Rear wheel speed sensor bolt	9	-	80
Brake disc shield to wheel knuckle bolt	9	-	80

+ Halfshaft retaining nut	-	-	-
---------------------------	---	---	---

* New bolt must be installed.

** New nut and bolt must be installed.

+ For additional information, refer to: [Rear Halfshaft](#) (205-05 Rear Drive Halfshafts, Removal and Installation).