

2016.0 RANGE ROVER (LG), 204-06

RIDE AND HANDLING OPTIMIZATION

SPECIFICATIONS

Lubricants, Fluids, Sealers and Adhesives

SPECIFICATIONS	
Dynamic Response Fluid	Texaco Cold Climate Fluid 33270

Capacities

LITERS	
Capacity	2.7 Litres (4.75 pints) (2.85 US quarts)

General Specification

System pressure	Variable between 3-180 bar dependant on lateral acceleration
-----------------	--

Torque Specifications

ITEM	NM	LB-FT	LB-IN
Dynamic Response actuator bleed screw	15	11	-
M10	48	35	-
M8	25	18	-

Dynamic Response Hydraulic Pump Pressure High Hose	10	7	-
* Front actuator pipes to valve block nuts	22	16	-
* Rear actuator pipes to valve block nuts	22	16	-
Valve block mounting bolts	9	-	
Valve block mounting stud	16	12	-
Dynamic Response fluid pipe securing bracket nuts/bolts	10	7	-
Fluid lines to actuator banjo bolts	22	16	-
Fluid lines to cooler bolts	9	7	-
* Stabilizer bar link nut	185	136	-
Front stabilizer bar to body clamp bolts	110	81	-
Rear stabilizer bar to body clamp bolt	110	81	-
Dynamic Response module	10	75	-
Upper Accelerometer	7	-	-
Lower Accelerometer	7	-	-
Front dynamic stabilizer bar support bracket to subframe bolts *			
M12 bolts			
Stage 1	90	66	
Stage 2	Then a further 180 degrees	Then a further 180 degrees	Then a further 180 degrees
M12 bolts			
Stage 1	140	103	
Stage 2	Then a further 120 degrees	Then a further 120 degrees	Then a further 120 degrees

