

2016.0 RANGE ROVER (LG), 204-01

FRONT SUSPENSION

SPECIFICATIONS

Torque Specifications

DESCRIPTION	NM	LB-FT
Stabilizer bar clamp bolts	110	81
Stabilizer bar link nuts +	185	136
Dynamic response actuator clamp nuts	110	81
Dynamic response actuator link nuts	185	136
Upper control arm to body nuts		
Stage 1	24	18
Stage 2	Then a further 60 degrees	Then a further 60 degrees
Upper ball joint knuckle nut	60	44
Air spring mounting nuts	40	29
Air spring to yoke bolt	95	70
Rear lower control arm to yoke bolt ++		
Stage 1	100	74
Stage 2	Then a further 240 degrees	Then a further 240 degrees
Rear lower control arm to subframe bolt ++		
Stage 1	100	74

Stage 2	Then a further 360 degrees	Then a further 360 degrees
Front lower control arm to subframe bolt ++		
Stage 1	100	59
Stage 2	Then a further 360 degrees	Then a further 300 degrees
Rear lower control arm ball joint nut +	290	214
Front lower control arm ball joint nut +	290	214
Subframe to body front bolts +		
Stage 1	100	74
Stage 2	Then a further 300 degrees	Then a further 300 degrees
Subframe to body centre bolts +		
Stage 1	100	74
Stage 2	Then a further 240 degrees	Then a further 240 degrees
Subframe to body rear bolts +		
Stage 1	70	52
Stage 2	Then a further 120 degrees	Then a further 120 degrees

+ New nut/bolts must be installed

++ New nut and bolt must be installed