

2016.0 RANGE ROVER (LG), 204-00

SUSPENSION SYSTEM – GENERAL INFORMATION

SPECIFICATIONS

Air Spring Suspension

ITEM	SPECIFICATION
Type - Front	Independent double wishbone suspension with air springs, mono tube dampers, height sensors and stabilizer bar. Driver selectable ride heights – Standard, off road and access.
Type - Rear	Independent suspension with air springs, mono tube dampers, height sensors and either a conventional or dynamic response stabilizer bar depending on vehicle specification. Driver selectable ride heights – Standard, off road and access
* Nominal heights from hub centre to underside of wheel arch (not liner):	
Front	471 mm (18.54 in)
Rear	468 mm (18.43 in)

*** Measurement taken with vehicle at unladen weight**

Wheel Alignment Specification - Front

NOTE:

All figures are with vehicle at 'Showroom' ride height - full fluids, full tank of fuel, no occupants/luggage, tires inflated to normal pressures

ITEM		LEFT-HAND		RIGHT-HAND		TOTAL/BALANCE	
Camber		Nominal	Tolerance	Nominal	Tolerance	Nominal	Tolerance
	Decimal degrees	-0.68°	± 0.75°	-0.68°	± 0.75°	0°	± 0.75°
	Degrees/minutes	-41'	± 45'	-41'	± 45'	0'	± 45'
		Minimum	Maximum	Minimum	Maximum	Minimum	Maximum
	Decimal degrees	-1.43°	0.07°	-1.43°	0.07	-0.75°	0.75°
	Degrees/minutes	-1°26'	4'	-1°26'	4'	-45'	45'
Castor		Nominal	Tolerance	Nominal	Tolerance	Nominal	Tolerance
	Decimal degrees	4.12°	± 0.75°	4.12°	± 0.75°	0°	± 0.75°
	Degrees/minutes	4.7'	± 45'	4°7'	± 45'	0'	± 45'
		Minimum	Maximum	Minimum	Maximum	Minimum	Maximum
	Decimal degrees	3.75°	4.87°	3.75°	4.87°	-0.75°	0.75°
	Degrees/minutes	3°22'	4°52'	3°22'	4°52'	-45'	45'
Toe		Nominal	Tolerance	Nominal	Tolerance	Nominal	Tolerance
	Decimal degrees	0.07°	± 0.10°	0.07°	± 0.10°	0.14°	±0.20°
	Degrees/minutes	4'	± 6'	4'	± 6'	8'	±12'
		Minimum	Maximum	Minimum	Maximum	Minimum	Maximum
	Decimal degrees	-0.03°	0.17°	-0.03°	0.17	-0.06°	0.34°
	Degrees/minutes	-2'	10'	-2'	10'	-4'	20'

Wheel Alignment Specification - Rear

NOTE:

All figures are with vehicle at 'Showroom' ride height - full fluids, full tank of fuel, no occupants/luggage, tires inflated to normal pressures

ITEM		LEFT-HAND		RIGHT-HAND		TOTAL/BALANCE	
Camber		Nominal	Tolerance	Nominal	Tolerance		
	Decimal degrees	-1.42°	± 0.75°	-1.42°	± 0.75°		
	Degrees/minutes	-1°-25'	± 45'	-1°-25'	± 45'		
		Minimum	Maximum	Minimum	Maximum		
	Decimal degrees	-2.17°	-0.67°	-2.17°	-0.67°		
	Degrees/minutes	-2°10'	-40'	-2°10'	-40'		
Toe		Nominal	Tolerance	Nominal	Tolerance	Nominal	Tolerance
	Decimal degrees	0.15°	±0.14°	0.15°	±0.14°	0.30°	±0.20°
	Degrees/minutes	9'	±8'	9'	±8'	18'	±12'
		Minimum	Maximum	Minimum	Maximum	Minimum	Maximum
	Decimal degrees	0.01°	0.29°	0.01°	0.29°	0.10°	0.50°
	Degrees/minutes	1'	17'	1'	17'	6'	30'