

2016.0 RANGE ROVER (LG), 204-02

REAR SUSPENSION

SPECIFICATIONS

Torque Specifications

DESCRIPTION	NM	LB-FT
Shock absorber to knuckle bolt ++		
Stage 1	100	66
Stage 2	Then a further 240 degrees	Then a further 240 degrees
Shock absorber top nut	27	20
Shock absorber mounting nuts +	48	35
Upper control arm to subframe bolt		
Stage 1	50	37
Stage 2	Then a further 60 degrees	Then a further 60 degrees
Upper control arm to knuckle bolt		
Stage 1	50	37
Stage 2	Then a further 60 degrees	Then a further 60 degrees
Lower control arm to subframe front bolt ++		
Stage 1	100	74
Stage 2	Then a further 240 degrees	Then a further 240 degrees
Lower control arm to subframe rear		

bolt ++		
Stage 1	100	74
Stage 2	Then a further 240 degrees	Then a further 240 degrees
Lower control arm to knuckle bolt ++		
Stage 1	70	52
stage 2	Then a further 240 degrees	Then a further 240 degrees
Lower control arm to integral link bolt ++		
Stage 1	50	37
Stage 2	Then a further 180 degrees	Then a further 180 degrees
Integral link to knuckle bolt ++		
Stage 1	50	37
Stage 2	Then a further 180 degrees	Then a further 180 degrees
Toe link to subframe bolt		
Stage 1	40	30
Stage 2	Then a further 60 degrees	Then a further 60 degrees
Toe link to knuckle bolt ++		
Stage 1	70	52
Stage 2	Then a further 240 degrees	Then a further 240 degrees
Stabilizer bar clamp nuts / bolts	110	81
Stabilizer link nuts	185	136
Dynamic response actuator clamp nuts / bolts	110	81
Dynamic response actuator link nuts	185	136
Subframe to body rear bolts +		
Stage 1	100	74

Stage 2	Then a further 300 degrees	Then a further 300 degrees
Subframe to body front bolts	170	125
Subframe support bracket to body bolts	60	44

+ A new nut or bolt must be installed

++ New nut and bolt must be installed