

2016.0 RANGE ROVER (LG), 204-05

VEHICLE DYNAMIC SUSPENSION

SPECIFICATIONS

Air Suspension - General Specification

ITEM	SPECIFICATION
Ride height:	
Off road 1	40 mm above standard.
Off road 2	75mm above standard.
Access - re-selectable whilst vehicle is moving	50 mm below standard.
High speed	n/a
Trim height	Configured using the Land Rover approved diagnostic system.
Height sensors:	
Front location	Mounted to the front suspension towers with mechanical linkages to the upper suspension arms.
Rear location	Mounted to the rear suspension sub-frame with mechanical linkages to the lower suspension arms.
Height sensor operating voltages:	
Supply voltage	5 volts - supplied by air suspension control module.
Output voltage	Left-hand front and left-hand rear: Voltage increases with compression and decreases with rebound. Right-hand front and right-hand rear:

	Voltage decreases with compression and increases with rebound.
Spring/damper module types:	
Front	Guided air spring surrounding mono-tube damper.
Rear	Unguided air spring, separate mono-tube damper.
Pressures:	
Normal - Front	800 to 1000 kPa (8.0 to 10.0 bar) (116.0 to 145.0 lbf/in ²)
Normal - Rear	500 to 800 kPa (5.0 to 8.0 bar) (72.5 to 116.0 lbf/in ²)
Air supply unit:	Comprises a piston compressor, 12 volt electric motor, solenoid operated exhaust pilot valve, combined slave exhaust valve and pressure relief valve, and air dryer unit and a temperature sensor.
Controlled by	Air suspension control module.
Working pressure	1650 kPa (16.5 bar)
Maximum pressure	2200 kPa (22 bar)
Air reservoir:	
Volume	11 liters
Nominal working pressure	1525-1650 kPa)
Maximum operating pressure	2200 kPa (22 bar) (319 lbf/in ²)
Valve blocks:	
Front	2 corner valves, 1 cross link valve - all mounted on RH inner wing panel, between the main bulkhead and secondary bulkhead.
Rear	Incorporates pressure sensor to monitor spring and air reservoir pressures, reservoir valve, 2 corner valves, 1 cross link valve - all mounted on the upper rearward RH side of the spare wheel well, beneath rear load space carpet.

Torque Specifications

DESCRIPTION	NM

Air suspension compressor mounting bolts	10
Airline connector to the front solenoid valve block	3.5
Airline connector to the rear solenoid valve block. 6mm pipe	3.5
Airline connector to the rear solenoid valve block. 8mm pipe	4.5
Airline connector to the air suspension reservoir	5
Airline connector to front air suspension spring.	3.5
Airline connector to rear air suspension spring.	3.5
Air suspension reservoir bolts:	24
Suspension front height sensor bolt.	7
Suspension front height sensor Torx screws.	4
Suspension rear height sensor bolts.	7
Suspension rear height sensor Torx screws.	4
Height sensor linkage suspension arm pin	6
Front stabilizer bar to sub frame.	110
Front stabilizer bar links.	185
Rear stabilizer bar to sub frame.	110
Rear stabilizer bar links.	185
ASU pipe and harness clip	1.5