

2016.0 RANGE ROVER (LG), 204-04

WHEELS AND TIRES

SPECIFICATIONS

Wheels

WHEEL TYPE	WHEEL SIZE
Alloy wheel	7.5J x19 EH2+44.5 8.5J x20 EH2+47 9.5J x21 EH2+49 9.5J x22 CH49
Steel (temporary spare) wheel	6.0J x20 CH30

Tire Size

NOTES:

- The tire size is displayed on the outer wall of each tire.
- All Range Rover tyres are rated as XL (Extra Load) or ‘Reinforced’

WHEEL SIZE	TIRE SIZE
19 inch - Alloy	235/65 R19 109V
20 inch - Alloy	255/55 R20 110W
21 inch - Alloy	275/45 R21 110V
22 inch - Alloy	275/40 R22 108Y

Tire Pressures - RoW vehicles (Dual Load Conditions)

LOADING CONDITION	BAR	KPA
Normal operating conditions**:		
Front	2.3	230
Rear	2.5	250
Vehicle loaded to maximum gross vehicle weight:		
Front - 19 inch wheels	2.6	260
Rear - 19 inch wheels	3.1	310
Front - other sizes	2.5	250
Rear - other sizes	3.0	

**** Normal operating conditions: Carrying up to 4 passengers and luggage**

Tire Pressures – NAS/Gulf/Brazil vehicles (Dual Load Conditions)

LOADING CONDITION	BAR	KPA
Normal operating conditions**:		
Front	2.3	230
Rear	2.5	250
Vehicle loaded to maximum gross vehicle weight:		
Front	2.5	250
Rear	3.0	300

**** Normal operating conditions: Carrying up to 4 passengers and luggage**

Tire Pressures – Temporary Spare

LOADING CONDITION	BAR	KPA
All operating conditions:	4.2	420

Torque Specifications

DESCRIPTION	NM	LB-FT
Road wheel nuts	140	103
Tire low pressure sensor	8	6